

ATA 32-21-00 - LANDING GEAR - NOSE GEAR ASSEMBLY

SYNTHETIC TEST DOCUMENT - NOT A REAL MANUAL

1. Torque Specifications

The nose gear assembly retaining bolt (P/N SYN-32210-01) shall be torqued to 120 Nm +/- 5 Nm, applied in two stages.

Lubricate threads with approved grease (SYN-LUBE-4) prior to installation.

2. Inspection Interval

Inspect nose gear seal integrity every 400 flight hours or 90 days, whichever occurs first.

3. Safety Warning

WARNING: Ensure aircraft is on jacks and hydraulic pressure is relieved before removing the retaining bolt.

ATA 24-10-00 - ELECTRICAL POWER - MAIN BATTERY BUS

SYNTHETIC TEST DOCUMENT - NOT A REAL MANUAL

1. Isolation Procedure

Toggle main battery switches to the OFF position before inspecting any primary electrical bus in the forward avionics bay.

2. Reset Procedure

Following a bus trip event (fault code FLT-24-5), reset the main battery bus switch and confirm nominal voltage (27.5V DC +/- 1V) before returning aircraft to service.

ATA 79-00-00 - ENGINE OIL SYSTEM

SYNTHETIC TEST DOCUMENT - NOT A REAL MANUAL

1. Oil Specification

Use only approved synthetic turbine oil, specification SYN-OIL-5606. Do not mix with mineral-based oils.

2. Servicing Interval

Check oil quantity every 50 flight hours. Top up if below the MIN mark on the sight gauge; do not exceed MAX.