


Practical aspects of deep learning

LATEST SUBMISSION GRADE

100%


1. If you have 10,000,000 examples, how would you split the train/dev/test set?

- ☐ 33% train . 33% dev . 33% test
- ☒ 98% train . 1% dev . 1% test
- ☐ 60% train . 20% dev . 20% test

 Correct

2. The dev and test set should:

- ☒ Come from the same distribution
- ☐ Come from different distributions
- ☐ Be identical to each other (same (x,y) pairs)
- ☐ Have the same number of examples

 Correct

3. If your Neural Network model seems to have high variance, what of the following would be promising things to try?

- ☐ Increase the number of units in each hidden layer
- ☒ Add regularization

✓ Correct

- ☐ Make the Neural Network deeper
- ☐ Get more test data
- ☒ Get more training data

✓ Correct

4. You are working on an automated check-out kiosk for a supermarket, and are building a classifier for apples, bananas and oranges. Suppose your classifier obtains a training set error of 0.5%, and a dev set error of 7%. Which of the following are promising things to try to improve your classifier? (Check all that apply.)

- ☒ Increase the regularization parameter λ

✓ Correct

- ☐ Decrease the regularization parameter λ
- ☒ Get more training data

✓ Correct

- ☐ Use a bigger neural network

5. What is weight decay?

- ☒ A regularization technique (such as L2 regularization) that results in gradient descent shrinking the weights on every iteration.
- ☐ The process of gradually decreasing the learning rate during training.
- ☐ A technique to avoid vanishing gradient by imposing a ceiling on the values of the weights.
- ☐ Gradual corruption of the weights in the neural network if it is trained on noisy data.

✓ Correct


6. What happens when you increase the regularization hyperparameter lambda?

- ☒ Weights are pushed toward becoming smaller (closer to 0)
- ☐ Weights are pushed toward becoming bigger (further from 0)
- ☐ Doubling lambda should roughly result in doubling the weights
- ☐ Gradient descent taking bigger steps with each iteration (proportional to lambda)

 Correct


7. With the inverted dropout technique, at test time:

- ☐ You do not apply dropout (do not randomly eliminate units), but keep the $1/\text{keep_prob}$ factor in the calculations used in training.
- ☐ You apply dropout (randomly eliminating units) but keep the $1/\text{keep_prob}$ factor in the calculations used in training.
- ☒ You do not apply dropout (do not randomly eliminate units) and do not keep the $1/\text{keep_prob}$ factor in the calculations used in training
- ☐ You apply dropout (randomly eliminating units) and do not keep the $1/\text{keep_prob}$ factor in the calculations used in training


 Correct

8. Increasing the parameter keep_prob from (say) 0.5 to 0.6 will likely cause the following: (Check the two that apply)

- ☐ Increasing the regularization effect
- ☒ Reducing the regularization effect

 Correct

- ☐ Causing the neural network to end up with a higher training set error
- ☒ Causing the neural network to end up with a lower training set error

 Correct

9. Which of these techniques are useful for reducing variance (reducing overfitting)? (Check all that apply.)

☐ Xavier initialization

☐ Exploding gradient

☐ Gradient Checking

☒ Dropout

✓ Correct

☐ Vanishing gradient

☒ L2 regularization

✓ Correct

☒ Data augmentation

✓ Correct

10. Why do we normalize the inputs x ?

☒ It makes the cost function faster to optimize

☐ It makes it easier to visualize the data

☐ Normalization is another word for regularization--It helps to reduce variance

☐ It makes the parameter initialization faster

✓ Correct