


Type Enforced: A Python type enforcer for type annotations

Connor Makowski¹, Willem Guter¹, and Timothy Russell¹

¹ Massachusetts Institute of Technology Cambridge, United States  Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#))

TODO

- [T] Check your name
- ☐ Who else are we going to include on this?
- ☐ I read this as Connor needs to be the corresponding author
- [T] Check the list of tags

JOSS Software Requirements

- ☒ Be stored in a repository that can be cloned without registration.
- ☒ Be stored in a repository that is browsable online without registration.
- ☒ Have an issue tracker that is readable without registration.
- ☒ Permit individuals to create issues/file tickets against your repository.

Summary

`type_enforced` is a pure Python package designed to enforce type annotations at runtime without the need for a special compiler. It provides an intuitive decorator-based interface that allows developers to enforce explicit typing constraints on function and method inputs, return types, dataclasses, and class instances. The package supports a comprehensive set of Python's built-in types, typing module constructs (such as `List`, `Dict`, `Union`, `Optional`, and `Literal`), nested data structures, and custom constraints. By offering runtime validation of type annotations and constraints, `type_enforced` enhances code reliability, readability, and maintainability.

Statement of Need

Python's dynamic typing system offers flexibility but can lead to runtime errors that are difficult to diagnose in web applications, complex scientific software, and research applications. Static type checking tools such as `Mypy` provide valuable compile-time validation; however, they do not prevent runtime type errors. Existing runtime enforcement libraries often require extensive boilerplate code or lack support for advanced typing features and nested structures.

The `type_enforced` package addresses these limitations by providing robust runtime enforcement of Python type annotations with minimal overhead. It supports advanced typing features including nested iterables, union types, dataclasses, inheritance-based validation, uninitialized class type checks, and custom constraints (`Constraint`, `GenericConstraint`). This makes it particularly suitable for research software development where correctness of data types is critical for reproducibility and reliability.

Functionality and Features

Key features provided by the package include:

- **Decorator-based enforcement:** Easily apply enforcement to functions, methods, classes, static methods, class methods, and dataclasses.
- **Comprehensive typing support:** Supports built-in Python types (`int`, `str`, `list`, `dict`, etc.), typing module constructs (`List`, `Dict`, `Union`, `Optional`, `Literal`, `Any`), union types (`int | float`), nested structures (`dict[str, dict[str, int]]`), and deeply nested iterables (`list[set[str]]`).
- **Custom constraints:** Validate input values with built-in constraint classes (e.g., numerical bounds) or user-defined generic constraints (e.g., membership in a predefined set).
- **Inheritance-aware validation:** Validate instances against class hierarchies.
- **Flexible enable/disable mechanism:** Enable or disable enforcement selectively at the function or class level to accommodate debugging versus production environments.

TODO - [X] Check if what I wrote makes any sense

Research Applications

The functionality provided by `type_enforced` is particularly beneficial in scientific computing contexts where strict data validation is crucial. Potential research applications include:

- Ensuring correctness of numerical simulations by enforcing precise data types.
- Validating complex data pipelines in machine learning workflows.
- Enhancing reproducibility in computational experiments by preventing subtle runtime type errors.
- Improving the robustness of research software for transportation modeling and logistics optimization, particularly in collaborative environments where contributors have diverse levels of Python expertise. For example, type enforcement has proven valuable when domain experts develop models and their outputs are integrated through APIs for interactive applications, ensuring reliability and consistency across the workflow.

Related Work

Python's ecosystem for type checking and data validation is rich and rapidly evolving, reflecting the growing need for both static and runtime type safety in scientific and production code. The landscape can be broadly divided into static type checkers, runtime type checkers, and project-based frameworks. Recent empirical studies, such as (Rak-amnouykit et al., 2020), have analyzed the adoption and semantics of Python's type systems in real-world codebases, highlighting both the promise and the challenges of practical type enforcement.

Static Type Checkers

Static type checkers analyze code before execution, using type hints to catch potential errors and improve code reliability without incurring runtime overhead.

- **Mypy** (Lehtosalo, 2012): Mypy is the most widely adopted static type checker for Python, implementing a conventional static type system based on PEP 484. It enforces fixed variable types and reports errors when type annotations are violated. As detailed by (Rak-amnouykit et al., 2020), Mypy represents the canonical approach to static type

checking in Python, and its semantics have become a baseline for evaluating new type inference tools.

- **Pyright** : A fast type checker developed by Microsoft, offering real-time feedback in editors.
- **PyType**: Developed by Google, PyType also provides static analysis and type inference for Python code, but with a distinct approach. Unlike Mypy, PyType maintains separate type environments for different branches in control flow and can infer more precise union types for variables that take on multiple types. The comparative study by ([Rak-amnouykit et al., 2020](#)) shows that PyType and Mypy differ in their handling of type joins, attribute typing, and error reporting, reflecting broader trade-offs in static analysis for dynamic languages.

Runtime Type Checkers and Data Validation

Runtime type checkers enforce type constraints as the program executes, which is particularly valuable when handling external data or integrating with user-facing APIs.

- **Pydantic** ([Colvin, 2017](#)): Pydantic is a widely used library for runtime data validation targeted at dataclass like objects, leveraging type hints to enforce data schemas and automatically cast input values. It is central to frameworks like FastAPI and is particularly effective for validating input from untrusted sources.
- **Typeguard** ([Grönholm, 2016](#)): Typeguard offers single type level runtime enforcement of function type annotations, raising errors when arguments or return values violate declared types. It is lightweight and integrates easily into existing codebases.
- **Enforce** ([Keith-Magee, 2016](#)): Provides basic runtime enforcement but does not support advanced typing features such as deeply nested structures or constraint-based validations.
- **Marshmallow**: ([Loria, 2013](#)): Marshmallow provides serialization, deserialization, and validation of complex data structures, with support for custom validation logic. It is commonly used in web frameworks for API data validation.
- **type_enforced**: In contrast to the above, type_enforced offers decorator-based runtime enforcement of Python type annotations, including support for nested structures, custom constraints, and inheritance-aware validation. Its focus is on minimal boilerplate and compatibility with modern Python typing constructs, making it suitable for research and collaborative environments where correctness and ease of use are paramount.

Project-Based Type Checkers

These tools integrate type checking with specific frameworks, providing tailored solutions for popular Python ecosystems.

- **django-stubs** and **typeddjango**: Extend static type checking to Django projects, enabling type-safe development in large web applications.
- **flask-pydantic** and **flask-marshmallow**: Provide seamless integration of runtime validation into Flask applications, leveraging Pydantic and Marshmallow models, respectively.
- **FastAPI**: Built on top of Pydantic, FastAPI uses type hints for both static analysis and runtime validation of HTTP request and response bodies, ensuring robust API contracts.

Discussion

The diversity of tools reflects the dual nature of Python's type system—supporting both static and dynamic paradigms. As ([Rak-amnouykit et al., 2020](#)) demonstrate, the adoption of type annotations is increasing, but real-world usage patterns remain heterogeneous, and the semantics of type checking tools can differ in subtle but important ways. Packages like type_enforced complement this landscape by providing runtime guarantees that static checkers cannot, especially in collaborative or data-driven research settings. Compared to

these tools, `type_enforced` uniquely combines comprehensive type annotation enforcement with powerful constraint validation capabilities and inheritance-aware checks.

128

129 TODO

- 130 ☐ Figure out how to reference something in the `paper.bib` file
- 131 ☐ Do we need to have the project-based type checkers listed or `marshmallow`?
- 132 ☐ Should I get rid of the last sentence?
- 133 ☐ Can someone take a look at these and see if what Tim wrote makes sense?
- 134 ☐ Are there other better known examples of Python type checkers?

135

136 Usage Example

137 A simple example demonstrating basic usage:

```
import type_enforced

@type_enforced.Enforcer()
def calculate_area(width: int | float, height: int | float) -> int | float:
    return width * height

calculate_area(3.0, 4.5) # Passes
calculate_area('3', 4.5) # Raises TypeError at runtime
```

138 An example demonstrating constraint validation:

```
import type_enforced
from type_enforced.utils import Constraint

@type_enforced.Enforcer()
def positive_integer(value: int | Constraint(ge=0)) -> int:
    return value

positive_integer(10) # Passes
positive_integer(-5) # Raises TypeError due to constraint violation
```

139 Acknowledgments

140 Development of this software was supported by: - MIT Center for Transportation & Logistics
141 (CTL) - MIT Computational Analytics, Visualization & Education Lab (CAVE)

142 References

- 143 Colvin, S. (2017). *Pydantic*. <https://github.com/pydantic/pydantic>.
- 144 Grönholm, A. (2016). *Typeguard*. <https://github.com/agronholm/typeguard>.
- 145 Keith-Magee, R. (2016). *Enforce*. <https://github.com/Russell91/python-enforce>.
- 146 Lehtosalo, J. (2012). *Mypy*. <https://github.com/python/mypy>.
- 147 Loria, S. (2013). *Marshmallow*. <https://github.com/marshmallow-code>.
- 148 Rak-amnouykit, I., McCreavan, D., Milanova, A., Hirzel, M., & Dolby, J. (2020). Python 3
149 types in the wild: A tale of two type systems. *Proceedings of the 16th ACM SIGPLAN*

150 *International Symposium on Dynamic Languages (DLS 2020)*, 59–72. [https://doi.org/10.](https://doi.org/10.1145/3426422.3426984)
151 [1145/3426422.3426984](https://doi.org/10.1145/3426422.3426984)

DRAFT