

# CRF Word Alignment & Noisy Channel Translation

January 31, 2013



# Last Time ...

$$p(\text{Translation}) = \sum_{\text{Alignment}} p(\text{Alignment}, \text{Translation})$$

# Last Time ...

$$p(\text{Translation}) = \sum_{\text{Alignment}} p(\text{Alignment}, \text{Translation})$$

$$= \sum_{\text{Alignment}} p(\text{Alignment}) \times p(\text{Translation} \mid \text{Alignment})$$

# Last Time ...

$$p(\text{Translation}) = \sum_{\text{Alignment}} p(\text{Alignment}, \text{Translation})$$

$$= \sum_{\text{Alignment}} \underbrace{p(\text{Alignment})}_{\text{Alignment}} \times \underbrace{p(\text{Translation} \mid \text{Alignment})}_{\text{Translation}}$$


$$p(\mathbf{e} \mid \mathbf{f}, m) = \sum_{\mathbf{a} \in [0, n]^m} \underbrace{p(\mathbf{a} \mid \mathbf{f}, m)}_{\text{Alignment}} \times \prod_{i=1}^m \underbrace{p(e_i \mid f_{a_i})}_{\text{Translation}}$$

# MAP alignment

	myrY	AbtdAYY	xyAlAt	tEjb	,	fkr	,	nApsndygy	,	wGyrh	KY	t@Y	.
my	■												
initial		■											
reaction													
was													
of													
surprise													
,													
concern													
and													
dislike			■	■	■	■	■	■	■				
etc										■		■	
.													■

IBM Model 4 alignment

# MAP alignment



IBM Model 4 alignment

# A few tricks...

$p(f|e)$

	michael	geht	davon	aus	.	dass	er	im	haus	bleibt
michael										
assumes										
that										
he										
will										
stay										
in										
the										
house										

English to German

# A few tricks...

$p(f|e)$

	michael	geht	davon	aus	,	dass	er	im	haus	bleibt
michael	■									
assumes		■	■	■						
that						■				
he							■			
will										
stay										■
in								■		
the										
house									■	

English to German

	michael	geht	davon	aus	,	dass	er	im	haus	bleibt
michael	■									
assumes		■								
that						■				
he							■			
will										■
stay										
in								■		
the										
house									■	


German to English

$p(e|f)$





# A few tricks...

$p(f|e)$



$p(e|f)$



# Another View

With this model:

$$p(\mathbf{e} \mid \mathbf{f}, m) = \sum_{\mathbf{a} \in [0, n]^m} p(\mathbf{a} \mid \mathbf{f}, m) \times \prod_{i=1}^m p(e_i \mid f_{a_i})$$

The problem of word alignment is as:


$$\mathbf{a}^* = \arg \max_{\mathbf{a} \in [0, n]^m} p(\mathbf{a} \mid \mathbf{e}, \mathbf{f}, m)$$

# Another View

With this model:


$$p(\mathbf{e} \mid \mathbf{f}, m) = \sum_{\mathbf{a} \in [0, n]^m} p(\mathbf{a} \mid \mathbf{f}, m) \times \prod_{i=1}^m p(e_i \mid f_{a_i})$$

The problem of word alignment is as:

$$\mathbf{a}^* = \arg \max_{\mathbf{a} \in [0, n]^m} p(\mathbf{a} \mid \mathbf{e}, \mathbf{f}, m)$$



**Can we model this distribution directly?**

# Markov Random Fields (MRFs)




$$p(A, B, C, X, Y, Z) = \\ p(A) \times p(B \mid A) \times p(C \mid B) \times \\ p(X \mid A)p(Y \mid B)p(Z \mid C)$$

# Markov Random Fields (MRFs)




$$p(A, B, C, X, Y, Z) = p(A) \times p(B \mid A) \times p(C \mid B) \times p(X \mid A) p(Y \mid B) p(Z \mid C)$$




$$p(A, B, C, X, Y, Z) = \frac{1}{Z} \times \Psi_1(A, B) \times \Psi_2(B, C) \times \Psi_3(C, D) \times \Psi_4(X) \times \Psi_5(Y) \times \Psi_6(Z)$$

# Markov Random Fields (MRFs)




$$p(A, B, C, X, Y, Z) = p(A) \times p(B \mid A) \times p(C \mid B) \times p(X \mid A) p(Y \mid B) p(Z \mid C)$$



$$p(A, B, C, X, Y, Z) = \frac{1}{Z} \times \Psi_1(A, B) \times \Psi_2(B, C) \times \Psi_3(C, D) \times \Psi_4(X) \times \Psi_5(Y) \times \Psi_6(Z)$$

“Factors”

# Computing $Z$



$$\mathcal{X} = \{a, b, c\}$$

$$X \in \mathcal{X}$$


$$Y \in \mathcal{X}$$

$$Z = \sum_{x \in \mathcal{X}} \sum_{y \in \mathcal{X}} \Psi_1(x, y) \Psi_2(x) \Psi_3(y)$$

When the graph has certain structures (e.g., chains), you can factor to get polytime DP algorithms.

$$Z = \sum_{x \in \mathcal{X}} \Psi_2(x) \sum_{y \in \mathcal{X}} \Psi_1(x, y) \Psi_3(y)$$


# Log-linear models



$$\Psi_{1,2,3}(x, y) = \exp \sum_k w_k f_k(x, y)$$




# Log-linear models



$$\Psi_{1,2,3}(x, y) = \exp \sum_k w_k f_k(x, y)$$

Weights (learned)

# Log-linear models



$$\Psi_{1,2,3}(x, y) = \exp \sum_k w_k f_k(x, y)$$

Weights (learned)

Feature functions  
(specified)

# Random Fields

- **Benefits**

- Potential functions can be defined with respect to arbitrary features (functions) of the variables
- Great way to incorporate knowledge

- **Drawbacks**

- Likelihood involves computing  $Z$
- Maximizing likelihood usually requires computing  $Z$  (often over and over again!)

# Conditional Random Fields

- Use MRFs to parameterize a conditional distribution. Very easy: let feature functions look at **anything** they want in the “input”

# Conditional Random Fields

- Use MRFs to parameterize a conditional distribution. Very easy: let feature functions look at **anything** they want in the “input”

$$p(\mathbf{y} \mid \mathbf{x}) = \frac{1}{Z_{\mathbf{w}}(\mathbf{y})} \exp \sum_{F \in \mathcal{G}} \sum_k w_k f_k(F, \mathbf{x})$$

# Conditional Random Fields

- Use MRFs to parameterize a conditional distribution. Very easy: let feature functions look at **anything** they want in the “input”

$$p(\mathbf{y} \mid \mathbf{x}) = \frac{1}{Z_{\mathbf{w}}(\mathbf{y})} \exp \sum_{F \in \mathcal{G}} \sum_k w_k f_k(F, \mathbf{x})$$

All factors in the graph of  $\mathbf{y}$



# Parameter Learning

- CRFs are trained to maximize conditional likelihood

$$\hat{\mathbf{w}}_{\text{MLE}} = \arg \max_{\mathbf{w}} \prod_{(\mathbf{x}_i, \mathbf{y}_i) \in \mathcal{D}} p(\mathbf{y}_i \mid \mathbf{x}_i ; \mathbf{w})$$

- Recall we want to directly model

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f})$$

- The likelihood of what alignments?

# Parameter Learning

- CRFs are trained to maximize conditional likelihood

$$\hat{\mathbf{w}}_{\text{MLE}} = \arg \max_{\mathbf{w}} \prod_{(\mathbf{x}_i, \mathbf{y}_i) \in \mathcal{D}} p(\mathbf{y}_i \mid \mathbf{x}_i ; \mathbf{w})$$

- Recall we want to directly model

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f})$$

- The likelihood of what alignments?

**Gold reference alignments!**



# CRF for Alignment

- One of many possibilities, due to Blunsom & Cohn (2006)

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f}) = \frac{1}{Z_{\mathbf{w}}(\mathbf{e}, \mathbf{f})} \exp \sum_{i=1}^{|\mathbf{e}|} \sum_k w_k f(a_i, a_{i-1}, i, \mathbf{e}, \mathbf{f})$$

- $\mathbf{a}$  has the same form as in the lexical translation models (still make a one-to-many assumption)
- $w_k$  are the model parameters
- $f_k$  are the feature functions

# CRF for Alignment


- One of many possibilities, due to Blunsom & Cohn (2006)

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f}) = \frac{1}{Z_{\mathbf{w}}(\mathbf{e}, \mathbf{f})} \exp \sum_{i=1}^{|\mathbf{e}|} \sum_k w_k f(a_i, a_{i-1}, i, \mathbf{e}, \mathbf{f})$$

- $\mathbf{a}$  has the same form as in the lexical translation models (still make a one-to-many assumption)
- $w_k$  are the model parameters
- $f_k$  are the feature functions

$$O(n^2 m) \approx O(n^3)$$

# Model



- Labels (one per target word) index source sentence
- Train model (e,f) and (f,e) [inverting the reference alignments]

# Experiments

## Alignment Experiments:

- French - English (Canadian Hansards corpus NAACL '03)
- 484 word-aligned sentences (100 training, 37 devel. and 347 testing)
- 1.1M sentence-aligned sentences
- We present GIZA++ model 4 results for comparison

pervez

musharrafs langer abschied

Identical word

pervez

musharraf 's long goodbye

Identical word

pervez **musharrafs** langer abschied

**Matching prefix**

pervez **musharra**f 's long goodbye

**Identical word**  
**Matching prefix**

pervez **musharrafs** langer abschied

**Matching suffix**

pervez musharra**f** **'s** long goodbye

**Identical word**

**Matching prefix**

**Matching suffix**

pervez musharrafs **langer** abschied

**Orthographic similarity**

pervez musharrafa 's **long** goodbye

**Identical word**

**Matching prefix**

**Matching suffix**

**Orthographic similarity**



pervez musharrafs langer **abschied**

**In dictionary**

pervez musharraf 's long **goodbye**

**Identical word**

**Matching prefix**

**Matching suffix**

**Orthographic similarity**

**In dictionary**

...

pervez musharrafs langer abschied

pervez musharraf 's long goodbye

**Identical word**

**Matching prefix**

**Matching suffix**

**Orthographic similarity**

**In dictionary**

...

# Lexical Features

- Word  $\leftrightarrow$  word indicator features
- Various word  $\leftrightarrow$  word co-occurrence scores
  - IBM Model 1 probabilities ( $t \rightarrow s$  ,  $s \rightarrow t$ )
  - Geometric mean of Model 1 probabilities
  - Dice's coefficient [binned]
  - Products of the above

# Lexical Features

- Word class  $\leftrightarrow$  word class indicator
  - **NN** translates as **NN** (NN\_NN=1)
  - **NN** does not translate as **MD** (NN\_MD=1)
- Identical word feature
  - **2010 = 2010** (IdentWord=1 IdentNum=1)
- Identical prefix feature
  - **Obama ~ Obamu** (IdentPrefix=1)
- Orthographic similarity measure [binned]
  - **Al-Qaeda ~ Al-Kaida** (OrthoSim050\_080=1)

# Other Features

- Compute features from large amounts of unlabeled text
- Does the Model 4 alignment contain this alignment point?
- What is the Model 1 posterior probability of this alignment point?

# Results

Alignment Results:

	Precision	Recall	F-score
French → English	0.97	0.86	0.91
French ← English	<b>0.98</b>	0.83	0.91
French ↔ English	0.96	0.90	0.93
French → English (+ibm model4)	<b>0.98</b>	0.88	0.93
French ← English (+ibm model4)	<b>0.98</b>	0.87	0.93
French ↔ English (+ibm model4)	<b>0.98</b>	0.91	<b>0.95</b>
GIZA++ (French ↔ English)	0.87	<b>0.95</b>	0.91

# Summary

- CRFs provide an efficient model for word alignment that outperforms current models, even when only a small number of word aligned sentences are available
- A diverse range of features can be beneficial to word alignment performance, in particular Markov sequence features improve f-score
- Incorporating features from unsupervised models such as IBM Model 4 can lead to a large increase in f-score



# Summary

- CRFs provide an efficient model for word alignment that outperforms current models, even when only a small number of word aligned sentences are available
- A diverse range of features can be beneficial to word alignment performance, in particular Markov sequence features improve f-score
- Incorporating features from unsupervised models such as IBM Model 4 can lead to a large increase in f-score

Unfortunately, you need **gold alignments!**



# Putting the pieces together

$$p(\mathbf{e})$$

$$p(\mathbf{e} \mid \mathbf{f}, m)$$

$$p(\mathbf{e}, \mathbf{a} \mid \mathbf{f}, m)$$

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f})$$

# Putting the pieces together

- We have seen how to model the following:

$$p(\mathbf{e})$$

$$p(\mathbf{e} \mid \mathbf{f}, m)$$

$$p(\mathbf{e}, \mathbf{a} \mid \mathbf{f}, m)$$

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f})$$

# Putting the pieces together

- We have seen how to model the following:

$$p(\mathbf{e})$$

$$p(\mathbf{e} \mid \mathbf{f}, m)$$

$$p(\mathbf{e}, \mathbf{a} \mid \mathbf{f}, m)$$

$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f})$$

# Putting the pieces together

- We have seen how to model the following:

$$p(\mathbf{e})$$

$$p(\mathbf{e} \mid \mathbf{f}, m)$$

$$p(\mathbf{e}, \mathbf{a} \mid \mathbf{f}, m)$$


$$p(\mathbf{a} \mid \mathbf{e}, \mathbf{f})$$

- Goal: a better model of  $p(\mathbf{e} \mid \mathbf{f}, m)$  that knows about  $p(\mathbf{e})$


One naturally wonders if the problem of translation could conceivably be treated as a problem in cryptography. When I look at an article in Russian, I say: *‘This is really written in English, but it has been coded in some strange symbols. I will now proceed to decode.’*




Warren Weaver to Norbert Wiener, March, 1947



Claude Shannon. “A Mathematical Theory of Communication” 1948.



Claude Shannon. "A Mathematical Theory of Communication" 1948.



Claude Shannon. "A Mathematical Theory of Communication" 1948.






$$p(y) \quad p(x|y)$$


## Shannon's theory tells us:


- 1) how much data you can send
- 2) the limits of compression
- 3) why your download is so slow
- 4) how to translate




Claude Shannon. "A Mathematical Theory of Communication" 1948.











$$\boxed{y'} = \arg \max_y p(y|x)$$






$$p(y) \quad p(x|y) \quad \nexists$$

$$y' = \arg \max_y p(y|x)$$




I can help.




$$\boxed{y'} = \arg \max_y p(y|x)$$
$$= \arg \max_y \frac{p(x|y)p(y)}{p(x)}$$






$$\boxed{y'} = \arg \max_y p(y|x)$$
$$= \arg \max_y \frac{p(x|y)p(y)}{p(x)}$$


Denominator doesn't depend on  $y$ .



$$\begin{aligned} \boxed{y'} &= \arg \max_y p(y|x) \\ &= \arg \max_y \frac{p(x|y)p(y)}{p(x)} \\ &= \arg \max_y p(x|y)p(y) \end{aligned}$$




$$y' = \arg \max_y p(x|y)p(y)$$



~~$$y' = \arg \max_y p(x|y)p(y)$$~~

$$e' = \arg \max_e p(\mathbf{f}|\mathbf{e})p(\mathbf{e})$$




$$y' = \arg \max_y p(x|y)p(y)$$

$$e' = \arg \max_e p(\mathbf{f}|\mathbf{e})p(\mathbf{e})$$



translation model




~~$$y' = \arg \max_y p(x|y)p(y)$$~~


$$e' = \arg \max_e p(\mathbf{f}|\mathbf{e})p(\mathbf{e})$$



translation model



language model



~~$$y' = \arg \max_y p(x|y)p(y)$$~~

$$e' = \arg \max_e p(\mathbf{f}|e)p(e)$$



translation model



language model

**Other noisy channel applications: OCR, speech recognition, spelling correction...**

# Division of labor

- **Translation model**
  - probability of translation *back* into the source
  - ensures **adequacy** of translation
- **Language model**
  - is a translation hypothesis “good” English?
  - ensures **fluency** of translation



$p(\mathbf{e})$  English

$p(\mathbf{e})$  English  $\xrightarrow{p(\mathbf{f} \mid \mathbf{e})}$  Հայերեն



SimplePlants.com - Plants, Animals and tools for Home-Kitchen



$$\begin{aligned} \mathbf{e}^* &= \arg \max_{\mathbf{e}} p(\mathbf{e} \mid \mathbf{f}) \\ &= \arg \max_{\mathbf{e}} p(\mathbf{f} \mid \mathbf{e}) \times p(\mathbf{e}) \end{aligned}$$

# Announcements

- Upcoming language-in-10
  - Tuesday: Jon/Austin - Русский
- Leaderboard is functional

Rank	Handle	Assignments				
		#0	#1 AER	#3 Spearman's	#2 model score	#4 BLEU
	<b>oracle</b>	8	0			
1	db	16	0.433932			
	<b>baseline</b>	10	0.434484			
2	zero	18	0.434484			
3	Victor	24	0.438705			
	<b>default</b>	9	0.788911			
4	HBH	10				