

Load Cell Central

1-800-LOADCEL

*** LOAD CELL CALIBRATION CERTIFICATE ***

Model:	HRS-3K
Capacity:	3,000 LB
Serial Number:	430836
Compression FSO mV/V:	-2.0686
Calibration Date:	5/24/2023

Safe Overload:	150% FS	Zero Balance:	1.0% FS
Non-Linearity:	$\pm 0.1\%$ R.O.	Compensated Temp:	60 to 160°F
Hysteresis:	$\pm 0.1\%$ R.O.	Operating Temp:	-65 to 200°F
Non-Repeatability:	$\pm 0.05\%$ R.O.	Input Resistance:	350 Ohms Nominal
Max. Excitation:	10Vdc	Output Resistance:	350 Ohms Nominal
		Ultimate Overload:	300% FS

Electrical Connections		
Pin	Function	Color
A	+Excitation	Red
B	+Signal	Green
C	-Signal	Red/White
D	-Excitation	Red/Black
	Not Used	Red/Yellow
	Not Used	Red/Blue
Positive Output in Tension		

!!! SAFETY INSTRUCTIONS!!!

To ensure sufficient overload capacity for the designed load, the dimensions of all mounting and structural elements have to be calculated. In particular, upright weighing objects (vessels and the like) have to be safeguarded against the weighing installation turning over or being shifted.

In the event of a break in suspension, load cell, or mounting part etc., representing a hazard to health and/or safety and/or damage to goods, additional safety devices are necessary.

Load Cell Central
28175 Rte. 220
Milan, PA 18831
Web: www.800loadcel.com

Toll Free: 1-800-562-3235
Phone: 1-570-731-7048
Fax: 1-570-731-7054
Email: sales@800loadcel.com

Load Cell Central

1-800-LOADCEL

*** LOAD CELL CALIBRATION CERTIFICATE ***

Model:	HRS-3K
Capacity:	3,000 LB
Serial Number:	430837
Compression FSO mV/V:	-2.0193
Calibration Date:	5/24/2023

Safe Overload:	150% FS	Zero Balance:	1.0% FS
Non-Linearity:	$\pm 0.1\%$ R.O.	Compensated Temp:	60 to 160°F
Hysteresis:	$\pm 0.1\%$ R.O.	Operating Temp:	-65 to 200°F
Non-Repeatability:	$\pm 0.05\%$ R.O.	Input Resistance:	350 Ohms Nominal
Max. Excitation:	10Vdc	Output Resistance:	350 Ohms Nominal
		Ultimate Overload:	300% FS

Electrical Connections		
Pin	Function	Color
A	+Excitation	Red
B	+Signal	Green
C	-Signal	Red/White
D	-Excitation	Red/Black
	Not Used	Red/Yellow
	Not Used	Red/Blue
Positive Output in Tension		

!!! SAFETY INSTRUCTIONS!!!

To ensure sufficient overload capacity for the designed load, the dimensions of all mounting and structural elements have to be calculated. In particular, upright weighing objects (vessels and the like) have to be safeguarded against the weighing installation turning over or being shifted.

In the event of a break in suspension, load cell, or mounting part etc., representing a hazard to health and/or safety and/or damage to goods, additional safety devices are necessary.

Load Cell Central
28175 Rte. 220
Milan, PA 18831
Web: www.800loadcel.com

Toll Free: 1-800-562-3235
Phone: 1-570-731-7048
Fax: 1-570-731-7054
Email: sales@800loadcel.com

Load Cell Central

1-800-LOADCEL

*** LOAD CELL CALIBRATION CERTIFICATE ***

Model:	HRS-3K
Capacity:	3,000 LB
Serial Number:	430838
Compression FSO mV/V:	-2.0293
Calibration Date:	5/24/2023

Safe Overload:	150% FS	Zero Balance:	1.0% FS
Non-Linearity:	$\pm .1\%$ R.O.	Compensated Temp:	60 to 160°F
Hysteresis:	$\pm .1\%$ R.O.	Operating Temp:	-65 to 200°F
Non-Repeatability:	$\pm .05\%$ R.O.	Input Resistance:	350 Ohms Nominal
Max. Excitation:	10Vdc	Output Resistance:	350 Ohms Nominal
		Ultimate Overload:	300% FS

Electrical Connections		
Pin	Function	Color
A	+Excitation	Red
B	+Signal	Green
C	-Signal	Red/White
D	-Excitation	Red/Black
	Not Used	Red/Yellow
	Not Used	Red/Blue
Positive Output in Tension		

!!! SAFETY INSTRUCTIONS!!!

To ensure sufficient overload capacity for the designed load, the dimensions of all mounting and structural elements have to be calculated. In particular, upright weighing objects (vessels and the like) have to be safeguarded against the weighing installation turning over or being shifted.

In the event of a break in suspension, load cell, or mounting part etc., representing a hazard to health and/or safety and/or damage to goods, additional safety devices are necessary.

Load Cell Central
28175 Rte. 220
Milan, PA 18831
Web: www.800loadcel.com

Toll Free: 1-800-562-3235
Phone: 1-570-731-7048
Fax: 1-570-731-7054
Email: sales@800loadcel.com