




Shanghai HongSheng Wire&Cable Co.,Ltd

Approval Sheets

Customer/客户	Jon Pompa		
Standard/标准	/		
Construction/规格	ROV tether 4X16awg +2X2X26AWG		
Conductor（导体）			
Construction Item	Units	16AWG	26AWG
Construction/构造	mm	27/0.24±0.008	7/0.15±0.008
Material/材质	---	Bare copper wire	
O.D/绞合外径	mm	1.44	0.45
Insulation（绝缘）			
Material/材质	---	PE	PE
Avg.Thick/标准厚度	mm	0.50	0.25
Min.Thick最小厚度	mm	0.35	0.15
O.D/线径	mm	2.5±0.1	0.95±0.1
Color/颜色	---	Red, black, brown, blue	Blue white, orange white
Shield（屏蔽）			
Material/材质	---	Aluminum foil shield	
Construction/结构	---	/	
Coverage/覆盖率	%	/	
filling（填充）			
Tensile filling Material/抗拉材质	---	Kevlar	
water-blocking material./阻水材质	---	SAR	
Jacket（护套）			
Material/材质	---	PUR	
Avg.Thick/标准厚度	mm	1.30	
Min.Thick/最小厚度	mm	1.00	
O.D/线径	mm	10.5±0.3	
Color/颜色	'---	Yellow	
Surface/外观	---		
Marking（印字）			
SHANGHAI HONGSHENG ROV CABLE CO.,LTD ROV tether 4X16awg +2X2X26AWG meters			

Sheet NO/编号	S200319-2020	
Construction Figure/截面图：		
		
Electric Characters 电气性能		
Voltage rating/额定电压:300/500V		
Testing volatge: 2.0KV/5Min		
Max.Conductor DC Resitance at20°C(Ω/km):16AWG13.5Ω/km 26AWG 143Ω/km		
Mechanical Characteristics		
Temperature range: -25°C till +80°C		
Operating temperature: -25°C till +90°C		
Working load : 200kg		
Maximum breaking strength: 600kg		
上海宏胜电线电缆有限公司 ShangHai HongSheng Wire&Cable Co.,Ltd		
Add:No. 4769, Money Road, Fengxian District, Shanghai China		
地址：上海市奉贤区金钱公路4769号		
APPROVED批准	CHECKED审查	DESIGNED编制
Tony	Tony	WKB
APPROVED BY THE CLIENT 客户认可		
Jon Pompa		
Revision Date:2020-4-22		