Chapter 4: outline

Interplay between routing, forwarding



Graph abstraction



graph: G = (N,E)

N = set of routers = { u, v, w, x, y, z }

E = set of links ={ (u,v), (u,x), (v,x), (v,w), (x,w), (x,y), (w,y), (w,z), (y,z) }

aside: graph abstraction is useful in other network contexts, e.g., P2P, where *N* is set of peers and *E* is set of TCP connections

Graph abstraction: costs



c(x,x') = cost of link (x,x')
e.g., c(w,z) = 5

cost could always be 1, or inversely related to bandwidth, or inversely related to congestion

cost of path $(x_1, x_2, x_3,\ldots, x_p) = c(x_1,x_2) + c(x_2,x_3) + \ldots + c(x_{p-1},x_p)$

key question: what is the least-cost path between u and z ?
routing algorithm: algorithm that finds that least cost path

Routing algorithm classification

Q: global or decentralized information?

global:

- all routers have complete topology, link cost info
- "link state" algorithms

decentralized:

- router knows physically-connected neighbors, link costs to neighbors
- iterative process of computation, exchange of info with neighbors
- "distance vector" algorithms

Q: static or dynamic?

static:

- routes change slowly over time

dynamic:

- routes change more quickly
  - periodic update
  - in response to link cost changes

Chapter 4: outline

A Link-State Routing Algorithm

Dijkstra's algorithm

- net topology, link costs known to all nodes
  - accomplished via "link state broadcast"
  - all nodes have same info
- computes least cost paths from one node ('source") to all other nodes
  - gives *forwarding table* for that node
- iterative: after k iterations, know least cost path to k dest.'s

notation:

- c(x,y): link cost from node x to y; = ∞ if not direct neighbors
- D(v): current value of cost of path from source to dest. v
- p(v): predecessor node along path from source to v
- N': set of nodes whose least cost path definitively known

Dijsktra's Algorithm

```
 Initialization:
   N' = {u}
   for all nodes v
     if v adjacent to u
        then D(v) = c(u,v)
     else D(v) = ∞

 Loop
   find w not in N' such that D(w) is a minimum
   add w to N'
   update D(v) for all v adjacent to w and not in N' :
      D(v) = min( D(v), D(w) + c(w,v) )
   /* new cost to v is either old cost to v or known
    shortest path cost to w plus cost from w to v */
 until all nodes in N'
```

Dijkstra's algorithm: example

Step	N'	D(v) p(v)	D(w) p(w)	D(x) p(x)	D(y) p(y)	D(z) p(z)
0	u	7,u	3,u	5,u	∞	∞
1	uw	6,w		5,u	11,w	∞
2	uwx	6,w			11,w	14,x
3	uwxv				10,y	14,x
4	uwxvy					12,y
5	uwxvyz					

notes:
- construct shortest path tree by tracing predecessor nodes
- ties can exist (can be broken arbitrarily)



Dijkstra's algorithm: another example

Step	N'	D(v),p(v)	D(w),p(w)	D(x),p(x)	D(y),p(y)	D(z),p(z)
0	u	2,u	5,u	1,u	∞	∞
1	ux	2,u	4,x		2,x	∞
2	uxy	2,u	3,y			4,y
3	uxyv		3,y			4,y
4	uxyvw					4,y
5	uxyvwz					



Dijkstra's algorithm: example (2)

resulting shortest-path tree from u:



resulting forwarding table in u:

destination	link
v	(u,v)
x	(u,x)
y	(u,x)
w	(u,x)
z	(u,x)

Dijkstra's algorithm, discussion

algorithm complexity: n nodes
- each iteration: need to check all nodes, w, not in N
- n(n+1)/2 comparisons: O(n^2)
- more efficient implementations possible: O(nlogn)

oscillations possible:
- e.g., support link cost equals amount of carried traffic:



initially

given these costs, find new routing…. resulting in new costs

given these costs, find new routing…. resulting in new costs

given these costs, find new routing…. resulting in new costs

Chapter 4: outline

Distance vector algorithm

Bellman-Ford equation (dynamic programming)

let
$d_x(y)$:= cost of least-cost path from x to y
then

$$d_x(y) = \min_v \{c(x,v) + d_v(y)\}$$

cost from neighbor v to destination y

cost to neighbor v

min taken over all neighbors v of x

Bellman-Ford example



clearly, $d_v(z) = 5$, $d_x(z) = 3$, $d_w(z) = 3$

B-F equation says:

$$\begin{aligned} d_u(z) &= \min \{ c(u,v) + d_v(z), \\ &\qquad c(u,x) + d_x(z), \\ &\qquad c(u,w) + d_w(z) \} \\ &= \min \{2 + 5, \\ &\qquad 1 + 3, \\ &\qquad 5 + 3\} = 4 \end{aligned}$$

node achieving minimum is next hop in shortest path, used in forwarding table

Distance vector algorithm

- $D_x(y)$ = estimate of least cost from x to y
  - x maintains distance vector $\mathbf{D}_x = [D_x(y): y \in N]$
- node x:
  - knows cost to each neighbor v: c(x,v)
  - maintains its neighbors' distance vectors. For each neighbor v, x maintains $\mathbf{D}_v = [D_v(y): y \in N]$

Distance vector algorithm

key idea:
- from time-to-time, each node sends its own distance vector estimate to neighbors
- when x receives new DV estimate from neighbor, it updates its own DV using B-F equation:

$$D_x(y) \leftarrow \min_v\{c(x,v) + D_v(y)\} \quad \text{for each node } y \in N$$

- under minor, natural conditions, the estimate $D_x(y)$ *converge to the actual least cost* $d_x(y)$

Distance vector algorithm

iterative, asynchronous: each local iteration caused by:
- local link cost change
- DV update message from neighbor

distributed:
- each node notifies neighbors *only* when its DV changes
  - neighbors then notify their neighbors if necessary

each node:

wait for (change in local link cost or msg from neighbor)

↓

recompute estimates

↓

if DV to any dest has changed, ***notify*** neighbors

$D_x(y) = \min\{c(x,y) + D_y(y), c(x,z) + D_z(y)\}$
$= \min\{2+0 , 7+1\} = 2$

$D_x(z) = \min\{c(x,y) + D_y(z), c(x,z) + D_z(z)\}$
$= \min\{2+1 , 7+0\} = 3$



$D_x(y) = \min\{c(x,y) + D_y(y), c(x,z) + D_z(y)\}$
$= \min\{2+0 , 7+1\} = 2$

$D_x(z) = \min\{c(x,y) + D_y(z), c(x,z) + D_z(z)\}$
$= \min\{2+1 , 7+0\} = 3$



Distance vector: link cost changes

link cost changes:

- node detects local link cost change
- updates routing info, recalculates distance vector
- if DV changes, notify neighbors



"good news travels fast"

t_0 : *y* detects link-cost change, updates its DV, informs its neighbors.

t_1 : *z* receives update from *y*, updates its table, computes new least cost to *x* , sends its neighbors its DV.

t_2 : *y* receives *z*' s update, updates its distance table. *y*' s least costs do *not* change, so *y* does *not* send a message to *z*.

Distance vector: link cost changes

link cost changes:

- node detects local link cost change
- *bad news travels slow* - "count to infinity" problem!
- 44 iterations before algorithm stabilizes: see text



poisoned reverse:

- If Z routes through Y to get to X :
  - Z tells Y its (Z' s) distance to X is infinite (so Y won' t route to X via Z)
- will this completely solve count to infinity problem?

Comparison of LS and DV algorithms

message complexity

- ***LS:*** with n nodes, E links, O(nE) msgs sent
- ***DV:*** exchange between neighbors only
  - convergence time varies

speed of convergence

- ***LS:*** $O(n^2)$ algorithm requires O(nE) msgs
  - may have oscillations
- ***DV:*** convergence time varies
  - may be routing loops
  - count-to-infinity problem

robustness: what happens if router malfunctions?

LS:

- node can advertise incorrect *link* cost
- each node computes only its *own* table

DV:

- DV node can advertise incorrect *path* cost
- each node' s table used by others
  - error propagate thru network

Chapter 4: outline

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what' s inside a router

4.4 IP: Internet Protocol

- datagram format
- IPv4 addressing
- ICMP
- IPv6

4.5 routing algorithms

- link state
- distance vector
- hierarchical routing

4.6 routing in the Internet

- RIP
- OSPF
- BGP

4.7 broadcast and multicast routing

Hierarchical routing

our routing study thus far - idealization
- all routers identical
- network "flat"

… *not* true in practice

scale: with 600 million destinations:
- can't store all dest's in routing tables!
- routing table exchange would swamp links!

administrative autonomy
- internet = network of networks
- each network admin may want to control routing in its own network

Hierarchical routing

- aggregate routers into regions, "autonomous systems" (AS)
- routers in same AS run same routing protocol
  - "intra-AS" routing protocol
  - routers in different AS can run different intra-AS routing protocol

gateway router:
- at "edge" of its own AS
- has link to router in another AS

Interconnected ASes



- forwarding table configured by both intra- and inter-AS routing algorithm
  - intra-AS sets entries for internal dests
  - inter-AS & intra-AS sets entries for external dests

Inter-AS tasks

- suppose router in AS1 receives datagram destined outside of AS1:
  - router should forward packet to gateway router, but which one?

AS1 must:
1. learn which dests are reachable through AS2, which through AS3
2. propagate this reachability info to all routers in AS1

job of inter-AS routing!



Example: setting forwarding table in router 1d

- suppose AS1 learns (via inter-AS protocol) that subnet *x* reachable via AS3 (gateway 1c), but not via AS2
  - inter-AS protocol propagates reachability info to all internal routers
- router 1d determines from intra-AS routing info that its interface *I* is on the least cost path to 1c
  - installs forwarding table entry *(x,I)*



Example: choosing among multiple ASes

- now suppose AS1 learns from inter-AS protocol that subnet *x* is reachable from AS3 *and* from AS2.
- to configure forwarding table, router 1d must determine which gateway it should forward packets towards for dest x
  - this is also job of inter-AS routing protocol!



Example: choosing among multiple ASes

- now suppose AS1 learns from inter-AS protocol that subnet *x* is reachable from AS3 *and* from AS2.
- to configure forwarding table, router 1d must determine towards which gateway it should forward packets for dest x
  - this is also job of inter-AS routing protocol!
- *hot potato routing: send* packet towards closest of two routers.



Chapter 4: outline

Intra-AS Routing

- also known as *interior gateway protocols (IGP)*
- most common intra-AS routing protocols:
  - RIP: Routing Information Protocol
  - OSPF: Open Shortest Path First
  - IGRP: Interior Gateway Routing Protocol (Cisco proprietary)

RIP (Routing Information Protocol)

- included in BSD-UNIX distribution in 1982
- distance vector algorithm
  - distance metric: # hops (max = 15 hops), each link has cost 1
  - DVs exchanged with neighbors every 30 sec in response message (aka advertisement)
  - each advertisement: list of up to 25 destination *subnets (in IP addressing sense)*



from router A to destination *subnets:*

subnet	hops
u	1
v	2
w	2
x	3
y	3
z	2

RIP: example



routing table in router D

destination subnet	next router	# hops to dest
w	A	2
y	B	2
x	--	1
….	….	....

RIP: example



routing table in router D

destination subnet	next router	# hops to dest
w	A	2
y	B	2
z	~~B~~ A	~~7~~ 5
x	--	1
….	….	....

RIP: link failure, recovery

if no advertisement heard after 180 sec -->
neighbor/link declared dead

- routes via neighbor invalidated
- new advertisements sent to neighbors
- neighbors in turn send out new advertisements (if tables changed)
- link failure info quickly (?) propagates to entire net
- *poison reverse* used to prevent ping-pong loops (infinite distance = 16 hops)

RIP table processing

- RIP routing tables managed by *application-level* process called route-d (daemon)
- advertisements sent in UDP packets, periodically repeated



OSPF (Open Shortest Path First)

- "open": publicly available
- uses link state algorithm
  - LS packet dissemination
  - topology map at each node
  - route computation using Dijkstra's algorithm
- OSPF advertisement carries one entry per neighbor
- advertisements flooded to *entire* AS
  - carried in OSPF messages directly over IP (rather than TCP or UDP
- *IS-IS routing* protocol: nearly identical to OSPF

OSPF "advanced" features (not in RIP)

- *security:* all OSPF messages authenticated (to prevent malicious intrusion)
- multiple same-cost paths allowed (only one path in RIP)
- for each link, multiple cost metrics for different TOS (e.g., satellite link cost set "low" for best effort ToS; high for real time ToS)
- integrated uni- and multicast support:
  - Multicast OSPF (MOSPF) uses same topology data base as OSPF
- hierarchical OSPF in large domains.

Hierarchical OSPF



Hierarchical OSPF

- *two-level hierarchy:* local area, backbone.
  - link-state advertisements only in area
  - each nodes has detailed area topology; only know direction (shortest path) to nets in other areas.
- *area border routers:* "summarize" distances to nets in own area, advertise to other Area Border routers.
- *backbone routers:* run OSPF routing limited to backbone.
- *boundary routers:* connect to other AS' s.

Internet inter-AS routing: BGP

- BGP (Border Gateway Protocol): *the* de facto inter-domain routing protocol
  - "glue that holds the Internet together"
- BGP provides each AS a means to:
  - eBGP: obtain subnet reachability information from neighboring ASs.
  - iBGP: propagate reachability information to all AS-internal routers.
  - determine "good" routes to other networks based on reachability information and policy.
- allows subnet to advertise its existence to rest of Internet: *"I am here"*

BGP basics

- BGP session: two BGP routers ("peers") exchange BGP messages:
  - advertising *paths* to different destination network prefixes ("path vector" protocol)
  - exchanged over semi-permanent TCP connections
- when AS3 advertises a prefix to AS1:
  - AS3 *promises* it will forward datagrams towards that prefix
  - AS3 can aggregate prefixes in its advertisement



BGP basics: distributing path information

- using eBGP session between 3a and 1c, AS3 sends prefix reachability info to AS1.
  - 1c can then use iBGP do distribute new prefix info to all routers in AS1
  - 1b can then re-advertise new reachability info to AS2 over 1b-to-2a eBGP session
- when router learns of new prefix, it creates entry for prefix in its forwarding table.



Path attributes and BGP routes

- advertised prefix includes BGP attributes
  - prefix + attributes = "route"
- two important attributes:
  - AS-PATH: contains ASs through which prefix advertisement has passed: e.g., AS 67, AS 17
  - NEXT-HOP: indicates specific internal-AS router to next-hop AS. (may be multiple links from current AS to next-hop-AS)
- gateway router receiving route advertisement uses import policy to accept/decline
  - e.g., never route through AS x
  - *policy-based* routing

BGP route selection

- router may learn about more than 1 route to destination AS, selects route based on:
  1. local preference value attribute: policy decision
  2. shortest AS-PATH
  3. closest NEXT-HOP router: hot potato routing
  4. additional criteria

BGP messages

- BGP messages exchanged between peers over TCP connection
- BGP messages:
  - OPEN: opens TCP connection to peer and authenticates sender
  - UPDATE: advertises new path (or withdraws old)
  - KEEPALIVE: keeps connection alive in absence of UPDATES; also ACKs OPEN request
  - NOTIFICATION: reports errors in previous msg; also used to close connection

Putting it Altogether: *How Does an Entry Get Into a Router's Forwarding Table?*

- Answer is complicated!
- Ties together hierarchical routing (Section 4.5.3) with BGP (4.6.3) and OSPF (4.6.2).
- Provides nice overview of BGP!

How does entry get in forwarding table?



How does entry get in forwarding table?

High-level overview

1. Router becomes aware of prefix
2. Router determines output port for prefix
3. Router enters prefix-port in forwarding table

Router becomes aware of prefix



- BGP message contains "routes"
- "route" is a prefix and attributes: AS-PATH, NEXT-HOP,…
- Example: route:
  - Prefix:138.16.64/22 ; AS-PATH: AS3 AS131 ; NEXT-HOP: 201.44.13.125

Router may receive multiple routes



- Router may receive multiple routes for <u>same</u> prefix
- Has to select one route

Select best BGP route to prefix

- Router selects route based on shortest AS-PATH
- Example:

  select

  - AS2 AS17 to 138.16.64/22
  - AS3 AS131 AS201 to 138.16.64/22

- What if there is a tie? We'll come back to that!

Find best intra-route to BGP route

- Use selected route's NEXT-HOP attribute
  - Route's NEXT-HOP attribute is the IP address of the router interface that begins the AS PATH.
- Example:
  - AS-PATH: AS2 AS17 ; NEXT-HOP: 111.99.86.55
- Router uses OSPF to find shortest path from 1c to 111.99.86.55



Router identifies port for route

- Identifies port along the OSPF shortest path
- Adds prefix-port entry to its forwarding table:
  - (138.16.64/22 , port 4)



Hot Potato Routing

- Suppose there two or more best inter-routes.
- Then choose route with closest NEXT-HOP
  - Use OSPF to determine which gateway is closest
  - Q: From 1c, chose AS3 AS131 or AS2 AS17?
  - A: route AS3 AS201 since it is closer



How does entry get in forwarding table?

Summary

1. Router becomes aware of prefix
   - via BGP route advertisements from other routers
2. Determine router output port for prefix
   - Use BGP route selection to find best inter-AS route
   - Use OSPF to find best intra-AS route leading to best inter-AS route
   - Router identifies router port for that best route
3. Enter prefix-port entry in forwarding table

BGP routing policy



- A,B,C are *provider networks*
- X,W,Y are customer (of provider networks)
- X is *dual-homed:* attached to two networks
  - X does not want to route from B via X to C
  - .. so X will not advertise to B a route to C

BGP routing policy (2)



- A advertises path AW to B
- B advertises path BAW to X
- Should B advertise path BAW to C?
  - No way! B gets no "revenue" for routing CBAW since neither W nor C are B's customers
  - B wants to force C to route to w via A
  - B wants to route *only* to/from its customers!

Why different Intra-, Inter-AS routing ?

policy:

- inter-AS: admin wants control over how its traffic routed, who routes through its net.
- intra-AS: single admin, so no policy decisions needed

scale:

- hierarchical routing saves table size, reduced update traffic

performance:

- intra-AS: can focus on performance
- inter-AS: policy may dominate over performance

Chapter 4: outline

Broadcast routing

- deliver packets from source to all other nodes
- source duplication is inefficient:



- source duplication: how does source determine recipient addresses?

In-network duplication

- *flooding:* when node receives broadcast packet, sends copy to all neighbors
  - problems: cycles & broadcast storm
- *controlled flooding:* node only broadcasts pkt if it hasn't broadcast same packet before
  - node keeps track of packet ids already broadacsted
  - or reverse path forwarding (RPF): only forward packet if it arrived on shortest path between node and source
- *spanning tree:*
  - no redundant packets received by any node

Spanning tree

- first construct a spanning tree
- nodes then forward/make copies only along spanning tree



(a) broadcast initiated at A



(b) broadcast initiated at D

Spanning tree: creation

- center node
- each node sends unicast join message to center node
  - message forwarded until it arrives at a node already belonging to spanning tree



(a) stepwise construction of spanning tree (center: E)



(b) constructed spanning tree

Multicast routing: problem statement

goal: find a tree (or trees) connecting routers having local mcast group members

- *tree:* not all paths between routers used
- *shared-tree:* same tree used by all group members
- *source-based:* different tree from each sender to rcvrs



shared tree

source-based trees

Approaches for building mcast trees

approaches:

- *source-based tree:* one tree per source
  - shortest path trees
  - reverse path forwarding
- *group-shared tree:* group uses one tree
  - minimal spanning (Steiner)
  - center-based trees

…we first look at basic approaches, then specific protocols adopting these approaches

Shortest path tree

- mcast forwarding tree: tree of shortest path routes from source to all receivers
  - Dijkstra's algorithm



Reverse path forwarding

- rely on router's knowledge of unicast shortest path from it to sender
- each router has simple forwarding behavior:

if (mcast datagram received on incoming link on shortest path back to center)
then flood datagram onto all outgoing links
else ignore datagram

Reverse path forwarding: example



- result is a source-specific *reverse* SPT
  - may be a bad choice with asymmetric links

Reverse path forwarding: pruning

- forwarding tree contains subtrees with no mcast group members
  - no need to forward datagrams down subtree
  - "prune" msgs sent upstream by router with no downstream group members



Shared-tree: steiner tree

- *steiner tree:* minimum cost tree connecting all routers with attached group members
- problem is NP-complete
- excellent heuristics exists
- not used in practice:
  - computational complexity
  - information about entire network needed
  - monolithic: rerun whenever a router needs to join/leave

Center-based trees

- single delivery tree shared by all
- one router identified as *"center"* of tree
- to join:
  - edge router sends unicast *join-msg* addressed to center router
  - *join-msg* "processed" by intermediate routers and forwarded towards center
  - *join-msg* either hits existing tree branch for this center, or arrives at center
  - path taken by *join-msg* becomes new branch of tree for this router

Center-based trees: example

suppose R6 chosen as center:



Internet Multicasting Routing: DVMRP

- DVMRP: distance vector multicast routing protocol, RFC1075
- *flood and prune:* reverse path forwarding, source-based tree
  - RPF tree based on DVMRP's own routing tables constructed by communicating DVMRP routers
  - no assumptions about underlying unicast
  - initial datagram to mcast group flooded everywhere via RPF
  - routers not wanting group: send upstream prune msgs

DVMRP: continued…

- *soft state:* DVMRP router periodically (1 min.) "forgets" branches are pruned:
  - mcast data again flows down unpruned branch
  - downstream router: reprune or else continue to receive data
- routers can quickly regraft to tree
  - following IGMP join at leaf
- odds and ends
  - commonly implemented in commercial router

Tunneling

Q: how to connect "islands" of multicast routers in a "sea" of unicast routers?



- mcast datagram encapsulated inside "normal" (non-multicast-addressed) datagram
- normal IP datagram sent thru "tunnel" via regular IP unicast to receiving mcast router (recall IPv6 inside IPv4 tunneling)
- receiving mcast router unencapsulates to get mcast datagram

PIM: Protocol Independent Multicast

- not dependent on any specific underlying unicast routing algorithm (works with all)
- two different multicast distribution scenarios :

dense:
- group members densely packed, in "close" proximity.
- bandwidth more plentiful

sparse:
- # networks with group members small wrt # interconnected networks
- group members "widely dispersed"
- bandwidth not plentiful

Consequences of sparse-dense dichotomy:

dense
- group membership by routers *assumed* until routers explicitly prune
- *data-driven* construction on mcast tree (e.g., RPF)
- bandwidth and non-group-router processing *profligate*

sparse:
- no membership until routers explicitly join
- *receiver- driven* construction of mcast tree (e.g., center-based)
- bandwidth and non-group-router processing *conservative*

PIM- dense mode

flood-and-prune RPF: similar to DVMRP but…

- underlying unicast protocol provides RPF info for incoming datagram
- less complicated (less efficient) downstream flood than DVMRP reduces reliance on underlying routing algorithm
- has protocol mechanism for router to detect it is a leaf-node router

PIM - sparse mode

- center-based approach
- router sends *join* msg to rendezvous point (RP)
  - intermediate routers update state and forward *join*
- after joining via RP, router can switch to source-specific tree
  - increased performance: less concentration, shorter paths



PIM - sparse mode

sender(s):

- unicast data to RP, which distributes down RP-rooted tree
- RP can extend mcast tree upstream to source
- RP can send *stop* msg if no attached receivers
  - "no one is listening!"



Chapter 4: *done!*

4.1 introduction

4.2 virtual circuit and datagram networks

4.3 what's inside a router

4.4 IP: Internet Protocol
- datagram format, IPv4 addressing, ICMP, IPv6

4.5 routing algorithms
- link state, distance vector, hierarchical routing

4.6 routing in the Internet
- RIP, OSPF, BGP

4.7 broadcast and multicast routing

- understand principles behind network layer services:
  - network layer service models, forwarding versus routing how a router works, routing (path selection), broadcast, multicast
- instantiation, implementation in the Internet