

Proofs and Models in Philosophical Logic

propositional logic, modal logic, and identity

Greg Restall



University of
St Andrews

BRITISH LOGIC COLLOQUIUM · 3 SEPTEMBER 2021

<https://consequently.org/presentation/2021/pmpl-blc>

Soundness and Completeness

Propositional Logic: the case of classical proof

Modal Logic: the significance of worlds

Identity: *necessary or contingent?*

SOUNDNESS AND COMPLETENESS

- ▷ **SOUNDNESS:** If $X \vdash A$ then $X \vDash A$.
- ▷ **COMPLETENESS:** If $X \vDash A$ then $X \vdash A$.

- ▷ **SOUNDNESS:** If $X \vdash A$ then $X \vDash A$.
- ▷ **COMPLETENESS:** If $X \vDash A$ then $X \vdash A$.
- $X \vdash A$ — $(\exists \pi)(\pi \text{ is a proof from } X \text{ to } A)$.
- $X \vDash A$ — $(\forall \mathfrak{M})(\text{if } X \text{ holds at } \mathfrak{M}, \text{ so does } A)$.

- ▷ **SOUNDNESS:** If $X \vdash A$ then $X \vDash A$.
 - ▷ **COMPLETENESS:** If $X \vDash A$ then $X \vdash A$.
-
- $X \vdash A$ — $(\exists \pi)(\pi \text{ is a proof from } X \text{ to } A)$.
 - $X \vDash A$ — $(\forall \mathfrak{M})(\text{if } X \text{ holds at } \mathfrak{M}, \text{ so does } A)$.
 - $X \not\models A$ — $(\exists \mathfrak{M})(X \text{ holds at } \mathfrak{M}, \text{ but } A \text{ doesn't})$.
 - $X \not\vdash A$ — $(\forall \pi)(\text{if } \pi \text{ is from } X, \text{ isn't to } A)$.

- ▷ **SOUNDNESS:** If $X \vdash A$ then $X \vDash A$.
 - ▷ **COMPLETENESS:** If $X \vDash A$ then $X \vdash A$.
-
- $X \vdash A$ — $(\exists \pi)(\pi \text{ is a proof from } X \text{ to } A)$.
 - $X \vDash A$ — $(\forall \mathfrak{M})(\text{if } X \text{ holds at } \mathfrak{M}, \text{ so does } A)$.
 - $X \not\models A$ — $(\exists \mathfrak{M})(X \text{ holds at } \mathfrak{M}, \text{ but } A \text{ doesn't})$.
 - $X \not\vdash A$ — $(\forall \pi)(\text{if } \pi \text{ is from } X, \text{ isn't to } A)$.

Can we harness *both* proofs and models
to do interesting philosophical work?

PROPOSITIONAL LOGIC: THE CASE OF CLASSICAL PROOF

Models for classical logic

p	q	$p \wedge q$	$p \vee q$
0	0	0	0
0	1	0	1
1	0	0	1
1	1	1	1

$A \not\models B$ iff $(\exists v)(v(A) = 1 \text{ and } v(B) = 0)$

Models for classical logic

p	q	$p \wedge q$	$p \vee q$
0	0	0	0
0	1	0	1
1	0	0	1
1	1	1	1

$A \not\models B$ iff $(\exists v)(v(A) = 1 \text{ and } v(B) = 0)$

... iff $(\exists v)(v^-(A^-) = 0 \text{ and } v^-(B^-) = 1)$ iff $B^- \not\models A^-$.

Standard Proof Systems are *not* self-dual: Hilbert Proofs

1. $(A \rightarrow (A \rightarrow A)) \rightarrow ((A \rightarrow ((A \rightarrow A) \rightarrow A)) \rightarrow (A \rightarrow A))$ (DIST)
2. $A \rightarrow (A \rightarrow A)$ (WEAK)
3. $(A \rightarrow ((A \rightarrow A) \rightarrow A)) \rightarrow (A \rightarrow A)$ 1,2 (MP)
4. $A \rightarrow ((A \rightarrow A) \rightarrow A)$ (WEAK)
5. $A \rightarrow A$ 3,4 (MP)

Standard Proof Systems are *not* self-dual: Natural Deduction

$$\frac{\frac{p}{p \vee q} \vee I \quad p}{(p \vee q) \wedge p} \wedge I$$

$$\frac{p \vee (p \wedge q) \quad [p]^1 \quad \frac{[p \wedge q]^2}{p} \wedge E}{p} \vee E^{1,2}$$

Standard Proof Systems are *not* self-dual: Natural Deduction

$$\frac{p}{p \vee q} \vee I \quad \frac{p}{(p \vee q) \wedge p} \wedge I$$

$$\frac{p \vee (p \wedge q) \quad [p]^1 \quad \frac{[p \wedge q]^2}{p}}{p} \vee E^{1,2} \quad \wedge E$$

$$p \vdash (p \vee q) \wedge p$$

$$p \vee (q \wedge p) \vdash p$$

The Sequent Calculus *is* self-dual

$$\frac{\frac{p \succ p}{p \succ p \vee q} \vee R \quad p \succ p}{p, p \succ (p \vee q) \wedge p} \wedge R \quad \frac{\frac{p \succ p}{p \wedge q \succ p} \wedge L}{p \vee (p \wedge q) \succ p, p} \vee L$$

Generalising the proof context

From $X \succ A$ to $X \succ Y$.

Cut (two forms)

$$\frac{X \succ A, Y \quad X', A \succ Y'}{X, X' \succ Y, Y'} \textit{mCut}$$

$$\frac{X \succ A, Y \quad X, A \succ Y}{X \succ Y} \textit{aCut}$$

The Completeness Proof is *beautiful*

If there is no derivation of $X \succ Y$, then there is a valuation assigning 1 to each member of X and 0 to each member of Y .

The Completeness Proof is *beautiful*

If there is no derivation of $X \succ Y$, then there is a valuation assigning 1 to each member of X and 0 to each member of Y .

$$\frac{X \succ A, Y \quad X, A \succ Y}{X \succ Y} aCut$$

The Completeness Proof is *beautiful*

If there is no derivation of $X \succ Y$, then there is a valuation assigning 1 to each member of X and 0 to each member of Y .

$$\frac{X \succ A, Y \quad X, A \succ Y}{X \succ Y} aCut$$

If $[X : Y]$ is *available*, then so is either $[X : A, Y]$ or $[X, A : Y]$.

The Completeness Proof is *beautiful*

If there is no derivation of $X \succ Y$, then there is a valuation assigning 1 to each member of X and 0 to each member of Y .

$$\frac{X \succ A, Y \quad X, A \succ Y}{X \succ Y} aCut$$

If $[X : Y]$ is *available*, then so is either $[X : A, Y]$ or $[X, A : Y]$.

... and take this process *to the limit*.

Connective Rules

$$\frac{X, A, B \succ Y}{X, A \wedge B \succ Y} \wedge Df \quad \frac{X \succ A, B, Y}{X \succ A \vee B, Y} \vee Df$$

$$\frac{X, A \succ Y}{X \succ \neg A, Y} \neg Df \quad \frac{X, A \succ B, Y}{X \succ A \rightarrow B, Y} \rightarrow Df$$

An Interpretation

A derivation of $X \succ Y$ shows us how asserting each member of X and denying each member of Y is *out of bounds*.

An Interpretation

A derivation of $X \succ Y$ shows us how asserting each member of X and denying each member of Y is *out of bounds*.

$$X, A \succ A, Y \quad \frac{X \succ A, Y \quad X, A \succ Y}{X \succ Y} _{aCut}$$

Me, in 2005

MULTIPLE CONCLUSIONS

"Multiple Conclusions,"
in *Logic, Methodology and
Philosophy of Science:
Proceedings of the Twelfth
International Congress*,
edited by Petr Hajek,
Luis Valdes-Villanueva
and Dag Westerståhl,
Kings' College
Publications, 2005, 189–
205.

I argue for the following four theses. (1) Denial is not to be analysed as the assertion of a negation. (2) Given the concepts of assertion and denial, we have the resources to analyse logical consequence as relating arguments with multiple premises and multiple conclusions. Gentzen's multiple conclusion calculus can be understood in a straightforward, motivated, non-question-begging way. (3) If a broadly anti-realist or inferentialist justification of a logical system works, it works just as well for classical logic as it does for intuitionistic logic. The special case for an anti-realist justification of intuitionistic logic over and above a justification of classical logic relies on an unjustified assumption about the shape of proofs. Finally, (4) this picture of logical consequence provides a relatively neutral shared vocabulary which can help us understand and adjudicate debates between proponents of classical and non-classical logics.

 DOWNLOAD PDF

This paper has now been reprinted in *Analysis and Metaphysics*, 6, 2007, 14-34.

<https://consequently.org/writing/multipleconclusions/>

Invertible Rules look like *definitions*

$$\frac{X, A, B \succ Y}{X, A \wedge B \succ Y} \wedge Df \quad \frac{X \succ A, B, Y}{X \succ A \vee B, Y} \vee Df$$

$$\frac{X, A \succ Y}{X \succ \neg A, Y} \neg Df \quad \frac{X, A \succ B, Y}{X \succ A \rightarrow B, Y} \rightarrow Df$$

Are sequent derivations *proofs*?

The mistake in this position, however, resides in the idea that any formal game incorporating what appear to be inference rules will confer meanings on its logical symbols. Adherence to inferentialism importantly constrains one's choice of proof-theoretic frameworks and thus requires one to reject Carnap's amoralism about logic: the inferentialist must remain faithful to our ordinary inferential practice. Only those deductive systems that answer to the use we put our logical vocabulary to fit the bill. After all, it is the practice represented, not the formalism as such, that confers meanings. Therefore, the formalism is of meaning-theoretic significance and hence of interest to the inferentialist only if it succeeds in capturing (in a perhaps idealised form) the relevant meaning-constituting features of our practice. It is in this sense, then, that the inferentialist position imposes strict demands on the form deductive systems may take. For future reference, let us refer to these demands as the

Principle of answerability only such deductive systems are permissible as can be seen to be suitably connected to our ordinary deductive inferential practices.

Florian Steinberger, "Why Conclusions Should Remain Single"

JPL (2011) 40:333–355 <https://dx.doi.org/10.1007/s10992-010-9153-3>

This is not just *conservatism*

What is a proof of A?

This is not just *conservatism*

What is a proof of A?

A proof of A meets a *justification request* for the assertion of A.

This is not just *conservatism*

What is a proof of A?

A proof of A meets a *justification request* for the assertion of A.

(Not every way to meet a justification request is a *proof*,
but proofs meet justification requests in a *very* stringent way.)

What is the *context* in which justification requests are met?

- ▶ If it's other assertions (*assumptions*), the natural *shape* is $X \succ A$.

What is the *context* in which justification requests are met?

- ▶ If it's other assertions (*assumptions*), the natural *shape* is $X \succ A$.
- ▶ If it's *bilateralist*, the natural shape is $X \succ A; Y$.

What is justified *in* that context?

- If it's assertions only, the shape is $X \succ A; Y$.

What is justified *in* that context?

- ▶ If it's assertions only, the shape is $X \succ A; Y$.
- ▶ If it's assertions *and denials*, we have $X \succ A; Y$, and $X; A \succ Y$, and duality is restored.
- ▶ In the first case, we have the $\lambda\mu$ calculus, and in the second, fully *bilateralist* natural deduction.

MODAL LOGIC: THE SIGNIFICANCE OF WORLDS

Necessity and Possibility

It is necessary that p

It is possible that p

Necessity and Possibility


It is necessary that p

$$\Box p$$


It is possible that p

$$\Diamond p$$


Possible Worlds Models




Possible Worlds Models




Possible Worlds Models




Possible Worlds Models



Possible Worlds Models



Possible Worlds Models



How seriously should we take these models?

- ▶ What sort of thing *is* a world?
- ▶ Given a world, what is *true* at that world?
- ▶ Given any such world, how can we *know* what holds there?

... possible worlds, in the sense of possible states of affairs are not *really* individuals (just as numbers are not *really* individuals).

To say that a state of affairs obtains is just to say that something is the case; to say that something is a possible state of affairs is just to say that something could be the case; and to say that something is the case 'in' a possible state of affairs is just to say that the thing in question would necessarily be the case if that state of affairs obtained, i.e. if something else were the case ...

We understand 'truth in states of affairs' because we understand 'necessarily'; not *vice versa*.

— "Worlds, Times and Selves"
(1969)



Yes, but ...

How *do* we understand ‘*necessarily*’ and ‘*possibly*’?

Yes, but ...

How *do* we understand ‘*necessarily*’ and ‘*possibly*’?

... and what’s more, why does their logic
have possible worlds models *as models*?

Modal reasoning trades on *supposition* and *context shift*

Oswald shot Kennedy. But suppose he *hadn't*.

Modal reasoning trades on *supposition* and *context shift*

Oswald shot Kennedy. But suppose he *hadn't*.

I think that Oswald shot Kennedy.
But let's suppose that you're right and he didn't.

Modal reasoning trades on *supposition* and *context shift*

Oswald shot Kennedy. But suppose he *hadn't*.

I think that Oswald shot Kennedy.
But let's suppose that *you're* right and he *didn't*.

Oswald shot Kennedy | Oswald didn't shoot Kennedy

Two notions of necessity



1. SUBJUNCTIVE/METAPHYSICAL — how things *could have been* (had things gone differently) — If Oswald *hadn't* shot Kennedy ...

Two notions of necessity



1. SUBJUNCTIVE/METAPHYSICAL — how things *could have been* (had things gone differently) — If Oswald *hadn't* shot Kennedy ...
2. INDICATIVE/EPISTEMIC — how things *could actually be* (given some body of evidence) — If Oswald *didn't* shoot Kennedy ...

Two notions of necessity



1. SUBJUNCTIVE/METAPHYSICAL — how things *could have been* (had things gone differently) — If Oswald *hadn't* shot Kennedy ...
 2. INDICATIVE/EPISTEMIC — how things *could actually be* (given some body of evidence) — If Oswald *didn't* shoot Kennedy ...
- + Possible worlds semantics is useful in modelling *both* modal notions.

Two notions of necessity



1. SUBJUNCTIVE/METAPHYSICAL — how things *could have been* (had things gone differently) — If Oswald *hadn't* shot Kennedy ...
2. INDICATIVE/EPISTEMIC — how things *could actually be* (given some body of evidence) — If Oswald *didn't* shoot Kennedy ...
 - + Possible worlds semantics is useful in modelling *both* modal notions.
 - + Let's consider both these options in the development of a *proof system*.

Hypersequents

$$\Box A \succ \mid \succ A$$

A Defining Rule for Necessity

$$\frac{\succ A \mid X \succ Y \mid \mathcal{S}}{X \succ \Box A, Y \mid \mathcal{S}} \Box Df$$

A Defining Rule for Necessity

$$\frac{\succ A \mid X \succ Y \mid \mathcal{S}}{X \succ \Box A, Y \mid \mathcal{S}} \Box Df$$

Denying that A is necessary has the force of denying A in a fresh *context*.

A Defining Rule for Necessity

$$\frac{\succ A \mid X \succ Y \mid \mathcal{S}}{X \succ \Box A, Y \mid \mathcal{S}} \Box Df$$

Denying that A is necessary has the force of denying A in a fresh *context*.

Or, to *prove* that A is necessary, you *prove* A in an arbitrary context.

A Defining Rule for Necessity

$$\frac{\succ A \mid X \succ Y \mid \mathcal{S}}{X \succ \Box A, Y \mid \mathcal{S}} \Box Df$$

Denying that A is necessary has the force of denying A in a fresh *context*.

Or, to *prove* that A is necessary, you *prove* A in an arbitrary context.

So, necessity expresses a kind of *preservation across contexts*.

A Defining Rule for Necessity

$$\frac{\succ A \mid X \succ Y \mid S}{X \succ \Box A, Y \mid S} \Box Df$$

Denying that A is necessary has the force of denying A in a fresh *context*.

Or, to *prove* that A is necessary, you *prove* A in an arbitrary context.

So, necessity expresses a kind of *preservation across contexts*.

Indicative context shifts produce an epistemic necessity (\Box_E).

Subjunctive context shifts produce a metaphysical necessity (\Box_M).

A Defining Rule for Necessity

$$\frac{\succ A \mid X \succ Y \mid S}{X \succ \Box A, Y \mid S} \Box Df$$

Denying that A is necessary has the force of denying A in a fresh *context*.

Or, to *prove* that A is necessary, you *prove* A in an arbitrary context.

So, necessity expresses a kind of *preservation across contexts*.

Indicative context shifts produce an epistemic necessity (\Box_E).

Subjunctive context shifts produce a metaphysical necessity (\Box_M).

The *form* of the rule is the same in either case, though the *content* differs.

An example derivation

$$\frac{\begin{array}{c} \square p \succ \square p \\ \hline \succ p \mid \square p \succ \end{array} \square Df \uparrow \quad \frac{\begin{array}{c} \neg \square p \succ \neg \square p \\ \hline \square p, \neg \square p \succ \end{array} \neg Df \uparrow}{\square p, \neg \square p \succ} \neg Df \downarrow}{\square p \succ \square \neg \square p} mCut$$
$$\frac{\begin{array}{c} \neg \square p \succ \mid \square p \succ \\ \hline \neg \square p \succ \mid \succ \neg \square p \end{array} \neg Df \downarrow}{\neg \square p \succ \square \neg \square p} \square Df \downarrow$$

Cut (multiplicative and additive)

$$\frac{X \succ A, Y | \mathcal{S} \quad X', A \succ Y' | \mathcal{S}'}{X, X' \succ Y, Y' | \mathcal{S} | \mathcal{S}'} mCut$$

Cut (multiplicative and additive)

$$\frac{X \succ A, Y | \mathcal{S} \quad X', A \succ Y' | \mathcal{S}'}{X, X' \succ Y, Y' | \mathcal{S} | \mathcal{S}'} mCut$$

$$\frac{X \succ A, Y | \mathcal{S} \quad X, A \succ Y | \mathcal{S}}{X \succ Y | \mathcal{S}} aCut$$

Expanding Positions

$$\frac{X \succ A, Y | \mathcal{S} \quad X, A \succ Y | \mathcal{S}}{X \succ Y | \mathcal{S}} \text{ } aCut \qquad \frac{\succ A | X \succ \Box A, Y | \mathcal{S}}{X \succ \Box A, Y | \mathcal{S}} \text{ } \Box R'$$

Hypersequents in the Limit

- ▶ Zones in limit positions are like *worlds*.

Hypersequents in the Limit

- ▶ Zones in limit positions are like *worlds*.
- ▶ Each *world* decides every statement, one way or another.

Hypersequents in the Limit

- ▶ Zones in limit positions are like *worlds*.
- ▶ Each *world* decides every statement, one way or another.
- ▶ The Boolean connectives have the usual properties.

Hypersequents in the Limit

- ▶ Zones in limit positions are like *worlds*.
- ▶ Each *world* decides every statement, one way or another.
- ▶ The Boolean connectives have the usual properties.
- ▶ $\Box A$ is false in one iff A is false in one.

Hypersequents in the Limit

- ▶ Zones in limit positions are like *worlds*.
- ▶ Each *world* decides every statement, one way or another.
- ▶ The Boolean connectives have the usual properties.
- ▶ $\Box A$ is false in one iff A is false in one.
- ▶ $\Box A$ is true in one iff A is true in all.

We can help Prior answer his open question

- We *understand* modal concepts by governing our assertions and denials (and inferences) by way of these rules, connecting the modal operators with zone shifts.

We can help Prior answer his open question

- ▶ We *understand* modal concepts by governing our assertions and denials (and inferences) by way of these rules, connecting the modal operators with zone shifts.
- ▶ Since they have *this* logical structure, possible worlds models get their behaviour *right*.

We can help Prior answer his open question

- ▶ We *understand* modal concepts by governing our assertions and denials (and inferences) by way of these rules, connecting the modal operators with zone shifts.
- ▶ Since they have *this* logical structure, possible worlds models get their behaviour *right*.
- ▶ But those models are only ever *models* of the contexts arising out of our *use*.

This is explanatorily rich

- ▶ The models work equally well for *epistemic* and *metaphysical* modals.

This is explanatorily rich

- ▶ The models work equally well for *epistemic* and *metaphysical* modals.
- ▶ The simple (S5) hypersequent structure can be generalised (see Poggiolesi on *Tree Hypersequents*).

This is explanatorily rich

- ▶ The models work equally well for *epistemic* and *metaphysical* modals.
- ▶ The simple (S5) hypersequent structure can be generalised (see Poggiolesi on *Tree Hypersequents*).
- ▶ The result is two different perspectives on modal vocabulary:
(1) *representational* (models), and (2) *normative pragmatic* (proofs).

IDENTITY: NECESSARY OR CONTINGENT?

Identity

Identity and harmony

STEPHEN READ

1. Harmony

The inferentialist account of logic says that the meaning of a logical operator is given by the rules for its application. Prior (1960–61) showed that a simple and straightforward interpretation of this account of logicality reduces to absurdity. For if ‘tonk’ has the meaning given by the rules Prior proposed for it, contradiction follows. Accordingly, a more subtle interpretation of inferentialism is needed. Such a proposal was put forward initially by Gentzen (1934) and elaborated by, e.g., Prawitz (1977). The meaning of a logical expression is given by the rules for the assertion of statements containing that expression (as designated component); these are its introduction-rules. The meaning so given justifies further rules for drawing inferences from such assertions; these are its elimination-rules:

The introductions represent, as it were, the ‘definitions’ of the symbols concerned, and the eliminations are no more, in the final analysis, than the consequence of these definitions. (Gentzen 1934: 80)

For example, if the only ground for assertion of ‘ p tonk q ’ is given by Prior’s rule:

$$\frac{p}{p \text{ tonk } q} \text{ tonk-I}$$

then Prior mis-stated the elimination-rule. It should read

$$\frac{(p) \quad p \text{ tonk } q \quad r}{r} \text{ tonk-E}$$



A Defining Rule for Identity

$$\frac{X, Fa \succ Fb, Y \quad X, Fb \succ Fa, Y}{X \succ a = b, Y} =Df$$

A Defining Rule for Identity

$$\frac{X, Fa \succ Fb, Y \quad X, Fb \succ Fa, Y}{X \succ a = b, Y} =Df$$

Denying $a = b$ has the same significance as taking there to be *some* feature F that holds of a but not b , or *vice versa*.

A Defining Rule for Identity

$$\frac{X, Fa \succ Fb, Y \quad X, Fb \succ Fa, Y}{X \succ a = b, Y} =Df$$

Denying $a = b$ has the same significance as taking there to be *some* feature F that holds of a but not b , or *vice versa*.

Or equivalently, to prove that $a = b$, prove Fb from the assumption Fa (and *vice versa*), where the predicate F is *arbitrary*.

A Defining Rule for Identity

$$\frac{X, Fa \succ Fb, Y \quad X, Fb \succ Fa, Y}{X \succ a = b, Y} = Df$$

Denying $a = b$ has the same significance as taking there to be *some* feature F that holds of a but not b , or *vice versa*.

Or equivalently, to prove that $a = b$, prove Fb from the assumption Fa (and *vice versa*), where the predicate F is *arbitrary*.


Identity is a kind of *indistinguishability*.

Doesn't identity become necessary, *automatically*?

$$\frac{\frac{\frac{\frac{\vdash a = a}{\vdash a = a}^{Refl}}{\vdash \Box(a = a)} \Box I}{\vdash \lambda x. \Box(a = x) a} \lambda Df \downarrow \quad \frac{}{a = b, \lambda x. \Box(a = x) a \succ \lambda x. \Box(a = x) b} = L.ax_1}{a = b \succ \lambda x. \Box(a = x) b} \quad Cut$$

$$\frac{}{a = b \succ \Box(a = b)} \lambda Df \uparrow$$

Willamson *defends* the necessity of identity



Williamson on the necessity of identity

... to mess with the modal or temporal logic of identity in order to avoid ontological inflation would be a lapse of methodological good taste, or good sense, for it means giving more weight to ontology than to the vastly better developed and more successful discipline of logic.

More specifically, the classical modal or temporal logic is a strong, simple, and elegant theory. To weaken, complicate, and uglify it without overwhelming reason to do so merely in order to block the derivation of the necessity or permanence of identity would be as retrograde and wrong-headed a step in logic and metaphysics as natural scientists would consider a comparable sacrifice of those virtues in a physical theory.

— Timothy Williamson, *Modal Logic as Metaphysics*, pp. 26, 27.


Modal Logic with Contingent Identity




Giovanna Corsi “Counterpart Semantics” 2002




Maria Aloni “Individual Concepts in Modal Predicate Logic” 2005




Hesperus



Phosphorous



Hesperus



Phosphorous

$$h = p \mid h \neq p$$

Identity and Context Shift

$$a = b \succ | Fa \succ Fb$$

Is it consistent to grant that $a = b$ in one context,
while distinguishing a from b in another?

Identity and Context Shift

$$a = b \succ | Fa \succ Fb$$

Is it consistent to grant that $a = b$ in one context,
while distinguishing a from b in another?

Indicative shifts (*disagreement*): This seems consistent.
(We *learned* that $h = p$. The possibility that $h \neq p$ was open to us.)

Identity and Context Shift

$$a = b \succ | Fa \succ Fb$$

Is it consistent to grant that $a = b$ in one context,
while distinguishing a from b in another?

- Indicative shifts (*disagreement*): This seems consistent.
(We *learned* that $h = p$. The possibility that $h \neq p$ was open to us.)
- Subjunctive shifts (*planning*): This is much less plausible.
($h = p$. Were I to travel to h , then of necessity, I am going to p .)

More from Williamson

... we are not interested in epistemic readings of 'it is possible that'.

— Timothy Williamson, *Modal Logic as Metaphysics*, p. 11, fn. 17.

Subjunctive Context Shifts: Necessary Identity Rules

$$\frac{\mathsf{Fa} \succ \mathsf{Fb} \mid X \succ Y \mid \mathcal{S} \quad \mathsf{Fb} \succ \mathsf{Fa} \mid X \succ Y \mid \mathcal{S}}{X \succ a = b, Y \mid \mathcal{S}} = Df$$

Subjunctive Context Shifts: *Necessary Identity Rules*

$$\frac{Fa \succ Fb \mid X \succ Y \mid S \quad Fb \succ Fa \mid X \succ Y \mid S}{X \succ a = b, Y \mid S} =Df$$

To deny $a = b$ is to take a and b to be distinguishable.

A Derivation

$$\frac{\frac{a = b \succ a = b}{a = b \succ | Fa \succ Fb} =Df\uparrow \quad \frac{a = b \succ a = b}{a = b \succ | Fb \succ Fa} =Df\uparrow}{\frac{a = b \succ | \succ a = b}{a = b \succ \Box a = b}} =Df\downarrow \quad \Box Df\downarrow$$

Epistemic Shifts: Contingent Identity

- ▶ BLOCK THIS: $a = b \succ | Fa \succ Fb$

Epistemic Shifts: Contingent Identity

- ▶ BLOCK THIS: $a = b \succ | Fa \succ Fb$
- ▶ DERIVE THIS: $a = b, Fa \succ Fb$

Epistemic Shifts: Contingent Identity

- ▶ BLOCK THIS: $a = b \succ | Fa \succ Fb$
- ▶ DERIVE THIS: $a = b, Fa \succ Fb$
- ▶ This requires distinguishing kinds of predicates, because we *also* want to reject $a = b, \lambda x. \Box_E(a = x)a \succ \lambda x. \Box_E(a = x)b$.

Epistemic Shifts: Contingent Identity

- ▶ BLOCK THIS: $a = b \succ | Fa \succ Fb$
- ▶ DERIVE THIS: $a = b, Fa \succ Fb$
- ▶ This requires distinguishing kinds of predicates, because we *also* want to reject $a = b, \lambda x. \Box_E(a = x)a \succ \lambda x. \Box_E(a = x)b$.
 - ▶ To distinguish a from b we want to find some *feature* a has that b lacks (or *vice versa*).

Epistemic Shifts: Contingent Identity

- ▶ BLOCK THIS: $a = b \succ | Fa \succ Fb$
- ▶ DERIVE THIS: $a = b, Fa \succ Fb$
- ▶ This requires distinguishing kinds of predicates, because we *also* want to reject $a = b, \lambda x. \Box_E(a = x)a \succ \lambda x. \Box_E(a = x)b$.
 - ▶ To distinguish a from b we want to find some *feature* a has that b lacks (or *vice versa*). Epistemic modalities do not always generate features.

Epistemic Shifts: Contingent Identity

- ▶ BLOCK THIS: $a = b \succ | Fa \succ Fb$
- ▶ DERIVE THIS: $a = b, Fa \succ Fb$
- ▶ This requires distinguishing kinds of predicates, because we *also* want to reject $a = b, \lambda x. \Box_E(a = x)a \succ \lambda x. \Box_E(a = x)b$.
 - ▶ To distinguish a from b we want to find some *feature* a has that b lacks (or *vice versa*). Epistemic modalities do not always generate features.
 - ▶ After all, it's no argument against $h = p$ that it's epistemically necessary that $h = h$ and not epistemically necessary that $h = p$.

Two Kinds of Predicates

F : *feature predicates*

G : *general predicates*

Two Kinds of Predicates

F : *feature predicates*

G : *general predicates*

- ▶ Feature predicates are closed under the classical connectives and quantifiers and λ .

Two Kinds of Predicates

F : *feature predicates*

G : *general predicates*

- ▶ Feature predicates are closed under the classical connectives and quantifiers and λ .
- ▶ Applying λ into \Box_E contexts creates a *general predicate*.

Two Kinds of Predicates

F : *feature predicates*

G : *general predicates*

- ▶ Feature predicates are closed under the classical connectives and quantifiers and λ .
- ▶ Applying λ into \Box_E contexts creates a *general predicate*.
- ▶ There are two kinds of *Spec* rule: one for feature predicates, and one for general predicates.

Contingent Identity Rules

$$\frac{X, Fa \succ Fb, Y | \mathcal{S} \quad X, Fb \succ Fa, Y | \mathcal{S}}{a = b, X \succ Y | \mathcal{S}} =Df$$

Contingent Identity Rules

$$\frac{X, Fa \succ Fb, Y | \mathcal{S} \quad X, Fb \succ Fa, Y | \mathcal{S}}{a = b, X \succ Y | \mathcal{S}} =Df$$

To deny $a = b$ is to take there to be some way to *distinguish* a and b .

Two Dimensions—with *actuality*

$$\begin{array}{c} X_1^1 \succ_{@} Y_1^1 \quad | \quad X_2^1 \succ Y_2^1 \quad | \quad \cdots \quad | \quad X_{m_1}^1 \succ Y_{m_1}^1 \quad || \\ X_1^2 \succ_{@} Y_1^2 \quad | \quad X_2^2 \succ Y_2^2 \quad | \quad \cdots \quad | \quad X_{m_2}^2 \succ Y_{m_2}^2 \quad || \\ \vdots \qquad \qquad \vdots \qquad \qquad \vdots \\ X_1^n \succ_{@} Y_1^n \quad | \quad X_2^n \succ Y_2^n \quad | \quad \cdots \quad | \quad X_{m_n}^n \succ Y_{m_n}^n \end{array}$$

Features of these rules

- ▶ The modal rules are conservative and uniquely defining, relative to the choice of *context shift*.

Features of these rules

- ▶ The modal rules are conservative and uniquely defining, relative to the choice of *context shift*. (If \Box is introduced twice, given the same hypersequent separator, those operators are equivalent.)

Features of these rules

- ▶ The modal rules are conservative and uniquely defining, relative to the choice of *context shift*. (If \Box is introduced twice, given the same hypersequent separator, those operators are equivalent.)
- ▶ The necessary identity rules are conservative and uniquely defining, relative to the choice of *predicates* in the language.

Features of these rules

- ▶ The modal rules are conservative and uniquely defining, relative to the choice of *context shift*. (If \Box is introduced twice, given the same hypersequent separator, those operators are equivalent.)
- ▶ The necessary identity rules are conservative and uniquely defining, relative to the choice of *predicates* in the language. (If two identity predicates are added using the same form of rules, they are equivalent, provided that both identity predicates count as *predicates* for the purposes of both sets of rules.)

Features of these rules

- ▶ The modal rules are conservative and uniquely defining, relative to the choice of *context shift*. (If \Box is introduced twice, given the same hypersequent separator, those operators are equivalent.)
- ▶ The necessary identity rules are conservative and uniquely defining, relative to the choice of *predicates* in the language. (If two identity predicates are added using the same form of rules, they are equivalent, provided that both identity predicates count as *predicates* for the purposes of both sets of rules.)
- ▶ The contingent identity rules are conservative and uniquely defining, relative to the choice of *feature predicates* in the language.

Features of these rules

- ▶ The modal rules are conservative and uniquely defining, relative to the choice of *context shift*. (If \Box is introduced twice, given the same hypersequent separator, those operators are equivalent.)
- ▶ The necessary identity rules are conservative and uniquely defining, relative to the choice of *predicates* in the language. (If two identity predicates are added using the same form of rules, they are equivalent, provided that both identity predicates count as *predicates* for the purposes of both sets of rules.)
- ▶ The contingent identity rules are conservative and uniquely defining, relative to the choice of *feature predicates* in the language. (If two identity predicates are added using the same form of rules, they are equivalent, provided that both identity predicates count as *feature predicates* for the purposes of both sets of rules.)

SLOGAN: The *limit* of the process of filling out an underivable (hyper)sequent describes a *model*.

Models

SLOGAN: The *limit* of the process of filling out an underivable (hyper)sequent describes a *model*.

$$\frac{X \succ A, Y | \mathcal{S} \quad X, A \succ Y | \mathcal{S}}{X \succ Y | \mathcal{S}} aCut \qquad \frac{\succ A | X \succ \Box A, Y | \mathcal{S}}{X \succ \Box A, Y | \mathcal{S}} \Box Df\uparrow$$

Models

SLOGAN: The *limit* of the process of filling out an underivable (hyper)sequent describes a *model*.

$$\frac{X \succ A, Y | \mathcal{S} \quad X, A \succ Y | \mathcal{S}}{X \succ Y | \mathcal{S}} \text{aCut} \qquad \frac{\succ A | X \succ \Box A, Y | \mathcal{S}}{X \succ \Box A, Y | \mathcal{S}} \Box Df\uparrow$$

The zones in correspond to *worlds*,
the formulas in the LHS are *true*
and those in the RHS are *false*.

Necessary Identity Models

- ▶ ‘ \equiv ’ determines an equivalence relation on terms.

Necessary Identity Models

- ▶ ‘ \equiv ’ determines an equivalence relation on terms.
- ▶ Its extension is constant across each world.

Necessary Identity Models

- ▶ ‘ \equiv ’ determines an equivalence relation on terms.
- ▶ Its extension is constant across each world.
- ▶ ‘ \equiv ’ determines a congruence relation for each predicate at each world.

Necessary Identity Models

- ▶ ‘ \equiv ’ determines an equivalence relation on terms.
- ▶ Its extension is constant across each world.
- ▶ ‘ \equiv ’ determines a congruence relation for each predicate at each world.
- ▶ Take the quotient of the terms by identity to form your ‘domain’.

Necessary Identity Models

- ▶ ‘ \equiv ’ determines an equivalence relation on terms.
- ▶ Its extension is constant across each world.
- ▶ ‘ \equiv ’ determines a congruence relation for each predicate at each world.
- ▶ Take the quotient of the terms by identity to form your ‘domain’.
- ▶ The expected truth conditions hold for the logical operators.

Necessary Identity Models

- ▶ ‘ \equiv ’ determines an equivalence relation on terms.
- ▶ Its extension is constant across each world.
- ▶ ‘ \equiv ’ determines a congruence relation for each predicate at each world.
- ▶ Take the quotient of the terms by identity to form your ‘domain’.
- ▶ The expected truth conditions hold for the logical operators.
- ▶ These are regular models for constant domain s5 with necessary identity.

Necessary Identity Models


- ▶ ‘ \equiv ’ determines an equivalence relation on terms.
- ▶ Its extension is constant across each world.
- ▶ ‘ \equiv ’ determines a congruence relation for each predicate at each world.
- ▶ Take the quotient of the terms by identity to form your ‘domain’.
- ▶ The expected truth conditions hold for the logical operators.
- ▶ These are regular models for constant domain s5 with necessary identity.
- ▶ (The usual rules for quantifiers work, too.)

Contingent Identity Models

$$a = b, c = d \succ b = c \mid b = c \succ a = d \mid a = b, b = c \succ a = d$$


Contingent Identity Models

$$a = b, c = d \succ b = c \mid b = c \succ a = d \mid a = b, b = c \succ a = d$$



Contingent Identity Models

$$a = b, c = d \succ b = c \mid b = c \succ a = d \mid a = b, b = c \succ a = d$$



Contingent Identity Models

F_a, F_b

F_c, F_d


F_a, F_d

F_b, F_c

F_a, F_b, F_c


F_d

$a = b, c = d \succ b = c \mid b = c \succ a = d \mid a = b, b = c \succ a = d$




F : feature predicate

Contingent Identity Models



F: feature predicate
G: general predicate

Contingent Identity Models



BEYOND

Where to from here?

1. Philosophically:

What speech acts and parts of speech play semantically significant roles?

If we start from the normative pragmatics, what should we look for in a *model*?

2. Formally:

There are many open questions around hypersequent calculi:

Cut elimination procedures, expressive power, complexity,

identity of proofs, and more ...

Thank you!

SLIDES: <https://consequently.org/presentation/2021/pmpl-blc>

FEEDBACK: @consequently on *Twitter*,
or *email* at greg@consequently.org