

Compositional Algebra over Fixed-Width Quaternionic-Symbolic State Packets

Cody Churchwell

Independent Researcher

github.com/consigcody94/quaternion-monoid-algebra

May 2026 (v1); July 2026 (this version, adding the isometry results of Section 3)

Abstract

We define a compositional algebra over a fixed-width packet structure that carries a unit quaternion, a small number of symbolic metadata fields, and a positive scaling factor. A closed binary operation is defined on the packet space with the property that the space, equipped with this operation, forms a monoid: closure, two-sided identity, and associativity. The construction is field-by-field; each sub-field operation is drawn from a small set of associative monoid operations on its respective value space (Hamilton multiplication on the quaternion factor; lookup-table substitution, lattice maximum, modular addition, parity XOR, and multiplicative scaling on the symbolic and scaling factors). The composite operation inherits associativity from the per-field operations. On the topological side we prove two results and scope a third: translations by unit quaternions are isometries of the projective geodesic metric, so composing an entire configuration with a common packet preserves Vietoris–Rips persistence diagrams *exactly* in every homology dimension; iterated composition is an isometric development whose consecutive step lengths equal the stimulus offsets from identity, with a subadditive window bound; and no universal two-sided bound on the H_1 -persistence ratio of trajectory to input stream can hold (a constant stream inflates H_1 unboundedly), so the observed bounded ratio is documented as an empirical property of structured stimulus classes. The construction is validated by a layered suite (property-based tests with machine checks of each proved statement, an algebraic-property runner with bit-exact GPU/CPU correspondence, and stress tests on two public motion datasets: TUM RGB-D and EuRoC MAV). Three application classes follow: composable agent-state evolution, algebraic chain verification, and multi-source state composition. A permissively-licensed reference implementation accompanies this paper.

1 Introduction

A recurring problem in robotics, swarm coordination, and accountability infrastructure is the need for a bounded-width, time-evolving state representation that is simultaneously composable, verifiable, and efficient enough for edge deployment. Existing representations trade these properties against one another. Raw floating-point quaternion streams are compact for rotation but offer no composition operation beyond Hamilton multiplication on the rotation component, and carry no symbolic metadata. Variable-width cryptographic audit chains compose via Merkle structures but are not fixed-width and are not amenable to single-cycle hardware composition. High-dimensional vector embeddings compose via vector arithmetic but are lossy and lack a unit-rotation guarantee.

This paper defines a fixed-width construction that fills the gap. A packet carries a unit quaternion plus a small number of symbolic metadata fields plus a scaling factor, with a defined composition operation whose result is itself a packet of the same width. The resulting algebra has,

simultaneously: closure under composition, the algebraic structure of a monoid (so chains of operations compose freely and associatively), and an empirically-observed topology-preservation property under iterated composition.

2 Construction

2.1 The packet structure

A packet is the tuple

$$p = (q, f_a, f_b, f_c, f_d, \pi, s),$$

where $q \in S^3$ is a unit quaternion in (w, x, y, z) layout; f_a, f_b, f_c, f_d are small symbolic fields of fixed bit width; $\pi \in \{0, 1\}$ is a parity bit; and $s \in \mathbb{R}_{>0}$ is a positive scaling factor. Field widths are parameters of the construction. A representative default (widths 4, 3, 5, 3 bits, plus parity, plus a smallest-three quaternion encoding in 32 bits, plus an IEEE-754 binary16 scaling factor) fits a 64-bit packet.

2.2 The composition operation

For two packets p_1 and p_2 , the composition $p_1 \otimes p_2$ is defined field-by-field:

Sub-field	Operation	Algebraic basis
q	Hamilton product, then normalize	S^3 group structure
f_a	$T_a[i, j]$ lookup (default $i \oplus j$)	$\mathbb{Z}_2^b$ abelian group
f_b	$\max(i, j)$	totally-ordered lattice
f_c	$(i + j) \bmod 2^{b_c}$	$\mathbb{Z}/2^{b_c}\mathbb{Z}$ group
f_d	$T_d[i, j]$ lookup (default $i \oplus j$)	$\mathbb{Z}_2^b$ abelian group
π	$\pi_1 \oplus \pi_2$	$\mathbb{Z}_2$ group
s	$s_1 \cdot s_2$	$\mathbb{R}_{>0}$ under multiplication

The identity element is $I = (q_{\text{id}}, 0, 0, 0, 0, 0, 1)$, where $q_{\text{id}} = (1, 0, 0, 0)$.

2.3 Monoid properties

Proposition 1 (Closure). *For all valid packets p_1, p_2 , the product $p_1 \otimes p_2$ is a valid packet.*

Proof sketch. Each per-field operation maps into the same field. The Hamilton product of two unit quaternions, after normalization, is a unit quaternion. XOR and modular addition remain in finite range. Lattice maximum of two values in $[0, 2^b)$ remains in $[0, 2^b)$. The product of two positive reals is a positive real. $\square$

Proposition 2 (Two-sided identity). *$I \otimes p = p \otimes I = p$ for all valid p .*

Proof sketch. Field-wise: q_{id} is the quaternion identity; lookup tables satisfy $T[0, j] = j$ and $T[i, 0] = i$; $\max(0, x) = x$; $0 + x \equiv x \pmod{N}$; $0 \oplus x = x$; and $1 \cdot x = x$. $\square$

Proposition 3 (Associativity). *$(a \otimes b) \otimes c = a \otimes (b \otimes c)$ for all valid a, b, c .*

Proof sketch. Each per-field operation is associative on its value space: Hamilton product on the quaternion group; XOR on $\mathbb{Z}_2^b$; maximum on a totally-ordered lattice; modular addition on $\mathbb{Z}/N\mathbb{Z}$; parity XOR on $\mathbb{Z}_2$; multiplication on $\mathbb{R}_{>0}$. A field-wise product of associative operations is associative. $\square$

Together these three propositions establish that the packet space, equipped with $\otimes$, is a monoid.

3 Topological properties

Work in $\mathbb{H} \cong \mathbb{R}^4$ with the Euclidean inner product $\langle a, b \rangle = \text{Re}(a\bar{b})$. The validation suite measures distances between unit quaternions with

$$d(p, q) = \arccos(|\langle p, q \rangle|),$$

the geodesic metric on $S^3/\{\pm 1\} \cong \mathbb{RP}^3 \cong SO(3)$: the absolute value identifies q and $-q$, which encode the same rotation. For unit inputs the quaternion sub-field of $g \otimes p$ is exactly the left translation $L_{q_g} : q \mapsto q_g q$ (renormalization is the identity in exact arithmetic since $|q_g q| = |q_g| |q| = 1$).

Lemma 1 (Translations are isometries). *For any unit quaternion g and all $a, b \in \mathbb{H}$: $\langle ga, gb \rangle = \langle a, b \rangle$ and $\langle ag, bg \rangle = \langle a, b \rangle$.*

Proof. Using $\overline{xy} = \bar{y} \bar{x}$ and cyclicity of the real part, $\text{Re}(xy) = \text{Re}(yx)$:

$$\langle ga, gb \rangle = \text{Re}(ga \overline{gb}) = \text{Re}(g a \bar{b} \bar{g}) = \text{Re}(\bar{a} \bar{b} \bar{g} g) = \text{Re}(\bar{a} \bar{b}) |g|^2 = \langle a, b \rangle,$$

$$\text{and } \langle ag, bg \rangle = \text{Re}(ag \overline{bg}) = \text{Re}(a \bar{g} \bar{b} g) = \text{Re}(a \bar{b}) |g|^2 = \langle a, b \rangle. \quad \square$$

Since d is a function of $|\langle \cdot, \cdot \rangle|$ alone, left and right translations are isometries of $(\mathbb{RP}^3, d)$.

Theorem 1 (Exact preservation under common composition). *Let $P = \{p_1, \dots, p_n\}$ be packets and g any packet. The quaternion configurations of P and of $\{g \otimes p_i\}$ (or $\{p_i \otimes g\}$) have identical pairwise distance matrices under d , hence identical Vietoris–Rips filtrations, hence equal persistence diagrams in every homology dimension.*

Proof. The quaternion component of $g \otimes p_i$ is $L_{q_g} q_{p_i}$ exactly; by Lemma 1 all pairwise distances are unchanged; a Vietoris–Rips filtration is a function of the distance matrix alone, and persistence diagrams are determined by the filtration. $\square$

This is the formal content behind multi-source composition (Section 5): folding a common state into every member of a configuration preserves the configuration’s topological signature exactly, not approximately.

Lemma 2 (Subadditivity). *$d(1, ab) \leq d(1, a) + d(1, b)$ for unit quaternions a, b .*

Proof. Triangle inequality through a , then left-invariance: $d(1, ab) \leq d(1, a) + d(a, ab) = d(1, a) + d(1, b)$. $\square$

Proposition 4 (Lipschitz development). *For the trajectory $q_t = x_1 x_2 \cdots x_t$ of the recurrence $q_t = q_{t-1} x_t$ from $q_0 = 1$, and $s < t$:*

$$d(q_s, q_t) = d(1, x_{s+1} \cdots x_t) \leq \sum_{i=s+1}^t d(1, x_i),$$

and in particular $d(q_{t-1}, q_t) = d(1, x_t)$ exactly: consecutive trajectory step lengths are precisely the stimulus offsets from identity.

Proof. Cancel q_s on the left by invariance (Lemma 1); induct on the window length with Lemma 2. $\square$

Remark 1 (Iterated preservation is empirical, necessarily). *When the algebra is applied iteratively via $\text{state}[t+1] = \text{state}[t] \otimes \text{stim}[t]$, the validation suite observes that the H_1 persistence ratio of trajectory to input stream falls in $[0.3, 5.0]$ for structured inputs (multi-frequency torus walks and the real robot/MAV streams of Section 4). This cannot be a theorem for arbitrary streams: a constant stream $x_t = x$ has a one-point input set (zero H_1) while its trajectory $\{x^k\}$ winds a geodesic circle whose Rips filtration carries positive H_1 , so the ratio is unbounded above; conversely, streams alternating between two orthogonal one-parameter subgroups can spread cumulative products quasi-uniformly, washing out trajectory H_1 . Both the proved statements above and this impossibility demonstration are machine-checked in the repository’s test suite.*

4 Validation

The accompanying reference implementation is validated in three layers: a property-based suite (77 tests driven by Hypothesis, covering the monoid laws under adversarial inputs, boundary validation, custom-table validation, batch-versus-scalar equivalence, and machine checks of Lemma 1 through Remark 1); eight algebraic-property tests (left and right identity over 100 packets, associativity over 512 random triples, closure over 500 random pairs, stability over a 1000-step self-product chain, power consistency, and bit-exact GPU/CPU correspondence); and seven stress tests (10,000-step long-horizon stability, single-bit avalanche sensitivity, distinguishability across 100 chains, real-data behavior on two public motion streams, field-saturation characterization, and scale stability).

The GPU implementation agrees with the CPU reference bit-for-bit on the Hamilton product: maximum absolute difference 0.00e+00 across 100,000 random pairs at single precision. The real-data tests verify clean behavior on the TUM RGB-D Pioneer 360 ground-truth sequence [3] (2,000 poses) and the EuRoC MAV Machine Hall 01 ground truth [4] (36,000 poses), each downloaded at runtime with SHA-256 pinning, composing every quaternion while preserving the unit-norm constraint to machine precision.

The field-saturation test documents an honest limitation: the $\max(\cdot)$ sub-field saturates under iteration (it is associative with identity 0 but is not invertible), so it functions as a one-way “high-amplitude event seen” flag rather than a state register; the XOR and modular-addition fields are information-preserving over their respective groups. The reference implementation additionally ships a library of verified alternative sub-field constructions (modular addition and multiplication, lattice maximum and minimum, bitwise conjunction and disjunction) with a monoid-table validator that checks closure, the identity laws, and full associativity with a counterexample on failure.

5 Applications

Composable agent-state evolution. $\text{state}[t+1] = \text{state}[t] \otimes \text{stimulus}[t]$ is a single bounded-width operation per time step. The agent’s internal state is the running composition of all stimuli received.

Algebraic chain verification. For an N -packet chain produced sequentially, a verifier computes the cumulative product $I \otimes p_1 \otimes \cdots \otimes p_N$ and compares to a separately-signed chain-head value. Verification runs in $O(N)$ operations at constant per-operation cost. Empirically, a single-bit change

anywhere in the chain produces a divergent head, so the construction functions as a chain digest under any cryptographic signature layered on top.

Multi-source state composition. N independently-evolving state packets compose via the left-fold $p_1 \otimes \cdots \otimes p_N$. By associativity the fold may be computed in any order or as a parallel tree-reduce. By non-commutativity of the quaternion factor, the order of sources is significant.

6 Relationship to prior work

The construction does not introduce new mathematics; each component has a long literature: quaternion algebra [1], persistent homology [2], finite-group operations on $\mathbb{Z}_2^b$ and $\mathbb{Z}/N\mathbb{Z}$, and lookup-table substitution. The contribution is the specific combination: a closed associative binary operation on a fixed-width packet that simultaneously preserves a unit-quaternion integrity check, symbolic-metadata semantics under per-field associative operations, algebraic-chain composability, and an empirically-observed topology-preservation property under iterated composition. We are not aware of this combination in a single prior-art reference and welcome pointers to closer prior work.

7 Availability

A reference implementation (CPU and GPU), the full validation suite, worked examples, and this paper are available under the MIT License at <https://github.com/consigcody94/quaternion-monoid-algebra> and archived at [doi:10.5281/zenodo.20301069](https://doi.org/10.5281/zenodo.20301069).

Provenance. This work was developed by the author with artificial-intelligence assistance used as an engineering aid for implementation, validation, GPU porting, and documentation. The conceptual direction and the specific algebraic structure imposed on the packet space were the author’s.

References

- [1] W. R. Hamilton. *On quaternions; or on a new system of imaginaries in algebra*. Philosophical Magazine, 25(3):489–495, 1844.
- [2] H. Edelsbrunner, D. Letscher, and A. Zomorodian. *Topological persistence and simplification*. Discrete & Computational Geometry, 28(4):511–533, 2002.
- [3] J. Sturm, N. Engelhard, F. Endres, W. Burgard, and D. Cremers. *A benchmark for the evaluation of RGB-D SLAM systems*. In Proc. International Conference on Intelligent Robot Systems (IROS), 2012.
- [4] M. Burri, J. Nikolic, P. Gohl, T. Schneider, J. Rehder, S. Omari, M. W. Achtelik, and R. Siegwart. *The EuRoC micro aerial vehicle datasets*. The International Journal of Robotics Research, 35(10):1157–1163, 2016.