

Compositional Algebra over Fixed-Width Quaternionic-Symbolic State Packets

Cody Churchwell

Independent Researcher

github.com/consigcody94/quaternion-monoid-algebra

May 2026

Abstract

We define a compositional algebra over a fixed-width packet structure that carries a unit quaternion, a small number of symbolic metadata fields, and a positive scaling factor. A closed binary operation is defined on the packet space with the property that the space, equipped with this operation, forms a monoid: closure, two-sided identity, and associativity. The construction is field-by-field; each sub-field operation is drawn from a small set of associative monoid operations on its respective value space (Hamilton multiplication on the quaternion factor; lookup-table substitution, lattice maximum, modular addition, parity XOR, and multiplicative scaling on the symbolic and scaling factors). The composite operation inherits associativity from the per-field operations. We document an additional empirically-observed property, topology preservation under iterated composition, and validate the construction with a suite of fourteen automated tests including bit-exact GPU/CPU correspondence and verification on a public motion-capture dataset. Three application classes follow: composable agent-state evolution, algebraic chain verification, and multi-source state composition. A permissively-licensed reference implementation accompanies this paper.

1 Introduction

A recurring problem in robotics, swarm coordination, and accountability infrastructure is the need for a bounded-width, time-evolving state representation that is simultaneously composable, verifiable, and efficient enough for edge deployment. Existing representations trade these properties against one another. Raw floating-point quaternion streams are compact for rotation but offer no composition operation beyond Hamilton multiplication on the rotation component, and carry no symbolic metadata. Variable-width cryptographic audit chains compose via Merkle structures but are not fixed-width and are not amenable to single-cycle hardware composition. High-dimensional vector embeddings compose via vector arithmetic but are lossy and lack a unit-rotation guarantee.

This paper defines a fixed-width construction that fills the gap. A packet carries a unit quaternion plus a small number of symbolic metadata fields plus a scaling factor, with a defined composition operation whose result is itself a packet of the same width. The resulting algebra has, simultaneously: closure under composition, the algebraic structure of a monoid (so chains of operations compose freely and associatively), and an empirically-observed topology-preservation property under iterated composition.

2 Construction

2.1 The packet structure

A packet is the tuple

$$p = (q, f_a, f_b, f_c, f_d, \pi, s),$$

where $q \in S^3$ is a unit quaternion in (w, x, y, z) layout; f_a, f_b, f_c, f_d are small symbolic fields of fixed bit width; $\pi \in \{0, 1\}$ is a parity bit; and $s \in \mathbb{R}_{>0}$ is a positive scaling factor. Field widths are parameters of the construction. A representative default (widths 4, 3, 5, 3 bits, plus parity, plus a smallest-three quaternion encoding in 32 bits, plus an IEEE-754 binary16 scaling factor) fits a 64-bit packet.

2.2 The composition operation

For two packets p_1 and p_2 , the composition $p_1 \otimes p_2$ is defined field-by-field:

Sub-field	Operation	Algebraic basis
q	Hamilton product, then normalize	S^3 group structure
f_a	$T_a[i, j]$ lookup (default $i \oplus j$)	$\mathbb{Z}_2^b$ abelian group
f_b	$\max(i, j)$	totally-ordered lattice
f_c	$(i + j) \bmod 2^{b_c}$	$\mathbb{Z}/2^{b_c}\mathbb{Z}$ group
f_d	$T_d[i, j]$ lookup (default $i \oplus j$)	$\mathbb{Z}_2^b$ abelian group
π	$\pi_1 \oplus \pi_2$	$\mathbb{Z}_2$ group
s	$s_1 \cdot s_2$	$\mathbb{R}_{>0}$ under multiplication

The identity element is $I = (q_{\text{id}}, 0, 0, 0, 0, 0, 1)$, where $q_{\text{id}} = (1, 0, 0, 0)$.

2.3 Monoid properties

Proposition 1 (Closure). *For all valid packets p_1, p_2 , the product $p_1 \otimes p_2$ is a valid packet.*

Proof sketch. Each per-field operation maps into the same field. The Hamilton product of two unit quaternions, after normalization, is a unit quaternion. XOR and modular addition remain in finite range. Lattice maximum of two values in $[0, 2^b)$ remains in $[0, 2^b)$. The product of two positive reals is a positive real. $\square$

Proposition 2 (Two-sided identity). *$I \otimes p = p \otimes I = p$ for all valid p .*

Proof sketch. Field-wise: q_{id} is the quaternion identity; lookup tables satisfy $T[0, j] = j$ and $T[i, 0] = i$; $\max(0, x) = x$; $0 + x \equiv x \pmod{N}$; $0 \oplus x = x$; and $1 \cdot x = x$. $\square$

Proposition 3 (Associativity). *$(a \otimes b) \otimes c = a \otimes (b \otimes c)$ for all valid a, b, c .*

Proof sketch. Each per-field operation is associative on its value space: Hamilton product on the quaternion group; XOR on $\mathbb{Z}_2^b$; maximum on a totally-ordered lattice; modular addition on $\mathbb{Z}/N\mathbb{Z}$; parity XOR on $\mathbb{Z}_2$; multiplication on $\mathbb{R}_{>0}$. A field-wise product of associative operations is associative. $\square$

Together these three propositions establish that the packet space, equipped with $\otimes$, is a monoid.

2.4 Topology preservation

A property additional to the monoid structure: when the algebra is applied iteratively to a stream of input packets via $\text{state}[t+1] = \text{state}[t] \otimes \text{stim}[t]$, the H_1 persistent-homology signature of the resulting trajectory of quaternion components is bounded relative to the H_1 signature of the input stream. Empirically, the ratio of total bar persistence (output to input) falls in $[0.3, 5.0]$ for structured inputs. We state this as an empirical observation rather than a theorem; a formal characterization is left to future work.

3 Validation

The accompanying reference implementation passes fourteen automated tests: eight algebraic-property tests (left and right identity over 100 packets, associativity over 512 random triples, closure over 500 random pairs, stability over a 1000-step self-product chain, power consistency, and bit-exact GPU/CPU correspondence) and six stress tests (10,000-step long-horizon stability, single-bit avalanche sensitivity, distinguishability across 100 chains, real-data behavior, field-saturation characterization, and scale stability).

The GPU implementation agrees with the CPU reference bit-for-bit on the Hamilton product: maximum absolute difference $0.00\text{e}+00$ across 100,000 random pairs at single precision. The real-data test verifies clean behavior on the TUM RGB-D Pioneer 360 ground-truth sequence [3], downloaded at runtime with SHA-256 verification, composing 2,000 unit quaternions while preserving the unit-norm constraint to machine precision.

The field-saturation test documents an honest limitation: the $\max(\cdot)$ sub-field saturates under iteration (it is associative with identity 0 but is not invertible), so it functions as a one-way “high-amplitude event seen” flag rather than a state register; the XOR and modular-addition fields are information-preserving over their respective groups.

4 Applications

Composable agent-state evolution. $\text{state}[t+1] = \text{state}[t] \otimes \text{stimulus}[t]$ is a single bounded-width operation per time step. The agent’s internal state is the running composition of all stimuli received.

Algebraic chain verification. For an N -packet chain produced sequentially, a verifier computes the cumulative product $I \otimes p_1 \otimes \cdots \otimes p_N$ and compares to a separately-signed chain-head value. Verification runs in $O(N)$ operations at constant per-operation cost. Empirically, a single-bit change anywhere in the chain produces a divergent head, so the construction functions as a chain digest under any cryptographic signature layered on top.

Multi-source state composition. N independently-evolving state packets compose via the left-fold $p_1 \otimes \cdots \otimes p_N$. By associativity the fold may be computed in any order or as a parallel tree-reduce. By non-commutativity of the quaternion factor, the order of sources is significant.

5 Relationship to prior work

The construction does not introduce new mathematics; each component has a long literature: quaternion algebra [1], persistent homology [2], finite-group operations on $\mathbb{Z}_2^b$ and $\mathbb{Z}/N\mathbb{Z}$, and

lookup-table substitution. The contribution is the specific combination: a closed associative binary operation on a fixed-width packet that simultaneously preserves a unit-quaternion integrity check, symbolic-metadata semantics under per-field associative operations, algebraic-chain composability, and an empirically-observed topology-preservation property under iterated composition. We are not aware of this combination in a single prior-art reference and welcome pointers to closer prior work.

6 Availability

A reference implementation (CPU and GPU), the full validation suite, worked examples, and this paper are available under the MIT License at <https://github.com/consigcody94/quaternion-monoid-algebra> and archived at [doi:10.5281/zenodo.20301069](https://doi.org/10.5281/zenodo.20301069).

Provenance. This work was developed by the author with artificial-intelligence assistance used as an engineering aid for implementation, validation, GPU porting, and documentation. The conceptual direction and the specific algebraic structure imposed on the packet space were the author’s.

References

- [1] W. R. Hamilton. *On quaternions; or on a new system of imaginaries in algebra*. Philosophical Magazine, 25(3):489–495, 1844.
- [2] H. Edelsbrunner, D. Letscher, and A. Zomorodian. *Topological persistence and simplification*. Discrete & Computational Geometry, 28(4):511–533, 2002.
- [3] J. Sturm, N. Engelhard, F. Endres, W. Burgard, and D. Cremers. *A benchmark for the evaluation of RGB-D SLAM systems*. In Proc. International Conference on Intelligent Robot Systems (IROS), 2012.