# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation: 132 KV Vehari Road | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-25

Feeder: Old S.R. Alam | T/F Make: PEL | General Duty ✓ | Ded

Transformer Code: T-5118,7136 | Inspectors: Ali | Location: f Block Near T-chowk

Feeder Code: 22011 | Division: S.R. Alam | Sub-Division: S.R. Alam | Sub Division Code

| S/E | Grp 0 | Grp 1 | Date d | Date d | Date m | Date m | Date y | Date y | GPS WP 0 | GPS WP 0 | GPS WP 1 | Conductor: Phase | R | Y | B | Neutral | Equipment Type: Type | Pole Class | Pole Height | Consumer Type: RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 5 | 1 | 1 | 0 | 8 | 1 | 7 | 1 | 3 | 6 | RYB | W | W | W | W | TR | PCO | 36 | | | | | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 3 | 9 | | | | | | SP | N | 11 | | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 3 | 9 | | | | | | | N | N | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 0 | | | | | | | S | 31 | 3 | 1 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 4 | 0 | | | | | | | N | N | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 1 | | | | | | | PCO | 36 | 3 | 2 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 4 | 1 | | | | | | | N | N | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 2 | | | | | | | S | 31 | 11 | 1 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 4 | 2 | | | | | | | N | N | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 3 | | | | | | | PCO | 31 | 51 | | | | | | | | | 31 | 10974 10988602 | 24 | 35.51 | |
| S | | | | | | | | | 6 | 4 | 3 | | | | | | | N | N | | | | | | | | | | | 1098600 | | | |
| E | | | | | | | | | 6 | 4 | 4 | | | | | | | S | 31 | 2 | | | | | | | | | 24 | 1098600 1098703 1097000 1097200 1098900 | 22 | 32.56 | |
| S | | | | | | | | | 6 | 4 | 4 | RYBG | G | G | G | SP | N | N | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 5 | | | | | | | N | N | 6 | 1 | | | | | | | | | 1 | | 9 | 13.32 | |
| S | | | | | | | | | 6 | 3 | 9 | RYB | W | W | W | W | SP | PCO | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 6 | | | | | | | S | 31 | 2 | | | | | | | | | 1 | ✓ 13847 | 7 | 10.5 | |
| S | | | | | | | | | 6 | 4 | 6 | | | | | | | N | N | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 7 | | | | | | | N | N | 7 | 1 | | | | | | | | | 2 | 1095804 1095700 | 12 | 30.08 | |
| S | | | | | | | | | 6 | 4 | 7 | | | | | | | N | N | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 8 | | | | | | | | N | 7 | | | | | | | | | 3 | 1096100 10956 | 18 | 25.53 | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ph Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure - (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31

PV Solar/Net-Metering Data

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

10962

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | T/F Cap: | | S.Pole | | D.Pole | | Pad | | Survey Date: | 12-12-25 |
| Feeder: 1336 | | T/F Make: | | General Duty | | | | Ded | | | |
| Transformer Code: | | Inspectors: | | | | Location | | | | | |
| Feeder Code: | Division: | Sub-Division: | | | | | | Sub Division Code | | | |

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | | | | |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 4 | 8 | RYB | W | W | W | W | SP | S | 31 | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 4 | 9 | | | | | | | | | 1 | 2 | | | | | | | | 1 | | 10964 | 7 | 5.34 | |
| S | | | | | | | | | 6 | 4 | 9 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 0 | | | | | | | | | 6 | | | | | | | | | 1 | | 1096605 10966 → 1098804 | 22 | 32.67 | 25370M |
| S | | | | | | | | | 6 | 4 | 6 | RYB | A | A | A | A | SP | S | 31 | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 1 | | | | | | | | | 3 | | 5 | | | | | | | | ✓ | | | | |
| S | | | | | | | | | 6 | 5 | 1 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 2 | | | | | | | | | 20 | 1 | 13 | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 5 | 1 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 3 | | | | | | | | | 2 | | 4 | 1 | | | | | | | | | | | |
| S | | | | | | | | | 6 | 5 | 3 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 4 | | | | | | | | | 3 | 1 | 4 | 1 | | | | | | 1 | | 1085400 | 5 | 6.54 | |
| S | | | | | | | | | 6 | 5 | 4 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 5 | | | | | | | | | 2 | | 2 | 1 | | | | | | | | | | | |
| S | | | | | | | | | 6 | 5 | 5 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 6 | | | | | | | | | 4 | | 10 | | | | | | | 1 | | 10825 | 7 | 9.72 | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | 1 | | 2 | 7 | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

### PV Solar/Net-Metering Data

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | Vehari Road | T/F Cap: | 200 | S.Pole | | D.Pole ✓ | Pad | Survey Date: | 12-12-23 |
| Feeder: | New S.R. Alam | T/F Make: | Reclaim | General Duty ✓ | | Ded | | | |
| Transformer Code: | T911081709A | Inspectors: | Ali | Location | C Block S.R. Alam | | | | |
| Feeder Code: | 22023 | Division: | S.R. Alam | Sub-Division: | S.R. Alam | Sub Division Code | | | |

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 9 | 1 | 1 | 0 | 8 | 1 | 7 | 0 | 9 | 4 | R/B | W | W | W | W | TR | S | 36 | | | | | | | | | | | | | | at site 100KVA |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 5 | 6 | " | " | " | " | " | SP | " | " | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 5 | 6 | " | " | " | " | " | " | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 7 | " | " | " | " | " | " | " | " | 1 | | | | | | | | | 1 | | 15501-01 | | | Not Found |
| S | | | | | | | | | 6 | 5 | 7 | R/B | A | A | A | A | SP | S | 36 | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 8 | | | | | | | | " | 11 | | | | | | | | | ✓ | | | | |
| S | | | | | | | | | 6 | 5 | 8 | | | | | | | | " | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 5 | 9 | | | | | | | | 31 | 7 | | | | | | | | | 1 | 1549801 | 7 | 10.2 | |
| S | | | | | | | | | 6 | 5 | 9 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 0 | | | | | | | | | 6 | | | | | | | | | H1 | 1549504 1548408 | 14 | 8.76 | |
| S | | | | | | | | | 6 | 6 | 0 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 1 | | | | | | | | | 4 | | | | | | | | | 1 | 1549401 | 7 | 10.5 | |
| S | | | | | | | | | 6 | 6 | 1 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 2 | | | | | | | | | 3 | | | | | | | | | 1 | ✓ 1548706 | 5 | 7.5 | |
| S | | | | | | | | | 6 | 6 | 2 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 3 | | | | | | | | | 4 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 6 | 2 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 4 | | | | | | | | | 14 | | 10 | | | | | | | | | | | |
| S | | | | | | | | | 6 | 6 | 4 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 5 | | | | | | | | | 10 | | 4 | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1p Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Substation: | | | T/F Cap: | | S.Pole | | D.Pole | | Pad | | Survey Date: 12-12-24 |
| Feeder: | | | T/F Make: | | General Duty | | | | Ded | | |
| Transformer Code: 094 | | | Inspectors: | | | | Location | | | | |
| Feeder Code: | Division: | | Sub-Division: | | | | | | Sub Division Code | | |

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 5 | 8 | R-R | A | BC | 50 | MM | SP | S | 36 | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 6 | - | ~ | ~ | ~ | ~ | ~ | ~ | 31 | 8 | | | | | | | | | 2 | 1477200<br>1477906 | 14 | 2094 | |
| S | | | | | | | | | 6 | 6 | 6 | R-B | A | ~~A~~ | A | A | ~ | ~ | ~ | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 7 | ~ | ~ | ~ | ~ | ~ | ~ | ~ | ~ | 11 | 1 | | | | | | | | 1 | 1472009 | 7 | 105 | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation: Vehari Road | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-24

Feeder: New S.R. Alam | T/F Make: Reclaim | General Duty | Ded

Transformer Code: T-911081097 | Inspectors: AL | Location: A BLOCK S.R Alam

Feeder Code: 22023 | Division: S.R. Alam | Sub-Division: S.R. Alam | Sub Division Code

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT |
| S | 0 | 9 | 1 | 1 | 0 | 8 | 1 | 7 | 0 | 9 | 7 | R/Y/B | W | W | W | W | TR | PCO | 36 | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 6 | 8 | | | | | | SP | ~ | 11 | | | | | | | | | | | |
| S | | | | | | | | | 6 | 6 | 8 | | | | | | | ~ | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 6 | 9 | | | | | | | S | 31 | 9 | | | | | | | | | 1 | |
| S | | | | | | | | | 6 | 6 | 9 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 0 | | | | | | | | | 10 | | | | | | | | | 1 | |
| S | | | | | | | | | 6 | 7 | 0 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 1 | | | | | | | | | 6 | | | | | | | | | 1 | |
| S | | | | | | | | | 6 | 7 | 1 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 2 | | | | | | | | | 16 | | | | | | | | | 1 | |
| S | | | | | | | | | 6 | 7 | 2 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 3 | | | | | | | | | 5 | 1 | | | | | | | | | |
| S | | | | | | | | | 6 | 7 | 3 | R/Y/B | G | G | G | G | SP | S | 31 | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 4 | | | | | | | PC | 31 | | | | | | | | | | | |
| S | | | | | | | | | 6 | 7 | 4 | | | | | | | | ~ | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 5 | | | | | | | S | ~ | 8 | 1 | | | | | | | | 1 | |
| S | | | | | | | | | 6 | 7 | 5 | B | — | — | W | W | | ~ | ~ | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 6 | B | — | — | ~ | ~ | SP | ~ | ~ | 7 | | | | | | | | | | |
| S | | | | | | | | | 6 | 6 | 8 | R/B | W | W | W | W | SP | PCO | 36 | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 7 | | | | | | | S | 31 | 13 | | | | | | | | | | |

### PV Solar/Net-Metering Data

| Consumer Reference No. | PV Solar Sanc LD (kW) | PV Solar Cap (kW) | Remarks |
|---|---|---|---|
| 1547103 | 5 | 6.43 | |
| | | | |
| 20123688M | | | New connection Not found |
| " | | | |
| 15412 | 5 | 3.3 | |
| | | | |
| 20133986 | | | New connection ~~Not found~~ |
| | | | |
| | | | |
| | | | |
| | | | |
| 154390 | | | Not found |
| | | | |
| | | | |
| | | | |
| | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary - 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | T/F Cap: | | S.Pole | | D.Pole | | Pad | | Survey Date: | 12-12-23 |
| Feeder: | 097 | T/F Make: | | | | General Duty | | Ded | | | |
| Transformer Code: | | Inspectors: | | | | | | Location | | | |
| Feeder Code: | Division: | Sub-Division: | | | | | | Sub Division Code | | | |

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2/5 | | 6 | 7 | 7 | R/Y/B | W | W | W | W | SP | S | 31 | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 8 | | | | | | | " | 1 | 16 | 1 | | | | | | | | 1 | 2012303 | 7 | 105 | |
| S | | | | | | | | | 6 | 6 | 9 | | | | | | | S | 3 | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 7 | 9 | | | | | | | | | 17 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 7 | 9 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 0 | | | | | | | | | 9 | | | | | | | | | 3 | 1509401<br>~~1509901~~<br>1509510 | 26 | 38.32 | |
| S | | | | | | | | | 6 | 8 | 0 | | | | | | | | | | | | | | | | | | | 15081 | | | |
| E | | | | | | | | | 6 | 8 | 1 | | | | | | | | | 7 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 1 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 2 | | | | | | | | | 10 | | | | | | | | | 3 | 1539704<br>1539800<br>1539602 | 18 | 20.22 | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) - Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights .. Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary - 36,31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation: Vehari Road | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-25

Feeder: Gulshan Market | T/F Make: Reclaim | General Duty ✓ | Ded

Transformer Code: 4200917003 | Inspectors: | Location: Near Nadra office

Feeder Code: 22012 | Division: S.R. Alam | Sub-Division: S.R. Alam | Sub Division Code

| S/E | Grp 0 | Grp 1 | Date d | Date d | Date m | Date m | Date y | Date y | GPS WP 0 | GPS WP 0 | GPS WP 1 | Conductor: Phase | R | Y | B | Neutral | Equipment Type: Type | Pole Class | Pole Height | Consumer Type: RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 4 | 2 | 0 | 0 | 9 | 1 | 7 | 6 | 0 | 3 | RYB | W | W | W | W | TR | S | 36 | | | | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 8 | 2 | | | | | | SP | 〃 | 〃 | 3 | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 2 | | | | | | 〃 | 〃 | 〃 | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 3 | | | | | | 〃 | 〃 | 〃 | 2 | 2 | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 3 | RYB | A | A | A | A | SP | 〃 | 〃 | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 4 | | | | | | | PCC | 36 | | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 4 | | | | | | | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 5 | | | | | | | 〃 | 〃 | | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 5 | | | | | | | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 6 | | | | | | | S | 36 | 6 | | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 6 | | | | | | | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 7 | | | | | | | 〃 | 〃 | 3 | 1 | | | | | | | | | | | | | |
| S | | | | | | | | | 6 | 8 | 7 | | | | | | | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 8 | | | | | | | 〃 | 〃 | 25 | | | | | | | | | 1 | | 156600 | 5 | 6.54 | |
| S | | | | | | | | | 6 | 8 | 2 | RYB | W | W | W | W | SP | S | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 8 | 9 | | | | | | | | 31 | 2 | 2 | | | | | | | | 3 | | 14625<br>14624<br>14621 | 27 | 34.92 | |
| S | | | | | | | | | 6 | 8 | 9 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 0 | | | | | | | | | 1 | 1 | | 1 | | | | | | | | | | | |
| S | | | | | | | | | 6 | 9 | 0 | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 1 | | | | | | | | | | | | 3 | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

PV Solar/Net-Metering Data

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation:

Feeder:

Transformer Code: 003

Feeder Code: Division:

T/F Cap: S.Pole D.Pole Pad Survey Date: 12-12-25

T/F Make: General Duty Ded

Inspectors: Location

Sub-Division: Sub Division Code

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 1 | 1 | 2 | 7 | 2 | 2 | 5 | G | 9 | 1 | R/Y/B | W | W | W | W | SP | S | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 2 | | | | | | | | | | | 2 | 1 | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation: Vehari Road | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-23

Feeder: Usman E Ghani | T/F Make: Reliance | General Duty ✓ | Ded

Transformer Code: T-2210618247 | Inspectors: Ali

Feeder Code: 22025 | Division: S.R. Alam | Sub-Division: New Multan | Location: Mansab wala | Sub Division Code

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 2 | 2 | 1 | 0 | 6 | 1 | 8 | 2 | 4 | 7 | RyB | | | | | TR | PCO | 36 | | | | | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 6 | 9 | 3 | RyB | W | W | W | W | ST | " | " | | | | | | | | | | | | | | | cosp conduc |
| S | | | | | | | | | 6 | 9 | 3 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 4 | | | | | | | " | " | 6 | | | | | | | | | 1 | | 20124896 | 6 | 9 | |
| S | | | | | | | | | 6 | 9 | 4 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 5 | | | | | | | S | 36 | 8 | | | | | | | | | | | 1278504 | 5 | 7.41 | |
| S | | | | | | | | | 6 | 9 | 5 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 6 | | | | | | | " | " | 18 | | | | | | | | | 1 | | 496870 | 5 | 7 | |
| S | | | | | | | | | 6 | 9 | 3 | | | | | | | PCO | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 7 | | | | | | | S | " | 3 | | | | | | | | | | ✓ | | | | |
| S | | | | | | | | | 6 | 9 | 7 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 8 | | | | | | | " | 31 | 13 | | | | | | | | | 2 | | 1353500 6691a m | | | Not found |
| S | | | | | | | | | 6 | 9 | 8 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 6 | 9 | 9 | | | | | | | PCO | | 12 | | | | | | | | | 2 | | 1353801 1354103 | 5 | 7.5 | |
| S | | | | | | | | | 6 | 9 | 7 | | | | | | | S | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 0 | | | | | | | S | 31 | 7 | | 1 | | | | | | 2 | ✓ | 1352701 1352 6 ✗ | 7 | 10 | |
| S | | | | | | | | | 7 | 0 | 0 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 1 | | | | | | | " | " | 14 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 0 | 1 | | | | | | | " | " | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 2 | | | | | | | | | 18 | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) - Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | T/F Cap: | | S.Pole | | D.Pole | | Pad | | Survey Date: | 12-12-25 |
| Feeder: | 247 | T/F Make: | | General Duty | | Ded | | | |
| Transformer Code: | | Inspectors: | | | | Location | | | |
| Feeder Code: | Division: | Sub-Division: | | | | Sub Division Code | | | |

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 0 | 2 | RYB | W | W | W | W | SP | S | 31 | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 3 | | | | | | | ^ | N | 22 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 0 | 3 | | | | | | | ~ | N | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 4 | | | | | | | PG | 31 | 10 | | | | | | | | | 2 | | 1351401 3789M | $ | TBS |
| S | | | | | | | | | 7 | 0 | 0 | RYB | A | A | A | A | SP | S | 31 | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 5 | | | | | | | S | 31 | 12 | | | | | | | | | 1 | ✓ | 1265301 | 7 | 9.28 |
| S | | | | | | | | | 7 | 0 | 5 | | | | | | | ~ | ~ | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 6 | | | | | | | PCO | 31 | 13 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 0 | 6 | | | | | | | ~ | ^ | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 7 | | | | | | | ~ | ~ | 15 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 0 | 5 | | | | | | | S | 31 | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 8 | | | | | | | PCS | 31 | 16 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 0 | 8 | | | | | | | N | N | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 0 | 9 | | | | | | | ~ | ~ | 11 | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

# Data Input Form for LT Survey

Substation: Khanewal Road | T/F Capacity: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-25

Feeder: Chawan Colony | T/F Make: Reclaim | General Duty | ✓ Dedicated

Transformer Code: T-3311 0772-18 | Inspectors: Atif Ajmal Jaffri | Location: Lidal meer Masjid

Feeder Code: 10401 | Division: | Sub-Division: | Sub Division Code

Location correction

PV Solar/Net-Metering Data

Case (Provided (-21))

| S/E | Group 0 | Group 1 | Date d | d | m | m | y | y | GPS WP 0 | 0 | 1 | Conductor Phase | R | Y | B | Neutral | Equipment Type Type | Pole Class | Pole Height | Consumer Type RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 3 | 3 | 1 | 1 | 0 | 7 | 7 | 2 | 1 | 8 | RyB | A | A | A | A | TR | PCO | 36 | | | | | | | | | | | | | |
| E | 0 | 1 | | | | | 2 | 5 | 7 | 1 | 0 | | | | | | SP | N | N | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 0 | | | | | | | | N | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 1 | | | | | | | | 31 | 9 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 1 | | | | | | | | ~ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 2 | | | | | | | | N | 23 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 0 | | | | | | | | 36 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 3 | | | | | | | | 31 | 18 | | | | | | | | ✓ | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 3 | | | | | | | | N | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 4 | | | | | | | N | ~ | 12 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 4 | B | — | — | A | A | SP | ~ | ~ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 5 | N | — | — | A | A | ~ | ~ | | 15 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 5 | ~ | — | — | A | A | | 1 | ~ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 6 | ^ | — | — | A | N | N | N | N | 11 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 3 | RyB | A | A | A | A | SP | N | ~ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 7 | | | | | | | PCO | 36 | 8 | | 2 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 7 | Y | — | G | ~~C~~ | G | SP | ~ | N | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 8 | Y | — | G | — | G | | S | 31 | 8 | | | | | | | | | | | | |

Conductor - (A) Ant - (W) Wasp - (GN) Goat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) HDA19 Cable (50mm) (95mm) (Ang-Angle) (Int-Intersection)

Pole Class - Steel Structure(S) - PC Ordinary (PCO) - PC Span(PCS) - Rail Steel (RS) - Tubular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters.

Consumer - RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights:- Steel Structure:- (SS) 58, 45, 40, 36, 31 PC Span:- 45, 40, 36, 31 PC Ordinary:- 36, 31

# Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | | T/F Capacity: | | S.Pole | | D.Pole | Pad | Survey Date: 12-12-25 |
| Feeder: 218 | | | T/F Make: | | General Duty | | Dedicated | | |
| Transformer Code: | | | Inspectors: | | | Location | | | |
| Feeder Code: | Division: | | Sub-Division: | | | | Sub Division Code | | |

PV Solar/Net-Metering Data

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | | | |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 1 | 8 | Y | — | A | — | A | SP | S | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 1 | 8 | Y | — | A | — | A | SP | PCC | 31 | 9 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 7 | R | B | A | [redacted] | A | SP | " | " | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 0 | R | B | A | — | " | " | " | S | 31 | 14 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 1 | 7 | " | | A | — | " | " | - | PCC | 36 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 1 | 0 | | A | — | " | " | - | PCC | 36 | 8 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |

Conductors - (A) Ant - (W) Wasp - (G) Goat - 2/0 ABC, (PIC 7/0.662) (PIC 19/0.662) (PIC 19/0.912) (PIC 37/0.912) USAID Cable (35mm) (95mm) (Mag-Angle) (Int-Intersection)

Pole Class - Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tubular Steel (TS) Rail Bracket (RB)

Note: The Surveyor will mark each of the Solar PV Net Metering Consumer site and note the above parameters

Consumer - RS - 1ph Res - RL - 3p Res - SC - 1p Com - SI - 1p Ind - LI - 3p Ind - PB - Public Building - AG - Agricultural - ST - Street Light

Pole Heights:- Steel Structure:- (SS) 38, 45, 49, 36, 31 PC Spun - 31, (0, 36, 31 PC Ordinary - 36, 31

# Data Input Form for LT Survey

Substation: Vehari Road | T/F Capacity: 25 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-25

Feeder: Sameja Abad | T/F Make: Siemens | General Duty ✓ | Dedicated

Transformer Code: T-2070918135 | Inspectors: | Location: Pull Chawan

Feeder Code: 22016 | Division: | Sub-Division: | Sub Division Code: New Multan

PV Solar/Net-Metering Data

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | | | |
| S | 0 | 2 | 0 | 7 | 0 | 9 | 1 | 8 | 1 | 3 | 5 | RYB | A | A | A | A | TL | PCO | 36 | | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 2 | 2 | | | | | | SP | PCO | 36 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 2 | | | | | | | ~ | 〃 | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 3 | | | | | | | PCS | 31 | | | | | | | | | | ✓ | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 3 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 4 | | | | | | | | | 10 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 4 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 5 | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 5 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 6 | | | | | | | | | 2 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 3 | RB | A | — | A | A | SP | 〃 | 〃 | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 7 | | | — | | | | ~ | 36 | 1 | | 2 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 7 | | | — | | | | ~ | 〃 | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 8 | | | — | | | | ~ | 31 | 10 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 8 | | | — | | | | ~ | 〃 | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 2 | 9 | | | — | | | | ~ | 〃 | 4 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 2 | 2 | YB | — | A | A | A | SP | PCO | 36 | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 0 | YB | — | A | A | A | SP | PCS | 31 | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Goat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm) (95mm) (Ang-Angle) (Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Span(PCS) - Rail Steel (RS) - Tabular Steel (TS) Rail Bracket (WB)

Note: The Surveyor will visit each of the Solar PV Net Metering Consumer site and note the above parameters

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights··· Steel Structure·· (SS) 38, 45, 40, 36, 31 PC Span:- 45, 40, 36, 31 PC Ordinary:- 36, 31

# Data Input Form for LT Survey

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Substation: | | T/F Capacity: | | S.Pole | | D.Pole | Pad |
| Feeder: | | T/F Make: | | General Duty | | Dedicated | |
| Transformer Code: | 135 | Inspectors: | | Location | | Sub Division Code | |
| Feeder Code: | Division: | Sub-Division: | | | | | |

Survey Date: 12-12-25

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 09 | | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 3 | 0 | YB | — | A | A | A | SP | PCS | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 1 | 〃 | — | 〃 | 〃 | 〃 | 〃 | 〃 | 〃 | 5 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AAC (PIC 7/0.052) (PVC 19/0.052) (PVC 19/0/083)
(PVC 37/083) ABC Cable (50mm) (95mm)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Span(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights:- Steel Structure:- (SS) 38, 15, 40, 36, 31 PC Span:- 45, 40, 36, 31 PC Ordinary - 36, 31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters

# Data Input Form for LT Survey

Substation: Bosan Road | T/F Capacity: 50 | S.Pole | D.Pole 4 | Pad | Survey Date: 12-12-25

Feeder: Nagshband | T/F Make: Reclaim | General Duty | Dedicated

Transformer Code: T-23105 B 28 | Inspectors: BZ. Mus Abbas | Location: Near Imam Bargah

Feeder Code: 1810 | Division: | Sub-Division: A. Abad | Sub Division Code

PV Solar/Net-Metering Data

| S/E | Group | | Date | | | | | | GPS WP | | | Phase | Conductor | | | | Equipment Type | | | Consumer Type | | | | | | | | | | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | | | |
| S | 0 | 2 | 3 | 1 | 0 | 5 | 2 | 5 | 7 | 2 | 9 | 3ph | A | A | A | A | SP | PCC | 36 | | | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 3 | 2 | | | | | | SP | " | " | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 2 | | | | | | | " | " | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 3 | | | | | | | " | " | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 2 | | | | | | | RSC | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 4 | | | | | | | PCC | 36 | 7 | | 5 | 1 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 4 | | | | | | | 1 | " | [illegible] | | [illegible] | [illegible] | | | | | 1 | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 5 | | | | | | | " | | 4 | | [illegible] | [illegible] | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 5 | | | | | | | " | " | | | | | | | | | 1 | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 6 | | | | | | | " | " | 22 | | 4 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 6 | | | | | | | " | " | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 7 | | | | | | | PCC | " | | | 2 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 7 | | | | | | | " | " | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 3 | 8 | | | | | | | S | " | | | 6 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm) (95mm) (Ang-Angle) (Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights··· Steel Structure:- (SS) 58, 45, 40, 36, 31 PC Spun:- 45, 40, 36, 31 PC Ordinary:- 36, 31

# Data Input Form for LT Survey

Substation: Wadda Town | T/F Capacity: 100 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-15

Feeder: Dehar | T/F Make: Reclaim | General Duty | ✓ | Dedicated

Transformer Code: T-4260222730 | Inspectors: Ali Akbar | Location | Haji Tent Wadda

Feeder Code: 0401 | Division: BT. M. Pak | Sub-Division: | Sub Division Code

Basit Sharafat — PV Solar/Net-Metering Data

| S/E | Group 0 | Group 1 | Date d | Date d | Date m | Date m | Date y | Date y | GPS WP 0 | GPS WP 0 | GPS WP 1 | Conductor: Phase | R | Y | B | Neutral | Equipment Type: Type | Pole Class | Pole Height | Consumer Type: RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 4 | 2 | 6 | 0 | 2 | 2 | 3 | 7 | 3 | 0 | RyB | A | A | A | A | TR | S | 40 | | | | | | | | | | | | | 200 KVA installed |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 3 | 9 | | | | | | ST | ^ | ^ | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 9 | | | | | | | ~ | ^ | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 9 | | | | | | | ~ | 31 | | | 2 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 3 | 9 | | | | | | | ~ | 40 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 1 | | | | | | | | ^ | 5 | | 8 | 1 | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 7 | 4 | 1 | | | | | | | ~ | ^ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 2 | | | | | | | PCS | ^ | 7 | | 8 | | | | | | | 1 | | 413647 | | Not Found |
| S | | | | | | | 2 | 5 | 7 | 4 | 2 | | | | | | | PCS | ^ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 3 | | | | | | | S | ~ | 6 | | 8 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 4 | 3 | | | | | | | ~ | ^ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 4 | RyB | A | A | A | A | SP | PCO | 31 | 8 | | 5 | 1 | | | | | 1 | | 4153620 | 7 \| 1044 | |
| S | | | | | | | 2 | 5 | 7 | 4 | 1 | RyB | A | A | A | A | ^ | S | 40 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 5 | RyB | A | A | A | A | SP | ^ | ^ | | | 4 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 4 | 5 | YB | — | | | | | ~ | ~ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 6 | N | — | | | | | PCO | 31 | 6 | | 3 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 4 | 6 | N | — | | | | | ~ | ^ | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 7 | ^ | — | | | | | ^ | ^ | | | 9 | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC 37.083) USAID Cable (50mm²/95mm²) (Ang-Angle) (Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV Net Metering Consumer site and note the above parameters

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights:- Steel Structure:- (SS) 38, 45, 40, 36, 31 PC Spun:- 45, 40, 36, 31 PC Ordinary:- 36, 31

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | T/F Capacity: | | S.Pole | | D.Pole | | Pad | Survey Date: 12-12-25 |
| Feeder: | | T/F Make: | | General Duty | | | Dedicated | | |
| Transformer Code: 930 | | Inspectors: | | | | Location | | | |
| Feeder Code: | Division: | | Sub-Division: | | | | Sub Division Code | | |

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 9 | 7 | YB | – | A | A | A | SP | PCO | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 8 | ∩ | – | | | | | | | 9 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 7 | 4 | 8 | ∼ | – | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 7 | 4 | 9 | ∩ | – | | | | | | | 20 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Goat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USA10 Cable (50mm) (95mm) (Arg-Angle) (Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV Net Metering Consumer site and note the above parameters

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights··· Steel Structure:- (SS) 58, 45, 40, 36, 31 PC Spun:- 45, 40, 36, 31 PC Ordinary - 36, 31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation: Bosan Road | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 12-12-24

Feeder: Khan village | T/F Make: Reclaim | General Duty ✓ | Ded

Transformer Code: 7-21716722 | Inspectors: Dgi | Location: Chak Doray wala

Feeder Code: 1820 | Division: BZ - M. Park | Sub-Division: Gulgasht | Sub Division Code

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 2 | 1 | 7 | 1 | 0 | 1 | 7 | 2 | 2 | 1 | RyB | W | W | W | W | TR | PCC | 36 | | | | | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 5 | 1 | | | | | | SP | 〃 | 〃 | 7 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 1 | | | | | | 〃 | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 2 | | | | | | 〃 | 〃 | 31 | 5 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 2 | B | — | — | A | A | 〃 | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 3 | 〃 | — | — | 〃 | 〃 | 〃 | PCS | | 13 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 3 | 〃 | — | — | 〃 | 〃 | 〃 | 〃 | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 4 | 〃 | — | — | 〃 | 〃 | 〃 | PCC | 31 | 42 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 1 | RY | A | G | — | A | 〃 | 〃 | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 5 | RY | A | G | — | A | 〃 | 〃 | 〃 | 28 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 1 | RyB | A | A | A | A | SP | PCC | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 6 | | | | | | | | 〃 | 19 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 6 | | | | | | | | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 7 | | | | | | | | 〃 | 26 | | | | | | | | | | 4 | | | | |
| S | | | | | | | | | 7 | 5 | 7 | | | | | | | | 〃 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 8 | | | | | | | | 31 | 6 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 8 | Y | — | A | — | A | SP | PCC | 31 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 5 | 9 | Y | — | A | — | 〃 | 〃 | 〃 | 〃 | 5 | | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 5 | 8 | RyB | A | A | A | A | SP | PCC | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 0 | 〃 | 〃 | A | A | A | SP | 〃 | 〃 | 18 | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | T/F Cap: | | S.Pole | | D.Pole | | Pad | | Survey Date: | 12-12-23 |
| Feeder: | 221 | T/F Make: | | | | General Duty | | Ded | | | |
| Transformer Code: | | Inspectors: | | | | | Location | | | | |
| Feeder Code: | Division: | Sub-Division: | | | | | | Sub Division Code | | | |

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT | Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 6 | 0 | RYB | A | A | A | A | SP | PCO | 36 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 1 | " | " | " | " | " | " | S | 31 | 15 | | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 1 | RY | A | A | — | A | SP | S | 31 | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 2 | | | | — | | | | | 12 | | | | | | | | | 1 | | 177711407 | 7 | 10.5 | |
| S | | | | | | | | | 7 | 6 | 2 | | | | — | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 3 | | | | — | A | SP | PCS | 31 | 20 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 3 | | | | — | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 4 | | | | — | | | | | 7 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 4 | | | | — | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 5 | | | | — | | | | | 11 | | | | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 0 | RYB | A | A | A | A | SP | PCO | 36 | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 6 | | | | | | | | | 5 | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

**Data Input Form for LT Survey**

Substation: Wapda Town | T/F Cap: 200 | S.Pole | D.Pole | Pad | Survey Date: 12-12-25

Feeder: Garay wala | T/F Make: Reclaim | General Duty | Ded

Transformer Code: | Inspectors: Ali | Location: Haidara Road

Feeder Code: 1812 | Division: BZ. M.Park | Sub-Division: Gulgasht | Sub Division Code

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT |
| S | 0 | 4 | 2 | 5 | 0 | 6 | 1 | 68 | 2 | 3 | 4 | R | Y | B | A | BC 95 MM | TK | S | 36 | | | | | | | | | | | |
| E | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 6 | 7 | | | | | | SP | " | " | 6 | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 7 | | | | | | " | " | " | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 8 | | | | | | " | " | 31 | | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 8 | | | | | | " | " | " | | | | | | | | | | | |
| E | | | | | | | | | 7 | 6 | 9 | | | | | | " | " | " | 5 | 2 | | | | | | | | 1 | |
| S | | | | | | | | | 7 | 6 | 9 | | | | | | " | " | " | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 0 | | | | | | SP | PLO | " | | | | | | | | | | | L |
| S | | | | | | | | | 7 | 7 | 0 | | | | | | " | " | " | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 1 | | | | | | " | [illegible] | " | 9 | 1 | | | | | | | | | |
| S | | | | | | | | | 7 | 7 | 1 | | | | | | " | S | " | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 2 | | | | | | | | | 8 | 2 | | | | | | | | | |
| S | | | | | | | | | 7 | 7 | 0 | R | Y | B | ABC | 50mm | SP | S | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 3 | | | | | | | | | 4 | | | | | | | | | | |
| S | | | | | | | | | 7 | 7 | 3 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 4 | | | | | | | | | 8 | | | | | | | | 1 | | |
| S | | | | | | | | | 7 | 7 | 4 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 5 | | | | | | | | | 9 | | | | | | | | 1 | | |
| S | | | | | | | | | 7 | 6 | 7 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 6 | | | | | | | | | 6 | | | | | | | | | | |

PV Solar/Net-Metering Data — Grid No. 2

| Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks |
|---|---|---|---|
| 60934-1 | 7 | 9.9 | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| 6096801 | 7 | 9.9 | |
| | | | |
| 609403 | | | Not Found |
| | | | |
| | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation: | T/F Cap: | S.Pole | D.Pole | Pad | Survey Date: 12-12-25

Feeder: | T/F Make: | General Duty | Ded

Transformer Code: 234 | Inspectors: | Location

Feeder Code: | Division: | Sub-Division: | Sub Division Code

| S/E | Grp | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | PV | INT |
| S | 0 | 1 | 1 | 2 | 1 | 2 | 2 | 5 | 7 | 7 | 6 | RYB | | ABC | | 50mm | SP | S | 31 | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 7 | | | | | | | | | 8 | | | | | | | | | | |
| S | | | | | | | | | 7 | 7 | 6 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 8 | | | | | | | | | 5 | | | | | | | | | 3 | |
| S | | | | | | | | | 7 | 7 | 8 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 7 | 9 | | | | | | | | | 4 | | | | | | | | | | |
| S | | | | | | | | | 7 | 6 | 2 | RYB | | ABC | | 95 | mm | SP | S | 36 | | | | | | | | | | |
| E | | | | | | | | | 7 | 8 | 0 | | | | | | | | | 31 | 16 | | | | | | | | | |
| S | | | | | | | | | 7 | 8 | 0 | | | | | | | | | | | | | | | | | | 1 | |
| E | | | | | | | | | 7 | 8 | 1 | | | | | | | | | 10 | | | | | | | | | | |
| S | | | | | | | | | 7 | 8 | 1 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 8 | 2 | | | | | | | | | 8 | | | | | | | | | | |
| S | | | | | | | | | 7 | 8 | 2 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 8 | 3 | | | | | | | | | 7 | | | | | | | | | | |
| S | | | | | | | | | 7 | 8 | 3 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 8 | 4 | | | | | | | | | 11 | | | | | | | | | | |
| S | | | | | | | | | 7 | 8 | 1 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 8 | 5 | | | | | | | | | 4 | | | | | | | | | | |
| S | | | | | | | | | 7 | 8 | 5 | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | | | 7 | 8 | 6 | | | | | | | | | | | | | | | | | | | |

### PV Solar/Net-Metering Data

| Consumer Reference No. | PV Solar Sanc LD (kW) | PV Solar Cap (kW) | Remarks |
|---|---|---|---|
| 6127003 | 27 | 33.89 | |
| 6098501 | | | |
| 6098901 | | | |
| 6133801 | 6 | 9 | |

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

06/11/25

A - 12 - 12 - 25

T/F = 11