T-3140421102

Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation: 132kV K/Garh | T/F Capacity: 200kVA | S.Pole | | D.Pole ✓ | Pad | Survey Date: 10/09/25

Feeder: Khan Garh | T/F Make: PEL | General Duty ✓ | Dedicated

Transformer Code: T-3140421102 | Inspectors: Station | Location: Police station

Feeder Code: 76901 | Division: Khan Garh | Sub-Division: Khan Garh | Sub Division Code

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data		
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	4	0	4	2	4	1	0	1	3	R	R	R		PP	PCC	36													
E							2	4	1	0	2						TP		4													
S							2	4	1	0	2	3	A	A	A	A	CP		31													
E	0	3	1	0	0	9	2	5	2	3	1																					
S							2	5	2	3	1																					
E								5	2	3	2																					
S							2	5	2	3	2	3	GN	GN	GN	GN																
E							2	5	2	3	3							S	31										✓			
S							2	5	2	3	3	3	A	A	A	A				1		2										
E							2	5	2	3	4									3												
S							2	5	2	3	4																					
E							2	5	2	3	5									7												
S							2	5	2	3	5																					
E							2	5	2	3	6									9												
S							2	5	2	3	6																					
E							2	5	2	3	7									2												

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar Power Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:

Feeder: | T/F Capacity: | S.Pole | D.Pole | Pad | Survey Date: 10/09/21

Transformer Code: | T/F Make: | General Duty | Dedicated

Feeder Code: | Division: | Inspectors: | Location

Sub-Division: | Sub Division Code

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data		
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	0	0	9	2	5	2	3	7	3	A	A	A	A	ST	RC	37													
E							2	5	2	3	8							S		1												
S							2	5	2	3	3																					
E							2	5	2	3	8									3		4										
S							2	5	2	3	9											.										
E							2	5	2	4	0									4		8										
S							2	5	2	4	0																					
E							2	5	2	4	1									14		16										
S							2	5	2	4	1																					
E							2	5	2	4	2									8		10										
S							2	5	2	3	1																					
E							2	5	2	4	3									4		3										
S							2	5	2	4	3																					
E							2	5	2	4	4									8		6	1									
S							2	5	2	4	4																					
E							2	5	2	4	5									15		8										

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar Power Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:		T/F Capacity:		S.Pole		D.Pole	Pad	Survey Date: 10/09/25
Feeder:		T/F Make:		General Duty		Dedicated		
Transformer Code:		Inspectors:		Location				
Feeder Code:	Division:	Sub-Divisiolo:		Sub Divisiolo Code				

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type									
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int
S	0	3	1	0	0	9	2	5	2	4	5	3	A	A	A	A	SM	S	31										
E							2	5	2	4	6									12		14							
S							2	5	2	4	6																		
E							2	5	2	4	7									7		10							
S							2	5	2	4	7																		
E							2	5	2	4	8									3		6							
S							2	5																					
E							2	5													

T-3140421105

Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation: BZCV K/Garh
Feeder: Khan Garh
Transformer Code: T-3140421105
Feeder Code: 9690 | Division: Khan Garh | Sub-Division: Khan Garh

T/F Capacity: 200kVA | S.Pole | D.Pole ✓ | Pad | Survey Date: 10/09/25
T/F Make: Siemens | General Duty ✓ | Dedicated
Inspectors: Shafiq | Location: Mohallah Shamliscabad | Sub Division Code

S/E	Group 0	Group 1	Date d	Date d	Date m	Date m	Date y	Date y	GPS WP 0	GPS WP 0	GPS WP 1	Conductor Phase	Conductor R	Conductor Y	Conductor B	Conductor Neutral	Equipment Type	Pole Class	Pole Height	Consumer Type RS	RL	SC	LC	SI	LI	PB	AG	ST	Int
S	0	3	1	4	0	4	2	1	1	0	4	3	R	R	R	R	PCO	8	36										
E							2	1	1	0	5	"	"	"	"	"	"	"	"										
S							2	1	1	0	5	3	W	W	W	W	SP	4	31										
E	0	3	1	0	0	9	2	5	2	4	8									3									✓
S							2	5	2	4	8																		
E							2	5	2	5	0																		
S							2	5	2	5	0																		
E							2	5	2	5	1							Bla	31	15									
S							2	5	2	5	1	3	A	A	A	A														
E							2	5	2	5	2									10									✓
S							2	5	2	5	2																		
E							2	5	2	5	3									8									✓
S							2	5	2	5	3	1	A	+	+	A													
E							2	5	2	5	4									9									
S							2	5	2	5	4																		
E							2	5	2	5	5									10									

Consumer Reference No.	Installed PV Capacity (kW)	Remarks

PV Solar/Net-Metering Data

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights: Steel Structure: (SS) 58,45,40,38,31 PC Spun: 45,40,38,31 PC Ordinary: 38,31

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:		T/F Capacity:		S.Pole		D.Pole	Pad	Survey Date:	10/09/25
Feeder:		T/F Make:		General Duty		Dedicated			
Transformer Code:		Inspectors:				Location			
Feeder Code:	Division:	Sub-Division:				Sub Division Code			

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data		
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	0	0	9	2	5	2	5	5	1	A	+	+	A	ST	Pc	31													
E							2	5	2	5	6									24												
S							2	5	2	5	7																					
E							2	5	2	5	7									09												
S							2	5	2	5	7																					
E							2	5	2	5	8																					
S							2	5	2	5	8									08												
E							2	5	2	5	9									28												
S							2	5	2	5	9																					
E							2	5	2	6	0									26												
S							2	5	2	6	0																					
E							2	5	2	6	1									22												
S							2	5	2	6	1	1	A	+	+	A																
E							2	5	2	6	2									12												
S							2	5	2	6	2																					
E							2	5	2	6	3									7												

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

105

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:		T/F Capacity:		S.Pole		D.Pole	Pad
Feeder:		T/F Make:		General Duty		Dedicated	Survey Date: 10/09/25
Transformer Code:		Inspectors:		Location			
Feeder Code:	Division:	Sub-Division:		Sub Division Code			

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data		
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	0	0	9	2	5	2	6	3	1	A	+	+	A	SP	PC	31													
E							2	5	2	6	3									7												
S							2	5	2	6	4																					
E							2	5	2	6	5									6												
S							2	5	2	5	3																					
E							2	5	2	6	6							S														
S							2	5	2	6	6									26		3										
E							2	5	2	6	7																					
S							2	5	2	6	7									25		1										
E							2	5	2	6	8																					
S							2	5	2	6	8									32		1										
E							2	5	2	6	9																					
S							2	5	2	6	9									27		2										
E							2	5	2	7	0																					
S							2	5	2	4	9	1	A	+	+	A				28		3										
E							2	5	2	7	1							S		19												

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

T-3190421209

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation: 132KV Khan Garh | T/F Capacity: 200KVA | S.Pole | D.Pole ✓ | Pad | Survey Date: 10/09/25

Transformer Code: T-3190421209 | T/F Make: Reliance | General Duty ✓ | Dedicated

Feeder Code: 76401 | Division: Khan Garh | Inspectors: Shuja | Location | Sub-Division: Khan Garh | Sub Division Code

S/E	Group 0	Group 1	Date d	Date d	Date m	Date m	Date y	Date y	GPS WP 0	GPS WP 0	GPS WP 1	Conductor Phase	Conductor R	Conductor Y	Conductor B	Conductor Neutral	Equipment Type	Pole Class	Pole Height	Consumer Type RS	RL	SC	LC	SI	LI	PB	AG	ST	Int
S	0	3	1	9	0	4	2	1	2	0	8	3	R	R	R		DP	5	36										
E							2	1	2	0	8	〃	〃	〃	〃	〃	TP	〃	〃										
S							2	1	2	0	8	3	W	W	W	W	SP	4	31										
E	0	3	1	0	0	9	2	5	2	7	2									6		10							
S							2	5	2	7	2																		
E							2	5	2	7	3																		
S							2	5	2	7	3	3	A	A	A	A													
E							2	5	2	7	4									3		5							
S							2	5	2	7	4																		
E							2	5	2	7	5									36									
S							2	5	2	7	5																		
E							2	5	2	7	6									33									
S							2	5	2	7	2																		
E							2	5	2	7	7									6		8							✓
S							2	5	2	7	7	1	A	+	+	A													
278 E							2	5	2	8	8							RS	31	15		18							

PV Solar/Net-Metering Data

Consumer Reference No.	Installed PV Capacity (kW)	Remarks

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights: Steel Structure (SS) 58,45,40,36,31 PC Spun: 45,40,36,31 PC Ordinary: 36,31

Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:

Feeder:

Transformer Code:

Feeder Code:

Division:

T/F Capacity:

T/F Make:

Inspectors:

S.Pole

General Duty

D.Pole

Pad

Dedicated

Survey Date: 10/09/25

Location

Sub-Division:

Sub Division Code

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data		
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	0	0	9	2	5	2	7	7	3	A	A	A	A	SP	9	31													
E							2	5	2	7	8																					
S							2	5	2	7	9									28												
E							2	5	2	8	0																					
S							2	5	2	7	7									14												
E							2	5	2	8	1																					
S							2	5												6		10										
E							2	5																								
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel ; (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31

T. 106021685O

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation: 132KV K/Garh | T/F Capacity: 200KVA | S.Pole | | D.Pole ✓ | Pad | Survey Date: 10/09/25

Feeder: Shamsabad | T/F Make: Dawlance | General Duty | ✓ | Dedicated

Transformer Code: T.106021685O | Inspectors: Shahzad | Location | Barri Deewan Wala

Feeder Code: | Division: Khan Garh | Sub-Division: Khan Garh | Sub Division Code

S/E	Group 0	Group 1	Date d	Date d	Date m	Date m	Date y	Date y	GPS WP 0	GPS WP 0	GPS WP 1	Conductor Phase	Conductor R	Conductor Y	Conductor B	Conductor Neutral	Equipment Type	Pole Class	Pole Height	Consumer Type RS	RL	SC	LC	SI	LI	PB	AG	ST	Int
S	0	1	0	6	0	2	1	6	8	4	9	3	R	R	R		DP	S	36										
E							1	6	8	5	0	〃	〃	〃	〃	〃	TP	C	〃										
S							1	6	8	5	0	3	W	W	W	W	SP	1	31										
E	0	3	1	0	0	9	2	5	2	8	2									10		3							✓
S							2	5	2	8	2																		
E							2	5	2	8	3																		
S							2	5	2	8	3	2	A	+	A	A														
E							2	5	2	8	4									15		12							
S							2	5	2	8	2	3	A	A	A	A	SP	S	31										
E							2	5	2	8	5							Rco		1									
S							2	5	2	8	5																		
E							2	5	2	8	6									28									
S							2	5	2	8	2																		
E							2	5	2	8	7									6		7							✓
S							2	5	2	8	7																		
E							2	5	2	8	8									8		9							

PV Solar/Net-Metering Data

Consumer Reference No.	Installed PV Capacity (kW)	Remarks

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

850

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:

Feeder: | T/F Capacity: | S.Pole | D.Pole | Pad | Survey Date: 10/09/25

Transformer Code: | T/F Make: | General Duty | Dedicated

Feeder Code: | Division: | Inspectors: | Location

Sub-Division: | Sub Division Code

S/E	Group		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data		
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	0	0	9	2	5	2	8	8	3	A	A	A	A	SP	S	31													
E							2	5	2	8	8									22												
S							2	5	2	8	8	2	A	A	+	A																
E							2	5	2	9	0									18												
S							2	5	2	9	0																					
F							2	5	2	9	1									16												
S							2	5	2	8	7	3	A	A	A	A	SP	PC	37													
F							2	5	2	9	2									8												
S							2	5	2	9	2																					
E							2	5	2	9	3									18												✓
S							2	5	2	9	3	1	+	A	+	A																
E							2	5	2	9	4									20												
S							2	5	2	9	3	1	+	+	GN	GN		S														
E							2	5	2	9	5									25												
S							2	5	2	9	5																					
E							2	5	2	9	6									7												

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights - Steel Structure (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31

Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

| | | |

T-1060216855

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation: 132KV K/Garh
Feeder: Shamsabad
Transformer Code: T-1060216855
Feeder Code: 26903 Division: Khan Garh Sub-Division: Khan Garh

T/F Capacity: 100kVA S.Pole D.Pole Pad ✓ Survey Date: 6/09/25
T/F Make: Siemens General Duty ✓ Dedicated
Inspectors: Shafiq Location Basti Sandeela Jamoobi Sub Division Code

S/E	Group 0	Group 1	Date d	Date d	Date m	Date m	Date y	Date y	GPS WP 0	GPS WP 0	GPS WP 1	Conductor Phase	R	Y	B	Neutral	Equipment Type	Pole Class	Pole Height	Consumer Type RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	1	0	6	0	2	1	6	8	5	4	3	R	R	R		PP	S	36													
E							1	6	8	5	5	〃	〃	〃	〃	〃	TP	〃	9													
S							1	6	8	5	5	3	A	A	A	A	SM	〃	31													
E	0	3	1	0	0	9	2	5	3	0	1	〃	〃	〃	〃	〃	〃	〃	〃	7	1								✓	Ref: 31123707		
S							2	5	3	0	1			.															SR: 20029185		
E							2	5	3	0	2									13										20029185		
S							2	5	3	0	2																					
E							2	5	3	0	3									15												
S							2	5	3	0	3	1	×	A	×	A																	
E							2	5	3	0	4									16												
S							2	5	3	0	4	1	+	+	GN	GN																	
E							2	5	3	0	5									8									✓			
S							2	5	3	0	5																					
E							2	5	3	0	6									16												
S							2	5	3	0	6																					
E							2	5	3	0	7									14												

302

PV Solar/Net-Metering Data

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58 45 40 36 31 PC Spun 45 40 36 31 PC Ordinary 36 31

Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

Data Input Form for LT Survey

Substation:
Feeder:
Transformer Code:
Feeder Code:
Division:
T/F Capacity:
T/F Make:
Inspectors:
Sub-Division:
S.Pole
General Duty
D.Pole
Pad
Dedicated
Location
Survey Date: 10/09/25
Sub Division Code

S/E	Group 0	Group 1	Date d	Date d	Date m	Date m	Date y	Date y	GPS WP 0	GPS WP 0	GPS WP 1	Conductor Phase	Conductor R	Conductor Y	Conductor B	Conductor Neutral	Equipment Type	Pole Class	Pole Height	Consumer Type RS	RL	SC	LC	SI	LI	PB	AG	ST	Int	Consumer Reference No.	Installed PV Capacity (kW)	Remarks
S	0	3	1	0	0	9	2	5	3	0	5	1	+	+	GN	GN	S	S	31													
E							2	5	3	0	8									3	8					1				~~2312~~ 3707	~~200~~	
S							2	5																					~~200~~ 29184		
E							2	5																					~~200~~ 29185		
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								
S							2	5																								
E							2	5																								

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel ; (RS) - Tabular Steel (TS) Wall Bracket (WB)

PV Solar/Net-Metering Data

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure - (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31