T-2080316916

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | 132 CV Khan Garh | T/F Capacity: | 100 KVA | S.Pole | | D.Pole ✓ | Pad | Survey Date: | 10/09/25 |
| Feeder: | City II Khan Garh | T/F Make: | Siemens | General Duty | | Dedicated | | | |
| Transformer Code: | T-2080316916 | Inspectors: | Hammad | Location | Chonar pur | | | | |
| Feeder Code: | 76604 | Division: | Khan Garh | Sub-Division: | Khan Garh | Sub Division Code | | | |

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| 915 S | 0 | 2 | 0 | 8 | 0 | 3 | 2 | 6 | 9 | 4 | 5 | 3 | R | R | R | | DP | S | 36 | | | | | | | | | | | | | |
| 916 E | | | | | | | 1 | 6 | 9 | 1 | 6 | " | " | " | " | " | TP | 4 | 7 | | | | | | | | | | | | | |
| 916 S | | | | | | | 1 | 6 | 9 | 1 | 6 | 3 | A | A | A | A | SP | 4 | 31 | | | | | | | | | | | | | |
| E | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 0 | 8 | | | | | | | | | 18 | 2 | | | | | | | | Ref | SR 2 | 158519 158520 |
| S | | | | | | | 2 | 5 | 3 | 0 | 9 | | | | | | | | | | | | | | | | | | | SR 2 | 158521 158522 |
| E | | | | | | | 2 | 5 | 3 | 1 | 0 | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 0 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 1 | | | | | | | | | 14 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 1 | 1 | A | + | + | A | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 2 | | | | | | | | | 5 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 2 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 3 | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 0 | 8 | 3 | A | A | A | A | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 4 | | | | | | | | | 8 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 4 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 5 | | | | | | | | | 13 | | | | | | | | | ✓ | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights - Steel Structure - (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Substation: | | T/F Capacity: | | S.Pole | | D.Pole | Pad |
| Feeder: | | T/F Make: | | General Duty | | Dedicated | Survey Date: 10/09/25 |
| Transformer Code: | | Inspectors: | | Location | | | |
| Feeder Code: | Division: | Sub-Division: | | Sub Division Code | | | |

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 1 | 5 | 3 | A | A | A | A | ST | S | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 6 | | | | | | | | | | | | | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 6 | 1 | A | + | + | A | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 7 | | | | | | | | | 3 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 5 | 1 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 8 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 8 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 1 | 9 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 1 | 9 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 0 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 2 | 0 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 1 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 2 | 1 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 2 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 2 | 2 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 3 | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

(916)

# Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | T/F Capacity: | | S.Pole | | D.Pole | Pad | Survey Date: | 10/09/25 |
| Feeder: | | T/F Make: | | General Duty | | | Dedicated | | |
| Transformer Code: | | Inspectors: | | | | Location | | | |
| Feeder Code: | Division: | Sub-Divisiln: | | | | | Sub Division Code | | |

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutra l | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 1 | 6 | 7 | A | A | A | A | SP | S | 37 | | | | | | | | | | | | | 324 |
| E | | | | | | | 2 | 5 | 3 | 2 | 5 | | | | | | | | | 1 | | | | | | | | | | | | GPS point miss or delete |
| S | | | | | | | 2 | 5 | 3 | 2 | 5 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 6 | | | | | | | | | 8 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

T.3170321103

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | 132KV Khan Garh | T/F Capacity: | 200KVA | S.Pole | | D.Pole | Pad ✓ | Survey Date: | 10/09/23 |
| Feeder: | City II Khan Garh | T/F Make: | Transformer | General Duty | | ✓ | Dedicated | | Sadeer Abad |
| Transformer Code: | | Inspectors: | Hammad | | | Location | | | |
| Feeder Code: | Division: | Khan Garh | Sub-Division: | | Khan Garh | Sub Division Code | | | |

| S/E | Group 0 | Group 1 | Date d | Date d | Date m | Date m | Date y | Date y | GPS WP 0 | GPS WP 0 | GPS WP 1 | Conductor Phase | Conductor R | Conductor Y | Conductor B | Conductor Neutral | Equipment Type | Pole Class | Pole Height | Consumer Type RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 3 | 1 | 7 | 0 | 3 | 2 | 1 | 1 | 0 | 2 | 3 | R | R | R | | PP | S | 38 | | | | | | | | | | | | |
| E | | | | | | | 2 | 1 | 1 | 0 | 3 | 4 | 4 | 4 | 4 | 4 | TP | 4 | 4 | | | | | | | | | | | | |
| S | | | | | | | 2 | 1 | 1 | 0 | 3 | 3 | A | A | A | A | SP | 1 | 37 | 12 | | 3 | | | | | | | | | |
| E | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 2 | 7 | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 2 | 7 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 8 | | | | | | | | | 10 | | 4 | | | | | | | ✓ | | |
| S | | | | | | | 2 | 5 | 3 | 2 | 8 | 2 | + | GN A | GN | GN | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 2 | 9 | | | | | | | | | 12 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 2 | 9 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 3 | 0 | | | | | | | | | 16 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 0 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 3 | 1 | | | | | | | | | 17 | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 1 | 1 | + | GN | + | GN | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 3 | 2 | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 2 | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 3 | 3 | | | | | | | | | 7 | | | | | | | | | | | |

PV Solar/Net-Metering Data

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Agg-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

# Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | |

T-2080316916

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | 132KV K/Garh | T/F Capacity: | 300KVA | S.Pole | | D.Pole ✓ | Pad | Survey Date: | 10/09/25 |
| Feeder: | city-II K/Garh | T/F Make: | PEL | General Duty | ✓ | Dedicated | | | |
| Transformer Code: | T-2080316916 | Inspectors: | Hammad | Location | Chohan pur | | | | |
| Feeder Code: | 76904 | Division: | khan Garh | Sub-Division: | khan Garh | Sub Division Code | | | |

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 0 | 2 | 0 | 8 | 0 | 3 | 1 | 6 | 9 | 1 | 5 | 3 | R | R | R | | | S | 36 | | | | | | | | | | | | | |
| E | | | | | | | 1 | 6 | 9 | 1 | 6 | 4 | 4 | 4 | 4 | 4 | TP | 4 | 4 | | | | | | | | | | | | | |
| S | | | | | | | 1 | 6 | 9 | 1 | 6 | 3 | Insulated | | | Ant | 4 | 37 | | | | | | | | | | | | | | |
| E | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 3 | 8 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 8 | 3 | GN | GN | GN | GN | SP | S | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 3 | 9 | | | | | | | | | 6 | | | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 9 | 1 | GN | + | + | GN | SP | S | 37 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 0 | | | | | | | | | 18 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 9 | 2 | GN | + | GN | GN | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 1 | | | | | | | | | 7 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 1 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 2 | | | | | | | | | 14 | | | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 2 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 3 | | | | | | | | | 15 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 3 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 4 | | | | | | | | | 14 | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure - (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31

916

# Evaluation of Distributioln Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation:

Feeder: | T/F Capacity: | S.Pole | D.Pole | Pad | Survey Date: 10/09/25

Transformer Code: | T/F Make: | General Duty | Dedicated

Feeder Code: | Division: | Inspectors: | Location

Sub-Division: | Sub Division Code

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 4 | 2 | 2 | GN | + | GN | GN | SD | S | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 5 | | | | | | | | | 7 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 5 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 6 | | | | | | | | | 14 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 6 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 7 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 7 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 8 | | | | | | | | | 4 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 8 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 4 | 9 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 4 | 9 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 0 | 1 | GN | + | + | GN | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 0 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 1 | | | | | | | | | 1 | | | | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 1 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 2 | | | | | | | | | 11 | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31

(916)

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation:

Feeder:

Transformer Code:

Feeder Code:

Division:

T/F Capacity:

T/F Make:

Inspectors:

S.Pole | D.Pole | Pad | Survey Date: 10/09/25

General Duty | Dedicated

Location

Sub-Division:

Sub Divisiion Code

| S/E | Group 0 | Group 1 | Date d | Date d | Date m | Date m | Date y | Date y | GPS WP 0 | GPS WP 0 | GPS WP 1 | Conductor Phase | Conductor R | Conductor Y | Conductor B | Conductor Neutral | Equipment Type | Pole Class | Pole Height | Consumer Type RS | RL | SC | LC | SI | LI | PB | AG | ST | Int |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 5 | 1 | 1 | GN | + | + | GN | SP | Po | 37 | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 2 | 4 | " | 4 | " | 4 | 4 | 4 | 4 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 3 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 3 | | | | | | | | | 4 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 3 | 8 | 2 | GN | GN | + | GN | SP | S | 37 | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 5 | | | | | | | | | 6 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 5 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 6 | | | | | | | | | 7 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 6 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 7 | | | | | | | | | 6 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 7 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 8 | | | | | | | | | 7 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 8 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 5 | 9 | | | | | | | | | 6 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 5 | 9 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 0 | | | | | | | | | 7 | | | | | | | | | |

PV Solar/Net-Metering Data

| Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|
| | | |
| | | |
| | | |

(9/6)

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

Substation:

Feeder:

Transformer Code:

Feeder Code: Division:

T/F Capacity: S.Pole D.Pole Pad Survey Date: 10/09/25

T/F Make: General Duty Dedicated

Inspectors: Location

Sub-Division: Sub Division Code

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | | PV Solar/Net-Metering Data | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int | Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
| S | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 6 | 0 | 2 | GN | GN | x | GN | SP | S | 31 | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 1 | | | | | | | | | 2 | | | | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 1 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 2 | | | | | | | | | 4 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 1 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 3 | | | | | | | | | 2 | | | | | | | | | ✓ | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 3 | 1 | x | GN | x | GN | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 4 | | | | | | | | | 5 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 3 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 5 | | | | | | | | | 8 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 0 | 2 | GN | GN | x | GN | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 6 | | | | | | | | | 18 | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | | | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

T-3170321112

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | 132KV K/Garh | T/F Capacity: | 200KVA | S.Pole | | D.Pole ✓ | Pad | Survey Date: | 10/09/25 |
| Feeder: | City II K/Garh | T/F Make: | PEL | General Duty | | ✓ | Dedicated | | |
| Transformer Code: | T-3170321112 | Inspectors: | Hammad | Location | | Dhand Wala | | | |
| Feeder Code: | 76904 | Division: | Khan Garh | Sub-Division: | | Khan Garh | Sub Divisfon Code | | |

| S/E | Group 0 | Group 1 | Date d | Date d | Date m | Date m | Date y | Date y | GPS WP 0 | GPS WP 0 | GPS WP 1 | Conductor Phase | Conductor R | Conductor Y | Conductor B | Conductor Neutral | Equipment Type | Pole Class | Pole Height | Consumer Type RS | RL | SC | LC | SI | LI | PB | AG | ST | Int |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| S | 0 | 3 | 1 | 7 | 0 | 3 | 2 | 1 | 1 | 1 | 1 | 3 | R | R | R | | PP | S | 38 | | | | | | | | | | |
| E | | | | | | | 2 | 1 | 1 | 1 | 2 | 4 | 4 | 4 | 4 | 4 | HP | 4 | 4 | | | | | | | | | | |
| S | | | | | | | 2 | 1 | 1 | 1 | 2 | 3 | GN | GN | GN | GN | SP | 1 | 37 | | | | | | | | | | |
| E | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 6 | 7 | | | | | | | | | 12 | | | | | | | | | ✓ |
| S | | | | | | | 2 | 5 | 3 | 6 | 7 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 8 | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 8 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 6 | 9 | | | | | | | | | 12 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 9 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 7 | 0 | | | | | | | | | 15 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 7 | 1 | X | GN | X | GN | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 7 | 1 | | | | | | | | | 10 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 7 | 1 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 7 | 2 | | | | | | | | | 7 | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 6 | 7 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 7 | 3 | | | | | | | | | | | | | | | | | | |

### PV Solar/Net-Metering Data

| Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar Power Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights ... Steel Structure ... (SS) 58,45,40,36,31 PC Spun ... 45,40,36,31 PC Ordinary ... 36,31

# Evaluation of Distributioin Losses of MEPCO'S Network for the FY 2023-24

## Data Input Form for LT Survey

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Substation: | | | | | | | | | |
| Feeder: | | T/F Capacity: | | S.Pole | | D.Pole | Pad | Survey Date: | 10/09/25 |
| Transformer Code: | | T/F Make: | | General Duty | | Dedicated | | | |
| Feeder Code: | Division: | Inspectors: | | Location | | | | | |
| | | Sub-Division: | | | | Sub Division Code | | | |

| S/E | Group | | Date | | | | | | GPS WP | | | Conductor | | | | | Equipment Type | | | Consumer Type | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | d | d | m | m | y | y | 0 | 0 | 1 | Phase | R | Y | B | Neutral | Type | Pole Class | Pole Height | RS | RL | SC | LC | SI | LI | PB | AG | ST | Int |
| S | 0 | 5 | 1 | 0 | 0 | 9 | 2 | 5 | 3 | 7 | 3 | 1 | x | GN | x | GN | SP | Pa | 31 | | | | | | | | | | |
| F | | | | | | | 2 | 5 | 3 | 7 | 4 | 〃 | 〃 | 〃 | 〃 | 〃 | 〃 | 〃 | 〃 | | | | | | | | | | |
| S | | | | | | | 2 | 5 | 3 | 7 | 4 | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | 3 | 7 | 5 | | | | | | | | | 7 | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| F | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| F | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| F | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| S | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |
| E | | | | | | | 2 | 5 | | | | | | | | | | | | | | | | | | | | | |

### PV Solar/Net-Metering Data

| Consumer Reference No. | Installed PV Capacity (kW) | Remarks |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/37.083) USAID Cable (50mm)(95mm) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light

Pole Heights = Steel Structure (SS) 58,45,40,36,31 PC Spun 45,40,36,31 PC Ordinary 36,31