Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:	132 KVA Abbotabad	T/F Cap:	100	S.Pole		D.Pole ✓	Pad	Survey Date:	08-10-25
Feeder:	Nawa Shehr	T/F Make:				General Duty ✓	Ded		
Transformer Code:	T-111312221104	Inspectors:	Ali Raza			Location	Near Arisons Grammer school		
Feeder Code:	000407	Division:	Rural Abbotabad	Sub-Division:	Nawan Shehr		Sub Division Code	27143	

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type									PV Solar/Net-Metering Data			
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	1	3	1	2	2	2	1	0	4	R/B	A	A	A	A	TR	S	36														
E	0	1	0	8	1	0	2	6	0	0	1	~	~	~	~	N	SP	S	36	3										✓			
S									0	0	1																						
E									0	0	2								31	4													
S									0	0	2																			✓			
E									0	0	3									14													
S									0	0	3																						
E									0	0	4									11								1		3298083266			
S									0	0	4	R/B	A	A	A	A	SP	S	31														
E									0	0	5									4													
S									0	0	5																						
E									0	0	6									7													
S									0	0	6																						
E									0	0	7									9													
S									0	0	7																						
E									0	0	8									8													
S									0	0	8																						
E									0	0	9									15													
S									0	0	9																						
E									0	1	0									12													

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure - (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation: 132 KVA Abbottabad
Feeder: Nawan Shehr
Transformer Code: T-1113122104
Feeder Code: 000407
Division:
Sub-Division:

T/F Cap: 100 | S.Pole | D.Pole ✓ | Pad
T/F Make: | General Duty ✓ | Ded
Inspectors: Ali Raza
Location: Near Abisons Grammer School
Survey Date: 08-10-26
Sub Division Code

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	D	t	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	0	1	0	R-Y-B	A	A	A	A	SP	S	31															
E	0	1	0	8	1	0	2	6	0	1	1									13														
S									0	1	1																							
E									0	1	2									10														
S									0	0	2	R-Y	A	A	-	A	SP	S	31															
E									0	1	3						〃	〃	36	10		2												
S									0	0	1	Y	-	A	-	A	SP	S	36															
E									0	1	4									8									1	20025484			
S									0	1	4																							
E									0	1	5									3													3 conductors
S									0	1	5																							〃
E									0	1	6									2													〃
S									0	1	6																							〃
E									0	1	7									7													〃
S																																		
E																																		
S														1			11																	
E																																		
S																																		
E																																		

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

02

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:	132 KVA Abbottabad	T/F Cap:	200	S.Pole		D.Pole ✓	Pad	Survey Date:	08-10-25
Feeder:	Nawan Shehr	T/F Make:	Elmetec	General Duty	✓	Ded			
Transformer Code:	T-1123617182	Inspectors:	Ali Raza			Location	Oresh colony		
Feeder Code:	000407	Division:	Kusal Abbottabad	Sub-Division:	Nawan Shehr			Sub Division Code	27143

SE	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	D	t	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	1	1	23	0	6	1	7		1	8	2	R/B	W	W	W	W	TR	S	36														
E	0	1	0	8	1	0	26		0	1	8	"	"	"	"	"	SP	"	"	6	1	1											
S									0	1	8								7														
E									0	1	9								31														
S									0	1	9																						
E									0	2	0							S	31	6									✓			
S									0	2	0	B	—	—	G/N	G/N	SP																
E									0	2	1						SP	W/B	—	2													
S									0	2	1						SP	W/B	—														
E									0	2	2						SP	"		6													
S									0	2	0	R/B	A	A	A	A	M	S	31														
E									0	2	3						"	S	31	7													
S									0	2	3	R/	A	A	—	A	SP	S	31														
E									0	2	4							S	31	3													
S									0	2	4																						
E									0	2	5									3													
S									0	2	0	R/B	W	W	W	W	SP	S	31														
E									0	2	6									14									✓			
S									0	2	6																						
E									0	2	7									5													

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1p Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure - (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:	132 KVA, Abbotabad	T/F Cap:	200	S.Pole		D.Pole ✓	Pad	Survey Date:	08-10-26
Feeder:	Nawan sheher	T/F Make:	Elmetec			General Duty ✓	Ded		
Transformer Code:	T-11230617/82	Inspectors:	Ali Raza			Location		Oresh colony	
Feeder Code:	000407	Division:		Sub-Division:				Sub Division Code	

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	D	I	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	01		28	1	0	2	6		0	2	7	R4B	W	W	W	W	SP	S	31														
E									0	2	8	~	N	N	~	~	~	~	~	9													
S									0	2	8	R4B	A	A	A	A	SP	S	31														
E									0	2	9									6													
S									0	2	9					/																	
E									0	3	0					/				2													
S									0	3	0																						
E									0	3	1									17													
S									0	3	1	R4B	A	A	A	A	SP	S	31														
E									0	3	2									12													
S									0	3	2					/																	
E									0	3	3					/				5													
S									0	3	3																						
E									0	3	4									14		2							✓				
S									0	3	4	R4	A	A	-	A	SP	S	31														
E									0	3	5				-			/		8													
S									0	3	5		/		-		/																
E									0	3	6				-					12													
S									0	3	4	R4B	A	A	A	A	SP	S	31														
E									0	3	7									15									✓				

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary.- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation: 132 KVA Abbotabad | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 08-10-25

Feeder: Nawan Shehr | T/F Make: Elmetec | General Duty ✓ | Ded

Transformer Code: T-1123061782 | Inspectors: Ali Raza | Location: Oresh colony

Feeder Code: 000407 | Division: | Sub-Division: | Sub Division Code:

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	0	3	7	R/Y/B	A	A	A	A	SP	S	31															
E									0	3	8									5														
S									0	3	8																							
E									0	3	9									10														
S									0	3	9																							
E									0	4	0									8														
S									0	3	7	R/B	A	A	A	A	SP	S	31															
E									0	4	1							~	~	2										✓				
S									0	4	1							~	~															
E									0	4	2							w/B	—	2														
S									0	4	2							w/B	—															
E									0	4	3							S	31	6														
S									0	4	3																							
E									0	4	4									11														
S									0	4	1	R/B	A	A	A	A	SP	S	31															
E									0	4	5									3														
S									0	4	5																							
E									0	4	6									5										✓				
S									0	4	6	R	A	—	—	A	SP	S	31															
E									0	4	7							w/B	—	1														

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0/083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:	132 kVA Abbotabad	T/F Cap:	200	S.Pole		D.Pole ✓	Pad	Survey Date:	08-10-26
Feeder:	Nawan Shehr	T/F Make:	Elnetec			General Duty ✓	Ded		
Transformer Code:	T-1123061782	Inspectors:	Ali Raza			Location		Obesh colony	
Feeder Code:	000407	Division:		Sub-Division:				Sub Division Code	

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	0	4	7	R	A	—	—	A	SP	W/B	—														
E									0	4	8							S	31	13													
S									0	4	6	R,Y,B	A	A	A	A	DP	〃	〃														
E									0	4	9									48													
S									0	4	9																						
E									0	5	0									5		1							✓				
S									0	5	2																						
E									0	5	1	R,Y,B	A	A	A	A	SP	W/B	—														
S									0	5	1							〃	〃														
E									0	5	2							S	31	17													
S									0	5	2							〃	〃														
E									0	5	3							W/B	—	6													
S									0	5	3							〃	〃														
E									0	5	4							S	31	15													
S									0	5	0																						
E									0	5	5									42													
S																																	
E																																	
S																																	
E																																	

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

03

Data Input Form for LT Survey

Substation:	132 kVA, Abbotabad	T/F Cap:	200	S.Pole		D.Pole	✓	Pad		Survey Date:	08-10-26
Feeder:	Nawan shehr	T/F Make:	TF Industries	General Duty	✓	Ded					
Transformer Code:	T-11/3222/07	Inspectors:	Ali Raza					Location	Gohar Colony Masjid Khazrai		
Feeder Code:	000407	Division:	Rural Abbotabad	Sub-Division:		Nawan shehr		Sub Division Code	27148		

PV Solar/Net-Metering Data

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type									Consumer Reference No.	PV Solar Sanc LD (kW)	PV Solar Cap (kW)	Remarks
	g	t	d	d	m	m	y	y	g	g	t	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT				
S	1	1	1	3	1	2	2	2	1	0	7	R4B	W	W	W	W	TK	S	36														
E	0	1	0	8	1	0	2	6	0	5	6	~	~	~	~	~	SP	S	36			5	1										
S									0	5	6																						
E									0	5	7								31			2											
S									0	5	7																						
E									0	5	8								40	3									✓				
S									0	5	8																						
E									0	5	9								40	12		1	6										
S									0	5	9																						
E									0	6	0									10		3											
S									0	6	0																						
E									0	6	1									5		1											
S									0	6	1																						
E									0	6	2								36	4													
S									0	6	2	R4B	GN	GN	GN	GN	SP	S	~														
E									0	6	3								31	8		2								✓			
S									0	6	3	R4B	PVC 3/0.083				SP	S	31														4 Core
E									0	6	4																						
S									0	6	4																						
E									0	6	5							S	31											✓			

Conductor = (A) Ant - (W) Wasp - (GN) Goat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)/(95mm2) (Ang- Angle/Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) - Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure - (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary - 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation: 132 KVA Abbotabad | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 08-10-26

Feeder: Nawan Shehr | T/F Make: | General Duty ✓ | Ded

Transformer Code: T-111312221107 | Inspectors: Ali Raza | Location: Gohar Colony Masjid Ichazrai

Feeder Code: 000407 | Division: Rural Abbotabad | Sub-Division: Nawan Shehr | Sub Division Code: 22438

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	0	6	5	R-Y-B	PVC	37/0.083			SP	TS	31															
E									0	6	6																							(20feet)
S									0	6	6																							
E									0	6	7																							
S									0	6	7																							
E									0	6	8																							
S									0	6	8																							
E									0	6	9								14															
S									0	6	5	R-Y	A	A	-	A	SP	S	31															
E									0	7	0				-				-															
S									0	7	0				-																			
E									0	7	1				-				6															
S									0	7	1				-																			
E									0	7	2				-				1															
S									0	7	2				-																			
E									0	7	3				-				2															
S									0	7	3				-																			
E									0	7	4				-				-															
S									0	6	3	R-Y-B	GN	GN	GN	GN	SP	S	B6															
E									0	7	5								34	4	2													

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) - Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ph Res - RL = 3ph Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:		**T/F Cap:**		**S.Pole**		**D.Pole**	**Pad**	**Survey Date:** 08-10-25
Feeder:		**T/F Make:**			**General Duty**		**Ded**	
Transformer Code:	T-1113122107	**Inspectors:**				**Location**		
Feeder Code:	**Division:**		**Sub-Division:**				**Sub Division Code**	

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	D	t	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	0	7	5	R/Y/B	A	A	A	A	SP	S	7/0														
E									0	7	6									8													
S									0	7	6																						
E									0	7	7								40	2			1										
S									0	7	7																						
E									0	7	8									6		2	3										
S									0	7	8																						
E									0	7	9									2			1										
S									0	7	9																						
E									0	8	0								40	-													
S									0	5	8	R/Y/B	A	A	A	A	SP	S	36														
E									0	8	1								36	4													
S									0	8	1																						
E									0	8	2								31	6													
S									0	8	2																						
E									0	8	3									23										✓			
S									0	8	3	R/Y/B	PVC-37/0.083				SP	S	31														
E									0	8	4							W/B	-	11													
S									0	8	3	R/Y/B	A	A	A	A	SP	W/B	-														
E									0	8	5									15	3												

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure - (SS) 58,45,40,36,31 PC Spun: - 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:		T/F Cap:		S.Pole		D.Pole		Pad		Survey Date:	08-10-26
Feeder:		T/F Make:				General Duty		Ded			
Transformer Code:	T-111312 22/07	Inspectors:						Location			
Feeder Code:		Division:		Sub-Division:						Sub Division Code	

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type									PV Solar/Net-Metering Data			
	D	T	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	0	8	6	R4B	W	W	W	W	SP	S	36														
E									0	8	6								40	7		1											
S									0	8	6																						
E									0	8	7									10		5								✓			
S									0	8	7	R4B	A	A	A	A	SP	S															
E									0	8	8								31	6		4	1										
S									0	8	7								40														
E									0	8	9								40	7		4	1										
S									0	8	9	R	A	A	–	A	SP	S	36														
E									0	9	0									9		8											
S																																	
E																																	
S																																	
E																																	
S																																	
E																																	
S																																	
E																																	
S																																	
E																																	

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ph Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

04

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:	132 KV Abbatabad	T/F Cap:	100	S.Pole		D.Pole ✓	Pad
Feeder:		T/F Make:	Reclaimed	General Duty		✓	Ded
Transformer Code:	T-1163077217	Inspectors:		Location		Jamea Masjid Usmanedy	
Feeder Code:	Division:	Sub-Division:				Sub Division Code	

Survey Date: 08-10-25

PV Solar/Net-Metering Data: Muhallah Qi

SE	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										
	D	t	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT
S	1	1	0	3	0	7	1	7	2	1	7	~~RYB~~	A	A	A	A	~~AR~~ SP	S	36											
E	0	1	0	8	1	0	2	~~6~~	0	9	1						SP	S	36	1		3								
S									0	9	1						N	N	N											
E									0	9	2						SP	S	31	1		5								
S									0	9	2	B	—	-	A	GSL	SP	S	31											Half Span
E									0	9	3		—	—	A	GSL			40	4		7								Not
S									0	9	1	RYB	A	A	A	A	SP	S	36											
E									0	9	4									5		4	1							
S									0	9	4																			
E									0	9	5									12		1								
S									0	9	5																			
E									0	9	6									9		1								
S									0	9	6																			
E									0	9	7									9										
S									0	9	7																			
E									0	9	8									2										
S									0	9	8	YB	—	A	A	A	SP	S	36											
E									0	9	9		—							3										
S									0	9	9		—																	
E									1	0	0		—							8										

Consumer Reference No. | PV Solar Sen LD (kW) | PV Solar Cap (kW) | Remarks

Conductor = (A) Ant - (W) Wasp - (GN) Goat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure - (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation: 132 KV Adpat Abad | T/F Cap: 200 | S.Pole | D.Pole ✓ | Pad | Survey Date: 08-10-26

Feeder: Nawan Shehm | T/F Make: Reclaim | General Duty ✓ | Ded

Transformer Code: T-110307 17223 | Inspectors: | Location: Near Hamalia Black Factory

Feeder Code: | Division: Rural A.Abad | Sub-Division: Nawan Shehm | Sub Division Code

PV Solar/Net-Metering Data

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
	d	t	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT				
S	1	1	0	3	0	7	1	7	2	3	3	R-Y-B	W	W	W	W	TR	S	36														
E	0	1	0	8	1	0	2	6	1	0	1	〃	〃	〃	〃	〃	SP	〃	〃	2										✓			
S									1	0	1																						
E									1	0	2								31	6													
S									1	0	1																						
E									1	0	3									11													
S									1	0	3																						
E									1	0	4									7													
S									1	0	4	R-Y-B	G/N	G/N	G/N	G/N	SP	S	31														
E									1	0	5		G/N	G/N	G/N	G/N	〃	〃	〃	2													
S									1	0	1	R-Y-B	W	W	W	W	SP	S	36														
E									1	0	6	〃	〃	〃	〃	〃	〃	〃	31	7		1								N			
S									1	0	6	R-Y-B	A	A	A	A	SP	S	31														
E									1	0	7									8													
S									1	0	7																						
E									1	0	8									9													
S									1	0	6	R-Y-B	A	A	A	A	SP	S	31														
E									1	0	9								36	22		2											
S									1	0	8																						
E									1	1	0								36	10													

Conductor = (A) Ant - (W) Wasp - (GN) Goat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2/95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer sits and note the above parameters accordingly.

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights : Steel Structure - (SS) 58,45,40,36,31 PC Spun - 45,40,36,31 PC Ordinary:- 36,31

Evaluation of Distribution Losses of HAZECO Network for the FY 2025-26

Data Input Form for LT Survey

Substation:		T/F Cap:		S.Pole		D.Pole	Pad	Survey Date:	08-10-26
Feeder:	T-1103071723	T/F Make:		General Duty			Ded		
Transformer Code:		Inspectors:				Location			
Feeder Code:	Division:	Sub-Division:					Sub Division Code		

S/E	Grp		Date						GPS WP			Conductor					Equipment Type			Consumer Type										PV Solar/Net-Metering Data			
	0	1	d	d	m	m	y	y	0	0	1	Phase	R	Y	B	Neutral	Type	Pole Class	Pole Height	RS	RL	SC	LC	SI	LI	PB	AG	ST	PV	INT	Consumer Reference No.	PV Solar Sen LD (kW)	PV Solar Cap (kW)	Remarks
S	0	1	0	8	1	0	2	6	1	1	0	RYB	A	A	A	A	SP	S	31															
E									1	1	1							W/B	–															
S									1	1	1																							
E									1	1	2	RYB	A	A	A	A	SP	S	31	6														
S									1	1	2																							
E									1	1	3									9		2							✓				
S									1	1	3																							
E									1	1	4									10													
S									1	1	4																							
E									1	1	5									23													
S									1	1	5																							
E									1	1	6									11													
S									1	1	6																							
E									1	1	7									7													
S									1	1	7																							
E									1	1	8									11													
S									1	1	8																							
E									1	1	9									35													
S									1	1	3	RYB	A	A	A	A	SP	S	36															
E									1	2	0																							

Conductor = (A) Ant - (W) Wasp - (GN) Gnat - 2/0 AWG (PVC 7/0.052) (PVC 19/0.052) (PVC 19/0.083) (PVC/0.083) ABC Cable (50mm2)(95mm2) (Ang-Angle)(Int-Intersection)

Pole Class = Steel Structure(S) - PC Ordinary (PCO) - PC Spun(PCS) - Rail Steel (RS) - Tabular Steel (TS) Wall Bracket (WB)

Consumer = RS = 1ps Res - RL = 3p Res - SC = 1p Com - SI = 1p Ind - LI = 3p Ind - PB = Public Building - AG = Agricultural - ST = Street Light - PV = PV Solar

Pole Heights... Steel Structure:- (SS) 58,45,40,36,31 PC Spun:- 45,40,36,31 PC Ordinary:- 36,31

Note: The Surveyor will visit each of the Solar PV/Net Metering Consumer site and note the above parameters accordingly.

A088/026

Feeder = Nawan Shehr

Sub Div = Nawan Shehr

T/F = 05