

RestTemplate


Tuesday, 13 May 2025 3:20 PM

In this topic today, will cover:

1st : Set up of 2 microservice i.e. "OrderService" and "ProductService" running on different port numbers.



2nd : How two microservices can communicate with each other



Let's start:

1st : Set up of 2 microservice

OrderService Go to Spring Initializer (start.spring.io)

Project

☐ Gradle - Groovy

☐ Gradle - Kotlin

☒ Maven

Language

☒ Java

☐ Kotlin

☐ Groovy

Spring Boot

☐ 3.5.0 (SNAPSHOT)

☐ 3.5.0 (RC1)

☐ 3.4.6 (SNAPSHOT)

☒ 3.4.5

☐ 3.3.12 (SNAPSHOT)

☐ 3.3.11

Project Metadata

Dependencies

ADD DEPENDENCIES... ⌘ + B

Spring Web WEB

Build web, including RESTful, applications using Spring MVC. Uses Apache Tomcat as the default embedded container.

Group

com.conceptandcoding

Artifact

orderservice

Name

orderservice

Description

learning SpringBoot Microservices

Package name

com.conceptandcoding.orderservice

Packaging

☒ Jar

☐ War

Java

☐ 24

☐ 21

☒ 17

Similarly, set up **ProductService**

Project

☐ Gradle - Groovy

☐ Gradle - Kotlin

☒ Maven

Language

☒ Java

☐ Kotlin

☐ Groovy

Spring Boot

☐ 3.5.0 (SNAPSHOT)

☐ 3.5.0 (RC1)

☐ 3.4.6 (SNAPSHOT)

☒ 3.4.5

☐ 3.3.12 (SNAPSHOT)

☐ 3.3.11

Project Metadata

Group

com.conceptandcoding

Artifact

productservice

Name

productservice

Description

learning SpringBoot Microservices

Package name

com.conceptandcoding.productservice

Packaging

☒ Jar

☐ War

Java

☐ 24

☐ 21

☒ 17

Dependencies

ADD DEPENDENCIES... % + B

Spring Web

WEB

Build web, including RESTful, applications using Spring MVC. Uses Apache Tomcat as the default embedded container.

OrderService

application.properties

1

server.port=8081


2

3

4

```
2025-05-14T13:11:25.863+05:30 INFO 11440 --- [main] c.c.o.OrderserviceApplication : Starting OrderserviceApplication using Java 17.0.12 with PID 11440
2025-05-14T13:11:25.865+05:30 INFO 11440 --- [main] c.c.o.OrderserviceApplication : No active profile set, falling back to 1 default profile: "default"
2025-05-14T13:11:26.183+05:30 INFO 11440 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8081 (http)
2025-05-14T13:11:26.188+05:30 INFO 11440 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2025-05-14T13:11:26.188+05:30 INFO 11440 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.40]
2025-05-14T13:11:26.203+05:30 INFO 11440 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2025-05-14T13:11:26.204+05:30 INFO 11440 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 320 ms
2025-05-14T13:11:26.331+05:30 INFO 11440 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8081 (http) with context path '/'
2025-05-14T13:11:26.335+05:30 INFO 11440 --- [main] c.c.o.OrderserviceApplication : Started OrderserviceApplication in 0.618 seconds (process running)
```

ProductService




```
2025-05-14T13:11:28.522+05:30 INFO 11442 --- [main] c.c.p.ProductserviceApplication : Starting ProductserviceApplication using Java 17.0.12 with
2025-05-14T13:11:28.523+05:30 INFO 11442 --- [main] c.c.p.ProductserviceApplication : No active profile set, falling back to 1 default profile: "
2025-05-14T13:11:28.816+05:30 INFO 11442 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8082 (http)
2025-05-14T13:11:28.821+05:30 INFO 11442 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2025-05-14T13:11:28.821+05:30 INFO 11442 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/10.1.40]
2025-05-14T13:11:28.839+05:30 INFO 11442 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicationContext
2025-05-14T13:11:28.840+05:30 INFO 11442 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initialization completed in 297
2025-05-14T13:11:28.964+05:30 INFO 11442 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8082 (http) with context path '/'
2025-05-14T13:11:28.967+05:30 INFO 11442 --- [main] c.c.p.ProductserviceApplication : Started ProductserviceApplication in 0.595 seconds (process
```

Synchronous Asynchronous

Synchronous Communication :

- ## Synchronous Communication Types in SpringBoot



User-Agent: curl/8.7.1

Which client/tool is used to make the request

Accept: application/json ↘

Format in which client want response

Sample HTTP POST Request call:

POST /products HTTP/1.1

Host: localhost:8081

User-Agent: curl/8.7.1

Accept: application/json

Content-Type: application/json

→ Tell server that, request body is JSON

Content-Length: 65

→ Tells the number of bytes in the request body

{

 "name": "Ice-Cream",

→ Actual data, a new product object

 "price": 200

}

Sample HTTP GET Response call, with keep alive:

The diagram illustrates the components of an HTTP response. It shows a sequence of lines representing the response headers and body. Annotations with arrows point to specific parts of the response:


- HTTP/1.1 200 OK**: An arrow points to this line with the text "2xx : request is successful".
- Date: Fri, 16 May 2025 10:00:00 GMT**: No annotation.
- Content-Type: application/json**: An arrow points to this line with the text "Tells client to expect JSON response".
- Content-Length: 65**: An arrow points to this line with the text "No of bytes in response body".
- Connection: keep-alive**: No annotation.
- Keep-alive: timeout=5, max=50**: No annotation.
- { "id": 10, "name": "SJ" }**: An arrow points to this JSON body with the text "Response body".

A blue line with an arrow at the bottom indicates the flow of the response from the headers to the body.


```
HTTP/1.1 200 OK
Date: Fri, 16 May 2025 10:00:00 GMT
Content-Type: application/json
Content-Length: 65
Connection: keep-alive
Keep-alive: timeout=5, max=50
{
  "id": 10,
  "name": "SJ"
}
```


- By default, **connection** is set to **keep-alive** in HTTP/1.1
- In HTTP/1.0 by-default **connection** is set to **close**.
- Keep-alive:
 - timeout=5, tells close the TCP connection if its idle for 5 seconds
 - Max=50, tells the maximum number of requests can be send over same TCP connection.
- When **Connection: close** is set, it tells after every response from the server, TCP connection is closed, its not reused.

Flow, when keep-alive is set:



Flow, when connection: close is set:





Let's first see, without using above SpringBoot communication types, what it takes to invoke the REST endpoint just using plain **JAVA**.

OrderService

```
@RestController
@RequestMapping("/orders")
public class OrderController {
```

ProductService

```
@RestController
@RequestMapping("/products")
public class ProductController {
```

```
@GetMapping("/{id}")
public ResponseEntity<String> getOrder(@PathVariable String id) {

    HttpURLConnection httpURLConnection = null;
    try {
        String url = "http://localhost:8082/products/" + id;

        URL obj = new URL(url);
        httpURLConnection = (HttpURLConnection) obj.openConnection();

        // Setting http request method and header
        httpURLConnection.setRequestMethod("GET");
        httpURLConnection.setRequestProperty("Accept", "application/json");

        //max time to establish TCP connection, timeout in millisecond
        httpURLConnection.setConnectTimeout(100);
        //max time to wait for server response after connection is established, timeout in millisecond
        httpURLConnection.setReadTimeout(500);

        // Opens the TCP connection trigger the http request and Read response
        BufferedReader in = new BufferedReader(new InputStreamReader(httpURLConnection.getInputStream()));
        StringBuilder response = new StringBuilder();
        String responseLine;
        while ((responseLine = in.readLine()) != null) {
            response.append(responseLine);
        }
        in.close();
        System.out.println("Response: " + response.toString());

    } catch (Exception e) {
        //exception handling here
    } finally {
        if (httpURLConnection != null) {
            httpURLConnection.disconnect();
        }
    }
    return ResponseEntity.ok( body: "order call successful");
}
```

Creates an Object of HttpURLConnection, consider it like an envelop or request, in which we specify all the details like URL, Request Method, timeouts etc.

Here it opens up a TCP connection and send the HTTP request, also reads the response.

TCP connection is created, when we make the first Input/Output request on HttpURLConnection such as:

- `getInputStream()`
- `getResponseCode()`
- `connect()` etc....

HttpClient object is a wrapper around TCP connection, so before creating new HttpClient object, if first checks with "KeepAliveCache" class, if there is already an object present, if not it creates one object and also puts into the cache.

key -> host:port
value -> httpClient object

If Response is fully read properly, the TCP Connection i.e. HttpClient is returned back to KeepAlive cache else TCP connection get closed.

```
public void disconnect() {
    if (input Stream Not Fully Read) {
        httpClient.closeServer(); // Close TCP socket
    } else {
        httpClient.finished(); // Return to KeepAlive Cache
    }
}
```

```
@GetMapping("/{id}")
public String getProduct(@PathVariable String id) {
    return "Product fetched with id: " + id;
}
```

GET

localhost:8081/orders/1

Params

Authorization

Headers (6)

Body

Scripts

Settings

Query Params

	Key	Value
	Key	Value

Body

Cookies

Headers (5)

Test Results

1 order call successful

```

2025-05-15T17:22:49.440+05:30 INFO 14790 --- [main] c.c.o.OrderserviceApplication : Starting OrderserviceApplication using
2025-05-15T17:22:49.441+05:30 INFO 14790 --- [main] c.c.o.OrderserviceApplication : No active profile set, falling back to
2025-05-15T17:22:49.760+05:30 INFO 14790 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8081 (http
2025-05-15T17:22:49.765+05:30 INFO 14790 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2025-05-15T17:22:49.765+05:30 INFO 14790 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat
2025-05-15T17:22:49.780+05:30 INFO 14790 --- [main] o.a.c.c.Ç.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplica
2025-05-15T17:22:49.781+05:30 INFO 14790 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initializat
2025-05-15T17:22:49.902+05:30 INFO 14790 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8081 (http) with
2025-05-15T17:22:49.906+05:30 INFO 14790 --- [main] c.c.o.OrderserviceApplication : Started OrderserviceApplication in 0.61
2025-05-15T17:22:52.341+05:30 INFO 14790 --- [nio-8081-exec-3] o.a.c.c.Ç.[Tomcat].[localhost].[/] : Initializing Spring DispatcherServlet '
2025-05-15T17:22:52.341+05:30 INFO 14790 --- [nio-8081-exec-3] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet
2025-05-15T17:22:52.341+05:30 INFO 14790 --- [nio-8081-exec-3] o.s.web.servlet.DispatcherServlet : Completed initialization in 0 ms
Response: Product fetched with id: 1

```

Couple of **Disadvantage** of above approach is:

- Too much Boilerplate code:
 - Open connection
 - Setting headers
 - Reading response
 - Closing streams and connections.
- Response should be handled manually.
 - No automatic mapping to some Objects.
- Limited support for Advance features like
 - Connection pooling
 - Interceptors etc.

RestTemplate

- . Abstract low level code like creating HttpURLConnection object etc.
- . Traditional/Legacy way to call REST APIs in Spring application.

OrderService

```
@Configuration
public class AppConfig {

    @Bean
    public RestTemplate restTemplate() {
        return new RestTemplate();
    }
}
```

ProductService

```
@RestController
@RequestMapping("/products")
public class ProductController {

    @GetMapping("/{id}")
    public String getProduct(@PathVariable String id) {
        return "Product fetched with id: " + id;
    }
}
```

Or, use below, if we want to set timeouts too

```
@Configuration
public class AppConfig {

    @Bean
    public RestTemplate restTemplate() {

        SimpleClientHttpRequestFactory factory = new SimpleClientHttpRequestFactory();

        // Set the timeouts in milliseconds
        factory.setConnectTimeout(1000); // 1 sec for connection timeout
        factory.setReadTimeout(5000);    // 5 sec for response timeout

        return new RestTemplate();
    }
}
```

```
@RestController
@RequestMapping("/orders")
public class OrderController {

    @Autowired
    RestTemplate restTemplate;

    @GetMapping("/{id}")
    public ResponseEntity<String> getOrder(@PathVariable String id) {

        //invoke product API
        String response = restTemplate.getForObject( url: "http://localhost:8082/products/"+id, String.class);
        System.out.println("Response from Product APi called from order service: " + response);

        return ResponseEntity.ok( body: "order call successful");
    }
}
```

GET

localhost:8081/orders/1

Params

Authorization

Headers (6)

Body

Scripts

Settings

Query Params

	Key	Value
	Key	Value

Body

Cookies

Headers (5)

Test Results

Raw

Preview

Visualize

1

order call successful

```
2025-05-14T14:43:48.260+05:30 INFO 12346 --- [main] c.c.o.OrderserviceApplication : Starting OrderserviceApplication using Ja
2025-05-14T14:43:48.261+05:30 INFO 12346 --- [main] c.c.o.OrderserviceApplication : No active profile set, falling back to 1
2025-05-14T14:43:48.584+05:30 INFO 12346 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat initialized with port 8081 (http)
2025-05-14T14:43:48.589+05:30 INFO 12346 --- [main] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2025-05-14T14:43:48.589+05:30 INFO 12346 --- [main] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/1
2025-05-14T14:43:48.604+05:30 INFO 12346 --- [main] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring embedded WebApplicati
2025-05-14T14:43:48.605+05:30 INFO 12346 --- [main] w.s.c.ServletWebServerApplicationContext : Root WebApplicationContext: initializati
```

```

2025-05-14T14:43:48.729+05:30 INFO 12346 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8081 (http) with d
2025-05-14T14:43:48.734+05:30 INFO 12346 --- [main] c.c.o.OrderserviceApplication : Started OrderserviceApplication in 0.62 s
2025-05-14T14:43:51.223+05:30 INFO 12346 --- [nio-8081-exec-1] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring DispatcherServlet 'di
2025-05-14T14:43:51.223+05:30 INFO 12346 --- [nio-8081-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2025-05-14T14:43:51.224+05:30 INFO 12346 --- [nio-8081-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 1 ms
Response from Product API called from order service: Product fetched with id: 1


```


So, what exactly happened, RestTemplate works internally:

When below method "*getForObject*" invoked:

```
String response = restTemplate.getForObject("http://localhost:8082/products/"+id, String.class);
```

RestTemplate





Notice one thing that:

- RestTemplate do not close the TCP connection explicitly.
- Once Response stream is closed, TCP connection (i.e. HttpClient object, is ready to be re-used till is not expired based on idle Timeout or max Connection configuration)

Lets see, some of the other methods which are available in RestTemplate

Method Name	Description
GET	
getForObject(String url, Class<T> responseType)	Returns the response body as an Object. String url = " http://localhost:8080/api/products/1 "; Product product = restTemplate.getForObject(url, Product.class);
getForEntity(String url, Class<T> responseType)	Returns full ResponseEntity with status and header String url = " http://localhost:8080/api/products/1 "; ResponseEntity<Product> response = restTemplate.getForEntity(url, Product.class); HttpStatus status = response.getStatusCode(); Product product = response.getBody();
POST	
postForObject(String url, Object request, Class<T> responseType)	Sends POST and get just the response body. String url = " http://localhost:8080/api/products "; Product newProduct = new Product("Ice-cream", 100); Product createdProduct = restTemplate.postForObject(url, newProduct, Product.class);
postForEntity(String url, Object request, Class<T> responseType)	Sends POST and get just the full ResponseEntity object. String url = " http://localhost:8080/api/products "; Product newProduct = new Product("Ice-cream", 100); ResponseEntity<Product> response = restTemplate.postForEntity(url, newProduct, Product.class); Product createdProduct = response.getBody(); HttpStatus status = response.getStatusCode();
PUT	
put(String url, Object request)	Sends PUT and no response body is expected. String url = " http://localhost:8080/api/products/1 "; Product updatedProduct = new Product("Ice-cream", 150);

	<pre>restTemplate.put(url, updatedProduct);</pre>
DELETE	
delete(String url)	<p>Sends DELETE request and no response body is expected.</p> <p>String url = "http://localhost:8080/api/products/1"; restTemplate.delete(url);</p>
GENERAL PURPOSE	
exchange(String url, HttpMethod method, HttpEntity<?> requestEntity, Class<T> responseType)	<p>When we want to customize :</p> <ul style="list-style-type: none">• HTTP method (GET, PUT, POST etc.)• HTTP header and body (HttpEntity)• But want Spring automatic Conversion <p>String url = "http://localhost:8080/api/products/";</p> <p>//customizing header HttpHeaders headers = new HttpHeaders(); headers.setContentType(MediaType.APPLICATION_JSON)headers.set("Authoriz ation", "Bearer my-token");</p> <p>//preparing http request body Product product = new Product(); product.setName("Ice-cream"); product.setPrice(100);</p> <p>//setting both header and body in the HttpEntity HttpEntity<Product > requestEntity = new HttpEntity<>(product, headers);</p> <p>ResponseEntity<Product> response = restTemplate.exchange(url, HttpMethod.POST, requestEntity, Product.class);</p> <p>Product product = response.getBody(); HttpStatus status = response.getStatusCode();</p>
execute(String url, HttpMethod method, RequestCallback requestCallback, ResponseExtractor<T> responseExtractor)	<p>When we want full control like in plain java we use HttpURLConnection object. Header, body, Request, Response, serialization etc. need to be handled manually.</p> <p>RequestCallback interface, gives us full control over the request. We can set header, write body etc.</p> <p>@FunctionalInterface public interface RequestCallback { void doWithRequest(ClientHttpRequest request) throws IOException; }</p> <p>Similarly, ResponseExtractor, gives us full control over, how the response is read and converted to desired object.</p>

```

@FunctionalInterface
public interface ResponseExtractor<T> {
    T extractData(ClientHttpResponse response) throws IOException;
}

RestTemplate restTemplate = new RestTemplate();

String url = "http://localhost:8080/api/products";

//setting both header and body
RequestCallback requestCallback = request -> {
    request.getHeaders().setContentType(MediaType.APPLICATION_JSON);
    Product product = new Product("Ice-cream", 100);
    ObjectMapper mapper = new ObjectMapper();
    byte[] body = mapper.writeValueAsBytes(product);
    StreamUtils.copy(body, request.getBody());
};

//parsing the response
ResponseExtractor<String> responseExtractor = response -> {
    return StreamUtils.copyToString(response.getBody(), StandardCharsets.UTF_8);
};

String response = restTemplate.execute(
    url,
    HttpMethod.POST,
    requestCallback,
    responseExtractor
);

System.out.println("response is: " + response);

```

Limitation of RestTemplate:

- In RestTemplate, there are already so many overloaded methods, so its hard to remember and maintain.(Above we have just covered few)
- RestTemplate was build before concepts like Retry, circuit breaker etc.. So adding support means more overloaded methods and not user friendly.

- RestTemplate is in Maintenance mode - means no new feature, only bug fixes.

That's where latest **RestClient** comes into the picture:

- Introduction of Fluent, builder-style API (more readable and user friendly way of configuring and invoking the endpoint)
- RestClient supports easy integration with interceptors, filters etc.