



ConTeXt

přikazy

CS

ConTeXt

příkazy

cs / český
14. října 2016

<code>\AfterPar {...}</code> * BEFEHL
<code>\Alphabeticnumerals {...}</code> * NUMMER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abjadnaivenumerals {...}</code> * NUMMER
<code>\abjadnodotnumerals {...}</code> * NUMMER
<code>\abjadnumerals {...}</code> * NUMMER
<code>\activatespacehandler {...}</code> * zap vyp ano fixne
<code>\acute {...}</code> * CHARACTER
<code>\adaptcollector [...]¹ [...,...²...,...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 NAME 2 inherits: \setupcollector
<code>\adaptfontfeature [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \definefontfeature
<code>\adaptpapersize [...]¹,... [...]²,...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 inherits: \nastavvelikostpapiru 2 inherits: \nastavvelikostpapiru
<code>\addfeature [...]</code> * NAME
<code>\addfeature {...}</code> * NAME
<code>\addtocommalist {...}¹ \...²</code> 1 TEXT 2 CSNAME

<p><code>\addtoJSreamble {...} {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\addvalue {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\aftersplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring ... \at ... \to ...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aktualnicislonaDPisu</code></p>
<p><code>\aktualnidatum [...;...]</code></p> <p style="text-align: center;">OPT</p> <p>* rok mesic den vsedniden y yy Y m mm M d dd D w W mezera _ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT znacka day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...;...] {...}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...;...] \^... {...}</code></p> <p>1 vlevo nastred vpravo vrsek spodek radek l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\alignedline {...} {...} {...}</code></p> <p>1 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana</p> <p>2 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana</p> <p>3 CONTENT</p>
<p><code>\alignmentcharacter</code></p>
<p><code>\allinputpaths</code></p>
<p><code>\alphabeticnumerals {...}</code></p> <p>* NUMMER</p>

`\alwayscitation [...1...2...] [...]`
OPT

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx

2 REFERENCE
```

`\alwayscitation [...1] [...2]`
OPT

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear

2 REFERENCE
```

`\alwayscitation [...1...2...] [...2...1...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx

2 KEY = VALUE
```

`\alwayscite [...1...2...] [...2...1...]`
OPT

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx

2 REFERENCE
```

`\alwayscite [...1] [...2]`
OPT

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear

2 REFERENCE
```

`\alwayscite [...1...2...] [...2...1...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
               authornum authoryear
  pred       = BEFEHL
  po         = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  inherits: \setupbtx

2 KEY = VALUE
```

`\ampersand`

`\anchor [...1] [...2...3...] [...3...2...] {...4}`
OPT OPT

```
1 NAME

2 inherits: \setuplayer

3 inherits: \setuplayerinherits: \nastavoramovani

4 CONTENT
```

<code>\antikva</code>
<code>\appendetoks ¹ \to ²...</code> 1 BEFEHL 2 CSNAME
<code>\appendgvalue {¹..} {²..}</code> 1 NAME 2 BEFEHL
<code>\appendtocommalist {¹..} ²...</code> 1 TEXT 2 CSNAME
<code>\appendtoks ¹ \to ²...</code> 1 BEFEHL 2 CSNAME
<code>\appendtoksonce ¹ \to ²...</code> 1 BEFEHL 2 CSNAME
<code>\appendvalue {¹..} {²..}</code> 1 NAME 2 BEFEHL
<code>\apply {¹..} {²..}</code> 1 CONTENT 2 CONTENT
<code>\applyalternativestyle {[*]..}</code> * NAME
<code>\applyprocessor {¹..} {²..}</code> 1 NAME 2 CONTENT
<code>\applytofirstcharacter ¹..²..}</code> 1 CSNAME 2 TEXT
<code>\applytocharacters ¹..²..}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringchar ¹..²..}</code> 1 CSNAME 2 TEXT

<code>\applytosplitstringcharspaced \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringline \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringlinespaced \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringword \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringwordspaced \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\applytowords \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\arabicdecimals {[*]...}</code> * NUMMER
<code>\arabicexnumerals {[*]...}</code> * NUMMER
<code>\arabicnumerals {[*]...}</code> * NUMMER
<code>\arg {[*]...}</code> * CONTENT
<code>\asciistr {[*]...}</code> * CONTENT
<code>\aside [_{OPT}¹...] {²...}</code> 1 SPRACHE 2 CONTENT

`\assignalfadimension {...} \^2... {...} {...} {...}`

1 male stredni velke zadny DIMENSION
2 CSNAME
3 DIMENSION
4 DIMENSION
5 DIMENSION

`\assigndimen \^1... {...}`

1 CSNAME
2 DIMENSION

`\assigndimension {...} \^2... {...} {...} {...}`

1 [-+]male [-+]stredni [-+]velke zadny DIMENSION
2 CSNAME
3 DIMENSION
4 DIMENSION
5 DIMENSION

`\assignifempty \^1... {...}`

1 CSNAME
2 BEFEHL

`\assigntranslation [...,\^1...,...] \to \^2...`

1 SPRACHE = TEXT
2 CSNAME

`\assignvalue {...} \^2... {...} {...} {...}`

1 male stredni velke TEXT
2 CSNAME
3 BEFEHL
4 BEFEHL
5 BEFEHL

`\assignwidth {...} \^2... {...} {...}`

1 prizpusobive siroky DIMENSION
2 CSNAME
3 TEXT
4 DIMENSION

`\assumelongusagecs \^1... {...}`

1 CSNAME
2 CONTENT

`\astype {...}`

* CONTENT

$\backslash\text{atleftmargin}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 odkaz = REFERENCE inherits: \setupmargindata 2 CONTENT
$\backslash\text{atrightmargin}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 odkaz = REFERENCE inherits: \setupmargindata 2 CONTENT
$\backslash\text{attachment}$ [$\overset{1}{\dots}$] [\dots , \dots , $\overset{2}{=}\dots$, \dots] <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupattachment
$\backslash\text{ATTACHMENT}$ [$\overset{1}{\dots}$] [\dots , \dots , $\overset{2}{=}\dots$, \dots] <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupattachment instances: attachment
$\backslash\text{autocap}$ $\{\dots\}$ * TEXT
$\backslash\text{autodirhbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{autodirvbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{autodirvtop}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{automathematics}$ $\{\dots\}$ * CONTENT
$\backslash\text{autosetups}$ $\{\dots, \dots\}$ * NAME
$\backslash\text{autostarttext}$ \dots $\backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$

<p><code>\BeforePar {...}</code></p> <p>* BEFEHL</p>
<p><code>\Big ...</code></p> <p>* CHARACTER</p>
<p><code>\Bigg ...</code></p> <p>* CHARACTER</p>
<p><code>\Biggl ...</code></p> <p>* CHARACTER</p>
<p><code>\Biggm ...</code></p> <p>* CHARACTER</p>
<p><code>\Biggr ...</code></p> <p>* CHARACTER</p>
<p><code>\Bigl ...</code></p> <p>* CHARACTER</p>
<p><code>\Bigm ...</code></p> <p>* CHARACTER</p>
<p><code>\Bigr ...</code></p> <p>* CHARACTER</p>
<p><code>\backgroundimage {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 BEFEHL</p>
<p><code>\backgroundimagefill {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 BEFEHL</p>
<p><code>\backgroundline [...] {...}</code></p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\bar {...}</code></p> <p>* CHARACTER</p>
<p><code>\barevnaalista [...*,...]</code></p> <p>* COLOR</p>

`\barva [1...] {2...}`

1 COLOR
2 CONTENT

`\BAR {...}`

* CONTENT

instances: nadtrzeno podtrzeno preskrtnuto understrike nadtrzeni podtrzeni preskrtnuti
understrikes underrandom underrandoms underdash underdashes underdot underdots nobar
hiddenbar

`\basegrid [...,*...,...]`
OPT

* nx = NUMMER
ny = NUMMER
dx = NUMMER
dy = NUMMER
faktor = NUMMER
meritko = NUMMER
xkrok = NUMMER
ykrok = NUMMER
offset = DIMENSION
xoffset = DIMENSION
yoffset = DIMENSION
zarovnnani = nastred
jednotka = cm mm in pc pt bp
pismo = STYLE BEFEHL
barva = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

* CONTENT

`\baselinemiddlebox {...}`

* CONTENT

`\baselinerrightbox {...}`

* CONTENT

`\bbox {...}`

* CONTENT

`\beforesplitstring 1... \at 2... \to 3...`

1 TEXT
2 TEXT
3 CSNAME

`\beforetestandsplitstring 1... \at 2... \to 3...`

1 TEXT
2 TEXT
3 CSNAME

`\beginBLOCK [...,*...] ... \endBLOCK`
OPT

* + -

<code>\beginhbox ... \endhbox</code>
<code>\beginofshapebox ... \endofshapebox</code>
<code>\beginvbox ... \endvbox</code>
<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bezserifu</code>
<code>\bigbodyfont</code>
<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER
<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\binom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\bitmapimage [...,\overset{1}{...}] {\overset{2}{...}}</code> 1 barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER 2 NUMMER

<code>\blap {...}</code> * CONTENT
<code>\bleed [...,\u00b1,...] {...}</code> <small>OPT</small> 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockquote [...]\u00b1] {...}</code> <small>OPT</small> 1 SPRACHE 2 CONTENT
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue {...}</code> * NAME
<code>\bottombox {...}</code> * CONTENT
<code>\bottomleftbox {...}</code> * CONTENT
<code>\bottomrightbox {...}</code> * CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...}\u00b1] {...}</code> 1 NAME 2 NUMMER
<code>\boxofsize \u00b1... \u00b1... \u00b1... \u00b1... \u00b1...]</code> <small>OPT</small> 1 CSNAME 2 DIMENSION 3 CONTENT
<code>\boxreference [...,\u00b1,...] \u00b1... \u00b1...]</code> 1 REFERENCE 2 CSNAME 3 CONTENT

<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breve {...}</code> * CHARACTER
<code>\bTABLE [...,..[*]...,...] ... \eTABLE</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEbody [...,..[*]...,...] ... \eTABLEbody</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEfoot [...,..[*]...,...] ... \eTABLEfoot</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEhead [...,..[*]...,...] ... \eTABLEhead</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTABLEnext [...,..[*]...,...] ... \eTABLEnext</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTC [...,..[*]...,...] ... \eTC</code> <small>OPT</small> * inherits: \bTD
<code>\bTD [...,..[*]...,...] ... \eTD</code> <small>OPT</small> * nx = NUMBER * ny = NUMBER * nc = NUMBER * nr = NUMBER * n = NUMBER * m = NUMBER * akce = REFERENCE * inherits: \setupTABLE
<code>\bTDs [...] ... \eTDs</code> * NAME
<code>\bTH [...,..[*]...,...] ... \eTH</code> <small>OPT</small> * inherits: \bTD
<code>\bTN [...,..[*]...,...] ... \eTN</code> <small>OPT</small> * inherits: \bTD
<code>\bTR [...,..[*]...,...] ... \eTR</code> <small>OPT</small> * inherits: \setupTABLE
<code>\bTRs [...] ... \eTRs</code> * NAME

<p><code>\bTX [...,..[*]...,...] ... \eTX</code> <small>OPT</small></p> <p>* inherits: \bTD</p>
<p><code>\bTY [...,..[*]...,...] ... \eTY</code> <small>OPT</small></p> <p>* inherits: \setupTABLE</p>
<p><code>\bthiddencitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\btxabbreviatedjournal {...}</code></p> <p>* NAME</p>
<p><code>\btxaddjournal [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\btxalwayscitation [...,..¹...,...] [...²]</code> <small>OPT</small></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\btxalwayscitation [...¹] [...²]</code> <small>OPT</small></p> <p>1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\btxalwayscitation [...,..¹...,...] [...,..²...,...]</code></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 KEY = VALUE</p>
<p><code>\btxauthorfield {...}</code></p> <p>* initials firstnames vons surnames juniors</p>
<p><code>\btxdetail {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>
<p><code>\btxdirect {...}</code></p> <p>* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME</p>

\btxdoif {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE

\btxdoifcombiinlistelse {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdoifelse {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifelsecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

- 1 vzdy dvoustranny
- 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdoifnot {...} {...}

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE

`\btxdfsameaspreviouselse {...} {...} {...}`

- 1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 2 TRUE
- 3 FALSE

`\btxdfsameaspreviouscheckedelse {...} {...} {...} {...}`

- 1 vzdy dvoustranny
- 2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
- 3 TRUE
- 4 FALSE

`\btxdfuservariableelse {...} {...} {...}`

- 1 KEY
- 2 TRUE
- 3 FALSE

`\btfxexpandedjournal {...}`

- * NAME

`\btxfielf {...}`

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

`\btxfielfname {...}`

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

`\btxfielftype {...}`

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

`\btxfirstofrange {...}`

- * volume pages

`\btxfielflush {...}`

- * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

`\btxfielflushauthor [...]OPT {...}`

- 1 num normalni normalshort inverted invertedshort
- 2 autor editor

`\btxfielflushauthorinverted {...}`

- * autor editor

\btxflushauthorinvertedshort {...} * autor editor
\btxflushauthorname {...} * autor editor
\btxflushauthornormal {...} * autor editor
\btxflushauthornormalshort {...} * autor editor
\btxflushsuffix
\btxfoundname {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxfoundtype {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\btxhybridcite [... ¹ ... ² ...] [...] <div style="text-align: center;">OPT</div> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
\btxhybridcite [... ¹ ...] [... ²] <div style="text-align: center;">OPT</div> 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE
\btxhybridcite {...} * REFERENCE
\btxhybridcite [... ¹ ... ² ...] [... ² ... ² ...] <div style="text-align: center;">OPT</div> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE
\btxlabellanguage

`\btxlabeltext {...}`

* KEY

`\btxlistcitation [...,\overset{1}{=}{...}] [\overset{2}{...}]`
OPT

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx

2 REFERENCE

`\btxlistcitation [\overset{1}{...}] [\overset{2}{...}]`
OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

`\btxlistcitation [...,\overset{1}{=}{...}] [...,\overset{2}{=}{...}]`

1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx

2 KEY = VALUE

`\btxloadjournalist [...]`

* FILE

`\btxoneorange {\overset{1}{...}} {\overset{2}{...}} {\overset{3}{...}}`

1 volume pages

2 TRUE

3 FALSE

`\btxremapauthor [\overset{1}{...}] [\overset{2}{...}]`

1 TEXT

2 TEXT

`\btxsavejournalist [...]`

* FILE

`\btxsetup {...}`

* NAME

`\btxsingularorplural {\overset{1}{...}} {\overset{2}{...}} {\overset{3}{...}}`

1 editor producer director

2 TRUE

3 FALSE

`\btxsingularplural {...} {...} {...}`

- 1 editor producer director
- 2 TRUE
- 3 FALSE

`\btxttextcitation [...1...OPT...] [...2]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\btxttextcitation [...1] [...2]`
_{OPT}

- 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\btxttextcitation [...1...OPT...] [...2...OPT...]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

`\bublinkovanapoveda [...1...OPT...] {...2} {...3}`

- 1 inherits: \setuptooltip
- 2 TEXT
- 3 TEXT

`\bublinkovanapoveda [...1] {...2} {...3}`
_{OPT}

- 1 vlevo nastred vpravo
- 2 TEXT
- 3 TEXT

`\TOOLTIP [...1...OPT...] {...2} {...3}`
_{OPT}

- 1 inherits: \setuptooltip
- 2 TEXT
- 3 TEXT

`instances: tooltip`

`\TOOLTIP [...1] {...2} {...3}`
_{OPT}

- 1 vlevo nastred vpravo
- 2 TEXT
- 3 TEXT

`instances: tooltip`

$\backslash\text{buildmathaccent}$ $\{.^1.\}\{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextaccent}$ $\{.^1.\}\{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextbottomcomma}$ $\{.^*.\}$ * CHARACTER
$\backslash\text{buildtextbottomdot}$ $\{.^*.\}$ * CHARACTER
$\backslash\text{buildtextcedilla}$ $\{.^*.\}$ * CHARACTER
$\backslash\text{buildtextgrave}$ $\{.^*.\}$ * CHARACTER
$\backslash\text{buildtextmacron}$ $\{.^*.\}$ * CHARACTER
$\backslash\text{buildtextognek}$ $\{.^*.\}$ * CHARACTER
$\backslash\text{Caps}$ $\{.^*.\}$ * TEXT
$\backslash\text{Cisla}$ $\{.^*.\}$ * NUMBER
$\backslash\text{CONTEXT}$
$\backslash\text{ConTeXt}$
$\backslash\text{Context}$
$\backslash\text{ConvertConstantAfter}$ $\backslash.^1.\{.^2.\}\{.^3.\}$ 1 CSNAME 2 TEXT 3 TEXT
$\backslash\text{ConvertToConstant}$ $\backslash.^1.\{.^2.\}\{.^3.\}$ 1 CSNAME 2 TEXT 3 TEXT

$\backslash\text{camel}\{...\}$ * TEXT
$\backslash\text{cast}\left[...^{1},...^{2}\right]\{...\}$ <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{catcodetablename}$
$\backslash\text{cbox}\left...^{1}\{...\}^{2}\right.$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeraligned}\{...\}$ * CONTENT
$\backslash\text{centerbox}\left...^{1}\{...\}^{2}\right.$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeredbox}\left...^{1}\{...\}^{2}\right.$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeredlastline}$
$\backslash\text{centerednextbox}\left...^{1}\{...\}^{2}\right.$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centerline}\{...\}$ * CONTENT
$\backslash\text{cernalinka}\left[...^{*}=...^{*},...\right]$ <small>OPT</small> * inherits: \nastavcernelinky
$\backslash\text{cernelinky}\left[...^{*}=...^{*},...\right]$ <small>OPT</small> * inherits: \nastavcernelinky
$\backslash\text{cfrac}\left[\left...^{1}\right]\left\{...\right\}^{2}\left\{...\right\}^{3}\right.$ <small>OPT</small> 1 l c r ll lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT
$\backslash\text{cisla}\{...\}$ * NUMMER

<p><code>\cislomadpisu [...]¹ [...]²</code> <small>OPT</small></p> <p>1 ABSCHNITT</p> <p>2 predchozi aktualni dalsi prvni posledni</p>
<p><code>\cislorovnice [...][*] [...]</code> <small>OPT</small></p> <p>* REFERENCE</p>
<p><code>\cislostrany</code></p>
<p><code>\citace [...]¹ {...}²</code> <small>OPT</small></p> <p>1 SPRACHE</p> <p>2 CONTENT</p>
<p><code>\citation [...]¹ [...]²</code> <small>OPT</small></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\citation [...]¹ [...]²</code> <small>OPT</small></p> <p>1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\citation {...}</code></p> <p>* REFERENCE</p>
<p><code>\citation [...]¹ [...]²</code> <small>OPT</small></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 KEY = VALUE</p>
<p><code>\cite [...]¹ [...]²</code> <small>OPT</small></p> <p>1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\cite [...]¹ [...]²</code> <small>OPT</small></p> <p>1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>

* REFERENCE

```

1      odkaz      = REFERENCE
      alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                  authornum authoryear
      pred        = BEFEHL
      po          = BEFEHL
      vlevo       = BEFEHL
      vpravo      = BEFEHL
      inherits: \setupbtx
2  KEY = VALUE

```

1	SPRACHE
2	CONTENT

* CONTENT

1	NAME
2	FONT

* BEFEHL

* BEFEHL

* FILE

* FILE

1	TEXT
2	TEXT

* CONTENT

```

1 inherits: \setupcollector
2 pismeno = STYLE BEFEHL
  barva = COLOR
  inherits: \nastavoramovani
3 TEXT
4 CONTENT

```

<code>\collectexpanded {...}</code> * CONTENT
<code>\colorcomponents {...}</code> * COLOR
<code>\colored [...¹...²...] {...}</code> 1 inherits: \definujbarvu 2 CONTENT
<code>\colored [...¹] {...²}</code> 1 COLOR 2 CONTENT
<code>\coloronly [...¹] {...²}</code> 1 COLOR 2 CONTENT
<code>\columnbreak [...[*]...]</code> <div style="text-align: center;"><small>OPT</small></div> * ano ne nastaveni lokalne sila prvni posledni NUMMER NAME
<code>\combinepages [...¹] [...²...²...]</code> <div style="text-align: center;"><small>OPT</small></div> 1 FILE 2 alternativa = a b c horizontalne vertikalne n = NUMMER nx = NUMMER ny = NUMMER start = NUMMER stop = NUMMER vzdalenost = DIMENSION vrsek = BEFEHL spodek = BEFEHL vlevo = BEFEHL vpravo = BEFEHL pred = BEFEHL po = BEFEHL mezi = BEFEHL ramecek = zap vyp pozadi = popredi barevne NAME barvapozadi = COLOR
<code>\commalistelement</code>
<code>\commalistsentence [...¹...] [...²...]</code> <div style="text-align: center;"><small>OPT</small></div> 1 TEXT 2 TEXT
<code>\commalistsize</code>
<code>\comparedimension {...¹} {...²}</code> 1 DIMENSION 2 DIMENSION

1 DIMENSION

2 DIMENSION

```
1  NAME
2  inherits: \setupbtxrendering
```

```
* inherits: \nastavseznam

instances: obsah
```

```
* inherits: \nastavseznam
```

```
* inherits: \nastavrejstrik
```

```
1  LISTE
2  inherits: \nastavseznam
```

```
* inherits: \nastavsynonyma
```

```
* inherits: \nastavseznam
```

```
* inherits: \nastavseznam
```

```
* inherits: \nastavseznam
```

```
* inherits: \nastavseznam
```

```
* inherits: \nastavseznam
```

```
* inherits: \nastavtrideni
```

```
1 NAME
2 inherits: \setupbtxrendering
```

$\backslash\text{completelistofsorts} [\dots] [\dots, \dots, \dots]$ OPT 1 SINGULAR 2 inherits: \nastavtrideni
$\backslash\text{completelistofSORTS} [\dots, \dots, \dots]$ OPT * inherits: \nastavtrideni instances: loga
$\backslash\text{completelistofsynonyms} [\dots] [\dots, \dots, \dots]$ OPT 1 SINGULAR 2 inherits: \nastavsynonyma
$\backslash\text{completelistofSYNONYMS} [\dots, \dots, \dots]$ OPT * inherits: \nastavsynonyma instances: zkratky
$\backslash\text{completelistoftables} [\dots, \dots, \dots]$ OPT * inherits: \nastavseznam
$\backslash\text{completepagenumber}$
$\backslash\text{completeregister} [\dots] [\dots, \dots, \dots]$ OPT 1 NAME 2 inherits: \nastavrejstrik
$\backslash\text{uplnyREJSTRIK} [\dots, \dots, \dots]$ OPT * inherits: \nastavrejstrik instances: rejstrik
$\backslash\text{complexorsimple} \backslash\dots$ * CSNAME
$\backslash\text{complexorsimpleempty} \backslash\dots$ * CSNAME
$\backslash\text{complexorsimpleempty} \{\dots\}$ * TEXT CSNAME
$\backslash\text{complexorsimple} \{\dots\}$ * TEXT CSNAME
$\backslash\text{composedcollector} \{\dots\}$ * NAME
$\backslash\text{composedlayer} \{\dots\}$ * NAME

<code>\compresult</code>
<code>\constantdimen *..</code> <code>* CSNAME</code>
<code>\constantdimenargument *..</code> <code>* CSNAME</code>
<code>\constantemptyargument *..</code> <code>* CSNAME</code>
<code>\constantnumber *..</code> <code>* CSNAME</code>
<code>\constantnumberargument *..</code> <code>* CSNAME</code>
<code>\contentreference [...¹,...] [...²,...²...] {...³}</code> <small>OPT</small> <code>1 REFERENCE</code> <code>2 inherits: \nastavoramovani</code> <code>3 CONTENT</code>
<code>\continuednumber {...}</code> <code>* NUMMER</code>
<code>\continueifinputfile {...}</code> <code>* FILE</code>
<code>\convertargument ... \to ...²</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\convertcommand *... \to ...²</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\convertedcounter [...¹] [...²,...²,...]</code> <small>OPT</small> <code>1 NAME</code> <code>2 inherits: \setupcounter</code>
<code>\converteddimen {...¹} {...²}</code> <code>1 DIMENSION</code> <code>2 ex em pt in cm mm sp bp pc dd cc nc</code>
<code>\convertedsubcounter [...¹] [...²] [...³,...³,...]</code> <small>OPT</small> <small>OPT</small> <code>1 NAME</code> <code>2 NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse</code> <code>3 inherits: \setupcounter</code>

$\backslash\text{convertmonth} \{...\}$ * NUMMER
$\backslash\text{convertvalue} \overset{1}{...} \backslash\text{to} \overset{2}{...}$ 1 NAME 2 CSNAME
$\backslash\text{convertvboxtohbox}$
$\backslash\text{copybtxlabeltext} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyheadtext} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copylabeltext} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyPOPISEKtext} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY instances: hlavicka popisek mathlabel taglabel jednotka operator prefix suffix btxlabel
$\backslash\text{copymathlabeltext} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyoperatorortext} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copypages} [\overset{1}{...}] [\dots,\dots,\overset{2}{...},\dots] [\dots,\dots,\overset{3}{...},\dots]$ <small>OPT</small> <small>OPT</small> 1 FILE 2 znaceni = zap vyp offset = DIMENSION n = NUMMER 3 inherits: \setupexternalfigure
$\backslash\text{copyparameters} [\overset{1}{...}] [\overset{2}{...}] [\dots,\overset{3}{...}]$ 1 TEXT 2 TEXT 3 KEY

$\backslash\text{copyposition} \{...\} \{...\}$ 1 NAME 2 NAME
$\backslash\text{copprefixtext} \overset{1}{[...]} \overset{2}{[...,...,...]}$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copytaglabeltext} \overset{1}{[...]} \overset{2}{[...,...,...]}$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyunittext} \overset{1}{[...]} \overset{2}{[...,...,...]}$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{countersubs} \overset{1}{[...]} \overset{2}{[...]}$ <small>OPT</small> 1 NAME 2 NUMMER
$\backslash\text{counttoken} \overset{1}{...} \backslash\text{in} \overset{2}{...} \backslash\text{to} \overset{3}{...}$ 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens} \overset{1}{...} \backslash\text{to} \overset{2}{...}$ 1 TEXT 2 CSNAME
$\backslash\text{cramped} \{...\}$ * CONTENT
$\backslash\text{crampedclap} \{...\}$ * CONTENT
$\backslash\text{crapedllap} \{...\}$ * CONTENT
$\backslash\text{crapedrlap} \{...\}$ * CONTENT
$\backslash\text{crightarrow} \overset{1}{...} \overset{2}{...}$ <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT

$\crightharpoonoverleftarrow{}$ $\{\dots\}$ $\{\dots\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\ctop $\overset{1}{}$ $\{\dots\}$ <small>OPT</small> 1 TEXT 2 CONTENT
\ctxcommand $\{...\}$ * BEFEHL
\ctxdirectcommand $\{...\}$ * BEFEHL
\ctxdirectlua $\{...\}$ * BEFEHL
\ctxfunction $\{...\}$ * NAME
\CTXFUNCTIONDEFINITION
\CTXFUNCTION
\ctxlatecommand $\{...\}$ * BEFEHL
\ctxlatelua $\{...\}$ * BEFEHL
\ctxloadluafile $\{...\}$ * FILE
\ctxlua $\{...\}$ * BEFEHL
\ctxluabuffer $[\dots]$ <small>OPT</small> * BUFFER
\ctxluacode $\{...\}$ * BEFEHL
\ctxreport $\{...\}$ * BEFEHL
\ctxsprint $\{...\}$ * BEFEHL

<code>\currentassignmentlistkey</code>
<code>\currentassignmentlistvalue</code>
<code>\currentbtxuservariable {...}</code> * KEY
<code>\currentcommalistitem</code>
<code>\currentcomponent</code>
<code>\currentenvironment</code>
<code>\currentfeaturetest</code>
<code>\currentinterface</code>
<code>\currentPOPISEK [...¹...]²{...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> <small>OPT</small> </div> 1 REFERENCE 2 TEXT
<code>\currentlanguage</code>
<code>\currentlistentrydestinationattribute</code>
<code>\currentlistentrylimitedtext {...}</code> * TEXT
<code>\currentlistentrynumber</code>
<code>\currentlistentrypagenumber</code>
<code>\currentlistentryreferenceattribute {...}</code> * cislo text cislostranky vse
<code>\currentlistentrytitle</code>
<code>\currentlistentrytitlerendered</code>
<code>\currentlistsymbol</code>
<code>\currentmainlanguage</code>
<code>\currentmessagetext</code>
<code>\currentmoduleparameter {...}</code> * KEY
<code>\currentoutputstream</code>

<code>\currentproduct</code>
<code>\currentproject</code>
<code>\currentregime</code>
<code>\currentregisterpageuserdata {...}</code> * KEY
<code>\currentresponses</code>
<code>\currenttime [...*,...]</code> <small>OPT</small> * h m TEXT
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\d {...}</code> * CHARACTER
<code>\dalsipodstranka</code>
<code>\datasetvariable {...¹} {...²} {...³}</code> 1 NAME 2 NAME NUMMER 3 KEY realpage
<code>\datum [...*,...¹*,...]</code> <code>[...*,...²*,...]</code> <small>OPT</small> <small>OPT</small> 1 d = NUMMER m = NUMMER y = NUMMER 2 inherits: \aktualnidatum
<code>\dayoftheweek {...¹} {...²} {...³}</code> 1 NUMMER 2 NUMMER 3 NUMMER
<code>\dayspermonth {...¹} {...²}</code> 1 NUMMER 2 NUMMER
<code>\dbinom {...¹} {...²}</code> 1 CONTENT 2 CONTENT

<code>\ddot {...}</code> * CHARACTER
<code>\decrement \...</code> * CSNAME
<code>\decrementcounter [...]¹ [...]²</code> <div> <div>1 NAME</div> <div>2 NUMMER</div> <div>OPT</div> </div>
<code>\decrementedcounter [...]</code> * NAME
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code> * NAME
<code>\decrement cd:parentheses-1</code> * CSNAME NUMBER
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \... \... {...}</code> <div> <div>1 CSNAME</div> <div>2 CHARACTER NUMBER</div> <div>3 BEFEHL</div> </div>
<code>\defconvertedargument \... {...}</code> <div> <div>1 CSNAME</div> <div>2 TEXT</div> </div>
<code>\defconvertedcommand \... \...</code> <div> <div>1 CSNAME</div> <div>2 CSNAME</div> </div>
<code>\defconvertedvalue \... {...}</code> <div> <div>1 CSNAME</div> <div>2 NAME</div> </div>

`\defineactivecharacter 1... {2...}`

- 1 CHARACTER
- 2 BEFEHL

`\definealternativestyle [...,1...] [2...] [3...]`

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

`\defineanchor [1...] [2...] [...,3...,...] [...,4...,...]
OPT OPT`

- 1 NAME
- 2 NAME
- 3 inherits: \setupplayer
- 4 inherits: \setupplayerinherits: \nastavoramovani

`\defineattachment [1...] [2...] [...,3...,...]
OPT OPT`

- 1 NAME
- 2 NAME
- 3 inherits: \setupattachment

`\defineattribute [1...] [...,2...,...]
OPT`

- 1 NAME
- 2 lokalne globalne public private

`\definebackground [1...] [2...] [...,3...,...]
OPT OPT`

- 1 NAME
- 2 NAME
- 3 inherits: \nastavpozadi

`\definebar [1...] [2...] [...,3...,...]
OPT OPT`

- 1 NAME
- 2 NAME
- 3 inherits: \setupbar

`\definebodyfontswitch [1...] [...,2...,...]`

- 1 NAME
- 2 inherits: \nastavzakladnifont

`\definebreakpoint [1...] [2...] [...,3...,...]
OPT`

- 1 NAME
- 2 CHARACTER
- 3 typ = 1 2 3 4 5
nvlevo = NUMMER
nvpravo = NUMMER
vlevo = BEFEHL
stredni = BEFEHL
vpravo = BEFEHL
range = ano ne
language = SPRACHE

<pre> \definebreakpoints [...] * NAME </pre>
<pre> \definebtx [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtx </pre>
<pre> \definebtxdataset [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxdataset </pre>
<pre> \definebtxregister [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxregister </pre>
<pre> \definebtxrendering [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxrendering </pre>
<pre> \definebutton [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbutton </pre>
<pre> \definecapitals [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \nastavkapitalky </pre>
<pre> \definecollector [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupcollector </pre>
<pre> \definecolumnbreak [...] [...] 1 NAME 2 ano ne nastaveni lokalne sila prvni posledni NUMMER </pre>
<pre> \definecombination [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupcombination </pre>

```
\definecomment [...] [...] [...]
1 NAME
2 NAME
3 inherits: \nastavkomentar
```

```
\definecomplexorsimple \*...
* CSNAME
```

```
\definecomplexorsimpleempty \*...
* CSNAME
```

```
\definecomplexorsimpleempty {...}
* TEXT CSNAME
```

```
\definecomplexorsimple {...}
* TEXT CSNAME
```

```
\defineconversionset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\definecounter [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupcounter
```

```
\definedataset [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdataset
```

```
\definedelimitedtext [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupdelimitedtext
```

```
\definedfont [...]
* FONT
```

```
\defineeffect [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupeffect
```

`\defineexpandable` [¹...] \²... {³...}
OPT

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

`\defineexternalfigure` [¹...] [²...] [³...³...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupexternalfigure

`\definefallbackfamily` [¹...] [²...] [³...] [⁴...⁴...]
OPT

- 1 NAME
- 2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
- 3 FONT
- 4
 - rscale = NUMMER
 - designsize = implicitni auto
 - goodies = FILE
 - range = NUMMER NAME
 - offset = NUMMER NAME
 - check = ano ne
 - sila = ano ne
 - features = NAME
 - tf = TEXT
 - bf = TEXT
 - it = TEXT
 - sl = TEXT
 - bi = TEXT
 - bs = TEXT
 - sc = TEXT

`\definefallbackfamily` [¹...] [²...] [³...] [⁴...⁴...]
OPT

- 1 NAME
- 2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
- 3 FONT
- 4 NAME

`\definefieldbody` [¹...] [²...] [³...³...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldbody

`\definefieldbodyset` [¹...] [²...]
2

- 1 NAME
- 2 NAME

`\definefieldcategory` [¹...] [²...] [³...³...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldcategory

`\definefileconstant {1...} {2...}`

1 NAME

2 NAME

`\definefilefallback [1...] [2...,...]`

1 NAME

2 FILE

`\definefilesynonym [1...] [2...]`

1 NAME

2 FILE

`\definefiller [1...] [2...] [3...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupfiller

`\definefirstline [1...] [2...] [3...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupfirstline

`\definefittingpage [1...] [2...] [3...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupfittingpage

`\definefontalternative [...]`

* NAME

`\definefontfallback [1...] [2...] [3...,...]4 [4...,...4...,...]`
OPT

1 NAME

2 FONT NAME

3 NAME NUMMER

4 rscale = NUMMER
sila = ano ne
check = ano ne
offset = NUMMER NAME

```
\definefontfamily [...]1 [...]2 [...]3 [...]4OPT,...]
```

1 NAME

2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika

3 FONT

4 rscale = NUMBER
designsize = implicitni auto
goodies = FILE
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT

```
\definefontfamilypreset [...]1 [...]2,...]
```

1 NAME

2 inherits: \definefontfamily

```
\definefontfamilypreset [...]1 [...]2
```

1 NAME

2 NAME

```
\definefontfamily [...]1 [...]2 [...]3 [...]4OPT,...]
```

1 NAME

2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika

3 FONT

4 NAME

`\definefontfeature [...]1 [...]2 [...,...3...,...]`

OPT

1 NAME

2 NAME

3 language = NAME
script = NAME auto
mode = node base auto zadny
liga = ano ne
kern = ano ne
extrakerns = ano ne
tlig = ano ne
trep = ano ne
missing = ano ne
dummies = ano ne
analyze = ano ne
unicoding = ano ne
expanden = NAME
protrusion = NAME
nostackmath = ano ne
realdimensions = ano ne
itlc = ano ne
textitalics = ano ne
mathitalics = ano ne
slant = NUMMER
extend = NUMMER
dimensions = NUMMER
boundingbox = ano ne
compose = ano ne
char-ligatures = ano ne
compat-ligatures = ano ne
goodies = FILE
extrafeatures = ano ne
featureset = NAME
colorscheme = NAME
postprocessor = NAME
mathdimensions = NAME
keepligatures = ano ne auto
devanagari = ano ne
features = ano ne
tcom = ano ne
anum = ano ne
mathsize = ano ne
decomposehangul = ano ne
mathalternatives = ano ne
mathgaps = ano ne
checkmarks = ano ne
NAME = ano ne
mathnolimitsmode = NUMMER

`\definefontfile [...]1 [...]2 [...,...3...,...]`

OPT

1 NAME

2 FILE

3 features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicitni

`\definefontsize [...]`

* NAME

`\definefontsolution [...]1 [...]2 [...,...3...,...]`

OPT

OPT

1 NAME

2 NAME

3 inherits: \setupfontsolution

`\defineformula` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformula

`\defineformulaalternative` [¹...] [²...] [³...]

- 1 NAME
- 2 CSNAME
- 3 CSNAME

`\defineformulaframed` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformulaframed

`\defineframedcontent` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupframedcontent

`\definefrozenfont` [¹...] [²...]

- 1 NAME
- 2 FONT

`\defineglobalcolor` [¹...] [²...₂...]

- 1 NAME
- 2 inherits: \definujbarvu

`\defineglobalcolor` [¹...] [²...]

- 1 NAME
- 2 COLOR

`\definegraphictypesynonym` [¹...] [²...]

- 1 NAME
- 2 NAME

`\definegridsnapping` [¹...] [²...,...]

- 1 NAME
- 2 lokalne globalne noheight nodepth box max min zadny radek pulradku prvni posledni minvyska maxheight mindepth maxdepth vrsek spodek strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER

`\defineheadalternative` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupheadalternative

`\definehelp [...]1 [...]2 [...,...3...,...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphelp

`\definehigh [...]1 [...]2 [...,...3...,...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphigh

`\definehighlight [...]1 [...]2 [...,...3...,...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphighlight

`\definehspace [...]1 [...]2 [...]3`
 OPT

- 1 NAME
- 2 NAME
- 3 DIMENSION

`\definehyphenationfeatures [...]1 [...,...2...,...]`

- 1 NAME
- 2 characters = TEXT
hyphens = ano vse TEXT
joiners = ano vse TEXT
rightwords = NUMMER
hyphenmin = NUMMER
lefthyphenmin = NUMMER
righthyphenmin = NUMMER
lefthyphenchar = NUMMER
righthyphenchar = NUMMER
alternativa = original tex hyphenate expanded traditional zadny
pravahrana = tex
rightchars = slovo NUMMER

`\definecharacterkerning [...]1 [...]2 [...,...3...,...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupcharacterkerning

`\definecharacterspacing [...]*`

- * NAME

`\definechemical [...]1 {...}2`

- 1 NAME
- 2 CONTENT

`\definechemicals [...]1 [...]2 [...,...3...,...]`
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupchemical

`\definechemicalsymbol [...]1 [...]2`

1 NAME

2 TEXT

`\defineindentedtext [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupindentedtext

`\defineindenting [...]1 [...,2,...]`

1 NAME

2 [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION

`\defineinitial [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupinitial

`\defineinsertion [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupinsertion

`\defineinteraction [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavinterakci

`\defineinteractionbar [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavinterakcnilistu

`\defineinterfaceconstant {...}1 {...}2`

1 NAME

2 NAME

`\defineinterfaceelement {...}1 {...}2`

1 NAME

2 NAME

`\defineinterfacevariable {...}1 {...}2`

1 NAME

2 NAME

`\defineinterlinespace` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavmeziradkovoumezeru

`\defineintermediatecolor` [¹...] [²..._{OPT}...] [³..._{OPT}...]

- 1 NAME
- 2 COLOR NUMMER
- 3 a = NUMMER
t = NUMMER

`\defineitemgroup` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupitemgroup

`\defineitems` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavpolozky

`\definelabelclass` [¹...] [²..._{OPT}]

- 1 NAME
- 2 NUMMER

`\definelayer` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer

`\definelayerpreset` [¹...] [²..._{OPT}...]

- 1 NAME
- 2 inherits: \setuplayer

`\definelayerpreset` [¹...] [²...]

- 1 NAME
- 2 NAME

`\definelayout` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \nastavvzhled

`\definelinefiller` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinefiller

`\defineline1note [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplinenote

`\definelinenum1bering [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavcislovaniradku

`\definelines [...]1 [...]2 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavradky

`\definelist1alternative [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplistalternative

`\definelist1extra [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplistextra

`\definelow [...]1 [...]2 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplow

`\definelow1high [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplowhigh

`\definelow1midhigh [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuplowmidhigh

`\defineMP1instance [...]2 [...]3 [...,...,3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupMPinstance

`\definemarginblock` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmarginblock

`\definemargindata` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmargindata

`\definemarkers` [...]

- * NAME

`\definemathaccent` ...¹ ...²

- 1 NAME
- 2 CHARACTER

`\definemathalignment` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathalignment

`\definemathcases` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathcases

`\definemathcommand` [¹...] [²...] [³...] {⁴..._{OPT}..._{OPT}..._{OPT}}

- 1 NAME
- 2 ord op bin rel open close punct alpha uvnitr nothing limop noloop box
- 3 jedna dve
- 4 BEFEHL \...##1 \...##1##2

`\definemathdoubleextensible` [¹...] [²...] [³...] [⁴..._{OPT}...]

- 1 obe vfenced
- 2 NAME
- 3 NUMMER
- 4 NUMMER

`\definemathtics` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathtics

```
\definemathextensible [1...] [2...] [3...]
                        OPT
1  reverse matematika text chemistry
2  NAME
3  NUMMER
```

```
\definemathfence [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathfence
```

```
\definemathfraction [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathfraction
```

```
\definemathframed [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathframed
```

```
\definemathmatrix [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathmatrix
```

```
\definemathornament [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathornament
```

```
\definemathoverextensible [1...] [2...] [3...]
                        OPT
1  vrsek vfenced
2  NAME
3  NUMMER
```

```
\definemathovertextextensible [1...] [2...] [3...]
                        OPT
1  bothtext
2  NAME
3  NUMMER
```

```
\definemathradical [1...] [2...] [3...,...3...,...]
                        OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathradical
```

```
\definemathstackers [...]1 [...]2 [...,...]3...,...]  

                                OPT      OPT  

1  NAME  

2  NAME  

3  inherits: \setupmathstackers
```

```
\definemathstyle [...]1 [...]2,...]  

1  NAME  

2  obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
```

```
\definemathtriplet [...]1 [...]2 [...]3  

                                OPT      OPT  

1  NAME  

2  NAME  

3  TEXT
```

```
\definemathunderextensible [...]1 [...]2 [...]3  

                                OPT  

1  spodek vfenced  

2  NAME  

3  NUMMER
```

```
\definemathundertextextensible [...]1 [...]2 [...]3  

                                OPT  

1  bothtext  

2  NAME  

3  NUMMER
```

```
\definemathunstacked [...]1 [...]2 [...]3  

                                OPT  

1  siroce  

2  NAME  

3  NUMMER
```

```
\definemeasure [...]1 [...]2  

1  NAME  

2  DIMENSION
```

```
\definemessageconstant {...}  

*  NAME
```

```
\definemixedcolumns [...]1 [...]2 [...,...]3...,...]  

                                OPT      OPT  

1  NAME  

2  NAME  

3  inherits: \setupmixedcolumns
```

```
\definemode [...]1,...]2 [...]3  

                                OPT  

1  NAME  

2  ano ne drzet
```

```

\definemultitonecolor [...]1 [...]2 [...]3 [...]4
                                     OPT
1  NAME
2  COLOR = NUMMER
3  inherits: \definujbarvu
4  inherits: \definespotcolor

```

```

\definenamecolor [...]1 [...]2
1  NAME
2  inherits: \definujbarvu

```

```

\definenamecolor [...]1 [...]2
1  NAME
2  COLOR

```

```

\definamespace [...]1 [...]2
1  NAME
2  jmeno = TEXT
   parent = TEXT
   pismo = ano ne
   prikaz = ano ne seznam
   setup  = ano ne seznam
   set     = ano ne seznam
   ramecek = ano ne

```

```

\definennarrower [...]1 [...]2 [...]3
                  OPT      OPT
1  NAME
2  NAME
3  inherits: \nastavzuzeni

```

```

\definernote [...]1 [...]2 [...]3
              OPT      OPT
1  NAME
2  NAME
3  inherits: \setupnote

```

```

\defineornament [...]1 [...]2 [...]3
                  OPT
1  NAME
2  alternativa = a b
   inherits: \setupcollector
3  pismo = STYLE BEFEHL
   barva = COLOR
   inherits: \nastavoramovani

```

```

\defineornament [...]1 [...]2 [...]3
                  OPT
1  NAME
2  alternativa = a b
   inherits: \setuplayer
3  inherits: \setuplayeredtext

```

```

\defineoutputroutine [...]1 [...]2 [...]3
                      OPT      OPT
1  NAME
2  NAME
3  inherits: \setupoutputroutine

```

<pre>\defineoutputroutinecommand [...,*,...]</pre> <p>* KEY</p>
<pre>\definepage [...¹] [...²]</pre> <p>1 NAME</p> <p>2 REFERENCE</p>
<pre>\definepagebreak [...¹] [...,²,...]</pre> <p>1 NAME</p> <p>2 prazdne zahlavi upati dummy ramecek NUMMER +NUMMER implicitni reset zablockovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop</p>
<pre>\definepagegrid [...¹] [...²]_{OPT} [...,³,...]_{OPT}</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagegrid</p>
<pre>\definepagegridarea [...¹] [...²]_{OPT} [...,³,...]_{OPT}</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagegridarea</p>
<pre>\definepagegridspan [...¹] [...²]_{OPT} [...,³,...]_{OPT}</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagegridspan</p>
<pre>\definepagechecker [...¹] [...²]_{OPT} [...,³,...]_{OPT}</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppagechecker</p>
<pre>\definepageinjection [...¹] [...²]_{OPT} [...,³,...]_{OPT}</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppageinjection</p>
<pre>\definepageinjectionalternative [...¹] [...²]_{OPT} [...,³,...]_{OPT}</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setuppageinjectionalternative</p>
<pre>\definepageshift [...¹] [...²]_{OPT} [...,³,...]</pre> <p>1 NAME</p> <p>2 horizontalne vertikalne</p> <p>3 DIMENSION</p>

```

\definepagestate [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setuppagestate

```

```

\definepairedbox [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setuppairedbox

```

```

\defineparagraph [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupparagraph

```

```

\defineparallel [...] [...]
1 NAME
2 NAME

```

```

\defineparbuilder [...]
* NAME

```

```

\defineplacement [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupplacement

```

```

\definepositioning [...] [...] [...]
1 NAME
2 NAME
3 inherits: \nastavumistovani

```

```

\defineprefixset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME
2 ABSCHNITT
3 ABSCHNITT

```

```

\defineprocesscolor [...] [...] [...]
1 NAME
2 COLOR
3 inherits: \definujbarvu

```

```

\defineprocessor [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupprocessor

```

`\definepushbutton [1...] [2...OPT...]`

- 1 NAME
- 2 inherits: \setupfieldcontentframed

`\definepushsymbol [1...] [2...]`

- 1 NAME
- 2 n r d

`\definerenderingwindow [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setuprenderingwindow

`\defineresetset [1...] [2...OPT...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 NUMMER
- 3 NUMMER

`\definescale [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscale

`\definescript [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupscript

`\definesectionlevels [1...] [2...]`

- 1 NAME
- 2 ABSCHNITT

`\defineselector [1...] [2...OPT...]`

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [1...] [2...OPT...] [3...]`

- 1 NAME SECTIONBLOCK:NAME
- 2 BEFEHL PROCESSOR->BEFEHL
- 3 BEFEHL PROCESSOR->BEFEHL

`\defineshift [1...] [2...OPT] [3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

`\definesidebar [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupsidebar

`\definesort [...]1 [...]2 [...]3 {...}4`
OPT

- 1 ano ne
- 2 SINGULAR
- 3 NAME
- 4 CONTENT

`\definespotcolor [...]1 [...]2 [...,...3...,...]`

- 1 NAME
- 2 COLOR
- 3 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference
exclusion hue saturation barevne luminosity
- t = NUMMER
- e = TEXT
- p = NUMMER

`\definestyleinstance [...]1 [...]2 [...]3 [...]4`
OPT OPT

- 1 NAME
- 2 rm ss tt mm hw cg
- 3 tf bf it sl bi bs sc
- 4 BEFEHL

`\definesubformula [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupsubformula

`\definesynonym [...]1 [...]2 [...]3 {...}4 {...}5`
OPT

- 1 ano ne
- 2 SINGULAR
- 3 NAME
- 4 TEXT
- 5 CONTENT

`\definesystemattribute [...]1 [...]2,...]`
OPT

- 1 NAME
- 2 lokalne globalne public private

`\definesystemconstant {...}*`

- * NAME

`\definesystemvariable {...}*`

- * NAME

<pre> \defineTABLEsetup [...] [...] 1 NAME 2 inherits: \setupTABLE </pre>
<pre> \definetabulation [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NAME </pre>
<pre> \definetwopasslist {...} * NAME </pre>
<pre> \definetype [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavtype </pre>

```

\definetypesface [...] [...] [...] [...] [...] [...] [...] [...] [...]
1 OPT 2 OPT 3 4 5 6
1 NAME
2 rm ss tt mm hw cg
3 serif sans mono math handwriting calligraphy
4 NAME
5 implicitni dtp
6 rscale = auto NUMMER
  features = NAME
  fallbacks = NAME
  goodies = NAME
  designsize = auto implicitni
  smer = obe

```

```

\definetypescriptprefix [...] [...]
1 NAME
2 TEXT

```

```

\definetypescriptsynonym [...] [...]
1 NAME
2 TEXT

```

```

\definetypesetting [...] [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 TEXT
3 inherits: \setuexternalfigure

```

```

\defineunit [...] [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 NAME
3 inherits: \setupunit

```

```

\defineviewerlayer [...] [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 NAME
3 inherits: \setupviewerlayer

```

```

\definevspace [...] [...] [...]
1 OPT 2 3
1 NAME
2 NAME
3 DIMENSION

```

```

\definevspacing [...] [...]
1 NAME
2 inherits: \vspacing

```

```

\definevspacingamount [...] [...] [...]
1 OPT 2 OPT 3
1 NAME
2 DIMENSION
3 DIMENSION

```

```
\definetable [1...] [2...] [3...OPT...OPT]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

```
\definuj [1...] \2... {3...OPT}
```

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

```
\definujakcent 1... 2... 3...
```

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

```
\definujbarvu [1...] [2...OPT...]
```

- 1 NAME
- 2 r = NUMMER
g = NUMMER
b = NUMMER
c = NUMMER
m = NUMMER
y = NUMMER
k = NUMMER
h = NUMMER
s = NUMMER
v = NUMMER
x = NUMMER
a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference
exclusion hue saturation barevne luminosity
t = NUMMER

```
\definujbarvu [1...] [2...]
```

- 1 NAME
- 2 COLOR

```
\definujblok [1...] [2...OPT] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \nastavblok

```
\definujbloksekce [1...] [2...] [3...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \nastavbloksekce

```
\definujbuffer [1...] [2...OPT] [3...OPT...]
```

- 1 NAME
- 2 BUFFER
- 3 inherits: \nastavbuffer

`\definujfont [...]1 [...]2 [...,...3...,...]`
OPT

1 NAME

2 FONT

3 inherits: \nastavmeziradkovoumezeru

`\definujfont [...]1 [...]2 [...]3`
OPT

1 NAME

2 FONT

3 NAME

`\definujformatodkazu [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupreferenceformat

`\definujhbox [...]1 [...]2`

1 NAME

2 DIMENSION

`\definujinterakcnimenu [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavinterakcnimenu

`\definujkombinovanyseznam [...]1 [...,...]2 [...,...3...,...]`
OPT

1 NAME

2 LISTE

3 inherits: \nastavseznam

`\definujkonverzi [...]1 [...]2 [...]3`
OPT

1 SPRACHE

2 NAME

3 CSNAME

`\definujkonverzi [...]1 [...]2 [...,...]3`
OPT

1 SPRACHE

2 NAME

3 TEXT

`\definujnadpis [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 ABSCHNITT

3 inherits: \nastavnadpis

`\definujobrazeksymbol [...]1 [...]2 [...,...3...,...]`
OPT

1 NAME

2 FILE NAME

3 inherits: \externiobraz

`\definujodkaz [...]1 [...]2,...]`

1 NAME

2 REFERENCE

`\definujodstavce [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavodstavce

`\definujopis [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavopis

`\definujoramovani [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \nastavoramovani

`\definujoramovanytext [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupframedtext

`\definujpaletu [...]1 [...,...2...,...]`

1 NAME

2 NAME = COLOR

`\definujpaletu [...]1 [...]2`

1 NAME

2 NAME

`\definujplvouciobjekt [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 SINGULAR

2 PLURAL

3 inherits: \nastavplvouciobjekt

instances: chemical figure table intermezzo graphic

`\definujplvouciobjekt [...]1 [...]2 [...]3`
OPT OPT

- 1 SINGULAR
- 2 PLURAL
- 3 SINGULAR

instances: chemical figure table intermezzo graphic

`\definujpodpole [...]1 [...]2 [...]3, [...]`

- 1 NAME
- 2 NAME
- 3 NAME

`\definujpole [...]1 [...]2 [...]3 [...]4, [...]5`

- 1 NAME
- 2 radio pod text radek push check signature
- 3 NAME
- 4 NAME
- 5 NAME

`\definujpopis [...]1 [...]2 [...]3, [...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupdescription

`\definujpopisek [...]1 [...]2 [...]3, [...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuplabel

`\definujprekryv [...]1, [...]2 [...]3`
OPT

- 1 NAME
- 2 NAME
- 3 BEFEHL

`\definujprikaz ...1 ...2`

- 1 CHARACTER
- 2 BEFEHL

`\definujprofil [...]1 [...]2 [...]3, [...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupprofile

`\definujprogram [...]1 [...]2 [...]3`
OPT

- 1 NAME
- 2 TEXT
- 3 TEXT

`\definujprostredizakladnihofontu` [¹...] [²...] [³...,...³...,...]

OPT

OPT

1 NAME

2 implicitni DIMENSION

3 velky = DIMENSION NUMMER
 male = DIMENSION NUMMER
 a = DIMENSION NUMMER
 b = DIMENSION NUMMER
 c = DIMENSION NUMMER
 d = DIMENSION NUMMER
 text = DIMENSION NUMMER
 x = DIMENSION NUMMER
 xx = DIMENSION NUMMER
 script = DIMENSION NUMMER
 scriptscript = DIMENSION NUMMER
 meziradkovamezera = DIMENSION
 em = sklonene kurziva STYLE BEFEHL
 * = NUMMER

`\definujrejstrik` [¹...] [²...] [³...,...³...,...]

OPT

OPT

1 NAME

2 NAME

3 inherits: \nastavrejstrik

`\definujsablonutabulky` [¹...] [|²...|] [³...] [⁴...]

OPT

OPT

1 NAME

2 TEMPLATE

3 NAME

4 NAME

`\definujsekci` [...]

* NAME

`\definujseznam` [¹...] [²...] [³...,...³...,...]

OPT

OPT

1 NAME

2 LISTE

3 inherits: \nastavseznam

`\definujskupinubarev` [¹...] [²...] [x:y:³z,...]

OPT

1 NAME

2 seda rgb cmyk spot

3 TRIPLET

`\definujstartstop` [¹...] [²...] [³...,...³...,...]

OPT

OPT

1 NAME

2 NAME

3 inherits: \setupstartstop

`\definujstyl` [¹...] [²...] [³...,...³...,...]

OPT

OPT

1 NAME

2 NAME

3 inherits: \setupstyle

`\definujstylfontu [...1,...] [...2]`

1 NAME

2 NAME

`\definujsymbol [...1] [...2] [...3]`
OPT

1 NAME

2 NAME

3 BEFEHL

`\definujsynonumfontu [...1] [...2] [...3OPT,...3,...]`

1 NAME

2 FONT

3 features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicitni

`\definujsynonyma [...1] [...2] [...3OPT] [...4OPT]`

1 SINGULAR

2 PLURAL

3 CSNAME

4 CSNAME

`\definujtabelaci [...1] [...2OPT] [...3OPT /.../]`

1 NAME

2 NAME

3 TEMPLATE

`\definujtext [...1] [...2] [...3OPT] [...4] [...5OPT] [...6OPT] [...7OPT]`

1 NAME

2 vrsek zahlavi text upati spodek

3 text marginalie hrana

4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

6 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

7 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

`\definujtrideni [...1] [...2] [...3OPT]`

1 SINGULAR

2 PLURAL

3 zadny CSNAME

`\definujupravu [...1] [...2OPT] [...3OPT,...3,...]`

1 NAME

2 NAME

3 inherits: \nastavupravu

`\definujvelikostpapiru [.1.] [...,2...]`

```
1  NAME
2  sirka      = DIMENSION
   vyska     = DIMENSION
   vrsek     = BEFEHL
   spodek    = BEFEHL
   vlevo     = BEFEHL
   vpravo    = BEFEHL
   vzdalenost = DIMENSION
   stranka   = inherits: \nastavvelikostpapiru
   papir     = inherits: \nastavvelikostpapiru
```

`\definujvelikostpapiru [.1.] [...,2...] [...,3...]OPT`

```
1  NAME
2  inherits: \nastavvelikostpapiru
3  inherits: \nastavvelikostpapiru
```

`\definujvycet [.1.] [...,2...] [...,3...]OPT`

```
1  NAME
2  NAME
3  inherits: \setupenumeration
```

`\definujzakladnifont [...,1...] [...,2...] [...,3...] [...,4...]OPT`

```
1  NAME implicitni
2  NAME DIMENSION
3  rm ss tt hw cg
4  tf  = FILE
   bf  = FILE
   it  = FILE
   sl  = FILE
   bi  = FILE
   bs  = FILE
   sc  = FILE
   mr  = FILE
   mrlr = FILE
   mrrl = FILE
   mb  = FILE
   mblr = FILE
   mbrl = FILE
```

`\definujzakladnifont [...,1...] [...,2...] [...,3...] [...]OPT`

```
1  NAME implicitni
2  NAME DIMENSION
3  rm ss tt hw cg
4  NAME
```

`\definujzasobnikpoli [.1.] [...,2...] [...,3...]OPT`

```
1  NAME
2  NAME
3  inherits: \setupfieldcategory
```

`\definujznaceni [.1.] [...,2...] [...,3...]OPT`

```
1  NAME
2  BESCHRIFTUNG
3  inherits: \nastavznaceni
```

$\backslash\text{definujznak}$ ¹ ... ² ... 1 CHARACTER 2 NUMMER
$\backslash\text{delimited}$ [¹ ...] [² ...] { ³ ...} <small>OPT</small> 1 NAME 2 SPRACHE 3 CONTENT
$\backslash\text{delimitedtext}$ [¹ ...] [² ...] { ³ ...} <small>OPT</small> 1 NAME 2 SPRACHE 3 CONTENT
$\backslash\text{DELIMITEDTEXT}$ [¹ ...] { ² ...} <small>OPT</small> 1 SPRACHE 2 CONTENT instances: citace citovat blockquote speech aside
$\backslash\text{delkaseznamu}$
$\backslash\text{depthofstring}$ {...} * TEXT
$\backslash\text{depthonlybox}$ {...} * CONTENT
$\backslash\text{depthspanningtext}$ { ¹ ...} { ² ...} { ³ ...} 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{determinenoflines}$ {...} * CONTENT
$\backslash\text{devanagarinumeral}$ s {...} * NUMMER
$\backslash\text{dfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{digits}$ {...} * NUMMER
$\backslash\text{digits}$... * NUMMER

<code>\dimensiontocount {¹...} \²...</code> 1 DIMENSION 2 CSNAME
<code>\directcolor [...]</code> * COLOR
<code>\directcolored [...,...[*]...,...]</code> * inherits: \definujbarvu
<code>\directcolored [...]</code> * COLOR
<code>\directconvertedcounter {¹...} {²...}</code> 1 NAME 2 prvni predchozi dalsi posledni cislo
<code>\directdummyparameter {...}</code> * KEY
<code>\directgetboxllx ...</code> * CSNAME NUMBER
<code>\directgetboxlly ...</code> * CSNAME NUMBER
<code>\directhighlight {¹...} {²...}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...] {...}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * BEFEHL
<code>\directselect {¹...} {²...} {³...} {⁴...} {⁵...} {⁶...}</code> <div style="display: flex; justify-content: space-around; margin-top: -10px;"> OPTOPTOPTOPTOPT </div> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME

$\backslash\text{directsetup}$ {...} * NAME
$\backslash\text{directsymbol}$ {... ¹ } {... ² } 1 NAME 2 NAME
$\backslash\text{directvspacing}$ {...,*...} * inherits: \vspacing
$\backslash\text{dis}$ {...} * CONTENT
$\backslash\text{disabledirectives}$ [...,*...]
* NAME
$\backslash\text{disableexperiments}$ [...,*...]
* NAME
$\backslash\text{disablemode}$ [...,*...]
* NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ [...,*...]
* NAME
$\backslash\text{displaymath}$ {...} * CONTENT
$\backslash\text{displaymathematics}$ {...} * CONTENT
$\backslash\text{displaymessage}$ {...} * TEXT
$\backslash\text{distributedhsize}$ {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 DIMENSION 3 NUMMER

`\dividedsize {...} {...} {...}`

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMMER

`\doadaptleftskip {...}`

- * ano ne standardni DIMENSION

`\doadaptrightskip {...}`

- * ano ne standardni DIMENSION

`\doaddfeature {...}`

- * NAME

`\doassign [...]1 [...]2...`

- 1 TEXT
- 2 KEY = VALUE

`\doassignempty [...]1 [...]2...`

- 1 TEXT
- 2 KEY = VALUE

`\doboundtext {...}1 {...}2 {...}3`

- 1 TEXT
- 2 DIMENSION
- 3 BEFEHL

`\documentvariable {...}`

- * KEY

`\dodoubleargument \1... [...]2 [...]3`

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleargumentwithset \1... [...]2,... [...]3`

- 1 CSNAME
- 2 TEXT
- 3 TEXT

`\dodoubleempty \1... [...]2 [...]3`
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleemptywithset \...¹ [...,²...] [...]³
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoublegroupempty \... {...}² {...}³
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\doeassign [...]¹ [...]²

- 1 TEXT
- 2 KEY = VALUE

\doexpandedrecurse {...}¹ {...}²

- 1 NUMMER
- 2 BEFEHL

\dogetattribute {...}

- * NAME

\dogetattributeid {...}

- * NAME

\dogetcommacommandelement ...¹ \from ...² \to ...³

- 1 NUMMER
- 2 TEXT
- 3 CSNAME

\dogobbledoubleempty [...]¹ [...]²
OPT OPT

- 1 TEXT
- 2 TEXT

\dogobblesingleempty [...]^{*}
OPT

- * TEXT

\docheckassignment {...}

- * TEXT

\docheckedpagestate {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶ {...}⁷

- 1 REFERENCE
- 2 BEFEHL
- 3 BEFEHL
- 4 BEFEHL
- 5 BEFEHL
- 6 BEFEHL
- 7 BEFEHL

`\docheckedpair {...,*...}`

* TEXT

`\doif {...} {...} {...}`

1 CONTENT

2 CONTENT

3 TRUE

`\doifallcommon {...}`

* TRUE

`\doifallcommonelse {...} {...}`

1 TRUE

2 FALSE

`\doifalldefinedelse {...,1...} {...} {...}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodes {...,1...} {...} {...}`

1 NAME

2 TRUE

3 FALSE

`\doifallmodeselse {...,1...} {...} {...}`

1 NAME

2 TRUE

3 FALSE

`\doifassignmentelse {...} {...} {...}`

1 TEXT

2 TRUE

3 FALSE

`\doifblackelse {...} {...} {...}`

1 COLOR

2 TRUE

3 FALSE

`\doifbothsides {...} {...} {...}`

1 BEFEHL

2 BEFEHL

3 BEFEHL

`\doifbothsidesoverruled {...} {...} {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 BEFEHL

`\doifboxelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifbufferelse {...} {...} {...}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifcolor {...} {...}`

- 1 COLOR
- 2 TRUE

`\doifcolorelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifcommandhandler \... {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifcommon {...}`

- * TRUE

`\doifcommonelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifcontent {...} {...} {...} \... {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 BEFEHL
- 4 CSNAME
- 5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifconversionnumberelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifcurrentfonthasfeatureelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefined {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMMER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelse {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE
- 4 FALSE

`\doifelseallcommon {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsealldefined {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseallmodes {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseassignment {...1} {...2} {...3}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseblack {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsebox {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsebuffer {...1} {...2} {...3}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifelsecolor {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsecommandhandler \1... {...2} {...3} {...4}`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsecommon {...1} {...2}`

- 1 TRUE
- 2 FALSE

\doifelseconversiondefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsecounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentsortingingused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymshown {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsedefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedefinedcounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedimension {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsedimenstring {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsedocumentargument {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedocumentfilename {...} {...} {...}

- 1 NUMMER
- 2 TRUE
- 3 FALSE

\doifelsedrawingblack {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseempty {...} {...} {...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifelseemptyvalue {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifelseenv {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\doifelsefastoptionalcheck {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsefastoptionalcheckcs \... \...

- 1 CSNAME
- 2 CSNAME

\doifelsefieldbody {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefieldcategory {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefigure {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefiledefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefileexists {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefirstchar {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseflagged {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefontchar {...} {...} {...} {...}

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsefontpresent {...} {...} {...}

- 1 FONT
- 2 TRUE
- 3 FALSE

\doifelsefontsynonym {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsehasspace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsehelp {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseincsname {...} {...} {...} {...}

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

\doifelseinelement {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinputfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseinsertion {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinset {...} {...} {...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifelseinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseintoks {...} {...} {...} {...}

- 1 BEFEHL
- 2 BEFEHL
- 3 TRUE
- 4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseitalic {...} {...}

- 1 TRUE
- 2 FALSE

\doifelselanguage {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doifelselayerdata {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutdefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutsomeline {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayouttextline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseleapyear {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelselist {...} {...} {...}`

- 1 LISTE
- 2 TRUE
- 3 FALSE

`\doifelselocation {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \... \...1 \...2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \... \...1 \...2...`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextparenthesis {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenonzeropositive {...1} {...2} {...3}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsenoteonsamepage {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenothing {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsenumber {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseobjectfound {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseobjectreferencefound {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoddpage {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\doifelseoddpagefloat {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseoldercontext {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelseolderversion {...} {...} {...} {...}`

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifelseoverlapping {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoverlay {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseparallel {...} {...,2...} {...} {...4}`

- 1 NAME
- 2 NAME vse
- 3 TRUE
- 4 FALSE

`\doifelseparentfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsepath {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifelsepathexists {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifelsepatterns {...} {...} {...}`

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

`\doifelseposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositiononpage {...} {...} {...} {...4}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsepositionsonsamepage {...¹,...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionsonthispage {...¹,...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionsused {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifelserreferencefound {...¹} {...²} {...³}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelserightpagefloat {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifelserighttoleftinbox ...¹ {...²} {...³}

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

\doifelsesamelinereference {...¹} {...²} {...³}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelsesamestring {...¹} {...²} {...³} {...⁴}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsesetups {...¹} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomebackground {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomespace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesomething {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesometoks \... {...} {...}

- 1 CSNAME
- 2 TRUE
- 3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsestructurelisthasnumber {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsestructurelisthaspage {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsesymboldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesymbolset {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetext {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsetextflow {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetextflowcollector {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetypingfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseundefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseurldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsevalue {...} {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsevaluenothing {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsevariable {...} {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

<pre> \doifempty {...} {...} 1 CONTENT 2 TRUE </pre>
<pre> \doifemptyelse {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \doifemptytoks \.^ {...} 1 CSNAME 2 TRUE </pre>
<pre> \doifemptyvalue {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifemptyvalueelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifemptyvariable {...} {...} {...} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifemptyvariableelse {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doifenv {...} {...} 1 KEY 2 TRUE </pre>
<pre> \doifenvelse {...} {...} {...} 1 KEY 2 TRUE 3 FALSE </pre>
<pre> \doiffastoptionalcheckcselse \.^ \.^ 1 CSNAME 2 CSNAME </pre>

`\doiffastoptionalcheckelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiffieldbodyelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffieldcategoryelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffigureelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffile {...} {...}`

- 1 FILE
- 2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifflaggedelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doiffontcharelse {...} {...} {...} {...}

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doiffontpresentelse {...} {...} {...}

- 1 FONT
- 2 TRUE
- 3 FALSE

\doiffontsynonymelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifhasspaceelse {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifhelpelse {...} {...}

- 1 TRUE
- 2 FALSE

\doifincsnameelse {...} {...} {...} {...}

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

\doifinelementelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifinputfileelse {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

```
\doifinsertionelse {...} {...} {...}
```

```
1  NAME  
2  TRUE  
3  FALSE
```

```
\doifinset {...} {...}
```

```
1  CONTENT  
2  TRUE
```

```
\doifinsetelse {...} {...} {...}
```

```
1  CONTENT  
2  TRUE  
3  FALSE
```

```
\doifinstring {...} {...} {...}
```

```
1  TEXT  
2  TEXT  
3  TRUE
```

```
\doifinstringelse {...} {...} {...} {...}
```

```
1  TEXT  
2  TEXT  
3  TRUE  
4  FALSE
```

```
\doifinsymbolset {...} {...} {...} {...}
```

```
1  NAME  
2  NAME  
3  TRUE  
4  FALSE
```

```
\doifinsymbolsetelse {...} {...} {...} {...}
```

```
1  NAME  
2  NAME  
3  TRUE  
4  FALSE
```

```
\doifintokselse {...} {...} {...} {...}
```

```
1  BEFEHL  
2  BEFEHL  
3  TRUE  
4  FALSE
```

`\doifintwopassdataelse {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifitalicelse {...} {...}`

1 TRUE
2 FALSE

`\doiflanguageelse {...} {...} {...}`

1 SPRACHE
2 TRUE
3 FALSE

`\doiflayerdataelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMMER
2 TRUE
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LISTE
2 TRUE
3 FALSE

`\doiflocationelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflocfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifmainfloatbodyelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifmarkingelse {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifmeaningelse \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMMER
- 3 TRUE
- 4 FALSE

`\doifmode {...,1...} {...2}`

- 1 NAME
- 2 TRUE

`\doifmodeelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnextbgroupcselse \1... \2...`

- 1 CSNAME
- 2 CSNAME

<pre> \doifnextbgroupelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifnextcharelse {...} {...} {...} 1 CHARACTER 2 TRUE 3 FALSE </pre>
<pre> \doifnextoptionalcselse \^1... \^2... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextoptionalelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifnextparenthesiselse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifnonzeropositiveelse {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doifnot {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifnotallcommon {...} * TRUE </pre>
<pre> \doifnotallmodes {...,^1...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotcommandhandler \^1... {...} {...} 1 CSNAME 2 NAME 3 TRUE </pre>
<pre> \doifnotcommon {...} * TRUE </pre>

\doifnotcounter {...} {...}

- 1 NAME
- 2 TRUE

\doifnotdocumentargument {...} {...}

- 1 NAME
- 2 TRUE

\doifnotdocumentfilename {...} {...}

- 1 NUMMER
- 2 TRUE

\doifnotempty {...} {...}

- 1 CONTENT
- 2 TRUE

\doifnotemptyvalue {...} {...}

- 1 NAME
- 2 TRUE

\doifnotemptyvariable {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE

\doifnotenv {...} {...}

- 1 KEY
- 2 TRUE

\doifnoteonsamepageelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifnotescollected {...} {...}

- 1 NAME
- 2 TRUE

\doifnotfile {...} {...}

- 1 FILE
- 2 TRUE

\doifnotflagged {...} {...}

- 1 NAME
- 2 TRUE

`\doifnothing {...} {...}`

1 TEXT
2 TRUE

`\doifnothingelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifnotinset {...} {...}`

1 CONTENT
2 TRUE

`\doifnotinfloat {...}`

* TRUE

`\doifnotinstring {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifnotmode {...,1...} {...}`

1 NAME
2 TRUE

`\doifnotnumber {...} {...}`

1 TEXT
2 TRUE

`\doifnotsamestring {...1} {...2} {...3}`

1 TEXT
2 TEXT
3 TRUE

`\doifnotsetups {...} {...}`

1 NAME
2 TRUE

`\doifnotvalue {...} {...} {...}`

1 NAME
2 TEXT
3 TRUE

`\doifnotvariable {...} {...} {...}`

1 NAME
2 KEY
3 TRUE

`\doifnumber {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnumberelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifobjectfoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifobjectreferencefoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoddpagelse {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\doifoddpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifoldercontextelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifolderversionelse {...} {...} {...} {...}`

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifoverlappingelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoverlayelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifparallelelse {...} {...,2...} {...} {...4}`

- 1 NAME
- 2 NAME vse
- 3 TRUE
- 4 FALSE

`\doifparentfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpathelse {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifpathexistselse {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifpatternseelse {...} {...} {...}`

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

`\doifposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionactionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositiononpageelse {...} {...} {...} {...}

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifpositionsonsamepageelse {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionsonthispageelse {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifpositionsusedelse {...} {...}

- 1 TRUE
- 2 FALSE

\doifreferencefoundelse {...} {...} {...}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifrightpagefloatelse {...} {...}

- 1 TRUE
- 2 FALSE

\doifrighttoleftinboxelse ...¹ {...} {...}

- 1 CSNAME NUMMER
- 2 TRUE
- 3 FALSE

\doifsamelinereferenceelse {...} {...} {...}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifsamestringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifsetupself {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackground {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomespaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsomething {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifsomethingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsometoks \... {...}`

- 1 CSNAME
- 2 TRUE

`\doifsometokselsetelse \1... {\2...} {\3...}`

1 CSNAME
2 TRUE
3 FALSE

`\doifstringinstringelse {\1...} {\2...} {\3...} {\4...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifstructurelisthasnumberelse {\1...} {\2...}`

1 TRUE
2 FALSE

`\doifstructurelisthaspageelse {\1...} {\2...}`

1 TRUE
2 FALSE

`\doifsymboldefinedelse {\1...} {\2...} {\3...}`

1 NAME
2 TRUE
3 FALSE

`\doifsymbolsetelse {\1...} {\2...} {\3...}`

1 NAME
2 TRUE
3 FALSE

`\doiftext {\1...} {\2...} {\3...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextelse {\1...} {\2...} {\3...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextflowcollectorelse {\1...} {\2...} {\3...}`

1 NAME
2 TRUE
3 FALSE

`\doiftextflowelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftypingfileelse {1.} {2.} {3.}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifundefined {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifundefinedcounter {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifundefinedelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifurldefinedelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvalue {1.} {2.} {3.}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifvalueelse {1.} {2.} {3.} {4.}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifvaluenothing {1.} {2.}`

- 1 NAME
- 2 TRUE

`\doifvaluenothingelse {1.} {2.} {3.}`

- 1 NAME
- 2 TRUE
- 3 FALSE

<pre>\doifvaluesomething {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifvariable {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 TRUE</pre>
<pre>\doifvariableelse {...} {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 TRUE</pre> <pre>4 FALSE</pre>
<pre>\doindentation</pre>
<pre>\dollar</pre>
<pre>\doloop {...}</pre> <pre>* BEFEHL</pre>
<pre>\doloopoverlist {...,¹...} {...²}</pre> <pre>1 TEXT</pre> <pre>2 BEFEHL</pre>
<pre>\donothing</pre>
<pre>\dontconvertfont</pre>
<pre>\dontleavehmode</pre>
<pre>\dontpermitspacesbetweenegroups</pre>
<pre>\dopositionaction {...}</pre> <pre>* NAME</pre>
<pre>\doprocesslocalsetups {...,*...}</pre> <pre>* NAME</pre>
<pre>\doquadrupleargument \¹... [²...] [³...] [⁴...] [⁵...]</pre> <pre>1 CSNAME</pre> <pre>2 TEXT</pre> <pre>3 TEXT</pre> <pre>4 TEXT</pre> <pre>5 TEXT</pre>

`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`
OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`
OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintuplegroupempty \1... {2...} {3...} {4...} {5...} {6...}`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\dorecurse {1...} {2...}`

- 1 NUMMER
- 2 BEFEHL

`\dorechecknextindentation`

`\dorepeatwithcommand [1...] \2...`

- 1 TEXT NUMMER*TEXT
- 2 CSNAME

<p><code>\doreplacefeature {...}</code></p> <p>* NAME</p>
<p><code>\doresetandafffeature {...}</code></p> <p>* NAME</p>
<p><code>\doresetattribute {...}</code></p> <p>* NAME</p>
<p><code>\dorotatebox {...} \dots {...}</code></p> <p>1 NUMMER</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\dosetattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\dosetleftskipadaption {...}</code></p> <p>* ano ne standardni DIMENSION</p>
<p><code>\dosetrighskipadaption {...}</code></p> <p>* ano ne standardni DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* inherits: \nastavmeziradkovoumezeru</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* zap vyp reset auto male stredni velke NUMMER DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...}</code></p> <p>* NAME</p>
<p><code>\doseventupleargument \dots [..] [..] [..] [..] [..] [..] [..] [..]</code></p> <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p> <p>7 TEXT</p> <p>8 TEXT</p>

\doseventupleempty \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷ ⁸
 OPT OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT
- 8 TEXT

\dosingleargument \... ¹ ²
 OPT

- 1 CSNAME
- 2 TEXT

\dosingleempty \... ¹ ²
 OPT

- 1 CSNAME
- 2 TEXT

\dosinglegroupempty \... ¹ {²...}
 OPT

- 1 CSNAME
- 2 TEXT

\dosixtupleargument \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷
 OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

\dosixtupleempty \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷
 OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

\dostarttagged {¹...} {²...} ... \dostoptagged

- 1 NAME
- 2 NAME

`\dostepwiserecurse {...} {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 [-+]NUMBER
- 4 BEFEHL

`\dosubtractfeature {...}`

- * NAME

`\dotfskip {...}`

- * DIMENSION

`\dotoks \...`

- * CSNAME

`\dotripleargument \... [...] [...] [...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \... [...,2...] [...3] [...4]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \... [...2] [...3] [...4]`
 OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleemptywithset \... [...,2...] [...3] [...4]`
 OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotriplegroupempty \... {...2} {...3} {...4}`
 OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\doublebar {...}`

- * TEXT

<code>\doublebond</code>
<code>\doublebrace {...}</code> * TEXT
<code>\doublebracket {...}</code> * TEXT
<code>\doubleparent {...}</code> * TEXT
<code>\dowith {...¹,...} {...²}</code> 1 BEFEHL 2 BEFEHL
<code>\dowithnextbox {...¹} \... {...³}</code> 1 BEFEHL 2 CSNAME 3 CONTENT
<code>\dowithnextboxcontent {...¹} {...²} \... {...⁴}</code> 1 BEFEHL 2 BEFEHL 3 CSNAME 4 CONTENT
<code>\dowithnextboxcontentcs \...¹ \...² \...³ {...⁴}</code> 1 CSNAME 2 CSNAME 3 CSNAME 4 CONTENT
<code>\dowithnextboxcs \...¹ \...² {...³}</code> 1 CSNAME 2 CSNAME 3 CONTENT
<code>\dowithpargument \...</code> * CSNAME
<code>\dowithrange {...¹,...} \...²</code> 1 NUMMER NUMMER:NUMMER 2 CSNAME
<code>\dowithwargument \...</code> * CSNAME

<code>\dpofstring {...}</code> * TEXT
<code>\dummydigit</code>
<code>\dummyparameter {...}</code> * KEY
<code>\ETEX</code>
<code>\EveryLine {...}</code> * BEFEHL
<code>\EveryPar {...}</code> * BEFEHL
<code>\edefconvertedargument \¹... {\²...}</code> 1 CSNAME 2 TEXT
<code>\efcmaxheight {...}</code> * NAME
<code>\efcmaxwidth {...}</code> * NAME
<code>\efcminheight {...}</code> * NAME
<code>\efcminwidth {...}</code> * NAME
<code>\efcparameter {\¹...} {\²...}</code> 1 NAME 2 KEY
<code>\effect [¹...] {\²...}</code> 1 NAME 2 CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {\¹...} {\²...}</code> _{OPT} _{OPT} 1 TEXT 2 TEXT

$\backslash\mathrm{eleft harpoon down fill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{eleft harpoon up fill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{eleft rightright arrow fill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{emphasis bold face}$
$\backslash\mathrm{emphasis type face}$
$\backslash\mathrm{empty lines}$ $[\overset{*}{\dots}]$ <div>OPT</div> <div> <div>* NUMBER</div> </div>
$\backslash\mathrm{emspace}$
$\backslash\mathrm{enabledirectives}$ $[\dots,*,\dots]$ <div> <div>* NAME</div> </div>
$\backslash\mathrm{enableexperiments}$ $[\dots,*,\dots]$ <div> <div>* NAME</div> </div>
$\backslash\mathrm{enablemode}$ $[\dots,*,\dots]$ <div> <div>* NAME</div> </div>
$\backslash\mathrm{enableoutputstream}$ $[\dots]$ <div> <div>* NAME</div> </div>
$\backslash\mathrm{enableparpositions}$
$\backslash\mathrm{enableregime}$ $[\dots]$ <div> <div> <div>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</div> </div> </div>
$\backslash\mathrm{enabletrackers}$ $[\dots,*,\dots]$ <div> <div>* NAME</div> </div>
$\backslash\mathrm{endnote}$ $[\dots,\overset{1}{\dots}]\{\overset{2}{\dots}\}$ <div>OPT</div> <div> <div>1 REFERENCE</div> <div>2 TEXT</div> </div>

<p><code>\endnote [...,*=...,...]</code></p> <p>* titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE</p>
<p><code>\enskip</code></p>
<p><code>\enspace</code></p>
<p><code>\env {...}</code></p> <p>* KEY</p>
<p><code>\envvar {...} {...}</code></p> <p>1 KEY 2 BEFEHL</p>
<p><code>\eoverbarfill {...} {...}</code> _{OPT} _{OPT}</p> <p>1 TEXT 2 TEXT</p>
<p><code>\eoverbracefill {...} {...}</code> _{OPT} _{OPT}</p> <p>1 TEXT 2 TEXT</p>
<p><code>\eoverbracketfill {...} {...}</code> _{OPT} _{OPT}</p> <p>1 TEXT 2 TEXT</p>
<p><code>\eoverparentfill {...} {...}</code> _{OPT} _{OPT}</p> <p>1 TEXT 2 TEXT</p>
<p><code>\epos {...}</code></p> <p>* NAME</p>
<p><code>\equaldigits {...}</code></p> <p>* TEXT</p>
<p><code>\erightarrowfill {...} {...}</code> _{OPT} _{OPT}</p> <p>1 TEXT 2 TEXT</p>
<p><code>\erightharpoondownfill {...} {...}</code> _{OPT} _{OPT}</p> <p>1 TEXT 2 TEXT</p>

$\backslash\mathrm{erightharpoonupfill}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 TEXT 2 TEXT
$\backslash\mathrm{eTeX}$
$\backslash\mathrm{ethiopic}$
$\backslash\mathrm{etwoheadrightarrowfill}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 TEXT 2 TEXT
$\backslash\mathrm{eunderbarfill}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 TEXT 2 TEXT
$\backslash\mathrm{eunderbracefill}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 TEXT 2 TEXT
$\backslash\mathrm{eunderbracketfill}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 TEXT 2 TEXT
$\backslash\mathrm{eunderparentfill}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 TEXT 2 TEXT
$\backslash\mathrm{executeifdefined}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 NAME 2 BEFEHL
$\backslash\mathrm{exitloop}$
$\backslash\mathrm{exitloopnow}$
$\backslash\mathrm{expanded}\ \overset{*}{\dots}$ * CONTENT
$\backslash\mathrm{expandfontsynonym}\ \overset{1}{\dots}\ \overset{2}{\dots}$ 1 CSNAME 2 NAME
$\backslash\mathrm{expandcheckedcsname}\ \overset{1}{\dots}\ \overset{2}{\dots}\ \overset{3}{\dots}$ 1 CSNAME 2 KEY 3 TEXT

\externalfigurecollectionmaxheight {...} * NAME
\externalfigurecollectionmaxwidth {...} * NAME
\externalfigurecollectionminheight {...} * NAME
\externalfigurecollectionminwidth {...} * NAME
\externalfigurecollectionparameter {...} {...} 1 NAME 2 KEY
\externiobraz [¹ ...] [² ...] [³ ...,... _{OPT} ...,...] 1 FILE 2 NAME 3 inherits: \setupeexternalfigure
\fakebox ... * CSNAME NUMMER
\fastdecrement \... * CSNAME
\fastincrement \... * CSNAME
\fastlocalframed [¹ ...] [..., ² ...,...] ³ {...} 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\fastscale {...} {...} 1 NUMMER 2 CONTENT
\fastsetup {...} * NAME
\fastsetupwithargument {...} {...} 1 NAME 2 CONTENT

<p><code>\fastsetupwithargumentsswapped {...} {...}</code></p> <p>1 CONTENT</p> <p>2 NAME</p>
<p><code>\fastswitchtobodyfont {...}</code></p> <p>* x xx male velke script scriptscript</p>
<p><code>\fastsxsy {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 CONTENT</p>
<p><code>\feature [...] [...]</code></p> <p>1 + - = ! > < more less novy reset implicitni old lokalne</p> <p>2 NAME</p>
<p><code>\feature {...} {...}</code></p> <p>1 + - = ! > < more less novy reset implicitni old lokalne</p> <p>2 NAME</p>
<p><code>\fence</code></p>
<p><code>\fenced [...] [...]</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\FENCE {...}</code></p> <p>* CONTENT</p>
<p><code>\fetchallmarkings [...] [...]</code></p> <p>1 BESCHRIFTUNG</p> <p>2 stranka NAME</p>
<p><code>\fetchallmarks [...] [...]</code></p> <p>* BESCHRIFTUNG</p>
<p><code>\fetchmark [...] [...]</code> <div>OPT</div> </p> <p>1 BESCHRIFTUNG</p> <p>2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\fetchmarking [...] [...] [...]</code></p> <p>1 BESCHRIFTUNG</p> <p>2 stranka NAME</p> <p>3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>

<p><code>\fetchonemark [...]</code> ² <small>OPT</small></p> <p>1 BESCHRIFTUNG</p> <p>2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\fetchonemarking [...]</code> ² ³</p> <p>1 BESCHRIFTUNG</p> <p>2 stranka NAME</p> <p>3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\fetchruntimecommand \...</code> ²</p> <p>1 CSNAME</p> <p>2 FILE</p>
<p><code>\fetchtwomarkings [...]</code> ²</p> <p>1 BESCHRIFTUNG</p> <p>2 stranka NAME</p>
<p><code>\fetchtwomarks [...]</code></p> <p>* BESCHRIFTUNG</p>
<p><code>\fieldbody [...]</code> ² <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupfieldbody</p>
<p><code>\fifthoffivearguments {...}</code> ² ³ ⁴ ⁵</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p>
<p><code>\fifthofsixarguments {...}</code> ² ³ ⁴ ⁵ ⁶</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<p><code>\figurefilename</code></p>
<p><code>\figurefilepath</code></p>
<p><code>\figurefiletype</code></p>
<p><code>\figurefullname</code></p>

<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<code>\figuresymbol [...]¹ [...,...²...,...]</code> <small>OPT</small> 1 FILE NAME 2 inherits: \externiobraz
<code>\figurewidth</code>
<code>\filename {...}</code> * FILE
<code>\filledhboxb ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filledhboxc ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filledhboxg ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filledhboxk ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filledhboxm ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filledhboxr ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filledhboxy ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\filler [...]</code> * sym symbol linka sirka mezera NAME

\filterfromnext {...} {...}

- 1 NUMMER
- 2 NUMMER

\filterfromvalue {...} {...} {...}

- 1 NAME
- 2 NUMMER
- 3 NUMMER

\filterpages [...]¹ [...]²,... [...]³,...³
OPT

- 1 FILE
- 2 sude liche NUMMER NUMMER:NUMMER
- 3 sirka = DIMENSION
n = NUMMER
category = NAME

\filterreference {...}

* implicitni text titul cislo stranka realpage

\findtwopassdata {...} {...}

- 1 NAME
- 2 NAME

\finishregisterentry [...]¹ [...]²,... [...]³,...³
OPT

- 1 NAME
- 2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
alternativa = TEXT
- 3 KEY = VALUE

\firstcounter [...]¹ [...]²
OPT

- 1 NAME
- 2 NUMMER

\firstcountervalue [...]

* NAME

\firstcharacter

\firstoffivearguments {...} {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

<p><code>\firstoffourarguments {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p>
<p><code>\firstofoneargument {...}</code></p> <p>* TEXT</p>
<p><code>\firstofoneunexpanded {...}</code></p> <p>* TEXT</p>
<p><code>\firstofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<p><code>\firstofthreearguments {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\firstofthreeunexpanded {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\firstoftwoarguments {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\firstoftwounexpanded {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\firstrealpage</code></p>
<p><code>\firstrealpagenumber</code></p>
<p><code>\firstsubcountervalue [...] [...]</code></p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\firstsubpagenumber</code></p>

<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
$\text{\fitfieldframed } [\dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ <p>1 inherits: \nastavoramovani</p> <p>2 CONTENT</p>
<code>\fittopbaselinegrid {...}</code> * CONTENT
<code>\flag {...}</code> * NAME
<code>\floatuserdataparameter {...}</code> * KEY
<code>\flushboxregister ...</code> * CSNAME NUMBER
<code>\flushcollector [...]</code> * NAME
<code>\flushedrightlastline</code>
<code>\flushlayer [...]</code> * NAME
<code>\flushlocalfloats</code>
<code>\flushnextbox</code>
<code>\flushnotes</code>
<code>\flushoutputstream [...]</code> * NAME
<code>\flushshapebox</code>
<code>\flushtextflow {...}</code> * NAME
<code>\flushtokens [...]</code> * NAME
<code>\flushtoks \...</code> * CSNAME
<code>\fontalternative</code>

<code>\fontbody</code>
<code>\fontclass</code>
<code>\fontclassname {¹.} {².}</code> 1 NAME 2 FONT
<code>\fontface</code>
<code>\fontfeaturelist [¹.] [².]</code> 1 NAME 2 TEXT
<code>\fontchar {*.}</code> * NAME
<code>\fontcharbyindex {*.}</code> * NUMMER
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [¹...,²...] {...}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\footnotetext [...,.*...,...]</code> * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [¹.] [...,²...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\foundbox {¹.} {².}</code> 1 NAME 2 NAME

`\fourthoffivearguments {...} {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT

`\fourthoffourarguments {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT

`\fourthofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

`\frac {...} {...}`

1 CONTENT
2 CONTENT

`\frameddimension {...}`

* KEY

`\framedparameter {...}`

* KEY

`\freezedimenmacro \.^... \.^...`

1 CSNAME
2 CSNAME

`\freezemeasure [.^...] [.^...]`

1 NAME
2 DIMENSION

`\frenchspacing`

`\fromlinenote [.^...] {...}`

1 REFERENCE
2 TEXT

`\frozenhbox {...}`

* CONTENT

<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumpals {...}</code> * NUMMER
<code>\gdefconvertedargument \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\gdefconvertedcommand \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\getboxllx ...</code> * CSNAME NUMMER
<code>\getboxlly ...</code> * CSNAME NUMMER
<code>\getbufferdata [...]_{OPT}</code> * BUFFER
<code>\getcommacommandsize [...,*,...]</code> * BEFEHL
<code>\getcommalistsize [...,*,...]</code> * BEFEHL
<code>\getdayoftheweek {¹...} {²...} {³...}</code> 1 NUMMER 2 NUMMER 3 NUMMER
<code>\getdayspermonth {¹...} {²...}</code> 1 NUMMER 2 NUMMER
<code>\getdefinedbuffer [...]</code> * BUFFER
<code>\getdocumentargument {[*]...}</code> * NAME
<code>\getdocumentargumentdefault {¹...} {²...}</code> 1 NAME 2 TEXT

\getdocumentfilename {...} * NUMMER
\getdummyparameters [...,.. ¹ ...,...] * KEY = VALUE
\getemptyparameters [...,.. ¹] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getparameters [...,.. ¹] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getexpandedparameters [...,.. ¹] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getfiguredimensions [...,.. ¹] [...,.. ² ...,...] <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 FILE 2 inherits: \setupexternalfigure
\getfirstcharacter {...} * TEXT
\getfirsttwopassdata {...} * NAME
\getfromcommacommand [..., ¹ ...] [... ² ...] 1 BEFEHL 2 NUMMER
\getfromcommalist [..., ¹ ...] [... ² ...] 1 BEFEHL 2 NUMMER
\getfromtwopassdata {... ¹ } {... ² } 1 NAME 2 NAME
\getglyphdirect {... ¹ } {... ² } 1 FONT 2 NUMMER CHARACTER
\getglyphstyled {... ¹ } {... ² } 1 FONT 2 NUMMER CHARACTER

\getgparameters [¹ ...] [² ... ² ...] 1 TEXT 2 KEY = VALUE
\getlasttwopassdata {...} * NAME
\getlocalfloat {...} * NUMMER
\getlocalfloats
\getMPdrawing
\getMPlayer [¹ ...] [² ... ² ...] ³ {...} <small>OPT</small> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
\getmessage {...} {...} 1 NAME 2 NAME NUMMER
\getnamedglyphdirect {...} {...} 1 FONT 2 NAME
\getnamedglyphstyled {...} {...} 1 FONT 2 NAME
\getnamedtwopassdatalist \ ¹ ... {...} 1 CSNAME 2 NAME
\getnaturaldimensions ... * CSNAME NUMMER
\getnoflines {...} * DIMENSION
\getobject {...} {...} 1 NAME 2 NAME
\getobjectdimensions {...} {...} 1 NAME 2 NAME

\getpaletsize [...] * NAME
\getparameters [...] ¹ [...,... ² ...,...] 1 TEXT 2 KEY = VALUE
\getprivatechar {...} * NAME
\getprivateslot {...} * NAME
\getrandomcount \... {...} ² {...} ³ 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomdimen \... {...} ² {...} ³ 1 CSNAME 2 DIMENSION 3 DIMENSION
\getrandomfloat \... {...} ² {...} ³ 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomnumber \... {...} ² {...} ³ 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomseed \... * CSNAME
\getraweparameters [...] ¹ [...,... ² ...,...] 1 TEXT 2 KEY = VALUE
\getrawgparameters [...] ¹ [...,... ² ...,...] 1 TEXT 2 KEY = VALUE
\getrawnoflines {...} * DIMENSION

<pre> \getrawparameters [...]¹ [...,...²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawxparameters [...]¹ [...,...²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getreference [...]¹ [...]² 1 implicitni text titul cislo stranka realpage 2 REFERENCE </pre>
<pre> \getreferenceentry {...} * implicitni text titul cislo stranka realpage </pre>
<pre> \getroundednoflines {...} * DIMENSION </pre>
<pre> \getsubstring {...}¹ {...}² {...}³ 1 NUMMER 2 NUMMER 3 TEXT </pre>
<pre> \gettwopassdata {...} * NAME </pre>
<pre> \gettwopassdatalist {...} * NAME </pre>
<pre> \getuvalue {...} * NAME </pre>
<pre> \getvalue {...} * NAME </pre>
<pre> \getvariable {...}¹ {...}² 1 NAME 2 KEY </pre>
<pre> \getvariabledefault {...}¹ {...}² {...}³ 1 NAME 2 KEY 3 BEFEHL </pre>
<pre> \getxparameters [...]¹ [...,...²...,...] 1 TEXT 2 KEY = VALUE </pre>

\globaldisablemode [...,*,...] * NAME
\globalenablemode [...,*,...] * NAME
\globalletempty *.. * CSNAME
\globalpopbox ... * CSNAME NUMBER
\globalpopmacro *.. * CSNAME
\globalpreventmode [...,*,...] * NAME
\globalprocesscommalist [... ¹] *.. ² 1 BEFEHL 2 CSNAME
\globalpushbox ... * CSNAME NUMBER
\globalpushmacro *.. * CSNAME
\globalpushreferenceprefix {...} ... \globalpopreferenceprefix * + - TEXT
\globalswapcounts *.. ¹ *.. ² 1 CSNAME 2 CSNAME
\globalswapdimens *.. ¹ *.. ² 1 CSNAME 2 CSNAME
\globalswapmacros *.. ¹ *.. ² 1 CSNAME 2 CSNAME
\globalundefine {...} * NAME
\glyphfontfile {...} * FONT

`\gobbledoubleempty [...]1 [...]2`
 OPT OPT

1 TEXT

2 TEXT

`\gobbleeightarguments {...}1 {...}2 {...}3 {...}4 {...}5 {...}6 {...}7 {...}8`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

`\gobblefivearguments {...}1 {...}2 {...}3 {...}4 {...}5`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

`\gobblefiveoptionals [...]1 [...]2 [...]3 [...]4 [...]5`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\gobblefourarguments {...}1 {...}2 {...}3 {...}4`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

`\gobblefouroptionals [...]1 [...]2 [...]3 [...]4`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

`\gobbleninearguments {1...} {2...} {3...} {4...} {5...} {6...} {7...} {8...} {9...}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT
8 CONTENT
9 CONTENT

`\gobbleoneargument {*...}`

* CONTENT

`\gobbleoneoptional [...]`

* TEXT

`\gobblesevenarguments {1...} {2...} {3...} {4...} {5...} {6...} {7...}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT

`\gobblesingleempty [...]`
OPT

* TEXT

`\gobblesixarguments {1...} {2...} {3...} {4...} {5...} {6...}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT

`\gobblespacetokens`

`\gobbletenarguments {1.} {2.} {3.} {4.} {5.} {6.} {7.} {8.} {9.} {10.}`

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT
8 CONTENT
9 CONTENT
10 CONTENT

`\gobblethreearguments {1.} {2.} {3.}`

1 CONTENT
2 CONTENT
3 CONTENT

`\gobblethreeoptionals [1.] [2.] [3.]`

1 TEXT
2 TEXT
3 TEXT

`\gobbletwoarguments {1.} {2.}`

1 CONTENT
2 CONTENT

`\gobbletwooptionals [1.] [2.]`

1 TEXT
2 TEXT

`\gobbleuntil \...`

* CSNAME

`\gobbleuntilrelax ... \relax`

* CONTENT

`\grabbufferdata [1.] [2.] [3.] [4.]`
OPT

1 CATEGORY
2 NAME
3 NAME
4 NAME

`\grabbufferdatadirect {1.} {2.} {3.}`

1 NAME
2 NAME
3 NAME

<code>\grabuntil {...} \^2.</code> 1 NAME 2 CSNAME
<code>\grave {...}</code> * CHARACTER
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring ... \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMMER
<code>\groupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\gsetboxllx ... {...}</code> 1 CSNAME NUMMER 2 DIMENSION
<code>\gsetboxlly ... {...}</code> 1 CSNAME NUMMER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMMER
<code>\gurmukhinumerals {...}</code> * NUMMER
<code>\hairspace</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens ... \with ...</code> 1 TEXT 2 CSNAME
<code>\hangul</code>

<code>\hanzi</code>
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...¹,...] {...²}</code> 1 REFERENCE 2 CONTENT
<code>\hboxBOX {...}</code> * CONTENT
<code>\hdofstring {...}</code> * TEXT
<code>\headhbox ...¹ {...²}</code> OPT 1 TEXT 2 CONTENT
<code>\headlanguage</code>
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtexts {...¹} {...²}</code> 1 KEY 2 TEXT
<code>\headtextwidth</code>
<code>\headvbox ...¹ {...²}</code> OPT 1 TEXT 2 CONTENT
<code>\headwidth</code>

<code>\heightanddepthofstring {...}</code> * TEXT
<code>\heightofstring {...}</code> * TEXT
<code>\heightspanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\HELP [...]</code> <small>OPT</small> 1 REFERENCE 2 TEXT 3 TEXT instances: textnapovedy
<code>\hglue ...</code> * DIMENSION
<code>\hiddenbar {...}</code> * CONTENT
<code>\hiddencitation [...]</code> * REFERENCE
<code>\hiddencite [...]</code> * REFERENCE
<code>\highlight [...]</code> 1 NAME 2 TEXT
<code>\HIGHLIGHT {...}</code> * TEXT
<code>\highordinalstr {...}</code> * TEXT
<code>\hilo [...]</code> <small>OPT</small> 1 vlevo vpravo 2 CONTENT 3 CONTENT

$\backslash\mathrm{himilo}\{\ldots\}\{\ldots\}\{\ldots\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\mathrm{hl}\left[\ldots\right]$ <small>OPT</small> * NUMMER
$\backslash\mathrm{hlavni}\mathrm{jazyk}\left[\ldots\right]$ * SPRACHE
$\backslash\mathrm{hodnotabarvy}\{\ldots\}$ * COLOR
$\backslash\mathrm{horizontalgrowingbar}\left[\ldots,\ldots^*\ldots,\ldots\right]$ * inherits: $\backslash\mathrm{setuppositionbar}$
$\backslash\mathrm{horizontalpositionbar}\left[\ldots,\ldots^*\ldots,\ldots\right]$ * inherits: $\backslash\mathrm{setuppositionbar}$
$\backslash\mathrm{hphantom}\{\ldots\}$ * CONTENT
$\backslash\mathrm{hpos}\{\ldots\}\{\ldots\}$ 1 NAME 2 CONTENT
$\backslash\mathrm{hsizedfraction}\{\ldots\}\{\ldots\}$ 1 DIMENSION 2 NUMMER
$\backslash\mathrm{hsmash}\{\ldots\}$ * CONTENT
$\backslash\mathrm{hsmashbox}\ldots$ * CSNAME NUMMER
$\backslash\mathrm{hsmashed}\{\ldots\}$ * CONTENT
$\backslash\mathrm{hspace}\left[\ldots\right]\left[\ldots\right]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 male stredni velke normalni implicitni zadny .5 1 2 3 speech citovat interquotation citace sentence intersentence NAME
$\backslash\mathrm{htdpofstring}\{\ldots\}$ * TEXT

\htofstring {...} * TEXT
\hyphen
\hyphenatedcoloredword {...} * TEXT
\hyphenatedfile {...} * FILE
\hyphenatedfilename {...} * TEXT
\hyphenatedhbox {...} * CONTENT
\hyphenatedpar {...} * TEXT
\hyphenatedurl {...} * TEXT
\hyphenatedword {...} * TEXT
\CHARACTERKERNING [...] {...} <small>OPT</small> 1 NUMMER 2 TEXT
\chardescription {...} * NUMMER
\charwidthlanguage
\check {...} * CHARACTER
\checkedfiller {...} * sym symbol linka sirka mezera NAME BEFEHL
\checkedchar {...} {...} 1 NUMMER 2 CHARACTER
\checkedstrippedcsname *.. * CSNAME

\checkedstrippedcsname ... * TEXT
\checkcharacteralign {...} * CONTENT
\checkinjector [...] * NAME
\checknextindentation [...] * ano ne auto
\checknextinjector [...] * NAME
\checkpage [...] ¹ [...,... ² ...] _{OPT} 1 NAME 2 inherits: \setuppagechecker
\checkparameters [...] * TEXT
\checkpreviousinjector [...] * NAME
\checksoundtrack {...} * NAME
\checktwopassdata {...} * NAME
\checkvariables [...] ¹ [...,... ² ...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\chem {...} ¹ {...} ² {...} ³ 1 TEXT 2 TEXT 3 TEXT
\chemical [...] ¹ [...,... ² ...] _{OPT} [...,... ³ ...] _{OPT} 1 NAME 2 TEXT 3 TEXT

<code>\chemicalbottext {...}</code> * TEXT
<code>\chemicalmidtext {...}</code> * TEXT
<code>\chemicalsymbol [...]</code> * NAME
<code>\chemicaltext {...}</code> * TEXT
<code>\chemicaltoptext {...}</code> * TEXT
<code>\chineseallnumerals {...}</code> * NUMMER
<code>\chinesecapnumerals {...}</code> * NUMMER
<code>\chinesenumerals {...}</code> * NUMMER
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE

<code>\iftrialtypesetting ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata ¹{...} ²{...} ³{...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\includemenu [...]</code> * NAME
<code>\includeversioninfo {...}</code> * NAME
<code>\incrementcounter [...] [²...] _{OPT}</code> 1 NAME 2 NUMMER
<code>\incrementedcounter [...]</code> * NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> * NAME
<code>\indentation</code>
<code>\infofont</code>
<code>\infofontbold</code>
<code>\inheritparameter [...] [²...] [³...]</code> 1 TEXT 2 TEXT 3 KEY

<code>\inhibitblank</code>
$\text{\ininner } [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \{\overset{3}{\dots}\}$ $\text{\ininner } [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \{\dots\}$ <ol style="list-style-type: none"> odkaz = REFERENCE inherits: \setupmargindata inherits: \setupmarginframed CONTENT
$\text{\ininneredge } [\dots, \dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ $\text{\ininneredge } [\dots, \dots, \overset{1}{\dots}, \dots] \{\dots\}$ <ol style="list-style-type: none"> odkaz = REFERENCE inherits: \setupmargindata CONTENT
$\text{\ininnermargin } [\dots, \dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ $\text{\ininnermargin } [\dots, \dots, \overset{1}{\dots}, \dots] \{\dots\}$ <ol style="list-style-type: none"> odkaz = REFERENCE inherits: \setupmargindata CONTENT
$\text{\initializeboxstack } \{\dots\}$ <ol style="list-style-type: none"> NAME
$\text{\inlinebuffer } [\dots, \dots, \overset{*}{\dots}]$ $\text{\inlinebuffer } [\dots, \dots, \overset{*}{\dots}]$ <ol style="list-style-type: none"> BUFFER
$\text{\inlinedbox } \{\dots\}$ <ol style="list-style-type: none"> CONTENT
$\text{\inlinemath } \{\dots\}$ <ol style="list-style-type: none"> CONTENT
$\text{\inlinemathematics } \{\dots\}$ <ol style="list-style-type: none"> CONTENT
$\text{\inlinemessage } \{\dots\}$ <ol style="list-style-type: none"> TEXT
$\text{\inlineordisplaymath } \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\text{\inlineordisplaymath } \{\dots\} \{\dots\}$ <ol style="list-style-type: none"> CONTENT CONTENT
$\text{\inlinerange } [\dots]$ <ol style="list-style-type: none"> REFERENCE
<code>\innerflushshapebox</code>
$\text{\inothet } [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \{\overset{3}{\dots}\}$ $\text{\inothet } [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \{\dots\}$ <ol style="list-style-type: none"> odkaz = REFERENCE inherits: \setupmargindata inherits: \setupmarginframed CONTENT

<pre> \inouter [...,\overset{1}{=}\dots] [...,\overset{2}{=}\dots] {\overset{3}{...}} OPT OPT 1 odkaz = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT </pre>
<pre> \inouteredge [...,\overset{1}{=}\dots] {\overset{2}{...}} OPT 1 odkaz = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \inoutermargin [...,\overset{1}{=}\dots] {\overset{2}{...}} OPT 1 odkaz = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \input {...} * FILE </pre>
<pre> \inputfilebarename </pre>
<pre> \inputfilename </pre>
<pre> \inputfilerealsuffix </pre>
<pre> \inputfilesuffix </pre>
<pre> \inputgivenfile {...} * FILE </pre>
<pre> \input ... * FILE </pre>
<pre> \insertpages [...] [...,\overset{2}{=}\dots] [...,\overset{3}{=}\dots] OPT OPT 1 FILE 2 NUMMER 3 sirka = DIMENSION n = NUMMER category = NAME </pre>
<pre> \instalacejazyka [...] [...,\overset{2}{=}\dots] 1 NAME 2 inherits: \nastavjazyk </pre>
<pre> \instalacejazyka [...] [...] 1 NAME 2 SPRACHE </pre>
<pre> \installactionhandler {...} * NAME </pre>

<pre>\installactivecharacter ...</pre> <p>* CHARACTER</p>
<pre>\installanddefineactivecharacter ... {^1} {^2}</pre> <p>1 CHARACTER</p> <p>2 BEFEHL</p>
<pre>\installattributestack *</pre> <p>* CSNAME</p>
<pre>\installautocommandhandler \... {^1} {^2} \... {^3}</pre> <p>1 CSNAME</p> <p>2 NAME</p> <p>3 CSNAME</p>
<pre>\installautosetuphandler \... {^1} {^2}</pre> <p>1 CSNAME</p> <p>2 NAME</p>
<pre>\installbasicautosetuphandler \... {^1} {^2} \... {^3}</pre> <p>1 CSNAME</p> <p>2 NAME</p> <p>3 CSNAME</p>
<pre>\installbasicparameterhandler \... {^1} {^2}</pre> <p>1 CSNAME</p> <p>2 NAME</p>
<pre>\installbottomframerenderer {^1} {^2} {^3}</pre> <p>1 NAME</p> <p>2 BEFEHL</p>
<pre>\installcommandhandler \... {^1} {^2} \... {^3}</pre> <p>1 CSNAME</p> <p>2 NAME</p> <p>3 CSNAME</p>
<pre>\installcorenamespace {...}</pre> <p>* NAME</p>
<pre>\installdefinehandler \... {^1} {^2} \... {^3}</pre> <p>1 CSNAME</p> <p>2 NAME</p> <p>3 CSNAME</p>

<pre>\installdefinitionset \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdefinitionsetmember \... {...} \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre> <pre>4 NAME</pre>
<pre>\installdirectcommandhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectparameterhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectparametersethandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectsetuphandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectstyleandcolorhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installframedautocommandhandler \... {...} \...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installframedcommandhandler \... {...} \...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installleftframerenderer {...} {...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\installnamespace {...}</pre> <pre>* NAME</pre>

\installoutputroutine \... {...}

- 1 CSNAME
- 2 BEFEHL

\installpagearrangement ... {...}

- 1 NAME
- 2 BEFEHL

\installparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installparameterhashhandler \... {...}

- 1 CSNAME
- 2 NAME

\installparametersethandler \... {...}

- 1 CSNAME
- 2 NAME

\installparentinjector \... {...}

- 1 CSNAME
- 2 NAME

\installrightframerenderer {...} {...}

- 1 NAME
- 2 BEFEHL

\installrootparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuphandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuponlycommandhandler \... {...}

- 1 CSNAME
- 2 NAME

\installshipoutmethod {...} {...}

- 1 NAME
- 2 BEFEHL

`\installsimplecommandhandler \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installsimpleframedcommandhandler \.^{.} \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installstyleandcolorhandler \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME

`\installswitchcommandhandler \.^{.} \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installswitchsetuphandler \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME

`\installtexdirective \.^{.} \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

`\installtextracker \.^{.} \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

`\installtopframerenderer \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL

`\installunitsseparator \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL

`\installunitsspace \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL

$\backslash\text{installversioninfo}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 BEFEHL
$\backslash\text{integerrounding}$ $\{.^*.\}$ * NUMMER
$\backslash\text{interakcnilista}$ $[.^1.]$ $[.^2.]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \nastavinterakcnilistu
$\backslash\text{interakcnitlacitka}$ $[.^1.]$ $[.^2.]$ <small>OPT</small> <small>OPT</small> 1 inherits: \nastavinterakcnilistu 2 stranka podstranka REFERENCE
$\backslash\text{interaktivnimenu}$ $[.^1.]$ $[.^2.]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \nastavinterakcnimenu
$\backslash\text{intertext}$ $\{.^*.\}$ * TEXT
$\backslash\text{invokepagehandler}$ $\{.^1.\}$ $\{.^2.\}$ 1 normalni zadny NAME 2 CONTENT
$\backslash\text{istltdir}$ $.^*$ * TLT TRT
$\backslash\text{istrtdir}$ $.^*$ * TLT TRT
$\backslash\text{italiccorrection}$
$\backslash\text{itemtag}$ $[.^*.]$ <small>OPT</small> * REFERENCE
$\backslash\text{jazyk}$ $[.^*.]$ * SPRACHE
$\backslash\text{LANGUAGE}$
$\backslash\text{jdidolu}$ $[.^*.]$ * DIMENSION
$\backslash\text{jdina}$ $\{.^1.\}$ $[.^2.]$ 1 CONTENT 2 REFERENCE

<p><code>\jdinabox {...} [...]</code></p> <p>1 CONTENT</p> <p>2 REFERENCE</p>
<p><code>\jdinastranu {...} [...]</code></p> <p>1 TEXT</p> <p>2 REFERENCE</p>
<p><code>\jednotka {...}</code></p> <p>* CONTENT</p>
<p><code>\JEDNOTKA {...}</code></p> <p>* CONTENT</p> <p>instances: jednotka</p>
<p><code>\jobfilename</code></p>
<p><code>\jobfilesuffix</code></p>
<p><code>\Kap {...}</code></p> <p>* TEXT</p>
<p><code>\kaligraficke</code></p>
<p><code>\kap {...}</code></p> <p>* TEXT</p>
<p><code>\kapitola [...¹,...] {...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\keeplinestogether {...}</code></p> <p>* NUMMER</p>
<p><code>\keepunwantedspaces</code></p>
<p><code>\kerncharacters [...¹] {...}</code> <small>OPT</small></p> <p>1 NUMMER</p> <p>2 TEXT</p>
<p><code>\klonujpole [...¹] [...²] [...³] [...⁴,...]</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>

<p><code>\komentar</code> [¹...] [²...²...³...] {...}</p> <p>1 TEXT</p> <p>2 inherits: \nastavkomentar</p> <p>3 TEXT</p>
<p><code>\KOMENTAR</code> [¹...] [²...²...³...] {...}</p> <p>1 TEXT</p> <p>2 inherits: \nastavkomentar</p> <p>3 TEXT</p> <p>instances: komentar</p>
<p><code>\komponenta</code> [...]</p> <p>* FILE</p>
<p><code>\komponenta</code> ...</p> <p>* FILE</p>
<p><code>\konvertujcislo</code> {...} {...}</p> <p>1 prazdne implicitni zadny mesic month:mnem pismo Pismo pisma Pisma a A Csla slovo words Slovo Slova n N rimskecislice Rimskecislice i I r R KR RK recky Recky g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarnumerals gurmukhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclednumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set₀ set₁ set₂ set₃ continued NAME</p> <p>2 NUMMER</p>
<p><code>\kopirujpole</code> [¹...] [²...]</p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\koreancirclednumerals</code> {...}</p> <p>* NUMMER</p>
<p><code>\koreannumerals</code> {...}</p> <p>* NUMMER</p>
<p><code>\koreannumeralsc</code> {...}</p> <p>* NUMMER</p>
<p><code>\koreannumeralsp</code> {...}</p> <p>* NUMMER</p>
<p><code>\koreanparentnumerals</code> {...}</p> <p>* NUMMER</p>
<p><code>\korekcebilehomista</code> {...}</p> <p>* CONTENT</p>
<p><code>\kurziva</code></p>

<code>\kurzivnitucne</code>
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\labellanguage</code>
<code>\POPISEKjazyk</code> instances: hlavicka popisek mathlabel taglabel jednotka operator prefix suffix btxlabel
<code>\labeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\POPISEKtexts {...} {...}</code> 1 KEY 2 TEXT instances: hlavicka popisek mathlabel
<code>\languagecharacters {...}</code> * NUMMER
<code>\languageCharacters {...}</code> * NUMMER
<code>\languagecharwidth {...}</code> * SPRACHE
<code>\lastcounter [...]</code> ¹ <code>[...]</code> ² <small>OPT</small> 1 NAME 2 NUMMER
<code>\lastcountervalue [...]</code> * NAME

<code>\lastdigit {...}</code> * NUMMER
<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [...]¹ [...]²</code> 1 NAME 2 NUMMER
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {...}</code> * NUMMER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {...}</code> * BEFEHL
<code>\latin</code>
<code>\layeredtext [...]_{OPT}¹ [...]_{OPT}² {...}³ {...}⁴</code> 1 inherits: \setuplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {...}¹ {...}² {...}³ {...}⁴</code> 1 NAME 2 NUMMER 3 NAME 4 CONTENT

$\backslash\text{lazysavetwopassdata } \{.^1.\} \{.^2.\} \{.^3.\}$ 1 NAME 2 NUMMER 3 CONTENT
$\backslash\text{lbox } \overset{1}{...} \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{leftbottombox } \{.^*\}$ * CONTENT
$\backslash\text{leftbox } \{.^*\}$ * CONTENT
$\backslash\text{lefthbox } \{.^*\}$ * CONTENT
$\backslash\text{leftheadtext } \{.^*\}$ * KEY
$\backslash\text{leftlabeltext } \{.^*\}$ * KEY
$\backslash\text{leftPOPISEKtext } \{.^*\}$ * KEY instances: hlavicka popisek mathlabel
$\backslash\text{leftline } \{.^*\}$ * CONTENT
$\backslash\text{leftmathlabeltext } \{.^*\}$ * KEY
$\backslash\text{lefttorrighthbox } \overset{1}{...} \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{lefttorrightvbox } \overset{1}{...} \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{lefttorrightvtop } \overset{1}{...} \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{leftskipadaption}$

<code>\leftsubguillemot</code>
<code>\lefttopbox {...}</code> * CONTENT
<code>\lefttoright</code>
<code>\lefttorighthbox ¹... {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\lefttorightvbox ¹... {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\lefttorightvtop ¹... {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\letbeundefined {...}</code> * NAME
<code>\letcatcodecommand \¹... ²... \³...</code> 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
<code>\letcscsname \¹... \csname ²... \endcsname</code> 1 CSNAME 2 NAME
<code>\letcsnamecs \csname ¹... \endcsname \²...</code> 1 NAME 2 CSNAME
<code>\letcsnamecsname \csname ¹... \endcsname \csname ²... \endcsname</code> 1 NAME 2 NAME
<code>\letdummyparameter {...} \¹... \²...</code> 1 KEY 2 CSNAME
<code>\letempty \[*]...</code> * CSNAME

<code>\letgvalue {...} \...</code> 1 NAME 2 CSNAME
<code>\letgvalueempty {...}</code> * NAME
<code>\letgvalurelax {...}</code> * NAME
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>

<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> $[.^{.1}] \{.^{.2}\}$ <small>OPT</small> 1 NUMMER 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> $\{.^{.1}\} \backslash.^{.2}$ 1 NAME 2 CSNAME
<code>\letvalueempty</code> $\{.^{*}\}$ * NAME
<code>\letvaluerelax</code> $\{.^{*}\}$ * NAME
<code>\lfence</code> $\{.^{*}\}$ * CHARACTER
<code>\lhbox</code> $\{.^{*}\}$ * CONTENT
<code>\limitatelines</code> $\{.^{.1}\} \{.^{.2}\} \{.^{.3}\}$ 1 NUMMER 2 BEFEHL 3 TEXT
<code>\limitatetext</code> $\{.^{.1}\} \{.^{.2}\} \{.^{.3}\}$ 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext</code> $\{.^{.1}\} \{.^{.2},.^{.2}\} \{.^{.3}\}$ 1 TEXT 2 [-+]DIMENSION 3 BEFEHL

`\limtatefirstline {...} {...} {...}`

- 1 TEXT
- 2 DIMENSION
- 3 BEFEHL

`\linenote {...}`

- * TEXT

`\LINENOTE {...}`

- * TEXT

instances: linenote

`\linespanningtext {...} {...} {...}`

- 1 TEXT
- 2 DIMENSION
- 3 FONT

`\listcitation [...1...] [...2]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\listcitation [...1...] [...2]`

- 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\listcitation [...1...] [...2...]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

`\listcite [...1...] [...2]`

- 1 odkaz = REFERENCE
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

<pre> \listcite [...] [...] ^{OPT} 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \listcite [...,¹...,...] [...,²...,...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \listnamespaces </pre>
<pre> \llap {...} * CONTENT </pre>
<pre> \loadanyfile [...] * FILE </pre>
<pre> \loadanyfileonce [...] * FILE </pre>
<pre> \loadbtxdefinitionfile [...] * FILE </pre>
<pre> \loadbtxreplacementfile [...] * FILE </pre>
<pre> \loadcldfile [...] * FILE </pre>
<pre> \loadcldfileonce [...] * FILE </pre>
<pre> \loadfontgoodies [...] * FILE </pre>
<pre> \loadluafile [...] * FILE </pre>
<pre> \loadluafileonce [...] * FILE </pre>
<pre> \loadspellchecklist [¹...] [²...] 1 NAME 2 FILE </pre>

<code>\loadtexfile [...]</code> * FILE
<code>\loadtexfileonce [...]</code> * FILE
<code>\loadtypescriptfile [...]</code> * FILE
<code>\localframed [...] [...²..._{OPT}...] {...³}</code> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
<code>\localframedwithsettings [...] [...²..._{OPT}...] {...³}</code> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
<code>\localhsize</code>
<code>\localpopbox ...</code> * CSNAME NUMBER
<code>\localpopmacro \...</code> * CSNAME
<code>\localpushbox ...</code> * CSNAME NUMBER
<code>\localpushmacro \...</code> * CSNAME
<code>\localundefine {...}</code> * NAME
<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> * FILE
<code>\locfilename {...}</code> * FILE
<code>\logo [...¹] {...²}</code> _{OPT} 1 NAME 2 CONTENT

$\backslash\text{lohihi } \{.^1.\} \{.^2.\} \{.^3.\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{lowerbox } \{.^1.\} \backslash.^2.\{.^3.\}$ 1 DIMENSION 2 CSNAME 3 CONTENT
$\backslash\text{lowercased } \{.*.\}$ * TEXT
$\backslash\text{lowercasestring } .^1.\ \backslash\text{to } \backslash.^2.\$ 1 TEXT 2 CSNAME
$\backslash\text{lowerlefthdoubleninequote}$
$\backslash\text{lowerleftsingleninequote}$
$\backslash\text{lowerrighthdoubleninequote}$
$\backslash\text{lowerrightsingleninequote}$
$\backslash\text{LOWHIGH } [.^1.] \{.^2.\} \{.^3.\}$ <small>OPT</small> 1 vlevo vpravo 2 CONTENT 3 CONTENT
$\backslash\text{LOWMIDHIGH } \{.^1.\} \{.^2.\} \{.^3.\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{lrtbbox } \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\} \{.^5.\}$ 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
$\backslash\text{ltop } .^1.\{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{luacode } \{.*.\}$ * BEFEHL

\luaconditional *.. * CSNAME
\luaenvironment ... * FILE
\luaexpanded {...} * BEFEHL
\luafunction {...} * BEFEHL
\luajitTeX
\luamajorversion
\luaminorversion
\luaparameterset {...} {...} 1 NAME 2 CONTENT
\luasetup {...} * NAME
\luaTeX
\luaversion
\MESIC {...} * NUMMER
\METAFONT
\METAFUN
\METAPOST
\MetaFont
\MetaFun
\MetaPost
\MKII
\MKIV
\MKIX

<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {...}</code> * NUMBER
<code>\MONTHSHORT {...}</code> * NUMBER
<code>\MPanchor {...}</code> * NAME
<code>\MPbetex {...}</code> * NAME
<code>\MPc {...}</code> * NAME
<code>\MPcode {...} {...}</code> <div style="margin-left: 100px;"><small>OPT</small></div> 1 NAME 2 CONTENT
<code>\MPcolor {...}</code> * COLOR
<code>\MPcoloronly {...}</code> * COLOR
<code>\MPcolumn {...}</code> * NAME
<code>\MPd {...}</code> * NAME
<code>\MPdrawing {...}</code> * CONTENT
<code>\MPfontsizehskip {...}</code> * FONT
<code>\MPgetmultipars {...} {...}</code> 1 NAME 2 NAME
<code>\MPgetmultishape {...} {...}</code> 1 NAME 2 NAME

\MPgetposboxes {..., ¹ ...} {... ² } 1 NAME 2 NAME
\MP _h {...} * NAME
\MPII
\MPIV
\MPinclusions [...] _{OPT} {...} _{OPT} {...} ³ 1 + 2 NAME 3 CONTENT
\MPl _{eftskip} {...} * NAME
\MP _{l1} {...} * NAME
\MP _{l_r} {...} * NAME
\MP _{l_s} {...} * NAME
\MP _{menubuttons} {...} * NAME
\MP _n {...} * NAME
\MP _{options} {...} * COLOR
\MP _{overlayanchor} {...} * NAME
\MP _p {...} * NAME
\MP _{page} {...} * NAME
\MP _{pardata} {...} * NAME

\MPplus {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic {...} {..., <small>2</small> ...} <small>OPT</small> 1 NAME 2 KEY = VALUE
\MPposset {...} * NAME
\MPr {...} * NAME
\MPravvar {...} {...} 1 NAME 2 KEY
\MPreion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPstring {...} * NAME
\MPText {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME

\MPur {...} * NAME
\MPVI
\MPv {... ¹ } {... ² } {... ³ } 1 NAME 2 NUMMER 3 CONTENT
\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {... ¹ } {... ² } 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME
\MPxy {...} * NAME
\MPxywhd {...} * NAME
\MPy {...} * NAME
\m [... ¹] [... ²] <small>OPT</small> 1 NAME 2 CONTENT
\makecharacteractive ... * CHARACTER
\makerawcommalist [... ¹ ,...] ² ... 1 BEFEHL 2 CSNAME

$\backslash\text{makestrutofbox}$... * CSNAME NUMMER
$\backslash\text{male}$
$\backslash\text{malekurzivnitucne}$
$\backslash\text{malenormalni}$
$\backslash\text{malesklonene}$
$\backslash\text{malesklonenetucne}$
$\backslash\text{maletucne}$
$\backslash\text{maletucnekurzivni}$
$\backslash\text{maletucnesklonene}$
$\backslash\text{maletype}$
$\backslash\text{maoramovani}$ [... ¹ ... _{OPT} ...] { ² ...} 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT
$\backslash\text{mapfontsize}$ [... ¹ ...] [... ² ...] 1 DIMENSION 2 DIMENSION
$\backslash\text{marginalninadpis}$ [... ¹ ... _{OPT} ...] { ² ...} 1 odkaz = REFERENCE inherits: $\backslash\text{setupmargindata}$ 2 CONTENT
$\backslash\text{marginalnislovo}$ [... ¹ ... _{OPT} ...] { ² ...} 1 odkaz = REFERENCE inherits: $\backslash\text{setupmargindata}$ 2 CONTENT
$\backslash\text{marginalnitext}$ [... ¹ ... _{OPT} ...] { ² ...} 1 odkaz = REFERENCE inherits: $\backslash\text{setupmargindata}$ 2 CONTENT
$\backslash\text{margindata}$ [... ¹ ...] [... ² ... _{OPT} ...] [... ³ ... _{OPT} ...] { ⁴ ...} 1 NAME 2 odkaz = REFERENCE inherits: $\backslash\text{setupmargindata}$ 3 inherits: $\backslash\text{setupmarginframed}$ 4 CONTENT

\backslash MARGINDATA [... ¹ ... _{OPT} ...] [... ² ... _{OPT} ...] {... ³ } 1 odkaz = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances: nalevyokraj napravyokraj inoutermargin ininnermargin nalevo napravo inouteredge ininneredge atleftmargin atrightmargin ivlevo ivpravo inouter ininner naokraji inother marginalnitext
\backslash markcontent [... ¹ ... _{OPT}]{... ² } 1 reset vse NAME 2 CONTENT
\backslash markinjector [...*...] * NAME
\backslash mat {...*...} * CONTENT
\backslash matematika [... ¹ ... _{OPT}]{... ² } 1 NAME 2 CONTENT
\backslash math [... ¹ ... _{OPT}]{... ² } 1 NAME 2 CONTENT
\backslash mathbf
\backslash mathbi
\backslash mathblackboard
\backslash mathbs
\backslash mathcommand {...*...} * NAME
\backslash MATHCOMMAND {... ¹ ... _{OPT} }{... ² ... _{OPT} } 1 TEXT 2 TEXT
\backslash mathdefault
\backslash MATHDOUBLEEXTENSIBLE {...*...} * TEXT

$\backslash\text{MATHEXTENSIBLE}$ [$\overset{1}{\dots}$] $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ <small>OPT OPT OPT</small> 1 reverse mathematika text chemistry 2 TEXT 3 TEXT
$\backslash\text{mathfraktur}$
$\backslash\text{MATHFRAMED}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT instances: mframed inmframed mcframed
$\backslash\text{mathfunction}$ $\{\dots\}$ * CONTENT
$\backslash\text{mathit}$
$\backslash\text{mathitalic}$
$\backslash\text{mathlabellanguage}$
$\backslash\text{mathlabeltext}$ $\{\dots\}$ * KEY
$\backslash\text{mathlabeltexts}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ 1 KEY 2 TEXT
$\backslash\text{mathop}$ $\{\dots\}$ * CONTENT
$\backslash\text{MATHORNAMENT}$ $\{\dots\}$ * CONTENT
$\backslash\text{MATHOVEREXTENSIBLE}$ $\{\dots\}$ * TEXT
$\backslash\text{MATHOVERTEXTEXTENSIBLE}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ 1 TEXT 2 TEXT
$\backslash\text{MATHRADICAL}$ [$\overset{1}{\dots}$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{mathrm}$
$\backslash\text{mathscript}$

<code>\mathsl</code>
<code>\mathss</code>
$\text{\texttt{\textbackslash mathtext}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash mathtextbf}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash mathtextbi}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash mathtextbs}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash mathtextit}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash mathtextsl}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash mathtexttf}} \overset{1}{\dots} \{\overset{2}{\dots}\}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
<code>\mathtf</code>
$\text{\texttt{\textbackslash mathtriplet}} [\overset{1}{\dots}] \{\overset{2}{\dots}\} \{\overset{3}{\dots}\} \{\overset{4}{\dots}\}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div> <div> <div>4</div> <div>TEXT</div> </div>
$\text{\texttt{\textbackslash MATHTRIPLET}} [\overset{1}{\dots}] \{\overset{2}{\dots}\} \{\overset{3}{\dots}\} \{\overset{4}{\dots}\}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div> <div> <div>4</div> <div>TEXT</div> </div>
<code>\mathtt</code>

$\backslash\text{MATHUNDEREXTENSIBLE}$ {...} * TEXT
$\backslash\text{MATHUNDERTEXTEXTENSIBLE}$ {...} {...} 1 TEXT 2 TEXT
$\backslash\text{MATHUNSTACKED}$
$\backslash\text{mathupright}$
$\backslash\text{mathword}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mathwordbf}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mathwordbi}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mathwordbs}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mathwordit}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mathwordsl}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mathwordtf}$ ¹ ... {...} <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{maxaligned}$ {...} * CONTENT
$\backslash\text{mazaramovani}$ [... ¹ ... ¹ ...] {...} <small>OPT</small> 1 inherits: <code>\setupmathframed</code> 2 CONTENT
$\backslash\text{mbox}$ {...} * CONTENT

$\backslash\mathrm{mcframed} [\dots\overset{1}{=}\dots] \{\overset{2}{\dots}\}$ OPT 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{measure} \{\dots\}$ * NAME
$\backslash\mathrm{measured} \{\dots\}$ * NAME
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{mequal} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ OPT OPT 1 TEXT 2 TEXT
$\backslash\mathrm{meritko} [\overset{1}{\dots}] [\dots\overset{2}{=}\dots] \{\overset{3}{\dots}\}$ OPT OPT 1 NAME 2 inherits: $\backslash\mathrm{setupscale}$ 3 CONTENT
$\backslash\mathrm{mesic} \{\dots\}$ * NUMMER
$\backslash\mathrm{message} \{\dots\}$ * TEXT
$\backslash\mathrm{metaTeX}$
$\backslash\mathrm{mezera}$
$\backslash\mathrm{mfence} \{\dots\}$ * CHARACTER
$\backslash\mathrm{mfunction} \{\dots\}$ * CONTENT
$\backslash\mathrm{mfunctionlabeltext} \{\dots\}$ * NAME
$\backslash\mathrm{mhbox} \{\dots\}$ * CONTENT
$\backslash\mathrm{mhookleftarrow} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ OPT OPT 1 TEXT 2 TEXT

\mhookeightarrow $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\middlealigned $\{...\}$ * CONTENT
\middlebox $\{...\}$ * CONTENT
\midhbox $\{...\}$ * CONTENT
\minimalhbox $\{...\}^1 \{...\}^2$ <small>OPT</small> 1 TEXT 2 CONTENT
\mixedcaps $\{...\}$ * TEXT
\mkvibuffer $[...]^*$ <small>OPT</small> * BUFFER
\mLeftarrow $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mLeftrightarrow $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mleftarrow $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mleftharpoondown $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mleftharpoonup $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mleftrightharpoonup $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT

\mleftrightharpoons $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT
\mmapsto $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT
\moduleparameter $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 FILE 2 KEY
\molecule $\{...\}^{*}$ * CONTENT
\mono
\mononormal
\monotucne
\monthlong $\{...\}^{*}$ * NUMBER
\monthshort $\{...\}^{*}$ * NUMBER
\mprandomnumber
\mRrightarrow $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT
\mrel $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT
\mrightarrow $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT
\mrightharpoondown $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT
\mrightharpoonup $\{...\}^{1}_{\text{OPT}} \{...\}^{2}_{\text{OPT}}$ 1 TEXT 2 TEXT

$\backslash\mathrm{mrightharpoonleft}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mrightharpoonoverleftarrow}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mrizka}[\dots,\overset{*}{\dots},\dots]$ <div> <div>OPT</div> </div> <div> <div>* inherits: \basegrid</div> </div>
$\backslash\mathrm{mtext}\{\dots\}$ <div> <div>* CONTENT</div> </div>
$\backslash\mathrm{mtriplelrel}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mtwoheadleftarrow}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mtwoheadrightarrow}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{NormalizeFontHeight}\backslash\dots\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 CSNAME</div> <div>2 TEXT</div> <div>3 DIMENSION</div> <div>4 FONT</div> </div>
$\backslash\mathrm{NormalizeFontWidth}\backslash\dots\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 CSNAME</div> <div>2 TEXT</div> <div>3 DIMENSION</div> <div>4 FONT</div> </div>
$\backslash\mathrm{NormalizeTextHeight}\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 FONT</div> <div>2 DIMENSION</div> <div>3 TEXT</div> </div>
$\backslash\mathrm{NormalizeTextWidth}\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 FONT</div> <div>2 DIMENSION</div> <div>3 TEXT</div> </div>

<p><code>\nadtrzeni {...}</code></p> <p>* CONTENT</p>
<p><code>\nadtrzeno {...}</code></p> <p>* CONTENT</p>
<p><code>\nalevo [...¹...²] {...}</code></p> <p> OPT</p> <p>1 odkaz = REFERENCE inherits: \setupmargindata</p> <p>2 CONTENT</p>
<p><code>\nalevyokraj [...¹...²] {...}</code></p> <p> OPT</p> <p>1 odkaz = REFERENCE inherits: \setupmargindata</p> <p>2 CONTENT</p>
<p><code>\namedheadnumber {...}</code></p> <p>* ABSCHNITT</p>
<p><code>\namedstructureheadlocation {...}</code></p> <p>* ABSCHNITT</p>
<p><code>\namedstructureuservariable {...¹} {...²}</code></p> <p>1 ABSCHNITT</p> <p>2 KEY</p>
<p><code>\namedstructurevariable {...¹} {...²}</code></p> <p>1 ABSCHNITT</p> <p>2 KEY</p>
<p><code>\namedtaggedlabeltexts {...¹} {...²} {...³} {...⁴} {...⁵}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p> <p>5 CONTENT</p>
<p><code>\naokraj [...¹...²...³] {...}</code></p> <p> OPT OPT</p> <p>1 odkaz = REFERENCE inherits: \setupmargindata</p> <p>2 inherits: \setupmarginframed</p> <p>3 CONTENT</p>
<p><code>\napravo [...¹...²] {...}</code></p> <p> OPT</p> <p>1 odkaz = REFERENCE inherits: \setupmargindata</p> <p>2 CONTENT</p>

\napravyokraj [...,¹...²...] {...}

- 1 odkaz = REFERENCE
inherits: \setupmargindata
- 2 CONTENT

\nastavbarvu [...]

- * FILE

\nastavbarvy [...,^{*}...]

- * status = start stop
spot = ano ne
expanzen = ano ne
faktor = ano ne
rgb = ano ne
cmyk = ano ne
konverze = ano ne vzdy
pagecolormodel = auto zadny NAME
barvatextu = COLOR
intent = overprint knockout zadny

\nastavbilamista [...,^{*}...]

- * fixuj fixne prizpusobive radek pulradku quarterline zadny male stredni velke implicitni DIMENSION

\nastavblok [...,¹...] [...,²...]

- 1 NAME
- 2 pred = BEFEHL
po = BEFEHL
vnitrni = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR

\nastavbloksekce [...,¹...] [...,²...]

- 1 NAME
- 2 stranka = inherits: \strana
pred = BEFEHL
po = BEFEHL
cislo = ano ne

\nastavbuffer [...,¹...] [...,²...]

- 1 BUFFER
- 2 pred = BEFEHL
po = BEFEHL

\nastavcernelinky [...,^{*}...]

- * sirka = max DIMENSION
vyska = max DIMENSION
hloubka = max DIMENSION
vzdalenost = DIMENSION
n = NUMMER
alternativa = a b
pismo = STYLE BEFEHL
barva = COLOR
typ = mp ano ne
mp = NAME

\nastavcislonadpisu [...¹] [...²]

- 1 ABSCHNITT
- 2 [-+] NUMMER

\nastavcislostrany [...,.*,...]

* inherits: \setupuserpagenumber

\nastavcislovaniodstavcu [...,.*,...]

* status = start stop radek reset
vzdalenost = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

\nastavcislovaniradku [...,¹...] [...,²...] _{OPT}

1 NAME
2 start = NUMMER
krok = NUMMER
metoda = stranka prvni dalsi
konverze = NAME
pokracovat = ano ne
misto = text begin end implicitni vlevo vpravo uvnitr vnejsi ivlevo ivpravo marginalie naokraji
vzdalenost = DIMENSION
zarovnani = uvnitr vnejsi flushleft flushright vlevo vpravo nastred auto
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
marginalie = DIMENSION
sirka = marginalie DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

\nastavcislovanistran [...,.*,...]

* alternativa = jednostranne dvoustranny
stranka = inherits: \strana
strut = ano ne
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
status = start stop
sirka = DIMENSION
misto = zahlavi upati vlevo nastred vpravo ivlevo ivpravo marginalie naokraji naokraji textovahrana
pismo = STYLE BEFEHL
barva = COLOR

\nastavcitaci [...,.*,...]

* inherits: \setupdelimitedtext

\nastavdeleniplvoucichobjektu [...,.*,...]

* pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
radky = auto NUMMER
konverze = NAME

\nastavdelitko [...,.*,...]

* znak = normalni siroce

\nastavdolnitexty [¹...] [²...] [³...] [⁴...] [⁵...] _{OPT OPT OPT OPT OPT}

1 text marginalie hrana
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastaveni [...]

* NAME

\nastaveni {...}

* NAME

\nastavhorejsek [...]¹ [...,...²...,...]
OPT

1 text marginalie hrana

2 inherits: \setuplayoutelement

\nastavhornitexty [...]¹ [...]² [...]³ [...]⁴ [...]⁵
OPT OPT OPT OPT OPT

1 text marginalie hrana

2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavinterakci [...]¹ [...,...²...,...]
OPT

1 NAME

2 status = start stop
pismeno = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
titul = TEXT
podtitulek = COLOR
autor = TEXT
datum = TEXT
keyword = TEXT
zaostreni = standardni ramecek sirka minsirka vyska minvyska prizpusobive tight
menu = zap vyp
fieldlayer = auto NAME
pocitat = REFERENCE
klik = ano ne
obrazovka = normalni novy
stranka = ano ne stranka jmeno auto
otevriakci = REFERENCE
zavriakci = REFERENCE
akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
sadasymbolu = NAME
vyska = DIMENSION
hloubka = DIMENSION
focusoffset = DIMENSION

\nastavinterakci [...]^{*}
OPT

* NAME

\nastavinterakcnilistu [...,¹...] [...,²...]
OPT

```

1  NAME

2  alternativa      = a b c d e f g
   status           = start stop
   prikaz           = CSNAME
   sirka            = DIMENSION
   vyska            = DIMENSION max široky
   hloubka          = DIMENSION max
   vzdalenost       = DIMENSION
   krok             = male stredni velke
   barvapoziadi     = COLOR
   pismeno          = STYLE BEFEHL
   barva            = COLOR
   kontrastnibarva  = COLOR
   symbol           = ano ne
   inherits: \nastavoramovani

```

\nastavinterakcnimenu [...,¹...] [...,²...]
OPT

```

1  NAME

2  alternativa      = vertikalne horizontalne skryte
   category         = NAME
   levyoffset       = prekryv ramecek zadny implicitni DIMENSION
   pravyoffset      = prekryv ramecek zadny implicitni DIMENSION
   offsetvrsku      = prekryv ramecek zadny implicitni DIMENSION
   offsetspodku     = prekryv ramecek zadny implicitni DIMENSION
   maxsirka         = DIMENSION
   maxvyska         = DIMENSION
   itemalign        = vlevo nastred vpravo flushleft flushright nizko vysoko nivy
   status           = start prazdne lokalne
   vlevo            = BEFEHL
   vpravo           = BEFEHL
   vzdalenost       = prekryv DIMENSION
   pred             = BEFEHL
   po               = BEFEHL
   mezi             = BEFEHL
   position         = ano ne
   stredni          = BEFEHL
   pismeno          = STYLE BEFEHL
   barva            = COLOR
   stejnastranka    = ano ne prazdne zadny normalni implicitni
   kontrastnibarva  = COLOR
   inherits: \nastavoramovani

```

\nastavinterakcniobrazovku [...,^{*}...]

```

*  sirka            = prizpusobive max tight DIMENSION
   vyska            = prizpusobive max tight DIMENSION
   zpetnamezera     = DIMENSION
   horoffset        = DIMENSION
   offsethlavicky   = DIMENSION
   svrchnamezera    = DIMENSION
   volba            = prizpusobive max jednostranne dvoustranny zalozka auto zadny implicitni fixne nasirku portrait
                     stranka papier
   copies           = NUMMER
   prodleva         = zadny NUMMER

```


\nastavjazyk [...]¹ [...]²...

OPT

```
1  SPRACHE implicitni
2  implicitni      = SPRACHE
   status          = start stop
   datum           = inherits: \aktualnidatum
   patterns        = FILE
   lefthyphenmin   = NUMMER
   righthyphenmin  = NUMMER
   lefthyphenchar  = NUMMER
   righthyphenchar = NUMMER
   setups          = NAME
   mezerovani      = siroky zhustene
   font            = auto
   text            = TEXT
   limitttext      = TEXT
   hyphen          = TEXT
   compoundhyphen  = TEXT
   leftcompoundhyphen = TEXT
   rightcompoundhyphen = TEXT
   citovatvlevo    = BEFEHL
   citovatvpravo   = BEFEHL
   citacevlevo     = BEFEHL
   citacevpravo    = BEFEHL
   leftspeech      = BEFEHL
   rightspeech     = BEFEHL
   vetavlevo       = BEFEHL
   middlespeech    = BEFEHL
   vetavpravo      = BEFEHL
   midsentence     = BEFEHL
   podvetavlevo    = BEFEHL
   podvetavpravo   = BEFEHL
   faktor          = ano ne
```

\nastavkapitalky [...]¹ [...]²...

OPT

```
1  NAME
2  titul    = ano ne
   sc       = ano ne
   pismeno  = STYLE BEFEHL
```

\nastavkombinovanyseznam [...]¹ [...]²...

```
1  LISTE
2  inherits: \nastavseznam
```

\nastaveniCOMBINEDLIST [...]^{*}...

* inherits: \nastavseznam

instances: obsah

\nastavkomentar [...]¹ [...]²...

OPT

```
1  NAME
2  status      = start stop zadny
   metoda     = normalni skryte
   symbol      = Comment Napoveda Insert Klavesa Newparagraph Note Odstavec Default
   sirka       = prizpusobive DIMENSION
   vyska       = prizpusobive DIMENSION
   hloubka     = prizpusobive DIMENSION
   titul       = TEXT
   podtitulek  = TEXT
   autor       = TEXT
   nx          = NUMMER
   ny          = NUMMER
   barva       = COLOR
   volba       = xml max
   textlayer   = NAME
   misto       = levahrana pravahrana naokraj levyokraj pravyokraj text vysoko zadny
   vzdalenost  = DIMENSION
```

`\nastavkomentarstrany [...,*...]`

* misto = vlevo vpravo vrsek spodek zadny
status = start stop zadny
offset = DIMENSION
vzdalenost = DIMENSION
sirka = DIMENSION
vyska = DIMENSION

`\nastavlegendu [...,*...]`

* inherits: \setuppairedbox

`\nastavmarginalnilinky [...]1 [...]2...`
OPT

1 NUMMER

2 inherits: \setupmarginrule

`\nastavmeziradkovoumezeru [...]1 [...]2...`
OPT

1 NAME

2 radek = DIMENSION
vyska = NUMMER
hloubka = NUMMER
minvyska = NUMMER
mindepth = NUMMER
vzdalenost = DIMENSION
vrsek = NUMMER vyska
spodek = NUMMER
natahnout = NUMMER
shrink = NUMMER

`\nastavmeziradkovoumezeru [...]*...`
OPT

* zap vyp reset auto male stredni velke NUMMER DIMENSION

`\nastavmeziradkovoumezeru [...]*`

* NAME

\nastavnapis [...¹,...] [...²,...]

OPT

```

1  ABSCHNITT
2  frontpartlabel      = NAME
   bodypartlabel       = NAME
   appendixlabel       = NAME
   backpartlabel       = NAME
   expanzen            = ano ne xml
   catcodes            = NAME
   sectionresetset     = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   konverze           = NAME
   sectionstarter      = BEFEHL PROCESSOR->BEFEHL
   sectionstopper      = BEFEHL PROCESSOR->BEFEHL
   sectionset          = NAME
   sectionsegments     = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   referenceprefix     = + - TEXT
   pismeno             = STYLE BEFEHL
   barva               = COLOR
   styltextu           = STYLE BEFEHL
   barvatextu          = COLOR
   stylcisla           = STYLE BEFEHL
   barvacisla          = COLOR
   propojeni           = ABSCHNITT
   vlastnicislo        = ano ne
   beforesection       = BEFEHL
   aftersection        = BEFEHL
   insidesection       = BEFEHL
   zvysujicicislo     = ano ne seznam prazdne
   umistihlavicku      = ano ne skryte prazdne
   cislo               = ano ne
   stranka             = inherits: \strana
   znaceni             = stranka reset
   zahlavi             = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   text                = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   upati               = start stop vysoko zadny normalni prazdne zadneznaceni NAME
   pred                = BEFEHL
   po                  = BEFEHL
   mezi                = BEFEHL
   pokracovat          = ano ne
   zarovnejtitul       = ano ne plvouciobjekt
   meziradkovamezera   = NAME
   interakce           = seznam odkaz
   internalgrid        = NAME
   mrizka              = normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni
                        posledni vysoko jedna nizko zadny radek strut box min max nastred NAME
   zarovnani           = inherits: \nastavzarovnani
   tolerance           = inherits: \nastavtoleranci
   strut               = ano ne
   zaveseni            = radek široky prizpusobive zadny NUMMER
   marginalie          = DIMENSION
   odsadpristi         = ano ne auto
   alternativa         = text odstavec normalni marginalie naokraji vrsek nastred spodek reverse NAME
   sirka               = DIMENSION
   numberwidth         = DIMENSION
   sirkatextu          = DIMENSION
   vzdalenost          = DIMENSION
   predchoziprikaz     = BEFEHL
   prikazpo            = BEFEHL
   prikaz              = \...#1#2
   textovyprikaz       = \...#1
   deeptextcommand     = \...#1
   ciselnyprikaz       = \...#1
   deepnumbercommand   = \...#1

```

\nastavodkazovani [...,*=...,...]

```
*  status      = start stop
   expanzen    = ano ne xml
   autofile    = ano ne
   export      = ano ne
   vlevo       = BEFEHL
   vpravo      = BEFEHL
   sirka       = DIMENSION
   oboustranne = ano ne
   interakce   = popisek text symbol vse
   oddelovac   = BEFEHL
   prefix      = + - TEXT
```

\nastavodsazovani [...,*=...,...]

OPT
* [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION
NAME

\nastavodstavce [...¹] [...²,...] [...³,...,...]
OPT OPT

```
1  NAME
2  kazdy NUMMER
3  n      = NUMBER
   pred   = BEFEHL
   po     = BEFEHL
   sirka  = DIMENSION
   vzdalenost = DIMENSION
   vyska  = DIMENSION prizpusobive
   vrsek  = BEFEHL
   spodek = BEFEHL
   zarovnani = inherits: \nastavzarovnani
   vnitrni  = BEFEHL
   prikaz   = BEFEHL
   linka    = zap vyp
   tloustkalinky = DIMENSION
   barvalinky = COLOR
   pismeno  = STYLE BEFEHL
   barva    = COLOR
```

\nastavodstavce [...¹] [...²,...,...]
OPT

```
1  NAME:NUMMER
2  n      = NUMBER
   pred   = BEFEHL
   po     = BEFEHL
   sirka  = DIMENSION
   vzdalenost = DIMENSION
   vyska  = DIMENSION prizpusobive
   vrsek  = BEFEHL
   spodek = BEFEHL
   zarovnani = inherits: \nastavzarovnani
   vnitrni  = BEFEHL
   prikaz   = BEFEHL
   linka    = zap vyp
   tloustkalinky = DIMENSION
   barvalinky = COLOR
   pismeno  = STYLE BEFEHL
   barva    = COLOR
```

\nastavopis [...,*...]

```
* lichyokraj = DIMENSION
sudamarginalie = DIMENSION
marginalie = ano ne standardni DIMENSION
volba = mp lua xml parsed-xml nested tex context zadny NAME
pismeno = STYLE BEFEHL
barva = COLOR
zarovnnani = inherits: \nastavzarovnnani
radky = ano ne normalni hyphenated
mezera = zap vyp normalni fixne natahnout
keeptogether = ano ne
pred = BEFEHL
po = BEFEHL
strip = ano ne NUMMER
range = NUMMER NAME
tab = ano ne NUMMER
escape = ano ne TEXT PROCESSOR->TEXT
odsadpristi = ano ne auto
pokracovat = ano ne
start = NUMMER
stop = NUMMER
krok = NUMMER
cislovani = soubor radek ne
prazdny = inherits: \preskoc
```

\nastavoramovani [...¹,...] [...²,...]
OPT

```
1 NAME
2 roh = pravouhly zaobleny NUMMER
rohramecku = pravouhly zaobleny NUMMER
rohpozadi = pravouhly zaobleny NUMMER
polomer = DIMENSION
polomerramecku = DIMENSION
polomerpozadi = DIMENSION
hloubka = DIMENSION
hloubkaramecku = DIMENSION
hloubkapozadi = DIMENSION
barvaramecku = COLOR
rameceknahore = zap vyp NAME
ramecekdole = zap vyp NAME
ramecekvlevo = zap vyp NAME
ramecekvpravo = zap vyp NAME
region = ano ne
tloustkalinky = DIMENSION
offsetramecku = DIMENSION
ramecek = zap vyp prekryv zadny
pozadi = popredi barevne NAME
offsetpozadi = ramecek DIMENSION
component = NAME
extras = BEFEHL
foregroundstyle = STYLE BEFEHL
foregroundcolor = COLOR
setups = NAME
offset = implicitni prekryv zadny DIMENSION
sirka = lokalne prizpusobive max siroky fixne DIMENSION
vyska = prizpusobive max siroky DIMENSION
zarovnnani = inherits: \nastavzarovnnani
strut = ano ne zadny lokalne globalne
autostrut = ano ne
misto = vyska podlehloubky vysoko nizko vrsek nastred spodek radek nivy visici drzet rovnice matematika
normalni
autosirka = ano ne sila
radky = NUMMER
vrsek = BEFEHL
spodek = BEFEHL
prazdny = ano ne
profile = NAME
prazdne = ano ne
loffset = DIMENSION
roffset = DIMENSION
toffset = DIMENSION
boffset = DIMENSION
orientation = NUMMER
```

\nastavorez [...,*...]

```
* status      = start stop
sirka         = DIMENSION
vyska        = DIMENSION
hoffset      = DIMENSION
voffset      = DIMENSION
x            = NUMMER
y            = NUMMER
nx           = NUMMER
ny           = NUMMER
sx           = NUMMER
sy           = NUMMER
levyoffset   = DIMENSION
pravyoffset  = DIMENSION
offsetvrsku  = DIMENSION
offsetspodku = DIMENSION
mp           = NAME
n            = NUMMER
offset       = DIMENSION
```

\nastavotoceni [...,*...]

```
* misto = prizpusobive široky podlehloubky vysoko nastred implicitni normalni
rotace  = vlevo vpravo uvnitr vnejsi NUMMER
inherits: \nastavoramovani
```

\nastavpaletu [...]

```
* NAME
```

\nastavplvouciobjekt [...¹,...] [...²,...]

1 SINGULAR

```
2 odsadpristi      = ano ne auto
implicitni         = inherits: \placefloat
fallback           = inherits: \placefloat
vnitrni            = BEFEHL
kriterium          = DIMENSION
metoda             = NUMMER
sidemethod         = NUMMER
textmethod         = NUMMER
sidealign          = vyska podlehloubky radek pulradku mrizka normalni
lokalne            = ano ne
prikaz             = \...#1
availablewidth     = DIMENSION
availableheight    = DIMENSION
minsirka           = DIMENSION
maxsirka           = DIMENSION
misto              = vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin
                   inneredge outeredge zpetnamezera cutspace levyokraj pravyokraj levahrana pravahrana
vzdalenostlevehookraje = DIMENSION
vzdalenostpravehookraje = DIMENSION
levyokraj          = DIMENSION
pravyokraj         = DIMENSION
innermargin        = DIMENSION
outermargin        = DIMENSION
bottombefore       = BEFEHL
bottomafter        = BEFEHL
mezerapred         = zadny inherits: \preskoc
mezeraza           = zadny inherits: \preskoc
sirka              = DIMENSION
vyska              = DIMENSION
offset             = DIMENSION zadny prekryv
bocnimezerapred    = zadny inherits: \preskoc
bocnimezeraza      = zadny inherits: \preskoc
marginalie         = DIMENSION
nvrsek             = DIMENSION
nspodek            = DIMENSION
krok               = male stredni velke radek podlehloubky
nradky             = NUMMER
cache              = ano ne
```

\nastavpodcislostrany [...,*...]

```
* inherits: \setupcounter
```

`\nastavpole` [¹...] [²...,...]_{OPT} [³...,...]_{OPT} [⁴...,...]_{OPT} [⁵...,...]

- 1 NAME
- 2 reset popisek ramecek horizontalne vertikalne
- 3 inherits: \setupfieldtotalframed
- 4 inherits: \setupfieldlabelframed
- 5 inherits: \setupfieldcontentframed

`\nastavpolozky` [¹...,...]_{OPT} [²...,...]

- 1 NAME
- 2
 - alternativa = vlevo vpravo vrsek spodek naokraji
 - sirkatextu = DIMENSION
 - sirka = DIMENSION
 - vzdalenost = DIMENSION
 - symbol = zadny NAME
 - zarovnani = vlevo nastred vpravo flushleft flushright uvnitr vnejsi marginalie
 - textalign = vlevo nastred vpravo flushleft flushright uvnitr vnejsi
 - n = NUMMER
 - pred = BEFEHL
 - po = BEFEHL
 - mezi = BEFEHL

`\nastavpopisek` [¹...,...]_{OPT} [²...,...]

- 1 NAME
- 2 inherits: \setupfloatcaption

`\nastavpozadi` [¹...,...]_{OPT} [²...,...]

- 1 NAME
- 2
 - status = start stop
 - levyoffset = DIMENSION
 - pravyoffset = DIMENSION
 - offsetvrsku = DIMENSION
 - offsetspodku = DIMENSION
 - pred = BEFEHL
 - po = BEFEHL
 - inherits: \nastavoramovani

`\nastavpozadi` [¹...,...]_{OPT} [²...,...]

- 1 papir stranka levastranka pravastranka text skryte
- 2
 - status = start stop
 - inherits: \nastavoramovani

`\nastavprechodstrany` [...]

- * reset auto start nahodny NUMMER

`\nastavpreskok` [...]_{OPT}

- * inherits: \vspacing

`\nastavprogramy` [...]_{OPT}

- * pismo = STYLE BEFEHL
- * barva = COLOR

`\nastavradkovani` [...]_{OPT}

- * fixne zhustene siroky

\nastavradky [...¹,...] [...²,...]
 OPT

```
1  NAME
2  volba      = zhustene
   pred       = BEFEHL
   po         = BEFEHL
   mezi       = BEFEHL
   odsazovani = inherits: \nastavodsazovani
   zarovnani  = inherits: \nastavzarovnani
   mezero     = ano zap vyp fixne implicitni
   prikaz     = BEFEHL
   pismeno    = STYLE BEFEHL
   barva      = COLOR
   vlevo     = BEFEHL
   vpravo     = BEFEHL
```

\nastavrejstrik [...¹] [...²,...]
 OPT

```
1  NAME NAME:NUMBER
2  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda               = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress             = ano ne vse
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
   pageprefixconnector  = BEFEHL
   pageprefix           = ano ne
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   maxsirka             = DIMENSION
   indikator            = ano ne
   pred                 = BEFEHL
   po                   = BEFEHL
   prikaz               = \...##1
   textovyprikaz        = \...##1
   deeptextcommand      = \...##1
   strankovyprikaz      = \...##1
   vzdalenost           = DIMENSION
   interakce            = text cislostranky
   cislostranky         = ano ne
   symbol               = a n zadny 1 2 BEFEHL
   language             = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismeno              = STYLE BEFEHL
   barva                = COLOR
   styltextu            = STYLE BEFEHL
   barvatextu           = COLOR
   stylstranky          = STYLE BEFEHL
   barvastranky         = COLOR
   n                    = NUMBER
   rovnovaha            = ano ne
   zarovnani            = inherits: \nastavzarovnani
   numberorder          = ciska
```


\nastavrejstrik [...,¹...] [...,²...] [...,³...,...]
OPT OPT

```

1  NAME
2  NUMMER
3  referencemethod      = vpred
    expanzen            = ano ne xml
    vlastnicislo        = ano ne
    xmlsetup            = NAME
    alternativa         = a b A B
    metoda              = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
    compress            = ano ne vse
    kriterium           = lokalne text aktualni predchozi vse ABSCHNITT
    pageprefixseparatorset = BEFEHL
    pageprefixconversionset = NAME
    pageprefixstarter   = BEFEHL PROCESSOR->BEFEHL
    pageprefixstopper   = BEFEHL PROCESSOR->BEFEHL
    pageprefixset       = NAME
    pageprefixsegments  = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:vse
    pageprefixconnector = BEFEHL
    pageprefix          = ano ne
    pageseparatorset    = NAME
    pageconversionset    = NAME
    pagestarter         = BEFEHL PROCESSOR->BEFEHL
    pagestopper         = BEFEHL PROCESSOR->BEFEHL
    pagesegments        = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
    maxsirka            = DIMENSION
    indikator           = ano ne
    pred                = BEFEHL
    po                  = BEFEHL
    prikaz              = \...##1
    textovyprikaz       = \...##1
    deeptextcommand     = \...##1
    strankovyprikaz     = \...##1
    vzdalenost          = DIMENSION
    interakce           = text cislostranky
    cislostranky        = ano ne
    symbol              = a n zadny 1 2 BEFEHL
    language            = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
    pismeno             = STYLE BEFEHL
    barva               = COLOR
    styltextu           = STYLE BEFEHL
    barvatextu          = COLOR
    stylstranky         = STYLE BEFEHL
    barvastranky        = COLOR
    n                   = NUMBER
    rovnovaha           = ano ne
    zarovnani           = inherits: \nastavzarovnani
    numberorder         = cisla

```

\nastaveniREJSTRIK [...,¹...] [...,²...,...]
OPT

```

1  NUMMER
2  inherits: \nastavrejstrik

```

instances: rejstrik

\nastavsadusymbolu [...*...]

```

*  NAME

```

\nastavseznam [...,¹...] [...,²...,...]
OPT

```

1  LISTE

2  status          = start stop
   misto           = zadny zde
   typ             = simple prikaz userdata
   kriterium       = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text
                   aktualni SECTIONBLOCK:aktualni zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT
                   SECTIONBLOCK:ABSCHNITT

   seznam          = NAME
   sirka           = prizpusobive siroky auto DIMENSION
   vyska           = prizpusobive siroky DIMENSION
   hloubka         = prizpusobive siroky DIMENSION
   symbol          = jedna dve tri zadny implicitni
   popisek         = ano ne zadny NAME
   starter         = BEFEHL
   predel         = BEFEHL
   prikaz          = \...#1#2#3
   ciselnyprikaz   = \...#1
   textovyprikaz   = \...#1
   strankovyprikaz = \...#1
   cislostranky    = ano ne vzdy
   cislonadpisu    = ano ne vzdy
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   marginalie      = zadny DIMENSION
   vzdalenost      = zadny DIMENSION
   zarovnejtitul   = ano ne
   numberalign     = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   zarovnnani      = inherits: \nastavzarovnnani
   zaveseni        = ano ne
   vlevo          = BEFEHL
   vpravo          = BEFEHL
   interakce       = ano ne vse cislo text titul stranka cislooddilu cislostranky
   limittext       = ano ne TEXT
   pismeno         = STYLE BEFEHL
   barva          = COLOR
   stylcisla       = STYLE BEFEHL
   barvacisla      = COLOR
   styltextu       = STYLE BEFEHL
   barvatextu      = COLOR
   stylstranky     = STYLE BEFEHL
   barvastranky    = COLOR
   odkaz          = NUMMER
   extras          = NAME
   order           = prikaz vse titul
   alternativa     = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne
                   vertikalne NAME

   maxsirka        = DIMENSION
   pageprefix      = ano ne
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset    = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                   ABSCHNITT:vse
   pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
   pageconversionset = NAME
   pagestarter     = BEFEHL PROCESSOR->BEFEHL
   pagestopper     = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \nastavoramovani

```

\nastavsirkucary [...]

* male stredni velke DIMENSION

`\nastavsloupce [...,.*,...]`

```
*  n          = NUMMER
   vzdalenost = DIMENSION
   volba      = pozadi
   offset     = DIMENSION
   prikaz     = \...##1
   vyska      = DIMENSION
   smer       = vlevo vpravo
   rovnovaha  = ano ne
   zarovnani  = setupalign
   tolerance  = setuptolerance
   prazdny    = inherits: \preskoc
   nvrsek     = NUMMER
   linka      = zap vyp BEFEHL
```

`\nastavspodek [...1][...2...]`
OPT

```
1  text marginalie hrana
2  inherits: \setuplayoutelement
```

`\nastavsynonyma [...1,...][...2...]`
OPT

```
1  SINGULAR
2  expanzen      = ano ne xml
   alternativa   = prvni posledni normalni NAME
   dalsi         = BEFEHL
   prikaz        = \...##1##2##3
   textovyprikaz = \...##1
   synonymcommand = \...##1
   language      = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
   metoda        = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   kriterium     = aktualni predchozi lokalne text vse ABSCHNITT
   pismo         = STYLE BEFEHL
   barva         = COLOR
   styltextu     = STYLE BEFEHL
   barvatextu    = COLOR
   stylsynonyma  = STYLE BEFEHL
   barvasynonyma = COLOR
```

`\nastavtabelaci [...1][...2][...3...]`
OPT OPT

```
1  NAME
2  NAME
3  inherits: \setuptabulation
```

`\nastavtabulky [...,.*,...]`

```
*  text          = DIMENSION max
   split         = ano ne opakovat auto
   ramecek       = zap vyp
   NL            = inherits: \preskoc
   VL            = male stredni velke zadny NUMMER
   HL            = male stredni velke zadny NUMMER
   vzdalenost    = male stredni velke zadny
   zarovnani     = vlevo nastred vpravo
   prikazy       = BEFEHL
   zakladnifont  = inherits: \nastavzakladnifont
   tloustkalinky = DIMENSION
   vyska         = strut NUMMER
   hloubka       = strut NUMMER
```

`\nastavtenkelinky [...,*...]`

```
*   vyska           = max DIMENSION
    hloubka         = max DIMENSION
    pozadi          = barevne
    ramecek         = zap vyp
    tloustkalinky   = DIMENSION
    alternativa     = a b c zadny
    barvapoziadi    = COLOR
    barva           = COLOR
    meziradkovamezera = male stredni velke NUMMER
    pred            = BEFEHL
    po              = BEFEHL
    mezi           = BEFEHL
    n              = NUMMER
```

`\nastavtext [...]1 [...,*...]2`
OPT

```
1   text marginalie hrana
2   inherits: \setuplayoutelement
```

`\nastavtexthlavicky [...]1 [...,*...]2`
OPT

```
1   SPRACHE
2   KEY = VALUE
```

`\nastavtextovelinky [...,*...]`

```
*   pred           = BEFEHL
    po             = BEFEHL
    mezi           = BEFEHL
    tloustkalinky  = DIMENSION
    misto          = vlevo naokraji
    pismeno        = STYLE BEFEHL
    barva          = COLOR
    barvalinky     = COLOR
    sirka          = DIMENSION
    vyska          = DIMENSION
    vzdalenost     = DIMENSION
    korekcehloubky = zap vyp
    zakladnifont   = inherits: \nastavzakladnifont
```

`\nastavtextpopisku [...]1 [...,*...]2`
OPT

```
1   SPRACHE
2   KEY = VALUE
```

`\nastaveniPOPISEKtext [...]1 [...,*...]2`
OPT

```
1   SPRACHE
2   KEY = VALUE
```

`instances: hlavicka popisek mathlabel taglabel jednotka operator prefix suffix btxlabel`

`\nastavtexttexty [...]1 [...]2 [...]3 [...]4 [...]5`
OPT OPT OPT OPT OPT

```
1   text marginalie hrana
2   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5   datum cislostranky BESCHRIFTUNG TEXT BEFEHL
```

\nastavtextyupati [...] [...] [...] [...] [...] ¹ ² ³ ⁴ ⁵
OPT OPT OPT OPT OPT

- 1 text marginalie hrana
- 2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavtextyzahlavi [...] [...] [...] [...] [...] ¹ ² ³ ⁴ ⁵
OPT OPT OPT OPT OPT

- 1 text marginalie hrana
- 2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\nastavtoleranci [...]*,...]

- * horizontalne vertikalne velmistriktni striktni tolerantni velmitolerantni mezera natahnout

\nastavtrideni [...,¹...] [...,...²...] OPT

- 1 SINGULAR
- 2

expanzen	=	ano ne xml
alternativa	=	prvni posledni normalni NAME
dalsi	=	BEFEHL
prikaz	=	\...##1##2##3
textovyprikaz	=	\...##1
synonymcommand	=	\...##1
language	=	implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
metoda	=	implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
kriterium	=	aktualni predchozi lokalne text vse ABSCHNITT
pismeno	=	STYLE BEFEHL
barva	=	COLOR
styltextu	=	STYLE BEFEHL
barvatextu	=	COLOR
stylsynonyma	=	STYLE BEFEHL
barvasynonyma	=	COLOR

\nastavtype [...,¹...] [...,...²...] OPT

- 1 NAME
- 2

volba	=	mp lua xml parsed-xml nested tex context zadny NAME
prikaz	=	CSNAME
vlevo	=	BEFEHL
vpravo	=	BEFEHL
tab	=	ano ne NUMMER
compact	=	absolutni posledni vse
escape	=	ano ne TEXT PROCESSOR->TEXT
pismeno	=	STYLE BEFEHL
barva	=	COLOR
radky	=	ano ne normalni hyphenated
mezera	=	zap vyp normalni fixne natahnout

\nastavumisteniprotejsku [...,...*...] ^{*}

- * status = start stop
- pred = BEFEHL
- po = BEFEHL
- mezi = BEFEHL

\nastavumistovani [...,¹...] [...,²...,...]
OPT

```
1  NAME

2  offset      = ano ne
   jednotka    = ex em pt in cm mm sp bp pc dd cc nc
   status      = start prekryv
   xoffset     = DIMENSION
   yoffset     = DIMENSION
   xkrok       = absolutni relativni
   ykrok       = absolutni relativni
   xmeritko    = NUMMER
   ymeritko    = NUMMER
   xfaktor     = NUMMER
   yfaktor     = NUMMER
   faktor      = NUMMER
   meritko     = NUMMER
```

\nastavupati [...,¹...] [...,²...,...]
OPT

```
1  text marginalie hrana

2  inherits: \setuplayoutelement
```

\nastavupravu [...,¹...] [...,²...,...]
OPT

```
1  NAME

2  stranka      = inherits: \strana
   prikaz       = BEFEHL
   sirka        = DIMENSION
   vyska        = DIMENSION
   zarovnani    = inherits: \nastavzarovnani
   setups       = NAME
   vrsek        = BEFEHL
   spodek       = BEFEHL
   pred         = BEFEHL
   po           = BEFEHL
   misto        = vrsek
   odkaz        = REFERENCE
   pagestate    = start stop
   statuszahlavi = start stop vysoko prazdne zadny normalni
   statusupati  = start stop vysoko prazdne zadny normalni
   statusvrsku  = start stop vysoko prazdne zadny normalni
   statusspodku = start stop vysoko prazdne zadny normalni
   statutextu   = start stop vysoko prazdne zadny normalni
   oboustranne  = ano ne prazdne
   pismo        = inherits: \value-style
   barva        = COLOR
```

\nastavurl [...,^{*}...,...]

```
*  pismo        = STYLE BEFEHL
   barva        = COLOR
```

\nastavusporadani [...,^{*}...]

```
*  zablokovat zrcadleno dvoustranny negativ 90 180 270 reset pozadi normalni 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP
   2UP 2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12
   DOUBLEWINDOW 1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME
```

\nastavvelikostpapiru [...]¹ [...]²...

OPT

```
1 NAME
2 vrsek = BEFEHL
  spodek = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  metoda = normalni zadny NAME
  meritko = NUMMER
  nx = NUMMER
  ny = NUMMER
  dx = DIMENSION
  dy = DIMENSION
  sirka = DIMENSION
  vyska = DIMENSION
  svrchnimezera = DIMENSION
  zpetnamezera = DIMENSION
  offset = DIMENSION
  stranka = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
  papir = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
  volba = prizpusobive max
  vzdalenost = DIMENSION
```

\nastavvelikostpapiru [...]¹ [...]²...

OPT

OPT

```
1 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
2 reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
```

\nastavvsechnapole [...]¹ [...]²... [...]³... [...]⁴...

OPT

OPT

OPT

```
1 reset popiscek ramecek horizontalne vertikalne
2 inherits: \setupfieldtotalframed
3 inherits: \setupfieldlabelframed
4 inherits: \setupfieldcontentframed
```

\nastavvycty [...]¹ [...]²...

OPT

```
1 NAME NAME:NUMMER
2 inherits: \setupitemgroup
```

\nastavvyplnovelinky [...]^{*}...

```
* pred = BEFEHL
  po = BEFEHL
  n = NUMMER
  meziradkovamezera = male stredni velke NUMMER
  vzdalenost = DIMENSION
  sirka = prizpusobive siroky DIMENSION
  oddelovac = BEFEHL
  pismo = STYLE BEFEHL
  barva = COLOR
```

\nastavvyplnoveradky [...]^{*}...

```
* pred = BEFEHL
  po = BEFEHL
  marginalie = DIMENSION
  sirka = DIMENSION
  vzdalenost = DIMENSION
  tloustkalinky = DIMENSION
  barva = COLOR
```

\nastavvzhled [¹...] [²..._{OPT}...]

```

1  NAME

2  status          = start stop normalni opakovat
   marginalie      = DIMENSION
   hrana           = DIMENSION
   vzdalenostkraje = DIMENSION
   vzdalenosthrany = DIMENSION
   vzdalenostlevehrapy = DIMENSION
   vzdalenostpravehrany = DIMENSION
   vzdalenostlevehookraje = DIMENSION
   vzdalenostpravehookraje = DIMENSION
   vzdalenostvrsku = DIMENSION
   vzdalenostzahlavi = DIMENSION
   vzdalenostupati = DIMENSION
   vzdalenostspodku = DIMENSION
   prednastaveni   = NAME
   levyokraj       = DIMENSION
   pravyokraj      = DIMENSION
   levahrana       = DIMENSION
   pravahrana      = DIMENSION
   zahlavi        = DIMENSION
   upati           = DIMENSION
   vrsek           = DIMENSION
   spodek          = DIMENSION
   zpetnamezera    = DIMENSION
   svrchnamezera   = DIMENSION
   setups          = NAME
   cutspace        = DIMENSION
   sirka           = DIMENSION nastred prizpusobive
   bottomspace     = DIMENSION
   radky           = NUMBER
   vyska           = DIMENSION nastred prizpusobive
   horoffset       = DIMENSION
   offsethlavicky  = DIMENSION
   sloupce         = NUMBER
   vzdalenostsloupcu = DIMENSION
   metoda         = implicitni normalni NAME
   misto           = vlevo nastred vpravo vrsek spodek jednostranne dvoustranny
   sirkatextu      = DIMENSION
   vyskatextu      = DIMENSION
   nx              = NUMBER
   ny              = NUMBER
   dx              = DIMENSION
   dy              = DIMENSION
   meritko         = NUMBER
   sx              = NUMBER
   sy              = NUMBER
   znaceni         = zap vyp stranka prazdne barevne jedna dve ctyri
   mrizka          = ano ne vyp
   textdistance    = DIMENSION
   alternativa     = implicitni normalni zlom NAME
   clipoffset      = DIMENSION
   cropoffset      = DIMENSION
   trimoffset      = DIMENSION
   bleedoffset     = DIMENSION
   artoffset       = DIMENSION

```

\nastavvzhled [...]

* reset NAME

\nastavzahlavi [¹...] [²..._{OPT}...]

```

1  text marginalie hrana

2  inherits: \setuplayoutelement

```

\nastavzakladnifont [..._{OPT}...]

* DIMENSION NAME globalne reset x xx male velke script scriptscript rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke

`\nastavzarovnnani [...*...]`

* široky siroce spodek vyska radek vysoko nizko nivы flushright flushleft nastred ano ne sirka normalni reset uvnitr vnejsi flushinner flushouter vlevo vpravo center zablockovat posledni end odstavec lefttoright righttoleft l2r r2l tabulka lesshyphenation morehyphenation visici nothanging hz fullhz nohz hyphenated nothyphenated tolerantni velmitolerantni natahnout extremestretch finalni 2*final 3*final 4*final

`\nastavznaceni [...1...]OPT [...,...2...]`

1 BESCHRIFTUNG
2 status = start stop
expanden = ano ne
oddelovac = BEFEHL
filtercommand = \...\##1

`\nastavzuzeni [...1...]OPT [...,...2...]`

1 NAME
2 vlevo = DIMENSION
stredni = DIMENSION
vpravo = DIMENSION
implicitni = [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
pred = BEFEHL
po = BEFEHL

`\nastrane [...]`

* REFERENCE

`\nastred ...`

* CHARACTER

`\naturalhbox [...1...]{...2...}OPT`

1 TEXT
2 CONTENT

`\naturalhpack [...1...]{...2...}OPT`

1 TEXT
2 CONTENT

`\naturalvbox [...1...]{...2...}OPT`

1 TEXT
2 CONTENT

`\naturalvcenter [...1...]{...2...}OPT`

1 TEXT
2 CONTENT

`\naturalvpack [...1...]{...2...}OPT`

1 TEXT
2 CONTENT

`\naturalvtop [...1...]{...2...}OPT`

1 TEXT
2 CONTENT

<code>\naturalwd ...</code> * CSNAME NUMMER
<code>\negatecolorbox ...</code> * CSNAME NUMMER
<code>\negated {...}</code> * TEXT
<code>\negthinspace</code>
<code>\nejakyradek [...]</code> * REFERENCE
<code>\nekde {...} {...} [...]</code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\newattribute *</code> * CSNAME
<code>\newcatcodetable *</code> * CSNAME
<code>\newcounter *</code> * CSNAME
<code>\newevery \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> * NAME
<code>\newsignal *</code> * CSNAME
<code>\newsystemmode {...}</code> * NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>

<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...]</code> ¹ ² <small>OPT</small> <code>[...]</code> 1 NAME 2 NUMMER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\dalsiPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]</code> ¹ ² <code>[...]</code> 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\neznamo</code>
<code>\nihongo</code>
<code>\nivy [...]</code> ¹ ² ³ <small>OPT</small> <code>{...}</code> <code>{...}</code> 1 vlevo vpravo 2 CONTENT 3 CONTENT
<code>\nizky {...}</code> * CONTENT
<code>\NIZKO {...}</code> * CONTENT instances: unitslow
<code>\nobar {...}</code> * CONTENT

<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \¹... {²...}</code> 1 CSNAME 2 CONTENT
<code>\nofffigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,¹...¹...,...] {²...}</code> 1 inherits: \nastavoramovani 2 CONTENT
<code>\normalizebodyfontsize \¹... {²...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>

`\normalizefontdepth \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontheight \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontline \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontwidth \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizetextdepth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextheight {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextline {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalni`

`\normaltypeface`

$\backslash\text{notesymbol}$ [¹ ...] [² ...] <small>OPT</small> 1 NAME 2 REFERENCE
$\backslash\text{notragged}$
$\backslash\text{ntimes}$ {...} {...} 1 TEXT 2 NUMMER
$\backslash\text{numberofpoints}$ {...} * DIMENSION
$\backslash\text{obeydepth}$
$\backslash\text{objectdepth}$
$\backslash\text{objectheight}$
$\backslash\text{objectmargin}$
$\backslash\text{objectwidth}$
$\backslash\text{obox}$ {...} * CONTENT
$\backslash\text{obrazovka}$ [...,*...] <small>OPT</small> * inherits: \strana
$\backslash\text{odkaz}$ [..., ¹ ...] {... ² } 1 REFERENCE 2 TEXT
$\backslash\text{odkaznastranu}$ [...,*...] * REFERENCE
$\backslash\text{odkaznatext}$ [..., ¹ ...] {... ² } 1 REFERENCE 2 TEXT
$\backslash\text{odkazujici}$ (... ¹ ,...) (... ² ,...) [... ³ .] 1 POSITION 2 POSITION 3 REFERENCE
$\backslash\text{offset}$ [..., ¹ ... ² ...] <small>OPT</small> 1 inherits: \setupoffset 2 CONTENT

$\backslash\text{offsetbox}$ [$\dots\overset{1}{=}\dots$] $\backslash\overset{2}{\dots}$ $\{\overset{3}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{setupoffsetbox}$ 2 CSNAME 3 CONTENT
$\backslash\text{onedigitrounding}$ $\{\dots\}$ * NUMMER
$\backslash\text{operatorlanguage}$
$\backslash\text{operatorortext}$ $\{\dots\}$ * KEY
$\backslash\text{opis}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{nastavtype}$ 2 CONTENT
$\backslash\text{opissoubor}$ [$\overset{1}{\dots}$] [$\dots\overset{2}{=}\dots$] $\{\overset{3}{\dots}\}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{nastavopis}$ 3 FILE
$\backslash\text{opis}$ [$\dots\overset{1}{=}\dots$] $\ll\overset{2}{\dots}\gg$ <small>OPT</small> 1 inherits: $\backslash\text{nastavtype}$ 2 ANGLES
$\backslash\text{OPIS}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{nastavtype}$ 2 CONTENT
$\backslash\text{OPIS}$ [$\dots\overset{1}{=}\dots$] $\ll\overset{2}{\dots}\gg$ <small>OPT</small> 1 inherits: $\backslash\text{nastavtype}$ 2 ANGLES
$\backslash\text{orarovani}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{nastavorarovani}$ 2 CONTENT
$\backslash\text{FRAMED}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{nastavorarovani}$ 2 CONTENT instances: unframed fitfieldframed
$\backslash\text{orarovanytext}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{setupframedtext}$ 2 CONTENT

$\backslash ORAMOVANYTEXT$ [\dots , \dots ^{$\frac{1}{2}$} \dots , \dots] { \dots } <small>OPT</small> 1 inherits: \setupframedtext 2 CONTENT instances: oramovanytext
$\backslash ordinaldaynumber$ { \dots } * NUMMER
$\backslash ordinalstr$ { \dots } * TEXT
$\backslash oref$ [\dots] * REFERENCE
$\backslash orez$ [\dots , \dots ^{$\frac{1}{2}$} \dots , \dots] { \dots } <small>OPT</small> 1 inherits: \nastavorez 2 CONTENT
$\backslash ornamenttext$ [\dots , \dots ^{$\frac{1}{2}$} \dots , \dots] [\dots , \dots ^{$\frac{2}{2}$} \dots , \dots] { \dots } { \dots } <small>OPT</small> 1 alternativa = a b inherits: \setupcollector 2 pismeno = STYLE BEFEHL barva = COLOR inherits: \nastavoramovani 3 TEXT 4 CONTENT
$\backslash ornamenttext$ [\dots ^{$\frac{1}{2}$}] { \dots } { \dots } 1 NAME 2 TEXT 3 CONTENT
$\backslash ornamenttext$ [\dots , \dots ^{$\frac{1}{2}$} \dots , \dots] [\dots , \dots ^{$\frac{2}{2}$} \dots , \dots] { \dots } { \dots } <small>OPT</small> 1 alternativa = a b inherits: \setuplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
$\backslash ORNAMENT$ { \dots } { \dots } 1 TEXT 2 CONTENT
$\backslash otocit$ [\dots , \dots ^{$\frac{1}{2}$} \dots , \dots] { \dots } <small>OPT</small> 1 inherits: \nastavotoceni 2 CONTENT
$\backslash outputfilename$

$\backslash\text{outputstreambox}$ [...] * NAME
$\backslash\text{outputstreamcopy}$ [...] * NAME
$\backslash\text{outputstreamunvbox}$ [...] * NAME
$\backslash\text{outputstreamunvcopy}$ [...] * NAME
$\backslash\text{over}$ [...] * REFERENCE
$\backslash\text{overbartext}$ { ¹ .} { ² .} 1 TEXT 2 TEXT
$\backslash\text{overbarunderbar}$ {...} * TEXT
$\backslash\text{overbrace}$ {...} * TEXT
$\backslash\text{overbracetext}$ { ¹ .} { ² .} 1 TEXT 2 TEXT
$\backslash\text{overbraceunderbrace}$ {...} * TEXT
$\backslash\text{overbracket}$ {...} * TEXT
$\backslash\text{overbrackettext}$ { ¹ .} { ² .} 1 TEXT 2 TEXT
$\backslash\text{overbracketunderbracket}$ {...} * TEXT
$\backslash\text{overlaybutton}$ [...] * REFERENCE
$\backslash\text{overlaybutton}$ {...} * REFERENCE

<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [..¹..] [..²..]</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overleftarrow {...}</code> * TEXT
<code>\overleftharpoontdown {...}</code> * TEXT
<code>\overleftharpoonup {...}</code> * TEXT
<code>\overleftrightarrow {...}</code> * TEXT
<code>\overloaderror</code>
<code>\overparent {...}</code> * TEXT
<code>\overparenttext {...¹} {...²}</code> 1 TEXT 2 TEXT
<code>\overparentunderparent {...}</code> * TEXT
<code>\overrightarrow {...}</code> * TEXT

$\backslash\overrightharpoonpoondown \{...\}$ * TEXT
$\backslash\overrightharpoonup \{...\}$ * TEXT
$\backslashoverset {.^1.} {.^2.}$ 1 TEXT 2 TEXT
$\backslashovertwoheadleftarrow \{...\}$ * TEXT
$\backslashovertwoheadrightarrow \{...\}$ * TEXT
$\backslashoznaceni (...^{.1},...) (...^{.2},...) [...^{.3}...^{.4}] \{...\}$ 1 POSITION 2 POSITION 3 inherits: \nastavoramovani 4 TEXT
$\backslashPDFcolor \{...\}$ * NAME
\backslashPDFETEX
\backslashPDFTEX
\backslashPICTEX
\backslashPiCTeX
$\backslashPointsToBigPoints \{.^1.\} \backslash.^2..$ 1 DIMENSION 2 CSNAME
$\backslashPointsToReal \{.^1.\} \backslash.^2..$ 1 DIMENSION 2 CSNAME
$\backslashPointsToWholeBigPoints \{.^1.\} \backslash.^2..$ 1 DIMENSION 2 CSNAME
\backslashPPCHTEX
\backslashPPCHTeX

\PRAGMA
\PtToCm {...} * DIMENSION
\pagearea [¹ ...] [² ...] [³ ...] <div style="margin-left: 100px;">OPT OPT</div> 1 vrsek zahlaví text upatí spodek 2 text marginalie hrana 3 vlevo vpravo lefttext middletext righttext
\pagebreak [...;...] <div style="margin-left: 100px;">OPT</div> * prázdné zahlaví upatí dummy rámeček NUMBER +NUMBER implicitní reset zablokovat ano ne zlom prázdný nastavení vysoká priorita vlevo vpravo sude liché čtyřnásobný poslední poslední strana start stop NAME
\pagefigure [¹ ...] [..., ² ...] <div style="margin-left: 100px;">OPT OPT</div> 1 FILE 2 inherits: \setupexternalfigure
\pagegridspanwidth {...} * NUMBER
\pageinjection [¹ ...] [..., ² ...] <div style="margin-left: 100px;">OPT OPT</div> 1 NAME 2 KEY = VALUE
\pageinjection [..., ¹ ...] <div style="margin-left: 100px;">OPT</div> 1 inherits: \setuppageinjection 2 KEY = VALUE
\pagestaterealpage { ¹ ...} { ² ...} 1 NAME 2 NAME NUMBER
\paletsize
\PARAGRAPHS
\pdfactualtext { ¹ ...} { ² ...} 1 CONTENT 2 TEXT
\pdfbackendactualtext { ¹ ...} { ² ...} 1 CONTENT 2 TEXT
\pdfbackendcurrentresources

<p><code>\pdfbackendsetcatalog {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetcolorspace {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsettextgstate {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetinfo {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\percent</code></p>

$\backslash\text{percentdimen}$ $\{.^1.\}$ $\{.^2.\}$ 1 DIMENSION CSNAME 2 DIMENSION NUMMER
$\backslash\text{permitcaretescape}$
$\backslash\text{permitcircumflexescape}$
$\backslash\text{permitspacesbetweenegroups}$
$\backslash\text{persiandecimals}$ $\{.^*\}$ * NUMMER
$\backslash\text{persiannumerals}$ $\{.^*\}$ * NUMMER
$\backslash\text{phantom}$ $\{.^*\}$ * CONTENT
$\backslash\text{phantombox}$ $[...^*...]$ * sirka = DIMENSION * vyska = DIMENSION * hloubka = DIMENSION
$\backslash\text{pickupgroupedcommand}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 BEFEHL 2 BEFEHL 3 BEFEHL
$\backslash\text{pis}$ $[...^1...]$ $\{.^2.\}$ <small>OPT</small> 1 inherits: $\backslash\text{nastavtype}$ 2 CONTENT
$\backslash\text{pis}$ $[...^1...]$ $\langle\langle.^2.\rangle\rangle$ <small>OPT</small> 1 inherits: $\backslash\text{nastavtype}$ 2 ANGLES
$\backslash\text{placeattachments}$
$\backslash\text{placebtxrendering}$ $[...^1]$ $[...^2...]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupbtxrendering}$
$\backslash\text{placecitation}$ $[.^*]$ * REFERENCE
$\backslash\text{placecomments}$

<p><code>\placecontent [...,[*]...,...]</code> <small>OPT</small></p> <p>* inherits: \nastavseznam</p>
<p><code>\placecurrentformulanumber</code></p>
<p><code>\placedbox {...}</code></p> <p>* CONTENT</p>
<p><code>\placefloat [...,¹...] [...,²...,...]_{OPT} [...,³...,...]_{OPT} {...,⁴} {...,⁵}</code></p> <p>1 SINGULAR</p> <p>2 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placefloatwithsetups [...,¹...] [...,²...,...]_{OPT} [...,³...,...]_{OPT} {...,⁴} {...,⁵}</code></p> <p>1 NAME</p> <p>2 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\umistiPLVOUCIOBJEKT [...,¹...,...]_{OPT} [...,²...,...]_{OPT} {...,³} {...,⁴}</code></p> <p>1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p> <p>instances: chemical figure table intermezzo graphic</p>
<p><code>\umisti [...,¹...,...]_{OPT} [...,²...,...]_{OPT}</code></p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective odkaz = REFERENCE</p> <p>2 KEY = VALUE</p>

`\placeframed [...]1 [...]2...OPT {...}3`

1 NAME

2 inherits: \nastavoramovani

3 CONTENT

`\placegraphic [...]1 [...]2...OPT {...}3 {...}4`

1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective

2 REFERENCE

3 TEXT

4 CONTENT

`\placeheadnumber [...]`

* ABSCHNITT

`\placeheadtext [...]`

* ABSCHNITT

`\placehelp`

`\placechemical [...]1 [...]2...OPT {...}3 {...}4`

1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective

2 REFERENCE

3 TEXT

4 CONTENT

`\placeindex [...]*...OPT...`

* inherits: \nastavrejstrik

`\placeinitial [...]OPT`

* NAME

`\placeintermezzo [...]1 [...]2...OPT {...}3 {...}4`

1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective

2 REFERENCE

3 TEXT

4 CONTENT

`\placelayer [...]`

* NAME

<p><code>\placelayeredtext</code> [¹...] [²..._{OPT}...] [³..._{OPT}...] {⁴...} {⁵...}</p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placelistofabbreviations</code> [..._{OPT}...]</p> <p>* inherits: \nastavsynonyma</p>
<p><code>\placelistoffigures</code> [..._{OPT}...]</p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistofFLOATS</code> [..._{OPT}...]</p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistofgraphics</code> [..._{OPT}...]</p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistofchemicals</code> [..._{OPT}...]</p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistofintermezzi</code> [..._{OPT}...]</p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistoflogos</code> [..._{OPT}...]</p> <p>* inherits: \nastavtrideni</p>
<p><code>\placelistofpublications</code> [¹...] [²..._{OPT}...]</p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placelistofsorts</code> [¹...] [²..._{OPT}...]</p> <p>1 SINGULAR</p> <p>2 inherits: \nastavtrideni</p>
<p><code>\placelistofSORTS</code> [..._{OPT}...]</p> <p>* inherits: \nastavtrideni</p> <p>instances: loga</p>
<p><code>\placelistofsynonyms</code> [¹...] [²..._{OPT}...]</p> <p>1 SINGULAR</p> <p>2 inherits: \nastavsynonyma</p>

```
instances: zkratky
```

```
* inherits: \nastavseznam
```

```
2 inherits: \setupnote
```

3 CONTENT

2 CONTENT

2 REFERENCE

2 TEXT

```
2 inherits: \setupnote
```

\placepagenumber

4 TEXT

3 TEXT

```
instances: legenda
```

<p><code>\placeparallel [...]¹ [...]²,...] [...]³,...,...</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p><code>\placeraawlist [...]¹ [...]²,...,...</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 LISTE</p> <p>2 inherits: \nastavseznam</p>
<p><code>\placereadingwindow [...]¹ [...]²,...</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\placetable [...]¹,...] [...]²,...] {...}³ {...}⁴</code></p> <p style="text-align: center;"><small>OPT OPT</small></p> <p>1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\plnezneni {...}</code></p> <p>* NAME</p>
<p><code>\podpodpodpodsekce [...]¹,...] {...}²</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podpodpodpodtema [...]¹,...] {...}²</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podpodpodsekce [...]¹,...] {...}²</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podpodpodtema [...]¹,...] {...}²</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podpodsekce [...]¹,...] {...}²</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podpodtema [...]¹,...] {...}²</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>

<p><code>\podsekce [...¹,...] {...²}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podtema [...¹,...] {...²}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\podtrzeni {...}</code></p> <p>* CONTENT</p>
<p><code>\podtrzeno {...}</code></p> <p>* CONTENT</p>
<p><code>\pole [...¹] [...²]</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\polozka [...[*],...]</code></p> <p>* REFERENCE</p>
<p><code>\polozky [...¹,...¹,...] {...²}</code></p> <p>1 inherits: \nastavpolozky</p> <p>2 TEXT</p>
<p><code>\popattribute *..</code></p> <p>* CSNAME</p>
<p><code>\POPIS [...¹,...] {...²} ...³ \par</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\popmacro *..</code></p> <p>* CSNAME</p>
<p><code>\popmode [...]</code></p> <p>* NAME</p>
<p><code>\POPISEK [...¹,...] {...²}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\porovnejpaletu [...]</code></p> <p>* NAME</p>

<p><code>\porovnejskupinubarev [...]</code></p> <p>* NAME</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>
<p><code>\positionregionoverlay {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\poslaednipodstranka</code></p>
<p><code>\postponenotes</code></p>
<p><code>\pozadi {...}</code></p> <p>* CONTENT</p>
<p><code>\POZADI {...}</code></p> <p>* CONTENT</p> <p>instances: pozadi</p>
<p><code>\pozice [...,¹...,_{OPT}...] (...²,...) {...³}</code></p> <p>1 inherits: \nastavumistovani</p> <p>2 POSITION</p> <p>3 CONTENT</p>
<p><code>\poznamka [...¹]_{OPT} [...²]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\poznamkapodcarou [...,¹...,_{OPT}...] {...²}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\poznamkapodcarou [...,[*]...,...]</code></p> <p>* titul = TEXT</p> <p> zalozka = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p>
<p><code>\NOTE [...,¹...,_{OPT}...] {...²}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>instances: poznamkapodcarou endnote</p>

<p><code>\NOTE [...,.*=...,...]</code></p> <p>* titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE</p> <p>instances: poznamkapodcarou endnote</p>
<code>\pravidelne</code>
<p><code>\predefinedfont [...]</code></p> <p>* FONT</p>
<p><code>\predefinefont [¹.] [².]</code></p> <p>1 NAME 2 FONT</p>
<p><code>\predefinesymbol [...]</code></p> <p>* NAME</p>
<p><code>\pref {¹...} {²...} [³.]</code> <small> OPT OPT</small></p> <p>1 TEXT 2 TEXT 3 REFERENCE</p>
<code>\prefixedpagenumber</code>
<code>\prefixlanguage</code>
<p><code>\prefixtext {.*.}</code></p> <p>* KEY</p>
<p><code>\prelozit [...,.*=...,...]</code> <small> OPT</small></p> <p>* SPRACHE = TEXT</p>
<p><code>\prependetoks ¹... \to \²...</code></p> <p>1 BEFEHL 2 CSNAME</p>
<p><code>\prependgvalue {¹...} {²...}</code></p> <p>1 NAME 2 BEFEHL</p>
<p><code>\prependtocommalist {¹...} \²...</code></p> <p>1 TEXT 2 CSNAME</p>
<p><code>\prependtoks ¹... \to \²...</code></p> <p>1 BEFEHL 2 CSNAME</p>

<pre> \prependtoksonce ¹... \to \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \prependvalue {¹...} {²...} 1 NAME 2 BEFEHL </pre>
<pre> \prepninazakladnifont [...[*]...] * inherits: \nastavzakladnifont </pre>
<pre> \presetbtxlabeltext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetdocument [...[*]...] * inherits: \setupdocument </pre>
<pre> \presetfieldsymbols [...[*]...] * NAME </pre>
<pre> \presetheadtext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetlabeltext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetPOPISEKtext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE instances: hlavicka popisek mathlabel taglabel jednotka operator prefix suffix btxlabel </pre>
<pre> \presetmathlabeltext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetoperatortext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetprefixtext [¹...] [...²...] OPT 1 SPRACHE 2 KEY = VALUE </pre>

<pre> \presettaglabeltext [...] [...] ¹ ² OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetunittext [...] [...] ¹ ² OPT 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \preskoc [...] [*] OPT * inherits: \vspacing </pre>
<pre> \preskrtnuti {...} * CONTENT </pre>
<pre> \preskrtnuto {...} * CONTENT </pre>
<pre> \pretocommalist {...} \²... 1 TEXT 2 CSNAME </pre>
<pre> \prevcounter [...] [²...] ¹ OPT 1 NAME 2 NUMMER </pre>
<pre> \prevcountervalue [...] * NAME </pre>
<pre> \preventmode [...,*...] * NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>
<pre> \prevsubcountervalue [¹...] [²...] 1 NAME 2 NUMMER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>

<pre> \prizpusobivepole [...] [.,.,.².,.,.] OPT 1 NAME 2 inherits: \setupfieldbody </pre>
<pre> \prizpusobvzhled [.,.,.¹,.,.] [.,.,.².,.,.] OPT 1 NUMMER 2 vyska = max DIMENSION radky = NUMMER </pre>
<pre> \procent </pre>
<pre> \processaction [.¹.] [.,.,.²>.,.,.] 1 BEFEHL 2 APPLY </pre>
<pre> \processallactionsinset [.¹.] [.,.,.²>.,.,.] 1 BEFEHL 2 APPLY </pre>
<pre> \processassignlist [.,.,.¹,.,.] \.².. 1 TEXT 2 CSNAME </pre>
<pre> \processassignmentcommand [.,.,.¹.,.,.] \.².. 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processassignmentlist [.,.,.¹.,.,.] \.².. 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processbetween {.¹.} \.².. 1 NAME 2 CSNAME </pre>
<pre> \processbodyfontenvironmentlist \.*.. * CSNAME </pre>
<pre> \processcolorcomponents {.*} * COLOR </pre>
<pre> \processcommaccommand [.,.,.¹,.,.] \.².. 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalist [.,.,.¹,.,.] \.².. 1 BEFEHL 2 CSNAME </pre>

<pre>\processcommalistwithparameters [...¹,...] \²...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\processcontent {...} \²...</pre> <pre>1 NAME</pre> <pre>2 CSNAME</pre>
<pre>\processfile {...}</pre> <pre>* FILE</pre>
<pre>\processfilemany {...}</pre> <pre>* FILE</pre>
<pre>\processfilenone {...}</pre> <pre>* FILE</pre>
<pre>\processfileonce {...}</pre> <pre>* FILE</pre>
<pre>\processfirstactioninset [...¹] [...²=>...,...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>
<pre>\processisolatedchars {...} \²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processisolatedwords {...} \²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processlinetablebuffer [...]_{OPT}</pre> <pre>* BUFFER</pre>
<pre>\processlinetablefile {...}</pre> <pre>* FILE</pre>
<pre>\processlist {...¹} {...²} {...³} \⁴...</pre> <pre>1 CHARACTER</pre> <pre>2 CHARACTER</pre> <pre>3 TEXT</pre> <pre>4 CSNAME</pre>
<pre>\processMPbuffer [...[*],...]_{OPT}</pre> <pre>* NAME</pre>

\processMPfigurefile {...} * FILE
\processmonth {...} {...} {...} 1 NUMMER 2 NUMMER 3 BEFEHL
\processranges [... ¹ ,...] \ ² .. 1 NUMMER NUMMER:NUMMER 2 CSNAME
\processseparatedlist [... ¹] [... ²] {... ³ } 1 TEXT 2 TEXT 3 CSNAME BEFEHL
\processTEXbuffer [...] <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div> * BUFFER
\processtokens {... ¹ } {... ² } {... ³ } {... ⁴ } {... ⁵ } 1 BEFEHL 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 TEXT
\processuntil *.. * CSNAME
\processxtablebuffer [...] <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div> * NAME
\processyear {... ¹ } {... ² } {... ³ } {... ⁴ } 1 NUMMER 2 BEFEHL 3 BEFEHL 4 BEFEHL
\produkt [...] * FILE
\produkt ... * FILE

<p><code>\profiledbox</code> [¹...] [²..._{OPT}..._{OPT}...] {³...}</p> <p>1 zadny fixne striktni halffixed quarterfixed eightsfixed NAME</p> <p>2 inherits: \setupprofile</p> <p>3 CONTENT</p>
<p><code>\profilegivenbox</code> {¹...} ²...</p> <p>1 zadny fixne striktni halffixed quarterfixed eightsfixed NAME</p> <p>2 CSNAME NUMMER</p>
<p><code>\program</code> [...]</p> <p>* NAME</p>
<p><code>\projekt</code> [...]</p> <p>* FILE</p>
<p><code>\projekt</code> ...</p> <p>* FILE</p>
<p><code>\prostredi</code> [...]</p> <p>* FILE</p>
<p><code>\prostredi</code> ...</p> <p>* FILE</p>
<p><code>\prvnipodstranka</code></p>
<p><code>\pseudoMixedCapped</code> {...}</p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped</code> {...}</p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped</code> {...}</p> <p>* TEXT</p>
<p><code>\pseudosmallcapped</code> {...}</p> <p>* TEXT</p>
<p><code>\purenumber</code> {...}</p> <p>* NUMMER</p>
<p><code>\pusharrangedpages</code> ... <code>\poparrangedpages</code></p>
<p><code>\pushattribute</code> \...</p> <p>* CSNAME</p>
<p><code>\pushbar</code> [...] ... <code>\popbar</code></p> <p>* NAME</p>

<p><code>\pushbarva [...] ... \popbarva</code></p> <p>* COLOR</p>
<p><code>\pushbutton [¹] [²]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro *...</code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]</code> OPT</p> <p>* NAME</p>
<p><code>\pushpath [...] ... \poppath</code></p> <p>* PATH</p>
<p><code>\pushpozadi [...] ... \poppozadi</code></p> <p>* NAME</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...} ... \popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\qqquad</code></p>
<p><code>\quad</code></p>
<p><code>\quads [...]</code> OPT</p> <p>* NUMMER</p>

<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {...}</code> * FILE
<code>\Rimskecislice {...}</code> * NUMMER
<code>\radek {...}</code> * CONTENT
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {...} \²... {³...}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {...}</code> * TEXT
<code>\randomnumber {¹...} {²...}</code> 1 NUMMER 2 NUMMER
<code>\rawcounter [¹...] [²...]</code> <small>OPT</small> 1 NAME 2 NUMMER
<code>\rawcountervalue [...]</code> * NAME
<code>\rawdate [...,*...]</code> * inherits: \aktualnidatum

<pre>\rawdoifelseinset {...} {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\rawdoifinset {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 TRUE</pre>
<pre>\rawdoifinsetelse {...} {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\rawgetparameters [...]¹ [...,²...,...]</pre> <pre>1 TEXT</pre> <pre>2 KEY = VALUE</pre>
<pre>\rawprocessaction [...]¹ [...,²=>...,...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>
<pre>\rawprocesscommacommand [...,¹...] \²...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\rawprocesscommalist [...,¹...] \²...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\rawstructurelistuservariable {...}</pre> <pre>* KEY</pre>
<pre>\rawsubcountervalue [...]¹ [...]²</pre> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\rbox ¹... {...}</pre> <div>OPT</div> <pre>1 TEXT</pre> <pre>2 CONTENT</pre>
<pre>\readfile {...} {...} {...}</pre> <pre>1 FILE</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>

\readfixfile {...} {...} {...} {...}

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

\readjobfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readlocfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readsetfile {...} {...} {...} {...}

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

\readsysfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readtexfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readxmlfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\realpagenumber

\realSmallCapped {...}

- * TEXT

\realSmallcapped {...}

- * TEXT

\realSmallcapped {...}

- * TEXT

<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...]¹ [...]²</code> 1 <code>implicitni text titul cislo stranka realpage</code> 2 <code>REFERENCE</code>
<code>\REFERENCEFORMAT {...}_{OPT} {...}_{OPT} [...]³</code> 1 <code>TEXT</code> 2 <code>TEXT</code> 3 <code>REFERENCE</code>
<code>\referenceprefix</code>
<code>\registerattachment [...]¹ [...]_{...}² [...]</code> 1 <code>NAME</code> 2 <code>inherits: \setupattachment</code>
<code>\registerctxluafile {...}¹ {...}²</code> 1 <code>FILE</code> 2 <code>NUMMER</code>
<code>\registerexternalfigure [...]¹ [...]_{OPT}² [...]_{...}³ [...]</code> 1 <code>FILE</code> 2 <code>NAME</code> 3 <code>inherits: \setupexternalfigure</code>
<code>\registerfontclass {...}[*]</code> * <code>NAME</code>
<code>\registerhyphenationexception [...]¹ [...]_{OPT}²</code> 1 <code>SPRACHE</code> 2 <code>TEXT</code>
<code>\registerhyphenationpattern [...]_{OPT}¹ [...]²</code> 1 <code>SPRACHE</code> 2 <code>TEXT</code>
<code>\registermenubuttons [...]¹ [...]²</code> 1 <code>NAME</code> 2 <code>TEXT</code>

<pre> \registersort [...] [...] 1 SINGULAR 2 NAME </pre>
<pre> \registersynonym [...] [...] 1 SINGULAR 2 NAME </pre>
<pre> \registerunit [...] [...] OPT 1 prefix jednotka operator suffixe symbol packaged 2 KEY = VALUE </pre>
<pre> \rejstrik [...] [...] OPT 1 TEXT PROCESSOR->TEXT 2 INDEX </pre>
<pre> \REJSTRIK [...] [...] OPT 1 TEXT PROCESSOR->TEXT 2 INDEX instances: rejstrik </pre>
<pre> \REJSTRIK [...] {...} [...] [...] OPT 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: rejstrik </pre>
<pre> \rejstrik [...] {...} [...] [...] OPT 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX </pre>
<pre> \relatemarking [...] [...] 1 BESCHRIFTUNG 2 BESCHRIFTUNG </pre>
<pre> \relateparameterhandlers {...} {...} {...} {...} 1 NAME 2 NAME 3 NAME 4 NAME </pre>
<pre> \relaxvalueifundefined {...} * NAME </pre>
<pre> \remainingcharacters </pre>

<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...} \^2.</code> 1 TEXT 2 CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...]</code> * NAME
<code>\removepunctuation</code>
<code>\removesubstring ... \from ... \to \^3.</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\removetoks ... \from \^2.</code> 1 BEFEHL 2 CSNAME
<code>\removeunwantedspaces</code>
<code>\replacefeature [...]</code> * NAME
<code>\replacefeature {...}</code> * NAME
<code>\replaceincommalist \^1. {...}</code> 1 CSNAME 2 NUMMER
<code>\replaceword [...] [...] [...]</code> 1 NAME 2 TEXT 3 TEXT
<code>\rescan {...}</code> * CONTENT

<pre>\rescanwithsetup {...} {...}</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\resetallattributes</pre>
<pre>\resetandaddfeature [...]</pre> <pre>* NAME</pre>
<pre>\resetandaddfeature {...}</pre> <pre>* NAME</pre>
<pre>\resetbar</pre>
<pre>\resetbreakpoints</pre>
<pre>\resetbuffer [...]</pre> <pre>* BUFFER</pre>
<pre>\resetcollector [...]</pre> <pre>* NAME</pre>
<pre>\resetcounter [...¹] [...²]</pre> <div>OPT</div> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\resetdigitsmanipulation</pre>
<pre>\resetdirection</pre>
<pre>\resetfeature</pre>
<pre>\resetflag {...}</pre> <pre>* NAME</pre>
<pre>\resetfontcolorsheme</pre>
<pre>\resetfontfallback [...¹] [...²]</pre> <div>OPT</div> <pre>1 NAME</pre> <pre>2 FONT</pre>
<pre>\resetfontsolution</pre>
<pre>\resethyphenationfeatures</pre>
<pre>\resetcharacteralign</pre>
<pre>\resetcharacterkerning</pre>

<code>\resetcharacterspacing</code>
<code>\resetcharacterstripping</code>
<code>\resetinjector [...]</code> * NAME
<code>\resetinteractionmenu [...]</code> * NAME
<code>\resetitaliccorrection</code>
<code>\resetlayer [...]</code> * NAME
<code>\resetlocalfloats</code>
<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> * NAME
<code>\resetmarker [...]</code> * NAME
<code>\resetmode {...}</code> * NAME
<code>\resetpagenumber</code>
<code>\resetparallel [...]¹ [...,²...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 NAME 2 NAME vse
<code>\resetpath</code>
<code>\resetpenalties \...</code> * CSNAME
<code>\resetprofile</code>
<code>\resetreference [...]</code> * NAME
<code>\resetreplacement</code>
<code>\resetscript</code>

\resetsetups [...] * NAME
\resetshownsynonyms [...] * SINGULAR
\resetsubpagenumber
\resetsymbolset
\resetsystemmode {...} * NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\resetznaceni [...] * BESCHRIFTUNG
\reshapebox {...} * BEFEHL
\restartcounter [...] [¹ ...] [² ...] [³ ...] <div> <div>OPT</div> <div> 1 NAME 2 NUMMER 3 NUMMER </div> </div>
\restorebox [¹ ...] [² ...] <div> 1 NAME 2 NAME </div>
\restorecatcodes

<code>\restorecounter [...]</code> * NAME
<code>\restorecurrentattributes {...}</code> * NAME
<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
<code>\reusableMPgraphic {...} {...,²...}</code> <small>OPT</small> 1 NAME 2 KEY = VALUE
<code>\reuseMPgraphic {...} {...,²...}</code> <small>OPT</small> 1 NAME 2 KEY = VALUE
<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> * CHARACTER
<code>\rhbox {...}</code> * CONTENT
<code>\rightbottombox {...}</code> * CONTENT
<code>\rightbox {...}</code> * CONTENT
<code>\righthbox {...}</code> * CONTENT
<code>\rightheadtext {...}</code> * KEY
<code>\rightlabeltext {...}</code> * KEY
<code>\rightPOPISEKtext {...}</code> * KEY instances: hlavicka popisek mathlabel

$\backslash\mathrm{rightline}\{\dots\}$ * CONTENT
$\backslash\mathrm{rightmathlabeltext}\{\dots\}$ * KEY
$\backslash\mathrm{righttorleftpageaction}\{\dots\}\{\dots\}$ 1 BEFEHL 2 BEFEHL
$\backslash\mathrm{rightskipadaption}$
$\backslash\mathrm{rightsubguillemot}$
$\backslash\mathrm{righttopleft}$
$\backslash\mathrm{righttopleftthbox}\overset{1}{\dots}\overset{\mathrm{OPT}}{\{\dots\}}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{righttoplefttvbox}\overset{1}{\dots}\overset{\mathrm{OPT}}{\{\dots\}}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopleftvtop}\overset{1}{\dots}\overset{\mathrm{OPT}}{\{\dots\}}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopbox}\{\dots\}$ * CONTENT
$\backslash\mathrm{rimskecislice}\{\dots\}$ * NUMMER
$\backslash\mathrm{rlap}\{\dots\}$ * CONTENT
$\backslash\mathrm{robustaddtocommalist}\{\dots\}\backslash\dots$ 1 TEXT 2 CSNAME
$\backslash\mathrm{robustdoifelseinset}\{\dots\}\{\dots\}$ 1 TRUE 2 FALSE
$\backslash\mathrm{robustdoifinsetelse}\{\dots\}\{\dots\}$ 1 TRUE 2 FALSE

$\backslash\text{robustpretocommalist } \{.^1.\} \backslash.^2.$ 1 TEXT 2 CSNAME
$\backslash\text{rollbutton } [..., \dots.^1\dots, \dots] \dots.^2. [...].^3.$ 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{rollbutton } [.^1.] [..., \dots.^2\dots, \dots] \dots.^3. [...].^4.$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
$\backslash\text{rovnice } [..., \dots.^1\dots] \{.^2.\}$ <small>OPT</small> 1 zhustene tight nastred ramecek inherits: \nastavzakladnifont 2 CONTENT
$\backslash\text{rozdelplvouciobjekt } [..., \dots.^1\dots, \dots] \{.^2.\} \{.^3.\}$ <small>OPT</small> 1 inherits: \nastavdeleniplvoucichobjektu 2 BEFEHL 3 CONTENT
$\backslash\text{roztazene } [..., \dots.^1\dots, \dots] \{.^2.\}$ <small>OPT</small> 1 inherits: \setupstretched 2 TEXT
$\backslash\text{rtop } \dots.^1. \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{rukopisne}$
$\backslash\text{ruledhbox } \dots.^1. \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledhpack } \dots.^1. \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledmbox } \{.^*.\}$ * CONTENT

<pre> \ruledtopv ... {...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledtpack ... {...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvbox ... {...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvpack ... {...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvtop ... {...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \runMPbuffer [...*,...] OPT * NAME </pre>
<pre> \runninghbox {...} * CONTENT </pre>
<pre> \ScaledPointsToBigPoints {...} \^2... 1 DIMENSION 2 CSNAME </pre>
<pre> \ScaledPointsToWholeBigPoints {...} \^2... 1 DIMENSION 2 CSNAME </pre>
<pre> \SLOVA {...} * TEXT </pre>
<pre> \SLOVO {...} * TEXT </pre>
<pre> \Slova {...} * TEXT </pre>
<pre> \Slovo {...} * TEXT </pre>
<pre> \Smallcapped {...} * TEXT </pre>

* NUMMER

\sansnormal

\sanstucne

\savebarva ... \restorebarva

1	NAME
2	NAME
3	CONTENT

```

1  NAME
2  FILE
3  dataset      = NAME
   typ          = bib lua xml
   soubor       = FILE
   kritérium    = vse text uvod odkaz aktualni zde predchozi lokalne komponenta SECTIONBLOCK:vse SECTIONBLOCK:odkaz
                  SECTIONBLOCK:aktualni SECTIONBLOCK:predchozi

```

```
*   seznam  =  NAME
    soubor   =  FILE
    prefix   =  ano ne
```

```
1  BUFFER
2  FILE
```

* NAME

* NAME

* CSNAME

1	NAME
2	NUMMER
3	NAME
4	CONTENT

`\savetwopassdata {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 CONTENT

`\sbox {...}`

- * CONTENT

`\SCRIPT`

instances: hangul hanzi nihongo ethiopic thai latin test

`\secondoffivearguments {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\secondoffourarguments {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\secondofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\secondofthreearguments {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondofthreeunexpanded {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondoftwoarguments {...} {...}`

- 1 TEXT
- 2 TEXT

\secondoftwounexpanded {...} {...}

- 1 TEXT
- 2 TEXT

\sedabarva [...] {...}

- 1 COLOR
- 2 CONTENT

\seeindex [...] [...] {...}

- 1 TEXT PROCESSOR->TEXT
- 2 INDEX
- 3 TEXT PROCESSOR->TEXT

\vizREJSTRIK [...] [...] {...}

- 1 TEXT PROCESSOR->TEXT
- 2 INDEX
- 3 TEXT PROCESSOR->TEXT

instances: rejstrik

\sekce [...,¹...] {...}

- 1 REFERENCE
- 2 TEXT

\SEKCE [...,¹...] {...}

- 1 REFERENCE
- 2 TEXT

instances: cast kapitola sekce podsekce podpodsekce podpodpodsekce podpodpodpodsekce titul
tema podtema podpodtema podpodpodtema podpodpodpodtema

\SEKCE [...,^{*}...] [...]

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

instances: cast kapitola sekce podsekce podpodsekce podpodpodsekce podpodpodpodsekce titul
tema podtema podpodtema podpodpodtema podpodpodpodtema

\SEKCE [...,¹...] {...} {...}

- 1 REFERENCE
- 2 NUMMER
- 3 TEXT

instances: cast kapitola sekce podsekce podpodsekce podpodpodsekce podpodpodpodsekce titul
tema podtema podpodtema podpodpodtema podpodpodpodtema

<pre> \select {...} {...} {...} {...} {...} {...} OPT OPT OPT OPT OPT 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT </pre>
<pre> \serializecommalist [...,*,...] * BEFEHL </pre>
<pre> \serializedcommalist </pre>
<pre> \serif </pre>
<pre> \serifbold </pre>
<pre> \serifnormal </pre>
<pre> \setbar [...] * NAME </pre>
<pre> \setbigbodyfont </pre>
<pre> \setboxllx .¹. {...} 1 CSNAME NUMMER 2 DIMENSION </pre>
<pre> \setboxlly .¹. {...} 1 CSNAME NUMMER 2 DIMENSION </pre>
<pre> \setbreakpoints [...] * reset NAME </pre>
<pre> \setbuffer [...] ... \endbuffer * NAME </pre>
<pre> \setcapstrut </pre>
<pre> \setcatcodetable *... * CSNAME </pre>
<pre> \setcollector [...] [...,²...,...] {...} OPT 1 NAME 2 inherits: \setupcollector 3 CONTENT </pre>

<pre>\setcolormodell [...]</pre> <p>* black bw seda rgb cmyk vse zadny</p>
<pre>\setcounter [...]¹ [...]² [...]³ OPT</pre> <p>1 NAME</p> <p>2 NUMMER</p> <p>3 NUMMER</p>
<pre>\setcounterown [...]¹ [...]² [...]³ OPT</pre> <p>1 NAME</p> <p>2 NUMMER</p> <p>3 TEXT</p>
<pre>\setcurrentfontclass {...}</pre> <p>* NAME</p>
<pre>\setdataset [...]¹ [...]² [...]³...,...] OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 KEY = VALUE</p>
<pre>\setdefaultpenalties</pre>
<pre>\setdigitsmanipulation [...]</pre> <p>* reset NUMMER</p>
<pre>\setdirection [...]</pre> <p>* NUMMER</p>
<pre>\setdocumentargument {...}¹ {...}²</pre> <p>1 NAME</p> <p>2 TEXT</p>
<pre>\setdocumentargumentdefault {...}¹ {...}²</pre> <p>1 NAME</p> <p>2 TEXT</p>
<pre>\setdocumentfilename {...}¹ {...}²</pre> <p>1 NUMMER</p> <p>2 TEXT</p>
<pre>\setdummyparameter {...}¹ {...}²</pre> <p>1 KEY</p> <p>2 BEFEHL</p>

<pre> \setelementexporttag [...] [...] [...] OPT 1 NAME 2 export nature pdf 3 inline obrazovka mixed </pre>
<pre> \setemeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setevalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setevariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setevariables [...] [...] [...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \setfirstline [...] OPT * NAME </pre>
<pre> \setflag {...} * NAME </pre>
<pre> \setfont ... * FONT </pre>
<pre> \setfontcolorsheme [...] * NAME </pre>
<pre> \setfontfeature {...} * NAME </pre>
<pre> \setfontsolution [...] * NAME </pre>
<pre> \setfontstrut </pre>
<pre> \setgmeasure {...} {...} 1 NAME 2 DIMENSION </pre>

`\setgvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setgvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setgvariables [...] [...,2...,...]`

- 1 NAME
- 2 `set` = BEFEHL
`reset` = BEFEHL
KEY = VALUE

`\sethboxregister 1... {...}`

- 1 CSNAME NUMMER
- 2 CONTENT

`\sethyphenatedurlafter {...}`

- * TEXT

`\sethyphenatedurlbefore {...}`

- * TEXT

`\sethyphenatedurlnormal {...}`

- * TEXT

`\sethyphenationfeatures [...,*...]`
OPT

- * NAME reset

`\setcharacteralign {...} {...}`

- 1 NUMMER
- 2 TEXT number->TEXT text->TEXT

`\setcharactercasing [...]`

- * reset SLOVO slovo Slovo Slova kapitalky Kapitalky zadny nahodny mixed camel kap Kap

`\setcharactercleaning [...]`

- * reset 1

`\setcharacterkerning [...]`

- * reset NAME

`\setcharacterspacing [...]`

- * reset NAME

<pre> \setcharacterstripping [...] * reset 1 </pre>
<pre> \setcharstrut {...} * TEXT </pre>
<pre> \setinitial [...] [...²...²...] OPT OPT 1 NAME 2 inherits: \setupinitial </pre>
<pre> \setinjector [¹...] [...²...] [³...] 1 NAME 2 NUMMER 3 BEFEHL </pre>
<pre> \setinteraction [...] * skryte NAME </pre>
<pre> \setinterfacecommand {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceconstant {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceelements {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinterfacemessage {...} {...} {...} 1 NAME 2 titul NAME NUMMER 3 TEXT </pre>
<pre> \setinterfacevariable {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinternalrendering [¹...] [...²] {...} 1 NAME 2 auto embed 3 CONTENT </pre>
<pre> \setitaliccorrection [...] * reset 1 2 </pre>

`\setJSpreamble {...} {...}`

- 1 NAME
- 2 CONTENT

`\setlayer [...]OPT [...]OPT {...}`

- 1 NAME
- 2 vlevo vpravo sude liche
- 3 inherits: \setuplayer
- 4 CONTENT

`\setlayerframed [...]OPT [...]OPT {...}`

- 1 NAME
- 2 inherits: \setuplayer
- 3 inherits: \nastavoramovani
- 4 CONTENT

`\setlayerframed [...]OPT {...}`

- 1 NAME
- 2 inherits: \setuplayerinherits: \nastavoramovani
- 3 CONTENT

`\setlayertext [...]OPT [...]OPT {...}`

- 1 NAME
- 2 inherits: \setuplayer
- 3 zarovnani = inherits: \nastavzarovnani
sirka = DIMENSION
pismeno = STYLE BEFEHL
barva = COLOR
- 4 TEXT

`\setlinefiller [...]`

- * filler NAME

`\setlocalhsize [...]OPT`

- * [-+]DIMENSION

`\setMPlayer [...]OPT [...]OPT {...}`

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer
- 4 CONTENT

`\setMPpositiongraphic {...} {...} {...}OPT`

- 1 NAME
- 2 NAME
- 3 KEY = VALUE

```

1  NAME
2  NAME
3  NAME
4  KEY  =  VALUE

```

```
1  NAME
2  TEXT
```

```
1  NAME
2  KEY  =  VALUE
```

```
1  NAME
2  KEY  =  VALUE
```

```
\setmainparbuilder [...]
*   implicitni oneline basic NAME
```

```

1  NAME
2  NUMMER

```

1 BESCHRIFTUNG

2 TEXT

* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

1	NAME
2	DIMENSION

```
1  NAME
2  NAME NUMMER
```

* NAME

240

`\setnote [...]1 [...,2...] {3...}`
OPT

- 1 NAME
- 2 REFERENCE
- 3 TEXT

`\setnotetext [...]1 [...,2...] {3...}`
OPT

- 1 NAME
- 2 REFERENCE
- 3 TEXT

`\setnotetext [...]1 [...,2...,...]`

- 1 NAME
- 2 titul = TEXT
zalozka = TEXT
seznam = TEXT
odkaz = REFERENCE

`\setnote [...]1 [...,2...,...]`

- 1 NAME
- 2 titul = TEXT
zalozka = TEXT
seznam = TEXT
odkaz = REFERENCE

`\setobject {1...} {2...} \3... {4...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\setoldstyle`

`\setpagegrid [...]1...,... {2...}`
OPT

- 1 c = NUMBER
r = NUMBER
volba = zadny
- 2 CONTENT

`\setpagereference {1...} {2...,...}`

- 1 NAME
- 2 REFERENCE

`\setpagestate [...]1 [2...]`
OPT

- 1 NAME
- 2 NAME NUMBER

`\setpagestaterealpageno {1...} {2...}`

- 1 NAME
- 2 NAME NUMBER

\setpenalties \.¹ {²} {³}

- 1 CSNAME
- 2 NUMMER
- 3 NUMMER

\setpercentdimen {¹} {²}

- 1 DIMENSION CSNAME
- 2 DIMENSION NUMMER

\setposition {^{*}}

- * NAME

\setpositionbox {¹} \.² {³}

- 1 NAME
- 2 CSNAME
- 3 CONTENT

\setpositiondata {¹} {²} {³} {⁴}

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION

\setpositiondataplus {¹} {²} {³} {⁴} {⁵,...}

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION
- 4 DIMENSION
- 5 TEXT

\setpositiononly {^{*}}

- * NAME

\setpositionplus {¹} {²,...} \.³ {⁴}

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

\setpositionstrut {^{*}}

- * NAME

\setprofile [^{*}]

- * zadny fixne striktni halffixed quarterfixed eightsfixed NAME

\setrandomseed {^{*}}

- * NUMMER

`\setreference [...1,...] [...2...,...]`

- 1 REFERENCE
- 2 KEY = VALUE

`\setreferencedobject {...1.} {...2.} \... {...4.}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\setregisterentry [...1.] [...2...,...] [...3...,...] OPT`

- 1 NAME
- 2

popisek	=	NAME
keys	=	TEXT PROCESSOR->TEXT
entries	=	TEXT PROCESSOR->TEXT
keys:1	=	TEXT
keys:2	=	TEXT
keys:3	=	TEXT
entries:1	=	TEXT
entries:2	=	TEXT
entries:3	=	TEXT
alternativa	=	TEXT
- 3 KEY = VALUE

`\setreplacement [...]`

- * reset NAME

`\setrigidcolumnbalance ...`

- * CSNAME NUMBER

`\setrigidcolumnhsize {...1.} {...2.} {...3.}`

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMMER

`\setscript [...]`

- * hangul hanzi nihongo ethiopic thai test NAME

`\setsectionblock [...1.] [...2...,...] OPT`

- 1 NAME
- 2 zalozka = TEXT

`\setsimplecolumnhsize [...*...,...]`

- *

n	=	NUMMER
sirka	=	DIMENSION
vzdalenost	=	DIMENSION
radky	=	NUMMER

`\setsmallbodyfont`

`\setsmallcaps`

\setstackbox {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 CONTENT

\setstructurepageregister [...]¹ [...,...²...,...]³ [...,...³...,...]^{OPT}

- 1 NAME
- 2

popisek	=	NAME
keys	=	TEXT PROCESSOR->TEXT
entries	=	TEXT PROCESSOR->TEXT
keys:1	=	TEXT
keys:2	=	TEXT
keys:3	=	TEXT
entries:1	=	TEXT
entries:2	=	TEXT
entries:3	=	TEXT
alternativa	=	TEXT
- 3 KEY = VALUE

\setstrut

\setsuperiors

\setsystemmode {...}

- * NAME

\settabular

\settaggedmetadata [...,...^{*}...,...]

- * KEY = VALUE

\settextcontent [...]¹ [...]² [...]³ [...]⁴ [...]⁵
OPT OPT

- 1 vrsek zahlavi text upati spodek
- 2 text marginalie hrana
- 3 vlevo nastred vpravo
- 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
- 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

\settightobject {...}¹ {...}² \...³ {...}⁴

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\settightreferencedobject {...}¹ {...}² \...³ {...}⁴

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightunreferencedobject {...} {...} \... {...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settrialtypesetting`

`\setuevalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setugvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setunreferencedobject {...} {...} \... {...}`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\setupattachment [...1,...] [...2,...]`
OPT

- 1 NAME
- 2

titul	=	TEXT
podtitulek	=	TEXT
autor	=	TEXT
soubor	=	FILE
jmeno	=	NAME
buffer	=	BUFFER
status	=	start stop
metoda	=	normalni skryte
symbol	=	Graph Paperclip Pushpin Default
sirka	=	prizpusobive DIMENSION
vyska	=	prizpusobive DIMENSION
hloubka	=	prizpusobive DIMENSION
barva	=	COLOR
textlayer	=	NAME
misto	=	levahrana pravahrana naokraji lev yokraj pravyokraj text vysoko zadny
vzdalenost	=	DIMENSION

`\setupbackend [...*,...]`

- *

export	=	ano FILE
xhtml	=	FILE
soubor	=	FILE
intent	=	NAME
mezera	=	ano ne
xmpfile	=	FILE
formatovat	=	version implicitni NAME
uroven	=	NUMMER
volba	=	vzdy nikdy
profile	=	FILE

`\setupbar [...1,...] [...2,...]`
OPT

```
1  NAME

2  barva           = COLOR
   pokracovat     = ano ne vse
   prazdne        = ano ne
   jednotka       = ex em pt in cm mm sp bp pc dd cc nc
   order          = popredi pozadi
   tloustkalinky  = DIMENSION
   metoda         = NUMMER
   offset         = NUMMER
   dy             = NUMMER
   max            = NUMMER
   foregroundstyle = STYLE BEFEHL
   foregroundcolor = COLOR
   mp             = NAME
   vlevo          = TEXT
   vpravo         = TEXT
```

`\setupbleeding [...*,...]`

```
*  sirka          = DIMENSION
   vyska          = DIMENSION
   offset         = DIMENSION
   hoffset       = DIMENSION
   voffset        = DIMENSION
   misto          = t b l r bl lb br rb tl lt tr rt
   natahnout     = ano ne
   stranka       = ano ne
```

`\setupbookmark [...*,...]`

```
*  sila           = ano ne
   cislo          = ano ne
   numberseparatorset = NAME
   numberconversionset = NAME
   numberstarter  = BEFEHL
   numberstopper  = BEFEHL
   numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
   sectionblock   = ano ne
```

`\setupbtx [...1,...] [...2,...]`
OPT

```
1  NAME

2  specification = implicitni apa aps NAME
   dataset      = implicitni NAME
   prikaz       = \...##1
   vlevo        = BEFEHL
   vpravo       = BEFEHL
   authorconversion = normalni normalshort normalinverted invertedshort short
   etallimit    = NUMMER
   etaldisplay  = NUMMER
   etaloption   = posledni
   predel       = initials
   interakce    = start stop vse
   alternativa  = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
                  authornum authoryear
   sorttype     = normalni reverse
   compress     = ano ne
   implicitni   = implicitni NAME
   pismo       = STYLE BEFEHL
   barva       = COLOR
```

`\setupbtxdataset [...1,...] [...2,...]`
OPT

```
1  NAME

2  language = SPRACHE
```

`\setupbtxlabeltext [...1,...] [...2,...]`
OPT

```
1  SPRACHE

2  KEY = VALUE
```

\setupbtxlist [...]¹ [...]²...

OPT

1 NAME

2 inherits: \nastavseznam

\setupbtxregister [...]¹ [...]²...

OPT

1 NAME

2 status = start stop
dataset = NAME
field = keyword range cislostranky autor
register = NAME
metoda = once
alternativa = normalshort invertedshort
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxrendering [...]¹ [...]²...

OPT

1 NAME

2 statustextu = start stop
pagestate = start stop
oddelovac = BEFEHL
kriterium = predchozi cite zde vse zadny
specification = NAME
titul = TEXT
pred = BEFEHL
po = BEFEHL
dataset = NAME
metoda = dataset sila lokalne globalne zadny
sorttype = short dataset seznam odkaz uzito implicitni cite rejstrik
opakovat = ano ne
group = NAME
cislovani = ano ne num rejstrik tag short stranka

\setupbtx [...]

* NAME

\setupbutton [...]¹ [...]²...

OPT

1 NAME

2 status = start stop
stejnastranka = ano ne prazdne zadny normalni implicitni
pismo = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
alternativa = skryte
inherits: \nastavoramovani

\setupcollector [...]¹ [...]²...

OPT

1 NAME

2 rotace = vlevo vpravo uvnitr vnejsi NUMMER
roh = vlevo nastred vpravo vrsek spodek
x = DIMENSION
y = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
misto = vlevo nastred vpravo vrsek spodek radek l c r m t b g
status = start stop

\setupcolumnspan [...]^{*}...

* n = NUMMER
inherits: \nastavoramovani

\setupcombination [...,¹...] [...,²...]
OPT

```

1  NAME

2  nx          =  NUMBER
   ny          =  NUMBER
   sirka       =  prizpusobive DIMENSION
   vyska       =  prizpusobive DIMENSION
   misto       =  vlevo nastred vpravo vrsek spodek
   vzdalenost  =  DIMENSION
   alternativa =  popisek text
   zarovnnani  =  inherits: \nastavzarovnnani
   pokracovat  =  ano ne
   pred        =  BEFEHL
   po          =  BEFEHL
   mezi        =  BEFEHL
   pismeno     =  STYLE BEFEHL
   barva       =  COLOR

```

\setupcontent [...,*...]

* inherits: \nastavseznam

\setupcounter [...,¹...] [...,²...]
OPT

```

1  NAME

2  start          =  NUMBER
   counter        =  NAME
   metoda         =  stranka
   status         =  start stop
   zpusob         =  bystranka byblock bytext byhlavicka byABSCHNITT
   prefix         =  ano ne
   prefixseparatorset =  NAME
   prefixconversion =  NAME
   prefixconversionset =  NAME
   prefixstarter  =  BEFEHL PROCESSOR->BEFEHL
   prefixstopper  =  BEFEHL PROCESSOR->BEFEHL
   prefixset      =  NAME
   prefixsegments =  NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
   numberorder    =  reverse
   numberseparatorset =  NAME
   numberconversion =  NAME
   numberconversionset =  NAME
   numberstarter  =  BEFEHL PROCESSOR->BEFEHL
   numberstopper  =  BEFEHL PROCESSOR->BEFEHL
   numbersegments =  NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   typ            =  prvni predchozi dalsi posledni cislo
   kriterium      =  striktni pozitiv vse
   prefixconnector =  BEFEHL PROCESSOR->BEFEHL

```

\setupdataset [...,*...]

* prodleva = ano ne

`\setupdelimitedtext [...1,...] [...2...]`
OPT

```

1  NAME

2  pred      = BEFEHL
   po        = BEFEHL
   language  = lokalne globalne SPRACHE
   metoda    = font
   opakovat  = ano ne
   misto      = text odstavec marginalie
   vlevo     = BEFEHL
   stredni    = BEFEHL
   vpravo     = BEFEHL
   nextleft  = BEFEHL
   nextright = BEFEHL
   mezerapred = inherits: \preskoc
   mezeraza  = inherits: \preskoc
   levyokraj = ano ne standardni DIMENSION
   pravyokraj = ano ne standardni DIMENSION
   odsazovani = inherits: \nastavodsazovani
   odsadpristi = ano ne auto
   pismo     = STYLE BEFEHL
   barva     = COLOR
   stylymboly = STYLE BEFEHL
   barvasymbolu = COLOR

```

`\setupdescription [...1,...] [...2...]`
OPT

```

1  NAME

2  titul      = ano ne
   uroven     = NUMMER
   text       = TEXT
   headcommand = \...##1
   pred       = BEFEHL
   po         = BEFEHL
   mezi       = BEFEHL
   alternativa = vlevo vpravo naokrajivlevo ivpravo marginalie levyokraj pravyokraj innermargin outermargin
                  semknuto visici vrsek prikaz NAME
   zarovnnani = inherits: \nastavzarovnnani
   headalign  = inherits: \nastavzarovnnani
   odsazovani = inherits: \nastavodsazovani
   obrazovka  = ano ne
   odsadpristi = ano ne auto
   sirka      = prizpusobive siroky radek DIMENSION
   vzdalenost = zadny DIMENSION
   zaveseni   = prizpusobive siroky zadny marginalie NUMMER
   closesymbol = BEFEHL
   closecommand = \...##1
   expanzen   = ano ne xml
   vzor       = TEXT
   marginalie = ano ne standardni DIMENSION
   pismo     = STYLE BEFEHL
   barva     = COLOR
   stylhlavicky = STYLE BEFEHL
   barvahlavicky = COLOR

```

`\setupdirections [...*...]`

```

*  bidi      = zap vyp lokalne globalne
   metoda    = jedna dve implicitni
   fences    = ano ne

```

`\setupdocument [...*...]`

```

*  pred      = BEFEHL
   po        = BEFEHL
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY          = VALUE

```

`\setupeffect [...,1...] [...,2...,...]`
OPT

1 NAME

2 metoda = zadny prikaz
 natahnout = NUMMER
 tloustkalinky = NUMMER
 alternativa = normalni uvnitr vnejsi obe skryte natahnout

`\setupenumeration [...,1...] [...,2...,...]`
OPT

1 NAME

2 titul = ano ne
 cislo = ano ne
 ciselnyprikaz = \...##1
 vzdalenosttitulek = DIMENSION
 styltitulek = STYLE BEFEHL
 barvatitulek = COLOR
 titlecommand = \...##1
 titleleft = BEFEHL
 titleright = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 symbol = BEFEHL
 starter = BEFEHL
 predel = BEFEHL
 propojeni = NAME
 counter = NAME
 uroven = NUMMER
 text = TEXT
 headcommand = \...##1
 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 alternativa = vlevo vpravo naokrajiv vlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin
 semknuto visici vrsek prikaz NAME
 zarovnani = inherits: \nastavzarovnani
 headalign = inherits: \nastavzarovnani
 odsazovani = inherits: \nastavodsazovani
 obrazovka = ano ne
 odsadpristi = ano ne auto
 sirka = prizpusobive siroky radek DIMENSION
 vzdalenost = zadny DIMENSION
 zaveseni = prizpusobive siroky zadny marginalie NUMMER
 closesymbol = BEFEHL
 closecommand = \...##1
 expanzen = ano ne xml
 vzor = TEXT
 marginalie = ano ne standardni DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR
 stylhlavicky = STYLE BEFEHL
 barvahlavicky = COLOR
 inherits: \setupcounter

`\setupenv [...,*...,...]`

* set = BEFEHL
 reset = BEFEHL
 KEY = VALUE

`\setupexport [...,*...,...]`

* zarovnani = flushleft nastred flushright normalni
 zakladnifont = DIMENSION
 sirka = DIMENSION
 titul = TEXT
 podtitulek = TEXT
 autor = TEXT
 alternativa = html div
 properties = ano ne
 hyphen = ano ne
 cssfile = FILE
 prvnistranka = FILE
 poslednistrana = FILE

`\setupexternalfigure [...1,...] [...2,...]`
OPT

```

1  NAME

2  sirka          = DIMENSION
   vyska         = DIMENSION
   popisek       = NAME
   stranka       = NUMMER
   objekt        = ano ne
   prefix        = TEXT
   metoda        = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controls      = ano ne
   nahled        = ano ne
   mask          = zadny
   rozliseni     = NUMMER
   barva         = COLOR
   arguments     = TEXT
   opakovat      = ano ne
   faktor        = prizpusobive siroky max auto implicitni
   vfaktor       = prizpusobive siroky max auto implicitni
   sfaktor       = prizpusobive siroky max auto implicitni
   maxsirka      = DIMENSION
   maxvyska      = DIMENSION
   equalwidth    = DIMENSION
   equalheight   = DIMENSION
   meritko       = NUMMER
   xmeritko      = NUMMER
   ymeritko      = NUMMER
   s             = NUMMER
   sx            = NUMMER
   sy            = NUMMER
   radky         = NUMMER
   misto         = lokalne globalne implicitni
   adresar       = PATH
   volba         = test ramecek prazdne
   foregroundcolor = COLOR
   reset         = ano ne
   pozadi        = barevne popredi NAME
   ramecek       = zap vyp
   barvapozadi   = COLOR
   zarovnnani    = inherits: \nastavzarovnnani
   xmax          = NUMMER
   ymax          = NUMMER
   ramecky       = zap vyp
   interakce     = ano vse zadny odkaz layer zalozka
   zakladnifont  = DIMENSION
   comment       = BEFEHL TEXT
   velikost      = zadny media crop trim art
   cache         = PATH
   resources     = PATH
   obrazovka     = FILE
   konverze      = TEXT
   order         = LISTE
   crossreference = ano ne NUMMER

```

`\setupexternalsoundtracks [...*,...]`

* volba = opakovat

`\setupfieldbody [...1,...] [...2,...]`
OPT

```

1  NAME

2  category = NAME
   inherits: \setupfieldcategory

```

`\setupfieldcategory [...1,...] [...2,...]`
OPT

```

1  NAME

2  start          = NUMMER
   pismeno        = STYLE BEFEHL
   barva          = COLOR
   typ            = radio pod text radek push check signature
   values         = TEXT
   implicitni     = TEXT
   barvareckupole = COLOR
   barvapožadipole = COLOR
   sirka          = DIMENSION
   vyska          = DIMENSION
   hloubka        = DIMENSION
   zarovnani      = vlevo nastred vpravo flushleft center flushright
   n              = NUMMER
   symbol         = NAME
   fieldlayer     = NAME
   volba          = pouzeprocteni pozadovane chranene tridene nedostupne nocheck fixne soubor skryte tisknutelne
                   auto
   klikuvnitr     = REFERENCE
   klikvne        = REFERENCE
   oblastuvnitr   = REFERENCE
   oblastvne      = REFERENCE
   klavesapo      = REFERENCE
   formatovat     = REFERENCE
   validovat      = REFERENCE
   pocitat        = REFERENCE
   focusin        = REFERENCE
   focusout       = REFERENCE
   openpage       = REFERENCE
   closepage      = REFERENCE

```

`\setupfieldcontentframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \nastavoramovaniinherits: \setupfieldcategory

```

`\setupfieldlabelframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \nastavoramovani

```

`\setupfieldtotalframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  pred          = BEFEHL
   po            = BEFEHL
   mezi          = BEFEHL
   vzdalenost    = DIMENSION
   alternativa   = reset popisek ramecek horizontalne vertikalne
   inherits: \nastavoramovani

```

`\setupfiller [...1,...] [...2,...]`
OPT

```

1  NAME

2  levyokraj     = DIMENSION
   pravyokraj    = DIMENSION
   vlevo         = BEFEHL
   vpravo        = BEFEHL
   alternativa   = symbol natahnout linka mezera
   metoda        = lokalne globalne nastred siroky
   sirka         = DIMENSION
   vyska         = DIMENSION
   hloubka       = DIMENSION
   offset        = DIMENSION
   vzdalenost    = DIMENSION
   zarovnani     = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   symbol        = BEFEHL
   pismeno       = STYLE BEFEHL
   barva         = COLOR

```


\setupfirstline [...¹,...] [...²,...]
OPT

1 NAME

2 n = NUMMER
 alternativa = implicitni radek slovo
 pismo = STYLE BEFEHL
 barva = COLOR

\setupfittingpage [...¹,...] [...²,...]
OPT

1 NAME

2 pagestate = start stop
 prikaz = \...##1
 marginalie = stranka
 meritko = NUMMER
 papir = auto default NAME
 inherits: \nastavoramovani

\setupfloatcaption [...¹,...] [...²,...]
OPT

1 NAME

2 suffix = BEFEHL
 suffixseparator = BEFEHL
 suffixstopper = BEFEHL
 misto = vlevo vpravo nastred nizko vysoko mrizka prekryv uvnitr vnejsi innermargin outermargin levyokraj
 pravyokraj lefthanging righthanging zaveseni vrsek spodek natahnout zadny implicitni
 prikaz = \...##1
 ciselny prikaz = \...##1
 textovy prikaz = \...##1
 mezerapred = inherits: \preskoc
 spaceinbetween = inherits: \preskoc
 mezeraza = inherits: \preskoc
 vzdalenost = DIMENSION
 mezi = BEFEHL
 pismo = STYLE BEFEHL
 barva = COLOR
 offsetvrsku = DIMENSION
 offsetspodku = DIMENSION
 cislo = ano ne zadny
 group = TEXT
 levyokraj = DIMENSION
 pravyokraj = DIMENSION
 innermargin = DIMENSION
 outermargin = DIMENSION
 zarovnnani = inherits: \nastavzarovnnani
 sirka = prizpusobive max DIMENSION
 minsirka = prizpusobive DIMENSION
 maxsirka = DIMENSION
 inherits: \setupcounter

\setupfontexpansion [...¹] [...²,...]
OPT

1 NAME

2 vector = NAME
 faktor = NUMMER
 natahnout = NUMMER
 shrink = NUMMER
 krok = NUMMER

\setupfontprotrusion [...¹] [...²,...]
OPT

1 NAME

2 vector = NAME
 faktor = NUMMER
 vlevo = NUMMER
 vpravo = NUMMER

\setupfonts [...^{*},...]

* language = ne auto

`\setupfontsolution [...1,...] [...2,...]`
OPT

1 NAME

2 goodies = FILE
 solution = NAME
 less = NAME
 more = NAME
 metoda = preroll split normalni reverse nahodny
 kriterium = NUMMER

`\setupforms [...*,...]`

* metoda = XML HTML PDF
 export = ano ne

`\setupformula [...1,...] [...2,...]`
OPT

1 NAME

2 misto = vlevo vpravo
 zarovnani = vlevo nastred vpravo flushleft center flushright normalni
 strut = ano ne
 vzdalenost = DIMENSION
 vlevo = BEFEHL
 vpravo = BEFEHL
 mezerapred = inherits: \preskoc
 mezeraza = inherits: \preskoc
 ciselnyprkaz = \...##1
 barva = COLOR
 stylciska = STYLE BEFEHL
 barvaciska = COLOR
 volba = zhustene tight nastred ramecek inherits: \nastavzakladnifont
 marginalie = ano ne standardni DIMENSION
 levyokraj = DIMENSION
 pravyokraj = DIMENSION
 alternativa = NAME
 odsadpristi = ano ne auto
 mrizka = inherits: \snaptogrid
 ramecek = cislo
 inherits: \setupcounter

`\setupformulaframed [...1,...] [...2,...]`
OPT

1 NAME

2 inherits: \nastavoramovani

`\setupframedcontent [...1,...] [...2,...]`
OPT

1 NAME

2 vlevo = BEFEHL
 vpravo = BEFEHL
 leftoffser = DIMENSION
 pravyoffset = DIMENSION
 offsetvrsku = DIMENSION
 offsetspodku = DIMENSION
 korekceradku = ano ne
 inherits: \nastavoramovani

`\setupframedtext [...1,...] [...2,...]`
OPT

1 NAME

2 vlevo = BEFEHL
 vpravo = BEFEHL
 vnitrni = BEFEHL
 misto = vlevo vpravo nastred zadny
 korekcehloubky = zap vyp
 zakladnifont = inherits: \nastavzakladnifont
 odsazovani = inherits: \nastavodsazovani
 pismo = STYLE BEFEHL
 barva = COLOR
 inherits: \nastavoramovani inherits: \setupplacement

`\setupglobalreferenceprefix [...]`

* + - TEXT

`\setupheadalternative [...1,...] [...2,...]`
OPT

1 NAME

2 alternativa = horizontalne vertikalne
renderingsetup = NAME

`\setuphelp [...1,...] [...2,...]`
OPT

1 NAME

2 inherits: \nastavoramovani

`\setuphigh [...1,...] [...2,...]`
OPT

1 NAME

2 vzdalenost = DIMENSION
up = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\setuphighlight [...1,...] [...2,...]`
OPT

1 NAME

2 prikaz = ano ne
pismo = STYLE BEFEHL
barva = COLOR

`\setuphyphenation [...*,...]`

* metoda = original tex implicitni hyphenate expanded traditional zadny

`\setupcharacterkerning [...1,...] [...2,...]`
OPT

1 NAME

2 faktor = max NUMMER
sirka = DIMENSION
features = NAME
pismo = STYLE BEFEHL
barva = COLOR

`\setupcharacterspacing [...1] [...2] [...3,...]`
OPT

1 NAME

2 NUMMER

3 vlevo = NUMMER
vpravo = NUMMER
alternativa = 0 1

`\setupchemical [...,1...] [...,2...,...]`
OPT

```
1 NAME

2 strut      = inherits: \value-strut
  sirka      = prizpusobive zadny NUMMER
  vyska      = prizpusobive zadny NUMMER
  vlevo      = prizpusobive zadny NUMMER
  vpravo     = prizpusobive zadny NUMMER
  vrsek      = prizpusobive zadny NUMMER
  spodek     = prizpusobive zadny NUMMER
  meritko    = male stredni velke normalni NUMMER
  rotace     = NUMMER
  symzarovnani = auto
  osa        = zap vyp
  barvaramecku = COLOR
  tloustkalinky = DIMENSION
  offset     = DIMENSION
  jednotka   = DIMENSION
  faktor     = NUMMER
  ramecek    = zap vyp
  barvalinky  = COLOR
  zakladnifont = inherits: \nastavzakladnifont
  velikost   = male stredni velke
  pismo     = STYLE BEFEHL
  barva      = COLOR
```

`\setupchemicalframed [...,1...] [...,2...,...]`
OPT

```
1 NAME

2 inherits: \nastavoramovani
```

`\setupindentedtext [...,1...] [...,2...,...]`
OPT

```
1 NAME

2 pred      = BEFEHL
  po        = BEFEHL
  vzdalenost = DIMENSION
  vzor      = TEXT
  text      = TEXT
  sirka     = prizpusobive siroky DIMENSION
  oddelovac = BEFEHL
  pismo     = STYLE BEFEHL
  barva     = COLOR
  stylhlavicky = STYLE BEFEHL
  barvahlavicky = COLOR
```

`\setupindex [...,1...] [...,2...,...]`
OPT

```
1 NUMMER

2 inherits: \nastavrejstrik
```

`\setupinitial [...,1...] [...,2...,...]`
OPT

```
1 NAME

2 n      = NUMMER
  m      = NUMMER
  pred   = BEFEHL
  vzdalenost = DIMENSION
  hoffset = DIMENSION
  voffset = radek DIMENSION
  pismo   = STYLE BEFEHL
  barva   = COLOR
  font    = FONT
  text    = TEXT
  misto   = marginalie text
  metoda = prvni posledni auto zadny
```

`\setupinsertion [...,1...] [...,2...,...]`
OPT

```
1 NAME

2 misto = stranka text sloupce firstcolumn lastcolumn
```

\setupitaliccorrection [...,*...]

* text vzdy globalne zadny

\setupitemgroup [...¹] [...²,...] [...³,...] [...⁴,...=...]

OPT

OPT

OPT

1 NAME

2 kazdy NUMMER

3 uvod nahodny pokracovat zhustene autouvod siroky text pred po zadnabila marginalie naokraji naokraji dotextu
uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbalene opakovat norepeat reverse sloupce jedna dve
tri ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto horizontalne NAME

4 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavicce = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyyokraj = ano ne standardni DIMENSION
zarovnnani = inherits: \nastavzarovnnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitrni = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
predelmista = ano ne
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
inherits: \setupcounter

`\setupitemgroup [...,1...] [...,2...,...]`
OPT

1 NAME NAME:NUMMER

2 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 predhlavickou = BEFEHL
 pohlavicce = BEFEHL
 textvlevo = BEFEHL
 textvpravo = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 faktor = NUMMER
 krok = DIMENSION
 sirka = DIMENSION
 vzdalenost = DIMENSION
 volba = uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraji
 naokraji dotextu uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbalene opakovat
 norepeat reverse sloupce jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky
 NUMMER*semknuto horizontalne NAME
 marginalie = ano ne standardni DIMENSION
 levyokraj = ano ne standardni DIMENSION
 pravyokraj = ano ne standardni DIMENSION
 zarovnani = inherits: \nastavzarovnani
 odsazovani = inherits: \nastavodsazovani
 start = NUMMER
 symzarovnani = vlevo nastred vpravo flushleft center flushright
 symbol = NAME
 n = NUMMER
 odsadpristi = ano ne auto
 vnitrni = BEFEHL
 prikaz = CSNAME
 polozky = NUMMER
 maxsirka = DIMENSION
 itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
 alignsymbol = ano ne
 textdistance = male stredni velke zadny mezera DIMENSION
 predelmista = ano ne
 pismeno = STYLE BEFEHL
 barva = COLOR
 stylhlavicky = STYLE BEFEHL
 barvahlavicky = COLOR
 stylsnacky = STYLE BEFEHL
 barvaznacky = COLOR
 stylsymboly = STYLE BEFEHL
 barvasymbolu = COLOR
 inherits: \setupcounter

`\nastaveniITEMGROUP [...,1...] [...,2...] [...,3...,...]`
OPT OPT OPT

1 kazdy NUMMER

2 inherits: \setupitemgroup

3 inherits: \setupitemgroup

instances: vycet

`\setupitemize [...,1...] [...,2...] [...,3...,...]`
OPT OPT OPT

1 kazdy NUMMER

2 inherits: \setupitemgroup

3 inherits: \setupitemgroup

\setuplabel [...¹,...] [...²,...]

OPT

```

1  NAME

2  titul          = ano ne
   cislo          = ano ne
   ciselnyprikaz  = \...##1
   vzdalenosttitulek = DIMENSION
   styltitulek    = STYLE BEFEHL
   barvatitulek   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   vlevo          = BEFEHL
   vpravo         = BEFEHL
   symbol         = BEFEHL
   starter        = BEFEHL
   predel         = BEFEHL
   propojeni      = NAME
   counter        = NAME
   uroven         = NUMMER
   text           = TEXT
   headcommand    = \...##1
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   alternativa    = vlevo vpravo naokrajiv vlevo ivpravo marginalie lev yokraj prav yokraj innermargin outermargin
                   semknuto visici vrsek prikaz dotextu NAME

   zarovnnani     = inherits: \nastavzarovnnani
   headalign      = inherits: \nastavzarovnnani
   odsazovani     = inherits: \nastavodsazovani
   obrazovka      = ano ne
   odsadpristi    = ano ne auto
   sirka          = prizpusobive siroky radek DIMENSION
   vzdalenost     = zadny DIMENSION
   zaveseni       = prizpusobive siroky zadny marginalie NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expanzen       = ano ne xml
   vzor           = TEXT
   marginalie     = ano ne standardni DIMENSION
   pismo          = STYLE BEFEHL
   barva          = COLOR
   stylhlavicky   = STYLE BEFEHL
   barvahlavicky  = COLOR
   inherits: \setupcounter

```

\setuplayer [...¹,...] [...²,...]

OPT

```

1  NAME

2  status          = start stop pokracovat dalsi opakovat
   volba           = test
   stranka         = NUMMER
   sirka           = DIMENSION
   vyska           = DIMENSION
   region          = NAME
   rotace          = vlevo vpravo uvnitr vnejsi NUMMER
   position        = ano ne prekryv
   hoffset         = max DIMENSION
   voffset         = max DIMENSION
   offset          = DIMENSION
   dx              = DIMENSION
   dy              = DIMENSION
   sx              = NUMMER
   sy              = NUMMER
   x               = DIMENSION
   y               = DIMENSION
   roh             = vlevo nastred vpravo vrsek spodek
   misto           = mrizka vlevo nastred vpravo vrsek spodek radek l c r m t b g
   radek           = NUMMER
   sloupec         = NUMMER
   smer            = normalni reverse
   oboustranne     = ano ne
   metoda          = prizpusobive prekryv
   opakovat        = ano
   prednastaveni   = lefttop righttop leftbottom rightbottom nastred middletop middlebottom middleleft middleright
                   lefttopleft lefttopright NAME

```

`\setuplayeredtext` [...¹,...] [...²,...]

OPT

1 NAME

2 pismo = STYLE BEFEHL
 barva = COLOR
 inherits: \nastavoramovani

`\setuplayouttext` [...¹,...] [...²,...] [...³,...]

OPT

1 vrsek zahlevi text upati spodek

2 text marginalie hrana

3 status = start stop prazdne vysoko zadny normalni zadneznaceni NAME
 pismo = STYLE BEFEHL
 barva = COLOR
 strut = ano ne
 n = NUMMER
 pred = BEFEHL
 po = BEFEHL
 stylvlevo = STYLE BEFEHL
 stylvpravo = STYLE BEFEHL
 barvavlevo = COLOR
 barvavpravo = COLOR
 sirka = DIMENSION
 sirkavlevo = DIMENSION
 sirkavpravo = DIMENSION

`\setuplinefiller` [...¹,...] [...²,...]

OPT

1 NAME

2 misto = vlevo vpravo obe
 rozsah = vlevo vpravo lokalne
 mp = NAME
 vyska = DIMENSION
 hloubka = DIMENSION
 vzdalenost = DIMENSION
 threshold = DIMENSION
 tloustkalinky = DIMENSION
 pred = BEFEHL
 po = BEFEHL
 barva = COLOR
 styltextu = STYLE BEFEHL
 barvatextu = COLOR
 zarovnani = inherits: \nastavzarovnani

`\setuplinefillers` [...¹,...] [...²,...]

OPT

1 NAME

2 inherits: \setuplinefiller

`\setuplinenote` [...¹,...] [...²,...]

OPT

1 NAME

2 compress = ano ne
 compressmethod = separator predel mezera
 compressseparator = BEFEHL
 compressdistance = DIMENSION
 inherits: \setupnote

`\setuplinetable [...]1 [...]2 [...,...3...,...]`

OPT OPT

```
1 r c
2 liche sude zahlavi NUMMER
3 radky      = prizpusobive NUMMER
  pred       = BEFEHL
  po         = BEFEHL
  mezi       = BEFEHL
  natahnout  = ano ne DIMENSION
  maxsirka   = prizpusobive DIMENSION
  nvlevo     = NUMMER
  n          = NUMMER
  opakovat   = ano ne
  nx         = NUMMER
  sirka      = DIMENSION
  vyska      = prizpusobive radek DIMENSION
  vzdalenost = DIMENSION
  levyoffset = DIMENSION
  pravyoffset = DIMENSION
  zarovnani  = inherits: \nastavzarovnani
  pozadi     = barevne
  barvapozadi = COLOR
  xheight    = max DIMENSION
  xdepth     = max DIMENSION
  pismo      = STYLE BEFEHL
  barva      = COLOR
```

`\setuplistalternative [...]1,... [-,...,2...,...]`

OPT

```
1 NAME
2 pred      = BEFEHL
  po        = BEFEHL
  prikaz     = \...##1##2##3
  renderingsetup = NAME
  sirka      = DIMENSION
  vzdalenost = DIMENSION
  natahnout  = DIMENSION
  filler     = BEFEHL
```

`\setuplistextra [...]1,... [-,...,2...,...]`

OPT

```
1 NAME
2 pred = BEFEHL
  po   = BEFEHL
```

`\setuplocalfloats [...,...*...,...]`

```
* pred = BEFEHL
  po   = BEFEHL
  mezi = BEFEHL
```

`\setuplocalinterlinespace [...]1,... [-,...,2...,...]`

OPT

```
1 NAME
2 inherits: \nastavmeziradkovoumezeru
```

`\setuplocalinterlinespace [...]*,...`

OPT

```
* zap vyp reset auto male stredni velke NUMMER DIMENSION
```

`\setuplocalinterlinespace [...]*`

```
* NAME
```

`\setuplow [...,1...] [...,2...,...]`
OPT

1 NAME
 2 vzdalenost = DIMENSION
 down = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 vzdalenost = DIMENSION
 up = DIMENSION
 down = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 up = DIMENSION
 down = DIMENSION
 pismo = STYLE BEFEHL
 barva = COLOR

`\setupMPgraphics [...,*...,...]`

* barva = lokalne globalne
 mpy = FILE

`\setupMPinstance [...,1...] [...,2...,...]`
OPT

1 NAME
 2 formatovat = metafun mpost
 initializations = ano ne
 setups = NAME
 styltextu = STYLE BEFEHL
 barvatextu = COLOR
 extensions = ano ne
 metoda = binary decimal double scaled implicitni

`\setupMPpage [...,*...,...]`

* inherits: \setupfittingpage

`\setupMPvariables [...,1...] [...,2...,...]`
OPT

1 NAME
 2 KEY = VALUE

`\setupmarginblock [...,1...] [...,2...,...]`
OPT

1 NAME
 2 status = start stop
 sirka = DIMENSION
 pred = BEFEHL
 po = BEFEHL
 mezi = BEFEHL
 zarovnani = inherits: \nastavzarovnani
 pismo = STYLE BEFEHL
 barva = COLOR
 vrsek = BEFEHL
 spodek = BEFEHL
 misto = vlevo vpravo nastred naokraj
 vlevo = BEFEHL
 vpravo = BEFEHL

`\setupmargindata [...1,...] [...2,...]`
OPT

```
1 NAME

2 strut      = ano ne auto kap prizpusobive radek implicitni CHARACTER
  prikaz     = \...##1
  sirka      = DIMENSION
  zarovnani  = inherits: \nastavzarovnani
  anchor     = region text
  misto      = vlevo vpravo uvnitr vnejsi
  metoda    = vrsek radek prvni podlehloubky vyska
  category   = implicitni hrana
  rozsah     = lokalne globalne
  volba      = text odstavec
  marginalie = lokalne normalni marginalie hrana
  vzdalenost = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  dy         = DIMENSION
  bottomspace = DIMENSION
  threshold  = DIMENSION
  radek      = NUMMER
  stack      = ano pokracovat
  pismo     = STYLE BEFEHL
  barva      = COLOR
```

`\setupmarginframed [...1,...] [...2,...]`
OPT

```
1 NAME

2 inherits: \nastavoramovani
```

`\setupmarginrule [...1] [...2,...]`
OPT

```
1 NUMMER

2 inherits: \setupsidebar
```

`\setupmathalignment [...1,...] [...2,...]`
OPT

```
1 NAME

2 n      = NUMMER
  m      = NUMMER
  vzdalenost = DIMENSION
  zarovnani = vlevo nastred vpravo normalni
```

`\setupmathcases [...1,...] [...2,...]`
OPT

```
1 NAME

2 vlevo      = BEFEHL
  vpravo     = BEFEHL
  strut      = ano ne
  pismo     = STYLE BEFEHL
  vzdalenost = DIMENSION
  numberdistance = DIMENSION
```

`\setupmathematics [...1,...] [...2,...]`
OPT

```

1  NAME

2  openup           = ano ne
   sadasymbolu      = NAME
   functionstyle    = STYLE BEFEHL
   compact          = ano ne
   zarovnani        = l2r r2l
   bidi             = ano ne
   sygreek          = normalni kurziva zadny
   lcgreek          = normalni kurziva zadny
   ucgreek          = normalni kurziva zadny
   italics          = 1 2 3 4 zadny reset
   autopunctuation = ano ne vse
   setups           = NAME
   domain           = NAME reset
   styltextu        = STYLE BEFEHL
   barvatextu        = COLOR
   functioncolor     = COLOR
   integral         = limits nolimits autolimits displaylimits zadny
   stylealternative = NAME
   implicitni       = normalni kurziva
   fraction         = ams ctx

```

`\setupmathfence [...1,...] [...2,...]`
OPT

```

1  NAME

2  prikaz          = ano ne
   vlevo           = NUMMER
   stredni         = NUMMER
   vpravo          = NUMMER
   mathstyle       = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
   barva           = COLOR
   status          = auto

```

`\setupmathfraction [...1,...] [...2,...]`
OPT

```

1  NAME

2  vzdalenostvrsku = DIMENSION
   vzdalenostspodku = DIMENSION
   marginalie      = DIMENSION
   barva           = COLOR
   strut           = ano ne math tight
   alternativa     = uvnitr vnejsi obe
   linka           = ano ne auto
   vlevo           = NUMMER
   vpravo          = NUMMER
   tloustkalinky   = DIMENSION
   mathstyle       = STYLE BEFEHL
   vzdalenost      = ne zadny prekryv

```

`\setupmathframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \nastavoramovani

```

`\setupmathlabeltext [...1,...] [...2,...]`
OPT

```

1  SPRACHE

2  KEY = VALUE

```

`\setupmathmatrix [...1,...] [...2,...]`
OPT

```

1  NAME

2  vlevo           = BEFEHL
   vpravo          = BEFEHL
   strut           = ano ne NUMMER
   zarovnani       = vlevo nastred vpravo normalni
   pismo           = STYLE BEFEHL
   vzdalenost      = DIMENSION
   misto           = vrsek spodek vysoko nizko nivy normalni

```

`\setupmathornament [...,1...] [...,2...,...]`
OPT

1 NAME
 2 alternativa = mp
 barva = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathradical [...,1...] [...,2...,...]`
OPT

1 NAME
 2 alternativa = implicitni normalni mp
 barva = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathstackers [...,1...] [...,2...,...]`
OPT

1 NAME
 2 vlevo = BEFEHL
 vpravo = BEFEHL
 topcommand = \...##1
 bottomcommand = \...##1
 middlecommand = \...##1
 mp = NAME
 mpheight = DIMENSION
 mpdepth = DIMENSION
 mpoffset = DIMENSION
 barva = COLOR
 hoffset = DIMENSION
 voffset = DIMENSION
 minvyska = DIMENSION
 mindepth = DIMENSION
 mathclass = rel ord
 offset = min max normalni
 misto = vrsek spodek vysoko nizko nastred NUMBER
 strut = ano ne
 alternativa = normalni implicitni mp
 minsirka = DIMENSION
 vzdalenost = DIMENSION
 moffset = DIMENSION
 order = normalni reverse
 mathlimits = ano ne

`\setupmathstyle [...,*,...]`

* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

`\setupmixedcolumns [...,1...] [...,2...,...]`
OPT

1 NAME
 2 mrizka = inherits: \definegridsnapping
 tloustkalinky = DIMENSION
 metoda = otr box
 pred = BEFEHL
 po = BEFEHL
 vzdalenost = DIMENSION
 n = NUMMER
 maxvyska = DIMENSION
 maxsirka = DIMENSION
 krok = DIMENSION
 profile = NAME
 zarovnani = inherits: \nastavzarovnani
 setups = NAME
 rovnovaha = ano ne
 splitmethod = zadny fixne
 alternativa = lokalne globalne
 internalgrid = radek pulradku
 oddelovac = linka
 strut = ano ne
 barva = COLOR
 barvalinky = COLOR
 smer = normalni reverse
 inherits: \nastavoramovani

```
\setupmodule [...]1 [...]2...]
```

OPT

1 FILE

2 test = ano ne
KEY = VALUE

```
\setupnotation [...]1 [...]2...]
```

OPT

1 NAME

2 titul = ano ne
cislo = ano ne
typ = note
ciselnyprikaz = \...##1
vzdalenosttitulek = DIMENSION
styltitulek = STYLE BEFEHL
barvatitulek = COLOR
titlecommand = \...##1
titleleft = BEFEHL
titleright = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
symbol = BEFEHL
starter = BEFEHL
predel = BEFEHL
propojeni = NAME
counter = NAME
uroven = NUMMER
text = TEXT
headcommand = \...##1
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
alternativa = vlevo vpravo naokrajz ivlevo ivpravo marginalie levokraj pravokraj innermargin outermargin
semknuto visici vrsek prikaz note NAME
zarovnani = inherits: \nastavzarovnani
headalign = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
obrazovka = ano ne
odsadpristi = ano ne auto
sirka = prizpusobive siroky radek DIMENSION
vzdalenost = zadny DIMENSION
zaveseni = prizpusobive siroky zadny marginalie NUMMER
closesymbol = BEFEHL
closecommand = \...##1
expanzen = ano ne xml
vzor = TEXT
marginalie = ano ne standardni DIMENSION
pismo = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
inherits: \setupcounter

\setupnote [...¹...] [...²...] OPT

```

1  NAME

2  interakce      = ano ne cislo text vse
   symbolcommand  = \...##1
   textovyprikaz  = \...##1
   indikator      = ano ne
   oddelovactextu = BEFEHL
   sirka          = DIMENSION
   vyska          = DIMENSION
   vzdalenost     = DIMENSION
   rulecommand    = BEFEHL
   linka          = zap vyp normalni vlevo vpravo prikaz odstavec
   split          = tolerantni striktni velmistriktni NUMMER
   faktor         = NUMMER
   misto          = text stranka vysoko spodek zadny sloupce firstcolumn lastcolumn
   dalsi          = BEFEHL
   n              = NUMMER
   barvalinky     = COLOR
   tloustkalinky  = DIMENSION
   setups         = NAME
   meziradkovamezera = NAME
   odstavec       = ano ne
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   rozsah         = stranka
   vzdalenostsloupcu = DIMENSION
   pokračovat     = ano ne
   alternativa    = mrizka fixne sloupce note zadny
   kriterium      = stranka
   zakladnifont   = inherits: \nastavzakladnifont
   zarovnani      = inherits: \nastavzarovnani
   styltextu      = STYLE BEFEHL
   barvatextu     = COLOR
   anchor         = dalsi
   inherits: \nastavoramovani

```

\setupoffset [...^{*}...]

* inherits: \setupoffsetbox

\setupoffsetbox [...^{*}...]

```

*  x              = DIMENSION
   y              = DIMENSION
   levyoffset     = DIMENSION
   pravyoffset    = DIMENSION
   offsetvrsku    = DIMENSION
   offsetspodku   = DIMENSION
   metoda        = fixne
   sirka          = DIMENSION
   vyska          = DIMENSION
   hloubka        = DIMENSION
   misto          = vlevo nastred vpravo vrsek spodek radek l c r m t b g

```

\setupoperatortext [...¹...] [...²...] OPT

```

1  SPRACHE
2  KEY = VALUE

```

\setupoutputroutine [...¹...] [...²...] OPT

```

1  NAME
2  KEY = CSNAME

```

\setupoutputroutine [...^{*}...]

* NAME

\setuppagegrid [...¹,...] [...²,...]
OPT

1 NAME
2 n = NUMBER
nvlevo = NUMBER
nvpravo = NUMBER
sirka = DIMENSION auto
vzdalenost = DIMENSION
radky = NUMBER
maxsirka = DIMENSION
maxvyska = DIMENSION
smer = normalni reverse
stranka = inherits: \strana
inherits: \nastavoramovani

\setuppagegridarea [...¹,...] [...²,...]
OPT

1 NAME
2 status = start stop opakovat
x = NUMBER
y = NUMBER
nx = NUMBER
ny = NUMBER
pismo = STYLE BEFEHL
barva = COLOR
clipoffset = DIMENSION
pravyoffset = DIMENSION
inherits: \nastavoramovani

\setuppagegridareatext [...¹] [...²]

1 NAME
2 TEXT

\setuppagegridlines [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppagegridspan [...¹,...] [...²,...]
OPT

1 NAME
2 n = NUMBER
pismo = STYLE BEFEHL
barva = COLOR
pred = BEFEHL
po = BEFEHL
inherits: \nastavoramovani

\setuppagegridstart [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppagechecker [...¹,...] [...²,...]
OPT

1 NAME
2 radky = NUMBER
offset = DIMENSION
metoda = 0 1 2 3
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL

`\setuppageinjection [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 status      = predchozi dalsi NUMMER
  prodleva    = ano ne
  alternativa = obrazek buffer setups zadny NAME
  stranka     = inherits: \strana
  pagestate   = start stop
  n           = NUMMER
  inherits: \nastavoramovani
```

`\setuppageinjectionalternative [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 renderingsetup = NAME
```

`\setuppageshift [...1...] [...2...] [...3...]`
OPT OPT

```
1 stranka papir
2 NAME
3 NAME
```

`\setuppagestate [...,*...,...]`

```
* prodleva = ano ne
```

`\setuppairedbox [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 pred      = BEFEHL
  po        = BEFEHL
  mezi      = BEFEHL
  misto     = vlevo nastred vpravo vrsek spodek vysoko nizko
  n         = NUMMER
  vzdalenost = DIMENSION
  zakladnifont = inherits: \nastavzakladnifont
  sirka     = DIMENSION
  vyska     = DIMENSION
  maxsirka  = DIMENSION
  maxvyska  = DIMENSION
  zarovnani = inherits: \nastavzarovnani
  pismo     = STYLE BEFEHL
  barva     = COLOR
```

`\nastaveniPAIREDBOX [...,*...,...]`

```
* inherits: \setuppairedbox
```

```
instances: legenda
```

`\setuppaper [...,*...,...]`

```
* inherits: \nastavvelikostpapiru
```

`\setupparagraph [...,1...] [...,2...,...]`
OPT

```
1 NAME
2 pismo     = STYLE BEFEHL
  barva     = COLOR
  zarovnani = inherits: \nastavzarovnani
  setups    = NAME
```

`\setupparagraphintro [...,1...] [...2...]`

```
1 reset kazdy prvni dalsi
2 BEFEHL
```

`\setupparallel [...]1 [...]2,...] [...]3,...,...`

```
1 NAME
2 NAME
3 setups      = NAME
  start       = NUMMER
  n           = NUMMER
  kriterium   = vse
```

`\setupperiods [...]*,...,...`

```
* n           = NUMMER
  sirka       = DIMENSION prizpusobive
  vzdalenost  = DIMENSION
  symbol      = BEFEHL
```

`\setupplacement [...]1,...] [...]2,...,...`
OPT

```
1 NAME
2 pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  mrizka      = inherits: \snaptogrid
  korekceradku = zap vyp
  korekcehloubky = zap vyp
  marginalie  = ano ne standardni
```

`\setuppositionbar [...]*,...,...`

```
* pismeno     = STYLE BEFEHL
  barva       = COLOR
  n           = NUMMER
  min         = NUMMER
  max         = NUMMER
  text        = TEXT
  sirka       = DIMENSION
  vyska       = DIMENSION
  hloubka     = DIMENSION
```

`\setupprefixtext [...]1,...] [...]2,...,...`
OPT

```
1 SPRACHE
2 KEY = VALUE
```

`\setupprocessor [...]1,...] [...]2,...,...`
OPT

```
1 NAME
2 status      = start stop
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  prikaz      = \...##1
  pismeno     = STYLE BEFEHL
  barva       = COLOR
```

`\setupprofile [...]1,...] [...]2,...,...`
OPT

```
1 NAME
2 vyska       = DIMENSION
  hloubka     = DIMENSION
  vzdalenost  = DIMENSION
  faktor      = NUMMER
  radky       = NUMMER
  metoda      = striktni fixne zadny
```

`\setupquotation [...]*,...,...`

```
* inherits: \setupdelimitedtext
```

\setuprealpagenumber [...,*...]

* inherits: \setupcounter

\setupreferenceformat [...,¹...] [...,²...] _{OPT}

1 NAME

2 popisek = * NAME
vlevo = BEFEHL
vpravo = BEFEHL
typ = implicitni text titul cislo stranka realpage
setups = NAME
autocase = ano ne
text = TEXT
pismeno = STYLE BEFEHL
barva = COLOR

\setupreferenceprefix [...]

* + - TEXT

\setupreferencestructureprefix [...,¹...] [...,²...] [...,³...] _{OPT OPT}

1 NAME ABSCHNITT

2 implicitni

3 prefix = ano ne
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
numberseparatorset = NAME
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setuprenderingwindow [...,¹...] [...,²...] _{OPT}

1 NAME

2 akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
inherits: \nastavoramovani

\setups [...,*...]

* NAME

```

\setupscale [...,1...] [...,2...]
                        OPT
1  NAME

2  meritko      =  NUMMER
   xmeritko     =  NUMMER
   ymeritko     =  NUMMER
   sirka        =  DIMENSION
   vyska        =  DIMENSION
   hloubka      =  ano ne
   radky        =  NUMMER
   faktor       =  prizpusobive siroky max auto implicitni
   vfaktor      =  prizpusobive siroky max auto implicitni
   sfaktor      =  prizpusobive siroky max auto implicitni
   maxsirka     =  DIMENSION
   maxvyska     =  DIMENSION
   s            =  NUMMER
   sx           =  NUMMER
   sy           =  NUMMER
   equalwidth   =  DIMENSION
   equalheight  =  DIMENSION
   mrizka       =  ano prizpusobive vyska podlehloubky pulradku

```

```

\setupscript [...,1...] [...,2...]
                        OPT
1  NAME

2  metoda       =  hangul hanzi nihongo ethiopic thai test
   prednastaveni =  NAME
   features      =  auto

```

```

\setupselector [...,1...] [...,2...]
1  NAME

2  n = NUMMER
   m = NUMMER

```

```

\setupshift [...,1...] [...,2...]
                        OPT
1  NAME

2  pokracovat   =  ano ne
   jednotka     =  ex em pt in cm mm sp bp pc dd cc nc
   metoda       =  NUMMER
   dy           =  NUMMER
   zarovnnani   =  inherits: \nastavzarovnnani
   pismo        =  STYLE BEFEHL
   barva        =  COLOR

```

```

\setupsidebar [...,1...] [...,2...]
                        OPT
1  NAME

2  tloustkalinky =  DIMENSION
   barvalinky    =  COLOR
   alternativa   =  NUMMER
   offsetvrsku   =  DIMENSION
   offsetspodku  =  DIMENSION
   vzdalenost    =  DIMENSION
   vzdalenostlevehookraje =  DIMENSION
   uroven        =  NUMMER

```

```

\setupspellchecking [...,*...]
*  status = start stop
   metoda = 1 2 3
   seznam = NAME

```

`\setupstartstop [...1,...] [...2,...]`
OPT

```
1 NAME
2 pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  setups = NAME
  vlevo = BEFEHL
  vpravo = BEFEHL
  pismo = STYLE BEFEHL
  barva = COLOR
```

`\setupstretched [...*,...]`

* inherits: \setupcharacterkerning

`\setupstruts [...*]`
OPT

* ano ne auto kap prizpusobive radek implicitni CHARACTER

`\setupstyle [...1,...] [...2,...]`
OPT

```
1 NAME
2 metoda = prikaz
  pismo = STYLE BEFEHL
  barva = COLOR
```

`\setupsbformula [...1,...] [...2,...]`
OPT

```
1 NAME
2 odsadpristi = ano ne auto
```

`\setups {...*,...}`

* NAME

`\setupTABLE [...1,...] [...2,...] [...3,...]`
OPT OPT OPT

```
1 r c x y row column prvni posledni start zahlavi kazdy liche sude jedna NUMMER -NUMMER
2 prvni least kazdy dve liche sude NUMMER -NUMMER
3 extras = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  barvahlavicky = COLOR
  stylhlavicky = STYLE BEFEHL
  vzdalenostlevehookraje = DIMENSION
  vzdalenostpravehookraje = DIMENSION
  vzdalenostsloupcu = DIMENSION
  maxsirka = DIMENSION
  setups = NAME
  sirkatextu = DIMENSION lokalne
  split = ano ne opakovat auto
  zahlavi = opakovat
  volba = natahnout tight
  pred = BEFEHL
  po = BEFEHL
  stejnastranka = pred po obe
  spaceinbetween = inherits: \preskoc
  splitoffset = DIMENSION
  aligncharacter = ano ne
  alignmentcharacter = TEXT number->TEXT text->TEXT
  vzdalenost = DIMENSION
  barva = COLOR
  pismo = math STYLE BEFEHL
  inherits: \nastavoramovani
```

`\setupTEXpage [...*,...]`

* inherits: \setupfittingpage

`\setuptabulation [...1,...] [...2,...]`
OPT

```
1 NAME

2 formatovat = TEMPLATE zadny
pred = BEFEHL
po = BEFEHL
vzdalenost = male stredni velke zadny prazdny podlehloubky mrizka DIMENSION
zarovnani = vlevo nastred vpravo dimension
linka = radek normalni
barvalinky = COLOR
tloustkalinky = DIMENSION
zakladnifont = inherits: \nastavzakladnifont
odsazovani = ano ne
split = ano ne opakovat auto
jednotka = DIMENSION
marginalie = DIMENSION
vnitrni = BEFEHL
EQ = BEFEHL
zahlavi = ano opakovat text
ramecek = zap vyp
titul = TEXT
keeptogether = ano ne
```

`\setuptagging [...*,...]`

```
* status = start stop
metoda = auto
```

`\setuptaglabeltext [...1,...] [...2,...]`
OPT

```
1 SPRACHE

2 KEY = VALUE
```

`\setuptextbackground [...1,...] [...2,...]`
OPT

```
1 NAME

2 status = start stop
misto = text odstavec zadny
alternativa = NUMMER
mp = NAME
metoda = NAME
pozadi = barevne
barvapoziadi = COLOR
roh = pravouhly zaobleny
uroven = NUMMER
offsetpozadi = DIMENSION
pred = BEFEHL
po = BEFEHL
zarovnani = inherits: \nastavzarovnani
pomlcka = NUMMER
polomer = DIMENSION
ramecek = zap vyp
barvaramecku = COLOR
tloustkalinky = DIMENSION
voffset = DIMENSION
offsetramecku = DIMENSION
levyoffset = ano ne standardni DIMENSION
pravyoffset = ano ne standardni DIMENSION
offsetvrsku = male stredni velke radek DIMENSION
offsetspodku = male stredni velke radek DIMENSION
pismo = STYLE BEFEHL
barva = COLOR
```

`\setuptextflow [...1,...] [...2,...]`
OPT

```
1 NAME

2 sirka = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR
```

\setuptooltip [...,¹...] [...,²...,...]
OPT

1 NAME

2 misto = vlevo nastred vpravo
inherits: \nastavoramovani

\setupunit [...,¹...] [...,²...,...]
OPT

1 NAME

2 metoda = 1 2 3 4 5 6
language = SPRACHE
alternativa = text matematika
order = reverse normalni
oddelovac = male stredni velke normalni zadny NAME
mezera = male stredni velke normalni zadny NAME
pismo = STYLE BEFEHL
barva = COLOR

\setupunittext [...,¹...] [...,²...,...]
OPT

1 SPRACHE

2 KEY = VALUE

\setupuserpagenumber [...,^{*}...,...]

* viewerprefix = TEXT
status = start stop zadny drzet prazdne
inherits: \setupcounter

\setupversion [...]

* koncept soubor docasne finalni NAME

\setupviewerlayer [...,^{*}...,...]

* titul = TEXT
status = start stop
export = ano ne
tisknutelne = ano ne
rozsah = lokalne globalne
metoda = zadny prikaz

\setupvspacing [...,^{*}...]
OPT

* inherits: \vspacing

\setupwithargument {...} {...¹} {...²}

1 NAME

2 CONTENT

\setupwithargumentswapped {...} {...¹} {...²}

1 CONTENT

2 NAME

\setupxml [...,^{*}...,...]

* implicitni = skryte zadny text
compress = ano ne

`\setupxtable [...1,...2] [...2,...1,...]`
OPT

1 NAME

2 sirkatextu = DIMENSION lokalne
zakladnifont = inherits: \nastavzakladnifont
spaceinbetween = inherits: \preskoc
volba = tight max natahnout sirka vyska fixne
vyskatextu = DIMENSION
maxsirka = DIMENSION
vzdalenostsloupcu = DIMENSION
vzdalenostlevehookraje = DIMENSION
vzdalenostpravehookraje = DIMENSION
zahlavi = opakovat
upati = opakovat
tloustkalinky = DIMENSION
split = ano ne opakovat auto
splitoffset = DIMENSION
stejnastranka = pred po obe
vzdalenost = DIMENSION
inherits: \nastavoramovani

`\setuvalue {...1} {...2}`

1 NAME
2 CONTENT

`\setuxvalue {...1} {...2}`

1 NAME
2 CONTENT

`\setvalue {...1} {...2}`

1 NAME
2 CONTENT

`\setvariable {...1} {...2} {...3}`

1 NAME
2 KEY
3 VALUE

`\setvariables [...1] [...2,...1,...]`

1 NAME

2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\setvboxregister ... {...1} {...2}`

1 CSNAME NUMBER
2 CONTENT

`\setvisualizerfont [...1]`
OPT

* FONT

`\setvtopregister ... {...1} {...2}`

1 CSNAME NUMBER
2 CONTENT

<pre>\setwidthof ¹... \to ²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\setxmeasure {...} {...}</pre> <pre>1 NAME</pre> <pre>2 DIMENSION</pre>
<pre>\setxvalue ¹ {...} ² {...}</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\setxvariable ¹ {...} ² {...} ³ {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 VALUE</pre>
<pre>\setxvariables [¹...] [²...,...]</pre> <pre>1 NAME</pre> <pre>2 set = BEFEHL</pre> <pre>reset = BEFEHL</pre> <pre>KEY = VALUE</pre>
<pre>\sfrac {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 CONTENT</pre>
<pre>\shapedhbox {...}</pre> <pre>* CONTENT</pre>
<pre>\shiftdown {...}</pre> <pre>* CONTENT</pre>
<pre>\shiftup {...}</pre> <pre>* CONTENT</pre>
<pre>\SHIFT {...}</pre> <pre>* CONTENT</pre> <pre>instances: shiftup shiftdown</pre>
<pre>\showallmakeup</pre>
<pre>\showattributes</pre>
<pre>\showboxes</pre>

<pre> \showbtxdatasetauthors [..., ...[*]..., ...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [...[*]] OPT * NAME </pre>
<pre> \showbtxdatasetcompleteness [..., ...[*]..., ...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...[*]] OPT * NAME </pre>
<pre> \showbtxdatasetfields [..., ...[*]..., ...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...[*]] OPT * NAME </pre>
<pre> \showbtxfields [..., ...[*]..., ...] OPT * rotace = NUMBER specification = NAME </pre>
<pre> \showbtxfields [...[*]] OPT * NAME </pre>
<pre> \showbtxhashedauthors [...[*]] OPT * TEXT </pre>
<pre> \showbtxtables [...[*]] OPT * TEXT </pre>
<pre> \showcolorbar [...[*]] * COLOR </pre>
<pre> \showcolorcomponents [...[*]] * COLOR </pre>
<pre> \showcolorset [...[*]] * COLOR </pre>
<pre> \showcolorstruts </pre>

\showcounter [...] * NAME
\showdirectives
\showdirlsinmargin
\showedebuginfo
\showexperiments
\showfont [...] ¹ [...] ² [...] <div> <div>1 FONT</div> <div>2 NUMMER</div> <div>OPT</div> </div>
\showfontdata
\showfontkerns
\showfontparameters
\showfontstrip [...]*[...] * inherits: \nastavzakladnifont
\showfontstyle [...] ¹ [...] [...] ² [...] [...] ³ [...] [...] ⁴ [...] <div> <div>1 inherits: \nastavzakladnifont</div> <div>2 rm ss tt mm hw cg</div> <div>3 tf bf it sl bi bs</div> <div>4 vse NUMMER</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> <div>OPT</div> </div>
\showglyphs
\showgridsnapping
\showhelp {...} ¹ [...] ² <div> <div>1 TEXT</div> <div>2 REFERENCE</div> </div>
\showhyphenationtrace [...] ¹ [...] ² <div> <div>1 SPRACHE</div> <div>2 TEXT</div> <div>OPT</div> </div>
\showhyphens {...} * TEXT
\showchardata {...} * TEXT

\showcharratio {...} * TEXT
\showinjector [...,*,...] <div>OPT</div> * NAME
\showjustification
\showkerning {...} * TEXT
\showlayoutcomponents
\showligature {...} * TEXT
\showligatures [...] * FONT
\showlogcategories
\showmargins
\showmessage {... ¹ } {... ² } {... ³ ,...} 1 NAME 2 NAME NUMBER 3 TEXT
\showminimalbaseline
\shownextbox \... {... ¹ } {... ² } 1 CSNAME 2 CONTENT
\showotfcomposition {... ¹ } {... ² } {... ³ } 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
\showparentchain \... {... ¹ } {... ² } 1 CSNAME 2 NAME
\showsetupsdefinition [...] * NAME
\showtimer {...} * TEXT

<code>\showtokens [...]</code> * NAME
<code>\showtrackers</code>
<code>\showvalue {...}</code> * NAME
<code>\showvariable {...} {...}</code> 1 NAME 2 KEY
<code>\showwarning {...} {...} {...,<small>3</small>...}</code> 1 NAME 2 NAME NUMBER 3 TEXT
<code>\schovejbloky [...,<small>1</small>...] [...,<small>2</small>...] [<small>3</small>...]</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 + -
<code>\simplealignedbox {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
<code>\simplealignedboxplus {...} {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 TEXT 4 CONTENT
<code>\simplealignedspreadbox {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT
<code>\simplegroupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\simplereversealignedbox {...} {...} {...}</code> 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi
- 3 TEXT
- 4 CONTENT

`\singalcharacteralign {...} {...}`

- 1 NUMMER
- 2 NUMMER

`\singlebond`

`\sixthofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\sklonene`

`\sklonenetucne`

`\slicepages [...]1 [...,...2...,...]OPT [...,...3...,...]OPT`

- 1 FILE
- 2 offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
n = NUMMER
- 3 offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
sirka = DIMENSION
vyska = DIMENSION
n = NUMMER

`\sloupec [...]*...,...]OPT`

- * inherits: \columnbreak

`\slovenianNumerals {...}`

- * NUMMER

`\sloveniannumerals {...}`

- * NUMMER

`\slovo {...}`

- * TEXT

$\backslash\text{slovovpravo}$ [¹ ...] { ² ...} <small>OPT</small> 1 vpravo DIMENSION 2 CONTENT
$\backslash\text{smallbodyfont}$
$\backslash\text{smallcappedcharacters}$ {...} * NUMMER
$\backslash\text{smallcappedromannumerals}$ {...} * NUMMER
$\backslash\text{smaller}$
$\backslash\text{smallskip}$
$\backslash\text{smash}$ [¹ ...] { ² ...} <small>OPT</small> 1 w h d t b 2 CONTENT
$\backslash\text{smashbox}$... * CSNAME NUMMER
$\backslash\text{smashboxed}$... * CSNAME NUMMER
$\backslash\text{smashedhbox}$ [¹ ...] { ² ...} <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{smashedvbox}$ [¹ ...] { ² ...} <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{snaptogrid}$ [¹ ...] \^ ² ... { ³ ...} <small>OPT</small> 1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME 2 CSNAME 3 CONTENT
$\backslash\text{snaptogrid}$ [..., ¹ ...] \^ ² ... { ³ ...} <small>OPT</small> 1 inherits: \definegridsnapping 2 CSNAME 3 CONTENT
$\backslash\text{someheadnumber}$ [¹ ...] [² ...] 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni

<p><code>\somekindoftab [...[*]...]</code> <small>OPT</small></p> <p>* <code>alternativa</code> = <code>horizontalne</code> <code>vertikalne</code> <code>sirka</code> = <code>DIMENSION</code> <code>vyska</code> = <code>DIMENSION</code> <code>n</code> = <code>NUMMER</code> <code>m</code> = <code>NUMMER</code></p>
<code>\somalocalfloat</code>
<p><code>\somenamedheadnumber {...} {...}</code></p> <p>1 <code>ABSCHNITT</code></p> <p>2 <code>predchozi</code> <code>aktualni</code> <code>dalsi</code> <code>prvni</code> <code>posledni</code></p>
<p><code>\someplace {...} {...} {...} {...} {...} [...]</code></p> <p>1 <code>TEXT</code></p> <p>2 <code>TEXT</code></p> <p>3 <code>TEXT</code></p> <p>4 <code>TEXT</code></p> <p>5 <code>TEXT</code></p> <p>6 <code>REFERENCE</code></p>
<p><code>\SORTING [...¹] {...²}</code> <small>OPT</small></p> <p>1 <code>NAME</code></p> <p>2 <code>CONTENT</code></p> <p><code>instances: logo</code></p>
<p><code>\spanishNumerals {...}</code></p> <p>* <code>NUMMER</code></p>
<p><code>\spanishnumerals {...}</code></p> <p>* <code>NUMMER</code></p>
<p><code>\speech [...¹] {...²}</code> <small>OPT</small></p> <p>1 <code>SPRACHE</code></p> <p>2 <code>CONTENT</code></p>
<p><code>\splitdfrac {...} {...}</code></p> <p>1 <code>CONTENT</code></p> <p>2 <code>CONTENT</code></p>
<p><code>\splitfilename {...}</code></p> <p>* <code>FILE</code></p>
<p><code>\splitfrac {...¹} {...²}</code></p> <p>1 <code>CONTENT</code></p> <p>2 <code>CONTENT</code></p>
<code>\splitoffbase</code>

<code>\splitofffull</code>
<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens</code> ¹ ... \from ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> ¹ ... \at ² ... \to \ ³ ... \and \ ⁴ ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> ... * CSNAME NUMBER
<code>\sqrt</code> [¹ ...] { ² ...} <small>OPT</small> 1 TEXT 2 CONTENT
<code>\stackrel</code> { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
<code>\stanovcislona</code> <code>\pisu</code> [[*] ...] * ABSCHNITT
<code>\stanovcharakteristickuseznamu</code> [..., ¹ ...] [..., ² ...,...] <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam
<code>\startalign</code> [..., [*] ...,...] ... \stopalign <small>OPT</small> * inherits: \setupmathalignment
<code>\startalignment</code> [..., [*] ...] ... \stopalignment * inherits: \nastavzarovnani

<pre> \startallmodes [...,*...] ... \stopallmodes * NAME </pre>
<pre> \startaside [...¹] [...²,...] ... \stopaside OPT OPT 1 SPRACHE 2 inherits: \startzuzeni </pre>
<pre> \startattachment [...¹] [...²,...²,...] ... \stopattachment OPT OPT 1 NAME 2 inherits: \setupattachment </pre>
<pre> \startATTACHMENT [...¹] [...²,...²,...] ... \stopATTACHMENT OPT OPT 1 NAME 2 inherits: \setupattachment instances: attachment </pre>
<pre> \startbar [...] ... \stopbar * NAME </pre>
<pre> \startbarva [...] ... \stopbarva * COLOR </pre>
<pre> \startbitmapimage [...,*...] ... \stopbitmapimage * barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER </pre>
<pre> \startblockquote [...¹] [...²,...] ... \stopblockquote OPT OPT 1 SPRACHE 2 inherits: \startzuzeni </pre>
<pre> \startboxedcolumns [...,*...] ... \stopboxedcolumns OPT * inherits: \setupmixedcolumns </pre>
<pre> \startbtxlabeltext [...¹] [...²] ... \stopbtxlabeltext OPT 1 SPRACHE 2 KEY </pre>
<pre> \startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions * NAME </pre>
<pre> \startbuffer [...[*]] ... \stopbuffer OPT * NAME </pre>
<pre> \startBUFFER ... \stopBUFFER instances: skryt </pre>

<pre> \startcases [...,*...,...] ... \stopcases OPT * inherits: \setupmathcases </pre>
<pre> \startcast [...,*...,...] [...,*...,...] ... \stopcast OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE </pre>
<pre> \startcatcodetable *... ... \stopcatcodetable * CSNAME </pre>
<pre> \startcenteraligned ... \stopcenteraligned </pre>
<pre> \startcitace [...¹,...²,...] ... \stopcitace OPT OPT 1 SPRACHE 2 inherits: \startzuzeni </pre>
<pre> \startcitovat [...*] ... \stopcitovat OPT * SPRACHE </pre>
<pre> \startcollect ... \stopcollect </pre>
<pre> \startcollecting ... \stopcollecting </pre>
<pre> \startcolorintent [...*] ... \stopcolorintent * knockout overprint zadny </pre>
<pre> \startcoloronly [...*] ... \stopcoloronly * COLOR </pre>
<pre> \startcolorset [...*] ... \stopcolorset * NAME </pre>
<pre> \startcolumnspan [...,*...,...] ... \stopcolumnspan OPT * inherits: \setupcolumnspan </pre>
<pre> \startcombination [...¹,...²,...] ... \stopcombination OPT OPT 1 NAME 2 inherits: \setupcombination </pre>
<pre> \startcombination [...¹,...²] ... \stopcombination OPT OPT 1 NAME 2 N*M </pre>
<pre> \startcontextcode ... \stopcontextcode </pre>

<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction ... \stopctxfunction</code> <code>* NAME</code>
<code>\startctxfunctiondefinition ... \stopctxfunctiondefinition</code> <code>* NAME</code>
<code>\startcurrentcolor ... \stopcurrentcolor</code>
<code>\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper</code>
<code>\startdelimited [...] [...] [...] ... \stopdelimited</code> <code>1 NAME</code> <code>2 SPRACHE</code> <code>3 inherits: \startzuzeni</code>
<code>\startdelimitedtext [...] [...] [...] ... \stopdelimitedtext</code> <code>1 NAME</code> <code>2 SPRACHE</code> <code>3 inherits: \startzuzeni</code>
<code>\startDELIMITEDTEXT [...] [...] [...] ... \stopDELIMITEDTEXT</code> <code>1 SPRACHE</code> <code>2 inherits: \startzuzeni</code> <code>instances: citace citovat blockquote speech aside</code>
<code>\startdisplaymath ... \stopdisplaymath</code>
<code>\startdmath ... \stopdmath</code>
<code>\startdocument [...] [...] [...] ... \stopdocument</code> <code>* inherits: \setupdocument</code>
<code>\startdodatký [...] [...] [...] ... \stopdodatký</code> <code>* zalozka = TEXT</code> <code>inherits: \nastavbloksekce</code>
<code>\starteffect [...] ... \stopeffect</code> <code>* NAME</code>
<code>\startEFFECT ... \stopEFFECT</code>
<code>\startembeddedxtable [...] [...] [...] ... \stopembeddedxtable</code> <code>* inherits: \setupxtable</code>
<code>\startembeddedxtable [...] [...] [...] ... \stopembeddedxtable</code> <code>* NAME</code>

$\backslash\text{startendnote}$ [\dots , [*] \dots] ... $\backslash\text{stopendnote}$ <small>OPT</small> * REFERENCE
$\backslash\text{startendnote}$ [\dots , [*] \dots , \dots] ... $\backslash\text{stopendnote}$ <small>OPT</small> * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE
$\backslash\text{startepilgy}$ [\dots , [*] \dots , \dots] ... $\backslash\text{stopetilgy}$ <small>OPT</small> * zalozka = TEXT inherits: \nastavbloksekce
$\backslash\text{startexceptions}$ [\dots] ... $\backslash\text{stopexceptions}$ * SPRACHE
$\backslash\text{startexpanded}$... $\backslash\text{stopexpanded}$
$\backslash\text{startexpandedcollect}$... $\backslash\text{stopexpandedcollect}$
$\backslash\text{startextendedcatcodetable}$ \... ... $\backslash\text{stopextendedcatcodetable}$ * CSNAME
$\backslash\text{startexternalfigurecollection}$ [\dots] ... $\backslash\text{stopexternalfigurecollection}$ * NAME
$\backslash\text{startfakt}$ [\dots] ¹ [\dots , \dots , ² \dots , \dots] ... $\backslash\text{stopfakt}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \nastavtabelaci
$\backslash\text{startfiguretext}$ [\dots] ¹ [\dots , \dots , ² \dots] { \dots } ³ ... $\backslash\text{stopfiguretext}$ <small>OPT</small> <small>OPT</small> 1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective 2 REFERENCE 3 TEXT
$\backslash\text{startfittingpage}$ [\dots] ¹ [\dots , \dots , ² \dots , \dots] ... $\backslash\text{stopfittingpage}$ <small>OPT</small> 1 NAME 2 inherits: \setupfittingpage
$\backslash\text{startFITTINGPAGE}$ [\dots , \dots , [*] \dots , \dots] ... $\backslash\text{stopFITTINGPAGE}$ <small>OPT</small> * inherits: \setupfittingpage instances: TEXpage MPpage
$\backslash\text{startfloatcombination}$ [\dots , \dots , [*] \dots , \dots] ... $\backslash\text{stopfloatcombination}$ <small>OPT</small> * inherits: \setupcombination

<p><code>\startfloatcombination [...]</code> ... <code>\stopfloatcombination</code></p> <p style="text-align: center;">OPT</p> <p>* N*M NAME</p>
<p><code>\startPLVOUCIOBJEKTtext [...,¹...] [...,²...] {...³} ... \stopPLVOUCIOBJEKTtext</code></p> <p style="text-align: center;">OPT OPT</p> <p>1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startfont [...]</code> ... <code>\stopfont</code></p> <p style="text-align: center;">OPT</p> <p>* FONT</p>
<p><code>\startfontclass [...]</code> ... <code>\stopfontclass</code></p> <p>* kazdy NAME</p>
<p><code>\startfontsolution [...]</code> ... <code>\stopfontsolution</code></p> <p>* NAME</p>
<p><code>\startframedcontent [...]</code> ... <code>\stopframedcontent</code></p> <p style="text-align: center;">OPT</p> <p>* NAME vyp</p>
<p><code>\startgraphictext [...,¹...] [...,²...] {...³} ... \stopgraphictext</code></p> <p style="text-align: center;">OPT OPT</p> <p>1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levyokraj pravyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startgridsnapping [...]</code> ... <code>\stopgridsnapping</code></p> <p style="text-align: center;">OPT</p> <p>* normalni standardni ano striktni tolerantni vrsek spodek obe siroky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME</p>
<p><code>\startgridsnapping [...,[*]...] ... \stopgridsnapping</code></p> <p style="text-align: center;">OPT</p> <p>* inherits: \definegridsnapping</p>
<p><code>\starthboxestohbox ... \stophboxestohbox</code></p>
<p><code>\starthboxregister ... \stophboxregister</code></p> <p>* CSNAME NUMBER</p>
<p><code>\starthelp [...]</code> ... <code>\stophelp</code></p> <p style="text-align: center;">OPT</p> <p>* REFERENCE</p> <p>instances: textnapovedy</p>
<p><code>\starthighlight [...]</code> ... <code>\stophighlight</code></p> <p>* NAME</p>

$\backslash\mathrm{starthlavnicasti} [\dots,\overset{*}{\underset{\mathrm{OPT}}{=}}\dots] \dots \backslash\mathrm{stophlavnicasti}$ <p>* zalozka = TEXT inherits: \nastavbloksekce</p>
$\backslash\mathrm{starthyphenation} [\dots,\dots] \dots \backslash\mathrm{stophyphenation}$ <p>* original tex implicitni hyphenate expanded traditional zadny</p>
$\backslash\mathrm{startcharacteralign} [\overset{*}{\underset{\mathrm{OPT}}{\dots}}] \dots \backslash\mathrm{stopcharacteralign}$ <p>* TEXT number->TEXT text->TEXT</p>
$\backslash\mathrm{startcheckedfences} \dots \backslash\mathrm{stopcheckedfences}$
$\backslash\mathrm{startchemical} [\overset{1}{\underset{\mathrm{OPT}}{\dots}}] [\dots,\overset{2}{\underset{\mathrm{OPT}}{=}}\dots] \dots \backslash\mathrm{stopchemical}$ <p>1 NAME 2 inherits: \setupchemical</p>
$\backslash\mathrm{startimath} \dots \backslash\mathrm{stopimath}$
$\backslash\mathrm{startindentedtext} [\overset{*}{\dots}] \dots \backslash\mathrm{stopindentedtext}$ <p>* NAME</p>
$\backslash\mathrm{startINDENTEDTEXT} \dots \backslash\mathrm{stopINDENTEDTEXT}$
$\backslash\mathrm{startinterakce} [\overset{*}{\dots}] \dots \backslash\mathrm{stopinterakce}$ <p>* skryte NAME</p>
$\backslash\mathrm{startinteraktivnimenu} [\overset{*}{\dots}] \dots \backslash\mathrm{stopinteraktivnimenu}$ <p>* NAME</p>
$\backslash\mathrm{startinterface} \overset{*}{\dots} \dots \backslash\mathrm{stopinterface}$ <p>* vse SPRACHE</p>
$\backslash\mathrm{startintermezzotext} [\dots,\overset{1}{\underset{\mathrm{OPT}}{\dots}}] [\dots,\overset{2}{\underset{\mathrm{OPT}}{\dots}}] \{\overset{3}{\dots}\} \dots \backslash\mathrm{stopintermezzotext}$ <p>1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levvyokraj pravvyokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
$\backslash\mathrm{startintertext} \dots \backslash\mathrm{stopintertext}$
$\backslash\mathrm{startitemgroup} [\overset{1}{\dots}] [\dots,\overset{2}{\underset{\mathrm{OPT}}{\dots}}] [\dots,\overset{3}{\underset{\mathrm{OPT}}{\dots}}] \dots \backslash\mathrm{stopitemgroup}$ <p>1 NAME</p> <p>2 inherits: \setupitemgroup</p> <p>3 inherits: \setupitemgroup</p>

```

\startITEMGROUP [...1...] [...2...] ... \stopITEMGROUP
                        OPT          OPT
1  inherits: \setupitemgroup
2  inherits: \setupitemgroup

instances: vycet

```

```

\startJScode ...1 ...2 ...3 ... \stopJScode
1  NAME
2  uses
3  NAME

```

```

\startJSreamble ...1 ...2 ...3 ... \stopJSreamble
1  NAME
2  uzito
3  now later

```

```

\startjdina [...*] ... \stopjdina
*  REFERENCE

```

```

\startkapitola [...1...] [...2...] ... \stopkapitola
                        OPT          OPT
1  titul      = TEXT
   zalozka    = TEXT
   znaceni    = TEXT
   seznam     = TEXT
   odkaz      = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startknockout ... \stopknockout

```

```

\startkomentar [...1] [...2...] ... \stopkomentar
                  OPT          OPT
1  TEXT
2  inherits: \nastavkomentar

```

```

\startkomentarstranky ... \stopkomentarstranky

```

```

\startKOMENTAR [...1] [...2...] ... \stopKOMENTAR
                  OPT          OPT
1  TEXT
2  inherits: \nastavkomentar

instances: komentar

```

```

\startkomponenta [...*] ... \stopkomponenta
*  FILE *

```

```

\startkomponenta ...* ... \stopkomponenta
*  FILE *

```

```

\startkonectabulky [...*] ... \stopkonectabulky
*  NAME

```


$\backslash\text{startLUA } [\dots, \dots, \overset{*}{\text{...}}] \dots \backslash\text{stopLUA}$ <small>OPT</small> * inherits: \nastavopis
$\backslash\text{startLUA } [\dots, \dots, \overset{*}{\text{...}}] \dots \backslash\text{stopLUA}$ <small>OPT</small> * pokračovat
$\backslash\text{startlayout } [\dots] \dots \backslash\text{stoplayout}$ * NAME
$\backslash\text{startlegenda } [\overset{1}{\text{...}}] [\dots, \dots, \overset{2}{\text{...}}] \dots \backslash\text{stoplegenda}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \nastavtabelaci
$\backslash\text{startlinealignment } [\dots] \dots \backslash\text{stoplinealignment}$ * vlevo nastred vpravo max
$\backslash\text{startlinecorrection } [\dots, \dots, \overset{*}{\text{...}}] \dots \backslash\text{stoplinecorrection}$ <small>OPT</small> * prazdny inherits: \preskoc
$\backslash\text{startlinefiller } [\overset{1}{\text{...}}] [\dots, \dots, \overset{2}{\text{...}}] \dots \backslash\text{stoplinefiller}$ <small>OPT</small> 1 filler NAME 2 inherits: \setuplinefiller
$\backslash\text{startlinenote } [\overset{1}{\text{...}}] \{\overset{2}{\text{...}}\}$ 1 REFERENCE 2 TEXT
$\backslash\text{startLINENOTE } [\overset{1}{\text{...}}] \{\overset{2}{\text{...}}\}$ 1 REFERENCE 2 TEXT instances: linenote
$\backslash\text{startlinenumbering } [\overset{1}{\text{...}}] [\dots, \dots, \overset{2}{\text{...}}] \dots \backslash\text{stoplinenumbering}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \nastavcislovaniradku
$\backslash\text{startlinenumbering } [\overset{1}{\text{...}}] [\overset{2}{\text{...}}] \dots \backslash\text{stoplinenumbering}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 pokračovat NUMMER
$\backslash\text{startlinetable } \dots \backslash\text{stoplinetable}$
$\backslash\text{startlinetablebody } \dots \backslash\text{stoplinetablebody}$
$\backslash\text{startlinetablecell } [\dots, \dots, \overset{*}{\text{...}}] \dots \backslash\text{stoplinetablecell}$ <small>OPT</small> * inherits: \setuplinetable

<code>\startlinetablehead ... \stoplinetablehead</code>
<code>\startlocalfootnotes ... \stoplocalfootnotes</code>
<code>\startlocalheadsetup ... \stoplocalheadsetup</code>
<code>\startlocallinecorrection [...,*...] ... \stoplocallinecorrection</code> <small>OPT</small> <code>* prazdny inherits: \preskoc</code>
<code>\startlocalnotes [...,*...] ... \stoplocalnotes</code> <code>* NAME</code>
<code>\startlocalsetups [...¹] [...²] ... \stoplocalsetups</code> <small>OPT</small> <code>1 mrizka</code> <code>2 NAME</code>
<code>\startlocalsetups .* ... \stoplocalsetups</code> <code>* NAME</code>
<code>\startlua ... \stoplua</code>
<code>\startluacode ... \stopluacode</code>
<code>\startluaparameterset [...] ... \stopluaparameterset</code> <code>* NAME</code>
<code>\startluasetups [...¹] [...²] ... \stopluasetups</code> <small>OPT</small> <code>1 mrizka</code> <code>2 NAME</code>
<code>\startluasetups .* ... \stopluasetups</code> <code>* NAME</code>
<code>\startMP [...,*=...,...] ... \stopMP</code> <small>OPT</small> <code>* inherits: \nastavopis</code>
<code>\startMPclip {...} ... \stopMPclip</code> <code>* NAME</code>
<code>\startMPcode {...} ... \stopMPcode</code> <small>OPT</small> <code>* NAME</code>
<code>\startMPdefinitions {...} ... \stopMPdefinitions</code> <small>OPT</small> <code>* NAME</code>
<code>\startMPdrawing [...¹] ... \stopMPdrawing</code> <small>OPT</small> <code>* -</code>

$\backslash\text{startMPEnvironment}$ [\dots] \dots $\backslash\text{stopMPEnvironment}$ <small>OPT</small> * reset globalne +
$\backslash\text{startMPextensions}$ $\{\dots,*\dots\}$ \dots $\backslash\text{stopMPextensions}$ <small>OPT</small> * NAME
$\backslash\text{startMPinclusions}$ [\dots] $\{\dots\}$ \dots $\backslash\text{stopMPinclusions}$ <small>OPT</small> <small>OPT</small> 1 + 2 NAME
$\backslash\text{startMPinitializations}$ \dots $\backslash\text{stopMPinitializations}$
$\backslash\text{startMPpage}$ [$\dots,*\dots$] \dots $\backslash\text{stopMPpage}$ <small>OPT</small> * inherits: $\backslash\text{setupfittingpage}$
$\backslash\text{startMPpositiongraphic}$ $\{\dots\}$ $\{\dots,*\dots\}$ \dots $\backslash\text{stopMPpositiongraphic}$ <small>OPT</small> 1 NAME 2 KEY
$\backslash\text{startMPpositionmethod}$ $\{\dots\}$ \dots $\backslash\text{stopMPpositionmethod}$ * NAME
$\backslash\text{startMPrun}$ $\{\dots\}$ \dots $\backslash\text{stopMPrun}$ <small>OPT</small> * NAME
$\backslash\text{startMP}$ [$\dots,*\dots$] \dots $\backslash\text{stopMP}$ <small>OPT</small> * pokračovat
$\backslash\text{startmarginalnilinka}$ [\dots] \dots $\backslash\text{stopmarginalnilinka}$ <small>OPT</small> * NUMMER
$\backslash\text{startmarginalnilinka}$ [$\dots,*\dots$] \dots $\backslash\text{stopmarginalnilinka}$ <small>OPT</small> * inherits: $\backslash\text{setupmarginrule}$
$\backslash\text{startmarginblock}$ [\dots] \dots $\backslash\text{stopmarginblock}$ <small>OPT</small> * NAME
$\backslash\text{startmarkedcontent}$ [\dots] \dots $\backslash\text{stopmarkedcontent}$ <small>OPT</small> * reset vse NAME
$\backslash\text{startmathalignment}$ [$\dots,*\dots$] \dots $\backslash\text{stopmathalignment}$ <small>OPT</small> * inherits: $\backslash\text{setupmathalignment}$
$\backslash\text{startMATHALIGNMENT}$ [$\dots,*\dots$] \dots $\backslash\text{stopMATHALIGNMENT}$ <small>OPT</small> * inherits: $\backslash\text{setupmathalignment}$ instances: align mathalignment

$\backslash\mathrm{startmathcases} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmathcases}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathcases}$</p>
$\backslash\mathrm{startMATHCASES} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHCASES}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathcases}$</p> <p>instances: cases mathcases</p>
$\backslash\mathrm{startmathlabeltext} [\overset{1}{.}] [\overset{2}{.}] \dots \backslash\mathrm{stopmathlabeltext}$ <p><small>OPT</small></p> <p>1 SPRACHE</p> <p>2 KEY</p>
$\backslash\mathrm{startmathmatrix} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmathmatrix}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathmatrix}$</p>
$\backslash\mathrm{startMATHMATRIX} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMATHMATRIX}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathmatrix}$</p> <p>instances: matrix mathmatrix</p>
$\backslash\mathrm{startmathmode} \dots \backslash\mathrm{stopmathmode}$
$\backslash\mathrm{startmathstyle} [\dots,\dots] \dots \backslash\mathrm{stopmathstyle}$ <p>* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME</p>
$\backslash\mathrm{startmatrices} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmatrices}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathmatrix}$</p>
$\backslash\mathrm{startmatrix} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmatrix}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmathmatrix}$</p>
$\backslash\mathrm{startmaxaligned} \dots \backslash\mathrm{stopmaxaligned}$
$\backslash\mathrm{startmdformula} [\dots,\dots] \dots \backslash\mathrm{stopmdformula}$ <p><small>OPT</small></p> <p>* zhustene tight nastred ramecek inherits: $\backslash\mathrm{nastavzakladnifont}$</p>
$\backslash\mathrm{startmiddlealigned} \dots \backslash\mathrm{stopmiddlealigned}$
$\backslash\mathrm{startmiddlemakeup} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopmiddlemakeup}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{nastavupravu}$</p>
$\backslash\mathrm{startmixedcolumns} [\overset{1}{.}] [\dots,\overset{2}{=}\dots] \dots \backslash\mathrm{stopmixedcolumns}$ <p><small>OPT</small> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: $\backslash\mathrm{setupmixedcolumns}$</p>
$\backslash\mathrm{startMIXEDCOLUMNS} [\dots,\overset{*}{=}\dots] \dots \backslash\mathrm{stopMIXEDCOLUMNS}$ <p><small>OPT</small></p> <p>* inherits: $\backslash\mathrm{setupmixedcolumns}$</p> <p>instances: itemgroupcolumns boxedcolumns</p>

$\backslash\text{startmode} [\dots,*,\dots] \dots \backslash\text{stopmode}$ * NAME
$\backslash\text{startmodeset} [\dots,\overset{1}{\dots}] \{\dots\} \dots \backslash\text{stopmodeset}$ 1 NAME implicitni 2 CONTENT
$\backslash\text{startmodule} [\dots] \dots \backslash\text{stopmodule}$ * FILE
$\backslash\text{startmoduletestsection} \dots \backslash\text{stopmoduletestsection}$
$\backslash\text{startmodule} \overset{*}{\dots} \dots \backslash\text{stopmodule}$ * FILE
$\backslash\text{startmpformula} [\dots,\overset{*}{\dots}] \dots \backslash\text{stopmpformula}$ <small>OPT</small> * zhustene tight nastred ramecek inherits: \nastavzakladnifont
$\backslash\text{startnadpis} [\dots,\overset{1}{\dots}] \{\dots\} \dots \backslash\text{stopnadpis}$ <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{startnamedsection} [\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots] [\dots,\overset{3}{\dots},\dots] \dots \backslash\text{stopnamedsection}$ <small>OPT</small> <small>OPT</small> 1 ABSCHNITT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE
$\backslash\text{startnamedsubformulas} [\dots,\overset{1}{\dots}] \{\dots\} \dots \backslash\text{stopnamedsubformulas}$ <small>OPT</small> 1 + - REFERENCE 2 TEXT
$\backslash\text{startnaproti} \dots \backslash\text{stopnaproti}$
$\backslash\text{startnarrower} [\dots,\overset{*}{\dots}] \dots \backslash\text{stopnarrower}$ <small>OPT</small> * [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
$\backslash\text{startNARROWER} [\dots,\overset{*}{\dots}] \dots \backslash\text{stopNARROWER}$ <small>OPT</small> * [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset
$\backslash\text{startnegativ} \dots \backslash\text{stopnegativ}$
$\backslash\text{startnicelyfilledbox} [\dots,\overset{*}{\dots},\dots] \dots \backslash\text{stopnicelyfilledbox}$ <small>OPT</small> * sirka = DIMENSION vyska = DIMENSION offset = DIMENSION strut = ano ne

<code>\startnointerference ... \stopnointerference</code>
<code>\startnotallmodes [...,*...] ... \stopnotallmodes</code> <code>* NAME</code>
<code>\startnotext ... \stopnotext</code>
<code>\startnotmode [...,*...] ... \stopnotmode</code> <code>* NAME</code>
<code>\startobrazek [¹...] [²] [...,³...,...] ... \stopobrazek</code> <small>OPT</small> <code>1 NAME</code> <code>2 FILE</code> <code>3 inherits: \externiobraz</code>
<code>\startodlozit [[*]...] ... \stopodlozit</code> <small>OPT</small> <code>* [-+]NUMBER</code>
<code>\startodstavec [¹...] [...,²...,...] ... \stopodstavec</code> <small>OPT</small> <small>OPT</small> <code>1 NAME</code> <code>2 inherits: \setupparagraph</code>
<code>\startoperatortext [¹...] [²] ... \stopoperatortext</code> <small>OPT</small> <code>1 SPRACHE</code> <code>2 KEY</code>
<code>\startoramovani [¹...] [...,²...,...] ... \stoporamovani</code> <small>OPT</small> <small>OPT</small> <code>1 NAME</code> <code>2 inherits: \nastavoramovani</code>
<code>\startoramovanytext [¹...] [...,²...,...] ... \stoporamovanytext</code> <small>OPT</small> <small>OPT</small> <code>1 vlevo vpravo nastred zadny</code> <code>2 inherits: \setupframedtext</code>
<code>\startORAMOVANYTEXT [¹...] [...,²...,...] ... \stopORAMOVANYTEXT</code> <small>OPT</small> <small>OPT</small> <code>1 vlevo vpravo nastred zadny</code> <code>2 inherits: \setupframedtext</code> <code>instances: oramovanytext</code>
<code>\startoutputstream [...] ... \stopoutputstream</code> <code>* NAME</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startPARSEDXML [...,[*]...,...] ... \stopPARSEDXML</code> <small>OPT</small> <code>* inherits: \nastavopis</code>

<p><code>\startPARSEDXML [...¹,...] ... \stopPARSEDXML</code> <small>OPT</small></p> <p>* pokračovat</p>
<p><code>\startpagefigure [...¹] [...²,...] ... \stoppagefigure</code> <small>OPT</small></p> <p>1 FILE</p> <p>2 inherits: \setupexternalfigure</p>
<p><code>\startpagegrid [...¹] [...²,...] ... \stoppagegrid</code> <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setuppagegrid</p>
<p><code>\startpagegridspan [...¹] [...²,...] ... \stoppagegridspan</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setuppagegridspan</p>
<p><code>\startPAGEGRID [...¹,...] ... \stopPAGEGRID</code> <small>OPT</small></p> <p>* inherits: \setuppagegrid</p>
<p><code>\startpagelayout [...] ... \stoppagelayout</code></p> <p>* stranka levastranka pravastranka</p>
<p><code>\startpagemakeup [...¹,...] ... \stoppagemakeup</code> <small>OPT</small></p> <p>* inherits: \nastavupravu</p>
<p><code>\startpar [...¹] [...²,...] ... \stoppar</code> <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupparagraph</p>
<p><code>\startparagraphs [...] ... \stopparagraphs</code></p> <p>* NAME</p>
<p><code>\startparagraphscell ... \stopparagraphscell</code></p>
<p><code>\startPARAGRAPHS ... \stopPARAGRAPHS</code></p>
<p><code>\startPARALLEL ... \stopPARALLEL</code></p>
<p><code>\startparbuilder [...] ... \stopparbuilder</code></p> <p>* implicitni oneline basic NAME</p>
<p><code>\startplacefigure [...¹,...] [...²,...] ... \stopplacefigure</code> <small>OPT OPT</small></p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpenamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective odkaz = REFERENCE</p> <p>2 KEY = VALUE</p>

```

\startplacefloat [...1...] [...2...2...] [...3...2...] ... \stopplacefloat
                                OPT          OPT
1  SINGULAR
2  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [--]radek pulradku mritzka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective
   odkaz    = REFERENCE
3  KEY = VALUE

```

```

\startumistiPLVOUCIOBJEKT [...1...1...] [...2...2...] ... \stopumistiPLVOUCIOBJEKT
                                OPT          OPT
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [--]radek pulradku mritzka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective
   odkaz    = REFERENCE
2  KEY = VALUE

instances: chemical figure table intermezzo graphic

```

```

\startplacegraphic [...1...1...] [...2...2...] ... \stopplacegraphic
                                OPT          OPT
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [--]radek pulradku mritzka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective
   odkaz    = REFERENCE
2  KEY = VALUE

```

```

\startplacechemical [...1...1...] [...2...2...] ... \stopplacechemical
                                OPT          OPT
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [--]radek pulradku mritzka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective
   odkaz    = REFERENCE
2  KEY = VALUE

```

```

\startplaceintermezzo [...1...1...] [...2...2...] ... \stopplaceintermezzo
                                OPT          OPT
1  titul    = TEXT
   zalozka  = TEXT
   znaceni  = TEXT
   seznam   = TEXT
   misto    = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
              [--]radek pulradku mritzka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
              [--]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
              effective
   odkaz    = REFERENCE
2  KEY = VALUE

```


\startplacepairedbox [...]¹ [...]²... \stopplacepairedbox

OPT

1 NAME

2 inherits: \setuppairedbox

\startumistiPAIREDBOX [...]^{*}... \stopumistiPAIREDBOX

OPT

* inherits: \setuppairedbox

instances: legenda

\startplacetable [...]¹ [...]²... \stopplacetable

OPT

OPT

1 titul = TEXT

zalozka = TEXT

znaceni = TEXT

seznam = TEXT

misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky
[-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie
[-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde
effective

odkaz = REFERENCE

2 KEY = VALUE

\startpodpodpodpodsekce [...]¹ [...]²... \stoppodpodpodpodsekce

OPT

OPT

1 titul = TEXT

zalozka = TEXT

znaceni = TEXT

seznam = TEXT

odkaz = REFERENCE

vlastnicislo = TEXT

2 KEY = VALUE

\startpodpodpodpodtema [...]¹ [...]²... \stoppodpodpodpodtema

OPT

OPT

1 titul = TEXT

zalozka = TEXT

znaceni = TEXT

seznam = TEXT

odkaz = REFERENCE

vlastnicislo = TEXT

2 KEY = VALUE

\startpodpodpodsekce [...]¹ [...]²... \stoppodpodpodsekce

OPT

OPT

1 titul = TEXT

zalozka = TEXT

znaceni = TEXT

seznam = TEXT

odkaz = REFERENCE

vlastnicislo = TEXT

2 KEY = VALUE

\startpodpodpodtema [...]¹ [...]²... \stoppodpodpodtema

OPT

OPT

1 titul = TEXT

zalozka = TEXT

znaceni = TEXT

seznam = TEXT

odkaz = REFERENCE

vlastnicislo = TEXT

2 KEY = VALUE

<p>\startpodpodsekcce [...¹...²...] ... \stoppodpodsekcce</p> <p style="text-align: center;">OPT OPT</p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT</p> <p>2 KEY = VALUE</p>
<p>\startpodpodtema [...¹...²...] ... \stoppodpodtema</p> <p style="text-align: center;">OPT OPT</p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT</p> <p>2 KEY = VALUE</p>
<p>\startpodsekcce [...¹...²...] ... \stoppodsekcce</p> <p style="text-align: center;">OPT OPT</p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT</p> <p>2 KEY = VALUE</p>
<p>\startpodtema [...¹...²...] ... \stoppodtema</p> <p style="text-align: center;">OPT OPT</p> <p>1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT</p> <p>2 KEY = VALUE</p>
<p>\startpolozka [...[*]...] ... \stoppolozka</p> <p style="text-align: center;">OPT</p> <p>* REFERENCE</p>
<p>\startPOPIS [...[*]...] ... \stopPOPIS</p> <p style="text-align: center;">OPT</p> <p>* titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE</p>
<p>\startPOPIS [...¹...²...] ... \stopPOPIS</p> <p style="text-align: center;">OPT OPT</p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p>\startpositioning [...¹...²...] ... \stoppositioning</p> <p style="text-align: center;">OPT OPT</p> <p>1 NAME</p> <p>2 inherits: \nastavumistovani</p>
<p>\startpositionoverlay {...} ... \stoppositionoverlay</p> <p>* NAME</p>
<p>\startpositiv ... \stoppositiv</p>

<p><code>\startpozadi [...,..[*]...,...] ... \stoppozadi</code> <small>OPT</small></p> <p>* inherits: \nastavpozadi</p>
<p><code>\startPOZADI [...,..[*]...,...] ... \stopPOZADI</code> <small>OPT</small></p> <p>* inherits: \nastavpozadi</p> <p>instances: pozadi</p>
<p><code>\startpoznampakodcarou [...,..[*]...,...] ... \stoppoznampakodcarou</code> <small>OPT</small></p> <p>* REFERENCE</p>
<p><code>\startpoznampakodcarou [...,..[*]...,...] ... \stoppoznampakodcarou</code> <small>OPT</small></p> <p>* titul = TEXT zalogka = TEXT seznam = TEXT odkaz = REFERENCE</p>
<p><code>\startNOTE [...,..[*]...,...] ... \stopNOTE</code> <small>OPT</small></p> <p>* REFERENCE</p> <p>instances: poznampakodcarou endnote</p>
<p><code>\startNOTE [...,..[*]...,...] ... \stopNOTE</code> <small>OPT</small></p> <p>* titul = TEXT zalogka = TEXT seznam = TEXT odkaz = REFERENCE</p> <p>instances: poznampakodcarou endnote</p>
<p><code>\startprednicasti [...,..[*]...,...] ... \stopprednicasti</code> <small>OPT</small></p> <p>* zalogka = TEXT inherits: \nastavbloksekce</p>
<p><code>\startprefixtext [...¹...] [...²...] ... \stopprefixtext</code> <small>OPT</small></p> <p>1 SPRACHE 2 KEY</p>
<p><code>\startprekryv ... \stopprekryv</code></p>
<p><code>\startprocessassignmentcommand [...,..[*]...,...] ... \stopprocessassignmentcommand</code></p> <p>* KEY = VALUE</p>
<p><code>\startprocessassignmentlist [...,..[*]...,...] ... \stopprocessassignmentlist</code></p> <p>* KEY = VALUE</p>
<p><code>\startprocesscommacommand [...,..[*]...,...] ... \stopprocesscommacommand</code></p> <p>* BEFEHL</p>
<p><code>\startprocesscommalist [...,..[*]...,...] ... \stopprocesscommalist</code></p> <p>* BEFEHL</p>

<pre> \startprodukt [...] ... \stopprodukt * FILE *</pre>
<pre> \startprodukt \stopprodukt * FILE *</pre>
<pre> \startprojekt [...] ... \stopprojekt * FILE *</pre>
<pre> \startprojekt \stopprojekt * FILE *</pre>
<pre> \startprostredi [...] ... \stopprostredi * FILE *</pre>
<pre> \startprostredi \stopprostredi * FILE *</pre>
<pre> \startprotectedcolors ... \stopprotectedcolors</pre>
<pre> \startpublikace [¹...] [²...,...²...,...] ... \stoppublikace OPT OPT 1 NAME 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT</pre>
<pre> \startradek [...]</pre> <p>* REFERENCE</p>
<pre> \startradky [...,...[*]...,...] ... \stopradky OPT * inherits: \nastavradky</pre>
<pre> \startRADKY [...,...[*]...,...] ... \stopRADKY OPT * inherits: \nastavradky instances: radky</pre>
<pre> \startrandomized ... \stoprandomized</pre>
<pre> \startrawsetups [¹...] [²...] ... \stoprawsetups OPT 1 mrizka 2 NAME</pre>
<pre> \startrawsetups \stoprawsetups * NAME</pre>
<pre> \startreadingfile ... \stopreadingfile</pre>

<pre> \startregime [...] ... \stopregime * inherits: \enableregime </pre>
<pre> \startregister [¹.] [².] [³.] [⁴.] [⁵...+...+...] OPT OPT 1 NAME 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX </pre>
<pre> \startreusableMPgraphic {¹.} {²...²...} ... \stopreusableMPgraphic OPT 1 NAME 2 KEY </pre>
<pre> \starttrovnice [...[*]...] ... \stoprovnice OPT * zhustene tight nastred ramecek inherits: \nastavzakladnifont </pre>
<pre> \startROVNICEformula [...[*]...] ... \stopROVNICEformula OPT * zhustene tight nastred ramecek inherits: \nastavzakladnifont instances: sp sd mp md </pre>
<pre> \startrozbalene ... \stoprozbalene </pre>
<pre> \startscript [...] ... \stopscript * hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsdformula [...[*]...] ... \stopsdformula OPT * zhustene tight nastred ramecek inherits: \nastavzakladnifont </pre>
<pre> \startsectionblock [¹.] [...²...²...] ... \stopsectionblock OPT 1 NAME 2 zalozka = TEXT inherits: \nastavbloksekce </pre>
<pre> \startsectionblockenvironment [...] ... \stopsectionblockenvironment * NAME </pre>
<pre> \startSECTIONBLOCK [...[*]...[*]...] ... \stopSECTIONBLOCK OPT * zalozka = TEXT inherits: \nastavbloksekce instances: prednicasti hlavnicasti dodatky epilogy </pre>

<pre> \startsectionlevel [...] [...] [...] ... \stopsectionlevel OPT OPT OPT 1 NAME 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE </pre>
<pre> \startsekce [...] [...] ... \stopsekce OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE </pre>
<pre> \startSEKCE [...] [...] ... \stopSEKCE OPT OPT 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE instances: cast kapitola sekce podsekce podpodsekce podpodpodsekce podpodpodpodsekce titul tema podtema podpodtema podpodpodtema podpodpodpodtema </pre>
<pre> \startsetups [...] [...] ... \stopsetups OPT 1 mrizka 2 NAME </pre>
<pre> \startsetups \stopsetups * NAME </pre>
<pre> \startshift [...] ... \stopshift * NAME </pre>
<pre> \startsidebar [...] [...] ... \stopsidebar OPT OPT 1 NAME 2 inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...] [...] ... \stopsimplecolumns OPT * inherits: \setsimplecolumnhsize </pre>
<pre> \startskryt ... \stopskryt </pre>
<pre> \startsloupce [...] [...] ... \stopsloupce OPT * inherits: \nastavsloupce </pre>

$\backslash\text{startspecialitem} [\overset{1}{\dots}] [\overset{2}{\dots},\dots] \dots \backslash\text{stopspecialitem}$ <p>1 položka</p> <p>2 REFERENCE</p>
$\backslash\text{startspecialitem} [\dots] \dots \backslash\text{stopspecialitem}$ <p>* pod pol</p>
$\backslash\text{startspecialitem} [\overset{1}{\dots}] \{\overset{2}{\dots}\} \dots \backslash\text{stopspecialitem}$ <p>1 sym rozsah mar</p> <p>2 TEXT</p>
$\backslash\text{startspeech} [\dots,\overset{*}{\dots}] \dots \backslash\text{stopspeech}$ <p>* inherits: \startzuzeni</p>
$\backslash\text{startspformula} [\dots,\overset{*}{\dots}] \dots \backslash\text{stopspformula}$ <p>* zhustene tight nastred ramecek inherits: \nastavzakladnifont</p>
$\backslash\text{startspread} \dots \backslash\text{stopspread}$
$\backslash\text{startstandardmakeup} [\dots,\overset{*}{\dots},\dots] \dots \backslash\text{stopstandardmakeup}$ <p>* inherits: \nastavupravu</p>
$\backslash\text{start} [\overset{*}{\dots}] \dots \backslash\text{stop}$ <p>* NAME</p>
$\backslash\text{startSTARTSTOP} \dots \backslash\text{stopSTARTSTOP}$
$\backslash\text{startstaticMPfigure} \{\overset{*}{\dots}\} \dots \backslash\text{stopstaticMPfigure}$ <p>* NAME</p>
$\backslash\text{startstaticMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopstaticMPgraphic}$ <p>1 NAME</p> <p>2 KEY</p>
$\backslash\text{STARTSTOP} \{\overset{*}{\dots}\}$ <p>* CONTENT</p>
$\backslash\text{startstrictinspectnextcharacter} \dots \backslash\text{stopstrictinspectnextcharacter}$

`\startstructurepageregister [...]1 [...]2 [...,...3...,...]4 [...,...4...,...]OPT`

```
1  NAME
2  NAME
3  popisek      = NAME
   keys        = TEXT PROCESSOR->TEXT
   entries     = TEXT PROCESSOR->TEXT
   keys:1      = TEXT
   keys:2      = TEXT
   keys:3      = TEXT
   entries:1   = TEXT
   entries:2   = TEXT
   entries:3   = TEXT
   alternativa = TEXT
4  KEY = VALUE
```

`\startstyle [...,...*...,...]OPT ... \stopstyle`

`* inherits: \setupstyle`

`\startstyle [...]* ... \stopstyle`

`* NAME FONT`

`\startSTYLE ... \stopSTYLE`

`\startsubformulas [...,...*...,...]OPT ... \stopsubformulas`

`* + - REFERENCE`

`\startsubjectlevel [...]1 [...,...2...,...]OPT [...,...3...,...]OPT ... \stopsubjectlevel`

```
1  NAME
2  titul        = TEXT
   zalozka     = TEXT
   znaceni     = TEXT
   seznam      = TEXT
   odkaz       = REFERENCE
   vlastnicislo = TEXT
3  KEY = VALUE
```

`\startsubsentence ... \stopsubsentence`

`\startsubstack ... \stopsubstack`

`\startsymbolset [...]* ... \stopsymbolset`

`* NAME`

`\startTABLE [...,...*...,...]OPT ... \stopTABLE`

`* inherits: \setupTABLE`

`\startTABLEbody [...,...*...,...]OPT ... \stopTABLEbody`

`* inherits: \setupTABLE`

`\startTABLEfoot [...,...*...,...]OPT ... \stopTABLEfoot`

`* inherits: \setupTABLE`

`\startTABLEhead [...,...*...,...]OPT ... \stopTABLEhead`

`* inherits: \setupTABLE`

$\backslash\text{startTABLEnext}$ [$\dots\overset{*}{=}\dots$] ... $\backslash\text{stopTABLEnext}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{startTEX}$ [$\dots\overset{*}{=}\dots$] ... $\backslash\text{stopTEX}$ <small>OPT</small> * inherits: $\backslash\text{nastavopis}$
$\backslash\text{startTEXpage}$ [$\dots\overset{*}{=}\dots$] ... $\backslash\text{stopTEXpage}$ <small>OPT</small> * inherits: $\backslash\text{setupfittingpage}$
$\backslash\text{startTEX}$ [$\dots\overset{*}{=}\dots$] ... $\backslash\text{stopTEX}$ <small>OPT</small> * pokračovat
$\backslash\text{starttabelator}$ [$\overset{1}{/}$] [$\dots\overset{2}{=}\dots$] ... $\backslash\text{stoptabelator}$ <small>OPT</small> <small>OPT</small> 1 TEMPLATE 2 inherits: $\backslash\text{nastvtabelaci}$
$\backslash\text{startTABELATOR}$ [$\overset{1}{/}$] [$\dots\overset{2}{=}\dots$] ... $\backslash\text{stopTABELATOR}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{nastvtabelaci}$ instances: legenda fakt
$\backslash\text{starttabletext}$ [$\overset{1}{/}\dots$] [$\overset{2}{/}\dots$] $\{\overset{3}{/}\}$... $\backslash\text{stoptabletext}$ <small>OPT</small> <small>OPT</small> 1 split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraji levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřížka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective 2 REFERENCE 3 TEXT
$\backslash\text{starttabulatehead}$ [$\overset{*}{/}$] ... $\backslash\text{stoptabulatehead}$ <small>OPT</small> * NAME
$\backslash\text{starttabulatetail}$ [$\overset{*}{/}$] ... $\backslash\text{stoptabulatetail}$ <small>OPT</small> * NAME
$\backslash\text{startTABULATION}$ [$\overset{1}{/}$] [$\dots\overset{2}{=}\dots$] ... $\backslash\text{stopTABULATION}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setuptabulation}$
$\backslash\text{starttabulka}$ [$\overset{1}{/}$] [$\dots\overset{2}{=}\dots$] ... $\backslash\text{stoptabulka}$ <small>OPT</small> 1 TEMPLATE 2 inherits: $\backslash\text{nastvtabulky}$
$\backslash\text{starttabulka}$ [$\overset{1}{/}$] [$\dots\overset{2}{=}\dots$] ... $\backslash\text{stoptabulka}$ <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{nastvtabulky}$

<code>\starttabulky [.*.] ... \stoptabulky</code> * TEMPLATE
<code>\starttabulky [.*] ... \stoptabulky</code> * NAME
<code>\starttaglabeltext [.¹.] [.².] ... \stoptaglabeltext</code> <div style="text-align: center;"><small>OPT</small></div> 1 SPRACHE 2 KEY
<code>\starttema [...,¹...,...] [...,²...,...] ... \stoptema</code> <div style="display: flex; justify-content: space-around; width: 100%;"><div><small>OPT</small></div><div><small>OPT</small></div></div> 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE
<code>\starttexcode ... \stoptexcode</code>
<code>\starttexdefinition ¹... ²... ³... ⁴... ⁵... ⁶... \stoptexdefinition</code> <div style="display: flex; justify-content: space-around; width: 100%;"><div><small>OPT</small></div><div><small>OPT</small></div><div><small>OPT</small></div><div><small>OPT</small></div><div><small>OPT</small></div><div><small>OPT</small></div></div> 1 spaces nospaces 2 globalne 3 unexpanded 4 expanded 5 NAME 6 TEMPLATE
<code>\starttext ... \stoptext</code>
<code>\starttextbackground [.¹.] [...,²...,...] ... \stoptextbackground</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 inherits: \setuptextbackground
<code>\starttextbackgroundmanual ... \stoptextbackgroundmanual</code>
<code>\startTEXTBACKGROUND [...,[*]...,...] ... \stopTEXTBACKGROUND</code> <div style="text-align: center;"><small>OPT</small></div> * inherits: \setuptextbackground
<code>\starttextcolor [.*] ... \stoptextcolor</code> * COLOR
<code>\starttextcolorintent ... \stoptextcolorintent</code>
<code>\starttextflow [...] ... \stoptextflow</code> * NAME

$\backslash\text{starttexthlavicky}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stoptexthlavicky}$ <small>OPT</small> 1 SPRACHE 2 KEY
$\backslash\text{starttextmakeup}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stoptextmakeup}$ <small>OPT</small> * inherits: \nastavupravu
$\backslash\text{starttextnapovedy}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptextnapovedy}$ <small>OPT</small> * REFERENCE
$\backslash\text{starttextovalinka}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptextovalinka}$ * TEXT
$\backslash\text{starttextpopisku}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stoptextpopisku}$ <small>OPT</small> 1 SPRACHE 2 KEY
$\backslash\text{startPOPISEKtext}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stopPOPISEKtext}$ <small>OPT</small> 1 SPRACHE 2 KEY instances: hlavicka popisek mathlabel taglabel jednotka operator prefix suffix btxlabel
$\backslash\text{starttitul}$ [$\dots,\dots,\overset{1}{\dots},\dots$] [$\dots,\dots,\overset{2}{\dots},\dots$] ... $\backslash\text{stoptitul}$ <small>OPT</small> <small>OPT</small> 1 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 2 KEY = VALUE
$\backslash\text{starttokens}$ [\dots] ... $\backslash\text{stoptokens}$ * NAME
$\backslash\text{starttransparent}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptransparent}$ * COLOR
$\backslash\text{starttypescript}$ [$\overset{1}{\dots},\dots$] [$\overset{2}{\dots},\dots$] [$\overset{3}{\dots},\dots$] ... $\backslash\text{stoptypescript}$ <small>OPT</small> <small>OPT</small> <small>OPT</small> 1 serif sans mono math handwriting calligraphy 2 NAME 3 size jmeno
$\backslash\text{starttypescriptcollection}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptypescriptcollection}$ * NAME
$\backslash\text{starttyping}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stoptyping}$ <small>OPT</small> * inherits: \nastavopis

$\backslash\text{starttyping} [\dots,\overset{\text{OPT}}{\dots}] \dots \backslash\text{stoptyping}$ * pokračovat
$\backslash\text{startTYPING} [\dots,\overset{\text{OPT}}{\dots}] \dots \backslash\text{stopTYPING}$ * inherits: \nastavopis instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startTYPING} [\dots,\overset{\text{OPT}}{\dots}] \dots \backslash\text{stopTYPING}$ * pokračovat instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startumistilegendu} [\dots,\overset{\text{OPT}}{\dots}] \dots \backslash\text{stopumistilegendu}$ * inherits: \setuppairedbox
$\backslash\text{startumistirovnici} [\dots,\overset{\text{OPT}}{\dots}] \dots \backslash\text{stopumistirovnici}$ * titul = TEXT suffix = TEXT odkaz = + - REFERENCE
$\backslash\text{startumistirovnici} [\dots,\overset{\text{OPT}}{\dots}] \dots \backslash\text{stopumistirovnici}$ * + - REFERENCE
$\backslash\text{startuniqueMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopuniqueMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuniqueMPpagegraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopuniqueMPpagegraphic}$ 1 NAME 2 KEY
$\backslash\text{startunittext} [\overset{1}{\dots}] [\overset{2}{\dots}] \dots \backslash\text{stopunittext}$ 1 SPRACHE 2 KEY
$\backslash\text{startusableMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopusableMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuseMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\text{stopuseMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startusemathstyleparameter} \backslash\overset{*}{\dots} \dots \backslash\text{stopusemathstyleparameter}$ * CSNAME
$\backslash\text{startusingbtxs specification} [\overset{*}{\dots}] \dots \backslash\text{stopusingbtxs specification}$ * NAME

<p><code>\startuzky [...¹] [...²...] ... \stopuzky</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \nastavzuzeni</p>
<p><code>\startuzky [...¹...] [...²...] ... \stopuzky</code></p> <p><small>OPT OPT</small></p> <p>1 inherits: \nastavzuzeni</p> <p>2 [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset</p>
<p><code>\startuzky [...¹] [...²...] ... \stopuzky</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset</p>
<p><code>\startvboxregister ... \stopvboxregister</code></p> <p>* CSNAME NUMBER</p>
<p><code>\startvboxtohbox ... \stopvboxtohbox</code></p>
<p><code>\startvboxtohboxseparator ... \stopvboxtohboxseparator</code></p>
<p><code>\startviewerlayer [...] ... \stopviewerlayer</code></p> <p>* NAME</p>
<p><code>\startVIEWERLAYER ... \stopVIEWERLAYER</code></p>
<p><code>\startvtopregister ... \stopvtopregister</code></p> <p>* CSNAME NUMBER</p>
<p><code>\startvycet [...¹...] [...²...] ... \stopvycet</code></p> <p><small>OPT OPT</small></p> <p>1 inherits: \setupitemgroup</p> <p>2 inherits: \setupitemgroup</p>
<p><code>\startVYCET [...[*]...] ... \stopVYCET</code></p> <p><small>OPT</small></p> <p>* titul = TEXT</p> <p>zalozka = TEXT</p> <p>seznam = TEXT</p> <p>odkaz = REFERENCE</p>
<p><code>\startVYCET [...¹...] {²} ... \stopVYCET</code></p> <p><small>OPT OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\startXML [...[*]...] ... \stopXML</code></p> <p><small>OPT</small></p> <p>* inherits: \nastavopis</p>
<p><code>\startXML [...[*]...] ... \stopXML</code></p> <p><small>OPT</small></p> <p>* pokračovat</p>

<pre> \startxcell [...] [...] ... \stopxcell OPT OPT 1 NAME 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: \setupxtable </pre>
<pre> \startxcellgroup [...] [...] ... \stopxcellgroup OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxgroup [...] [...] ... \stopxgroup OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxmldisplayverbatim [...] ... \stopxmldisplayverbatim * NAME </pre>
<pre> \startxmllineverbatim [...] ... \stopxmllineverbatim * NAME </pre>
<pre> \startxmlraw ... \stopxmlraw </pre>
<pre> \startxmlsetups [...] [...] ... \stopxmlsetups OPT 1 mrizka 2 NAME </pre>
<pre> \startxmlsetups \stopxmlsetups * NAME </pre>
<pre> \startxrow [...] [...] ... \stopxrow OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxrowgroup [...] [...] ... \stopxrowgroup OPT OPT 1 NAME 2 inherits: \setupxtable </pre>
<pre> \startxtable [...] [...] ... \stopxtable OPT * inherits: \setupxtable </pre>
<pre> \startxtablebody [...] [...] ... \stopxtablebody OPT * inherits: \setupxtable </pre>
<pre> \startxtablebody [...] ... \stopxtablebody OPT * NAME </pre>

$\backslash\text{startxtablefoot}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopxtablefoot}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablefoot}$ [... [*] ...] ... $\backslash\text{stopxtablefoot}$ * NAME
$\backslash\text{startxtablehead}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopxtablehead}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablehead}$ [... [*] ...] ... $\backslash\text{stopxtablehead}$ * NAME
$\backslash\text{startxtablenext}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopxtablenext}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablenext}$ [... [*] ...] ... $\backslash\text{stopxtablenext}$ * NAME
$\backslash\text{startXTABLE}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopXTABLE}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ [... [*] ...] ... $\backslash\text{stopxtable}$ * NAME
$\backslash\text{startzahlavitabulky}$ [... [*] ...] ... $\backslash\text{stopzahlavitabulky}$ * NAME
$\backslash\text{startzarovnanonastred}$... $\backslash\text{stopzarovnanonastred}$
$\backslash\text{startzarovnanovlevo}$... $\backslash\text{stopzarovnanovlevo}$
$\backslash\text{startzarovnanovpravo}$... $\backslash\text{stopzarovnanovpravo}$
$\backslash\text{startzhustene}$ [... [*] ...] ... $\backslash\text{stopzhustene}$ * prazdny
$\backslash\text{startzlom}$ [... ¹ ...] [... ² ... ^{OPT} ...] ... $\backslash\text{stopzlom}$ 1 NAME 2 inherits: $\backslash\text{nastavupravu}$
$\backslash\text{startZLOMzlom}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopZLOMzlom}$ * inherits: $\backslash\text{nastavupravu}$ instances: standardni stranka text nastred
$\backslash\text{stoplinenote}$ [... [*] ...]
* REFERENCE

<code>\stopLINENOTE [...]</code> * REFERENCE instances: linenote
<code>\stopradek [...]</code> * REFERENCE
<code>\stopregister [...¹] [...²]</code> 1 NAME 2 NAME
<code>\stopstructurepageregister [...¹] [...²]</code> 1 NAME 2 NAME
<code>\strana [...[*],...]</code> <div style="text-align: center;"><small>OPT</small></div> * inherits: \pagebreak
<code>\strictdoifelsenextoptional {...¹} {...²}</code> 1 TRUE 2 FALSE
<code>\strictdoifnextoptionalelse {...¹} {...²}</code> 1 TRUE 2 FALSE
<code>\stripcharacter ...¹ \from ...² \to ...³</code> 1 CHARACTER 2 TEXT 3 CSNAME
<code>\strippedcsname *...</code> * CSNAME
<code>\strippedcsname ...</code> * TEXT
<code>\stripspaces \from ...¹ \to ...²</code> 1 TEXT 2 CSNAME
<code>\structurelistuservariable {...[*]}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>

<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...,¹...,²...] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...¹] {...²}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...¹} {...²} \...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME

<code>\swapcounts \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swapdimens \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swaptypesface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke
<code>\switchstyleonly \[*]...</code> * CSNAME
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...,¹...] [...,²...,...]</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 inherits: \nastavmeziradkovoumezeru
<code>\switchtointerlinespace [...,[*]...]</code> <div style="text-align: center;"><small>OPT</small></div> * zap vyp reset auto male stredni velke NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbol [...¹] [...²]</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 NAME
<code>\symbolreference [...]</code> * REFERENCE
<code>\symbol {...}</code> * NAME
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>

\synchro ¹ zemarking [...] [² ...] [³ ...] <div> <div>1</div> <div>BESCHRIFTUNG</div> </div> <div> <div>2</div> <div>NUMMER</div> </div> <div> <div>3</div> <div>drzet</div> </div> <div>OPT</div>
\synthesizeoutputstreams [...,*,...] <div> <div>*</div> <div>NAME</div> </div>
\synchronizestrut {...} <div> <div>*</div> <div>ano ne auto kap prizpusobive radek implicitni CHARACTER</div> </div>
\synchronizewhitespace
\SYNONYM [¹ ...] {...} {...} <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>CONTENT</div> </div> <div>OPT</div> <div>instances: zkratka</div>
\systemlog {...} {...} {...} <div> <div>1</div> <div>FILE</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
\systemlogfirst {...} {...} {...} <div> <div>1</div> <div>FILE</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
\systemloglast {...} {...} {...} <div> <div>1</div> <div>FILE</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
\systemsetups {...} <div> <div>*</div> <div>NAME</div> </div>
\TABLE
\TaBlE
\TEX
\TeX
\TheNormalizedFontSize
\TransparencyHack

<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\taglabellanguage</code>
<code>\taglabeltext {...}</code> * KEY
<code>\tbinom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\tecka {...}</code> * CHARACTER
<code>\tecky [...]</code> <small>OPT</small> * NUMMER
<code>\tecky [..., ..., ..., ...]</code> <small>OPT</small> * inherits: \setupperiods
<code>\tema [..., ..., ..., ...]</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\tenkalinka</code>
<code>\tenkelinky [..., ..., ..., ..., ...]</code> <small>OPT</small> * inherits: \nastavtenkelinky

$\backslash\mathrm{tequal}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{testandsplitstring}$ $\overset{1}{\dots}$ $\backslash\mathrm{at}$ $\overset{2}{\dots}$ $\backslash\mathrm{to}$ $\overset{3}{\dots}$ $\backslash\mathrm{and}$ $\overset{4}{\dots}$ 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
$\backslash\mathrm{testcolumn}$ $[\overset{1}{\dots}]$ $[\overset{2}{\dots}]$ <small>OPT</small> 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testfeature}$ $\{\dots\}$ * NUMMER
$\backslash\mathrm{testfeatureonce}$ $\{\dots\}$ * NUMMER
$\backslash\mathrm{testpage}$ $[\overset{1}{\dots}]$ $[\overset{2}{\dots}]$ <small>OPT</small> 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testpageonly}$ $[\overset{1}{\dots}]$ $[\overset{2}{\dots}]$ <small>OPT</small> 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testpagesync}$ $[\overset{1}{\dots}]$ $[\overset{2}{\dots}]$ <small>OPT</small> 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testtokens}$ $[\dots]$ * NAME
$\backslash\mathrm{tex}$ $\{\dots\}$ * CONTENT
$\backslash\mathrm{texdefinition}$ $\{\dots\}$ * NAME
$\backslash\mathrm{texsetup}$ $\{\dots\}$ * NAME
$\backslash\mathrm{TEXTBACKGROUND}$ $\{\dots\}$ * CONTENT

`\textcitation [...1...2...] [...]`

OPT

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 REFERENCE

`\textcitation [...1...] [...]`

OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\textcitation [...1...2...] [...2...]`

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 KEY = VALUE

`\textcite [...1...2...] [...]`

OPT

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 REFERENCE

`\textcite [...1...] [...]`

OPT

1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\textcite [...1...2...] [...2...]`

1 odkaz = REFERENCE
 alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
 authornum authoryear
 pred = BEFEHL
 po = BEFEHL
 vlevo = BEFEHL
 vpravo = BEFEHL
 inherits: \setupbtx

2 KEY = VALUE

`\textcontrolspace`

`\textflowcollector {...}`

* NAME

`\texthlavicky {...}`

* KEY

$\backslash\text{textmath}\{...\}$ * CONTENT
$\backslash\text{textminus}$
$\backslash\text{texnapovedy}\left[\overset{1}{...}\right]\{\overset{2}{...}\}\{\overset{3}{...}\}$ <small>OPT</small> 1 REFERENCE 2 TEXT 3 TEXT
$\backslash\text{textormathchar}\{...\}$ * NUMMER
$\backslash\text{textovalinka}\left[\overset{1}{...}\right]\{\overset{2}{...}\}$ <small>OPT</small> <small>OPT</small> 1 vrsek nastred spodek 2 TEXT
$\backslash\text{textplus}$
$\backslash\text{textpopisku}\{...\}$ * KEY
$\backslash\text{POPISEKtext}\{...\}$ * KEY instances: hlavicka popisek mathlabel taglabel jednotka operator prefix suffix btxlabel
$\backslash\text{textvisiblespace}$
$\backslash\text{tfrac}\{\overset{1}{...}\}\{\overset{2}{...}\}$ 1 CONTENT 2 CONTENT
$\backslash\text{thai}$
$\backslash\text{thainumerals}\{...\}$ * NUMMER
$\backslash\text{thefirstcharacter}\{...\}$ * TEXT
$\backslash\text{thenormalizedbodyfontsize}\{...\}$ * DIMENSION
$\backslash\text{theremainingcharacters}\{...\}$ * TEXT
$\backslash\text{thickspace}$

<code>\thinspace</code>
<code>\thirtoffivearguments {¹...} {²...} {³...} {⁴...} {⁵...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\thirtoffourarguments {¹...} {²...} {³...} {⁴...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\thirdofsixarguments {¹...} {²...} {³...} {⁴...} {⁵...} {⁶...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\thirdofthreearguments {¹...} {²...} {³...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thirdofthreeunexpanded {¹...} {²...} {³...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thookleftarrow {¹...} {²...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\thookrightarrow {¹...} {²...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\threedigitrounding {...}</code> * NUMMER
<code>\tibetannumerals {...}</code> * NUMMER

<p><code>\tightlayer [...]</code></p> <p>* NAME</p>
<p><code>\tilde {...}</code></p> <p>* CHARACTER</p>
<p><code>\tinyfont</code></p>
<p><code>\titul [...¹,...²]{...}</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\tLeftarrow {...¹}{...²}</code> <small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\tLeftrightarrow {...¹}{...²}</code> <small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\tlacitko [...¹,...²]{...} [...³]</code> <small>OPT</small></p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\tlacitkomenu [...¹,...²,...³]{...}{...}</code></p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\tlacitkomenu [...¹][...²,...³]{...}{...}</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \nastavinterakcnimenu</p> <p>3 TEXT</p> <p>4 REFERENCE</p>
<p><code>\BUTTON [...¹,...²]{...} [...³]</code> <small>OPT</small></p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p> <p>instances: button</p>
<p><code>\tlap {...}</code></p> <p>* CONTENT</p>

$\xleftarrow{\text{...}}$ $\xleftarrow{\text{...}}$ 1 TEXT 2 TEXT
$\leftharpoondown \text{...}$ $\leftharpoondown \text{...}$ 1 TEXT 2 TEXT
$\leftharpoonup \text{...}$ $\leftharpoonup \text{...}$ 1 TEXT 2 TEXT
$\xrightarrow{\text{...}}$ $\xrightarrow{\text{...}}$ 1 TEXT 2 TEXT
$\leftrightharpoons \text{...}$ $\leftrightharpoons \text{...}$ 1 TEXT 2 TEXT
\loustkacary
$\tmapsto \text{...}$ $\tmapsto \text{...}$ 1 TEXT 2 TEXT
$\tochar \text{...}$ * NAME
$\tolinenote [\text{...}]$ * REFERENCE
$\topbox \text{...}$ * CONTENT
$\topleftbox \text{...}$ * CONTENT
$\toplinebox \text{...}$ * CONTENT
$\toprightbox \text{...}$ * CONTENT
$\topskippedbox \text{...}$ * CONTENT

$\backslash\mathrm{tRightarrow}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{tracecatcodetables}$
$\backslash\mathrm{tracedfontname}$ $\{...\}$ <div> <div>* FONT</div> </div>
$\backslash\mathrm{traceoutputroutines}$
$\backslash\mathrm{tracepositions}$
$\backslash\mathrm{transparencycomponents}$ $\{...\}$ <div> <div>* COLOR</div> </div>
$\backslash\mathrm{transparent}$ $[\overset{1}{\dots}]\{\overset{2}{\dots}\}$ <div> <div>1 COLOR</div> <div>2 CONTENT</div> </div>
$\backslash\mathrm{tref}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}[\overset{3}{\dots}]$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> <div>3 REFERENCE</div> </div>
$\backslash\mathrm{trel}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{trightarrow}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{trightharpoondown}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{trightharpoonup}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{trightleftharpoons}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{trightoverleftarrow}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>

<code>\triplebond</code>
<code>\truefilename {...}</code> * FILE
<code>\truefontname {...}</code> * FONT
<code>\ttraggedright</code>
<code>\ttriplerel {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>1</small> OPT <small>2</small> OPT </div> 1 TEXT 2 TEXT
<code>\twoheadleftarrow {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>1</small> OPT <small>2</small> OPT </div> 1 TEXT 2 TEXT
<code>\twoheadrightarrow {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>1</small> OPT <small>2</small> OPT </div> 1 TEXT 2 TEXT
<code>\tucne</code>
<code>\tucnekurzivni</code>
<code>\tucnesklonene</code>
<code>\tvr damezera</code>
<code>\tvr demezery</code>
<code>\twodigitrounding {...}</code> * NUMMER
<code>\tx</code>
<code>\txx</code>
<code>\typebuffer [...¹...] [...²...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>1</small> OPT <small>2</small> OPT </div> 1 BUFFER 2 inherits: \nastavopis
<code>\opisBUFFER [...[*]...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>1</small> OPT </div> * inherits: \nastavopis
<code>\typedefinedbuffer [...¹] [...²...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>1</small> OPT </div> 1 BUFFER 2 inherits: \nastavopis

<code>\typeface</code>
<code>\typescriptone</code>
<code>\typescriptprefix {...}</code> * NAME
<code>\typescriptthree</code>
<code>\typescripttwo</code>
<code>\typesetbuffer</code> ¹ <code>[...]</code> ² <code>[...,...]</code> OPT OPT 1 * BUFFER 2 inherits: \setupexternalfigure
<code>\typesetfile</code> ¹ <code>[...]</code> ² <code>[...]</code> ³ <code>[...,...]</code> OPT OPT 1 NAME FILE 2 FILE TEXT 3 inherits: \setupexternalfigure
<code>\uconvertnumber</code> ¹ <code>{...}</code> ² <code>{...}</code> 1 inherits: \konvertujcislo 2 NUMMER
<code>\uedcatcodecommand</code> ¹ <code>\...</code> ² <code>...</code> ³ <code>{...}</code> 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
<code>\ukazbarvu</code> ¹ <code>[...]</code> * COLOR
<code>\ukazmrizku</code> ¹ <code>[...*,...]</code> OPT * reset spodek vrsek zadny vse radky ramecek nonumber vpravo vlevo vnejsi sloupce
<code>\ukaznastaveni</code> ¹ <code>[...*,...]</code> OPT * pt bp cm mm dd cc pc nd nc sp in
<code>\ukazpaletu</code> ¹ <code>[...]</code> ² <code>[...,...]</code> OPT 1 NAME 2 horizontalne vertikalne cislo hodnota jmeno
<code>\ukazpodpery</code>
<code>\ukazpostredizakladnihofontu</code> ¹ <code>[...*,...]</code> * inherits: \nastavzakladnifont

<p><code>\ukazramecek [...¹,...] [...²,...]</code> <small>OPT OPT</small></p> <p>1 vrsek zahlavi text upati spodek</p> <p>2 levahrana levyokraj text pravyokraj pravahrana</p>
<p><code>\ukazsadasymbolu [...]</code></p> <p>* NAME</p>
<p><code>\ukazskupinubarev [...¹] [...²,...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 horizontalne vertikalne cislo hodnota jmeno</p>
<p><code>\ukazupravu [...[*]]</code> <small>OPT</small></p> <p>* zlom vse boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math kurziva origin reset</p>
<p><code>\ukazvytisk [...¹,...] [...²,...] [...³,...]</code> <small>OPT OPT OPT</small></p> <p>1 inherits: \nastavvelikostpapiu</p> <p>2 inherits: \nastavvelikostpapiu</p> <p>3 inherits: \nastavvzhled</p>
<p><code>\ukazvzhled [...[*],...]</code> <small>OPT</small></p> <p>* pt bp cm mm dd cc pc nd nc sp in</p>
<p><code>\ukazzakladnifont [...[*],...]</code></p> <p>* inherits: \nastavzakladnifont</p>
<p><code>\umistikombinovanyseznam [...¹] [...²,...]</code> <small>OPT</small></p> <p>1 LISTE</p> <p>2 inherits: \nastavseznam</p>
<p><code>\umistiCOMBINEDLIST [...[*],...]</code> <small>OPT</small></p> <p>* inherits: \nastavseznam</p> <p>instances: obsah</p>
<p><code>\umistilegendu [...¹,...] {...²} {...³}</code> <small>OPT</small></p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p>
<p><code>\umistilokalnipoznamkypodcarou [...[*],...]</code> <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p><code>\umistinadsebe {...¹} {...²}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>

<p><code>\umistinamrizku [...]¹ {...}²</code> <small>OPT</small></p> <p>1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred NAME</p> <p>2 CONTENT</p>
<p><code>\umistinamrizku [...]¹,...² {...}</code> <small>OPT</small></p> <p>1 inherits: \definegridsnapping</p> <p>2 CONTENT</p>
<p><code>\umistipodrovnici [...][*],...^{OPT}</code></p> <p>* + - REFERENCE</p>
<p><code>\umistipoznamkypodcarou [...][*],...^{OPT},...[*]</code></p> <p>* inherits: \setupnote</p>
<p><code>\umistirejstrik [...]¹ [...]²,...^{OPT},...[*]</code></p> <p>1 NAME</p> <p>2 inherits: \nastavrejstrik</p>
<p><code>\umistiREJSTRIK [...][*],...^{OPT},...[*]</code></p> <p>* inherits: \nastavrejstrik</p> <p>instances: rejstrik</p>
<p><code>\umistirovnici [...][*],...^{OPT}</code></p> <p>* + - REFERENCE</p>
<p><code>\umistiseznam [...]¹,...^{OPT} [...]²,...^{OPT},...[*]</code></p> <p>1 LISTE</p> <p>2 inherits: \nastavseznam</p>
<p><code>\umistivedlesebe {...}¹ {...}²</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><code>\umistizalozky [...]¹,...^{OPT} [...]²,...^{OPT} [...]³,...^{OPT},...[*]</code></p> <p>1 ABSCHNITT LISTE</p> <p>2 ABSCHNITT LISTE</p> <p>3 inherits: \setupbookmark</p>
<p><code>\undefinevalue {...}[*]</code></p> <p>* NAME</p>
<p><code>\undepthed {...}[*]</code></p> <p>* CONTENT</p>

$\underbartext{...}{...}$ 1 TEXT 2 TEXT
$\underbrace{...}$ * TEXT
$\underbracetext{...}{...}$ 1 TEXT 2 TEXT
$\underbracket{...}$ * TEXT
$\underbrackettext{...}{...}$ 1 TEXT 2 TEXT
$\underdash{...}$ * CONTENT
$\underdashes{...}$ * CONTENT
$\underdot{...}$ * CONTENT
$\underdots{...}$ * CONTENT
$\underleftarrow{...}$ * TEXT
$\underleftharpoondown{...}$ * TEXT
$\underleftharpoonup{...}$ * TEXT
$\underleftrightharpoonup{...}$ * TEXT
$\underparent{...}$ * TEXT
$\underparenttext{...}{...}$ 1 TEXT 2 TEXT

`\underrandom {.*.}`

* CONTENT

$$\backslash\underandoms \{.\!.\!.^*\}$$

* CONTENT

 $\underrightarrow{\{...\}}$

* TEXT

 $\underset{\cdot}{\rightarrow} \{...\}$

* TEXT

 $\underset{\text{right}}{\text{harpoonup}} \{...\}$

* TEXT

$$\backslashunderset{\dots}{\dots}$$

1 TEXT

2 TEXT

`\underline {...}`

* CONTENT

`\understrikes {...}`

* CONTENT

 $\xrightarrow{\dots}$

* TEXT

 $\xrightarrow{\dots}$

* TEXT

```
\undoassign [...] [..2..]
```

1 TEXT

2 KEY = VALUE

$$\backslash\mathrm{unframed} \left[\dots, \dots \stackrel{1}{=} \dots, \dots \right] \{ \dots \stackrel{2}{\dots} \}$$

OPT

```
1 inherits: \nastavoramovani
```

2 CONTENT

$$\backslash unhhhbox \dots \backslash with \{...\}$$

1 CSNAME NUMMER

2 BEFEHL

`\unihex {...}`

* NUMMER

$\backslash\text{uniqueMPgraphic} \{.^1.\} \{.^2.\}$ <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash\text{uniqueMPpagegraphic} \{.^1.\} \{.^2.\}$ <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash\text{unitlanguage}$
$\backslash\text{unittext} \{.^*.\}$ * KEY
$\backslash\text{unprotect} \dots \backslash\text{protect}$
$\backslash\text{unprotected} .^* \backslash\text{par}$ * CONTENT
$\backslash\text{unregisterhyphenationpattern} [.^1.] [.^2.]$ <small>OPT</small> 1 SPRACHE 2 TEXT
$\backslash\text{unspaceafter} \backslash.^1. \{.^2.\}$ 1 CSNAME 2 TEXT
$\backslash\text{unspaceargument} .^1. \backslash\text{to} \backslash.^2.$ 1 TEXT 2 CSNAME
$\backslash\text{unspaced} \{.^*.\}$ * TEXT
$\backslash\text{unspacestring} .^1. \backslash\text{to} \backslash.^2.$ 1 TEXT 2 CSNAME
$\backslash\text{untexargument} \{.^1.\} \backslash\text{to} \backslash.^2.$ 1 TEXT 2 CSNAME
$\backslash\text{untexcommand} \{.^1.\} \backslash\text{to} \backslash.^2.$ 1 CSNAME 2 CSNAME
$\backslash\text{uppercased} \{.^*.\}$ * TEXT

\uppercasestring ¹ ... \to \ ² ... 1 TEXT 2 CSNAME
\upperlefthdoubleninequote
\upperlefthdoublesixquote
\upperleftsingleninequote
\upperleftsinglesixquote
\upperrighthdoubleninequote
\upperrighthdoublesixquote
\upperrightsingleninequote
\upperrightsinglesixquote
\urcicarakteristikurejstriku [¹ ...] [² ... _{OPT} ...] 1 NAME 2 language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc numberorder = cisl compress = ano ne vse kriterium = lokalne text aktualni predchozi vse ABSCHNITT
\url [...] * NAME
\usealignparameter *... * CSNAME
\useblankparameter *... * CSNAME
\usebodyfont [...,*...] * inherits: \nastavzakladnifont
\usebodyfontparameter *... * CSNAME
\usebtxdataset [¹ ...] [² ...] [³ ... _{OPT} ...] 1 NAME 2 FILE 3 specification = NAME
\usebtdefinitions [...] * FILE

\usecolors [...] * FILE
\usecomponent [...] * FILE
\usedummycolorparameter {...} * KEY
\usedummystyleandcolor {...} {...} 1 KEY 2 KEY
\usedummystyleparameter {...} * KEY
\useenvironment [...] * FILE
\useexternalrendering [...] [...] [...] [...] 1 NAME 2 NAME 3 FILE 4 auto embed
\usefigurebase [...] * reset FILE
\usefile [...] [...] [...] 1 NAME 2 FILE 3 TEXT
\usegridparameter *... * CSNAME
\useindentingparameter *... * CSNAME
\useindentnextparameter *... * CSNAME
\useinterlinespaceparameter *... * CSNAME
\uselanguageparameter *... * CSNAME

$\backslash\text{uselua module}$ [...] * FILE
$\backslash\text{useMPenvironmentbuffer}$ [...] * NAME
$\backslash\text{useMPgraphic}$ { ¹ ...} {..., ² _{OPT} ...,...} 1 NAME 2 KEY = VALUE
$\backslash\text{useMPlibrary}$ [...] * FILE
$\backslash\text{useMPrun}$ { ¹ ...} { ² ...} 1 NAME 2 NUMMER
$\backslash\text{useMPvariables}$ [¹ ...] [..., ² ...] 1 NAME 2 KEY
$\backslash\text{usemathstyleparameter}$ \... * CSNAME
$\backslash\text{useproduct}$ [...] * FILE
$\backslash\text{useprofileparameter}$ \... * CSNAME
$\backslash\text{useproject}$ [...] * FILE
$\backslash\text{userferenceparameter}$ \... * CSNAME
$\backslash\text{userpagenumber}$
$\backslash\text{usesetupparameter}$ \... * CSNAME
$\backslash\text{usestaticMPfigure}$ [..., ¹ _{OPT} ...,...] [² ...] 1 inherits: \setupscale 2 NAME
$\backslash\text{usesubpath}$ [...,*...] * PATH

```

\usetexmodule [1...] [2...,...] [3...,...]
               OPT          OPT
1  m p s x t
2  FILE
3  KEY = VALUE

```

```

\usetypescript [1...] [2...] [3...]
                OPT          OPT
1  serif sans mono math handwriting calligraphy casual vse
2  NAME fallback implicitni dtp simple
3  size jmeno

```

```

\usetypescriptfile [...*]

*  reset FILE

```

```

\usezipfile [1...] [2...]
              OPT
1  FILE
2  FILE

```

```

\utfchar {...}

*  NUMMER

```

```

\utflower {...}

*  TEXT

```

```

\utfupper {...}

*  TEXT

```

```

\utilityregisterlength

```

```

\uzijadresar [...*...]

*  PATH

```

```

\uzijbloky [...1...] [...2...] [...3...,...]
              OPT          OPT
1  NAME
2  + -
3  kriterium = text ABSCHNITT

```

```

\uzijexternidokument [1...] [2...] [3...]
                      OPT
1  NAME
2  FILE
3  TEXT

```

```

\uzijexterniobraz [1...] [2...] [3...] [...4...,...]
                      OPT          OPT
1  NAME
2  FILE
3  NAME
4  inherits: \setupexternalfigure

```

\uzijexternizvuk [...] ¹ [...] ² 1 NAME 2 FILE
\uzijJSscripts [...] ¹ [...] ² ,...] _{OPT} 1 FILE 2 NAME
\uzijmodul [...] ¹ [...] ² ,...] _{OPT} [...] ³ ,...] _{OPT} 1 m p s x t 2 FILE 3 KEY = VALUE
\uzijsymbol [...] [*] * FILE
\uzijURL [...] ¹ [...] ² [...] ³ [...] ⁴ _{OPT} _{OPT} 1 NAME 2 URL 3 FILE 4 TEXT
\uzijurl [...] ¹ [...] ² [...] ³ [...] ⁴ _{OPT} _{OPT} 1 NAME 2 URL 3 FILE 4 TEXT
\VerboseNumber {...} [*] * NUMMER
\VSEDNIDEN {...} [*] * NUMMER
\vboxreference [...] ¹ ,...] ₁ {...] ₂ 1 REFERENCE 2 CONTENT
\vec {...} [*] * CHARACTER
\velke ... [*] * CHARACTER
\verbatim {...} [*] * CONTENT

<code>\verbatimstring {...}</code> * CONTENT
<code>\verbosenummer {...}</code> * NUMMER
<code>\verticalgrowingbar [...,..[*]...,...]</code> * inherits: \setuppositionbar
<code>\verticalpositionbar [...,..[*]...,...]</code> * inherits: \setuppositionbar
<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\verze [...]</code> * koncept soubor docasne finalni NAME
<code>\vglue ...</code> * DIMENSION
<code>\viewerlayer [...]¹ {...}²</code> 1 NAME 2 CONTENT
<code>\vl [...]</code> <small>OPT</small> * NUMMER
<code>\vlasovalinka</code>
<code>\vlevo [...,..¹...,...]^{OPT} [...,..²...,...]^{OPT} {...}³</code> 1 odkaz = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\vphantom {...}</code> * CONTENT
<code>\vpos {...}¹ {...}²</code> 1 NAME 2 CONTENT

$\backslash\text{vpravo}$ $[...,\overset{1}{=},...]$ $[...,\overset{2}{=},...]$ $\{\overset{3}{...}\}$ <small>OPT OPT OPT</small> 1 odkaz = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
$\backslash\text{vradku}$ $\{\overset{1}{...}\}$ $[\overset{2}{...}]$ <small>OPT</small> 1 TEXT 2 REFERENCE
$\backslash\text{vsedniden}$ $\{\overset{*}{...}\}$ * NUMMER
$\backslash\text{vsmash}$ $\{\overset{*}{...}\}$ * CONTENT
$\backslash\text{vsmashbox}$ $\overset{*}{...}$ * CSNAME NUMMER
$\backslash\text{vsmashed}$ $\{\overset{*}{...}\}$ * CONTENT
$\backslash\text{vspace}$ $[\overset{1}{...}]$ $[\overset{2}{...}]$ <small>OPT OPT</small> 1 NAME 2 NAME
$\backslash\text{vspacing}$ $[\overset{*}{...},...]$ <small>OPT</small> * nastaveni stejnastranka max sila enable zablokovat zadnabila zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME
$\backslash\text{vyberbloky}$ $[...,\overset{1}{...}]$ $[...,\overset{2}{...}]$ $[...,\overset{3}{=},...]$ <small>OPT OPT OPT</small> 1 NAME 2 + - 3 kriterium = text ABSCHNITT
$\backslash\text{VYCET}$ $[...,\overset{1}{...}]$ $\{\overset{2}{...}\}$ $\overset{3}{...}$ $\backslash\text{par}$ <small>OPT OPT</small> 1 REFERENCE 2 TEXT 3 CONTENT
$\backslash\text{vyplnenytext}$ $[...,\overset{1}{=},...]$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ <small>OPT OPT OPT</small> 1 inherits: \nastavvyplnovelinky 2 TEXT 3 TEXT

\vyplnovelinky [...,.. ¹ ...,..] {...} ² {...} ³ <div> <div>OPT</div> <div>OPT</div> <div>OPT</div> </div> 1 inherits: \nastavvyplnovelinky 2 TEXT 3 TEXT
\vyplnovyradek [...,.. [*] ...,..] * inherits: \nastavvyplnoveradky
\vysoky {...} * CONTENT
\VYSOKO {...} * CONTENT instances: unitshigh
\WidthSpanningText {...} ¹ {...} ² {...} ³ 1 TEXT 2 DIMENSION 3 FONT
\wdofstring {...} * TEXT
\widthhofstring {...} * TEXT
\widthspanningtext {...} ¹ {...} ² {...} ³ 1 TEXT 2 DIMENSION 3 FONT
\withoutpt {...} * DIMENSION
\words {...} * TEXT
\wordtonumber {...} ¹ {...} ² 1 jedna dve tri ctyri pet 2 TEXT
\writadatolist [...] ¹ [...,.. ² ...,..] [...,.. ³ ...,..] <div>OPT</div> 1 LISTE 2 inherits: \nastavseznam 3 KEY = VALUE

$\backslash\mathrm{writestatus}\{\ldots\}\{\ldots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{XETEX}$
$\backslash\mathrm{XeTeX}$
$\backslash\mathrm{xdefconvertedargument}\backslash\ldots\{\ldots\}$ 1 CSNAME 2 TEXT
$\backslash\mathrm{xequal}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xfrac}\{\ldots\}\{\ldots\}$ 1 CONTENT 2 CONTENT
$\backslash\mathrm{xhookleftarrow}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xhookrightarrow}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xLeftarrow}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xLeftrightarrow}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xleftarrow}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xleftharpoonupdown}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\mathrm{xleftharpoonup}\{\ldots\}\{\ldots\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT

$\xleftarrow{\text{...}} \text{...}$ $\xrightarrow{\text{...}} \text{...}$ 1 TEXT 2 TEXT
$\xleftrightharpoons{\text{...}} \text{...}$ $\xrightarrow{\text{...}} \text{...}$ 1 TEXT 2 TEXT
$\xmapsto{\text{...}} \text{...}$ 1 TEXT 2 TEXT
$\xmladdindex \text{...}$ * NODE
$\xmلاfterdocumentsetup \text{...} \text{...} \text{...}$ 1 NAME 2 SETUP 3 SETUP
$\xmلاftersetup \text{...} \text{...}$ 1 SETUP 2 SETUP
$\xmlall \text{...} \text{...}$ 1 NODE 2 LPATH
$\xmلاppenddocumentsetup \text{...} \text{...}$ 1 NAME 2 SETUP
$\xmلاppendsetup \text{...}$ * SETUP
$\xmلاpplyselectors \text{...}$ * NODE
$\xmلاtt \text{...} \text{...}$ 1 NODE 2 NAME
$\xmلاttdef \text{...} \text{...} \text{...}$ 1 NODE 2 NAME 3 TEXT

`\xmlattribute {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 NAME

`\xmlattributedef {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 TEXT

`\xmlbadinclusions {...}`

- * NODE

`\xmlbeforedocumentsetup {...} {...} {...}`

- 1 NAME
- 2 SETUP
- 3 SETUP

`\xmlbeforesetup {...} {...}`

- 1 SETUP
- 2 SETUP

`\xmlcommand {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 XMLSETUP

`\xmlconcat {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT
- 4 FIRST
- 5 LAST

`\xmlcontext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlcount {...}`

- * NODE

\xmldefaulttotext {...} * NODE
\xmldirectives {...} * NODE
\xmldirectivesafter {...} * NODE
\xmldirectivesbefore {...} * NODE
\xmldisplayverbatim {...} * NODE
\xmldoif {...} {...} {...} 1 NODE 2 LPATH 3 TRUE
\xmldoifelse {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelseempty {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelseselfempty {...} {...} {...} 1 NODE 2 TRUE 3 FALSE
\xmldoifelsesetText {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE

\xmldoifelsevalue {...} {...} {...} {...}

- 1 CATEGORY
- 2 NAME
- 3 TRUE
- 4 FALSE

\xmldoifnot {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmldoifnotselfempty {...} {...}

- 1 NODE
- 2 TRUE

\xmldoifnottext {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmldoifselfempty {...} {...}

- 1 NODE
- 2 TRUE

\xmldoiftext {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmlelement {...} {...}

- 1 NODE
- 2 NUMMER

\xmlfilter {...} {...}

- 1 NODE
- 2 LPATH

\xmlfirst {...} {...}

- 1 NODE
- 2 LPATH

\xmlflush {...}

- * NODE

\xmlflushcontext {...}

- * NODE

<pre>\xmlflushdocumentsetups {...} {...}</pre> <pre>1 NAME</pre> <pre>2 SETUP</pre>
<pre>\xmlflushlinewise {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushpure {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushspacewise {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushtext {...}</pre> <pre>* NODE</pre>
<pre>\xmlchainatt {...} {...}</pre> <pre>1 NODE</pre> <pre>2 NAME</pre>
<pre>\xmlchainattdef {...} {...} {...}</pre> <pre>1 NODE</pre> <pre>2 NAME</pre> <pre>3 TEXT</pre>
<pre>\xmlchecknamespace {...} {...}</pre> <pre>1 NODE</pre> <pre>2 NAME</pre>
<pre>\xmlinclude {...} {...} {...}</pre> <pre>1 NODE</pre> <pre>2 LPATH</pre> <pre>3 NAME</pre>
<pre>\xmlinclusion {...}</pre> <pre>* NODE</pre>
<pre>\xmlinclusions {...}</pre> <pre>* NODE</pre>
<pre>\xmlinfo {...}</pre> <pre>* NODE</pre>
<pre>\xmlinjector {...}</pre> <pre>* NAME</pre>
<pre>\xmlinlineverbatim {...}</pre> <pre>* NODE</pre>

\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE

<code>\xmlnonspace {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlpath {...}</code> * NODE
<code>\xmlpos {...}</code> * NODE
<code>\xmlposition {...} {...} {...}</code> 1 NODE 2 LPATH 3 NUMMER
<code>\xmlprependdocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {...}</code> * SETUP
<code>\xmlprettyprint {...} {...}</code> 1 NODE 2 NAME
<code>\xmlprocessbuffer {...} {...} {...}</code> 1 BUFFER 2 NAME 3 XMLSETUP
<code>\xmlprocessdata {...} {...} {...}</code> 1 NAME 2 TEXT 3 XMLSETUP
<code>\xmlprocessfile {...} {...} {...}</code> 1 NAME 2 FILE 3 XMLSETUP
<code>\xmlpure {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlraw {...}</code> * NODE

\xmlrefatt {...} {...} 1 NODE 2 NAME
\xmlregistereddokumentsetups {...} {...} 1 NAME 2 SETUP
\xmlregisteredsetups
\xmlregisterns {...} {...} 1 NAME 2 URL
\xmlremapname {...} {...} {...} {...} 1 NODE 2 LPATH 3 NAME 4 NAME
\xmlremapnamespace {...} {...} {...} 1 NODE 2 NAME 3 NAME
\xmlremoveddocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlremovesetup {...} * SETUP
\xmlresetdocumentsetups {...} * NAME
\xmlresetinjectors
\xmlresetsetups {...} * NAME
\xmlsave {...} {...} 1 NODE 2 FILE
\xmlsetentity {...} {...} 1 NAME 2 TEXT

`\xmlsetfunction {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 LUAFUNCTION

`\xmlsetinjectors [...]*...`

- * NAME

`\xmlsetsetup {...} {...} {...}`

- 1 NAME
- 2 LPATH
- 3 SETUP

`\xmlsetup {...} {...}`

- 1 NODE
- 2 SETUP

`\xmlshow {...}`

- * NODE

`\xmlsnippet {...} {...}`

- 1 NODE
- 2 NUMMER

`\xmlstrip {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstripnolines {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstripped {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlstrippednolines {...} {...}`

- 1 NODE
- 2 LPATH

`\xmltag {...}`

- * NODE

`\xmltexentity {...} {...}`

- 1 NAME
- 2 TEXT

`\xmltext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmltobuffer {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltobufferverbose {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 BUFFER

`\xmltofile {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 FILE

`\xmlvalue {...} {...} {...}`

- 1 CATEGORY
- 2 NAME
- 3 TEXT

`\xmlverbatim {...}`

- * NODE

`\xrightarrow[OPT]{...} [OPT]{...}`

- 1 TEXT
- 2 TEXT

`\xrel [OPT]{...} [OPT]{...}`

- 1 TEXT
- 2 TEXT

`\xrightarrow[OPT]{...} [OPT]{...}`

- 1 TEXT
- 2 TEXT

`\xrightarrow[OPT]{...} [OPT]{...}`

- 1 TEXT
- 2 TEXT

`\xrightarrow[OPT]{...} [OPT]{...}`

- 1 TEXT
- 2 TEXT

$\backslash\mathrm{xrightleftharpoons}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xrightoverleftarrow}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xsplitstring}$ $\backslash\overset{1}{\dots}\{\overset{2}{\dots}\}$ 1 CSNAME 2 TEXT
$\backslash\mathrm{xtriplerel}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xtwoheadleftarrow}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xtwoheadrightarrow}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xxfrac}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1 CONTENT 2 CONTENT
$\backslash\mathrm{xypos}$ $\{\overset{*}{\dots}\}$ * NAME
$\backslash\mathrm{Znak}$ $\{\overset{*}{\dots}\}$ * NUMMER
$\backslash\mathrm{Znaky}$ $\{\overset{*}{\dots}\}$ * NUMMER
$\backslash\mathrm{zadnamezera}$
$\backslash\mathrm{zadnehorniadolniradky}$
$\backslash\mathrm{zadnezahlaviaupati}$
$\backslash\mathrm{zachovejbloky}$ $[\overset{1}{\dots},\dots][\overset{2}{\dots},\dots]$ <small>OPT</small> 1 NAME 2 + -

\zalozka [¹ ...] { ² ...} <small>OPT</small> 1 ABSCHNITT LISTE 2 TEXT
\zapidoseznamu [¹ ...] [..., ² ...,...] { ³ ...} { ⁴ ...} <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam 3 NUMMER 4 TEXT
\zapismeziseznam [¹ ...] [..., ² ...,...] { ³ ...} <small>OPT</small> 1 LISTE 2 inherits: \nastavseznam 3 BEFEHL
\zaramovani [..., ¹ ...,...] { ² ...} <small>OPT</small> 1 inherits: \nastavoramovani 2 CONTENT
\zarovnanonastred {...} * CONTENT
\zarovnanovlevo {...} * CONTENT
\zarovnanovpravo {...} * CONTENT
\zasobnikpoli [¹ ...] [..., ² ...,...] [..., ³ ...,...] <small>OPT</small> <small>OPT</small> 1 NAME 2 NAME 3 inherits: \setupfieldcategory
\ziskejbuffer [[*] ...] <small>OPT</small> * BUFFER
\ziskatBUFFER
\ziskejznaceni [¹ ...] [² ...] [³ ...] <small>OPT</small> <small>OPT</small> 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\zkratka [¹ ...] { ² ...} { ³ ...} <small>OPT</small> 1 NAME 2 TEXT 3 CONTENT

$\backslash FRACTION \{...\} \{...\}$ 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash znaceni (...^1,...) (...^2,...) [...^3]$ 1 POSITION 2 POSITION 3 REFERENCE
$\backslash znak \{...\}$ * NUMMER
$\backslash znaky \{...\}$ * NUMMER
$\backslash zpracujbloky [...^1,...] [...^2,...] [...^3,...]$ <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 NAME 2 + - 3 kriterium = text ABSCHNITT
$\backslash zrcadlit \{...\}$ * CONTENT
$\backslash zref [...]$ * REFERENCE
$\backslash zvysit \backslash ...$ * CSNAME
$\backslash zvysit cd:parentheses-1$ * CSNAME NUMMER



PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com