



ConTeXt

přikazy

CS

ConTeXt

příkazy

cs / český
9. února 2018

\AfterPar {...} * BEFEHL
\Alphabeticnumerals {...} * NUMMER
\AMSTEX
\AmSTeX
\And
\abjadnaivenumerals {...} * NUMMER
\abjadnodotnumerals {...} * NUMMER
\abjadnumerals {...} * NUMMER
\activatespacehandler {...} * zap vyp ano fixne
\acute {...} * CHARACTER
\adaptcollector [... ¹] [..., ² ...,...] 1 NAME OPT 2 inherits: \setupcollector
\adaptfontfeature [... ¹] [..., ² ...,...] 1 NAME 2 inherits: \definefontfeature
\adaptpapersize [... ¹ ,...] [..., ² ...,...] 1 inherits: \nastavvelikostpapiu OPT 2 inherits: \nastavvelikostpapiu
\addfeature [...] * NAME
\addfeature {...} * NAME
\addfontpath [...,*...] * PATH
\addtocommalist {... ¹ } \... ² 1 TEXT 2 CSNAME
\addtoJSreamble {... ¹ } {... ² } 1 NAME 2 CONTENT
\addvalue {... ¹ } {... ² } 1 NAME 2 TEXT

\aftersplitstring ¹... \at ²... \to \³...

1 TEXT
2 TEXT
3 CSNAME

\aftertestandsplitstring ¹... \at ²... \to \³...

1 TEXT
2 TEXT
3 CSNAME

\aktualnicislonaDPisu

\aktualnidatum [...,*...]

* rok mesic den vsednica y yy Y m mm M d dd D w W mezera \ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT znacka day:++ day:++ d:++ d:++ dd:++ dd:++ D:++ D:++ month:jalali m:jalali jalali:to jalali:from

\alignbottom

\aligned [...¹,...] {²...}

1 vlevo nastred vpravo vrsek spodek radek l c r m t b g
2 CONTENT

\alignedbox [...¹,...] \²... {³...}

1 vlevo nastred vpravo vrsek spodek radek l c r m t b g
2 CSNAME
3 CONTENT

\alignedline {¹...} {²...} {³...}

1 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana
2 vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin inneredge outeredge zpetnamezera cutspace levyokraj prav yokraj levahrana pravahrana
3 CONTENT

\alignhere

\alignmentcharacter

\allinputpaths

\alphabeticnumerals {^{*}...}

* NUMMER

\alwayscitation [...¹,...¹,...] [...²...]

1 odkaz = REFERENCE^P
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
inherits: \setupbtx
2 REFERENCE

\alwayscitation [...¹...] [...²...]

1 implicitni category^Pentry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

```

\alwayscitation [...1...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
    authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE

```

```

\alwayscite [...1...] [...2]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
    authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE

```

```

\alwayscite [...1] [...2]
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

```

```

\alwayscite [...1...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
    authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE

```

\ampersand

```

\anchor [...1] [...2...] [...3...] {...4}
1 NAME OPT OPT
2 inherits: \setupplayer
3 inherits: \setupplayerinherits: \nastavoramovani
4 CONTENT

```

\antikva

```

\appendetoks ...1 \to ...2
1 BEFEHL
2 CSNAME

```

```

\appendgvalue {...1} {...2}
1 NAME
2 BEFEHL

```

```

\appendtocommalist {...1} \...2
1 TEXT
2 CSNAME

```

```

\appendtoks ...1 \to ...2
1 BEFEHL
2 CSNAME

```

```

\appendtoksonce ...1 \to ...2
1 BEFEHL
2 CSNAME

```

<code>\appendvalue {...} {...}</code> 1 NAME 2 BEFEHL
<code>\apply {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\applyalternativestyle {...}</code> * NAME
<code>\applyprocessor {...} {...}</code> 1 NAME 2 CONTENT
<code>\applytofirstcharacter \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytocharacters \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringchar \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringcharspaced \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringline \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringlinespaced \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringword \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringwordspaced \... {...}</code> 1 CSNAME 2 TEXT
<code>\applytowords \... {...}</code> 1 CSNAME 2 TEXT
<code>\arabicdecimals {...}</code> * NUMMER
<code>\arabicexnumerals {...}</code> * NUMMER
<code>\arabicnumerals {...}</code> * NUMMER
<code>\arg {...}</code> * CONTENT

<pre> \asciistr {...} * CONTENT </pre>
<pre> \assignalfadimension {...} \^2... {...} {...} {...} 1 male stredni velke zadny DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION </pre>
<pre> \assigndimen \^1... {...} 1 CSNAME 2 DIMENSION </pre>
<pre> \assigndimension {...} \^2... {...} {...} {...} 1 [-+]male [-+]stredni [-+]velke zadny DIMENSION 2 CSNAME 3 DIMENSION 4 DIMENSION 5 DIMENSION </pre>
<pre> \assignifempty \^1... {...} 1 CSNAME 2 BEFEHL </pre>
<pre> \assigntranslation [...,\^1...,\^2... \to \^2... 1 SPRACHE = TEXT 2 CSNAME </pre>
<pre> \assignvalue {...} \^2... {...} {...} {...} 1 male stredni velke TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL </pre>
<pre> \assignwidth {...} \^2... {...} {...} 1 prizpusobive siroky DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION </pre>
<pre> \assumelongusagecs \^1... {...} 1 CSNAME 2 CONTENT </pre>
<pre> \astype {...} * CONTENT </pre>
<pre> \ATTACHMENT [...]\^1... [\^2...,\^2...,\^2...,\^2... 1 NAME OPT OPT 2 inherits: \setupattachment instances: attachment </pre>
<pre> \attachment [...]\^1... [\^2...,\^2...,\^2...,\^2... 1 NAME OPT OPT 2 inherits: \setupattachment </pre>
<pre> \autocap {...} * TEXT </pre>
<pre> \autodirhbox \^1... {...} 1 TEXT OPT 2 CONTENT </pre>

$\backslash\text{autodirvbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvtop}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{automathematics}$ $\{.*\}$ * CONTENT
$\backslash\text{autosetups}$ $\{...,...\}$ * NAME
$\backslash\text{autostarttext}$... $\backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar}$ $\{.*\}$ * BEFEHL
$\backslash\text{Big}$ $.*$ * CHARACTER
$\backslash\text{Bigg}$ $.*$ * CHARACTER
$\backslash\text{Biggl}$ $.*$ * CHARACTER
$\backslash\text{Biggm}$ $.*$ * CHARACTER
$\backslash\text{Biggr}$ $.*$ * CHARACTER
$\backslash\text{Bigl}$ $.*$ * CHARACTER
$\backslash\text{Bigm}$ $.*$ * CHARACTER
$\backslash\text{Bigr}$ $.*$ * CHARACTER
$\backslash\text{backgroundimage}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ $\{\overset{4}{...}\}$ 1 NUMMER 2 DIMENSION 3 DIMENSION 4 BEFEHL

$\backslash\text{backgroundimagefill}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1 NUMBER 2 DIMENSION 3 DIMENSION 4 BEFEHL
$\backslash\text{backgroundline}$ $[.^1.]$ $\{.^2.\}$ 1 COLOR 2 CONTENT
$\backslash\text{bar}$ $\{.^{..}\}$ * CHARACTER
$\backslash\text{barevnaalista}$ $[...,*,...]$ * COLOR
$\backslash\text{barva}$ $[.^1.]$ $\{.^2.\}$ 1 COLOR 2 CONTENT
$\backslash\text{BAR}$ $\{.^{..}\}$ * CONTENT instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar
$\backslash\text{hiddenbar}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{nobar}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{overbar}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{overbars}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{overstrike}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{overstrikes}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{underbar}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{underbars}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{underdash}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{underdashes}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{underdot}$ $\{.^{..}\}$ * CONTENT
$\backslash\text{underdots}$ $\{.^{..}\}$ * CONTENT

<code>\underrandom {...}</code> <code>* CONTENT</code>
<code>\underrandoms {...}</code> <code>* CONTENT</code>
<code>\understrike {...}</code> <code>* CONTENT</code>
<code>\understrikes {...}</code> <code>* CONTENT</code>
<code>\basegrid [...,..^{OPT}...,...]</code> <code>* nx = NUMMER</code> <code> ny = NUMMER</code> <code> dx = NUMMER</code> <code> dy = NUMMER</code> <code> faktor = NUMMER</code> <code> meritko = NUMMER</code> <code> xkrok = NUMMER</code> <code> ykrok = NUMMER</code> <code> offset = DIMENSION</code> <code> xoffset = DIMENSION</code> <code> yoffset = DIMENSION</code> <code> zarovnani = nastred</code> <code> jednotka = cm mm in pc pt bp</code> <code> pismo = STYLE BEFEHL</code> <code> barva = COLOR</code>
<code>\baselinebottom</code>
<code>\baselineleftbox {...}</code> <code>* CONTENT</code>
<code>\baselinemiddlebox {...}</code> <code>* CONTENT</code>
<code>\baselinerrightbox {...}</code> <code>* CONTENT</code>
<code>\bbordermatrix {...}</code> <code>* CONTENT</code>
<code>\bbox {...}</code> <code>* CONTENT</code>
<code>\beforesplitstring ... \at ... \to ...</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 CSNAME</code>
<code>\beforetestandsplitstring ... \at ... \to ...</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 CSNAME</code>
<code>\beginBLOCK [...,*,...] ... \endBLOCK</code> <code>* + - NAME OPT</code>
<code>\beginhbox ... \endhbox</code>
<code>\beginofshapebox ... \endofshapebox</code>
<code>\beginvbox ... \endvbox</code>

<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bezserifu</code>
<code>\bigbodyfont</code>
<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER
<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\bitmapimage [...,\stackrel{1}{...}] {\stackrel{2}{...}}</code> 1 barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMBER y = NUMBER 2 NUMBER
<code>\blap {...}</code> * CONTENT
<code>\bleed [...,\stackrel{1}{...}] {\stackrel{2}{...}}</code> 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockligatures [...,*...]</code> * TEXT
<code>\blocksynctexfile [...,*...]</code> * FILE
<code>\bodyfontenvironmentlist</code>

<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue {...}</code> * NAME
<code>\bordermatrix {...}</code> * CONTENT
<code>\bottombox {...}</code> * CONTENT
<code>\bottomleftbox {...}</code> * CONTENT
<code>\bottomrightbox {...}</code> * CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...} {...}</code> 1 NAME 2 NUMMER
<code>\boxofsize \...¹ ... \...² ... \...³</code> 1 CSNAME 2 DIMENSION 3 CONTENT
<code>\boxreference [...,¹...] \...² {...}</code> 1 REFERENCE 2 CSNAME 3 CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breakhere</code>
<code>\breve {...}</code> * CHARACTER
<code>\bTABLE [...,[*]...,...] ... \eTABLE</code> * inherits: \setupTABLE
<code>\bTABLEbody [...,[*]...,...] ... \eTABLEbody</code> * inherits: \setupTABLE
<code>\bTABLEfoot [...,[*]...,...] ... \eTABLEfoot</code> * inherits: \setupTABLE
<code>\bTABLEhead [...,[*]...,...] ... \eTABLEhead</code> * inherits: \setupTABLE
<code>\bTABLEnext [...,[*]...,...] ... \eTABLEnext</code> * inherits: \setupTABLE

\btC [...,.. [*] ...,...] ... \eTC * inherits: \BT
\btD [...,.. [*] ...,...] ... \eD * nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER akce = REFERENCE inherits: \setupTABLE
\btDs [...] ... \eDs * NAME
\btH [...,.. [*] ...,...] ... \eH * inherits: \BT
\btN [...,.. [*] ...,...] ... \eN * inherits: \BT
\btR [...,.. [*] ...,...] ... \eR * inherits: \setupTABLE
\btRs [...] ... \eRs * NAME
\btX [...,.. [*] ...,...] ... \eX * inherits: \BT
\btY [...,.. [*] ...,...] ... \eY * inherits: \setupTABLE
\btabbreviatedjournal {...} * NAME
\btaddjournal [... ¹] [... ²] 1 NAME 2 NAME
\btalwayscitation [...,.. ¹ ...,...] [... ²] 1 odkaz = REFERENCE ^{OPT} alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
\btalwayscitation [... ¹] [... ²] 1 implicitni category entry ^{OPT} short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE
\btalwayscitation [...,.. ¹ ...,...] [...,.. ² ...,...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE

\btxauthorfield {...}

* initials firstnames vons surnames juniors

\btxdetail {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxdirect {...}

* address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME

\btxdoif {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
2 TRUE

\btxdoifcombiinlistelse {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\btxdoifelse {...} {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
2 TRUE
3 FALSE

\btxdoifelsecombiinlist {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
2 TRUE
3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

1 vzdy dvoustranny
2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
3 TRUE
4 FALSE

\btxdoifelseuservariable {...} {...} {...}

1 KEY
2 TRUE
3 FALSE

\btxdoifnot {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
2 TRUE

\btxdoifsameaspreviouselse {...} {...} {...}

1 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
2 TRUE
3 FALSE

\btxdoifsameaspreviouscheckedelse {...} {...} {...} {...}

1 vzdy dvoustranny
2 address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic
monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
3 TRUE
4 FALSE

\btxdfuservariableelse {...} {...} {...} 1 KEY 2 TRUE 3 FALSE
\bttxexpandedjournal {...} * NAME
\bttxfield {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\bttxfieldname {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\bttxfieldtype {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\bttxfirstofrange {...} * volume pages
\bttxflush {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\bttxflushauthor [...] {...} 1 num normalni normalshort inverted invertedshort 2 autor editor
\bttxflushauthorinverted {...} * autor editor
\bttxflushauthorinvertedshort {...} * autor editor
\bttxflushauthorname {...} * autor editor
\bttxflushauthornormal {...} * autor editor
\bttxflushauthornormalshort {...} * autor editor
\bttxflushsuffix
\bttxfoundname {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\bttxfoundtype {...} * address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series titul opis volume rok yearfiled NAME
\bttxhiddencitation [...] * REFERENCE

```

\btxhybridcite [...1...2...] [...]
1 odkaz = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE

```

```

\btxhybridcite [...1] [...2]
1 implicitni categoryOPT entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

```

```

\btxhybridcite {...}
* REFERENCE

```

```

\btxhybridcite [...1...2...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE

```

```

\btxlistcitation [...1...2...] [...]
1 odkaz = REFERENCEOPT
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 REFERENCE

```

```

\btxlistcitation [...1] [...2]
1 implicitni categoryOPT entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE

```

```

\btxlistcitation [...1...2...] [...2...]
1 odkaz = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred = BEFEHL
  po = BEFEHL
  vlevo = BEFEHL
  vpravo = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE

```

```

\btxloadjournalist [...]
* FILE

```

```

\btxoneorrange {...} {...} {...}
1 volume pages
2 TRUE
3 FALSE

```

```

\btxremapauthor [...1] [...2]
1 TEXT
2 TEXT

```

```

\btxsavejournalist [...]
* FILE

```

$\backslash\text{btxssetup} \{...\}$ * NAME
$\backslash\text{btxsingularorplural} \{.^1.\} \{.^2.\} \{.^3.\}$ 1 editor producer director 2 TRUE 3 FALSE
$\backslash\text{btxsingularplural} \{.^1.\} \{.^2.\} \{.^3.\}$ 1 editor producer director 2 TRUE 3 FALSE
$\backslash\text{btxttextcitation} [,...,.^1,...,] [.^2.]$ 1 odkaz = REFERENCE ^{OPT} alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
$\backslash\text{btxttextcitation} [.^1.] [.^2.]$ 1 implicitni category ^{OPT} entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE
$\backslash\text{btxttextcitation} [,...,.^1,...,] [...,.^2,...,]$ 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE
$\backslash\text{TOOLTIP} [,...,.^1,...,] \{.^2.\} \{.^3.\}$ 1 inherits: \setup ^{OPT} tooltip 2 TEXT 3 TEXT instances: tooltip
$\backslash\text{TOOLTIP} [.^1.] \{.^2.\} \{.^3.\}$ 1 vlevo nast ^{OPT} řed vpravo 2 TEXT 3 TEXT instances: tooltip
$\backslash\text{tooltip} [.^1.] \{.^2.\} \{.^3.\}$ 1 vlevo nast ^{OPT} řed vpravo 2 TEXT 3 TEXT
$\backslash\text{tooltip} [,...,.^1,...,] \{.^2.\} \{.^3.\}$ 1 inherits: \setup ^{OPT} tooltip 2 TEXT 3 TEXT
$\backslash\text{buildmathaccent} \{.^1.\} \{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextaccent} \{.^1.\} \{.^2.\}$ 1 CHARACTER 2 CHARACTER

<code>\buildtextbottomcomma {...}</code> * CHARACTER
<code>\buildtextbottomdot {...}</code> * CHARACTER
<code>\buildtextcedilla {...}</code> * CHARACTER
<code>\buildtextgrave {...}</code> * CHARACTER
<code>\buildtextmacron {...}</code> * CHARACTER
<code>\buildtextognek {...}</code> * CHARACTER
<code>\Caps {...}</code> * TEXT
<code>\Cisla {...}</code> * NUMBER
<code>\CONTEXT</code>
<code>\ConTeXt</code>
<code>\Context</code>
<code>\ConvertConstantAfter \.¹... {..²} {..³}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\ConvertToConstant \.¹... {..²} {..³}</code> 1 CSNAME 2 TEXT 3 TEXT
<code>\camel {...}</code> * TEXT
<code>\catcodetablename</code>
<code>\cbox ...¹ {..²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\centeraligned {...}</code> * CONTENT
<code>\centerbox ...¹ {..²}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\centeredbox ...¹ {..²}</code> 1 TEXT ^{OPT} 2 CONTENT

<code>\centeredlastline</code>
<code>\centerednextbox ¹... {²...}</code> 1 TEXT OPT 2 CONTENT
<code>\centerline {...}</code> * CONTENT
<code>\cernalinka [...,..[*]...,...]</code> * inherits: \nastavceHielinky
<code>\cernelinky [...,..[*]...,...]</code> * inherits: \nastavceHielinky
<code>\cfrac [¹] {²...} {³...}</code> 1 l c r lP ^P l c lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT
<code>\cisla {...}</code> * NUMMER
<code>\cisonadpisu [¹] [²...]</code> 1 ABSCHNITT OPT 2 predchozi aktualni dalsi prvni posledni
<code>\cislrorovnice [...,..[*]...,...]</code> * REFERENCE OPT
<code>\cislostrany</code>
<code>\citation [...,..¹...,...] [²...]</code> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
<code>\citation [¹] [²...]</code> 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE
<code>\citation {...}</code> * REFERENCE
<code>\citation [...,..¹...,...] [...,..²...,...]</code> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE

`\cite [...]{...} [...]`

```
1 odkaz      OPT= REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
               authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\cite [...]{...}`

```
1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\cite {...}`

* REFERENCE

`\cite [...]{...} [...]{...}`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
               authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\clap {...}`

* CONTENT

`\classfont {...}{...}`

```
1 NAME
2 FONT
```

`\cldcommand {...}`

* BEFEHL

`\cldcontext {...}`

* BEFEHL

`\cldloadfile {...}`

* FILE

`\cldprocessfile {...}`

* FILE

`\collect {...}`

* CONTENT

`\collectedtext [...]{...} [...]{...} {...}{...}`

```
1 inherits: \setupcollectif
2 pismo     = STYLE BEFEHL
  barva     = COLOR
  inherits: \nastavoramovani
3 TEXT
4 CONTENT
```

`\collectexpanded {...}`

* CONTENT

`\colorcomponents {...}`

* COLOR

$\backslash\text{colored} [\dots, \overset{1}{=}\dots, \dots] \{\overset{2}{\dots}\}$ 1 inherits: $\backslash\text{definujbarvu}$ 2 CONTENT
$\backslash\text{colored} [\overset{1}{\dots}] \{\overset{2}{\dots}\}$ 1 COLOR 2 CONTENT
$\backslash\text{coloronly} [\overset{1}{\dots}] \{\overset{2}{\dots}\}$ 1 COLOR 2 CONTENT
$\backslash\text{columnbreak} [\dots, \overset{OPT}{*}, \dots]$ * ano ne nastaveni $\overset{OPT}{\text{lokalne}}$ sila prvni posledni NUMBER NAME
$\backslash\text{combinepages} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{=}\dots, \dots]$ 1 FILE 2 alternativa = a b c horizontalne vertikalne n = NUMBER nx = NUMBER ny = NUMBER start = NUMBER stop = NUMBER vzdalenost = DIMENSION vrsek = BEFEHL spodek = BEFEHL vlevo = BEFEHL vpravo = BEFEHL pred = BEFEHL po = BEFEHL mezi = BEFEHL ramecek = zap vyp pozadi = popredi barevne NAME barvapozadi = COLOR
$\backslash\text{commalistelement}$
$\backslash\text{commalistsentence} [\dots, \overset{1}{\dots}] [\dots, \overset{2}{\dots}, \dots]$ 1 TEXT 2 TEXT
$\backslash\text{commalistsize}$
$\backslash\text{comparedimension} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 DIMENSION 2 DIMENSION
$\backslash\text{comparedimensioneps} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 DIMENSION 2 DIMENSION
$\backslash\text{completebtxrendering} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{=}\dots, \dots]$ 1 NAME 2 inherits: $\backslash\text{setupbtxrendering}$
$\backslash\text{uplnyCOMBINEDLIST} [\dots, \dots, \overset{*}{=}\dots, \dots]$ * inherits: $\backslash\text{nastavseznam}$ instances: content
$\backslash\text{uplnycontent} [\dots, \dots, \overset{*}{=}\dots, \dots]$ * inherits: $\backslash\text{nastavseznam}$
$\backslash\text{completelist} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{=}\dots, \dots]$ 1 LISTE 2 inherits: $\backslash\text{nastavseznam}$

$\backslash\text{completelistofFLOATS}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavseznam <small>OPT</small> instances: chemicals figures tables intermezzi graphics
$\backslash\text{completelistoffigures}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavseznam <small>OPT</small>
$\backslash\text{completelistofgraphics}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavseznam <small>OPT</small>
$\backslash\text{completelistofchemicals}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavseznam <small>OPT</small>
$\backslash\text{completelistofintermezzi}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavseznam <small>OPT</small>
$\backslash\text{completelistoftables}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavseznam <small>OPT</small>
$\backslash\text{completelistofpublications}$ [¹ ...] [..., ..., $\overset{2}{=}$..., ...] 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupbt rendering
$\backslash\text{completelistofsorts}$ [¹ ...] [..., ..., $\overset{2}{=}$..., ...] 1 SINGULAR <small>OPT</small> 2 inherits: \nastavtrideni
$\backslash\text{completelistofSORTS}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavtrideni <small>OPT</small> instances: logos
$\backslash\text{completelistoflogos}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavtrideni <small>OPT</small>
$\backslash\text{completelistofsynonyms}$ [¹ ...] [..., ..., $\overset{2}{=}$..., ...] 1 SINGULAR <small>OPT</small> 2 inherits: \nastavsynonyma
$\backslash\text{completelistofSYNONYMS}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavsynonyma <small>OPT</small> instances: abbreviations
$\backslash\text{completelistofabbreviations}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavsynonyma <small>OPT</small>
$\backslash\text{completepagenumber}$
$\backslash\text{completeregister}$ [¹ ...] [..., ..., $\overset{2}{=}$..., ...] 1 NAME <small>OPT</small> 2 inherits: \nastavrejstrik
$\backslash\text{uplnyREGISTER}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavrejstrik <small>OPT</small> instances: index
$\backslash\text{uplnyindex}$ [..., ..., $\overset{*}{=}$..., ...] * inherits: \nastavrejstrik <small>OPT</small>
$\backslash\text{complexorsimple}$ *.. * CSNAME

\complexorsimpleempty \... * CSNAME
\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple {...} * TEXT CSNAME
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen \... * CSNAME
\constantdimenargument \... * CSNAME
\constantemptyargument \... * CSNAME
\constantnumber \... * CSNAME
\constantnumberargument \... * CSNAME
\contentreference [... ¹ ,...] [... ² ,... ² ,...] {... ³ } 1 REFERENCE 2 inherits: \nastavoramovani 3 CONTENT OPT
\continuednumber {...} * NUMMER
\continueifinputfile {...} * FILE
\convertargument ¹ ... \to \ ² ... 1 TEXT 2 CSNAME
\convertcommand \ ¹ ... \to \ ² ... 1 CSNAME 2 CSNAME
\convertedcounter [¹ ...] [... ² ,... ² ,...] 1 NAME 2 inherits: \setupcounter OPT
\converteddimen {... ¹ } {... ² } 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc

$\backslash\text{convertedsubcounter}$ [¹ ...] [² ...] [³ ...,... ² ...,...] 1 NAME 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse 3 inherits: \setupcounter
$\backslash\text{convertmonth}$ {...} * NUMBER
$\backslash\text{convertvalue}$.. \to \^2. 1 NAME 2 CSNAME
$\backslash\text{convertvboxtohbox}$
$\backslash\text{copyboxfromcache}$ { ¹ ...} { ² ...} ³ . 1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
$\backslash\text{copyLABELtext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash\text{copybtxlabeltext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyheadtext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copylabeltext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copymathlabeltext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyoperatortext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyprefixtext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copysuffixtext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyunittext}$ [¹ ...] [² ...,... ² ...,...] 1 SPRACHE 2 KEY = KEY

$\backslash\text{coppages}$ [¹ ...] [² ... _{OPT} ...] [³ ... _{OPT} ...] 1 FILE 2 znaceni = zap vyp offset = DIMENSION n = NUMMER 3 inherits: \setuexternalfigure
$\backslash\text{copyparameters}$ [¹] [²] [³ ...] 1 TEXT 2 TEXT 3 KEY
$\backslash\text{copyposition}$ { ¹ .} { ² .} 1 NAME 2 NAME
$\backslash\text{countersubs}$ [¹] [² .] 1 NAME 2 NUMBER
$\backslash\text{counttoken}$ ¹ ... \in ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ ¹ ... \to \ ² ... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ { [*] .} * CONTENT
$\backslash\text{crampedclap}$ { [*] .} * CONTENT
$\backslash\text{crampedllap}$ { [*] .} * CONTENT
$\backslash\text{crampedrlap}$ { [*] .} * CONTENT
$\backslash\text{ctop}$ ¹ ... { ² .} 1 TEXT _{OPT} 2 CONTENT
$\backslash\text{ctxcommand}$ { [*] .} * BEFEHL
$\backslash\text{ctxdirectcommand}$ { [*] .} * BEFEHL
$\backslash\text{ctxdirectlua}$ { [*] .} * BEFEHL
$\backslash\text{ctxfunction}$ { [*] .} * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$

\ctxlatecommand {...} * BEFEHL
\ctxlatelua {...} * BEFEHL
\ctxloadluafile {...} * FILE
\ctxlua {...} * BEFEHL
\ctxluabuffer [...] * BUFFER OPT
\ctxluacode {...} * BEFEHL
\ctxreport {...} * BEFEHL
\ctxsprint {...} * BEFEHL
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentPOPISEK [... ¹ ...] {... ² } 1 REFERENCE OPT OPT 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber

\currentlistentryreferenceattribute {...} * cislo text cislostranky vse
\currentlistentrytitle
\currentlistentrytitlrendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY
\currentresponses
\currenttime [...,*,...] * h m TEXT OPT
\currentvalue
\currentxtablecolumn
\currentxtablerow
\d {...} * CHARACTER
\dalsipodstranka
\datasetvariable {...} {...} {...} 1 NAME 2 NAME NUMMER 3 KEY realpage
\datum [...,* ¹ ...,* ² ...] [...,* ² ...] 1 d = NUMMER OPT OPT m = NUMMER y = NUMMER 2 inherits: \aktualnidatum
\dayoftheweek {...} {...} {...} 1 NUMMER 2 NUMMER 3 NUMMER


```

\defineanchor [...] [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupplayer
4 inherits: \setupplayerinherits: \nastavoramovani

```

```

\defineattachment [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupattachment

```

```

\defineattribute [...] [...]
1 NAME
2 lokalne globalne public private

```

```

\definebackground [...] [...] [...]
1 NAME
2 NAME
3 inherits: \nastavpozadi

```

```

\definebar [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupbar

```

```

\definebodyfontswitch [...] [...]
1 NAME
2 inherits: \nastavzakladnifont

```

```

\definebreakpoint [...] [...] [...]
1 NAME
2 CHARACTER
3 typ = 1 2 3 4 5
nvlevo = NUMMER
nvpravo = NUMMER
vlevo = BEFEHL
stredni = BEFEHL
vpravo = BEFEHL
range = ano ne
language = SPRACHE

```

```

\definebreakpoints [...]
* NAME

```

```

\definebtx [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupbtx

```

```

\definebtxdataset [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupbtxdataset

```

```

\definebtxregister [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupbtxregister

```

```

\definebtxrendering [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupbtxrendering

```

```

\definebutton [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupbutton

```

```
\definecapitals [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavkapitalky
```

```
\definecollector [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcollector
```

```
\definecolumnbreak [...] [...]
1 NAME
2 ano ne nastaveni lokalne sila prvni posledni NUMMER
```

```
\definecombination [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcombination
```

```
\definecomment [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \nastavkomentar
```

```
\definecomplexorsimple \*...
* CSNAME
```

```
\definecomplexorsimpleempty \*...
* CSNAME
```

```
\definecomplexorsimpleempty {...}
* TEXT CSNAME
```

```
\definecomplexorsimple {...}
* TEXT CSNAME
```

```
\defineconversionset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\definecounter [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcounter
```

```
\definedataset [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupdataset
```

```
\definedelimitedtext [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupdelimitedtext
```

```
\definedfont [...]
* FONT OPT
```

```
\defineeffect [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupeffect
```



```
\defineexpandable [.1.] \.2. {.3.}
1  NUMBER
2  CSNAME
3  CONTENT
```

```
\defineexternalfigure [...] [...2.] [...,3...,...]
```

1 NAME OPT OPT

2 NAME

3 inherits: \setupexternalfigure

```

\definefallbackfamily [^1] [^2] [^3] [^4] [^5] [^6] [^7] [^8] [^9] [^10] [^11] [^12] [^13] [^14] [^15] [^16] [^17] [^18] [^19] [^20] [^21] [^22] [^23] [^24] [^25] [^26] [^27] [^28] [^29] [^30] [^31] [^32] [^33] [^34] [^35] [^36] [^37] [^38] [^39] [^40] [^41] [^42] [^43] [^44] [^45] [^46] [^47] [^48] [^49] [^50] [^51] [^52] [^53] [^54] [^55] [^56] [^57] [^58] [^59] [^60] [^61] [^62] [^63] [^64] [^65] [^66] [^67] [^68] [^69] [^70] [^71] [^72] [^73] [^74] [^75] [^76] [^77] [^78] [^79] [^80] [^81] [^82] [^83] [^84] [^85] [^86] [^87] [^88] [^89] [^90] [^91] [^92] [^93] [^94] [^95] [^96] [^97] [^98] [^99] [^100] [^101] [^102] [^103] [^104] [^105] [^106] [^107] [^108] [^109] [^110] [^111] [^112] [^113] [^114] [^115] [^116] [^117] [^118] [^119] [^120] [^121] [^122] [^123] [^124] [^125] [^126] [^127] [^128] [^129] [^130] [^131] [^132] [^133] [^134] [^135] [^136] [^137] [^138] [^139] [^140] [^141] [^142] [^143] [^144] [^145] [^146] [^147] [^148] [^149] [^150] [^151] [^152] [^153] [^154] [^155] [^156] [^157] [^158] [^159] [^160] [^161] [^162] [^163] [^164] [^165] [^166] [^167] [^168] [^169] [^170] [^171] [^172] [^173] [^174] [^175] [^176] [^177] [^178] [^179] [^180] [^181] [^182] [^183] [^184] [^185] [^186] [^187] [^188] [^189] [^190] [^191] [^192] [^193] [^194] [^195] [^196] [^197] [^198] [^199] [^200] [^201] [^202] [^203] [^204] [^205] [^206] [^207] [^208] [^209] [^210] [^211] [^212] [^213] [^214] [^215] [^216] [^217] [^218] [^219] [^220] [^221] [^222] [^223] [^224] [^225] [^226] [^227] [^228] [^229] [^230] [^231] [^232] [^233] [^234] [^235] [^236] [^237] [^238] [^239] [^240] [^241] [^242] [^243] [^244] [^245] [^246] [^247] [^248] [^249] [^250] [^251] [^252] [^253] [^254] [^255] [^256] [^257] [^258] [^259] [^260] [^261] [^262] [^263] [^264] [^265] [^266] [^267] [^268] [^269] [^270] [^271] [^272] [^273] [^274] [^275] [^276] [^277] [^278] [^279] [^280] [^281] [^282] [^283] [^284] [^285] [^286] [^287] [^288] [^289] [^290] [^291] [^292] [^293] [^294] [^295] [^296] [^297] [^298] [^299] [^300] [^301] [^302] [^303] [^304] [^305] [^306] [^307] [^308] [^309] [^310] [^311] [^312] [^313] [^314] [^315] [^316] [^317] [^318] [^319] [^320] [^321] [^322] [^323] [^324] [^325] [^326] [^327] [^328] [^329] [^330] [^331] [^332] [^333] [^334] [^335] [^336] [^337] [^338] [^339] [^340] [^341] [^342] [^343] [^344] [^345] [^346] [^347] [^348] [^349] [^350] [^351] [^352] [^353] [^354] [^355] [^356] [^357] [^358] [^359] [^360] [^361] [^362] [^363] [^364] [^365] [^366] [^367] [^368] [^369] [^370] [^371] [^372] [^373] [^374] [^375] [^376] [^377] [^378] [^379] [^380] [^381] [^382] [^383] [^384] [^385] [^386] [^387] [^388] [^389] [^390] [^391] [^392] [^393] [^394] [^395] [^396] [^397] [^398] [^399] [^400] [^401] [^402] [^403] [^404] [^405] [^406] [^407] [^408] [^409] [^410] [^411] [^412] [^413] [^414] [^415] [^416] [^417] [^418] [^419] [^420] [^421] [^422] [^423] [^424] [^425] [^426] [^427] [^428] [^429] [^430] [^431] [^432] [^433] [^434] [^435] [^436] [^437] [^438] [^439] [^440] [^441] [^442] [^443] [^444] [^445] [^446] [^447] [^448] [^449] [^450] [^451] [^452] [^453] [^454] [^455] [^456] [^457] [^458] [^459] [^460] [^461] [^462] [^463] [^464] [^465] [^466] [^467] [^468] [^469] [^470] [^471] [^472] [^473] [^474] [^475] [^476] [^477] [^478] [^479] [^480] [^481] [^482] [^483] [^484] [^485] [^486] [^487] [^488] [^489] [^490] [^491] [^492] [^493] [^494] [^495] [^496] [^497] [^498] [^499] [^500] [^501] [^502] [^503] [^504] [^505] [^506] [^507] [^508] [^509] [^510] [^511] [^512] [^513] [^514] [^515] [^516] [^517] [^518] [^519] [^520] [^521] [^522] [^523] [^524] [^525] [^526] [^527] [^528] [^529] [^530] [^531] [^532] [^533] [^534] [^535] [^536] [^537] [^538] [^539] [^540] [^541] [^542] [^543] [^544] [^545] [^546] [^547] [^548] [^549] [^550] [^551] [^552] [^553] [^554] [^555] [^556] [^557] [^558] [^559] [^560] [^561] [^562] [^563] [^564] [^565] [^566] [^567] [^568] [^569] [^570] [^571] [^572] [^573] [^574] [^575] [^576] [^577] [^578] [^579] [^580] [^581] [^582] [^583] [^584] [^585] [^586] [^587] [^588] [^589] [^590] [^591] [^592] [^593] [^594] [^595] [^596] [^597] [^598] [^599] [^600] [^601] [^602] [^603] [^604] [^605] [^606] [^607] [^608] [^609] [^610] [^611] [^612] [^613] [^614] [^615] [^616] [^617] [^618] [^619] [^620] [^621] [^622] [^623] [^624] [^625] [^626] [^627] [^628] [^629] [^630] [^631] [^632] [^633] [^634] [^635] [^636] [^637] [^638] [^639] [^640] [^641] [^642] [^643] [^644] [^645] [^646] [^647] [^648] [^649] [^650] [^651] [^652] [^653] [^654] [^655] [^656] [^657] [^658] [^659] [^660] [^661] [^662] [^663] [^664] [^665] [^666] [^667] [^668] [^669] [^670] [^671] [^672] [^673] [^674] [^675] [^676] [^677] [^678] [^679] [^680] [^681] [^682] [^683] [^684] [^685] [^686] [^687] [^688] [^689] [^690] [^691] [^692] [^693] [^694] [^695] [^696] [^697] [^698] [^699] [^7
```

```
\definefallbackfamily [^1] [^2] [^3] [^4,...]
1 NAME OPT
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojepis opis mono rukopisne kaligraficke math matematika
3 FONT
4 NAME
```

```
\definefieldbody [...] [..2] [...,3..4,...]
```

1 NAME OPT OPT

2 NAME

3 inherits: \setupfieldbody

```
\definefieldbodyset [...] [...1,...2,...]
1  NAME
2  NAME
```

```
\definefieldcategory [..1] [..2] [..3..4..5..6..7..8..9..10..11..12..13..14..15..16..17..18..19..20..21..22..23..24..25..26..27..28..29..30..31..32..33..34..35..36..37..38..39..40..41..42..43..44..45..46..47..48..49..50..51..52..53..54..55..56..57..58..59..60..61..62..63..64..65..66..67..68..69..70..71..72..73..74..75..76..77..78..79..80..81..82..83..84..85..86..87..88..89..90..91..92..93..94..95..96..97..98..99..100..101..102..103..104..105..106..107..108..109..110..111..112..113..114..115..116..117..118..119..120..121..122..123..124..125..126..127..128..129..130..131..132..133..134..135..136..137..138..139..140..141..142..143..144..145..146..147..148..149..150..151..152..153..154..155..156..157..158..159..160..161..162..163..164..165..166..167..168..169..170..171..172..173..174..175..176..177..178..179..180..181..182..183..184..185..186..187..188..189..190..191..192..193..194..195..196..197..198..199..200..201..202..203..204..205..206..207..208..209..210..211..212..213..214..215..216..217..218..219..220..221..222..223..224..225..226..227..228..229..230..231..232..233..234..235..236..237..238..239..240..241..242..243..244..245..246..247..248..249..250..251..252..253..254..255..256..257..258..259..260..261..262..263..264..265..266..267..268..269..270..271..272..273..274..275..276..277..278..279..280..281..282..283..284..285..286..287..288..289..290..291..292..293..294..295..296..297..298..299..300..301..302..303..304..305..306..307..308..309..310..311..312..313..314..315..316..317..318..319..320..321..322..323..324..325..326..327..328..329..330..331..332..333..334..335..336..337..338..339..340..341..342..343..344..345..346..347..348..349..350..351..352..353..354..355..356..357..358..359..360..361..362..363..364..365..366..367..368..369..370..371..372..373..374..375..376..377..378..379..380..381..382..383..384..385..386..387..388..389..390..391..392..393..394..395..396..397..398..399..400..401..402..403..404..405..406..407..408..409..410..411..412..413..414..415..416..417..418..419..420..421..422..423..424..425..426..427..428..429..430..431..432..433..434..435..436..437..438..439..440..441..442..443..444..445..446..447..448..449..450..451..452..453..454..455..456..457..458..459..460..461..462..463..464..465..466..
```

```
\definefileconstant {...} {...}
1 NAME
2 NAME
```

```
\definefilefallback [...] [...]
1  NAME
2  FILE
```

```
\definefilesynonym [...] [...]
```

1 NAME

2 FILE

```
\definefiller [...] [^2] [...,^3=...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfiller
```

```

\definefirstline [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfirstline

```

```

\definefittingpage [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfittingpage

```

```

\definefontalternative [...]
* NAME

```

```

\definefontfallback [...] [...] [...] [...]
1 NAME
2 FONT NAME
3 NAME NUMBER
4 rscale = NUMBER
  sila = ano ne
  check = ano ne
  offset = NUMBER NAME
  features = NAME

```

```

\definefontfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
3 FONT
4 rscale = NUMBER
  designsizes = implicitni auto
  goodies = FILE
  features = NAME
  tf = TEXT
  bf = TEXT
  it = TEXT
  sl = TEXT
  bi = TEXT
  bs = TEXT
  sc = TEXT

```

```

\definefontfamilypreset [...] [...]
1 NAME
2 inherits: \definefontfamily

```

```

\definefontfamilypreset [...] [...]
1 NAME
2 NAME

```

```

\definefontfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg antikva serif pravidelne bezserifu sans podpora strojopis opis mono rukopisne kaligraficke math matematika
3 FONT
4 NAME

```

```

\definefontfeature [...] [...] [...] [...]
1  NAME
2  NAME
3  language      = NAME
    script       = NAME auto
    mode         = node base auto zadny
    liga         = ano ne
    kern         = ano ne
    extrakerns   = ano ne
    tlig         = ano ne
    trep         = ano ne
    missing      = ano ne
    dummies      = ano ne
    analyze      = ano ne
    unicoding    = ano ne
    expanzen     = NAME
    protrusion   = NAME
    nostackmath  = ano ne
    realdimensions = ano ne
    itlc         = ano ne
    textitalics  = ano ne
    mathitalics  = ano ne
    slant        = NUMMER
    extend       = NUMMER
    dimensions   = NUMMER
    boundingbox  = ano ne pozadi ramecek prazdne COLOR
    compose      = ano ne
    char-ligatures = ano ne
    compat-ligatures = ano ne
    goodies      = FILE
    extrafeatures = ano ne
    featureset   = NAME
    colorscheme  = NAME
    postprocessor = NAME
    mathdimensions = NAME
    keepligatures = ano ne auto
    devanagari   = ano ne
    features     = ano ne
    tcom         = ano ne
    anum        = ano ne
    mathsize     = ano ne
    decomposehangul = ano ne
    mathalternatives = ano ne
    mathgaps     = ano ne
    checkmarks   = ano ne
    NAME         = ano ne
    mathnolimitsmode = NUMMER
    blockligatures = ano ne

```

```

\definefontfile [...] [...] [...]
1  NAME
2  FILE
3  features      = NAME
    fallbacks    = NAME
    goodies      = NAME
    designsize   = auto implicitni

```

```

\definefontsize [...]
*  NAME

```

```

\definefontsolution [...] [...] [...]
1  NAME
2  NAME
3  inherits: \setupfontsolution

```

```

\defineformula [...] [...] [...]
1  NAME
2  NAME
3  inherits: \setupformula

```

```

\defineformulaalternative [...] [...] [...]
1  NAME
2  CSNAME
3  CSNAME

```

<pre> \defineformulaframed [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupformulaframed </pre>
<pre> \defineframedcontent [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupframedcontent </pre>
<pre> \defineframedtable [...] [...] 1 NAME 2 NAME </pre>
<pre> \definefrozenfont [...] [...] 1 NAME 2 FONT </pre>
<pre> \defineglobalcolor [...] [...] 1 NAME 2 inherits: \definujbarvu </pre>
<pre> \defineglobalcolor [...] [...] 1 NAME 2 COLOR </pre>
<pre> \definegraphicstypesynonym [...] [...] 1 NAME 2 NAME </pre>
<pre> \definegridsnapping [...] [...] 1 NAME 2 lokalne globalne noheight nodepth box max min zadny radek pulradku prvni posledni minvyska maxheight mindepth maxdepth vrsek spodek strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER </pre>
<pre> \defineheadalternative [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupheadalternative </pre>
<pre> \definehelp [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuphelp </pre>
<pre> \definehigh [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuphigh </pre>
<pre> \definehighlight [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuphighlight </pre>
<pre> \definehspace [...] [...] [...] 1 NAME 2 NAME 3 DIMENSION </pre>

`\definehyphenationfeatures [.1.] [...,2...]`

```
1 NAME
2 characters      = TEXT
  hyphens         = ano vse TEXT
  joiners         = ano vse TEXT
  rightwords      = NUMMER
  hyphenmin       = NUMMER
  lefthyphenmin   = NUMMER
  righthyphenmin  = NUMMER
  lefthyphenchar  = NUMMER
  righthyphenchar = NUMMER
  alternativa     = original tex hyphenate expanded traditional zadny
  pravahrana      = tex
  rightchars      = slovo NUMMER
```

`\definecharacterkerning [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \setupcharacterkerning
```

`\definecharacterspacing [.*]`

```
* NAME
```

`\definechemical [.1.] {.2.}`

```
1 NAME
2 CONTENT
```

`\definechemicals [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \setupchemical
```

`\definechemicalsymbol [.1.] [.2.]`

```
1 NAME
2 TEXT
```

`\defineindentedtext [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \setupindentedtext
```

`\defineindenting [.1.] [...,2...]`

```
1 NAME
2 [-+]male [-+]stredni [-+]velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION
```

`\defineinitial [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \setupinitial
```

`\defineinsertion [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \setupinsertion
```

`\defineinteraction [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \nastavinterakci
```

`\defineinteractionbar [.1.] [.2.] [...,3...]`

```
1 NAME
2 NAME
3 inherits: \nastavinterakcnilistu
```

`\defineinterfaceconstant {.1.} {.2.}`

```
1 NAME
2 NAME
```

<pre> \defineinterfaceelement {...} {...} 1 NAME 2 NAME </pre>
<pre> \defineinterfacevariable {...} {...} 1 NAME 2 NAME </pre>
<pre> \defineinterlinespace [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavmeziradkovoumezeru </pre>
<pre> \defineintermediatecolor [...] [...] [...] [...] 1 NAME 2 COLOR NUMBER 3 a = NUMBER t = NUMBER </pre>
<pre> \defineitemgroup [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupitemgroup </pre>
<pre> \defineitems [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavpolozky </pre>
<pre> \definelabelclass [...] [...] 1 NAME 2 NUMBER </pre>
<pre> \definelayer [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...] [...] [...] 1 NAME 2 inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...] 1 NAME 2 NAME </pre>
<pre> \definelayout [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavvzhled </pre>
<pre> \definelinefiller [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuplinefiller </pre>
<pre> \definelinenote [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuplinenote </pre>
<pre> \definelinenumbers [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavcislovaniradku </pre>

`\definelines [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \nastavradky

`\definelistalternative [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setuplistalternative

`\definelistextra [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setuplistextra

`\definelow [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setuplow

`\definelowhigh [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setuplowhigh

`\definelowmidhigh [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setuplowmidhigh

`\defineMPinstance [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setupMPinstance

`\definemarginblock [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setupmarginblock

`\definemargindata [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setupmargindata

`\definemarker [...]`

* NAME

`\definemathaccent ...1 ...2`

1 NAME
2 CHARACTER

`\definemathalignment [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setupmathalignment

`\definemathcases [...]1 [...]2 [...]3...`

1 NAME
2 NAME
3 inherits: \setupmathcases

`\definemathcommand [...]1 [...]2 [...]3 {...}4`

1 NAME
2 ord op bin rel open close punct alpha uvnitr nothing limop noloop box
3 jedna dve
4 BEFEHL \...#1 \...#1##2

```
\definemathdouble [...]1 [...]2 [...]3 [...]4
1 obe vfenced NAME
2 NAME
3 NUMMER
4 NUMMER
```

```
\definemathdoubleextensible [...]1 [...]2 [...]3 [...]4
1 obe vfenced OPT
2 NAME
3 NUMMER
4 NUMMER
```

```
\definemathtics [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathtics
```

```
\definemathextensible [...]1 [...]2 [...]3
1 reverse mathematika text chemistry OPT
2 NAME
3 NUMMER
```

```
\definemathfence [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathfence
```

```
\definemathfraction [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathfraction
```

```
\definemathframed [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathframed
```

```
\definemathmatrix [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathmatrix
```

```
\definemathornament [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathornament
```

```
\definemathover [...]1 [...]2 [...]3
1 vrsek vfenced NAME
2 NAME
3 NUMMER
```

```
\definemathoverextensible [...]1 [...]2 [...]3
1 vrsek vfenced OPT
2 NAME
3 NUMMER
```

```
\definemathovertextextensible [...]1 [...]2 [...]3
1 bothtext OPT
2 NAME
3 NUMMER
```

```
\definemathradical [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathradical
```



```
\definemathstackers [...1] [...2] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathstackers
```

```
\definemathstyle [...1] [...,2,...]
1 NAME
2 obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
```

```
\definemathtriplet [...1] [...2] [...3]
1 NAME OPT OPT
2 NAME
3 TEXT
```

```
\definemathunder [...1] [...2] [...3]
1 spodek vfenced NAME
2 NAME
3 NUMMER
```

```
\definemathunderextensible [...1] [...2] [...3]
1 spodek vfenced OPT
2 NAME
3 NUMMER
```

```
\definemathundertextextensible [...1] [...2] [...3]
1 bothtext OPT
2 NAME
3 NUMMER
```

```
\definemathunstacked [...1] [...2] [...3]
1 siroce OPT
2 NAME
3 NUMMER
```

```
\definemeasure [...1] [...2]
1 NAME
2 DIMENSION
```

```
\definemessageconstant {...}
* NAME
```

```
\definemixedcolumns [...1] [...2] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmixedcolumns
```

```
\definemode [...,1,...] [...2]
1 NAME OPT
2 ano ne drzet
```

```
\definemultitonecolor [...1] [...,2...,...] [...,3...,...] [...,4...,...]
1 NAME OPT
2 COLOR = NUMMER
3 inherits: \definujbarvu
4 inherits: \definespotcolor
```

```
\definenamecolor [...1] [...,2...,...]
1 NAME
2 inherits: \definujbarvu
```

```
\definenamecolor [...1] [...2]
1 NAME
2 COLOR
```

\definenamespace [¹...] [²...²...]

```
1 NAME
2 jmeno = TEXT
  parent = TEXT
  pismeno = ano ne
  prikaz = ano ne seznam
  setup = ano ne seznam
  set = ano ne seznam
  ramecek = ano ne
```

\definennarrower [¹...] [²...] [³...³...]

```
1 NAME
2 NAME
3 inherits: \nastavzuzeni
```

\definernote [¹...] [²...] [³...³...]

```
1 NAME
2 NAME
3 inherits: \setupnote
```

\defineornament [¹...] [²...²...] [³...³...]

```
1 NAME
2 alternativa = a b
  inherits: \setupcollector
3 pismeno = STYLE BEFEHL
  barva = COLOR
  inherits: \nastavoramovani
```

\defineornament [¹...] [²...²...] [³...³...]

```
1 NAME
2 alternativa = a b
  inherits: \setupplayer
3 inherits: \setuplayeredtext
```

\defineoutputroutine [¹...] [²...] [³...³...]

```
1 NAME
2 NAME
3 inherits: \setupoutputroutine
```

\defineoutputroutinecommand [...]*...]

```
* KEY
```

\definepage [¹...] [²...]

```
1 NAME
2 REFERENCE
```

\definepagebreak [¹...] [²...²...]

```
1 NAME
2 prazdne zahlevi upati dummy ramecek NUMMER +NUMMER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita
  vlevo vpravo sude liche ctyrnasobny posledni poslednistrana start stop
```

\definepagegrid [¹...] [²...] [³...³...]

```
1 NAME
2 NAME
3 inherits: \setuppagegrid
```

\definepagegridarea [¹...] [²...] [³...³...]

```
1 NAME
2 NAME
3 inherits: \setuppagegridarea
```

\definepagegridspan [¹...] [²...] [³...³...]

```
1 NAME
2 NAME
3 inherits: \setuppagegridspan
```

<pre> \definepagechecker [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagechecker </pre>
<pre> \definepageinjection [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjection </pre>
<pre> \definepageinjectionalternative [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppageinjectionalternative </pre>
<pre> \definepageshift [...] [...] [...] 1 NAME 2 horizontalne vertikalne 3 DIMENSION </pre>
<pre> \definepagestate [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppagestate </pre>
<pre> \definepairedbox [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuppairedbox </pre>
<pre> \defineparagraph [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupparagraph </pre>
<pre> \defineparallel [...] [...] 1 NAME 2 NAME </pre>
<pre> \defineparbuilder [...] * NAME </pre>
<pre> \defineplacement [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupplacement </pre>
<pre> \definepositioning [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavumistovani </pre>
<pre> \defineprefixset [...] [...] [...] 1 NAME SECTIONBLOCK:NAME 2 ABSCHNITT 3 ABSCHNITT </pre>
<pre> \defineprocesscolor [...] [...] [...] 1 NAME 2 COLOR 3 inherits: \definujbarvu </pre>
<pre> \defineprocessor [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupprocessor </pre>

<pre> \definepushbutton [¹...] [²..._{OPT}...] 1 NAME 2 inherits: \setupfieldcontentframed </pre>
<pre> \definepushsymbol [¹...] [²...] 1 NAME 2 n r d </pre>
<pre> \definerenderingwindow [¹...] [²...] [³..._{OPT}...] 1 NAME 2 NAME 3 inherits: \setuprenderingwindow </pre>
<pre> \defineresetset [¹...] [²..._{OPT}] [³...] 1 NAME SECTIONBLOCK:NAME 2 NUMMER 3 NUMMER </pre>
<pre> \definescale [¹...] [²...] [³..._{OPT}...] 1 NAME 2 NAME 3 inherits: \setupscale </pre>
<pre> \definescript [¹...] [²...] [³..._{OPT}...] 1 NAME 2 NAME 3 inherits: \setupscript </pre>
<pre> \definesectionlevels [¹...] [²..._{OPT}] 1 NAME 2 ABSCHNITT </pre>
<pre> \defineselector [¹...] [²..._{OPT}...] 1 NAME 2 inherits: \setupselector </pre>
<pre> \defineseparatorset [¹...] [²..._{OPT}] [³...] 1 NAME SECTIONBLOCK:NAME 2 BEFEHL PROCESSOR->BEFEHL 3 BEFEHL PROCESSOR->BEFEHL </pre>
<pre> \defineshift [¹...] [²...] [³..._{OPT}...] 1 NAME 2 NAME 3 inherits: \setupshift </pre>
<pre> \definesidebar [¹...] [²...] [³..._{OPT}...] 1 NAME 2 NAME 3 inherits: \setupsidebar </pre>
<pre> \definesort [¹...] [²...] [³...] {⁴...} 1 ano ne 2 SINGULAR 3 NAME 4 CONTENT </pre>
<pre> \definespotcolor [¹...] [²...] [³..._{OPT}...] 1 NAME 2 COLOR 3 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER e = TEXT p = NUMMER </pre>

<pre> \definestyleinstance [...] [...] [...] [...] 1 NAME 2 rm ss tt mm hw cg 3 tf bf it sl bi bs sc 4 BEFEHL </pre>
<pre> \definesubformula [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupsbformula </pre>
<pre> \definesynonym [...] [...] [...] [...] 1 ano ne 2 SINGULAR 3 NAME 4 TEXT 5 CONTENT </pre>
<pre> \definesystemattribute [...] [...] 1 NAME 2 lokalne globalne public private </pre>
<pre> \definesystemconstant {...} * NAME </pre>
<pre> \definesystemvariable {...} * NAME </pre>
<pre> \defineTABLEsetup [...] [...] 1 NAME 2 inherits: \setupTABLE </pre>
<pre> \definetabulation [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 a = NUMMER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation barevne luminosity t = NUMMER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NAME </pre>

<pre> \definetwopasslist {.*} * NAME </pre>
<pre> \definetype [...] [...] [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavtype </pre>
<pre> \definetypeface [...] [...] [...] [...] [...] [...] [...] 1 NAME 2 rm ss tt mm hw cg 3 serif sans mono math handwriting calligraphy 4 NAME 5 implicitni dtp 6 rscale = auto NUMMER features = NAME fallbacks = NAME goodies = NAME designsize = auto implicitni smer = obe </pre>
<pre> \definetypescriptprefix [...] [...] 1 NAME 2 TEXT </pre>
<pre> \definetypescriptsynonym [...] [...] 1 NAME 2 TEXT </pre>
<pre> \definetypesetting [...] [...] [...] 1 NAME OPT OPT 2 TEXT 3 inherits: \setuexternalfigure </pre>
<pre> \defineunit [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupunit </pre>
<pre> \defineviewerlayer [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupviewerlayer </pre>
<pre> \definevspace [...] [...] [...] 1 NAME OPT 2 NAME 3 DIMENSION </pre>
<pre> \definevspacing [...] [...] 1 NAME 2 inherits: \vspacing </pre>
<pre> \definevspacingamount [...] [...] [...] 1 NAME OPT OPT 2 DIMENSION 3 DIMENSION </pre>
<pre> \definextable [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupxtable </pre>
<pre> \definujs [...] \[...] [...] 1 NUMMER OPT 2 CSNAME 3 CONTENT </pre>

\definujakcent ¹... ²... ³...

1 CHARACTER
2 CHARACTER
3 CHARACTER

\definujbarvu [¹...] [²...³...]

1 NAME
2 r = NUMBER
g = NUMBER
b = NUMBER
c = NUMBER
m = NUMBER
y = NUMBER
k = NUMBER
h = NUMBER
s = NUMBER
v = NUMBER
x = NUMBER
a = NUMBER zadny normalni multiply rastr prekryv softlight hardlight colordodge colorburn darken lighten difference
exclusion hue saturation barevne luminosity
t = NUMBER

\definujbarvu [¹...] [²...]

1 NAME
2 COLOR

\definujblok [¹...] [²...] [³...³...]

1 NAME OPT
2 NAME OPT
3 inherits: \nastavblok

\definujbloksekce [¹...] [²...] [³...³...]

1 NAME OPT
2 NAME
3 inherits: \nastavbloksekce

\definujbuffer [¹...] [²...] [³...³...]

1 NAME OPT OPT
2 BUFFER
3 inherits: \nastavbuffer

\definujfont [¹...] [²...] [³...³...]

1 NAME OPT
2 FONT
3 inherits: \nastavmeziradkovoumezeru

\definujfont [¹...] [²...] [³...]

1 NAME OPT
2 FONT
3 NAME

\definujformatodkazu [¹...] [²...] [³...³...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupreferenceformat

\definujhbox [¹...] [²...]

1 NAME
2 DIMENSION

\definujinterakcnimenu [¹...] [²...] [³...³...]

1 NAME OPT OPT
2 NAME
3 inherits: \nastavinterakcnimenu

\definujkombinovanyseznam [¹...] [²...²...] [³...³...]

1 NAME OPT
2 LISTE
3 inherits: \nastavseznam

<pre> \definujkonverzi [...] [...] [...] 1 SPRACHE 2 NAME 3 CSNAME </pre>
<pre> \definujkonverzi [...] [...] [...] [...] 1 SPRACHE 2 NAME 3 TEXT </pre>
<pre> \definujnadpis [...] [...] [...] [...] 1 NAME 2 ABSCHNITT 3 inherits: \nastavnadpis </pre>
<pre> \definujobrazeksymbol [...] [...] [...] [...] 1 NAME 2 FILE NAME 3 inherits: \externiobraz </pre>
<pre> \definujodkaz [...] [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definujodstavce [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavodstavce </pre>
<pre> \definujopis [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavopis </pre>
<pre> \definujoramovani [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \nastavoramovani </pre>
<pre> \definujoramovanytext [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupframedtext </pre>
<pre> \definujpaletu [...] [...] [...] 1 NAME 2 NAME = COLOR </pre>
<pre> \definujpaletu [...] [...] 1 NAME 2 NAME </pre>
<pre> \definujplvouciobjekt [...] [...] [...] [...] 1 SINGULAR 2 SINGULAR PLURAL 3 inherits: \nastavplvouciobjekt instances: chemical figure table intermezzo graphic </pre>
<pre> \definujplvouciobjekt [...] [...] [...] 1 SINGULAR 2 PLURAL 3 SINGULAR instances: chemical figure table intermezzo graphic </pre>

\definujpodpole [...]¹ [...]² [...]³,...]

1 NAME
2 NAME
3 NAME

\definujpole [...]¹ [...]² [...]³ [...]⁴,...]⁵

1 NAME
2 radio pod text radek push check signature
3 NAME
4 NAME
5 NAME

\definujpopis [...]¹ [...]² [...]³,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupdescription

\definujpopisek [...]¹ [...]² [...]³,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuplabel

\definujprekryv [...]¹,...]² [...]³

1 NAME OPT
2 NAME
3 BEFEHL

\definujprikaz ...¹ ...²

1 CHARACTER
2 BEFEHL

\definujprofil [...]¹ [...]² [...]³,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setupprofile

\definujprogram [...]¹ [...]² [...]³

1 NAME OPT
2 TEXT
3 TEXT

\definujprostredizakladnihofontu [...]¹ [...]² [...]³,...]

1 NAME OPT OPT
2 implicitni DIMENSION
3 velky = DIMENSION NUMMER
male = DIMENSION NUMMER
a = DIMENSION NUMMER
b = DIMENSION NUMMER
c = DIMENSION NUMMER
d = DIMENSION NUMMER
text = DIMENSION NUMMER
x = DIMENSION NUMMER
xx = DIMENSION NUMMER
script = DIMENSION NUMMER
scriptscript = DIMENSION NUMMER
meziradkovamezera = DIMENSION
em = sklonene kurziva STYLE BEFEHL
* = NUMMER

\definujrejstrik [...]¹ [...]² [...]³,...]

1 NAME OPT OPT
2 NAME
3 inherits: \nastavrejstrik

\definujsablonutabulky [...]¹ [...]² [...]³ [...]⁴

1 NAME OPT OPT
2 TEMPLATE
3 NAME
4 NAME

<pre> \definujsekci [...] * NAME </pre>
<pre> \definujseznam [...] [...] [...] [...] 1 NAME OPT OPT 2 LISTE 3 inherits: \nastavseznam </pre>
<pre> \definujskupinubarev [...] [...] [x:y:z,...] 1 NAME OPT 2 seda rgb cmyk spot 3 TRIPLET </pre>
<pre> \definujstartstop [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupstartstop </pre>
<pre> \definujstyl [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupstyle </pre>
<pre> \definujstylfontu [...] [...] 1 NAME 2 NAME </pre>
<pre> \definujsymbol [...] [...] 1 NAME OPT 2 NAME 3 BEFEHL </pre>
<pre> \definujsynonumumfontu [...] [...] 1 NAME OPT 2 FONT 3 features = NAME fallbacks = NAME goodies = NAME designsize = auto implicitni </pre>
<pre> \definujsynonyma [...] [...] 1 SINGULAR 2 PLURAL 3 CSNAME 4 CSNAME </pre>
<pre> \definujtabelaci [...] [...] 1 NAME OPT OPT 2 NAME 3 TEMPLATE </pre>
<pre> \definujtext [...] [...] [...] [...] [...] 1 NAME OPT OPT OPT OPT 2 vrsek zahlavi text upati spodek 3 text marginalie hrana 4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 6 datum cislostranky BESCHRIFTUNG TEXT BEFEHL 7 datum cislostranky BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \definujtrideni [...] [...] 1 SINGULAR OPT 2 PLURAL 3 zadny CSNAME </pre>
<pre> \definujupravu [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \nastavupravu </pre>

`\definujvelikostpapiru [1...] [2...2...]`

```
1 NAME
2 sirka      = DIMENSION
  vyska      = DIMENSION
  vrsek      = BEFEHL
  spodek     = BEFEHL
  vlevo      = BEFEHL
  vpravo     = BEFEHL
  vzdalenost = DIMENSION
  stranka    = inherits: \nastavvelikostpapiru
  papir      = inherits: \nastavvelikostpapiru
```

`\definujvelikostpapiru [1...] [2...2...] [3...3...]`

```
1 NAME
2 inherits: \nastavvelikostpapiru
3 inherits: \nastavvelikostpapiru
```

`\definujvycet [1...] [2...] [3...3...]`

```
1 NAME
2 NAME
3 inherits: \setupenumeration
```

`\definujzakladnifont [1...1...] [2...2...] [3...3...] [4...4...]`

```
1 NAME implicitni
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf      = FILE
  bf      = FILE
  it      = FILE
  sl      = FILE
  bi      = FILE
  bs      = FILE
  sc      = FILE
  mr      = FILE
  mrlr    = FILE
  mrrl    = FILE
  mb      = FILE
  mblr    = FILE
  mbrl    = FILE
```

`\definujzakladnifont [1...1...] [2...2...] [3...3...] [4...]`

```
1 NAME implicitni
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME
```

`\definujzasobnikpoli [1...] [2...2...] [3...3...]`

```
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```

`\definujznaceni [1...] [2...] [3...3...]`

```
1 NAME
2 BESCHRIFTUNG
3 inherits: \nastavznaceni
```

`\definujznak 1... 2...`

```
1 CHARACTER
2 NUMMER
```

`\delimited [1...] [2...] {3...}`

```
1 NAME
2 SPRACHE
3 CONTENT
```

`\delimitedtext [1...] [2...] {3...}`

```
1 NAME
2 SPRACHE
3 CONTENT
```

<code>\DELIMITEDTEXT [...] {...}</code> 1 SPRACHE OPT 2 CONTENT instances: quotation quote blockquote speech aside
<code>\aside [...] {...}</code> 1 SPRACHE ^{OPT} 2 CONTENT
<code>\blockquote [...] {...}</code> 1 SPRACHE OPT 2 CONTENT
<code>\quotation [...] {...}</code> 1 SPRACHE OPT 2 CONTENT
<code>\quote [...] {...}</code> 1 SPRACHE ^{OPT} 2 CONTENT
<code>\speech [...] {...}</code> 1 SPRACHE OPT 2 CONTENT
<code>\delkaseznamu</code>
<code>\depthofstring {...}</code> * TEXT
<code>\depthonlybox {...}</code> * CONTENT
<code>\depthspanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\depthstrut</code>
<code>\determinenoflines {...}</code> * CONTENT
<code>\devanagarinumerals {...}</code> * NUMMER
<code>\digits {...}</code> * NUMMER
<code>\digits ...</code> * NUMMER
<code>\dimensiontocount {...} {...}</code> 1 DIMENSION 2 CSNAME
<code>\directboxfromcache {...} {...}</code> 1 NAME 2 NUMMER TEXT

\directcolor [...] * COLOR
\directcolored [...,*...] * inherits: \definujbarvu
\directcolored [...] * COLOR
\directconvertedcounter {. ¹ .} {. ² .} 1 NAME 2 prvni predchozi dalsi posledni cislo
\directcopyboxfromcache {. ¹ .} {. ² .} 1 NAME 2 NUMMER TEXT
\directdummyparameter {.*.} * KEY
\directgetboxllx ... * CSNAME NUMMER
\directgetboxlly ... * CSNAME NUMMER
\directhighlight {. ¹ .} {. ² .} 1 NAME 2 TEXT
\directlocalframed [. ¹ .] {. ² .} 1 NAME 2 CONTENT
\directluacode {...} * BEFEHL
\directselect {. ¹ .} {. ² .} {. ³ .} {. ⁴ .} {. ⁵ .} {. ⁶ .} 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
\directsetbar {...} * NAME
\directsetup {...} * NAME
\directsymbol {. ¹ .} {. ² .} 1 NAME 2 NAME
\directvspacing {...,*...} * inherits: \vspacing
\dis {...} * CONTENT

<code>\disabledirectives [...,*,...]</code> <code>* NAME</code>
<code>\disableexperiments [...,*,...]</code> <code>* NAME</code>
<code>\disablemode [...,*,...]</code> <code>* NAME</code>
<code>\disableoutputstream</code>
<code>\disableparpositions</code>
<code>\disableregime</code>
<code>\disabletrackers [...,*,...]</code> <code>* NAME</code>
<code>\displaymath {...}</code> <code>* CONTENT</code>
<code>\displaymathematics {...}</code> <code>* CONTENT</code>
<code>\displaymessage {...}</code> <code>* TEXT</code>
<code>\distributedhsize {...} {...} {...}</code> <code>1 DIMENSION</code> <code>2 DIMENSION</code> <code>3 NUMMER</code>
<code>\dividedsize {...} {...} {...}</code> <code>1 DIMENSION</code> <code>2 DIMENSION</code> <code>3 NUMMER</code>
<code>\loadaptleftskip {...}</code> <code>* ano ne standardni DIMENSION</code>
<code>\loadaptrightskip {...}</code> <code>* ano ne standardni DIMENSION</code>
<code>\doaddfeature {...,*,...}</code> <code>* NAME</code>
<code>\doassign [...¹] [...²..]</code> <code>1 TEXT</code> <code>2 KEY = VALUE</code>
<code>\doassignempty [...¹] [...²..]</code> <code>1 TEXT</code> <code>2 KEY = VALUE</code>
<code>\doboundtext {...} {...} {...}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 BEFEHL</code>
<code>\documentvariable {...}</code> <code>* KEY</code>

\doDOUBLEargument \ ¹ ... [² ...] [³ ...] 1 CSNAME 2 TEXT 3 TEXT
\doDOUBLEargumentwithset \ ¹ ... [² ..., ³ ...] [³ ...] 1 CSNAME 2 TEXT 3 TEXT
\doDOUBLEempty \ ¹ ... [² ...] [³ ...] 1 CSNAME 2 TEXT 3 TEXT
\doDOUBLEemptywithset \ ¹ ... [² ..., ³ ...] [³ ...] 1 CSNAME 2 TEXT 3 TEXT
\doDOUBLEgroupempty \ ¹ ... { ² ...} { ³ ...} 1 CSNAME 2 TEXT 3 TEXT
\doeassign [¹ ...] [² ...] 1 TEXT 2 KEY = VALUE
\doexpandedrecurse { ¹ ...} { ² ...} 1 NUMBER 2 BEFEHL
\doFASTloopcs { ¹ ...} \ ² ... 1 NUMBER 2 CSNAME
\dogetattribute {.*} * NAME
\dogetattributeid {.*} * NAME
\dogetcommacommandelement ¹ ... \from ² ... \to \ ³ ... 1 NUMBER 2 TEXT 3 CSNAME
\dogobbledoubleempty [¹ ...] [² ...] 1 TEXT 2 TEXT
\dogobblesingleempty [¹ ...] * TEXT
\docheckassignment {.*} * TEXT
\docheckedpagestate { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} { ⁵ ...} { ⁶ ...} { ⁷ ...} 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL

<pre> \docheckedpair {...,*...} * TEXT </pre>
<pre> \doif {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifallcommon {...,¹...} {...,²...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifallcommonelse {...,¹...} {...,²...} {...³} {...⁴} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifalldefinedelse {...,¹...} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifallmodes {...,¹...} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifallmodeselse {...,¹...} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifassignmentelse {...¹} {...²} {...³} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifblackelse {...¹} {...²} {...³} 1 COLOR 2 TRUE 3 FALSE </pre>
<pre> \doifbothsides {...¹} {...²} {...³} 1 BEFEHL 2 BEFEHL 3 BEFEHL </pre>
<pre> \doifbothsidesoverruled {...¹} {...²} {...³} 1 BEFEHL 2 BEFEHL 3 BEFEHL </pre>
<pre> \doifboxelse {...¹} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifbufferelse {...¹} {...²} {...³} 1 BUFFER 2 TRUE 3 FALSE </pre>

\doifcolor {...} {...}

1 COLOR
2 TRUE

\doifcolorelse {...} {...} {...}

1 COLOR
2 TRUE
3 FALSE

\doifcommandhandler \... {...} {...}

1 CSNAME
2 NAME
3 TRUE

\doifcommandhandlerelse \... {...} {...} {...}

1 CSNAME
2 NAME
3 TRUE
4 FALSE

\doifcommon {...,¹...} {...,²...} {...}

1 TEXT
2 TEXT
3 TRUE

\doifcommonelse {...,¹...} {...,²...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifcontent {...} {...} {...} \... {...}

1 BEFEHL
2 BEFEHL
3 BEFEHL
4 CSNAME
5 CONTENT

\doifconversiondefinedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifconversionnumberelse {...} {...} {...} {...}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifcounter {...} {...}

1 NAME
2 TRUE

\doifcounterelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifcurrentfonthasfeatureelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifdefined {...} {...}

1 NAME
2 TRUE

<pre> \doifdefinedcounter {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifdefinedcounterelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdimensionelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifdimenstringelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifdocumentargument {...} {...} 1 NAME 2 TRUE </pre>
<pre> \doifdocumentargumentelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifdocumentfilename {...} {...} 1 NUMBER 2 TRUE </pre>
<pre> \doifdocumentfilenameelse {...} {...} {...} 1 NUMBER 2 TRUE 3 FALSE </pre>
<pre> \doifdrawingblackelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelse {...} {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE 4 FALSE </pre>
<pre> \doifelseallcommon {...,¹...} {...,²...} {...} {...⁴} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifelsealldefined {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelseallmodes {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>

\doifelseassignment {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifelseblack {...} {...} {...}

1 COLOR
2 TRUE
3 FALSE

\doifelsebox {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseboxincache {...} {...} {...} {...}

1 NAME
2 NUMMER TEXT
3 TRUE
4 FALSE

\doifelsebuffer {...} {...} {...}

1 BUFFER
2 TRUE
3 FALSE

\doifelsecolor {...} {...} {...}

1 COLOR
2 TRUE
3 FALSE

\doifelsecommandhandler \... {...} {...} {...}

1 CSNAME
2 NAME
3 TRUE
4 FALSE

\doifelsecommon {...,¹...} {...,²...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelseconversiondefined {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifelsecounter {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsecurrentsortingused {...} {...}

1 TRUE
2 FALSE

<pre> \doifelsecurrentsynonymshown {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelsecurrentsynonymused {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelsedefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsedefinedcounter {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsedimension {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifelsedimenstring {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifelsedocumentargument {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsedocumentfilename {...} {...} {...} 1 NUMBER 2 TRUE 3 FALSE </pre>
<pre> \doifelsedrawingblack {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifelseempty {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \doifelseemptyvalue {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelseemptyvariable {...} {...} {...} {...} 1 NAME 2 KEY 3 TRUE 4 FALSE </pre>
<pre> \doifelseenv {...} {...} {...} 1 KEY 2 TRUE 3 FALSE </pre>
<pre> \doifelsefastoptionalcheck {...} {...} 1 TRUE 2 FALSE </pre>

<pre> \doifelsefastoptionalcheckcs \.^.^ 1 CSNAME 2 CSNAME </pre>
<pre> \doifelsefieldbody {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsefieldcategory {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsefigure {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifelsefile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifelsefiledefined {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsefileexists {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \doifelsefirstchar {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \doifelseflagged {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsefontchar {...} {...} {...} {...} 1 FONT 2 NUMMER 3 TRUE 4 FALSE </pre>
<pre> \doifelsefontpresent {...} {...} {...} 1 FONT 2 TRUE 3 FALSE </pre>
<pre> \doifelsefontsynonym {...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifelsehasspace {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>

\doifelsehelp {...} {...}

1 TRUE
2 FALSE

\doifelseincsname {...} {...} {...} {...}

1 TEXT
2 CSNAME
3 TRUE
4 FALSE

\doifelseinelement {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseinputfile {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doifelseinsertion {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseinset {...} {...,²...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelseinstring {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseintoks {...} {...} {...} {...}

1 BEFEHL
2 BEFEHL
3 TRUE
4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseitalic {...} {...}

1 TRUE
2 FALSE

\doifelselanguage {...} {...} {...}

1 SPRACHE
2 TRUE
3 FALSE

\doifelselayerdata {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelselayoutdefined {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelselayoutsheadline {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelselayouttextline {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseleapyear {...} {...} {...}

1 NUMBER
2 TRUE
3 FALSE

\doifselist {...} {...} {...}

1 LISTE
2 TRUE
3 FALSE

\doifselocation {...} {...}

1 TRUE
2 FALSE

\doifselocfile {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doifelseMPgraphic {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsemainfloatbody {...} {...}

1 TRUE
2 FALSE

\doifelsemarkedpage {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsemarking {...} {...} {...}

1 BESCHRIFTUNG
2 TRUE
3 FALSE

\doifelsemeaning \^1... \^2... {...} {...}

1 CSNAME
2 CSNAME
3 TRUE
4 FALSE

\doifelsemessage {...} {...} {...} {...}

1 NAME
2 NAME NUMBER
3 TRUE
4 FALSE

\doifelsemode {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsenextbgroup {...¹} {...²}

1 TRUE
2 FALSE

\doifelsenextbgroupcs \... \...¹ \...²

1 CSNAME
2 CSNAME

\doifelsenextchar {...¹} {...²} {...³}

1 CHARACTER
2 TRUE
3 FALSE

\doifelsenextoptional {...¹} {...²}

1 TRUE
2 FALSE

\doifelsenextoptionalcs \... \...¹ \...²

1 CSNAME
2 CSNAME

\doifelsenextparenthesis {...¹} {...²}

1 TRUE
2 FALSE

\doifelsenonzeropositive {...¹} {...²} {...³}

1 NUMBER
2 TRUE
3 FALSE

\doifelsenoteonsamepage {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsenothing {...¹} {...²} {...³}

1 TEXT
2 TRUE
3 FALSE

\doifelsenumber {...¹} {...²} {...³}

1 TEXT
2 TRUE
3 FALSE

\doifelseobjectfound {...¹} {...²} {...³} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseobjectreferencefound {...¹} {...²} {...³} {...⁴}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseoddpage {...¹} {...²}

1 BEFEHL
2 BEFEHL

\doifelseoddpagefloat {...} {...}

1 TRUE
2 FALSE

\doifelseoldercontext {...} {...} {...}

1 NUMMER
2 TRUE
3 FALSE

\doifelseolderversion {...} {...} {...} {...}

1 NUMMER
2 NUMMER
3 TRUE
4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifelseoverlay {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelseparallel {...} {...²,...} {...} {...}

1 NAME
2 NAME vse
3 TRUE
4 FALSE

\doifelseparentfile {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doifelsepath {...} {...} {...}

1 PATH
2 TRUE
3 FALSE

\doifelsepathexists {...} {...} {...}

1 PATH
2 TRUE
3 FALSE

\doifelsepatterns {...} {...} {...}

1 SPRACHE
2 TRUE
3 FALSE

\doifelseposition {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsepositionaction {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifelsepositiononpage {...} {...} {...} {...}

1 NAME
2 NUMMER
3 TRUE
4 FALSE

\doifelsepositionsonsamepage {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsepositionsonthispage {...¹,...} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsepositionsused {...¹} {...²}

1 TRUE
2 FALSE

\doifelserreferencefound {...¹} {...²} {...³}

1 REFERENCE
2 TRUE
3 FALSE

\doifelserightpagefloat {...¹} {...²}

1 TRUE
2 FALSE

\doifelserighttoleftinbox ...¹ {...²} {...³}

1 CSNAME NUMMER
2 TRUE
3 FALSE

\doifelsesamelinereference {...¹} {...²} {...³}

1 REFERENCE
2 TRUE
3 FALSE

\doifelsesamestring {...¹} {...²} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifelsesetups {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsesomebackground {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifelsesomespace {...¹} {...²} {...³}

1 TEXT
2 TRUE
3 FALSE

\doifelsesomething {...¹} {...²} {...³}

1 TEXT
2 TRUE
3 FALSE

\doifelsesometoks \...¹ {...²} {...³}

1 CSNAME
2 TRUE
3 FALSE

```
\doifelsestringinstring {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelsestructurelisthasnumber {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsestructurelisthaspage {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsesymboldefined {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsesymbolset {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsetext {...} {...} {...}
1 TEXT
2 TRUE
3 FALSE
```

```
\doifelsetextflow {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsetextflowcollector {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsetopofpage {...} {...}
1 TRUE
2 FALSE
```

```
\doifelsetypingfile {...} {...} {...}
1 FILE
2 TRUE
3 FALSE
```

```
\doifelseundefined {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelseurldefined {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsevalue {...} {...} {...} {...}
1 NAME
2 TEXT
3 TRUE
4 FALSE
```

`\doifelsevaluenothing {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifelsevariable {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doifempty {...} {...}`

1 CONTENT
2 TRUE

`\doifemptyelse {...} {...} {...}`

1 CONTENT
2 TRUE
3 FALSE

`\doifemptytoks \... {...}`

1 CSNAME
2 TRUE

`\doifemptyvalue {...} {...}`

1 NAME
2 TRUE

`\doifemptyvalueelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifemptyvariable {...} {...} {...}`

1 NAME
2 KEY
3 TRUE

`\doifemptyvariableelse {...} {...} {...} {...}`

1 NAME
2 KEY
3 TRUE
4 FALSE

`\doifenv {...} {...}`

1 KEY
2 TRUE

`\doifenvelse {...} {...} {...}`

1 KEY
2 TRUE
3 FALSE

`\doiffastoptionalcheckcselse \... \...`

1 CSNAME
2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

1 TRUE
2 FALSE

`\doiffieldbodyelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

\doiffieldcategoryelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiffigureelse {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doiffile {...} {...}

1 FILE
2 TRUE

\doiffiledefinedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiffileelse {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doiffileexistselfelse {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doiffirstcharelse {...} {...} {...} {...}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifflaggedelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doiffontcharelse {...} {...} {...} {...}

1 FONT
2 NUMMER
3 TRUE
4 FALSE

\doiffontpresentelse {...} {...} {...}

1 FONT
2 TRUE
3 FALSE

\doiffontsynonymelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifhasspaceelse {...} {...} {...}

1 TEXT
2 TRUE
3 FALSE

\doifhelpelse {...} {...}

1 TRUE
2 FALSE

```
\doifincsnameelse {...} {...} {...} {...}
1 TEXT
2 CSNAME
3 TRUE
4 FALSE
```

```
\doifinelementelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifinputfileelse {...} {...} {...}
1 FILE
2 TRUE
3 FALSE
```

```
\doifinsectionelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifinset {...} {...,2...} {...}
1 TEXT
2 TEXT
3 TRUE
```

```
\doifinsetelse {...} {...,2...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifinstring {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
```

```
\doifinstringelse {...} {...} {...} {...}
1 TEXT
2 TEXT
3 TRUE
4 FALSE
```

```
\doifinsymbolset {...} {...} {...} {...}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifinsymbolsetelse {...} {...} {...} {...}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

```
\doifintokselse {...} {...} {...} {...}
1 BEFEHL
2 BEFEHL
3 TRUE
4 FALSE
```

```
\doifintwopassdataelse {...} {...} {...} {...}
1 NAME
2 NAME
3 TRUE
4 FALSE
```

\doifitalicelse {...} {...} 1 TRUE 2 FALSE
\doiflanguageelse {...} {...} {...} 1 SPRACHE 2 TRUE 3 FALSE
\doiflayerdataelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doiflayoutdefinedelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doiflayoutsomelineelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doiflayouttextlineelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifleapyearelse {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE
\doiflistelse {...} {...} {...} 1 LISTE 2 TRUE 3 FALSE
\doiflocationelse {...} {...} 1 TRUE 2 FALSE
\doiflocfileelse {...} {...} {...} 1 FILE 2 TRUE 3 FALSE
\doifMPgraphicelse {...} {...} {...} 1 NAME 2 TRUE 3 FALSE
\doifmainfloatbodyelse {...} {...} 1 TRUE 2 FALSE
\doifmarkingelse {...} {...} {...} 1 BESCHRIFTUNG 2 TRUE 3 FALSE
\doifmeaningelse \^1... \^2... {...} {...} 1 CSNAME 2 CSNAME 3 TRUE 4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

1 NAME
2 NAME NUMBER
3 TRUE
4 FALSE

`\doifmode {...,1...} {...2}`

1 NAME
2 TRUE

`\doifmodeelse {...,1...} {...2} {...3}`

1 NAME
2 TRUE
3 FALSE

`\doifnextbgroupcselse \1... \2...`

1 CSNAME
2 CSNAME

`\doifnextbgroupelse {...1} {...2}`

1 TRUE
2 FALSE

`\doifnextcharelse {...1} {...2} {...3}`

1 CHARACTER
2 TRUE
3 FALSE

`\doifnextoptionalcselse \1... \2...`

1 CSNAME
2 CSNAME

`\doifnextoptionalelse {...1} {...2}`

1 TRUE
2 FALSE

`\doifnextparenthesiselse {...1} {...2}`

1 TRUE
2 FALSE

`\doifnonzeropositiveelse {...1} {...2} {...3}`

1 NUMBER
2 TRUE
3 FALSE

`\doifnot {...1} {...2} {...3}`

1 CONTENT
2 CONTENT
3 TRUE

`\doifnotallcommon {...,1...} {...,2...} {...3}`

1 TEXT
2 TEXT
3 TRUE

`\doifnotallmodes {...,1...} {...2} {...3}`

1 NAME
2 TRUE
3 FALSE

`\doifnotcommandhandler \1... {...2} {...3}`

1 CSNAME
2 NAME
3 TRUE

<pre> \doifnotcommon {...¹,...} {...²,...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotcounter {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentargument {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentfilename {...¹} {...²} 1 NUMMER 2 TRUE </pre>
<pre> \doifnotempty {...¹} {...²} 1 CONTENT 2 TRUE </pre>
<pre> \doifnotemptyvalue {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotemptyvariable {...¹} {...²} {...³} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnotenv {...¹} {...²} 1 KEY 2 TRUE </pre>
<pre> \doifnoteonsamepageelse {...¹} {...²} {...³} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotescollected {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotfile {...¹} {...²} 1 FILE 2 TRUE </pre>
<pre> \doifnotflagged {...¹} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnothing {...¹} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnothingelse {...¹} {...²} {...³} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifnotinset {...¹} {...²,...} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>

<pre> \doifnotinsidesplitfloat {...} * TRUE </pre>
<pre> \doifnotinstring {...} {...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotmode {...¹,...} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotnumber {...} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnotsamestring {...¹} {...²} {...³} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotsetups {...} {...²} 1 NAME 2 TRUE </pre>
<pre> \doifnotvalue {...} {...²} {...³} 1 NAME 2 TEXT 3 TRUE </pre>
<pre> \doifnotvariable {...} {...²} {...³} 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnumber {...} {...²} 1 TEXT 2 TRUE </pre>
<pre> \doifnumberelse {...} {...²} {...³} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifobjectfoundelse {...} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifobjectreferencefoundelse {...} {...²} {...³} {...⁴} 1 NAME 2 NAME 3 TRUE 4 FALSE </pre>
<pre> \doifoddpagelse {...} {...²} 1 BEFEHL 2 BEFEHL </pre>
<pre> \doifoddpagefloatelse {...¹} {...²} 1 TRUE 2 FALSE </pre>

\doifoldercontextelse {...} {...} {...}

1 NUMBER
2 TRUE
3 FALSE

\doifolderversionelse {...} {...} {...} {...}

1 NUMBER
2 NUMBER
3 TRUE
4 FALSE

\doifoverlappingelse {...} {...} {...} {...}

1 NAME
2 NAME
3 TRUE
4 FALSE

\doifoverlayelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifparallelelse {...} {...,
...} {...} {...}

1 NAME
2 NAME vse
3 TRUE
4 FALSE

\doifparentfileelse {...} {...} {...}

1 FILE
2 TRUE
3 FALSE

\doifpathelse {...} {...} {...}

1 PATH
2 TRUE
3 FALSE

\doifpathexistseelse {...} {...} {...}

1 PATH
2 TRUE
3 FALSE

\doifpatternselse {...} {...} {...}

1 SPRACHE
2 TRUE
3 FALSE

\doifposition {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifpositionaction {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifpositionactionelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifpositionelse {...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME
2 NUMBER
3 TRUE
4 FALSE

\doifpositionsonsamepageelse {...¹,...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifpositionsonthispageelse {...¹,...} {...} {...}

1 NAME
2 TRUE
3 FALSE

\doifpositionsusedelse {...¹} {...²}

1 TRUE
2 FALSE

\doifreferencefoundelse {...¹} {...²} {...³}

1 REFERENCE
2 TRUE
3 FALSE

\doifrightpagefloatelse {...¹} {...²}

1 TRUE
2 FALSE

\doifrighttoleftinboxelse ...¹ {...²} {...³}

1 CSNAME NUMBER
2 TRUE
3 FALSE

\doifsamelinereferenceelse {...¹} {...²} {...³}

1 REFERENCE
2 TRUE
3 FALSE

\doifsamestring {...¹} {...²} {...³}

1 TEXT
2 TEXT
3 TRUE

\doifsamestringelse {...¹} {...²} {...³} {...⁴}

1 TEXT
2 TEXT
3 TRUE
4 FALSE

\doifsetups {...¹} {...²}

1 NAME
2 TRUE

\doifsetupselse {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

\doifsomebackground {...¹} {...²} {...³}

1 NAME
2 TRUE
3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsomespaceelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifsomething {...} {...}`

1 TEXT
2 TRUE

`\doifsomethingelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifsometoks \... {...}`

1 CSNAME
2 TRUE

`\doifsometokselse \... {...} {...}`

1 CSNAME
2 TRUE
3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

1 TRUE
2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

1 TRUE
2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsymbolsetelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiftext {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextflowcollectorelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiftextflowelse {1.} {2.} {3.}`

1 NAME
2 TRUE
3 FALSE

`\doiftopofpageelse {1.} {2.}`

1 TRUE
2 FALSE

`\doiftypingfileelse {1.} {2.} {3.}`

1 FILE
2 TRUE
3 FALSE

`\doifundefined {1.} {2.}`

1 NAME
2 TRUE

`\doifundefinedcounter {1.} {2.}`

1 NAME
2 TRUE

`\doifundefinedelse {1.} {2.} {3.}`

1 NAME
2 TRUE
3 FALSE

`\doifurldefinedelse {1.} {2.} {3.}`

1 NAME
2 TRUE
3 FALSE

`\doifvalue {1.} {2.} {3.}`

1 NAME
2 TEXT
3 TRUE

`\doifvalueelse {1.} {2.} {3.} {4.}`

1 NAME
2 TEXT
3 TRUE
4 FALSE

`\doifvaluenothing {1.} {2.}`

1 NAME
2 TRUE

`\doifvaluenothingelse {1.} {2.} {3.}`

1 NAME
2 TRUE
3 FALSE

`\doifvaluesomething {1.} {2.}`

1 NAME
2 TRUE

`\doifvariable {1.} {2.} {3.}`

1 NAME
2 KEY
3 TRUE

`\doifvariableelse {1.} {2.} {3.} {4.}`

1 NAME
2 KEY
3 TRUE
4 FALSE

<code>\doindentation</code>
<code>\dollar</code>
<code>\doloop {..}</code> * BEFEHL
<code>\doloopoverlist {...¹...} {...²}</code> 1 TEXT 2 BEFEHL
<code>\donothing</code>
<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweengroups</code>
<code>\dopositionaction {..}</code> * NAME
<code>\doprocesslocalsetups {...[*]...}</code> * NAME
<code>\doquadrupleargument \¹... [²...] [³...] [⁴...] [⁵...]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquadrupleempty \¹... [²...]_{OPT} [³...]_{OPT} [⁴...]_{OPT} [⁵...]_{OPT}</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquadruplegroupempty \¹... {²...}_{OPT} {³...}_{OPT} {⁴...}_{OPT} {⁵...}_{OPT}</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\doquintupleargument \¹... [²...] [³...] [⁴...] [⁵...] [⁶...]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\doquintupleempty \¹... [²...]_{OPT} [³...]_{OPT} [⁴...]_{OPT} [⁵...]_{OPT} [⁶...]_{OPT}</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT

<pre> \doquintuplegroupempty \¹... {²...} {³...} {⁴...} {⁵...} {⁶...} 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT </pre>
<pre> \dorecurse {¹...} {²...} 1 NUMBER 2 BEFEHL </pre>
<pre> \dorechecknextindentation </pre>
<pre> \dorepeatwithcommand [¹...] \²... 1 TEXT NUMBER*TEXT 2 CSNAME </pre>
<pre> \doreplacefeature {...,*...} * NAME </pre>
<pre> \doresetandafffeature {...,*...} * NAME </pre>
<pre> \doresetattribute {[*]...} * NAME </pre>
<pre> \dorotatebox {¹...} \²... {³...} 1 NUMBER 2 CSNAME 3 CONTENT </pre>
<pre> \dosetattribute {¹...} {²...} 1 NAME 2 NUMMER </pre>
<pre> \dosetleftskipadaption {[*]...} * ano ne standardni DIMENSION </pre>
<pre> \dosetrighskipadaption {[*]...} * ano ne standardni DIMENSION </pre>
<pre> \dosetupcheckedinterlinespace {...,*...} * inherits: \nastavmeziradkovoumezeru </pre>
<pre> \dosetupcheckedinterlinespace {...,*...} * zap vyp reset auto male stredni velke NUMMER DIMENSION </pre>
<pre> \dosetupcheckedinterlinespace {[*]...} * NAME </pre>
<pre> \doseventupleargument \¹... [²...] [³...] [⁴...] [⁵...] [⁶...] [⁷...] [⁸...] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT 8 TEXT </pre>


```
\doseventupleempty \... [1... [2... [3... [4... [5... [6... [7... [8...]
```

1	CSNAME	OPT	OPT	OPT	OPT	OPT	OPT	OPT
2	TEXT							
3	TEXT							
4	TEXT							
5	TEXT							
6	TEXT							
7	TEXT							
8	TEXT							

```
\dosingleargument \... [1... [2...]
```

1	CSNAME
2	TEXT

```
\dosingleempty \... [1... [2...]
```

1	CSNAME	OPT
2	TEXT	

```
\dosinglegroupempty \... {1... {2...}}
```

1	CSNAME	OPT
2	TEXT	

```
\dosixtupleargument \... [1... [2... [3... [4... [5... [6... [7...]
```

1	CSNAME
2	TEXT
3	TEXT
4	TEXT
5	TEXT
6	TEXT
7	TEXT

```
\dosixtupleempty \... [1... [2... [3... [4... [5... [6... [7...]
```

1	CSNAME	OPT	OPT	OPT	OPT	OPT	OPT
2	TEXT						
3	TEXT						
4	TEXT						
5	TEXT						
6	TEXT						
7	TEXT						

```
\dostarttagged {1...} {2...} ... \dostoptagged
```

1	NAME
2	NAME

```
\dostepwiserecurse {1...} {2...} {3...} {4...}
```

1	NUMBER
2	NUMBER
3	[-+]NUMBER
4	BEFEHL

```
\dosubtractfeature {...,*...}
```

*	NAME
---	------

```
\dotfskip {...}
```

*	DIMENSION
---	-----------

```
\dotoks \...
```

*	CSNAME
---	--------

```
\dotripleargument \... [1... [2... [3... [4...]
```

1	CSNAME
2	TEXT
3	TEXT
4	TEXT

`\dotripleargumentwithset \1... [2...,3...] [4...] [5...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleempty \1... [2...] [3...] [4...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotripleemptywithset \1... [2...,3...] [4...] [5...]`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\dotriplegroupempty \1... {2...} {3...} {4...}`

1 CSNAME
2 TEXT
3 TEXT
4 TEXT

`\doublebond`

`\dowith {...,1...} {2...}`

1 BEFEHL
2 BEFEHL

`\dowithnextbox {1...} \2... {3...}`

1 BEFEHL
2 CSNAME
3 CONTENT

`\dowithnextboxcontent {1...} {2...} \3... {4...}`

1 BEFEHL
2 BEFEHL
3 CSNAME
4 CONTENT

`\dowithnextboxcontentcs \1... \2... \3... {4...}`

1 CSNAME
2 CSNAME
3 CSNAME
4 CONTENT

`\dowithnextboxcs \1... \2... {3...}`

1 CSNAME
2 CSNAME
3 CONTENT

`\dowithpargument *...`

* CSNAME

`\dowithrange {...,1...} \2...`

1 NUMBER NUMBER:NUMBER
2 CSNAME

`\dowithwargument *...`

* CSNAME

`\dpofstring {*...}`

* TEXT

`\dummydigit`

<code>\dummyparameter {...}</code> * KEY
<code>\ETEX</code>
<code>\EveryLine {...}</code> * BEFEHL
<code>\EveryPar {...}</code> * BEFEHL
<code>\edefconvertedargument \¹... {²...}</code> 1 CSNAME 2 TEXT
<code>\efcmaxheight {...}</code> * NAME
<code>\efcmaxwidth {...}</code> * NAME
<code>\efcminheight {...}</code> * NAME
<code>\efcminwidth {...}</code> * NAME
<code>\efcparameter {¹...} {²...}</code> 1 NAME 2 KEY
<code>\effect [¹...] {²...}</code> 1 NAME 2 CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\em</code>
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...]</code> * NUMMER OPT
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code> * NAME
<code>\enableexperiments [...,*,...]</code> * NAME
<code>\enablemode [...,*,...]</code> * NAME

<code>\enableoutputstream [...]</code> * NAME
<code>\enableparpositions</code>
<code>\enableregime [...]</code> * cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows
<code>\enabletrackers [...,*,...]</code> * NAME
<code>\enskip</code>
<code>\enspace</code>
<code>\env {...}</code> * KEY
<code>\envvar {.¹.} {.².}</code> 1 KEY 2 BEFEHL
<code>\epos {...}</code> * NAME
<code>\equaldigits {...}</code> * TEXT
<code>\eTeX</code>
<code>\executeifdefined {.¹.} {.².}</code> 1 NAME 2 BEFEHL
<code>\exitloop</code>
<code>\exitloopnow</code>
<code>\expanded {...}</code> * CONTENT
<code>\expandfontsynonym \.¹. {.².}</code> 1 CSNAME 2 NAME
<code>\expandcheckedcsname \.¹. {.².} {.³.}</code> 1 CSNAME 2 KEY 3 TEXT
<code>\expdoif {.¹.} {.².} {.³.}</code> 1 CONTENT 2 CONTENT 3 TRUE

```
\expdoifcommonelse {...,1...} {...,2...} {...3} {...4}  
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\expdoifelse {...1} {...2} {...3} {...4}  
1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE
```

```
\expdoifelsecommon {...,1...} {...,2...} {...3} {...4}  
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\expdoifelseinset {...1} {...,2...} {...3} {...4}  
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\expdoifinsetelse {...1} {...,2...} {...3} {...4}  
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\expdoifnot {...1} {...2} {...3}  
1 CONTENT  
2 CONTENT  
3 TRUE
```

```
\externalfigurecollectionmaxheight {...}  
* NAME
```

```
\externalfigurecollectionmaxwidth {...}  
* NAME
```

```
\externalfigurecollectionminheight {...}  
* NAME
```

```
\externalfigurecollectionminwidth {...}  
* NAME
```

```
\externalfigurecollectionparameter {...1} {...2}  
1 NAME  
2 KEY
```

```
\externiobraz [...1] [...2] [...,3...,...]  
1 FILE OPT OPT  
2 NAME  
3 inherits: \setupexternalfigure
```

```
\fakebox ...  
* CSNAME NUMBER
```

```
\fastdecrement \...  
* CSNAME
```

```
\fastincrement \...  
* CSNAME
```

<code>\fastlocalframed [..¹] [...²..³] {...}</code> 1 NAME 2 inherits: \nastavoramovani 3 CONTENT
<code>\fastloopfinal</code>
<code>\fastloopindex</code>
<code>\fastscale {..¹} {..²}</code> 1 NUMBER 2 CONTENT
<code>\fastsetup {..[*]}</code> * NAME
<code>\fastsetupwithargument {..¹} {..²}</code> 1 NAME 2 CONTENT
<code>\fastsetupwithargumentswapped {..¹} {..²}</code> 1 CONTENT 2 NAME
<code>\fastswitchtobodyfont {..[*]}</code> * x xx male velke script scriptscript
<code>\fastxsxy {..¹} {..²} {..³}</code> 1 NUMBER 2 NUMBER 3 CONTENT
<code>\feature [..¹] [...²,...]</code> 1 + - = ! > < more less novy reset implicitni old lokalne 2 NAME
<code>\feature {..¹} {...²,...}</code> 1 + - = ! > < more less novy reset implicitni old lokalne 2 NAME
<code>\fence</code>
<code>\fenced [..¹] {..²}</code> 1 NAME 2 CONTENT
<code>\FENCE {..[*]}</code> * CONTENT
<code>\fetchallmarkings [..¹] [..²]</code> 1 BESCHRIFTUNG 2 stranka NAME
<code>\fetchallmarks [..[*]]</code> * BESCHRIFTUNG
<code>\fetchmark [..¹] [..²]</code> 1 BESCHRIFTUNG <small>OPT</small> 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck

\fetchmarking [...] [...] [...] 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchonemark [...] [...] 1 BESCHRIFTUNG OPT 2 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchonemarking [...] [...] [...] 1 BESCHRIFTUNG 2 stranka NAME 3 prvni posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchruntimecommand \^... {^...} 1 CSNAME 2 FILE
\fetchtwomarkings [...] [...] 1 BESCHRIFTUNG 2 stranka NAME
\fetchtwomarks [...] * BESCHRIFTUNG
\fieldbody [...] [...] 1 NAME OPT 2 inherits: \setupfieldbody
\fifthoffivearguments {^...} {^...} {^...} {^...} {^...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\fifthofsixarguments {^...} {^...} {^...} {^...} {^...} {^...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\figurefilename
\figurefilepath
\figurefiletype
\figurefullname
\figureheight
\figurenaturalheight
\figurenaturalwidth
\figuresymbol [...] [...] 1 FILE NAME OPT 2 inherits: \externiobraz


```
\finishregisterentry [...]1 [...,...2...,...]2 [...,...3...,...]3
1 NAME OPT
2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
alternativa = TEXT
3 KEY = VALUE
```

```
\firstcounter [...]1 [...]2
1 NAME OPT
2 NUMMER
```

```
\firstcountervalue [...]  
* NAME
```

```
\firstcharacter
```

```
\firstoffivearguments {...}1 {...}2 {...}3 {...}4 {...}5  
1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT
```

```
\firstoffourarguments {...}1 {...}2 {...}3 {...}4  
1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT
```

```
\firstofoneargument {...}*  
* TEXT
```

```
\firstofoneunexpanded {...}*  
* TEXT
```

```
\firstofsixarguments {...}1 {...}2 {...}3 {...}4 {...}5 {...}6  
1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT
```

```
\firstofthreearguments {...}1 {...}2 {...}3  
1 TEXT  
2 TEXT  
3 TEXT
```

```
\firstofthreeunexpanded {...}1 {...}2 {...}3  
1 TEXT  
2 TEXT  
3 TEXT
```

```
\firstoftwoarguments {...}1 {...}2  
1 TEXT  
2 TEXT
```

```
\firstoftwounexpanded {...}1 {...}2  
1 TEXT  
2 TEXT
```

```
\firstrealpage
```

```
\firstrealpagenumber
```

\firstsubcountervalue [...] [...] 1 NAME 2 NUMBER
\firstsubpagenumber
\firstuserpage
\firstuserpagenumber
\fitfieldframed [... ¹ ... ²] {...} 1 inherits: \nastavoramova ^{OFF} 2 CONTENT
\fittopbaselinegrid {...} * CONTENT
\flag {...} * NAME
\floatuserdataparameter {...} * KEY
\flushbox {...} {...} 1 NAME 2 NAME
\flushboxregister ... * CSNAME NUMBER
\flushcollector [...] * NAME
\flushedrightlastline
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks *... * CSNAME

<code>\fontalternative</code>
<code>\fontbody</code>
<code>\fontclass</code>
<code>\fontclassname {¹. . . } {². . . }</code> 1 NAME 2 FONT
<code>\fontface</code>
<code>\fontfeaturelist [¹. . .] [². . .]</code> 1 NAME 2 TEXT
<code>\fontchar {[*]. . . }</code> * NAME
<code>\fontcharbyindex {[*]. . . }</code> * NUMBER
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [¹. . . ,². . .] {². . . }</code> 1 REFERENCE OPT 2 TEXT
<code>\footnotetext [[*]. . . ,[*]. . . ,[*]. . .]</code> * titul = TEXT * zalozka = TEXT * seznam = TEXT * odkaz = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [¹. . .] [². . . ,². . . ,². . .]</code> 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\foundbox {¹. . . } {². . . }</code> 1 NAME 2 NAME
<code>\fourthoffivearguments {¹. . . } {². . . } {³. . . } {⁴. . . } {⁵. . . }</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT

`\fourthoffourarguments {1.} {2.} {3.} {4.}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT

`\fourthofsixarguments {1.} {2.} {3.} {4.} {5.} {6.}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

`\frameddimension {*.}`

* KEY

`\framedparameter {*.}`

* KEY

`\freezedimenmacro \1. \2.`

1 CSNAME
2 CSNAME

`\freezemeasure [1.] [2.]`

1 NAME
2 DIMENSION

`\frenchspacing`

`\fromlinenote [1.] {2.}`

1 REFERENCE
2 TEXT

`\frozenhbox {*.}`

* CONTENT

`\frule .. *. .. \relax`

* width_␣DIMENSION height_␣DIMENSION depth_␣DIMENSION radius_␣DIMENSION line_␣DIMENSION type_␣TEXT data_␣TEXT name_␣TEXT

`\GetPar`

`\GotoPar`

`\Greeknumerals {*.}`

* NUMBER

`\gdefconvertedargument \1. {2.}`

1 CSNAME
2 TEXT

`\gdefconvertedcommand \1. \2.`

1 CSNAME
2 CSNAME

`\getboxfromcache {1.} {2.} 3.`

1 NAME
2 NUMBER TEXT
3 CSNAME NUMBER

`\getboxllx *.`

* CSNAME NUMBER

<pre>\getboxlly ... * CSNAME NUMMER</pre>
<pre>\getbufferdata [...] * BUFFER OPT</pre>
<pre>\getcommacommandsize [...,*...] * BEFEHL</pre>
<pre>\getcommalistsize [...,*...] * BEFEHL</pre>
<pre>\getdayoftheweek {...} {...} {...} 1 NUMBER 2 NUMBER 3 NUMBER</pre>
<pre>\getdayspermonth {...} {...} 1 NUMBER 2 NUMBER</pre>
<pre>\getdefinedbuffer [...] * BUFFER</pre>
<pre>\getdocumentargument {...} * NAME</pre>
<pre>\getdocumentargumentdefault {...} {...} 1 NAME 2 TEXT</pre>
<pre>\getdocumentfilename {...} * NUMMER</pre>
<pre>\getdummyparameters [...,*...,...] * KEY = VALUE</pre>
<pre>\getemptyparameters [...] [...,*...,...] 1 TEXT 2 KEY = VALUE</pre>
<pre>\getparameters [...] [...,*...,...] 1 TEXT 2 KEY = VALUE</pre>
<pre>\getexpandedparameters [...] [...,*...,...] 1 TEXT 2 KEY = VALUE</pre>
<pre>\getfiguredimensions [...] [...,*...,...] 1 FILE OPT 2 inherits: \setupexternalfigure</pre>
<pre>\getfirstcharacter {...} * TEXT</pre>
<pre>\getfirsttwopassdata {...} * NAME</pre>

<pre> \getfromcommaccommand [...¹,...] [...²] 1 BEFEHL 2 NUMMER </pre>
<pre> \getfromcommalist [...¹,...] [...²] 1 BEFEHL 2 NUMMER </pre>
<pre> \getfromtwopassdata {...¹} {...²} 1 NAME 2 NAME </pre>
<pre> \getglyphdirect {...¹} {...²} 1 FONT 2 NUMMER CHARACTER </pre>
<pre> \getglyphstyled {...¹} {...²} 1 FONT 2 NUMMER CHARACTER </pre>
<pre> \getgparameters [...¹] [...²,...²,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getlasttwopassdata {...} * NAME </pre>
<pre> \getlocalfloat {...} * NUMMER </pre>
<pre> \getlocalfloats </pre>
<pre> \getMPdrawing </pre>
<pre> \getMPlayer [...¹] [...²,...²,...] {...³} 1 NAME OPT 2 inherits: \nastavoramovani 3 CONTENT </pre>
<pre> \getmessage {...¹} {...²} 1 NAME 2 NAME NUMMER </pre>
<pre> \getnamedglyphdirect {...¹} {...²} 1 FONT 2 NAME </pre>
<pre> \getnamedglyphstyled {...¹} {...²} 1 FONT 2 NAME </pre>
<pre> \getnamedtwopassdatalist \... {...²} 1 CSNAME 2 NAME </pre>
<pre> \getnaturaldimensions ... * CSNAME NUMMER </pre>
<pre> \getnoflines {...} * DIMENSION </pre>

\getobject {...} {...} 1 NAME 2 NAME
\getobjectdimensions {...} {...} 1 NAME 2 NAME
\getpaletsize [...] * NAME
\getparameters [...] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getprivatechar {...} * NAME
\getprivateslot {...} * NAME
\getrandomcount \... {...} {...} 1 CSNAME 2 NUMBER 3 NUMBER
\getrandomdimen \... {...} {...} 1 CSNAME 2 DIMENSION 3 DIMENSION
\getrandomfloat \... {...} {...} 1 CSNAME 2 NUMBER 3 NUMBER
\getrandomnumber \... {...} {...} 1 CSNAME 2 NUMBER 3 NUMBER
\getrandomseed \... * CSNAME
\getrawparameters [...] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getrawgparameters [...] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getrawnoflines {...} * DIMENSION
\getrawparameters [...] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getrawxparameters [...] [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE

<pre> \getreference [...] [...] 1 implicitni text titul cislo stranka realpage 2 REFERENCE </pre>
<pre> \getreferenceentry {...} * implicitni text titul cislo stranka realpage </pre>
<pre> \getroundednoflines {...} * DIMENSION </pre>
<pre> \getsubstring {...} {...} {...} 1 NUMBER 2 NUMBER 3 TEXT </pre>
<pre> \gettwopassdata {...} * NAME </pre>
<pre> \gettwopassdatalist {...} * NAME </pre>
<pre> \getuvalue {...} * NAME </pre>
<pre> \getvalue {...} * NAME </pre>
<pre> \getvariable {...} {...} 1 NAME 2 KEY </pre>
<pre> \getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL </pre>
<pre> \getxparameters [...] [...,...²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \globaldisablemode [...,*...] * NAME </pre>
<pre> \globalenablemode [...,*...] * NAME </pre>
<pre> \globalletempty *.. * CSNAME </pre>
<pre> \globalpopbox *.. * CSNAME NUMMER </pre>
<pre> \globalpopmacro *.. * CSNAME </pre>
<pre> \globalpreventmode [...,*...] * NAME </pre>
<pre> \globalprocesscommalist [...] *.. 1 BEFEHL 2 CSNAME </pre>

\globalpushbox *...*

* CSNAME NUMBER

\globalpushmacro *\...*

* CSNAME

\globalpushreferenceprefix *{...}* ... **\globalpopreferenceprefix**

* + - TEXT

\globalswapcounts *\¹...* *\²...*

1 CSNAME

2 CSNAME

\globalswapdims *\¹...* *\²...*

1 CSNAME

2 CSNAME

\globalswapmacros *\¹...* *\²...*

1 CSNAME

2 CSNAME

\globalundefine *{...}*

* NAME

\glyphfontfile *{...}*

* FONT

\gobbledoubleempty [*¹...*] [*²...*]

1 TEXT

OPT

OPT

2 TEXT

\gobbleeightarguments *{¹...}* *{²...}* *{³...}* *{⁴...}* *{⁵...}* *{⁶...}* *{⁷...}* *{⁸...}*

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

\gobblefivearguments *{¹...}* *{²...}* *{³...}* *{⁴...}* *{⁵...}*

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

\gobblefiveoptionals [*¹...*] [*²...*] [*³...*] [*⁴...*] [*⁵...*]

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

\gobblefourarguments *{¹...}* *{²...}* *{³...}* *{⁴...}*

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

\gobblefouroptionals [*¹...*] [*²...*] [*³...*] [*⁴...*]

1 TEXT

2 TEXT

3 TEXT

4 TEXT

\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT
8 CONTENT
9 CONTENT

\gobbleoneargument {...}

* CONTENT

\gobbleoneoptional [...]

* TEXT

\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT

\gobblesingleempty [...]

* TEXT OPT

\gobblesixarguments {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT

\gobblespacetokens

\gobbletenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
7 CONTENT
8 CONTENT
9 CONTENT
10 CONTENT

\gobblethreearguments {...} {...} {...}

1 CONTENT
2 CONTENT
3 CONTENT

\gobblethreeoptionals [...] [...] [...]

1 TEXT
2 TEXT
3 TEXT

\gobbletwoarguments {...} {...}

1 CONTENT
2 CONTENT

\gobbletwooptionals [...] [...]

1 TEXT
2 TEXT

<p><code>\gobbleuntil \...</code></p> <p>* CSNAME</p>
<p><code>\gobbleuntilrelax ... \relax</code></p> <p>* CONTENT</p>
<p><code>\grabbufferdata [¹...] [²...] [³...] [⁴...]</code></p> <p>1 CATEGORY OPT</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p><code>\grabbufferdatadirect {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p>
<p><code>\grabuntil {...} \²...</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\grave {...}</code></p> <p>* CHARACTER</p>
<p><code>\grayvalue {...}</code></p> <p>* COLOR</p>
<p><code>\greedyplitstring ¹... \at ²... \to ³... \and \⁴...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p> <p>4 CSNAME</p>
<p><code>\greeknumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\groupedcommand {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p>
<p><code>\gsetboxllx ¹... {...}</code></p> <p>1 CSNAME NUMBER</p> <p>2 DIMENSION</p>
<p><code>\gsetboxlly ¹... {...}</code></p> <p>1 CSNAME NUMBER</p> <p>2 DIMENSION</p>
<p><code>\gujaratinumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\gurmukhinumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\hairspace</code></p>
<p><code>\halflinestrut</code></p>
<p><code>\halfstrut</code></p>
<p><code>\halfwaybox {...}</code></p> <p>* CONTENT</p>

<code>\handletokens ... \with ...</code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...¹,...] {...²}</code> 1 REFERENCE 2 CONTENT
<code>\hboxBOX {...}</code> * CONTENT
<code>\hdofstring {...}</code> * TEXT
<code>\headhbox ...¹ {...²}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox ...¹ {...²}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring {...}</code> * TEXT
<code>\heightofstring {...}</code> * TEXT
<code>\heightspanningtext {...¹} {...²} {...³}</code> 1 TEXT 2 DIMENSION 3 FONT

<code>\HELP [...] {...} {...}</code> 1 REFERENCE ^{WVE} 2 TEXT 3 TEXT instances: helptext
<code>\helptext [...] {...} {...}</code> 1 REFERENCE ^{OPT} 2 TEXT 3 TEXT
<code>\hglue ...</code> * DIMENSION
<code>\hiddencitation [...]</code> * REFERENCE
<code>\hiddencite [...]</code> * REFERENCE
<code>\highlight [...] {...}</code> 1 NAME 2 TEXT
<code>\HIGHLIGHT {...}</code> * TEXT
<code>\highordinalstr {...}</code> * TEXT
<code>\hilo [...] {...} {...}</code> 1 vlevo ^{OPT} vpravo 2 CONTENT 3 CONTENT
<code>\himilo {...} {...} {...}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\hl [...]</code> * NUMBER ^{WER}
<code>\hlavnijazyk [...]</code> * SPRACHE
<code>\hodnotabarvy {...}</code> * COLOR
<code>\horizontalgrowingbar [...,...[*]...,...]</code> * inherits: \setuppositionbar
<code>\horizontalpositionbar [...,...[*]...,...]</code> * inherits: \setuppositionbar
<code>\hphantom {...}</code> * CONTENT
<code>\hpos {...} {...}</code> 1 NAME 2 CONTENT

\backslash hsizefraction {...} {...} 1 DIMENSION 2 NUMBER
\backslash hsmash {...} * CONTENT
\backslash hsmashbox ... * CSNAME NUMBER
\backslash hsmashed {...} * CONTENT
\backslash hspace [... ¹] [... ²] 1 NAME OPT OPT 2 male stredni velke normalni implicitni zadny .5 1 2 3 speech citovat interquotation citace sentence intersentence NAME
\backslash htdpostring {...} * TEXT
\backslash htofstring {...} * TEXT
\backslash hyphen
\backslash hyphenatedcoloredword {...} * TEXT
\backslash hyphenatedfile {...} * FILE
\backslash hyphenatedfilename {...} * TEXT
\backslash hyphenatedhbox {...} * CONTENT
\backslash hyphenatedpar {...} * TEXT
\backslash hyphenatedurl {...} * TEXT
\backslash hyphenatedword {...} * TEXT
\backslash CHARACTERKERNING [... ¹] {... ² } 1 NUMBER OPT 2 TEXT
\backslash chardescription {...} * NUMBER
\backslash charwidthlanguage
\backslash check {...} * CHARACTER

\checkedfiller {...} * sym symbol linka sirka mezera NAME BEFEHL
\checkedchar {...} {...} 1 NUMBER 2 CHARACTER
\checkedstrippedcsname \... * CSNAME
\checkedstrippedcsname ... * TEXT
\checkcharacteralign {...} * CONTENT
\checkinjector [...]
\checknextindentation [...]
\checknextinjector [...]
\checkpage [...] [... ² ...] 1 NAME OPT 2 inherits: \setuppagechecker
\checkparameters [...]
\checkpreviousinjector [...]
\checksoundtrack {...} * NAME
\checktwopassdata {...} * NAME
\checkvariables [...] [... ² ...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\chem {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\chemical [...] [... ² ...] [... ³ ...] 1 NAME OPT OPT 2 TEXT 3 TEXT
\chemicalbottext {...} * TEXT

<code>\chemicalmidtext {...}</code> * TEXT
<code>\chemicalsymbol [...]</code> * NAME
<code>\chemicaltext {...}</code> * TEXT
<code>\chemicaltoptext {...}</code> * TEXT
<code>\chineseallnumerals {...}</code> * NUMBER
<code>\chinesecapnumerals {...}</code> * NUMBER
<code>\chinesenumerals {...}</code> * NUMBER
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iftrialtypesetting ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {...¹} {...²} {...³}</code> 1 NAME 2 NUMBER 3 CONTENT
<code>\impliedby</code>

<code>\implies</code>
<code>\includemenu [...]</code> * NAME
<code>\includeversioninfo {...}</code> * NAME
<code>\incrementcounter [...]¹ [...]²</code> 1 NAME OPT 2 NUMBER
<code>\incrementedcounter [...]</code> * NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> * NAME
<code>\indentation</code>
<code>\infofont</code>
<code>\infofontbold</code>
<code>\inheritparameter [...]¹ [...]² [...]³</code> 1 TEXT 2 TEXT 3 KEY
<code>\inhibitblank</code>
<code>\initializeboxstack {...}</code> * NAME
<code>\inlinebuffer [...][*] [...]</code> * BUFFER OPT
<code>\inlinedbox {...}</code> * CONTENT
<code>\inlinemath {...}</code> * CONTENT
<code>\inlinemathematics {...}</code> * CONTENT
<code>\inlinemessage {...}</code> * TEXT
<code>\inlineordisplaymath {...}¹ {...}²</code> 1 CONTENT 2 CONTENT

```
\inlineprettyprintbuffer {...} {...}
1  BUFFER
2  mp lua xml parsed-xml nested tex context zadny NAME
```

`\inlinerange [...]`
* REFERENCE

\innerflushshapebox

```
\input {...}
* FILE
```

`\inputfilebarename`

\inputfilename

\inputfilesuffix

```
\inputgivenfile {...}
* FILE
```

```
\input ...
* FILE
```

```
\insertpages [1] [2,...] [3,...]
1 FILE
2 NUMBER
3 sirka = DIMENSION
  n = NUMBER
  category = NAME
```

```
\instalacejazyka [...] [...2...]
```

```
1  NAME
```

```
2  inherits: \nastavjazyk
```

```
\instalacejazyka [...] [...]
```

```
\installactionhandler {...}
* NAME
```

```
\installactivecharacter ...
* CHARACTER
```

```
\installanddefineactivecharacter ... {1...2}
```

```
1 CHARACTER
```

```
2 BEFEHL
```

```
\installattributestack \.*
* CSNAME
```

```
\installautocommandhandler \^1. {^2.} \^3.
1 CSNAME
2 NAME
3 CSNAME
```

<pre> \installautosetuphandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbasicautosetuphandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installbasicparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbottomframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installcommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installcorenamespace {...} * NAME </pre>
<pre> \installdefinehandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installdefinitionset \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installdefinitionsetmember \... {...} \... {...} 1 CSNAME 2 NAME 3 CSNAME 4 NAME </pre>
<pre> \installdirectcommandhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installdirectparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installdirectparametersethandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installdirectsetuphandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installdirectstyleandcolorhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installframedautocommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>

<pre> \installframedcommandhandler \¹... {²...} \³... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installleftframerenderer {¹...} {²...} 1 NAME 2 BEFEHL </pre>
<pre> \installnamespace {[*]...} * NAME </pre>
<pre> \installoutputroutine \¹... {²...} 1 CSNAME 2 BEFEHL </pre>
<pre> \installpagearrangement ¹... {²...} 1 NAME 2 BEFEHL </pre>
<pre> \installparameterhandler \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installparameterhashhandler \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installparametersethandler \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installparentinjector \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installrightframerenderer {¹...} {²...} 1 NAME 2 BEFEHL </pre>
<pre> \installrootparameterhandler \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installsetuphandler \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installsetuponlycommandhandler \¹... {²...} 1 CSNAME 2 NAME </pre>
<pre> \installshipoutmethod {¹...} {²...} 1 NAME 2 BEFEHL </pre>
<pre> \installsimplecommandhandler \¹... {²...} \³... 1 CSNAME 2 NAME 3 CSNAME </pre>

<code>\installsimpleframedcommandhandler \¹... {²...} \³...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installstyleandcolorhandler \¹... {²...}</code> 1 CSNAME 2 NAME
<code>\installswitchcommandhandler \¹... {²...} \³...</code> 1 CSNAME 2 NAME 3 CSNAME
<code>\installswitchsetuphandler \¹... {²...}</code> 1 CSNAME 2 NAME
<code>\installtexdirective {¹...} {²...} {³...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtextracker {¹...} {²...} {³...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtopframerenderer {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\installunitsseparator {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\installunitsspace {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\installversioninfo {¹...} {²...}</code> 1 NAME 2 BEFEHL
<code>\integerrounding {[*]...}</code> * NUMMER
<code>\interakcnilista [¹...] [²...,...²...,...]</code> 1 NAME OPT OPT 2 inherits: \nastavinterakcnilistu
<code>\interakcnitlacitka [¹...,...¹...,...] [²...,...]</code> 1 inherits: \nastavinterakcnilistu 2 stranka podstranka REFERENCE
<code>\interaktivnimenu [¹...] [²...,...²...,...]</code> 1 NAME OPT 2 inherits: \nastavinterakcnimenu
<code>\intertext {[*]...}</code> * TEXT

<code>\invokepagehandler {...} {...}</code> 1 normalni zadny NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italiccorrection</code>
<code>\italicface</code>
<code>\itemtag [...*,...]</code> * REFERENCE OPT
<code>\jazyk [...]</code> * SPRACHE
<code>\LANGUAGE</code>
<code>\jdidolu [...]</code> * DIMENSION
<code>\jdina {...} [...]</code> 1 CONTENT 2 REFERENCE
<code>\jdinabox {...} [...]</code> 1 CONTENT 2 REFERENCE
<code>\jdinastranu {...} [...]</code> 1 TEXT 2 REFERENCE
<code>\UNIT {...}</code> * CONTENT instances: unit
<code>\unit {...}</code> * CONTENT
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\Kap {...}</code> * TEXT
<code>\kaligraficke</code>
<code>\kap {...}</code> * TEXT
<code>\keeplinestogether {...}</code> * NUMMER

<code>\keepunwantedspaces</code>
<code>\kerncharacters [...]¹{...}²</code> 1 NUMBER OPT 2 TEXT
<code>\klonujpole [...]¹[...]²[...]³[...]⁴,...]</code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\COMMENT [...]¹[...]²=...³{...}</code> 1 TEXT OPT OPT 2 inherits: \nastavkomentar 3 TEXT instances: comment
<code>\comment [...]¹[...]²=...³{...}</code> 1 TEXT OPT OPT 2 inherits: \nastavkomentar 3 TEXT
<code>\komponenta [...]</code> * FILE
<code>\komponenta ...</code> * FILE
<code>\konvertujcislo {...}¹{...}²</code> 1 prazdne implicitni zadny mesic month:mnem pismo Pismo pisma Pisma a A Csla slovo words Slovo Slova n N rimskecislice Rimskecislice i I r R KR RK recky Recky g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2 NUMBER
<code>\kopirujpole [...]¹[...]²</code> 1 NAME 2 NAME
<code>\koreancirclenumerals {...}</code> * NUMBER
<code>\koreannumerals {...}</code> * NUMBER
<code>\koreannumeralsc {...}</code> * NUMBER
<code>\koreannumeralsp {...}</code> * NUMBER
<code>\koreanparentnumerals {...}</code> * NUMBER
<code>\korekcebilehomista {...}</code> * CONTENT
<code>\kurziva</code>
<code>\kurzivnitucne</code>

<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\LABELjazyk</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabeljazyk</code>
<code>\headjazyk</code>
<code>\labeljazyk</code>
<code>\mathlabeljazyk</code>
<code>\operatorjazyk</code>
<code>\prefixjazyk</code>
<code>\suffixjazyk</code>
<code>\taglabeljazyk</code>
<code>\unitjazyk</code>
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances: head label mathlabel
<code>\headtexts {...} {...}</code> 1 KEY 2 TEXT
<code>\labeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\mathlabeltexts {...} {...}</code> 1 KEY 2 TEXT

<code>\lazysavetaggedtwopassdata {...} {...} {...} {...}</code> 1 NAME 2 NUMBER 3 NAME 4 CONTENT
<code>\lazysavetwopassdata {...} {...} {...}</code> 1 NAME 2 NUMBER 3 CONTENT
<code>\lbox ... {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\leftbottombox {...}</code> * CONTENT
<code>\leftbox {...}</code> * CONTENT
<code>\lefthbox {...}</code> * CONTENT
<code>\leftLABELtext {...}</code> * KEY instances: head label mathlabel
<code>\leftheadtext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY
<code>\leftmathlabeltext {...}</code> * KEY
<code>\leftline {...}</code> * CONTENT
<code>\lefttorrighthbox ...¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\lefttorrightvbox ...¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\lefttorrightvtop ...¹ {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\leftskipadaption</code>
<code>\leftsubguillemot</code>
<code>\lefttopbox {...}</code> * CONTENT
<code>\lefttoright</code>

$\backslash\text{lefttorighthbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{lefttorightvbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{lefttorightvtop}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{letbeundefined}$ $\{...\}$ * NAME
$\backslash\text{letcatcodecommand}$ $\overset{1}{...}$ $\overset{2}{...}$ $\overset{3}{...}$ 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
$\backslash\text{letcscsname}$ $\overset{1}{...}$ $\backslash\text{csname}$ $\overset{2}{...}$ $\backslash\text{endcsname}$ 1 CSNAME 2 NAME
$\backslash\text{letcsnamecs}$ $\backslash\text{csname}$ $\overset{1}{...}$ $\backslash\text{endcsname}$ $\overset{2}{...}$ 1 NAME 2 CSNAME
$\backslash\text{letcsnamecsname}$ $\backslash\text{csname}$ $\overset{1}{...}$ $\backslash\text{endcsname}$ $\backslash\text{csname}$ $\overset{2}{...}$ $\backslash\text{endcsname}$ 1 NAME 2 NAME
$\backslash\text{letdummysparameter}$ $\{\overset{1}{...}\}$ $\overset{2}{...}$ 1 KEY 2 CSNAME
$\backslash\text{letempty}$ $\overset{*}{...}$ * CSNAME
$\backslash\text{letgvalue}$ $\{\overset{1}{...}\}$ $\overset{2}{...}$ 1 NAME 2 CSNAME
$\backslash\text{letgvalueempty}$ $\{\overset{*}{...}\}$ * NAME
$\backslash\text{letgvalurelax}$ $\{\overset{*}{...}\}$ * NAME
$\backslash\text{letterampersand}$
$\backslash\text{letterat}$
$\backslash\text{letterbackslash}$
$\backslash\text{letterbar}$
$\backslash\text{letterbgroup}$
$\backslash\text{letterclosebrace}$

<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterleftbracket</code>
<code>\letterleftparenthesis</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\letterrightbracket</code>
<code>\letterrightparenthesis</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> [¹ ...] { ² ...} 1 NUMBER OPT 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> { ¹ ...} \ ² ... 1 NAME 2 CSNAME

<code>\letvalueempty {...}</code> * NAME
<code>\letvaluerelax {...}</code> * NAME
<code>\lfence {...}</code> * CHARACTER
<code>\lhbox {...}</code> * CONTENT
<code>\limitatefirstline {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\limitatelines {...} {...} {...}</code> 1 NUMBER 2 BEFEHL 3 TEXT
<code>\limitatetext {...} {...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext {...} {...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\LINENOTE {...}</code> * TEXT instances: linenote
<code>\linenote {...}</code> * TEXT
<code>\linespanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\listcitation [...¹...] [...²]</code> 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE
<code>\listcitation [...¹] [...²]</code> 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE

`\listcitation [...,\sup{1}...,\sup{2}...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\listcite [...,\sup{1}...,\sup{2}] [...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 REFERENCE
```

`\listcite [...]\sup{1} [...] [...]\sup{2} [...]`

```
1 implicitni OPTcategory entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear
2 REFERENCE
```

`\listcite [...,\sup{1}...,\sup{2}...]`

```
1 odkaz      = REFERENCE
  alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum
                authoryear
  pred        = BEFEHL
  po          = BEFEHL
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  inherits: \setupbtx
2 KEY = VALUE
```

`\listnamespaces`

`\llap {...}`

* CONTENT

`\loadanyfile [...]`

* FILE

`\loadanyfileonce [...]`

* FILE

`\loadbtxdefinitionfile [...]`

* FILE

`\loadbtxreplacementfile [...]`

* FILE

`\loadcldfile [...]`

* FILE

`\loadcldfileonce [...]`

* FILE

`\loadfontgoodies [...]`

* FILE

`\loadluafile [...]`

* FILE

[illegible]

<code>\lowercased {...}</code> * TEXT
<code>\lowercasestring ... \to ...</code> 1 TEXT 2 CSNAME
<code>\lowerleftdoubleninequote</code>
<code>\lowerleftsingleninequote</code>
<code>\lowerrightdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\LOWHIGH [...] {...} {...}</code> 1 vlevo vpra ^{OPT} 2 CONTENT 3 CONTENT
<code>\LOWMIDHIGH [...] {...} {...}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\lrbbox [...] {...} {...} {...} {...}</code> 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
<code>\ltop ... {...}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\luacode {...}</code> * BEFEHL
<code>\luaconditional ...</code> * CSNAME
<code>\luaenvironment ...</code> * FILE
<code>\luaexpanded {...}</code> * BEFEHL
<code>\luaexpr {...}</code> * CONTENT
<code>\luafunction {...}</code> * BEFEHL
<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luaminorversion</code>

<code>\luaparameterset {¹.².}</code> 1 NAME 2 CONTENT
<code>\luasetup {[*].[*].}</code> * NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\MESIC {[*].[*].}</code> * NUMBER
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {[*].[*].}</code> * NUMBER
<code>\MONTHSHORT {[*].[*].}</code> * NUMBER
<code>\MPanchor {[*].[*].}</code> * NAME
<code>\MPbetex {[*].[*].}</code> * NAME
<code>\MPc {[*].[*].}</code> * NAME
<code>\MPcode {¹.².}</code> 1 NAME OPT 2 CONTENT
<code>\MPcolor {[*].[*].}</code> * COLOR

\MPcoloronly {...} * COLOR
\MPcolumn {...} * NAME
\MPd {...} * NAME
\MPdrawing {...} * CONTENT
\MPfontsizehskip {...} * FONT
\MPgetmultipars {...} {...} 1 NAME 2 NAME
\MPgetmultishape {...} {...} 1 NAME 2 NAME
\MPgetposboxes {..., ¹ ...} {... ² } 1 NAME 2 NAME
\MPh {...} * NAME
\MPII
\MPIV
\MPinclusions [...] ¹ {...} ² {...} ³ 1 + OPT OPT 2 NAME 3 CONTENT
\MPleftskip {...} * NAME
\MPll {...} * NAME
\MPlr {...} * NAME
\MPls {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPoptions {...} * COLOR

\MPoverlayanchor {...} * NAME
\MPp {...} * NAME
\MPpage {...} * NAME
\MPpardata {...} * NAME
\MPplus {...} {...} {...} 1 NAME 2 NUMBER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic {...} {... ² ...} 1 NAME 2 KEY = VALUE <small>OPT</small>
\MPposset {...} * NAME
\MPr {...} * NAME
\MPrawvar {...} {...} 1 NAME 2 KEY
\MPregion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPstring {...} * NAME
\MPtext {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME

\MPur {...} * NAME
\MPVI
\MPv {...} {...} {...} 1 NAME 2 NUMBER 3 CONTENT
\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {...} {...} 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME
\MPxy {...} * NAME
\MPxywhd {...} * NAME
\MPy {...} * NAME
\m [...] {...} 1 NAME 2 CONTENT
\makecharacteractive ... * CHARACTER
\makerawcommalist [... ¹ ,...] \ ² .. 1 BEFEHL 2 CSNAME
\makestrutofbox ... * CSNAME NUMMER
\male
\malekurzivnitucne
\malenormalni
\malesklonene

<code>\malesklonenetucne</code>
<code>\maletucne</code>
<code>\maletucnekurzivni</code>
<code>\maletucnesklonene</code>
<code>\maletype</code>
<code>\mapfontsize [...]¹ [...]²</code> 1 DIMENSION 2 DIMENSION
<code>\margindata [...]¹ [...]² [...]³ {...}⁴</code> 1 NAME 2 odkaz = REFERENCE inherits: \setupmargindata 3 inherits: \setupmarginframed 4 CONTENT
<code>\MARGINDATA [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin inother margintext
<code>\atleftmargin [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\atrighmargin [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\ininner [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\ininneredge [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\ininnermargin [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\inleft [...]¹ [...]² {...}³</code> 1 odkaz = REFERENCE ^{OPT} inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT

```

\inleftedge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inother [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouter [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouteredge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inoutermargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inright [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightedge [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightmargin [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\margintext [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {\stackrel{3}{.}}
1 odkaz = REFERENCEOPT
inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\markcontent [\stackrel{1}{.}] {\stackrel{2}{.}}
1 reset vse NAMEOPT
2 CONTENT

```

\backslash markinjector [...] * NAME
\backslash markpage [...] [...] 1 NAME OPT 2 [-+]NUMBER
\backslash mat {...} * CONTENT
\backslash matematika [...] {...} 1 NAME OPT 2 CONTENT
\backslash math [...] {...} 1 NAME OPT 2 CONTENT
\backslash mathbf
\backslash mathbi
\backslash mathblackboard
\backslash mathbs
\backslash MATHCOMMAND [...] {...} 1 TEXT OPT OPT 2 TEXT
\backslash mathdefault
\backslash mathdouble [...] [...] [...] [...] 1 obe vfenced OPT 2 NUMBER 3 TEXT 4 TEXT
\backslash MATHDOUBLEEXTENSIBLE [...] [...] 1 TEXT 2 TEXT instances: doublebar doublebrace doubleparent doublebracket overbarunderbar overbraceunderbrace overparentunderparent overbracketunderbracket
\backslash doublebar [...] [...] 1 TEXT 2 TEXT
\backslash doublebrace [...] [...] 1 TEXT 2 TEXT
\backslash doublebracket [...] [...] 1 TEXT 2 TEXT
\backslash doubleparent [...] [...] 1 TEXT 2 TEXT

$\overline{\underbrace{\dots}}^{\dots}$ 1 TEXT 2 TEXT
$\overbrace{\underbrace{\dots}}^{\dots}$ 1 TEXT 2 TEXT
$\overbracket{\underbracket{\dots}}^{\dots}$ 1 TEXT 2 TEXT
$\overparent{\underparent{\dots}}^{\dots}$ 1 TEXT 2 TEXT
$\mathcal{M}\over{\underbrace{\dots}}^{\dots}$ 1 TEXT OPT OPT 2 TEXT instances: xrel xequal xleftarrow xrightarrow xleftrightharrow xLeftarrow xRightarrow xLeftrightharrow xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow xleftharpoondown xleftharpoonup xrightharpoondown xrightharpoonup xrightoverleftarrow xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharrow mLeftarrow mRightarrow mLeftrightharrow mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow mhookrightarrow mleftharpoondown mleftharpoonup mrightharpoondown mrightharpoonup mrightoverleftarrow mleftrightharpoons mrightleftharpoons mtriplerel elefarrowfill erightarrowfill eleftrightharrowfill etwoheadrightarrowfill eleftharpoondownfill eleftharpoonupfill erightharpoondownfill erightharpoonupfill eoverbarfill eunderbarfill eoverbracefill eunderbracefill eoverparentfill eunderparentfill eoverbracketfill eunderbracketfill trel tequal tmapsto tleftarrow trightarrow tleftrightharrow tLeftarrow tRightarrow tLeftrightharrow ttwoheadleftarrow ttwoheadrightarrow thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup trightoverleftarrow tleftrightharpoons trightleftharpoons ttriplerel cleftarrow crightarrow crightoverleftarrow
$\overleftarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overleftarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overleftharpoondown{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overleftharpoonup{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overleftrightharrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\overleftarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT

$\backslash\mathrm{eoverbracefill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{eoverbracketfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{eoverparentfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{erightarrowfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{erightharpoondownfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{erightharpoonupfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{etwoheadrightarrowfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{eunderbarfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{eunderbracefill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{eunderbracketfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{eunderparentfill}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{mequal}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{mhookleftarrow}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{mhookrightarrow}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{mLeftarrow}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{mLeftrightarrow}\{\dots\}^1{\dots}^2$ 1 TEXT OPT OPT 2 TEXT

$\mleftarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mleftharpoonowdown{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mleftharpoonowup{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mleftrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mleftrightharpoons{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mmapsto{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrel{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrightharpoonowdown{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrightharpoonowup{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrightrightarrows{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mrightharpoonowleftarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mtriplerel{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mtwoheadleftarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT
$\mtwoheadrightarrow{\dots}^{\dots}$ 1 TEXT OPT OPT 2 TEXT

$\backslash\mathrm{tequal} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{thookleftarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{thookrightarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tLeftarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tLeftrightarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tleftarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tlefttharpoondown} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tlefttharpoonup} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tleftrightarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tleftrightharpoons} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tmapsto} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{tRrightarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{trel} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{trightarrow} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{trightharpoondown} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\mathrm{trightharpoonup} \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT

$\backslash trightleftharpoons \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash trightoverleftarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash ttriplerel \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash ttwoheadleftarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash ttwoheadrightarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xequal \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xhookleftarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xhookrightarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xLeftarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xLeftrightarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xleftarrow \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xleftharpoondown \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xleftharpoonup \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xleftrightharpoonup \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xleftrightharpoons \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT
$\backslash xmapsto \{...\} \{...\}$ 1 TEXT OPT OPT 2 TEXT

1	TEXT	OPT	OPT
2	TEXT		

```

1  TEXT  OPT      OPT
2  TEXT

```

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

1	TEXT	OPT	OPT
2	TEXT		

```
1  TEXT                                OPT      OPT
2  TEXT
```

$$\frac{1}{\sqrt{2}}$$

```

1 inherits: \setupmathframedGPT
2 CONTENT

```

```
instances: mframed inmframed mcframed
```

```
1 inherits: \setupmathframedOPT
2 CONTENT
```

```
1 inherits: \setupOPTmathframed
2 CONTENT
```

```
1 inherits: \setupOPTmathframed
2 CONTENT
```

* CONTENT

 \mathit

<code>\mathitalic</code>
<code>\mathop {...}</code> * CONTENT
<code>\MATHORNAMENT {...}</code> * CONTENT
<code>\mathover [...]¹ {...}² {...}³</code> 1 <code>vrsek vfenc</code> 2 NUMBER 3 TEXT
<code>\MATHOVEREXTENSIBLE {...}</code> * TEXT
<code>\MATHOVERTEXTEXTENSIBLE [...]¹ {...}²</code> 1 TEXT 2 TEXT instances:
<code>\MATHRADICAL [...]¹ {...}²</code> 1 TEXT 2 CONTENT
<code>\mathrm</code>
<code>\mathscript</code>
<code>\mathsl</code>
<code>\mathss</code>
<code>\mathtext ...¹ {...}²</code> 1 TEXT 2 TEXT
<code>\mathtextbf ...¹ {...}²</code> 1 TEXT 2 TEXT
<code>\mathtextbi ...¹ {...}²</code> 1 TEXT 2 TEXT
<code>\mathtextbs ...¹ {...}²</code> 1 TEXT 2 TEXT
<code>\mathtextit ...¹ {...}²</code> 1 TEXT 2 TEXT
<code>\mathtextsl ...¹ {...}²</code> 1 TEXT 2 TEXT
<code>\mathtexttf ...¹ {...}²</code> 1 TEXT 2 TEXT

<code>\mathtf</code>
<code>\mathtriplet [...]¹ {...}² {...}³ {...}⁴</code> 1 NAME OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT
<code>\MATHTRIPLET [...]¹ {...}² {...}³ {...}⁴</code> 1 NAME OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT
<code>\mathtt</code>
<code>\mathunder [...]¹ {...}² {...}³</code> 1 spodek vfence ^{OPT} 2 NUMMER 3 TEXT
<code>\MATHUNDEREXTENSIBLE {...}[*]</code> * TEXT
<code>\MATHUNDERTEXTTEXTENSIBLE {...}¹ {...}²</code> 1 TEXT 2 TEXT instances:
<code>\MATHUNSTACKED</code>
<code>\mathupright</code>
<code>\mathword ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\mathwordbf ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\mathwordbi ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\mathwordbs ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\mathwordit ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\mathwordsl ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\mathwordtf ...¹ {...}²</code> 1 TEXT OPT 2 TEXT
<code>\maxaligned {...}[*]</code> * CONTENT

$\backslash\mathrm{mbox}\{...\}$ * CONTENT
$\backslash\mathrm{measure}\{...\}$ * NAME
$\backslash\mathrm{measured}\{...\}$ * NAME
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{meritko}\overset{1}{[...]}[\dots,\overset{2}{\dots},\dots]\overset{3}{\{...\}}$ 1 NAME OPT OPT 2 inherits: $\backslash\mathrm{setupscale}$ 3 CONTENT
$\backslash\mathrm{mesic}\{...\}$ * NUMMER
$\backslash\mathrm{message}\{...\}$ * TEXT
$\backslash\mathrm{metaTeX}$
$\backslash\mathrm{mezera}$
$\backslash\mathrm{mfence}\{...\}$ * CHARACTER
$\backslash\mathrm{mfunction}\{...\}$ * CONTENT
$\backslash\mathrm{mfunctionlabeltext}\{...\}$ * NAME
$\backslash\mathrm{mhbox}\{...\}$ * CONTENT
$\backslash\mathrm{middlealigned}\{...\}$ * CONTENT
$\backslash\mathrm{middlebox}\{...\}$ * CONTENT
$\backslash\mathrm{midhbox}\{...\}$ * CONTENT
$\backslash\mathrm{midsubsentence}$
$\backslash\mathrm{minimalhbox}\overset{1}{...}\overset{2}{\{...\}}$ 1 TEXT OPT 2 CONTENT
$\backslash\mathrm{mixedcaps}\{...\}$ * TEXT

\mkvibuffer [...] * BUFFER OPT
\moduleparameter {...} {...} 1 FILE 2 KEY
\molecule {...} * CONTENT
\mono
\mononormal
\monotucne
\monthlong {...} * NUMBER
\monthshort {...} * NUMBER
\mprandomnumber
\mrizka [...,...*=...,...] * inherits: \basegrid ^{OPT}
\mtext {...} * CONTENT
\NormalizeFontHeight \ ¹ ... {\ ² ...} {\ ³ ...} {\ ⁴ ...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\NormalizeFontWidth \ ¹ ... {\ ² ...} {\ ³ ...} {\ ⁴ ...} 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
\NormalizeTextHeight {\ ¹ ...} {\ ² ...} {\ ³ ...} 1 FONT 2 DIMENSION 3 TEXT
\NormalizeTextWidth {\ ¹ ...} {\ ² ...} {\ ³ ...} 1 FONT 2 DIMENSION 3 TEXT
\namedheadnumber {...} * ABSCHNITT
\namedstructureheadlocation {...} * ABSCHNITT
\namedstructureuservariable {\ ¹ ...} {\ ² ...} 1 ABSCHNITT 2 KEY

\namedstructurevariable {...} {...}

1 ABSCHNITT
2 KEY

\namedtaggedlabeltexts {...} {...} {...} {...} {...}

1 NAME
2 NAME
3 NAME
4 NAME
5 CONTENT

\nastavbarvu [...]

* FILE

\nastavbarvy [..., ...^{*}..., ...]

* status = start stop
spot = ano ne
expanzen = ano ne
faktor = ano ne
rgb = ano ne
cmyk = ano ne
konverze = ano ne vzdy
pagecolormodel = auto zadny NAME
barvatextu = COLOR
intent = overprint knockout zadny

\nastavbilamista [...^{*}..., ...]

* fixuj fixne prizpusobi^{OPT}v radek pulradku quarterline zadny male stredni velke implicitni DIMENSION

\nastavblok [...¹..., ...] [...²..., ...]

1 NAME ^{OPT}
2 pred = BEFEHL
po = BEFEHL
vnitrni = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR

\nastavbloksekce [...¹..., ...] [...²..., ...]

1 NAME ^{OPT}
2 stranka = inherits: \strana
pred = BEFEHL
po = BEFEHL
cislo = ano ne

\nastavbuffer [...¹..., ...] [...²..., ...]

1 BUFFER ^{OPT}
2 pred = BEFEHL
po = BEFEHL

\nastavcernelinky [...^{*}..., ...]

* sirka = max DIMENSION
vyska = max DIMENSION
hloubka = max DIMENSION
vzdalenost = DIMENSION
n = NUMMER
alternativa = a b
pismo = STYLE BEFEHL
barva = COLOR
typ = mp ano ne
mp = NAME

\nastavcislonadpisu [...¹...] [...²...]

1 ABSCHNITT
2 [-+]NUMMER

\nastavcislostrany [...^{*}..., ...]

* inherits: \setupuserpagenumber

`\nastavcislovaniodstavcu [...,.*=...,...]`

* status = start stop radek reset
vzdalenost = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcislovaniradku [...,1...] [...,.*2...,...]`

1 NAME OPT
2 start = NUMMER
krok = NUMMER
metoda = stranka prvni dalsi
konverze = NAME
pokracovat = ano ne
misto = text begin end implicitni vlevo vpravo uvnitr vnejsi ivlevo ivpravo marginalie naokraj
vzdalenost = DIMENSION
zarovnani = uvnitr vnejsi flushleft flushright vlevo vpravo nastred auto
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
marginalie = DIMENSION
sirka = marginalie DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcislovanistran [...,.*=...,...]`

* alternativa = jednostranne dvoustranny
stranka = inherits: \strana
strut = ano ne
prikaz = \...##1
vlevo = BEFEHL
vpravo = BEFEHL
status = start stop
sirka = DIMENSION
misto = zahlevi upati vlevo nastred vpravo ivlevo ivpravo marginalie naokraj naokraj textovahrana
pismo = STYLE BEFEHL
barva = COLOR

`\nastavcitaci [...,.*=...,...]`

* inherits: \setupdelimitedtext

`\nastavdeleniplvoucichobjektu [...,.*=...,...]`

* pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
radky = auto NUMMER
konverze = NAME

`\nastavdelitko [...,.*=...,...]`

* znak = normalni siroce

`\nastavdolnitexty [...,1...] [...,2...] [...,3...] [...,4...] [...,5...]`

1 text marginalie hrana OPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

`\nastaveni [...]`

* NAME

`\nastaveni {...}`

* NAME

`\nastavhorejsek [...,1...] [...,.*2...,...]`

1 text marginalie hrana OPT
2 inherits: \setuplayoutelement

```

\nastavhornitexty [...]1 [...]2 [...]3 [...]4 [...]5
1 text marginalie hrana OPT OPT OPT OPT OPT
2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

```

```

\nastavinterakci [...]1, [...]2, [...]3, [...]4, [...]5
1 NAME OPT
2 status = start stop
pismeno = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
titul = TEXT
podtitulek = COLOR
autor = TEXT
datum = TEXT
keyword = TEXT
zaostreni = standardni ramecek sirka minsirka vyska minvyska prizpusobive tight
menu = zap vyp
fieldlayer = auto NAME
pocitat = REFERENCE
klik = ano ne
obrazovka = normalni novy
stranka = ano ne stranka jmeno auto
otevriakci = REFERENCE
zavriakci = REFERENCE
akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
sadasymbolu = NAME
vyska = DIMENSION
hloubka = DIMENSION
focusoffset = DIMENSION

```

```

\nastavinterakci [...]*
* NAME OPT

```

```

\nastavinterakcnilistu [...]1, [...]2, [...]3, [...]4, [...]5
1 NAME OPT
2 alternativa = a b c d e f g
status = start stop
prikaz = CSNAME
sirka = DIMENSION
vyska = DIMENSION max široky
hloubka = DIMENSION max
vzdalenost = DIMENSION
krok = male stredni velke
barvapoziadi = COLOR
pismeno = STYLE BEFEHL
barva = COLOR
kontrastnibarva = COLOR
symbol = ano ne
inherits: \nastavoramovani

```

```

\nastavinterakcnimenu [...]1, [...]2, [...]3, [...]4, [...]5
1 NAME OPT
2 alternativa = vertikalne horizontalne skryte
category = NAME
levyoffset = prekryv ramecek zadny implicitni DIMENSION
pravyyoffset = prekryv ramecek zadny implicitni DIMENSION
offsetvrsku = prekryv ramecek zadny implicitni DIMENSION
offsetspodku = prekryv ramecek zadny implicitni DIMENSION
maxsirka = DIMENSION
maxvyska = DIMENSION
itemalign = vlevo nastred vpravo flushleft flushright nizko vysoko nivu
status = start prazdne lokalne
vlevo = BEFEHL
vpravo = BEFEHL
vzdalenost = prekryv DIMENSION
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
position = ano ne
stredni = BEFEHL
pismeno = STYLE BEFEHL
barva = COLOR
stejnastranka = ano ne prazdne zadny normalni implicitni
kontrastnibarva = COLOR
inherits: \nastavoramovani

```

\nastavinterakcniobrazovku [...¹...²...]

* sirka = prizpusobive max tight DIMENSION
 vyska = prizpusobive max tight DIMENSION
 zpetnamezera = DIMENSION
 horoffset = DIMENSION
 offsethlavicky = DIMENSION
 svrchnamezera = DIMENSION
 volba = prizpusobive max jednostranne dvoustranny zalozka auto zadny implicitni fixne nasirku portrait stranka
 papir attachment layer
 copies = NUMMER
 prodleva = zadny NUMMER

\nastavjazyk [...¹...²...]

1 SPRACHE implicitni
 2 implicitni = SPRACHE
 status = start stop
 datum = inherits: \aktualnidatum
 patterns = FILE
 lefthyphenmin = NUMMER
 righthyphenmin = NUMMER
 lefthyphenchar = NUMMER
 righthyphenchar = NUMMER
 setups = NAME
 mezerovani = siroky zhustene
 font = auto
 text = TEXT
 limittext = TEXT
 hyphen = TEXT
 compoundhyphen = TEXT
 leftcompoundhyphen = TEXT
 rightcompoundhyphen = TEXT
 citovatvlevo = BEFEHL
 citovatvpravo = BEFEHL
 citacevlevo = BEFEHL
 citacevpravo = BEFEHL
 leftspeech = BEFEHL
 rightspeech = BEFEHL
 vetavlevo = BEFEHL
 middlespeech = BEFEHL
 vetavpravo = BEFEHL
 midsentence = BEFEHL
 podvetavlevo = BEFEHL
 podvetavpravo = BEFEHL
 faktor = ano ne

\nastavkapitalky [...¹...²...]

1 NAME OPT
 2 titul = ano ne
 sc = ano ne
 pismo = STYLE BEFEHL

\nastavkombinovanyseznam [...¹...²...]

1 LISTE
 2 inherits: \nastavseznam

\nastaveniCOMBINEDLIST [...¹...²...]

* inherits: \nastavseznam
 instances: content

\nastavenicontent [...¹...²...]

* inherits: \nastavseznam

`\nastavkomentar [...1,...] [...2,...]`

1 NAME OPT
2 status = start stop zadny
metoda = normalni skryte
symbol = Comment Napoveda Insert Klavesa Newparagraph Note Odstavec Default
sirka = prizpusobive DIMENSION
vyska = prizpusobive DIMENSION
hloubka = prizpusobive DIMENSION
titul = TEXT
podtitulek = TEXT
autor = TEXT
nx = NUMMER
ny = NUMMER
barva = COLOR
volba = xml max
textlayer = NAME
misto = levahrana pravahrana naokraji levyokraj pravyokraj text vysoko zadny
vzdalenost = DIMENSION
mezera = ano
buffer = BUFFER

`\nastavkomentarstrany [...*,...]`

* misto = vlevo vpravo vrsek spodek zadny
status = start stop zadny
offset = DIMENSION
vzdalenost = DIMENSION
sirka = DIMENSION
vyska = DIMENSION

`\nastavmarginalnilinky [...1] [...2,...]`

1 NUMMER OPT
2 inherits: \setupmarginrule

`\nastavmeziradkovoumezeru [...1,...] [...2,...]`

1 NAME OPT
2 radek = DIMENSION
vyska = NUMMER
hloubka = NUMMER
minvyska = NUMMER
mindepth = NUMMER
vzdalenost = DIMENSION
vrsek = NUMMER vyska
spodek = NUMMER
natahnout = NUMMER
shrink = NUMMER

`\nastavmeziradkovoumezeru [...*,...]`

* zap vyp reset auto male stredni velke NUMMER DIMENSION OPT

`\nastavmeziradkovoumezeru [...*]`

* NAME

```

\nastavnadpis [...1,...] [...2,...]
1 ABSCHNITT OPT
2 frontpartlabel = NAME
  bodypartlabel = NAME
  appendixlabel = NAME
  backpartlabel = NAME
  expanzen = ano ne xml
  catcodes = NAME
  sectionresetset = NAME
  sectionseparatorset = NAME
  sectionconversionset = NAME
  konverze = NAME
  sectionstarter = BEFEHL PROCESSOR->BEFEHL
  sectionstopper = BEFEHL PROCESSOR->BEFEHL
  sectionset = NAME
  sectionsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
  referenceprefix = + - TEXT
  pismeno = STYLE BEFEHL
  barva = COLOR
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  stylcisla = STYLE BEFEHL
  barvacisla = COLOR
  propojeni = ABSCHNITT
  vlastnicislo = ano ne
  beforesection = BEFEHL
  aftersection = BEFEHL
  insidesection = BEFEHL
  zvysujicicislo = ano ne seznam prazdne
  umistihlavicku = ano ne skryte prazdne sekce
  cislo = ano ne
  stranka = inherits: \strana
  znaceni = stranka reset
  zahlavi = start stop vysoko zadny normalni prazdne zadneznaceni NAME
  text = start stop vysoko zadny normalni prazdne zadneznaceni NAME
  upati = start stop vysoko zadny normalni prazdne zadneznaceni NAME
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  pokracovat = ano ne
  zarovnejtitul = ano ne plvouciobjekt
  meziradkovamezera = NAME
  interakce = seznam odkaz
  internalgrid = NAME
  mrizka = normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni
  vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line
  math:-halfline NAME
  zarovnani = inherits: \nastavzarovnani
  tolerance = inherits: \nastavtoleranci
  strut = ano ne
  zaveseni = radek široky prizpusobive zadny NUMMER
  marginalie = DIMENSION
  odsadpristi = ano ne auto
  alternativa = text odstavec normalni marginalie naokraji vrsek nastred spodek reverse marginalnitext NAME
  sirka = DIMENSION
  numberwidth = DIMENSION
  sirkatextu = DIMENSION
  vzdalenost = DIMENSION
  textdistance = DIMENSION
  predchoziprikaz = BEFEHL
  prikazpo = BEFEHL
  prikaz = \...##1##2
  textovyprikaz = \...##1
  deeptextcommand = \...##1
  ciselnyprikaz = \...##1
  deepnumbercommand = \...##1
  misto = NAME
  kriterium = striktni pozitiv vse

```

```

\nastavnadpisy [...1,...] [...2,...]
1 ABSCHNITT OPT
2 inherits: \nastavnadpis

```

`\nastavodkazovani [...,*...]`

```
* status      = start stop
  expanzen    = ano ne xml
  autofile    = ano ne
  export      = ano ne
  vlevo       = BEFEHL
  vpravo      = BEFEHL
  sirka       = DIMENSION
  oboustranne = ano ne
  interakce   = popisec text symbol vse
  oddelovac   = BEFEHL
  prefix      = + - TEXT
```

`\nastavodsazovani [...,*...]`

```
* [-+]male [-+]stredni [-+]99%velke zadny ne ne prvni dalsi ano vzdy nikdy liche sude normalni reset toggle DIMENSION NAME
```

`\nastavodstavce [1...] [...,2...] [...,3...]`

```
1 NAME          OPT
2 kazdy NUMBER
3 n             = NUMBER
  pred          = BEFEHL
  po            = BEFEHL
  sirka         = DIMENSION
  vzdalenost    = DIMENSION
  vyska         = DIMENSION prizpusobive
  vrsek         = BEFEHL
  spodek        = BEFEHL
  zarovnani     = inherits: \nastavzarovnani
  vnitrni       = BEFEHL
  prikaz        = BEFEHL
  linka         = zap vyp
  tloustkalinky = DIMENSION
  barvalinky    = COLOR
  pismeno       = STYLE BEFEHL
  barva         = COLOR
```

`\nastavodstavce [1...] [...,2...]`

```
1 NAME:NUMBER  OPT
2 n            = NUMBER
  pred         = BEFEHL
  po           = BEFEHL
  sirka        = DIMENSION
  vzdalenost   = DIMENSION
  vyska        = DIMENSION prizpusobive
  vrsek        = BEFEHL
  spodek       = BEFEHL
  zarovnani    = inherits: \nastavzarovnani
  vnitrni      = BEFEHL
  prikaz       = BEFEHL
  linka        = zap vyp
  tloustkalinky = DIMENSION
  barvalinky   = COLOR
  pismeno      = STYLE BEFEHL
  barva        = COLOR
```

`\nastavopis [...,1...] [...,2...]`

```
1 NAME          OPT
2 lichyokraj     = DIMENSION
  sudamarginalie = DIMENSION
  marginalie     = ano ne standardni DIMENSION
  volba         = mp lua xml parsed-xml nested tex context zadny NAME
  pismeno       = STYLE BEFEHL
  barva         = COLOR
  zarovnani     = inherits: \nastavzarovnani
  radky         = ano ne normalni hyphenated
  mezera        = zap vyp normalni fixne natahnout
  keeptogether  = ano ne
  pred          = BEFEHL
  po            = BEFEHL
  strip         = ano ne NUMBER
  range         = NUMBER NAME
  tab           = ano ne NUMBER
  escape        = ano ne TEXT PROCESSOR->TEXT
  odsadpristi   = ano ne auto
  pokracovat    = ano ne
  start         = NUMBER
  stop          = NUMBER
  krok          = NUMBER
  cislovani     = soubor radek ne
  prazdny       = inherits: \preskoc
```


\nastavoramovanetexty [...,¹...] [...,²...,...]

1 NAME OPT
2 inherits: \setupframedtext

\nastavoramovani [...,¹...] [...,²...,...]

1 NAME OPT
2 roh = pravouhly zaobleny NUMMER
rohramecku = pravouhly zaobleny NUMMER
rohpozadi = pravouhly zaobleny NUMMER
polomer = DIMENSION
polomerramecku = DIMENSION
polomerpozadi = DIMENSION
hloubka = DIMENSION
hloubkaramecku = DIMENSION
hloubkapozadi = DIMENSION
barvaramecku = COLOR
rameceknahore = zap vyp NAME
ramecekdole = zap vyp NAME
ramecekvlevo = zap vyp NAME
ramecekvpravo = zap vyp NAME
region = ano ne
tloustkalinky = DIMENSION
offsetramecku = DIMENSION
ramecek = zap vyp prekryv zadny
pozadi = popredi barevne NAME
offsetpozadi = ramecek DIMENSION
component = NAME
extras = BEFEHL
foregroundstyle = STYLE BEFEHL
foregroundcolor = COLOR
setups = NAME
offset = implicitni prekryv zadny DIMENSION
sirka = lokalne prizpusobive max široky fixne DIMENSION
vyska = prizpusobive max široky DIMENSION
zarovnani = inherits: \nastavzarovnani
strut = ano ne zadny lokalne globalne
autostrut = ano ne
misto = vyska podlehloubky vysoko nizko vrsek nastred spodek radek nivy visici drzet rovnice matematika
normalni
autosirka = ano ne sila
radky = NUMMER
vrsek = BEFEHL
spodek = BEFEHL
prazdny = ano ne
profile = NAME
prazdne = ano ne
loffset = DIMENSION
roffset = DIMENSION
toffset = DIMENSION
boffset = DIMENSION
orientation = NUMMER

\nastavorez [...,*...,...]

* status = start stop
sirka = DIMENSION
vyska = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
x = NUMMER
y = NUMMER
nx = NUMMER
ny = NUMMER
sx = NUMMER
sy = NUMMER
levyoffset = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
mp = NAME
n = NUMMER
offset = DIMENSION

\nastavotoceni [...,*...,...]

* misto = prizpusobive široky podlehloubky vysoko nastred implicitni normalni
rotace = vlevo vpravo uvnitr vnejsi NUMMER
inherits: \nastavoramovani

\nastavpaletu [...*...]

* NAME

\nastavplvouciobjekt [...¹,...] [...²,...]

```

1 SINGULAR OPT
2 odsadpristi = ano ne auto
  implicitni = inherits: \placefloat
  fallback = inherits: \placefloat
  vnitrni = BEFEHL
  kriterium = DIMENSION
  metoda = NUMMER
  sidemethod = NUMMER
  textmethod = NUMMER
  sidealign = vyska podlehloubky radek pulradku mrizka normalni
  mrizka = inherits: \snaptogrid
  lokalne = ano ne
  prikaz = \...##1
  availablewidth = DIMENSION
  availableheight = DIMENSION
  minsirka = DIMENSION
  maxsirka = DIMENSION
  misto = vlevo vpravo nastred flushleft flushright center max uvnitr vnejsi innermargin outermargin
        inneredge outeredge zpetnamezera cutspace lev yokraj prav yokraj levahrana pravahrana

  vzdalenostlevehookraje = DIMENSION
  vzdalenostpravehookraje = DIMENSION
  lev yokraj = DIMENSION
  prav yokraj = DIMENSION
  innermargin = DIMENSION
  outermargin = DIMENSION
  bottombefore = BEFEHL
  bottomafter = BEFEHL
  expanzen = ano ne xml
  referenceprefix = + - TEXT
  xmlsetup = NAME
  catcodes = NAME
  freeregion = ano ne
  mezerapred = zadny inherits: \preskoc
  mezeraza = zadny inherits: \preskoc
  sirka = DIMENSION
  vyska = DIMENSION
  offset = DIMENSION zadny prekryv
  bocnimezerapred = zadny inherits: \preskoc
  bocnimezeraza = zadny inherits: \preskoc
  spacebeforeside = zadny inherits: \preskoc
  spaceafterside = zadny inherits: \preskoc
  sidethreshold = old dimension
  marginalie = DIMENSION
  nvrsek = DIMENSION
  nspondek = DIMENSION
  krok = male stredni velke radek podlehloubky
  nradky = NUMMER
  cache = ano ne

```

\nastavplvouciobjekty [...¹,...] [...²,...]

```

1 SINGULAR OPT
2 inherits: \nastavplvouciobjekt

```

\nastavpodcislostrany [...^{*},...]

```

* inherits: \setupcounter

```

\nastavpole [...¹] [...²,...] [...³,...] [...⁴,...] [...⁵,...]

```

1 NAME OPT OPT OPT OPT
2 reset popisec ramecek horizontalne vertikalne
3 inherits: \setupfieldtotalframed
4 inherits: \setupfieldlabelframed
5 inherits: \setupfieldcontentframed

```

\nastavpolozky [...¹,...] [...²,...]

```

1 NAME OPT
2 alternativa = vlevo vpravo vrsek spodek naokraj
  sirkatextu = DIMENSION
  sirka = DIMENSION
  vzdalenost = DIMENSION
  symbol = zadny NAME
  zarovnani = vlevo nastred vpravo flushleft flushright uvnitr vnejsi marginalie
  textalign = vlevo nastred vpravo flushleft flushright uvnitr vnejsi
  n = NUMMER
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL

```

\nastavpopisek [...,¹...] [...,²...,...]

1 NAME OPT
2 inherits: \setupfloatcaption

\nastavpopisky [...,¹...] [...,²...,...]

1 NAME OPT
2 inherits: \setupfloatcaption

\nastavpozadi [...,¹...] [...,²...,...]

1 NAME OPT
2 status = start stop
levyoffset = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
pred = BEFEHL
po = BEFEHL
inherits: \nastavoramovani

\nastavpozadi [...,¹...] [...,²...,...]

1 papir stranka levastranka pravastranka text skryte OPT
2 status = start stop
inherits: \nastavoramovani

\nastavprechodstrany [...]

* reset auto start nahodny NUMMER

\nastavpreskok [...,^{*}...]

* inherits: \preskoc OPT

\nastavprogramy [...,^{*}...,...]

* pismo = STYLE BEFEHL
barva = COLOR

\nastavradkovani [...]

* fixne zhustene sirok^{OPT}

\nastavradky [...,¹...] [...,²...,...]

1 NAME OPT
2 volba = zhustene
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
odsazovani = inherits: \nastavodsazovani
zarovnani = inherits: \nastavzarovnani
mezera = ano zap vyp fixne implicitni
prikaz = BEFEHL
pismo = STYLE BEFEHL
barva = COLOR
vlevo = BEFEHL
vpravo = BEFEHL

\nastavrejstrik [¹...] [²...,...]

```

1  NAME NAME:NUMMER OPT
2  referencemethod      = vpred
   expanzen             = ano ne xml
   vlastnicislo         = ano ne
   xmlsetup             = NAME
   alternativa          = a b A B
   metoda               = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress             = ano ne vse
   kriterium            = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
   pageprefixconnector  = BEFEHL
   pageprefix           = ano ne
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
   maxsirka             = DIMENSION
   indikator            = ano ne
   pred                 = BEFEHL
   po                   = BEFEHL
   prikaz               = \...##1
   textovyprikaz        = \...##1
   deeptextcommand      = \...##1
   strankovyprikaz      = \...##1
   vzdalenost           = DIMENSION
   interakce            = text cislostranky
   cislostranky         = ano ne
   symbol               = a n zadny 1 2 BEFEHL
   language              = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   pismo                = STYLE BEFEHL
   barva                = COLOR
   styltextu            = STYLE BEFEHL
   barvatextu           = COLOR
   stylstranky          = STYLE BEFEHL
   barvastranky         = COLOR
   n                    = NUMMER
   rovnovaha            = ano ne
   zarovnnani           = inherits: \nastavzarovnnani
   numberorder          = ciska

```

\nastavrejstrik [...,¹...] [...,²...] [...,³...,...]

```

1  NAME                                OPT      OPT
2  NUMMER
3  referencemethod                    = vpred
   expanzen                          = ano ne xml
   vlastnicislo                       = ano ne
   xmlsetup                           = NAME
   alternativa                        = a b A B
   metoda                            = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
   compress                           = ano ne vse zhustene
   kriterium                          = lokalne text aktualni predchozi vse ABSCHNITT
   pageprefixseparatorset             = BEFEHL
   pageprefixconversionset            = NAME
   pageprefixstarter                  = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper                  = BEFEHL PROCESSOR->BEFEHL
   pageprefixset                      = NAME
   pageprefixsegments                 = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
   pageprefixconnector                = BEFEHL
   pageprefix                         = ano ne
   pageseparatorset                   = NAME
   pageconversionset                  = NAME
   pagestarter                        = BEFEHL PROCESSOR->BEFEHL
   pagestopper                        = BEFEHL PROCESSOR->BEFEHL
   pagesegments                       = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
   maxsirka                           = DIMENSION
   indikator                          = ano ne
   pred                               = BEFEHL
   po                                 = BEFEHL
   prikaz                             = \...\##1
   textovyprikaz                      = \...\##1
   deeptextcommand                    = \...\##1
   strankovyprikaz                    = \...\##1
   vzdalenost                         = DIMENSION
   interakce                          = text cislostranky
   cislostranky                       = ano ne
   symbol                             = a n zadny 1 2 BEFEHL
   language                           = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
   pismeno                            = STYLE BEFEHL
   barva                              = COLOR
   styltextu                          = STYLE BEFEHL
   barvatextu                         = COLOR
   stylstranky                        = STYLE BEFEHL
   barvastranky                       = COLOR
   n                                  = NUMBER
   rovnovaha                          = ano ne
   zarovnani                          = inherits: \nastavzarovnani
   numberorder                        = cisla

```

\nastaveniREGISTER [...,¹...] [...,²...,...]

```

1  NUMMER                                OPT
2  inherits: \nastavrejstrik
instances: index

```

\nastaveniindex [...,¹...] [...,²...,...]

```

1  NUMMER                                OPT
2  inherits: \nastavrejstrik

```

\nastavrovnice [...,¹...] [...,²...,...]

```

1  NAME                                OPT
2  inherits: \setupformula

```

\nastavsadusymbolu [...]

```

*  NAME

```

```

\nastavseznam [...,1...] [...,2...,...]
1 LISTE
2 status = start stop
   misto = zadny zde
   typ = simple prikaz userdata
   kriterium = lokalne uvod odkaz SECTIONBLOCK:odkaz vse SECTIONBLOCK:vse text SECTIONBLOCK:text aktualni
               SECTIONBLOCK:aktualni zde predchozi SECTIONBLOCK:predchozi komponenta ABSCHNITT SECTIONBLOCK:ABSCHNITT

   seznam = NAME
   sirka = prizpusobive siroky auto DIMENSION
   vyska = prizpusobive siroky DIMENSION
   hloubka = prizpusobive siroky DIMENSION
   symbol = jedna dve tri zadny implicitni
   popisek = ano ne zadny NAME
   starter = BEFEHL
   predel = BEFEHL
   prikaz = \...##1##2##3
   ciselnyprikaz = \...##1
   textovyprikaz = \...##1
   strankovyprikaz = \...##1
   cislostranky = ano ne vzdy
   cislonadpisu = ano ne vzdy
   pred = BEFEHL
   po = BEFEHL
   mezi = BEFEHL
   marginalie = zadny DIMENSION
   vzdalenost = zadny DIMENSION
   zarovnejtitul = ano ne
   numberalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   zarovnani = inherits: \nastavzarovnani
   zaveseni = ano ne
   vlevo = BEFEHL
   vpravo = BEFEHL
   interakce = ano ne vse cislo text titul stranka cislooddilu cislostranky
   limittext = ano ne TEXT
   pismeno = STYLE BEFEHL
   barva = COLOR
   stylcisla = STYLE BEFEHL
   barvacisla = COLOR
   styltextu = STYLE BEFEHL
   barvatextu = COLOR
   stylstranky = STYLE BEFEHL
   barvastranky = COLOR
   odkaz = NUMMER
   extras = NAME
   order = prikaz vse titul
   alternativa = a b c d e f g vlevo vpravo vrsek spodek prikaz zadny interactive odstavec horizontalne vertikalne
               NAME
               DIMENSION
   maxsirka = DIMENSION
   pageprefix = ano ne
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
   pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
   pageconversionset = NAME
   pagestarter = BEFEHL PROCESSOR->BEFEHL
   pagestopper = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \nastavoramovani

```

```

\nastavsirkucary [...]
* male stredni velke DIMENSION

```

```

\nastavsloupce [...,*...,...]
* n = NUMMER
  vzdalenost = DIMENSION
  volba = pozadi
  offset = DIMENSION
  prikaz = \...##1
  vyska = DIMENSION
  smer = vlevo vpravo
  rovnovaha = ano ne
  zarovnani = setupalign
  tolerance = setuptolerance
  prazdny = inherits: \preskoc
  nvrsek = NUMMER
  linka = zap vyp BEFEHL

```

```

\nastavspodek [...,1] [...,2...,...]
1 text marginalie HfTana
2 inherits: \setuplayoutelement

```

\nastavsynonyma [...¹,...] [...²,...]

1 SINGULAR OPT
2 expanzen = ano ne xml
alternativa = prvni posledni normalni NAME
dalsi = BEFEHL
prikaz = \...##1##2##3
textovyprikaz = \...##1
synonymcommand = \...##1
language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc
kriterium = aktualni predchozi lokalne text vse ABSCHNITT
pismo = STYLE BEFEHL
barva = COLOR
styltextu = STYLE BEFEHL
barvatextu = COLOR
styleynonyma = STYLE BEFEHL
barvasynonyma = COLOR

\nastavtabelaci [...¹] [...²] [...³,...]

1 NAME OPT OPT
2 NAME
3 inherits: \setuptabulation

\nastavtabulky [...^{*},...]

* text = DIMENSION max
split = ano ne opakovat auto
ramecek = zap vyp
NL = inherits: \preskoc
VL = male stredni velke zadny NUMMER
HL = male stredni velke zadny NUMMER
vzdalenost = male stredni velke zadny
zarovnani = vlevo nastred vpravo
prikazy = BEFEHL
zakladnifont = inherits: \nastavzakladnifont
tloustkalinky = DIMENSION
vyska = strut NUMMER
hloubka = strut NUMMER
openup = DIMENSION

\nastavtenkelinky [...^{*},...]

* vyska = max DIMENSION
hloubka = max DIMENSION
pozadi = barevne
ramecek = zap vyp
tloustkalinky = DIMENSION
alternativa = a b c zadny
barvapozadi = COLOR
barva = COLOR
meziradkovamezera = male stredni velke NUMMER
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
n = NUMMER

\nastavtext [...¹] [...²,...]

1 text marginali^{OPT}hrana
2 inherits: \setuplayoutelement

\nastavtextovelinky [...^{*},...]

* pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
tloustkalinky = DIMENSION
misto = vlevo naokraji
pismo = STYLE BEFEHL
barva = COLOR
barvalinky = COLOR
sirka = DIMENSION
vyska = DIMENSION
vzdalenost = DIMENSION
korekcehloubky = zap vyp
zakladnifont = inherits: \nastavzakladnifont

\nastaveniLABELtext [...¹] [...²,...]

1 SPRACHE OPT
2 KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

<p><code>\nastavenibtxlabeltext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastaveniheadtext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastavenilabeltext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastavenimathlabeltext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastavenioperatortext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastaveniprefixtext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastavenisuffixtext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastavenitaglabeltext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastaveniunittext [...]¹ [...,...²...,...]</code></p> <p>1 SPRACHE OPT</p> <p>2 KEY = VALUE</p>
<p><code>\nastavtexttexty [...]¹ [...]² [...]³ [...]⁴ [...]⁵</code></p> <p>1 text marginalie hrana^{PT} OPT OPT OPT OPT OPT</p> <p>2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p>
<p><code>\nastavtextyupati [...]¹ [...]² [...]³ [...]⁴ [...]⁵</code></p> <p>1 text marginalie hrana^{PT} OPT OPT OPT OPT OPT</p> <p>2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p>
<p><code>\nastavtextyzahlavi [...]¹ [...]² [...]³ [...]⁴ [...]⁵</code></p> <p>1 text marginalie hrana OPT OPT OPT OPT OPT</p> <p>2 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>3 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p> <p>5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL</p>
<p><code>\nastavtoleranci [...,*,...]</code></p> <p>* horizontalne vertikalne velmistriktni striktni tolerantni velmitolerantni mezera natahnout</p>

`\nastavtrideni [...1,...] [...2,...]`

```
1 SINGULAR OPT
2 expanden = ano ne xml
  alternativa = prvi posledni normalni NAME
  dalsi = BEFEHL
  prikaz = \...##1##2##3
  textovyprikaz = \...##1
  synonymcommand = \...##1
  language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
  metoda = implicitni pred po prvi posledni ch mm zm pm mc zc pc uc
  kriterium = aktualni predchozi lokalne text vse ABSCHNITT
  pismo = STYLE BEFEHL
  barva = COLOR
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  stylsynonyma = STYLE BEFEHL
  barvasynonyma = COLOR
```

`\nastavtype [...1,...] [...2,...]`

```
1 NAME OPT
2 volba = mp lua xml parsed-xml nested tex context zadny NAME
  prikaz = CSNAME
  vlevo = BEFEHL
  vpravo = BEFEHL
  tab = ano ne NUMMER
  compact = absolutni posledni vse
  escape = ano ne TEXT PROCESSOR->TEXT
  pismo = STYLE BEFEHL
  barva = COLOR
  radky = ano ne normalni hyphenated
  mezera = zap vyp normalni fixne natahnout
```

`\nastavumisteniprotejsku [...*,...]`

```
* status = start stop
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
```

`\nastavumistovani [...1,...] [...2,...]`

```
1 NAME OPT
2 offset = ano ne
  jednotka = ex em pt in cm mm sp bp pc dd cc nc
  status = start prekryv
  xoffset = DIMENSION
  yoffset = DIMENSION
  xkrok = absolutni relativni
  ykrok = absolutni relativni
  xmeritko = NUMMER
  ymeritko = NUMMER
  xfaktor = NUMMER
  yfaktor = NUMMER
  faktor = NUMMER
  meritko = NUMMER
```

`\nastavupati [...1,...] [...2,...]`

```
1 text marginalieOPTtrana
2 inherits: \setuplayoutelement
```

\nastavupravu [...¹,...] [...²,...]

```
1  NAME                      OPT
2  stranka                   = inherits: \strana
   prikaz                    = BEFEHL
   sirka                     = DIMENSION
   vyska                     = DIMENSION
   zarovnani                 = inherits: \nastavzarovnani
   setups                    = NAME
   vrsek                     = BEFEHL
   spodek                    = BEFEHL
   pred                      = BEFEHL
   po                        = BEFEHL
   misto                     = vrsek
   odkaz                     = REFERENCE
   pagestate                 = start stop
   statuszhlavi              = start stop vysoko prazdne zadny normalni
   statusupati               = start stop vysoko prazdne zadny normalni
   statusvrsku               = start stop vysoko prazdne zadny normalni
   statusspodku              = start stop vysoko prazdne zadny normalni
   statustextu               = start stop vysoko prazdne zadny normalni
   oboustranne               = ano ne prazdne
   pismeno                   = STYLE BEFEHL
   barva                     = COLOR
```

\nastavurl [...^{*},...]

```
*  pismeno = STYLE BEFEHL
   barva   = COLOR
```

\nastavusporadani [...^{*},...]

```
*  zablokovat zrcadleno dvoustranny negativ 90 180 270 reset pozadi normalni 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP 2DOWN 2*4*2
   2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW 1*2-Conference
   1*4-Conference 2*2*2 2*2*3 XY NAME
```

\nastavvelikostpapiru [...¹,...] [...²,...]

```
1  NAME                      OPT
2  vrsek                     = BEFEHL
   spodek                    = BEFEHL
   vlevo                     = BEFEHL
   vpravo                    = BEFEHL
   metoda                   = normalni zadny NAME
   meritko                  = NUMMER
   nx                       = NUMMER
   ny                       = NUMMER
   dx                       = DIMENSION
   dy                       = DIMENSION
   sirka                    = DIMENSION
   vyska                    = DIMENSION
   svrchnamezera            = DIMENSION
   zpetnamezera             = DIMENSION
   offset                   = DIMENSION
   stranka                  = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
   papir                    = reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
   volba                    = prizpusobive max
   vzdalenost               = DIMENSION
```

\nastavvelikostpapiru [...¹,...] [...²,...]

```
1  reset nasirku zrcadleno negativOPT otoceno 90OPT 180 270 NAME
2  reset nasirku zrcadleno negativ otoceno 90 180 270 NAME
```

\nastavvsechnapole [...¹,...] [...²,...] [...³,...] [...⁴,...]

```
1  reset popisec ramecek horizontalneOPT vertikalneOPT
2  inherits: \setupfieldtotalframed
3  inherits: \setupfieldlabelframed
4  inherits: \setupfieldcontentframed
```

\nastavvycty [...¹,...] [...²,...]

```
1  NAME                      OPT
2  inherits: \setupenumeration
```

\nastavvyplnovelinky [...,..^{*}...,...]

```
*   pred      = BEFEHL
    po        = BEFEHL
    n         = NUMMER
    meziradkovamezera = male stredni velke NUMMER
    vzdalenost = DIMENSION
    sirka      = prizpusobive siroky DIMENSION
    oddelovac  = BEFEHL
    pismeno    = STYLE BEFEHL
    barva      = COLOR
```

\nastavvyplnoveradky [...,..^{*}...,...]

```
*   pred      = BEFEHL
    po        = BEFEHL
    marginalie = DIMENSION
    sirka      = DIMENSION
    vzdalenost = DIMENSION
    tloustkalinky = DIMENSION
    barva      = COLOR
```

\nastavvzhled [...,..¹...] [...,..²...,...]

```
1  NAME      OPT
2  status    = start stop normalni opakovat
    marginalie = DIMENSION
    hrana     = DIMENSION
    vzdalenostokraje = DIMENSION
    vzdalenosthrany = DIMENSION
    vzdalenostlevehrany = DIMENSION
    vzdalenostpravehrany = DIMENSION
    vzdalenostlevehookraje = DIMENSION
    vzdalenostpravehookraje = DIMENSION
    vzdalenostvrsku = DIMENSION
    vzdalenostzahlavi = DIMENSION
    vzdalenostupati = DIMENSION
    vzdalenostspodku = DIMENSION
    prednastaveni = NAME
    levyokraj    = DIMENSION
    pravyokraj   = DIMENSION
    levahrana    = DIMENSION
    pravahrana   = DIMENSION
    zahlavi      = DIMENSION
    upati        = DIMENSION
    vrsek        = DIMENSION
    spodek       = DIMENSION
    zpetnamezera = DIMENSION
    svrchnimezera = DIMENSION
    setups       = NAME
    cutspace     = DIMENSION
    sirka        = DIMENSION nastred prizpusobive
    bottomspace  = DIMENSION
    radky        = NUMMER
    vyska        = DIMENSION nastred prizpusobive
    horoffset    = DIMENSION
    offsethlavicky = DIMENSION
    sloupce      = NUMMER
    vzdalenostsloupce = DIMENSION
    metoda       = implicitni normalni NAME
    misto        = vlevo nastred vpravo vrsek spodek jednostranne dvoustranny
    sirkatextu   = DIMENSION
    vyskatextu   = DIMENSION
    nx           = NUMMER
    ny           = NUMMER
    dx           = DIMENSION
    dy           = DIMENSION
    meritko      = NUMMER
    sx           = NUMMER
    sy           = NUMMER
    znaceni      = zap vyp stranka prazdne barevne jedna dve ctyri
    mrizka       = ano ne vyp
    textdistance = DIMENSION
    alternativa  = implicitni normalni zlom NAME
    clipoffset   = DIMENSION
    cropoffset   = DIMENSION
    trimoffset   = DIMENSION
    bleedoffset  = DIMENSION
    artoffset    = DIMENSION
```

\nastavvzhled [...,..^{*}...]

```
*   reset NAME
```

<p>\nastavzahnavi [...] [...] ²</p> <p>1 text marginalie hr^{OPT}a</p> <p>2 inherits: \setuplayoutelement</p>
<p>\nastavzakladnifont [...]*...]</p> <p>* DIMENSION NAME globalne reset x xx male velke script scriptscript rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke</p>
<p>\nastavzarovnnani [...]*...]</p> <p>* široky siroce spodek vyska radek vysoko nizko nivy flushright flushleft nastred ano ne sirka normalni reset uvnitr vnejsi flushinner flushouter vlevo vpravo center zablokovat posledni end odstavec lefttoright righttoleft l2r r2l tabulka lessshyphenation morehyphenation visici nothanging hz fullhz nohz hyphenated nothyphenated tolerantni velmitolerantni natahnout extremestretch finalni 1*final 2*final 3*final 4*final more 1*more 2*more</p>
<p>\nastavznaceni [...] ¹ [...] ²</p> <p>1 BESCHRIFTUNG ^{OPT}</p> <p>2 status = start stop</p> <p>expanden = ano ne</p> <p>oddelovac = BEFEHL</p> <p>filtercommand = \...##1</p>
<p>\nastavzuzeni [...] ¹ [...] ²</p> <p>1 NAME ^{OPT}</p> <p>2 vlevo = DIMENSION</p> <p>stredni = DIMENSION</p> <p>vpravo = DIMENSION</p> <p>implicitni = [-+]vlevo [-+]nastred [-+]vpravo NUMMER*vlevo NUMMER*nastred NUMMER*vpravo reset</p> <p>pred = BEFEHL</p> <p>po = BEFEHL</p>
<p>\nastrane [...]</p> <p>* REFERENCE</p>
<p>\nastred ...</p> <p>* CHARACTER</p>
<p>\naturalhbox [...] ¹ {...} ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalhpack [...] ¹ {...} ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvbox [...] ¹ {...} ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvcenter [...] ¹ {...} ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvpack [...] ¹ {...} ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalvtop [...] ¹ {...} ²</p> <p>1 TEXT ^{OPT}</p> <p>2 CONTENT</p>
<p>\naturalwd ...</p> <p>* CSNAME NUMMER</p>
<p>\negatecolorbox ...</p> <p>* CSNAME NUMMER</p>

<code>\negated {...}</code> * TEXT
<code>\negthinspace</code>
<code>\nejakyradek [...]</code> * REFERENCE
<code>\nekde {.¹.} {.².} [.³.]</code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\newattribute *..</code> * CSNAME
<code>\newcatcodetable *..</code> * CSNAME
<code>\newcounter *..</code> * CSNAME
<code>\newevery \.¹. \.².]</code> 1 CSNAME 2 CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> * NAME
<code>\newsignal *..</code> * CSNAME
<code>\newsystemmode {...}</code> * NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...]¹ [...]²]</code> 1 NAME 2 NUMBER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>

<code>\dalsiPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...] [...]</code> 1 NAME 2 NUMBER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\neznamo</code>
<code>\nivy [...] {...} {...}</code> 1 vlevo ^{OPT} pravo 2 CONTENT 3 CONTENT
<code>\nizky {...}</code> * CONTENT
<code>\LOW {...}</code> * CONTENT instances: unitslow
<code>\unitslow {...}</code> * CONTENT
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \... {...}</code> 1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheightstrut</code>
<code>\noindentation</code>

<code>\noitem</code>
<code>\nokap {...}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\normalboldface</code>
<code>\normalframedwithsettings [...¹...²...] {...}</code> 1 inherits: \nastavoramovani 2 CONTENT
<code>\normalitalicface</code>
<code>\normalizebodyfontsize \¹... {²...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontline \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontwidth \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizetextdepth {¹...} {²...} {³...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextheight {¹...} {²...} {³...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextline {¹...} {²...} {³...}</code> 1 FONT 2 DIMENSION 3 TEXT

<code>\normalizetextwidth {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalni</code>
<code>\normalslantedface</code>
<code>\normaltypeface</code>
<code>\notesymbol [...] [...]</code> 1 NAME 2 REFERENCE
<code>\notragged</code>
<code>\ntimes {...} {...}</code> 1 TEXT 2 NUMMER
<code>\numberofpoints {...}</code> * DIMENSION
<code>\obeydepth</code>
<code>\objectdepth</code>
<code>\objectheight</code>
<code>\objectmargin</code>
<code>\objectwidth</code>
<code>\obox {...}</code> * CONTENT
<code>\obrazovka [...]*...]</code> * inherits: \strah
<code>\odkaz [...¹,...] {...}</code> 1 REFERENCE 2 TEXT
<code>\odkaznastranu [...]*...]</code> * REFERENCE
<code>\odkaznatext [...¹,...] {...}</code> 1 REFERENCE 2 TEXT
<code>\odkazujici (...¹,...) (...²,...) [...]</code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\offset [...,...¹,...] {...}</code> 1 inherits: \setupoffset 2 CONTENT

<p>\offsetbox [...¹...] \² {...³}</p> <p>1 inherits: \setupoffsetbox^{OPT}</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p>\onedigitrounding {...}</p> <p>* NUMMER</p>
<p>\opis [...¹...] {...²}</p> <p>1 inherits: \nastavopis^{OPT}</p> <p>2 CONTENT</p>
<p>\opissoubor [...¹] [...²...] {...³}</p> <p>1 NAME^{OPT}</p> <p>2 inherits: \nastavopis</p> <p>3 FILE^{OPT}</p>
<p>\opis [...¹...] <<...²>></p> <p>1 inherits: \nastavtype^{OPT}</p> <p>2 ANGLES</p>
<p>\OPIS [...¹...] {...²}</p> <p>1 inherits: \nastavtype^{OPT}</p> <p>2 CONTENT</p>
<p>\OPIS [...¹...] <<...²>></p> <p>1 inherits: \nastavtype^{OPT}</p> <p>2 ANGLES</p>
<p>\oramovani [...¹...] {...²}</p> <p>1 inherits: \nastavoramovani^{OPT}</p> <p>2 CONTENT</p>
<p>\FRAMED [...¹...] {...²}</p> <p>1 inherits: \nastavoramovani^{OPT}</p> <p>2 CONTENT</p> <p>instances: unframed fitfieldframed</p>
<p>\fitfieldframed [...¹...] {...²}</p> <p>1 inherits: \nastavoramova^{OPT}</p> <p>2 CONTENT</p>
<p>\unframed [...¹...] {...²}</p> <p>1 inherits: \nastavoramovani^{OPT}</p> <p>2 CONTENT</p>
<p>\FRAMEDTEXT [...¹...] {...²}</p> <p>1 inherits: \setupframedtext^{OPT}</p> <p>2 CONTENT</p> <p>instances: framedtext</p>
<p>\framedtext [...¹...] {...²}</p> <p>1 inherits: \setupframedtext^{OPT}</p> <p>2 CONTENT</p>
<p>\ordinaldaynumber {...}</p> <p>* NUMMER</p>
<p>\ordinalstr {...}</p> <p>* TEXT</p>
<p>\oref [...]</p> <p>* REFERENCE</p>

$\backslash\text{orez}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] $\{\dots\}$ 1 inherits: $\backslash\overset{\text{RET}}{\text{nastavorez}}$ 2 CONTENT
$\backslash\text{ornamenttext}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] [\dots , \dots , $\overset{2}{=}\dots$, \dots] $\{\dots\}$ $\{\dots\}$ 1 alternativa = a b OPT inherits: $\backslash\text{setupcollector}$ 2 pismo = STYLE BEFEHL barva = COLOR inherits: $\backslash\text{nastavoramovani}$ 3 TEXT 4 CONTENT
$\backslash\text{ornamenttext}$ [$\overset{1}{.}\dots$] $\{\overset{2}{.}\dots\}$ $\{\overset{3}{.}\dots\}$ 1 NAME 2 TEXT 3 CONTENT
$\backslash\text{ornamenttext}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] [\dots , \dots , $\overset{2}{=}\dots$, \dots] $\{\dots\}$ $\{\dots\}$ 1 alternativa = a b OPT inherits: $\backslash\text{setuplayer}$ 2 inherits: $\backslash\text{setuplayeredtext}$ 3 TEXT 4 CONTENT
$\backslash\text{ORNAMENT}$ $\{\overset{1}{.}\dots\}$ $\{\overset{2}{.}\dots\}$ 1 TEXT 2 CONTENT
$\backslash\text{otocit}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] $\{\overset{2}{.}\dots\}$ 1 inherits: $\backslash\overset{\text{OPT}}{\text{nastavotoceni}}$ 2 CONTENT
$\backslash\text{outputfilename}$
$\backslash\text{outputstreambox}$ [\dots] * NAME
$\backslash\text{outputstreamcopy}$ [\dots] * NAME
$\backslash\text{outputstreamunvbox}$ [\dots] * NAME
$\backslash\text{outputstreamunvcopy}$ [\dots] * NAME
$\backslash\text{over}$ [\dots] * REFERENCE
$\backslash\text{overlaybutton}$ [\dots] * REFERENCE
$\backslash\text{overlaybutton}$ $\{\dots\}$ * REFERENCE
$\backslash\text{overlaycolor}$
$\backslash\text{overlaydepth}$
$\backslash\text{overlayfigure}$ $\{\dots\}$ * FILE

<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton</code> [¹ ...] [² ...] 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overloaderror</code>
<code>\overset</code> { ¹ ...} { ² ...} 1 TEXT 2 TEXT
<code>\oznaceni</code> (... ¹ ,...) (... ² ,...) [... ³ _{OPT} ...,...] { ⁴ ...} 1 POSITION 2 POSITION 3 inherits: \nastavoramovani 4 TEXT
<code>\PDFcolor</code> { [*] ...} * NAME
<code>\PDFETEX</code>
<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints</code> { ¹ ...} \ ² ... 1 DIMENSION 2 CSNAME
<code>\PointsToReal</code> { ¹ ...} \ ² ... 1 DIMENSION 2 CSNAME
<code>\PointsToWholeBigPoints</code> { ¹ ...} \ ² ... 1 DIMENSION 2 CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm</code> { [*] ...} * DIMENSION

<p>\pagearea [¹...] [²...] [³...]</p> <p>1 vrsek zhlavi text ^{OPT}upati ^{OPT}spódek</p> <p>2 text marginalie hrana</p> <p>3 vlevo vpravo lefttext middletext righttext</p>
<p>\pagebreak [...[*]...]</p> <p>[*] prazdne zhlavi ^{OPT}upati dummy ramecek NUMMER +NUMMER implicitni reset zablokovat ano ne zlom prazdny nastaveni vysokapriorita vlevo vpravo sude liche ctynasobny posledni poslednistrana start stop NAME</p>
<p>\pagefigure [¹...] [...²...]</p> <p>1 FILE ^{OPT}</p> <p>2 offset = implicitni prekryv zadny DIMENSION</p>
<p>\pagegridspanwidth {[*]...}</p> <p>[*] NUMMER</p>
<p>\pageinjection [¹...] [...²...]</p> <p>1 NAME ^{OPT} ^{OPT}</p> <p>2 KEY = VALUE</p>
<p>\pageinjection [...¹...] [...²...]</p> <p>1 inherits: \setuppageinjection ^{OPT}</p> <p>2 KEY = VALUE</p>
<p>\pagestaterealpage {¹...} {²...}</p> <p>1 NAME</p> <p>2 NAME NUMMER</p>
<p>\paletsize</p>
<p>\PARAGRAPHS</p>
<p>\pdfactualtext {¹...} {²...}</p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p>\pdfbackendactualtext {¹...} {²...}</p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p>\pdfbackendcurrentresources</p>
<p>\pdfbackendsetcatalog {¹...} {²...}</p> <p>1 NAME</p> <p>2 TEXT</p>
<p>\pdfbackendsetcolorspace {¹...} {²...}</p> <p>1 NAME</p> <p>2 TEXT</p>
<p>\pdfbackendsettextgstate {¹...} {²...}</p> <p>1 NAME</p> <p>2 TEXT</p>
<p>\pdfbackendsetinfo {¹...} {²...}</p> <p>1 NAME</p> <p>2 TEXT</p>
<p>\pdfbackendsetname {¹...} {²...}</p> <p>1 NAME</p> <p>2 TEXT</p>

<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\percent</code></p>
<p><code>\percentdimen {...} {...}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMBER</p>
<p><code>\permitcaretescape</code></p>
<p><code>\permitcircumflexescape</code></p>
<p><code>\permitspacesbetweengroups</code></p>
<p><code>\persiandecimals {...}</code></p> <p>* NUMBER</p>
<p><code>\persiannumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\phantom {...}</code></p> <p>* CONTENT</p>
<p><code>\phantombox [..., ...[*]..., ...]</code></p> <p>* sirka = DIMENSION</p> <p>* vyska = DIMENSION</p> <p>* hloubka = DIMENSION</p>
<p><code>\pickupgroupedcommand {...} {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p>
<p><code>\pis [..., ...¹..., ...] {...}</code></p> <p>1 inherits: $\stackrel{\text{?}}{\text{?}}$</p> <p>2 CONTENT</p>

<p><code>\pis [...¹...<...>]</code></p> <p>1 inherits: \mathbb{P}^T hastavtype</p> <p>2 ANGLES</p>
<p><code>\placeattachments</code></p>
<p><code>\placebtxrendering [...¹] [...²...]</code></p> <p>1 NAME OPT OPT</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placecitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\placecomments</code></p>
<p><code>\placecurrentformulanumber</code></p>
<p><code>\placedbox {...}</code></p> <p>* CONTENT</p>
<p><code>\placefloat [...¹] [...²...] [...³...] {...⁴} {...⁵}</code></p> <p>1 SINGULAR OPT OPT</p> <p>2 split vzdý vlevo vpravo uvnitř vnější zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokálne zde síla marginalie [--]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placefloatwithsetups [...¹] [...²...] [...³...] {...⁴} {...⁵}</code></p> <p>1 NAME OPT OPT</p> <p>2 split vzdý vlevo vpravo uvnitř vnější zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokálne zde síla marginalie [--]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\umistiFLOAT [...¹...] [...²...] {...³} {...⁴}</code></p> <p>1 split vzdý vlevo vpravo uvnitř vnější zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokálne zde síla marginalie [--]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p> <p>instances: chemical figure table intermezzo graphic</p>
<p><code>\umistifigure [...¹...] [...²...] {...³} {...⁴}</code></p> <p>1 split vzdý vlevo vpravo uvnitř vnější zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokálne zde síla marginalie [--]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\umistigraphic [...¹...] [...²...] {...³} {...⁴}</code></p> <p>1 split vzdý vlevo vpravo uvnitř vnější zpetnamezera cutspace ivlevo ivpravo naokraj levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokálne zde síla marginalie [--]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>

<p><code>\umistischechemical [...¹,...] [...²,...] {...³} {...⁴}</code></p> <p>1 split vzdy vľavo vpravo^{OPT} uvnitr^{OPT} vnejsi^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levyokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\umistiintermezzo [...¹,...] [...²,...] {...³} {...⁴}</code></p> <p>1 split vzdy vľavo vpravo^{OPT} uvnitr^{OPT} vnejsi^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levyokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\umistitable [...¹,...] [...²,...] {...³} {...⁴}</code></p> <p>1 split vzdy vľavo vpravo^{OPT} uvnitr^{OPT} vnejsi^{OPT} zpetnamezera cutspace ivľavo ivpravo naokraji levyokraj pravýokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mřizka vysoko nízko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\placeframed [...¹] [...²,...²,...] {...³}</code></p> <p>1 NAME</p> <p>2 inherits: \nastavoramovani</p> <p>3 CONTENT</p>
<p><code>\placeheadnumber [...]</code></p> <p>* ABSCHNITT</p>
<p><code>\placeheadtext [...]</code></p> <p>* ABSCHNITT</p>
<p><code>\placehelp</code></p>
<p><code>\placeinitial [...]</code></p> <p>* NAME</p>
<p><code>\placelayer [...]</code></p> <p>* NAME</p>
<p><code>\placelayeredtext [...¹] [...²,...²,...] [...³,...³,...] {...⁴} {...⁵}</code></p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placelistofFLOATS [...¹,...¹,...]</code></p> <p>* inherits: \nastavseznam</p> <p>instances: chemicals figures tables intermezzi graphics</p>
<p><code>\placelistoffigures [...¹,...¹,...]</code></p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistofgraphics [...¹,...¹,...]</code></p> <p>* inherits: \nastavseznam</p>
<p><code>\placelistofchemicals [...¹,...¹,...]</code></p> <p>* inherits: \nastavseznam</p>

$\backslash\text{placelistofintermezzi}$ [... [*] ...] * inherits: \nastavseznam OPT
$\backslash\text{placelistoftables}$ [... [*] ...] * inherits: \nastavseznam OPT
$\backslash\text{placelistofpublications}$ [... ¹] [... ² ...] 1 NAME OPT 2 inherits: \setupbtxrendering OPT
$\backslash\text{placelistofsorts}$ [... ¹] [... ² ...] 1 SINGULAR OPT 2 inherits: \nastavtrideni
$\backslash\text{placelistofSORTS}$ [... [*] ...] * inherits: \nastavtrideni OPT instances: logos
$\backslash\text{placelistoflogos}$ [... [*] ...] * inherits: \nastavtrideni OPT
$\backslash\text{placelistofsynonyms}$ [... ¹] [... ² ...] 1 SINGULAR OPT 2 inherits: \nastavsynonyma
$\backslash\text{placelistofSYNONYMS}$ [... [*] ...] * inherits: \nastavsynonyma OPT instances: abbreviations
$\backslash\text{placelistofabbreviations}$ [... [*] ...] * inherits: \nastavsynonyma OPT
$\backslash\text{placelocalnotes}$ [... ¹] [... ² ...] 1 NAME OPT 2 inherits: \setupnote
$\backslash\text{placement}$ [... ¹] [... ² ...] {... ³ } 1 NAME OPT 2 inherits: \setupplacement 3 CONTENT
$\backslash\text{PLACEMENT}$ [... ¹ ...] {... ² } 1 inherits: \setupplacement OPT 2 CONTENT
$\backslash\text{placenamedfloat}$ [... ¹] [... ²] 1 NAME 2 REFERENCE
$\backslash\text{placenamedformula}$ [... ¹ ...] {... ² } 1 + - REFERENCE OPT 2 TEXT
$\backslash\text{placenotes}$ [... ¹ ...] [... ² ...] 1 NAME OPT 2 inherits: \setupnote
$\backslash\text{placepagenumber}$

<p>\placepairedbox [¹...] [²...²...²] {...³} {...⁴}</p> <p>1 NAME OPT</p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>
<p>\umistiPAIREDBOX [¹...¹...¹] {...²} {...³}</p> <p>1 inherits: \setuppairedbox OPT</p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances: legend</p>
<p>\umistilegend [¹...¹...¹] {...²} {...³}</p> <p>1 inherits: \setuppairedbox OPT</p> <p>2 CONTENT</p> <p>3 TEXT</p>
<p>\placeparallel [¹...] [²...²...²] [³...³...³]</p> <p>1 NAME OPT</p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p>\placerawlist [¹...] [²...²...²]</p> <p>1 LISTE OPT</p> <p>2 inherits: \nastavseznam</p>
<p>\placereadingwindow [¹...] [²...²]</p> <p>1 NAME OPT</p> <p>2 NAME</p>
<p>\plnezneni {...}</p> <p>* NAME</p>
<p>\pole [¹...] [²...²]</p> <p>1 NAME OPT</p> <p>2 TEXT</p>
<p>\polozka [...[*]...]</p> <p>* REFERENCE OPT</p>
<p>\polozky [¹...¹...¹] {...²}</p> <p>1 inherits: \nastavpolozky OPT</p> <p>2 TEXT</p>
<p>\popattribute *...</p> <p>* CSNAME</p>
<p>\POPIS [¹...¹...¹] {...²} ...³ \par</p> <p>1 REFERENCE OPT OPT</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p>\popmacro *...</p> <p>* CSNAME</p>
<p>\popmode [...]</p> <p>* NAME</p>
<p>\POPISEK [¹...¹...¹] {...²}</p> <p>1 REFERENCE OPT OPT</p> <p>2 TEXT</p>
<p>\popsystemmode {...}</p> <p>* NAME</p>

\porovnejpaletu [...] * NAME
\porovnejskupinubarev [...] * NAME
\positionoverlay {...} * NAME
\positionregionoverlay {...} {...} 1 NAME 2 NAME
\poslaednipodstranka
\postponenotes
\pozadi {...} * CONTENT
\POZADI {...} * CONTENT instances: pozadi
\pozice [...,.. ¹ ...,...] (..., ² ...) {... ³ } 1 inherits: \nastavumistovani ^{OPT} 2 POSITION 3 CONTENT
\poznanka [... ¹ ...] [... ²] 1 NAME ^{OPT} 2 REFERENCE
\NOTE [..., ¹ ...] {... ² } 1 REFERENCE ^{OPT} 2 TEXT instances: footnote endnote
\NOTE [...,.. [*] ...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE instances: footnote endnote
\endnote [...,.. [*] ...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE
\footnote [...,.. [*] ...,...] * titul = TEXT zalozka = TEXT seznam = TEXT odkaz = REFERENCE
\endnote [..., ¹ ...] {... ² } 1 REFERENCE ^{OPT} 2 TEXT
\footnote [..., ¹ ...] {... ² } 1 REFERENCE ^{OPT} 2 TEXT

<code>\pravidelne</code>
<code>\predefinedfont [...]</code> <code>* FONT</code>
<code>\predefinefont [...]¹ [...]²</code> <code>1 NAME</code> <code>2 FONT</code>
<code>\predefinesymbol [...]</code> <code>* NAME</code>
<code>\pref {...}¹ {...}² [...]³</code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code> <code>3 REFERENCE</code>
<code>\prefixedpagenumber</code>
<code>\prelozit [...][*]...]</code> <code>* SPRACHE = TEXT OPT</code>
<code>\prependetoks ...¹ \to ...²</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\prependgvalue {...}¹ {...}²</code> <code>1 NAME</code> <code>2 BEFEHL</code>
<code>\prependtocommalist {...}¹ ...²</code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\prependtoks ...¹ \to ...²</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\prependtoksonce ...¹ \to ...²</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\prependvalue {...}¹ {...}²</code> <code>1 NAME</code> <code>2 BEFEHL</code>
<code>\prepninazakladnifont [...][*]...]</code> <code>* inherits: \nastavzakladnifont</code>
<code>\presetdocument [...][*]...]</code> <code>* inherits: \setupdocument</code>
<code>\presetfieldsymbols [...][*]...]</code> <code>* NAME</code>
<code>\presetLABELtext [...]¹ [...]²...]</code> <code>1 SPRACHE OPT</code> <code>2 KEY = VALUE</code> <code>instances: head label mathlabel taglabel unit operator prefix suffix btxlabel</code>

<pre> \presetbtxlabeltext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetheadtext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetlabeltext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetmathlabeltext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetoperatortext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetprefixtext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetsuffixtext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presettaglabeltext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \presetunittext [...] [...] 1 SPRACHE 2 KEY = VALUE </pre>
<pre> \preskoc [...]*[...] * nastaveni stejhastranka max sila enable zablokovat zadnabila zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME </pre>
<pre> \pretocommalist {...} \^2. 1 TEXT 2 CSNAME </pre>
<pre> \prettyprintbuffer {...} {...} 1 BUFFER 2 mp lua xml parsed-xml nested tex context zadny NAME </pre>
<pre> \prevcounter [...] [...] 1 NAME 2 NUMMER </pre>
<pre> \prevcountervalue [...] * NAME </pre>
<pre> \preventmode [...]*[...] * NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>

<pre> \prevsubcountervalue [...] [...] 1 NAME 2 NUMBER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>
<pre> \prizpusobivepole [...] [...] 1 NAME 2 inherits: \setupfieldbody </pre>
<pre> \prizpusobvzhled [...] [...] 1 NUMBER 2 vyska = max DIMENSION rady = NUMBER </pre>
<pre> \procent </pre>
<pre> \processaction [...] [...] 1 BEFEHL 2 APPLY </pre>
<pre> \processallactionsinset [...] [...] 1 BEFEHL 2 APPLY </pre>
<pre> \processassignlist [...] \... 1 TEXT 2 CSNAME </pre>
<pre> \processassignmentcommand [...] \... 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processassignmentlist [...] \... 1 KEY = VALUE 2 CSNAME </pre>
<pre> \processbetween {...} \... 1 NAME 2 CSNAME </pre>
<pre> \processbodyfontenvironmentlist \... * CSNAME </pre>
<pre> \processcolorcomponents {...} * COLOR </pre>
<pre> \processcommaccommand [...] \... 1 BEFEHL 2 CSNAME </pre>
<pre> \processcommalist [...] \... 1 BEFEHL 2 CSNAME </pre>

\processcommalistwithparameters [... ¹ ,...] \ ² .. 1 BEFEHL 2 CSNAME
\processcontent {.. ¹ } \ ² .. 1 NAME 2 CSNAME
\processfile {.. [*] } * FILE
\processfilemany {.. [*] } * FILE
\processfilenone {.. [*] } * FILE
\processfileonce {.. [*] } * FILE
\processfirstactioninset [... ¹] [... ² ⇒...] 1 BEFEHL 2 APPLY
\processisolatedchars {.. ¹ } \ ² .. 1 TEXT 2 CSNAME
\processisolatedwords {.. ¹ } \ ² .. 1 TEXT 2 CSNAME
\processlinetablebuffer [... [*]] <small>OPT</small> * BUFFER
\processlinetablefile {.. [*] } * FILE
\processlist {.. ¹ } {.. ² } {.. ³ } \ ⁴ .. 1 CHARACTER 2 CHARACTER 3 TEXT 4 CSNAME
\processMPbuffer [... [*] ,...] <small>OPT</small> * NAME
\processMPfigurefile {.. [*] } * FILE
\processmonth {.. ¹ } {.. ² } {.. ³ } 1 NUMMER 2 NUMMER 3 BEFEHL
\processranges [... ¹ ,...] \ ² .. 1 NUMMER NUMMER:NUMMER 2 CSNAME
\processseparatedlist [... ¹] [... ²] {.. ³ } 1 TEXT 2 TEXT 3 CSNAME BEFEHL

<p><code>\processTeXbuffer [...]</code></p> <p>* BUFFER OPT</p>
<p><code>\processtokens {¹.} {².} {³.} {⁴.} {⁵.}</code></p> <p>1 BEFEHL 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 TEXT</p>
<p><code>\processuntil \...</code></p> <p>* CSNAME</p>
<p><code>\processxtablebuffer [...]</code></p> <p>* NAME OPT</p>
<p><code>\processyear {¹.} {².} {³.} {⁴.}</code></p> <p>1 NUMBER 2 BEFEHL 3 BEFEHL 4 BEFEHL</p>
<p><code>\produkt [...]</code></p> <p>* FILE</p>
<p><code>\produkt ...</code></p> <p>* FILE</p>
<p><code>\profiledbox [¹.] [...,²...²...] {³.}</code></p> <p>1 zadny fixne striktni^{OPT} halffixed^{OPT} quarterfixed eightsfixed NAME 2 inherits: \setupprofile 3 CONTENT</p>
<p><code>\profilegivenbox {¹.} ²...</code></p> <p>1 zadny fixne striktni^{OPT} halffixed^{OPT} quarterfixed eightsfixed NAME 2 CSNAME NUMBER</p>
<p><code>\program [...]</code></p> <p>* NAME</p>
<p><code>\projekt [...]</code></p> <p>* FILE</p>
<p><code>\projekt ...</code></p> <p>* FILE</p>
<p><code>\prostredi [...]</code></p> <p>* FILE</p>
<p><code>\prostredi ...</code></p> <p>* FILE</p>
<p><code>\prvnipodstranka</code></p>
<p><code>\pseudoMixedCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped {...}</code></p> <p>* TEXT</p>

<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMBER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \...</code></p> <p>* CSNAME</p>
<p><code>\pushbar [...] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbarva [...] ... \popbarva</code></p> <p>* COLOR</p>
<p><code>\pushbutton [¹...] [²...]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \...</code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]</code></p> <p>* NAME</p> <p>OPT</p>
<p><code>\pushpath [...] ... \poppath</code></p> <p>* PATH</p>
<p><code>\pushpozadi [...] ... \poppozadi</code></p> <p>* NAME</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...} ... \popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>* NAME</p>

<code>\putboxincache {¹...} {²...} ³...</code> 1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
<code>\putnextboxincache {¹...} {²...} \³... {⁴...}</code> 1 NAME 2 NUMBER TEXT 3 CSNAME 4 CONTENT
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [...]</code> * NUMBER OPT
<code>\quarterstrut</code>
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {[*]...}</code> * FILE
<code>\Rimskecislice {[*]...}</code> * NUMBER
<code>\radek {[*]...}</code> * CONTENT
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {¹...} \²... {³...}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {[*]...}</code> * TEXT
<code>\randomnumber {¹...} {²...}</code> 1 NUMBER 2 NUMBER

\rawcounter [...] [² ...] 1 NAME OPT 2 NUMMER
\rawcountervalue [...] * NAME
\rawdate [...*,...] * inherits: \aktualnidatum
\rawdoifelseinset { ¹ ...} { ² ...,...} { ³ ...} { ⁴ ...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
\rawdoifinset { ¹ ...} { ² ...,...} { ³ ...} 1 TEXT 2 TEXT 3 TRUE
\rawdoifinsetelse { ¹ ...} { ² ...,...} { ³ ...} { ⁴ ...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE
\rawgetparameters [¹ ...] [..., ² ...,...] 1 TEXT 2 KEY = VALUE
\rawprocessaction [¹ ...] [..., ² =>...,...] 1 BEFEHL 2 APPLY
\rawprocesscommacommand [..., ¹ ...] \ ² ... 1 BEFEHL 2 CSNAME
\rawprocesscommalist [..., ¹ ...] \ ² ... 1 BEFEHL 2 CSNAME
\rawstructurelistuservariable {.*} * KEY
\rawsubcountervalue [¹ ...] [² ...] 1 NAME 2 NUMMER
\rbox ¹ ... { ² ...} 1 TEXT OPT 2 CONTENT
\readfile { ¹ ...} { ² ...} { ³ ...} 1 FILE 2 TRUE 3 FALSE
\readfixfile { ¹ ...} { ² ...} { ³ ...} { ⁴ ...} 1 PATH 2 FILE 3 TRUE 4 FALSE

<code>\readjobfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readlocfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readsetfile {...} {...} {...} {...}</code> 1 PATH 2 FILE 3 TRUE 4 FALSE
<code>\readsysfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readtexfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readxmlfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...] [...]</code> 1 implicitni text titul cislo stranka realpage 2 REFERENCE
<code>\REFERENCEFORMAT {...} {...} [...]</code> 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>

<pre> \registerattachment [...] [...²...] 1 NAME 2 inherits: \setupattachment </pre>
<pre> \registerctxluafile {...} {...} 1 FILE 2 NUMBER </pre>
<pre> \registerexternalfigure [...] [...²] [...³...] 1 FILE 2 NAME 3 inherits: \setuexternalfigure </pre>
<pre> \registerfontclass {...} * NAME </pre>
<pre> \registerhyphenationexception [...] [...²] 1 SPRACHE 2 TEXT </pre>
<pre> \registerhyphenationpattern [...] [...²] 1 SPRACHE 2 TEXT </pre>
<pre> \registermenubuttons [...] [...²] 1 NAME 2 TEXT </pre>
<pre> \registersort [...] [...²] 1 SINGULAR 2 NAME </pre>
<pre> \registersynonym [...] [...²] 1 SINGULAR 2 NAME </pre>
<pre> \registerunit [...] [...²...] 1 prefix jednotka ^{OPT}operator suffixe symbol packaged 2 KEY = VALUE </pre>
<pre> \REGISTER [...] [...².+...] 1 TEXT PROCESSOR->TEXT 2 INDEX instances: index </pre>
<pre> \index [...] [...².+...] 1 TEXT PROCESSOR->TEXT 2 INDEX </pre>
<pre> \REGISTER [...] {...²} [...³.+...] 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: index </pre>
<pre> \index [...] {...²} [...³.+...] 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX </pre>
<pre> \relatemarking [...] [...²] 1 BESCHRIFTUNG 2 BESCHRIFTUNG </pre>

<code>\relateparameterhandlers {...} {...} {...} {...}</code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\relaxvalueifundefined {...}</code> * NAME
<code>\remainingcharacters</code>
<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...} \^2..</code> 1 TEXT 2 CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...]</code> * NAME
<code>\removepunctuation</code>
<code>\removesubstring \^1.. \from \^2.. \to \^3..</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\removetoks \^1.. \from \^2..</code> 1 BEFEHL 2 CSNAME
<code>\removeunwantedspaces</code>
<code>\replacefeature [...]</code> * NAME
<code>\replacefeature {...}</code> * NAME
<code>\replaceincommalist \^1.. {...}</code> 1 CSNAME 2 NUMBER
<code>\replaceword [...] [...] [...]</code> 1 NAME 2 TEXT 3 TEXT
<code>\rescan {...}</code> * CONTENT
<code>\rescanwithsetup {...} {...}</code> 1 NAME 2 CONTENT

<code>\resetallattributes</code>
<code>\resetandaddfeature [...]</code> * NAME
<code>\resetandaddfeature {...}</code> * NAME
<code>\resetbar</code>
<code>\resetboxesincache {...}</code> * NAME
<code>\resetbreakpoints</code>
<code>\resetbuffer [...]</code> * BUFFER
<code>\resetcollector [...]</code> * NAME
<code>\resetcounter [...] [...]</code> 1 NAME ² 2 NUMMER OPT
<code>\resetdigitsmanipulation</code>
<code>\resetdirection</code>
<code>\resetfeature</code>
<code>\resetflag {...}</code> * NAME
<code>\resetfontcolorscheme</code>
<code>\resetfontfallback [...] [...]</code> 1 NAME ² 2 FONT OPT
<code>\resetfontsolution</code>
<code>\resethyphenationfeatures</code>
<code>\resetcharacteralign</code>
<code>\resetcharacterkerning</code>
<code>\resetcharacterspacing</code>
<code>\resetcharacterstripping</code>
<code>\resetinjector [...]</code> * NAME
<code>\resetinteractionmenu [...]</code> * NAME

<code>\resettrackers</code>
<code>\resettrialtypesetting</code>
<code>\resetusedsortings [...]</code> * SINGULAR
<code>\resetusedsynonyms [...]</code> * SINGULAR
<code>\resetuserpagenumber</code>
<code>\resetvalue {...}</code> * NAME
<code>\resetvisualizers</code>
<code>\resetznaceni [...]</code> * BESCHRIFTUNG
<code>\reshapebox {...}</code> * BEFEHL
<code>\resolvedglyphdirect {...} {...}</code> 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\resolvedglyphstyled {...} {...}</code> 1 FONT 2 e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\restartcounter [...] [...²...] [...³]</code> 1 NAME 2 NUMMER 3 NUMMER
<code>\restorebox {...} {...}</code> 1 NAME 2 NAME
<code>\restorecatcodes</code>
<code>\restorecounter [...]</code> * NAME
<code>\storecurrentattributes {...}</code> * NAME
<code>\storeendofline</code>
<code>\storeglobalbodyfont</code>
<code>\reusableMPgraphic {...} {...²...}</code> 1 NAME 2 KEY = VALUE
<code>\reuseMPgraphic {...} {...²...}</code> 1 NAME 2 KEY = VALUE

<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> * CHARACTER
<code>\rhbox {...}</code> * CONTENT
<code>\rightbottombox {...}</code> * CONTENT
<code>\rightbox {...}</code> * CONTENT
<code>\righthbox {...}</code> * CONTENT
<code>\rightLABELtext {...}</code> * KEY instances: head label mathlabel
<code>\righttheadtext {...}</code> * KEY
<code>\rightlabeltext {...}</code> * KEY
<code>\rightmathlabeltext {...}</code> * KEY
<code>\rightline {...}</code> * CONTENT
<code>\rightorleftpageaction {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\rightskipadaption</code>
<code>\rightsubguillemot</code>
<code>\righttoleft</code>
<code>\righttoleftthbox ... {...}</code> 1 TEXT OPT 2 CONTENT
<code>\righttoleftvbox ... {...}</code> 1 TEXT OPT 2 CONTENT
<code>\righttoleftvtop ... {...}</code> 1 TEXT OPT 2 CONTENT
<code>\righttopbox {...}</code> * CONTENT

<code>\rimskecislice {...}</code> * NUMBER
<code>\ring {...}</code> * CHARACTER
<code>\rlap {...}</code> * CONTENT
<code>\robustaddtocommalist {...} \^2.</code> 1 TEXT 2 CSNAME
<code>\robustdoifelseinset {...} {...^2,...} {...^3} {...^4}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustdoifinsetelse {...} {...^2,...} {...^3} {...^4}</code> 1 TEXT 2 TEXT 3 TRUE 4 FALSE
<code>\robustpretocommalist {...} \^2.</code> 1 TEXT 2 CSNAME
<code>\rollbutton [...,...^1,...] .^2. [...^3]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\rollbutton [...^1] [...,...^2,...] .^3. [...^4]</code> 1 NAME OPT OPT 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
<code>\rovnice [...,...^1,...] {...^2}</code> 1 zhustene tight^OPT nastred ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont 2 CONTENT
<code>\rozdelplvouciobjekt [...,...^1,...] {...^2} {...^3}</code> 1 inherits: \nastavdeleniplvouciobjektu 2 BEFEHL 3 CONTENT
<code>\roztazene [...,...^1,...] {...^2}</code> 1 inherits: \setupstretched^OPT 2 TEXT
<code>\rtop .^1. {...^2}</code> 1 TEXT ^OPT 2 CONTENT
<code>\rukopisne</code>
<code>\ruledhbox .^1. {...^2}</code> 1 TEXT ^OPT 2 CONTENT

<pre> \ruledhpack ... {...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \ruledmbox {...} * CONTENT </pre>
<pre> \ruledtopv ... {...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \ruledtpack ... {...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \ruledvbox ... {...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \ruledvpack ... {...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \ruledvtop ... {...} 1 TEXT OPT 2 CONTENT </pre>
<pre> \runMPbuffer [...*,...] * NAME OPT </pre>
<pre> \runninghbox {...} * CONTENT </pre>
<pre> \ScaledPointsToBigPoints {...} \^2... 1 DIMENSION 2 CSNAME </pre>
<pre> \ScaledPointsToWholeBigPoints {...} \^2... 1 DIMENSION 2 CSNAME </pre>
<pre> \SLOVA {...} * TEXT </pre>
<pre> \SLOVO {...} * TEXT </pre>
<pre> \Slova {...} * TEXT </pre>
<pre> \Slovo {...} * TEXT </pre>
<pre> \Smallcapped {...} * TEXT </pre>
<pre> \safechar {...} * NUMBER </pre>
<pre> \samplefile {...} * FILE </pre>

<code>\sans</code>
<code>\sansnormal</code>
<code>\sanstucne</code>
<code>\savebarva ... \restorebarva</code>
<code>\savebox {¹..} {²..} {³..}</code> 1 NAME 2 NAME 3 CONTENT
<code>\savebtxdataset [¹...] [²...] [³...³...]</code> 1 NAME OPT OPT OPT 2 FILE 3 dataset = NAME typ = bib lua xml soubor = FILE kritérium = vse text uvod odkaz aktualni zde predchozi lokalne komponenta SECTIONBLOCK:vse SECTIONBLOCK:odkaz SECTIONBLOCK:aktualni SECTIONBLOCK:predchozi
<code>\savebuffer [...[*]...]</code> * seznam = NAME soubor = FILE prefix = ano ne
<code>\savebuffer [...¹...] [...²..]</code> 1 BUFFER 2 FILE
<code>\savecounter [...]</code> * NAME
<code>\savecurrentattributes {[*]..}</code> * NAME
<code>\savenormalmeaning \[*]..</code> * CSNAME
<code>\savetaggedtwopassdata {¹..} {²..} {³..} {⁴..}</code> 1 NAME 2 NUMMER 3 NAME 4 CONTENT
<code>\savetwopassdata {¹..} {²..} {³..}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\sbox {[*]..}</code> * CONTENT
<code>\SCRIPT</code> instances: hangul hanzi nihongo ethiopic thai latin test
<code>\ethiopic</code>
<code>\hangul</code>
<code>\hanzi</code>

<code>\latin</code>
<code>\nihongo</code>
<code>\test</code>
<code>\thai</code>
<code>\secondoffivearguments {.^1.} {.^2.} {.^3.} {.^4.} {.^5.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\secondoffourarguments {.^1.} {.^2.} {.^3.} {.^4.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\secondofsixarguments {.^1.} {.^2.} {.^3.} {.^4.} {.^5.} {.^6.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\secondofthreearguments {.^1.} {.^2.} {.^3.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\secondofthreeunexpanded {.^1.} {.^2.} {.^3.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\secondoftwoarguments {.^1.} {.^2.}</code> 1 TEXT 2 TEXT
<code>\secondoftwounexpanded {.^1.} {.^2.}</code> 1 TEXT 2 TEXT
<code>\sedabarva [.^1.] {.^2.}</code> 1 COLOR 2 CONTENT
<code>\vizREGISTER [.^1.] [.^2.+.^2.+.^2.] {.^3.}</code> 1 TEXT PROCESSOR->TEXT 2 INDEX 3 TEXT PROCESSOR->TEXT instances: index
<code>\vizindex [.^1.] [.^2.+.^2.+.^2.] {.^3.}</code> 1 TEXT PROCESSOR->TEXT 2 INDEX 3 TEXT PROCESSOR->TEXT

```
\SECTION [...1,...2] {...}
1 REFERENCE OPT
2 TEXT
instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title
subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
```

```
\SECTION [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title
subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject
```

```
\chapter [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

```
\part [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

```
\section [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

```
\subject [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

```
\subsection [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

```
\subsubject [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

```
\subsubsection [...*,...*]
* titul = TEXT
  zalozka = TEXT
  znaceni = TEXT
  seznam = TEXT
  odkaz = REFERENCE
  vlastnicislo = TEXT
```

`\subsubsubject [...,.*,...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\subsubsubsection [...,.*,...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\subsubsubsubject [...,.*,...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\subsubsubsubsection [...,.*,...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\subsubsubsubsubject [...,.*,...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\title [...,.*,...]`

* titul = TEXT
zalozka = TEXT
znaceni = TEXT
seznam = TEXT
odkaz = REFERENCE
vlastnicislo = TEXT

`\chapter [...,1...] {2...}`

1 REFERENCE OPT
2 TEXT

`\SECTION [...,1...] {2...} {3...}`

1 REFERENCE OPT
2 NUMMER
3 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title
subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,1...] {2...} {3...}`

1 REFERENCE OPT
2 NUMMER
3 TEXT

`\part [...,1...] {2...} {3...}`

1 REFERENCE^{PT}
2 NUMMER
3 TEXT

`\section [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subject [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsection [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubject [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubsection [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubsubject [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubsubsection [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubsubsubject [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubsubsubsection [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\subsubsubsubsubject [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\title [...,1...] {...} {...}`

1 REFERENCE OPT
2 NUMBER
3 TEXT

`\part [...,1...] {...}`

1 REFERENCE OPT
2 TEXT

`\section [...,1...] {...}`

1 REFERENCE OPT
2 TEXT

`\subject [...,1...] {...}`

1 REFERENCE OPT
2 TEXT

$\backslash\text{subsection} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubject} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsection} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubject} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubsection} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubsubject} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubsubsection} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubsubsubject} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubsubsubsection} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{subsubsubsubsubsubject} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{title} [\dots,\dots] \{\dots\}$ 1 REFERENCE OPT 2 TEXT
$\backslash\text{select} \{\dots\} \{\dots\} \{\dots\} \{\dots\} \{\dots\} \{\dots\}$ 1 NAME OPT OPT OPT OPT OPT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
$\backslash\text{serializecommalist} [\dots,*\dots]$ * BEFEHL
$\backslash\text{serializedcommalist}$
$\backslash\text{serif}$
$\backslash\text{serifbold}$
$\backslash\text{serifnormal}$
$\backslash\text{setbar} [\dots]$ * NAME
$\backslash\text{setbigbodyfont}$

<pre> \setboxllx ¹... {²...} 1 CSNAME NUMBER 2 DIMENSION </pre>
<pre> \setboxlly ¹... {²...} 1 CSNAME NUMBER 2 DIMENSION </pre>
<pre> \setbreakpoints [...] * reset NAME </pre>
<pre> \setbuffer [...] ... \endbuffer * NAME </pre>
<pre> \setcapstrut </pre>
<pre> \setcatcodetable *... * CSNAME </pre>
<pre> \setcollector [¹...] [²..._{OPT}...] {³...} 1 NAME 2 inherits: \setupcollector 3 CONTENT </pre>
<pre> \setcolormodel1 [...] * black bw seda rgb cmyk vse zadny </pre>
<pre> \setcounter [¹...] [²..._{OPT}] [³...] 1 NAME 2 NUMBER 3 NUMBER </pre>
<pre> \setcounterown [¹...] [²..._{OPT}] [³...] 1 NAME 2 NUMBER 3 TEXT </pre>
<pre> \setcurrentfontclass {[*]...} * NAME </pre>
<pre> \setdataset [¹...] [²..._{OPT}] [³...₃...] 1 NAME 2 NAME 3 KEY = VALUE </pre>
<pre> \setdefaultpenalties </pre>
<pre> \setdigitsmanipulation [...] * reset NUMBER </pre>
<pre> \setdirection [...] * NUMBER </pre>
<pre> \setdocumentargument {¹...} {²...} 1 NAME 2 TEXT </pre>
<pre> \setdocumentargumentdefault {¹...} {²...} 1 NAME 2 TEXT </pre>

<pre> \setdocumentfilename {...} {...} 1 NUMBER 2 TEXT </pre>
<pre> \setdummysparameter {...} {...} 1 KEY 2 BEFEHL </pre>
<pre> \setelementexporttag [...]¹ [...]² [...]³ 1 NAME 2 export nature pdf 3 inline obrazovka mixed </pre>
<pre> \setemeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setevalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setevariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setevariables [...]¹ [...]²...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \setfirstline [...][*] * NAME </pre>
<pre> \setflag {...} * NAME </pre>
<pre> \setfont ... * FONT </pre>
<pre> \setfontcolorsheme [...][*] * NAME </pre>
<pre> \setfontfeature {...} * NAME </pre>
<pre> \setfontsolution [...][*] * NAME </pre>
<pre> \setfontstrut </pre>
<pre> \setgmeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setgvalue {...} {...} 1 NAME 2 CONTENT </pre>

```
\setgvariable {...} {...} {...}
```

1	NAME
2	KEY
3	VALUE

$$\backslash\mathrm{setgvariables} \left[\dots \right] \left[\dots, \dots \overset{2}{=} \dots, \dots \right]$$

```

1  NAME
2  set      =  BEFEHL
   reset    =  BEFEHL
   KEY      =  VALUE

```

$$\backslash\text{sethboxregister} \dots \{ \dots \}$$

```

1 CSNAME NUMMER
2 CONTENT

```

```
\sethyphenatedurlafter {...}
```

* TEXT

`\sethyphenatedurlbefore {...}`

* TEXT

`\sethyphenatedurlnormal {...}`

* TEXT

```
\sethyphenationfeatures [...,*,...]
```

```
* NAME reset OPT
```

$$\backslash\mathrm{setcharacteralign}\{\ldots\}^1\{\ldots\}^2$$

```
1  NUMBER
2  TEXT number->TEXT text->TEXT
```

```
\setcharactercasing [...]
```

* reset SLOVO slovo Slovo Slova kapitalky Kapitalky zadny nahodny mixed camel kap Kap

```
\setcharactercleaning [...]
```

```
* reset 1
```

`\setcharacterkerning [...]`

```
* reset NAME
```

`\setcharacterspacing [...]`

```
* reset NAME
```

`\setcharacterstripping [...]`

```
* reset 1
```

`\setcharstrut {...}`

* TEXT

$$\backslash\mathrm{setinitial} \left[\dots \right] \left[\dots, \dots \stackrel{2}{=} \dots, \dots \right]$$

```
1 NAME OPT OPT
2 inherits: \setupinitial
```

$$\backslash \text{setinjector} \left[\dots^1 \right] \left[\dots^2, \dots \right] \left[\dots^3 \right]$$

1	NAME
2	NUMMER
3	BEFEHL

```
\setinteraction [...]
```

```
* skryte NAME
```

```

1  NAME
2  NAME

```

```
1  NAME
2  NAME
```

```
1  NAME
2  NAME
```

```

1  NAME
2  titul NAME NUMMER
3  TEXT

```

```
1  NAME
2  NAME
```

```
1  NAME
2  auto embed
3  CONTENT
```

```
* reset 1 2
```

1	NAME
2	CONTENT

```

1  NAME                                OPT
2  vlevo vpravo sude liche
3  inherits: \setupplayer
4  CONTENT

```

```
1  NAME
2  inherits: \setupplayer
3  inherits: \nastavoramovani
4  CONTENT
```

1	NAME	OPT
2	inherits: \setupplayerinherits: \nastavoramovani	
3	CONTENT	

```

1  NAME                                OPT
2  inherits: \setupplayer
3  zarovnani = inherits: \nastavzarovnani
   sirka     = DIMENSION
   pismo     = STYLE BEFEHL
   barva     = COLOR
4  TEXT

```

```
*  filler NAME
```

* [-+]DIMENSION OPT

```
\setMPLayer [.1.] [2..] [...,3..4...] {5...}
1 NAME
2 NAME
3 inherits: \setupplayer
4 CONTENT
```

```
\setMPpositiongraphic {...1} {...2} {...3=...,...}
1 NAME OPT
2 NAME
3 KEY = VALUE
```

```
\setMPpositiongraphicrange {1.} {2.} {3.} {4....,...}
1 NAME OPT
2 NAME
3 NAME
4 KEY = VALUE
```

```
\setMPtext {1...} {2...}
```

1 NAME

2 TEXT

```
\setMPvariable [...] [1..2..]
1  NAME
2  KEY = VALUE
```

```
\setMPvariables [...]1 [...]2...,...]
1 NAME OPT
2 KEY = VALUE
```

`\setmainbodyfont`

```
\setmainparbuilder [...]
*   implicitni oneline basic NAME
```

```
\setmarker [...] [1...] [2...]
```

1	NAME
2	NUMMER

```
\setmarking [...] {...}
1  BESCHRIFTUNG
2  TEXT
```

`\setmathstyle {...,*...}`

* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

```
\setmeasure {...} {...}
```

1	NAME
2	DIMENSION

```
\setmessagetext {...} {...}
1  NAME
2  NAME NUMBER
```

```
\setmode {...}
* NAME
```

`\setnostrut`

```
\setnote [...] [...] {...}
```

1 NAME OPT

2 REFERENCE

3 TEXT

```
\setnotetext [...]1 [...,...]2 {...}3
1 NAME
2 REFERENCE
3 TEXT
```

```
\setnotetext [...]1 [...,...2...,...]
```

1 NAME

2 titul = TEXT

zalozka = TEXT

seznam = TEXT

odkaz = REFERENCE

```
\setnote [...]1 [...,...2...,...]
```

1 NAME

2 titul = TEXT

zalozka = TEXT

seznam = TEXT

odkaz = REFERENCE

```
\setobject {...}1 {...}2 \... {...}4
```

1 NAME

2 NAME

3 CSNAME

4 CONTENT

```
\setoldstyle
```

```
\setpagegrid [...,...1...,...]2 {...}
```

1 c = NUMBER ^{OPT}

r = NUMBER

volba = zadny

2 CONTENT

```
\setpagereference {...}1 {...,2...,...}
```

1 NAME

2 REFERENCE

```
\setpagestate [...]1 [...]2
```

1 NAME ^{OPT}

2 NAME NUMBER

```
\setpagestaterealpageno {...}1 {...}2
```

1 NAME

2 NAME NUMBER

```
\setpenalties \... {...}1 {...}2 {...}3
```

1 CSNAME

2 NUMBER

3 NUMBER

```
\setpercentdimen {...}1 {...}2
```

1 DIMENSION CSNAME

2 DIMENSION NUMBER

```
\setposition {...}
```

* NAME

```
\setpositionbox {...}1 \... {...}3
```

1 NAME

2 CSNAME

3 CONTENT

```
\setpositiondata {...}1 {...}2 {...}3 {...}4
```

1 NAME

2 DIMENSION

3 DIMENSION

4 DIMENSION

\setpositiondataplus {...} {...} {...} {...} {...,⁵...}

1 NAME
2 DIMENSION
3 DIMENSION
4 DIMENSION
5 TEXT

\setpositiononly {...}

* NAME

\setpositionplus {...} {...,²...} \... {...}

1 NAME
2 TEXT
3 CSNAME
4 CONTENT

\setpositionstrut {...}

* NAME

\setprofile [...]

* zadny fixne striktni halffixed quarterfixed eightsfixed NAME

\setrandomseed {...}

* NUMMER

\setreference [...,¹...] [...,²...,...]

1 REFERENCE
2 KEY = VALUE

\setreferencedobject {...} {...} \... {...}

1 NAME
2 NAME
3 CSNAME
4 CONTENT

\setregisterentry [...]¹ [...,²...,...]³ [...,³...,...]^{OPT}

1 NAME
2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternativa = TEXT
3 KEY = VALUE

\setreplacement [...]

* reset NAME

\setrigidcolumnbalance ...

* CSNAME NUMMER

\setrigidcolumnhsize {...} {...} {...}

1 DIMENSION
2 DIMENSION
3 NUMMER

\setscript [...]

* hangul hanzi nihongo ethiopic thai test NAME

\setsectionblock [...]¹ [...,²...,...]^{OPT}

1 NAME
2 zalozka = TEXT

`\setsimplecolumnhsize [...,*...]`

* n = NUMBER
sirka = DIMENSION
vzdalenost = DIMENSION
radky = NUMBER

`\setsmallbodyfont`

`\setsmallcaps`

`\setstackbox {.1.} {.2.} {.3.}`

1 NAME
2 NAME
3 CONTENT

`\setstructurepageregister [.1.] [...,*2...] [...,*3...]`

1 NAME
2 popisek = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternativa = TEXT
3 KEY = VALUE

`\setstrut`

`\setsuperiors`

`\setsystemmode {.*}`

* NAME

`\settabular`

`\settaggedmetadata [...,*...]`

* KEY = VALUE

`\settextcontent [.1.] [.2.] [.3.] [.4.] [.5.]`

1 vrsek zahlavi text upati spodek
2 text marginalie hrana
3 vlevo nastred vpravo
4 datum cislostranky BESCHRIFTUNG TEXT BEFEHL
5 datum cislostranky BESCHRIFTUNG TEXT BEFEHL

`\settightobject {.1.} {.2.} \3. {.4.}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\settightreferencedobject {.1.} {.2.} \3. {.4.}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\settightunreferencedobject {.1.} {.2.} \3. {.4.}`

1 NAME
2 NAME
3 CSNAME
4 CONTENT

`\settrialtypesetting`

\setuevalue {...} {...}

1 NAME
2 CONTENT

\setugvalue {...} {...}

1 NAME
2 CONTENT

\setunreferencedobject {...} {...} \^ {...} {...}

1 NAME
2 NAME
3 CSNAME
4 CONTENT

\setupalternativestyles [...,...*...,...]

* metoda = normalni auto

\setupattachment [...,...¹...] [...,...²...,...]

1 NAME
2 titul = TEXT
podtitulek = TEXT
autor = TEXT
soubor = FILE
jmeno = NAME
buffer = BUFFER
status = start stop
metoda = normalni skryte
symbol = Graph Paperclip Pushpin Default
sirka = prizpusobive DIMENSION
vyska = prizpusobive DIMENSION
hloubka = prizpusobive DIMENSION
barva = COLOR
textlayer = NAME
misto = levahrana pravahrana naokraji lev yokraj prav yokraj text vysoko zadny
vzdalenost = DIMENSION

\setupattachments [...,...¹...] [...,...²...,...]

1 NAME
2 inherits: \setupattachment

\setupbackend [...,...*...,...]

* export = ano FILE
xhtml = FILE
soubor = FILE
intent = Coated FOGRA39 (ISO 12647-2:2004) GRACoL2006_Coated1v2.icc ISO Coated v2 300 ISO Coated v2 (ECI) ISOnewspaper26v4
ISOnewspaper26v4_gr ISO Uncoated ISO Uncoated Yellowish ISO Web Coated Japan Color 2001 Coated Japan Color
2002 Newspaper Japan Web Coated (Ad) SNAP 2007 SWOP2006_Coated3v2.icc SWOP2006_Coated5v2.icc Uncoated
FOGRA29 (ISO 12647-2:2004) Web Coated FOGRA28 (ISO 12647-2:2004) PSR_LWC_PLUS_V2_PT PSR_LWC_STD_V2_PT
PSR_SC_PLUS_V2_PT PSR_SC_STD_V2_PT PSRgravureMF
mezera = ano ne
xmpfile = FILE
formatovat = version implicitni PDF/X-1a:2001 PDF/X-1a:2003 PDF/X-3:2002 PDF/X-3:2003 PDF/X-4 PDF/X-4p PDF/X-5g PDF/X-5pg
PDF/X-5n PDF/A-1a:2005 PDF/A-1b:2005 PDF/A-2a PDF/A-3a PDF/UA-1
uroven = NUMMER
volba = vzdy nikdy
profile = FILE

\setupbar [...,...¹...] [...,...²...,...]

1 NAME
2 barva = COLOR
pokracovat = ano ne vse
prazdne = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
order = popredi pozadi
tloustkalinky = DIMENSION
metoda = NUMMER
offset = NUMMER
dy = NUMMER
max = NUMMER
foregroundstyle = STYLE BEFEHL
foregroundcolor = COLOR
mp = NAME
vlevo = TEXT
vpravo = TEXT

\setupbars [...¹,...] [...²,...]

1 NAME OPT
2 inherits: \setupbar

\setupbleeding [...^{*},...]

* sirka = DIMENSION
vyska = DIMENSION
offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
misto = t b l r bl lb br rb tl lt tr rt
natahnout = ano ne
stranka = ano ne

\setupbookmark [...^{*},...]

* sila = ano ne
cislo = ano ne
numberseparatorset = NAME
numberconversionset = NAME
numberstarter = BEFEHL
numberstopper = BEFEHL
numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
sectionblock = ano ne

\setupbtx [...¹] [...²,...]

1 NAME OPT
2 specification = implicitni apa aps NAME
dataset = implicitni NAME
prikaz = \...#1
vlevo = BEFEHL
vpravo = BEFEHL
authorconversion = normalni normalshort normalinverted invertedshort short
etallimit = NUMMER
etalldisplay = NUMMER
etaloption = posledni
predel = initials
interakce = start stop cislo text stranka vse
alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears
authornum authoryear
sorttype = normalni reverse
compress = ano ne
implicitni = implicitni NAME
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxdataset [...¹,...] [...²,...]

1 NAME OPT
2 language = SPRACHE

\setupbtxlist [...¹] [...²,...]

1 NAME OPT
2 inherits: \nastavseznam

\setupbtxregister [...¹,...] [...²,...]

1 NAME OPT
2 status = start stop
dataset = NAME
field = keyword range cislostranky autor
register = NAME
metoda = once
alternativa = normalshort invertedshort
pismo = STYLE BEFEHL
barva = COLOR

\setupbtxrendering [...¹,...] [...²...,...]

```
1  NAME                      OPT
2  statustextu               = start stop
   pagestate                 = start stop
   oddelevac                  = BEFEHL
   kriterium                  = predchozi cite zde vse zadny
   filter                     = TEXT
   specification              = NAME
   titul                      = TEXT
   pred                       = BEFEHL
   po                         = BEFEHL
   dataset                    = NAME
   metoda                     = dataset sila lokalne globalne zadny
   sorttype                   = short dataset seznam odkaz uzito implicitni cite rejstrik
   opakovat                   = ano ne
   group                      = NAME
   cislovani                  = ano ne num rejstrik tag short stranka
```

\setupbtx [...]

* NAME

\setupbutton [...¹,...] [...²...,...]

```
1  NAME                      OPT
2  status                     = start stop
   stejnastranka              = ano ne prazdne zadny normalni implicitni
   pismo                      = STYLE BEFEHL
   barva                      = COLOR
   kontrastnibarva           = COLOR
   alternativa                = skryte
   inherits: \nastavoramovani
```

\setupcollector [...¹,...] [...²...,...]

```
1  NAME                      OPT
2  rotace                     = vlevo vpravo uvnitr vnejsi NUMMER
   roh                        = vlevo nastred vpravo vrsek spodek
   x                          = DIMENSION
   y                          = DIMENSION
   hoffset                    = DIMENSION
   voffset                    = DIMENSION
   misto                      = vlevo nastred vpravo vrsek spodek radek l c r m t b g
   status                     = start stop
```

\setupcolumnspan [...^{*}...,...]

```
*  n = NUMMER
   inherits: \nastavoramovani
```

\setupcombination [...¹,...] [...²...,...]

```
1  NAME                      OPT
2  nx                         = NUMMER
   ny                         = NUMMER
   sirka                      = prizpusobive DIMENSION
   vyska                      = prizpusobive DIMENSION
   misto                      = vlevo nastred vpravo vrsek spodek
   vzdalenost                 = DIMENSION
   alternativa                = popisek text
   zarovnani                  = inherits: \nastavzarovnani
   pokracovat                 = ano ne
   pred                       = BEFEHL
   po                         = BEFEHL
   mezi                       = BEFEHL
   pismo                      = STYLE BEFEHL
   barva                      = COLOR
```

\setupcounter [...¹,...] [...²,...]

```
1 NAME OPT
2 start = NUMBER
  counter = NAME
  metoda = stranka
  status = start stop
  zpusob = bystranka byblock bytext byhlavicka byABSCHNITT
  prefix = ano ne
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = BEFEHL PROCESSOR->BEFEHL
  prefixstopper = BEFEHL PROCESSOR->BEFEHL
  prefixset = NAME
  prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
  numberorder = reverse
  numberseparatorset = NAME
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = BEFEHL PROCESSOR->BEFEHL
  numberstopper = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:vse
  typ = prvni predchozi dalsi posledni cislo
  kriterium = striktni pozitiv vse
  prefixconnector = BEFEHL PROCESSOR->BEFEHL
```

\setupdataset [...¹,...] [...²,...]

```
1 NAME OPT
2 prodleva = ano ne
```

\setupdelimitedtext [...¹,...] [...²,...]

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  language = lokalne globalne SPRACHE
  metoda = font
  opakovat = ano ne
  misto = text odstavec marginalie
  vlevo = BEFEHL
  stredni = BEFEHL
  vpravo = BEFEHL
  nextleft = BEFEHL
  nextright = BEFEHL
  mezerapred = inherits: \preskoc
  mezeraza = inherits: \preskoc
  levyokraj = ano ne standardni DIMENSION
  pravyokraj = ano ne standardni DIMENSION
  odsazovani = inherits: \nastavodsazovani
  odsadpristi = ano ne auto
  pismo = STYLE BEFEHL
  barva = COLOR
  stylsymboly = STYLE BEFEHL
  barvasymbolu = COLOR
```

\setupdescription [...¹,...] [...²,...]

```

1  NAME                      OPT
2  titul                    = ano ne
   uroven                  = NUMMER
   text                    = TEXT
   headcommand             = \...##1
   pred                    = BEFEHL
   po                      = BEFEHL
   mezi                    = BEFEHL
   alternativa            = vlevo vpravo naokraj ivlevo ivpravo marginalie levyokraj prav yokraj innermargin outermargin semknuto
                           visici vrsek prikaz NAME
   zarovnnani              = inherits: \nastavzarovnnani
   headalign               = inherits: \nastavzarovnnani
   odsazovani              = inherits: \nastavodsazovani
   obrazovka               = ano ne
   odsadpristi             = ano ne auto
   sirka                   = prizpusobive siroky radek DIMENSION
   vzdalenost              = zadny DIMENSION
   natahnout               = NUMMER
   shrink                  = NUMMER
   zaveseni                = prizpusobive siroky zadny marginalie NUMMER
   closesymbol             = BEFEHL
   closecommand            = \...##1
   expanzen                = ano ne xml
   referenceprefix         = + - TEXT
   vzor                    = TEXT
   marginalie              = ano ne standardni DIMENSION
   pismo                   = STYLE BEFEHL
   barva                   = COLOR
   stylhlavicky            = STYLE BEFEHL
   barvahlavicky           = COLOR

```

\setupdirections [...,*=...]

```

*  bidi    = zap vyp lokalne globalne
   metoda  = jedna dve implicitni
   fences  = ano ne
   break   = obe pred

```

\setupdocument [...,*=...]

```

*  pred    = BEFEHL
   po      = BEFEHL
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY       = VALUE

```

\setupeffect [...¹,...] [...²,...]

```

1  NAME                      OPT
2  metoda                  = zadny prikaz
   natahnout              = NUMMER
   tloustkalinky          = NUMMER
   alternativa            = normalni uvnitr vnejsi obe skryte natahnout

```

\setupenumeration [...,¹...] [...,²...,...]

```

1  NAME                                OPT
2  titul                             = ano ne
   cislo                             = ano ne
   ciselnyprikaz                     = \...##1
   vzdalenosttitulek                 = DIMENSION
   styltitulek                       = STYLE BEFEHL
   barvatitulek                      = COLOR
   titlecommand                      = \...##1
   titleleft                         = BEFEHL
   titleright                        = BEFEHL
   vlevo                             = BEFEHL
   vpravo                            = BEFEHL
   symbol                            = BEFEHL
   starter                           = BEFEHL
   predel                            = BEFEHL
   propojeni                         = NAME
   counter                           = NAME
   uroven                             = NUMMER
   text                              = TEXT
   headcommand                       = \...##1
   pred                              = BEFEHL
   po                                 = BEFEHL
   mezi                              = BEFEHL
   alternativa                       = vlevo vpravo naokraj i vlevo i vpravo
                                     marginalie levýokraj pravýokraj
                                     innermargin outermargin semknuto
                                     visici vrsek prikaz NAME
   zarovnnani                        = inherits: \nastavzarovnnani
   headalign                         = inherits: \nastavzarovnnani
   odsazovani                        = inherits: \nastavodsazovani
   obrazovka                         = ano ne
   odsadpristi                       = ano ne auto
   sirka                             = prizpusobive široky radek DIMENSION
   vzdalenost                        = zadny DIMENSION
   natahnout                         = NUMMER
   shrink                            = NUMMER
   zaveseni                          = prizpusobive široky zadny marginalie NUMMER
   closesymbol                       = BEFEHL
   closecommand                      = \...##1
   expanzen                          = ano ne xml
   referenceprefix                   = + - TEXT
   vzor                              = TEXT
   marginalie                        = ano ne standardni DIMENSION
   pismo                             = STYLE BEFEHL
   barva                             = COLOR
   stylhlavicky                     = STYLE BEFEHL
   barvahlavicky                     = COLOR
   inherits: \setupcounter

```

\setupenv [...,^{*}...,...]

```

*  set      = BEFEHL
   reset    = BEFEHL
   KEY      = VALUE

```

\setupexport [...,^{*}...,...]

```

*  zarovnnani      = flushleft nastred flushright normalni
   zakladnifont     = DIMENSION
   sirka            = DIMENSION
   titul            = TEXT
   podtitulek       = TEXT
   autor            = TEXT
   alternativa      = html div
   properties       = ano ne
   hyphen           = ano ne
   cssfile          = FILE
   prvnistranka     = FILE
   poslednistrana   = FILE

```

`\setupexternalfigure [...1,...] [...2,...,...]`

```

1 NAME OPT
2 sirka = DIMENSION
  vyska = DIMENSION
  popisek = NAME
  stranka = NUMMER
  objekt = ano ne
  prefix = TEXT
  metoda = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
  controls = ano ne
  nahled = ano ne
  mask = zadny
  rozliseni = NUMMER
  barva = COLOR
  arguments = TEXT
  opakovat = ano ne
  faktor = prizpusobive siroky max auto implicitni
  vfaktor = prizpusobive siroky max auto implicitni
  sfaktor = prizpusobive siroky max auto implicitni
  maxsirka = DIMENSION
  maxvyska = DIMENSION
  equalwidth = DIMENSION
  equalheight = DIMENSION
  meritko = NUMMER
  xmeritko = NUMMER
  ymeritko = NUMMER
  s = NUMMER
  sx = NUMMER
  sy = NUMMER
  radky = NUMMER
  misto = lokalne globalne implicitni
  adresar = PATH
  volba = test ramecek prazdne
  foregroundcolor = COLOR
  reset = ano ne
  pozadi = barevne popredi NAME
  ramecek = zap vyp
  barvapozadi = COLOR
  xmax = NUMMER
  ymax = NUMMER
  ramecky = zap vyp
  interakce = ano vse zadny odkaz layer zalozka
  zakladnifont = DIMENSION
  comment = BEFEHL TEXT
  velikost = zadny media crop trim art
  cache = PATH
  resources = PATH
  obrazovka = FILE
  konverze = TEXT
  order = LISTE
  crossreference = ano ne NUMMER

```

`\setupexternalsoundtracks [...*,...,...]`

`* volba = opakovat`

`\setupfielddbody [...1,...] [...2,...,...]`

```

1 NAME OPT
2 category = NAME
  inherits: \setupfieldcategory

```


\setupfieldcategory [...¹,...] [...²,...]

```
1 NAME OPT
2 start = NUMMER
  pismo = STYLE BEFEHL
  barva = COLOR
  typ = radio pod text radek push check signature
  values = TEXT
  implicitni = TEXT
  barvameckupole = COLOR
  barvapozaadipole = COLOR
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
  zarovnani = vlevo nastred vpravo flushleft center flushright
  n = NUMMER
  symbol = NAME
  fieldlayer = NAME
  volba = pouzeprocteni pozadovane chranene tridene nedostupne nocheck fixne soubor skryte tisknutelne auto
  klikuvnitř = REFERENCE
  klikvne = REFERENCE
  oblastuvnitř = REFERENCE
  oblastvne = REFERENCE
  klavesapo = REFERENCE
  formatovat = REFERENCE
  validovat = REFERENCE
  pocitat = REFERENCE
  focusin = REFERENCE
  focusout = REFERENCE
  openpage = REFERENCE
  closepage = REFERENCE
```

\setupfieldcontentframed [...¹,...] [...²,...]

```
1 NAME OPT
2 inherits: \nastavoramovaniinherits: \setupfieldcategory
```

\setupfieldlabelframed [...¹,...] [...²,...]

```
1 NAME OPT
2 inherits: \nastavoramovani
```

\setupfieldtotalframed [...¹,...] [...²,...]

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  vzdalenost = DIMENSION
  alternativa = reset popisek ramecek horizontalne vertikalne
  inherits: \nastavoramovani
```

\setupfiller [...¹,...] [...²,...]

```
1 NAME OPT
2 levyokraj = DIMENSION
  pravyokraj = DIMENSION
  vlevo = BEFEHL
  vpravo = BEFEHL
  alternativa = symbol natahnout linka mezera
  metoda = lokalne globalne nastred siroky
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
  offset = DIMENSION
  vzdalenost = DIMENSION
  zarovnani = vlevo vpravo nastred flushleft flushright uvnitř vnejsi
  symbol = BEFEHL
  pismo = STYLE BEFEHL
  barva = COLOR
```

\setupfirstline [...¹,...] [...²,...]

```
1 NAME OPT
2 n = NUMMER
  alternativa = implicitni radek slovo
  pismo = STYLE BEFEHL
  barva = COLOR
```

\setupfittingpage [...¹,...] [...²,...]

```
1 NAME OPT
2 pagestate = start stop
  prikaz = \...##1
  marginalie = stranka
  meritko = NUMMER
  papir = auto implicitni NAME
  inherits: \nastavoramovani
```

\setupfloatcaption [...¹,...] [...²,...]

```
1 NAME OPT
2 suffix = BEFEHL
  suffixseparator = BEFEHL
  suffixstopper = BEFEHL
  misto = vlevo vpravo nastred nizko vysoko mizka prekryv uvnitr vnejsi innermargin outermargin levyokraj
          pravyokraj lefthanging righthanging zaveseni vrsek spodek natahnout zadny implicitni
  prikaz = \...##1
  ciselnyprikaz = \...##1
  textovyprikaz = \...##1
  mezerapred = inherits: \preskoc
  spaceinbetween = inherits: \preskoc
  mezeraza = inherits: \preskoc
  vzdalenost = DIMENSION
  headseparator = TEXT
  mezi = BEFEHL
  pismeno = STYLE BEFEHL
  barva = COLOR
  offsetvrsku = DIMENSION
  offsetspodku = DIMENSION
  cislo = ano ne zadny
  group = TEXT
  levyokraj = DIMENSION
  pravyokraj = DIMENSION
  innermargin = DIMENSION
  outermargin = DIMENSION
  zarovnani = inherits: \nastavzarovnani
  sirka = prizpusobive max DIMENSION
  minsirka = prizpusobive DIMENSION
  maxsirka = DIMENSION
  inherits: \setupcounter
```

\setupfontexpansion [...¹,] [...²,...]

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  natahnout = NUMMER
  shrink = NUMMER
  krok = NUMMER
```

\setupfontprotrusion [...¹,] [...²,...]

```
1 NAME
2 vector = NAME
  faktor = NUMMER
  vlevo = NUMMER
  vpravo = NUMMER
```

\setupfonts [...^{*},...]

```
* language = ne auto
```

\setupfontsolution [...¹,...] [...²,...]

```
1 NAME OPT
2 goodies = FILE
  solution = NAME
  less = NAME
  more = NAME
  metoda = preroll split normalni reverse nahodny
  kriterium = NUMMER
```

\setupforms [...^{*},...]

```
* metoda = XML HTML PDF
  export = ano ne
```

```

\setupformula [...1,...] [...2...,...]
1 NAME OPT
2 misto = vlevo vpravo
zarovnani = vlevo nastred vpravo flushleft center flushright normalni
split = ano ne stranka
strut = ano ne
vzdalenost = DIMENSION
vlevo = BEFEHL
vpravo = BEFEHL
mezerapred = inherits: \preskoc
mezeraza = inherits: \preskoc
ciselny prikaz = \...##1
barva = COLOR
stylciska = STYLE BEFEHL
barvaciska = COLOR
volba = zhustene tight nastred ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont
marginalie = ano ne standardni DIMENSION
levyokraj = DIMENSION
pravyokraj = DIMENSION
alternativa = NAME
odsadpristi = ano ne auto
mrizka = inherits: \snaptogrid
ramecek = cislo
zaveseni = zadny auto
expanzen = ano ne xml
referenceprefix = + - TEXT
xmlsetup = NAME
catcodes = NAME
inherits: \setupcounter

```

```

\setupformulaframed [...1,...] [...2...,...]
1 NAME OPT
2 inherits: \nastavoramovani

```

```

\setupframedcontent [...1,...] [...2...,...]
1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
leftoffser = DIMENSION
pravyoffset = DIMENSION
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
korekceradku = ano ne
inherits: \nastavoramovani

```

```

\setupframedtable [...1] [...2...,...]
1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
vzdalenost = DIMENSION
inherits: \nastavoramovani

```

```

\setupframedtablecolumn [...1] [...2] [...3...,...]
1 NAME OPT
2 NUMMER kazdy
3 inherits: \nastavoramovani

```

```

\setupframedtablerow [...1] [...2] [...3...,...]
1 NAME OPT
2 NUMMER kazdy
3 inherits: \nastavoramovani

```

```

\setupframedtext [...1,...] [...2...,...]
1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
vnitrni = BEFEHL
misto = vlevo vpravo nastred zadny
korekcehloubky = zap vyp
zakladnifont = inherits: \nastavzakladnifont
odsazovani = inherits: \nastavodsazovani
pismeno = STYLE BEFEHL
barva = COLOR
inherits: \nastavoramovani inherits: \setupplacement

```

`\setupglobalreferenceprefix [...]`

* + - TEXT

`\setupheadalternative [...1,...] [...2,...]`

1 NAME OPT
2 alternativa = horizontalne vertikalne nekde
renderingsetup = NAME

`\setuphelp [...1,...] [...2,...]`

1 NAME OPT
2 inherits: \nastavoramovani

`\setuphigh [...1,...] [...2,...]`

1 NAME OPT
2 vzdalenost = DIMENSION
up = DIMENSION
pismo = STYLE BEFEHL
barva = COLOR

`\setuphighlight [...1,...] [...2,...]`

1 NAME OPT
2 prikaz = ano ne
pismo = STYLE BEFEHL
barva = COLOR

`\setuphyphenation [...*,...]`

* metoda = original tex implicitni hyphenate expanded traditional zadny

`\setupcharacterkerning [...1,...] [...2,...]`

1 NAME OPT
2 faktor = max NUMMER
sirka = DIMENSION
features = NAME
pismo = STYLE BEFEHL
barva = COLOR

`\setupcharacterspacing [...1] [...2] [...3,...]`

1 NAME OPT
2 NUMMER
3 vlevo = NUMMER
vpravo = NUMMER
alternativa = 0 1

`\setupchemical [...1,...] [...2,...]`

1 NAME OPT
2 strut = ano ne auto kap prizpusobive radek implicitni CHARACTER
sirka = prizpusobive zadny NUMMER
vyska = prizpusobive zadny NUMMER
vlevo = prizpusobive zadny NUMMER
vpravo = prizpusobive zadny NUMMER
vrsek = prizpusobive zadny NUMMER
spodek = prizpusobive zadny NUMMER
meritko = male sredni velke normalni NUMMER
rotace = NUMMER
symzarovnani = auto
osa = zap vyp
barvaramecku = COLOR
tloustkalinky = DIMENSION
offset = DIMENSION
jednotka = DIMENSION
faktor = NUMMER
ramecek = zap vyp
barvalinky = COLOR
zakladnifont = inherits: \nastavzakladnifont
velikost = male sredni velke
pismo = STYLE BEFEHL
barva = COLOR

`\setupchemicalframed [...1,...] [...2,...]`

1 NAME OPT
2 inherits: \nastavoramovani

`\setupindentedtext [...1,...] [...2,...,...]`

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
vzdalenost = DIMENSION
vzor = TEXT
text = TEXT
sirka = prizpusobive siroky DIMENSION
oddelovac = BEFEHL
pismeno = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR

`\setupinitial [...1,...] [...2,...,...]`

1 NAME OPT
2 n = NUMMER
m = NUMMER
pred = BEFEHL
vzdalenost = DIMENSION
hoffset = DIMENSION
voffset = radek DIMENSION
pismeno = STYLE BEFEHL
barva = COLOR
font = FONT
text = TEXT
misto = marginalie text
metoda = prvni posledni auto zadny

`\setupinsertion [...1,...] [...2,...,...]`

1 NAME OPT
2 misto = stranka text sloupce firstcolumn lastcolumn

`\setupitaliccorrection [...*,...]`

* text vzdy globalne zadny

```

\setupitemgroup [^1] [^2,...] [^3,...] [^4,...]
1 NAME OPT OPT OPT
2 kazdy NUMMER
3 uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraji naokraji dotextu uvolnene
prizpusobive nofit odstavec spojeny semknuto predel nostopper rozbalene opakovat norepeat reverse sloupce jedna dve tri
ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto horizontalne NAME
4 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
predhlavickou = BEFEHL
pohlavicce = BEFEHL
textvlevo = BEFEHL
textvpravo = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
faktor = NUMMER
krok = DIMENSION
sirka = DIMENSION
vzdalenost = DIMENSION
marginalie = ano ne standardni DIMENSION
levyokraj = ano ne standardni DIMENSION
pravyokraj = ano ne standardni DIMENSION
zarovnani = inherits: \nastavzarovnani
odsazovani = inherits: \nastavodsazovani
start = NUMMER
symzarovnani = vlevo nastred vpravo flushleft center flushright
symbol = NAME
n = NUMMER
odsadpristi = ano ne auto
vnitri = BEFEHL
prikaz = CSNAME
polozky = NUMMER
maxsirka = DIMENSION
itemalign = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
alignsymbol = ano ne
textdistance = male stredni velke zadny mezera DIMENSION
predelmista = ano ne
pismeno = STYLE BEFEHL
barva = COLOR
stylhlavicky = STYLE BEFEHL
barvahlavicky = COLOR
stylsnacky = STYLE BEFEHL
barvaznacky = COLOR
stylsymboly = STYLE BEFEHL
barvasymbolu = COLOR
mrizka = inherits: \definegridsnapping
inherits: \setupcounter

```

\setupitemgroup [...¹,...] [...²,...] [...³,...]

```

1  NAME NAME:NUMMER OPT
2  pred             = BEFEHL
   po               = BEFEHL
   mezi            = BEFEHL
   predhlavickou   = BEFEHL
   pohlavice       = BEFEHL
   textvlevo       = BEFEHL
   textvpravo      = BEFEHL
   vlevo           = BEFEHL
   vpravo          = BEFEHL
   faktor          = NUMMER
   krok            = DIMENSION
   sirka           = DIMENSION
   vzdalenost      = DIMENSION
   volba           = uvod nahodny pokracovat zhustene autouvod široky text pred po zadnabila marginalie naokraji naokraji
                    dotextu uvolnene prizpusobive nofit odstavec spojeno semknuto predel rozbale ne opakovat norepeat reverse
                    sloupce jedna dve tri ctyri pet six seven eight nine standardni NUMMER*siroky NUMMER*semknuto horizontalne
                    NAME
   marginalie      = ano ne standardni DIMENSION
   levyokraj       = ano ne standardni DIMENSION
   pravyokraj      = ano ne standardni DIMENSION
   zarovnani       = inherits: \nastavzarovnani
   odsazovani      = inherits: \nastavodsazovani
   start           = NUMMER
   symzarovnani    = vlevo nastred vpravo flushleft center flushright
   symbol          = NAME
   n               = NUMMER
   odsadpristi     = ano ne auto
   vnitri          = BEFEHL
   prikaz          = CSNAME
   polozky         = NUMMER
   maxsirka        = DIMENSION
   itemalign       = vlevo vpravo nastred flushleft flushright uvnitr vnejsi
   alignsymbol     = ano ne
   textdistance    = male stredni velke zadny mezera DIMENSION
   predelmista     = ano ne
   pismo           = STYLE BEFEHL
   barva           = COLOR
   stylhlavicky    = STYLE BEFEHL
   barvahlavicky   = COLOR
   stylsnacky      = STYLE BEFEHL
   barvaznacky     = COLOR
   stylsymboly     = STYLE BEFEHL
   barvasymbolu    = COLOR
   mritzka         = inherits: \definegridsnapping
   inherits: \setupcounter

```

\nastaveniITEMGROUP [...¹,...] [...²,...] [...³,...]

```

1  kazdy NUMMER OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup
instances: itemize

```

\nastaveniitemize [...¹,...] [...²,...] [...³,...]

```

1  kazdy NUMMER OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup

```

\setuplabel [...¹,...] [...²,...]

```

1  NAME          OPT
2  titul          = ano ne
   cislo          = ano ne
   ciselnyprikaz  = \...##1
   vzdalenosttitulek = DIMENSION
   styltitulek    = STYLE BEFEHL
   barvatitulek   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   vlevo          = BEFEHL
   vpravo         = BEFEHL
   symbol         = BEFEHL
   starter        = BEFEHL
   predel         = BEFEHL
   propojeni      = NAME
   counter        = NAME
   uroven         = NUMMER
   text           = TEXT
   headcommand    = \...##1
   pred           = BEFEHL
   po             = BEFEHL
   mezi           = BEFEHL
   alternativa    = vlevo vpravo naokraj i vlevo i vpravo marginalie lev yokraj prav yokraj innermargin outermargin semknuto
                   visici vrsek prikaz dotextu NAME
   zarovnani      = inherits: \nastavzarovnani
   headalign      = inherits: \nastavzarovnani
   odsazovani     = inherits: \nastavodsazovani
   obrazovka      = ano ne
   odsadpristi    = ano ne auto
   sirka          = prizpusobive siroky radek DIMENSION
   vzdalenost     = zadny DIMENSION
   natahnout      = NUMMER
   shrink         = NUMMER
   zaveseni       = prizpusobive siroky zadny marginalie NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expanzen       = ano ne xml
   referenceprefix = + - TEXT
   vzor           = TEXT
   marginalie     = ano ne standardni DIMENSION
   pismo          = STYLE BEFEHL
   barva          = COLOR
   stylhlavicky   = STYLE BEFEHL
   barvahlavicky  = COLOR
   inherits: \setupcounter

```

\setuplayer [...¹,...] [...²,...]

```

1  NAME          OPT
2  status        = start stop pokracovat dalsi opakovat
   volba         = test
   stranka       = NUMMER
   sirka         = DIMENSION
   vyska         = DIMENSION
   region        = NAME
   rotace        = vlevo vpravo uvnitr vnejsi NUMMER
   position      = ano ne prekryv
   hoffset       = max DIMENSION
   voffset       = max DIMENSION
   offset        = DIMENSION
   dx            = DIMENSION
   dy            = DIMENSION
   sx            = NUMMER
   sy            = NUMMER
   x             = DIMENSION
   y             = DIMENSION
   roh           = vlevo nastred vpravo vrsek spodek
   misto         = mrizka vlevo nastred vpravo vrsek spodek radek l c r m t b g
   radek         = NUMMER
   sloupec       = NUMMER
   smer          = normalni reverse
   oboustranne   = ano ne
   metoda        = prizpusobive prekryv
   opakovat      = ano
   prednastaveni = lefttop righttop leftbottom rightbottom nastred middletop middlebottom middleleft middleright lefttoleft
                   lefttopright NAME

```

\setuplayeredtext [...¹,...] [...²,...]

```

1  NAME          OPT
2  pismo         = STYLE BEFEHL
   barva         = COLOR
   inherits: \nastavoramovani

```


\setuplayouttext [¹...] [²...] [...³...]

```

1 vrsek zahlavi text upati OPTspodek
2 text marginalie hrana
3 status      = start stop prazdne vysoko zadny normalni zadneznaceni NAME
  pismeno     = STYLE BEFEHL
  barva       = COLOR
  strut       = ano ne
  n           = NUMMER
  pred        = BEFEHL
  po          = BEFEHL
  stylvlevo   = STYLE BEFEHL
  stylvpravo  = STYLE BEFEHL
  barvavlevo  = COLOR
  barvavpravo = COLOR
  sirka       = DIMENSION
  sirkavlevo  = DIMENSION
  sirkavpravo = DIMENSION

```

\setuplinefiller [...¹...] [...²...]

```

1 NAME OPT
2 misto      = vlevo vpravo obe
  rozsah     = vlevo vpravo lokalne
  mp         = NAME
  vyska      = DIMENSION
  hloubka    = DIMENSION
  vzdalenost = DIMENSION
  threshold  = DIMENSION
  tloustkalinky = DIMENSION
  pred       = BEFEHL
  po         = BEFEHL
  barva      = COLOR
  styltextu  = STYLE BEFEHL
  barvatextu = COLOR
  zarovnani  = inherits: \nastavzarovnani

```

\setuplinefillers [...¹...] [...²...]

```

1 NAME OPT
2 inherits: \setuplinefiller

```

\setuplinenote [...¹...] [...²...]

```

1 NAME OPT
2 compress      = ano ne
  compressmethod = separator predel mezera
  compressseparator = BEFEHL
  compressdistance = DIMENSION
  inherits: \setupnote

```

\setuplinetable [¹...] [²...] [...³...]

```

1 r c OPT OPT
2 liche sude zahlavi NUMMER
3 radky      = prizpusobive NUMMER
  pred       = BEFEHL
  po         = BEFEHL
  mezi       = BEFEHL
  natahnout  = ano ne DIMENSION
  maxsirka   = prizpusobive DIMENSION
  nvlevo     = NUMMER
  n          = NUMMER
  opakovat   = ano ne
  nx         = NUMMER
  sirka      = DIMENSION
  vyska      = prizpusobive radek DIMENSION
  vzdalenost = DIMENSION
  levyoffset = DIMENSION
  pravyoffset = DIMENSION
  zarovnani  = inherits: \nastavzarovnani
  pozadi     = barevne
  barvapoziadi = COLOR
  xheight    = max DIMENSION
  xdepth     = max DIMENSION
  pismeno    = STYLE BEFEHL
  barva      = COLOR

```

`\setuplistalternative [...,1...] [...,2...]`

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
  prikaz = \...##1##2##3
  renderingsetup = NAME
  sirka = DIMENSION
  vzdalenost = DIMENSION
  natahnout = DIMENSION
  filler = BEFEHL
```

`\setuplistextra [...,1...] [...,2...]`

```
1 NAME OPT
2 pred = BEFEHL
  po = BEFEHL
```

`\setuplocalfloats [...,*...]`

```
* pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
```

`\setuplocalinterlinespace [...,1...] [...,2...]`

```
1 NAME OPT
2 inherits: \nastavmeziradkovoumezeru
```

`\setuplocalinterlinespace [...,*...]`

```
* zap vyp reset auto male stredni vel4PTke NUMMER DIMENSION
```

`\setuplocalinterlinespace [...]`

```
* NAME
```

`\setuplow [...,1...] [...,2...]`

```
1 NAME OPT
2 vzdalenost = DIMENSION
  down = DIMENSION
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\setuplowhigh [...,1...] [...,2...]`

```
1 NAME OPT
2 vzdalenost = DIMENSION
  up = DIMENSION
  down = DIMENSION
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\setuplowmidhigh [...,1...] [...,2...]`

```
1 NAME OPT
2 up = DIMENSION
  down = DIMENSION
  pismeno = STYLE BEFEHL
  barva = COLOR
```

`\setupMPgraphics [...,*...]`

```
* barva = lokalne globalne
  mpy = FILE
```

`\setupMPinstance [...,1...] [...,2...]`

```
1 NAME OPT
2 formatovat = metafun mpost
  initializations = ano ne
  setups = NAME
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  extensions = ano ne
  metoda = binary decimal double scaled implicitni
```

`\setupMPpage [...,*...]`

```
* inherits: \setupfittingpage
```

`\setupMPvariables [...1] [...2...]`

1 NAME OPT
2 KEY = VALUE

`\setupmarginblock [...1] [...2...]`

1 NAME OPT
2 status = start stop
sirka = DIMENSION
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
zarovnani = inherits: \nastavzarovnani
pismo = STYLE BEFEHL
barva = COLOR
vrsek = BEFEHL
spodek = BEFEHL
misto = vlevo vpravo nastred naokraji
vlevo = BEFEHL
vpravo = BEFEHL

`\setupmargindata [...1] [...2...]`

1 NAME OPT
2 strut = ano ne auto kap prizpusobive radek implicitni CHARACTER
prikaz = \...##1
sirka = DIMENSION
zarovnani = inherits: \nastavzarovnani
anchor = region text
misto = vlevo vpravo uvnitr vnejsi
metoda = vrsek radek prvni podlehloubky vyska
category = implicitni hrana
rozsah = lokalne globalne
volba = text odstavec
marginalie = lokalne normalni marginalie hrana
vzdalenost = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
dy = DIMENSION
bottomspace = DIMENSION
threshold = DIMENSION
radek = NUMMER
stack = ano pokracovat
pismo = STYLE BEFEHL
barva = COLOR

`\setupmarginframed [...1] [...2...]`

1 NAME OPT
2 inherits: \nastavoramovani

`\setupmarginrule [...1] [...2...]`

1 NUMMER OPT
2 inherits: \setupsidebar

`\setupmathalignment [...1] [...2...]`

1 NAME OPT
2 n = NUMMER
m = NUMMER
vzdalenost = DIMENSION
cislo = auto
oddelovac = TEXT
zarovnani = vlevo nastred vpravo normalni
misto = vrsek center spodek normalni
mrizka = math ne

`\setupmathcases [...1] [...2...]`

1 NAME OPT
2 vlevo = BEFEHL
vpravo = BEFEHL
strut = ano ne
pismo = STYLE BEFEHL
vzdalenost = DIMENSION
numberdistance = DIMENSION

```

\setupmathematics [...1,...] [...2.,...]
1 NAME OPT
2
openup = ano ne
sadasymbolu = NAME
functionstyle = STYLE BEFEHL
compact = ano ne
zarovnani = l2r r2l
bidi = ano ne
sygreek = normalni kurziva zadny
lcgreek = normalni kurziva zadny
ucgreek = normalni kurziva zadny
italics = 1 2 3 4 zadny reset
autopunctuation = ano ne vse comma yes,semicolon comma,semicolon all,semicolon
setups = NAME
domain = NAME reset
styltextu = STYLE BEFEHL
barvatextu = COLOR
functioncolor = COLOR
integral = limits nolimits autolimits displaylimits zadny
stylealternative = NAME
implicitni = normalni kurziva
fraction = ams ctx
ampersand = normalni

```

```

\setupmathfence [...1,...] [...2.,...]
1 NAME OPT
2
prikaz = ano ne
vlevo = NUMMER
stredni = NUMMER
vpravo = NUMMER
mathstyle = obrazovka text script scriptscript cramped uncramped normalni zhustene male velke
barva = COLOR
status = auto
metoda = auto
faktor = zadny auto NUMMER
mathclass = NUMMER

```

```

\setupmathfraction [...1,...] [...2.,...]
1 NAME OPT
2
vzdalenostvrsku = DIMENSION
vzdalenostspodku = DIMENSION
marginalie = DIMENSION
barva = COLOR
strut = ano ne math tight
alternativa = uvnitr vnejsi obe
linka = ano ne auto
vlevo = NUMMER
vpravo = NUMMER
tloustkalinky = DIMENSION
mathstyle = STYLE BEFEHL
vzdalenost = ne zadny prekryv
inlinethreshold = auto NUMMER
displaythreshold = auto NUMMER
fences = NAME

```

```

\setupmathfractions [...1,...] [...2.,...]
1 NAME OPT
2 inherits: \setupmathfraction

```

```

\setupmathframed [...1,...] [...2.,...]
1 NAME OPT
2 inherits: \nastavoramovani

```

```

\setupmathmatrix [...1,...] [...2.,...]
1 NAME OPT
2
vlevo = BEFEHL
vpravo = BEFEHL
strut = ano ne NUMMER
zarovnani = vlevo nastred vpravo normalni
pismeno = STYLE BEFEHL
vzdalenost = DIMENSION
simplecommand = TEXT
misto = vrsek spodek vysoko nizko nivy normalni

```

```

\setupmathornament [...1,...] [...2,...]
1 NAME OPT
2 alternativa = mp
  barva       = COLOR
  mpoffset    = DIMENSION
  mp          = NAME

```

```

\setupmathradical [...1,...] [...2,...]
1 NAME OPT
2 alternativa = implicitni normalni mp
  barva       = COLOR
  mpoffset    = DIMENSION
  mp          = NAME

```

```

\setupmathstackers [...1,...] [...2,...]
1 NAME OPT
2 vlevo       = BEFEHL
  vpravo      = BEFEHL
  topcommand  = \...##1
  bottomcommand = \...##1
  middlecommand = \...##1
  mp          = NAME
  mpheight    = DIMENSION
  mpdepth     = DIMENSION
  mpoffset    = DIMENSION
  barva       = COLOR
  hoffset     = DIMENSION
  voffset     = DIMENSION
  minvyska    = DIMENSION
  mindepth    = DIMENSION
  mathclass   = rel ord
  offset      = min max normalni
  misto       = vrsek spodek vysoko nizko nastred NUMMER
  strut       = ano ne
  alternativa = normalni implicitni mp
  minsirka    = DIMENSION
  vzdalenost  = DIMENSION
  moffset     = DIMENSION
  order       = normalni reverse
  mathlimits  = ano ne

```

```

\setupmathstyle [...*...]
* obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME

```

```

\setupmixedcolumns [...1,...] [...2,...]
1 NAME OPT
2 mrizka      = inherits: \definegridsnapping
  tloustkalinke = DIMENSION
  metoda      = otr box
  pred        = BEFEHL
  po          = BEFEHL
  vzdalenost  = DIMENSION
  n           = NUMMER
  maxvyska    = DIMENSION
  maxsirka    = DIMENSION
  krok        = DIMENSION
  profile     = NAME
  zarovnani   = inherits: \nastavzarovnani
  setups      = NAME
  rovnovaha   = ano ne
  splitmethod = zadny fixne
  alternativa = lokalne globalne
  internalgrid = radek pulradku
  oddelovac   = linka
  strut       = ano ne
  barva       = COLOR
  barvalinke  = COLOR
  smer        = normalni reverse
  inherits: \nastavoramovani

```

```

\setupmodule [...1,...] [...2,...]
1 FILE OPT
2 test = ano ne
  KEY  = VALUE

```

`\setupnotation [...1,...] [...2...,...]`

```

1  NAME                      OPT
2  titul                     = ano ne
   cislo                     = ano ne
   typ                       = note
   ciselnyprikaz             = \...##1
   vzdalenosttitulek        = DIMENSION
   styltitulek               = STYLE BEFEHL
   barvatitulek              = COLOR
   titlecommand              = \...##1
   titleleft                 = BEFEHL
   titleright                = BEFEHL
   vlevo                     = BEFEHL
   vpravo                    = BEFEHL
   symbol                    = BEFEHL
   starter                   = BEFEHL
   predel                    = BEFEHL
   propojeni                 = NAME
   counter                   = NAME
   uroven                    = NUMMER
   text                      = TEXT
   headcommand               = \...##1
   pred                      = BEFEHL
   po                        = BEFEHL
   mezi                      = BEFEHL
   alternativa               = vlevo vpravo naokraj i vlevo i vpravo
                               marginalie levyokraj pravyokraj innermargin outermargin semknuto
                               visici vrsek prikaz note NAME
   zarovnnani                = inherits: \nastavzarovnnani
   headalign                  = inherits: \nastavzarovnnani
   odsazovani                = inherits: \nastavodsazovani
   obrazovka                 = ano ne
   odsadpristi               = ano ne auto
   sirka                     = prizpusobive siroky radek DIMENSION
   vzdalenost                = zadny DIMENSION
   natahnout                 = NUMMER
   shrink                    = NUMMER
   zaveseni                  = prizpusobive siroky zadny marginalie NUMMER
   closesymbol               = BEFEHL
   closecommand              = \...##1
   expanzen                  = ano ne xml
   referenceprefix           = + - TEXT
   vzor                      = TEXT
   marginalie                 = ano ne standardni DIMENSION
   pismo                     = STYLE BEFEHL
   barva                     = COLOR
   stylhlavicky              = STYLE BEFEHL
   barvahlavicky             = COLOR
   inherits: \setupcounter

```

`\setupnotations [...1,...] [...2...,...]`

```

1  NAME                      OPT
2  inherits: \setupnotation

```

\setupnote [...¹,...] [...²...,...]

```
1 NAME OPT
2 interakce = ano ne cislo text vse
  symbolcommand = \...##1
  textovyprikaz = \...##1
  indikator = ano ne
  oddelovactextu = BEFEHL
  sirka = DIMENSION
  vyska = DIMENSION
  vzdalenost = DIMENSION
  rulecommand = BEFEHL
  linka = zap vyp normalni vlevo vpravo prikaz odstavec
  split = tolerantni striktni velmistriktni NUMMER
  faktor = NUMMER
  misto = text stranka vysoko spodek zadny sloupce firstcolumn lastcolumn
  dalsi = BEFEHL
  n = NUMMER
  barvalinky = COLOR
  tloustkalinky = DIMENSION
  setups = NAME
  meziradkovamezera = NAME
  odstavec = ano ne
  pred = BEFEHL
  po = BEFEHL
  mezi = BEFEHL
  rozsah = stranka
  vzdalenostsloupcu = DIMENSION
  pokracovat = ano ne
  alternativa = mrizka fixne sloupce note zadny
  kriterium = stranka
  zakladnifont = inherits: \nastavzakladnifont
  zarovnani = inherits: \nastavzarovnani
  styltextu = STYLE BEFEHL
  barvatextu = COLOR
  anchor = dalsi
  mezerapred = inherits: \preskoc
  spaceinbetween = inherits: \preskoc
  inherits: \nastavoramovani
```

\setupnotes [...¹,...] [...²...,...]

```
1 NAME OPT
2 inherits: \setupnote
```

\setupoffset [...^{*}...,...]

* inherits: \setupoffsetbox

\setupoffsetbox [...^{*}...,...]

```
* x = DIMENSION
  y = DIMENSION
  levyoffset = DIMENSION
  pravyoffset = DIMENSION
  offsetvrsku = DIMENSION
  offsetspodku = DIMENSION
  metoda = fixne
  sirka = DIMENSION
  vyska = DIMENSION
  hloubka = DIMENSION
  misto = vlevo nastred vpravo vrsek spodek radek l c r m t b g
```

\setupoutputroutine [...¹] [...²...,...]

```
1 NAME OPT
2 KEY = CSNAME
```

\setupoutputroutine [...]

* NAME

\setuppagegrid [...¹,...] [...²,...]

1 NAME OPT
2 n = NUMMER
nvlevo = NUMMER
nvpravo = NUMMER
sirka = DIMENSION auto
vzdalenost = DIMENSION
radky = NUMMER
maxsirka = DIMENSION
maxvyska = DIMENSION
smer = normalni reverse
stranka = inherits: \strana
inherits: \nastavoramovani

\setuppagegridarea [...¹,...] [...²,...]

1 NAME OPT
2 status = start stop opakovat
x = NUMMER
y = NUMMER
nx = NUMMER
ny = NUMMER
pismeno = STYLE BEFEHL
barva = COLOR
clipoffset = DIMENSION
pravyoffset = DIMENSION
inherits: \nastavoramovani

\setuppagegridareatext [...¹] [...²]

1 NAME
2 TEXT

\setuppagegridlines [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppagegridspan [...¹,...] [...²,...]

1 NAME OPT
2 n = NUMMER
pismeno = STYLE BEFEHL
barva = COLOR
pred = BEFEHL
po = BEFEHL
inherits: \nastavoramovani

\setuppagegridstart [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppagechecker [...¹,...] [...²,...]

1 NAME OPT
2 radky = NUMMER
offset = DIMENSION
metoda = 0 1 2 3
pred = BEFEHL
po = BEFEHL
mezi = BEFEHL

\setuppageinjection [...¹,...] [...²,...]

1 NAME OPT
2 status = predchozi dalsi NUMMER
prodleva = ano ne
alternativa = obrazek buffer setups zadny NAME
stranka = inherits: \strana
pagestate = start stop
n = NUMMER
inherits: \nastavoramovani

\setuppageinjectionalternative [...¹,...] [...²,...]

1 NAME OPT
2 renderingsetup = NAME

\setuppageshift [...]¹ [...]² [...]³

1 stranka papir OPT OPT
2 NAME
3 NAME

\setuppagestate [...]¹ [...]² [...]

1 NAME OPT
2 prodleva = ano ne

\setuppairedbox [...]¹ [...]² [...]

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
misto = vlevo nastred vpravo vrsek spodek vysoko nizko
n = NUMMER
vzdalenost = DIMENSION
zakladnifont = inherits: \nastavzakladnifont
sirka = DIMENSION
vyska = DIMENSION
maxsirka = DIMENSION
maxvyska = DIMENSION
zarovnani = inherits: \nastavzarovnani
pismo = STYLE BEFEHL
barva = COLOR

\nastaveniPAIREDBOX [...]^{*} [...]

* inherits: \setuppairedbox
instances: legend

\nastavenilegend [...]^{*} [...]

* inherits: \setuppairedbox

\setuppaper [...]^{*} [...]

* inherits: \nastavvelikostpapiru

\setupparagraph [...]¹ [...]² [...]

1 NAME OPT
2 pismo = STYLE BEFEHL
barva = COLOR
zarovnani = inherits: \nastavzarovnani
setups = NAME

\setupparagraphintro [...]¹ [...]²

1 reset kazdy prvni dalsi
2 BEFEHL

\setupparallel [...]¹ [...]² [...]³ [...]

1 NAME
2 NAME
3 setups = NAME
start = NUMMER
n = NUMMER
kriterium = vse

\setupperiods [...]^{*} [...]

* n = NUMMER
sirka = DIMENSION prizpusobive
vzdalenost = DIMENSION
symbol = BEFEHL

\setupplacement [...]¹ [...]² [...]

1 NAME OPT
2 pred = BEFEHL
po = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
mrizka = inherits: \snaptogrid
korekceradku = zap vyp
korekcehloubky = zap vyp
marginalie = ano ne standardni

\setuppositionbar [...,¹...²...]

* pismo = STYLE BEFEHL
barva = COLOR
n = NUMMER
min = NUMMER
max = NUMMER
text = TEXT
sirka = DIMENSION
vyska = DIMENSION
hloubka = DIMENSION

\setupprocessor [...,¹...] [...,²...]

1 NAME ^{OPT}
2 status = start stop
vlevo = BEFEHL
vpravo = BEFEHL
prikaz = \...##1
pismo = STYLE BEFEHL
barva = COLOR

\setupprofile [...,¹...] [...,²...]

1 NAME ^{OPT}
2 vyska = DIMENSION
hloubka = DIMENSION
vzdalenost = DIMENSION
faktor = NUMMER
radky = NUMMER
metoda = striktni fixne zadny

\setupquotation [...,¹...]

* inherits: \setupdelimitedtext

\setuprealpagenumber [...,¹...]

* inherits: \setupcounter

\setupreferenceformat [...,¹...] [...,²...]

1 NAME ^{OPT}
2 popis = * NAME
vlevo = BEFEHL
vpravo = BEFEHL
typ = implicitni text titul cislo stranka realpage
setups = NAME
autocase = ano ne
text = TEXT
pismo = STYLE BEFEHL
barva = COLOR

\setupreferenceprefix [...]

* + - TEXT

\setupreferencestructureprefix [...¹] [...²] [...,³...]

1 NAME ABSCHNITT ^{OPT} ^{OPT}
2 implicitni
3 prefix = ano ne
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:vse
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:vse
numberseparatorset = NAME
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupregisters [...¹] [...,²...]

1 NAME NAME:NUMMER ^{OPT}
2 inherits: \nastavrejstrik

```
\setupregisters [...,1...] [...,2...] [...,3...,...]
1 NAME OPT OPT
2 NUMMER
3 inherits: \nastavrejstrik
```

```
\setuprenderingwindow [...,1...] [...,2...,...]
1 NAME OPT
2 akceotevrenistranky = REFERENCE
akcezavrenistranky = REFERENCE
inherits: \nastavoramovani
```

```
\setups [...,*...]
* NAME
```

```
\setupscale [...,1...] [...,2...,...]
1 NAME OPT
2 meritko = NUMMER
xmeritko = NUMMER
ymeritko = NUMMER
sirka = DIMENSION
vyska = DIMENSION
hloubka = ano ne
radky = NUMMER
faktor = prizpusobive siroky max auto implicitni
vfaktor = prizpusobive siroky max auto implicitni
sfaktor = prizpusobive siroky max auto implicitni
maxsirka = DIMENSION
maxvyska = DIMENSION
s = NUMMER
sx = NUMMER
sy = NUMMER
equalwidth = DIMENSION
equalheight = DIMENSION
mrizka = ano prizpusobive vyska podlehloubky pulradku
```

```
\setupscript [...,1...] [...,2...,...]
1 NAME OPT
2 metoda = hangul hanzi nihongo ethiopic thai test
prednastaveni = NAME
features = auto
```

```
\setupscripts [...,1...] [...,2...,...]
1 NAME OPT
2 inherits: \setupscript
```

```
\setupselector [...,1...] [...,2...,...]
1 NAME
2 n = NUMMER
m = NUMMER
```

```
\setupshift [...,1...] [...,2...,...]
1 NAME OPT
2 pokracovat = ano ne
jednotka = ex em pt in cm mm sp bp pc dd cc nc
metoda = NUMMER
dy = NUMMER
zarovnani = inherits: \nastavzarovnani
pismo = STYLE BEFEHL
barva = COLOR
```

```
\setupsidebar [...,1...] [...,2...,...]
1 NAME OPT
2 tloustkalinky = DIMENSION
barvalinky = COLOR
alternativa = NUMMER
offsetvrsku = DIMENSION
offsetspodku = DIMENSION
vzdalenost = DIMENSION
vzdalenostlevehookraje = DIMENSION
uroven = NUMMER
```

`\setupspellchecking [...,*...,...]`

* status = start stop
metoda = 1 2 3
seznam = NAME

`\setupstartstop [...,1...] [...,2...,...]`

1 NAME ^{OPT}
2 pred = BEFEHL
po = BEFEHL
mezi = BEFEHL
setups = NAME
vlevo = BEFEHL
vpravo = BEFEHL
pismoeno = STYLE BEFEHL
barva = COLOR

`\setupstretched [...,*...,...]`

* inherits: \setupcharacterkerning

`\setupstruts [...*...]`

* ano ne auto kap^{OPT}prizpusobive radek implicitni CHARACTER

`\setupstyle [...,1...] [...,2...,...]`

1 NAME ^{OPT}
2 metoda = prikaz
pismoeno = STYLE BEFEHL
barva = COLOR

`\setupsubformula [...,1...] [...,2...,...]`

1 NAME ^{OPT}
2 odsadpristi = ano ne auto

`\setupsubformulas [...,1...] [...,2...,...]`

1 NAME ^{OPT}
2 inherits: \setupsubformula

`\setupsyntex [...,*...,...]`

* status = start stop
metoda = min max

`\setups {...,*...}`

* NAME

`\setupTABLE [...,1...] [...,2...] [...,3...,...]`

1 r c x y row column^{OPT} prvni posledni start zahlavi kazdy liche sude jedna NUMMER -NUMMER
2 prvni least kazdy dve liche sude NUMMER -NUMMER
3 extras = BEFEHL
vlevo = BEFEHL
vpravo = BEFEHL
barvahlavicky = COLOR
stylhlavicky = STYLE BEFEHL
vzdalenostlevehookraje = DIMENSION
vzdalenostpravehookraje = DIMENSION
vzdalenostsloupcu = DIMENSION
maxsirka = DIMENSION
setups = NAME
sirkatextu = DIMENSION lokalne
split = ano ne opakovat auto
zahlavi = opakovat
volba = natahnout tight
pred = BEFEHL
po = BEFEHL
stejnastranka = pred po obe
spaceinbetween = inherits: \preskoc
splitoffset = DIMENSION
aligncharacter = ano ne
alignmentcharacter = TEXT number->TEXT text->TEXT
vzdalenost = DIMENSION
barva = COLOR
pismoeno = math STYLE BEFEHL
inherits: \nastavoramovani

`\setupTEXpage [...,..1...,...]`

* inherits: \setupfittingpage

`\setuptabulation [...,..1...] [...,..2...,...]`

```

1  NAME                      OPT
2  formatovat               = TEMPLATE zadny
   pred                    = BEFEHL
   po                      = BEFEHL
   vzdalenost              = male stredni velke zadny prazdny podlehloubky mrizka DIMENSION
   zarovnani               = vlevo nastred vpravo dimension
   linka                   = radek normalni
   barvalinky              = COLOR
   tloustkalinky          = DIMENSION
   zakladnifont            = inherits: \nastavzakladnifont
   odsazovani              = ano ne
   split                   = ano ne opakovat auto
   jednotka                = DIMENSION
   marginalie              = DIMENSION
   vnitrni                 = BEFEHL
   EQ                      = BEFEHL
   zhlavi                  = ano opakovat text
   ramecek                 = zap vyp
   titul                   = TEXT
   keptogether             = ano ne

```

`\setuptagging [...,..1...,...]`

* status = start stop
metoda = auto

`\setuptextbackground [...,..1...] [...,..2...,...]`

```

1  NAME                      OPT
2  status                   = start stop
   misto                    = text odstavec vzdy zadny
   kriterium                = NUMMER
   alternativa              = NUMMER
   mp                       = NAME
   metoda                   = NAME
   pozadi                   = barevne
   barvapozadi              = COLOR
   roh                      = pravouhly zaobleny
   uroven                   = NUMMER
   offsetpozadi             = DIMENSION
   pred                     = BEFEHL
   po                       = BEFEHL
   zarovnani                = inherits: \nastavzarovnani
   pomlcka                  = NUMMER
   polomer                  = DIMENSION
   ramecek                  = zap vyp
   barvaramecku             = COLOR
   tloustkalinky            = DIMENSION
   voffset                  = DIMENSION
   offsetramecku            = DIMENSION
   levyoffset               = ano ne standardni DIMENSION
   pravyoffset              = ano ne standardni DIMENSION
   offsetvrsku              = male stredni velke radek DIMENSION
   offsetspodku             = male stredni velke radek DIMENSION
   pismo                     = STYLE BEFEHL
   barva                    = COLOR

```

`\setuptextflow [...,..1...] [...,..2...,...]`

```

1  NAME                      OPT
2  sirka                    = DIMENSION
   pismo                     = STYLE BEFEHL
   barva                     = COLOR

```

`\setuptooltip [...,..1...] [...,..2...,...]`

```

1  NAME                      OPT
2  misto                    = vlevo nastred vpravo
   inherits: \nastavoramovani

```

\setupunit [...¹...] [...²...]

1 NAME OPT
2 metoda = 1 2 3 4 5 6
language = SPRACHE
alternativa = text matematika
order = reverse normalni
oddelovac = male stredni velke normalni zadny NAME
mezera = male stredni velke normalni zadny NAME
pismo = STYLE BEFEHL
barva = COLOR

\setupuserpagenumber [...^{*}...]

* viewerprefix = TEXT
status = start stop zadny drzet prazdne
inherits: \setupcounter

\setupversion [...]

* koncept soubor docasne finalni NAME

\setupviewerlayer [...^{*}...]

* titul = TEXT
status = start stop
export = ano ne
tisknutelne = ano ne
rozsah = lokalne globalne
metoda = zadny prikaz

\setupvspacing [...^{*}...]

* inherits: \vspacing OPT

\setupwithargument {...¹} {...²}

1 NAME
2 CONTENT

\setupwithargumentswapped {...¹} {...²}

1 CONTENT
2 NAME

\setupxml [...^{*}...]

* implicitni = skryte zadny text
compress = ano ne

\setupxtable [...¹...] [...²...]

1 NAME OPT
2 sirkatextu = DIMENSION lokalne
zakladnifont = inherits: \nastavzakladnifont
spaceinbetween = inherits: \preskoc
volba = tight max natahnout sirka vyska fixne
vyskatextu = DIMENSION
maxsirka = DIMENSION
vzdalenostsloupcu = DIMENSION
vzdalenostlevehookraje = DIMENSION
vzdalenostpravehookraje = DIMENSION
zahlavi = opakovat
upati = opakovat
tloustkalinky = DIMENSION
split = ano ne opakovat auto
splitoffset = DIMENSION
stejnastranka = pred po obe
vzdalenost = DIMENSION
inherits: \nastavoramovani

\setuvalue {...¹} {...²}

1 NAME
2 CONTENT

\setuxvalue {...¹} {...²}

1 NAME
2 CONTENT

<pre> \setvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setvariables [...] [...,..²...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \setvboxregister ... {...} 1 CSNAME NUMMER 2 CONTENT </pre>
<pre> \setvisualizerfont [...] * FONT OPT </pre>
<pre> \setvtopregister ... {...} 1 CSNAME NUMMER 2 CONTENT </pre>
<pre> \setwidthof ... \to \^2... 1 TEXT 2 CSNAME </pre>
<pre> \setxmeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setxvalue {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setxvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE </pre>
<pre> \setxvariables [...] [...,..²...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE </pre>
<pre> \shapedhbox {...} * CONTENT </pre>
<pre> \SHIFT {...} * CONTENT instances: shiftup shiftdown </pre>
<pre> \shiftdown {...} * CONTENT </pre>
<pre> \shiftup {...} * CONTENT </pre>
<pre> \showallmakeup </pre>

<code>\showattributes</code>
<code>\showboxes</code>
<code>\showbtxdatasetauthors [...,.*,...]</code> <code>* specification = NAME</code> <small>OPT</small> <code>dataset = NAME</code> <code>field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal</code> <code>language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series</code> <code>titul opis volume rok yearfiled NAME</code>
<code>\showbtxdatasetauthors [...]</code> <code>* NAME</code> <small>OPT</small>
<code>\showbtxdatasetcompleteness [...,.*,...]</code> <code>* specification = NAME</code> <small>OPT</small> <code>dataset = NAME</code> <code>field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal</code> <code>language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series</code> <code>titul opis volume rok yearfiled NAME</code>
<code>\showbtxdatasetcompleteness [...]</code> <code>* NAME</code> <small>OPT</small>
<code>\showbtxdatasetfields [...,.*,...]</code> <code>* specification = NAME</code> <small>OPT</small> <code>dataset = NAME</code> <code>field = address assignee autor booktitle kapitola den dayfiled edition editor howpublished institution journal</code> <code>language mesic monthfiled nationality note cislo jedna dve organization pages publisher school series</code> <code>titul opis volume rok yearfiled NAME</code>
<code>\showbtxdatasetfields [...]</code> <code>* NAME</code> <small>OPT</small>
<code>\showbtxfields [...,.*,...]</code> <code>* rotace = NUMBER</code> <small>OPT</small> <code>specification = NAME</code>
<code>\showbtxfields [...]</code> <code>* NAME</code> <small>OPT</small>
<code>\showbtxhashedauthors [...]</code> <code>* TEXT</code> <small>OPT</small>
<code>\showbtxtables [...]</code> <code>* TEXT</code> <small>OPT</small>
<code>\showcolorbar [...]</code> <code>* COLOR</code>
<code>\showcolorcomponents [...]</code> <code>* COLOR</code>
<code>\showcolorset [...]</code> <code>* COLOR</code>
<code>\showcolorstruts</code>
<code>\showcounter [...]</code> <code>* NAME</code>
<code>\showdirectives</code>

<code>\showdirsmargin</code>
<code>\showedebuginfo</code>
<code>\showexperiments</code>
<code>\showfont [...]¹ [...]²,...]</code> 1 FONT OPT 2 NUMMER
<code>\showfontdata</code>
<code>\showfontitalics</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...]*...]</code> * inherits: \nastavzakladnifont
<code>\showfontstyle [...]¹,...]</code> <code>[...]²,...]</code> <code>[...]³,...]</code> <code>[...]⁴,...]</code> 1 inherits: \nastavzakladnifont OPT OPT OPT 2 rm ss tt mm hw cg 3 tf bf it sl bi bs 4 vse NUMMER
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...}¹ [...]²]</code> 1 TEXT 2 REFERENCE
<code>\showhyphenationtrace [...]¹ [...]²]</code> 1 SPRACHE OPT 2 TEXT
<code>\showhyphens {...}</code> * TEXT
<code>\showchardata {...}</code> * TEXT
<code>\showcharratio {...}</code> * TEXT
<code>\showinjector [...]*...]</code> * NAME OPT
<code>\showjustification</code>
<code>\showkerning {...}</code> * TEXT
<code>\showlayoutcomponents</code>

\showligature {...} * TEXT
\showligatures [...]
\showlogcategories
\showmargins
\showmessage {...} {...} {..., 1 NAME 2 NAME NUMBER 3 TEXT
\showminimalbaseline
\shownextbox ... {...} 1 CSNAME 2 CONTENT
\showotfcomposition {...} {...} {...} 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
\showparentchain ... {...} 1 CSNAME 2 NAME
\showsetupsdefinition [...]
\showtimer {...}
\showtokens [...]
\showtrackers
\showvalue {...}
\showvariable {...} {...} 1 NAME 2 KEY
\showwarning {...} {...} {..., 1 NAME 2 NAME NUMBER 3 TEXT
\schovejbloky [..., 1 NAME 2 NAME
\simplealignedbox {...} {...} {...} 1 DIMENSION 2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi 3 CONTENT

```
\simplealignedboxplus {.1.} {.2.} {.3.} {.4.}
1 DIMENSION
2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi
3 TEXT
4 CONTENT
```

```
\simplealignedspreadbox {1.} {2.} {3.}
```

1	DIMENSION
2	vlevo vpravo nastred flushleft flushright uvnitr vnejsi
3	CONTENT

```
\simplegroupedcommand {...} {...}
1  BEFEHL
2  BEFEHL
```

```
\simplereversealignedbox {...} {...} {...}
```

1 DIMENSION

2 vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3 CONTENT

```
\simplereversealignedboxplus {.^1.} {.^2.} {.^3.} {.^4.}
```

1

DIMENSION

2

vlevo vpravo nastred flushleft flushright uvnitr vnejsi

3

TEXT

4

CONTENT

```
\singalcharacteralign {...} {...}
1  NUMBER
2  NUMBER
```

\singlebond

```
\sixthofsixarguments {.1.} {.2.} {.3.} {.4.} {.5.} {.6.}
```

```
1 TEXT
```

```
2 TEXT
```

```
3 TEXT
```

```
4 TEXT
```

```
5 TEXT
```

```
6 TEXT
```

\sklonene

\sklonenetucne

\slantedface

```

\slicepages [1...] [2...,...2...] [3...,...3...]
1 FILE
2 offset = DIMENSION
  hoffset = DIMENSION
  voffset = DIMENSION
  sirka = DIMENSION
  vyska = DIMENSION
  n = NUMBER
3 offset = DIMENSION
  hoffset = DIMENSION
  voffset = DIMENSION
  sirka = DIMENSION
  vyska = DIMENSION
  n = NUMBER

```

```
\slouppec [...,*,...]
* inherits: \columnbreak
```

```
\slovenianNumerals {...}
*   NUMMER
```

<code>\sloveniannumerals {...}</code> * NUMBER
<code>\slovo {...}</code> * TEXT
<code>\slovovpravo [...] {...}</code> 1 vpravo DIMENSION ^{OPT} 2 CONTENT
<code>\smallbodyfont</code>
<code>\smallcappedcharacters {...}</code> * NUMBER
<code>\smallcappedromannumerals {...}</code> * NUMBER
<code>\smaller</code>
<code>\smallskip</code>
<code>\smash [...] {...}</code> 1 w h d t ^{OPT} 2 CONTENT
<code>\smashbox ...</code> * CSNAME NUMBER
<code>\smashboxed ...</code> * CSNAME NUMBER
<code>\smashedhbox ...¹ {...}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\smashedvbox ...¹ {...}</code> 1 TEXT ^{OPT} 2 CONTENT
<code>\suptogrid [...] \²... {...}</code> 1 normalni standardni ano striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halflines NAME 2 CSNAME 3 CONTENT
<code>\suptogrid [...,¹...] \²... {...}</code> 1 inherits: \definegridsnapping ^{OPT} 2 CSNAME 3 CONTENT
<code>\someheadnumber [...] [...]</code> 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
<code>\somekindoftab [...,[*]...,...]</code> * alternativa = horizont ^{OPT} alne vertikalne sirka = DIMENSION vyska = DIMENSION n = NUMBER m = NUMBER

<code>\somalocalfloat</code>
<code>\somenamedheadnumber {...} {...}</code> 1 ABSCHNITT 2 predchozi aktualni dalsi prvni posledni
<code>\someplace {...} {...} {...} {...} {...} [...]</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 REFERENCE
<code>\SORTING [...] {...}</code> 1 NAME <small>OPT</small> 2 CONTENT instances: logo
<code>\logo [...] {...}</code> 1 NAME <small>OPT</small> 2 CONTENT
<code>\spanishNumerals {...}</code> * NUMMER
<code>\spanishnumerals {...}</code> * NUMMER
<code>\splitatasterisk ... \... \...</code> 1 TEXT 2 CSNAME 3 CSNAME
<code>\splitatcolon ... \... \...</code> 1 TEXT 2 CSNAME 3 CSNAME
<code>\splitatcolons ... \... \...</code> 1 TEXT 2 CSNAME 3 CSNAME
<code>\splitatcomma ... \... \...</code> 1 TEXT 2 CSNAME 3 CSNAME
<code>\splitatperiod ... \... \...</code> 1 TEXT 2 CSNAME 3 CSNAME
<code>\splitdfrac {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\splitfilename {...}</code> * FILE
<code>\splitfrac {...} {...}</code> 1 CONTENT 2 CONTENT

<code>\splitoffbase</code>
<code>\splitofffull</code>
<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens</code> ¹ ... \from ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> ¹ ... \at ² ... \to \ ³ ... \and \ ⁴ ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> [*] ... * CSNAME NUMMER
<code>\sqrt</code> [¹ ...] { ² ...} 1 TEXT ^{OPT} 2 CONTENT
<code>\stackrel</code> { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
<code>\stanovcislona</code> [*] ... * ABSCHNITT
<code>\stanovcharakteristickuseznamu</code> [..., ¹ ...] [..., ² ...,...] ^{OPT} 1 LISTE 2 inherits: \nastavseznam
<code>\startalignment</code> [..., [*] ...] ... \stopalignment * inherits: \nastavzarovnani
<code>\startallmodes</code> [..., [*] ...] ... \stopallmodes * NAME
<code>\startATTACHMENT</code> [¹ ...] [..., ² ...,...] ... \stopATTACHMENT ^{OPT} ^{OPT} 1 NAME 2 inherits: \setupattachment instances: attachment
<code>\startattachment</code> [¹ ...] [..., ² ...,...] ... \stopattachment ^{OPT} ^{OPT} 1 NAME 2 inherits: \setupattachment
<code>\startbar</code> [[*] ...] ... \stopbar * NAME

\startbarva [...] ... \stopbarva * COLOR
\startbbordermatrix ... \stopbbordermatrix
\startbitmapimage [...,... [*] ...,...] ... \stopbitmapimage * barva = rgb cmyk seda sirka = DIMENSION vyska = DIMENSION x = NUMMER y = NUMMER
\startbordermatrix ... \stopbordermatrix
\startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions * NAME
\startbuffer [...] ... \stopbuffer * NAME OPT
\startBUFFER ... \stopBUFFER instances: hiding
\starthiding ... \stophiding
\startcatcodetable *... ... \stopcatcodetable * CSNAME
\startcenteraligned ... \stopcenteraligned
\startcollect ... \stopcollect
\startcollecting ... \stopcollecting
\startcolorintent [...] ... \stopcolorintent * knockout overprint zadny
\startcoloronly [...] ... \stopcoloronly * COLOR
\startcolorset [...] ... \stopcolorset * NAME
\startcolumnspan [...,... [*] ...,...] ... \stopcolumnspan * inherits: \setupcolumnspan ^{OPT}
\startcombination [¹ ...] [² ...,... ² ...,...] ... \stopcombination 1 NAME OPT OPT 2 inherits: \setupcombination
\startcombination [¹] [² ...] ... \stopcombination 1 NAME OPT OPT 2 N*M
\startcontextcode ... \stopcontextcode
\startcontextdefinitioncode ... \stopcontextdefinitioncode

$\backslash\text{startctxfunction}$ \dotscdots $\backslash\text{stopctxfunction}$ \ast NAME
$\backslash\text{startctxfunctiondefinition}$ \dotscdots $\backslash\text{stopctxfunctiondefinition}$ \ast NAME
$\backslash\text{startcurrentcolor}$ \dots $\backslash\text{stopcurrentcolor}$
$\backslash\text{startcurrentlistentrywrapper}$ \dots $\backslash\text{stopcurrentlistentrywrapper}$
$\backslash\text{startdelimited}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] [$\overset{3}{\dots},\dots$] \dots $\backslash\text{stopdelimited}$ 1 NAME OPT OPT 2 SPRACHE 3 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startdelimitedtext}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] [$\overset{3}{\dots},\dots$] \dots $\backslash\text{stopdelimitedtext}$ 1 NAME OPT OPT 2 SPRACHE 3 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startDELIMITEDTEXT}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopDELIMITEDTEXT}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$ instances: quotation quote blockquote speech aside
$\backslash\text{startaside}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopaside}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startblockquote}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopblockquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startquotation}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopquotation}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startquote}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopquote}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startspeech}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopspeech}$ 1 SPRACHE OPT OPT 2 inherits: $\backslash\text{startzuzeni}$
$\backslash\text{startdisplaymath}$ \dots $\backslash\text{stopdisplaymath}$
$\backslash\text{startdmath}$ \dots $\backslash\text{stopdmath}$
$\backslash\text{startdocument}$ [$\dots,\overset{\ast}{=}\dots$] \dots $\backslash\text{stopdocument}$ \ast inherits: $\backslash\text{setupdocument}$ ^{OPT}
$\backslash\text{starteffect}$ [$\overset{\ast}{\dots}$] \dots $\backslash\text{stopeffect}$ \ast NAME
$\backslash\text{startEFFECT}$ \dots $\backslash\text{stopEFFECT}$
$\backslash\text{startelement}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] \dots $\backslash\text{stopelement}$ 1 NAME OPT 2 KEY = VALUE

$\backslash\text{startembeddedxtable} [\dots, \dots, \dots] \dots \backslash\text{stopembeddedxtable}$ \ast inherits: $\backslash\text{setupxtable}$ <small>OPT</small>
$\backslash\text{startembeddedxtable} [\dots] \dots \backslash\text{stopembeddedxtable}$ \ast NAME <small>OPT</small>
$\backslash\text{startexceptions} [\dots] \dots \backslash\text{stopexceptions}$ \ast SPRACHE
$\backslash\text{startexpanded} \dots \backslash\text{stopexpanded}$
$\backslash\text{startexpandedcollect} \dots \backslash\text{stopexpandedcollect}$
$\backslash\text{startextendedcatcodetable} \backslash\dots \dots \backslash\text{stopextendedcatcodetable}$ \ast CSNAME
$\backslash\text{startexternalfigurecollection} [\dots] \dots \backslash\text{stopexternalfigurecollection}$ \ast NAME
$\backslash\text{startfittingpage} [\dots] [\dots, \dots, \dots] \dots \backslash\text{stopfittingpage}$ 1 NAME <small>OPT</small> 2 inherits: $\backslash\text{setupfittingpage}$
$\backslash\text{startFITTINGPAGE} [\dots, \dots, \dots] \dots \backslash\text{stopFITTINGPAGE}$ \ast inherits: $\backslash\text{setupfittingpage}$ <small>OPT</small> instances: TEXpage MPpage
$\backslash\text{startMPpage} [\dots, \dots, \dots] \dots \backslash\text{stopMPpage}$ \ast inherits: $\backslash\text{setupfittingpage}$ <small>OPT</small>
$\backslash\text{startTEXpage} [\dots, \dots, \dots] \dots \backslash\text{stopTEXpage}$ \ast inherits: $\backslash\text{setupfittingpage}$ <small>OPT</small>
$\backslash\text{startfixne} [\dots] \dots \backslash\text{stopfixne}$ \ast nizko nastred <small>OPT</small> vysoko nivy implicitni
$\backslash\text{startfloatcombination} [\dots, \dots, \dots] \dots \backslash\text{stopfloatcombination}$ \ast inherits: $\backslash\text{setupcombination}$ <small>OPT</small>
$\backslash\text{startfloatcombination} [\dots] \dots \backslash\text{stopfloatcombination}$ \ast N*M NAME <small>OPT</small>
$\backslash\text{startFLOAttext} [\dots, \dots] [\dots, \dots] \{\dots\} \dots \backslash\text{stopFLOAttext}$ 1 split vzdy vlevo vpravo <small>OPT</small> uvnitr vnejsi <small>OPT</small> zpetnamezera cutspace ivlevo ivpravo naokrazi levyokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati 2 REFERENCE 3 TEXT instances: chemical figure table intermezzo graphic
$\backslash\text{startfiguretext} [\dots, \dots] [\dots, \dots] \{\dots\} \dots \backslash\text{stopfiguretext}$ 1 split vzdy vlevo vpravo <small>OPT</small> uvnitr vnejsi <small>OPT</small> zpetnamezera cutspace ivlevo ivpravo naokrazi levyokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati 2 REFERENCE 3 TEXT

<p><code>\startgraphicstext [...¹,...] [...²,...] {...³} ... \stopgraphicstext</code></p> <p>1 split vždy vlevo vpravo ^{OPT}uvnitř vnější ^{OPT}zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--+]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadný lokálně zde síla marginalie [--+]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlaví upatí</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startchemicaltext [...¹,...] [...²,...] {...³} ... \stopchemicaltext</code></p> <p>1 split vždy vlevo vpravo ^{OPT}uvnitř vnější ^{OPT}zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--+]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadný lokálně zde síla marginalie [--+]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlaví upatí</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startintermezzotext [...¹,...] [...²,...] {...³} ... \stopintermezzotext</code></p> <p>1 split vždy vlevo vpravo ^{OPT}uvnitř vnější ^{OPT}zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--+]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadný lokálně zde síla marginalie [--+]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlaví upatí</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\starttabletext [...¹,...] [...²,...] {...³} ... \stoptabletext</code></p> <p>1 split vždy vlevo vpravo ^{OPT}uvnitř vnější ^{OPT}zpetnamezera cutspace ivlevo ivpravo naokrají levýokraj pravýokraj leváhrana praváhrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [--+]radek pulradku mřížka vysoko nízko prizpusobive 90 180 270 nonumber zadný lokálně zde síla marginalie [--+]zavesení visící vysoko obe nastřed offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlaví upatí</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startfont [...] ... \stopfont</code></p> <p>* FONT ^{OPT}</p>
<p><code>\startfontclass [...] ... \stopfontclass</code></p> <p>* každý NAME</p>
<p><code>\startfontsolution [...] ... \stopfontsolution</code></p> <p>* NAME</p>
<p><code>\startframedcell [...[*],...] ... \stopframedcell</code></p> <p>* inherits: \nastavoramování ^{OPT}</p>
<p><code>\startframedcontent [...] ... \stopframedcontent</code></p> <p>* NAME vyp ^{OPT}</p>
<p><code>\startframedrow [...[*],...] ... \stopframedrow</code></p> <p>* inherits: \nastavoramování ^{OPT}</p>
<p><code>\startframedtable [¹...] [...²,...] ... \stopframedtable</code></p> <p>1 NAME ^{OPT}</p> <p>2 inherits: \nastavoramování ^{OPT}</p>
<p><code>\startgridsnapping [...] ... \stopgridsnapping</code></p> <p>* normalní standardní ano ^{OPT}striktní tolerantní vrsek spodek obe široky prizpusobive první poslední vysoko jedna nízko zadný radek strut box min max nastřed math math:radek math:pulradku math:-line math:-halflíne NAME</p>
<p><code>\startgridsnapping [...[*],...] ... \stopgridsnapping</code></p> <p>* inherits: \definegridsnapping ^{OPT}</p>
<p><code>\starthboxestohbox ... \stophboxestohbox</code></p>
<p><code>\starthboxregister .*. ... \stophboxregister</code></p> <p>* CSNAME NUMBER</p>

$\backslash\text{startHELP} [\dots] \dots \backslash\text{stopHELP}$ * REFERENCE <small>OPT</small> instances: helptext
$\backslash\text{starthelptext} [\dots] \dots \backslash\text{stophelptext}$ * REFERENCE <small>OPT</small>
$\backslash\text{starthighlight} [\dots] \dots \backslash\text{stophighlight}$ * NAME
$\backslash\text{starthyphenation} [\dots, \dots] \dots \backslash\text{stophyphenation}$ * original tex implicitni hyphenate expanded traditional zadny
$\backslash\text{startcharacteralign} [\dots] \dots \backslash\text{stopcharacteralign}$ * TEXT number->TEXT text-> <small>TEXT</small>
$\backslash\text{startcheckedfences} \dots \backslash\text{stopcheckedfences}$
$\backslash\text{startchemical} [\dots] [\dots, \dots, \dots] \dots \backslash\text{stopchemical}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupchemical
$\backslash\text{startimath} \dots \backslash\text{stopimath}$
$\backslash\text{startindentedtext} [\dots] \dots \backslash\text{stopindentedtext}$ * NAME
$\backslash\text{startINDENTEDTEXT} \dots \backslash\text{stopINDENTEDTEXT}$
$\backslash\text{startinterakce} [\dots] \dots \backslash\text{stopinterakce}$ * skryte NAME
$\backslash\text{startinteraktivnimenu} [\dots] \dots \backslash\text{stopinteraktivnimenu}$ * NAME
$\backslash\text{startinterface} \dots \dots \backslash\text{stopinterface}$ * vse SPRACHE
$\backslash\text{startintertext} \dots \backslash\text{stopintertext}$
$\backslash\text{startitemgroup} [\dots] [\dots, \dots] [\dots, \dots, \dots] \dots \backslash\text{stopitemgroup}$ 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupitemgroup 3 inherits: \setupitemgroup
$\backslash\text{startITEMGROUP} [\dots, \dots] [\dots, \dots, \dots] \dots \backslash\text{stopITEMGROUP}$ 1 inherits: \setupitemgroup ^{<small>OPT</small>} 2 inherits: \setupitemgroup ^{<small>OPT</small>} instances: itemize
$\backslash\text{startitemize} [\dots, \dots] [\dots, \dots, \dots] \dots \backslash\text{stopitemize}$ 1 inherits: \setupitemgroup ^{<small>OPT</small>} 2 inherits: \setupitemgroup
$\backslash\text{startJScode} \dots \dots \dots \dots \backslash\text{stopJScode}$ 1 NAME 2 uses 3 NAME

\startJSreamble ¹ ... ² ... ³ ... \stopJSreamble 1 NAME 2 uzito 3 now later
\startjdina [...] ... \stopjdina * REFERENCE
\startknockout ... \stopknockout
\startkomentarstranky ... \stopkomentarstranky
\startCOMMENT [¹ ...] [..., ² ...,...] ... \stopCOMMENT 1 TEXT OPT OPT 2 inherits: \nastavkomentar instances: comment
\startcomment [¹ ...] [..., ² ...,...] ... \stopcomment 1 TEXT OPT OPT 2 inherits: \nastavkomentar
\startkomponenta [...] ... \stopkomponenta * FILE *
\startkomponenta ¹ ... \stopkomponenta * FILE *
\startkonectabulky [...] ... \stopkonectabulky * NAME
\startlayout [...] ... \stoplayout * NAME
\startlinealignment [...] ... \stoplinealignment * vlevo nastred vpravo max
\startlinecorrection [...; ¹ ...] ... \stoplinecorrection * prazdny inherits: \preskoc OPT
\startlinefiller [¹ ...] [..., ² ...,...] ... \stoplinefiller 1 filler NAME OPT 2 inherits: \setuplinefiller
\startLINENOTE [¹ ...] { ² ...} 1 REFERENCE 2 TEXT instances: linenote
\startlinenote [...] { ² ...} 1 REFERENCE 2 TEXT
\startlinenumbering [¹ ...] [..., ² ...,...] ... \stoplinenumbering 1 NAME OPT OPT 2 pokracovat = ano ne start = NUMMER krok = NUMMER metoda = stranka prvni dalsi
\startlinenumbering [¹ ...] [² ...] ... \stoplinenumbering 1 NAME OPT OPT 2 pokracovat NUMMER

<code>\startlinetable ... \stoplinetable</code>
<code>\startlinetablebody ... \stoplinetablebody</code>
<code>\startlinetablecell [...,*,...] ... \stoplinetablecell</code> <code>* inherits: \setuplinetable</code> <small>OPT</small>
<code>\startlinetablehead ... \stoplinetablehead</code>
<code>\startlocalfootnotes ... \stoplocalfootnotes</code>
<code>\startlocalheadsetup ... \stoplocalheadsetup</code>
<code>\startlocallinecorrection [...,*,...] ... \stoplocallinecorrection</code> <code>* prazdny inherits: \preskoc</code> <small>OPT</small>
<code>\startlocalnotes [...,*,...] ... \stoplocalnotes</code> <code>* NAME</code>
<code>\startlocalsetups [...¹] [...²] ... \stoplocalsetups</code> <code>1 mrizka</code> <small>OPT</small> <code>2 NAME</code>
<code>\startlocalsetups .* ... \stoplocalsetups</code> <code>* NAME</code>
<code>\startlua ... \stoplua</code>
<code>\startluacode ... \stopluacode</code>
<code>\startluaparameterset [...] ... \stopluaparameterset</code> <code>* NAME</code>
<code>\startluasetups [...¹] [...²] ... \stopluasetups</code> <code>1 mrizka</code> <small>OPT</small> <code>2 NAME</code>
<code>\startluasetups .* ... \stopluasetups</code> <code>* NAME</code>
<code>\startMPclip {...} ... \stopMPclip</code> <code>* NAME</code>
<code>\startMPcode {...} ... \stopMPcode</code> <code>* NAME</code> <small>OPT</small>
<code>\startMPdefinitions {...} ... \stopMPdefinitions</code> <code>* NAME</code> <small>OPT</small>
<code>\startMPdrawing [...] ... \stopMPdrawing</code> <code>* -</code> <small>OPT</small>
<code>\startMPenvironment [...] ... \stopMPenvironment</code> <code>* reset globalne +</code> <small>OPT</small>
<code>\startMPextensions {...,*,...} ... \stopMPextensions</code> <code>* NAME</code> <small>OPT</small>

$\backslash\text{startMPinclusions} [\dots] \{\dots\} \dots \backslash\text{stopMPinclusions}$ $\begin{array}{l} 1 \quad + \\ 2 \quad \text{NAME} \end{array}$	$\text{OPT} \quad \text{OPT}$
$\backslash\text{startMPinitializations} \dots \backslash\text{stopMPinitializations}$	
$\backslash\text{startMPpositiongraphic} \{\dots\} \{\dots,\dots\} \dots \backslash\text{stopMPpositiongraphic}$ $\begin{array}{l} 1 \quad \text{NAME} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startMPpositionmethod} \{\dots\} \dots \backslash\text{stopMPpositionmethod}$ $\ast \quad \text{NAME}$	
$\backslash\text{startMPrun} \{\dots\} \dots \backslash\text{stopMPrun}$ $\ast \quad \text{NAME}$	OPT
$\backslash\text{startmarginalnilinka} [\dots] \dots \backslash\text{stopmarginalnilinka}$ $\ast \quad \text{NUMMER}$	OPT
$\backslash\text{startmarginalnilinka} [\dots,\dots,\dots] \dots \backslash\text{stopmarginalnilinka}$ $\ast \quad \text{inherits: } \backslash\text{setupmarginrule}$	OPT
$\backslash\text{startmarginblock} [\dots] \dots \backslash\text{stopmarginblock}$ $\ast \quad \text{NAME}$	OPT
$\backslash\text{startmarkedcontent} [\dots] \dots \backslash\text{stopmarkedcontent}$ $\ast \quad \text{reset vse NAME}$	OPT
$\backslash\text{startMATHALIGNMENT} [\dots,\dots,\dots] \dots \backslash\text{stopMATHALIGNMENT}$ $\ast \quad \text{inherits: } \backslash\text{setupmathalignment}$ $\text{instances: align mathalignment}$	OPT
$\backslash\text{startalign} [\dots,\dots,\dots] \dots \backslash\text{stopalign}$ $\ast \quad \text{inherits: } \backslash\text{setupmathalignment}$	OPT
$\backslash\text{startmathalignment} [\dots,\dots,\dots] \dots \backslash\text{stopmathalignment}$ $\ast \quad \text{inherits: } \backslash\text{setupmathalignment}$	OPT
$\backslash\text{startMATHCASES} [\dots,\dots,\dots] \dots \backslash\text{stopMATHCASES}$ $\ast \quad \text{inherits: } \backslash\text{setupmathcases}$ $\text{instances: cases mathcases}$	OPT
$\backslash\text{startcases} [\dots,\dots,\dots] \dots \backslash\text{stopcases}$ $\ast \quad \text{inherits: } \backslash\text{setupmathcases}$	OPT
$\backslash\text{startmathcases} [\dots,\dots,\dots] \dots \backslash\text{stopmathcases}$ $\ast \quad \text{inherits: } \backslash\text{setupmathcases}$	OPT
$\backslash\text{startMATHMATRIX} [\dots,\dots,\dots] \dots \backslash\text{stopMATHMATRIX}$ $\ast \quad \text{inherits: } \backslash\text{setupmathmatrix}$ $\text{instances: matrix mathmatrix}$	OPT
$\backslash\text{startmathmatrix} [\dots,\dots,\dots] \dots \backslash\text{stopmathmatrix}$ $\ast \quad \text{inherits: } \backslash\text{setupmathmatrix}$	OPT
$\backslash\text{startmatrix} [\dots,\dots,\dots] \dots \backslash\text{stopmatrix}$ $\ast \quad \text{inherits: } \backslash\text{setupmathmatrix}$	OPT
$\backslash\text{startmathmode} \dots \backslash\text{stopmathmode}$	

$\backslash\mathrm{startmathstyle} [\ldots,*\ldots] \ldots \backslash\mathrm{stopmathstyle}$ * obrazovka text script scriptscript cramped uncramped normalni zhustene male velke NAME
$\backslash\mathrm{startmatrices} [\ldots,*\ldots] \ldots \backslash\mathrm{stopmatrices}$ * inherits: $\backslash\mathrm{setupmathmat}^{\mathrm{OPT}}\mathrm{fix}$
$\backslash\mathrm{startmaxaligned} \ldots \backslash\mathrm{stopmaxaligned}$
$\backslash\mathrm{startmiddlealigned} \ldots \backslash\mathrm{stopmiddlealigned}$
$\backslash\mathrm{startmixedcolumns} [\ldots,*\ldots] \ldots \backslash\mathrm{stopmixedcolumns}$ 1 NAME OPT OPT 2 inherits: $\backslash\mathrm{setupmixedcolumns}$
$\backslash\mathrm{startMIXEDCOLUMNS} [\ldots,*\ldots] \ldots \backslash\mathrm{stopMIXEDCOLUMNS}$ * inherits: $\backslash\mathrm{setupmixedcolumns}^{\mathrm{OPT}}$ instances: itemgroupcolumns boxedcolumns
$\backslash\mathrm{startboxedcolumns} [\ldots,*\ldots] \ldots \backslash\mathrm{stopboxedcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}^{\mathrm{OPT}}$
$\backslash\mathrm{startitemgroupcolumns} [\ldots,*\ldots] \ldots \backslash\mathrm{stopitemgroupcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}$ OPT
$\backslash\mathrm{startmode} [\ldots,*\ldots] \ldots \backslash\mathrm{stopmode}$ * NAME
$\backslash\mathrm{startmodeset} [\ldots,*\ldots] \{\ldots\} \ldots \backslash\mathrm{stopmodeset}$ 1 NAME implicitni 2 CONTENT
$\backslash\mathrm{startmodule} [\ldots,*\ldots] \ldots \backslash\mathrm{stopmodule}$ * FILE
$\backslash\mathrm{startmoduletestsection} \ldots \backslash\mathrm{stopmoduletestsection}$
$\backslash\mathrm{startmodule} \ldots \ldots \backslash\mathrm{stopmodule}$ * FILE
$\backslash\mathrm{startnadpis} [\ldots,*\ldots] \{\ldots\} \ldots \backslash\mathrm{stopnadpis}$ 1 REFERENCE OPT 2 TEXT
$\backslash\mathrm{startnamedsection} [\ldots,*\ldots] [\ldots,*\ldots] [\ldots,*\ldots] \ldots \backslash\mathrm{stopnamedsection}$ 1 ABSCHNITT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE
$\backslash\mathrm{startnamedsubformulas} [\ldots,*\ldots] \{\ldots\} \ldots \backslash\mathrm{stopnamedsubformulas}$ 1 + - REFERENCE OPT 2 TEXT
$\backslash\mathrm{startnaproti} \ldots \backslash\mathrm{stopnaproti}$
$\backslash\mathrm{startnarrower} [\ldots,*\ldots] \ldots \backslash\mathrm{stopnarrower}$ * [-+]vlevo [-+]nastred OPT [-+]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset

$\backslash\text{startNARROWER} [\dots, \dots] \dots \backslash\text{stopNARROWER}$ $\ast \quad [-+] \text{vlevo} \quad [-+] \text{nastred}^{\text{OPT}} [-+] \text{vpravo} \text{ NUMMER} \ast \text{vlevo} \text{ NUMMER} \ast \text{nastred} \text{ NUMMER} \ast \text{vpravo} \text{ reset}$
$\backslash\text{startnegativ} \dots \backslash\text{stopnegativ}$
$\backslash\text{startnicelyfilledbox} [\dots, \dots, \dots, \dots] \dots \backslash\text{stopnicelyfilledbox}$ $\ast \quad \text{sirka} = \text{DIMENSION} \quad \text{OPT}$ $\quad \text{vyska} = \text{DIMENSION}$ $\quad \text{offset} = \text{DIMENSION}$ $\quad \text{strut} = \text{ano ne}$
$\backslash\text{startnointerference} \dots \backslash\text{stopnointerference}$
$\backslash\text{startnotallmodes} [\dots, \dots] \dots \backslash\text{stopnotallmodes}$ $\ast \quad \text{NAME}$
$\backslash\text{startnotext} \dots \backslash\text{stopnotext}$
$\backslash\text{startnotmode} [\dots, \dots] \dots \backslash\text{stopnotmode}$ $\ast \quad \text{NAME}$
$\backslash\text{startobrazek} [\dots] [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stopobrazek}$ $1 \quad \text{NAME}$ $2 \quad \text{FILE}$ $3 \quad \text{inherits: } \backslash\text{externiobraz}$
$\backslash\text{startodlozit} [\dots] \dots \backslash\text{stopodlozit}$ $\ast \quad [-+] \text{NUMMER} \quad \text{OPT}$
$\backslash\text{startodstavec} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stopodstavec}$ $1 \quad \text{NAME} \quad \text{OPT} \quad \text{OPT}$ $2 \quad \text{inherits: } \backslash\text{setupparagraph}$
$\backslash\text{startoramovani} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stoporamovani}$ $1 \quad \text{NAME} \quad \text{OPT} \quad \text{OPT}$ $2 \quad \text{inherits: } \backslash\text{nastavoramovani}$
$\backslash\text{startFRAMEDTEXT} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stopFRAMEDTEXT}$ $1 \quad \text{vlevo vpravo nastred}^{\text{OPT}} \text{zadny} \quad \text{OPT}$ $2 \quad \text{inherits: } \backslash\text{setupframedtext}$ $\text{instances: framedtext}$
$\backslash\text{startframedtext} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stopframedtext}$ $1 \quad \text{vlevo vpravo nastred}^{\text{OPT}} \text{zadny} \quad \text{OPT}$ $2 \quad \text{inherits: } \backslash\text{setupframedtext}$
$\backslash\text{startoutputstream} [\dots] \dots \backslash\text{stopoutputstream}$ $\ast \quad \text{NAME}$
$\backslash\text{startoverprint} \dots \backslash\text{stopoverprint}$
$\backslash\text{startpagefigure} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stoppagefigure}$ $1 \quad \text{FILE} \quad \text{OPT}$ $2 \quad \text{offset} = \text{implicitni prekryv zadny DIMENSION}$
$\backslash\text{startpagegrid} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stoppagegrid}$ $1 \quad \text{NAME} \quad \text{OPT} \quad \text{OPT}$ $2 \quad \text{inherits: } \backslash\text{setuppagegrid}$
$\backslash\text{startpagegridspan} [\dots] [\dots, \dots, \dots, \dots] \dots \backslash\text{stoppagegridspan}$ $1 \quad \text{NAME} \quad \text{OPT}$ $2 \quad \text{inherits: } \backslash\text{setuppagegridspan}$

<pre> \startPAGEGRID [...¹...²...] ... \stopPAGEGRID * inherits: \setuppagegrid^{OPT} </pre>
<pre> \startpagelayout [...] ... \stoppagelayout * stranka levastranka pravastranka </pre>
<pre> \startpar [...¹] [...²...] ... \stoppar 1 NAME OPT OPT 2 inherits: \setupparagraph </pre>
<pre> \startparagraphs [...] ... \stopparagraphs * NAME </pre>
<pre> \startparagraphscell ... \stopparagraphscell </pre>
<pre> \startPARAGRAPHS ... \stopPARAGRAPHS </pre>
<pre> \startPARALLEL ... \stopPARALLEL </pre>
<pre> \startparbuilder [...] ... \stopparbuilder * implicitni oneline basic NAME </pre>
<pre> \startplacefloat [...¹] [...²...] [...³...] ... \stopplacefloat 1 SINGULAR OPT OPT 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati odkaz = REFERENCE 3 KEY = VALUE </pre>
<pre> \startumistiFLOAT [...¹...] [...²...] ... \stopumistiFLOAT 1 titul = TEXT OPT OPT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati odkaz = REFERENCE 2 KEY = VALUE instances: chemical figure table intermezzo graphic </pre>
<pre> \startumistifigure [...¹...] [...²...] ... \stopumistifigure 1 titul = TEXT OPT OPT zalozka = TEXT znaceni = TEXT seznam = TEXT misto = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi upati odkaz = REFERENCE 2 KEY = VALUE </pre>

```

\startumistigraphic [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistigraphic
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek
              pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
              visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi
              upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistichemical [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistichemical
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek
              pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
              visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi
              upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistiintermezzo [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistiintermezzo
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek
              pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
              visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi
              upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startumistitable [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopumistitable
1  titul    = TEXT
    zalozka = TEXT
    znaceni = TEXT
    seznam  = TEXT
    misto   = split vzdy vlevo vpravo uvnitr vnejsi zpetnamezera cutspace ivlevo ivpravo naokraj levokraj pravokraj
              levahrana pravahrana innermargin outermargin inneredge outeredge text naproti reset vyska podlehloubky [-+]radek
              pulradku mrizka vysoko nizko prizpusobive 90 180 270 nonumber zadny lokalne zde sila marginalie [-+]zaveseni
              visici vysoko obe nastred offset vrsek spodek auto stranka levastranka pravastranka nekde effective zahlavi
              upati
    odkaz   = REFERENCE
2  KEY = VALUE

```

```

\startplacepairedbox [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplacepairedbox
1  NAME
2  inherits: \setuppairedbox

```

```

\startumistiPAIREDBOX [...,\stackrel{*}{=},...] ... \stopumistiPAIREDBOX
*  inherits: \setuppairedbox
instances: legend

```

```

\startumistilegend [...,\stackrel{*}{=},...] ... \stopumistilegend
*  inherits: \setuppairedbox

```

```

\startpolozka [...,\stackrel{*}{=},...] ... \stoppolozka
*  REFERENCE

```

```

\startPOPIS [...,\stackrel{*}{=},...] ... \stopPOPIS
*  titul    = TEXT
    zalozka = TEXT
    seznam  = TEXT
    odkaz   = REFERENCE

```

<p><code>\startPOPIS [...¹,...] {...²} ... \stopPOPIS</code></p> <p>1 REFERENCE OPT OPT</p> <p>2 TEXT</p>
<p><code>\startpositioning [...¹] [...²,...²,...] ... \stoppositioning</code></p> <p>1 NAME OPT OPT</p> <p>2 inherits: \nastavumistovani</p>
<p><code>\startpositionoverlay {...} ... \stoppositionoverlay</code></p> <p>* NAME</p>
<p><code>\startpositiv ... \stoppositiv</code></p>
<p><code>\startpozadi [...[*],...[*],...] ... \stoppozadi</code></p> <p>* inherits: \nastavpozadi^{OPT}</p>
<p><code>\startPOZADI [...[*],...[*],...] ... \stopPOZADI</code></p> <p>* inherits: \nastavpozadi^{OPT}</p> <p>instances: pozadi</p>
<p><code>\startNOTE [...[*],...] ... \stopNOTE</code></p> <p>* REFERENCE OPT</p> <p>instances: footnote endnote</p>
<p><code>\startNOTE [...[*],...[*],...] ... \stopNOTE</code></p> <p>* titul = TEXT OPT</p> <p> zalozka = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p> <p>instances: footnote endnote</p>
<p><code>\startendnote [...[*],...[*],...] ... \stopendnote</code></p> <p>* titul = TEXT OPT</p> <p> zalozka = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p>
<p><code>\startfootnote [...[*],...[*],...] ... \stopfootnote</code></p> <p>* titul = TEXT OPT</p> <p> zalozka = TEXT</p> <p> seznam = TEXT</p> <p> odkaz = REFERENCE</p>
<p><code>\startendnote [...[*],...] ... \stopendnote</code></p> <p>* REFERENCE OPT</p>
<p><code>\startfootnote [...[*],...] ... \stopfootnote</code></p> <p>* REFERENCE OPT</p>
<p><code>\startprekryv ... \stopprekryv</code></p>
<p><code>\startprocessassignmentcommand [...[*],...[*],...] ... \stopprocessassignmentcommand</code></p> <p>* KEY = VALUE</p>
<p><code>\startprocessassignmentlist [...[*],...[*],...] ... \stopprocessassignmentlist</code></p> <p>* KEY = VALUE</p>
<p><code>\startprocesscommaccommand [...[*],...] ... \stopprocesscommaccommand</code></p> <p>* BEFEHL</p>
<p><code>\startprocesscommalist [...[*],...] ... \stopprocesscommalist</code></p> <p>* BEFEHL</p>

\startprodukt [...] ... \stopprodukt * FILE *
\startprodukt \stopprodukt * FILE *
\startprojekt [...] ... \stopprojekt * FILE *
\startprojekt \stopprojekt * FILE *
\startprostredi [...] ... \stopprostredi * FILE *
\startprostredi \stopprostredi * FILE *
\startprotectedcolors ... \stopprotectedcolors
\startpublikace [. ¹ .] [... ² ... ² ...] ... \stoppublikace 1 NAME OPT OPT 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT
\starttradek [...] * REFERENCE
\startLINES [... [*] ... [*] ...] ... \stopLINES * inherits: \nastavradky instances: lines
\startlines [... [*] ... [*] ...] ... \stoplines * inherits: \nastavradky
\startrandomized ... \stoprandomized
\startrawsetups [. ¹ .] [... ² .] ... \stoprawsetups 1 mrizka OPT 2 NAME
\startrawsetups \stoprawsetups * NAME
\startreadingfile ... \stopreadingfile
\startregime [...] ... \stopregime * inherits: \enableregime
\startregister [. ¹ .] [... ² .] [... ³ .] [... ⁴ .] [... ⁵ ... ⁵ ...] 1 NAME OPT OPT 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX
\startreusableMPgraphic {. ¹ .} {... ² ... ² } ... \stopreusableMPgraphic 1 NAME OPT 2 KEY

<pre> \starttrovnice [...,*,...] ... \stoprovnice * zhustene tight nastred^{OPT} ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont </pre>
<pre> \startrovnice [...,*=,...] ... \stoprovnice * volba = zhustene^{OPT} tight nastred ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont marginalie = ano ne standardni DIMENSION mrizka = inherits: \snaptogrid </pre>
<pre> \startFORMULAformula [...,*,...] ... \stopFORMULAformula * zhustene tight nastred^{OPT} ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont instances: sp sd mp md </pre>
<pre> \startmdformula [...,*,...] ... \stopmdformula * zhustene tight nastred^{OPT} ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont </pre>
<pre> \startmpformula [...,*,...] ... \stopmpformula * zhustene tight nastred^{OPT} ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont </pre>
<pre> \startsdfformula [...,*,...] ... \stopsdfformula * zhustene tight nastred^{OPT} ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont </pre>
<pre> \startspformula [...,*,...] ... \stopspformula * zhustene tight nastred^{OPT} ramecek radek pulradku -radek -pulradku inherits: \nastavzakladnifont </pre>
<pre> \startrozbalene ... \stoprozbalene </pre>
<pre> \startscript [...*] ... \stopscript * hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsectionblock [...*¹] [...*²,...^{OPT}] ... \stopsectionblock 1 NAME 2 zalozka = TEXT inherits: \nastavbloksekce </pre>
<pre> \startsectionblockenvironment [...*] ... \stopsectionblockenvironment * NAME </pre>
<pre> \startSECTIONBLOCK [...,*=,...] ... \stopSECTIONBLOCK * zalozka = TEXT^{OPT} inherits: \nastavbloksekce instances: frontmatter bodymatter appendices backmatter </pre>
<pre> \startappendices [...,*=,...] ... \stopappendices * zalozka = TEXT^{OPT} inherits: \nastavbloksekce </pre>
<pre> \startbackmatter [...,*=,...] ... \stopbackmatter * zalozka = TEXT^{OPT} inherits: \nastavbloksekce </pre>
<pre> \startbodymatter [...,*=,...] ... \stopbodymatter * zalozka = TEXT^{OPT} inherits: \nastavbloksekce </pre>
<pre> \startfrontmatter [...,*=,...] ... \stopfrontmatter * zalozka = TEXT^{OPT} inherits: \nastavbloksekce </pre>

`\startsectionlevel [...1...] [...2...] [...3...] ... \stopsectionlevel`

1 NAME OPT OPT OPT
 2 titul = TEXT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 3 KEY = VALUE

`\startSECTION [...1...] [...2...] ... \stopSECTION`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title
 subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\startchapter [...1...] [...2...] ... \stopchapter`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startpart [...1...] [...2...] ... \stoppart`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsection [...1...] [...2...] ... \stopsection`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsubject [...1...] [...2...] ... \stopsubject`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsubsection [...1...] [...2...] ... \stopsubsection`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

`\startsubsubject [...1...] [...2...] ... \stopsubsubject`

1 titul = TEXT OPT OPT
 zalozka = TEXT
 znaceni = TEXT
 seznam = TEXT
 odkaz = REFERENCE
 vlastnicislo = TEXT
 2 KEY = VALUE

```

\startsubsubsection [...1...2...] ... \stopsubsubsection
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startsubsubsubject [...1...2...] ... \stopsubsubsubject
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsection [...1...2...] ... \stopsubsubsubsection
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubject [...1...2...] ... \stopsubsubsubsubject
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubsection [...1...2...] ... \stopsubsubsubsubsection
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubsubject [...1...2...] ... \stopsubsubsubsubsubject
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\starttitle [...1...2...] ... \stoptitle
1  titul      = TEXT      OPT      OPT
   zalozka   = TEXT
   znaceni   = TEXT
   seznam    = TEXT
   odkaz     = REFERENCE
   vlastnicislo = TEXT
2  KEY = VALUE

```

```

\startsetups [...1...2...] ... \stopsetups
1  mrizka     OPT
2  NAME

```

```

\startsetups ... \stopsetups
*  NAME

```

```

\startshift [...] ... \stopshift
*  NAME

```

$\backslash\text{startsidebar}$ [¹ ...] [² ... ² ...] ... $\backslash\text{stopsidebar}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupsidebar}$
$\backslash\text{startsimplecolumns}$ [... [*] ...] ... $\backslash\text{stopsimplecolumns}$ * inherits: $\backslash\text{setsimplecolumnhsiz}$ ² ₂
$\backslash\text{startsloupce}$ [... [*] ...] ... $\backslash\text{stopsloupce}$ * inherits: $\backslash\text{nastavsloupce}$ ² ₂
$\backslash\text{startspecialitem}$ [¹ ...] [² ... ² ...] ... $\backslash\text{stopspecialitem}$ 1 položka OPT OPT 2 REFERENCE
$\backslash\text{startspecialitem}$ [[*] ...] ... $\backslash\text{stopspecialitem}$ * pod pol
$\backslash\text{startspecialitem}$ [¹ ...] { ² ...} ... $\backslash\text{stopspecialitem}$ 1 sym rozsah mar 2 TEXT
$\backslash\text{startsplitformula}$... $\backslash\text{stopsplitformula}$
$\backslash\text{startspread}$... $\backslash\text{stopspread}$
$\backslash\text{start}$ [[*] ...] ... $\backslash\text{stop}$ * NAME OPT
$\backslash\text{startSTARTSTOP}$... $\backslash\text{stopSTARTSTOP}$
$\backslash\text{startstaticMPfigure}$ { [*] ...} ... $\backslash\text{stopstaticMPfigure}$ * NAME
$\backslash\text{startstaticMPgraphic}$ { ¹ ...} { ² ... ² ...} ... $\backslash\text{stopstaticMPgraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{STARTSTOP}$ { [*] ...} * CONTENT
$\backslash\text{startstrictinspectnextcharacter}$... $\backslash\text{stopstrictinspectnextcharacter}$
$\backslash\text{startstructurepageregister}$ [¹ ...] [² ...] [... ³ ... ³ ...] [... ⁴ ... ⁴ ...] 1 NAME OPT 2 NAME 3 popisek = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativa = TEXT 4 KEY = VALUE
$\backslash\text{startstyle}$ [... [*] ...] ... $\backslash\text{stopstyle}$ * inherits: $\backslash\text{setupstyle}$
$\backslash\text{startstyle}$ [[*] ...] ... $\backslash\text{stopstyle}$ * NAME FONT

<code>\startSTYLE ... \stopSTYLE</code>
<code>\startsubformulas [...,*...] ... \stopsubformulas</code> <code>* + - REFERENCE</code> <small>OPT</small>
<code>\startsubjectlevel [¹...] [...,²...,...] [...,³...,...] ... \stopsubjectlevel</code> 1 NAME <small>OPT</small> 2 titul = TEXT zalozka = TEXT znaceni = TEXT seznam = TEXT odkaz = REFERENCE vlastnicislo = TEXT 3 KEY = VALUE
<code>\startsubsentence ... \stopsubsentence</code>
<code>\startsubstack ... \stopsubstack</code>
<code>\startsymbolset [...*] ... \stopsymbolset</code> <code>* NAME</code>
<code>\startTABLE [...,*...] ... \stopTABLE</code> <code>* inherits: \setupTABLE</code>
<code>\startTABLEbody [...,*...] ... \stopTABLEbody</code> <code>* inherits: \setupTABLE</code> <small>OPT</small>
<code>\startTABLEfoot [...,*...] ... \stopTABLEfoot</code> <code>* inherits: \setupTABLE</code> <small>OPT</small>
<code>\startTABLEhead [...,*...] ... \stopTABLEhead</code> <code>* inherits: \setupTABLE</code> <small>OPT</small>
<code>\startTABLEnext [...,*...] ... \stopTABLEnext</code> <code>* inherits: \setupTABLE</code> <small>OPT</small>
<code>\starttabelator [/¹.../] [...,²...,...] ... \stoptabelator</code> 1 TEMPLATE <small>OPT</small> 2 inherits: \nastavtabelaci
<code>\startTABULATE [¹...] [...,²...,...] ... \stopTABULATE</code> 1 NAME <small>OPT</small> 2 inherits: \nastavtabelaci instances: legend fact
<code>\startfact [...*] [...,²...,...] ... \stopfact</code> 1 NAME <small>OPT</small> 2 inherits: \nastavtabelaci
<code>\startlegend [¹...] [...,²...,...] ... \stoplegend</code> 1 NAME <small>OPT</small> 2 inherits: \nastavtabelaci
<code>\starttabulatehead [...*] ... \stoptabulatehead</code> <code>* NAME</code> <small>OPT</small>
<code>\starttabulatetail [...*] ... \stoptabulatetail</code> <code>* NAME</code> <small>OPT</small>

$\backslash\text{startTABULATION}$ [¹ ...] [\dots , \dots , $\overset{2}{=}\dots$, \dots] ... $\backslash\text{stopTABULATION}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setuptabulation}$
$\backslash\text{starttabulka}$ [¹ ...] [\dots , \dots , $\overset{2}{=}\dots$, \dots] ... $\backslash\text{stoptabulka}$ 1 TEMPLATE OPT 2 inherits: $\backslash\text{nastavtabulky}$
$\backslash\text{starttabulka}$ [¹ ...] [\dots , \dots , $\overset{2}{=}\dots$, \dots] ... $\backslash\text{stoptabulka}$ 1 NAME OPT 2 inherits: $\backslash\text{nastavtabulky}$
$\backslash\text{starttabulky}$ [[*] ...] ... $\backslash\text{stoptabulky}$ * TEMPLATE
$\backslash\text{starttabulky}$ [[*] ...] ... $\backslash\text{stoptabulky}$ * NAME
$\backslash\text{starttexcode}$... $\backslash\text{stoptexcode}$
$\backslash\text{starttexdefinition}$ [¹ ... [² ... [³ ... [⁴ ... [⁵ ... [⁶ ... [⁷] $\backslash\text{stoptexdefinition}$] 1 spaces nospaces OPT OPT OPT OPT OPT OPT OPT 2 globalne 3 unexpanded 4 expanded 5 singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument tripleargument quadupleargument quintupleargument sextupleargument 6 NAME 7 TEMPLATE
$\backslash\text{starttext}$... $\backslash\text{stoptext}$
$\backslash\text{starttextbackground}$ [¹ ...] [\dots , \dots , $\overset{2}{=}\dots$, \dots] ... $\backslash\text{stoptextbackground}$ 1 NAME OPT 2 inherits: $\backslash\text{setuptextbackground}$
$\backslash\text{starttextbackgroundmanual}$... $\backslash\text{stoptextbackgroundmanual}$
$\backslash\text{startTEXTBACKGROUND}$ [\dots , \dots , $\overset{*}{=}\dots$, \dots] ... $\backslash\text{stopTEXTBACKGROUND}$ * inherits: $\backslash\text{setuptextbackground}$ OPT
$\backslash\text{starttextcolor}$ [[*] ...] ... $\backslash\text{stoptextcolor}$ * COLOR
$\backslash\text{starttextcolorintent}$... $\backslash\text{stoptextcolorintent}$
$\backslash\text{starttextflow}$ [[*] ...] ... $\backslash\text{stoptextflow}$ * NAME
$\backslash\text{starttextnapovedy}$ [[*] ...] ... $\backslash\text{stoptextnapovedy}$ * REFERENCE OPT
$\backslash\text{starttextovalinka}$ { [*] ...} ... $\backslash\text{stoptextovalinka}$ * TEXT
$\backslash\text{startLABELtext}$ [¹ ...] [² ...] ... $\backslash\text{stopLABELtext}$ 1 SPRACHE OPT 2 KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

$\backslash\text{startbtxlabeltext} [\dots] [\dots] \dots \backslash\text{stopbtxlabeltext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startheadtext} [\dots] [\dots] \dots \backslash\text{stopheadtext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startlabeltext} [\dots] [\dots] \dots \backslash\text{stoplabeltext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startmathlabeltext} [\dots] [\dots] \dots \backslash\text{stopmathlabeltext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startoperatortext} [\dots] [\dots] \dots \backslash\text{stopoperatortext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startprefixtext} [\dots] [\dots] \dots \backslash\text{stopprefixtext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startsuffixtext} [\dots] [\dots] \dots \backslash\text{stopsuffixtext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{starttaglabeltext} [\dots] [\dots] \dots \backslash\text{stoptaglabeltext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{startunittext} [\dots] [\dots] \dots \backslash\text{stopunittext}$ $\begin{array}{l} 1 \quad \text{SPRACHE} \\ 2 \quad \text{KEY} \end{array}$	OPT
$\backslash\text{starttokens} [\dots] \dots \backslash\text{stoptokens}$ $\begin{array}{l} * \quad \text{NAME} \end{array}$	
$\backslash\text{starttransparent} [\dots] \dots \backslash\text{stoptransparent}$ $\begin{array}{l} * \quad \text{COLOR} \end{array}$	
$\backslash\text{starttypescript} [\dots, \dots] [\dots, \dots] [\dots, \dots] \dots \backslash\text{stoptypescript}$ $\begin{array}{l} 1 \quad \text{serif sans mono math handwriting calligraphy} \\ 2 \quad \text{NAME} \\ 3 \quad \text{size jmeno} \end{array}$	OPT OPT OPT
$\backslash\text{starttypescriptcollection} [\dots] \dots \backslash\text{stoptypescriptcollection}$ $\begin{array}{l} * \quad \text{NAME} \end{array}$	
$\backslash\text{startTYPING} [\dots, \dots] \dots \backslash\text{stopTYPING}$ $\begin{array}{l} * \quad \text{inherits: \nastavopi} \\ \text{instances: typing LUA MP PARSEDXML TEX XML} \end{array}$	PT
$\backslash\text{startTYPING} [\dots, \dots] \dots \backslash\text{stopTYPING}$ $\begin{array}{l} * \quad \text{pokracovat} \\ \text{instances: typing LUA MP PARSEDXML TEX XML} \end{array}$	OPT
$\backslash\text{startLUA} [\dots, \dots] \dots \backslash\text{stopLUA}$ $\begin{array}{l} * \quad \text{pokracovat} \end{array}$	OPT

<pre> \startMP [...,*...] ... \stopMP * pokračovat OPT </pre>
<pre> \startPARSEDXML [...,*...] ... \stopPARSEDXML * pokračovat OPT </pre>
<pre> \startTEX [...,*...] ... \stopTEX * pokračovat OPT </pre>
<pre> \starttyping [...,*...] ... \stoptyping * pokračovat OPT </pre>
<pre> \startXML [...,*...] ... \stopXML * pokračovat OPT </pre>
<pre> \startLUA [...,*=...,...] ... \stopLUA * inherits: \nastavOPTpis </pre>
<pre> \startMP [...,*=...,...] ... \stopMP * inherits: \nastavOPTpis </pre>
<pre> \startPARSEDXML [...,*=...,...] ... \stopPARSEDXML * inherits: \nastavOPTpis </pre>
<pre> \startTEX [...,*=...,...] ... \stopTEX * inherits: \nastavOPTpis </pre>
<pre> \starttyping [...,*=...,...] ... \stoptyping * inherits: \nastavOPTpis </pre>
<pre> \startXML [...,*=...,...] ... \stopXML * inherits: \nastavOPTpis </pre>
<pre> \startumistirovnici [...,*=...,...] ... \stopumistirovnici * titul = TEXT OPT * suffix = TEXT * odkaz = + - REFERENCE </pre>
<pre> \startumistirovnici [...,*...] ... \stopumistirovnici * + - REFERENCE OPT </pre>
<pre> \startuniqueMPgraphic {...,¹} {...,²,...} ... \stopuniqueMPgraphic 1 NAME OPT 2 KEY </pre>
<pre> \startuniqueMPpagegraphic {...,¹} {...,²,...} ... \stopuniqueMPpagegraphic 1 NAME OPT 2 KEY </pre>
<pre> \startusableMPgraphic {...,¹} {...,²,...} ... \stopusableMPgraphic 1 NAME OPT 2 KEY </pre>
<pre> \startuseMPgraphic {...,¹} {...,²,...} ... \stopuseMPgraphic 1 NAME OPT 2 KEY </pre>
<pre> \startusemathstyleparameter \... ... \stopusemathstyleparameter * CSNAME </pre>

```
\startusingbtxs specification [...] ... \stopusingbtxs specification
* NAME
```

```
\startuzky [ 1... ] [ 2...,... ] ... \stopuzky
1  NAME           OPT           OPT
2  inherits: \nastavzuzeni
```

```
\startuzky [...1..2..3...] [...2..3..4...] ... \stopuzky
1 inherits: \nastavOPTzeniOPT
2 [--]vlevo [--]nastred [--]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset
```

```
\startuzky [...] [...2,...] ... \stopuzky
1  NAME          OPT          OPT
2  [--]vlevo [--]nastred [--]vpravo NUMBER*vlevo NUMBER*nastred NUMBER*vpravo reset
```

```
\startvboxregister ... .. \stopvboxregister
* CSNAME NUMBER
```

```
\startvboxtohbox ... \stopvboxtohbox
```

```
\startvboxtohboxseparator ... \stopvboxtohboxseparator
```

```
\startviewerlayer [...] ... \stopviewerlayer
* NAME
```

```
\startVIEWERLAYER ... \stopVIEWERLAYER
```

```
\startvisici [...1...] {...} ... \stopvisici
1  vzdalenost = DIMENSION
   n          = NUMBER
   misto      = vlevo vpravo
2  CONTENT
```

```
\startvisici [.1] {...} ... \stopvisici
1   vlevo vpravo      OPT
2   CONTENT
```

```
\startvtopregister ... \stopvtopregister
* CSNAME NUMBER
```

```
\startVYCET [...,*=...,...] ... \stopVYCET
*   titul    = TEXT
    zalozka  = TEXT
    seznam   = TEXT
    odkaz     = REFERENCE
```

$$\backslash startVYCET [\dots^1, \dots] \{ \dots^2 \} \dots \backslash stopVYCET$$

1 REFERENCE

2 TEXT

OPT

OPT

```
\startxcell [.1] [.,..2.,..] ... \stopxcell
1  NAME
2  nx = NUMBER
   ny = NUMBER
   nc = NUMBER
   nr = NUMBER
   inherits: \setupxtable
```

```
\startxcellgroup [.1.] [.,.,.2.,.,] ... \stopxcellgroup
1  NAME OPT OPT
2  inherits: \setupxtable
```

$\backslash\text{startxgroup}$ [¹ ...] [² ... _{OPT} ...] ... $\backslash\text{stopxgroup}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxmldisplayverbatim}$ [...] ... $\backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmllineverbatim}$ [...] ... $\backslash\text{stopxmllineverbatim}$ * NAME
$\backslash\text{startxmlraw}$... $\backslash\text{stopxmlraw}$
$\backslash\text{startxmlsetups}$ [¹] [² ...] ... $\backslash\text{stopxmlsetups}$ 1 mrizka 2 NAME
$\backslash\text{startxmlsetups}$.* ... $\backslash\text{stopxmlsetups}$ * NAME
$\backslash\text{startxrow}$ [¹] [² ... _{OPT} ...] ... $\backslash\text{stopxrow}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxrowgroup}$ [¹] [² ... _{OPT} ...] ... $\backslash\text{stopxrowgroup}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ [_{OPT} ... [*] ...] ... $\backslash\text{stopxtable}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablebody}$ [_{OPT} ... [*] ...] ... $\backslash\text{stopxtablebody}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablebody}$ [...] ... $\backslash\text{stopxtablebody}$ * NAME
$\backslash\text{startxtablefoot}$ [_{OPT} ... [*] ...] ... $\backslash\text{stopxtablefoot}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablefoot}$ [...] ... $\backslash\text{stopxtablefoot}$ * NAME
$\backslash\text{startxtablehead}$ [_{OPT} ... [*] ...] ... $\backslash\text{stopxtablehead}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablehead}$ [...] ... $\backslash\text{stopxtablehead}$ * NAME
$\backslash\text{startxtablenext}$ [_{OPT} ... [*] ...] ... $\backslash\text{stopxtablenext}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablenext}$ [...] ... $\backslash\text{stopxtablenext}$ * NAME
$\backslash\text{startXTABLE}$ [_{OPT} ... [*] ...] ... $\backslash\text{stopXTABLE}$ * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ [...] ... $\backslash\text{stopxtable}$ * NAME

\startzahlavitabulky [...] ... \stopzahlavitabulky * NAME
\startzarovnanonastred ... \stopzarovnanonastred
\startzarovnanovlevo ... \stopzarovnanovlevo
\startzarovnanovpravo ... \stopzarovnanovpravo
\startzhustene [...] ... \stopzhustene * prazdny OPT
\startzlom [¹ ...] [..., ² ...,...] ... \stopzlom 1 NAME OPT 2 inherits: \nastavupravu
\startMAKEUPzlom [..., [*] ...,...] ... \stopMAKEUPzlom * inherits: \nastavupravu OPT instances: standard page text middle
\startmiddlezlom [..., [*] ...,...] ... \stopmiddlezlom * inherits: \nastavupravu OPT
\startpagezlom [..., [*] ...,...] ... \stoppagezlom * inherits: \nastavupravu OPT
\startstandardzlom [..., [*] ...,...] ... \stopstandardzlom * inherits: \nastavupravu OPT
\starttextzlom [..., [*] ...,...] ... \stoptextzlom * inherits: \nastavupravu OPT
\stopLINENOTE [...]
* REFERENCE instances: linenote
\stoplinenote [...]
* REFERENCE
\stoppradek [...]
* REFERENCE
\stopregister [¹ ...] [² ...]
1 NAME 2 NAME
\stopstructurepageregister [...] [² ...]
1 NAME 2 NAME
\strana [..., [*] ...]
* inherits: \pagebreak
\strictdoifelsenextoptional { ¹ ...} { ² ...}
1 TRUE 2 FALSE
\strictdoifnextoptionalelse { ¹ ...} { ² ...}
1 TRUE 2 FALSE

<code>\stripcharacter ... \from ... \to ...</code> 1 CHARACTER 2 TEXT 3 CSNAME
<code>\strippedcsname ...</code> * CSNAME
<code>\strippedcsname ...</code> * TEXT
<code>\stripspaces \from ... \to ...</code> 1 TEXT 2 CSNAME
<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutgap</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...¹...] {...²}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...¹] {...²}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subpagenumber</code>

<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...} {...} \^3...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME
<code>\swapcounts \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\swapdimens \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\swaptypesface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg antikva serif pravidelne sans bezserifu podpora opis strojopis mono rukopisne kaligraficke
<code>\switchstyleonly \^...</code> * CSNAME
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...,¹...] [...,²...,...]</code> 1 NAME OPT 2 inherits: \nastavmeziradkovoumezeru
<code>\switchtointerlinespace [...,[*]...]</code> * zap vyp reset auto male stredni ^{OPT} velke NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbol [...¹] [...²]</code> 1 NAME OPT 2 NAME
<code>\symbolreference [...]</code> * REFERENCE
<code>\symbol {...}</code> * NAME

\synctexblockfilename {...} * FILE
\synctexresetfilename
\synctexsetfilename {...} * FILE
\synchronizeblank
\synchronizeindenting
\synchronizemarking [...] ¹ [...] ² [...] ³ 1 BESCHRIFTUNG OPT 2 NUMMER 3 drzet
\synchronizeoutputstreams [...;...] * NAME
\synchronizestrut {...} * ano ne auto kap prizpusobive radek implicitni CHARACTER
\synchronizewhitespace
\SYNONYM [...] ¹ {...} ² {...} ³ 1 NAME OPT 2 TEXT 3 CONTENT instances: abbreviation
\abbreviation [...] ¹ {...} ² {...} ³ 1 NAME OPT 2 TEXT 3 CONTENT
\systemlog {...} ¹ {...} ² {...} ³ 1 FILE 2 TEXT 3 TEXT
\systemlogfirst {...} ¹ {...} ² {...} ³ 1 FILE 2 TEXT 3 TEXT
\systemloglast {...} ¹ {...} ² {...} ³ 1 FILE 2 TEXT 3 TEXT
\systemsetups {...} * NAME
\TABLE
\TaBlE
\TEX
\TeX

<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {*.}</code> * BEFEHL
<code>\taggedlabeltexts {¹.} {².} {³.}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbox {*.}</code> * CONTENT
<code>\tecka {*.}</code> * CHARACTER
<code>\tecky [...]</code> * NUMMER <small>OPT</small>
<code>\tecky [...,...[*]...,...]</code> * inherits: \setupperperiods
<code>\tenkalinka</code>
<code>\tenkelinky [...,...[*]...,...]</code> * inherits: \nastavtenkelinky
<code>\testandsplitstring ¹. \at ². \to \³. \and \⁴.</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\testcolumn [...]¹ [...]²</code> 1 NUMBER <small>OPT</small> 2 DIMENSION
<code>\testfeature {¹.} {².}</code> 1 NUMBER 2 CONTENT
<code>\testfeatureonce {¹.} {².}</code> 1 NUMBER 2 CONTENT
<code>\testpage [...]¹ [...]²</code> 1 NUMBER <small>OPT</small> 2 DIMENSION

<pre> \testpageonly [...] [..] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testpagesync [...] [..] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testtokens [...] * NAME </pre>
<pre> \tex {...} * CONTENT </pre>
<pre> \texdefinition {...} * NAME </pre>
<pre> \texsetup {...} * NAME </pre>
<pre> \TEXTBACKGROUND {...} * CONTENT </pre>
<pre> \textcitation [...,..¹...,..] [..] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \textcitation [..¹] [..] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>
<pre> \textcitation [...,..¹...,..] [...,..²...,..] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \textcite [...,..¹...,..] [..] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \textcite [..¹] [..] 1 implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear 2 REFERENCE </pre>

<pre> \textcite [...¹...] [...²...] 1 odkaz = REFERENCE alternativa = implicitni category entry short stranka num textnum rok rejstrik tag keywords autor authoryears authornum authoryear pred = BEFEHL po = BEFEHL vlevo = BEFEHL vpravo = BEFEHL inherits: \setupbtx 2 KEY = VALUE </pre>
<pre> \textcontrolspace </pre>
<pre> \textflowcollector {...} * NAME </pre>
<pre> \textmath {...} * CONTENT </pre>
<pre> \textminus </pre>
<pre> \textnapovedy [...¹] {...²} {...³} 1 REFERENCE OPT 2 TEXT 3 TEXT </pre>
<pre> \textormathchar {...} * NUMMER </pre>
<pre> \textovalinka [...¹] {...²} 1 vrsek nastred spodek OPT 2 TEXT </pre>
<pre> \textplus </pre>
<pre> \LABELtext {...} * KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel </pre>
<pre> \btxlabeltext {...} * KEY </pre>
<pre> \headtext {...} * KEY </pre>
<pre> \labeltext {...} * KEY </pre>
<pre> \mathlabeltext {...} * KEY </pre>
<pre> \operatorortext {...} * KEY </pre>
<pre> \prefixtext {...} * KEY </pre>
<pre> \suffixtext {...} * KEY </pre>
<pre> \taglabeltext {...} * KEY </pre>

<code>\unittext {...}</code> * KEY
<code>\textvisiblespace</code>
<code>\thainumerals {...}</code> * NUMBER
<code>\thefirstcharacter {...}</code> * TEXT
<code>\thenormalizedbodyfontsize {...}</code> * DIMENSION
<code>\theremainingcharacters {...}</code> * TEXT
<code>\thickspace</code>
<code>\thinspace</code>
<code>\thirddoffivearguments {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\thirddoffourarguments {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\thirddofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\thirddofthreearguments {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thirddofthreeunexpanded {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\threedigitrounding {...}</code> * NUMBER
<code>\tibetannumerals {...}</code> * NUMBER
<code>\tightlayer [...]</code> * NAME
<code>\tilde {...}</code> * CHARACTER

<code>\tinyfont</code>
<code>\tlacitko [...¹...¹...] {...²} [...³]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\tlacitkomenu [...¹...¹...] {...²} {...³}</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\tlacitkomenu [...¹] [...²...²...] {...³} {...⁴}</code> 1 NAME 2 inherits: \nastavinterakcnimenu 3 TEXT 4 REFERENCE
<code>\BUTTON [...¹...¹...] {...²} [...³]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
<code>\tlap {...}</code> * CONTENT
<code>\tloustkacary</code>
<code>\tochar {...}</code> * e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME
<code>\tolinenote [...]</code> * REFERENCE
<code>\topbox {...}</code> * CONTENT
<code>\topleftbox {...}</code> * CONTENT
<code>\toplinebox {...}</code> * CONTENT
<code>\toprightbox {...}</code> * CONTENT
<code>\topskippedbox {...}</code> * CONTENT
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code> * FONT
<code>\traceoutputroutines</code>
<code>\tracepositions</code>
<code>\transparencycomponents {...}</code> * COLOR

<code>\transparent [...] {...}</code> 1 COLOR 2 CONTENT
<code>\tref {...} {...} [...]</code> 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\triplebond</code>
<code>\truefilename {...}</code> * FILE
<code>\truefontname {...}</code> * FONT
<code>\ttraggedright</code>
<code>\tucne</code>
<code>\tucnekurzivni</code>
<code>\tucnesklonene</code>
<code>\tvr damezera</code>
<code>\tvr demezery</code>
<code>\twodigitrounding {...}</code> * NUMMER
<code>\tx</code>
<code>\txx</code>
<code>\typebuffer [...,¹...] [...,²...,...]</code> 1 BUFFER OPT OPT 2 inherits: \nastavopis
<code>\opisBUFFER [...,[*]...,...]</code> * inherits: \nastavopis ^{OPT}
<code>\typedefinedbuffer [...]¹ [...,²...,...]</code> 1 BUFFER OPT OPT 2 inherits: \nastavopis
<code>\typeface</code>
<code>\typeinlinebuffer [...,¹...] [...,²...,...]</code> 1 BUFFER OPT OPT 2 inherits: \nastavtype
<code>\typescriptone</code>
<code>\typescriptprefix {...}</code> * NAME

<code>\typescriptthree</code>
<code>\typescripttwo</code>
<code>\typesetbuffer [...¹...] [...²...,...]</code> 1 * BUFFER OPT OPT 2 inherits: \setuexternalfigure
<code>\typesetfile [...¹...] [...²...] [...³...,...]</code> 1 NAME FILE OPT OPT 2 FILE TEXT 3 inherits: \setuexternalfigure
<code>\uconvertnumber {...¹} {...²}</code> 1 inherits: \konvertujcislo 2 NUMMER
<code>\uedcatcodecommand \...¹...² {...³}</code> 1 CSNAME 2 CHARACTER NUMBER 3 BEFEHL
<code>\ukazbarvu [...[*]...]</code> * COLOR
<code>\ukazmrizku [...[*]...,...]</code> * reset spodek vršek zadny vse radky ramecek nonumber vpravo vlevo vnejsi sloupce
<code>\ukaznastaveni [...[*]...,...]</code> * pt bp cm mm dd cc pc ^{OPT} nd nc sp in
<code>\ukazpaletu [...¹...] [...²...,...]</code> 1 NAME OPT 2 horizontalne vertikálne číslo hodnota jmeno
<code>\ukazpodpery</code>
<code>\ukazpostredizakladnihofontu [...[*]...,...]</code> * inherits: \nastavzakladnifont
<code>\ukazramecek [...¹...,...] [...²...,...]</code> 1 vrsek zahlavi text ^{OPT} upati spodek ^{OPT} 2 levahrana levýokraj text pravýokraj pravahrana
<code>\ukazsadasymbolu [...[*]...]</code> * NAME
<code>\ukazskupinubarev [...¹...] [...²...,...]</code> 1 NAME OPT 2 horizontalne vertikálne číslo hodnota jmeno
<code>\ukazupravu [...[*]...]</code> * zlom vse boxes ^{OPT} řadek glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math kurziva origin reset
<code>\ukazvytisk [...¹...,...] [...²...,...] [...³...,...]</code> 1 inherits: \nastav ^{OPT} velikostpapi ^{OPT} řu OPT 2 inherits: \nastavvelikostpapiřu 3 inherits: \nastavvzhled
<code>\ukazvzhled [...[*]...,...]</code> * pt bp cm mm dd cc ^{OPT} pc nd nc sp in

\backslash ukazzakladnifont [...,*,...] * inherits: \nastavzakladnifont
\backslash umistikombinovanyseznam [... ¹ .] [...,... ² ...,...] 1 LISTE 2 inherits: \nastavseznam
\backslash umistiCOMBINEDLIST [...,...*...,...] * inherits: \nastavseznam instances: content
\backslash umisticontent [...,...*...,...] * inherits: \nastavseznam
\backslash umistilokalnipoznamkypodcarou [...,...*...,...] * inherits: \setupnote
\backslash umistinadsebe {... ¹ .} {... ² .} 1 CONTENT 2 CONTENT
\backslash umistinamrizku [... ¹ .] {... ² .} 1 normalni standardni ^{OPT} striktni tolerantni vrsek spodek obe široky prizpusobive prvni posledni vysoko jedna nizko zadny radek strut box min max nastred math math:radek math:pulradku math:-line math:-halflife NAME 2 CONTENT
\backslash umistinamrizku [... ¹ ...,...] {... ² .} 1 inherits: \definegridshapping 2 CONTENT
\backslash umistipodrovnici [...,*,...] * + - REFERENCE
\backslash umistipoznamkypodcarou [...,...*...,...] * inherits: \setupnote
\backslash umistirejstrik [... ¹ .] [...,... ² ...,...] 1 NAME 2 inherits: \nastavrejstrik
\backslash umistiREGISTER [...,...*...,...] * inherits: \nastavrejstrik instances: index
\backslash umistiindex [...,...*...,...] * inherits: \nastavrejstrik
\backslash umistirovnici [...,*,...] * + - REFERENCE
\backslash umistiseznam [... ¹ ...,...] [...,... ² ...,...] 1 LISTE 2 inherits: \nastavseznam
\backslash umistivedlesebe {... ¹ .} {... ² .} 1 CONTENT 2 CONTENT
\backslash umistizalozky [... ¹ ...,...] [... ² ...,...] [...,... ³ ...,...] 1 ABSCHNITT LISTE 2 ABSCHNITT LISTE 3 inherits: \setupbookmark

<code>\undefinevalue {...}</code> * NAME
<code>\undepthed {...}</code> * CONTENT
<code>\underset {...} {...}</code> 1 TEXT 2 TEXT
<code>\undoassign [...] [...]</code> 1 TEXT 2 KEY = VALUE
<code>\unexpandeddocumentvariable {...}</code> * KEY
<code>\unhhbox .¹. \with {...}</code> 1 CSNAME NUMBER 2 BEFEHL
<code>\unihex {...}</code> * NUMBER
<code>\uniqueMPgraphic {...} {...,²...,...}</code> 1 NAME 2 KEY = VALUE <small>OPT</small>
<code>\uniqueMPpagegraphic {...} {...,²...,...}</code> 1 NAME 2 KEY = VALUE <small>OPT</small>
<code>\unprotect ... \protect</code>
<code>\unprotected .[*]. \par</code> * CONTENT
<code>\unregisterhyphenationpattern [...] [...]</code> 1 SPRACHE <small>OPT</small> 2 TEXT
<code>\unspaceafter \... {².}</code> 1 CSNAME 2 TEXT
<code>\unspaceargument .¹. \to \²...</code> 1 TEXT 2 CSNAME
<code>\unspaced {...}</code> * TEXT
<code>\unspacestring .¹. \to \²...</code> 1 TEXT 2 CSNAME
<code>\untexargument {...} \to \²...</code> 1 TEXT 2 CSNAME

<code>\untextcommand {...} \to \^2..</code> 1 CSNAME 2 CSNAME
<code>\uppercased {...}</code> * TEXT
<code>\uppercasestring \^1. \to \^2..</code> 1 TEXT 2 CSNAME
<code>\upperleftdoubleninequote</code>
<code>\upperleftdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrightdoubleninequote</code>
<code>\upperrightdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\urcicharakteristikurejstriku [\^1.] [\^2.,.,.,.]</code> 1 NAME 2 language = implicitni DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE metoda = implicitni pred po prvni posledni ch mm zm pm mc zc pc uc numberorder = cisla compress = ano ne vse kriterium = lokalne text aktualni predchozi vse ABSCHNITT
<code>\url [...]</code> * NAME
<code>\usealignparameter \^1..</code> * CSNAME
<code>\useblankparameter \^1..</code> * CSNAME
<code>\usebodyfont [...,*,...]</code> * inherits: \nastavzakladnifont
<code>\usebodyfontparameter \^1..</code> * CSNAME
<code>\usebtxdataset [\^1.] [\^2.] [\^3.,.,.,.]</code> 1 NAME 2 FILE 3 specification = NAME
<code>\usebtdefinitions [...]</code> * FILE
<code>\usecitation [...]</code> * REFERENCE

\usecitation {...} * REFERENCE
\usecolors [...] * FILE
\usecomponent [...] * FILE
\usedummycolorparameter {...} * KEY
\usedummystyleandcolor {...} {...} 1 KEY 2 KEY
\usedummystyleparameter {...} * KEY
\useenvironment [...] * FILE
\useexternalrendering [...] [...] [...] [...] 1 NAME 2 NAME 3 FILE 4 auto embed
\usefigurebase [...] * reset FILE
\usefile [...] [...] [...] 1 NAME 2 FILE 3 TEXT
\usegridparameter *... * CSNAME
\useindentingparameter *... * CSNAME
\useindentnextparameter *... * CSNAME
\useinterlinespaceparameter *... * CSNAME
\uselanguageparameter *... * CSNAME
\uselua module [...] * FILE
\useMPenvironmentbuffer [...] * NAME
\useMPgraphic {...} {...} {...} 1 NAME 2 KEY = VALUE

<code>\useMPlibrary [...]</code> * FILE
<code>\useMPrun {...} {...}</code> 1 NAME 2 NUMMER
<code>\useMPvariables [...]¹ [...]²,...]</code> 1 NAME 2 KEY
<code>\usemathstyleparameter *..</code> * CSNAME
<code>\useproduct [...]</code> * FILE
<code>\useprofileparameter *..</code> * CSNAME
<code>\useproject [...]</code> * FILE
<code>\userreferenceparameter *..</code> * CSNAME
<code>\userpagenumber</code>
<code>\usesetupparameter *..</code> * CSNAME
<code>\usestaticMPfigure [...]¹,...²,...]</code> 1 inherits: \setupscale ^{OPT} 2 NAME
<code>\usesubpath [...][*],...]</code> * PATH
<code>\usetexmodule [...]¹ [...]²,...]</code> 1 m p s x t ^{OPT} 2 FILE 3 KEY = VALUE ^{OPT}
<code>\usetypescript [...]¹ [...]² [...]³</code> 1 serif sans mono ^{OPT} math handwriting ^{OPT} calligraphy casual vse 2 NAME fallback implicitni dtp simple 3 size jmeno
<code>\usetypescriptfile [...]</code> * reset FILE
<code>\usezipfile [...]¹ [...]²</code> 1 FILE ^{OPT} 2 FILE
<code>\utfchar {...}</code> * NUMMER
<code>\utflower {...}</code> * TEXT

\utfupper {...} * TEXT
\utilityregisterlength
\uzijadresar [...,*...] * PATH
\uzijbloky [..., ¹ ...] [..., ² ...] [..., ³ ...,...] 1 NAME OPT OPT 2 NAME 3 kriterium = text ABSCHNITT
\uzijexternidokument [... ¹] [... ²] [... ³] 1 NAME OPT 2 FILE 3 TEXT
\uzijexterniobraz [... ¹] [... ²] [... ³] [..., ⁴ ...,...] 1 NAME OPT OPT 2 FILE 3 NAME 4 inherits: \setuexternalfigure
\uzijexternizvuk [... ¹] [... ²]
\uzijJSscripts [... ¹] [..., ² ...] 1 FILE OPT 2 NAME
\uzijmodul [... ¹] [..., ² ...] [..., ³ ...,...] 1 m p s x t OPT OPT 2 FILE 3 KEY = VALUE
\uzijsymbol [...*]
\uzijURL [... ¹] [... ²] [... ³] [... ⁴] 1 NAME OPT OPT 2 URL 3 FILE 4 TEXT
\uzijurl [... ¹] [... ²] [... ³] [... ⁴] 1 NAME OPT OPT 2 URL 3 FILE 4 TEXT
\VerboseNumber {...}
\VSEDNIDEN {...}
\ vboxreference [..., ¹ ...] {... ² }
1 REFERENCE 2 CONTENT
\vec {...}
* CHARACTER

<code>\velke ...</code> * CHARACTER
<code>\verbatim {...}</code> * CONTENT
<code>\verbatimstring {...}</code> * CONTENT
<code>\verbosenummer {...}</code> * NUMBER
<code>\verticalgrowingbar [...,...=...,...]</code> * inherits: \setuppositionbar
<code>\verticalpositionbar [...,...=...,...]</code> * inherits: \setuppositionbar
<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\verze [...]</code> * koncept soubor docasne finalni NAME
<code>\vglue ...</code> * DIMENSION
<code>\viewerlayer [...¹...] {...²...}</code> 1 NAME 2 CONTENT
<code>\vl [...]</code> * NUMBER
<code>\vlasovalinka</code>
<code>\vlevo ...</code> * CHARACTER
<code>\vphantom {...}</code> * CONTENT
<code>\vpos {...¹...} {...²...}</code> 1 NAME 2 CONTENT
<code>\vpravo ...</code> * CHARACTER
<code>\vradku {...¹...} [...²...]</code> 1 TEXT <small>OPT</small> 2 REFERENCE
<code>\vsedniden {...}</code> * NUMBER

<code>\vsmash {...}</code> * CONTENT
<code>\vsmashbox ...</code> * CSNAME NUMMER
<code>\vsmashed {...}</code> * CONTENT
<code>\vspace [...]¹ [...]²</code> 1 NAME OPT OPT 2 NAME
<code>\vspacing [...][*] [...]</code> * nastaveni stejného stránka max sila enable zablockovat zadnabila zpet prekryv vzdy weak strong implicitni pred mezi po fixne prizpusobive zadny male stredni velke radek pulradku quarterline rovnice bily vyska podlehloubky standardni NUMMER*male NUMMER*stredni NUMMER*velke NUMMER*radek NUMMER*pulradku NUMMER*quarterline NUMMER*rovnice NUMMER*bily NUMMER*vyska NUMMER*podlehloubky category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME
<code>\vyberbloky [...]¹ [...]² [...]³ [...]</code> 1 NAME 2 NAME 3 kriterium = text ABSCHNITT
<code>\VYCET [...]¹ {...}² ...³ \par</code> 1 REFERENCE OPT OPT 2 TEXT 3 CONTENT
<code>\vyplnenytex [...]¹ {...}² {...}³</code> 1 inherits: \nastavvyplnovelinky OPT OPT 2 TEXT 3 TEXT
<code>\vyplnovelinky [...]¹ {...}² {...}³</code> 1 inherits: \nastavvyplnovelinky OPT OPT 2 TEXT 3 TEXT
<code>\vyplnovyradek [...][*] [...]</code> * inherits: \nastavvyplnoveradky
<code>\vysoky {...}</code> * CONTENT
<code>\HIGH {...}</code> * CONTENT instances: unitshigh
<code>\unitshigh {...}</code> * CONTENT
<code>\WidthSpanningText {...}¹ {...}² {...}³</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\wdofstring {...}</code> * TEXT
<code>\widthhofstring {...}</code> * TEXT

<code>\widthspanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\withoutpt {...}</code> * DIMENSION
<code>\words {...}</code> * TEXT
<code>\wordtonumber {...} {...}</code> 1 jedna dve tri ctyri pet 2 TEXT
<code>\writedatatolist [...]¹ [...,...²...,...]² [...,...³...,...]³</code> 1 LISTE 2 inherits: \nastavseznam 3 KEY = VALUE <small>OPT</small>
<code>\writestatus {...} {...}</code> 1 TEXT 2 TEXT
<code>\XETEX</code>
<code>\XeTeX</code>
<code>\xdefconvertedargument \... {...}</code> 1 CSNAME 2 TEXT
<code>\xmladdindex {...}</code> * NODE
<code>\xmlafterdocumentsetup {...} {...} {...}</code> 1 NAME 2 SETUP 3 SETUP
<code>\xmlaftersetup {...} {...}</code> 1 SETUP 2 SETUP
<code>\xmlall {...} {...}</code> 1 NODE 2 LPATH
<code>\xmlappenddocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlappendsetup {...}</code> * SETUP
<code>\xmlapplyselectors {...}</code> * NODE
<code>\xmlatt {...} {...}</code> 1 NODE 2 NAME

\xmllattdef {...} {...} {...}

1 NODE
2 NAME
3 TEXT

\xmllattribute {...} {...} {...}

1 NODE
2 LPATH
3 NAME

\xmllattributedef {...} {...} {...} {...}

1 NODE
2 LPATH
3 NAME
4 TEXT

\xmllbadinclusions {...}

* NODE

\xmllbeforedocumentssetup {...} {...} {...}

1 NAME
2 SETUP
3 SETUP

\xmllbeforesetup {...} {...}

1 SETUP
2 SETUP

\xmllcommand {...} {...} {...}

1 NODE
2 LPATH
3 XMLSETUP

\xmllconcat {...} {...} {...}

1 NODE
2 LPATH
3 TEXT

\xmllconcatrange {...} {...} {...} {...} {...}

1 NODE
2 LPATH
3 TEXT
4 FIRST
5 LAST

\xmllcontext {...} {...}

1 NODE
2 LPATH

\xmllcount {...}

* NODE

\xmlldefaulttotext {...}

* NODE

\xmlldirectives {...}

* NODE

\xmlldirectivesafter {...}

* NODE

\xmlldirectivesbefore {...}

* NODE

\xmldisplayverbatim {...} * NODE
\xmldoif {...} {...} {...} 1 NODE 2 LPATH 3 TRUE
\xmldoifelse {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelseempty {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelseselfempty {...} {...} {...} 1 NODE 2 TRUE 3 FALSE
\xmldoifelsetext {...} {...} {...} {...} 1 NODE 2 LPATH 3 TRUE 4 FALSE
\xmldoifelsevalue {...} {...} {...} {...} 1 CATEGORY 2 NAME 3 TRUE 4 FALSE
\xmldoifnot {...} {...} {...} 1 NODE 2 LPATH 3 TRUE
\xmldoifnotselfempty {...} {...} 1 NODE 2 TRUE
\xmldoifnottext {...} {...} {...} 1 NODE 2 LPATH 3 TRUE
\xmldoifselfempty {...} {...} 1 NODE 2 TRUE
\xmldoiftext {...} {...} {...} 1 NODE 2 LPATH 3 TRUE
\xmlelement {...} {...} 1 NODE 2 NUMMER
\xmlfilter {...} {...} 1 NODE 2 LPATH

<pre> \xmlfirst {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlflush {...} * NODE </pre>
<pre> \xmlflushcontext {...} * NODE </pre>
<pre> \xmlflushdocumentsetups {...} {...} 1 NAME 2 SETUP </pre>
<pre> \xmlflushlinewise {...} * NODE </pre>
<pre> \xmlflushpure {...} * NODE </pre>
<pre> \xmlflushspacewise {...} * NODE </pre>
<pre> \xmlflushtext {...} * NODE </pre>
<pre> \xmlchainatt {...} {...} 1 NODE 2 NAME </pre>
<pre> \xmlchainattdef {...} {...} {...} 1 NODE 2 NAME 3 TEXT </pre>
<pre> \xmlchecknamespace {...} {...} 1 NODE 2 NAME </pre>
<pre> \xmlinclude {...} {...} {...} 1 NODE 2 LPATH 3 NAME </pre>
<pre> \xmlinclusion {...} * NODE </pre>
<pre> \xmlinclusions {...} * NODE </pre>
<pre> \xmlinfo {...} * NODE </pre>
<pre> \xmlinjector {...} * NAME </pre>
<pre> \xmlinlineprettyprint {...} {...} 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME </pre>

\xmlinlineprettyprinttext {...} {...} 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
\xmlinlineverbatim {...} * NODE
\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmllastpar
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE
\xmlnonamespace {...} {...} 1 NODE 2 LPATH

<code>\xmlpar {¹.} {².}</code> 1 NODE 2 NAME
<code>\xmlparam {¹.} {².} {³.}</code> 1 NODE 2 LPATH 3 NAME
<code>\xmlpath {[*].}</code> * NODE
<code>\xmlpos {[*].}</code> * NODE
<code>\xmlposition {¹.} {².} {³.}</code> 1 NODE 2 LPATH 3 NUMBER
<code>\xmlprependdocumentsetup {¹.} {².}</code> 1 NAME 2 SETUP
<code>\xmlprependsetup {[*].}</code> * SETUP
<code>\xmlprettyprint {¹.} {².}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlprettyprinttext {¹.} {².}</code> 1 NODE 2 mp lua xml parsed-xml nested tex context zadny NAME
<code>\xmlprocessbuffer {¹.} {².} {³.}</code> 1 BUFFER 2 NAME 3 XMLSETUP
<code>\xmlprocessdata {¹.} {².} {³.}</code> 1 NAME 2 TEXT 3 XMLSETUP
<code>\xmlprocessfile {¹.} {².} {³.}</code> 1 NAME 2 FILE 3 XMLSETUP
<code>\xmlpure {¹.} {².}</code> 1 NODE 2 LPATH
<code>\xmlraw {[*].}</code> * NODE
<code>\xmlrefatt {¹.} {².}</code> 1 NODE 2 NAME
<code>\xmlregistereddokumentsetups {¹.} {².}</code> 1 NAME 2 SETUP

<code>\xmlregisteredsetups</code>
<code>\xmlregisterns {...} {...}</code> 1 NAME 2 URL
<code>\xmlremapname {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME 4 NAME
<code>\xmlremapnamespace {...} {...} {...}</code> 1 NODE 2 NAME 3 NAME
<code>\xmlremoveddocumentsetup {...} {...}</code> 1 NAME 2 SETUP
<code>\xmlremovesetup {...}</code> * SETUP
<code>\xmlresetdocumentsetups {...}</code> * NAME
<code>\xmlresetinjectors</code>
<code>\xmlresetsetups {...}</code> * NAME
<code>\xmlsave {...} {...}</code> 1 NODE 2 FILE
<code>\xmlsetatt {...} {...} {...}</code> 1 NODE 2 NAME 3 TEXT
<code>\xmlsetAttribute {...} {...} {...} {...}</code> 1 NODE 2 LPATH 3 NAME 4 TEXT
<code>\xmlsetentity {...} {...}</code> 1 NAME 2 TEXT
<code>\xmlsetfunction {...} {...} {...}</code> 1 NODE 2 LPATH 3 LUAFUNCTION
<code>\xmlsetinjectors [...,*,...]</code> * NAME
<code>\xmlsetpar {...} {...} {...}</code> 1 NODE 2 NAME 3 TEXT

\xmlsetparam {...} {...} {...} {...}

1 NODE
2 LPATH
3 NAME
4 TEXT

\xmlsetsetup {...} {...} {...}

1 NAME
2 LPATH
3 SETUP

\xmlsetup {...} {...}

1 NODE
2 SETUP

\xmlshow {...}

* NODE

\xmlsnippet {...} {...}

1 NODE
2 NUMMER

\xmlstrip {...} {...}

1 NODE
2 LPATH

\xmlstripnolines {...} {...}

1 NODE
2 LPATH

\xmlstripped {...} {...}

1 NODE
2 LPATH

\xmlstrippednolines {...} {...}

1 NODE
2 LPATH

\xmltag {...}

* NODE

\xmlexentity {...} {...}

1 NAME
2 TEXT

\xmltext {...} {...}

1 NODE
2 LPATH

\xmltobuffer {...} {...} {...}

1 NODE
2 LPATH
3 BUFFER

\xmltobufferverbose {...} {...} {...}

1 NODE
2 LPATH
3 BUFFER

\xmltofile {...} {...} {...}

1 NODE
2 LPATH
3 FILE

\xmlvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlverbatim {...} * NODE
\xsplitstring \... {...} 1 CSNAME 2 TEXT
\xypos {...} * NAME
\Znak {...} * NUMMER
\Znaky {...} * NUMMER
\zadnamezera
\zadnehorniadolniradky
\zadnezahlaviaupati
\zachovejbloky [... ¹ ,...] [... ² ,...] 1 NAME 2 NAME OPT
\zalozka [... ¹] {... ² } 1 ABSCHNITT LISTE 2 TEXT
\zapisdoseznamu [... ¹] [... ² ,... ² ,...] {... ³ } {... ⁴ } 1 LISTE 2 inherits: \nastavseznam 3 NUMMER 4 TEXT OPT
\zapismeziseznam [... ¹] [... ² ,... ² ,...] {... ³ } 1 LISTE 2 inherits: \nastavseznam 3 BEFEHL OPT
\zaramovani [... ¹ ,... ¹ ,...] {... ² } 1 inherits: \nastavoramovani 2 CONTENT OPT
\zarovnanonastred {...} * CONTENT
\zarovnanovlevo {...} * CONTENT
\zarovnanovpravo {...} * CONTENT

$\backslash\text{zasobnikpoli}$ [¹ ...] [² ...,...] [³ ...,...] 1 NAME 2 NAME 3 inherits: \setupfieldcategory
$\backslash\text{ziskejbuffer}$ [[*] ...] * BUFFER
$\backslash\text{ziskatBUFFER}$
$\backslash\text{ziskejznaceni}$ [¹ ...] [² ...] [³ ...] 1 BESCHRIFTUNG 2 stranka NAME 3 prvi posledni aktualni predchozi dalsi vrsek spodek implicitni obe vse first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
$\backslash\text{FRACTION}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash\text{binom}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{dbinom}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{dfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{frac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{sfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{tbinom}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{xfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{xxfrac}$ { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
$\backslash\text{znaceni}$ (... ¹ ,...) (... ² ,...) [... ³] 1 POSITION 2 POSITION 3 REFERENCE
$\backslash\text{znak}$ { [*] ...} * NUMMER
$\backslash\text{znaky}$ { [*] ...} * NUMMER

```
\zpracujbloky [...,1...] [...,2...] [...,3OPT...OPT,...]  
1 NAME  
2 NAME  
3 kriterium = text ABSCHNITT
```

```
\zrcadlit {...}  
* CONTENT
```

```
\zref [...]  
* REFERENCE
```

```
\zvysit \*...  
* CSNAME
```

```
\zvysit cd:parentheses-1  
* CSNAME NUMMER
```




PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com