MP attributes backends basexx bit32 blobs boolean buffers builders caches callbacks catcodes characters chemistry commands containers context converters coroutine ctxrunner debug dir directives document documentdata drivers environment experiments figures file fio floats font fonts functions global graphics gzip images interactions interfaces io iob languages layouts lfs libraries lmx logs lpdf luatex lxml math mathematics md5 metapost mime moduledata modules mp mplib noads mode nodes number objects optional os ckage pagebuilders parametersets pdfdecode pdfe physics pngdecode publications regimes resolvers sandbox scripts set sha2 sio socket sorters sparse statistics storage streams string structures tabl texconditionals **texconfig** texconstants texifs texisdefined texmodes texsystemmodes thirddata token tokens tracers trackers typesetters updaters url userdata utf8 utilities visualizers xcomplex xdecimal xmath xml xzip zip zlib

ConT_EXt LMTX

global (alias: _G)

| CONTEXTLMTXMODE | number | directives | table |
|---------------------|----------|-----------------------|----------|
| FFISUPPORTED | boolean | document | table |
| LUAMAJORVERSION | number | documentdata | table |
| LUAMINORVERSION | number | dofile | function |
| LUATEXENGINE | string | drivers | table |
| LUATEXFORMATID | number | environment | table |
| LUATEXFUNCTIONALITY | number | error | function |
| LUATEXVERSION | number | experiments | table |
| LUAVERSION | number | figures | table |
| MP | function | file | table |
| arg | table | fio | table |
| asnumber_p | function | floats | table |
| assert | function | flushsimplerule | function |
| attributes | table | flushspecialrule | function |
| backends | table | font | table |
| basexx | table | fonts | table |
| bit32 | table | functions | table |
| blobs | table | getmetatable | function |
| blockrequire | function | getscriptstatus | function |
| boolean | table | global | table |
| buffers | table | graphics | table |
| builders | table | gzip | table |
| caches | table | handledefinitions | function |
| callback | table | handletransformstring | function |
| callbacks | table | images | table |
| catcodes | table | inspect | function |
| characters | table | interactions | table |
| checkimage | function | interfaces | table |
| chemistry | table | io | table |
| collectgarbage | function | ipairs | function |
| commands | table | job | table |
| containers | table | language | table |
| context | function | languages | table |
| converters | table | layouts | table |
| coroutine | table | lfs | table |
| createmask | function | libraries | table |
| ctxrunner | table | lmx | table |
| data | table | load | function |
| debug | table | loadfile | function |
| dimen | function | loadstring - | function |
| dir | table | logs | table |

| lpdf | table | require | function |
|-----------------|----------|------------------|------------|
| lpeg | table | required | function |
| lua | table | resolvers | table |
| luatex | table | ruledspace | function |
| lxml | table | sandbox | table |
| math | table | scripts | table |
| mathematics | table | select | function |
| md5 | table | set | table |
| metapost | table | setinspector | function |
| mime | table | setmetatable | function |
| moduledata | table | setsplitlisthtdp | function |
| modules | table | sha2 | table |
| mp | function | shipbox_ref_h | number |
| mplib | table | shipbox_ref_v | number |
| next | function | sio | table |
| noads | table | socket | table |
| node | table | sorters | table |
| nodes | table | sparse | table |
| number | table | statistics | table |
| objects | table | status | table |
| optional | table | storage | table |
| optionalrequire | function | streams | table |
| os | table | string | table |
| p_number_p | userdata | structures | table |
| p_number_u | userdata | table | table |
| package | table | tex | table |
| pagebuilders | table | texconditionals | data table |
| pairs | function | texconfig | table |
| parametersets | table | texconstants | data table |
| pcall | function | texifs | data table |
| pdf | table | texio | table |
| pdfdecode | table | texisdefined | data table |
| pdfe | table | texmodes | data table |
| physics | table | texsystemmodes | data table |
| pngdecode | table | thirddata | table |
| popleaderlevel | function | toboolean | function |
| print | function | todecimal | function |
| publications | table | token | table |
| pushleaderlevel | function | tokens | table |
| rawequal | function | tonumber | function |
| rawget | function | tostring | function |
| rawlen | function | tracers | table |
| rawset | function | trackers | table |
| regimes | table | type | function |
| | | | |

| typesetters | table | warn | function |
|-------------|----------|----------|----------|
| unpack | function | xcomplex | table |
| updaters | table | xdecimal | table |
| url | table | xmath | table |
| userdata | table | xml | table |
| utf | table | xpcall | function |
| utf8 | table | xzip | table |
| utilities | table | zip | table |
| visualizers | table | zlib | table |

attributes (context)

| alternates | table | | formatgray |
|------------------|------------|---|------------------------|
| N attribute | | | getpagecolormodel |
| D data | | | gray |
| F enable | | | graytohsv |
| F handler | | | handler |
| F register | | Т | helpers |
| D registered | | | F complement |
| D values | | | F inbetween |
| applyoverloads | function | | F justone |
| colorintents | table | F | hsvtogray |
| N attribute | | F | hsvtorgb |
| D data | | F | hwbtorgb |
| F enable | | F | iccprofile |
| F handler | | F | isblack |
| F register | | F | labtorgb |
| D registered | | F | labtoxyz |
| colors | table | N | main |
| N attribute | | S | model |
| F cmyk | | D | models |
| F cmyktogray | | F | mpcolor |
| F cmyktorgb | | F | mpnamedcolor |
| F colorcomponent | s | F | mpoptions |
| D counts | | F | namedcolorattributes |
| B couple | | N | none |
| F currentmodel | | F | popset |
| F currentnamedmo | del | F | processcolorcomponents |
| D data | | F | pushset |
| N default | | F | register |
| F defineintermed | iatecolor | D | registered |
| F definemultiton | ecolor | F | registerspotcolor |
| F defineprocesso | olor | F | rgb |
| F defineprocesso | olordirect | F | rgbtocmyk |
| F definesimplegr | ay | F | rgbtogray |
| F definespotcolo | r | F | rgbtohsv |
| F definetranspar | ency | F | rgbtoxyz |
| F enable | | N | selector |
| F filter | | F | setlist |
| N forced | | F | setmodel |
| F forcedmodel | | F | setpagecolormodel |
| F forcesupport | | D | sets |
| F formatcolor | | F | spec |
| | | | |

| F spot | | F disabletrigger | ing |
|------------------|------------|------------------|----------|
| F spotcolorname | | F enabletriggeri | .ng |
| F spotcolorparer | t | F finalize | |
| F spotcolorvalue | | F initialize | |
| B supported | | F process | |
| F toattributes | | F selective | |
| F transparencyco | mponents | F simple | |
| B triggering | | F stacked | |
| F usecolors | | F stacker | |
| D valid | | system | function |
| F value | | tooverloads | function |
| D values | | transparencies | table |
| B weightgray | | N attribute | |
| F xyztolab | | D data | |
| F xyztorgb | | F enable | |
| define | function | F forcesupport | |
| effects | table | F handler | |
| N attribute | | T names | |
| D data | | N color | |
| F enable | | N colorburn | |
| F handler | | N colordodge | |
| F register | | N darken | |
| D registered | | N difference | |
| D values | | N exclusion | |
| handlers | table | N hardlight | |
| list | data table | N hue | |
| markasoverload | function | N lighten | |
| names | data table | N luminosity | |
| negatives | table | N multiply | |
| N attribute | | N none | |
| D data | | N normal | |
| F enable | | N overlay | |
| F handler | | N saturation | |
| F register | | N screen | |
| D registered | | N softlight | |
| F set | | N none | |
| numbers | data table | F register | |
| ofnode | function | D registered | |
| private | function | B supported | |
| public | function | F toattribute | |
| restore | function | B triggering | |
| save | function | F value | |
| showcurrent | function | D values | |
| states | table | unsetvalue | number |

viewerlayers table

N attribute

F cleanup

D data

F define

F definedlayoutcomponent

F enable

F forcesupport

F handler

B hasorder

D listwise

F register

D registered

F resolve_begin

F resolve_end

F resolve_reset

F resolve_step

D scopes

F setfeatures

F start F stop

B supported

D values

backends (context)

F embedimage

F enabletags

F exportformdata

F fieldsurrounding

F flushmergelayer

closeout function F getbookmarks codeinjections table F getdefaultfieldvalue F boxresourcedimensions F getfieldcategory F registerboxresource F aetfieldset F restoreboxresource F getformatoption current strina F getidentityvariable defaults table F getinfo T codeinjections F getpreviewfigure F insertrenderingwindow T nodeinjections T registrations F jp2 D tables F jpg getcallbackstate function F maptag included table F mergebookmarks B context F mergecomments R date F meraefields B id F mergereferences B metadata F mergeviewerlayers B pdf F newimage install function F png latelua function F prerollreference nodeinjections table F presetsymbol nothing function F presetsymbollist openout function F processrendering pdf table F registerdocumentcloseaction T codeinjections F registerdocumentopenaction F addbookmarks F registeredsymbol F analyzenormalsymbol F registerpagecloseaction F analyzesymbol F registerpageopenaction F attachmentid F registerpattern F bitmap F registersymbol F clonefield F scanimage F copyimage F setattachmentsupport F definefield F setfieldcalculationset F definefieldset F setfigurealternative F defineviewerlayer F setfigurecolorspace F embedfile F setfiguremask

previous 7 next

F setformat

F setformsmethod

F setupidentity

F setpagetransition

F settaggingsupport

F setxmpfile
F startlayer
F startunicodetoactualtext

F startunicodetoactualtextdirect

F stoplayer
F stopunicodetoactualtext

F stopunicodetoactualtextdirect

F supportedformats
F unicodetoactualtext

F useviewerlayer
F validfield

F validfieldcategory

F validfieldset F wrapimage

T nodeinjections

S comment

F addtags
F annotation
F attachfile

F changestackedlayer
F cmykcolor

F comment
F destination
F effect
F graycolor

F injectbitmap

F insertmovie
F insertsound
F insertu3d

F knockout F negative

F overprint

F positive F reference

F rgbcolor F spotcolor

F startalternate

F startlayer

F startstackedlayer
F stopalternate

F stoplayer

F stopstackedlayer
F transparency
F typesetfield

T registrations
F cmykindexcolor
F cmykspotcolor

F getspotcolorreference

F grayindexcolor
F grayspotcolor
F rgbindexcolor
F rgbspotcolor
F spotcolorname
F transparency

T tables

registrations table
tables table
writeout function

basexx (extra lua)

| decode16 | function | encode16 | function |
|-----------|----------|-----------|----------|
| decode64 | function | encode64 | function |
| decode85 | function | encode85 | function |
| decodeLZW | function | encodeLZW | function |
| decodeRL | function | encodeRL | function |

bit32 (basic lua)

| arshift | function | extract | function |
|---------|----------|---------|----------|
| band | function | lrotate | function |
| bnot | function | lshift | function |
| bor | function | replace | function |
| btest | function | rrotate | function |
| bxor | function | rshift | function |

blobs (context)

| append | function | strht | function |
|------------|----------|---------|----------|
| dimensions | function | strwd | function |
| dispose | function | tohpack | function |
| new | function | tonodes | function |
| pack | function | tovpack | function |
| strdp | function | write | function |
| strhd | function | | |

boolean (context)

tocontext function
tonumber function

buffers (context)

| append | function | F define | |
|----------------|----------|------------------|----------|
| assign | function | F hassomecontent | : |
| collectcontent | function | F next | |
| erase | function | F place | |
| exists | function | F reset | |
| get | function | F save | |
| getcontent | function | prepend | function |
| getlines | function | raw | function |
| gettexbuffer | function | run | function |
| loadcontent | function | samplefile | function |
| parallel | table | undent | function |

builders (context)

| checkparcontext | | F tag | |
|-------------------|----------|------------------------|---|
| checksidefloat | function | profiling table | |
| kernel | table | F add | |
| F collapsing | | F distance | |
| F hyphenating | | F fixedprofile | |
| F kerning | | F get | |
| F ligaturing | | F list | |
| F mlisttohlist | | F pagehandler | |
| paragraphs | table | F profilebox | |
| T constructors | | F set | |
| N attribute | | vspacing table | í |
| F define | | D categories | |
| F disable | | F checkstrutdepth | |
| F enable | | F collapsevbox | |
| F handler | | T data | |
| T methods | | D map | |
| F basic | | D skip | |
| F default | | D snapmethods | |
| F hpack | | F definesnapmethod | |
| F oneline | | B fixed | |
| D names | | F forcepageflush | |
| D numbers | | F forcestrutdepth | |
| F set | | F getnofpreviouslines | |
| F start | | F inject | |
| F stop | | F injectdisable | |
| T expansion | | F injectpenalty | |
| F trace | | F injectskip | |
| F keeptogether | | F pagehandler | |
| F registertogethe | r | F pageoverflow | |
| T solutions | | F popatsame | |
| T splitters | | F pushatsame | |
| F define | | F setmap | |
| F optimize | | F setskip | |
| T registered | | F snapbox | |
| F reset | | F synchronizepage | |
| F set | | F tocategories | |
| F split | | F tocategory | |
| F start | | F vboxhandler | |
| F stop | | | |

caches (context)

| base | string | loadcontent | function |
|----------------------|----------|----------------------|----------|
| collapsecontent | function | loaddata | function |
| configfiles | function | more | string |
| contentstate | function | savecontent | function |
| defaults | table | savedata | function |
| getfirstreadablefile | function | setfirstwritablefile | function |
| getreadablepaths | function | setluanames | function |
| getwritablepath | function | treehash | function |
| hashed | function | usedpaths | function |
| is_writable | function | | |

callback (basic tex)

find function
known function
list function

register overloaded function

usage function

callbacks (context)

freeze function functions table F start page number F stop page number function known list data table pop function push function register function report function supported table B append_to_vlist_filter B begin_paragraph B build page insert B buildpage_filter B contribute filter B define font B find format file B find log file B get attribute B glyph run B handle overload B hpack filter B hpack quality B hyphenate B insert par B intercept lua error

B intercept tex error B kerning B ligaturing B linebreak filter B make extensible B missing character B mlist to hlist B open data file B paragraph context B post linebreak filter B pre dump B pre_linebreak_filter B pre output filter B process jobname B register_extensible B show_error_message B show lua call B show warning message B show whatsit B start file B start run B stop file B stop run B trace memory B vpack filter B vpack_quality

B wrapup run

catcodes (context)

 register function

characters (context)

| adobename | function | T anudatta | |
|--------------------|------------|----------------------|------------|
| bidi | data table | T before_half | |
| blockrange | function | T before_main | |
| blocks | data table | T before_postscript | |
| casemap | table | T before_subscript | |
| categories | data table | T below_mark | |
| category | function | T consonant | |
| categorytags | data table | T dependent_vowel | |
| classifiers | table | T halant | |
| collapsed | data table | T independent_vowel | |
| combined | data table | T nukta | |
| contextname | function | T post_mark | |
| csletters | data table | T pre_mark | |
| data | data table | T ra | |
| decomposed | data table | T stress_tone_mark | |
| description | function | T twopart_mark | |
| descriptions | data table | T vowel_modifier | |
| detailtags | data table | initialize | function |
| directions | table | is_character | data table |
| emoji | table | is_command | data table |
| F compact | | is_hyphenator | data table |
| F known | | is_letter | data table |
| F resolve | | is_mark | data table |
| emojized | function | is_punctuation | data table |
| enccodes | data table | is_spacing | data table |
| entities | data table | is_symbol | data table |
| fallbacks | data table | lcchars | data table |
| filters | data table | lccode | function |
| fractions | table | lccodes | data table |
| fromnumber | function | lettered | function |
| fschars | data table | lhash | data table |
| fscodes | data table | linebreaks | data table |
| getrange | function | lower | function |
| graphemes | data table | mathlists | data table |
| hangul | data table | mirrors | table |
| indicgroups | table | otfscripts | data table |
| T above_mark | | private | table |
| T after_half | | ranges | data table |
| T after_main | | registerentities | function |
| T after_postscript | | remap_hangul_syllabe | function |
| T after_subscript | | scripthash | table |

function setactivecatcodes setlettercatcodes function setothercatcodes function function shape shaped function shash data table shchars data table data table shcodes showstring function **specialchars** data table specials data table splits table T char

T char
T compat

subscriptstablesuperscriptstablesynonymsdata tabletextable

D accentmapping
D commandmapping
F defineaccents
F safechar
F strtextoutf
F strtoutfpattern
F toutf

F toutfpattern

textclasses table tonumber function ucchars data table uccode function uccodes data table uhash data table unicodechar function function upper verbosemarks data table

chemistry (context)

| component | function |
|----------------|------------|
| define | function |
| definitions | data table |
| format | string |
| inlinechemical | function |
| instance | string |

method string
molecule function
moleculeparser userdata
start function
stop function
undefine function

containers (context)

| cleanname | function | is_valid | function |
|-----------|----------|----------|----------|
| content | function | read | function |
| define | function | usecache | boolean |
| is_usable | function | write | function |

converters (context)

| A | function | cn-c | function |
|--------------------|----------|---------------------|------------|
| A:es | function | convert | function |
| A:ru | function | decimals | function |
| A:sl | function | define | function |
| AK | function | gregorian to hebrew | function |
| Alphabetic | function | gregorian_to_jalali | function |
| Alphabetic:es | function | hebrewnumerals | function |
| Alphabetic:ru | function | helpers | table |
| Alphabetic:sl | function | hexstringtonumber | function |
| Character | function | i | function |
| Characters | function | isleapyear | function |
| I | function | jalali_to_gregorian | function |
| KA | function | lchexnumber | function |
| KR | function | lchexnumbers | function |
| R | function | leapyear | function |
| RK | function | lower | function |
| Romannumerals | function | max | function |
| Russiannumerals | function | maxchrs | function |
| Sloveniannumerals | function | nicenumber | function |
| Spanishnumerals | function | nofdays | function |
| Word | function | number | function |
| Words | function | numbers | function |
| a | function | octnumber | function |
| a:es | function | octstringtonumber | function |
| a:ru | function | ordinal | function |
| a:sl | function | r | function |
| abjadnodotnumerals | function | rawcharacter | function |
| abjadnumerals | function | romannumerals | function |
| alphabetic | function | russiannumerals | function |
| alphabetic:es | function | sequences | data table |
| alphabetic:ru | function | settime | function |
| alphabetic:sl | function | sloveniannumerals | function |
| character | function | spaceddigits | function |
| characters | function | spanishnumerals | function |
| chineseallnumerals | function | textime | function |
| chinesecapnumerals | function | toabjad | function |
| chinesenumerals | function | tochinese | function |
| chr | function | tohebrew | function |
| chrs | function | toroman | function |
| cn | function | totime | function |
| cn-a | function | uchexnumber | function |

uchexnumbers upper verbose function function table F translate
weekday
word
words

function function function

coroutine (basic lua)

| close | function | running | function |
|-------------|----------|---------|----------|
| create | function | status | function |
| isyieldable | function | wrap | function |
| resume | function | yield | function |

ctxrunner (context)

load function prepfiles data table
preparedfile function resolve function

data (context)

action function depth number height number prerolled string
width number

debug (basic lua)

getinfo function
sethook function

traceback function

dir (context)

| collectpattern | function |
|----------------|----------|
| current | function |
| expandname | function |
| found | function |
| glob | function |
| globdirs | function |
| globfiles | function |

| globpattern | function |
|-------------|----------|
| ls | function |
| makedirs | function |
| mkdirs | function |
| pop | function |
| push | function |

directives (context)

| data | data table |
|---------|------------|
| default | function |
| disable | function |
| done | table |
| enable | function |
| list | function |
| name | string |

| register | function |
|----------|----------|
| report | function |
| reset | function |
| show | function |
| value | function |
| values | function |

document (context)

arguments files functions getargument getfilename options data table table table function function table D modes
D modules
targument

function setargument setcommandline function setdefaultargument function setenvironments function setfilename function setfilenames function setmodes function setmodules function variables data table

T commandline
D environments

D modes
D modules
T ctxfile

D environments

documentdata (context)

variable function

drivers (context)

| 1 | £ | _ |
|--------------|----------|-------------------|
| applyanchor | function | F wrapup |
| convert | function | T flushers |
| converters | table | F character |
| F analyze | | F popleaderlevel |
| F engine | | F pushleaderlevel |
| F lmtx | | F rule |
| F resyncbox | 6 | F simplerule |
| enable | function | F specialrule |
| gethpos | function | F updatefontstate |
| getpos | function | T whatsit |
| getrpos | function | S name |
| getvpos | function | T json |
| helpers | table | T actions |
| install | function | F cleanup |
| instances | table | F convert |
| T default | | F finalize |
| T actions | | F initialize |
| F convert | | F outputfilename |
| F outputfile | ename | F prepare |
| T flushers | | F wrapup |
| F popleaderl | Level | T flushers |
| F pushleader | rlevel | F character |
| T whatsit | | F popleaderlevel |
| S name | | F pushleaderlevel |
| T empty | | F rule |
| T actions | | F simplerule |
| F convert | | F specialrule |
| F prepare | | F updatefontstate |
| T flushers | | T whatsit |
| F popleaderl | level | S name |
| F pushleader | rlevel | T lua |
| T whatsit | | T actions |
| S name | | F cleanup |
| T js | | F convert |
| T actions | | F finalize |
| F cleanup | | F initialize |
| F convert | | F outputfilename |
| F finalize | | F prepare |
| F initialize | 2 | F wrapup |
| F outputfile | ename | T flushers |
| F prepare | | F character |

F popleaderlevel F pushleaderlevel F pushleaderlevel T whatsit F rule S name T pdf F simplerule F specialrule T actions F updatefontstate F cleanup T whatsit F convert S name F finalize F initialize T mpo T actions F outputfilename F finalize F prepare F initialize F wrapup T flushers T flushers F character F character F popleaderlevel F fontchar F pushleaderlevel F group F rule F image F simplerule F literal F specialrule F popleaderlevel T whatsit F poporientation S name F pushleaderlevel T mps F pushorientation T actions F restore F cleanup F rule F convert F save F finalize F setmatrix F initialize F setstate F outputfilename F simplerule F prepare F specialrule F wrapup F startclipping F startmatrix T flushers F character F startmirroring F popleaderlevel F startrotation F pushleaderlevel F startscaling F rule F stopclipping F simplerule F stopmatrix F specialrule F stopmirroring F updatefontstate F stoprotation T whatsit F stopscaling S name F updatefontstate T none T whatsit T actions S name lmtxversion number T flushers

F popleaderlevel

outputfilename function
report function

environment (context)

| argument | function | luafile | function |
|---------------------|------------|------------------------|------------|
| arguments | data table | luafilechunk | function |
| basicengines | data table | luatexengine | string |
| currentrun | number | luatexfunctionality | number |
| definefilefallback | function | luatexversion | number |
| definefilesynonym | function | maxnofruns | number |
| engineflags | data table | oldhome | string |
| filename | string | originalarguments | data table |
| filenames | table | outputfilename | string |
| files | table | ownbin | string |
| filesynonyms | data table | ownmain | string |
| forcedruns | number | ownname | string |
| getargument | function | ownpath | string |
| homedir | string | prerollrun | boolean |
| initex | boolean | rawarguments | data table |
| initexmode | boolean | reconstructcommandline | function |
| initializearguments | function | relativepath | function |
| initializefilenames | function | setargument | function |
| inputfilebarename | string | splitarguments | function |
| inputfilename | string | suffix | string |
| inputfilesuffix | string | texfile | function |
| jitsupported | boolean | texmfos | string |
| jobfilefullname | string | texos | string |
| jobfilename | string | texroot | string |
| jobfilesuffix | string | truefilename | function |
| jobname | string | useluamodule | function |
| kindofrun | number | usemodules | function |
| lmtxmode | number | validengines | data table |
| loadexamodes | function | version | string |
| loadluafile | function | | |
| | | | |

experiments (context)

| data | data table |
|---------|------------|
| default | function |
| disable | function |
| done | table |
| enable | function |
| list | function |
| name | string |

| register | function |
|----------|----------|
| report | function |
| reset | function |
| show | function |
| value | function |
| values | function |

figures (context)

F resetstore

applvratio function F scan badname function F serialize bases data table T sizes bitmapimage function R art boxnumber number B bleed cachepaths data table B crop check function B media checkers data table R none converters data table R trim current function F storedata defaultdepth number F totable defaultheight number T types defaultsearch hool ean N jbig2 defaultwidth number N jp2 done function N jpg function dummv N none existers data table N pdf exists function N png formats data table N stream found data table F wrap function include function get includers data table aetinfo function initialize getpdfinfo function function getrealpage function loaded data table data table function localpaths auess guessfromstring data table function magics function function hash mergegoodies identifiers data table number nofmissing identify function nofprocessed number table data table images order data table F check paths data table F checksize patterns function F copy pop preferguality boolean F create data table programs F embed function F embedfromstore push function F fetchdata registerpattern registerresource function T keys function registersuffix F print data table F resetdata remappers resources data table

| scale | function | setpaths | function |
|------------|----------|----------|------------|
| set | function | suffixes | data table |
| setlookups | function | used | data table |
| setorder | function | | |

file (basic lua)

| addsuffix | function | needsupdating | function |
|-------------------|----------|---------------|----------|
| basename | function | pathpart | function |
| checksum | function | readdata | function |
| collapsepath | function | removesuffix | function |
| сору | function | replacesuffix | function |
| dirname | function | reslash | function |
| expandname | function | robustname | function |
| extname | function | savechecksum | function |
| is_qualified_path | function | savedata | function |
| is_readable | function | size | function |
| is_rootbased_path | function | splitbase | function |
| is_writable | function | splitname | function |
| isreadable | function | splitpath | function |
| iswritable | function | strip | function |
| join | function | suffix | function |
| joinpath | function | suffixes | function |
| loadchecksum | function | suffixesonly | function |
| nameonly | function | suffixonly | function |
| nametotable | function | syncmtimes | function |
| needs_updating | function | withinbase | function |

fio (extra lua)

| getposition | function | readinteger2le | function |
|-------------------|----------|------------------|----------|
| read2dot14 | function | readinteger3 | function |
| readbytes | function | readinteger3le | function |
| readbytetable | function | readinteger4 | function |
| readcardinal1 | function | readinteger4le | function |
| readcardinal1le | function | readintegertable | function |
| readcardinal2 | function | readline | function |
| readcardinal2le | function | setposition | function |
| readcardinal3 | function | skipposition | function |
| readcardinal3le | function | writecardinal1 | function |
| readcardinal4 | function | writecardinal1le | function |
| readcardinal4le | function | writecardinal2 | function |
| readcardinaltable | function | writecardinal2le | function |
| readfixed2 | function | writecardinal3 | function |
| readfixed4 | function | writecardinal3le | function |
| readinteger1 | function | writecardinal4 | function |
| readinteger1le | function | writecardinal4le | function |
| readinteger2 | function | | |

floats (context)

| analysemethod | function | nofstacked | function |
|------------------|----------|------------|----------|
| checkedpagefloat | function | рор | function |
| collect | function | push | function |
| consult | function | resave | function |
| flush | function | save | function |
| getvariable | function | stacked | function |
| hasstacked | function | | |

font (basic tex)

| addcharacters | function | id | function |
|---------------|----------|--------------|----------|
| current | function | max | function |
| define | function | nextid | function |
| getfont | function | setfont | function |
| getfontdimen | function | setfontdimen | function |

fonts (context)

| - | | |
|--------------------|----------|-------------------------|
| analyzers | table | F currentfonthasfeature |
| D features | | D designsizes |
| D initializers | | F enhanceparameters |
| D methods | | T enhancers |
| F setstate | | T afm |
| D states | | F apply |
| B useunicodemarks | | F patch |
| checkers | table | T patches |
| F getmissing | | F register |
| D mapping | | F report |
| F missing | | F register |
| F placeholder | | F report |
| cid | table | T otf |
| F getmap | | F addfeature |
| F loadfile | | F apply |
| collections | table | F enhance |
| F checkenabled | | F patch |
| F clonevector | | T patches |
| F define | | F register |
| T definitions | | F report |
| F found | | F register |
| F prepare | | F report |
| F process | | T tfm |
| F register | | F apply |
| F registermain | | F patch |
| F report | | T patches |
| F reset | | F register |
| T vectors | | F report |
| constructors | table | F register |
| F addcharacters | | F report |
| F addcoreunicodes | | N factor |
| F aftercopyingcha | racters | T features |
| F applyfinalizers | | D afm |
| F applymanipulato | rs · | D otf |
| F assignmathparame | eters | D tfm |
| F beforecopyingcha | aracters | F finalize |
| D cache | | F getfeatureaction |
| F calculatescale | | F getmathparameter |
| F checkedfeatures | | F getprivate |
| F checkedfilename | | T handlers |
| F collectprocessor | rs · | T afm |

| B autoprefixed | F getalternate |
|----------------------------|---|
| D cache | F getgsub |
| D features | F getkern |
| F getkern | F getmultiple |
| T helpdata | F getstreamhash |
| D bothkerned | F getsubstitution |
| D leftkerned | T handlers |
| D ligatures | F devanagari_remove_joiners |
| D rightkerned | F devanagari_reorder_matras |
| D texligatures | F devanagari_reorder_pre_base_reordering_consonants |
| F load | F devanagari_reorder_reph |
| T readers | F gpos_context |
| F getinfo | F gpos_contextchain |
| F loadfont | F gpos_cursive |
| F loadshapes | F gpos_mark2base |
| F setfeatures | F gpos_mark2ligature |
| B syncspace | F gpos_mark2mark |
| N version | F gpos_pair |
| T otf | F gpos_single |
| F addfeature | F gsub_alternate |
| F basemodeinitializer | F gsub_context |
| D cache | F gsub_contextchain |
| F collectlookups | F gsub_ligature |
| T coverup | F gsub_multiple |
| T actions | F gsub_reversecontextchain |
| F alternate | F gsub_single |
| F chainposition | F trigger_space_kerns |
| F chainsubstitution | T helpers |
| F kern | F blockligatures |
| F ligature | F pardirstate |
| F multiple | F txtdirstate |
| F pair | F load |
| F single | F loadoutlinedata |
| F substitution | F loadstreamdata |
| F register | F modeinitializer |
| S stepkey | D mpscache |
| F dataset | D pdfcache |
| F datasetpositionprocessor | F plugininitializer |
| S defaultbasealternate | F pluginprocessor |
| S defaultnodealternate | T plugins |
| D features | T text |
| F featuresinitializer | D pngcache |
| F featuresprocessor | B pngenabled |
| F getactualtext | T readers |
| | |

F addunicodetable F gvar F avar F head F cbdt T helpers F cblc F axistofactors F cff F cleanname F cff2 F getaxisscale F cffcheck F getfactors T cffencoder F getscales F checkhash F gotodatatable F cmap F normalizedaxis T normalizedaxishash F colr F readvariationdata F compact F cpal F reportskippedtable F setvariabledata F ebdt F eblc F hhea F ebsc F hmtx F expand F hvar F extend F kern F fvar F loadfont F qdef F loadshapes F getcomponents F loca F getinfo F math F glyf F maxp F gpos F mvar T gposhandlers F name F chainedcontext F os/2 F context F pack F cursive F parsecharstrings F extension F post F marktobase F registerextender F marktoligature F rehash F marktomark F shix F pair F stat T streamreader F single F qsub F close T gsubhandlers F getposition F alternate F getsize F chainedcontext F look F context F open F extension F read2dot14 F ligature F readbyte F multiple F readbytes F reversechainedcontextsingle F readbytetable F single F readcardinal

| F readcardinal1 | F writeinteger3 |
|---------------------|---------------------|
| F readcardinal1le | F writeinteger3le |
| F readcardinal2 | F writeinteger4 |
| F readcardinal2le | F writeinteger4le |
| F readcardinal3 | F writestring |
| F readcardinal3le | F stripredundant |
| F readcardinal4 | F svg |
| F readcardinal4le | N tableversion |
| F readcardinaltable | F unifymissing |
| F readchar | F unpack |
| F readfixed2 | F vhea |
| F readfixed4 | F vmtx |
| F readinteger | F vorg |
| F readinteger1 | F vvar |
| F readinteger1le | F woff2otf |
| F readinteger2 | F registerpalette |
| F readinteger2le | F registerplugin |
| F readinteger3 | F reorderlookups |
| F readinteger3le | F scriptandlanguage |
| F readinteger4 | F setdynamics |
| F readinteger4le | F setfeatures |
| F readintegertable | T statistics |
| F readsignedbyte | D usedfeatures |
| F readstring | D svgcache |
| F readtag | B svgenabled |
| F setposition | T tables |
| F size | D baselines |
| F skip | D features |
| F skiplong | D featuretypes |
| F skipposition | D languages |
| F skipshort | D scripts |
| F writebyte | F texthandler |
| F writecardinal1 | N version |
| F writecardinal1le | T pfb |
| F writecardinal2 | F loadvector |
| F writecardinal2le | T tfm |
| F writecardinal3 | D cache |
| F writecardinal3le | D features |
| F writecardinal4 | N maxnestingdepth |
| F writecardinal4le | N maxnestingsize |
| F writeinteger1 | T readers |
| F writeinteger1le | F loadpk |
| F writeinteger2 | F loadtfm |
| F writeinteger2le | F loadtfmvf |
| | |

| F loadvf | | F addlookup | |
|-------------------|----------|-------------------|----------|
| F pktopdf | | F analyze | |
| F showpk | | F applypostproces | sors |
| F reencode | | F checkedmode | |
| F setfeatures | | F checkedscript | |
| N version | | S defaultlookup | |
| Tvf | | F define | |
| T combinations | 5 | F getspecificatio | n |
| F combine | | F internal | |
| T combiner | | F loadfont | |
| D commands | | F makespecificati | on |
| D helpers | | T methods | |
| D math | | F install | |
| N version | | D variants | |
| D whatever | | F read | |
| F hashfeatures | | F register | |
| F hashinstance | | F registered | |
| T hashmethods | | F registerfallbac | kfont |
| F normal | | F registersplit | |
| F virtual | | F resetnullfont | |
| F initializefeatu | res | F resolve | |
| D loadedfonts | | T resolvers | |
| N noffontsloaded | | F file | |
| N nofsharedfonts | | F name | |
| N nofsharedhashes | | F spec | |
| N nofsharedvector | s | definetypeface | function |
| N privateoffset | | dropins | table |
| D privateslots | | F clone | |
| F readanddefine | | F getshape | |
| F registerfeature | | F getshapes | |
| F resetfeature | | F nextid | |
| B resolvevirtualt | 00 | F provide | |
| F scale | | F registerglyph | |
| F scaled | | F registerglyphs | |
| F setfactor | | F swap | |
| F setfeature | | F swapone | |
| F setmathparamete | r | encodings | table |
| F setname | | T agl | |
| B sharefonts | | D ctxcodes | |
| F trytosharefont | | D extras | |
| N version | | D names | |
| current | function | D synonyms | |
| currentid | function | D unicodes | |
| definers | table | D cache | |

| D known | | D | filenames | |
|--------------------|------------|------|------------------|-------|
| F load | | F | getcompositions | |
| F make_unicode_vec | tor | Т | list | |
| D math | | F | load | |
| N version | | F | prepare_features | |
| enhanceid | function | F | register | |
| expansions | data table | F | registerpostprod | essor |
| formats | data table | F | report | |
| getalternate | function | Т | suffixes | |
| getindices | function | hand | lers | table |
| getkern | function | hash | es | table |
| getmultiple | function | D | characters | |
| getsubstitution | function | D | classes | |
| getters | table | D | csnames | |
| T alternate | | D | descriptions | |
| F opentype | | D | dynamics | |
| T kern | | D | emwidths | |
| F opentype | | D | exheights | |
| F type1 | | D | extensibles | |
| F type3 | | D | features | |
| T multiple | | D | identifiers | |
| F opentype | | D | italics | |
| T substitution | | D | lastmathids | |
| F opentype | | D | marks | |
| goodies | table | D | mathparameters | |
| D colorschemes | | D | modes | |
| T data | | D | originals | |
| T dejavu-math | | D | parameters | |
| S author | | Т | processes | |
| S comment | | D | properties | |
| S copyright | | D | quads | |
| B initialized | | D | resources | |
| T mathematics | | Т | setdynamics | |
| T alternates | | Т | shapes | |
| T dotless | | D | spaces | |
| S comment | | D | spacings | |
| S feature | | Т | streams | |
| N value | | D | unicodes | |
| T kerns | | D | variants | |
| T *:0x1D449 | | | xheights | |
| T bottomr | ight | help | ers | table |
| S name | | F | addextraprivate | |
| S version | | F | addprivate | |

D designsizes

F is_known

| F | appendcommands | | F stopcolor | | |
|---|----------------------|------|------------------|-------|-------|
| F | appendcommandtable | Т | vfspecials | | |
| F | checkflags | | T backgrounds | | |
| F | checkmerge | | T outlines | | |
| F | checksteps | info | font | funct | ion |
| F | collectanchors | iter | ators | table | ! |
| F | combineglyphs | F | characters | | |
| D | commands | F | descriptions | | |
| F | composecharacters | F | glyphs | | |
| F | descriptiontoslot | logg | ers | table | ! |
| F | dimenfactor | F | format | | |
| F | expandglyph | F | onetimemessage | | |
| Т | extraprivates | F | register | | |
| F | fontpatternhassize | F | reportdefinedfon | its | |
| F | getcoloredglyphs | F | reportusedfeatur | ·es | |
| F | getdigitwidth | mapp | ings | table | ! |
| F | getinstancespec | F | addtounicode | | |
| F | getparameters | F | fromunicode16 | | |
| F | getprivatecharornode | F | getentry | | |
| F | getprivatenode | F | loadfile | | |
| F | getprivates | F | loadline | | |
| F | getprivateslot | F | makenameparser | | |
| F | hasprivate | D | overloads | | |
| F | indextoslot | F | reset | | |
| F | mathscriptslots | F | tounicode | | |
| F | name | F | tounicode16 | | |
| F | nametoslot | F | tounicode16seque | nce | |
| F | newprivateslot | meta | post | table | ! |
| F | prependcommands | F | boundingbox | | |
| F | prependcommandtable | F | boxtomp | | |
| F | privateslot | F | draw | | |
| F | registerglyphbox | F | fill | | |
| F | scalecommands | F | glyph | | |
| F | setboxdirectly | F | maxbounds | | |
| F | setboxglyph | | paths | | |
| F | setboxglyphs | F | widthline | | |
| F | setdigitwidth | F | zeroline | | |
| F | setmetaglyph | name | | | table |
| F | setmetaglyphs | | data | | table |
| | splitfontpattern | priv | ateoffsets | table | : |
| F | tochar | В | keepnames | | |
| Т | vfinjectors | N | mathbase | | |
| | F pdf | N | mathextrabase | | |
| | F startcolor | N | textbase | | |
| | | | | | |

| N textextrabase | | F registerfall | hack |
|---------------------|------------|-------------------------------|--------|
| protrusions | data table | F registerfalt | |
| readers | table | F registerfite F registerfont | |
| F afm | tabte | F registerion: | |
| | | F registerioni | ramity |
| F check_lua | | | |
| F check_tfm | | F typeface | |
| F lua F ofm | | F typescript F userdata | |
| | | specifiers | table |
| F opentype F otf | | - | |
| | | D contextmerge | |
| F pfb | | F contextnumbe | |
| D sequence | | D contextnumbe | |
| F tfm | | D contextsetup | |
| F ttc | | F contexttostr | • |
| F ttf | | F definecontex | τ |
| F woff reserveid | function | F mergecontext | |
| reserveid select | table | F presetcontex | |
| | table | F registercont | ext |
| D alternatives | | F showcontext | |
| F bodyfont | | F splitcontext | |
| D data | | D synonyms | |
| F default | | D variants | table |
| D defaults | ., | symbols | table |
| F definefallbackf | • | T emoji | |
| F definefontfamil | | F checked | |
| F definefontfamil | ypreset | F resolved | |
| D extras | | F uselibrary | table |
| F fallback | | tables tracers | table |
| D fallbacks | | tracers | table |
| F features | | | table |
| F filefallback | | F applyfixes | |
| F fontdata | | D data | |
| F fontfallback | | S filename | |
| F fontsynonym | | F ignoredfile | |
| F goodies | | F report | |
| F mathfallback | | F trace | +-61- |
| D methods | | typefaces | table |

D presets

functions (context)

dummy function

graphics (context)

| backgrounds | table |
|-----------------|----------|
| F fetchmultipar | |
| F pair | |
| F path | |
| F point | |
| bitmaps | table |
| F flush | |
| F new | |
| F placeholder | |
| F tocontext | |
| identifiers | table |
| F bitmap | |
| F jp2 | |
| F jpg | |
| F png | |
| identify | function |

```
synchronizers table

F collapse
F collect
F extend
F getbottom
F getd
F geth
F getkind
F getsize
F gettask
```

F gettop F getw

gzip (extra lua)

| compress | function | load | function |
|------------|----------|--------|----------|
| compressed | function | save | function |
| decompress | function | suffix | function |

images (context)

| check | function | В сгор | |
|------------------------|----------|-----------|----------|
| checksize | function | B media | |
| сору | function | B none | |
| create | function | B trim | |
| embed | function | storedata | function |
| ${\tt embedfromstore}$ | function | totable | function |
| fetchdata | function | types | table |
| keys | table | N jbig2 | |
| print | function | N jp2 | |
| resetdata | function | N jpg | |
| resetstore | function | N none | |
| scan | function | N pdf | |
| serialize | function | N png | |
| sizes | table | N stream | |
| B art | | wrap | function |
| B bleed | | | |

interactions (context)

attachments data table D functions fields table D preambles F clone F setpreamble F storecode F define F defineset F storepreamble F insert F usepreamblenow general table F usescripts linkedlists data table F getidentity pages table F setupidentity help table F setpagetransition F collect F setupcanvas table references F reference F register F setclosedocument javascripts table F setclosepage F addtopreamble F setopendocument F code F setopenpage renderings data table D codes soundclips F flushpreambles data table

interfaces (context)

| arrays | table | namesofscanners | table |
|----------------------|------------|-------------------|------------|
| cachedsetups | data table | namespaces | table |
| cachesetup | function | • F define | |
| cardinals | table | F list | |
| checkedspecification | function | numbers | table |
| complete | data table | registernamespace | function |
| constants | data table | registerscanner | function |
| corenamespaces | data table | scanners | data table |
| currentinterface | string | setconstant | function |
| currentresponse | string | setcount | function |
| definecommand | function | setdimen | function |
| defined | function | setelement | function |
| doifelsemessage | function | setformat | function |
| elements | data table | setmacro | function |
| floats | table | setmessage | function |
| formats | data table | setmessages | function |
| getmessage | function | settranslation | function |
| getnamespace | function | setupstrings | data table |
| getsetupstring | function | setvariable | function |
| hashedsetups | data table | showmessage | function |
| implement | function | storedscanners | data table |
| integers | table | tolist | function |
| interfacedcommand | function | translations | data table |
| interfaces | table | usednamespaces | data table |
| knownscanner | function | variables | data table |
| message | function | writestatus | function |
| nameofscanner | function | | |
| | | | |

io (basic lua)

ask function bytes function function characters function close copydata function exists function fileseparator string flush function input overloaded function

overloaded function lines loadchunk function

loaddata function loadlines function newreader function noflines function

open overloaded function output overloaded function pathseparator string

overloaded function popen

function read readall function readnumber function readstring function savedata function size function stderr userdata stdin userdata stdout userdata function tmpfile function type

function

write

job (context)

| | _ | | | |
|---|--|---|---|-------|
| comment | function | D | tobesaved | |
| datasets | table | - | rappers | table |
| D collected | | | collected | |
| F extend | | | tobesaved | |
| F getdata | | pass | | table |
| F setdata | | | check | |
| D tobesaved | | | collected | |
| disablesave | function | F | count | |
| embedded | table | F | define | |
| D collected | | F | find | |
| D tobesaved | | F | first | |
| fileobjreferences | table | F | get | |
| D collected | | F | getcollected | |
| D tobesaved | | F | getdata | |
| files | table | F | getfield | |
| D collected | | F | gettobesaved | |
| F context | | F | inlist | |
| B forcerun | | F | last | |
| F run | | F | list | |
| D tobesaved | | F | save | |
| | | | | |
| getrandomseed | function | F | savetagged | |
| getrandomseed initialize | function function | | savetagged tobesaved | |
| | | D | | table |
| initialize | function | posi | tobesaved | table |
| initialize load | function function | p osi | tobesaved tions | table |
| initialize load loadother | function function function | posi F | tobesaved tions b_column | table |
| initialize load loadother objects | function function function | posi F F F | tobesaved tions b_column b_region | table |
| initialize load loadother objects D collected | function function function | posi F F F D | tions b_column b_region c | table |
| <pre>initialize load loadother objects D collected F get</pre> | function function function | posi F F F D | tions b_column b_region c collected | table |
| <pre>initialize load loadother objects D collected F get F number</pre> | function function function | D posi | tions b_column b_region c collected column | table |
| <pre>initialize load loadother objects D collected F get F number F page</pre> | function function function | D posi | tobesaved tions b_column b_region c collected column columnofpos | table |
| <pre>initialize load loadother objects D collected F get F number F page F save</pre> | function function function | D posi | tobesaved tions b_column b_region c collected column columnofpos copy | table |
| <pre>initialize load loadother objects D collected F get F number F page F save F set</pre> | function function function | D posi | tions b_column b_region c collected column columnofpos copy depth | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved | function function function table | D posi | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved pack | function function table boolean | D posi F F F F F F F | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column e_region | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved pack packversion | function function function table boolean number | D posi | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column e_region enhance | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved pack packversion pagestates | function function function table boolean number | D posi F F D F F F F F F F F F F | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column e_region enhance extra | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved pack packversion pagestates D collected | function function function table boolean number | D posi | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column e_region enhance extra get | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved pack packversion pagestates D collected F countervalue | function function function table boolean number | D posi | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column e_region enhance extra get getfree | table |
| initialize load loadother objects D collected F get F number F page F save F set D tobesaved pack packversion pagestates D collected F countervalue F extend | function function function table boolean number | D posi | tobesaved tions b_column b_region c collected column columnofpos copy depth e_column e_region enhance extra get getfree gethpos | table |

F settobesaved F gettobesaved F getvpos D tobesaved F hangafter F upperleft F hangindent F upperright F height F used F whd F hsize N lastx F width N lasty Fχ F leftskip F xy F lowerleft Fу register function F lowerright function F markregionbox save table structure Fη D collected F onsamepage F overlapping T components Fр T tobesaved F page T branches S name T pagedata S type F paragraph variables table F parindent F position D checksums Fr D collected F region F getchecksum F registerhandlers F makechecksum F replace F restore F rightskip F save F set F setchecksum

F setall

F setspec

F setregionbox

D tobesaved

number

version

language (basic tex)

| clean | function | id | function |
|------------------|----------|------------------|----------|
| clearhyphenation | function | new | function |
| clearpatterns | function | patterns | function |
| current | function | postexhyphenchar | function |
| gethjcode | function | posthyphenchar | function |
| has_language | function | preexhyphenchar | function |
| hyphenate | function | prehyphenchar | function |
| hyphenation | function | sethjcode | function |
| hyphenationmin | function | setwordhandler | function |

languages (context)

F injecthyphens

| addgoodiesdata | function | F installmethod | |
|------------------------|------------|------------------------|------------|
| addgoodiesfile | function | F lasttrace | |
| appliedoptions | table | F loadpatterns | |
| associate | function | F registerexception | |
| associated | data table | F registerpattern | |
| association | function | F setfeatures | |
| counters | data table | installed | function |
| current | function | installhandler | function |
| data | data table | labels | table |
| decimals | data table | F define | |
| define | function | F split | |
| explicithyphen | function | loadable | function |
| flatten | function | loadwords | function |
| frequencies | table | logger | table |
| F averagecharwidth | | F report | |
| F getdata | | nofflattened | function |
| getdata | function | numbers | data table |
| getnumber | function | postexhyphenchar | function |
| goodiefiles | function | posthyphenchar | function |
| hjcounts | table | preexhyphenchar | function |
| hyphenate | function | prehyphenchar | function |
| hyphenators | table | registered | data table |
| T dictionaries | | registeredactions | table |
| D featuresets | | replacements | table |
| F handler | | F add | |
| T methods | | F addlist | |
| F expanded | | F handler | |
| B none | | F set | |
| F original | | serializediscretionary | function |
| F tex | | setexceptions | function |
| F traditional | | setgoodieshandler | function |
| F popmethod | | setoptions | function |
| F pushmethod | | setpatterns | function |
| F setmethod | | setsynonym | function |
| F setup | | setwordhandler | function |
| F showhyphenationtrace | | showdiscretionaries | function |
| T traditional | | strippedgoodiewords | function |
| F definefeatures | | tolang | function |
| F gettrace | | transliteration | table |
| F hyphenate | | F define | |
| | | | |

F handler

| F set | | words |
|------------------|----------|------------|
| unload | function | F check |
| urls | table | T data |
| D characters | | F disable |
| N lefthyphenmin | | F enable |
| D mapping | | T enablers |
| B packslashes | | B enables |
| N righthyphenmin | | F found |
| F setcharacters | | F load |
| version | number | T methods |

N threshold

visualizediscretionaries function

table

layouts (context)

setupcanvas

getcanvasfunctionstatustablegetpagedimensionsfunctionFisleftpage

F leftorrightpageaction

function

lfs (extra lua)

attributes overloaded function iswriteablefile function chdir overloaded function link overloaded function currentdir function mkdir overloaded function dir overloaded function mkdirs function isdir overloaded function modification function isfile overloaded function readlink function isfound function rmdir overloaded function isreadabledir function setexecutable function isreadablefile function symlink function iswriteabledir function overloaded function touch

libraries (context)

| basiclua | data table |
|----------|------------|
| basictex | data table |
| builtin | data table |
| extralua | data table |

extratex data table
functions data table
globals data table

lmx (context)

| color | function |
|---------------|----------|
| convert | function |
| convertfile | function |
| convertstring | function |
| einject | function |
| eprint | function |
| escape | function |
| finalized | function |
| finject | function |
| fprint | function |
| get | function |
| getvariables | function |
| htmfile | function |
| html | table |
| _ | |

F a F td F th

include function
inherited table

S color-background-four

S color-background-one

S color-background-three

S color-background-two

S title

initialize function
inject function
lmxfile function

| loadedfile | function |
|---------------|----------|
| make | function |
| new | function |
| overloaderror | function |
| popupfile | function |
| print | function |
| pv | function |
| report | function |
| reset | function |
| result | function |
| set | function |
| show | function |
| showerror | function |
| stripcss | function |
| tv | function |
| type | function |
| urlescape | function |
| variable | function |
| variables | table |

- S color-background-blue
- S color-background-body
- S color-background-green
- S color-background-main
- S color-background-purple
- S color-background-yellow
- S title-default

logs (context)

| application | function | setformatters | function |
|----------------------|----------|-------------------|----------|
| categories | function | setlogfile | function |
| direct | function | setmessenger | function |
| disable | function | setprocessor | function |
| enable | function | settarget | function |
| finalactions | function | settimedlog | function |
| flush | function | settranslations | function |
| loggingerrors | function | show | function |
| messenger | function | start_page_number | function |
| new | function | start_run | function |
| newline | function | starterrorlogging | function |
| poptarget | function | startfilelogging | function |
| private | table | status | function |
| F enablepagetiming | | stop_page_number | function |
| F getpagetiming | | stoperrorlogging | function |
| pushtarget | function | stopfilelogging | function |
| registerfinalactions | function | subdirect | function |
| report | function | subreport | function |
| reporter | function | texerrormessage | function |
| setformats | function | writer | function |

lpdf (context)

| action | function | delayedobject | function |
|-------------------------|------------|--------------------------|----------|
| adddocumentcolorspace | function | destinationspecification | function |
| adddocumentextgstate | function | dictionary | function |
| adddocumentpattern | function | docstring | function |
| adddocumentshade | function | epdf | table |
| addtocatalog | function | F analyzefonts | |
| addtoinfo | function | F contenttotext | |
| addtonames | function | F expanded | |
| addtopageattributes | function | F getpagecontent | |
| addtopageresources | function | F getstructure | |
| addtopagesattributes | function | T image | |
| addxmpinfo | function | F close | |
| annotationspecification | function | F copy | |
| array | function | F new | |
| attachmentsymbols | function | F open | |
| boolean | function | F query | |
| border | function | F load | |
| checkedkey | function | F parsecontent | |
| checkedvalue | function | F plugin | |
| circularshade | function | T resolvers | |
| cmykcode | function | F destinations | |
| collectedresources | function | F embeddedfiles | |
| color | function | F javascripts | |
| colorspace | function | F layers | |
| colorspaceconstants | data table | F pages | |
| colorspec | function | F structure | |
| colorvalue | function | F widgets | |
| colorvalues | function | F stripcontent | |
| commentsymbols | function | F unload | |
| compresslevel | function | escaped | function |
| constant | function | finalizedocument | function |
| copyarray | function | finalizefonts | function |
| copyboolean | function | finalizepage | function |
| copyconstant | function | finishtransparencycode | function |
| copydictionary | function | flags | table |
| copyfloat | function | T annotations | |
| copyinteger | function | N AutoView | |
| copynumber | function | N Hidden | |
| copystring | function | N Invisible | |
| copyunicode | function | N Locked | |
| deferredobject | function | N LockedContents | |

| N NoRotate | | F color indirect | |
|-----------------------|----------|---------------------|------------|
| N NoView | | formats | data table |
| N NoZoom | | frombytes | function |
| N Print | | fromeight | function |
| N Printable | | frompdfdoc | function |
| N ReadOnly | | fromsixteen | function |
| N ToggleNoView | | getcatalog | function |
| N auto | | getcompression | function |
| N hidden | | getfontname | function |
| N printable | | getfontobjectnumber | function |
| T widgets | | getinfo | function |
| N Comb | | getmatrix | function |
| N CommitOnSelChange | | getmetadata | function |
| N DoNotScroll | | getnofpages | function |
| N DoNotSpellCheck | | getpageproperties | function |
| N Edit | | getpagereference | function |
| N FileSelect | | getpagetags | function |
| N MultiLine | | getpos | function |
| N NoExport | | getversion | function |
| N NoToggleToOff | | getxformname | function |
| N Password | | graycode | function |
| N PopUp | | hasmatrix | function |
| N PushButton | | id | function |
| N Radio | | immediateobject | function |
| N RadiosInUnison | | includeimage | function |
| N ReadOnly | | injectors | table |
| N Required | | F bitmap | |
| N RichText | | F jp2 | |
| N Sort | | F jpg | |
| N file | | F png | |
| N fixed | | injectxmpinfo | function |
| N nocheck | | insertxmpinfo | function |
| N protected | | lastreferredpage | function |
| N readonly | | layerreference | function |
| N required | | limited | function |
| N sorted | | linearshade | function |
| N unavailable | | literal | function |
| flushfonts | function | majorversion | function |
| flushgroup | function | makenametree | function |
| flushobject | function | minorversion | function |
| flushstreamfileobject | function | nofpages | function |
| flushstreamobject | function | null | function |
| fonts | table | number | function |
| F color_direct | | object | function |

| objectcompresslevel | function | T characters |
|---------------------------|----------|-----------------|
| pagereference | function | T descriptions |
| patternstream | function | T fonts |
| pdfcolor | function | T goodies |
| pdftimestamp | function | S original |
| pdfvfimage | function | T parameters |
| permitdetail | function | N ascender |
| print | function | N descender |
| procset | function | N designsize |
| protectresources | boolean | T expansion |
| rectangle | function | N shrink |
| reference | function | N step |
| registerannotation | function | N stretch |
| registerdestination | function | N extendfactor |
| registerdocumentfinalizer | function | N extra_space |
| registerfont | function | N extrafactor |
| registerpagefinalizer | function | N factor |
| registerpattern | function | N forcedsize |
| reserveobject | function | N hfactor |
| rgbcode | function | N mathsize |
| rotationcm | function | N maxsize |
| setcompression | function | N minsize |
| setpageorder | function | N mode |
| setpagetag | function | N quad |
| settime | function | N scaledpoints |
| setversion | function | N size |
| sharedobject | function | N slant |
| shareobject | function | N slantfactor |
| shareobjectreference | function | N space |
| spotcode | function | N space_shrink |
| stream | function | N space_stretch |
| string | function | N squeezefactor |
| toeight | function | N textsize |
| topdfdoc | function | N units |
| tosixteen | function | N vfactor |
| transparency | function | N width |
| transparencycode | function | N x_height |
| transparencygroups | table | T properties |
| B none | | S filename |
| transparencyvalue | function | B finalized |
| unicode | function | S fontname |
| usedcharacters | table | S format |
| usedfontstreams | table | S fullname |
| T dejavusansmonoboldttf-1 | | S hash |
| | | |

| B hasmath | T char-ligatures |
|---------------|-----------------------|
| N id | T * |
| S language | В * |
| • • | |
| S mode | T collapse |
| S name | Т* |
| S psname | B * |
| S script | T compat-ligatures |
| S sharedwith | T * |
| N subfont | B * |
| S writingmode | T dlig |
| T resources | T latn |
| T alreadydone | B dflt |
| T classes | B ism |
| T duplicates | B ksm |
| T features | B lsm |
| T gpos | B mol |
| T mark | B nsm |
| T arab | B rom |
| B dflt | B sks |
| T cyrl | B ssm |
| B dflt | T locl |
| B srb | T cyrl |
| T grek | B srb |
| B dflt | T latn |
| T lao | B ism |
| B dflt | B ksm |
| T latn | B lsm |
| B dflt | B nsm |
| B ism | B sks |
| B ksm | B ssm |
| B lsm | T lowercasing |
| B mol | Т * |
| B nsm | B * |
| B rom | T tlig |
| B sks | Т * |
| B ssm | B * |
| T mkmk | T trep |
| T arab | T * |
| B dflt | B * |
| T gsub | T uppercasing |
| T anum | T * |
| T arab | B * |
| B dflt | S filename |
| B urd | S foundfilename |
| D ulu | 3 Toutiu Li Cettaille |

| T foundtables | N | Ecircumflex |
|---------------|---|--------------|
| T markclasses | N | Edieresis |
| T marks | N | Edotaccent |
| T marksets | N | Egrave |
| N private | N | Emacron |
| T sequences | N | Eng |
| T sublookups | N | Eng.alt |
| T unicodes | N | Eogonek |
| N .null | N | Epsilon |
| N A | N | Epsilontonos |
| N AE | N | Eta |
| N AEacute | N | Etatonos |
| N Aacute | N | Eth |
| N Abreve | N | Euro |
| N Acircumflex | N | F |
| N Acute | N | G |
| N Adieresis | N | Gamma |
| N Agrave | N | Gbreve |
| N Alpha | N | Gcaron |
| N Alphatonos | N | Gcircumflex |
| N Amacron | N | Gcommaaccent |
| N Aogonek | N | Gdotaccent |
| N Aring | N | Grave |
| N Atilde | N | Н |
| N B | N | Hbar |
| N Beta | N | Hcircumflex |
| N C | N | I |
| N Cacute | N | IJ |
| N Caron | N | Iacute |
| N Ccaron | N | Ibreve |
| N Ccedilla | N | Icircumflex |
| N Ccircumflex | N | Idieresis |
| N Cdotaccent | N | Idotaccent |
| N Chi | N | Igrave |
| N Circumflex | N | Imacron |
| N D | N | Iogonek |
| N Dcaron | N | Iota |
| N Dcroat | N | Iotadieresis |
| N Delta | N | Iotatonos |
| N Dieresis | N | Itilde |
| N E | N | J |
| N Eacute | N | Jcircumflex |
| N Ebreve | N | К |
| N Ecaron | N | Карра |
| | | |

| | | | 6 |
|---|---------------|---|-----------------|
| | Kcommaaccent | | Sacute |
| N | | | Scaron |
| | Lacute | | Scedilla |
| | Lambda | | Scircumflex |
| | Lcaron | | Scommaaccent |
| | Lcommaaccent | | Sigma |
| | Ldot | N | |
| | Lslash | | Tau |
| N | | | Tbar |
| N | Mu | N | Tcaron |
| N | | N | Tcommaaccent |
| N | Nacute | N | Theta |
| N | Ncaron | N | Thorn |
| N | Ncommaaccent | N | Tilde |
| N | Ntilde | N | U |
| N | Nu | N | Ugrave |
| N | 0 | N | Uhorn |
| N | 0E | N | Uhungarumlaut |
| N | Oacute | N | Umacron |
| N | Obreve Obreve | N | Uogonek |
| N | Ocircumflex | N | Upsilon |
| N | Odieresis | N | Upsilon1 |
| N | 0grave | N | Upsilondieresis |
| N | Ohorn | N | Upsilontonos |
| N | Ohungarumlaut | N | Uring |
| N | Omacron | N | Utilde |
| N | Omega | N | V |
| N | Omegatonos | N | W |
| N | Omicron | N | Wacute |
| N | Omicrontonos | N | Wcircumflex |
| N | Oslash | N | Wdieresis |
| N | Oslashacute | N | Wgrave |
| N | Otilde | N | X |
| N | P | N | Xi |
| N | Phi | N | Υ |
| N | Pi | N | Yacute |
| N | Psi | N | Ycircumflex |
| N | Q | N | Ydieresis |
| N | R | N | Ygrave |
| N | Racute | N | Z |
| N | Rcaron | N | Zacute |
| N | Rcommaaccent | N | Zcaron |
| N | Rho | N | Zdotaccent |
| N | S | N | Zeta |
| | | | |

| N a | N at |
|--------------------|---------------------|
| N aacute | N atilde |
| N abreve | N b |
| N acircumflex | N backslash |
| N acute | N bar |
| N acutecomb | N beta |
| N adieresis | N block |
| N ae | N braceleft |
| N aeacute | N braceright |
| N agrave | N bracketleft |
| N alpha | N bracketright |
| N alphatonos | N breve |
| N amacron | N brokenbar |
| N ampersand | N bullet |
| N angle | N c |
| N anoteleia | N cacute |
| N aogonek | N caron |
| N approxequal | N carriagereturn |
| N arabic_2dots | N ccaron |
| N arabic_2dots_a | N ccedilla |
| N arabic_3dots | N ccircumflex |
| N arabic_3dots_a | N cdotaccent |
| N arabic_4dots | N cedilla |
| N arabic_dot | N cent |
| N arabic_gaf_bar | N chi |
| N arabic_gaf_bar_a | N circle |
| N arabic_ring | N circlemultiply |
| N aring | N circleplus |
| N arrowboth | N circumflex |
| N arrowdblboth | N club |
| N arrowdbldown | N colon |
| N arrowdblleft | N colonmonetary |
| N arrowdblright | N comma |
| N arrowdblup | N congruent |
| N arrowdown | N copyright |
| N arrowleft | N currency |
| N arrowright | N d |
| N arrowup | N dagger |
| N arrowupdn | N daggerdbl |
| N arrowupdnbse | N dcaron |
| N asciicircum | N dcroat |
| N asciitilde | N degree |
| N asterisk | N delta |
| N asteriskmath | N diaeresis.symbols |
| | |

| N | diamond | N | female |
|---|---------------|---|----------------|
| N | dieresis | N | fi |
| N | dieresistonos | N | figuredash |
| N | divide | N | filledbox |
| N | dkshade | N | filledrect |
| N | dlLtcaron | N | five |
| N | dnblock | N | fiveeighths |
| N | dollar | N | fl |
| N | dong | N | florin |
| N | dotaccent | N | four |
| N | dotbelowcomb | N | fractionslash |
| N | dotlessi | N | franc |
| N | dotlessj | N | g |
| N | dotmath | N | gamma |
| N | e | N | gbreve |
| N | eacute | N | gcaron |
| N | ebreve | N | gcircumflex |
| N | ecaron | N | gcommaaccent |
| N | ecircumflex | N | gdotaccent |
| N | edieresis | N | germandbls |
| N | edotaccent | N | gradient |
| N | egrave | N | grave |
| N | eight | N | gravecomb |
| N | element | N | greater |
| N | ellipsis | N | greaterequal |
| N | emacron | N | guillemotleft |
| N | emdash | N | guillemotright |
| N | emptyset | N | guilsinglleft |
| N | endash | N | guilsinglright |
| N | eng | N | h |
| N | eogonek | N | hbar |
| | epsilon | N | hcircumflex |
| N | epsilontonos | N | heart |
| N | equal | N | hookabovecomb |
| N | equivalence | N | house |
| N | estimated | | hungarumlaut |
| N | eta | | hyphen |
| N | etatonos | N | i |
| | eth | | iacute |
| | exclam | | ibreve |
| | exclamdbl | | icircumflex |
| | exclamdown | | idieresis |
| | existential | | igrave |
| N | f | N | ij |
| | | | |

N imacron N mu N infinity N multiply N integral N musicalnote N musicalnotedbl N integralbt N integraltp Νn N intersection N nacute N invbullet N napostrophe N invcircle N ncaron N invsmileface N ncommaaccent N iogonek N nine N iota N nonbreakingspace N iotadieresis N nonmarkingreturn N iotadieresistonos N notdef N notelement N iotatonos N itilde N notequal Νi N notsubset N jcircumflex N ntilde N jot N nu Nk N numbersign Νo N kappa N kcommaaccent N oacute N kareenlandic N obreve Νl N ocircumflex N lacute N odieresis N lambda N oe N lcaron N ogonek N lcommaaccent N ograve N ldot N ohorn N less N ohungarumlaut N lessequal N omacron N lfblock N omega N lira N omega1 N logicaland N omegatonos N logicalnot N omicron N omicrontonos N logicalor N longs N one N lozenge N oneeighth N lslash N onehalf N ltshade N onequarter N m N onesuperior N macron N onethird N male N openbullet N minus N ordfeminine N minute N ordmasculine

N orthogonal N registered N oslash N revlogicalnot N oslashacute N rho N otilde N ring Νp N rtblock N paragraph Ns N parenleft N sacute N parenright N scaron N partialdiff N scedilla N percent N scircumflex N period N scommaaccent N periodcentered N second N perpendicular N section N perthousand N semicolon N peseta N seven N phi N seveneighths N phi1 N sfthyphen N pi N shade N plus N sigma N plusminus N sigma1 N product N similar N propersubset N six N propersuperset N slash N proportional N smileface N psi N space Νq N spade N question N sterling N questiondown N suchthat N quotedbl N summation N quotedblbase N sun N quotedblleft Νt N quotedblright N tau N quoteleft N thar N quotereversed N tcaron N quoteright N tcommaaccent N quotesinglbase N therefore N quotesingle N theta Νr N theta1 N racute N thinquestion N radical N thorn N rcaron N three N rcommaaccent N threeeighths N reflexsubset N threequarters N reflexsuperset N threesuperior

| N | tilde | ı | N ygrave |
|---|----------------------|------|------------------|
| N | tildecomb | ı | N z |
| N | tonos | ı | N zacute |
| N | trademark | ı | N zcaron |
| N | triagdn | 1 | N zdotaccent |
| N | triaglf | ı | N zero |
| N | triagrt | 1 | N zeta |
| N | triagup | S | version |
| N | two | T sh | ared |
| N | twosuperior | Т | dynamics |
| N | twothirds | Т | features |
| N | u | ı | 3 analyze |
| N | ugrave | ı | 3 checkmarks |
| N | uhorn | i | 3 devanagari |
| N | uhungarumlaut | ı | 3 dummies |
| N | umacron | 1 | 3 extensions |
| N | underbar | ı | 3 extrafeatures |
| N | underbar.small | ı | 3 extraprivates |
| N | underbar.wide | ı | 3 features |
| N | underscore | ı | 3 mathrules |
| N | underscoredbl | 9 | 5 mode |
| N | union | ı | N number |
| N | universal | 1 | 3 spacekern |
| N | uogonek | ı | 3 visualspace |
| N | upblock | Т | processes |
| N | upsilon | Т | rawdata |
| N | upsilondieresis | 9 | S cache_uuid |
| N | upsilondieresistonos | ı | N cache_version |
| N | upsilontonos | 1 | 3 compacted |
| N | uring | 9 | S creator |
| N | utilde | - | Γ descriptions |
| N | V | i | 3 expanded |
| N | W | 9 | 5 format |
| N | wacute | - | Γ goodies |
| N | wcircumflex | - | Γlookuphash |
| N | wdieresis | - | Γ metadata |
| N | wgrave | | N ascender |
| N | x | | N averagewidth |
| N | xi | | T boundingbox |
| N | у | | N defaultvheight |
| N | yacute | | N descender |
| N | ycircumflex | | S family |
| N | ydieresis | | S familyname |
| N | yen | | S fontname |
| | | | |

| S fullname | S cs |
|------------------------|------------------|
| T horizontalmetrics | S detail |
| N ascender | S fallbacks |
| N descender | T features |
| N linegap | T normal |
| N maxadvanceheight | B features |
| N maxadvancewidth | S mode |
| N maxextent | N number |
| N minbottomsidebearing | S filename |
| N mintopsidebearing | S forced |
| N version | S forcedname |
| N italicangle | B global |
| B monospaced | S goodies |
| S panoseweight | S hash |
| S panosewidth | N id |
| N pfmweight | S lookup |
| N pfmwidth | N mathsize |
| S subfamily | S method |
| S subfamilyname | S name |
| N subfontindex | S resolved |
| N units | N scalemode |
| S version | N size |
| T verticalmetrics | S source |
| N ascender | S specification |
| N descender | N textsize |
| N linegap | T unscaled |
| N maxadvanceheight | N cache_version |
| N maxadvancewidth | T changed |
| N maxextent | T characters |
| N minbottomsidebearing | T descriptions |
| N mintopsidebearing | T mathparameters |
| N version | T parameters |
| S weight | N ascender |
| S width | N charwidth |
| N nofglyphs | N descender |
| N private | N designsize |
| T properties | N extra_space |
| B hascolor | N italicangle |
| B hasitalics | N maxsize |
| B hasspacekerns | N minsize |
| N size | N quad |
| N tableversion | N slant |
| N time | N space |
| T specification | N space_shrink |
| | |

N space_stretch B monospaced N units S name N vheight N private N x_height S psname T properties B setitalics S filename S space S fontname N subfont S format S writingmode usedindices table S fullname B hasmath T dejavusansmonoboldttf-1 N id verbose function

S mode

lpeg (basic lua)

| В | function | firstofsplit | function |
|--------------|----------|-----------------------|------------|
| C | function | frontstripper | function |
| Carg | function | instringchecker | function |
| Cb | function | is_lpeg | function |
| Cc | function | keeper | function |
| Cf | function | locale | function |
| Cg | function | match | function |
| Cmt | function | oneof | function |
| Ср | function | patterns | data table |
| Cs | function | pcode | function |
| Ct | function | print | function |
| P | function | ptree | function |
| R | function | replacer | function |
| S | function | secondofsplit | function |
| UP | function | setmaxstack | function |
| UR | function | setutfcasers | function |
| US | function | split | function |
| V | function | splitat | function |
| afterprefix | function | splitter | function |
| anywhere | function | stripper | function |
| append | function | times | function |
| balancer | function | tsplitat | function |
| beforesuffix | function | tsplitter | function |
| checkedsplit | function | type | function |
| containsws | function | utfchartabletopattern | function |
| counter | function | utfreplacer | function |
| endstripper | function | version | function |
| finder | function | | |
| | | | |

lua (basic tex)

| bytecode | table | macros | table |
|--------------------------------|---------------------|-------------------|------------|
| bytedata | data table | B enabled | tabte |
| • | | | |
| bytedone | table | F loaded | |
| callbytecode | function | F required | |
| delay | function | F reset | |
| finalize | function | F resolvestring | |
| firstbytecode | number | F resolving | |
| flush | function | F showdefinitions | |
| flushdelayed | function | messages | data table |
| <pre>get_functions_table</pre> | function | newindex | function |
| getbytecode | function | newtable | function |
| getcurrenttime | function | numbers | data table |
| getdebuginfo | function | registercode | function |
| getfunctionstable | overloaded function | registeredcodes | function |
| getpreciseseconds | function | registerfinalizer | function |
| getpreciseticks | function | registername | function |
| getruntime | function | setbytecode | function |
| getstacktop | function | setexitcode | function |
| getstartupfile | function | startupfile | string |
| getversion | function | version | string |
| lastbytecode | number | | |

luatex (context)

abort function F enable cleanup function F finish cleanuptempfiles function F pause currentfile function F popline poprunstate function F pushline function pushrunstate F registerdisabler registerdumpactions function F registerenabler registerpageactions function F resetfilename registerstartactions function F resume registerstopactions function F setfilename registertempfile function F setup starttime number F start table synctex F stop F blockfilename F wrapup

F collect F disable

function wrapup

lxml (context)

| addindex | function | first | function |
|-----------------|------------|-------------------|----------|
| all | function | flush | function |
| applyfunction | function | flushlinewise | function |
| applyselectors | function | flushsetups | function |
| att | function | flushspacewise | function |
| attribute | function | get_id | function |
| badinclusions | function | getid | function |
| chainattribute | function | getindex | function |
| checkindex | function | id | function |
| collected | function | idsplitter | userdata |
| command | function | ifatt | function |
| concat | function | ifattempty | function |
| concatrange | function | include | function |
| content | function | inclusion | function |
| context | function | inclusions | function |
| convert | function | index | function |
| count | function | inlineverbatim | function |
| delete | function | installsetup | function |
| depth | function | last | function |
| direct | function | lastatt | function |
| directives | table | lastmatch | function |
| F after | | lastpar | function |
| F before | | load | function |
| F handle | | loadbuffer | function |
| F load | | loaddata | function |
| F setup | | loaded | table |
| displayverbatim | function | main | function |
| doif | function | match | function |
| doifelse | function | name | function |
| doifelseempty | function | namespace | function |
| doifelsetext | function | nonspace | function |
| doifempty | function | par | function |
| doifnot | function | param | function |
| doifnotempty | function | parameter | function |
| doifnottext | function | path | function |
| doiftext | function | popmatch | function |
| element | function | pos | function |
| elements | function | position | function |
| entities | data table | pure | function |
| filter | function | pushmatch | function |
| filterlist | function | raw | function |

| rawroot | function | sorters | table |
|----------------------------|----------|----------------|------------|
| rawtex | function | F add | |
| refatt | function | F compare | |
| register | function | F flush | |
| registerentity | function | F reset | |
| removesetup | function | F show | |
| replace | function | F sort | |
| resetcdata | function | splitid | function |
| resetsetups | function | startraw | function |
| resolvedentity | function | startunescaped | function |
| root | function | stopraw | function |
| save | function | stopunescaped | function |
| serialize | function | store | function |
| setaction | function | strip | function |
| setatt | function | stripped | function |
| setattribute | function | tag | function |
| setcdata | function | text | function |
| ${\tt setcommandtonone}$ | function | tobuffer | function |
| ${\tt setcommand to text}$ | function | tofile | function |
| setpar | function | toparameters | function |
| setparam | function | toverbatim | function |
| setparameter | function | verbatim | function |
| setsetup | function | withindex | function |
| snippet | function | xmltexhandler | data table |
| | | | |

math (basic lua)

| abs | function | |
|-------------|----------|--|
| acos | function | |
| asin | function | |
| atan | function | |
| atan2 | function | |
| ceil | function | |
| ceiling | function | |
| cos | function | |
| cosd | function | |
| cosh | function | |
| deg | function | |
| div | function | |
| even | function | |
| exp | function | |
| floor | function | |
| fmod | function | |
| huge | number | |
| initialseed | number | |
| ldexp | function | |
| log | function | |
| log10 | function | |
| max | function | |
| maxinteger | number | |

| min | function | |
|----------------|------------|----------|
| mininteger | number | |
| mod | function | |
| modf | function | |
| odd | function | |
| pi | number | |
| pow | function | |
| rad | function | |
| random | overloaded | function |
| randomseed | function | |
| round | function | |
| setrandomseedi | function | |
| sin | function | |
| sind | function | |
| sinh | function | |
| sqrt | function | |
| tan | function | |
| tand | function | |
| tanh | function | |
| tointeger | function | |
| type | function | |
| | | |

function

ult

mathematics (context)

| addfallbacks | function | mapremap | data table |
|------------------------|------------|------------------------|------------|
| alphabets | data table | overloadparameters | function |
| alternatives | data table | privatebase | number |
| big | function | registerdomain | function |
| boldmap | data table | registerfallbackid | function |
| categories | table | remapalphabets | function |
| D functions | | renderings | table |
| charactersets | data table | D mappings | |
| checkaccentbaseheight | function | D numbers | |
| checkprivateparameters | function | D sets | |
| classes | data table | renderset | function |
| codes | data table | resetattributes | function |
| define | function | resetitalics | function |
| dimensions | function | resolvefallbacks | function |
| domains | table | scaleparameters | function |
| extensiblecode | function | setdomain | function |
| extensibles | data table | setitalics | function |
| extrabase | number | setridofprime | function |
| extras | table | sets | data table |
| F add | | styles | data table |
| F copy | | syncboth | function |
| fallbacks | table | syncname | function |
| F apply | | syncstyle | function |
| F install | | toname | function |
| fallbackstyleattr | function | tostyle | function |
| families | data table | tweakaftercopyingfont | function |
| finishfallbacks | function | tweakbeforecopyingfont | function |
| gaps | data table | tweaks | table |
| getboth | function | utfmathaccent | function |
| getdomain | function | utfmathclass | function |
| getitalics | function | utfmathcommand | function |
| getridofprime | function | utfmathfiller | function |
| getstyle | function | utfmathstretch | function |
| horizontalcode | function | virtualize | function |
| initializeparameters | function | virtualized | data table |
| makefont | function | | |

md5 (extra lua)

| HEX | function | sum | function |
|-----|----------|---------|----------|
| dec | function | sumHEXA | function |
| hex | function | sumhexa | function |

metapost (context)

N message

N mode

checkformat function N newinternal function cm N nullary codes table N numeric N addto N of N ampersand N ofbinary N and N outertag N assignment N parametertype N atleast N plus or minus N begingroup N primarybinary N btex N primarydef N capsule N protection N colon N randomseed N comma N relax N repeat_loop N controls N curl N rightbrace N cycle N rightbracket N rightdelimiter N declare N def N runscript N definedmacro N save N delimiters N scantokens N endgroup N scope N equals N secondarybinary N etex N secondarydef N semicolon N everyjob N exitif N setbounds N expandafter N shipout N fi or else N show Nif N skip N input N slash N interim N step N internal N stop N iteration N str N join N string N leftbrace N tag N leftbracket N tension N leftdelimiter N tertiarybinary N let N tertiarydef N macrospecial N thingstoadd N maketext N to

N unary

N undefinedcs

| N until | | includesvgbuffer | function |
|---------------------|------------|---------------------|----------|
| N void | | includesvgfile | function |
| N with | | installplugin | function |
| N within | | isobject | function |
| N write | | knownparameters | table |
| colorinitializer | function | lastlog | string |
| convert | function | load | function |
| currentmpx | function | maketext | function |
| currentmpxstatus | function | metafonts | table |
| defaultformat | string | metafun | table |
| defaultinstance | string | F interpolate | |
| defaultmethod | string | F topath | |
| directrun | function | mptopdf | table |
| escaped | function | F convertmpstopdf | |
| exectime | table | N nofconverted | |
| extensiondata | data table | n | number |
| filterclippath | function | nofruns | number |
| flush | function | nofscriptruns | function |
| flushers | table | nvformat | function |
| T pdf | | pdfliterals | function |
| F flushfigure | | pluginactions | function |
| F startfigure | | popformat | function |
| F stopfigure | | popscriptrunner | function |
| F textfigure | | popvariable | function |
| F tocomment | | popvariables | function |
| flushnormalpath | function | preparetextextsdata | function |
| fonts | table | process | function |
| F define | | processing | function |
| format_number | function | processplugins | function |
| format_string | function | properties | table |
| formatnumber | function | pushformat | function |
| getbendtolerance | function | pushscriptrunner | function |
| getclippath | function | pushvariable | function |
| getextensions | function | pushvariables | function |
| getextradata | function | reducetogray | boolean |
| gethashentries | function | registerdirect | function |
| getinstancenames | function | registerscript | function |
| getjobdata | function | registertokens | function |
| getparameter | function | remappedtext | function |
| getparameterset | function | remaptext | function |
| getstatistics | function | reporterror | function |
| gettext | function | reportsvgfonts | function |
| graphic | function | reset | function |
| graphic_base_pass | function | resetlastlog | function |

| <pre>run function F get runscript function F reset scanparameters function F set scripterror function F setfrombuffer scriptindex function texerrors boolea setbendtolerance function texexp function</pre> | ion ion |
|---|------------|
| scanparametersfunctionF setscripterrorfunctionF setfrombufferscriptindexfunctiontexerrorsboolean | ion ion |
| scripterror function F setfrombuffer scriptindex function texerrors boolean | ion ion |
| scriptindex function texerrors booles | ion ion |
| | ion ion |
| setbendtolerance function texexp functi | Lon |
| | |
| setextensions function theclippath function | |
| setoutercolor function tographic function | .on |
| setparameterset function totable function | on |
| settext function types table | |
| setvariable function N boolean | |
| showlog boolean N cmykcolor | |
| showsvgpage function N color | |
| simple function N dependent | |
| <pre>splitprescript function N independent</pre> | |
| startgraphic function N known | |
| <pre>startsvghashing function N numeric</pre> | |
| stopgraphic function N pair | |
| <pre>stopsvghashing function N path</pre> | |
| <pre>svformat function N pen</pre> | |
| <pre>svgcolorremapper function N picture</pre> | |
| svgfactors table N protodependent | |
| N % N string | |
| N bp N structured | |
| N cm N suffixedmacro | |
| N em N tokenlist | |
| N ex N transform | |
| N in N unknownboolean | |
| N mm N unknownpath | |
| N pc N unknownpen | |
| N pt N unknownpicture | |
| N px N unknownstring | |
| <pre>svgglyphtomp function N unsuffixedmacro</pre> | |
| svgshapestomp function N vacuous | |
| <pre>svgshapestopdf function typesvgpage function</pre> | on |
| svgsplitcolor function unload function | on |
| <pre>svgtomp function untagvariable funct;</pre> | on |
| <pre>svgtopdf function variables table</pre> | |

function

sxsy

mime (extra lua)

b64 function decode function decodet table F base64 F quoted-printable function dot function encode encodet table

F base64

F quoted-printable

eol function normalize function function qр

qpwrp function function report stuff function unb64 function unqp function function wrap table wrapt F base64

F default

F quoted-printable

F text

function wrp

mp (context)

| autoiniost | function | direct3 | function |
|-------------------|----------|---------------------------------------|----------|
| autoinject aux | table | direct4 | function |
| F boolean | tabte | disposehash | function |
| F color | | draw | function |
| F direct | | expandtex | function |
| F direct1 | | fill | function |
| F direct2 | | flatten | function |
| | | flush | function |
| F direct3 | | format | function |
| F direct4 | | formatted | function |
| F draw | | | function |
| F fill | | fprint fromhash | function |
| F flush | | | table |
| F fprint | | get | table |
| F integer | | F hashentry | £ |
| F number | | graphformat | function |
| F numeric | | inhash | function |
| F pair | | inject | function |
| F pairpoints | | F boolean | |
| F path | | F cmykcolor | |
| F pathpoints | | F color | |
| F points | | F integer | |
| F print | | F number | |
| F quadruple | | F numeric | |
| F quadruplepoints | | F pair | |
| F quoted | | F path | |
| F size | | F quadruplet | |
| F string | | F string | |
| F transform | | F transform | |
| F triplet | | F triplet | |
| F tripletpoints | | F whatever | |
| F vprint | | integer | function |
| boolean | function | isarray | function |
| cleaned | function | isobject | function |
| color | function | <pre>lmt_color_functions</pre> | table |
| dataset | function | F shade | |
| datasets | function | F step | |
| F load | | lmt_contours_bitmap_get | function |
| dimension | function | <pre>lmt_contours_bitmap_set</pre> | function |
| direct | function | lmt_contours_cleanup | function |
| direct1 | function | lmt_contours_color | function |
| direct2 | function | <pre>lmt_contours_edge_get_band</pre> | function |

| <pre>lmt_contours_edge_get_cell</pre> | function | mf_graphic_text | function |
|--|----------|----------------------|----------|
| <pre>lmt_contours_edge_paths</pre> | function | mf_inject_blob | function |
| <pre>lmt_contours_edge_set</pre> | function | mf_map_move | function |
| <pre>lmt_contours_edge_set_by_band</pre> | function | mf_map_text | function |
| <pre>lmt_contours_edge_set_by_cell</pre> | function | mf_named_color | function |
| <pre>lmt_contours_format</pre> | function | mf_outline_text | function |
| <pre>lmt_contours_function</pre> | function | mf_save_data | function |
| lmt_contours_maxmean | function | mf_script_index | function |
| lmt_contours_maxz | function | mf_start_saving_data | function |
| lmt_contours_minmean | function | mf_stop_saving_data | function |
| lmt_contours_minz | function | mf_tb_dimensions | function |
| lmt_contours_nofvalues | function | mf_tt_dimensions | function |
| lmt_contours_nx | function | mf_tt_initialize | function |
| lmt_contours_ny | function | mode | function |
| <pre>lmt_contours_range</pre> | function | n | function |
| <pre>lmt_contours_shade_paths</pre> | function | newhash | function |
| <pre>lmt_contours_shade_set</pre> | function | number | function |
| <pre>lmt_contours_shape_paths</pre> | function | numeric | function |
| lmt_contours_start | function | pair | function |
| <pre>lmt_contours_stop</pre> | function | pairpoints | function |
| lmt_contours_value | function | path | function |
| lmt_contours_xrange | function | pathpoints | function |
| lmt_contours_yrange | function | points | function |
| <pre>lmt_function_x</pre> | function | positionanchor | function |
| <pre>lmt_mesh_set</pre> | function | positionbox | function |
| lmt_mesh_update | function | positioncurve | function |
| lmt_poisson_generate | function | positionpage | function |
| lmt_surface_do | function | positionpath | function |
| lmt_svg_include | function | positionpxy | function |
| mf_blob_add | function | positionregion | function |
| mf_blob_dimensions | function | positionwhd | function |
| mf_blob_index | function | positionxy | function |
| mf_blob_new | function | prefix | function |
| mf_blob_raw_content | function | print | function |
| mf_blob_raw_dimensions | function | processingmode | function |
| mf_blob_raw_reset | function | quadruple | function |
| mf_blob_raw_toutf | function | quadruplepoints | function |
| mf_blob_raw_wipe | function | quoted | function |
| mf_blob_size | function | report | function |
| mf_blob_width | function | scan | table |
| mf_external_figure | function | F boolean | |
| mf_finish_saving_data | function | F cmykcolor | |
| mf_formatted_text | function | F color | |
| me mak auklima kauk | £ | | |

F expression

function

mf_get_outline_text

| F integer | | size | function |
|-------------|-------|---------------|----------|
| F next | | skip | table |
| F number | | F token | |
| F numeric | | solve | function |
| F pair | | string | function |
| F path | | systemmode | function |
| F pen | | texstr | function |
| F property | | texvar | function |
| F string | | tohash | function |
| F symbol | | transform | function |
| F token | | triplet | function |
| F transform | | tripletpoints | function |
| set | table | vprint | function |

mplib (extra tex)

| execute | function | injecttransform | function |
|------------------|----------|-----------------|---------------------|
| expandtex | function | injectwhatever | function |
| finder | function | new | overloaded function |
| finders | table | peninfo | function |
| F file | | propertycodes | table |
| F mpstemplate | | realtimelogging | boolean |
| finish | function | scanboolean | function |
| getcallbackstate | function | scancmykcolor | function |
| getcodes | function | scancolor | function |
| getfields | function | scanexpression | function |
| gethashentries | function | scaninteger | function |
| gethashentry | function | scannext | function |
| getstates | function | scannumber | function |
| getstatistics | function | scannumeric | function |
| getstatus | function | scanpair | function |
| gettolerance | function | scanpath | function |
| gettype | function | scanpen | function |
| gettypes | function | scanproperty | function |
| injectboolean | function | scanstring | function |
| injectcmykcolor | function | scansymbol | function |
| injectcolor | function | scantoken | function |
| injectinteger | function | scantransform | function |
| injectnumber | function | settolerance | function |
| injectnumeric | function | showcontext | function |
| injectpair | function | skiptoken | function |
| injectpath | function | solvepath | function |
| injectstring | function | version | function |
| | | | |

noads (context)

F render

| handlers | table | F resize | |
|--------------|-------|----------------|----------|
| F align | | F showtree | |
| F alternates | | F tags | |
| F autofences | | F unscript | |
| F classes | | F unstack | |
| F collapse | | F variants | |
| F domains | | process | function |
| F families | | processnested | function |
| F fixscripts | | processors | table |
| F italics | | F mlisttohlist | |
| F kernpairs | | T unscript | |
| F makeup | | T unstack | |
| F relocate | | processouter | function |

node (basic tex)

checkdiscretionaries checkdiscretionary copy copy list copylist count current attributes currentattributes dimensions direct table F addmargins F addxoffset F addxymargins

> F checkdiscretionary F collapsing F copy F copy list F copylist F copyonly F count F current attributes F currentattributes

F addyoffset

F appendaftertail

F checkdiscretionaries

F dimensions F effective glue F effectiveglue F end of math F endofmath F exchange F fields F find node F findattribute F findattributerange F findnode

F first glyph F firstqlyph F flattendiscretionaries

F flush list F flush node function function function function function function function function

F qetattributelist F getattributes function F getboth F getbox F getchar F getcharspec F getdata F getdepth F getdirection F aetdisc F getdiscpart F getexpansion

> F getglyphdimensions F getheight F getid F getindex F getkern F getkerndimension

F getfam

F getfield

F getfont

F getglue

F getglyphdata

F flushlist

F flushnode

F get attribute

F get attributes

F getattribute

F free

F getlanguage F getleader F getlist F getnext F getnormalizedline

F getnucleus F getoffsets F getoptions F getorientation F getparstate F getpenalty F getpost

F getpre F isglyph F isnextchar F getprev F getpropertiestable F isnextqlyph F isnode F getproperty F getreplace F isprevchar F getscale F isprevglyph F getscales F isvalid F iszeroalue F getscript F getshift F kerning F getstate F length F getsub F ligaturing F getsubpre F makeextensible F getsubtype F migrate F getsup F mlist to hlist F getsuppre F mlisttohlist F getsynctexfields F naturalhsize F gettotal F naturalwidth F getwhd F new F getwidth F prependbeforehead F getxscale F protect glyph F getxyscales F protect_glyphs F getyscale F protectglyph F has attribute F protectglyphs F has field F protrusionskippable F has glyph F rangedimensions F hasattribute F remove F hasdimensions F reverse F hasfield F set attribute F hasglyph F set attributes F hasqlyphoption F setattribute F setattributelist F hpack F hyphenating F setattributes Fid F setboth F ignoremathskip F setbox F setchar F insert after F insert before F setdata F insertafter F setdepth F insertbefore F setdirection F is char F setdisc F is_glyph F setdiscpart F is node F setexpansion F is valid F setfam F is zero glue F setfield

F setfont

F ischar

| F | setglue | | F traverse | | |
|---|------------------|-----|--------------------|-----|----------|
| F | setglyphdata | | F traverse_char | | |
| F | setheight | | F traverse_content | | |
| F | setindex | | F traverse_glyph | | |
| F | setkern | | F traverse_id | | |
| F | setlanguage | | F traverse_list | | |
| F | setleader | | F traversechar | | |
| F | setlink | | F traversecontent | | |
| F | setlist | | F traverseglyph | | |
| F | setnext | | F traverseid | | |
| F | setnucleus | | F traverselist | | |
| F | setoffsets | | F type | | |
| F | setoptions | | F types | | |
| F | setorientation | | F unprotect_glyph | | |
| F | setpenalty | | F unprotect_glyphs | | |
| F | setpost | | F unprotectglyph | | |
| F | setpre | | F unprotectglyphs | | |
| F | setprev | | F unset_attribute | | |
| F | setproperty | | F unset_attributes | | |
| F | setreplace | | F unsetattribute | | |
| F | setscales | | F unsetattributes | | |
| F | setscript | | F usedlist | | |
| F | setshift | | F uses_font | | |
| F | setsplit | | F usesfont | | |
| F | setstate | | F values | | |
| F | setsub | | F verticalbreak | | |
| F | setsubpre | | F vpack | | |
| F | setsubtype | | F write | | |
| F | setsup | | F xscaled | | |
| F | setsuppre | | F yscaled | | |
| F | setsynctexfields | eff | ective_glue | | function |
| F | settotal | eff | ectiveglue | | function |
| F | setwhd | end | _of_math | | function |
| F | setwidth | | ofmath | | function |
| F | show | fam | ily_font | | function |
| F | slide | fie | elds | | function |
| F | start_of_par | | dattribute | | function |
| F | startofpar | | st_glyph | | function |
| F | subtypes | | stglyph | | function |
| F | tail | | ttendiscretionari | .es | function |
| F | todirect | | sh_list | | function |
| F | tonode | | sh_node | | function |
| F | tostring | | shlist | | function |
| F | tovaliddirect | flu | shnode | | function |
| | | | | | |

| free | function | new | function |
|--------------------|----------|---------------------|----------|
| get_attribute | function | protect_glyph | function |
| getattribute | function | protect_glyphs | function |
| getfield | function | protectglyph | function |
| getglue | function | protectglyphs | function |
| getpropertiestable | function | protrusionskippable | function |
| getproperty | function | rangedimensions | function |
| has_attribute | function | remove | function |
| has_field | function | set_attribute | function |
| has_glyph | function | setattribute | function |
| hasattribute | function | setfield | function |
| hasfield | function | setglue | function |
| hasglyph | function | setproperty | function |
| hpack | function | show | function |
| hyphenating | function | slide | function |
| id | function | subtypes | function |
| insert_after | function | tail | function |
| insert_before | function | tostring | function |
| insertafter | function | traverse | function |
| insertbefore | function | traverse_id | function |
| instock | function | traverseid | function |
| inuse | function | type | function |
| is_node | function | types | function |
| is_zero_glue | function | unprotect_glyph | function |
| isnode | function | unprotect_glyphs | function |
| iszeroglue | function | unprotectglyph | function |
| kerning | function | unprotectglyphs | function |
| last_node | function | unset_attribute | function |
| lastnode | function | unsetattribute | function |
| length | function | usedlist | function |
| ligaturing | function | usesfont | function |
| makeextensible | function | values | function |
| mlist_to_hlist | function | vpack | function |
| mlisttohlist | function | write | function |

nodes (context)

fieldtypes

| accentcodes | data table | fillcodes | | |
|--------------------|------------|-------------------|--|--|
| aligned | function | fillvalues | | |
| append - | function | firstcharacter | | |
| apply | function | firstcharinbox | | |
| applyvisuals | function | firstdirinbox | | |
| astable | function | flush | | |
| basepoints | function | flush_list | | |
| boundarycodes | data table | flush_node | | |
| boxes | table | flushlist | | |
| F dimensions | | flushnode | | |
| F direct | | fullhpack | | |
| F found | | getattr | | |
| F reset | | getattribute | | |
| F restore | | getboth | | |
| F save | | getbox | | |
| F savenode | | getchar | | |
| builders | table | getfield | | |
| F buildpage_filter | | getfont | | |
| F vpack_filter | | getid | | |
| concat | function | getleader | | |
| сору | function | getlist | | |
| copy_list | function | getnext | | |
| copylist | function | getprev | | |
| countall | function | getproperty | | |
| current_attributes | function | getsubtype | | |
| currentattributes | function | gluecodes | | |
| delete | function | glyphcodes | | |
| destinations | table | handlers | | |
| N attribute | | F accessibility | | |
| T done | | F backgrounds | | |
| F handler | | F backgroundspage | | |
| T stack | | F backgroundsvbox | | |
| dircodes | data table | F characters | | |
| directioncodes | data table | F checkglyphs | | |
| directionvalues | data table | F checkparcounter | | |
| dirvalues | data table | F cleanupbox | | |
| disccodes | data table | F cleanuppage | | |
| discretionarycodes | data table | F export | | |
| fencecodes | data table | F finalizebox | | |
| fields | function | F finalizelist | | |
| | | | | |

data table data table function data table data table table

F flatten

table

| F flattenline | | kerncodes | data table |
|-------------------------|----------|------------------|------------|
| F migrate | | leftmarginwidth | function |
| F protectglyphs | | linefillers | table |
| F show | | D data | |
| F showhyphenation | | F define | |
| F stripping | | F enable | |
| F textbackgrounds | | F filler | |
| F unprotectglyphs | | F handler | |
| F visualizehyphenation | | lines | table |
| F wipe | | T boxed | |
| has_attribute | function | F addlinenumbers | |
| has_field | function | F register | |
| hasattribute | function | F setup | |
| hasfield | function | D data | |
| hpack | function | F finalize | |
| idsandsubtypes | function | F number | |
| idstostring | function | link | function |
| injections | table | linked | function |
| F copy | | list | function |
| F getligaindex | | listcodes | data table |
| F getthreshold | | listtoutf | function |
| F handler | | literalvalues | data table |
| F installgetspaceboth | | locate | function |
| F installnewkern | | markers | table |
| F isspace | | F get | |
| F keepcounts | | mathcodes | data table |
| F reset | | mathvalues | data table |
| F resetcounts | | maxboxwidth | function |
| F setcursive | | migrations | table |
| F setkern | | F setinserts | |
| F setligaindex | | F setmarks | |
| F setmark | | new | function |
| F setmove | | noadcodes | data table |
| F setposition | | noadoptions | table |
| F setspacekerns | | N axis | |
| insert_after | function | N exact | |
| insert_before | function | N left | |
| insertafter | function | N middle | |
| insertbefore | function | N no_axis | |
| insertlistafter | function | N right | |
| installattributehandler | function | N set | |
| is_display_math | function | N unused_1 | |
| is_node | function | N unused_2 | |
| isnode | function | nodecodes | data table |

function nopts F findattribute table nuts F findnode F addmargins F first glyph F addxoffset F firstcharacter F firstcharinbox F addxymargins F addyoffset F firstqlyph F append F flattendiscretionaries F appendaftertail F flush F apply F flush list F applyvisuals F flush node F checkdiscretionaries F flushlist F flushnode F collapsing T colors F free F set F fullhpack T components F get attribute F copynocomponents F get synctex fields F copyonlyglyphs F getattr F count F getattribute F flush F getattributelist F get F getattributes F set F getattrlist F concat F getattrs F getboth F copy F getbox F copy list F copy node F getboxglue F copy_only F getchar F copy properties F getcharspec F copylist F getcomponents F copynode F getdata F copyonly F getdepth F copyvisual F getdirection F count F getdisc F countall F getdiscpart F current attr F getdiscretionary F currentattributes F getexpansion F delete F getfam F getfield F dimensions F dirdimensions F getfont F effective glue F getglue F effectiveglue F getglyphdata F end of math F getglyphdimensions F endofmath F getheight F exchange F getid

F getindex

F find attribute

F getkern F hasfield F getkerndimension F hasglyph F getlang F hasglyphoption F getlanguage F hpack F getleader F hyphenating F ignoremathskip F getlist F getnext F insert_after F getnormalizedline F insert before F insertafter F getnucleus F getoffsets F inserthefore F insertlistafter F getoptions F getorientation F is display math F getpenalty F is node F getpost F is zero glue F getpre F ischar F getprev F isdone F getprop F isqlyph F isnextchar F getreplace F getruledata F isnextglyph F getscale F isnode F getscales F isprevchar F getscript F isprevglyph F getshift F iszeroglue F kerning F getstate F getsub F length F getsubpre F ligaturing F link F getsubtype F getsup F linked F locate F getsuppre F getsurround F migrate F getsynctexfields F mlist to hlist F gettotal F mlisttohlist F getvalue F naturalhsize F naturalwidth F getwhd F nestedtracedslide F getwidth F getxscale F new T pool F getxyscales F getyscale F accent F has attribute F baselineskip F has dimensions F boundary F has field F choice F has glyph F cleanup F hasattribute F delim F hasdimensions F delimiter

F direction F stretch F directliteral F subbox F disc F submlist F temp F emptyrule F fence F usage F fontkern F userdefined F fraction T userids F alue F usernode Fuserrule F gluespec F glyph F vlist F hlist F wordboundary F indentskip F prepend F italickern F prependbeforehead F kern F processranges F latelua F processwords F leader F protect glyph F lefthangskip F protect glyphs F leftmarginkern F protectglyph F leftskip F protectglyphs F lineskip F protrusionskippable F literal F rangedimensions F mathchar F rawprop F mathtextchar F reference F negatedglue F rehpack F noad F remove F originliteral F repackhlist F outlinerule F replace F pageliteral F reverse F penalty T rules F radical T ruleactions F rawliteral F box F register F draw F restore F fill F righthangskip F mp F rightmarginkern F stroke F rightskip F userrule F rule F set attribute F setattr F save F savepos F setattribute F setmatrix F setattributelist F setstate F setattrlist F shrink F setattrs F startrotation F setboth

F setbox

F stock

F setboxglue F setsup F setchar F setsuppre F setcomponents F setsurround F setsynctexfields F setdata F setdepth F setvalue F setvisual F setdirection F setdisc F setvisuals F setdiscpart F setwhd F setwidth F setdiscretionary F setexpansion F show F setfam F slide F setfield F somepenalty F setfont F somespace F setglue F splitbox F setglyphdata F start_of_par F setheight F startofpar F setkern F striprange F tail F setlang F setlanguage F takeattr F setleader F takebox F setlink F takelist F setlist F theprop F setnext F tonode F setnucleus F tonodes F setoffsets F tonut F setoptions F tosequence F setorientation F tostring F setparproperty F tracedslide F setpenalty F traverse F setpost F traverse char F setpre F traverse glyph F traverse_id F setprev F setprop F traverse list F traversechar F setreplace F setruledata F traversecontent F setscale F traverseglyph F traverseid F setscales F traverselist F setscript F setshift T traversers F setsplit F boundary F setstate F char F setsub F content F dir F setsubpre F setsubtype F disc

| F glue | | F register | |
|--------------------|------------|-------------------------|------------|
| F glyph | | D registered | |
| F hlist | | D values | |
| F list | | F processor | |
| F next | | points | function |
| F node | | pool | table |
| F vlist | | F baselineskip | |
| F whatsit | | F cleanup | |
| T typesetters | | F directliteral | |
| F tohbox | | F glyph | |
| F tohpack | | F hlist | |
| F tonodes | | F latelua | |
| F tovbox | | F lineskip | |
| F tovpack | | F literal | |
| F unprotect_glyph | | F originliteral | |
| F unprotect_glyphs | | F register | |
| F unprotectglyph | | F restore | |
| F unprotectglyphs | | F rule | |
| F unset_attribute | | F save | |
| F unsetattribute | | F savepos | |
| F unsetattributes | | F setmatrix | |
| F untracedslide | | F stock | |
| F usedlist | | F usage | |
| F uses_font | | F usernode | |
| F usesfont | | F vlist | |
| F verticalbreak | | prepend | function |
| F vianodes | | print | function |
| F vianuts | | processors | table |
| F vpack | | F contribute_filter | |
| F write | | F glyph_run | |
| F xscaled | | F post_linebreak_filter | |
| F yscaled | | F pre_linebreak_filter | |
| packlist | function | F trace_glyph_run_a | |
| parcodes | data table | F trace_glyph_run_b | |
| penaltycodes | data table | properties | table |
| plugindata | table | T data | |
| F finalizer | | pts | function |
| F initializer | | radicalcodes | data table |
| S name | | references | table |
| T namespace | | N attribute | |
| N attribute | | T done | |
| D data | | F handler | |
| F enable | | T stack | |
| F handler | | rehpack | function |
| | | | |

| remove | function | somespace | function |
|-------------------|------------|----------------------|------------|
| repackhlist | function | specialskipcodes | table |
| replace | function | splitbox | function |
| report | function | startofpar | function |
| rightmarginwidth | function | stripdiscretionaries | function |
| rulecodes | data table | stripping | table |
| rules | table | T glyphs | |
| D data | | F set | |
| F define | | subtypes | data table |
| F enable | | tail | function |
| F handler | | takeattr | function |
| F process | | takebox | function |
| F userrule | | tasks | table |
| serialize | function | F actions | |
| serializebox | function | F appendaction | |
| set_attribute | function | F disableaction | |
| setattr | function | F disablegroup | |
| setattribute | function | F enableaction | |
| setboth | function | F enablegroup | |
| setbox | function | F freeze | |
| setboxtonaturalwd | function | F freezegroup | |
| setchar | function | F new | |
| setfield | function | F prependaction | |
| setfont | function | F removeaction | |
| setleader | function | F replaceaction | |
| setlink | function | F restart | |
| setlist | function | F setaction | |
| setnext | function | F showactions | |
| setprev | function | F table | |
| setproperty | function | tobasepoints | function |
| shifts | table | tocentimeters | function |
| D data | | tociceros | function |
| F define | | todidots | function |
| F enable | | todimen | function |
| F handler | | toinches | function |
| showboxes | function | tomillimeters | function |
| showlist | function | tonode | function |
| showsimplelist | function | tonodes | function |
| skipcodes | data table | tonut | function |
| snapshots | table | topicas | function |
| F getsamples | | topoints | function |
| F resetsamples | | toscaledpoints | function |
| F takesample | | tosequence | function |
| somepenalty | function | tostring | function |
| | | | |

| totable | function | T transparencies | |
|-------------------|----------|------------------|------------|
| totree | function | F reset | |
| toutf | function | F set | |
| tracers | table | F setlist | |
| T colors | cabic | traverse | function |
| F reset | | traverse id | function |
| F set | | traverseid | function |
| F setlist | | typesetters | table |
| F directions | | F hbox | 10010 |
| F fontchar | | F hpack | |
| T frequencies | | F tohbox | |
| F register | | F tohpack | |
| T pool | | F tonodes | |
| T nodes | | F toybox | |
| F rule | | F tovpack | |
| T nuts | | F vpack | |
| F rule | | unset_attribute | function |
| F resetproperties | | unsetattribute | function |
| F rule | | usedlist | function |
| F setlist | | vianodes | function |
| F setproperties | | vianuts | function |
| F start | | visualizebox | function |
| T steppers | | visualizers | table |
| F check | | F attribute | |
| F codes | | T attributes | |
| F features | | F box | |
| F font | | F handler | |
| F glyphs | | F markfonts | |
| F message | | F register | |
| F messages | | F setfont | |
| F nofsteps | | F setlayer | |
| F register | | F setruledglyph | |
| F reset | | F setvisual | |
| F start | | vpack | function |
| F stop | | whatsitcodes | data table |
| | | | |

F stop

write

function

number (context)

| | function | to16dot16 | function |
|----------------|------------|----------------|----------|
| basepoints | function | tobasepoints | function |
| bytetodecimal | function | tobitstring | function |
| compactfloat | function | tocentimeters | function |
| decimaltobyte | function | tociceros | function |
| dimenfactors | data table | tocontext | function |
| formatted | function | todidots | function |
| formattedfloat | function | todimen | function |
| idiv | function | toevenhex | function |
| maxdimen | number | toinches | function |
| nopts | function | tomillimeters | function |
| nubasepoints | function | tonumberf | function |
| nupoints | function | tonumberg | function |
| percent | function | topicas | function |
| points | function | topoints | function |
| pts | function | toscaled | function |
| signed | function | toscaledpoints | function |
| sparseexponent | function | valid | function |
| splitdimen | function | | |
| | | | |

objects (context)

| data | table | page | function |
|------------|----------|-----------|----------|
| dimensions | function | reference | function |
| found | function | register | function |
| n | number | restore | function |

optional (context)

| curl | table | F framecompress | |
|------------------|-------|------------------|----------|
| F escape | | F framedecompres | S |
| F fetch | | F initialize | |
| F getversion | | lzo | table |
| F initialize | | F compress | |
| F unescape | | F decompresssize | <u> </u> |
| foreign | table | F initialize | |
| F abivalues | | mujs | table |
| F getbuffer | | F dofile | |
| F initialize | | F execute | |
| F load | | F initialize | |
| F newbuffer | | F reset | |
| F totable | | F setclosefile | |
| F types | | F setconsole | |
| ghostscript | table | F setfindfile | |
| F execute | | F setopenfile | |
| F initialize | | F setreadfile | |
| graphicsmagick | table | F setseekfile | |
| F execute | | mysql | table |
| F initialize | | F close | |
| hb | table | F execute | |
| F getshapers | | F getmessage | |
| F getversion | | F initialize | |
| F initialize | | F open | |
| F loadfont | | postgress | table |
| F shapestring | | F close | |
| kpse | table | F execute | |
| F expand_braces | | F getmessage | |
| F expand_path | | F initialize | |
| F expand_var | | F open | |
| F find_file | | sqlite | table |
| F find_files | | F close | |
| F get_file_type | S | F execute | |
| F initialize | | F getmessage | |
| F readable_file | | F initialize | |
| F set_program_n | ame | F open | |
| F var_value | | zint | table |
| loaded | table | F execute | |
| lz4 | table | F initialize | |
| F compress | | zstd | table |
| F decompresssize | е | F compress | |

F initialize

os (basic lua)

| actony | function | ************** | overloaded function |
|--------------|---------------------|----------------|---------------------|
| getenv | | rename | 0.0 |
| setenv | function | resolvers | table |
| binsuffix | string | F bits | |
| binsuffixes | table | resultof | function |
| clock | function | runtime | function |
| converttime | function | selfarg | table |
| date | overloaded function | selfbase | string |
| difftime | function | selfbin | string |
| enableansi | function | selfcore | string |
| env | data table | selfdir | string |
| execute | overloaded function | selfname | string |
| exit | overloaded function | selfpath | string |
| fulltime | function | setenv | overloaded function |
| getcodepage | function | setexitcode | function |
| getenv | overloaded function | setlocale | overloaded function |
| gettimeofday | function | sleep | function |
| isleapyear | function | time | function |
| launch | function | timezone | function |
| libsuffix | string | tmpname | function |
| localtime | function | today | function |
| name | string | type | string |
| newline | string | uname | function |
| nofdays | function | uuid | function |
| now | function | validdate | function |
| pipeto | function | weekday | function |
| platform | string | where | function |
| remove | overloaded function | which | function |

package (basic lua)

| config | string | loadlib | function |
|---------------|----------|-------------|----------|
| cpath | string | luapaths | function |
| extralibpath | function | path | string |
| extralibpaths | function | poplibpath | function |
| extraluapath | function | popluapath | function |
| extraluapaths | function | preload | table |
| helpers | table | pushlibpath | function |
| libpaths | function | pushluapath | function |
| loaded | table | searchers | table |
| loaders | table | searchpath | function |
| | | | |

pagebuilders (context)

F setarea

| <pre>columnsets table</pre> | F sethsize |
|-----------------------------|-------------------------|
| F add | F sethspan |
| F block | F setlines |
| F check | F setproperties |
| F currentcolumn | F setstart |
| F define | F setvsize |
| F finishflush | injections table |
| F flushareas | F flushafter |
| F flushcolumn | F flushbefore |
| F flushrest | F save |
| F goto | mixedcolumns table |
| F noto | F cleanup |
| F prepareflush | F finalize |
| F put | F getlist |
| F registerarea | F getrest |
| F reset | F getsplit |
| | |

F setsplit

pdf (basic tex)

immediateobj function

pdfe (extra tex)

| | 6 | | |
|-------------------|------------|-----------------|------------|
| arraytotable | function | getnumber | function |
| close | function | getpage | function |
| closestream | function | getpages | function |
| dictionarytotable | function | getsize | function |
| encryptioncodes | data table | getstatus | function |
| getarray | function | getstream | function |
| getboolean | function | getstring | function |
| getbox | function | gettrailer | function |
| getcatalog | function | getversion | function |
| getdictionary | function | new | function |
| getfromarray | function | objectcodes | data table |
| getfromdictionary | function | open | function |
| getfromreference | function | openfile | function |
| getfromstream | function | openstream | function |
| getinfo | function | pagestotable | function |
| getinteger | function | readfromstream | function |
| getmemoryusage | function | readwholestream | function |
| getname | function | type | function |
| getnofobjects | function | unencrypt | function |
| getnofpages | function | | |

physics (context)

units table

F registerunit

D tables

previous 121 next

pngdecode (extra tex)

| applyfilter | function | splitmask | function |
|-------------|----------|-----------|----------|
| expand | function | tocmyk | function |
| interlace | function | tomask | function |

publications (context)

| addtexentry | function | converttoxml | function |
|-------------------|------------|----------------------|----------|
| analyze | function | currentspecification | table |
| anywhere | function | S author | |
| authorcache | data table | T categories | |
| authorcollapsers | data table | T article | |
| authorhashers | table | S category | |
| F invertedshort | | T extra | |
| F normal | | T fields | |
| F normalinverted | | S author | |
| F normalshort | | S editor | |
| F sequential | | S journal | |
| F sequentialshort | | S keywords | |
| F short | | S note | |
| authormap | data table | S number | |
| authortoregister | function | S pages | |
| casters | table | S title | |
| F author | | S volume | |
| F keyword | | S year | |
| F pagenumber | | T optional | |
| F range | | T required | |
| checkeddataset | function | T sets | |
| citevariants | table | T author | |
| F author | | T virtual | |
| F authornum | | T book | |
| F authoryear | | S category | |
| F authoryears | | T extra | |
| F category | | T fields | |
| F default | | S address | |
| F entry | | S author | |
| F index | | S edition | |
| F keywords | | S editor | |
| F num | | S keywords | |
| F page | | S note | |
| F short | | S number | |
| F tag | | S publisher | |
| F textnum | | S subtitle | |
| F year | d-4- 4-61- | S title | |
| collected | data table | S volume | |
| components | table | S year | |
| F author | function | T optional | |
| concatstate | function | T required | |

| T sets | S pages | |
|----------------|-----------------|------------|
| T author | S volume | |
| T editionset | S version | |
| T virtual | D virtual | |
| T demo-a | T virtualfields | |
| S category | B authornum | |
| T extra | B authoryear | |
| T fields | B authoryears | |
| S author | B num | |
| S institution | B suffix | |
| S organization | datasets | table |
| S subtitle | detailed | table |
| S title | endnotes_to_btx | function |
| S year | enhancer | table |
| T optional | S arguments | |
| T required | T askip | |
| T sets | B dirty | |
| T author | T gskip | |
| T virtual | T kind | |
| T demo-b | T list | |
| S category | T system | |
| T extra | T order | |
| T fields | N steps | |
| S author | enhancers | table |
| S institution | F details | |
| S organization | F order | |
| S subtitle | F suffixes | |
| S title | finder | function |
| S year | firstofrange | function |
| T optional | found | function |
| T required | get | function |
| T sets | getcasted | function |
| T authors | getdetail | function |
| T virtual | getdirect | function |
| S comment | getfaster | function |
| S copyright | getfield | function |
| T fields | getfuzzy | function |
| S name | getindex | function |
| T types | inspectors | data table |
| S author | journals | table |
| S editor | F abbreviated | |
| S keywords | F add | |
| S number | F expanded | |
| S page | F load | |
| | | |

| F save | | F lua | |
|--------------------|----------|---------------------|----------|
| lastofrange | function | F refman | |
| lists | table | F registercleaner | |
| F collectentries | | F xml | |
| F combiinlist | | loadreplacementfile | function |
| F fetchentries | | new | function |
| F filterall | | okay | function |
| F flushcombi | | oneorrange | function |
| F flushentry | | parenttag | function |
| F flushtag | | permitted | function |
| T methods | | prerollcmdstring | function |
| F dataset | | refman_to_btx | function |
| F force | | resolvedname | function |
| F global | | save | function |
| F local | | savers | table |
| F nofregistered | | F bib | |
| F prepareentries | | F lua | |
| F register | | F xml | |
| F sameasprevious | | search | function |
| T sorters | | setcategory | function |
| F cite | | setspecification | function |
| F dataset | | singularorplural | function |
| F default | | sortedentries | function |
| F index | | sortmethods | table |
| F list | | T authoryear | |
| F reference | | T sequence | |
| F short | | specifications | table |
| F used | | T default | |
| F uservariable | | S author | |
| listvariants | table | S comment | |
| F default | | S copyright | |
| F index | | S name | |
| F num | | S version | |
| F short | | D virtual | |
| F tag | | splitauthor | function |
| load | function | splitoneauthor | function |
| loadbibdata | function | statistics | table |
| loaddefinitionfile | function | N nofbytes | |
| loaders | table | N nofdatasets | |
| F bbl | | N nofdefinitions | |
| F bib | | N nofshortcuts | |
| F buffer | | tables | table |
| F endnote | | D implicits | |
| F json | | D origins | |
| | | | |

D privates
D sets
F showtables
D specials
F showvariants
Typesetters
Typesetters
Types
F author
F string
Types
Types
Types
F string
Types

tagsfunctionusedatasetfunctiontracerstableusedentriesfunctionF showdatasetauthorswriterstableF showdatasetcompletenessF author

F showdatasetcompleteness F author
F showdatasetfields F keyword
F showentry F pagenumber
F showfields F range
F showhashedauthors

regimes (context)

| backmapping | data table | mapping | data table |
|-------------|------------|-----------|------------|
| cleanup | function | pop | function |
| disable | function | process | function |
| enable | function | push | function |
| fromregime | function | toregime | function |
| list | function | translate | function |

resolvers (context)

| allprefixes | function | findtexfile | function |
|--|------------|-------------------------|------------|
| appendhash | function | findwildcardfile | function |
| automount | function | findwildcardfiles | function |
| booleanvariable | function | formatofsuffix | function |
| cacheversion | string | formatofvariable | function |
| checkedvariable | function | formats | data table |
| cleanedpathlist | function | foundintree | function |
| cleanpath | function | foundintrees | function |
| cleanpathlist | function | generators | data table |
| concatinators | data table | get from content | function |
| configbanner | string | getenv | function |
| configurationfiles | function | getextrapaths | function |
| dangerous | data table | getfilehashes | function |
| datastate | function | gethashes | function |
| defaultsuffixes | table | getownpath | function |
| dirstatus | function | getreadfilename | function |
| dowithfilesandreport | function | hashers | data table |
| dowithfilesintree | function | homedir | string |
| dowithpath | function | initialized | function |
| dowithvariable | function | installinputfilehandler | function |
| executers | table | installinputlinehandler | function |
| expandbraces | function | jobpath | function |
| expandedpathfromlist | function | jobs | table |
| expandedpathlist | function | F currentcomponent | |
| ${\it expanded path list from variable}$ | function | F currentenvironment | |
| expandpath | function | F currentproduct | |
| expandpathfromvariable | function | F currentproject | |
| expansion | function | F justacomponent | |
| extendtexmfvariable | function | D processors | |
| filtered_from_content | function | F productcomponent | |
| find_file | function | F usefile | |
| find_files | function | joinpath | function |
| findbinfile | function | knownvariables | function |
| findctxfile | function | libraries | table |
| finders | data table | F optionalloaded | |
| findfile | function | F validoptional | |
| findfiles | function | load | function |
| findgivenfile | function | loadbinfile | function |
| findgivenfiles | function | loaders | data table |
| findlib | function | loadlualib | function |
| findpath | function | loadtexfile | function |

loadtime function resetresolve function locateformat function resol ve function locators data table data table savers luacnffallback strina scandata function luacnfname string scanfiles function luacnfspec string schemes table luacnfstate strina T cleaners table macros F md5 F convertfile F none F decodecomment F strip F enablecomment F cleanname F encodecomment F fetchstring F preprocessed F fetchtable F install F processmk setdynamic function F processmklx setenv function F processmkvi function F version showpath maxreadlevel number simplescanfiles function methodhandler function splitconfigurationpath function openbinfile function splitexpansions function data table splitmethod openers function openfile function splitpath function function opentexfile stackpath function ownpath string starttiming function stoptimina function popextrapath function popinputname function suffixes data table function suffixmap data table poppath suffixofformat prefixes data table function prependhash function texdatablob function pushextrapath function function toppath pushinputname function unexpandedpath function pushpath function unexpandedpathlist function registerextrapath function unresolve function registerfile function updaterelations function registerfilehash function updatescript function registerintrees function uselibrary function registermethod function usertypes data table registerzipfile function usezipfile function validatedpath relations data table function function variable function renew renewcache function variableofformat function function variableofformatorsuffix function repath

wildcardpattern

function

function

function

reset

resetextrapaths

sandbox (context)

| disablelibraries | function | possiblepath | function |
|------------------|----------|-------------------|----------|
| disablerunners | function | redefine | function |
| enable | function | register | function |
| filehandlerone | function | registerbinary | function |
| filehandlertwo | function | registerlibrary | function |
| finalizer | function | registerroot | function |
| getrunner | function | registerrunner | function |
| initializer | function | report | function |
| iohandler | function | setfilenamelogger | function |
| logcalls | function | setlogger | function |
| logfiles | function | setreporter | function |
| original | function | settrace | function |
| overload | function | validfilename | function |

scripts (context)

autofontfeature table F disable F enable F handler colors data table decomposehangul function defaults table N inter_char_half_shrink factor N inter char half stretch factor N inter char hangul penalty N inter_char_quarter_shrink_factor N inter_char_quarter_stretch_factor N inter char shrink factor N inter char stretch factor N inter_word_stretch_factor getdata function getinjector function getsplitter function

function

getstatus

| handlers | data table |
|-------------------|------------|
| helpers | data table |
| injectors | data table |
| inserters | table |
| F nobreakspace_af | ter |
| F nobreakspace_be | fore |
| F space_after | |
| F space_before | |
| F zerowidthspace_ | after |
| F zerowidthspace_ | before |
| installdataset | function |
| installmethod | function |
| numbertodataset | data table |
| numbertohandler | data table |
| reset | function |
| set | function |
| setstatus | function |

splitters

data table

set (context)

contains function
create function
tolist function

tonumber function
totable function

sha2 (extra lua)

| HASH256 | function | hash256 | function |
|-----------|----------|---------|----------|
| HASH384 | function | hash384 | function |
| HASH512 | function | hash512 | function |
| HEX256 | function | hex256 | function |
| HEX384 | function | hex384 | function |
| HEX512 | function | hex512 | function |
| digest256 | function | sum256 | function |
| digest384 | function | sum384 | function |
| digest512 | function | sum512 | function |

sio (extra lua)

| read2dot14 | function | readfixed2 | function |
|-------------------|----------|------------------|----------|
| readbytes | function | readfixed4 | function |
| readbytetable | function | readinteger1 | function |
| readcardinal1 | function | readinteger1le | function |
| readcardinal1le | function | readinteger2 | function |
| readcardinal2 | function | readinteger2le | function |
| readcardinal2le | function | readinteger3 | function |
| readcardinal3 | function | readinteger3le | function |
| readcardinal3le | function | readinteger4 | function |
| readcardinal4 | function | readinteger4le | function |
| readcardinal4le | function | readintegertable | function |
| readcardinaltable | function | | |

socket (extra lua)

S content-location

BLOCKSIZE number S content-md5 DATAGRAMSIZE number S content-range SETSIZE number S content-transfer-encoding **SOCKETINVALID** number S content-type bind function S cookie function choose S date connect function S diagnostic-code function connect4 S dsn-gateway connect6 function S etag dns table S expect F getaddrinfo S expires F gethostname S final-log-id F getnameinfo S final-recipient F tohostname S from F toip S host aettime function S if-match headers table S if-modified-since T canonic S if-none-match S if-range S accept S accept-charset S if-unmodified-since S accept-encoding S in-reply-to S accept-language S keywords S last-attempt-date S accept-ranges S action S last-modified S age S location S allow S max-forwards S alternate-recipient S message-id S arrival-date S mime-version S authorization S original-envelope-id S bcc S original-recipient S cache-control S pragma S cc S proxy-authenticate S comments S proxy-authorization S connection S range S content-description S received S content-disposition S received-from-mta S content-encoding S references S content-id S referer S remote-mta S content-language S content-length S reply-to

S reporting-mta

| S rese | ent-bcc | protect | function |
|---------|--------------------|----------------|----------|
| S rese | ent-cc | report | function |
| S rese | ent-date | select | function |
| S rese | ent-from | sink | function |
| S rese | ent-message-id | sinkt | table |
| S rese | ent-reply-to | F close-when-d | lone |
| S rese | ent-sender | F default | |
| S rese | ent-to | F http-chunked | I |
| S reti | ry-after | F keep-open | |
| S retu | ırn-path | skip | function |
| S send | der | sleep | function |
| S serv | ver | source | function |
| S smtp | o-remote-recipient | sourcet | table |
| S stat | tus | F by-length | |
| S subj | ject | F default | |
| S te | | F http-chunked | I |
| S to | | F until-closed | I |
| S trai | iler | tcp | function |
| S tran | nsfer-encoding | tcp4 | function |
| S upgi | rade | tcp6 | function |
| S usei | r-agent | tp | table |
| S vary | <i>y</i> | N TIMEOUT | |
| S via | | F connect | |
| S warr | ning | try | function |
| S will | l-retry-until | udp | function |
| S www- | -authenticate | udp4 | function |
| S x-ma | ailer | udp6 | function |
| F lower | | url | table |
| F norma | lize | F absolute | |
| http | table | F build | |
| N TIMEO | UT | F build_path | |
| S USERA | GENT | F escape | |
| F gener | icform | F parse | |
| F open | | F parse_path | |
| F reque | st | F unescape | |

newtry function

sorters (context)

| basicsorter | function | D | |
|-------------------|-----------|-----------------|------------|
| pasicsol rei | TullCtIon | B pm | |
| comparers | table | B uc | |
| F basic | | B zc | |
| constants | table | B zm | |
| S defaultdigits | | definitions | data table |
| S defaultlanguage | | firstofsplit | function |
| S defaultmethod | | packch | function |
| N digitsmaximum | | packuc | function |
| N digitsoffset | | replacementlist | function |
| N ignoredoffset | | setlanguage | function |
| N replacementoffs | et | sort | function |
| T validmethods | | splitters | table |
| B ch | | F utf | |
| B mc | | strip | function |
| B mm | | tracers | data table |
| В рс | | update | function |

sparse (context)

| concat | function | range | function |
|--------|----------|----------|----------|
| get | function | restore | function |
| max | function | set | function |
| min | function | traverse | function |
| new | function | wipe | function |

statistics (context)

| benchmarktimer | function | resettiming | function |
|----------------|----------|---------------|----------|
| checkfmtstatus | function | runtime | function |
| currenttime | function | savefmtstatus | function |
| elapsed | function | show | function |
| elapsedindeed | function | showmemory | function |
| elapsedseconds | function | showusage | function |
| elapsedtime | function | starttiming | function |
| enable | boolean | stoptiming | function |
| formatruntime | function | threshold | number |
| hastiming | function | timed | function |
| memused | function | tracefunction | function |
| register | function | | |

status (basic tex)

| getbufferstate | function | getmarkstate | function |
|-----------------------|----------|-------------------|----------|
| getcallbackstate | function | getneststate | function |
| getconstants | function | getnodestate | function |
| geterrorlinestate | function | getparameterstate | function |
| geterrorstate | function | getpoolstate | function |
| getexpandstate | function | getreadstate | function |
| getextrastate | function | getsavestate | function |
| getfilestate | function | getsparsestate | function |
| getfontstate | function | getstringstate | function |
| gethalferrorlinestate | function | gettexstate | function |
| gethashstate | function | gettokenstate | function |
| getinputstate | function | getwarningstate | function |
| getinsertstate | function | iocodes | table |
| getlanguagestate | function | list | function |
| getlookupstate | function | resetmessages | function |
| getluastate | function | | |

storage (context)

| allocate | function | |
|------------|----------|--|
| data | table | |
| mark | function | |
| marked | function | |
| max | number | |
| min | number | |
| nofmodules | number | |

| noftables | number | |
|-----------------|------------|--|
| register | function | |
| shared | data table | |
| storedfunctions | data table | |
| strip | boolean | |
| tofmodules | number | |
| toftables | number | |

streams (context)

| collect | function | push | function |
|------------|----------|-------------|----------|
| disable | function | start | function |
| enable | function | stop | function |
| flush | function | synchronize | function |
| initialize | function | | |

string (basic lua)

| autodouble | function | nspaces | table |
|-------------------|----------|-------------------|----------|
| autosingle | function | optionalquoted | function |
| booleanstring | function | pack | function |
| byte | function | packsize | function |
| bytepairs | function | quote | function |
| bytes | function | quoted | function |
| bytetable | function | rep | function |
| char | function | replacenewlines | function |
| characterpairs | function | reverse | function |
| characters | function | split | function |
| checkedsplit | function | splitlines | function |
| collapsespaces | function | splitup | function |
| containsws | function | strip | function |
| count | function | sub | function |
| dawson | function | tformat | function |
| dump | function | toHEX | function |
| erf | function | toboolean | function |
| erfc | function | tobytes | function |
| erfcx | function | tocontext | function |
| erfi | function | todec | function |
| escapedpattern | function | todimen | function |
| escapedquotes | function | tohex | function |
| explode | function | tonodes | function |
| f6 | function | topattern | function |
| find | function | totable | function |
| format | function | tounicode16 | function |
| formatter | function | toutf | function |
| formatters | function | toutf32 | function |
| fullstrip | function | toutf8 | function |
| gmatch | function | tracedchar | function |
| gsub | function | tracedchars | table |
| is_boolean | function | unpack | function |
| is_empty | function | unquote | function |
| itself | function | unquoted | function |
| len | function | upper | function |
| limit | function | utfcharacter | function |
| linetable | function | utfcharacters | function |
| longtostring - | function | utfcharactertable | function |
| lower | function | utflength | function |
| match | function | utfpadd | function |
| nospaces | function | utfpadding | function |

| utfvalue | function | valid | function |
|---------------|----------|------------|----------|
| utfvalues | function | voigt | function |
| utfvaluetable | function | voigt_hwhm | function |

structures (context)

| atlocation | function | F next | |
|------------------|----------|----------------------|-------|
| blocks | table | F prev | |
| D collected | | F previous | |
| F define | | F raw | |
| F print | | F record | |
| F save | | F reset | |
| F select | | F restart | |
| F setstate | | F restore | |
| D states | | F save | |
| D tobesaved | | F set | |
| F uservariable | | F setlevel | |
| bookmarks | table | F setoffset | |
| T extras | | F setown | |
| F get | | F setstate | |
| F mergesections | | F setvalue | |
| F register | | T specials | |
| F reset | | F userpage | |
| F tosections | | F subs | |
| F finalize | | D tobesaved | |
| F flatten | | F value | |
| F installhandler | | F way | _ |
| F merge | | currentsectionnumber | |
| S method | | descriptions | table |
| F overload | | documents | table |
| F place | | D data | |
| F register | | F initialize | |
| F setopened | | F preset | |
| F setup | | F reset | |
| counters | table | floats | table |
| F add | | formulas | table |
| F analyze | | helpers | table |
| F check | | F analyze | |
| D collected | | F formulanumber | |
| F compact | | F merged | |
| F converted | | F page | |
| F currentvalue | | F pageofinternal | |
| D data | | F prefix | |
| F define | | F prefixlastpage | |
| F first | | F prefixpage | |
| F get | | F simplify | |
| F last | | F title | |

| F touserdata | | F reordered | |
|------------------|-------|----------------------------|--|
| inserts | table | T result | |
| D data | | F savedlistnumber | |
| F define | | F savedlistprefixednumber | |
| F getdata | | F savedlisttitle | |
| F getlocation | | D sectionblocks | |
| F getname | | F sectionnumber | |
| F getnumber | | F size | |
| F setlocation | | F title | |
| F setup | | D tobesaved | |
| D stored | | F userdata | |
| itemgroups | table | F uservalue | |
| lists | table | marks table | |
| F addto | | D data | |
| F analyze | | F define | |
| B autoreorder | | F exists | |
| D cached | | F fetch | |
| D collected | | F fetchallmarks | |
| F discard | | F fetched | |
| F enhance | | F fetchonemark | |
| T enhancers | | F fetchtwomarks | |
| F filter | | F get | |
| F formulanumber | | F number | |
| F getresult | | F relate | |
| F groupindex | | F reset | |
| F hasnumberdata | | F set | |
| F haspagedata | | F show | |
| F hastitledata | | F synchronize | |
| F iscached | | F title | |
| D kinds | | T tracers | |
| F label | | F showtable | |
| F location | | notes table | |
| D names | | F check_spacing | |
| F number | | F checkpagechange | |
| D ordered | | F define | |
| F page | | F doifonsamepageasprevious | |
| F popnesting | | F get | |
| F prefix | | F getdeltapage | |
| F prefixednumber | | F getinternal | |
| F prefixedpage | | F getn | |
| F process | | F getstate | |
| D pushed | | F hascontent | |
| F pushnesting | | F internal | |
| F realpage | | F internalid | |

| F listindex | | F expandcurrent |
|---------------------|-------|----------------------------------|
| D numbers | | F export |
| F ordered | | T files |
| F postpone | | T data |
| F resetpostponed | | F define |
| F restore | | F found |
| F save | | F get |
| F setstate | | F filter |
| D states | | F filterdefault |
| F store | | D filters |
| pages | table | D flaginternals |
| F allmarked | | F from |
| F analyze | | D functions |
| D collected | | F get |
| F fraction | | F getcurrentmetadata |
| F has_changed | | F getcurrentprefixspec |
| F in_body | | F getinnermethod |
| F is_odd | | F getinternalcachedlistreference |
| F mark | | F getinternallistreference |
| F marked | | F getinternalreference |
| F markedlist | | F getoutermethod |
| N nofpages | | D handlers |
| F number | | F identify |
| F on_right | | F import |
| F save | | F inject |
| D tobesaved | | F injectcurrentset |
| F toranges | | S innermethod |
| references | table | D internals |
| F analyze | | F load |
| F checkedfile | | F loadpresets |
| F checkedfileorurl | | F mark |
| F checkedprogram | | S outermethod |
| F checkedrealpage | | D pages |
| F checkedurl | | U prefixsplitter |
| D collected | | D productdata |
| U componentsplitter | | T programs |
| F currentmetadata | | T data |
| F currentorder | | F define |
| D currentset | | F get |
| F define | | F realpageofpage |
| D defined | | U referencesplitter |
| D derived | | D referred |
| F enhance | | F referredpage |
| D executers | | F registerfinalizer |

| F re | egisterinitializer | | D | collected | |
|--------|-----------------------|-------------|------|---------------------|-------|
| F re | egisterpage | | F | compare | |
| F re | eset | | F | define | |
| D ru | inners | | F | enhance | |
| F se | et | | F | extend | |
| F se | etandgetattribute | | F | filter | |
| F se | etcomponent | | F | filtercollected | |
| F se | etinternalreference | | F | finalize | |
| F se | etlinkmethod | | F | findinternal | |
| F se | etnextinternal | | F | flush | |
| F se | etnextorder | | F | get | |
| F se | etreferencerealpage | | F | prepare | |
| D sp | pecials | | F | process | |
| F sp | olitcomponent | | F | setmethod | |
| F sp | olitprefix | | F | sort | |
| F sp | olitreference | | F | store | |
| F sy | nchronizepage | | D | tobesaved | |
| T te | estrunners | | F | unique | |
| F | inner | | F | userdata | |
| F | special | | sect | ions | table |
| F : | special operation | | F | autodepth | |
| F | special operation wit | h arguments | F | cct | |
| T te | estspecials | | D | collected | |
| F | deltapage | | F | current | |
| F | i | | F | currentblock | |
| F | internal | | F | currentid | |
| F | page | | F | currentlevel | |
| F | realpage | | F | currentsectionindex | |
| F | section | | F | depthnumber | |
| F | userpage | | F | finddata | |
| D to | bereferred | | F | findnumber | |
| D to | besaved | | F | fullnumber | |
| Dtr | racedpages | | F | getcurrentlevel | |
| Tur | -ls | | F | getlevel | |
| Т | data | | F | getnumber | |
| F | define | | F | internalreference | |
| F | found | | D | levelmap | |
| F | get | | D | levels | |
| F | untex | | F | matchingtilldepth | |
| D us | sedinternals | | F | numberatdepth | |
| D us | sedviews | | F | numbers | |
| F va | | | | popblock | |
| regist | ers | table | F | prefixedconverted | |
| F an | nalyze | | F | pushblock | |
| | | | | | |

| E rogistor | | E register | |
|-----------------------------------|-------|--------------------------------------|-------|
| F register | | F register | |
| D registered F reportstructure | | F registershown F registerused | |
| F save | | F resetshown | |
| | | F resetused | |
| T sectionblockdata | | r resetused F sort | |
| T bodypart | | | |
| S bookmark | | F synonym | |
| F set F setblock | | D tobesaved | table |
| F setchecker | | tags T backend | table |
| | | T checks | |
| F setentry F setinitialblock | | | |
| F setlevel | | F marginanchor | |
| | | F margintext | |
| F setnumber | | F math F mrow | |
| F showstructure | | | |
| F structuredata F title | | F mtable T destinationhash | |
| D tobesaved | | T extras | |
| F typesetnumber | | F adddestination | |
| | | F addimplicit | |
| F userdata | | • | |
| B verbose sets | table | F addinternal F addreference | |
| | table | | |
| F define | | F combination F delimitedsymbol | |
| F get F getall | | , | |
| D setlist | | F description F descriptionsymbol | |
| specials | table | F document | |
| D collected | tabte | F float | |
| F retrieve | | F formulacontent | |
| F store | | F image | |
| D tobesaved | | F item | |
| synonyms | table | F itemgroup | |
| F analyzed | cabec | Flink | |
| D collected | | F listitem | |
| F compare | | F mi | |
| F define | | F msub | |
| F filter | | F msup | |
| F finalize | | F paragraph | |
| F flush | | F publication | |
| F isshown | | F reference | |
| F isused | | F registerlocation | |
| F meaning | | F registerpages | |
| F prepare | | F registerseparator | |
| F process | | F section | |
| 1 100033 | | i section | |

F sorting F registerextradata F subsentencesymbol F registermetadata F synonym F restart F tablecell F setaspect F tabulate F setattributehash F tabulatecell F setcombination T finalizers F setconstruct F descriptions F setfigure T fixes F setfloat F linenumher F setformulacontent T listdata F sethighlight T referencehash F setitem F setattribute F setitemgroup T usedimages F setlist T image F setnotation T usedstyles F setnotationsymbol T construct F setparagraph T highlight F setproperty F setpublication F current F elementtag F setregister F finishexport F setsorting F getextradata F setsynonym F getid F settablecell F getmetadata F settabulatecell F gettablecell F settagdelimitedsymbol F gettabulatecell F settagsubsentencesymbol F handler F initializeexport

D labels

F lastinchain

F locatedtag

U splitter

D properties

T patterns

F last

F setupexport F setuserproperties D specifications

F start F stop F strip D taglist T usewithcare

table (basic lua)

| allkeys | function | pack | function |
|-----------------|----------|----------------------|----------|
| append | function | prepend | function |
| are_equal | function | print | function |
| collapsed | function | remove | function |
| collapsedhash | function | reverse | function |
| compact | function | reversed | function |
| concat | function | save | function |
| contains | function | sequenced | function |
| сору | function | serialize | function |
| count | function | setmetatablecall | function |
| derive | function | setmetatableindex | function |
| deserialize | function | setmetatableindices | function |
| drop | function | setmetatablekey | function |
| fastcopy | function | setmetatablenewindex | function |
| fastserialize | function | sort | function |
| filtered | function | sorted | function |
| flattened | function | sortedhash | function |
| fromhash | function | sortedhashkeys | function |
| getmetatablekey | function | sortedhashonly | function |
| getn | function | sortedindexonly | function |
| has_one_entry | function | sortedkeys | function |
| hashed | function | sortedpairs | function |
| identical | function | sparse | function |
| imerge | function | strip | function |
| imerged | function | sub | function |
| insert | function | swapped | function |
| is_empty | function | tocontext | function |
| is_simple_table | function | tocsv | function |
| keys | function | tofile | function |
| load | function | tohandle | function |
| loweredkeys | function | tohash | function |
| makeweak | function | toxml | function |
| merge | function | twowaymapper | function |
| merged | function | unique | function |
| mirrored | function | unnest | function |
| move | function | unpack | function |
| ordered | function | values | function |
| orderedhash | function | | |

tex (basic tex)

| attribute | table | getboxresourcebox | function |
|----------------------------|----------------------|--------------------------|----------------------|
| badness | function | getboxresourcedimensions | function |
| box | table | getcatcode | function |
| boxresources | table | getcount | function |
| F getbox | | getdelcode | function |
| F getdimensions | | getdelcodes | function |
| F save | | getdelimitermodevalues | function |
| F use | | getdimen | function |
| catcode | table | getdimensionvalue | function |
| chardef | function | getdiscoptionvalues | function |
| codes | table | geterrorvalues | function |
| conditionals | data table | getflagvalues | function |
| constants | data table | getfontoffamily | function |
| count | table | getfrozenparvalues | function |
| cprint | function | getglue | function |
| ctdcatcodes | number | getglyphdata | function |
| ctxcatcodes | number | getglyphoptionvalues | function |
| definefont | function | getglyphscript | function |
| delcode | table | getglyphstate | function |
| dimen | table | getgroupvalues | function |
| dimensiondef | function | gethelptext | function |
| directives | data table | gethyphenationvalues | function |
| discoptioncodes | data table | getinsertcontent | function |
| enableprimitives | function | getinsertdepth | function |
| error | function | getinsertdistance | function |
| expandasvalue | function | getinsertheight | function |
| experiments | data table | getinsertlimit | function |
| extraprimitives | function | getinsertmultiplier | function |
| fatalerror | function | getinsertwidth | function |
| flagcodes | data table | getintegervalue | function |
| fontidentifier fontname | function function | getinteraction | function |
| | function | getiovalues | function |
| forcehmode | function | getlargestusedmark | function function |
| forcesynctextine | function | getlccode getlinedir | function |
| forcesynctextag fprint | function | • | function |
| frozenparcodes | data table | getlist getlocallevel | function |
| get | function | getmark | function |
| get getattribute | function | getmark | function |
| getbox | function | getmathcode | function |
| getbox | function | getmathcodes | function |
| Ae choyati | TUITCLIUIT | germariicoues | Tunction |

| getmathdir | function | ismuskip | overloaded function |
|------------------------|-------------------|------------------|---------------------|
| getmathoptionvalues | function | isprintable | function |
| getmathparametervalues | function | isskip | overloaded function |
| getmathstylenamevalues | function | istoken | function |
| getmathstylevalues | function | istoks | function |
| getmathvariantvalues | function | lastnodetype | function |
| getmodevalues | function | lccode | table |
| getmuglue | function | linebreak | function |
| getmuskip | function | lists | table |
| getnest | function | luacatcodes | number |
| getnormalizevalues | function | magicconstants | table |
| getoutputactive | function | N maxdimen | |
| getpacktypevalues | function | N running | |
| getpagestate | function | N trueinch | |
| getparbeginvalues | function | mathchardef | function |
| getparcontextvalues | function | mathcode | table |
| getpardir | function | mathoptioncodes | data table |
| getparmodevalues | function | modelevels | table |
| getprimitiveorigins | function | N horizontal | |
| getregisterindex | function | N math | |
| getrunstatevalues | function | N unset | |
| getsfcode | function | N vertical | |
| getskip | function | modes | data table |
| getsynctexline | function | mprint | function |
| getsynctexmode | function | muglue | table |
| getsynctextag | function | muskip | table |
| gettextdir | function | nest | table |
| gettoks | function | nilcatcodes | number |
| getuccode | function | normalizecodes | data table |
| glue | table | notcatcodes | number |
| glyphoptioncodes | data table | number | function |
| groupcodes | data table | poplocal | function |
| hashtokens | function | primitives | function |
| hyphenationcodes | data table | print | function |
| ifs | data table | prtcatcodes | number |
| inicatcodes | number | pushlocal | function |
| integerdef | function | quitlocal | function |
| isattribute | function | quittoks | function |
| isbox | function | resetparagraph | function |
| iscount | overloaded functi | ion rlncatcodes | number |
| isdefined | function | romannumeral | function |
| isdimen | overloaded functi | ion round | function |
| isglue | function | runlocal | function |
| ismuglue | function | runtoks | function |
| - | | | |

| saveboxresource | function | setskip | function |
|---------------------|---------------------|------------------|------------|
| scale | function | setsynctexline | function |
| scantoks | function | setsynctexmode | function |
| set | function | setsynctextag | function |
| setattribute | function | settextdir | function |
| setbox | function | settoks | function |
| setboxdir | function | setuccode | function |
| setcatcode | function | sfcode | table |
| setcount | function | shiftparshape | function |
| setdelcode | function | shipout | function |
| setdimen | function | showcontext | function |
| setdimensionvalue | function | skip | table |
| setglue | function | sp | function |
| setglyphdata | function | splitbox | function |
| setglyphscript | function | sprint | function |
| setglyphstate | function | systemmodes | data table |
| setinsertcontent | function | takebox | function |
| setinsertdistance | function | texcatcodes | number |
| setinsertlimit | function | toks | table |
| setinsertmultiplier | function | tonumber | function |
| setintegervalue | function | toscaled | function |
| setinteraction | function | tpacatcodes | number |
| setlccode | function | tpbcatcodes | number |
| setlinedir | function | tprint | function |
| setlist | function | trackers | data table |
| setmath | function | triggerbuildpage | function |
| setmathcode | function | txtcatcodes | number |
| setmathdir | function | type | function |
| setmuglue | function | uccode | table |
| setmuskip | function | uprint | function |
| setnest | function | useboxresource | function |
| setpardir | function | vrbcatcodes | number |
| setrunstate | overloaded function | nwrite | function |

function

setsfcode

texconfig (basic tex)

| buffersize | table | 1 | 4-bl- |
|-------------------|---------------------|----------------|--------|
| | table | languagesize | table |
| N size | | N size | |
| N step | | N step | |
| errorlinesize | table | marksize | table |
| N size | | N size | |
| expandsize | table | N step | |
| N size | | nestsize | table |
| filesize | table | N size | |
| N size | | N step | |
| N step | | nodesize | table |
| firstline | string | N size | |
| fontsize | table | N step | |
| N size | | parametersize | table |
| N step | | N size | |
| formatname | string | N step | |
| functionsize | number | poolsize | table |
| halferrorlinesize | table | N size | |
| N size | | N step | |
| hashsize | table | propertiessize | number |
| N size | | savesize | table |
| N step | | N size | |
| init | overloaded function | N step | |
| inputsize | table | shell_escape | string |
| N size | | stringsize | table |
| N step | | N size | |
| insertsize | table | N step | |
| N size | | tokensize | table |
| N step | | N size | |
| kpse_init | boolean | N step | |

texio (basic tex)

| closeinput | function | writenl | function |
|------------|----------|-----------------|----------|
| terminal | function | writeselector | function |
| write | function | writeselectorlf | function |
| write_nl | function | writeselectornl | function |

token (basic tex)

| create | function | getexpandable | function |
|--------------------------|----------|--------------------|----------|
| expand | function | getfields | function |
| expand macro | function | getflags | function |
| expandmacro | function | getfrozen | function |
| future expand | function | getfunctionvalues | function |
| futureexpand | function | getid | function |
| get_active | function | getimmutable | function |
| get_cmdchrcs | function | getindex | function |
| get_cmdname | function | getinstance | function |
| get_command | function | getinteger | function |
| get_csname | function | getmacro | function |
| get_cstoken | function | getmeaning | function |
| get_dimension | function | getnoaligned | function |
| get_expandable | function | getparameters | function |
| get_fields | function | getpermanent | function |
| get_flags | function | getprimitive | function |
| get_frozen | function | getprimitives | function |
| get_id | function | getprotected | function |
| <pre>get_immutable</pre> | function | getrange | function |
| get_index | function | gettok | function |
| get_instance | function | gettolerant | function |
| get_integer | function | gobble | function |
| get_macro | function | gobble_dimen | function |
| get_meaning | function | gobble_integer | function |
| get_noaligned | function | gobbledimen | function |
| get_parameters | function | gobbleinteger | function |
| get_permanent | function | is_defined | function |
| get_primitive | function | is_next_char | function |
| get_protected | function | is_token | function |
| get_range | function | isdefined | function |
| get_tok | function | isnextchar | function |
| get_tolerant | function | istoken | function |
| getactive | function | new | function |
| getcmdchrcs | function | peek_next | function |
| getcmdname | function | peek_next_char | function |
| getcommand | function | peek_next_expanded | function |
| getcommandid | function | peeknext | function |
| getcommandvalues | function | peeknextchar | function |
| getcsname | function | peeknextexpanded | function |
| getcstoken | function | pop_macro | function |
| getdimension | function | popmacro | function |

| push_macro | function | scanbox | function |
|-----------------------|----------|---------------------|----------|
| pushmacro | function | scancardinal | function |
| put_back | function | scanchar | function |
| put_next | function | scancmdchr | function |
| putback | function | scancmdchrexpanded | function |
| putnext | function | scancode | function |
| save_lua | function | scancsname | function |
| savelua | function | scandelimited | function |
| scan_argument | function | scandimen | function |
| scan_box | function | scandimenargument | function |
| scan_cardinal | function | scanfloat | function |
| scan_char | function | scanglue | function |
| scan_cmdchr | function | scaninteger | function |
| scan_cmdchr_expanded | function | scanintegerargument | function |
| scan_code | function | scankey | function |
| scan_csname | function | scankeyword | function |
| scan_delimited | function | scankeywordcs | function |
| scan_dimen | function | scanletters | function |
| scan_dimen_argument | function | scanluacardinal | function |
| scan_float | function | scanluainteger | function |
| scan_glue | function | scanluanumber | function |
| scan_integer | function | scannext | function |
| scan_integer_argument | function | scannextchar | function |
| scan_key | function | scannextexpanded | function |
| scan_keyword | function | scanreal | function |
| scan_keyword_cs | function | scanscale | function |
| scan_letters | function | scanskip | function |
| scan_luacardinal | function | scanstring | function |
| scan_luainteger | function | scantoken | function |
| scan_luanumber | function | scantokencode | function |
| scan_next | function | scantokenlist | function |
| scan_next_char | function | scantoks | function |
| scan_next_expanded | function | scanvalue | function |
| scan_real - | function | scanword | function |
| scan_scale | function | serialize | function |
| scan_skip | function | set_char | function |
| scan_string | function | set_dimension | function |
| scan_token | function | set_integer | function |
| scan_token_code | function | set_lua | function |
| scan_tokenlist | function | set_macro | function |
| scan_toks | function | setchar | function |
| scan_value | function | setdimension | function |
| scan_word | function | setinteger | function |
| scanargument | function | setlua | function |

| setmacro | function | skipnextexpanded | function |
|--------------------|----------|------------------|----------|
| skip_next | function | type | function |
| skip_next_expanded | function | undefine_macro | function |
| skipnext | function | undefinemacro | function |

tokens (context)

| accessors | table | | color | |
|-------------|----------|------|-----------|-----------------|
| Factive | table | | | 1 - |
| | | | colordefa | |
| F cmd | | | colordeff | |
| F cmdchrcs | | | colordeff | |
| F cmdname | | | colordefr | |
| F command | | | dofinishr | |
| F csname | | | dostartte | |
| F expandab | le | | finishjob | |
| F frozen | | | firstofon | _ |
| F index | | | | oarguments |
| F name | | | gobbleone | eargument |
| F protected | d | | goto | |
| F range | | | iftrue | |
| astable | function | | input | |
| bits | table | | | ltypescriptfile |
| N active | | | resetctxs | canner |
| N alignment | | | rlap | |
| N begingro | | | | woarguments |
| N characte | r | | setfalsev | |
| N close | | U | setsectio | nblock |
| N comment | | U | setupsyst | em |
| N endgroup | | U | startcolu | imns |
| N endofline | e | U | starttabu | late |
| N escape | | U | starttitl | e |
| N ignore | | U | startxtit | le |
| N invalid | | U | stopcolum | ins |
| N letter | | U | stoptabul | ate |
| N mathshif | t | U | stoptitle | • |
| N open | | U | stopxtitl | e |
| N other | | U | texsetup | |
| N paramete | r | U | xmlw | |
| N space | | comm | nands | data table |
| N subscrip | t | comp | oile | function |
| N supersor | ipt | cons | stant | function |
| N whitespa | ce | conv | erters | table |
| cache | table | S | toboolean | |
| U NC | | S | todimen | |
| U NR | | S | toglue | |
| U bf | | S | tonumber | |
| U buff_fin | ish | S | tostring | |
| U c_font_c | ompact | crea | ite | function |

| 4-6 | function | _ | |
|-------------|----------|---|-----------------|
| defined | function | | cmdchrexpanded |
| flags | function | | code |
| getinteger | function | | conditional |
| getters | table | | count |
| F box | | | csname |
| F count | | F | delimited |
| F cstoken | | | dimen |
| F dimen | | F | dimenargument |
| F glue | | F | dimension |
| F macro | | F | float |
| F meaning | | F | glue |
| F skip | | F | gluespec |
| F token | | F | gluevalues |
| gobble | function | F | hash |
| isdefined | function | F | hbox |
| istoken | function | F | integer |
| new | function | F | integerargument |
| pickup | function | F | ischar |
| popmacro | function | F | key |
| presets | table | F | keyword |
| T 1 argumen | t | F | keywordcs |
| T 1 string | | F | letters |
| T 2 argumen | ts | F | list |
| T 2 strings | | F | luacardinal |
| T 3 argumen | ts | F | luainteger |
| T 3 strings | | F | luanumber |
| T 4 argumen | ts | F | lxmlid |
| T 4 strings | | F | next |
| T 5 strings | | F | nextchar |
| T 6 strings | | F | nextexpanded |
| T 7 strings | | F | number |
| T 8 strings | | F | optional |
| pushmacro | function | F | peek |
| scanners | table | F | peekchar |
| F argument | | F | peekexpanded |
| F argumenta | sis | F | real |
| F array | | F | scanclose |
| F boolean | | F | scanopen |
| F box | | F | skip |
| F bracketed | | F | skipexpanded |
| F bracketed | asis | F | string |
| F cardinal | | F | table |
| F char | | F | token |
| F cmdchr | | F | tokencode |
| | | | |

| F tokenlist | F report |
|---------------------|-----------------------|
| F tokens | F scanargument |
| F toks | F scanargumentasis |
| F value | F scanarray |
| F vbox | F scanboolean |
| F verbatim | F scanbox |
| F vtop | F scanbracketed |
| F whd | F scanbracketedasis |
| F word | F scancardinal |
| setinteger function | F scanclose |
| setters table | F scancode |
| F box | F scanconditional |
| F char | F scancsname |
| F count | F scandelimited |
| F dimen | F scandimen |
| F glue | F scandimenargument |
| F lua | F scandimension |
| F macro | F scanglue |
| F skip | F scangluespec |
| shortcuts table | F scangluevalues |
| T bits | F scanhash |
| N active | F scanhbox |
| N alignment | F scaninteger |
| N begingroup | F scanintegerargument |
| N character | F scankeyword |
| N close | F scankeywordcs |
| N comment | F scanletters |
| N endgroup | F scanlist |
| N endofline | T scanners |
| N escape | F argument |
| N ignore | F argumentasis |
| N invalid | F array |
| N letter | F boolean |
| N mathshift | F box |
| N open | F bracketed |
| N other | F bracketedasis |
| N parameter | F cardinal |
| N space | F char |
| N subscript | F cmdchr |
| N superscript | F cmdchrexpanded |
| N whitespace | F code |
| N close | F conditional |
| F inspect | F count |
| N open | F csname |

| F delimited | F verbatim |
|-------------------|---------------------|
| F dimen | F vtop |
| F dimenargument | F whd |
| F dimension | F word |
| F float | F scannumber |
| F glue | F scanopen |
| F gluespec | F scanoptional |
| F gluevalues | F scanstring |
| F hash | F scantable |
| F hbox | F scantokenlist |
| F integer | F scantoks |
| F integerargument | F scanvbox |
| F ischar | F scanverbatim |
| F key | F scanvtop |
| F keyword | F scanword |
| F keywordcs | F toboolean |
| F letters | F todimen |
| F list | T tokens |
| F luacardinal | T accessors |
| F luainteger | F active |
| F luanumber | F cmd |
| F lxmlid | F cmdchrcs |
| F next | F cmdname |
| F nextchar | F command |
| F nextexpanded | F csname |
| F number | F expandable |
| F optional | F frozen |
| F peek | F index |
| F peekchar | F name |
| F peekexpanded | F protected |
| F real | F range |
| F scanclose | F astable |
| F scanopen | T cache |
| F skip | U NC |
| F skipexpanded | U NR |
| F string | U bf |
| F table | U buff_finish |
| F token | U c_font_compact |
| F tokencode | U color |
| F tokenlist | U colordefalc |
| F tokens | U colordefflc |
| F toks | U colordefflt |
| F value | U colordefrlt |
| F vbox | U dofinishreference |
| | |

U dostarttext F macro U finishjob F meaning U firstofoneargument F skip U firstoftwoarguments F token U gobbleoneargument F gobble F isdefined U goto U iftrue F istoken U input F new U loadfoundtypescriptfile F pickup U resetctxscanner F popmacro U rlap T presets U secondoftwoarguments F pushmacro U setfalsevalue F setinteger U setsectionblock T setters U setupsystem F box U startcolumns F char U starttabulate F count U starttitle F dimen U startxtitle F glue U stopcolumns F lua U stoptabulate F macro U stoptitle F skip U stopxtitle T shortcuts U texsetup N close U xmlw F inspect D commands N open F compile F report F scanargument F constant T converters F scanargumentasis S toboolean F scanarray S todimen F scanboolean S toglue F scanbox S tonumber F scanbracketed S tostring F scanbracketedasis F create F scancardinal F defined F scanclose F flags F scancode F scanconditional F getinteger T getters F scancsname F box F scandelimited F count F scandimen F cstoken F scandimenargument F scandimension F dimen F glue F scanglue

F scangluespec F scantokenlist F scangluevalues F scantoks F scanhash F scanvbox F scanhbox F scanverbatim F scaninteger F scanvtop F scanintegerargument F scanword F scankeyword F toboolean F scankeywordcs F todimen F scanletters F tonumber F scanlist F tostring F scannumber D values F scanopen F tonumber F scanoptional F tostring

F scanstring values data table

F scantable

tracers (context)

printerror function printwarning function

showlines function

trackers (context)

| data | data table | register | function |
|----------------|------------|----------|----------|
| default | function | report | function |
| disable | function | reset | function |
| done | table | savehash | function |
| dumphashtofile | function | show | function |
| enable | function | value | function |
| list | function | values | function |
| name | string | | |

typesetters (context)

| alignments | table | T handlers | |
|------------------|-------|------------------|-------|
| F handler | | F installhandler | |
| F set | | F processmath | |
| breakpoints | table | F set | |
| F define | | F setcolor | |
| F handler | | F setmath | |
| D mapping | | F tomode | |
| T methods | | firstlines | table |
| T numbers | | T actions | |
| F set | | F default | |
| F setreplacement | | F line | |
| cases | table | F word | |
| T actions | | F handler | |
| F handler | | F set | |
| F register | | fontkerns | table |
| F set | | F handler | |
| characteralign | table | initials | table |
| F handler | | T actions | |
| F resetcharacter | align | F default | |
| F setcharacteral | ign | F addanchortolin | e |
| characters | table | F addtoline | |
| F handler | | F calculatedelta | |
| T methods | | F checkline | |
| F replacenbsp | | F handler | |
| F replacenbspace | s | F moveinline | |
| checkers | table | F set | |
| F handler | | injectors | table |
| F reset | | F check | |
| F set | | T list | |
| cleaners | table | F mark | |
| F handler | | F reset | |
| F set | | F set | |
| digits | table | F show | |
| T actions | | italics | table |
| F handler | | F enablemath | |
| F set | | F enabletext | |
| directions | table | F forcevariant | |
| F getfences | | F handler | |
| F getglobal | | F reset | |
| F getmethod | | F set | |
| F handler | | kerns | table |
| | | | |

| 5.6.1 | | | |
|-----------------|----------|----------------|--------------|
| D factors | | F register | |
| F handler | | F reset | |
| F keepligature | | F split | |
| D mapping | | F startapply | |
| F set | | F stopapply | |
| manipulators | table | F stripped | |
| F apply | | F tostring | |
| F applyspecific | cation | rubies | table |
| T methods | | F attach | |
| F Word | | F check | |
| F Words | | showsuspects | function |
| F abbreviated | journal | spacings | table |
| F expandedjou | rnal | F define | |
| F lowercase | | F handler | |
| F stripperiod | | D mapping | |
| F uppercase | | T numbers | |
| T patterns | | T frenchpunct | tuation |
| U list | | T character | S |
| U pair | | S name | |
| F splitspecific | cation | N number | |
| margins | table | F reset | |
| F finalhandler | | F set | |
| F globalhandler | • | F setup | |
| F localhandler | | wrappers | table |
| F save | | F handler | |
| marksuspects | function | xtables | table |
| paragraphs | table | F cleanup | |
| F addanchortoli | ine | F construct | |
| F addtoline | | F create | |
| F calculatedelt | ta | F finish_row | |
| F checkline | | F flush | |
| F handler | | F initialize_c | onstruct |
| F moveinline | | F initialize_r | eflow_height |
| F set | | F initialize_r | eflow_width |
| periodkerns | table | F next_row | |
| D factors | | F reflow_heigh | t |
| F handler | | F reflow_width | |
| D mapping | | F set_construc | t |
| F set | | F set_reflow_h | eight |
| processors | table | F set_reflow_w | _ |
| F apply | | | |
| | | | |

updaters (context)

apply function
register function

url (context)

| addscheme | function | hashed | function |
|-----------|----------|-------------|----------|
| barepath | function | hasscheme | function |
| construct | function | query | function |
| decode | function | split | function |
| encode | function | toquery | function |
| escape | function | unescape | function |
| filename | function | unescapeget | function |

utf8 (basic lua)

| char | function | codes | function |
|-------------|----------|--------|----------|
| charpattern | string | len | function |
| codepoint | function | offset | function |

utilities (context)

| dohuman | +ahla | |
|-----------|------------|-----------------------------|
| debugger | table | F readtag |
| F disable | | F setposition |
| F enable | | F size |
| F savesta | | F skip |
| F showsta | | F skiplong |
| F showtra | | F skipposition |
| files | table | F skipshort |
| F close | | F writebyte |
| F getposi | tion | F writecardinal1 |
| F getsize | | F writecardinal1le |
| F look | | F writecardinal2 |
| F open | | F writecardinal2le |
| F read2do | | F writecardinal3 |
| F readbyt | | F writecardinal3le |
| F readbyt | | F writecardinal4 |
| F readbyt | | F writecardinal4le |
| F readcar | | F writeinteger1 |
| F readcar | | F writeinteger1le |
| F readcar | | F writeinteger2 |
| F readcar | | F writeinteger2le |
| F readcar | | F writeinteger3 |
| F readcar | dinal3 | F writeinteger3le |
| F readcar | dinal3le | F writeinteger4 |
| F readcar | dinal4 | F writeinteger4le |
| F readcar | dinal4le | F writestring |
| F readcar | dinaltable | formatters table |
| F readcha | r | F formatcolumns |
| F readfix | ed2 | F list |
| F readfix | ed4 | F stripzeros |
| F readint | eger | ghostscript table |
| F readint | eger1 | F convert |
| F readint | eger1le | F statistics |
| F readint | eger2 | graphicmagick table |
| F readint | eger2le | F convert |
| F readint | eger3 | F statistics |
| F readint | eger3le | graphicsmagick table |
| F readint | eger4 | F convert |
| F readint | eger4le | F statistics |
| F readint | egertable | lua table |
| F readsig | nedbyte | B alwaysstripcode |
| F readstr | ing | F checkmemory |

| F compile | B text |
|---|---------------------------------|
| F loadedluacode | F iterator |
| F loadstring | F keq to hash |
| F loadstripped | F listitem |
| N nofstrippedbytes | F make settings to hash pattern |
| N nofstrippedchunks | F mergehashes |
| F registerfinalizer | F options_to_array |
| B stripcode | F options_to_hash |
| T strippedchunks | T patterns |
| F strippedloadstring | U settings_to_array |
| T suffixes | U settings_to_hash_a |
| S lua | U settings_to_hash_b |
| S luc | U settings_to_hash_c |
| S lui | U settings_to_hash_d |
| S luj | U unittotex |
| S luv | F process_stripped_settings |
| S tma | F rfc4180splitter |
| S tmc | F runtime |
| S tua | F settings_to_array |
| S tuc | F settings_to_array_obey_fences |
| <pre>packers table</pre> | F settings_to_array_with_repeat |
| F hashed | F settings_to_hash |
| F new | F settings_to_hash_colon_too |
| F pack | F settings_to_hash_strict |
| F simplehashed | F settings_to_hash_tolerant |
| F strip | F settings_to_numbers |
| F unpack | F settings_to_set |
| N version | F simple_hash_to_string |
| parsers table | F splitmethod |
| F add_settings_to_array | F splitthousands |
| F arguments_to_table | F stepper |
| F array_to_string | F stripped_settings_to_array |
| F csvsplitter | F totime |
| F getparameters | F unittotex |
| F groupedsplitat | F unittoxml |
| F hash_to_string | randomizer table |
| T hashes | F get |
| T settings_to_set | F getnumber |
| T text,hidden,paper,page,leftpage,rightpage | F getseed |
| B hidden | F popseed |
| B leftpage | F pushseed |
| B page | F reuseseed |
| B paper | F setseed |
| B rightpage | F setseedi |

| randomizers | table | _ | look | |
|------------------|-------|------|------------------------------|-------|
| F poisson | tabte | | open | |
| sequencers | table | | openstring | |
| F appendaction | tabte | | read2dot14 | |
| F appendgroup | | | readbyte | |
| F compile | | | readbytes | |
| F disableaction | | | readbytetable | |
| F disablegroup | | | readcardinal | |
| F enableaction | | - | readcardinal1 | |
| F enablegroup | | | readcardinal11 | 2 |
| D functions | | - | readcardinal2 | _ |
| F localize | | | readcardinal2le | 2 |
| F new | | | readcardinal3 | _ |
| F nodeprocessor | | | readcardinal3le | 2 |
| F prependaction | | | readcardinal4 | _ |
| F prependgroup | | F | readcardinal4le | 2 |
| F removeaction | | F | readcardinalta | ole |
| F replaceaction | | F | readchar | |
| F setkind | | F | readfixed2 | |
| F tostring | | F | readfixed4 | |
| setters | table | F | readinteger | |
| F disable | | F | readinteger1 | |
| F enable | | F | readinteger1le | |
| F initialize | | F | readinteger2 | |
| F list | | F | readinteger2le | |
| F new | | F | readinteger3 | |
| F register | | F | readinteger3le | |
| F report | | F | readinteger4 | |
| F reset | | F | readinteger4le | |
| F show | | F | readintegertab | le |
| stacker | table | F | ${\tt readsigned}{\tt byte}$ | |
| F new | | F | readstring | |
| storage | table | F | setposition | |
| F allocate | | F | size | |
| F checked | | F | skip | |
| F mark | | F | skipbytes | |
| F marked | | F | skiplong | |
| F setinitializer | | | skipshort | |
| F sparse | | stri | _ | table |
| streams | table | F | collapse | |
| F close | | | collapsecrlf | |
| F getposition | | | formatters | |
| F getsize | | | F add | |
| F getstring | | | F new | |

F newcollector F insertaftervalue F newrepeater F insertbeforevalue F nice F migratetable T striplinepatterns F removevalue U collapse F replacevalue U prune templates table F load U prune and collapse U prune and no empty F replace U prune and to space F replacer U retain F resolve zipfiles table U retain and collapse U retain and no empty F close F striplines F found F gunzipfile F striplong F hash F tabtospace T tracers F list tables table F open F accesstable F unzip F definedtable F unzipdir

F zipdir

F definetable

F encapsulate

visualizers (context)

| escapepatterns | data table | signal | string |
|-----------------------|------------|-----------------|------------|
| • • | | • | 3 |
| getspecification | function | signalpattern | userdata |
| getvisualizer | function | specifications | data table |
| load | function | visualize | function |
| makenested | function | visualizebuffer | function |
| makepattern | function | visualizefile | function |
| newgrammar | function | visualizestring | function |
| newhandler | function | write | function |
| parsedxml | function | writeargument | function |
| pattern | function | writedefault | function |
| register | function | writeemptyline | function |
| registerescapecommand | function | writenewline | function |
| registerescapeline | function | writespace | function |
| registerescapepattern | function | | |

xcomplex (extra lua)

| I | function | |
|-----|----------------------|-------------------------|
| | | F sqrt |
| add | | Ftan |
| div | function | F tanh |
| eq | function ex table | F topair |
| ind | | F tostring |
| FI | | F totable |
| _ | _add | Fmul |
| _ | _div | Sname |
| F _ | | Fpow |
| | _index | Fsub |
| | I | Ftostring |
| | add | Funm |
| | div | F abs |
| | eq | F acos |
| | mul | F acosh |
| | name | F arg |
| | pow | Fasin |
| | sub | F asinh |
| | tostring | F atan |
| | unm | F atanh |
| | abs | F conj |
| | acos | F cos |
| | acosh | F cosh |
| | arg . | F exp |
| | asin | F i |
| | | F imag |
| | atan | F log |
| | atanh | F new |
| | cos | F pow F proj |
| | cosh | F real |
| | exp | Fin |
| | i | F sinh |
| | imag | F sqrt |
| | log | r sqrt F tan |
| | new | F tanh |
| | pow | |
| | • | F topair |
| | proj real | F tostring F totable |
| | | mul function |
| | sin | |
| ۲ | sinh | name string |

| pow | function | i | function |
|----------|----------|----------|----------|
| sub | function | imag | function |
| tostring | function | log | function |
| unm | function | new | function |
| abs | function | pow | function |
| acos | function | proj | function |
| acosh | function | real | function |
| arg | function | sin | function |
| asin | function | sinh | function |
| asinh | function | sqrt | function |
| atan | function | tan | function |
| atanh | function | tanh | function |
| conj | function | topair | function |
| cos | function | tostring | function |
| cosh | function | totable | function |
| exp | function | | |

xdecimal (extra lua)

| add | function | | F getprecision |
|-----------|----------|---|----------------|
| band | function | | F ln |
| bor | function | | F log |
| bxor | function | | F max |
| div | function | | F min |
| eq | function | | F minus |
| idiv | function | | F new |
| index | table | | F plus |
| Fadd | | | F pow |
| Fband | | | F rotate |
| Fbor | | | F setprecision |
| Fbxor | | | F shift |
| Fdiv | | | F sqrt |
| Feq | | | F toengstring |
| Fidiv | | | F tonumber |
| Tindex | | | F tostring |
| Fadd | | | F trim |
| Fband | | F | le |
| Fbor | | F | lt |
| Fbxor | | F | mod |
| Fdiv | | F | mul |
| Feq | | S | name |
| Fidiv | | F | pow |
| Fle | | F | shl |
| Flt | | F | shr |
| Fmod | | F | sub |
| Fmul | | F | tostring |
| Sname | | F | unm |
| Fpow | | F | abs |
| Fshl | | F | band |
| Fshr | | F | bor |
| Fsub | | F | bxor |
| Ftostring | | F | conj |
| Funm | | F | сору |
| F abs | | F | exp |
| F band | | F | getprecision |
| F bor | | F | ln |
| F bxor | | F | log |
| F conj | | F | max |
| F copy | | F | min |
| F exp | | F | minus |

| | F new | | band | function |
|---|---------------|----------|--------------|----------|
| | F plus | | bor | function |
| | F pow | | bxor | function |
| | F rotate | | conj | function |
| | F setprecisio | n | сору | function |
| | F shift | | exp | function |
| | F sqrt | | getprecision | function |
| | F toengstring | | ln | function |
| | F tonumber | | log | function |
| | F tostring | | max | function |
| | F trim | | min | function |
| _ | le | function | minus | function |
| _ | lt | function | new | function |
| _ | mod | function | plus | function |
| _ | mul | function | pow | function |
| _ | name | string | rotate | function |
| _ | pow | function | setprecision | function |
| _ | shl | function | shift | function |
| _ | shr | function | sqrt | function |
| _ | sub | function | toengstring | function |
| _ | tostring | function | tonumber | function |
| _ | unm | function | tostring | function |
| ě | abs | function | trim | function |
| | | | | |

xmath (extra lua)

| acos | function | isnormal | function |
|----------|----------|-----------|----------|
| acosh | function | j0 | function |
| asin | function | j1 | function |
| asinh | function | jn | function |
| atan | function | ldexp | function |
| atan2 | function | lgamma | function |
| atanh | function | log | function |
| cbrt | function | log10 | function |
| ceil | function | log1p | function |
| copysign | function | log2 | function |
| cos | function | logb | function |
| cosh | function | modf | function |
| deg | function | nan | number |
| erf | function | nearbyint | function |
| erfc | function | nextafter | function |
| exp | function | pi | number |
| exp2 | function | pow | function |
| expm1 | function | rad | function |
| fabs | function | remainder | function |
| fdim | function | remquo | function |
| floor | function | round | function |
| fma | function | scalbn | function |
| fmax | function | sin | function |
| fmin | function | sinh | function |
| fmod | function | sqrt | function |
| frexp | function | tan | function |
| gamma | function | tanh | function |
| hypot | function | tgamma | function |
| inf | number | trunc | function |
| isfinite | function | y0 | function |
| isinf | function | y1 | function |
| isnan | function | yn | function |
| | | | |

xml (context)

| | _ | | |
|--------------------------|---------------------|---------------------------|---------------------|
| addentitiesdoctype | function | F family | |
| addspecialcode | function | F fontspecification | |
| after | function | F mappedstylevalue | |
| all | function | F padding | |
| applylpath | function | F size | |
| applyselector | function | F style | |
| assign | function | F stylevalue | |
| attribute | function | F todimension | |
| badinclusions | function | F variant | |
| before | function | F weight | |
| body | function | defaulthandlers | table |
| builtinentities | table | D file | |
| B amp | | D parsedxml | |
| B apos | | D string | |
| B gt | | D tex | |
| B lt | | D texline | |
| B quot | | D texspace | |
| cdata | function | D verbose | |
| cdatatotext | function | defaultprotocol | string |
| checkbom | function | delete | function |
| checkedempty | function | delete_element | function |
| checkerror | function | despecialized | function |
| checknamespace | function | each | function |
| checkns | function | each_element | function |
| cleansed | function | elements | function |
| collect | function | elementtocdata | function |
| collect_elements | function | empty | function |
| collect_tags | function | entities | data table |
| collect_texts | function | erase | function |
| collected | function | errorhandler | function |
| collecttexts | function | escaped | function |
| compactelement | function | expressions | table |
| content | function | F attribute | |
| convert | function | F boolean | |
| сору | function | F child | |
| count | function | F contains | |
| cprint | function | F count | |
| css | table | F error | |
| F applyselector | | F find | |
| F colorspecification | | F hasclass | |
| F dimension | | F idstring | |

| Flower | | F upper | |
|------------------|----------|---------------------|----------|
| F name | | F upperall | |
| F number | | F xml | |
| F oneof | | T xml | |
| F print | | Fall | |
| F quit | | Fatt | |
| F tag | | F attribute | |
| F text | | F attributes | |
| F undefined | | F cdata | |
| F upper | | F chainattribute | |
| fillin | function | F count | |
| filter | function | F default | |
| finalizers | table | F elements | |
| F paragraphs | cabic | F empty | |
| T tex | | F first | |
| Fall | | F function | |
| F attribute | | F index | |
| F chainattribute | | F last | |
| F chainpath | | F lowerall | |
| F command | | F match | |
| F concat | | F name | |
| F concatrange | | F position | |
| F context | | F reverse | |
| F count | | F table | |
| F ctxtext | | F tag | |
| F default | | F tags | |
| F depth | | F text | |
| F first | | F texts | |
| F function | | F upperall | |
| F index | | first | function |
| F last | | found | function |
| F lettered | | functions | table |
| F lower | | F classes | |
| F lowerall | | F hasclass | |
| F match | | getbuffer | function |
| F name | | gethandlers | function |
| F param | | gethandlersfunction | function |
| F parameter | | helpers | table |
| F position | | F recursetext | |
| F reverse | | include | function |
| F stripped | | inclusion | function |
| F tag | | inclusions | function |
| F tags | | index | function |
| F text | | inheritattributes | function |
| | | | |

| inheritedconvert | function | privatetoken | function |
|-----------------------|----------|---------------------|---------------------|
| inject | function | process | function |
| inject_element | function | process attributes | function |
| inject_element_after | function | process_elements | function |
| inject element before | | processattributes | function |
| injectafter | function | profiled | table |
| injectbefore | function | pure | function |
| insert | function | pushmatch | function |
| insert element | function | raw | function |
| insert_element_after | function | registerentity | function |
| insert_element_before | function | registerns | function |
| insertafter | function | reindex | function |
| insertbefore | function | remap name | function |
| insertcdata | function | remap namespace | function |
| insertcomment | function | remap tag | function |
| inspect | function | remapname | function |
| is_valid | function | remapnamespace | function |
| kind | function | remaptag | function |
| last | function | rename | function |
| lastmatch | function | renamespace | function |
| load | function | reparsedentitylpeg | userdata |
| lpath | function | replace | function |
| lpathcached | function | replace_element | function |
| lpathcalls | function | resetinjectors | function |
| lshow | function | resolvens | function |
| makestandalone | function | root | function |
| match | function | save | function |
| name | function | selection | function |
| newhandlers | function | separate | function |
| nodesettostring | function | serialize | function |
| originalload | function | serializetotext | function |
| package | function | setcdata | function |
| parent | function | setcomment | function |
| parsedentitylpeg | userdata | sethandlersfunction | function |
| pihandlers | table | setinjectors | function |
| F injector | | setproperty | function |
| F tex | | settings | function |
| placeholders | table | specialcodes | table |
| F unknown_any_entity | | S " | |
| F unknown_dec_entity | | S # | |
| F unknown_hex_entity | | S \$ | |
| popmatch | function | S % | |
| position | function | S & | |
| privatecodes | table | S ' | |

| S < | | texttocdata | function |
|--------------------|-----------------|---------------------|----------|
| S > | | tocdata | function |
| S \ | | toelement | function |
| S { | | tostring | function |
| S | | totable | function |
| S } | | toxml | function |
| S ~ | | tprint | function |
| specialhandler | table | traverse | function |
| sprint | function | unescaped | function |
| string | function | unescapedentitylpeg | userdata |
| strip | function | unprivatized | function |
| strip_whitespace | function | unspecialized | function |
| stripelement | function | wipe | function |
| stripleadingspaces | function | withelement | function |
| table | function | withelements | function |
| text | function | wrap | function |
| textonly | function | xmlns | table |

xzip (extra lua)

| adler32 | function | crc32 | function |
|--------------|----------|----------------|----------|
| compress | function | decompress | function |
| compresssize | function | decompresssize | function |

zip (extra lua)

archives table
closearchive function

openarchive function
registeredfiles table

zlib (extra lua)

| adler32 | function | crc32 | function |
|--------------|----------|----------------|----------|
| compress | function | decompress | function |
| compresssize | function | decompresssize | function |