

attributes backends bibtex bit32 blobs
boolean buffers builders caches callback
callbacks catcodes characters chemistry
commands containers context converters
coroutine ctxrunner debug dir directives
document documentdata environment epdf
experiments figures file floats font
fontloader fonts functions global
graphics gzip img interactions
interfaces io job lang languages layouts
lfs libraries lmx logs lpdf lpeg ltn12
lua luatex lxml math mathematics mbox
md5 metapost mime moduledata modules
mplib noads node nodes number os package
pagebuilders parametersets pdf
pdfscanner physics profiler regimes
resolvers scripts set socket sorters
statistics status storage streams string
structures table tex texconfig texio
thirddata token tokens tracers trackers
typesetters unicode url userdata
utilities vf visualizers xml zip zlib

ConTExT MkIV

global (alias: _G)

| | | | |
|-----------------------------|----------|------------------------------|----------|
| <code>_LUAVERSION</code> | number | <code>floats</code> | table |
| <code>_MAJORVERSION</code> | number | <code>font</code> | table |
| <code>_MINORVERSION</code> | number | <code>fontloader</code> | table |
| <code>arg</code> | table | <code>fonts</code> | table |
| <code>assert</code> | function | <code>frozen</code> | boolean |
| <code>attributes</code> | table | <code>functions</code> | table |
| <code>backends</code> | table | <code>getmetatable</code> | function |
| <code>beginpage</code> | function | <code>getreadfilename</code> | function |
| <code>bibtex</code> | table | <code>global</code> | table |
| <code>bit32</code> | table | <code>graphics</code> | table |
| <code>blobs</code> | table | <code>gzip</code> | table |
| <code>boolean</code> | table | <code>img</code> | table |
| <code>buffers</code> | table | <code>inspect</code> | function |
| <code>builders</code> | table | <code>interactions</code> | table |
| <code>caches</code> | table | <code>interfaces</code> | table |
| <code>callback</code> | table | <code>io</code> | table |
| <code>callbacks</code> | table | <code>ipairs</code> | function |
| <code>catcodes</code> | table | <code>job</code> | table |
| <code>characters</code> | table | <code>lang</code> | table |
| <code>chemistry</code> | table | <code>languages</code> | table |
| <code>collectgarbage</code> | function | <code>layouts</code> | table |
| <code>commands</code> | table | <code>lfs</code> | table |
| <code>containers</code> | table | <code>libraries</code> | table |
| <code>context</code> | function | <code>lmx</code> | table |
| <code>converters</code> | table | <code>lmxconvert</code> | function |
| <code>coroutine</code> | table | <code>lmxnew</code> | function |
| <code>ctxrunner</code> | table | <code>load</code> | function |
| <code>debug</code> | table | <code>loadfile</code> | function |
| <code>dimen</code> | function | <code>loadstring</code> | function |
| <code>dir</code> | table | <code>logs</code> | table |
| <code>directives</code> | table | <code>lp_fastpos_n</code> | userdata |
| <code>document</code> | table | <code>lp_fastpos_p</code> | userdata |
| <code>documentdata</code> | table | <code>lpdf</code> | table |
| <code>dofile</code> | function | <code>lpeg</code> | table |
| <code>endpage</code> | function | <code>ltn12</code> | table |
| <code>environment</code> | table | <code>lua</code> | table |
| <code>epdf</code> | table | <code>luatex</code> | table |
| <code>error</code> | function | <code>lxml</code> | table |
| <code>experiments</code> | table | <code>math</code> | table |
| <code>figures</code> | table | <code>mathematics</code> | table |
| <code>file</code> | table | <code>mbox</code> | table |

| | | | |
|--------------------------|----------|-------------------------|----------|
| md5 | table | setmetatable | function |
| metapost | table | socket | table |
| mime | table | sorters | table |
| module | function | statistics | table |
| moduledata | table | status | table |
| modules | table | storage | table |
| mplib | table | streams | table |
| newline | function | string | table |
| next | function | stripmath | function |
| noads | table | structures | table |
| node | table | table | table |
| nodes | table | tex | table |
| number | table | texconfig | table |
| optionalrequire | function | texio | table |
| os | table | thirddata | table |
| outputpagestree | function | toboollean | function |
| package | table | token | table |
| pagebuilders | table | tokens | table |
| pairs | function | tonumber | function |
| parametersets | table | tostring | function |
| pcall | function | trace_characters | boolean |
| pdf | table | traceback | function |
| pdfscanner | table | tracers | table |
| physics | table | trackers | table |
| print | function | type | function |
| profiler | table | typesetters | table |
| protect | function | unicode | table |
| rawequal | function | unpack | function |
| rawget | function | url | table |
| rawlen | function | userdata | table |
| rawset | function | utf | table |
| regimes | table | utilities | table |
| report_characters | function | vf | table |
| require | function | visualizers | table |
| resolvers | table | xml | table |
| scripts | table | xmlconvert | function |
| select | function | xpcall | function |
| set | table | zip | table |
| setinspector | function | zlib | table |

attributes (context)

colorintents table

- N attribute
- D data
- F enable
- F handler
- F register
- D registered

colors table

- N attribute
- F cmyk
- F cmyktogray
- F cmyktorgb
- F colorcomponents
- B couple
- D data
- N default
- F defineintermediatecolor
- F definemixcolor
- F definemultitonecolor
- F defineprocesscolor
- F definesimplegray
- F definespotcolor
- F definetransparency
- F enable
- F filter
- F forcedmodel
- F forcesupport
- F formatcolor
- F formatgray
- F gray
- F graytohsv
- F handler
- F hsvtorgay
- F hsvtorgb
- F iccprofile
- F isblack
- N main
- S model
- D models
- F mpcolor
- F mpnamedcolor

- F mpoptions
- U none
- F popset
- F pushset
- F register
- D registered
- F registerspotcolor
- F rgb
- F rgbtocmyk
- F rgbtorgay
- F rgbtohsv
- N selector
- F setlist
- F setmodel
- D sets
- F spec
- F spot
- F spotcolorname
- F spotcolorparent
- F spotcolorvalue
- B supported
- F transparencycomponents
- B triggering
- F usecolors
- F value
- D values
- B weightgray

define function effects table

- N attribute
- D data
- F enable
- F handler
- F register
- D registered
- D values

handlers table list data table names data table negatives table

- N attribute

| | | | |
|-----------------------|------------|---------------------|--------|
| D data | | D registered | |
| F enable | | B supported | |
| F handler | | B triggering | |
| F register | | F value | |
| D registered | | D values | |
| numbers | data table | unsetvalue | number |
| ofnode | function | viewerlayers | table |
| private | function | N attribute | |
| showcurrent | function | D data | |
| states | table | F define | |
| F disabletriggering | | F enable | |
| F enabletriggering | | F forcesupport | |
| F finalize | | F handler | |
| F initialize | | B hasorder | |
| F process | | D listwise | |
| F selective | | F register | |
| F stacked | | D registered | |
| F stacker | | F resolve_begin | |
| transparencies | table | F resolve_end | |
| N attribute | | F resolve_step | |
| D data | | D scopes | |
| F enable | | F setfeatures | |
| F forcesupport | | F start | |
| F handler | | F stop | |
| U none | | B supported | |
| F register | | D values | |

backends (context)

codeinjections table

F synchronizecolormodel

current string

defaults table

T codeinjections

T nodeinjections

T registrations

D tables

install function

nodeinjections table

F restore

F save

F transform

nothing function

pdf table

T codeinjections

F addbookmarks

F attachmentid

F clonefield

F definefield

F definefieldset

F defineviewerlayer

F embedfile

F enabletags

F exportformdata

F finalizepage

F finishreference

F getdefaultfieldvalue

F getfieldcategory

F getfieldset

F getformatoption

F getoutputfilename

F getpreviewfigure

F insertrenderingwindow

F mergereferences

F mergeviewerlayers

F prerollreference

F presetsymbol

F presetsymbollist

F processrendering

F registerdocumentcloseaction

F registerdocumentopenaction

F registeredsymbol

F registerpagecloseaction

F registerpageopenaction

F registersymbol

F setfieldcalculationset

F setfigurealternative

F setfigurecolorspace

F setfiguremask

F setformat

F setformsmethod

F setpagetransition

F setupcanvas

F setupidentity

F setxmpfile

F startlayer

F stoplayer

F supportedformats

F useviewerlayer

F validfield

F validfieldcategory

F validfieldset

S comment

T nodeinjections

F addtags

F attachfile

F changestackedlayer

F cmykcolor

F comment

F destination

F effect

F graycolor

F injectbitmap

F insertmovie

F insertsound

F insertswf

F insertu3d

F knockout

F negative

F overprint

F positive

| | |
|---------------------|----------------------------|
| F reference | F getspotcolorreference |
| F rgbcolor | F grayindexcolor |
| F spotcolor | F grayspotcolor |
| F startlayer | F rgbindexcolor |
| F startstackedlayer | F rgbspotcolor |
| F stoplayer | F spotcolorname |
| F stopstackedlayer | F transparency |
| F transparency | T tables |
| F typesetfield | D vfspecials |
| T registrations | registrations table |
| F cmykindexcolor | tables table |
| F cmykspotcolor | |

bibtex (context)

| | | | |
|-----------------------|----------|-------------------------|----------|
| authorref | function | F flush | |
| authors | table | F nofregistered | |
| F concat | | F process | |
| F inverted | | F register | |
| F invertedshort | | F registerplaced | |
| F normal | | F reset | |
| F normalshort | | F resolve | |
| F setsettings | | load | function |
| F short | | new | function |
| authoryearref | function | singularorplural | function |
| authoryearsref | function | statistics | table |
| convert | function | N nofbytes | |
| hacks | table | N nofdefinitions | |
| F add | | N nofshortcuts | |
| F doifalreadypaced | | toxml | function |
| F filterall | | | |

bit32 (basic lua)

arshift function
band function
bnot function
bor function
btest function
bxor function

extract function
lrotate function
lshift function
replace function
rrotate function
rshift function

blobs (context)

append function
dimensions function
dispose function

new function
pack function
write function

boolean (context)

tocontext function

tonumber function

buffers (context)

| | | | |
|-----------------------|----------|------------------|----------|
| append | function | parallel | table |
| assign | function | F define | |
| collectcontent | function | F hassomecontent | |
| erase | function | F next | |
| exists | function | F place | |
| getcontent | function | F reset | |
| getlines | function | F save | |
| loadcontent | function | raw | function |

builders (context)

kernel table

- F hyphenation
- F kerning
- F ligaturing
- F mlist_to_hlist

paragraphs table

- T constructors
 - N attribute
 - F define
 - F disable
 - F enable
 - F handler
- T methods
 - F default
 - F oneline
- D names
- D numbers
- F set
- F start
- F stop
- F keptogether
- F registertogether
- T solutions
 - T splitters
 - F define

- F optimize
- T registered
- F reset
- F set
- F split
- F start
- F stop

F tag

vspacing table

- F analyze
- D categories
- F collapsevbox
- T data
- D map
- D skip
- D snapmethods
- F definesnapmethod
- B fixed
- F pagehandler
- F setmap
- F setskip
- F snapbox
- F tocategories
- F tocategory
- F vboxhandler

caches (context)

| | | | |
|-----------------------------|----------|-----------------------------|----------|
| ask | boolean | is_writable | function |
| base | string | loadcontent | function |
| collapsecontent | function | loaddata | function |
| configfiles | function | more | string |
| contentstate | function | relocate | boolean |
| defaults | table | savecontent | function |
| define | function | savedata | function |
| direct | boolean | setfirstwritablefile | function |
| force | boolean | setluanames | function |
| getfirstreadablefile | function | tree | string |
| getreadablepaths | function | treehash | function |
| getwritablepath | function | usedpaths | function |
| hashed | function | | |

callback (basic tex)

find function
list function

register overloaded function

callbacks (context)

freeze function
known function
list data table
pop function

push function
register function
report function

catcodes (context)

names data table

numbers data table

register function

characters (context)

| | | | |
|----------------------|------------|------------------------------|------------|
| activeoffset | number | lcchars | data table |
| adobename | function | lccode | function |
| bidirectional | data table | lccodes | data table |
| blocks | data table | lettered | function |
| casemap | table | lower | function |
| categories | data table | math | table |
| category | function | mathpairs | data table |
| categorytags | data table | otfscripts | data table |
| combined | data table | ranges | data table |
| contextname | function | registerentities | function |
| data | data table | remap_hangul_syllable | function |
| decomposed | data table | safechar | function |
| define | function | setcodes | function |
| description | function | shape | function |
| descriptions | data table | shaped | function |
| directions | table | shchars | data table |
| encodes | data table | shcodes | data table |
| entities | data table | specialchars | data table |
| fallbacks | data table | specials | data table |
| filters | data table | subscripts | table |
| fromnumber | function | superscripts | table |
| fschars | data table | synonyms | data table |
| fscodes | data table | tex | table |
| getrange | function | D accentmapping | |
| graphemes | data table | F defineaccents | |
| hangul | data table | F toutf | |
| initialize | function | tonumber | function |
| is_character | data table | ucchars | data table |
| is_command | data table | uccode | function |
| is_letter | data table | uccodes | data table |
| is_mark | data table | unicodechar | function |
| is_spacing | data table | upper | function |

chemistry (context)

| | | | |
|--------------------|------------|-----------------------|----------|
| component | function | moleculeparser | userdata |
| define | function | start | function |
| definitions | data table | stop | function |
| format | string | structures | number |
| instance | string | undefine | function |
| molecule | function | | |

commands (context)

| | | | |
|----------------------------------|----------|-------------------------------|----------|
| Alphabetic | function | autonextstructurelevel | function |
| Character | function | autosetups | function |
| Characters | function | autostarttext | function |
| MPc | function | autostoptext | function |
| MPd | function | bcolumn | function |
| MPh | function | boolcase | function |
| MPLl | function | character | function |
| MPlr | function | characters | function |
| MPls | function | checkcharactersinfont | function |
| MPn | function | checkcountersetup | function |
| MPP | function | checkedconversion | function |
| MPpardata | function | checkedpagefloat | function |
| MPplus | function | checktwopassdata | function |
| MPpos | function | chemicalcomponent | function |
| MPposset | function | chineseallnumerals | function |
| MPr | function | chinesecapnumerals | function |
| MPrest | function | chinesenumerals | function |
| MPrs | function | cleanfontname | function |
| MPul | function | cleanupplayers | function |
| MPur | function | clonefield | function |
| MPw | function | collectfloat | function |
| MPx | function | collecthelp | function |
| MPxy | function | colorcomponents | function |
| MPxywhd | function | concatcommalist | function |
| MPy | function | consultfloat | function |
| Romannumerals | function | copyposition | function |
| abjadnodotnumerals | function | cos | function |
| abjadnumerals | function | cosd | function |
| addcounter | function | countervalue | function |
| addlinklistelement | function | counttwopassdata | function |
| addtojavascriptpreamble | function | currentcomponent | function |
| addtolist | function | currentdate | function |
| allinputpaths | function | currentenvironment | function |
| alphabetic | function | currentproduct | function |
| analysefloatmethod | function | currentproject | function |
| analyzelist | function | currentreferenceorder | function |
| applytochars | function | currentregime | function |
| applytowords | function | datasetvariable | function |
| assignbuffer | function | dayname | function |
| autofinishstructurelevels | function | defineattribute | function |
| autonextspace | function | definebibtexsession | function |

| | | | |
|--------------------------------|----------|-------------------------------------|----------|
| definebreakpoint | function | doifblackelse | function |
| definebreakpoints | function | doifcommonelse | function |
| definecharacterspacing | function | doifcounter | function |
| definechemical | function | doifdimenstringelse | function |
| defineconversion | function | doifdrawingblackelse | function |
| definecounter | function | doifelse | function |
| definedviewerlayer | function | doifelsebuffer | function |
| definefield | function | doifelsecontinewithfile | function |
| definefieldset | function | doifelsecounter | function |
| definefilefallback | function | doifelsecurrentfontasfeature | function |
| definefilesynonym | function | doifelseintwopassdata | function |
| definefont_one | function | doifelsemarking | function |
| definefont_two | function | doifelsemessage | function |
| definefontfeature | function | doifelsemultipar | function |
| definefontsolution | function | doifelseparallel | function |
| defineinsertion | function | doifelsepositionsused | function |
| defineintermediatecolor | function | doifelserangeonpage | function |
| definelabels | function | doifelserreference | function |
| definelanguage | function | doifelsesavedfloat | function |
| definelinkedlist | function | doifelsespaces | function |
| definemarking | function | doifelseutfmathaccent | function |
| definemultitonecolor | function | doifelsevisualizer | function |
| definenote | function | doiffielddcategoryelse | function |
| defineparallel | function | doiffielddelse | function |
| defineparbuilder | function | doiffielddsetelse | function |
| defineprocesscolor | function | doiffiledefinedelse | function |
| defineprogram | function | doiffileexistelse | function |
| definereference | function | doiffirstcharelse | function |
| definesectionlevels | function | doifinputfileelse | function |
| definespotcolor | function | doifinsetelse | function |
| definestructureblock | function | doifleapyearelse | function |
| definestructureset | function | doiflisthasentry | function |
| definetransparency | function | doiflisthasnumberelse | function |
| definetwopasslist | function | doiflisthaspageelse | function |
| defineviewerlayer | function | doiflisthastitleelse | function |
| defrostrandomseed | function | doiflocfileelse | function |
| digits | function | doifnot | function |
| disableautofontscript | function | doifnotcounter | function |
| disableparbuilder | function | doifnotecontent | function |
| disableregime | function | doifnoteonsamepageasprevious | function |
| disablespellchecking | function | doifobjectreferencefoundelse | function |
| discardfromlist | function | doifolderversionelse | function |
| doanalyzeframedbox | function | doifoverlappingelse | function |
| doif | function | doifparentfileelse | function |

| | | | |
|------------------------------------|-----------------|------------------------------------|-----------------|
| doifposition | function | figurevariable | function |
| doifpositionelse | function | filterdefaultreference | function |
| doifpositiononpage | function | filterreference | function |
| doifpositionsonsamepageelse | function | finalizebox | function |
| doifpositionsonthispageelse | function | findtwopassdata | function |
| doifurldefinedelse | function | firstcountervalue | function |
| doprocесstypescriptfile | function | firstinset | function |
| doreshapeframedbox | function | flushfloat | function |
| dostarttextfile | function | flushnotes | function |
| dostoptextfile | function | flushpostponedblocks | function |
| ecolumn | function | flushpostponednotes | function |
| elapsedtime | function | fontchar | function |
| enableautofontscript | function | fontcollectionclone | function |
| enablecolor | function | fontcollectiondefine | function |
| enablecolorintents | function | fontcollectionprepare | function |
| enablefontcolor schemes | function | fontcollectionregister | function |
| enableparbuilder | function | fontcollectionreport | function |
| enableregime | function | fontcollectionreset | function |
| enablespellchecking | function | fontlookupgetkey | function |
| enabletransparency | function | fontlookupgetkeyofindex | function |
| enhancelinkedlist | function | fontlookupinitialize | function |
| enhancelist | function | fontlookupnoffound | function |
| enhancereference | function | forceendjob | function |
| erasebuffer | function | forcequitjob | function |
| expandcurrentreference | function | format | function |
| exportformdata | function | formatcolor | function |
| exportreferences | function | formatgray | function |
| extensiblecode | function | freezerandomseed | function |
| feature | function | from | function |
| featureattribute | function | getbuffer | function |
| featurelist | function | getbuffercctxlua | function |
| feedback | function | getbuffermkvi | function |
| fetchallmarks | function | getcommandline | function |
| fetchmultipar | function | getctxfile | function |
| fetchmultishape | function | getcurrentprefixspec | function |
| fetchonemark | function | getcurrentreferencemetadata | function |
| fetchposboxes | function | getdefaultfieldvalue | function |
| fetchtwomarks | function | getfieldcategory | function |
| figurefilename | function | getfirstcharacter | function |
| figurefilepath | function | getfirsttwopassdata | function |
| figurefiletype | function | getfloatvariable | function |
| figurerequest | function | getinternalreference | function |
| figurestatus | function | getlasttwopassdata | function |
| figureused | function | getmarking | function |

| | | | |
|--------------------------------|----------|-----------------------------------|----------|
| getmessage | function | lastcountervalue | function |
| getmpextensions | function | lchexnumber | function |
| getnotestate | function | lchexnumbers | function |
| getprivateattribute | function | leapyear | function |
| getprivatechar | function | linenumbersstageone | function |
| getprogram | function | linenumbersstagetwo | function |
| getrandomcounta | function | listlabel | function |
| getrandomcountb | function | listlocation | function |
| getrandomseed | function | listprefixednumber | function |
| getreadfilename | function | listprefixedpage | function |
| getsubstring | function | listrealpage | function |
| gettexbuffer | function | listsize | function |
| gettwopassdata | function | listtitle | function |
| gettwopassdatalist | function | listuserdata | function |
| geturl | function | loadexamodes | function |
| grabbuffer | function | loadfontgoodies | function |
| helpaction | function | loadspellchecklist | function |
| helpreference | function | loadtypescriptfile | function |
| hexstringtonumber | function | loadvisualizer | function |
| horizontalcode | function | locatefilepath | function |
| hour | function | locfilename | function |
| hyphenatedlist | function | makeactive | function |
| hyphenatedurl | function | markfonts | function |
| D characters | | markregionbox | function |
| N lefthyphenmin | | mathrenderset | function |
| D mapping | | maxitemwidth | function |
| N righthyphenmin | | minute | function |
| F setcharacters | | mixcleanup | function |
| incrementedcounter | function | mixfinalize | function |
| initializetexdirectives | function | mixflushlist | function |
| initializetextrackers | function | mixflushrest | function |
| injectcurrentreference | function | mixgetsplitted | function |
| injectreference | function | mixsetsplitted | function |
| inlinechemical | function | mixstate | function |
| insertattachment | function | molecule | function |
| insertcomment | function | month | function |
| insertfield | function | monthmnem | function |
| insertionnumber | function | monthname | function |
| insertrenderingwindow | function | mpcolor | function |
| insertsoundclip | function | mpoptions | function |
| installedlanguages | function | namedstructureuservariable | function |
| installtexdirective | function | namedstructurevariable | function |
| installtextracker | function | nbfs | function |
| languagenumber | function | nextcountervalue | function |

| | | | |
|-----------------------------|----------|-----------------------------------|----------|
| nextparallel | function | processedfiles | function |
| nofdays | function | processfile | function |
| nofitems | function | processfilemany | function |
| nofstackedfloats | function | processfilenone | function |
| notedeltapage | function | processfileonce | function |
| notelistindex | function | processlist | function |
| notenumberpage | function | pushfloat | function |
| noteprefixednumber | function | pushitaliccorrection | function |
| notesymbolpage | function | pushlist | function |
| notetitle | function | pushregime | function |
| ntimes | function | pushsectionblock | function |
| number | function | rawcharacter | function |
| numbers | function | rawcountervalue | function |
| objectnumber | function | rawdate | function |
| objectpage | function | referencepagestate | function |
| octnumber | function | referencerealpage | function |
| octstringtonumber | function | registerattachment | function |
| ordinal | function | registerbibtexentry | function |
| overloadbookmark | function | registerbibtexfile | function |
| pagestaterealpage | function | registerbookmark | function |
| parpos | function | registerbuttons | function |
| pdfrotation | function | registercolor | function |
| percentageof | function | registercolorintent | function |
| pgfxcolorspec | function | registeredviewerlayer | function |
| placeparallel | function | registerhelp | function |
| popfloat | function | registeritemgroup | function |
| popitaliccorrection | function | registerlanguagefeatures | function |
| poplist | function | registerlinenumbering | function |
| popregime | function | registermaintextcolor | function |
| popsectionblock | function | registernamespace | function |
| pos | function | registerpostponedblock | function |
| posplus | function | registerrendering | function |
| posstrut | function | registersoundclip | function |
| postponenotes | function | registerstructureprocessor | function |
| poswhd | function | registertransparency | function |
| posxy | function | registerunit | function |
| prepareMPvariable | function | relatemarking | function |
| preparebibtexsession | function | remapentity | function |
| preparedfile | function | removemissingcharacters | function |
| presetsymbollist | function | renderingvar | function |
| presettabulate | function | replacemissingcharacters | function |
| prevcountervalue | function | replacepospxywhd | function |
| processbuffer | function | resavefloat | function |
| processedfile | function | resetcounter | function |

| | | | |
|---------------------------------|----------|---------------------------------|----------|
| resetfontfeature | function | setdocumentenvironments | function |
| resetfontsolution | function | setdocumentfilenames | function |
| resetmarking | function | setdocumentmodes | function |
| resetmathitalics | function | setdocumentmodules | function |
| resetnullfont | function | setfigurelookuporder | function |
| resetparallel | function | setfontfeature | function |
| resetreference | function | setfontofid | function |
| resetstructureprocessor | function | setfontsolution | function |
| resettimer | function | setformat | function |
| restartcounter | function | setformsmethod | function |
| restorecounter | function | setinsertionlocation | function |
| restorecurrentattributes | function | setinterfaceconstant | function |
| restorenote | function | setinterfaceelement | function |
| romannumerals | function | setinterfacemessage | function |
| runbuffer | function | setinterfacemessages | function |
| safechar | function | setinterfacevariable | function |
| savebuffer | function | setinternalreference | function |
| savecounter | function | setlanguageexceptions | function |
| savecurrentattributes | function | setlanguagesynonym | function |
| savedlistnumber | function | setlayer | function |
| savedlistprefixednumber | function | setmarking | function |
| savedlisttitle | function | setmathalphabet | function |
| savefloat | function | setmathalternate | function |
| savenote | function | setmathattribute | function |
| saveobject | function | setmathitalics | function |
| saveparallel | function | setmathstyle | function |
| savestructureblock | function | setnextinternalreference | function |
| savetaggedtwopassdata | function | setnotestate | function |
| savetwopassdata | function | setnotesymbolpage | function |
| second | function | setobject | function |
| selectstructureblock | function | setopendocumentaction | function |
| setbreakpoints | function | setopenpageaction | function |
| setcharactercasing | function | setowncounter | function |
| setcharactercleaning | function | setpagestate | function |
| setcharacterkerning | function | setpagestaterealpageno | function |
| setcharacterspacing | function | setpagetransition | function |
| setcharacterstripping | function | setparbuilder | function |
| setcloseddocumentaction | function | setpos | function |
| setclosepageaction | function | setrandomseed | function |
| setcolormodel | function | setrealign | function |
| setcounter | function | setreferencearguments | function |
| setdataset | function | setreferenceattribute | function |
| setdigitsmanipulation | function | setreferenceoperation | function |
| setdirection | function | setsectionblock | function |

| | | | |
|--------------------------------|----------|----------------------------------|----------|
| setstructureblockstate | function | startparbuilder | function |
| settagcombination | function | startproduct | function |
| settagdescription | function | startproject | function |
| settagdescriptionsymbol | function | startregime | function |
| settagfigure | function | startsectionlevel | function |
| settaghighlight | function | starttag | function |
| settagitemgroup | function | starttext | function |
| settagproperty | function | startviewerlayer | function |
| settagsorting | function | stopchemical | function |
| settagsynonym | function | stopcolorset | function |
| settagtablecell | function | stopcomponent | function |
| settagtabulatecell | function | stopenvironment | function |
| setupbookmarks | function | stopfontsolution | function |
| setupcanvas | function | stopparbuilder | function |
| setupcharacterspacing | function | stopproduct | function |
| setupexport | function | stopproject | function |
| setupfontexpansion | function | stopregime | function |
| setupfontprotrusion | function | stopsectionlevel | function |
| setupidentity | function | stoptag | function |
| setupinsertion | function | stoptext | function |
| setupitaliccorrection | function | stopviewerlayer | function |
| setuplinenumbering | function | storejavascriptcode | function |
| setvisual | function | storejavascriptpreamble | function |
| setxmpfile | function | storenote | function |
| showassignerror | function | structureautocatcodedget | function |
| showattributes | function | structurecatcodedget | function |
| showcallbacks | function | structuregivencatcodedget | function |
| showchardata | function | structurenumber | function |
| showcounter | function | structuretitle | function |
| showfontparameters | function | structureuservariable | function |
| showhyphenatedinlist | function | structurevariable | function |
| showjustification | function | subcountervalues | function |
| showmessage | function | synchronizecolormodel | function |
| sin | function | synchronizemarking | function |
| sind | function | taggedmathfunction | function |
| splitfilename | function | tan | function |
| spotcolorname | function | tand | function |
| spotcolorparent | function | testcase | function |
| spotcolorvalue | function | textime | function |
| startchemical | function | transparencycomponents | function |
| startcolorset | function | triggereffect | function |
| startcomponent | function | triggernegative | function |
| startenvironment | function | truefilename | function |
| startfontsolution | function | typebuffer | function |

| | | | |
|------------------------------|----------|-----------------------------------|----------|
| typefile | function | utfmathclass | function |
| typestring | function | utfmathcommand | function |
| uchexnumber | function | utfmathfiller | function |
| uchexnumbers | function | utfmathstretch | function |
| undefinechemical | function | verbose | function |
| unicodechar | function | visual | function |
| unit | function | vspacing | function |
| unloadlanguage | function | vspacingcollapse | function |
| useMPlibrary | function | vspacingdefine | function |
| useanyfile | function | vspacingsetamount | function |
| usecldfile | function | vspacingsnap | function |
| usecolors | function | way | function |
| usecomponent | function | weekday | function |
| useenvironment | function | weekdayname | function |
| usefile | function | widthofstring | function |
| usejavascriptpreamble | function | writestatus | function |
| usejavascriptscripts | function | x_table_cleanup | function |
| uselibrary | function | x_table_construct | function |
| useluafile | function | x_table_create | function |
| uselua module | function | x_table_flush | function |
| usemodules | function | x_table_init_construct | function |
| usepath | function | x_table_init_reflow_height | function |
| useproduct | function | x_table_init_reflow_width | function |
| useproject | function | x_table_next_row | function |
| usesubpath | function | x_table_reflow_height | function |
| usesymbols | function | x_table_reflow_width | function |
| usetexfile | function | x_table_set_construct | function |
| useurl | function | x_table_set_reflow_height | function |
| usxmlfile | function | x_table_set_reflow_width | function |
| usezipfile | function | year | function |
| utfchar | function | | |

containers (context)

cleannname function
content function
define function
is_usable function

is_valid function
read function
usecache boolean
write function

converters (context)

| | | | |
|---------------------------|----------|--------------------------|------------|
| Alphabetic | function | minute | function |
| Character | function | month | function |
| Characters | function | nofdays | function |
| Romannumerals | function | number | function |
| abjadnodotnumerals | function | numbers | function |
| abjadnumerals | function | octnumber | function |
| alphabetic | function | octstringtonumber | function |
| character | function | ordinal | function |
| characters | function | rawcharacter | function |
| chineseallnumerals | function | romannumerals | function |
| chinesecapnumerals | function | second | function |
| chinesenumerals | function | sequences | data table |
| chr | function | textime | function |
| chrs | function | toabjad | function |
| convert | function | tochinese | function |
| define | function | toroman | function |
| hexstringtonumber | function | uchexnumber | function |
| hour | function | uchexnumbers | function |
| isleapyear | function | verbose | table |
| lchexnumber | function | D data | |
| lchexnumbers | function | F translate | |
| leapyear | function | weekday | function |
| maxchrs | function | year | function |

coroutine (basic lua)

create function
resume function
running function

status function
wrap function
yield function

ctxrunner (context)

| | | | |
|------------------|------------|----------------|----------|
| load | function | resolve | function |
| prepfiler | data table | | |

debug (basic lua)

| | | | |
|---------------------|----------|---------------------|----------|
| debug | function | sethook | function |
| gethook | function | setlocal | function |
| getinfo | function | setmetatable | function |
| getlocal | function | setupvalue | function |
| getmetatable | function | setuservalue | function |
| getregistry | function | traceback | function |
| getupvalue | function | upvalueid | function |
| getuservalue | function | upvaluejoin | function |

dir (context)

| | |
|-----------------------|----------|
| collectpattern | function |
| current | function |
| expandname | function |
| glob | function |
| globfiles | function |
| globpattern | function |

| | |
|-----------------|----------|
| ls | function |
| makedirs | function |
| makedirs | function |
| pop | function |
| push | function |

directives (context)

| | | | |
|----------------|------------|-----------------|----------|
| data | data table | name | string |
| default | function | register | function |
| disable | function | report | function |
| enable | function | show | function |
| list | function | value | function |

document (context)

| | | | |
|--------------------|------------|---------------------------|------------|
| arguments | data table | T ctxfile | |
| files | table | D environments | |
| getargument | function | D modes | |
| getfilename | function | D modules | |
| options | table | setargument | function |
| T cmdline | | setdefaultargument | function |
| D environments | | setfilename | function |
| D modes | | variables | data table |
| D modules | | | |

environment (context)

| | | | |
|----------------------------|------------|-------------------------------|------------|
| argument | function | luafile | function |
| arguments | data table | luafilechunk | function |
| basicengines | data table | maxnofruns | number |
| currentrun | number | originalarguments | data table |
| default_texmfcnf | string | outputfilename | string |
| engineflags | data table | ownbin | string |
| filename | string | ownmain | string |
| files | table | ownname | string |
| filesynonyms | data table | ownpath | string |
| getargument | function | rawarguments | data table |
| homedir | string | reconstructcommandline | function |
| initex | boolean | setargument | function |
| initializearguments | function | splitarguments | function |
| initializefilenames | function | suffix | string |
| inputfilebarename | string | texfile | function |
| inputfilename | string | texmfos | string |
| inputfilesuffix | string | texos | string |
| jobfilename | string | texroot | string |
| jobfilesuffix | string | truefilename | function |
| kindofrun | number | validengines | data table |
| loadluafile | function | | |

epdf (extra tex)

Array function
Dict function
Object function

PDFRectangle function
open function
type function

experiments (context)

| | | | |
|----------------|------------|-----------------|----------|
| data | data table | name | string |
| default | function | register | function |
| disable | function | report | function |
| enable | function | show | function |
| list | function | value | function |

figures (context)

| | | | |
|----------------------|------------|-------------------------|------------|
| applyratio | function | includes | data table |
| bitmapimage | function | initialize | function |
| boxnumber | number | loaded | data table |
| cachepaths | data table | localpaths | data table |
| check | function | magics | data table |
| checkers | data table | mergegoodies | function |
| converters | data table | nofprocessed | number |
| current | function | order | data table |
| defaultdepth | number | paths | data table |
| defaultheight | number | patterns | data table |
| defaultsearch | boolean | pop | function |
| defaultwidth | number | preferquality | boolean |
| done | function | programs | data table |
| dummy | function | push | function |
| exists | data table | registerpattern | function |
| exists | function | registerresource | function |
| formats | data table | registersuffix | function |
| found | data table | resources | data table |
| get | function | scale | function |
| guess | function | setlookups | function |
| hash | function | setorder | function |
| identifiers | data table | setpaths | function |
| identify | function | suffixes | data table |
| include | function | used | data table |

file (basic lua)

| | |
|--------------------------|----------|
| addsuffix | function |
| basename | function |
| checksum | function |
| collapsepath | function |
| copy | function |
| dirname | function |
| expandname | function |
| extname | function |
| is_qualified_path | function |
| is_readable | function |
| is_rootbased_path | function |
| is_writable | function |
| isreadable | function |
| iswritable | function |
| join | function |
| joinpath | function |
| loadchecksum | function |
| nameonly | function |
| nametotable | function |

| | |
|-----------------------|----------|
| needs Updating | function |
| needsupdating | function |
| pathpart | function |
| readdata | function |
| removesuffix | function |
| replacesuffix | function |
| reslash | function |
| robustname | function |
| savechecksum | function |
| savedata | function |
| size | function |
| splitbase | function |
| splitname | function |
| splitpath | function |
| strip | function |
| suffix | function |
| suffixonly | function |
| syncmtimes | function |

floats (context)

| | | | |
|-------------------------|----------|-------------------|----------|
| analysemethod | function | nofstacked | function |
| checkedpagefloat | function | pop | function |
| collect | function | push | function |
| consult | function | resave | function |
| flush | function | save | function |
| getvariable | function | stacked | function |

font (basic tex)

current function
define function
each function
fonts table
frozen function
getfont function

id function
max function
nextid function
read_tfm function
read_vf function
setfont function

fontloader (extra tex)

| | | | |
|--------------------------|----------|-----------------|----------|
| apply_afmfile | function | info | function |
| apply_featurefile | function | open | function |
| close | function | to_table | function |
| fields | function | totable | function |
| fullinfo | function | | |

fonts (context)

| | | |
|--------------------------|-------|---------------------------|
| analyzers | table | |
| T features | | B autocleanup |
| N fina | | F beforecopyingcharacters |
| N init | | D cache |
| N isol | | F calculatescale |
| N medi | | F checkedfeatures |
| D initializers | | F checkedfilename |
| D methods | | F cleanup |
| F setstate | | F collectprocessors |
| T states | | D designsizes |
| N blwf | | D dontembed |
| N fina | | F enhanceparameters |
| N half | | N factor |
| N init | | F finalize |
| N isol | | F getfeatureaction |
| N mark | | F hashfeatures |
| N medi | | F hashinstance |
| N pref | | T hashmethods |
| N pstf | | F normal |
| N rest | | F virtual |
| N rphf | | F initializefeatures |
| B useunicodemarks | | T keys |
| checkers | table | T character |
| F missing | | S depth |
| cid | table | S height |
| F getmap | | S italic |
| F loadfile | | S width |
| collections | table | T description |
| F clonevector | | T boundingbox |
| F define | | S depth |
| T definitions | | S height |
| F prepare | | S width |
| F process | | T parameters |
| F registermain | | S ascender |
| F report | | S descender |
| F reset | | S designsize |
| T vectors | | T expansion |
| constructors | table | S auto |
| F aftercopyingcharacters | | S shrink |
| F applymanipulators | | S step |
| F assignmathparameters | | S stretch |
| | | S extendfactor |

| | | |
|--------------------------|-----------------------|----------|
| S factor | S mathitalics | |
| S hfactor | S mode | |
| S mathsize | S name | |
| T protrusion | S noglyphnames | |
| S auto | S nostackmath | |
| S quad | S psname | |
| S scaledpoints | S textitalics | |
| S scriptpercentage | S virtualized | |
| S scriptscriptpercentage | D loadedfonts | |
| S size | S namemode | |
| S slantfactor | F newfeatures | |
| S slantperpoint | F newhandler | |
| T spacing | N privateoffset | |
| S extra | F readanddefine | |
| S shrink | F registerfeature | |
| S stretch | B resolvevirtualtoo | |
| S width | F scale | |
| T synonyms | F scaled | |
| S em | F setfactor | |
| S ex | F setname | |
| S extra_space | N version | |
| S extraspace | current | function |
| S slant | currentid | function |
| S space | definers | table |
| S space_shrink | F addlookup | |
| S space_stretch | F analyze | |
| S spaceshrink | F applypostprocessors | |
| S spacestretch | F checkedmode | |
| S x_height | F checkedscript | |
| S units | F current | |
| S vfactor | S defaultlookup | |
| S xheight | F define | |
| T properties | F getspecification | |
| S autoitalicamount | F loadfont | |
| T cidinfo | F makespecification | |
| S embedding | T methods | |
| S encodingbytes | F install | |
| S filename | D variants | |
| S finalized | F read | |
| S fontname | F register | |
| S format | F registered | |
| S fullname | F registersplit | |
| S hasitalics | F resetnullfont | |
| S hasmath | F resolve | |

- T resolvers
- F file
- F name
- F spec

definetypeface function

encodings table

- T agl
- D cache
- F is_known
- D known
- F load
- F make_unicode_vector
- D math
- N version

expansions data table

formats data table

goodies table

- D colorschemes
- D data
- D designsizes
- D filenames
- F getcompositions
- T list
- F compositions
- F designsizes
- F expansions
- F featureset
- F filenames
- F files
- F mathematics
- F protrusions
- F solutions
- F typefaces
- F load
- F prepare_features
- F register
- F registerpostprocessor
- F report

handlers table

- T afm
- B addkerns
- B addligatures
- B addtexligatures
- B autoprefixed

- D cache
- D features
- T helpdata
- D bothkerned
- D leftkerned
- D ligatures
- D rightkerned
- D texligatures

- F load
- F setfeatures
- B syncspace
- N version

T otf

- F addfeature
- D cache
- T chainhandlers
- F normal
- F verbose

- F collectlookups
- F dataset
- S defaultbasealternate
- S defaultnodealternate

- D enhancers
- D features

- F getalternate

- T glists

- T handlers

- F contextchain
- F devanagari_remove_joiners
- F devanagari_reorder_matras
- F devanagari_reorder_pre_base_reordering_consonants
- F devanagari_reorder_reph

- F gpos_context
- F gpos_contextchain
- F gpos_cursive
- F gpos_mark2base
- F gpos_mark2ligature

- F gpos_mark2mark
- F gpos_pair
- F gpos_single

- F gsub_alternate
- F gsub_context
- F gsub_contextchain
- F gsub_ligature

- F gsub_multiple
- F gsub_reversecontextchain
- F gsub_single
- F load
- F scriptandlanguage
- F setcontextchain
- F setdynamics
- F setfeatures
- T statistics
 - D usedfeatures
- T tables
 - D baselines
 - D features
 - D languages
 - D scripts
- N version
- T pfb
- T tfm
 - D features
 - F setfeatures
- T vf
 - T combinations
 - F combine
 - T combiner
 - D commands
 - F find
 - D helpers
 - D math
 - D predefined
 - D whatever

hashes table

- D characters
- D csnames
- D descriptions
- T dynamics
- D emwidths
- D exheights
- D extensibles
- D identifiers
- D italics
- D lastmathids
- D marks
- D parameters
- T processes

- D properties
- D quads
- D resources
- T setdynamics
- D xheights

helpers table

- F addprivate
- F dimenfactor
- F fontpatternhassize
- F getdigitwidth
- F getparameters
- F getprivatenode
- F hasprivate
- F nametoslot
- F setdigitwidth
- F splitfontpattern

iterators table

- F characters
- F descriptions
- F glyphs

loggers table

- T category_to_placeholder
- S ll
- S lm
- S lo
- S lt
- S lu
- S mc
- S me
- S mn
- S nd
- S nl
- S no
- S pc
- S pd
- S pe
- S pf
- S pi
- S po
- S ps
- S sc
- S sk
- S sm
- S so

| | |
|-----------------------|--------------------|
| F format | F pfb |
| F onetimemessage | D sequence |
| F register | F tfm |
| F reportdefinedfonts | F ttc |
| F reportusedfeatures | F ttf |
| mappings | specifiers |
| | table |
| F addtounicode | D contextmerged |
| F fromunicode16 | F contextnumber |
| F loadfile | D contextnumbers |
| F loadline | D contextsetups |
| F loadlumtable | F contextttoString |
| F makenameparser | F definecontext |
| F reset | F mergecontext |
| F tounicode16 | F presetcontext |
| F tounicode16sequence | F registercontext |
| names | F showcontext |
| | F splitcontext |
| protrusions | D synonyms |
| | D variants |
| readers | symbols |
| | table |
| F afm | F uselibrary |
| F check_lua | tables |
| F check_tfm | table |
| F dfont | tracers |
| F lua | table |
| F opentype | typefaces |
| F otf | data table |

functions (context)

dummy function

graphics (context)

backgrounds table

F calculatemultipar

F fetchmultipar

F pair

F path

F point

gzip (extra lua)

close function

lines function

open function

img (basic tex)

| | |
|-----------------------|----------|
| boxes | function |
| check | function |
| checksize | function |
| clone | function |
| copy | function |
| immediatewrite | function |
| keys | function |
| new | function |
| node | function |

| | |
|------------------|----------|
| ofindex | function |
| package | function |
| print | function |
| scan | function |
| serialize | function |
| totable | function |
| types | function |
| write | function |

interactions (context)

attachments table

F insert
F register

fields table

F clone
F define
F defineset
F insert

general table

F getidentity
F setupidentity

help table

F collect
F reference
F register

javascripts table

F addtopreamble
F code
D codes
F flushpreambles
D functions
D preambles

F setpreamble
F storecode
F storepreamble
F usepreamblenow
F usescripts

linkedlists table

pages table

F setpagetransition
F setupcanvas

references table

F setclosedocument
F setclosepage
F setopendocument
F setopenpage

renderings table

F register
F rendering
F var

soundclips table

F insert
F register

interfaces (context)

| | |
|-----------------------------|------------|
| addvalidkeys | function |
| cachedsetups | data table |
| cachesetup | function |
| complete | data table |
| constants | data table |
| corenamespaces | data table |
| definecommand | function |
| doifelsemessage | function |
| elements | data table |
| formats | data table |
| getcheckedparameters | function |
| getmessage | function |
| hashedsetups | data table |
| interfacedcommand | function |
| interfaces | table |
| invalidkey | function |
| is_command | function |
| namespaces | table |

F define

F list

| | |
|--------------------------|------------|
| registernamespace | function |
| setconstant | function |
| setelement | function |
| setformat | function |
| setmessage | function |
| setmessages | function |
| settranslation | function |
| setuserinterface | function |
| setvalidkeys | function |
| setvariable | function |
| showmessage | function |
| syntax | data table |
| tolist | function |
| translations | data table |
| variables | data table |

io (basic lua)

| | |
|----------------------|----------|
| ask | function |
| bytes | function |
| characters | function |
| close | function |
| exists | function |
| fileseparator | string |
| flush | function |
| i_limiter | function |
| i_limiters | table |
| T paranoid | |
| input | function |
| limiter | function |
| lines | function |
| loadchunk | function |
| loaddata | function |
| loadlines | function |
| noflines | function |
| o_limiter | function |

| | |
|----------------------|---------------------|
| o_limiters | table |
| T paranoid | |
| open | overloaded function |
| output | function |
| pathseparator | string |
| popen | overloaded function |
| read | function |
| readall | function |
| readnumber | function |
| readstring | function |
| savedata | function |
| size | function |
| stderr | userdata |
| stdin | userdata |
| stdout | userdata |
| tmpfile | function |
| type | function |
| write | function |

job (context)

| | |
|-----------------|----------|
| comment | function |
| datasets | table |
| D collected | |
| F extend | |
| F getdata | |
| F setdata | |
| D tobesaved | |

| | |
|--------------------|----------|
| disablesave | function |
| files | table |
| D collected | |
| F context | |
| B forcerun | |
| F run | |
| D tobesaved | |

| | |
|-------------------|----------|
| initialize | function |
| load | function |
| loadother | function |
| objects | table |
| D collected | |
| F get | |
| F number | |
| F page | |
| F save | |
| F set | |
| D tobesaved | |

| | |
|-------------------|---------|
| pack | boolean |
| pagestates | table |
| D collected | |
| F extend | |
| F realpage | |
| F setstate | |
| D tobesaved | |

| | |
|----------------|-------|
| passes | table |
| F check | |
| D collected | |
| F count | |
| F define | |
| F find | |
| F first | |
| F get | |
| F getcollected | |

| | |
|------------------|-------|
| F getdata | |
| F getfield | |
| F gettobesaved | |
| F inlist | |
| F last | |
| F list | |
| F save | |
| F savetagged | |
| D tobesaved | |
| positions | table |
| F b_col | |
| F b_region | |
| F c | |
| D collected | |
| F column | |
| F copy | |
| F depth | |
| F e_col | |
| F e_region | |
| F enhance | |
| F extra | |
| F get | |
| F getreserved | |
| F hangafter | |
| F hangindent | |
| F height | |
| F hsize | |
| F leftskip | |
| F lowerleft | |
| F lowerright | |
| F markregionbox | |
| F n | |
| F onsamepage | |
| F overlapping | |
| F p | |
| F page | |
| F paragraph | |
| F parindent | |
| F position | |
| F r | |
| F region | |

F replace
F rightskip
F set
F setall
F setdim
D tobesaved
F upperleft
F upperright
F width
F x
F xy
F y
register function
save function

structure table
D collected
T components
T tobesaved
T branches
S name
S type
variables table
D checksums
D collected
F save
D tobesaved
version string

lang (basic tex)

| | |
|--------------------------|----------|
| clean | function |
| clear_hyphenation | function |
| clear_patterns | function |
| exceptions | function |
| hyphenate | function |
| hyphenation | function |
| id | function |

| | |
|-------------------------|----------|
| new | function |
| patterns | function |
| postexhyphenchar | function |
| posthyphenchar | function |
| preexhyphenchar | function |
| prehyphenchar | function |

languages (context)

| | | | |
|----------------------|------------|-----------------------|------------|
| associate | function | posthyphenchar | function |
| associated | data table | prehyphenchar | function |
| association | function | registered | data table |
| counters | data table | righthyphenmin | function |
| current | function | setexceptions | function |
| data | data table | setsynonym | function |
| define | function | unload | function |
| getnumber | function | version | number |
| hyphenate | function | words | table |
| installed | function | | |
| labels | table | | |
| F define | | F check | |
| F split | | T data | |
| lefthyphenmin | function | F disable | |
| loadable | function | F enable | |
| loadwords | function | T enablers | |
| logger | table | B enables | |
| F report | | F found | |
| numbers | data table | F load | |
| | | T methods | |
| | | N threshold | |

layouts (context)

| | | |
|---------------|--------------|------------------------|
| status | table | F leftorrightpagection |
| | F isleftpage | |

lfs (extra lua)

| | | | |
|-------------------|---------------------|--------------------------|----------|
| attributes | function | mkdir | function |
| chdir | function | readlink | function |
| currentdir | function | rmdir | function |
| dir | function | setmode | function |
| isdir | overloaded function | shortname | function |
| isfile | function | symlinkattributes | function |
| lock | function | touch | function |
| lock_dir | function | unlock | function |

libraries (context)

basiclua data table
basictex data table
builtin data table
extralua data table

extratex data table
functions data table
globals data table

lmx (context)

| | |
|--------------------------|----------|
| color | function |
| convert | function |
| convertfile | function |
| convertstring | function |
| einject | function |
| eprint | function |
| escape | function |
| finalized | function |
| finject | function |
| fprint | function |
| get | function |
| getvariables | function |
| htmfile | function |
| html | table |
| F a | |
| F td | |
| F th | |
| include | function |
| inherited | table |
| S color-background-four | |
| S color-background-one | |
| S color-background-three | |
| S color-background-two | |
| S title | |
| initialize | function |
| inject | function |
| lmxfile | function |

| | |
|---------------------------|----------|
| loadedfile | function |
| new | function |
| overloaderror | function |
| popupfile | function |
| print | function |
| pv | function |
| report | function |
| reset | function |
| result | function |
| set | function |
| show | function |
| showdebuginfo | function |
| showerror | function |
| stripcss | function |
| tv | function |
| type | function |
| urlescape | function |
| variable | function |
| variables | table |
| S color-background-blue | |
| S color-background-body | |
| S color-background-green | |
| S color-background-main | |
| S color-background-purple | |
| S color-background-yellow | |
| S title-default | |

logs (context)

| | | | |
|---------------------|----------|--------------------------|----------|
| application | function | setmessenger | function |
| categories | function | setprogram | function |
| direct | function | settarget | function |
| disable | function | settranslations | function |
| enable | function | show | function |
| extendbanner | function | show_close | function |
| flush | function | show_load | function |
| help | function | show_open | function |
| messenger | function | simple | function |
| new | function | simpleline | function |
| newline | function | simplelines | function |
| poptarget | function | start_page_number | function |
| pushtarget | function | status | function |
| report | function | stop_page_number | function |
| reportbanner | function | subdirect | function |
| reporter | function | subreport | function |
| reportline | function | system | function |
| reportlines | function | texerrormessage | function |
| setformats | function | writer | function |

lpdf (context)

| | | | |
|-------------------------------|------------|----------------------------------|----------|
| action | function | id | function |
| adddocumentcolorspace | function | injectxmpinfo | function |
| adddocumenttextgstate | function | insertxmpinfo | function |
| adddocumentpattern | function | javascript | function |
| adddocumentshade | function | launch | function |
| addtocatalog | function | layerreference | function |
| addtoinfo | function | limited | function |
| addtonames | function | linearshade | function |
| addtopageattributes | function | link | function |
| addtopageresources | function | null | function |
| addtopagesattributes | function | number | function |
| addxmpinfo | function | pagedestination | function |
| array | function | pagereference | function |
| boolean | function | pdfcolor | function |
| checkedkey | function | pdftimestamp | function |
| checkedvalue | function | protectresources | boolean |
| circularshade | function | reference | function |
| cmykcode | function | registerannotation | function |
| collectedresources | function | registerdocumentfinalizer | function |
| color | function | registerpagefinalizer | function |
| colorspace | function | reserveannotation | function |
| colorspaceconstants | data table | reserveobject | function |
| colorspec | function | rgbcode | function |
| colorvalue | function | rotationcm | function |
| colorvalues | function | shareobject | function |
| constant | function | shareobjectreference | function |
| delayedobject | function | spotcode | function |
| dictionary | function | stream | function |
| epdf | table | string | function |
| F expand | | timestamp | function |
| F load | | toeight | function |
| finalizedocument | function | tosixteen | function |
| finalizepage | function | transparency | function |
| finishtransparencycode | function | transparencycode | function |
| flushobject | function | transparencygroups | table |
| flushstreamfileobject | function | B none | |
| flushstreamobject | function | transparencyvalue | function |
| formats | data table | unicode | function |
| graycode | function | verbose | function |

lpeg (basic lua)

| | | | |
|---------------------|----------|------------------------------|------------|
| B | function | finder | function |
| C | function | firstofsplit | function |
| Carg | function | frontstripper | function |
| Cb | function | instringchecker | function |
| Cc | function | is_lpeg | function |
| Cf | function | keeper | function |
| Cg | function | locale | function |
| Cmt | function | match | function |
| Cp | function | oneof | function |
| Cs | function | patterns | data table |
| Ct | function | print | function |
| P | function | replacer | function |
| R | function | secondofsplit | function |
| S | function | setmaxstack | function |
| UP | function | split | function |
| UR | function | splitat | function |
| US | function | splitter | function |
| V | function | stripper | function |
| anywhere | function | times | function |
| append | function | tsplitat | function |
| balancer | function | tsplitter | function |
| checkedsplit | function | type | function |
| counter | function | utfchartabletopattern | function |
| endstripper | function | version | function |

ltn12 (extra lua)

BLOCKSIZE number

filter table

F chain

F cycle

pump table

F all

F step

sink table

F chain

F error

F file

F null

F simplify

F table

source table

F cat

F chain

F empty

F error

F file

F rewind

F simplify

F string

lua (basic tex)

| | | | |
|-----------------------|------------|--------------------------|------------|
| bytecode | table | messages | data table |
| bytedata | data table | name | table |
| bytdone | table | numbers | data table |
| collectgarbage | function | registercode | function |
| delay | function | registeredcodes | function |
| finalize | function | registerfinalizer | function |
| firstbytecode | number | registername | function |
| flush | function | setbytecode | function |
| flushdelayed | function | setluaname | function |
| getbytecode | function | startupfile | string |
| getluaname | function | version | string |
| lastbytecode | number | | |

luatex (context)

| | | | |
|-----------------------------|----------|-------------------------|----------|
| cleanuptempfiles | function | registertempfile | function |
| registerstartactions | function | starttime | number |
| registerstopactions | function | | |

lxml (context)

| | |
|------------------------|------------|
| addindex | function |
| all | function |
| applyfunction | function |
| att | function |
| attribute | function |
| chainattribute | function |
| checkindex | function |
| collected | function |
| command | function |
| concat | function |
| concatrange | function |
| content | function |
| context | function |
| convert | function |
| count | function |
| delete | function |
| direct | function |
| directives | table |
| F after | |
| F before | |
| F handle | |
| F load | |
| F setup | |
| displayverbatim | function |
| doif | function |
| doifelse | function |
| doifsetext | function |
| doifnot | function |
| doifnottext | function |
| doiftext | function |
| element | function |
| elements | function |
| entities | data table |
| filter | function |
| filterlist | function |
| first | function |
| flush | function |
| flushlinewise | function |
| flushsetups | function |
| flushspacewise | function |
| get_id | function |

| | |
|-------------------------|----------|
| getid | function |
| getindex | function |
| id | function |
| idsplitter | userdata |
| include | function |
| index | function |
| info | function |
| inlineverbatim | function |
| installsetup | function |
| last | function |
| load | function |
| loadbuffer | function |
| loaddata | function |
| loaded | table |
| loadregistered | function |
| main | function |
| match | function |
| name | function |
| namespace | function |
| nonspace | function |
| pos | function |
| position | function |
| raw | function |
| rawroot | function |
| register | function |
| registerentity | function |
| removesetup | function |
| resetcdata | function |
| resetsetups | function |
| resolvedentity | function |
| root | function |
| serialize | function |
| setaction | function |
| setcdata | function |
| setcommandtonone | function |
| setcommandtotext | function |
| setsetup | function |
| snippet | function |
| sorters | table |
| F add | |
| F compare | |

| | | | |
|-----------------|----------|----------------------|------------|
| F flush | | stripped | function |
| F reset | | tag | function |
| F show | | text | function |
| F sort | | tofile | function |
| splitid | function | toparameters | function |
| startraw | function | toverbatim | function |
| stopraw | function | verbatim | function |
| store | function | withinindex | function |
| strip | function | xmltexhandler | data table |

math (basic lua)

| | | | |
|--------------------|----------|-----------------------|----------|
| abs | function | log10 | function |
| acos | function | max | function |
| asin | function | min | function |
| atan | function | mod | function |
| atan2 | function | modf | function |
| ceil | function | odd | function |
| cos | function | pi | number |
| cosd | function | pow | function |
| cosh | function | rad | function |
| deg | function | random | function |
| div | function | randomseed | function |
| even | function | round | function |
| exp | function | setrandomseedi | function |
| floor | function | sin | function |
| fmod | function | sind | function |
| frexp | function | sinh | function |
| huge | number | sqrt | function |
| initialseed | number | tan | function |
| ldexp | function | tand | function |
| log | function | tanh | function |

mathematics (context)

| | | | |
|-------------------------------|------------|-------------------------------|------------|
| addfallbacks | function | makefont | function |
| alphabets | data table | mapremap | data table |
| big | function | overloadparameters | function |
| boldmap | table | privatebase | number |
| categories | table | remapalphabets | function |
| D functions | | renderings | table |
| checkaccentbaseheight | function | D mappings | |
| checkprivateparameters | function | D numbers | |
| classes | data table | D sets | |
| codes | data table | renderset | function |
| define | function | resetitalics | function |
| dimensions | function | scaleparameters | function |
| extensiblecode | function | setalternate | function |
| extensibles | data table | setitalics | function |
| extrabase | number | syncboth | function |
| extras | table | syncname | function |
| F add | | syncstyle | function |
| F copy | | toname | function |
| fallbacks | table | tostyle | function |
| F apply | | tweakaftercopyingfont | function |
| F install | | tweakbeforecopyingfont | function |
| fallbackstyleattr | function | tweaks | table |
| families | data table | F fixbadprime | |
| gaps | table | utfmathclass | function |
| getboth | function | utfmathcommand | function |
| getstyle | function | utfmathfiller | function |
| initializeparameters | function | utfmathstretch | function |

mbox (context)

| | |
|----------------------|----------|
| parse | function |
| parse_from | function |
| parse_header | function |
| parse_headers | function |

| | |
|----------------------|----------|
| parse_message | function |
| split_headers | function |
| split_mbox | function |
| split_message | function |

md5 (extra lua)

HEX function

crypt function

dec function

decrypt function

exor function

hex function

sum function

sumhexa function

metapost (context)

| | | | |
|---------------------------|------------|-----------------------|----------|
| analyzeplugins | function | lastlog | string |
| checkformat | function | load | function |
| checktexts | function | makempy | table |
| collapse | boolean | N nofconverted | |
| colorinitializer | function | F processgraphics | |
| convert | function | metafun | table |
| defaultformat | string | F interpolate | |
| defaultinstance | string | F topath | |
| defaultmethod | string | method | number |
| directrun | function | mptopdf | table |
| edefsxsy | function | F convertmpstopdf | |
| escaped | function | N nofconverted | |
| exectime | table | multipass | boolean |
| extensiondata | data table | n | number |
| filterclippath | function | optimize | boolean |
| finder | function | parse | function |
| flush | function | pdfliterals | function |
| flushers | table | pluginactions | function |
| T pdf | | process | function |
| F comment | | processplugins | function |
| F flushfigure | | reducetogray | boolean |
| F startfigure | | reporterror | function |
| F stopfigure | | reset | function |
| F textfigure | | resetlastlog | function |
| flushliteral | function | resetplugins | function |
| flushnormalpath | function | resettexttexts | function |
| flushreset | function | setextensions | function |
| format | function | setoutercolor | function |
| formatnumber | function | settext | function |
| getclippath | function | showlog | boolean |
| getextensions | function | tex | table |
| gettext | function | F get | |
| graphic | function | F reset | |
| graphic_base_pass | function | F set | |
| graphic_extra_pass | function | texerrors | boolean |
| instance | function | texttextsdata | function |
| intermediate | table | theclippath | function |
| T actions | | totable | function |
| F makempy | | unload | function |
| B needed | | | |

mime (extra lua)

b64 function

decode function

decodet table

F base64

F quoted-printable

dot function

encode function

encodet table

F base64

F quoted-printable

eol function

normalize function

qp function

qpwrp function

stuff function

unb64 function

unqp function

wrap function

wrapt table

F base64

F default

F quoted-printable

F text

wrp function

mplib (extra tex)

| | | | |
|----------------|----------|---------------------|----------|
| fields | function | pen_info | function |
| finders | table | preprocessed | function |
| F file | | version | function |
| new | function | | |

noads (context)

handlers table

- F check
- F collapse
- F families
- F italics
- F relocate
- F render
- F resize
- F tags
- F unscript

F variants

process function

processors table

- T collapse
- F mlist_to_hlist
- T relocate
- T render
- T resize
- T unscript

node (basic tex)

| | | | |
|------------------------|----------|-----------------------------|----------|
| copy | function | ligaturing | function |
| copy_list | function | mlist_to_hlist | function |
| count | function | new | function |
| current_attr | function | next | function |
| dimensions | function | prev | function |
| do_ligature_n | function | protect_glyphs | function |
| family_font | function | protrusion_skippable | function |
| fields | function | remove | function |
| first_character | function | set_attribute | function |
| first_glyph | function | slide | function |
| flush_list | function | subtype | function |
| free | function | tail | function |
| has_attribute | function | traverse | function |
| has_field | function | traverse_id | function |
| hpack | function | type | function |
| id | function | types | function |
| insert_after | function | unprotect_glyphs | function |
| insert_before | function | unset_attribute | function |
| is_node | function | usedlist | function |
| kerning | function | vpack | function |
| last_node | function | whatsits | function |
| length | function | write | function |

nodes (context)

| | | | |
|-------------------------------|------------|--------------------------------|------------|
| after | function | F cleanuppage | |
| aligned | function | F export | |
| astable | function | F finalize | |
| before | function | F migrate | |
| builders | table | F protectglyphs | |
| F buildpage_filter | | F stripping | |
| F vpack_filter | | F unprotectglyphs | |
| codes | data table | has_attribute | function |
| concat | function | idstosting | function |
| count | function | ignorablefields | data table |
| delete | function | injections | table |
| destinations | table | F handler | |
| N attribute | | F installnewkern | |
| T done | | F setcursive | |
| F handler | | F setkern | |
| T stack | | F setmark | |
| | | F setpair | |
| dimensionfields | data table | installattributehandler | function |
| dir_is_pop | data table | is_display_math | function |
| dir_negation | data table | is_mirrored | data table |
| disccodes | data table | is_rotated | data table |
| discretionarycodes | data table | kerncodes | data table |
| endofmath | function | leftmarginwidth | function |
| fasthpack | function | lines | table |
| fields | function | T boxed | |
| fillcodes | data table | F register | |
| firstcharacter | function | F setup | |
| firstcharinbox | function | F stage_one | |
| firstglyph | function | F stage_two | |
| getattribute | function | F stage_zero | |
| gluecodes | data table | D data | |
| glyphcodes | data table | F finalize | |
| glyphdir_is_equal | data table | F number | |
| glyphdir_is_opposite | data table | N scratchbox | |
| glyphdir_is_orthogonal | data table | link | function |
| handlers | table | list | function |
| F accessibility | | listablefields | data table |
| F alignbackgrounds | | listcodes | data table |
| F backgrounds | | listtutf | function |
| F characters | | load | function |
| F checkforleaks | | locate | function |
| F checkglyphs | | | |

| | | | |
|----------------------------|------------|---------------------------|----------|
| margincodes | data table | F usage | |
| markers | table | T userids | |
| F get | | N margins.inline | |
| mathcodes | data table | N splitters.one | |
| noadcodes | data table | N splitters.two | |
| nodecodes | data table | F userlist | |
| packlist | function | F usernumber | |
| pardir_is_equal | data table | F userstring | |
| pardir_is_opposite | data table | F usertokens | |
| pardir_is_parallel | data table | F vlist | |
| partextdir_is_equal | data table | F zeroglue | |
| penaltycodes | data table | print | function |
| pool | table | processors | table |
| F baselineskip | | B enabled | |
| F cleanup | | F hpack_filter | |
| F disc | | F post_linebreak_filter | |
| F fontkern | | F pre_linebreak_filter | |
| F glue | | F tracer | |
| F gluespec | | processwords | function |
| F glyph | | reference | function |
| F hlist | | references | table |
| F kern | | N attribute | |
| F latelua | | T done | |
| F leftmarginkern | | F handler | |
| F leftskip | | T stack | |
| F lineskip | | remove | function |
| F noad | | repackhlist | function |
| F pdfannotation | | replace | function |
| F pdfdestination | | report | function |
| F pdfdirect | | rightmarginwidth | function |
| F pdfliteral | | rules | table |
| F pdfrestore | | D data | |
| F pdfsave | | F define | |
| F pdfsetmatrix | | F enable | |
| F penalty | | F handler | |
| F register | | save | function |
| F rightmarginkern | | serialize | function |
| F rightskip | | serializebox | function |
| F rule | | setattribute | function |
| F shrink | | setattributes | function |
| F special | | setunsetattributes | function |
| F stretch | | shifts | table |
| F temp | | D data | |
| F textdir | | F define | |

| | | | |
|----------------------------|------------|------------------------|------------|
| F enable | | F collect | |
| F handler | | F equal | |
| show | function | F indices | |
| showboxes | function | F start | |
| showcodes | function | F string | |
| showlist | function | F unicodes | |
| showsimplelist | function | T colors | |
| skipcodes | data table | F reset | |
| snapshots | table | F set | |
| F getparameters | | F setlist | |
| F getsamples | | F fontchar | |
| F resetsamples | | T frequencies | |
| F takesample | | F register | |
| somepenalty | function | F start | |
| somespace | function | T steppers | |
| stripping | table | F check | |
| T glyphs | | F codes | |
| F set | | F features | |
| striprange | function | F glyphs | |
| tasks | table | F message | |
| F actions | | F messages | |
| F appendaction | | F nofsteps | |
| F disableaction | | F register | |
| F disablegroup | | F reset | |
| F enableaction | | F start | |
| F enablegroup | | F stop | |
| F freeze | | F stop | |
| F freezegroup | | T transparencies | |
| F new | | F reset | |
| F prependaction | | F set | |
| F removeaction | | F setlist | |
| F restart | | unsetattribute | function |
| F showactions | | unsetattributes | function |
| F table | | visualizebox | function |
| texmdir_is_equal | data table | visualizers | table |
| texmdir_is_is | data table | F box | |
| texmdir_is_opposite | data table | F handler | |
| texmdir_is_parallel | data table | F markfonts | |
| tonodes | function | F setfont | |
| tosequence | function | F setlayer | |
| totable | function | F setvisual | |
| toutf | function | whatcodes | data table |
| tracers | table | whatsitcodes | data table |
| T characters | | writable_spec | function |

number (context)

| | | | |
|---------------------|------------|-----------------------|----------|
| | function | tocentimeters | function |
| basepoints | function | tociceros | function |
| bit | function | todidots | function |
| bits | function | todimen | function |
| clearbit | function | toevenhex | function |
| dimenfactors | data table | toinches | function |
| hasbit | function | tomillimeters | function |
| maxdimen | number | tonewciceros | function |
| nopts | function | tonewdidots | function |
| percent | function | tonumberf | function |
| points | function | tonumberg | function |
| pts | function | topics | function |
| setbit | function | topoints | function |
| signed | function | toscaled | function |
| splitdimen | function | toscaledpoints | function |
| tobasepoints | function | toset | function |
| tobitstring | function | valid | function |

os (basic lua)

| | | | |
|---------------------------|---------------------|------------------------|---------------------|
| <code>__getenv__</code> | function | <code>remove</code> | function |
| <code>__setenv__</code> | function | <code>rename</code> | function |
| <code>binsuffix</code> | string | <code>resolvers</code> | table |
| <code>binsuffixes</code> | table | <code>resultof</code> | function |
| <code>clock</code> | function | <code>runtime</code> | function |
| <code>converttime</code> | function | <code>selfdir</code> | string |
| <code>date</code> | function | <code>setenv</code> | overloaded function |
| <code>difftime</code> | function | <code>setlocale</code> | overloaded function |
| <code>env</code> | data table | <code>sleep</code> | function |
| <code>exec</code> | overloaded function | <code>spawn</code> | overloaded function |
| <code>execute</code> | overloaded function | <code>time</code> | function |
| <code>exit</code> | function | <code>times</code> | function |
| <code>fulltime</code> | function | <code>timezone</code> | function |
| <code>getenv</code> | overloaded function | <code>tmpdir</code> | function |
| <code>gettimeofday</code> | function | <code>tmpname</code> | function |
| <code>launch</code> | function | <code>today</code> | function |
| <code>libsuffix</code> | string | <code>type</code> | string |
| <code>localtime</code> | function | <code>uname</code> | function |
| <code>name</code> | string | <code>uuid</code> | function |
| <code>now</code> | function | <code>where</code> | function |
| <code>platform</code> | string | <code>which</code> | function |

package (basic lua)

| | | | |
|----------------------|----------|-------------------|----------|
| clibpaths | function | loaders | table |
| config | string | loadlib | function |
| cpath | string | path | string |
| extraclibpath | function | preload | table |
| extralibpath | function | searchers | table |
| helpers | table | searchpath | function |
| libpaths | function | seeall | function |
| loaded | table | | |

pagebuilders (context)

mixedcolumns table

F cleanup

F finalize

F getlist

F getrest

F getsplit

F setsplit

pdf (basic tex)

| | | | |
|-----------------------|----------|------------------------|----------|
| immediateobj | function | pageresources | string |
| mapfile | function | pagesattributes | string |
| mapline | function | pdfmapfile | function |
| maxobjnum | function | pdfmapline | function |
| obj | function | print | function |
| objtype | function | refobj | function |
| pageattributes | string | registerannot | function |
| pageref | function | reserveobj | function |

pdfscanner (context)

scan function

physics (context)

`units` table

D tables

profiler (extra lua)

pause function
resume function

start function
stop function

regimes (context)

| | |
|----------------|----------|
| cleanup | function |
| disable | function |
| enable | function |
| pop | function |

| | |
|------------------|----------|
| process | function |
| push | function |
| toregime | function |
| translate | function |

resolvers (context)

| | | | |
|-------------------------------------|------------|--------------------------------|------------|
| allprefixes | function | findfile | function |
| appendhash | function | findfiles | function |
| automount | function | findgivenfile | function |
| automounted | table | findgivenfiles | function |
| booleanvariable | function | findpath | function |
| cacheversion | string | findtexfile | function |
| checkedvariable | function | findwildcardfile | function |
| cleanpath | function | findwildcardfiles | function |
| cleanpathlist | function | formatofsuffix | function |
| concatinators | data table | formatofvariable | function |
| configbanner | string | formats | data table |
| criticalvars | data table | generators | data table |
| dangerous | data table | getenv | function |
| datastate | function | getownpath | function |
| defaultsuffixes | table | getreadfilename | function |
| dowithfilesandreport | function | hashers | data table |
| dowithfilesintree | function | homedir | string |
| dowithpath | function | inputstack | table |
| dowithvariable | function | installinputfilehandler | function |
| env | function | installinputlinehandler | function |
| executers | table | instance | table |
| F check | | D data | |
| F exec | | B diskcache | |
| F execute | | D environment | |
| F finalize | | D expansions | |
| F popen | | D fakepaths | |
| F register | | D files | |
| F spawn | | B force_suffixes | |
| expandbraces | function | D found | |
| expandedpathfromlist | function | D foundintrees | |
| expandedpathlist | function | D hashed | |
| expandedpathlistfromvariable | function | D hashes | |
| expandpath | function | D lists | |
| expandpathfromvariable | function | B loadererror | |
| expansion | function | D order | |
| extendtexmfvariable | function | B remember | |
| find_file | function | B renewcache | |
| find_files | function | B renewtree | |
| findbinfile | function | B savelists | |
| findctxfile | function | D setups | |
| finders | data table | D specification | |

| | | | |
|--------------------------|------------|-------------------------------|------------|
| D variables | | registerintrees | function |
| jobs | table | registermethod | function |
| F currentcomponent | | registerzipfile | function |
| F currentenvironment | | relations | data table |
| F currentproduct | | renew | function |
| F currentproject | | repath | function |
| F justacomponent | | reset | function |
| D processors | | resetextrapath | function |
| F productcomponent | | resetresolve | function |
| F usefile | | resolve | function |
| joinpath | function | savers | data table |
| load | function | scandata | function |
| loadbinfile | function | scanfiles | function |
| loaders | data table | schemes | table |
| loadlualib | function | T cleaners | |
| loadtexfile | function | F md5 | |
| loadtime | function | F none | |
| locateformat | function | F strip | |
| locators | data table | F cleannname | |
| luacnfname | string | F fetchstring | |
| luacnfspec | string | F fetchtable | |
| luacnfstate | string | F install | |
| macros | table | setenv | function |
| F convertfile | | setinstance | function |
| F decodecomment | | showpath | function |
| F enablecomment | | simplescanfiles | function |
| F encodecomment | | splitconfigurationpath | function |
| F preprocessed | | splitexpansions | function |
| F processmk | | splitmethod | function |
| F processmkvi | | splitpath | function |
| F version | | suffixes | data table |
| maxreadlevel | number | suffixmap | data table |
| methodhandler | function | suffixofformat | function |
| newinstance | function | texdatablob | function |
| openbinfile | function | toppath | function |
| openers | data table | unexpandedpath | function |
| openfile | function | unexpandedpathlist | function |
| opentexfile | function | unresolve | function |
| ownpath | string | updaterelations | function |
| prefixes | data table | updatescript | function |
| prependhash | function | usezipfile | function |
| registerextrapath | function | validatedpath | function |
| registerfile | function | variable | function |
| registerfilehash | function | variableofformat | function |

variableofformatorsuffix

function

wildcardpattern

function

scripts (context)

autofontfeature table

 F disable

 F enable

 F handler

categorytonumber data table

colors data table

defaults table

 N inter_char_half_shrink_factor

 N inter_char_half_stretch_factor

 N inter_char_hangul_penalty

 N inter_char_quarter_shrink_factor

 N inter_char_quarter_stretch_factor

 N inter_char_shrink_factor

 N inter_char_stretch_factor

handlers data table

hash table

installdataset function

installmethod function

numbertocategory data table

numbertodataset data table

preprocess function

reset function

set function

set (context)

contains function

create function

tolist function

tonumber function

totable function

socket (extra lua)

| | | |
|-----------------------|----------|-----------------------------|
| BLOCKSIZE | number | S connection |
| _DEBUG | boolean | S content-description |
| _SETSIZE | number | S content-disposition |
| bind | function | S content-encoding |
| choose | function | S content-id |
| connect | function | S content-language |
| connect4 | function | S content-length |
| connect6 | function | S content-location |
| dns | table | S content-md5 |
| F getaddrinfo | | S content-range |
| F gethostname | | S content-transfer-encoding |
| F getnameinfo | | S content-type |
| F tohostname | | S date |
| F toip | | S diagnostic-code |
| ftp | table | S dsn-gateway |
| S PASSWORD | | S etag |
| N PORT | | S expect |
| N TIMEOUT | | S expires |
| S USER | | S final-log-id |
| F command | | S final-recipient |
| F get | | S from |
| F open | | S host |
| F put | | S if-match |
| gettime | function | S if-modified-since |
| headers | table | S if-none-match |
| T canonic | | S if-range |
| S accept | | S if-unmodified-since |
| S accept-charset | | S in-reply-to |
| S accept-encoding | | S keywords |
| S accept-language | | S last-attempt-date |
| S accept-ranges | | S last-modified |
| S action | | S location |
| S age | | S max-forwards |
| S allow | | S message-id |
| S alternate-recipient | | S mime-version |
| S arrival-date | | S original-envelope-id |
| S authorization | | S original-recipient |
| S bcc | | S pragma |
| S cache-control | | S proxy-authenticate |
| S cc | | S proxy-authorization |
| S comments | | S range |

S received
 S received-from-mta
 S references
 S referer
 S remote-mta
 S reply-to
 S reporting-mta
 S resent-bcc
 S resent-cc
 S resent-date
 S resent-from
 S resent-message-id
 S resent-reply-to
 S resent-sender
 S resent-to
 S retry-after
 S return-path
 S sender
 S server
 S smtp-remote-recipient
 S status
 S subject
 S te
 S to
 S trailer
 S transfer-encoding
 S upgrade
 S user-agent
 S vary
 S via
 S warning
 S will-retry-until
 S www-authenticate
 S x-mailer

http **table**

N PORT
 N TIMEOUT
 S USERAGENT
 F open
 F request

newtry **function**

protect **function**
select **function**
sink **function**
sinkt **table**

F close-when-done
 F default
 F http-chunked
 F keep-open

skip **function**
sleep **function**
smtp **table**

S DOMAIN
 N PORT
 S SERVER
 N TIMEOUT
 S ZONE
 F message
 F open
 F send

source **function**
sourcet **table**

F by-length
 F default
 F http-chunked
 F until-closed

tcp **function**
tcp6 **function**
tp **table**

N TIMEOUT
 F connect

try **function**
udp **function**
udp6 **function**
url **table**

F absolute
 F build
 F build_path
 F escape
 F parse
 F parse_path
 F unescape

sorters (context)

comparers table

 F basic

constants table

 S defaultdigits

 S defaultlanguage

 S defaultmethod

 N digitmaximum

 N digitsoffset

 N ignoredoffset

 N replacementoffset

definitions data table

firstofsplit function

setlanguage function

sort function

splitters table

 F utf

strip function

tracers data table

update function

statistics (context)

| | | | |
|-----------------------|----------|----------------------|----------|
| checkfmtstatus | function | register | function |
| elapsed | function | resettiming | function |
| elapsedindeed | function | runtime | function |
| elapsedseconds | function | savefmtstatus | function |
| elapsedtime | function | show | function |
| enable | boolean | starttiming | function |
| formatruntime | function | stoptiming | function |
| hastiming | function | threshold | number |
| memused | function | timed | function |

status (basic tex)

list function

storage (context)

| | |
|-------------------|----------|
| allocate | function |
| data | table |
| evaluators | table |
| mark | function |
| marked | function |
| max | number |
| min | number |

| | |
|-------------------|------------|
| nofmodules | number |
| noftables | number |
| register | function |
| shared | data table |
| strip | boolean |
| tofmodules | number |
| toftables | number |

streams (context)

| | |
|-------------------|----------|
| collect | function |
| disable | function |
| enable | function |
| flush | function |
| initialize | function |

| | |
|--------------------|----------|
| push | function |
| start | function |
| stop | function |
| synchronize | function |

string (basic lua)

autodouble function
autosingle function
booleanstring function
byte function
bytepairs function
bytes function
char function
characterpairs function
characters function
checkedsplit function
collapsespaces function
count function
dump function
escapedpattern function
explode function
find function
format function
formatter function
formatters function

```
F %t (%t)
F %-t--cycle
F %-15s :
F %-15s : %s
F %-15s >
F %-15s >
F %-15s > %s
F %-15s > %s
F %-15s > %s >
F %-15s > %s >
F %-15s > %s > %s
F %-15s > %s > %s
F %.3f %.3f %.3f %.3f k %.3f %.3f %.3f %.3f K
F %.3f %.3f %.3f rg %.3f %.3f %.3f RG
F %.3f g %.3f G
F %U
F %U (%s)
F %a loaded
F %p
F %s
F %S %s
F %S %S %s
```

```
F %S %S %S %t
F %S %S %S %s
F %S Tc %S w %S Tr
F %S mul
F %S--%s
F %S->%S->%s
F %S->%S->%S->%S->%S->%S->%s
F %S:%s
F %S:%S:%s
F (%p,%p)
F /%S %s
F /%S << %t >>
F /%S [ %t ]
F /%S cs /%S CS %S SCN %s scn
F /Tr%s gs
F << %t >>
F << /Type /Annot %s /Rect [%0.3f %0.3f %0.3f %0.3f] >>
F MpSh%s
F Tr%s
F U+%04X:%s
F [ %t ]
F [%s][%s]
F \convertnumber{%s}{%s}
F _bpnf_ (%s,%s,%s, '%s')
T _extensions_
S chruni
S font:features
S font:name
S tex
S unichr
S xml
F _plib_.b_col(%q)
F _plib_.b_region(%q)
F _plib_.e_col()
F _plib_.e_region(%s)
F _plib_.enhance(%q)
S _preamble_
S _type_
F b:%s
F buffer.%s
F c:%s:%s:%s:%s
```

| | | |
|---|--|----------|
| F chem_%%s(%%s,%%s,"\\chemicaltext{%s}"); | F region:%%s | |
| F chem_%%s(%%s,%%s,%%s,%%s,%%s,%%s); | F s:%%s | |
| F chem_%%s(%%s,%%s,""); | F setbounds currentpicture to multibox ; | |
| F chem_%%s(%%s,%%s,%%s); | F unknown reference %a | |
| F chem_c%%s(%%s,%%s,""); | F using file %a | |
| F chem_pb; | F visualizers.%%s | |
| F chem_pe; | F w:%%s | |
| F chem_reset; | gmatch | function |
| F chem_restore; | gsub | function |
| F chem_save; | is_boolean | function |
| F chem_set(%%s); | is_empty | function |
| F chem_start_component; | itself | function |
| F chem_start_structure(%%s,%%s,%%s,%%s,%%s,%%s,%%s,%%s,%%s,%%s,%%s,%%s); | len | function |
| F chem_stop_component; | limit | function |
| F chem_stop_structure; | longtostring | function |
| F chem_symbol("\\chemicalsymbol[closecomplex]"); | lower | function |
| F chem_symbol("\\chemicalsymbol[equilibrium]{%s}{%s}"); | match | function |
| F chem_symbol("\\chemicalsymbol[gives]{%s}{%s}"); | nspaces | table |
| F chem_symbol("\\chemicalsymbol[mesomeric]{%s}{%s}"); | quote | function |
| F chem_symbol("\\chemicalsymbol[minus]"); | quoted | function |
| F chem_symbol("\\chemicalsymbol[opencomplex]"); | rep | function |
| F chem_symbol("\\chemicalsymbol[plus]"); | reverse | function |
| F chem_symbol("\\chemicalsymbol[space]"); | split | function |
| F chem_symbol("\\chemicaltext{%s}"); | splitlines | function |
| F dup %%s mul exch dup %%s mul exch %%s mul | splitup | function |
| F dup %%s mul exch dup %%s mul exch dup %%s mul exch dup %%s mul exch %%s mul | strip | function |
| F e:%%s | sub | function |
| F flushing realpage %%s, userpage %%s | tformat | function |
| F if unknown context_chem : input mp-chem.mpiv ; fi ; | toboollean | function |
| F jobname %a, input %a, result %a | tocontext | function |
| F language %a is active | todimen | function |
| F mfun_tt_w[%i] := %%f ; mfun_tt_h[%i] := %%f ; mfun_tt_d[%i] := %%f ; | topattern | function |
| F multilocs[%%s] := %%s ; multikind[%%s] := "%%s" ; multipars[%%s] := (%%s) ; | totable | function |
| F multiregs[%%s] := (%%s) shifted - %%s ; | toutf | function |
| F p:%%s | tracedchar | function |
| F p:%%s:%%s:%%s:%%s | tracedchars | table |
| F path multiregs[], multipars[], multibox ; string multiregs[], multipars[] ; | unquote | function |
| F path posboxes[], posregions[] ; numeric pospages[] ; numeric posboxes ; | unquoted | function |
| F pdf: q 1 0 %%f 1 0 0 cm | upper | function |
| F pospages[%%s] := %%s ; posboxes[%%s] := (%%p,%%p)--(%%p,%%p)-%%f ; | utfcharacters | function |
| F q %%f %%f %%f %%f %%f %%f cm | utfvalues | function |
| F r:%%s:%%s:%%s | valid | function |

structures (context)

| | | | |
|-------------------|----------|-----------------------------|----------|
| atlocation | function | F setlevel | |
| blocks | table | F setoffset | |
| D collected | | F setown | |
| F define | | F setstate | |
| F print | | F setvalue | |
| F save | | T specials | |
| F select | | F userpage | |
| F setstate | | F subs | |
| D states | | D tobesaved | |
| D tobesaved | | F value | |
| bookmarks | table | currentsectionnumber | function |
| F finalize | | descriptions | table |
| F flatten | | documents | table |
| S method | | D data | |
| F overload | | F initialize | |
| F place | | F preset | |
| F register | | F reset | |
| F setup | | floats | table |
| counters | table | formulas | table |
| F add | | F current | |
| F analyze | | F simplify | |
| F check | | F store | |
| D collected | | helpers | table |
| F compact | | F analyze | |
| F converted | | F formulanumber | |
| F currentvalue | | F merged | |
| D data | | F page | |
| F define | | F prefix | |
| F first | | F prefixlastpage | |
| F get | | F prefixpage | |
| F last | | F simplify | |
| F next | | F title | |
| F prev | | F touserdata | |
| F previous | | inserts | table |
| F raw | | D data | |
| F record | | F define | |
| F reset | | F getdata | |
| F restart | | F getlocation | |
| F restore | | F getname | |
| F save | | F getnumber | |
| F set | | F setlocation | |

| | |
|-------------------|--------------|
| F setup | |
| D stored | |
| itemgroups | table |
| F maxwidth | |
| F nofitems | |
| F register | |
| lists | table |
| F addto | |
| F analyze | |
| B autoreorder | |
| D cached | |
| D collected | |
| F discard | |
| F enhance | |
| T enhancers | |
| F filter | |
| F filtercollected | |
| F formulanumber | |
| F hasnumberdata | |
| F haspagedata | |
| F hastitledata | |
| D internals | |
| F iscached | |
| F label | |
| F location | |
| F number | |
| D ordered | |
| F page | |
| F popnesting | |
| F prefix | |
| F prefixednumber | |
| F prefixedpage | |
| F process | |
| D pushed | |
| F pushnesting | |
| F realpage | |
| F reordered | |
| T result | |
| F sectionnumber | |
| F size | |
| F title | |
| D tobesaved | |
| F userdata | |
| F uservalue | |

| | |
|----------------------------|--------------|
| marks | table |
| D data | |
| F define | |
| F exists | |
| F fetch | |
| F fetchallmarks | |
| F fetched | |
| F fetchonemark | |
| F fetchtwomarks | |
| F get | |
| F number | |
| F relate | |
| F reset | |
| F set | |
| F show | |
| F synchronize | |
| F title | |
| T tracers | |
| F showtable | |
| notes | table |
| F checkpagechange | |
| F define | |
| F doifonsamepageasprevious | |
| F get | |
| F getdeltapage | |
| F getn | |
| F getnumberpage | |
| F getstate | |
| F getsymbolpage | |
| F hascontent | |
| F internal | |
| F internalid | |
| F listindex | |
| F ordered | |
| F postpone | |
| F resetpostponed | |
| F restore | |
| F save | |
| F setstate | |
| F setsymbolpage | |
| D states | |
| F store | |
| pages | table |
| F analyze | |

D collected
F is_odd
F number
F save
D tobesaved

references

table

F analyze
F checkedfile
F checkedfileorurl
F checkedprogram
F checkedrealpage
F checkedurl
D collected
U componentsplitter
F currentmetadata
F currentorder
D currentset
F define
D defined
D derived
F enableinteraction
F enhance
D executors
F expandcurrent
F export
T files
 T data
 F define
 F get
F filter
F filterdefault
D filters
F from
F get
F getcurrentmetadata
F getcurrentprefixspec
F getinnermethod
F getinternalreference
D handlers
F identify
F import
F inject
F injectcurrentset
D internals

F load
F loadpresets
F mark
D pages
U prefixsplitter
D productdata
T programs
 T data
 F define
 F get
F realpageofpage
U referencesplitter
D referred
F referredpage
F registerfinalizer
F registerinitializer
F registerpage
F reportproblems
F reset
T resolvers
 F reference
 F section
D runners
F set
F setandgetattribute
F setcomponent
F setinnermethod
F setinternalreference
F setnextinternal
F setnextorder
D specials
F splitcomponent
F splitprefix
F splitreference
T testrunners
 F inner
 F special
 F special operation
 F special operation with arguments
T testspecials
 F deltapage
 F i
 F internal
 F page

- F realpage
- F section
- F userpage
- D tobereferred
- D tobesaved
- T urls
- T data
- F define
- F get
- F valid
- F whatfrom

registers table

- F analyze
- F analyzed
- D collected
- F compare
- F define
- F enhance
- F extend
- F filter
- F filtercollected
- F finalize
- F flush
- F prepare
- F process
- F sort
- F store
- D tobesaved
- F unique
- F userdata

sections table

- F autodepth
- F cct
- D collected
- F current
- F currentblock
- F currentid
- F currentlevel
- F depthnumber
- F finddata
- F findnumber
- F fullnumber
- F getcurrentlevel
- F getlevel

- F getnumber
- F internalreference
- D levelmap
- D levels
- F load
- F matchingtilldepth
- F numberatdepth
- F numbers
- F popblock
- F prefixedconverted
- F pushblock
- F register
- D registered
- F reportstructure
- F save
- F set
- F setblock
- F setchecker
- F setlevel
- F setnumber
- F somelevel
- F structuredata
- F title
- D tobesaved
- F typesetnumber
- F userdata
- B verbose

sets table

- F define
- F get
- F getall
- D setlist

specials table

- D collected
- F retrieve
- F store
- D tobesaved

synonyms table

- F analyzed
- D collected
- F compare
- F define
- F filter
- F finalize

| | |
|----------------|------------------------|
| F flush | F registerdata |
| F meaning | F registermetadata |
| F prepare | F restart |
| F process | F setattributehash |
| F register | F setcombination |
| F registerused | F setdescription |
| F sort | F setdescriptionsymbol |
| F synonym | F setfigure |
| D tobesaved | F sethighlight |
| tags | F setitemgroup |
| | F setproperty |
| T data | F setsorting |
| F detailedtag | F setsynonym |
| F getid | F settablecell |
| F handler | F settabulatecell |
| D labels | F start |
| F last | F stop |
| F lastinchain | D taglist |
| T metadata | T userdata |
| D properties | |
| table | |

table (basic lua)

| | | | |
|------------------------|----------|-----------------------------|----------|
| allkeys | function | prepend | function |
| append | function | print | function |
| are_equal | function | remove | function |
| autokey | function | reverse | function |
| compact | function | reversed | function |
| concat | function | save | function |
| contains | function | sequenced | function |
| copy | function | serialize | function |
| count | function | setmetatablecall | function |
| derive | function | setmetatableindex | function |
| deserialize | function | setmetatablekey | function |
| drop | function | setmetatablenewindex | function |
| fastcopy | function | sort | function |
| fastserialize | function | sorted | function |
| flattened | function | sortedhash | function |
| fromhash | function | sortedhashkeys | function |
| getmetatablekey | function | sortedkeys | function |
| has_one_entry | function | sortedpairs | function |
| identical | function | strip | function |
| imerge | function | sub | function |
| imerged | function | swapped | function |
| insert | function | tocontext | function |
| is_empty | function | tocsv | function |
| keys | function | tofile | function |
| load | function | tohandle | function |
| loweredkeys | function | tohash | function |
| maxn | function | toxml | function |
| merge | function | twowaymapper | function |
| merged | function | unique | function |
| mirrored | function | unnest | function |
| pack | function | unpack | function |

tex (basic tex)

| | | | |
|-------------------------|------------|----------------------|------------|
| attribute | table | istoken | function |
| badness | function | lccode | table |
| box | table | linebreak | function |
| catcode | table | lists | table |
| conditionals | data table | luacatcodes | number |
| constants | data table | mathcode | table |
| count | table | modes | data table |
| ctxcatcodes | number | nest | table |
| definefont | function | nilcatcodes | number |
| delcode | table | notcatcodes | number |
| dimen | table | number | function |
| directives | data table | pdffontname | function |
| enableprimitives | function | pdffontobjnum | function |
| error | function | pdffontsize | function |
| extraprimitives | function | pdfpageref | function |
| finish | function | pdfxformname | function |
| fontidentifier | function | primitives | function |
| fontname | function | print | function |
| fprint | function | printlist | function |
| get | function | prtcacodes | number |
| getattribute | function | romannumeral | function |
| getbox | function | round | function |
| getcatcode | function | run | function |
| getcount | function | scale | function |
| getdelcode | function | set | function |
| getdimen | function | setattribute | function |
| getlccode | function | setbox | function |
| getlist | function | setcatcode | function |
| getmath | function | setcount | function |
| getmathcode | function | setdelcode | function |
| getnest | function | setdimen | function |
| getsfcode | function | setfalse | function |
| getskip | function | setlccode | function |
| gettoks | function | setlist | function |
| getuccode | function | setmath | function |
| hashtokens | function | setmathcode | function |
| ifs | data table | setnest | function |
| inicatcodes | number | setsfcode | function |
| iscount | function | setskip | function |
| isdimen | function | settoks | function |
| isskip | function | settrue | function |

| | | | |
|--------------------|------------|-----------------------|------------|
| setuccode | function | tpbcatcodes | number |
| sfcode | table | tprint | function |
| shipout | function | trackers | data table |
| skip | table | txtcatcodes | number |
| sp | function | type | function |
| sprint | function | uccode | table |
| systemmodes | data table | uniformdeviate | function |
| texcatcodes | number | uprint | function |
| toks | table | vrbcacodes | number |
| tpacacodes | number | write | function |

texconfig (basic tex)

| | | | |
|------------------------|----------|-----------------------|--------|
| error_line | number | max_print_line | number |
| expand_depth | number | max_strings | number |
| formatname | string | nest_size | number |
| half_error_line | number | param_size | number |
| hash_extra | number | save_size | number |
| init | function | shell_escape | string |
| kpse_init | boolean | stack_size | number |
| max_in_open | number | | |

texio (basic tex)

write overloaded function

write_nl overloaded function

token (basic tex)

| | | | |
|---------------------|----------|----------------------|----------|
| command_id | function | get_next | function |
| command_name | function | is_activechar | function |
| create | function | is_expandable | function |
| csname_id | function | is_protected | function |
| csname_name | function | lookup | function |
| expand | function | | |

tokens (context)

bgroup table
collectors table
 T data
 F defaultwords
 F dowithwords
 F flush
 F handle
 F install
 F register
 T registered
 T remapper
 F convert
 T data
 F store
 F show

 T show_methods
 F a
 F b
 F c
 F showtoken
 F test
 F trace
egroup table
hbox table
letter function
letters function
other function
vbox table
vtop table

tracers (context)

| | |
|------------------|----------|
| count | function |
| cs | function |
| dimen | function |
| knownlist | function |
| lists | table |

- T context
- T internals
- T scratch

| | |
|------------------|----------|
| name | function |
| primitive | function |
| prnterror | function |
| showlines | function |
| strings | table |
| S undefined | |
| toks | function |
| type | function |

trackers (context)

| | | | |
|-----------------------|------------|-----------------|----------|
| data | data table | name | string |
| default | function | register | function |
| disable | function | report | function |
| dumphashtofile | function | savehash | function |
| enable | function | show | function |
| list | function | value | function |

typesetters (context)

alignments table

F handler

F set

breakpoints table

N attribute

F define

F handler

D mapping

T methods

T numbers

F set

F setreplacement

cases table

T actions

F handler

F register

F set

characters table

F handler

checkers table

F handler

F reset

F set

cleaners table

F handler

F set

digits table

T actions

N attribute

F handler

F set

directions table

F handler

F process

F set

fast_hpack function

hpack function

italics table

F forcevariant

F handler

F reset

F set

kerns table

D factors

F handler

B keepeligature

B keepetogether

D mapping

F set

margins table

F finalhandler

F globalhandler

F ha

F localhandler

F save

paragraphs table

N attribute

T droppers

F freeze

F set

F handler

F set

processors table

F apply

F register

F reset

F split

F startapply

F stopapply

F stripped

F toString

spacings table

N attribute

F define

F handler

D mapping

T numbers

T frenchpunctuation

T characters

S name

N number

F reset

| | |
|----------------|----------------------------|
| F set | F initialize_construct |
| F setup | F initialize_reflow_height |
| tonodes | F initialize_reflow_width |
| vpack | F next_row |
| xtables | F reflow_height |
| F cleanup | F reflow_width |
| F construct | F set_construct |
| F create | F set_reflow_height |
| F flush | F set_reflow_width |

unicode (extra lua)

ascii table

F byte
F char
F dump
F find
F format
F gfind
F gmatch
F gsub
F len
F lower
F match
F rep
F reverse
F sub
F upper

grapheme table

F byte
F char
F dump
F find
F format
F gfind
F gmatch
F gsub
F len
F lower
F match
F rep
F reverse
F sub
F upper

latin1 table

F byte
F char
F dump
F find
F format
F gfind
F gmatch
F gsub

F len
F lower
F match
F rep
F reverse
F sub
F upper

utf8 table

F byte
F char
F characters
F count
F dump
F filetype
F find
F format
F gfind
F gmatch
F gsub
F is_valid
F len
F length
F lower
F magic
F match
F remapper
F rep
F replacer
F reverse
F split
F splitlines
F sub
F subtituter
F tocodes
F toentities
F tostring
F totable
F upper
F ustring
F utf16_to_utf8
F utf16_to_utf8_be

F utf16_to_utf8_le
F utf32_to_utf8
F utf32_to_utf8_be
F utf32_to_utf8_le

F utf8_to_utf16
F utf8_to_utf8
F values
F xstring

url (context)

addscheme function
barepath function
construct function
escape function
filename function

hashed function
hasscheme function
query function
split function
toquery function

utilities (context)

debugger table

F disable
F enable
F savestats
F showstats

formatters table

F formatcolumns
F list
F stripzeros

garbagecollector table

F check
N criterium
B enabled

lua table

B alwaysstripcode
F compile
F loadedluacode
F loadstripped
N nofstrippedbytes
N nofstrippedchunks
B stripcode
T strippedchunks
F strippedloadstring
T suffixes
 S lua
 S luc
 S lui
 S luj
 S luv
 S tma
 S tmc
 S tua
 S tuc

packers table

F hashed
F new
F pack
F simplehashed
F strip
F unpack
N version

parsers table

F add_settings_to_array
F arguments_to_table
F array_to_string
F csvsplitter
F getparameters
F hash_to_string
F iterator
F keq_to_hash
F listitem
F make_settings_to_hash_pattern
T patterns
 U keq_to_hash_c
 U settings_to_array
 U settings_to_hash_a
 U settings_to_hash_b
 U settings_to_hash_c
 U unittotex
F rfc4180splitter
F settings_to_array
F settings_to_array_with_repeat
F settings_to_hash
F settings_to_hash_strict
F settings_to_hash_tolerant
F settings_to_set
F simple_hash_to_string
F splitthousands
F stepper
F unittotex
F unittoxml

report function

sequencers table

F appendaction
F appendgroup
F compile
F disableaction
F disablegroup
F enableaction
F enablegroup
D functions
F localize

| | | | |
|------------------|-------|---------------------|-------|
| F new | | F sparse | |
| F nodeprocessor | | strings | table |
| F prependaction | | F collapsecrlf | |
| F prependgroup | | T formatters | |
| F removeaction | | F add | |
| F setkind | | F new | |
| F toString | | F newrepeater | |
| setters | table | F nice | |
| F disable | | F striplong | |
| F enable | | F tabtospace | |
| F initialize | | T tracers | |
| F list | | tables | table |
| F new | | F accesstable | |
| F register | | F definedtable | |
| F report | | F definetable | |
| F reset | | F encapsulate | |
| F show | | F insertaftervalue | |
| stacker | table | F insertbeforevalue | |
| F new | | F migratetable | |
| storage | table | F removevalue | |
| F allocate | | templates | table |
| F checked | | F load | |
| F mark | | F replace | |
| F marked | | F resolve | |
| F setinitializer | | | |

vf (context)

| | |
|---------------|----------|
| char | function |
| down | function |
| fontid | function |
| image | function |
| node | function |
| nop | function |

| | |
|----------------|----------|
| pop | function |
| push | function |
| right | function |
| rule | function |
| special | function |

visualizers (context)

| | | | |
|------------------------------|------------|------------------------|------------|
| escapepatterns | data table | signal | string |
| getvisualizer | function | signalpattern | userdata |
| load | function | specifications | data table |
| makenested | function | visualize | function |
| makepattern | function | visualizebuffer | function |
| newgrammar | function | visualizefile | function |
| newhandler | function | visualizestring | function |
| parsedxml | function | write | function |
| pattern | function | writeargument | function |
| register | function | writedefault | function |
| registerescapecommand | function | writeemptyline | function |
| registerescapeline | function | writenewline | function |
| registerescapepattern | function | writespace | function |

xml (context)

| | | | |
|---------------------------|----------|------------------------|------------|
| addentitiesdoctype | function | D tex | |
| after | function | D texline | |
| all | function | D texspace | |
| applylpath | function | D verbose | |
| assign | function | defaultprotocol | string |
| attribute | function | delete | function |
| before | function | delete_element | function |
| body | function | each | function |
| builtinentities | table | each_element | function |
| B amp | | elements | function |
| B apos | | elementtocdata | function |
| B gt | | empty | function |
| B lt | | entities | data table |
| B quot | | erase | function |
| cdata | function | errorhandler | function |
| cdatatotext | function | escaped | function |
| checkbom | function | expressions | table |
| checkerror | function | F boolean | |
| checknamespace | function | F child | |
| checkns | function | F contains | |
| cleansed | function | F count | |
| collect | function | F error | |
| collect_elements | function | F find | |
| collect_tags | function | F lower | |
| collect_texts | function | F name | |
| collected | function | F number | |
| collecttexts | function | F oneof | |
| content | function | F print | |
| convert | function | F quit | |
| copy | function | F tag | |
| count | function | F text | |
| cprint | function | F undefined | |
| css | table | F upper | |
| F colorspecification | | fillin | function |
| F dimension | | filter | function |
| F fontspecification | | finalizers | table |
| F padding | | F paragraphs | |
| defaulthandlers | table | T tex | |
| D file | | F all | |
| D parsedxml | | F attribute | |
| D string | | F bibtexconcat | |

| | | |
|------------------|------------------------------|----------|
| F bibtexshort | F position | |
| F chainattribute | F reverse | |
| F command | F table | |
| F concat | F tag | |
| F concatrange | F tags | |
| F context | F text | |
| F count | F texts | |
| F ctxtext | F upperall | |
| F default | first | function |
| F first | found | function |
| F function | functions | table |
| F index | getbuffer | function |
| F last | gethandlers | function |
| F lettered | gethandlersfunction | function |
| F lower | helpers | table |
| F lowerall | F recursetext | |
| F match | include | function |
| F name | index | function |
| F position | inheritedconvert | function |
| F reverse | inject | function |
| F stripped | inject_element | function |
| F tag | inject_element_after | function |
| F tags | inject_element_before | function |
| F text | injectafter | function |
| F upper | injectbefore | function |
| F upperall | insert | function |
| T xml | insert_element | function |
| F all | insert_element_after | function |
| F att | insert_element_before | function |
| F attribute | insertafter | function |
| F attributes | insertbefore | function |
| F cdata | insertcomment | function |
| F chainattribute | inspect | function |
| F count | is_valid | function |
| F default | kind | function |
| F elements | last | function |
| F empty | load | function |
| F first | lpath | function |
| F function | lpathcached | function |
| F index | lpathcalls | function |
| F last | lshow | function |
| F lowerall | makestandalone | function |
| F match | match | function |
| F name | name | function |

| | | | |
|----------------------------|----------|----------------------------|----------|
| newhandlers | function | root | function |
| nodesettostring | function | save | function |
| originalload | function | selection | function |
| package | function | separate | function |
| parent | function | serialize | function |
| parsedentitylpeg | userdata | setcdata | function |
| pihandlers | table | sethandlersfunction | function |
| placeholders | table | setproperty | function |
| F unknown_any_entity | | settings | function |
| F unknown_dec_entity | | specialhandler | table |
| F unknown_hex_entity | | sprint | function |
| position | function | string | function |
| privatecodes | table | strip | function |
| privatetoken | function | strip_whitespace | function |
| process | function | stripelement | function |
| process_attributes | function | stripleadingspaces | function |
| process_elements | function | table | function |
| processattributes | function | text | function |
| profiled | table | textonly | function |
| raw | function | texttocdata | function |
| registerentity | function | tocdata | function |
| registers | function | toelement | function |
| remap_name | function | tostring | function |
| remap_namespace | function | toxml | function |
| remap_tag | function | tprint | function |
| remapname | function | traverse | function |
| remapnamespace | function | unescaped | function |
| remaptag | function | unprivatized | function |
| renamespace | function | withelement | function |
| replace | function | withelements | function |
| replace_element | function | wrap | function |
| resolvens | function | xmlns | table |

zip (extra lua)

archives

table

close

function

closearchive

function

open

function

openarchive

function

openfile

function

registeredfiles

table

type

function

zlib (extra lua)

adler32 function
compress function
compressobj function
crc32 function

decompress function
decompressobj function
version function