

MP UsedCommands attributes backends bit
bit32 blobs boolean buffers builders caches
callback callbacks catcodes characters
chemistry commands containers context
converters coroutine ctxrunner debug dir
directives document documentdata
environment epdf experiments figures file
floats font fontloader fonts functions
global graphics gzip img interactions
interfaces io jit job lang languages
layouts lfs libraries lmx logs lpdf lpeg
ltn12 lua luatex lxml math mathematics mbox
md5 metapost mime moduledata modules mp
mplib newtoken noads node nodes number os
package pagebuilders parametersets pdf
pdfscanner physics profiler publications
regimes resolvers sandbox scripts set
socket sorters statistics status storage
streams string structures table tex
texconfig texio thirddata token tokens
tracers trackers typesetters unicode url
userdata utilities vf visualizers xml zip
zlib

ConTEXT MkIV

global (alias: _G)

| | | | |
|----------------|----------|-----------------|----------|
| CheckCommand | function | endpage | function |
| MP | table | environment | table |
| ShowCommands | function | epdf | table |
| UsedCommands | table | error | function |
| _LUAVERSION | number | experiments | table |
| _MAJORVERSION | number | figures | table |
| _MINORVERSION | number | file | table |
| _cldo_ | function | floats | table |
| arg | table | font | table |
| assert | function | fontloader | table |
| attributes | table | fonts | table |
| backends | table | frozen | boolean |
| beginpage | function | functions | table |
| bit | table | gcinfo | function |
| bit32 | table | getfenv | function |
| blobs | table | getmetatable | function |
| boolean | table | getpos | function |
| border_set | boolean | getreadfilename | function |
| buffers | table | getvpos | function |
| builders | table | global | table |
| caches | table | graphics | table |
| callback | table | gzip | table |
| callbacks | table | img | table |
| catcodes | table | inspect | function |
| characters | table | interactions | table |
| chemistry | table | interfaces | table |
| collectgarbage | function | io | table |
| commands | table | ipairs | function |
| containers | table | jit | table |
| context | function | job | table |
| converters | table | lang | table |
| coroutine | table | languages | table |
| ctx_doifelse | function | layouts | table |
| ctxrunner | table | lfs | table |
| debug | table | libraries | table |
| dimen | function | lmx | table |
| dir | table | load | function |
| directives | table | loadfile | function |
| document | table | loadstring | function |
| documentdata | table | logs | table |
| dofile | function | lpdf | table |

| | | | |
|------------------------|----------|------------------------------|----------|
| lpeg | table | require | function |
| ltn12 | table | resolvers | table |
| lua | table | resolvestoredfunction | function |
| luatex | table | sandbox | table |
| lxml | table | scripts | table |
| m | string | select | function |
| math | table | set | table |
| mathematics | table | setfenv | function |
| mbox | table | setinspector | function |
| md5 | table | setmetatable | function |
| metapost | table | socket | table |
| mime | table | sorters | table |
| module | function | statistics | table |
| moduledata | table | status | table |
| modules | table | storage | table |
| mp | table | streams | table |
| mplib | table | string | table |
| newproxy | function | structures | table |
| newtoken | table | swiglib | function |
| next | function | table | table |
| noads | table | tex | table |
| node | table | texconfig | table |
| nodes | table | texio | table |
| number | table | thirddata | table |
| optionalrequire | function | toboollean | function |
| os | table | token | table |
| outputpagestree | function | tokens | table |
| package | table | tonumber | function |
| pagebuilders | table | tostring | function |
| pairs | function | tracers | table |
| parametersets | table | trackers | table |
| pcall | function | type | function |
| pdf | table | typesetters | table |
| pdfscanner | table | unicode | table |
| physics | table | unpack | function |
| print | function | url | table |
| profiler | table | userdata | table |
| protect | function | utf | table |
| publications | table | utilities | table |
| rawequal | function | vf | table |
| rawget | function | visualizers | table |
| rawlen | function | xml | table |
| rawset | function | xpcall | function |
| regimes | table | | |

zip
zlib

table
table

attributes (context)

colorintents table

- N attribute
- D data
- F enable
- F handler
- F register
- D registered

colors table

- N attribute
- F cmyk
- F cmyktogray
- F cmyktorgb
- F colorcomponents
- B couple
- D data
- N default
- F defineintermediatecolor
- F definemultitonecolor
- F defineprocesscolor
- F definesimplegray
- F definespotcolor
- F definetransparency
- F enable
- F filter
- F forcedmodel
- F forcesupport
- F formatcolor
- F formatgray
- F gray
- F graytohsv
- F handler
- F hsvtorgay
- F hsvtorgb
- F iccprofile
- F isblack
- N main
- S model
- D models
- F mpcolor
- F mpnamedcolor
- F mpoptions

- U none
- F popset
- F processcolorcomponents
- F pushset
- F register
- D registered
- F registerspotcolor
- F rgb
- F rgbtocmyk
- F rgbtorgay
- F rgbtohsv
- N selector
- F setlist
- F setmodel
- D sets
- F spec
- F spot
- F spotcolorname
- F spotcolorparent
- F spotcolorvalue
- B supported
- F transparencycomponents
- B triggering
- F usecolors
- F value
- D values
- B weightgray

define function effects table

- N attribute
- D data
- F enable
- F handler
- F register
- D registered
- D values

handlers table list data table names data table negatives table

- N attribute

| | | |
|-----------------------|------------|-----------------|
| D data | | D registered |
| F enable | | F resolve_begin |
| F handler | | F resolve_end |
| F register | | F resolve_reset |
| D registered | | F resolve_step |
| numbers | data table | D scopes |
| ofnode | function | F setfeatures |
| private | function | F start |
| public | function | F stop |
| showcurrent | function | B supported |
| states | table | D values |
| F disabletriggering | | |
| F enabletriggering | | |
| F finalize | | |
| F initialize | | |
| F process | | |
| F selective | | |
| F stacked | | |
| F stacker | | |
| system | function | |
| transparencies | table | |
| N attribute | | |
| D data | | |
| F enable | | |
| F forcesupport | | |
| F handler | | |
| U none | | |
| F register | | |
| D registered | | |
| B supported | | |
| B triggering | | |
| F value | | |
| D values | | |
| unsetvalue | number | |
| viewerlayers | table | |
| N attribute | | |
| D data | | |
| F define | | |
| F enable | | |
| F forcesupport | | |
| F handler | | |
| B hasorder | | |
| D listwise | | |
| F register | | |

backends (context)

codeinjections table

F synchronizecolormodel

current string

defaults table

T codeinjections

F gethpos

F getmatrix

F getpos

F getvpos

F hasmatrix

T nodeinjections

T registrations

D tables

install function

nodeinjections table

F restore

F save

F transform

nothing function

pdf table

T codeinjections

F addbookmarks

F attachmentid

F clonefield

F definefield

F definefieldset

F defineviewerlayer

F embedfile

F enabletags

F exportformdata

F getbookmarks

F getdefaultfieldvalue

F getfieldcategory

F getfieldset

F getformatoption

F gethpos

F getmatrix

F getoutputfilename

F getpos

F getpreviewfigure

F getvpos

F hasmatrix

F insertrenderingwindow

F mergebookmarks

F mergereferences

F mergeviewerlayers

F prerollreference

F presetsymbol

F presetsymbollist

F processrendering

F registerdocumentcloseaction

F registerdocumentopenaction

F registeredsymbol

F registerpagecloseaction

F registerpageopenaction

F registersymbol

F setfieldcalculationset

F setfigurealternative

F setfigurecolorspace

F setfiguremask

F setformat

F setformsmethod

F setpagetransition

F setupcanvas

F setupidentity

F setxmpfile

F startlayer

F stoplayer

F supportedformats

F unicodetoactualtext

F useviewerlayer

F validfield

F validfieldcategory

F validfieldset

S comment

T nodeinjections

F addtags

F annotation

F attachfile

F changestackedlayer

F cmykcolor

F comment

- F destination
- F effect
- F graycolor
- F injectbitmap
- F insertmovie
- F insertsound
- F insertswf
- F insertu3d
- F knockout
- F negative
- F overprint
- F positive
- F reference
- F rgbcolor
- F spotcolor
- F startlayer
- F startstackedlayer
- F stoplayer
- F stopstackedlayer
- F transparency
- F typesetfield
- T registrations
 - F cmykindexcolor
 - F cmykspotcolor
 - F getspotcolorreference
 - F grayindexcolor
 - F grayspotcolor
 - F rgbindexcolor
 - F rgbspotcolor
 - F spotcolorname
 - F transparency
- T tables
 - D vfspecials

registrations table

tables table

bit (context)

| | |
|----------------|----------|
| arshift | function |
| band | function |
| bnot | function |
| bor | function |
| bswap | function |
| bxor | function |
| lshift | function |
| rol | function |
| ror | function |
| rshift | function |
| tobit | function |
| tohex | function |

bit32 (basic lua)

| | |
|----------------|----------|
| arshift | function |
| band | function |
| bnot | function |
| bor | function |
| btest | function |
| bxor | function |
| extract | function |
| lrotate | function |
| lshift | function |
| replace | function |
| rrotate | function |
| rshift | function |

blobs (context)

| | |
|--------------------|----------|
| append | function |
| dimensions | function |
| dispose | function |
| new | function |
| pack | function |
| strdp | function |
| strhd | function |
| strht | function |
| strwd | function |
| tohpack | function |
| tohpackfast | function |
| tonodes | function |
| tovpack | function |
| tovpackfast | function |
| write | function |

boolean (context)

tocontext function

tonumber function

buffers (context)

| | |
|-----------------------|----------|
| append | function |
| assign | function |
| collectcontent | function |
| erase | function |
| exists | function |
| getcontent | function |
| getlines | function |
| loadcontent | function |
| parallel | table |
| F define | |
| F hassomecontent | |
| F next | |
| F place | |
| F reset | |
| F save | |
| pickup | function |
| prepend | function |
| raw | function |
| undent | function |

builders (context)

kernel table

- F hyphenation
- F kerning
- F ligaturing
- F mlist_to_hlist
- T originals
 - F hyphenate
 - F kerning
 - F ligaturing

paragraphs table

- T constructors
 - N attribute
 - F define
 - F disable
 - F enable
 - F handler
 - T methods
 - F basic
 - F default
 - F oneline
 - D names
 - D numbers
 - F set
 - F start
 - F stop
- T expansion
 - F trace
- F kepttogether
- F registertogether
- T solutions
 - T splitters
 - F define
 - F optimize
 - T registered
 - F reset
 - F set
 - F split
 - F start
 - F stop
- F tag

vspacing table

- F analyze
- D categories
- F collapsevbox
- T data
 - D map
 - D skip
 - D snapmethods
- F definesnapmethod
- B fixed
- F pagehandler
- F resetprevdepth
- F setmap
- F setskip
- F snapbox
- F tocategories
- F tocategory
- F vboxhandler

cache (context)

| | |
|---|----------|
| ask | boolean |
| base | string |
| collapsecontent | function |
| configfiles | function |
| contentstate | function |
| defaults | table |
| define | function |
| direct | boolean |
| force | boolean |
| getfirstreadablefile | function |
| getfirstreadablefile_TEST_ME_FIRST | function |
| getreadablepaths | function |
| getwritablepath | function |
| hashed | function |
| is_writable | function |
| loadcontent | function |
| loaddata | function |
| more | string |
| relocate | boolean |
| savecontent | function |
| savedata | function |
| setfirstwritablefile | function |
| setluaname | function |
| tree | string |
| treehash | function |
| usedpaths | function |

callback (basic tex)

find function

list function

register overloaded function

callbacks (context)

| | |
|-----------------|------------|
| freeze | function |
| known | function |
| list | data table |
| pop | function |
| push | function |
| register | function |
| report | function |

catcodes (context)

| | |
|-----------------|------------|
| names | data table |
| numbers | data table |
| register | function |

characters (context)

| | | |
|-----------------------|------------|-----|
| activeoffset | number | S B |
| adobename | function | S C |
| bidirectional | data table | S D |
| blockrange | function | S E |
| blocks | data table | S F |
| casemap | table | S G |
| categories | data table | S H |
| category | function | S I |
| categorytags | data table | S J |
| collapsed | data table | S K |
| combined | data table | S L |
| contextname | function | S M |
| data | data table | S N |
| decomposed | data table | S O |
| define | function | S P |
| description | function | S Q |
| descriptions | data table | S R |
| directions | table | S S |
| encodes | data table | S T |
| entities | data table | S U |
| fallbacks | data table | S V |
| filters | data table | S W |
| fromnumber | function | S X |
| fschars | data table | S Y |
| fscodes | data table | S Z |
| getrange | function | S Å |
| graphemes | data table | S Á |
| hangul | data table | S Â |
| initialize | function | S Ã |
| is_character | data table | S Ä |
| is_command | data table | S Å |
| is_letter | data table | S Æ |
| is_mark | data table | S Ç |
| is_punctuation | data table | S È |
| is_spacing | data table | S É |
| lcchars | data table | S Ê |
| lccode | function | S Ë |
| lccodes | data table | S Ì |
| lettered | function | S Í |
| lhash | table | S Î |
| S A | | S Ï |

S Ķ
 S Q
 S Ū
 S 3
 S
 S Ģ
 S H
 S
 S N
 S
 S Ē
 S Ō
 S Ā
 S Ā
 S Ē
 S Ī
 S Ī
 S Ō
 S Ō
 S R
 S R
 S Ū
 S Ū
 S Š
 S T
 S 3
 S H
 S Ņ
 S
 S Z
 S Ā
 S Ē
 S Ō
 S Ō
 S Ō
 S Ō
 S Ū
 S Ā
 S Ē
 S Ē
 S T
 S ?

| | |
|-----|------|
| S B | S ʁ |
| S H | S ŋ |
| S ʌ | S |
| S | S |
| S | S |
| S | S |
| S R | S |
| S | S |
| S A | S |
| S E | S θ |
| S H | S p |
| S I | S c |
| S D | S m |
| S Y | S ɔ |
| S ɒ | S ɕ |
| S A | S ɔ̃ |
| S B | S ě |
| S ɾ | S ě̃ |
| S Δ | S ħ |
| S E | S ġ |
| S Z | S € |
| S H | S s |
| S θ | S i |
| S I | S ĭ |
| S K | S j |
| S ʌ | S ʅ |
| S M | S ħ |
| S N | S ʱ |
| S ̄ | S k |
| S O | S ŋ |
| S Π | S ŷ |
| S P | S ɥ |
| S Σ | S A |
| S T | S Б |
| S Y | S В |
| S Φ | S ɾ |
| S X | S Д |
| S Ψ | S E |
| S Ω | S Ж |
| S Ĩ | S 3 |
| S Ỳ | S И |
| S Q | S Й |
| S Ç | S K |
| S F | S Л |

| | |
|-----|-----|
| S M | S 3 |
| S H | S K |
| S O | S |
| S П | S |
| S P | S |
| S C | S H |
| S T | S H |
| S Y | S |
| S Ø | S |
| S X | S Ç |
| S Ц | S Т |
| S Ч | S Y |
| S Ш | S ʏ |
| S Щ | S X |
| S Ъ | S |
| S Ы | S |
| S Ь | S |
| S Э | S h |
| S Ю | S |
| S Я | S |
| S | S I |
| S Ъ | S ǰ |
| S | S ȝ |
| S | S |
| S | S H |
| S | S |
| S | S ʏ |
| S | S |
| S | S Ā |
| S Ø | S Ā |
| S | S Æ |
| S | S Ē |
| S | S ə |
| S | S ǝ |
| S | S ǰ |
| S | S 3 |
| S | S 3 |
| S | S Ï |
| S | S Ï |
| S | S Ō |
| S Ğ | S 0 |
| S F | S 0 |
| S Ѓ | S 3 |
| S Ж | S Ÿ |

| | |
|------|-----|
| S Ÿ | S 2 |
| S Ÿ | S ņ |
| S ı | S U |
| S Ğ | S 4 |
| S 6l | S S |
| S | S Ğ |
| S | S 8 |
| S | S Ħ |
| S | S 0 |
| S | S 0 |
| S | S 3 |
| S | S |
| S | S |
| S | S |
| S | S |
| S E | S |
| S | S |
| S U | S |
| S P | S |
| S q | S |
| S 7 | S |
| S t | S |
| S 2 | S |
| S t | S |
| S 2 | S |
| S 0 | S |
| S d | S |
| S Ħ | S |
| S L | S |
| S hu | S |
| S 0 | S |
| S 4 | S |
| S 2 | S |
| S 2 | S |
| S 7 | S |
| S x | S |
| S U | S |
| S 3 | S |
| S 7 | S |
| S 0 | S |
| S 2 | S |
| S 2 | S |
| S 7 | S |

S Ő
 S
 S
 S P
 S P
 S R
 S R
 S R
 S S
 S S
 S
 S
 S Ş
 S T
 S T
 S T
 S T
 S U
 S U
 S U
 S Ó
 S
 S V
 S V
 S W
 S W
 S W
 S W
 S X
 S X
 S Y
 S Z
 S Z
 S Z
 S A
 S
 S
 S
 S
 S
 S A

S Å
S Å
S E
S E
S E
S E
S E
S H
S H
S H
S H
S H
S H
S H
S I
S I
S I
S I
S I
S I
S I
S I
S O
S O
S O
S O
S O
S Y
S Y
S Y
S Y
S N
S N
S N
S N
S N
S N
S N
S A
S A

[illegible]

| | | | |
|-------------------|--------------|-----------------------------|--------------|
| linebreaks | table | mirrors | table |
| S ai | | otfscripts | data table |
| S al | | ranges | data table |
| S b2 | | registerentities | function |
| S ba | | remap_hangul_syllabe | function |
| S bb | | setcodes | function |
| S bk | | shape | function |
| S cb | | shaped | function |
| S cj | | shash | table |
| S cl | | S Å | |
| S cm | | S Á | |
| S cp | | S Ă | |
| S cr | | S Ą | |
| S ex | | S Ǻ | |
| S gl | | S ǻ | |
| S h2 | | S Æ | |
| S h3 | | S Ç | |
| S hl | | S È | |
| S hy | | S É | |
| S id | | S Ê | |
| S in | | S Ë | |
| S is | | S Ĩ | |
| S jl | | S Í | |
| S jt | | S Î | |
| S jv | | S Ī | |
| S lf | | S Ñ | |
| S nl | | S Ò | |
| S ns | | S Ó | |
| S nu | | S Ô | |
| S op | | S Õ | |
| S po | | S Ö | |
| S pr | | S Ø | |
| S qu | | S Ù | |
| S ri | | S Ú | |
| S sa | | S Û | |
| S sg | | S Ü | |
| S sp | | S Ý | |
| S sy | | S ß | |
| S wj | | S à | |
| S xx | | S á | |
| S zw | | S â | |
| lower | function | S ă | |
| math | table | S ä | |
| mathpairs | data table | S å | |

| | |
|-----|------|
| S æ | S ẽ |
| S ç | S Ě |
| S è | S é |
| S é | S Ě |
| S ê | S ę |
| S ẽ | S Ě |
| S ì | S ẽ |
| S í | S Ğ |
| S î | S ğ |
| S ï | S Ğ |
| S ñ | S ğ |
| S ò | S Ğ |
| S ó | S ğ |
| S ô | S Ğ |
| S õ | S ğ |
| S ö | S Ĥ |
| S ø | S ĥ |
| S ù | S Ĥ |
| S ú | S ĥ |
| S û | S Ĩ |
| S ü | S ĩ |
| S ý | S Ĩ |
| S ÿ | S ĩ |
| S Ā | S Ĩ |
| S ā | S ĩ |
| S Ă | S Į |
| S ă | S į |
| S A | S Ĩ |
| S a | S ı |
| S Ć | S ij |
| S ć | S j |
| S Ĉ | S j |
| S ĉ | S Ƶ |
| S Ċ | S ƶ |
| S ċ | S Ĺ |
| S Č | S ĺ |
| S č | S Ľ |
| S Ď | S ľ |
| S đ | S Ľ |
| S Ð | S ʀ |
| S đ | S ʀ |
| S Ē | S ʀ |
| S ē | S Ł |
| S Ĕ | S ł |

S Ū
S ū
S Ŵ
S ŵ
S Ŷ
S ŷ
S Ÿ
S Ž
S ž
S Ż
S ż
S Ĺ
S ĺ
S Ł
S ł
S Ą
S ą
S Ƀ
S Ɔ
S ɔ
S ɖ
S Ḃ
S ḃ
S ɓ
S ɕ
S ʈ
S ʉ
S ɰ
S ʁ
S ʀ
S ʂ
S ʃ
S ʄ
S ʅ
S ʆ
S ʇ
S ʈ
S ʉ
S ʊ
S ʋ

| | |
|-----|-----|
| S y | S Ȯ |
| S Z | S Š |
| S z | S š |
| S ž | S j |
| S | S |
| S | S Ġ |
| S | S ġ |
| S | S Ñ |
| S | S ñ |
| S | S |
| S | S |
| S | S Æ |
| S | S æ |
| S Ä | S Ø |
| S ä | S ø |
| S Ĩ | S Ā |
| S ĩ | S ā |
| S Ŏ | S Ā |
| S ŏ | S ā |
| S Ů | S Ě |
| S ů | S ě |
| S Ű | S Ě |
| S ű | S ě |
| S Ų | S Ĩ |
| S ų | S ĭ |
| S Ŵ | S Ĩ |
| S ŵ | S ĭ |
| S Ŷ | S Ŏ |
| S ŷ | S Ȯ |
| S Ȧ | S Ŏ |
| S ă | S Ȯ |
| S Ā | S Ĥ |
| S ǎ | S Ȧ |
| S Ȧ | S Ĥ |
| S ǣ | S Ȧ |
| S Ȧ | S Ů |
| S | S ů |
| S | S Ű |
| S Ģ | S ű |
| S ģ | S Ş |
| S Ķ | S ş |
| S ķ | S Ț |
| S Q | S ț |
| S Ȯ | S Ħ |
| S Ȯ | |

S ǵ
 S ħ
 S ±
 S 𐀀
 S 𐀁
 S 𐀂
 S 𐀃
 S 𐀄
 S 𐀅
 S 𐀆
 S 𐀇
 S 𐀈
 S 𐀉
 S 𐀊
 S 𐀋
 S 𐀌
 S 𐀍
 S 𐀎
 S 𐀏
 S 𐀐
 S 𐀑
 S 𐀒
 S 𐀓
 S 𐀔
 S 𐀕
 S 𐀖
 S 𐀗
 S 𐀘
 S 𐀙
 S 𐀚
 S 𐀛
 S 𐀜
 S 𐀝
 S 𐀞
 S 𐀟
 S 𐀠
 S 𐀡
 S 𐀢
 S 𐀣
 S 𐀤
 S 𐀥
 S 𐀦
 S 𐀧
 S 𐀨
 S 𐀩
 S 𐀪
 S 𐀫
 S 𐀬
 S 𐀭
 S 𐀮
 S 𐀯
 S 𐀰
 S 𐀱
 S 𐀲
 S 𐀳
 S 𐀴
 S 𐀵
 S 𐀶
 S 𐀷
 S 𐀸
 S 𐀹
 S 𐀺
 S 𐀻
 S 𐀼
 S 𐀽
 S 𐀾
 S 𐀿
 S 𐁀
 S 𐁁
 S 𐁂
 S 𐁃
 S 𐁄
 S 𐁅
 S 𐁆
 S 𐁇
 S 𐁈
 S 𐁉
 S 𐁊
 S 𐁋
 S 𐁌
 S 𐁍
 S 𐁎
 S 𐁏
 S 𐁐
 S 𐁑
 S 𐁒
 S 𐁓
 S 𐁔
 S 𐁕
 S 𐁖
 S 𐁗
 S 𐁘
 S 𐁙
 S 𐁚
 S 𐁛
 S 𐁜
 S 𐁝
 S 𐁞
 S 𐁟
 S 𐁠
 S 𐁡
 S 𐁢
 S 𐁣
 S 𐁤
 S 𐁥
 S 𐁦
 S 𐁧
 S 𐁨
 S 𐁩
 S 𐁪
 S 𐁫
 S 𐁬
 S 𐁭
 S 𐁮
 S 𐁯
 S 𐁰
 S 𐁱
 S 𐁲
 S 𐁳
 S 𐁴
 S 𐁵
 S 𐁶
 S 𐁷
 S 𐁸
 S 𐁹
 S 𐁺
 S 𐁻
 S 𐁼
 S 𐁽
 S 𐁾
 S 𐁿
 S 𐂀
 S 𐂁
 S 𐂂
 S 𐂃
 S 𐂄
 S 𐂅
 S 𐂆
 S 𐂇
 S 𐂈
 S 𐂉
 S 𐂊
 S 𐂋
 S 𐂌
 S 𐂍
 S 𐂎
 S 𐂏
 S 𐂐
 S 𐂑
 S 𐂒
 S 𐂓
 S 𐂔
 S 𐂕
 S 𐂖
 S 𐂗
 S 𐂘
 S 𐂙
 S 𐂚
 S 𐂛
 S 𐂜
 S 𐂝
 S 𐂞
 S 𐂟
 S 𐂠
 S 𐂡
 S 𐂢
 S 𐂣
 S 𐂤
 S 𐂥
 S 𐂦
 S 𐂧
 S 𐂨
 S 𐂩
 S 𐂪
 S 𐂫
 S 𐂬
 S 𐂭
 S 𐂮
 S 𐂯
 S 𐂰
 S 𐂱
 S 𐂲
 S 𐂳
 S 𐂴
 S 𐂵
 S 𐂶
 S 𐂷
 S 𐂸
 S 𐂹
 S 𐂺
 S 𐂻
 S 𐂼
 S 𐂽
 S 𐂾
 S 𐂿
 S 𐃀
 S 𐃁
 S 𐃂
 S 𐃃
 S 𐃄
 S 𐃅
 S 𐃆
 S 𐃇
 S 𐃈
 S 𐃉
 S 𐃊
 S 𐃋
 S 𐃌
 S 𐃍
 S 𐃎
 S 𐃏
 S 𐃐
 S 𐃑
 S 𐃒
 S 𐃓
 S 𐃔
 S 𐃕
 S 𐃖
 S 𐃗
 S 𐃘
 S 𐃙
 S 𐃚
 S 𐃛
 S 𐃜
 S 𐃝
 S 𐃞
 S 𐃟
 S 𐃠
 S 𐃡
 S 𐃢
 S 𐃣
 S 𐃤
 S 𐃥
 S 𐃦
 S 𐃧
 S 𐃨
 S 𐃩
 S 𐃪
 S 𐃫
 S 𐃬
 S 𐃭
 S 𐃮
 S 𐃯
 S 𐃰
 S 𐃱
 S 𐃲
 S 𐃳
 S 𐃴
 S 𐃵
 S 𐃶
 S 𐃷
 S 𐃸
 S 𐃹
 S 𐃺
 S 𐃻
 S 𐃼
 S 𐃽
 S 𐃾
 S 𐃿
 S 𐄀
 S 𐄁
 S 𐄂
 S 𐄃
 S 𐄄
 S 𐄅
 S 𐄆
 S 𐄇
 S 𐄈
 S 𐄉
 S 𐄊
 S 𐄋
 S 𐄌
 S 𐄍
 S 𐄎
 S 𐄏
 S 𐄐
 S 𐄑
 S 𐄒
 S 𐄓
 S 𐄔
 S 𐄕
 S 𐄖
 S 𐄗
 S 𐄘
 S 𐄙
 S 𐄚
 S 𐄛
 S 𐄜
 S 𐄝
 S 𐄞
 S 𐄟
 S 𐄠
 S 𐄡
 S 𐄢
 S 𐄣
 S 𐄤
 S 𐄥
 S 𐄦
 S 𐄧
 S 𐄨
 S 𐄩
 S 𐄪
 S 𐄫
 S 𐄬
 S 𐄭
 S 𐄮
 S 𐄯
 S 𐄰
 S 𐄱
 S 𐄲
 S 𐄳
 S 𐄴
 S 𐄵
 S 𐄶
 S 𐄷
 S 𐄸
 S 𐄹
 S 𐄺
 S 𐄻
 S 𐄼
 S 𐄽
 S 𐄾
 S 𐄿
 S 𐅀
 S 𐅁
 S 𐅂
 S 𐅃
 S 𐅄
 S 𐅅
 S 𐅆
 S 𐅇
 S 𐅈
 S 𐅉
 S 𐅊
 S 𐅋
 S 𐅌
 S 𐅍
 S 𐅎
 S 𐅏
 S 𐅐
 S 𐅑
 S 𐅒
 S 𐅓
 S 𐅔
 S 𐅕
 S 𐅖
 S 𐅗
 S 𐅘
 S 𐅙
 S 𐅚
 S 𐅛
 S 𐅜
 S 𐅝
 S 𐅞
 S 𐅟
 S 𐅠
 S 𐅡
 S 𐅢
 S 𐅣
 S 𐅤
 S 𐅥
 S 𐅦
 S 𐅧
 S 𐅨
 S 𐅩
 S 𐅪
 S 𐅫
 S 𐅬
 S 𐅭
 S 𐅮
 S 𐅯
 S 𐅰
 S 𐅱
 S 𐅲
 S 𐅳
 S 𐅴
 S 𐅵
 S 𐅶
 S 𐅷
 S 𐅸
 S 𐅹
 S 𐅺
 S 𐅻
 S 𐅼
 S 𐅽
 S 𐅾
 S 𐅿
 S 𐆀
 S 𐆁
 S 𐆂
 S 𐆃
 S 𐆄
 S 𐆅
 S 𐆆
 S 𐆇
 S 𐆈
 S 𐆉
 S 𐆊
 S 𐆋
 S 𐆌
 S 𐆍
 S 𐆎
 S 𐆏
 S 𐆐
 S 𐆑
 S 𐆒
 S 𐆓
 S 𐆔
 S 𐆕
 S 𐆖

| | | | |
|---|---|---|---|
| Ѕ | Й | Ѕ | Ѓ |
| Ѕ | | Ѕ | |
| Ѕ | | Ѕ | |
| Ѕ | | Ѕ | |
| Ѕ | | Ѕ | |
| Ѕ | | Ѕ | Ă |
| Ѕ | | Ѕ | ă |
| Ѕ | Г | Ѕ | Ā |
| Ѕ | г | Ѕ | ā |
| Ѕ | Ƒ | Ѕ | Ě |
| Ѕ | Ƒ | Ѕ | ě |
| Ѕ | Ђ | Ѕ | Ď |
| Ѕ | ђ | Ѕ | ď |
| Ѕ | Ж | Ѕ | Ž |
| Ѕ | ж | Ѕ | ž |
| Ѕ | З | Ѕ | Ž |
| Ѕ | з | Ѕ | ž |
| Ѕ | Қ | Ѕ | Й |
| Ѕ | қ | Ѕ | й |
| Ѕ | | Ѕ | Й |
| Ѕ | | Ѕ | й |
| Ѕ | | Ѕ | Ö |
| Ѕ | | Ѕ | ö |
| Ѕ | Ң | Ѕ | Э |
| Ѕ | ң | Ѕ | э |
| Ѕ | | Ѕ | Ÿ |
| Ѕ | | Ѕ | ÿ |
| Ѕ | Ç | Ѕ | Ÿ |
| Ѕ | ç | Ѕ | ÿ |
| Ѕ | Т | Ѕ | Ÿ |
| Ѕ | т | Ѕ | ÿ |
| Ѕ | Х | Ѕ | Ч |
| Ѕ | х | Ѕ | č |
| Ѕ | | Ѕ | Č |
| Ѕ | | Ѕ | Г |
| Ѕ | | Ѕ | г |
| Ѕ | | Ѕ | Ы |
| Ѕ | | Ѕ | ы |
| Ѕ | Ж | Ѕ | |
| Ѕ | ж | Ѕ | |
| Ѕ | Қ | Ѕ | |
| Ѕ | қ | Ѕ | |
| Ѕ | | Ѕ | |
| Ѕ | | Ѕ | |
| Ѕ | | Ѕ | |
| Ѕ | Ң | Ѕ | |

§

§

S

S

S

S

§

S

S

§

§

S

S

S

S

§

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

§

S

§

S

S

S

S

§

§

| | |
|-----|------|
| S | S |
| S | S |
| S | S |
| S | S Å |
| S | S ą |
| S | S ß |
| S | S b |
| S | S B |
| S | S ḃ |
| S | S Ḃ |
| S | S b̈ |
| S | S Ç |
| S | S Ć |
| S | S Ď |
| S | S d |
| S | S D |
| S | S ḋ |
| S | S Ḋ |
| S | S d̈ |
| S | S D̈ |
| S | S d̊ |
| S | S D̊ |
| S | S d̋ |
| S | S |
| S | S |
| S | S |
| S | S |
| S | S E |
| S ĺ | S ę |
| S | S Ė |
| S | S ę̇ |
| S | S Ë |
| S | S ę̈ |
| S | S F |
| S | S f |
| S | S Ğ |
| S | S ğ |
| S | S H |
| S | S h |
| S | S Ḣ |
| S | S ḣ |
| S | S Ḧ |
| S | S ḧ |
| S | S H̊ |
| S | S h̊ |
| S | S H̋ |
| S | S H̋ |

S š
S Š
S š
S Š
S Ŗ
S r̃
S R̄
S ṙ
S R̈
S r̆
S R̆
S r̅
S R̅
S r̂
S Š
S š
S Ě
S ě
S Ṫ
S ṫ
S T̈
S ẗ
S T̉
S t̉
S T̊
S t̊
S U̇
S u̇
S Ü
S ü
S Ủ
S ủ
S Ů
S ů
S
S
S V̇
S v̇
S V̈
S v̈
S Ẇ

| | |
|-----|-----|
| S Ẁ | S |
| S Ẃ | S |
| S Ẅ | S |
| S Ẇ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S Ȧ |
| S Ẹ | S Ȧ |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S |
| S Ẹ | S |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |
| S Ẹ | S Ȧ |
| S Ẹ | S ă |

previous 40 next

S T
S T
S ũ
S ū
S ù
S ú
S ő
S ö
S õ
S ü
S ý
S Ÿ
S ŷ
S ʻ
S ẏ
S ȳ
S Ȳ
S Ɔ
S Ǫ
S ǫ
S Ǿ
S Ǟ
S ǟ
S Ǡ
S ǡ
S Ǣ
S ǣ
S Ǥ
S ǥ
S Ǧ
S ǧ
S Ǩ
S ǩ
S Ǭ
S ǭ
S fi
S fl
S
S
S

| | | |
|-----|---------------------|------------|
| S | S ĵ | |
| S | S ĩ | |
| S | shchars | data table |
| S | shcodes | data table |
| S | showstring | function |
| S | specialchars | data table |
| S | specials | data table |
| S | splits | table |
| S | T char | |
| S | T compat | |
| S | subscripts | table |
| S | superscripts | table |
| S | synonyms | data table |
| S | tex | table |
| S | D accentmapping | |
| S | D commandmapping | |
| S | F defineaccents | |
| S | F safechar | |
| S | F toutf | |
| S | F toutfpattern | |
| S | textclasses | table |
| S | tonumber | function |
| S | ucchars | data table |
| S | uccode | function |
| S | uccodes | data table |
| S | uhash | table |
| S | S a | |
| S | S b | |
| S | S c | |
| S | S d | |
| S | S e | |
| S | S f | |
| S | S g | |
| S | S h | |
| S Ī | S i | |
| S Ĭ | S j | |
| S Ĩ | S k | |
| S Ĭ | S l | |
| S ۞ | S m | |
| S ۞ | S n | |
| S | S o | |
| S ۞ | S p | |
| S ۞ | S q | |
| S ۞ | S r | |

| | |
|-----|-----|
| S s | S ś |
| S t | S ť |
| S u | S ů |
| S v | S ů |
| S w | S ų |
| S x | S ų |
| S y | S ē |
| S z | S ě |
| S μ | S è |
| S ß | S ę |
| S à | S ě |
| S á | S ğ |
| S â | S ğ |
| S ã | S ğ |
| S ä | S ğ |
| S å | S ħ |
| S æ | S ħ |
| S ç | S ĩ |
| S è | S ĩ |
| S é | S ĩ |
| S ê | S ĩ |
| S ë | S ĩ |
| S ì | S ĩ |
| S í | S ĩ |
| S î | S ĩ |
| S ï | S ĩ |
| S ð | S ĩ |
| S ñ | S ĩ |
| S ò | S ĩ |
| S ó | S ĩ |
| S ô | S ĩ |
| S õ | S ĩ |
| S ö | S ĩ |
| S ø | S ĩ |
| S ù | S ĩ |
| S ú | S ĩ |
| S û | S ĩ |
| S ü | S ĩ |
| S ý | S ĩ |
| S þ | S ĩ |
| S ÿ | S ĩ |
| S ā | S ĩ |
| S ă | S ĩ |
| S ą | S ĩ |

S ū
 S ú
 S ũ
 S ù
 S ə
 S ā
 S ǎ
 S æ
 S
 S ǵ
 S k̄
 S q̄
 S q̇
 S ǰ
 S
 S ǵ
 S ñ
 S
 S æ
 S ø
 S ä
 S â
 S ë
 S ê
 S ì
 S î
 S ò
 S ô
 S ŕ
 S ř
 S ù
 S û
 S ȳ
 S ȳ
 S ȳ
 S ħ
 S
 S ȳ
 S à
 S ę
 S ȳ
 S ȳ
 S ó
 S ȳ

S ζ
S η
S θ
S ι
S κ
S λ
S μ
S ν
S ξ
S ο
S π
S ρ
S σ
S τ
S υ
S φ
S χ
S ψ
S ω
S ῑ
S ῒ
S ó
S ú
S ō
S ø
S θ
S φ
S ɸ
S q
S ç
S f
S ħ
S λ
S
S
S
S
S
S
S
S x
S e
S c

| | |
|-----|------|
| Ѕ є | Ѕ љ |
| Ѕ ђ | Ѕ њ |
| Ѕ м | Ѕ ћ |
| Ѕ а | Ѕ к |
| Ѕ б | Ѕ њ |
| Ѕ в | Ѕ љ |
| Ѕ г | Ѕ ц |
| Ѕ д | Ѕ |
| Ѕ е | Ѕ љ |
| Ѕ ж | Ѕ |
| Ѕ з | Ѕ |
| Ѕ и | Ѕ |
| Ѕ њ | Ѕ |
| Ѕ к | Ѕ |
| Ѕ л | Ѕ |
| Ѕ м | Ѕ |
| Ѕ н | Ѕ ѓ |
| Ѕ о | Ѕ |
| Ѕ п | Ѕ |
| Ѕ р | Ѕ |
| Ѕ с | Ѕ |
| Ѕ т | Ѕ |
| Ѕ у | Ѕ |
| Ѕ ф | Ѕ |
| Ѕ х | Ѕ |
| Ѕ ц | Ѕ |
| Ѕ ч | Ѕ |
| Ѕ ш | Ѕ г' |
| Ѕ щ | Ѕ ф |
| Ѕ љ | Ѕ ѓ |
| Ѕ њ | Ѕ ж |
| Ѕ љ | Ѕ з |
| Ѕ э | Ѕ к |
| Ѕ ю | Ѕ |
| Ѕ я | Ѕ |
| Ѕ є | Ѕ |
| Ѕ ё | Ѕ њ |
| Ѕ ђ | Ѕ н |
| Ѕ ї | Ѕ |
| Ѕ є | Ѕ |
| Ѕ ѕ | Ѕ ц |
| Ѕ і | Ѕ т |
| Ѕ ї | Ѕ у |
| Ѕ ј | Ѕ у |

| | |
|-----|------|
| S x | S |
| S | S |
| S | S |
| S | S ε |
| S h | S |
| S | S w |
| S | S p |
| S ж | S q |
| S к | S η |
| S | S ti |
| S н | S q |
| S | S t |
| S ч | S n |
| S | S p |
| S l | S d |
| S ä | S h |
| S ä | S L |
| S æ | S hu |
| S ě | S b |
| S ə | S q |
| S ǝ | S h |
| S ж | S d |
| S ẽ | S η |
| S ʒ | S 6 |
| S й | S f |
| S й | S j |
| S ö | S u |
| S ø | S 2 |
| S ɵ | S n |
| S ẽ | S z |
| S ŷ | S w |
| S ŷ | S z |
| S ŷ | S n |
| S ü | S u |
| S r | S q |
| S ъ | S m |
| S | S p |
| S | S g |
| S | S L |
| S | S ψ |
| S | S p |
| S | S o |
| S | S f |
| S | S |

S ĩ
S ŕ
S ř
S ṛ
S ś
S ș
S
S
S ș
S ț
S ț
S ț
S ț
S u
S u
S ú
S
S ṽ
S v̇
S w̃
S ẇ
S w̄
S w̅
S x̃
S x̄
S ỹ
S ž
S z̃
S z̄
S f̃
S ạ
S
S
S
S
S
S â
S
S à
S
S
S ă

S ē
S ē
S ē
S ģ
S ģ
S ĥ
S ĥ
S ħ
S ħ
S ĩ
S ĩ
S İ
S İ
S İ
S İ
S ó
S ó
S ð
S ð
S õ
S õ
S ū
S ŭ
S ŷ
S ŷ
S Ź
S Ź
S ǎ
S ǎ
S ɛ̃
S ɛ̃
S Ĩ
S Ĩ

previous 50 next

| | |
|--------------------|----------|
| unicodechar | function |
| upper | function |

[previous](#) 53 [next](#)

chemistry (context)

| | |
|-----------------------|------------|
| component | function |
| define | function |
| definitions | data table |
| format | string |
| instance | string |
| molecule | function |
| moleculeparser | userdata |
| start | function |
| stop | function |
| structures | number |
| undefine | function |

commands (context)

| | | | |
|----------------------------------|----------|----------------------------------|----------|
| Alphabetic | function | btxcollectlistentries | function |
| Character | function | btxdetail | function |
| Characters | function | btxdoif | function |
| Romannumerals | function | btxdoifelse | function |
| abjadnodotnumerals | function | btxdoifelsesameasprevious | function |
| abjadnumerals | function | btxdoifelseuservariable | function |
| addbtxentry | function | btxdoifnot | function |
| addcounter | function | btxexpandedjournal | function |
| addlinklistelement | function | btxfetchlistentries | function |
| addreplacements | function | btxfield | function |
| addtojavascriptpreamble | function | btxfieldname | function |
| addtolist | function | btxfieldtype | function |
| allinputpaths | function | btxfirstofrange | function |
| alphabetic | function | btxflush | function |
| analysefloatmethod | function | btxflushlistentry | function |
| analyzeitemgroup | function | btxflushpages | function |
| analyzelist | function | btxfoundname | function |
| analyzeregister | function | btxfoundtype | function |
| applytochars | function | btxhandlecite | function |
| applytofirstcharacter | function | btxhandlenocite | function |
| applytowords | function | btxlistvariant | function |
| assignbuffer | function | btxloadjournalist | function |
| attachproperty | function | btxoneorrange | function |
| autofinishstructurelevels | function | btxpreparelistentries | function |
| autonextspace | function | btxsavedataset | function |
| autonextstructurelevel | function | btxsavejournalist | function |
| autosetups | function | btxsingularorplural | function |
| autostarttext | function | btxtoregister | function |
| autostoptext | function | btxuservariable | function |
| averagecharwidth | function | buildtextaccent | function |
| boolcase | function | character | function |
| boxtostring | function | characters | function |
| btx_a_f | function | chardescription | function |
| btx_a_i | function | checkcharactersinfont | function |
| btx_a_j | function | checkcounterssetup | function |
| btx_a_s | function | checkedconversion | function |
| btx_a_v | function | checkedpagefloat | function |
| btxabbreviatedjournal | function | checkinjector | function |
| btxaddjournal | function | checktwopassdata | function |
| btxauthor | function | chemicalcomponent | function |
| btxauthorfield | function | chineseallnumerals | function |

| | | | |
|--------------------------------|----------|----------------------------------|----------|
| chinesecapnumerals | function | definefilesynonym | function |
| chinesenumerals | function | definefont_one | function |
| cleanfontname | function | definefont_two | function |
| cleanupbox | function | definefontfamily | function |
| cleanuplayers | function | definefontfeature | function |
| clonefield | function | definefontsolution | function |
| collectfloat | function | definehyphenationfeatures | function |
| collecthelp | function | defineinsertion | function |
| collecttokens | function | defineintermediatecolor | function |
| colorcomponents | function | definelabels | function |
| concatcommalist | function | definelanguage | function |
| consultfloat | function | definelinkedlist | function |
| convertbtxdatasettoxml | function | definemarking | function |
| convertedddimen | function | definemetafont | function |
| cos | function | definemultitonecolor | function |
| cosd | function | definenote | function |
| countvalue | function | defineparallel | function |
| counttwopassdata | function | defineparbuilder | function |
| ctxfunction | function | defineprocesscolor | function |
| currentcomponent | function | defineprogram | function |
| currentdate | function | definereference | function |
| currentenvironment | function | defineregister | function |
| currentproduct | function | definesectionlevels | function |
| currentproject | function | defineselectfont | function |
| currentreferencedefault | function | definesnapmethod | function |
| currentreferenceorder | function | definespotcolor | function |
| currentregime | function | definestructureblock | function |
| currentsectiontolist | function | definestructureset | function |
| datasetvariable | function | definetransparency | function |
| dayname | function | definetwopasslist | function |
| deferredproperty | function | defineviewerlayer | function |
| defineattribute | function | defrostrandomseed | function |
| definebreakpoint | function | depthnumber | function |
| definebreakpoints | function | digits | function |
| definecatcodetable | function | disableautofontscript | function |
| definecharacterspacing | function | disableparbuilder | function |
| definechemical | function | disableregime | function |
| defineconversion | function | disablespellchecking | function |
| definecounter | function | discardfromlist | function |
| definedviewerlayer | function | doanalyzeframedbox | function |
| definefallbackfamily | function | doif | function |
| definefield | function | doifblackelse | function |
| definefieldset | function | doifcommonelse | function |
| definefilefallback | function | doifcounter | function |

| | | | |
|--------------------------------------|----------|-------------------------------|----------|
| doifdimenstringelse | function | doreshapeframedbox | function |
| doifdrawingblackelse | function | dostarttextfile | function |
| doifelse | function | dostoptextfile | function |
| doifelsebuffer | function | elapsedtime | function |
| doifelsecontinewithfile | function | enableautofontscript | function |
| doifelseconverter | function | enablecolor | function |
| doifelsecounter | function | enablecolorintents | function |
| doifelsecurrentfonthasfeature | function | enablecrlf | function |
| doifelseintwopassdata | function | enablefontcolorschemes | function |
| doifelsemarking | function | enableparbuilder | function |
| doifelsemessage | function | enableregime | function |
| doifelseparallel | function | enablespellchecking | function |
| doifelsereference | function | enabletransparency | function |
| doifelsesavedfloat | function | enhancelinkedlist | function |
| doifelsespaces | function | enhancelist | function |
| doifelseutfmathabove | function | enhancereference | function |
| doifelseutfmathaccent | function | enhanceregister | function |
| doifelseutfmathbelow | function | erasebuffer | function |
| doifelseutfmathfiller | function | execute | function |
| doifelsevisualizer | function | expandcurrentreference | function |
| doiffielddcategoryelse | function | exportformdata | function |
| doiffielddelse | function | exportreferences | function |
| doiffielddsetelse | function | extendregister | function |
| doiffiledefinedelse | function | extensiblecode | function |
| doiffileexistelse | function | feature | function |
| doiffirstcharelse | function | featureattribute | function |
| doifinputfileelse | function | featurelist | function |
| doifinsetelse | function | feedback | function |
| doifleapyearelse | function | fetchallmarks | function |
| doiflisthasentry | function | fetchonemark | function |
| doiflisthasnumberelse | function | fetchtwomarks | function |
| doiflisthaspageelse | function | figurefilename | function |
| doiflisthastitleelse | function | figurefilepath | function |
| doiflocfileelse | function | figurefiletype | function |
| doifnot | function | figurerequest | function |
| doifnotcounter | function | figurestatus | function |
| doifnotecontent | function | figureused | function |
| doifnoteonsamepageasprevious | function | figurevariable | function |
| doifobjectreferencefoundelse | function | filterdefaultreference | function |
| doifolderversionelse | function | filterreference | function |
| doifparentfileelse | function | finalizebox | function |
| doifpathexistelse | function | findtwopassdata | function |
| doifurldefinedelse | function | firstcountervalue | function |
| doprocесstypescriptfile | function | firstinset | function |

| | | | |
|------------------------------------|----------|--------------------------------|----------|
| flushfloat | function | getlasttwopassdata | function |
| flushmarked | function | getmarking | function |
| flushnotes | function | getmessage | function |
| flushpostponedblocks | function | getmpextensions | function |
| flushpostponednotes | function | getnotestate | function |
| flushtokens | function | getplaceholderchar | function |
| fontchar | function | getprivatechar | function |
| fontcharbyindex | function | getprogram | function |
| fontcollectionclone | function | getrandomcounta | function |
| fontcollectiondefine | function | getrandomcountb | function |
| fontcollectionprepare | function | getrandomseed | function |
| fontcollectionregister | function | getreadfilename | function |
| fontcollectionreport | function | getsectionnumber | function |
| fontcollectionreset | function | getstructuredata | function |
| fontlookupgetkey | function | getsubstring | function |
| fontlookupgetkeyofindex | function | gettexbuffer | function |
| fontlookupinitialize | function | gettwopassdata | function |
| fontlookupnofound | function | gettwopassdatalist | function |
| forceendjob | function | geturl | function |
| forcequitjob | function | grabbuffer | function |
| format | function | hboxtovbox | function |
| formatcolor | function | helpaction | function |
| formatgray | function | helpreference | function |
| freezerandomseed | function | hexstringtonumber | function |
| from | function | horizontalcode | function |
| getbidimode | function | hour | function |
| getbodyfontsizes | function | hyphenatedlist | function |
| getbuffer | function | hyphenatedurl | function |
| getbufferctxlua | function | D characters | |
| getbuffermkvi | function | N lefthyphenmin | |
| getcommandline | function | D mapping | |
| getctxfile | function | N righthyphenmin | |
| getcurrentprefixspec | function | F setcharacters | |
| getcurrentreferencemetadata | function | immediateproperty | function |
| getcurrentsectionlevel | function | incrementedcounter | function |
| getdefaultfieldvalue | function | initializetexdirectives | function |
| getelementtag | function | initializetextrackers | function |
| getfieldcategory | function | injectcurrentreference | function |
| getfirstcharacter | function | injectreference | function |
| getfirsttwopassdata | function | inlinechemical | function |
| getfloatvariable | function | insertattachment | function |
| getfullsectionnumber | function | insertcomment | function |
| getinternallistreference | function | insertfield | function |
| getinternalreference | function | insertionnumber | function |

| | | | |
|-------------------------------|----------|-----------------------------------|----------|
| insertrenderingwindow | function | mixflushrest | function |
| insertsoundclip | function | mixgetsplitleft | function |
| installedlanguages | function | mixsetsplitleft | function |
| installtexdirective | function | mixstate | function |
| installtextracker | function | molecule | function |
| language | function | month | function |
| lastcountvalue | function | monthmname | function |
| lastofrange | function | monthname | function |
| lchexnumber | function | mpcolor | function |
| lchexnumbers | function | mpoptions | function |
| leapyear | function | mprunvar | function |
| linenumberstageone | function | namedstructureuservariable | function |
| linenumberstagetwo | function | namedstructurevariable | function |
| listgroupindex | function | nbfs | function |
| listlabel | function | nextcountvalue | function |
| listlocation | function | nextparallel | function |
| listprefixednumber | function | nofdays | function |
| listprefixedpage | function | nofstackedfloats | function |
| listrealpage | function | notedeltapage | function |
| listsize | function | notelistindex | function |
| listtitle | function | notenumberpage | function |
| listuserdata | function | noteprefixednumber | function |
| loadbtxdefinitionfile | function | notesymbolpage | function |
| loadbtxreplacementfile | function | notetitle | function |
| loadexamodes | function | ntimes | function |
| loadfontgoodies | function | number | function |
| loadspellchecklist | function | F C | |
| loadtypescriptfile | function | F EQ | |
| loadvisualizer | function | F FL | |
| locatefilepath | function | F HL | |
| locfilename | function | F L | |
| lower | function | F LL | |
| makeactive | function | F LuaSnippet | |
| manipulated | function | F LuaSnippetBoundary | |
| markfonts | function | F LuaSnippetComment | |
| markingnumber | function | F LuaSnippetName | |
| markingtitle | function | F LuaSnippetNameBase | |
| markinjector | function | F LuaSnippetNameCore | |
| math_frac | function | F LuaSnippetNameLibraries | |
| mathrenderset | function | F LuaSnippetQuote | |
| minute | function | F LuaSnippetSpecial | |
| mixcleanup | function | F LuaSnippetString | |
| mixfinalize | function | F ML | |
| mixflushlist | function | F MPLIBsetCtext | |

| | |
|--------------------------------|--------------------------|
| F MPLIBsetNtext | F b |
| F MPcolor | F beginhbox |
| F MetapostSnippet | F beginvbox |
| F MetapostSnippetBoundary | F bf |
| F MetapostSnippetComment | F bgroup |
| F MetapostSnippetConstructor | F blank |
| F MetapostSnippetName | F btxcheckboxlistcombi |
| F MetapostSnippetNameMetafun | F btxcheckboxlistentry |
| F MetapostSnippetNamePlain | F btxciteauthorsetup |
| F MetapostSnippetNamePrimitive | F btxcitesetup |
| F MetapostSnippetQuote | F btxdirectlink |
| F MetapostSnippetSpecial | F btxflushauthor |
| F MetapostSnippetString | F btxhandlelistentry |
| F NC | F btxhandlelisttextentry |
| F NR | F btxlistauthorsetup |
| F ParsedXmlSnippetCdata | F btxlistsetup |
| F ParsedXmlSnippetComment | F btxpagesetup |
| F ParsedXmlSnippetDoctype | F btxsetafter |
| F ParsedXmlSnippetElement | F btxsetauthorindex |
| F ParsedXmlSnippetInstruction | F btxsetauthorvariant |
| F ParsedXmlSnippetKey | F btxsetbacklink |
| F ParsedXmlSnippetValue | F btxsetbacktrace |
| F TexSnippet | F btxsetbefore |
| F TexSnippetBoundary | F btxsetcategory |
| F TexSnippetComment | F btxsetcombis |
| F TexSnippetGroup | F btxsetconcat |
| F TexSnippetName | F btxsetcount |
| F TexSnippetSpecial | F btxsetcurrentlistentry |
| F XmlSnippet | F btxsetcurrentlistindex |
| F XmlSnippetBoundary | F btxsetdataset |
| F XmlSnippetCdata | F btxsetfirst |
| F XmlSnippetComment | F btxsetfirstinternal |
| F XmlSnippetEntity | F btxsetfirstnames |
| F XmlSnippetEqual | F btxsetfirstpage |
| F XmlSnippetKey | F btxsetinitials |
| F XmlSnippetName | F btxsetinternal |
| F XmlSnippetString | F btxsetjuniors |
| F __flush | F btxsetlanguage |
| F __flushdirect | F btxsetlastinternal |
| F __flushlines | F btxsetlastpage |
| F a | F btxsetlefttext |
| F addaskedblankskip | F btxsetnoflistentries |
| F addpredefinedblankskip | F btxsetnumber |
| F applyprocessor | F btxsetoverflow |

| | |
|----------------------|-------------------------------|
| F btxsetrighttext | F digitshighspace |
| F btxsetsecond | F digitsintermediatecomma |
| F btxsetsurnames | F digitsintermediateperiod |
| F btxsettag | F digitsminus |
| F btxsetthird | F digitsnegative |
| F btxsetvons | F digitsplus |
| F btxstartauthor | F digitspositive |
| F btxstartcite | F digitspower |
| F btxstartciteauthor | F digitspowerminus |
| F btxstartlistentry | F digitspowerplus |
| F btxstartsubcite | F digitsseparatorspace |
| F btxstopauthor | F digitssignspace |
| F btxstopcite | F digitsspace |
| F btxstopciteauthor | F digitsszeropadding |
| F btxstoplistentry | F direct |
| F btxstopsubcite | F doactivateinjector |
| F c | F dodisplayverbatimbeginline |
| F callfunctiononce | F dodisplayverbatimemptyline |
| F char | F dodisplayverbatiminitialize |
| F chardef | F dodisplayverbatimnewline |
| F color | F dodisplayverbatimstart |
| F colordefagc | F dodisplayverbatimstop |
| F colordefagt | F dofastdefinetypeface |
| F colordefalc | F dofinishsomereference |
| F colordefalt | F doflushparallel |
| F colordeffgc | F dofromfiledescription |
| F colordeffgt | F dofromfileliteral |
| F colordefflc | F dofromurldescription |
| F colordefflt | F dofromurlliteral |
| F colordefrgc | F doinlineverbatimbeginline |
| F colordefrgt | F doinlineverbatimemptyline |
| F colordefrlc | F doinlineverbatimnewline |
| F colordefrlt | F doinlineverbatimstart |
| F concat | F doinlineverbatimstop |
| F constructcs | F domarkinjector |
| F constructcsonly | F donestedtypingstart |
| F convertnumber | F donestedtypingstop |
| F ctxreport | F dosetfastregisterentry |
| F d | F dostarttext |
| F definefontsynonym | F doverbatimspace |
| T delayed | F dummyxcell |
| F digitsdigit | F egroup |
| F digitsfinalcomma | F emptyreference |
| F digitsfinalperiod | F enablemode |

| | |
|-------------------------------|------------------------|
| F endhbox | T metafun |
| F endvbox | F color |
| F environment | T delayed |
| F expandreferencearguments | F start |
| F expandreferenceoperation | F stop |
| F finalizeautostructurelevel | T nested |
| F finishjob | F markingcommand |
| F firstofoneargument | F markingseparator |
| F firstoftwoarguments | F newbox |
| F fixedblankskip | F newcount |
| F flexibleblankskip | F newdimen |
| F flushblankhandling | F newindexer |
| F flushboxregister | F newmuskip |
| F flushnode | F newskip |
| F fntsetdefname | F newtexthandler |
| F fntsetnopsiz | F newtoks |
| F fntsetsomename | F newverbosehandler |
| F fntsetsomesize | F nointerlineskip |
| T formatted | F normalatop |
| F monobold | F normalover |
| F verbatim | F overstrike |
| F fprint | F page |
| T generics | F par |
| S starttabulate | F pdfliteral |
| S stoptabulate | F popcatcodes |
| F getlogger | F poplogger |
| F getreferencestructureprefix | F printlines |
| F getvalue | F processfilemany |
| F glyph | F processfilenone |
| F gobbleoneargument | F processfileonce |
| F gobbletwoarguments | F protect |
| F goto | T puretext |
| F hrule | F pushcatcodes |
| F input | F pushlogger |
| T knownfunctions | F registerentry |
| F l | F registerfunction |
| F lateluafunction | F registeronepage |
| F letvaluerelax | F registerpagerange |
| F llap | F registerseeword |
| F loadfile | F reservefunction |
| F loadfoundtypescriptfile | F rlap |
| F luasetup | F rotate |
| F m | F runfile |
| F makelinenumber | F secondoftwoarguments |

| | |
|--------------------------|-------------------------|
| F setblankcategory | F stopParsedXmlSnippet |
| F setblankorder | F stopTexSnippet |
| F setblankpenalty | F stopXmlSnippet |
| F setconditional | F stopblankhandling |
| F setfalsevalue | F stopcolumns |
| F sethboxregister | F stopcomponentindeed |
| F setsomevalue | F stopenvironmentindeed |
| F settabulateentry | F stopfontclass |
| F settabulatelastentry | F stophboxregister |
| F settracing | F stopproductindeed |
| F setupsystem | F stopprojectindeed |
| F setupwithargument | F stopreadingfile |
| F setvalue | F stopregisterentries |
| F setvboxregister | F stopregisterentry |
| F setxvalue | F stopregisteroutput |
| F space | F stopregisterpages |
| F sprint | F stopregistersection |
| F startLuaSnippet | F stopregisterseewords |
| F startMetapostSnippet | F stoptabulate |
| F startParsedXmlSnippet | F stoptext |
| F startTexSnippet | F stoptitle |
| F startXmlSnippet | F stopvboxregister |
| F startblankhandling | F stopxtitle |
| F startcolumns | F storenode |
| F startcomponentindeed | F synonymentry |
| F startenvironmentindeed | F tabulaterow |
| F startfontclass | F tabulaterowbold |
| F starthboxregister | F tabulaterowtyp |
| F startproductindeed | F tabulaterowtype |
| F startprojectindeed | F template |
| F startreadingfile | T templates |
| F startregisterentries | F texsetup |
| F startregisterentry | F tobuffer |
| F startregisteroutput | F tocontext |
| F startregisterpages | F tolines |
| F startregistersection | F trialtypesetting |
| F startregisterseewords | F unitsC |
| F starttabulate | F unitsN |
| F starttext | F unitsNspace |
| F starttitle | F unitsNstart |
| F startvboxregister | F unitsNstop |
| F startxtitle | F unitsO |
| F stopLuaSnippet | F unitsP |
| F stopMetapostSnippet | F unitsPS |

F unitsPU
 F unitsPUS
 F unitsQ
 F unitsS
 F unitsU
 F unitsUS
 F unprotect
 F unregisterfunction
 F usemodule
 F utfchar
 T verbatim
 F LuaSnippetBoundary
 F LuaSnippetComment
 F LuaSnippetName
 F LuaSnippetNameBase
 F LuaSnippetNameCore
 F LuaSnippetNameLibraries
 F LuaSnippetQuote
 F LuaSnippetSpecial
 F LuaSnippetString
 F MetapostSnippetBoundary
 F MetapostSnippetComment
 F MetapostSnippetConstructor
 F MetapostSnippetName
 F MetapostSnippetNameMetafun
 F MetapostSnippetNamePlain
 F MetapostSnippetNamePrimitive
 F MetapostSnippetQuote
 F MetapostSnippetSpecial
 F MetapostSnippetString
 F ParsedXmlSnippetCdata
 F ParsedXmlSnippetComment
 F ParsedXmlSnippetDoctype
 F ParsedXmlSnippetElement
 F ParsedXmlSnippetInstruction
 F TexSnippetBoundary
 F TexSnippetComment
 F TexSnippetGroup
 F TexSnippetName
 F TexSnippetSpecial
 F XmlSnippetBoundary
 F XmlSnippetCdata
 F XmlSnippetComment
 F XmlSnippetEntity

F XmlSnippetEqual
 F XmlSnippetKey
 F XmlSnippetName
 F XmlSnippetString
 F ctxreport
 F viafile
 F vrule
 F xmldataaafter
 F xmldataabefore
 F xmldataabeyedline
 F xmldataabeyedspace
 F xmlprocessbuffer
 F xmlsetup

numbers

F C
 F EQ
 F FL
 F HL
 F L
 F LL
 F LuaSnippet
 F LuaSnippetBoundary
 F LuaSnippetComment
 F LuaSnippetName
 F LuaSnippetNameBase
 F LuaSnippetNameCore
 F LuaSnippetNameLibraries
 F LuaSnippetQuote
 F LuaSnippetSpecial
 F LuaSnippetString
 F ML
 F MPLIBsetCtext
 F MPLIBsetNtext
 F MPcolor
 F MetapostSnippet
 F MetapostSnippetBoundary
 F MetapostSnippetComment
 F MetapostSnippetConstructor
 F MetapostSnippetName
 F MetapostSnippetNameMetafun
 F MetapostSnippetNamePlain
 F MetapostSnippetNamePrimitive
 F MetapostSnippetQuote
 F MetapostSnippetSpecial

function

| | |
|-------------------------------|--------------------------|
| F MetapostSnippetString | F btchandlelistentry |
| F NC | F btchandlelisttextentry |
| F NR | F btxlistauthorsetup |
| F ParsedXmlSnippetCdata | F btxlistsetup |
| F ParsedXmlSnippetComment | F btxpagesetup |
| F ParsedXmlSnippetDoctype | F btxsetafter |
| F ParsedXmlSnippetElement | F btxsetauthorindex |
| F ParsedXmlSnippetInstruction | F btxsetauthorvariant |
| F ParsedXmlSnippetKey | F btxsetbacklink |
| F ParsedXmlSnippetValue | F btxsetbacktrace |
| F TexSnippet | F btxsetbefore |
| F TexSnippetBoundary | F btxsetcategory |
| F TexSnippetComment | F btxsetcombis |
| F TexSnippetGroup | F btxsetconcat |
| F TexSnippetName | F btxsetcount |
| F TexSnippetSpecial | F btxsetcurrentlistentry |
| F XmlSnippet | F btxsetcurrentlistindex |
| F XmlSnippetBoundary | F btxsetdataset |
| F XmlSnippetCdata | F btxsetfirst |
| F XmlSnippetComment | F btxsetfirstinternal |
| F XmlSnippetEntity | F btxsetfirstnames |
| F XmlSnippetEqual | F btxsetfirstpage |
| F XmlSnippetKey | F btxsetinitials |
| F XmlSnippetName | F btxsetinternal |
| F XmlSnippetString | F btxsetjuniors |
| F __flush | F btxsetlanguage |
| F __flushdirect | F btxsetlastinternal |
| F __flushlines | F btxsetlastpage |
| F a | F btxsetlefttext |
| F addaskedblankskip | F btxsetnoflistentries |
| F addpredefinedblankskip | F btxsetnumber |
| F applyprocessor | F btxsetoverflow |
| F b | F btxsetrighttext |
| F beginhbox | F btxsetsecond |
| F beginvbox | F btxsetsurnames |
| F bf | F btxsettag |
| F bgroup | F btxsetthird |
| F blank | F btxsetvons |
| F btxcheckboxlistcombi | F btxstartauthor |
| F btxcheckboxlistentry | F btxstartcite |
| F btxciteauthorsetup | F btxstartciteauthor |
| F btxcitesetup | F btxstartlistentry |
| F btxdirectlink | F btxstartsubcite |
| F btxflushauthor | F btxstopauthor |

| | |
|----------------------------|---------------------------------|
| F btxstopcite | F digitsspace |
| F btxstopciteauthor | F digitszeropadding |
| F btxstoplistentry | F direct |
| F btxstopsubcite | F doactivateinjector |
| F c | F dodisplayverbatimimbeginline |
| F callfunctiononce | F dodisplayverbatimimemptyline |
| F char | F dodisplayverbatimiminitialize |
| F chardef | F dodisplayverbatimimnewline |
| F color | F dodisplayverbatimimstart |
| F colordefagc | F dodisplayverbatimimstop |
| F colordefagt | F dofastdefinetypeface |
| F colordefalc | F dofinishsomereference |
| F colordefalt | F doflushparallel |
| F colordeffgc | F dofromfiledescription |
| F colordeffgt | F dofromfileliteral |
| F colordefflc | F dofromurldescription |
| F colordefflt | F dofromurlliteral |
| F colordefrgc | F doinlineverbatimimbeginline |
| F colordefrgt | F doinlineverbatimimemptyline |
| F colordefrlc | F doinlineverbatimimnewline |
| F colordefrlt | F doinlineverbatimimstart |
| F concat | F doinlineverbatimimstop |
| F constructcs | F domarkinjector |
| F constructcsonly | F donestedtypingstart |
| F convertnumber | F donestedtypingstop |
| F ctxreport | F dosetfastregisterentry |
| F d | F dostarttext |
| F definefontsynonym | F doverbatimimspace |
| T delayed | F dummyxcell |
| F digitsdigit | F egroup |
| F digitsfinalcomma | F emptyreference |
| F digitsfinalperiod | F enablemode |
| F digitshighspace | F endhbox |
| F digitsintermediatecomma | F endvbox |
| F digitsintermediateperiod | F environment |
| F digitsminus | F expandreferencearguments |
| F digitsnegative | F expandreferenceoperation |
| F digitsplus | F finalizeautostructurelevel |
| F digitspositive | F finishjob |
| F digitspower | F firstofoneargument |
| F digitspowerminus | F firstoftwoarguments |
| F digitspowerplus | F fixedblankskip |
| F digitsseparatorspace | F flexibleblankskip |
| F digitssignspace | F flushblankhandling |

| | |
|-------------------------------|------------------------|
| F flushboxregister | F newmuskip |
| F flushnode | F newskip |
| F fntsetdefname | F newtexthandler |
| F fntsetnopsiz | F newtoks |
| F fntsetsomename | F newverbosehandler |
| F fntsetsomesize | F nointerlineskip |
| T formatted | F normalatop |
| F monobold | F normalover |
| F verbatim | F overstrike |
| F fprint | F page |
| T generics | F par |
| S starttabulate | F pdfliteral |
| S stoptabulate | F popcatcodes |
| F getlogger | F poplogger |
| F getreferencestructureprefix | F printlines |
| F getvalue | F processfilemany |
| F glyph | F processfilenone |
| F gobbleoneargument | F processfileonce |
| F gobbletwoarguments | F protect |
| F goto | T puretext |
| F hrule | F pushcatcodes |
| F input | F pushlogger |
| T knownfunctions | F registerentry |
| F l | F registerfunction |
| F lateluafunction | F registeronepage |
| F letvaluerelax | F registerpagerange |
| F llap | F registerseeword |
| F loadfile | F reservefunction |
| F loadfoundtypescriptfile | F rlap |
| F luasetup | F rotate |
| F m | F runfile |
| F makelinenumber | F secondoftwoarguments |
| T metafun | F setblankcategory |
| F color | F setblankorder |
| T delayed | F setblankpenalty |
| F start | F setconditional |
| F stop | F setfalsevalue |
| T nested | F sethboxregister |
| F markingcommand | F setsomevalue |
| F markingseparator | F settabulateentry |
| F newbox | F settabulatelastentry |
| F newcount | F settracing |
| F newdimen | F setupsystem |
| F newindexer | F setupwithargument |

| | |
|--------------------------|------------------------|
| F setvalue | F stopregisterentries |
| F setvboxregister | F stopregisterentry |
| F setxvalue | F stopregisteroutput |
| F space | F stopregisterpages |
| F sprint | F stopregistersection |
| F startLuaSnippet | F stopregisterseewords |
| F startMetapostSnippet | F stoptabulate |
| F startParsedXmlSnippet | F stoptext |
| F startTexSnippet | F stoptitle |
| F startXmlSnippet | F stopvboxregister |
| F startblankhandling | F stopxtitle |
| F startcolumns | F storenode |
| F startcomponentindeed | F synonymentry |
| F startenvironmentindeed | F tabulaterow |
| F startfontclass | F tabulaterowbold |
| F starthboxregister | F tabulaterowtyp |
| F startproductindeed | F tabulaterowtype |
| F startprojectindeed | F template |
| F startreadingfile | T templates |
| F startregisterentries | F texsetup |
| F startregisterentry | F tobuffer |
| F startregisteroutput | F tocontext |
| F startregisterpages | F tolines |
| F startregistersection | F trialtypesetting |
| F startregisterseewords | F unitsC |
| F starttabulate | F unitsN |
| F starttext | F unitsNspace |
| F starttitle | F unitsNstart |
| F startvboxregister | F unitsNstop |
| F startxtitle | F unitsO |
| F stopLuaSnippet | F unitsP |
| F stopMetapostSnippet | F unitsPS |
| F stopParsedXmlSnippet | F unitsPU |
| F stopTexSnippet | F unitsPUS |
| F stopXmlSnippet | F unitsQ |
| F stopblankhandling | F unitsS |
| F stopcolumns | F unitsU |
| F stopcomponentindeed | F unitsUS |
| F stopenvironmentindeed | F unprotect |
| F stopfontclass | F unregisterfunction |
| F stophboxregister | F usemodule |
| F stopproductindeed | F utfchar |
| F stopprojectindeed | T verbatim |
| F stopreadingfile | F LuaSnippetBoundary |

| | | |
|--------------------------------|-------------------------------------|----------|
| F LuaSnippetComment | F xmlsetup | |
| F LuaSnippetName | objectnumber | function |
| F LuaSnippetNameBase | objectpage | function |
| F LuaSnippetNameCore | octnumber | function |
| F LuaSnippetNameLibraries | octstringtonumber | function |
| F LuaSnippetQuote | ordinal | function |
| F LuaSnippetSpecial | overloadbookmark | function |
| F LuaSnippetString | page_injections_flush_after | function |
| F MetapostSnippetBoundary | page_injections_flush_before | function |
| F MetapostSnippetComment | page_injections_save | function |
| F MetapostSnippetConstructor | pagestaterealpage | function |
| F MetapostSnippetName | percentageof | function |
| F MetapostSnippetNameMetafun | pgfxcolorspec | function |
| F MetapostSnippetNamePlain | pickupbuffer | function |
| F MetapostSnippetNamePrimitive | placeparallel | function |
| F MetapostSnippetQuote | popfloat | function |
| F MetapostSnippetSpecial | pophyphenation | function |
| F MetapostSnippetString | popitaliccorrection | function |
| F ParsedXmlSnippetCdata | poplist | function |
| F ParsedXmlSnippetComment | popreferenceprefix | function |
| F ParsedXmlSnippetDoctype | popregime | function |
| F ParsedXmlSnippetElement | popsectionblock | function |
| F ParsedXmlSnippetInstruction | postthyphenchar | function |
| F TexSnippetBoundary | postponenotes | function |
| F TexSnippetComment | prefixedconverted | function |
| F TexSnippetGroup | prehyphenchar | function |
| F TexSnippetName | prepareMPvariable | function |
| F TexSnippetSpecial | preparedfile | function |
| F XmlSnippetBoundary | presetsymbollist | function |
| F XmlSnippetCdata | presettabulate | function |
| F XmlSnippetComment | prevcountervalue | function |
| F XmlSnippetEntity | processbodyfontsizes | function |
| F XmlSnippetEqual | processbuffer | function |
| F XmlSnippetKey | processcolorcomponents | function |
| F XmlSnippetName | processedfile | function |
| F XmlSnippetString | processedfiles | function |
| F ctxreport | processfile | function |
| F viafile | processfilemany | function |
| F vrule | processfilenone | function |
| F xmldataafter | processfileonce | function |
| F xmldatabefore | processjob | function |
| F xmldataobeyedline | processlist | function |
| F xmldataobeyedspace | processregister | function |
| F xmlprocessbuffer | processsplit | function |

| | | | |
|-------------------------------------|-----------------|---------------------------------|-----------------|
| processsynonyms | function | renderingvar | function |
| purefontname | function | replacemissingcharacters | function |
| pushfloat | function | reportstructure | function |
| pushhyphenation | function | resavefloat | function |
| pushitaliccorrection | function | resetcharacteralign | function |
| pushlist | function | resetcounter | function |
| pushreferenceprefix | function | resetfontfeature | function |
| pushregime | function | resetfontsolution | function |
| pushsectionblock | function | resetinjector | function |
| rawcharacter | function | resetmarking | function |
| rawcountervalue | function | resetmathattributes | function |
| rawdate | function | resetmathitalics | function |
| referencepagestate | function | resetnullfont | function |
| referencerealpage | function | resetparallel | function |
| registerattachment | function | resetprevdepth | function |
| registerbodyfontsize | function | resetreference | function |
| registerbookmark | function | resetstructureprocessor | function |
| registerbuttons | function | resettimer | function |
| registercatcodetable | function | restartcounter | function |
| registercolor | function | restorecounter | function |
| registercolorintent | function | restorecurrentattributes | function |
| registeredviewerlayer | function | restorenote | function |
| registerhelp | function | romannumerals | function |
| registerhyphenationexception | function | runbuffer | function |
| registerhyphenationpattern | function | safechar | function |
| registeritemgroup | function | savebuffer | function |
| registerlanguagefeatures | function | savecounter | function |
| registerlinenumbering | function | savecurrentattributes | function |
| registermaintextcolor | function | savedlistnumber | function |
| registernamespace | function | savedlistprefixednumber | function |
| registerpostponedblock | function | savedlisttitle | function |
| registerrendering | function | savefloat | function |
| registersection | function | savemargindata | function |
| registersoundclip | function | savenote | function |
| registerstructureprocessor | function | saveobject | function |
| registersynonym | function | savepagedata | function |
| registertoken | function | saveparallel | function |
| registertransparency | function | savestructureblock | function |
| registerunit | function | savetaggedtwopassdata | function |
| registeruserdata | function | savetwopassdata | function |
| relatemarking | function | savevariable | function |
| remapentity | function | second | function |
| removemissingcharacters | function | selectstructureblock | function |
| removepunctuation | function | setbreakpoints | function |

| | | | |
|---------------------------------|----------|---------------------------------|----------|
| setbtxdataset | function | setmarking | function |
| setbtxentry | function | setmathalternate | function |
| setbtxregister | function | setmathdirection | function |
| setbtxspefication | function | setmathitalics | function |
| setcharacteralign | function | setnextinternalreference | function |
| setcharactercasing | function | setnextreferenceorder | function |
| setcharactercleaning | function | setnotestate | function |
| setcharactercodes | function | setnotesymbolpage | function |
| setcharacterkerning | function | setobject | function |
| setcharacterspacing | function | setopendocumentaction | function |
| setcharacterstripping | function | setopenpageaction | function |
| setclosedocumentaction | function | setowncounter | function |
| setclosepageaction | function | setpagestate | function |
| setcolormodel | function | setpagestaterealpageno | function |
| setcounter | function | setpagetransition | function |
| setdataset | function | setparbuilder | function |
| setdigitsmanipulation | function | setrandomseed | function |
| setdirection | function | setrealign | function |
| setdocumentenvironments | function | setrealspaces | function |
| setdocumentfilenames | function | setreferencearguments | function |
| setdocumentmodes | function | setreferenceattribute | function |
| setdocumentmodules | function | setreferenceoperation | function |
| setelementuserproperties | function | setregistermethod | function |
| setfigurelookuporder | function | setreplacements | function |
| setfirstline | function | setsectionblock | function |
| setfontfeature | function | setsectionentry | function |
| setfontofid | function | setsectionlevel | function |
| setfontsolution | function | setsectionnumber | function |
| setformat | function | setstructureblockstate | function |
| setformsmethod | function | settagaspect | function |
| sethyphenationfeatures | function | settagcombination | function |
| setinitial | function | settagdescription | function |
| setinjector | function | settagdescriptionsymbol | function |
| setinsertionlocation | function | settagfigure | function |
| setinterfaceconstant | function | settaghighlight | function |
| setinterfaceelement | function | settagitemgroup | function |
| setinterfacemessage | function | settaglist | function |
| setinterfacemessages | function | settagproperty | function |
| setinterfacevariable | function | settagregister | function |
| setinternalreference | function | settagsorting | function |
| setjobcomment | function | settagsynonym | function |
| setlanguageexceptions | function | settagtablecell | function |
| setlanguagesynonym | function | settagtabulatecell | function |
| setlayer | function | setupbookmarks | function |

| | | | |
|-----------------------------------|----------|----------------------------------|----------|
| setupcanvas | function | startparbuilder | function |
| setupcharacterspacing | function | startproduct | function |
| setupexport | function | startproject | function |
| setupfontexpansion | function | startregime | function |
| setupfontprotrusion | function | startsectionlevel | function |
| setuphyphenation | function | starttag | function |
| setupidentity | function | starttext | function |
| setupinsertion | function | startviewerlayer | function |
| setupitaliccorrection | function | stopactualtext | function |
| setuplinenumbering | function | stopchemical | function |
| setvisual | function | stopcolorset | function |
| setxmpfile | function | stopcomponent | function |
| showassignerror | function | stopenvironment | function |
| showattributes | function | stopfontsolution | function |
| showbtxdatasetauthors | function | stopparbuilder | function |
| showbtxdatasetcompleteness | function | stopproduct | function |
| showbtxdatasetfields | function | stopproject | function |
| showbtxentry | function | stopregime | function |
| showbtxfields | function | stopsectionlevel | function |
| showbtxtables | function | stoptag | function |
| showbtxvariants | function | stoptext | function |
| showcallbacks | function | stopviewerlayer | function |
| showchardata | function | storejavascriptcode | function |
| showcounter | function | storejavascriptpreamble | function |
| showdiscretionaries | function | storenote | function |
| showfontparameters | function | storeregister | function |
| showhyphenatedinlist | function | strdp | function |
| showhyphenationtrace | function | strhd | function |
| showinjector | function | strht | function |
| showjustification | function | strip | function |
| showmessage | function | structureautocatcodedget | function |
| showtokens | function | structurecatcodedget | function |
| sin | function | structuregivencatcodedget | function |
| sind | function | structurenumber | function |
| splitfilename | function | structuretitle | function |
| spotcolorname | function | structureuservariable | function |
| spotcolorparent | function | structurevariable | function |
| spotcolorvalue | function | strwd | function |
| startactualtext | function | subcountervalues | function |
| startchemical | function | synchronizecolormodel | function |
| startcolorset | function | synchronizemarking | function |
| startcomponent | function | systemlog | function |
| startenvironment | function | taggedmathfunction | function |
| startfontsolution | function | tan | function |

| | | | |
|-------------------------------|----------|-----------------------------------|----------|
| tand | function | usezipfile | function |
| testcase | function | utfchar | function |
| testtokens | function | utfmathclass | function |
| textime | function | utfmathcommand | function |
| thefirstcharacter | function | utfmathcommandabove | function |
| theremainingcharacters | function | utfmathcommandbelow | function |
| thetexdefinition | function | utfmathcommandfiller | function |
| tochar | function | utfmathfiller | function |
| transparencycomponents | function | utfmathstretch | function |
| triggereffect | function | vboxlisttohbox | function |
| triggernegative | function | verbose | function |
| truefilename | function | visual | function |
| typebuffer | function | vspacing | function |
| typefile | function | vspacingcollapse | function |
| typestring | function | vspacingdefine | function |
| uchexnumber | function | vspacingsetamount | function |
| uchexnumbers | function | vspacingsnap | function |
| undefinechemical | function | way | function |
| unicodechar | function | weekday | function |
| unit | function | weekdayname | function |
| unloadlanguage | function | writestatus | function |
| upper | function | x_table_c | function |
| useMPLibrary | function | x_table_cleanup | function |
| useanyfile | function | x_table_construct | function |
| usebtxdataset | function | x_table_create | function |
| usecldfilename | function | x_table_finish_row | function |
| usecolors | function | x_table_flush | function |
| usecomponent | function | x_table_init_construct | function |
| useenvironment | function | x_table_init_reflow_height | function |
| usefile | function | x_table_init_reflow_width | function |
| usejavascriptpreamble | function | x_table_next_row | function |
| usejavascriptscripts | function | x_table_r | function |
| uselibrary | function | x_table_reflow_height | function |
| useluafile | function | x_table_reflow_width | function |
| uselua module | function | x_table_set_construct | function |
| usemodules | function | x_table_set_reflow_height | function |
| usepath | function | x_table_set_reflow_width | function |
| useproduct | function | year | function |
| useproject | function | | |
| usesubpath | function | | |
| usesymbols | function | | |
| usetexfile | function | | |
| useurl | function | | |
| usexmlfile | function | | |

containers (context)

| | |
|-------------------|----------|
| cleannname | function |
| content | function |
| define | function |
| is_usable | function |
| is_valid | function |
| read | function |
| usecache | boolean |
| write | function |

converters (context)

| | | | |
|---------------------------|----------|--------------------------|------------|
| A | function | month | function |
| AK | function | nofdays | function |
| Alphabetic | function | number | function |
| Character | function | numbers | function |
| Characters | function | octstringtonumber | function |
| Characters:es | function | ordinal | function |
| I | function | r | function |
| KA | function | rawcharacter | function |
| KR | function | romannumerals | function |
| R | function | second | function |
| RK | function | sequences | data table |
| Romannumerals | function | sloviannumerals | function |
| Sloviannumerals | function | spanishnumerals | function |
| Spanishnumerals | function | textime | function |
| Word | function | toabjad | function |
| Words | function | tochinese | function |
| a | function | toroman | function |
| abjadnodotnumerals | function | upper | function |
| abjadnumerals | function | verbose | table |
| alphabetic | function | D data | |
| character | function | F translate | |
| characters | function | weekday | function |
| characters:es | function | word | function |
| chineseallnumerals | function | words | function |
| chinesecapnumerals | function | year | function |
| chinesenumerals | function | | |
| chr | function | | |
| chrs | function | | |
| cn | function | | |
| cn-a | function | | |
| cn-c | function | | |
| convert | function | | |
| define | function | | |
| hexstringtonumber | function | | |
| hour | function | | |
| i | function | | |
| isleapyear | function | | |
| leapyear | function | | |
| lower | function | | |
| maxchrs | function | | |
| minute | function | | |

coroutine (basic lua)

| | |
|----------------|----------|
| create | function |
| resume | function |
| running | function |
| status | function |
| wrap | function |
| yield | function |

ctxrunner (context)

| | |
|------------------|------------|
| load | function |
| prepfiles | data table |
| resolve | function |

debug (basic lua)

| | |
|---------------------|----------|
| debug | function |
| getfenv | function |
| gethook | function |
| getinfo | function |
| getlocal | function |
| getmetatable | function |
| getregistry | function |
| getupvalue | function |
| getuservalue | function |
| setfenv | function |
| sethook | function |
| setlocal | function |
| setmetatable | function |
| setupvalue | function |
| setuservalue | function |
| traceback | function |
| upvalueid | function |
| upvaluejoin | function |

dir (context)

| | |
|-----------------------|----------|
| collectpattern | function |
| current | function |
| expandname | function |
| found | function |
| glob | function |
| globfiles | function |
| globpattern | function |
| ls | function |
| makedirs | function |
| mkdirs | function |
| pop | function |
| push | function |

directives (context)

| | |
|-----------------|------------|
| data | data table |
| default | function |
| disable | function |
| enable | function |
| list | function |
| name | string |
| register | function |
| report | function |
| show | function |
| value | function |

document (context)

| | |
|---------------------------|------------|
| arguments | data table |
| files | table |
| getargument | function |
| getfilename | function |
| options | table |
| T commandline | |
| D environments | |
| D modes | |
| D modules | |
| T ctxfile | |
| D environments | |
| D modes | |
| D modules | |
| setargument | function |
| setdefaultargument | function |
| setfilename | function |
| variables | data table |

environment (context)

| | | | |
|-------------------------------|------------|---------------------|------------|
| argument | function | texroot | string |
| arguments | data table | truefilename | function |
| basicengines | data table | validengines | data table |
| currentrun | number | | |
| default_texmfcnf | string | | |
| engineflags | data table | | |
| filename | string | | |
| files | table | | |
| filesynonyms | data table | | |
| forcedruns | number | | |
| getargument | function | | |
| homedir | string | | |
| initex | boolean | | |
| initializearguments | function | | |
| initializefilenames | function | | |
| inputfilebarename | string | | |
| inputfilename | string | | |
| inputfilesuffix | string | | |
| jobfilename | string | | |
| jobfilesuffix | string | | |
| kindofrun | number | | |
| loadluafile | function | | |
| luafile | function | | |
| luafilechunk | function | | |
| maxnofruns | number | | |
| originalarguments | data table | | |
| outputfilename | string | | |
| ownbin | string | | |
| ownmain | string | | |
| ownname | string | | |
| ownpath | string | | |
| prerollrun | boolean | | |
| rawarguments | data table | | |
| reconstructcommandline | function | | |
| relativepath | function | | |
| setargument | function | | |
| splitarguments | function | | |
| suffix | string | | |
| texfile | function | | |
| texmfos | string | | |
| texos | string | | |

epdf (extra tex)

| | |
|----------------------------|---------------------|
| Array | function |
| Attribute | function |
| AttributeOwner_Type | function |
| Attribute_Type | function |
| Dict | function |
| Object | function |
| PDFRectangle | function |
| StructElement_Type | function |
| open | overloaded function |
| type | function |

experiments (context)

| | |
|-----------------|------------|
| data | data table |
| default | function |
| disable | function |
| enable | function |
| list | function |
| name | string |
| register | function |
| report | function |
| show | function |
| value | function |

figures (context)

| | | | |
|-------------------------|------------|-------------------------|------------|
| applyratio | function | F totable | |
| badname | function | F types | |
| bases | data table | F write | |
| bitmapimage | function | include | function |
| boxnumber | number | includes | data table |
| cachepaths | data table | initialize | function |
| check | function | loaded | data table |
| checkers | data table | localpaths | data table |
| converters | data table | magics | data table |
| current | function | mergegoodies | function |
| defaultdepth | number | nofprocessed | number |
| defaultheight | number | order | data table |
| defaultsearch | boolean | paths | data table |
| defaultwidth | number | patterns | data table |
| done | function | pop | function |
| dummy | function | preferquality | boolean |
| exists | data table | programs | data table |
| exists | function | push | function |
| formats | data table | registerpattern | function |
| found | data table | registerresource | function |
| get | function | registersuffix | function |
| getrealpage | function | resources | data table |
| guess | function | scale | function |
| hash | function | setlookups | function |
| identifiers | data table | setorder | function |
| identify | function | setpaths | function |
| images | table | suffixes | data table |
| F boxes | | used | data table |
| F check | | | |
| F checksize | | | |
| F clone | | | |
| F copy | | | |
| F immediatewrite | | | |
| F keys | | | |
| F new | | | |
| F node | | | |
| F ofindex | | | |
| F package | | | |
| F print | | | |
| F scan | | | |
| F serialize | | | |

file (basic lua)

| | |
|--------------------------|----------|
| addsuffix | function |
| basename | function |
| checksum | function |
| collapsepath | function |
| copy | function |
| dirname | function |
| expandname | function |
| extname | function |
| is_qualified_path | function |
| is_readable | function |
| is_rootbased_path | function |
| is_writable | function |
| isreadable | function |
| iswritable | function |
| join | function |
| joinpath | function |
| loadchecksum | function |
| nameonly | function |
| nametotable | function |
| needs Updating | function |
| needsupdating | function |
| pathpart | function |
| readdata | function |
| removesuffix | function |
| replacesuffix | function |
| reslash | function |
| robustname | function |
| savechecksum | function |
| savedata | function |
| size | function |
| splitbase | function |
| splitname | function |
| splitpath | function |
| strip | function |
| suffix | function |
| suffixes | function |
| suffixesonly | function |
| suffixonly | function |
| syncmtimes | function |

floats (context)

| | |
|-------------------------|----------|
| analysemethod | function |
| checkedpagefloat | function |
| collect | function |
| consult | function |
| flush | function |
| getvariable | function |
| nofstacked | function |
| pop | function |
| push | function |
| resave | function |
| save | function |
| stacked | function |

font (basic tex)

| | |
|-----------------|---------------------|
| current | function |
| define | function |
| each | function |
| fonts | table |
| frozen | function |
| getfont | overloaded function |
| id | function |
| max | function |
| nextid | function |
| read_tfm | function |
| read_vf | function |
| setfont | function |

fontloader (extra tex)

| | |
|--------------------------|---------------------|
| apply_afmfile | function |
| apply_featurefile | function |
| close | function |
| fields | function |
| fullinfo | function |
| info | overloaded function |
| open | overloaded function |
| to_table | function |
| totable | function |

fonts (context)

| | | | |
|--------------------|-------|---------------------------|-----------|
| analyzers | table | | |
| T features | | | F report |
| N blwf | | | F reset |
| N fina | | | T vectors |
| N half | | constructors | table |
| N init | | F addcoreunicodes | |
| N isol | | F aftercopyingcharacters | |
| N medi | | F applymanipulators | |
| N pref | | F assignmathparameters | |
| N pstf | | B autocleanup | |
| N rphf | | F beforecopyingcharacters | |
| D initializers | | D cache | |
| D methods | | B cacheintex | |
| F setstate | | F calculatescale | |
| T states | | F checkedfeatures | |
| N blwf | | F checkedfilename | |
| N fina | | F checkvirtualids | |
| N half | | F cleanupable | |
| N init | | F collectprocessors | |
| N isol | | D designsizes | |
| N mark | | D dontembed | |
| N medi | | F enhanceparameters | |
| N pref | | N factor | |
| N pstf | | F finalize | |
| N rest | | F getfeatureaction | |
| N rphf | | F hashfeatures | |
| B useunicodemarks | | F hashinstance | |
| checkers | table | T hashmethods | |
| F getmissing | | F normal | |
| F missing | | F virtual | |
| cid | table | F initializefeatures | |
| F getmap | | T keys | |
| F loadfile | | T character | |
| collections | table | S depth | |
| F checkenabled | | S height | |
| F clonevector | | S italic | |
| F define | | S width | |
| T definitions | | T description | |
| F prepare | | T boundingbox | |
| F process | | S depth | |
| F registermain | | S height | |
| | | S width | |

| | | |
|--------------------------|-----------------------|----------|
| T parameters | T cidinfo | |
| S ascender | S embedding | |
| S descender | S encodingbytes | |
| S designsize | S filename | |
| T expansion | S finalized | |
| S auto | S fontname | |
| S shrink | S format | |
| S step | S fullname | |
| S stretch | S hasitalics | |
| S extendfactor | S hasmath | |
| S factor | S mathitalics | |
| S hfactor | S mode | |
| S mathsize | S name | |
| T protrusion | S noglyphnames | |
| S auto | S nostackmath | |
| S quad | S psname | |
| S scaledpoints | S textitalics | |
| S scriptpercentage | S virtualized | |
| S scriptscriptpercentage | D loadedfonts | |
| S size | S namemode | |
| S slantfactor | F newfeatures | |
| S slantperpoint | F newhandler | |
| T spacing | N noffontsloaded | |
| S extra | N nofsharedfonts | |
| S shrink | N nofsharedhashes | |
| S stretch | N nofsharedvectors | |
| S width | N privateoffset | |
| T synonyms | F readanddefine | |
| S em | F registerfeature | |
| S ex | B resolvevirtualtoo | |
| S extra_space | F scale | |
| S extraspace | F scaled | |
| S slant | F setfactor | |
| S space | F setname | |
| S space_shrink | B sharefonts | |
| S space_stretch | F trytosharefont | |
| S spaceshrink | N version | |
| S spacestretch | current | function |
| S x_height | currentid | function |
| S units | definers | table |
| S vfactor | F addlookup | |
| S xheight | F analyze | |
| T properties | F applypostprocessors | |
| S autoitalicamount | F checkedmode | |

| | |
|--------------------------------|---------------------|
| F checkedscript | N Fitacyrillic |
| F current | N Gcedilla |
| S defaultlookup | N Gdot |
| F define | N Gecyrillic |
| F getspecification | N Gheupturncyrillic |
| F internal | N Gjecyrillic |
| F loadfont | N Hardsigncyrillic |
| F makespecification | N IAcyrillic |
| T methods | N IUcyrillic |
| F install | N Icyrillic |
| D variants | N Idot |
| F read | N Iecyrillic |
| F register | N Iicyrillic |
| F registered | N Iishortcyrillic |
| F registersplit | N Iocyrillic |
| F resetnullfont | N Izhitsacyrillic |
| F resolve | N Jecyrillic |
| T resolvers | N Kacyrillic |
| F file | N Kcedilla |
| F name | N Khacyrillic |
| F spec | N Kjecyrillic |
| definetypeface function | N Lcedilla |
| encodings table | N Ljecyrillic |
| T agl | N Ncedilla |
| D extras | N Njecyrillic |
| D names | N Ocyrillic |
| T synonyms | N Odblacute |
| N Acyrillic | N Ohm |
| N Becyrillic | N Pecyrillic |
| N Cdot | N Rcedilla |
| N Checyrillic | N Shacyrillic |
| N Decyrillic | N Shchacyrillic |
| N Djecyrillic | N Softsigncyrillic |
| N Dzecyrillic | N Tcedilla |
| N Dzhecyrillic | N Tecyrillic |
| N Ecyrillic | N Tsecyrillic |
| N Edot | N Tshacyrillic |
| N Efcyrillic | N Ucyrillic |
| N Elcyrillic | N Udblacute |
| N Emcyrillic | N Ushortcyrillic |
| N Encyrillic | N Vecyrillic |
| N Ercyrillic | N Yatcyrillic |
| N Ereversedcyrillic | N Yericyrillic |
| N Escyrillic | N Yicyrillic |

| | |
|-----------------------------|--------------------------|
| N Zdot | N daletqamats |
| N Zecyrillic | N daletqamatshebrew |
| N Zhecyrillic | N daletqubuts |
| N acutecmb | N daletqubutshebrew |
| N acyrillic | N daletsegol |
| N afii00208 | N daletsegolhebrew |
| N afii08941 | N daletsheva |
| N afii57694 | N daletshevahebrew |
| N afii57695 | N dalettsere |
| N afii57700 | N dammaarabic |
| N afii57705 | N dammatanaltonearabic |
| N afii57723 | N dargahebrew |
| N alef | N dbllowline |
| N alefmaksurainitialarabic | N decimalseparatorarabic |
| N alefmaksuramedialarabic | N dialytikatonos |
| N approximatelyequal | N dotbelowcmb |
| N asteriskaltonearabic | N doubleyodpatah |
| N ayin | N doubleyodpatahhebrew |
| N bet | N edot |
| N betdagesh | N eightarabic |
| N blackdownpointingtriangle | N eighthnotebeamed |
| N blackleftpointingpointer | N etnahtafoukhhebrew |
| N blackrectangle | N etnahtafoukhlefthebrew |
| N blackrightpointingpointer | N etnahtahebrew |
| N blacksmilingface | N fathaarabic |
| N blacksquare | N finalkaf |
| N blackuppointingtriangle | N finalkafdagesh |
| N bulletinverse | N finalkafhebrew |
| N cdot | N finalkafqamats |
| N compass | N finalkafqamatshebrew |
| N dagesh | N finalkafsheva |
| N dalet | N finalmem |
| N daletdagesh | N finalnun |
| N dalethatafpatah | N finalpe |
| N dalethatafpatahhebrew | N finaltsadi |
| N dalethatafsegol | N fivearabic |
| N dalethatafsegolhebrew | N forall |
| N dalethebrew | N fourarabic |
| N dalethiriq | N gcedilla |
| N dalethiriqhebrew | N gdot |
| N daletholam | N gimel |
| N daletholamhebrew | N gimeldagesh |
| N daletpatah | N gravecmb |
| N daletpatahhebrew | N haaltonearabic |

| | |
|----------------------------|----------------------------------|
| N hamzaarabic | N holamhebrew |
| N hamzadammaarabic | N holamnarrowhebrew |
| N hamzadammatanarabic | N holamquarterhebrew |
| N hamzafathaarabic | N ilde |
| N hamzafathatanarabic | N integralbottom |
| N hamzalowarabic | N integraltop |
| N hamzalowkasraarabic | N kaf |
| N hamzalowkasratanarabic | N kafdagesh |
| N hatafpatah | N kashidaautoarabic |
| N hatafpatah16 | N kashidaautonosidebearingarabic |
| N hatafpatah23 | N kcedilla |
| N hatafpatah2f | N lamed |
| N hatafpatahhebrew | N lameddagesh |
| N hatafpatahnarrowhebrew | N lamedhebrew |
| N hatafpatahquarterhebrew | N lamedholam |
| N hatafqamats | N lamedholamdagesh |
| N hatafqamats1b | N lamedholamdageshhebrew |
| N hatafqamats28 | N laminitialarabic |
| N hatafqamats34 | N lammeemjeeminitialarabic |
| N hatafqamatshebrew | N lcedilla |
| N hatafqamatsnarrowhebrew | N logicalnotreversed |
| N hatafqamatsquarterhebrew | N mahapakhhebrew |
| N hatafsegol | N mem |
| N hatafsegol17 | N memdagesh |
| N hatafsegol24 | N merkhahebrew |
| N hatafsegol30 | N merkhakefulahebrew |
| N hatafsegolhebrew | N middot |
| N hatafsegolnarrowhebrew | N munahhebrew |
| N hatafsegolquarterhebrew | N nbspace |
| N he | N ncedilla |
| N hedagesh | N newsheqelsign |
| N hefinalalttwoarabic | N ninearabic |
| N het | N noonhehinitialarabic |
| N hiriq | N nun |
| N hiriq14 | N nundagesh |
| N hiriq21 | N odblacute |
| N hiriq2d | N onearabic |
| N hiriqhebrew | N overscore |
| N hiriqnarrowhebrew | N patah |
| N hiriqqarterhebrew | N patah11 |
| N holam | N patah1d |
| N holam19 | N patah2a |
| N holam26 | N patahhebrew |
| N holam32 | N patahnarrowhebrew |

N patahquarterhebrew

N pe

N pedagesh

N qamats

N qamats10

N qamats1a

N qamats1c

N qamats27

N qamats29

N qamats33

N qamatsde

N qamatshebrew

N qamatsnarrowhebrew

N qamatsqatanhebrew

N qamatsqatannarrowhebrew

N qamatsqatanquarterhebrew

N qamatsqatanwidehebrew

N qamatsquarterhebrew

N qof

N qofdagesh

N qofhatafpatah

N qofhatafpatahhebrew

N qofhatafsegol

N qofhatafsegolhebrew

N qofhebrew

N qofhiriq

N qofhiriqhebrew

N qofholam

N qofholamhebrew

N qofpatah

N qofpatahhebrew

N qofqamats

N qofqamatshebrew

N qofqubuts

N qofqubutshebrew

N qofsegol

N qofsegolhebrew

N qofsheva

N qofshevahebrew

N qoftsere

N qubuts

N qubuts18

N qubuts25

N qubuts31

N qubutshebrew

N qubutsnarrowhebrew

N qubutsquarterhebrew

N quotelleftreversed

N rafe

N rcedilla

N reharabic

N resh

N reshhatafpatah

N reshhatafpatahhebrew

N reshhatafsegol

N reshhatafsegolhebrew

N reshhebrew

N reshhiriq

N reshhiriqhebrew

N reshholam

N reshholamhebrew

N reshpatah

N reshpatahhebrew

N reshqamats

N reshqamatshebrew

N reshqubuts

N reshqubutshebrew

N reshsegol

N reshsegolhebrew

N reshsheva

N reshshevahebrew

N reshtsere

N reviahebrew

N samekh

N samekhdagesh

N segol

N segol13

N segol1f

N segol2c

N segolhebrew

N segolnarrowhebrew

N segolquarterhebrew

N sevenarabic

N sfthyphen

N shaddaarabic

N sheqel

N sheva

N sheva115

| | | |
|----------------------------|-------------------------|------------|
| N sheva15 | N zayin | |
| N sheva22 | N zayindagesh | |
| N sheva2e | N zdot | |
| N shevahebrew | N zeroarabic | |
| N shevanarrowhebrew | D unicodes | |
| N shevaquarterhebrew | D cache | |
| N shin | F is_known | |
| N shindagesh | D known | |
| N shindageshshindot | F load | |
| N shindageshsindot | F make_unicode_vector | |
| N shinshindot | D math | |
| N shinsindot | N version | |
| N siluqhebrew | expansions | data table |
| N sixarabic | formats | data table |
| N tav | goodies | table |
| N tavadages | D colorschemes | |
| N tavadagesh | D data | |
| N tcedilla | D designsizes | |
| N tchehinitialarabic | D filenames | |
| N tet | F getcompositions | |
| N tetdagesh | T list | |
| N tevirhebrew | F compositions | |
| N thousandsseparatorarabic | F designsizes | |
| N threearabic | F expansions | |
| N tildecmb | F featureset | |
| N tipehahebrew | F filenames | |
| N tsadi | F files | |
| N tsadidagesh | F mathematics | |
| N tsere | F protrusions | |
| N tsere12 | F solutions | |
| N tsere1e | F treatments | |
| N tsere2b | F typefaces | |
| N tserehebrew | F load | |
| N tserenarrowhebrew | F prepare_features | |
| N tserequarterhebrew | F register | |
| N twoarabic | F registerpostprocessor | |
| N udblacute | F report | |
| N vav | handlers | table |
| N vavdagesh | T afm | |
| N vavdagesh65 | B addkerns | |
| N vavholam | B addligatures | |
| N yerahbenyomohebrew | B addtexligatures | |
| N yod | B autoprefixed | |
| N yoddagesh | D cache | |

| | |
|---|----------------------------|
| D features | F gsub_multiple |
| T helpdata | F gsub_reversecontextchain |
| D bothkerned | F gsub_single |
| D leftkerned | F load |
| D ligatures | F scriptandlanguage |
| D rightkerned | F setcontextchain |
| D texligatures | F setdynamics |
| F load | F setfeatures |
| F setfeatures | T statistics |
| B syncspace | D usedfeatures |
| N version | T tables |
| T otf | D baselines |
| F addfeature | D features |
| D cache | D languages |
| T chainhandlers | D scripts |
| F normal | N version |
| F verbose | T pfb |
| F collectlookups | T tfm |
| F dataset | D features |
| S defaultbasealternate | F setfeatures |
| S defaultnodealternate | T vf |
| D enhancers | T combinations |
| D features | F combine |
| F fileformat | T combiner |
| F getalternate | D commands |
| T glists | F find |
| T handlers | D helpers |
| F contextchain | D math |
| F devanagari_remove_joiners | D predefined |
| F devanagari_reorder_matras | D whatever |
| F devanagari_reorder_pre_base_reordering_consonants | hashes |
| F devanagari_reorder_reph | table |
| F gpos_context | D characters |
| F gpos_contextchain | D csnames |
| F gpos_cursive | D descriptions |
| F gpos_mark2base | D dynamics |
| F gpos_mark2ligature | D emwidths |
| F gpos_mark2mark | D exheights |
| F gpos_pair | D extensibles |
| F gpos_single | D features |
| F gsub_alterate | D identifiers |
| F gsub_context | D italics |
| F gsub_contextchain | D lastmathids |
| F gsub_ligature | D marks |
| | D modes |

| | |
|---------------------------|-----------------------|
| D originals | S pc |
| D parameters | S pd |
| T processes | S pe |
| D properties | S pf |
| D quads | S pi |
| D resources | S po |
| T setdynamics | S ps |
| D spaces | S sc |
| D spacings | S sk |
| D unicodes | S sm |
| D xheights | S so |
| helpers table | F format |
| F addprivate | F onetimemessage |
| F dimenfactor | F register |
| F expandglyph | F reportdefinedfonts |
| F fontpatternhassize | F reportusedfeatures |
| F getdigitwidth | mappings table |
| F getparameters | F addtounicode |
| F getprivatenode | F fromunicode16 |
| F hasprivate | F loadfile |
| F indextoslot | F loadline |
| F name | F loadlumtable |
| F nametoslot | F makenameparser |
| F setdigitwidth | T overloads |
| F splitfontpattern | T IJ |
| F tochar | N mess |
| iterators table | S name |
| F characters | T unicode |
| F descriptions | T I_J |
| F glyphs | N mess |
| loggers table | S name |
| F add_placeholders | T unicode |
| T category_to_placeholder | T f_f |
| S ll | N mess |
| S lm | S name |
| S lo | T unicode |
| S lt | T f_f_i |
| S lu | N mess |
| S mc | S name |
| S me | T unicode |
| S mn | T f_f_l |
| S nd | N mess |
| S nl | S name |
| S no | T unicode |

T f_i
 N mess
 S name
 T unicode
 T f_j
 S name
 T unicode
 T f_k
 S name
 T unicode
 T f_l
 N mess
 S name
 T unicode
 T ff
 N mess
 S name
 T unicode
 T ffi
 N mess
 S name
 T unicode
 T ffl
 N mess
 S name
 T unicode
 T fi
 N mess
 S name
 T unicode
 T fj
 S name
 T unicode
 T fk
 S name
 T unicode
 T fl
 N mess
 S name
 T unicode
 T i_j
 N mess
 S name
 T unicode

T ij
 N mess
 S name
 T unicode
 F reset
 F tounicode
 F tounicode16
 F tounicode16sequence
mp **table**
 D cache
 B inline
 N version
names **data table**
nulldata **data table**
protrusions **data table**
readers **table**
 F afm
 F check_lua
 F check_tfm
 F dfont
 F lua
 F opentype
 F otf
 F pfb
 D sequence
 F tfm
 F ttc
 F ttf
select **table**
 T data
 F definetypeface
 T fallbacks
 F filterinput
 T methods
 F default
 F features
 F file
 F goodies
 F name
 F selectfont
 F simplefonts
 F spec
 F style
 F registerfallback

- F searchfiles

specifiers table

- D contextmerged
- F contextnumber
- D contextnumbers
- D contextsetups
- F contexttostring
- F definecontext
- F mergecontext
- F presetcontext
- F registercontext
- F showcontext
- F splitcontext
- D synonyms
- D variants

symbols table

- F uselibrary

tables table

tracers table

treatments table

- F applyfixes
- D data
- S filename
- F ignoredfile
- F report
- F trace

typefaces data table

functions (context)

dummy function

graphics (context)

backgrounds table

F calculatemultipar

F fetchmultipar

F pair

F path

F point

gzip (extra lua)

close function
lines function
load function
open function
save function
suffix function

img (basic tex)

| | |
|-----------------------|----------|
| boxes | function |
| check | function |
| checksize | function |
| clone | function |
| copy | function |
| immediatewrite | function |
| keys | function |
| new | function |
| node | function |
| ofindex | function |
| package | function |
| print | function |
| scan | function |
| serialize | function |
| totable | function |
| types | function |
| write | function |

interactions (context)

attachments data table

fields table

F clone

F define

F defineset

F insert

general table

F getidentity

F setupidentity

help table

F collect

F reference

F register

javascripts table

F addtopreamble

F code

D codes

F flushpreambles

D functions

D preambles

F setpreamble

F storecode

F storepreamble

F usepreamblenow

F usescripts

linkedlists data table

pages table

F setpagetransition

F setupcanvas

references table

F setcloseddocument

F setclosepage

F setopendocument

F setopenpage

renderings data table

soundclips data table

interfaces (context)

| | | |
|-----------------------------|------------|-------------------------------|
| addvalidkeys | function | F MPx |
| cachedsetups | data table | F MPxy |
| cachesetup | function | F MPxywhd |
| checkedspecification | function | F MPy |
| complete | data table | F bposcolumn |
| constants | data table | F bposcolumnregistered |
| corenamespaces | data table | F btxauthorfield |
| definecommand | function | F btxdetail |
| doifelsemessage | function | F btxdoif |
| elements | data table | F btxdoifelse |
| formats | data table | F btxdoifelsesameasprevious |
| getcheckedparameters | function | F btxdoifnot |
| getmessage | function | F btxfield |
| hashedsetups | data table | F btxfieldname |
| interfacedcommand | function | F btxfieldtype |
| interfaces | table | F btxfirstofrange |
| invalidkey | function | F btxflush |
| is_command | function | F btxfoundname |
| namespaces | table | F btxfoundtype |
| F define | | F btxoneorrange |
| F list | | F btxsingularplural |
| registernamespace | function | F copyposition |
| scanners | table | F currentbtxfirstnames |
| F MPc | | F currentbtxinitials |
| F MPd | | F currentbtxjuniors |
| F MPH | | F currentbtxsurnames |
| F MPll | | F currentbtxvons |
| F MPlr | | F definefont_one |
| F MPls | | F definefont_two |
| F MPn | | F doifelsepositionsused |
| F MPp | | F doifelserangeonpage |
| F MPpardata | | F doifoverlappingelse |
| F MPplus | | F doifposition |
| F MPpos | | F doifpositionelse |
| F MPposset | | F doifpositiononpageelse |
| F MPr | | F doifpositionsonsamepageelse |
| F MPrest | | F doifpositionsonthispageelse |
| F MPrs | | F dopickupbuffer |
| F MPul | | F dosaveposition |
| F MPur | | F dosavepositionplus |
| F MPw | | F dosavepositionwhd |

| | | |
|--------------------------|-------------------------|------------|
| F dosetposition | F xmldoifelse | |
| F dosetpositionbox | F xmldoifelseempty | |
| F dosetpositionplus | F xmldoifelseselfempty | |
| F dosetpositionstrut | F xmldoifelsetext | |
| F dosetpositionwhd | F xmldoifempty | |
| F eposcolumn | F xmldoifnot | |
| F eposcolumnregistered | F xmldoifnotempty | |
| F fetchmultipar | F xmldoifnotselfempty | |
| F fetchmultishape | F xmldoifnottext | |
| F fetchposboxes | F xmldoifselfempty | |
| F lastcountervalue | F xmldoiftext | |
| F lastcountervaluesub | F xmlfilter | |
| F markregionbox | F xmlfirst | |
| F markregionboxcorrected | F xmlflush | |
| F markregionboxtagged | F xmltext | |
| F mpcolor | setconstant | function |
| F parpos | setelement | function |
| F pdfrotation | setformat | function |
| F pdfstartmatrix | setmessage | function |
| F pdfstartmirroring | setmessages | function |
| F pdfstartrotation | settranslation | function |
| F pdfstartscaling | setuserinterface | function |
| F pdfstopmatrix | setvalidkeys | function |
| F pdfstopmirroring | setvariable | function |
| F pdfstoprotation | showmessage | function |
| F pdfstopscaling | storedscanners | data table |
| F registerusedsynonym | syntax | data table |
| F replacepospxywhd | tolist | function |
| F setcharactercasing | translations | data table |
| F setmathalphabet | variables | data table |
| F setmathattribute | | |
| F setmathstyle | | |
| F synonymmeaning | | |
| F synonymname | | |
| F typenested | | |
| F typenormal | | |
| F vspacing | | |
| F way | | |
| F xmlall | | |
| F xmlatt | | |
| F xmlattdef | | |
| F xmlattribute | | |
| F xmlattributedef | | |
| F xmldoif | | |

io (basic lua)

| | |
|----------------------|---------------------|
| ask | function |
| bytes | function |
| characters | function |
| close | function |
| exists | function |
| fileseparator | string |
| flush | function |
| input | overloaded function |
| lines | overloaded function |
| loadchunk | function |
| loaddata | function |
| loadlines | function |
| noflines | function |
| open | overloaded function |
| output | overloaded function |
| pathseparator | string |
| popen | overloaded function |
| read | function |
| readall | function |
| readnumber | function |
| readstring | function |
| savedata | function |
| size | function |
| stderr | userdata |
| stdin | userdata |
| stdout | userdata |
| tmpfile | function |
| type | function |
| write | function |

jit (context)

| | |
|---------------|----------|
| arch | string |
| attach | function |
| flush | function |
| off | function |
| on | function |
| opt | table |
| F start | |
| os | string |
| status | function |
| util | table |

| |
|-----------------|
| F funcbc |
| F funcinfo |
| F funcck |
| F funcuvname |
| F ircalladdr |
| F traceexitstub |
| F traceinfo |
| F traceir |
| F tracek |
| F tracemc |
| F tracesnap |

| | |
|--------------------|--------|
| version | string |
| version_num | number |

job (context)

comment function

datasets table

D collected

F extend

F getdata

F setdata

D tobesaved

disablesave function

files table

D collected

F context

B forcerun

F run

D tobesaved

initialize function

load function

loadother function

objects table

D collected

F get

F number

F page

F save

F set

D tobesaved

pack boolean

packversion number

pagestates table

D collected

F extend

F realpage

F setstate

D tobesaved

passes table

F check

D collected

F count

F define

F find

F first

F get

F getcollected

F getdata

F getfield

F gettobesaved

F inlist

F last

F list

F save

F savetagged

D tobesaved

positions table

F b_col

F b_region

F c

D collected

F column

F copy

F depth

F e_col

F e_region

F enhance

F extra

F get

F getreserved

F hangafter

F hangindent

F height

F hsize

F leftskip

F lowerleft

F lowerright

F markregionbox

F n

F onsamepage

F overlapping

F p

F page

F paragraph

F parindent

F position

F r

- F region
- F replace
- F rightskip
- F set
- F setall
- F setdim
- D tobesaved
- F upperleft
- F upperright
- S used
- F width
- F x
- F xy
- F y
- register** function
- save** function
- structure** table
- D collected
- T components
- T tobesaved
- T branches
- S name
- S type
- variables** table
- D checksums
- D collected
- F getchecksum
- F makechecksum
- F restore
- F save
- F setchecksum
- D tobesaved
- version** number

lang (basic tex)

| | |
|--------------------------|----------|
| clean | function |
| clear_hyphenation | function |
| clear_patterns | function |
| exceptions | function |
| hyphenate | function |
| hyphenation | function |
| id | function |
| new | function |
| patterns | function |
| postexhyphenchar | function |
| posthyphenchar | function |
| preexhyphenchar | function |
| prehyphenchar | function |

languages (context)

| | | | |
|----------------------|------------|---------------------------------|------------|
| associate | function | numbers | data table |
| associated | data table | postexhyphenchar | function |
| association | function | posthyphenchar | function |
| counters | data table | preexhyphenchar | function |
| current | function | prehyphenchar | function |
| data | data table | registered | data table |
| define | function | replacements | table |
| expand | function | F add | |
| expanders | table | F handler | |
| frequencies | table | F set | |
| F averagecharwidth | | righthyphenmin | function |
| F getdata | | serializediscretionary | function |
| getdata | function | setexceptions | function |
| getnumber | function | setsynonym | function |
| hyphenate | function | unload | function |
| hyphenators | table | version | number |
| T dictionaries | | visualizediscretionaries | function |
| D featuresets | | words | table |
| F handler | | F check | |
| F popmethod | | T data | |
| F pushmethod | | F disable | |
| F setmethod | | F enable | |
| T traditional | | T enablers | |
| F definefeatures | | B enables | |
| F gettrace | | F found | |
| F hyphenate | | F load | |
| F injecthyphens | | T methods | |
| F installmethod | | N threshold | |
| F lasttrace | | | |
| F loadpatterns | | | |
| F registerexception | | | |
| F registerpattern | | | |
| installed | function | | |
| labels | table | | |
| F define | | | |
| F split | | | |
| lefthyphenmin | function | | |
| loadable | function | | |
| loadwords | function | | |
| logger | table | | |
| F report | | | |

layouts (context)

status table

F isleftpage

F leftorrightpagection

lfs (extra lua)

| | |
|--------------------------|---------------------|
| attributes | overloaded function |
| chdir | overloaded function |
| currentdir | function |
| dir | overloaded function |
| isdir | overloaded function |
| isfile | overloaded function |
| lock | function |
| lock_dir | overloaded function |
| mkdir | overloaded function |
| mkdirs | function |
| readlink | overloaded function |
| rmdir | overloaded function |
| setmode | overloaded function |
| shortname | overloaded function |
| symlinkattributes | overloaded function |
| touch | overloaded function |
| unlock | function |

libraries (context)

| | |
|------------------|------------|
| basiclua | data table |
| basictex | data table |
| builtin | data table |
| extralua | data table |
| extratex | data table |
| functions | data table |
| globals | data table |

lmx (context)

color function
convert function
convertfile function
convertstring function
einject function
eprint function
escape function
finalized function
finject function
fprint function
get function
getvariables function
htmfile function
html table

F a

F td

F th

include function
inherited table

S color-background-four

S color-background-one

S color-background-three

S color-background-two

S title

initialize function
inject function
lmxfile function
loadedfile function
make function
new function
overloaderror function
popupfile function
print function
pv function
report function
reset function
result function
set function
show function
showdebuginfo function
showerror function

stripcss function
tv function
type function
urlescape function
variable function
variables table

S color-background-blue

S color-background-body

S color-background-green

S color-background-main

S color-background-purple

S color-background-yellow

S title-default

logs (context)

| | |
|---------------------|----------|
| application | function |
| categories | function |
| direct | function |
| disable | function |
| enable | function |
| exporters | table |
| extendbanner | function |
| flush | function |
| help | function |
| messenger | function |
| new | function |
| newline | function |
| poptarget | function |
| pushtarget | function |
| report | function |
| reportbanner | function |
| reporter | function |
| reporters | table |

F banner

F export

F help

F info

F lines

F version

| | |
|------------------------|----------|
| reportline | function |
| reportlines | function |
| setformats | function |
| setformatters | function |
| setlogfile | function |
| setmessenger | function |
| setprocessor | function |
| setprogram | function |
| settarget | function |
| settimedlog | function |
| settranslations | function |
| show | function |
| show_close | function |
| show_load | function |
| show_open | function |
| simple | function |
| simpleline | function |

| | |
|--------------------------|----------|
| simplelines | function |
| start_page_number | function |
| status | function |
| stop_page_number | function |
| subdirect | function |
| subreport | function |
| system | function |
| texerrormessage | function |
| writer | function |

lpdf (context)

| | | | |
|---------------------------------|------------|----------------------------------|------------|
| action | function | finalizepage | function |
| adddocumentcolorspace | function | finishtransparencycode | function |
| adddocumenttextgstate | function | flushobject | function |
| adddocumentpattern | function | flushstreamfileobject | function |
| adddocumentshade | function | flushstreamobject | function |
| addtocatalog | function | formats | data table |
| addtoinfo | function | frompdfdoc | function |
| addtonames | function | fromsixteen | function |
| addtopageattributes | function | gethpos | function |
| addtopageresources | function | getmatrix | function |
| addtopagesattributes | function | getpos | function |
| addxmpinfo | function | getvpos | function |
| annotationspecification | function | graycode | function |
| array | function | hasmatrix | function |
| boolean | function | id | function |
| border | function | injectxmpinfo | function |
| checkedkey | function | insertxmpinfo | function |
| checkedvalue | function | layerreference | function |
| circularshade | function | limited | function |
| cmykcode | function | linearshade | function |
| collectedresources | function | nametree | function |
| color | function | null | function |
| colorspace | function | number | function |
| colorspaceconstants | data table | pagedestinations | data table |
| colorspec | function | pagereference | function |
| colorvalue | function | pagereferences | data table |
| colorvalues | function | pdfcolor | function |
| constant | function | pdftimestamp | function |
| delayedobject | function | protectresources | boolean |
| destinationspecification | function | rectangle | function |
| dictionary | function | reference | function |
| docstring | function | registerannotation | function |
| epdf | table | registerdestination | function |
| F contenttotext | | registerdocumentfinalizer | function |
| F expand | | registerpagefinalizer | function |
| F expanded | | reserveobject | function |
| F getpagecontent | | rgbcode | function |
| F getstructure | | rotationcm | function |
| F load | | shareobject | function |
| F unload | | shareobjectreference | function |
| finalizeddocument | function | spotcode | function |

| | |
|---------------------------|----------|
| stream | function |
| string | function |
| timestamp | function |
| toeight | function |
| topdfdoc | function |
| tosixteen | function |
| transform | function |
| transparency | function |
| transparencycode | function |
| transparencygroups | table |
| B none | |
| transparencyvalue | function |
| unicode | function |
| verbose | function |

lpeg (basic lua)

| | | | |
|------------------------|------------|------------------------------|----------|
| B | function | setmaxstack | function |
| C | function | split | function |
| Carg | function | splitat | function |
| Cb | function | splitter | function |
| Cc | function | stripper | function |
| Cf | function | times | function |
| Cg | function | tsplitat | function |
| Cmt | function | tsplitter | function |
| Cp | function | type | function |
| Cs | function | utfchartabletopattern | function |
| Ct | function | version | function |
| P | function | | |
| R | function | | |
| S | function | | |
| UP | function | | |
| UR | function | | |
| US | function | | |
| V | function | | |
| afterprefix | function | | |
| anywhere | function | | |
| append | function | | |
| balancer | function | | |
| beforesuffix | function | | |
| checkedsplit | function | | |
| counter | function | | |
| endstripper | function | | |
| finder | function | | |
| firstofsplit | function | | |
| frontstripper | function | | |
| instringchecker | function | | |
| is_lpeg | function | | |
| keeper | function | | |
| locale | function | | |
| match | function | | |
| oneof | function | | |
| patterns | data table | | |
| pcode | function | | |
| print | function | | |
| ptree | function | | |
| replacer | function | | |
| secondofsplit | function | | |

ltn12 (extra lua)

BLOCKSIZE number

filter table

F chain

F cycle

pump table

F all

F step

sink table

F chain

F error

F file

F null

F simplify

F table

source table

F cat

F chain

F empty

F error

F file

F rewind

F simplify

F string

lua (basic tex)

| | |
|----------------------------|------------|
| bytecode | table |
| bytedata | data table |
| bytdone | table |
| B toks-new | |
| B toks-sc | |
| collectgarbage | function |
| delay | function |
| finalize | function |
| firstbytecode | number |
| flush | function |
| flushdelayed | function |
| get_functions_table | function |
| getbytecode | function |
| getluaname | function |
| lastbytecode | number |
| mask | string |
| messages | data table |
| name | table |
| numbers | data table |
| registercode | function |
| registeredcodes | function |
| registerfinalizer | function |
| registername | function |
| setbytecode | function |
| setluaname | function |
| startupfile | string |
| version | string |

luatex (context)

| | |
|-----------------------------|----------|
| cleanuptempfiles | function |
| registerstartactions | function |
| registerstopactions | function |
| registertempfile | function |
| starttime | number |

lxml (context)

| | | | |
|------------------------|------------|-------------------------|----------|
| addindex | function | flushsetups | function |
| all | function | flushspacewise | function |
| applyfunction | function | get_id | function |
| att | function | getid | function |
| attribute | function | getindex | function |
| chainattribute | function | id | function |
| checkindex | function | idsplitter | userdata |
| collected | function | include | function |
| command | function | inclusion | function |
| concat | function | inclusions | function |
| concatrange | function | index | function |
| content | function | info | function |
| context | function | inlineverbatim | function |
| convert | function | installsetup | function |
| count | function | last | function |
| delete | function | load | function |
| direct | function | loadbuffer | function |
| directives | table | loaddata | function |
| F after | | loaded | table |
| F before | | loadregistered | function |
| F handle | | main | function |
| F load | | match | function |
| F setup | | name | function |
| displayverbatim | function | namespace | function |
| doif | function | nonspace | function |
| doifelse | function | pos | function |
| doifelseempty | function | position | function |
| doifelsetext | function | raw | function |
| doifempty | function | rawroot | function |
| doifnot | function | register | function |
| doifnotempty | function | registerentity | function |
| doifnottext | function | removesetup | function |
| doiftext | function | resetcdata | function |
| element | function | resetsetups | function |
| elements | function | resolvedentity | function |
| entities | data table | root | function |
| filter | function | save | function |
| filterlist | function | serialize | function |
| first | function | setaction | function |
| flush | function | setcdata | function |
| flushlinewise | function | setcommandtonone | function |

| | |
|-------------------------|------------|
| setcommandtotext | function |
| setsetup | function |
| snippet | function |
| sorters | table |
| F add | |
| F compare | |
| F flush | |
| F reset | |
| F show | |
| F sort | |
| splitid | function |
| startraw | function |
| stopraw | function |
| store | function |
| strip | function |
| stripped | function |
| tag | function |
| text | function |
| tobuffer | function |
| tofile | function |
| toparameters | function |
| toverbatim | function |
| verbatim | function |
| withindex | function |
| xmltexhandler | data table |

math (basic lua)

| | |
|-----------------------|----------|
| abs | function |
| acos | function |
| asin | function |
| atan | function |
| atan2 | function |
| ceil | function |
| cos | function |
| cosd | function |
| cosh | function |
| deg | function |
| div | function |
| even | function |
| exp | function |
| floor | function |
| fmod | function |
| frexp | function |
| huge | number |
| initialseed | number |
| ldexp | function |
| log | function |
| log10 | function |
| max | function |
| min | function |
| mod | function |
| modf | function |
| odd | function |
| pi | number |
| pow | function |
| rad | function |
| random | function |
| randomseed | function |
| round | function |
| setrandomseedi | function |
| sin | function |
| sind | function |
| sinh | function |
| sqrt | function |
| tan | function |
| tand | function |
| tanh | function |

mathematics (context)

| | | | |
|-------------------------------|------------|-------------------------------|------------|
| addfallbacks | function | resetitalics | function |
| alphabets | data table | scaleparameters | function |
| alternatives | data table | setalternate | function |
| big | function | setitalics | function |
| boldmap | data table | sets | data table |
| categories | table | styles | data table |
| D functions | | syncboth | function |
| charactersets | data table | syncname | function |
| checkaccentbaseheight | function | syncstyle | function |
| checkprivateparameters | function | toname | function |
| classes | data table | tostyle | function |
| codes | data table | tweakaftercopyingfont | function |
| define | function | tweakbeforecopyingfont | function |
| dimensions | function | tweaks | table |
| extensiblecode | function | utfmathaccent | function |
| extensibles | data table | utfmathclass | function |
| extrabase | number | utfmathcommand | function |
| extras | table | utfmathfiller | function |
| F add | | utfmathstretch | function |
| F copy | | | |
| fallbacks | table | | |
| F apply | | | |
| F install | | | |
| fallbackstyleattr | function | | |
| families | data table | | |
| gaps | data table | | |
| getboth | function | | |
| getstyle | function | | |
| initializeparameters | function | | |
| injectfallbacks | function | | |
| makefont | function | | |
| mapremap | data table | | |
| overloaddimensions | function | | |
| overloadparameters | function | | |
| privatebase | number | | |
| remapalphabets | function | | |
| renderings | table | | |
| D mappings | | | |
| D numbers | | | |
| D sets | | | |
| renderset | function | | |

mbox (context)

| | |
|----------------------|----------|
| parse | function |
| parse_from | function |
| parse_header | function |
| parse_headers | function |
| parse_message | function |
| split_headers | function |
| split_mbox | function |
| split_message | function |

md5 (extra lua)

| | |
|----------------|----------|
| HEX | function |
| crypt | function |
| dec | function |
| decrypt | function |
| exor | function |
| hex | function |
| sum | function |
| sumhexa | function |

metapost (context)

| | | | |
|-------------------------|------------|-------------------------------|----------|
| analyzeplugins | function | gettext | function |
| checkformat | function | graphic | function |
| checktexts | function | graphic_base_pass | function |
| collapse | boolean | initializescriptrunner | function |
| colorinitializer | function | instance | function |
| convert | function | intermediate | table |
| defaultformat | string | T actions | |
| defaultinstance | string | F makemply | |
| defaultmethod | string | lastlog | string |
| directrun | function | load | function |
| edefsxsy | function | makemply | table |
| escaped | function | N nofconverted | |
| exectime | table | F processgraphics | |
| extensiondata | data table | F registerfile | |
| filterclippath | function | metafun | table |
| flush | function | F interpolate | |
| flushers | table | F topath | |
| T pdf | | method | number |
| F comment | | mptopdf | table |
| F flushfigure | | F convertmptstopdf | |
| F startfigure | | N nofconverted | |
| F stopfigure | | n | number |
| F textfigure | | nvformat | function |
| flushliteral | function | optimize | boolean |
| flushnormalpath | function | parse | function |
| flushreset | function | pdfliterals | function |
| fonts | table | pluginactions | function |
| F define | | process | function |
| T flusher | | processplugins | function |
| F flushfigure | | processspecial | function |
| F startfigure | | properties | table |
| F stopfigure | | quickanddirty | function |
| N instances | | reducetogray | boolean |
| F process | | reporterror | function |
| format | function | reset | function |
| format_number | function | resetlastlog | function |
| format_string | function | resetplugins | function |
| formatnumber | function | runscript | function |
| getclippath | function | scripterror | function |
| getextensions | function | setextensions | function |
| getstatistics | function | setoutercolor | function |

| | |
|----------------------|----------|
| settext | function |
| showlog | boolean |
| svformat | function |
| tex | table |
| F get | |
| F reset | |
| F set | |
| texerrors | boolean |
| textextsdata | function |
| theclippath | function |
| totable | function |
| unload | function |
| untagvariable | function |
| variables | table |

mime (extra lua)

b64 function

decode function

decodet table

F base64

F quoted-printable

dot function

encode function

encodet table

F base64

F quoted-printable

eol function

normalize function

qp function

qpwrp function

stuff function

unb64 function

unqp function

wrap function

wrapt table

F base64

F default

F quoted-printable

F text

wrp function

mp (context)

| | |
|------------------|----------|
| _f_ | function |
| dataset | function |
| datasets | table |
| F load | |
| format | function |
| get | table |
| F boolean | |
| F number | |
| F numeric | |
| F string | |
| n | function |
| numeric | function |
| pair | function |
| path | function |
| print | function |
| quadruple | function |
| quoted | function |
| size | function |
| triplet | function |

mplib (extra tex)

| | |
|---------------------|---------------------|
| fields | function |
| finder | function |
| finders | table |
| F file | |
| get_boolean | function |
| get_number | function |
| get_numeric | function |
| get_string | function |
| new | overloaded function |
| pen_info | function |
| preprocessed | function |
| version | function |

newtoken (context)

| | |
|---------------------|----------|
| create | function |
| get_code | function |
| get_future | function |
| get_next | function |
| is_token | function |
| scan_code | function |
| scan_dimen | function |
| scan_glue | function |
| scan_int | function |
| scan_keyword | function |
| scan_string | function |
| scan_token | function |
| scan_toks | function |
| set_macro | function |
| type | function |

noads (context)

handlers table

- F check
- F classes
- F collapse
- F families
- F italics
- F relocate
- F render
- F resize
- F showtree
- F tags
- F unscript
- F variants

process function

processors table

- T collapse
- F mlist_to_hlist
- T relocate
- T render
- T resize
- T unscript

node (basic tex)

| | | | |
|--------------------------|----------|-------------------------------|----------|
| copy | function | F protect_glyphs | |
| copy_list | function | F protrusion_skippable | |
| count | function | F remove | |
| current_attr | function | F set_attribute | |
| dimensions | function | F set_properties_mode | |
| direct | table | F setbox | |
| F copy | | F setfield | |
| F copy_list | | F setproperty | |
| F count | | F slide | |
| F current_attr | | F tail | |
| F dimensions | | F todirect | |
| F do_ligature_n | | F tonode | |
| F end_of_math | | F toString | |
| F first_glyph | | F traverse | |
| F flush_list | | F traverse_id | |
| F flush_node | | F unprotect_glyphs | |
| F flush_properties_table | | F unset_attribute | |
| F free | | F usedlist | |
| F get_properties_table | | F vpack | |
| F getbox | | F write | |
| F getchar | | do_ligature_n | function |
| F getfield | | end_of_math | function |
| F getfont | | family_font | function |
| F getid | | fields | function |
| F getleader | | first_character | function |
| F getlist | | first_glyph | function |
| F getnext | | flush_list | function |
| F getprev | | flush_node | function |
| F getproperty | | flush_properties_table | function |
| F getsubtype | | free | function |
| F has_attribute | | get_properties_table | function |
| F has_field | | getchar | function |
| F has_glyph | | getfield | function |
| F hpack | | getfont | function |
| F insert_after | | getid | function |
| F insert_before | | getleader | function |
| F is_direct | | getlist | function |
| F is_node | | getnext | function |
| F last_node | | getprev | function |
| F length | | getproperty | function |
| F new | | getsubtype | function |

| | |
|-----------------------------|----------|
| has_attribute | function |
| has_field | function |
| has_glyph | function |
| hpack | function |
| id | function |
| insert_after | function |
| insert_before | function |
| is_node | function |
| kerning | function |
| last_node | function |
| length | function |
| ligaturing | function |
| mlist_to_hlist | function |
| new | function |
| next | function |
| prev | function |
| protect_glyphs | function |
| protrusion_skippable | function |
| remove | function |
| set_attribute | function |
| set_properties_mode | function |
| setfield | function |
| setProperty | function |
| slide | function |
| subtype | function |
| tail | function |
| tostring | function |
| traverse | function |
| traverse_id | function |
| type | function |
| types | function |
| unprotect_glyphs | function |
| unset_attribute | function |
| usedlist | function |
| vpack | function |
| whatsits | function |
| write | function |

nodes (context)

| | | | |
|---------------------------|------------|-------------------------------|------------|
| accentcodes | data table | free_spec | function |
| aligned | function | getattr | function |
| append | function | getattribute | function |
| astable | function | getbox | function |
| basepoints | function | getchar | function |
| builders | table | getfield | function |
| F buildpage_filter | | getfont | function |
| F vpack_filter | | getid | function |
| codes | data table | getleader | function |
| concat | function | getlist | function |
| copy | function | getnext | function |
| copy_list | function | getprev | function |
| copy_spec | function | getskip | function |
| count | function | getsubtype | function |
| current_attr | function | gluecodes | data table |
| delete | function | glyphcodes | data table |
| destinations | table | glyphdir_is_equal | data table |
| N attribute | | glyphdir_is_opposite | data table |
| T done | | glyphdir_is_orthogonal | data table |
| F handler | | gonuts | boolean |
| T stack | | handlers | table |
| dimensionfields | data table | F accessibility | |
| dimensions | function | F alignbackgrounds | |
| dir_is_pop | data table | F backgrounds | |
| dir_negation | data table | F characters | |
| disccodes | data table | F checkforleaks | |
| discretionarycodes | data table | F checkglyphs | |
| do_ligature_n | function | F cleanupbox | |
| end_of_math | function | F cleanuppage | |
| fasthpack | function | F export | |
| fencecodes | data table | F finalize | |
| fields | function | F migrate | |
| fillcodes | data table | F protectglyphs | |
| first_character | function | F stripping | |
| first_glyph | function | F unprotectglyphs | |
| firstcharacter | function | has_attribute | function |
| firstcharinbox | function | has_field | function |
| firstglyph | function | has_glyph | function |
| flush_list | function | hpack | function |
| flush_node | function | idstostring | function |
| free | function | ignorablefields | data table |

| | | | |
|--------------------------------|------------|------------------------|------------|
| injections | table | listtablefields | data table |
| F copy | | listcodes | data table |
| F getligaindex | | listtutf | function |
| F handler | | load | function |
| F installnewkern | | locate | function |
| F keepcounts | | margincodes | data table |
| F reset | | markers | table |
| F resetcounts | | F get | |
| F setcursive | | mathcodes | data table |
| F setkern | | maxboxwidth | function |
| F setligaindex | | mlist_to_hlist | function |
| F setmark | | new | function |
| F setpair | | noadcodes | data table |
| insert_after | function | nodecodes | data table |
| insert_before | function | nopts | function |
| insert_list_after | function | nuts | table |
| installattributehandler | function | F append | |
| is_direct | function | F concat | |
| is_display_math | function | F copy | |
| is_mirrored | data table | F copy_list | |
| is_node | function | F copy_properties | |
| is_nut | function | F count | |
| is_rotated | data table | F current_attr | |
| kerncodes | data table | F delete | |
| kerning | function | F dimensions | |
| keys | table | F do_ligature_n | |
| T Whatsit | | F end_of_math | |
| last_node | function | F fasthpack | |
| leftmarginwidth | function | F first_glyph | |
| ligaturing | function | F firstcharacter | |
| lines | table | F firstcharinbox | |
| T boxed | | F firstglyph | |
| F register | | F flush_list | |
| F setup | | F flush_node | |
| F stage_one | | F free | |
| F stage_two | | F getattr | |
| F stage_zero | | F getattribute | |
| D data | | F getbox | |
| F finalize | | F getchar | |
| F number | | F getfield | |
| N scratchbox | | F getfont | |
| link | function | F getid | |
| linked | function | F getleader | |
| list | function | F getlist | |

| | |
|---------------------|------------------------|
| F getnext | F pdfdestination |
| F getprev | F pdfdirect |
| F getprop | F pdfliteral |
| F getskip | F pdfrestore |
| F getsubtype | F pdfsave |
| F has_attribute | F pdfsetmatrix |
| F has_field | F penalty |
| F has_glyph | F register |
| F hpack | F rightmarginkern |
| F insert_after | F rightskip |
| F insert_before | F rule |
| F insert_list_after | F shrink |
| F is_direct | F special |
| F is_display_math | F stretch |
| F is_node | F temp |
| F is_nut | F textdir |
| F kerning | F usage |
| F last_node | T userids |
| F leftmarginwidth | N margins.inline |
| F ligaturing | N property |
| F link | N splitters.one |
| F linked | N splitters.two |
| F locate | F userlist |
| F mlist_to_hlist | F usernumber |
| F nestedtracedslide | F userstring |
| F new | F usertokens |
| T pool | F vlist |
| F baselineskip | F zeroglue |
| F cleanup | F prepend |
| F disc | F protect_glyphs |
| F fontkern | F protrusion_skippable |
| F glue | F reference |
| F gluespec | F remove |
| F glyph | F repackhlist |
| F hlist | F replace |
| F kern | F rightmarginwidth |
| F latelua | F set_attribute |
| F lateluafunction | F setattr |
| F leftmarginkern | F setattrtribute |
| F leftskip | F setattrtributes |
| F lineskip | F setbox |
| F negatedglue | F setfield |
| F noad | F setprop |
| F pdfannotation | F setunsetattributes |

| | | | |
|----------------------------|------------|-------------------------|----------|
| F slide | | N attribute | |
| F somepenalty | | D data | |
| F somespace | | F enable | |
| F tail | | F handler | |
| F takebox | | F register | |
| F tonode | | D registered | |
| F tonodes | | D values | |
| F tonut | | F processor | |
| F tosequence | | points | function |
| F tostring | | pool | table |
| F tracedslide | | F baselineskip | |
| F traverse | | F cleanup | |
| F traverse_id | | F glyph | |
| T typesetters | | F kern | |
| F fast_hpack | | F latelua | |
| F hpack | | F lateluafunction | |
| F tohpack | | F lineskip | |
| F tohpackfast | | F pdfdirect | |
| F tonodes | | F pdfliteral | |
| F tovpack | | F pdfrestore | |
| F tovpackfast | | F pdfsave | |
| F vpack | | F pdfsetmatrix | |
| F unprotect_glyphs | | F register | |
| F unset_attribute | | F rule | |
| F unsetattribute | | F special | |
| F unsetattributes | | F usage | |
| F untracedslide | | T userids | |
| F usedlist | | N margins.inline | |
| F vianodes | | N property | |
| F vianuts | | N splitters.one | |
| F vpack | | N splitters.two | |
| F writable_spec | | F usernumber | |
| F write | | prepend | function |
| packlist | function | print | function |
| pardir_is_equal | data table | processors | table |
| pardir_is_opposite | data table | B enabled | |
| pardir_is_parallel | data table | F hpack_filter | |
| partextdir_is_equal | data table | F post_linebreak_filter | |
| penaltycodes | data table | F pre_linebreak_filter | |
| plugindata | table | F tracer | |
| F finalizer | | processwords | function |
| F initializer | | properties | table |
| S name | | T actions | |
| T namespace | | F delayed | |

| | | | |
|-----------------------------|----------|----------------------------|------------|
| F delayed | | skipcodes | data table |
| F immediate | | slide | function |
| F attach | | snapshots | table |
| T data | | F getparameters | |
| F delayed | | F getsamples | |
| protect_glyphs | function | F resetsamples | |
| protrusion_skippable | function | F takesample | |
| pts | function | somepenalty | function |
| reference | function | somespace | function |
| references | table | stripping | table |
| N attribute | | T glyphs | |
| T done | | F set | |
| F handler | | striprange | function |
| T stack | | tail | function |
| remove | function | takebox | function |
| repackhlist | function | tasks | table |
| replace | function | F actions | |
| report | function | F appendaction | |
| rightmarginwidth | function | F disableaction | |
| rules | table | F disablegroup | |
| D data | | F enableaction | |
| F define | | F enablegroup | |
| F enable | | F freeze | |
| F handler | | F freezegroup | |
| save | function | F new | |
| serialize | function | F prependaction | |
| serializebox | function | F removeaction | |
| set_attribute | function | F replaceaction | |
| setattr | function | F restart | |
| setattribute | function | F setaction | |
| setattributes | function | F showactions | |
| setbox | function | F table | |
| setfield | function | texmdir_is_equal | data table |
| setunsetattributes | function | texmdir_is_is | data table |
| shifts | table | texmdir_is_opposite | data table |
| D data | | texmdir_is_parallel | data table |
| F define | | tobasepoints | function |
| F enable | | tocentimeters | function |
| F handler | | tociceros | function |
| show | function | todidots | function |
| showboxes | function | todimen | function |
| showcodes | function | toinches | function |
| showlist | function | tomillimeters | function |
| showsimplelist | function | tonewciceros | function |

| | | | |
|-----------------------|----------|-------------------------|------------|
| tonewdidots | function | F nofsteps | |
| tonode | function | F register | |
| tonodes | function | F reset | |
| tonut | function | F start | |
| topicas | function | F stop | |
| topoints | function | F stop | |
| toscaledpoints | function | T transparencies | |
| tosequence | function | F reset | |
| tostring | function | F set | |
| totable | function | F setlist | |
| totree | function | traverse | function |
| toutf | function | traverse_id | function |
| tracers | table | typesetters | table |
| T characters | | F hpack | |
| F collect | | F tohpack | |
| F equal | | F tohpackfast | |
| F start | | F tonodes | |
| F string | | F tovpack | |
| F unicodes | | F tovpackfast | |
| T colors | | F vpack | |
| F reset | | unprotect_glyphs | function |
| F set | | unset_attribute | function |
| F setlist | | unsetattribute | function |
| F fontchar | | unsetattributes | function |
| T frequencies | | usedlist | function |
| F register | | vianodes | function |
| T pool | | vianuts | function |
| T nodes | | visualizebox | function |
| F rule | | visualizers | table |
| T nuts | | F box | |
| F rule | | F handler | |
| F resetproperties | | F markfonts | |
| F rule | | F setfont | |
| F setlist | | F setlayer | |
| F setproperties | | F setvisual | |
| F start | | vpack | function |
| T steppers | | whatcodes | data table |
| F check | | whatsitcodes | data table |
| F codes | | writable_spec | function |
| F features | | write | function |
| F font | | | |
| F glyphs | | | |
| F message | | | |
| F messages | | | |

number (context)

| | |
|-----------------------|------------|
| | function |
| basepoints | function |
| bit | function |
| bits | function |
| clearbit | function |
| dimenfactors | data table |
| formatted | function |
| hasbit | function |
| maxdimen | number |
| nopts | function |
| percent | function |
| points | function |
| pts | function |
| setbit | function |
| signed | function |
| sparseexponent | function |
| splitdimen | function |
| tobasepoints | function |
| tobitstring | function |
| tocentimeters | function |
| toxiceros | function |
| todidots | function |
| todimen | function |
| toevenhex | function |
| toinches | function |
| tomillimeters | function |
| tonewciceros | function |
| tonewdidots | function |
| tonumberf | function |
| tonumberg | function |
| topics | function |
| topoints | function |
| toscaled | function |
| toscaledpoints | function |
| toset | function |
| valid | function |

os (basic lua)

| | | | |
|---------------------|---------------------|------------------|----------|
| __getenv__ | function | uname | function |
| __setenv__ | function | uuid | function |
| binsuffix | string | validdate | function |
| binsuffixes | table | weekday | function |
| clock | function | where | function |
| converttime | function | which | function |
| date | function | | |
| difftime | function | | |
| env | data table | | |
| exec | overloaded function | | |
| execute | overloaded function | | |
| exit | function | | |
| fulltime | function | | |
| getenv | overloaded function | | |
| gettimeofday | function | | |
| isleapyear | function | | |
| launch | function | | |
| libsuffix | string | | |
| localtime | function | | |
| name | string | | |
| nofdays | function | | |
| now | function | | |
| platform | string | | |
| remove | overloaded function | | |
| rename | overloaded function | | |
| resolvers | table | | |
| F bits | | | |
| resultof | function | | |
| runtime | function | | |
| selfdir | string | | |
| setenv | overloaded function | | |
| setlocale | overloaded function | | |
| sleep | function | | |
| spawn | overloaded function | | |
| time | function | | |
| times | function | | |
| timezone | function | | |
| tmpdir | function | | |
| tmpname | function | | |
| today | function | | |
| type | string | | |

package (basic lua)

| | |
|----------------------|----------|
| config | string |
| cpath | string |
| extralibpath | function |
| extralibpaths | function |
| extralupath | function |
| extralupaths | function |
| helpers | table |
| libpaths | function |
| loaded | table |
| loaders | table |
| loadlib | function |
| luapaths | function |
| path | string |
| preload | table |
| searchpath | function |
| seeall | function |

pagebuilders (context)

injections table

F flushafter
F flushbefore
F save

mixedcolumns table

F cleanup
F finalize
F getlist
F getrest
F getsplit
F setsplit

pdf (basic tex)

| | |
|---------------------------|---------------------|
| getcatalog | function |
| gethpos | function |
| getinfo | function |
| getmatrix | function |
| getnames | function |
| getpageattributes | function |
| getpageresources | function |
| getpagesattributes | function |
| getpos | function |
| gettrailer | function |
| getvpos | function |
| hasmatrix | function |
| immediateobj | function |
| mapfile | function |
| mapline | function |
| maxobjnum | function |
| obj | function |
| objtype | function |
| pageref | function |
| print | function |
| refobj | function |
| registerannot | overloaded function |
| reserveobj | function |
| setcatalog | overloaded function |
| setinfo | overloaded function |
| setnames | overloaded function |
| setpageattributes | overloaded function |
| setpageresources | overloaded function |
| setpagesattributes | overloaded function |
| settrailer | overloaded function |

pdfscanner (context)

scan function

physics (context)

units table

D tables

profiler (extra lua)

pause function
resume function
start function
stop function

publications (context)

| | | |
|-----------------------------|------------|----------------|
| addtexentry | function | S editor |
| analyze | function | S journal |
| anywhere | function | S keywords |
| authorcache | table | S number |
| authorcollapsers | data table | S pages |
| casters | table | S title |
| F author | | S volume |
| F keyword | | S year |
| F pagenumber | | T optional |
| F range | | T required |
| citevariants | table | T sets |
| F author | | T author |
| F authornum | | T virtual |
| F authoryear | | T book |
| F authoryears | | S category |
| F category | | T extra |
| F default | | T fields |
| F entry | | S address |
| F index | | S author |
| F key | | S edition |
| F keywords | | S editor |
| F num | | S keywords |
| F page | | S number |
| F serial | | S publisher |
| F short | | S subtitle |
| F tag | | S title |
| F type | | S volume |
| F year | | S year |
| collected | data table | T optional |
| components | table | T required |
| F author | | T sets |
| concatstate | function | T author |
| converttoxml | function | T editionset |
| currentspecification | table | T virtual |
| S author | | T demo-a |
| T categories | | S category |
| T article | | T extra |
| S category | | T fields |
| T extra | | S author |
| T fields | | S institution |
| S author | | S organization |

S subtitle
 S title
 S year
 T optional
 T required
 T sets
 T author
 T virtual
 T demo-b
 S category
 T extra
 T fields
 S author
 S institution
 S organization
 S subtitle
 S title
 S year
 T optional
 T required
 T sets
 T authors
 T virtual
 S comment
 S copyright
 T fields
 S name
 T types
 S author
 S editor
 S keywords
 S number
 S page
 S pages
 S volume
 S version
 T virtual
datasets
detailed
endnotes_to_btx
enhancer
 S arguments
 T askip
 B dirty

table
 table
 function
 table

T gskip
 T kind
 T list
 T system
 T order
enhancers
 F details
 F order
 F suffixes
finder
found
get
getcasted
getdetail
getdirect
getfaster
getfield
getfuzzy
getindex
inspectors
journals
 F abbreviated
 F add
 F expanded
 F load
 F save
lists
 F collectentries
 F fetchentries
 F filterall
 F flushentry
 T methods
 F dataset
 F force
 F global
 F local
 F nofregistered
 F prepareentries
 F register
 F sameasprevious
 T sorters
 F dataset
 F default
 F reference
 table
 function
 function
 function
 function
 function
 function
 function
 function
 data table
 table
 table

| | | |
|-------------------------|----------|----------------|
| F short | | S editor |
| F uservariable | | S journal |
| listvariants | table | S keywords |
| F bib | | S number |
| F default | | S pages |
| F num | | S title |
| F page | | S volume |
| F short | | S year |
| F yes | | T optional |
| load | function | T required |
| loadbibdata | function | T sets |
| loaders | table | T author |
| F bbl | | T virtual |
| F bib | | T book |
| F buffer | | S category |
| F endnote | | T extra |
| F lua | | T fields |
| F refman | | S address |
| F registercleaner | | S author |
| F xml | | S edition |
| new | function | S editor |
| okay | function | S keywords |
| parenttag | function | S number |
| permitted | function | S publisher |
| refman_to_btx | function | S subtitle |
| resolvedname | function | S title |
| save | function | S volume |
| search | function | S year |
| setcategory | function | T optional |
| setspecification | function | T required |
| singularorplural | function | T sets |
| sortedentries | function | T author |
| sortmethods | table | T editionset |
| T authorityyear | | T virtual |
| T sequence | | T demo-a |
| specifications | table | S category |
| T default | | T extra |
| S author | | T fields |
| T categories | | S author |
| T article | | S institution |
| S category | | S organization |
| T extra | | S subtitle |
| T fields | | S title |
| S author | | S year |

| | | | |
|-------------------|-------|---------------------------|----------|
| T optional | | D specials | |
| T required | | D types | |
| T sets | | D virtuals | |
| T author | | tags | function |
| T virtual | | tracers | table |
| T demo-b | | F showdatasetauthors | |
| S category | | F showdatasetcompleteness | |
| T extra | | F showdatasetfields | |
| T fields | | F showentry | |
| S author | | F showfields | |
| S institution | | F showtables | |
| S organization | | F showvariants | |
| S subtitle | | typesetters | table |
| S title | | F author | |
| S year | | F string | |
| T optional | | usedentries | function |
| T required | | writers | table |
| T sets | | F author | |
| T authors | | F keyword | |
| T virtual | | F pagenumber | |
| S comment | | F range | |
| S copyright | | | |
| T fields | | | |
| S name | | | |
| T types | | | |
| S author | | | |
| S editor | | | |
| S keywords | | | |
| S number | | | |
| S page | | | |
| S pages | | | |
| S volume | | | |
| S version | | | |
| T virtual | | | |
| statistics | table | | |
| N nofbytes | | | |
| N nofdatasets | | | |
| N nofdefinitions | | | |
| N nofshortcuts | | | |
| tables | table | | |
| D implicits | | | |
| D origins | | | |
| D privates | | | |
| D sets | | | |

regimes (context)

| | |
|-------------------|----------|
| cleanup | function |
| disable | function |
| enable | function |
| fromregime | function |
| pop | function |
| process | function |
| push | function |
| toregime | function |
| translate | function |

resolvers (context)

| | | | |
|-------------------------------------|------------|--------------------------------|------------|
| allprefixes | function | findtextfile | function |
| appendhash | function | findwildcardfile | function |
| automount | function | findwildcardfiles | function |
| automounted | table | formatofsuffix | function |
| booleanvariable | function | formatofvariable | function |
| cacheversion | string | formats | data table |
| checkedvariable | function | generators | data table |
| cleanedpathlist | function | get_from_content | function |
| cleanpath | function | getenv | function |
| cleanpathlist | function | getownpath | function |
| concatinators | data table | getreadfilename | function |
| configbanner | string | hashers | data table |
| criticalvars | data table | homedir | string |
| dangerous | data table | inputstack | table |
| datastate | function | installinputfilehandler | function |
| defaultsuffixes | table | installinputlinehandler | function |
| dowithfilesandreport | function | instance | table |
| dowithfilesintree | function | D data | |
| dowithpath | function | B diskcache | |
| dowithvariable | function | D environment | |
| env | function | D expansions | |
| executers | table | D fakepaths | |
| expandbraces | function | D files | |
| expandedpathfromlist | function | B force_suffixes | |
| expandedpathlist | function | D found | |
| expandedpathlistfromvariable | function | D foundintrees | |
| expandpath | function | D hashed | |
| expandpathfromvariable | function | D hashes | |
| expansion | function | D lists | |
| extendtexmfvariable | function | B loadererror | |
| filtered_from_content | function | D order | |
| find_file | function | D pathlists | |
| find_files | function | T pathstack | |
| findbinfile | function | B remember | |
| findctxfile | function | B renewcache | |
| finders | data table | B renewtree | |
| findfile | function | B savelists | |
| findfiles | function | D setups | |
| findgivenfile | function | D specification | |
| findgivenfiles | function | D variables | |
| findpath | function | jobpath | function |

| | | | |
|--------------------------|------------|-------------------------------|------------|
| jobs | table | registerfilehash | function |
| F currentcomponent | | registerintrees | function |
| F currentenvironment | | registermethod | function |
| F currentproduct | | registerzipfile | function |
| F currentproject | | relations | data table |
| F justacomponent | | renew | function |
| D processors | | repath | function |
| F productcomponent | | reset | function |
| F usefile | | resetextrapath | function |
| joinpath | function | resetresolve | function |
| load | function | resolve | function |
| loadbinfile | function | savers | data table |
| loaders | data table | scandata | function |
| loadlualib | function | scanfiles | function |
| loadtexfile | function | schemes | table |
| loadtime | function | T cleaners | |
| locateformat | function | F md5 | |
| locators | data table | F none | |
| luacnfname | string | F strip | |
| luacnfspec | string | F cleanname | |
| luacnfstate | string | F fetchstring | |
| macros | table | F fetchtable | |
| F convertfile | | F install | |
| F decodecomment | | setdynamic | function |
| F enablecomment | | setenv | function |
| F encodecomment | | setinstance | function |
| F preprocessed | | showpath | function |
| F processmk | | simplescanfiles | function |
| F processmkvi | | splitconfigurationpath | function |
| F version | | splitexpansions | function |
| maxreadlevel | number | splitmethod | function |
| methodhandler | function | splitpath | function |
| newinstance | function | stackpath | function |
| openbinfile | function | suffixes | data table |
| openers | data table | suffixmap | data table |
| openfile | function | suffixofformat | function |
| opentexfile | function | texdatablob | function |
| ownpath | string | toppath | function |
| poppath | function | unexpandedpath | function |
| prefixes | data table | unexpandedpathlist | function |
| prependhash | function | unresolve | function |
| pushpath | function | updaterelations | function |
| registerextrapath | function | updatescript | function |
| registerfile | function | usertypes | data table |

| | |
|---------------------------------|----------|
| usezipfile | function |
| validatedpath | function |
| variable | function |
| variableofformat | function |
| variableofformatorsuffix | function |
| wildcardpattern | function |

sandbox (context)

| | |
|--------------------------|----------|
| binaryhandler | function |
| disablerunners | function |
| enable | function |
| filehandlerone | function |
| filehandlertwo | function |
| finalizer | function |
| initializer | function |
| iohandler | function |
| logcalls | function |
| logfiles | function |
| original | function |
| overload | function |
| possiblepath | function |
| redefine | function |
| register | function |
| registerbinary | function |
| registerroot | function |
| registerrunner | function |
| report | function |
| run | function |
| runhandler | function |
| setfilenamelogger | function |
| setlogger | function |
| setreporter | function |
| settrace | function |
| validfilename | function |

scripts (context)

autofontfeature table
 F disable
 F enable
 F handler

categorytonumber data table

colors data table

decomposehangul function

defaults table
 N inter_char_half_shrink_factor
 N inter_char_half_stretch_factor
 N inter_char_hangul_penalty
 N inter_char_quarter_shrink_factor
 N inter_char_quarter_stretch_factor
 N inter_char_shrink_factor
 N inter_char_stretch_factor
 N inter_word_stretch_factor

handlers data table

hash table

injectors data table

installdataset function

installmethod function

numbertocategory data table

numbertodataset data table

numbertohandler data table

reset function

set function

splitters data table

set (context)

contains function
create function
tolist function
tonumber function
totable function

socket (extra lua)

| | | |
|-----------------------|----------|-----------------------------|
| BLOCKSIZE | number | S connection |
| _DEBUG | boolean | S content-description |
| _SETSIZE | number | S content-disposition |
| bind | function | S content-encoding |
| choose | function | S content-id |
| connect | function | S content-language |
| connect4 | function | S content-length |
| connect6 | function | S content-location |
| dns | table | S content-md5 |
| F getaddrinfo | | S content-range |
| F gethostname | | S content-transfer-encoding |
| F getnameinfo | | S content-type |
| F tohostname | | S date |
| F toip | | S diagnostic-code |
| ftp | table | S dsn-gateway |
| S PASSWORD | | S etag |
| N PORT | | S expect |
| N TIMEOUT | | S expires |
| S USER | | S final-log-id |
| F command | | S final-recipient |
| F get | | S from |
| F open | | S host |
| F put | | S if-match |
| gettime | function | S if-modified-since |
| headers | table | S if-none-match |
| T canonic | | S if-range |
| S accept | | S if-unmodified-since |
| S accept-charset | | S in-reply-to |
| S accept-encoding | | S keywords |
| S accept-language | | S last-attempt-date |
| S accept-ranges | | S last-modified |
| S action | | S location |
| S age | | S max-forwards |
| S allow | | S message-id |
| S alternate-recipient | | S mime-version |
| S arrival-date | | S original-envelope-id |
| S authorization | | S original-recipient |
| S bcc | | S pragma |
| S cache-control | | S proxy-authenticate |
| S cc | | S proxy-authorization |
| S comments | | S range |

S received
 S received-from-mta
 S references
 S referer
 S remote-mta
 S reply-to
 S reporting-mta
 S resent-bcc
 S resent-cc
 S resent-date
 S resent-from
 S resent-message-id
 S resent-reply-to
 S resent-sender
 S resent-to
 S retry-after
 S return-path
 S sender
 S server
 S smtp-remote-recipient
 S status
 S subject
 S te
 S to
 S trailer
 S transfer-encoding
 S upgrade
 S user-agent
 S vary
 S via
 S warning
 S will-retry-until
 S www-authenticate
 S x-mailer

http table

N PORT
 N TIMEOUT
 S USERAGENT
 F open
 F request

newtry function
protect function
select function
sink function

sinkt table

F close-when-done
 F default
 F http-chunked
 F keep-open

skip function

sleep function

smtp table

S DOMAIN
 N PORT
 S SERVER
 N TIMEOUT
 S ZONE
 F message
 F open
 F send

source function

sourcet table

F by-length
 F default
 F http-chunked
 F until-closed

tcp function

tcp6 function

tp table

N TIMEOUT
 F connect

try function

udp function

udp6 function

url table

F absolute
 F build
 F build_path
 F escape
 F parse
 F parse_path
 F unescape

sorters (context)

basicsorter function

comparers table

 F basic

constants table

 S defaultdigits

 S defaultlanguage

 S defaultmethod

 N digitmaximum

 N digitsoffset

 N ignoredoffset

 N replacementoffset

 T validmethods

 B ch

 B mc

 B mm

 B pc

 B pm

 B uc

 B zc

 B zm

definitions data table

firstofsplit function

setlanguage function

sort function

splitters table

 F utf

strip function

tracers data table

update function

statistics (context)

| | |
|-----------------------|----------|
| checkfmtstatus | function |
| elapsed | function |
| elapsedindeed | function |
| elapsedseconds | function |
| elapsedtime | function |
| enable | boolean |
| formatruntime | function |
| hastiming | function |
| memused | function |
| register | function |
| resettiming | function |
| runtime | function |
| savefmtstatus | function |
| show | function |
| starttiming | function |
| stoptiming | function |
| threshold | number |
| timed | function |
| tracefunction | function |

status (basic tex)

list function

storage (context)

| | |
|------------------------|------------|
| allocate | function |
| data | table |
| mark | function |
| marked | function |
| max | number |
| min | number |
| nofmodules | number |
| noftables | number |
| register | function |
| shared | data table |
| storedfunctions | data table |
| strip | boolean |
| tofmodules | number |
| toftables | number |

streams (context)

| | |
|--------------------|----------|
| collect | function |
| disable | function |
| enable | function |
| flush | function |
| initialize | function |
| push | function |
| start | function |
| stop | function |
| synchronize | function |

string (basic lua)

| | | | |
|-----------------------|----------|----------------------|----------|
| autodouble | function | tformat | function |
| autosingle | function | toHEX | function |
| booleanstring | function | toboollean | function |
| byte | function | tobytes | function |
| bytepairs | function | tocontext | function |
| bytes | function | todec | function |
| char | function | todimen | function |
| characterpairs | function | tohex | function |
| characters | function | tonodes | function |
| checkedsplit | function | topattern | function |
| collapsespaces | function | totable | function |
| count | function | toutf | function |
| dump | function | tracedchar | function |
| escapedpattern | function | tracedchars | table |
| explode | function | unquote | function |
| find | function | unquoted | function |
| format | function | upper | function |
| formatter | function | utfcharacters | function |
| formatters | function | utfvalues | function |
| fullstrip | function | valid | function |
| gmatch | function | | |
| gsub | function | | |
| is_boolean | function | | |
| is_empty | function | | |
| itself | function | | |
| len | function | | |
| limit | function | | |
| longtostring | function | | |
| lower | function | | |
| match | function | | |
| nspaces | table | | |
| optionalquoted | function | | |
| quote | function | | |
| quoted | function | | |
| rep | function | | |
| reverse | function | | |
| split | function | | |
| splitlines | function | | |
| splitup | function | | |
| strip | function | | |
| sub | function | | |

structures (context)

| | | |
|-------------------|----------|-----------------------------|
| allocation | function | F previous |
| blocks | table | F raw |
| D collected | | F record |
| F define | | F reset |
| F print | | F restart |
| F save | | F restore |
| F select | | F save |
| F setstate | | F set |
| D states | | F setlevel |
| D tobesaved | | F setoffset |
| bookmarks | table | F setown |
| T extras | | F setstate |
| F get | | F setvalue |
| F mergesections | | T specials |
| F register | | F userpage |
| F reset | | F subs |
| F tosections | | D tobesaved |
| F finalize | | F value |
| F flatten | | currentsectionnumber |
| F installhandler | | descriptions |
| F merge | | documents |
| S method | | D data |
| F overload | | F initialize |
| F place | | F preset |
| F register | | F reset |
| F setup | | floats |
| counters | table | formulas |
| F add | | F current |
| F analyze | | F simplify |
| F check | | F store |
| D collected | | helpers |
| F compact | | F analyze |
| F converted | | F formulanumber |
| F currentvalue | | F merged |
| D data | | F page |
| F define | | F prefix |
| F first | | F prefixlastpage |
| F get | | F prefixpage |
| F last | | F simplify |
| F next | | F title |
| F prev | | F touserdata |

inserts

D data
F define
F getdata
F getlocation
F getname
F getnumber
F setlocation
F setup
D stored

table

itemgroups

table

lists

table

F addto
F analyze
B autoreorder
D cached
D collected
F discard
F enhance
T enhancers
F filter
F formulanumber
F getresult
F groupindex
F hasnumberdata
F haspagedata
F hastitledata
F iscached
D kinds
F label
F location
D names
F number
D ordered
F page
F popnesting
F prefix
F prefixednumber
F prefixedpage
F process
D pushed
F pushnesting
F realpage
F reordered

T result
D sectionblocks
F sectionnumber
F size
F title
D tobesaved
F userdata
F uservalue

marks

table

D data
F define
F exists
F fetch
F fetchallmarks
F fetched
F fetchonemark
F fetchtwomarks
F get
F number
F relate
F reset
F set
F show
F synchronize
F title
T tracers
F showtable

notes

table

F checkpagechange
F define
F doifonsamepageasprevious
F get
F getdeltapage
F getn
F getnumberpage
F getstate
F getsymbolpage
F hascontent
F internal
F internalid
F listindex
F ordered
F postpone
F resetpostponed

| | | | |
|---------------------|--------------|------------------------|--|
| F restore | | F get | |
| F save | | F getcurrentmetadata | |
| F setstate | | F getcurrentprefixspec | |
| F setsymbolpage | | F getinnermethod | |
| D states | | F getinternalreference | |
| F store | | F getinternalreference | |
| pages | table | D handlers | |
| F analyze | | F identify | |
| D collected | | F import | |
| F is_odd | | F inject | |
| N nopages | | F injectcurrentset | |
| F number | | S innermethod | |
| F save | | D internals | |
| D tobesaved | | F load | |
| references | table | F loadpresets | |
| F analyze | | F mark | |
| F checkedfile | | D pages | |
| F checkedfileorurl | | U prefixsplitter | |
| F checkedprogram | | D productdata | |
| F checkedrealpage | | T programs | |
| F checkedurl | | T data | |
| D collected | | F define | |
| U componentsplitter | | F get | |
| F currentmetadata | | F realpageofpage | |
| F currentorder | | U referencesplitter | |
| D currentset | | D referred | |
| F define | | F referredpage | |
| D defined | | F registerfinalizer | |
| D derived | | F registerinitializer | |
| F enableinteraction | | F registerpage | |
| F enhance | | F reportproblems | |
| D executers | | F reset | |
| F expandcurrent | | D runners | |
| F export | | F set | |
| T files | | F setandgetattribute | |
| T data | | F setcomponent | |
| F define | | F setinnermethod | |
| F get | | F setinternalreference | |
| F filter | | F setnextinternal | |
| F filterdefault | | F setnextorder | |
| D filters | | F setreferencerealpage | |
| D flaginternals | | D specials | |
| F from | | F splitcomponent | |
| D functions | | F splitprefix | |

- F splitreference
- F synchronizepage
- T testrunners
 - F inner
 - F special
 - F special operation
 - F special operation with arguments
- T testspecials
 - F deltapage
 - F i
 - F internal
 - F page
 - F realpage
 - F section
 - F userpage
- D tobereferred
- D tobesaved
- T urls
 - T data
 - F define
 - F get
- D usedinternals
- D usedviews
- F valid
- F whatfrom

registers

table

- F analyze
- D collected
- F compare
- F define
- F enhance
- F extend
- F filter
- F filtercollected
- F finalize
- F flush
- F get
- F prepare
- F process
- F setmethod
- F sort
- F store
- D tobesaved
- F unique

- F userdata
- sections**
- table
 - F autodepth
 - F cct
 - D collected
 - F current
 - F currentblock
 - F currentid
 - F currentlevel
 - F currentsectionindex
 - F depthnumber
 - F finddata
 - F findnumber
 - F fullnumber
 - F getcurrentlevel
 - F getlevel
 - F getnumber
 - F internalreference
 - D levelmap
 - D levels
 - F load
 - F matchingtilldepth
 - F numberatdepth
 - F numbers
 - F popblock
 - F prefixedconverted
 - F pushblock
 - F register
 - D registered
 - F reportstructure
 - F save
 - T sectionblockdata
 - T bodypart
 - S bookmark
 - F set
 - F setblock
 - F setchecker
 - F setentry
 - F setlevel
 - F setnumber
 - F structuredata
 - F title
 - D tobesaved
 - F typesetnumber

| | | |
|--------------------|--------------|------------------------|
| F userdata | | F setdescriptionsymbol |
| B verbose | | F setfigure |
| sets | table | F sethighlight |
| F define | | F setitemgroup |
| F get | | F setlist |
| F getall | | F setproperty |
| D setlist | | F setregister |
| specials | table | F setsorting |
| D collected | | F setsynonym |
| F retrieve | | F settablecell |
| F store | | F settabulatecell |
| D tobesaved | | F setuserproperties |
| synonyms | table | D specifications |
| F analyzed | | F start |
| D collected | | F stop |
| F compare | | D taglist |
| F define | | |
| F filter | | |
| F finalize | | |
| F flush | | |
| F meaning | | |
| F prepare | | |
| F process | | |
| F register | | |
| F registerused | | |
| F sort | | |
| F synonym | | |
| D tobesaved | | |
| tags | table | |
| F getid | | |
| F handler | | |
| D labels | | |
| F last | | |
| F lastinchain | | |
| F locatedtag | | |
| T patterns | | |
| U splitter | | |
| D properties | | |
| F registermetadata | | |
| F restart | | |
| F setaspect | | |
| F setattributehash | | |
| F setcombination | | |
| F setdescription | | |

table (basic lua)

| | | | |
|------------------------|----------|-----------------------------|----------|
| allkeys | function | sequenced | function |
| append | function | serialize | function |
| are_equal | function | setmetatablecall | function |
| autokey | function | setmetatableindex | function |
| compact | function | setmetatablekey | function |
| concat | function | setmetatablenewindex | function |
| contains | function | sort | function |
| copy | function | sorted | function |
| count | function | sortedhash | function |
| derive | function | sortedhashkeys | function |
| deserialize | function | sortedhashonly | function |
| drop | function | sortedindexonly | function |
| fastcopy | function | sortedkeys | function |
| fastserialize | function | sortedpairs | function |
| filtered | function | sparse | function |
| flattened | function | strip | function |
| foreach | function | sub | function |
| foreachi | function | swapped | function |
| fromhash | function | tocontext | function |
| getmetatablekey | function | tocsv | function |
| getn | function | tofile | function |
| has_one_entry | function | tohandle | function |
| identical | function | tohash | function |
| imerge | function | toxml | function |
| imerged | function | twowaymapper | function |
| insert | function | unique | function |
| is_empty | function | unnest | function |
| keys | function | unpack | function |
| load | function | values | function |
| loweredkeys | function | | |
| maxn | function | | |
| merge | function | | |
| merged | function | | |
| mirrored | function | | |
| pack | function | | |
| prepend | function | | |
| print | function | | |
| remove | function | | |
| reverse | function | | |
| reversed | function | | |
| save | function | | |

tex (basic tex)

| | | | |
|-------------------------|------------|------------------------------|------------|
| attribute | table | isdefined | function |
| badness | function | isdimen | function |
| box | table | isskip | function |
| catcode | table | istoken | function |
| conditionals | data table | lccode | table |
| constants | data table | linebreak | function |
| count | table | lists | table |
| ctdcatcodes | number | lua_math_random | function |
| ctxcatcodes | number | lua_math_randomseed | function |
| definefont | function | luacatcodes | number |
| delcode | table | mathcode | table |
| dimen | table | modes | data table |
| directives | data table | nest | table |
| enableprimitives | function | nilcatcodes | number |
| error | function | normal_rand | function |
| extraprimitives | function | notcatcodes | number |
| finish | function | number | function |
| fontidentifier | function | pdffontname | function |
| fontname | function | pdffontobjnum | function |
| fprint | function | pdffontsize | function |
| get | function | pdfpageref | function |
| getattribute | function | pdfxformname | function |
| getbox | function | primitives | function |
| getcatcode | function | print | function |
| getcount | function | prtcacodes | number |
| getdelcode | function | romannumeral | function |
| getdimen | function | round | function |
| getlccode | function | run | function |
| getlist | function | scale | function |
| getmath | function | set | function |
| getmathcode | function | set_experimental_code | function |
| getnest | function | setattribute | function |
| getsfcode | function | setbox | function |
| getskip | function | setcatcode | function |
| gettoks | function | setcount | function |
| getuccode | function | setdelcode | function |
| hashtokens | function | setdimen | function |
| ifs | data table | setlccode | function |
| inicalcodes | number | setlist | function |
| init_rand | function | setmath | function |
| iscount | function | setmathcode | function |

| | |
|-----------------------|------------|
| setnest | function |
| setsfcode | function |
| setskip | function |
| settoks | function |
| setuccode | function |
| sfcode | table |
| shipout | function |
| show_context | function |
| skip | table |
| sp | function |
| sprint | function |
| systemmodes | data table |
| takebox | function |
| texcatcodes | number |
| toks | table |
| tpacatcodes | number |
| tpbcacodes | number |
| tprint | function |
| trackers | data table |
| txtcatcodes | number |
| type | function |
| uccode | table |
| uniform_rand | function |
| uniformdeviate | function |
| uprint | function |
| vrbcacodes | number |
| write | function |

texconfig (basic tex)

| | |
|------------------------|---------------------|
| error_line | number |
| expand_depth | number |
| formatname | string |
| half_error_line | number |
| hash_extra | number |
| init | overloaded function |
| kpse_init | boolean |
| max_in_open | number |
| max_print_line | number |
| max_strings | number |
| nest_size | number |
| param_size | number |
| save_size | number |
| shell_escape | string |
| stack_size | overloaded number |

texio (basic tex)

`write` function

`write_nl` function

token (basic tex)

| | |
|----------------------|----------|
| command_id | function |
| command_name | function |
| create | function |
| csname_id | function |
| csname_name | function |
| expand | function |
| get_next | function |
| is_activechar | function |
| is_expandable | function |
| is_protected | function |
| lookup | function |

tokens (context)

astable function
bgroup userdata
bits table

N active
N alignment
N begingroup
N character
N close
N comment
N endgroup
N endofline
N escape
N ignore
N invalid
N letter
N mathshift
N open
N other
N parameter
N space
N subscript
N superscript
N whitespace

collectors table

T data
F defaultwords
F dowithwords
F flush
F install
F register
T registered
F show
F test

compile function

converters table

S todimen
S toglue
S tonumber
S toString

egroup userdata

getters table

F token

hbox userdata

istoken function

letter function

letters function

other function

pickup function

printlist function

scanners table

F boolean

F code

F count

F dimen

F dimension

F glue

F integer

F keyword

F number

F skip

F string

F token

F tokens

F toks

F word

scantable function

setters table

F macro

vbox userdata

vtop userdata

tracers (context)

| | |
|------------------|----------|
| count | function |
| cs | function |
| dimen | function |
| knownlist | function |
| lists | table |

T context

T internals

T scratch

| | |
|------------------|----------|
| name | function |
| primitive | function |
| prnterror | function |
| showlines | function |
| strings | table |

S undefined

| | |
|-------------|----------|
| toks | function |
| type | function |

trackers (context)

| | |
|-----------------------|------------|
| data | data table |
| default | function |
| disable | function |
| dumphashtofile | function |
| enable | function |
| list | function |
| name | string |
| register | function |
| report | function |
| savehash | function |
| show | function |
| value | function |

typesetters (context)

| | | | |
|-----------------------|-------|----------------------|-------|
| alignments | table | F installhandler | |
| F handler | | F processmath | |
| F set | | F set | |
| breakpoints | table | F setcolor | |
| F define | | F setmath | |
| F handler | | F tomode | |
| D mapping | | firstlines | table |
| T methods | | T actions | |
| T numbers | | F default | |
| F set | | F line | |
| F setreplacement | | F word | |
| cases | table | F handler | |
| T actions | | F set | |
| F handler | | initials | table |
| F register | | T actions | |
| F set | | F default | |
| characteralign | table | F handler | |
| F handler | | F set | |
| F resetcharacteralign | | injectors | table |
| F setcharacteralign | | F check | |
| characters | table | T list | |
| F handler | | F mark | |
| F replacensp | | F reset | |
| F replacenspaces | | F set | |
| checkers | table | F show | |
| F handler | | italics | table |
| F reset | | F forcevariant | |
| F set | | F handler | |
| cleaners | table | F reset | |
| F handler | | F set | |
| F set | | kerns | table |
| digits | table | D factors | |
| T actions | | F handler | |
| F handler | | F keepligature | |
| F set | | B keeptogether | |
| directions | table | D mapping | |
| F getfences | | F set | |
| F getglobal | | manipulators | table |
| F getmethod | | F apply | |
| F handler | | F applyspecification | |
| T handlers | | T methods | |

| | | |
|----------------------|-----------------|----------------------------|
| F Word | | F construct |
| F Words | | F create |
| F abbreviatedjournal | | F finish_row |
| F expandedjournal | | F flush |
| F lowercase | | F initialize_construct |
| F stripperperiod | | F initialize_reflow_height |
| F uppercase | | F initialize_reflow_width |
| T patterns | | F next_row |
| U list | | F reflow_height |
| U pair | | F reflow_width |
| F splitspecification | | F set_construct |
| margins | table | F set_reflow_height |
| F finalhandler | | F set_reflow_width |
| F globalhandler | | |
| F ha | | |
| F localhandler | | |
| F save | | |
| marksuspects | function | |
| processors | table | |
| F apply | | |
| F register | | |
| F reset | | |
| F split | | |
| F startapply | | |
| F stopapply | | |
| F stripped | | |
| F tostring | | |
| showsuspects | function | |
| spacings | table | |
| F define | | |
| F handler | | |
| D mapping | | |
| T numbers | | |
| T frenchpunctuation | | |
| T characters | | |
| S name | | |
| N number | | |
| F reset | | |
| F set | | |
| F setup | | |
| wrappers | table | |
| F handler | | |
| xtables | table | |
| F cleanup | | |

unicode (extra lua)

ascii table

F byte
F char
F dump
F find
F format
F gfind
F gmatch
F gsub
F len
F lower
F match
F rep
F reverse
F sub
F upper

grapheme table

F byte
F char
F dump
F find
F format
F gfind
F gmatch
F gsub
F len
F lower
F match
F rep
F reverse
F sub
F upper

latin1 table

F byte
F char
F dump
F find
F format
F gfind
F gmatch
F gsub

F len
F lower
F match
F rep
F reverse
F sub
F upper

utf8 table

F byte
F char
F characters
F chrln
F count
F dump
F filetype
F find
F format
F gfind
F gmatch
F gsub
F is_valid
F len
F length
F lower
F magic
F match
F remapper
F rep
F replacer
F reverse
F split
F splitlines
F sub
F subtituter
F tocodes
F toeight
F toentities
F toString
F totable
F upper
F ustring

F utf16_to_utf8_be
F utf16_to_utf8_be_t
F utf16_to_utf8_le
F utf16_to_utf8_le_t
F utf16_to_utf8_t
F utf32_to_utf8_be
F utf32_to_utf8_be_t
F utf32_to_utf8_le
F utf32_to_utf8_le_t
F utf32_to_utf8_t
F utf8_to_utf16
F utf8_to_utf16_be
F utf8_to_utf16_le
F utf8_to_utf8_t
F values
F xstring

url (context)

| | |
|--------------------|----------|
| addscheme | function |
| barepath | function |
| construct | function |
| escape | function |
| filename | function |
| hashed | function |
| hasscheme | function |
| query | function |
| split | function |
| toquery | function |
| unescapeget | function |

utilities (context)

debugger table

F disable
F enable
F savestats
F showstats
F showtraceback

formatters table

F formatcolumns
F list
F stripzeros

garbagecollector table

F check
N criterium
B enabled

lua table

B alwaysstripcode
F compile
F loadedluacode
F loadstripped
N nofstrippedbytes
N nofstrippedchunks
B stripcode
T strippedchunks
F strippedloadstring
T suffixes
S lua
S luc
S lui
S luj
S luv
S tma
S tmc
S tua
S tuc

packers table

F hashed
F new
F pack
F simplehashed
F strip
F unpack

N version

parsers table

F add_settings_to_array
F arguments_to_table
F array_to_string
F csvsplitter
F getparameters
F groupedsplitat
F hash_to_string
F iterator
F keq_to_hash
F listitem
F make_settings_to_hash_pattern
F mergehashes
F options_to_hash
T patterns
U settings_to_array
U settings_to_hash_a
U settings_to_hash_b
U settings_to_hash_c
U unittotex
F process_stripped_settings
F rfc4180splitter
F runtime
F settings_to_array
F settings_to_array_with_repeat
F settings_to_hash
F settings_to_hash_strict
F settings_to_hash_tolerant
F settings_to_set
F simple_hash_to_string
F splitmethod
F splitthousands
F stepper
F stripped_settings_to_array
F unittotex
F unittotxml

report function sequencers table

F appendaction
F appendgroup

| | |
|----------------------|------------------------|
| F compile | U prune and collapse |
| F disableaction | U prune and no empty |
| F disablegroup | U retain |
| F enableaction | U retain and collapse |
| F enablegroup | U retain and no empty |
| D functions | F striplines |
| F localize | F striplong |
| F new | F tabtospace |
| F nodeprocessor | T tracers |
| F prependaction | tables table |
| F prependgroup | F accesstable |
| F removeaction | F definedtable |
| F replaceaction | F definetable |
| F setkind | F encapsulate |
| F tostring | F insertaftervalue |
| setters table | F insertbeforevalue |
| F disable | F migratetable |
| F enable | F removevalue |
| F initialize | F replacevalue |
| F list | templates table |
| F new | F load |
| F register | F replace |
| F report | F replacer |
| F reset | F resolve |
| F show | |
| stacker table | |
| F new | |
| storage table | |
| F allocate | |
| F checked | |
| F mark | |
| F marked | |
| F setinitializer | |
| F sparse | |
| strings table | |
| F collapsecrLf | |
| T formatters | |
| F add | |
| F new | |
| F newrepeater | |
| F nice | |
| T striplinepatterns | |
| U collapse | |
| U prune | |

vf (context)

| | |
|----------------|----------|
| char | function |
| down | function |
| fontid | function |
| image | function |
| node | function |
| nop | function |
| pop | function |
| push | function |
| right | function |
| rule | function |
| special | function |

visualizers (context)

| | |
|------------------------------|------------|
| escapepatterns | data table |
| getvisualizer | function |
| load | function |
| makenested | function |
| makepattern | function |
| newgrammar | function |
| newhandler | function |
| parsedxml | function |
| pattern | function |
| register | function |
| registerescapecommand | function |
| registerescapeline | function |
| registerescapepattern | function |
| signal | string |
| signalpattern | userdata |
| specifications | data table |
| visualize | function |
| visualizebuffer | function |
| visualizefile | function |
| visualizestring | function |
| write | function |
| writeargument | function |
| writedefault | function |
| writeemptyline | function |
| writenewline | function |
| writespace | function |

xml (context)

| | | | |
|---------------------------|----------|------------------------|------------|
| addentitiesdoctype | function | D tex | |
| after | function | D texline | |
| all | function | D texspace | |
| applylpath | function | D verbose | |
| assign | function | defaultprotocol | string |
| attribute | function | delete | function |
| before | function | delete_element | function |
| body | function | each | function |
| builtinentities | table | each_element | function |
| B amp | | elements | function |
| B apos | | elementtocdata | function |
| B gt | | empty | function |
| B lt | | entities | data table |
| B quot | | erase | function |
| cdata | function | errorhandler | function |
| cdatatotext | function | escaped | function |
| checkbom | function | expressions | table |
| checkerror | function | F boolean | |
| checknamespace | function | F child | |
| checkns | function | F contains | |
| cleansed | function | F count | |
| collect | function | F error | |
| collect_elements | function | F find | |
| collect_tags | function | F idstring | |
| collect_texts | function | F lower | |
| collected | function | F name | |
| collecttexts | function | F number | |
| content | function | F oneof | |
| convert | function | F print | |
| copy | function | F quit | |
| count | function | F tag | |
| cprint | function | F text | |
| css | table | F undefined | |
| F colorspecification | | F upper | |
| F dimension | | fillin | function |
| F fontspecification | | filter | function |
| F padding | | finalizers | table |
| defaulthandlers | table | F paragraphs | |
| D file | | T tex | |
| D parsedxml | | F all | |
| D string | | F attribute | |

| | | |
|------------------|------------------------------|----------|
| F chainattribute | F reverse | |
| F command | F table | |
| F concat | F tag | |
| F concatrange | F tags | |
| F context | F text | |
| F count | F texts | |
| F ctxtext | F upperall | |
| F default | first | function |
| F first | found | function |
| F function | functions | table |
| F index | getbuffer | function |
| F last | gethandlers | function |
| F lettered | gethandlersfunction | function |
| F lower | helpers | table |
| F lowerall | F recursetext | |
| F match | include | function |
| F name | inclusion | function |
| F position | inclusions | function |
| F reverse | index | function |
| F stripped | inheritedconvert | function |
| F tag | inject | function |
| F tags | inject_element | function |
| F text | inject_element_after | function |
| F upper | inject_element_before | function |
| F upperall | injectafter | function |
| T xml | injectbefore | function |
| F all | insert | function |
| F att | insert_element | function |
| F attribute | insert_element_after | function |
| F attributes | insert_element_before | function |
| F cdata | insertafter | function |
| F chainattribute | insertbefore | function |
| F count | insertcdata | function |
| F default | insertcomment | function |
| F elements | inspect | function |
| F empty | is_valid | function |
| F first | kind | function |
| F function | last | function |
| F index | load | function |
| F last | lpath | function |
| F lowerall | lpathcached | function |
| F match | lpathcalls | function |
| F name | lshow | function |
| F position | makestandalone | function |

| | | | |
|----------------------------|---------------------|---------------------------|----------|
| match | function | specialhandler | table |
| name | function | sprint | function |
| newhandlers | function | string | function |
| nodesettostring | function | strip | function |
| originalload | function | strip_whitespace | function |
| package | function | stripelement | function |
| parent | function | stripleadingspaces | function |
| parsedentitylpeg | userdata | table | function |
| pihandlers | table | text | function |
| placeholders | table | textonly | function |
| F unknown_any_entity | | texttocdata | function |
| F unknown_dec_entity | | tocdata | function |
| F unknown_hex_entity | | toelement | function |
| position | function | tostring | function |
| privatecodes | table | totable | function |
| privatetoken | function | toxml | function |
| process | function | tprint | function |
| process_attributes | function | traverse | function |
| process_elements | function | unescaped | function |
| processattributes | function | unprivatized | function |
| profiled | table | withelement | function |
| raw | function | withelements | function |
| registerentity | function | wrap | function |
| registers | function | xmlns | table |
| remap_name | function | | |
| remap_namespace | function | | |
| remap_tag | function | | |
| remapname | function | | |
| remapnamespace | function | | |
| remaptag | function | | |
| renamespace | function | | |
| replace | function | | |
| replace_element | function | | |
| resolvens | function | | |
| root | function | | |
| save | function | | |
| selection | function | | |
| separate | function | | |
| serialize | function | | |
| setcdata | function | | |
| setcomment | function | | |
| sethandlersfunction | function | | |
| setproperty | function | | |
| settings | function | | |

zip (extra lua)

| | |
|------------------------|---------------------|
| archives | table |
| close | function |
| closearchive | function |
| open | overloaded function |
| openarchive | function |
| openfile | function |
| registeredfiles | table |
| type | function |

zlib (extra lua)

| | |
|----------------------|----------|
| adler32 | function |
| compress | function |
| compressobj | function |
| crc32 | function |
| decompress | function |
| decompressobj | function |
| version | function |