

1 attributes backends bibtex blobs  
boolean buffers builders caches  
callback callbacks catcodes characters  
chemicals commands containers context  
converters coroutine debug dir  
directives document documentdata  
environment epdf experiments figures  
file floats font fontloader fonts  
global gzip img interactions interfaces  
io job lang languages layouts lfs  
libraries lmx logs lpdf lpeg ltn12  
lua luatex lxml math mathematics md5  
metapost mime moduledata modules mplib  
noads node nodes number os package  
parametersets pdf physics profiler  
regimes resolvers scripts set socket  
sorters statistics status storage  
streams string structures table tex  
texconfig texio token tokens tracers  
trackers typesetters unicode url  
utilities visualizers xml zip zlib

# ConT<sub>E</sub>Xt MkIV

# global (alias: \_G)

<a href="#">1</a>	table	<a href="#">io</a>	table
<a href="#">arg</a>	table	<a href="#">ipairs</a>	function
<a href="#">assert</a>	function	<a href="#">job</a>	table
<a href="#">attributes</a>	table	<a href="#">lang</a>	table
<a href="#">backends</a>	table	<a href="#">languages</a>	table
<a href="#">beginpage</a>	function	<a href="#">layouts</a>	table
<a href="#">bibtex</a>	table	<a href="#">lfs</a>	table
<a href="#">blobs</a>	table	<a href="#">libraries</a>	table
<a href="#">boolean</a>	table	<a href="#">lmx</a>	table
<a href="#">buffers</a>	table	<a href="#">load</a>	function
<a href="#">builders</a>	table	<a href="#">loadfile</a>	function
<a href="#">caches</a>	table	<a href="#">loadstring</a>	function
<a href="#">callback</a>	table	<a href="#">logs</a>	table
<a href="#">callbacks</a>	table	<a href="#">lpdf</a>	table
<a href="#">catcodes</a>	table	<a href="#">lpeg</a>	table
<a href="#">characters</a>	table	<a href="#">ltn12</a>	table
<a href="#">chemicals</a>	table	<a href="#">lua</a>	table
<a href="#">collectgarbage</a>	function	<a href="#">luatex</a>	table
<a href="#">commands</a>	table	<a href="#">lxml</a>	table
<a href="#">containers</a>	table	<a href="#">math</a>	table
<a href="#">context</a>	function	<a href="#">mathematics</a>	table
<a href="#">converters</a>	table	<a href="#">md5</a>	table
<a href="#">coroutine</a>	table	<a href="#">metapost</a>	table
<a href="#">debug</a>	table	<a href="#">mime</a>	table
<a href="#">dimen</a>	function	<a href="#">module</a>	function
<a href="#">dir</a>	table	<a href="#">moduledata</a>	table
<a href="#">directives</a>	table	<a href="#">modules</a>	table
<a href="#">document</a>	table	<a href="#">mplib</a>	table
<a href="#">documentdata</a>	table	<a href="#">newline</a>	function
<a href="#">dofile</a>	function	<a href="#">newproxy</a>	function
<a href="#">endpage</a>	function	<a href="#">next</a>	function
<a href="#">environment</a>	table	<a href="#">noads</a>	table
<a href="#">epdf</a>	table	<a href="#">node</a>	table
<a href="#">error</a>	function	<a href="#">nodes</a>	table
<a href="#">experiments</a>	table	<a href="#">number</a>	table
<a href="#">figures</a>	table	<a href="#">os</a>	table
<a href="#">file</a>	table	<a href="#">outputpagestree</a>	function
<a href="#">floats</a>	table	<a href="#">package</a>	table
<a href="#">font</a>	table	<a href="#">pairs</a>	function
<a href="#">fontloader</a>	table	<a href="#">parametersets</a>	table
<a href="#">fonts</a>	table	<a href="#">pcall</a>	function
<a href="#">gcinfo</a>	function	<a href="#">pdf</a>	table
<a href="#">getfenv</a>	function	<a href="#">physics</a>	table
<a href="#">getmetatable</a>	function	<a href="#">print</a>	function
<a href="#">getreadfilename</a>	function	<a href="#">profiler</a>	table
<a href="#">global</a>	table	<a href="#">protect</a>	function
<a href="#">gzip</a>	table	<a href="#">rawequal</a>	function
<a href="#">img</a>	table	<a href="#">rawget</a>	function
<a href="#">inspect</a>	function	<a href="#">rawset</a>	function
<a href="#">interactions</a>	table	<a href="#">regimes</a>	table
<a href="#">interfaces</a>	table	<a href="#">report_characters</a>	function

<code>require</code>	<code>function</code>	<code>tocontext</code>	<code>function</code>
<code>resolvers</code>	<code>table</code>	<code>token</code>	<code>table</code>
<code>scripts</code>	<code>table</code>	<code>tokens</code>	<code>table</code>
<code>select</code>	<code>function</code>	<code>tonumber</code>	<code>function</code>
<code>set</code>	<code>table</code>	<code>tostring</code>	<code>function</code>
<code>setfenv</code>	<code>function</code>	<code>trace_characters</code>	<code>boolean</code>
<code>setmetatable</code>	<code>function</code>	<code>traceback</code>	<code>function</code>
<code>socket</code>	<code>table</code>	<code>tracers</code>	<code>table</code>
<code>sorters</code>	<code>table</code>	<code>trackers</code>	<code>table</code>
<code>statistics</code>	<code>table</code>	<code>type</code>	<code>function</code>
<code>status</code>	<code>table</code>	<code>typesetters</code>	<code>table</code>
<code>storage</code>	<code>table</code>	<code>unicode</code>	<code>table</code>
<code>streams</code>	<code>table</code>	<code>unpack</code>	<code>function</code>
<code>string</code>	<code>table</code>	<code>url</code>	<code>table</code>
<code>stripmath</code>	<code>function</code>	<code>utf</code>	<code>table</code>
<code>structures</code>	<code>table</code>	<code>utilities</code>	<code>table</code>
<code>table</code>	<code>table</code>	<code>visualizers</code>	<code>table</code>
<code>tex</code>	<code>table</code>	<code>xml</code>	<code>table</code>
<code>texconfig</code>	<code>table</code>	<code>xpcall</code>	<code>function</code>
<code>texio</code>	<code>table</code>	<code>zip</code>	<code>table</code>
<code>toboolean</code>	<code>function</code>	<code>zlib</code>	<code>table</code>

# attributes (context)

**colorintents**      table

N attribute  
D data  
F enable  
F handler  
F register  
D registered

**colors**            table

N attribute  
F cmyk  
F cmyktogray  
F cmyktorgb  
F colorcomponents  
B couple  
D data  
N default  
F defineintermediatecolor  
F definemixcolor  
F definemultitonecolor  
F defineprocesscolor  
F definesimplegray  
F definespotcolor  
F definetransparency  
F enable  
F filter  
F forcedmodel  
F forcesupport  
F formatcolor  
F formatgray  
F gray  
F graytohsb  
F handler  
F hsbtogray  
F hsbtorgb  
F iccprofile  
F isblack  
N main  
S model  
F mpcolor  
F mpoptions  
U none  
F register  
D registered  
F registerspotcolor  
F rgb  
F rgbtocmyk  
F rgbtogray  
F rgbtohsb  
N selector  
F setmodel  
F spot

F spotcolorname  
F spotcolorparent  
F spotcolorvalue  
B supported  
F transparencycomponents  
B triggering  
F usecolors  
F value  
D values  
B weightgray

**define**            function

**effects**           table

N attribute  
D data  
F enable  
F handler  
F register  
D registered  
D values

**handlers**          table

**list**              data table

**names**             data table

**negatives**        table

N attribute  
D data  
F enable  
F handler  
F register  
D registered

**numbers**           data table

**ofnode**            function

**private**           function

**states**            table

F disabletriggering  
F enabletriggering  
F finalize  
F initialize  
F process  
F selective  
F stacked

**transparencies**   table

N attribute  
D data  
F enable  
F forcesupport  
F handler  
U none  
F register  
D registered  
B supported  
B triggering

F value		B hasorder
D values		D listwise
<b>unsetvalue</b>	number	F register
<b>viewerlayers</b>	table	D registered
N attribute		D scopes
D data		F setfeatures
F define		F start
F enable		F stop
F forcesupport		B supported
F handler		D values

# backends (context)

<b>codeinjections</b>	table	F setpagetransition
<b>current</b>	string	F setupcanvas
<b>defaults</b>	table	F setupidentity
T codeinjections		F setxmpfile
T nodeinjections		F startlayer
T registrations		F stoplayer
D tables		F supportedformats
<b>install</b>	function	F useviewerlayer
<b>nodeinjections</b>	table	F validfield
F restore		F validfieldcategory
F save		F validfieldset
F transform		S comment
<b>nothing</b>	function	T nodeinjections
<b>pdf</b>	table	F addtags
T codeinjections		F attachfile
F addbookmarks		F cmykcolor
F addtransparencygroup		F comment
F attachmentid		F destination
F clonefield		F effect
F definefield		F graycolor
F definefieldset		F injectbitmap
F defineviewerlayer		F insertmovie
F embedfile		F insertsound
F enabletags		F insertswf
F finalizepage		F insertu3d
F finishreference		F knockout
F getdefaultfieldvalue		F negative
F getfieldcategory		F overprint
F getfieldset		F positive
F getformatoption		F reference
F getoutputfilename		F rgbcolor
F getpreviewfigure		F spotcolor
F insertrenderingwindow		F startlayer
F mergereferences		F stoplayer
F mergeviewerlayers		F switchlayer
F prerollreference		F transparency
F presetsymbol		F typesetfield
F presetsymbollist		T registrations
F processrendering		F cmykindexcolor
F registerdocumentcloseaction		F cmykspotcolor
F registerdocumentopenaction		F getspotcolorreference
F registeredsymbol		F grayindexcolor
F registerpagecloseaction		F grayspotcolor
F registerpageopenaction		F rgbindexcolor
F registersymbol		F rgbspotcolor
F setfieldcalculationset		F spotcolorname
F setfigurealternative		F transparency
F setfigurecolorspace		T tables
F setfiguremask		T vfspecials
F setformat		T black
F setformsmethod		T blue

T green

T red

F startslant

T stopslant

**registrations** table

**tables** table

# bibtex (context)

<b>authorref</b>	function	<b>F flush</b>	
<b>authors</b>	table	<b>F nofregistered</b>	
<b>F concat</b>		<b>F process</b>	
<b>F inverted</b>		<b>F register</b>	
<b>F invertedshort</b>		<b>F registerplaced</b>	
<b>F normal</b>		<b>F reset</b>	
<b>F normalshort</b>		<b>F resolve</b>	
<b>F setsettings</b>		<b>load</b>	function
<b>F short</b>		<b>new</b>	function
<b>authoryearref</b>	function	<b>singularorplural</b>	function
<b>authoryearsref</b>	function	<b>statistics</b>	table
<b>convert</b>	function	<b>N nofbytes</b>	
<b>hacks</b>	table	<b>N nofdefinitions</b>	
<b>F add</b>		<b>N nofshortcuts</b>	
<b>F doifalreadyplaced</b>		<b>toxml</b>	function
<b>F filterall</b>			



# blobs (context)

<b>append</b>	function	<b>new</b>	function
<b>dimensions</b>	function	<b>pack</b>	function
<b>dispose</b>	function	<b>write</b>	function

# boolean (context)

`tocontext`    `function`  
`tonumber`    `function`

# buffers (context)

append	function	F define	
assign	function	F hassomecontent	
collectcontent	function	F next	
erase	function	F place	
exists	function	F reset	
getcontent	function	F save	
getlines	function	raw	function
parallel	table		

# builders (context)

<b>kernel</b>	<b>table</b>		F disable
	F hyphenation		F enable
	F kerning		F optimize
	F ligaturing		F setup
	F mlist_to_hlist		F split
<b>paragraphs</b>	<b>table</b>	F tag	
	T constructors	<b>vspacing</b>	<b>table</b>
	N attribute		F analyze
	F disable		D categories
	F enable		F collapsevbox
	F handler		T data
	T methods		D map
	F default		D skip
	F oneline		D snapmethods
	D names		F definesnapmethod
	D numbers		B fixed
	F register		F pagehandler
	F set		F setmap
F kepttogether			F setskip
F registertogether			F snapbox
T solutions			F tocategories
T splitters			F tocategory
F define			F vboxhandler

## cache (context)

ask	boolean	is_writable	function
base	string	loadcontent	function
collapsecontent	function	loaddata	function
configfiles	function	more	string
contentstate	function	relocate	boolean
defaults	table	savecontent	function
define	function	savadata	function
direct	boolean	setfirstwritablefile	function
force	boolean	setluanames	function
getfirstreadablefile	function	tree	string
getreadablepaths	function	treehash	function
getwritablepath	function	usedpaths	function
hashed	function		

## callback (basic tex)

<code>find</code>	function
<code>list</code>	function
<code>register</code>	overloaded function

# callbacks (context)

freeze	function	push	function
known	function	register	function
list	data table	report	function
pop	function	table	function

## catcodes (context)

<code>names</code>	data table
<code>numbers</code>	data table
<code>register</code>	function



# characters (context)

<b>activeoffset</b>	number	<b>is_mark</b>	data table
<b>adobename</b>	function	<b>is_spacing</b>	data table
<b>bidirectional</b>	data table	<b>lcchars</b>	data table
<b>blocks</b>	data table	<b>lccode</b>	function
<b>casemap</b>	table	<b>lccodes</b>	data table
<b>categories</b>	data table	<b>lettered</b>	function
<b>category</b>	function	<b>lower</b>	function
<b>categorytags</b>	data table	<b>makeactive</b>	function
<b>combined</b>	data table	<b>math</b>	table
<b>contextname</b>	function	<b>mathpairs</b>	data table
<b>data</b>	data table	<b>ranges</b>	data table
<b>decomposed</b>	data table	<b>registerentities</b>	function
<b>define</b>	function	<b>remap_hangul_syllable</b>	function
<b>description</b>	function	<b>remapentity</b>	function
<b>descriptions</b>	data table	<b>setcodes</b>	function
<b>directions</b>	data table	<b>shape</b>	function
<b>encodes</b>	data table	<b>shaped</b>	function
<b>entities</b>	data table	<b>shchars</b>	data table
<b>fallbacks</b>	data table	<b>shcodes</b>	data table
<b>filters</b>	data table	<b>specialchars</b>	data table
<b>flush</b>	function	<b>specials</b>	data table
<b>fromnumber</b>	function	<b>subscripts</b>	table
<b>fschars</b>	data table	<b>superscripts</b>	table
<b>fscodes</b>	data table	<b>synonyms</b>	data table
<b>getrange</b>	function	<b>tex</b>	table
<b>graphemes</b>	data table		
<b>hangul</b>	table		
		D accentmapping	
		F defineaccents	
		F toutf	
		<b>tonumber</b>	function
		<b>ucchars</b>	data table
		<b>uccode</b>	function
		<b>uccodes</b>	data table
		<b>unicodechar</b>	function
		<b>upper</b>	function
<b>initialize</b>	function		
<b>is_character</b>	data table		
<b>is_command</b>	data table		
<b>is_letter</b>	data table		

## chemicals (context)

<b>component</b>	function	<b>moleculeparser</b>	userdata
<b>define</b>	function	<b>start</b>	function
<b>format</b>	string	<b>stop</b>	function
<b>inline</b>	function	<b>structures</b>	number
<b>instance</b>	string	<b>undefine</b>	function
<b>molecule</b>	function		

## commands (context)

Alphabetic	function	collecthelp	function
Character	function	colorcomponents	function
Characters	function	consultfloat	function
MPd	function	copyfileto	function
MPh	function	copyposition	function
MPll	function	counttwopassdata	function
MPlr	function	currentcomponent	function
MPp	function	currentdate	function
MPplus	function	currentenvironment	function
MPpos	function	currentproduct	function
MPrest	function	currentproject	function
MPul	function	currentregime	function
MPur	function	dayname	function
MPw	function	defineattribute	function
MPx	function	definebibtexsession	function
MPxy	function	defineconversion	function
MPy	function	definefield	function
Romannumerals	function	definefieldset	function
abjadnodotnumerals	function	definefilefallback	function
abjadnumerals	function	definefilesynonym	function
addff	function	definefont_one	function
addfs	function	definefont_two	function
addlinklistelement	function	definefontcollection	function
addstructurecounter	function	defineintermediatecolor	function
allinputpaths	function	definelinkedlist	function
alphabetic	function	definemarking	function
analysefloatmethod	function	definemultitonecolor	function
applytochars	function	defineparallel	function
applytowords	function	defineprocesscolor	function
assignbuffer	function	definespotcolor	function
autofinishstructurelevels	function	definestructureblock	function
autonextspace	function	definestructurecounter	function
autonextstructurelevel	function	definestructureset	function
autosetups	function	definetransparency	function
autostarttext	function	definetwopasslist	function
autostoptext	function	defineviewerlayer	function
boolcase	function	defrostrandomseed	function
character	function	digits	function
characters	function	disableregime	function
checkcharactersinfont	function	doanalyzeframedbox	function
checkedconversion	function	doif	function
checkedpagefloat	function	doifblackelse	function
checktwopassdata	function	doifcommonelse	function
chineseallnumerals	function	doifdimenstringelse	function
chinesecapnumerals	function	doifdrawingblackelse	function
chinesenumerals	function	doifelse	function
cleanfontname	function	doifelsebuffer	function
clonefield	function	doifelsecurrentfontasfeature	function
clonefontcollection_one	function	doifelseintwopassdata	function
clonefontcollection_two	function	doifelsemarking	function
collectfloat	function	doifelseparallel	function

doifelsesavedfloat	function	forcequitjob	function
doifelsespaces	function	format	function
doifelsestructurecounter	function	formatcolor	function
doifelsevisualizer	function	formatgray	function
doiffielddcategoryelse	function	freezerandomseed	function
doiffielddelse	function	getbuffer	function
doiffielddsetelse	function	getbufferctxlua	function
doiffiledefinedelse	function	getbuffermkvi	function
doiffileexistelse	function	getdefaultfieldvalue	function
doiffirstcharelse	function	getfieldcategory	function
doifinputfileelse	function	getfirstcharacter	function
doifinsetelse	function	getfirsttwopassdata	function
doifleapyearelse	function	getfloatvariable	function
doiflocfileelse	function	getlasttwopassdata	function
doifnot	function	getmarking	function
doifnotstructurecounter	function	getprivateattribute	function
doifolderversionelse	function	getprivatechar	function
doifoverlappingelse	function	getrandomcounta	function
doifparentfileelse	function	getrandomcountb	function
doifpositionelse	function	getrandomseed	function
doifpositionsonsamepageelse	function	getreadfilename	function
doifpositionsonthispageelse	function	gettexbuffer	function
doifstructurecounter	function	gettwopassdata	function
doifurldefinedelse	function	gettwopassdatalist	function
doprocесstypescriptfile	function	geturl	function
doreshapeframedbox	function	grabbuffer	function
dostarttextfile	function	helpaction	function
dostoptextfile	function	helpreference	function
elapsedtime	function	hexstringtonumber	function
enablecolor	function	hour	function
enablecolorintents	function	hyphenatedlist	function
enablefontcolorschemas	function	hyphenatedurl	function
enableregime	function	D characters	
enabletransparency	function	N lefthyphenmin	
enhancelinkedlist	function	D mapping	
erasebuffer	function	N righthyphenmin	
featureattribute	function	F setcharacters	
feedback	function	incrementedstructurecounter	function
fetchallmarks	function	insertattachment	function
fetchonemark	function	insertcomment	function
fetchtwomarks	function	insertfield	function
filterreference	function	insertrenderingwindow	function
findtwopassdata	function	insertsoundclip	function
firstinlist	function	isleapyear	function
firststructurecounter	function	languagenumber	function
flushfloat	function	laststructurecounter	function
flushpostponedblocks	function	lchexnumber	function
fontchar	function	lchexnumbers	function
fontcollectionmessage	function	leapyear	function
fontlookupgetkey	function	loadctxpreplist	function
fontlookupgetkeyofindex	function	loadexamodes	function
fontlookupinitialize	function	loadfontgoodies	function
fontlookupnoffound	function	loadvisualizer	function
forceendjob	function	locatefilepath	function

locfilename	function	registerhelp	function
maxitemwidth	function	registeritemgroup	function
minute	function	registermaintextcolor	function
molecule	function	registerpostponedblock	function
month	function	registersoundclip	function
monthmnem	function	registerstructureprocessor	function
monthname	function	registertransparency	function
mpcolor	function	registerunit	function
mpoptions	function	relatemarking	function
namedstructureuservariable	function	removemissingcharacters	function
namedstructurevariable	function	replacemissingcharacters	function
nbfs	function	replacepospxywhd	function
nextparallel	function	resavefloat	function
nextstructurecounter	function	resetfontcollection	function
nofdays	function	resetfontfeature	function
nofitems	function	resetmarking	function
nofstackedfloats	function	resetmathitalics	function
number	function	resetnullfont	function
octnumber	function	resetparallel	function
octstringtonumber	function	resetstructurecounter	function
ordinal	function	resetstructureprocessor	function
overloadbookmark	function	resettimer	function
pdfrotation	function	restartstructurecounter	function
percentageof	function	restorecurrentattributes	function
placeparallel	function	restorestructurecounter	function
popfloat	function	romannumerals	function
popitaliccorrection	function	runbuffer	function
prepareMPvariable	function	savebuffer	function
preparebibtexsession	function	savecurrentattributes	function
preparedfile	function	savefloat	function
preparefontcollection	function	saveparallel	function
presetsymbollist	function	savestructureblock	function
presettabulate	function	savestructurecounter	function
prevstructurecounter	function	savetaggedtwopassdata	function
processbuffer	function	savetwopassdata	function
processedfile	function	second	function
processedfiles	function	selectstructureblock	function
processfile	function	setclosedocumentaction	function
processfilemany	function	setclosepageaction	function
processfilenone	function	setcolormodel	function
processfileonce	function	setfontfeature	function
pushfloat	function	setfontofid	function
pushitaliccorrection	function	setformat	function
rawcharacter	function	setformsmethod	function
rawdate	function	setmarking	function
referencepagestate	function	setmathalphabet	function
referencerealpage	function	setmathalternate	function
registerattachment	function	setmathattribute	function
registerbibtexentry	function	setmathitalics	function
registerbibtexfile	function	setmathstyle	function
registerbookmark	function	setopendocumentaction	function
registerbuttons	function	setopenpageaction	function
registercolor	function	setownstructurecounter	function
registercolorintent	function	setpagetransition	function

setrandomseed	function	structuretitle	function
setrastercolor	function	structureuservariable	function
setrealign	function	structurevariable	function
setreferencearguments	function	subff	function
setreferenceoperation	function	subfs	function
setstructureblockstate	function	synchronizemarking	function
setstructurecounter	function	taggedmathfunction	function
settagcombination	function	testcase	function
settagdescription	function	textime	function
settagdescriptionsymbol	function	transparencycomponents	function
settagfigure	function	triggereffect	function
settaghighlight	function	triggernegative	function
settagitemgroup	function	truefilename	function
settagproperty	function	typebuffer	function
settagsorting	function	typefile	function
settagsynonym	function	typestring	function
settagtablecell	function	uchexnumber	function
settagtabulatecell	function	uchexnumbers	function
setupbookmarks	function	unicodechar	function
setupcanvas	function	unit	function
setupexport	function	updatefilenames	function
setupfontexpansion	function	useMPlibrary	function
setupfontprotrusion	function	useanyfile	function
setupidentity	function	useclfile	function
setupitaliccorrection	function	usecolors	function
setxmpfile	function	usecomponent	function
showchardata	function	useenvironment	function
showfontparameters	function	usefile	function
showhyphenatedinlist	function	uselibrary	function
showstructurecounter	function	useluafile	function
splitfilename	function	usemodules	function
spotcolorname	function	usepath	function
spotcolorparent	function	useproduct	function
spotcolorvalue	function	useproject	function
startcomponent	function	usesubpath	function
startenvironment	function	usesymbols	function
startproduct	function	usetexfile	function
startproject	function	useurl	function
startregime	function	usexmlfile	function
starttag	function	usezipfile	function
starttext	function	utfchar	function
stopcomponent	function	weekday	function
stopenvironment	function	weekdayname	function
stopproduct	function	widthofstring	function
stopproject	function	writestatus	function
stopregime	function	x_table_cleanup	function
stoptag	function	x_table_construct	function
stoptext	function	x_table_create	function
structureautocatcodedget	function	x_table_flush	function
structurecatcodedget	function	x_table_init_construct	function
structurecountersubs	function	x_table_init_reflow_height	function
structurecountervalue	function	x_table_init_reflow_width	function
structuregivencatcodedget	function	x_table_next_row	function
structurenumber	function	x_table_reflow_height	function

<code>x_table_reflow_width</code>	function	<code>x_table_set_reflow_width</code>	function
<code>x_table_set_construct</code>	function	<code>year</code>	function
<code>x_table_set_reflow_height</code>	function		

## containers (context)

<code>cleanname</code>	function
<code>content</code>	function
<code>define</code>	function
<code>is_usable</code>	function

<code>is_valid</code>	function
<code>read</code>	function
<code>usecache</code>	boolean
<code>write</code>	function



## converters (context)

Alphabetic	function	leapyear	function
Character	function	maxchrs	function
Characters	function	minute	function
Romannumerals	function	month	function
abjadnodotnumerals	function	nofdays	function
abjadnumerals	function	number	function
alphabetic	function	octnumber	function
character	function	octstringtonumber	function
characters	function	ordinal	function
chineseallnumerals	function	rawcharacter	function
chinesecapnumerals	function	romannumerals	function
chinesenumerals	function	second	function
chr	function	sequences	data table
chrs	function	textime	function
convert	function	toabjad	function
define	function	tochinese	function
hexstringtonumber	function	toroman	function
hour	function	uchexnumber	function
isleapyear	function	uchexnumbers	function
lchexnumber	function	weekday	function
lchexnumbers	function	year	function

## coroutine (basic lua)

<code>coco</code>	boolean	<code>running</code>	function
<code>create</code>	function	<code>status</code>	function
<code>cstacksize</code>	function	<code>wrap</code>	function
<code>resume</code>	function	<code>yield</code>	function

## debug (basic lua)

<b>debug</b>	function
<b>getfenv</b>	function
<b>gethook</b>	function
<b>getinfo</b>	function
<b>getlocal</b>	function
<b>getmetatable</b>	function
<b>getregistry</b>	function

<b>getupvalue</b>	function
<b>setfenv</b>	function
<b>sethook</b>	function
<b>setlocal</b>	function
<b>setmetatable</b>	function
<b>setupvalue</b>	function
<b>traceback</b>	function

## dir (context)

<code>collectpattern</code>	function
<code>current</code>	function
<code>expandname</code>	function
<code>glob</code>	function
<code>globfiles</code>	function
<code>globpattern</code>	function

<code>ls</code>	function
<code>makedirs</code>	function
<code>mkdirs</code>	function
<code>pop</code>	function
<code>push</code>	function

# directives (context)

<b>data</b>	data table	<b>name</b>	string
<b>disable</b>	function	<b>register</b>	function
<b>enable</b>	function	<b>report</b>	function
<b>list</b>	function	<b>show</b>	function

# document (context)

arguments	data table	setargument	function
files	table	setdefaultargument	function
getargument	function	setfilename	function
getfilename	function		

## environment (context)

argument	function	luafile	function
arguments	data table	luafilechunk	function
engineflags	data table	originalarguments	data table
files	table	outputfilename	string
filesynonyms	data table	ownbin	string
homedir	string	ownname	string
initex	boolean	ownpath	string
initializearguments	function	rawarguments	data table
inputfilebarename	string	reconstructcommandline	function
inputfilename	string	setargument	function
inputfilesuffix	string	splitarguments	function
jobfilename	string	texfile	function
jobfilesuffix	string	texmfos	string
loadedluacode	function	texos	string
loadluafile	function	texroot	string

# epdf (extra tex)

<b>Annot</b>	function	<b>Object</b>	function
<b>Annots</b>	function	<b>PDFRectangle</b>	function
<b>Array</b>	function	<b>open</b>	function
<b>Dict</b>	function	<b>type</b>	function



# experiments (context)

data	data table	name	string
disable	function	register	function
enable	function	report	function
list	function	show	function

# figures (context)

<b>applyratio</b>	function	<b>hash</b>	function
<b>bases</b>	table	<b>identifiers</b>	data table
B enabled		<b>identify</b>	function
F find		<b>include</b>	function
T found		<b>includers</b>	data table
T list		<b>initialize</b>	function
F locate		<b>loaded</b>	data table
F use		<b>localpaths</b>	data table
T used		<b>mergegoodies</b>	function
<b>bitmapimage</b>	function	<b>nofprocessed</b>	number
<b>boxnumber</b>	number	<b>order</b>	data table
<b>cachepaths</b>	data table	<b>paths</b>	data table
<b>check</b>	function	<b>patterns</b>	data table
<b>checkers</b>	data table	<b>pop</b>	function
<b>converters</b>	data table	<b>preferquality</b>	boolean
<b>current</b>	function	<b>programs</b>	data table
<b>defaultdepth</b>	number	<b>push</b>	function
<b>defaultheight</b>	number	<b>registerpattern</b>	function
<b>defaultsearch</b>	boolean	<b>registerresource</b>	function
<b>defaultwidth</b>	number	<b>registersuffix</b>	function
<b>done</b>	function	<b>resources</b>	data table
<b>dummy</b>	function	<b>scale</b>	function
<b>exists</b>	data table	<b>setlookups</b>	function
<b>exists</b>	function	<b>setpaths</b>	function
<b>formats</b>	data table	<b>suffixes</b>	data table
<b>found</b>	data table	<b>tprint</b>	function
<b>get</b>	function	<b>used</b>	data table

## file (basic lua)

<code>addsuffix</code>	function	<code>joinpath</code>	function
<code>basename</code>	function	<code>loadchecksum</code>	function
<code>checksum</code>	function	<code>nameonly</code>	function
<code>collapsepath</code>	function	<code>nametotable</code>	function
<code>copy</code>	function	<code>needs Updating</code>	function
<code>dirname</code>	function	<code>readdata</code>	function
<code>expandname</code>	function	<code>removesuffix</code>	function
<code>extname</code>	function	<code>replacesuffix</code>	function
<code>is_qualified_path</code>	function	<code>robustname</code>	function
<code>is_readable</code>	function	<code>savechecksum</code>	function
<code>is_rootbased_path</code>	function	<code>savedata</code>	function
<code>is_writable</code>	function	<code>splitname</code>	function
<code>isreadable</code>	function	<code>splitpath</code>	function
<code>iswritable</code>	function	<code>strip</code>	function
<code>join</code>	function	<code>suffix</code>	function

# floats (context)

<code>analysemethod</code>	<code>function</code>	<code>nofstacked</code>	<code>function</code>
<code>checkedpagefloat</code>	<code>function</code>	<code>pop</code>	<code>function</code>
<code>collect</code>	<code>function</code>	<code>push</code>	<code>function</code>
<code>consult</code>	<code>function</code>	<code>resave</code>	<code>function</code>
<code>flush</code>	<code>function</code>	<code>save</code>	<code>function</code>
<code>getvariable</code>	<code>function</code>	<code>stacked</code>	<code>function</code>

## font (basic tex)

**current**    function  
**define**    function  
**each**       function  
**fonts**      table  
**frozen**     function  
**getfont**    function

**id**            function  
**max**           function  
**nextid**       function  
**read\_tfm**    function  
**read\_vf**     function  
**setfont**     function

## fontloader (extra tex)

<code>apply_afmfile</code>	<code>function</code>
<code>apply_featurefile</code>	<code>function</code>
<code>close</code>	<code>function</code>
<code>fields</code>	<code>function</code>
<code>fullinfo</code>	<code>function</code>

<code>info</code>	<code>function</code>
<code>open</code>	<code>function</code>
<code>to_table</code>	<code>function</code>
<code>totable</code>	<code>function</code>

# fonts (context)

## **analyzers**            table

- D initializers
- D methods
- F setstate
- B useunicodemarks

## **checkers**            table

- F missing

## **cid**                    table

- F getmap
- F loadfile

## **collections**        table

- F clone\_one
- F clone\_two
- F define
- T definitions
- F message
- F prepare
- F process
- F reset
- T vectors

## **constructors**        table

- F applymanipulators
- F assignmathparameters
- B autocleanup
- D cache
- F calculatyscale
- F checkedfeatures
- F checkedfilename
- F cleanupable
- F collectprocessors
- D designsizes
- D dontembed
- F enhanceparameters
- N factor
- F finalize
- F getfeatureaction
- F hashfeatures
- F hashinstance
- T hashmethods
  - F normal
  - F virtual
- F initializefeatures
- T keys
  - T character
    - S depth
    - S height
    - S italic
    - S width
  - T description
    - T boundingbox
    - S depth

- S height

- S width

- T parameters

- S ascender

- S descender

- S designsize

- T expansion

- S auto

- S shrink

- S step

- S stretch

- S extendfactor

- S factor

- S hfactor

- S mathsize

- T protrusion

- S auto

- S quad

- S scaledpoints

- S scriptpercentage

- S scriptscriptpercentage

- S size

- S slantfactor

- S slantperpoint

- T spacing

- S extra

- S shrink

- S stretch

- S width

- T synonyms

- S em

- S ex

- S extra\_space

- S extraspace

- S slant

- S space

- S space\_shrink

- S space\_stretch

- S spaceshrink

- S spacestretch

- S x\_height

- S units

- S vfactor

- S xheight

- T properties

- S autoitalicamount

- T cidinfo

- S embedding

- S encodingbytes

- S filename

- S finalized

S fontname		D cache	
S format		F is_known	
S fullname		D known	
S hasitalics		F load	
S hasmath		F make_unicode_vector	
S mathitalics		D math	
S mode		N version	
S name		<b>expansions</b>	data table
S noglyphnames		<b>formats</b>	data table
S nostackmath		<b>goodies</b>	table
S psname		T colorschemes	
S textitalics		F coloring	
S virtualized		T data	
D loadedfonts		F enable	
T mathactions		F getcompositions	
S namemode		T list	
F newfeatures		F compositions	
N privateoffset		F expansions	
F readanddefine		F featureset	
F registerfeature		F files	
B resolvevirtualtoo		F mathematics	
F scale		F protrusions	
F scaled		F solutions	
F setfactor		F typefaces	
F setname		F load	
N version		F prepare_features	
<b>current</b>	function	F register	
<b>currentid</b>	function	F registerpostprocessor	
<b>definers</b>	table	F report	
F addlookup		<b>handlers</b>	table
F analyze		T afm	
F applypostprocessors		B addkerns	
F current		B addligatures	
S defaultlookup		B addtexligatures	
F define		B autoprefixed	
F getspecification		D cache	
F loadfont		D features	
F makespecification		F load	
T methods		F setfeatures	
F install		B syncspace	
D variants		N version	
F read		T otf	
F register		F addfeature	
F registered		D cache	
F registersplit		T chainhandlers	
F resetnullfont		F normal	
F resolve		F verbose	
T resolvers		F collectlookups	
F file		F dataset	
F name		S defaultbasealternate	
F spec		S defaultnodealternate	
<b>definetypeface</b>	function	D enhancers	
<b>encodings</b>	table	D features	
T agl		F getalternate	



T glists		T category_to_placeholder	
F load		S ll	
F scriptandlanguage		S lm	
F setcontextchain		S lo	
F setdynamics		S lt	
F setfeatures		S lu	
T tables		S mc	
D baselines		S me	
D features		S mn	
D languages		S nd	
D scripts		S nl	
N version		S no	
T pfb		S pc	
T tfm		S pd	
D features		S pe	
F setfeatures		S pf	
T vf		S pi	
T combinations		S po	
F combine		S ps	
T combiner		S sc	
D commands		S sk	
F find		S sm	
D helpers		S so	
D math		F format	
D predefined		F onetimemessage	
D whatever		F register	
<b>hashes</b>	<b>table</b>	F reportdefinedfonts	
D characters		F reportusedfeatures	
D csnames		<b>mappings</b>	<b>table</b>
D descriptions		F addtounicode	
T dynamics		F fromunicode16	
D identifiers		F loadfile	
D italics		F loadline	
D marks		F loadlumtable	
D parameters		F makenameparser	
T processes		F reset	
D properties		F tounicode16	
D quads		F tounicode16sequence	
T setdynamics		<b>names</b>	<b>table</b>
D xheights		S basename	
<b>helpers</b>	<b>table</b>	B be_clever	
F addprivate		D cache	
F dimenfactor		F cleanfilename	
F getdigitwidth		F cleanname	
F getparameters		F collect	
F getprivatenode		F collectfiles	
F hasprivate		F collectspec	
F nametoslot		T data	
F setdigitwidth		B enabled	
<b>iterators</b>	<b>table</b>	F exists	
F characters		T filters	
F descriptions		F afm	
F glyphs		F dfont	
<b>loggers</b>	<b>table</b>	T list	

T names  
 F otf  
 T paths  
 F pfb  
 F ttc  
 F ttf  
 S fontconfigfile  
 F getfilename  
 F getlookupkey  
 F getlookups  
 F getpaths  
 F identify  
 F is\_permitted  
 F list  
 F load  
 B loaded  
 F lookup  
 F noflookups  
 S osfontdirvariable  
 F readdata  
 F register  
 F registered  
 F resolve  
 F resolvedspecification  
 F resolvespec  
 B saved  
 F specification  
 D specifications  
 F splitspec  
 N version  
 F writedata  
**protrusions**      data table

**readers**              table  
     F afm  
     F check\_lua  
     F check\_tfm  
     F dfont  
     F lua  
     F opentype  
     F otf  
     F pfb  
     D sequence  
     F tfm  
     F ttc  
     F ttf  
**specifiers**            table  
     D contextmerged  
     F contextnumber  
     D contextnumbers  
     D contextsetups  
     F contexttostring  
     F mergecontext  
     F presetcontext  
     F registercontext  
     F showcontext  
     F splitcontext  
     D synonyms  
     D variants  
**symbols**              table  
     F uselibrary  
**tables**                table  
**tracers**              table  
**typefaces**            data table

## gzip (extra lua)

`close` function  
`lines` function  
`open` function

## img (basic tex)

<code>boxes</code>	<code>function</code>
<code>checksize</code>	<code>function</code>
<code>clone</code>	<code>function</code>
<code>copy</code>	<code>function</code>
<code>immediatwrite</code>	<code>function</code>
<code>keys</code>	<code>function</code>
<code>new</code>	<code>function</code>
<code>node</code>	<code>function</code>

<code>ofindex</code>	<code>function</code>
<code>package</code>	<code>function</code>
<code>print</code>	<code>function</code>
<code>scan</code>	<code>function</code>
<code>serialize</code>	<code>function</code>
<code>totable</code>	<code>function</code>
<code>types</code>	<code>function</code>
<code>write</code>	<code>function</code>

# interactions (context)

## **attachments** table

F insert  
F register

## **fields** table

F clone  
F define  
F defineset  
F insert

## **general** table

F getidentity  
F setupidentity

## **help** table

F collect  
F reference  
F register

## **javascripts** table

F addtopreamble  
F code  
D codes  
F flushpreambles  
D functions  
D preambles

F setpreamble

F storecode

F storepreamble

F usepreamblenow

F usescripts

## **linkedlists** table

## **pages** table

F setpagetransition

F setupcanvas

## **references** table

F setcloseddocument

F setclosepage

F setopendocument

F setopenpage

## **renderings** table

F register

F rendering

F var

## **soundclips** table

F insert

F register

# interfaces (context)

<b>addvalidkeys</b>	function	<b>F define</b>	
<b>cachedsetups</b>	data table	<b>F list</b>	
<b>cachesetup</b>	function	<b>setconstant</b>	function
<b>complete</b>	data table	<b>setelement</b>	function
<b>constants</b>	data table	<b>setformat</b>	function
<b>definecommand</b>	function	<b>setmessage</b>	function
<b>doifelsemessage</b>	function	<b>setmessages</b>	function
<b>elements</b>	data table	<b>settranslation</b>	function
<b>formats</b>	data table	<b>setuserinterface</b>	function
<b>getcheckedparameters</b>	function	<b>setvalidkeys</b>	function
<b>getmessage</b>	function	<b>setvariable</b>	function
<b>hashedsetups</b>	data table	<b>showmessage</b>	function
<b>interfacedcommand</b>	function	<b>syntax</b>	data table
<b>interfaces</b>	table	<b>tolist</b>	function
<b>invalidkey</b>	function	<b>translations</b>	data table
<b>is_command</b>	function	<b>variables</b>	data table
<b>namespaces</b>	table		

# io (basic lua)

ask	function	out	table
bytes	function	F inhibit	
characters	function	D modes	
checkopeners	function	F permit	
close	function	output	function
exists	function	pathseparator	string
fileseparator	string	popen	overloaded function
finalizeopeners	function	read	function
flush	function	readnumber	function
inp	table	readstring	function
F inhibit		registeropener	function
D modes		savedata	function
F permit		size	function
input	function	stderr	userdata
lines	function	stdin	userdata
loaddata	function	stdout	userdata
noflines	function	tmpfile	function
open	function	type	function
open_ro	function	write	function

# job (context)

<b>comment</b>	function
<b>disablesave</b>	function
<b>files</b>	table
D collected	
F context	
B forcerun	
F run	
D tobesaved	
<b>initialize</b>	function
<b>load</b>	function
<b>loadother</b>	function
<b>objects</b>	table
D collected	
F doifelse	
F get	
F number	
F page	
F save	
F set	
D tobesaved	
<b>pack</b>	boolean
<b>passes</b>	table
F check	
D collected	
F count	
F define	
F find	
F first	
F get	
F getcollected	
F getdata	
F getfield	
F gettobesaved	
F inlist	
F last	
F list	
F save	
F savetagged	
D tobesaved	

<b>positions</b>	table
D collected	
F copy	
F depth	
F extra	
F height	
F lowerleft	
F lowerright	
F onsamepage	
F overlapping	
F page	
F position	
F replace	
F setall	
F setdim	
F setraw	
D tobesaved	
F upperleft	
F upperright	
F v	
F width	
F x	
F xy	
F y	
<b>register</b>	function
<b>save</b>	function
<b>structure</b>	table
D collected	
T tobesaved	
T branches	
S name	
S type	
<b>variables</b>	table
D checksums	
D collected	
F save	
D tobesaved	
<b>version</b>	number



# lang (basic tex)

`clean` function  
`clear_hyphenation` function  
`clear_patterns` function  
`exceptions` function  
`hyphenate` function  
`hyphenation` function  
`id` function

`new` function  
`patterns` function  
`postexhyphenchar` function  
`posthyphenchar` function  
`preexhyphenchar` function  
`prehyphenchar` function

# languages (context)

<b>associate</b>	function	<b>numbers</b>	data table
<b>associated</b>	data table	<b>posthyphenchar</b>	function
<b>association</b>	function	<b>prehyphenchar</b>	function
<b>counters</b>	data table	<b>registered</b>	data table
<b>current</b>	function	<b>righthyphenmin</b>	function
<b>data</b>	data table	<b>setdirty</b>	function
<b>define</b>	function	<b>synonym</b>	function
<b>exceptions</b>	function	<b>version</b>	number
<b>getnumber</b>	function	<b>words</b>	table
<b>hyphenate</b>	function		
<b>installed</b>	function	F check	
<b>labels</b>	table	T data	
F define		F disable	
F split		F enable	
<b>lefthyphenmin</b>	function	T enablers	
<b>loadable</b>	function	B enables	
<b>loadwords</b>	function	F found	
<b>logger</b>	table	F load	
F report		T methods	
		N threshold	

# layouts (context)

```
status table
  F isleftpage
  F leftorrightpagection
```

## lfs (extra lua)

<b>attributes</b>	function	<b>mkdir</b>	function
<b>chdir</b>	function	<b>readlink</b>	function
<b>currentdir</b>	function	<b>rmdir</b>	function
<b>dir</b>	function	<b>setmode</b>	function
<b>isdir</b>	overloaded function	<b>shortname</b>	function
<b>isfile</b>	function	<b>symlinkattributes</b>	function
<b>lock</b>	function	<b>touch</b>	function
<b>lock_dir</b>	function	<b>unlock</b>	function

# libraries (context)

<code>basiclua</code>	data table	<code>extralua</code>	data table
<code>basictex</code>	data table	<code>extratex</code>	data table
<code>builtin</code>	data table	<code>globals</code>	data table

## lmx (context)

<code>convert</code>	function	<code>pv</code>	function
<code>escape</code>	function	<code>reset</code>	function
<code>get</code>	function	<code>result</code>	function
<code>htmfile</code>	function	<code>set</code>	function
<code>include</code>	function	<code>show</code>	function
<code>lmxfile</code>	function	<code>showdebuginfo</code>	function
<code>loadedfile</code>	function	<code>showerror</code>	function
<code>make</code>	function	<code>tv</code>	function
<code>new</code>	function	<code>type</code>	function
<code>overloaderror</code>	function	<code>urlescape</code>	function
<code>popupfile</code>	function	<code>variable</code>	function
<code>print</code>	function	<code>variables</code>	data table

# logs (context)

<b>application</b>	function	<b>setmessenger</b>	function
<b>categories</b>	function	<b>setprogram</b>	function
<b>direct</b>	function	<b>settarget</b>	function
<b>disable</b>	function	<b>settranslations</b>	function
<b>enable</b>	function	<b>show</b>	function
<b>extendbanner</b>	function	<b>show_close</b>	function
<b>flush</b>	function	<b>show_load</b>	function
<b>help</b>	function	<b>show_open</b>	function
<b>messenger</b>	function	<b>simple</b>	function
<b>new</b>	function	<b>simpleline</b>	function
<b>newline</b>	function	<b>simplelines</b>	function
<b>poptarget</b>	function	<b>start_page_number</b>	function
<b>pushtarget</b>	function	<b>status</b>	function
<b>report</b>	function	<b>stop_page_number</b>	function
<b>report_job_stat</b>	function	<b>subdirect</b>	function
<b>reportbanner</b>	function	<b>subreport</b>	function
<b>reporter</b>	function	<b>system</b>	function
<b>reportline</b>	function	<b>texerrormessage</b>	function
<b>reportlines</b>	function	<b>writer</b>	function
<b>setformats</b>	function		

# lpdf (context)

action	function	id	function
adddocumentcolorspace	function	injectxmpinfo	function
adddocumenttextgstate	function	insertxmpinfo	function
adddocumentpattern	function	javascript	function
adddocumentshade	function	launch	function
addtocatalog	function	layerreference	function
addtoinfo	function	limited	function
addtonames	function	linearshade	function
addtopageattributes	function	link	function
addtopageresources	function	null	function
addtopagesattributes	function	number	function
addxmpinfo	function	pagedestination	function
array	function	pagereference	function
boolean	function	pdfcolor	function
checkedkey	function	pdftimestamp	function
checkedvalue	function	protectresources	boolean
circularshade	function	reference	function
cmykcode	function	registerannotation	function
collectedresources	function	registerdocumentfinalizer	function
color	function	registerpagefinalizer	function
colorspace	function	reserveannotation	function
colorspec	function	reserveobject	function
colorvalue	function	rgbcode	function
colorvalues	function	rotationcm	function
constant	function	shareobject	function
delayedobject	function	shareobjectreference	function
dictionary	function	spotcode	function
epdf	table	stream	function
F load		string	function
finalizedocument	function	timestamp	function
finalizepage	function	toeight	function
finishtransparencycode	function	tosixteen	function
flushobject	function	transparency	function
flushstreamfileobject	function	transparencycode	function
flushstreamobject	function	transparencyvalue	function
formats	data table	unicode	function
graycode	function	verbose	function



# lpeg (basic lua)

<b>C</b>	function	<b>endstripper</b>	function
<b>Carg</b>	function	<b>firstofsplit</b>	function
<b>Cb</b>	function	<b>frontstripper</b>	function
<b>Cc</b>	function	<b>is_lpeg</b>	function
<b>Cf</b>	function	<b>keeper</b>	function
<b>Cg</b>	function	<b>locale</b>	function
<b>Cmt</b>	function	<b>match</b>	function
<b>Cp</b>	function	<b>oneof</b>	function
<b>Cs</b>	function	<b>patterns</b>	data table
<b>Ct</b>	function	<b>print</b>	function
<b>P</b>	function	<b>replacer</b>	function
<b>R</b>	function	<b>secondofsplit</b>	function
<b>S</b>	function	<b>span</b>	function
<b>UP</b>	function	<b>split</b>	function
<b>UR</b>	function	<b>splitat</b>	function
<b>US</b>	function	<b>splitter</b>	function
<b>V</b>	function	<b>stripper</b>	function
<b>anywhere</b>	function	<b>tsplitat</b>	function
<b>append</b>	function	<b>tsplitter</b>	function
<b>balancer</b>	function	<b>type</b>	function
<b>checkedsplit</b>	function	<b>utfchartabletopattern</b>	function
<b>count</b>	function	<b>version</b>	function
<b>counter</b>	function		

# ltn12 (extra lua)

<b>BLOCKSIZE</b>	number	F simplify
<b>filter</b>	table	F table
	F chain	<b>source</b> table
	F cycle	F cat
<b>pump</b>	table	F chain
	F all	F empty
	F step	F error
<b>sink</b>	table	F file
	F chain	F rewind
	F error	F simplify
	F file	F string
	F null	

## lua (basic tex)

<b>bytecode</b>	<b>table</b>	<b>messages</b>	data table
<b>bytedata</b>	data table	<b>name</b>	<b>table</b>
<b>bytdone</b>	table	<b>numbers</b>	data table
<b>collectgarbage</b>	function	<b>registercode</b>	function
<b>delay</b>	function	<b>registeredcodes</b>	function
<b>finalize</b>	function	<b>registerfinalizer</b>	function
<b>firstbytecode</b>	number	<b>registername</b>	function
<b>flush</b>	function	<b>setbytecode</b>	<b>function</b>
<b>flushdelayed</b>	function	<b>setluaname</b>	<b>function</b>
<b>getbytecode</b>	<b>function</b>	<b>startupfile</b>	string
<b>getluaname</b>	<b>function</b>	<b>version</b>	string
<b>lastbytecode</b>	number		

# luatex (context)

<code>cleanuptempfiles</code>	function	<code>showjobstat</code>	function
<code>registerstartactions</code>	function	<code>showtexstat</code>	function
<code>registerstopactions</code>	function	<code>starttime</code>	number
<code>registertempfile</code>	function		

# lxml (context)

<code>addindex</code>	function	<code>last</code>	function
<code>all</code>	function	<code>load</code>	function
<code>applyfunction</code>	function	<code>loadbuffer</code>	function
<code>att</code>	function	<code>loaddata</code>	function
<code>attribute</code>	function	<code>loaded</code>	table
<code>chainattribute</code>	function	<code>loadregistered</code>	function
<code>checkindex</code>	function	<code>main</code>	function
<code>collected</code>	function	<code>match</code>	function
<code>command</code>	function	<code>name</code>	function
<code>concat</code>	function	<code>namespace</code>	function
<code>concatrange</code>	function	<code>nonspace</code>	function
<code>content</code>	function	<code>pos</code>	function
<code>context</code>	function	<code>position</code>	function
<code>convert</code>	function	<code>raw</code>	function
<code>count</code>	function	<code>rawroot</code>	function
<code>delete</code>	function	<code>register</code>	function
<code>direct</code>	function	<code>registerentity</code>	function
<code>directives</code>	table	<code>removesetup</code>	function
F after		<code>resetcdata</code>	function
F before		<code>resetsetups</code>	function
F handle		<code>resolvedentity</code>	function
F load		<code>root</code>	function
F setup		<code>serialize</code>	function
<code>displayverbatim</code>	function	<code>setaction</code>	function
<code>doif</code>	function	<code>setcdata</code>	function
<code>doifelse</code>	function	<code>setcommandtonone</code>	function
<code>doifelsetext</code>	function	<code>setcommandtotext</code>	function
<code>doifnot</code>	function	<code>setsetup</code>	function
<code>doifnottext</code>	function	<code>snippet</code>	function
<code>doiftext</code>	function	<code>sorters</code>	table
<code>element</code>	function	F add	
<code>elements</code>	function	F compare	
<code>entities</code>	data table	F flush	
<code>filter</code>	function	F reset	
<code>filterlist</code>	function	F show	
<code>first</code>	function	F sort	
<code>flush</code>	function	<code>splitid</code>	function
<code>flushlinewise</code>	function	<code>startraw</code>	function
<code>flushsetups</code>	function	<code>stopraw</code>	function
<code>flushspacewise</code>	function	<code>store</code>	function
<code>get_id</code>	function	<code>strip</code>	function
<code>getid</code>	function	<code>stripped</code>	function
<code>getindex</code>	function	<code>tag</code>	function
<code>id</code>	function	<code>text</code>	function
<code>idsplitter</code>	userdata	<code>tofile</code>	function
<code>include</code>	function	<code>toparameters</code>	function
<code>index</code>	function	<code>toverbatim</code>	function
<code>info</code>	function	<code>verbatim</code>	function
<code>inlineverbatim</code>	function	<code>withindex</code>	function
<code>installsetup</code>	function	<code>xmltexhandler</code>	data table

## math (basic lua)

<b>abs</b>	function	<b>max</b>	function
<b>acos</b>	function	<b>min</b>	function
<b>asin</b>	function	<b>mod</b>	function
<b>atan</b>	function	<b>modf</b>	function
<b>atan2</b>	function	<b>odd</b>	function
<b>ceil</b>	function	<b>pi</b>	number
<b>cos</b>	function	<b>pow</b>	function
<b>cosd</b>	function	<b>rad</b>	function
<b>cosh</b>	function	<b>random</b>	function
<b>deg</b>	function	<b>randomseed</b>	function
<b>div</b>	function	<b>round</b>	function
<b>even</b>	function	<b>setrandomseedi</b>	function
<b>exp</b>	function	<b>sin</b>	function
<b>floor</b>	function	<b>sind</b>	function
<b>fmod</b>	function	<b>sinh</b>	function
<b>frexp</b>	function	<b>sqrt</b>	function
<b>huge</b>	number	<b>tan</b>	function
<b>ldexp</b>	function	<b>tand</b>	function
<b>log</b>	function	<b>tanh</b>	function
<b>log10</b>	function		

# mathematics (context)

<b>addfallbacks</b>	function	<b>overloadparameters</b>	function
<b>alphabets</b>	data table	<b>privatebase</b>	number
<b>big</b>	function	<b>remapalphabets</b>	function
<b>boldmap</b>	table	<b>renderings</b>	table
<b>categories</b>	table	D mappings	
D functions		D numbers	
<b>checkaccentbaseheight</b>	function	D sets	
<b>checkprivateparameters</b>	function	<b>renderset</b>	function
<b>classes</b>	data table	<b>resetitalics</b>	function
<b>codes</b>	data table	<b>scaleparameters</b>	function
<b>define</b>	function	<b>setalternate</b>	function
<b>dimensions</b>	function	<b>setitalics</b>	function
<b>extrabase</b>	number	<b>syncboth</b>	function
<b>extras</b>	table	<b>syncname</b>	function
F add		<b>syncstyle</b>	function
F copy		<b>toname</b>	function
<b>families</b>	data table	<b>tostyle</b>	function
<b>gaps</b>	table	<b>utfmathclass</b>	function
<b>getboth</b>	function	<b>utfmathcommand</b>	function
<b>getstyle</b>	function	<b>utfmathfiller</b>	function
<b>initializeparameters</b>	function	<b>utfmathstretch</b>	function
<b>makefont</b>	function		

# md5 (extra lua)

HEX	function	exor	function
crypt	function	hex	function
dec	function	sum	function
decrypt	function	sumhexa	function



# metapost (context)

<b>analyzeplugins</b>	function	<b>makempy</b>	table
<b>checkformat</b>	function	N nofconverted	
<b>checktexts</b>	function	F processgraphics	
<b>colorinitializer</b>	function	<b>metafun</b>	table
<b>convert</b>	function	F interpolate	
<b>defaultformat</b>	string	F topath	
<b>directrun</b>	function	<b>method</b>	number
<b>edefsxsy</b>	function	<b>mptopdf</b>	table
<b>escaped</b>	function	F convertmpstopdf	
<b>exectime</b>	table	N nofconverted	
<b>filterclippath</b>	function	<b>multipass</b>	boolean
<b>finder</b>	function	<b>n</b>	number
<b>flush</b>	function	<b>optimize</b>	boolean
<b>flushers</b>	table	<b>parse</b>	function
T pdf		<b>pdfliterals</b>	function
F comment		<b>pluginactions</b>	function
F flushfigure		<b>process</b>	function
F startfigure		<b>processplugins</b>	function
F stopfigure		<b>reducetogray</b>	boolean
F textfigure		<b>reporterror</b>	function
<b>flushliteral</b>	function	<b>reset</b>	function
<b>flushnormalpath</b>	function	<b>resetlastlog</b>	function
<b>flushreset</b>	function	<b>resetplugins</b>	function
<b>format</b>	function	<b>resettexttexts</b>	function
<b>formatnumber</b>	function	<b>setoutercolor</b>	function
<b>getclippath</b>	function	<b>settext</b>	function
<b>gettext</b>	function	<b>showlog</b>	boolean
<b>graphic</b>	function	<b>tex</b>	table
<b>graphic_base_pass</b>	function	F get	
<b>graphic_extra_pass</b>	function	F reset	
<b>intermediate</b>	table	F set	
T actions		<b>texerrors</b>	boolean
F makempy		<b>texttextsdata</b>	function
B needed		<b>theclippath</b>	function
<b>lastlog</b>	string	<b>totable</b>	function
<b>load</b>	function	<b>unload</b>	function

## mime (extra lua)

**b64**           function  
**decode**       function  
**decodet**      table  
    F base64  
    F quoted-printable  
**dot**           function  
**encode**       function  
**encodet**      table  
    F base64  
    F quoted-printable  
**eol**           function  
**normalize**    function

**qp**            function  
**qpwrp**        function  
**stuff**        function  
**unb64**        function  
**unqp**         function  
**wrap**         function  
**wrapt**        table  
    F base64  
    F default  
    F quoted-printable  
    F text  
**wrp**           function

# mplib (extra tex)

fields	function	pen_info	function
new	function	version	function

# noads (context)

handlers	table
F check	
F collapse	
F families	
F italics	
F relocate	
F render	
F resize	
F respace	
F tags	
F unscript	

F variants
process function
processors table
T collapse
F mlist_to_hlist
T relocate
T render
T resize
T respace
T unscript

## node (basic tex)

<code>copy</code>	<code>function</code>	<code>ligaturing</code>	<code>function</code>
<code>copy_list</code>	<code>function</code>	<code>mlist_to_hlist</code>	<code>function</code>
<code>count</code>	<code>function</code>	<code>new</code>	<code>function</code>
<code>current_attr</code>	<code>function</code>	<code>next</code>	<code>function</code>
<code>dimensions</code>	<code>function</code>	<code>prev</code>	<code>function</code>
<code>do_ligature_n</code>	<code>function</code>	<code>protect_glyphs</code>	<code>function</code>
<code>family_font</code>	<code>function</code>	<code>protrusion_skippable</code>	<code>function</code>
<code>fields</code>	<code>function</code>	<code>remove</code>	<code>function</code>
<code>first_character</code>	<code>function</code>	<code>set_attribute</code>	<code>function</code>
<code>first_glyph</code>	<code>function</code>	<code>slide</code>	<code>function</code>
<code>flush_list</code>	<code>function</code>	<code>subtype</code>	<code>function</code>
<code>free</code>	<code>function</code>	<code>tail</code>	<code>function</code>
<code>has_attribute</code>	<code>function</code>	<code>traverse</code>	<code>function</code>
<code>has_field</code>	<code>function</code>	<code>traverse_id</code>	<code>function</code>
<code>hpack</code>	<code>function</code>	<code>type</code>	<code>function</code>
<code>id</code>	<code>function</code>	<code>types</code>	<code>function</code>
<code>insert_after</code>	<code>function</code>	<code>unprotect_glyphs</code>	<code>function</code>
<code>insert_before</code>	<code>function</code>	<code>unset_attribute</code>	<code>function</code>
<code>is_node</code>	<code>function</code>	<code>usedlist</code>	<code>function</code>
<code>kerning</code>	<code>function</code>	<code>vpack</code>	<code>function</code>
<code>last_node</code>	<code>function</code>	<code>whatsits</code>	<code>function</code>
<code>length</code>	<code>function</code>	<code>write</code>	<code>function</code>

# nodes (context)

<b>after</b>	function	F setkern	
<b>aligned</b>	function	F setmark	
<b>astable</b>	function	F setpair	
<b>before</b>	function	<b>installattributehandler</b>	function
<b>builders</b>	table	<b>is_display_math</b>	function
F buildpage_filter		<b>is_mirrored</b>	data table
F vpack_filter		<b>is_rotated</b>	data table
<b>codes</b>	data table	<b>kerncodes</b>	data table
<b>concat</b>	function	<b>leftmarginwidth</b>	function
<b>count</b>	function	<b>lines</b>	table
<b>delete</b>	function	T boxed	
<b>destinations</b>	table	F register	
N attribute		F setup	
T done		F stage_one	
F handler		F stage_two	
T stack		F stage_zero	
<b>dimensionfields</b>	data table	D data	
<b>dir_is_pop</b>	data table	F finalize	
<b>dir_negation</b>	data table	F number	
<b>fasthpack</b>	function	N scratchbox	
<b>fields</b>	function	<b>link</b>	function
<b>fillcodes</b>	data table	<b>list</b>	function
<b>firstcharacter</b>	function	<b>listablefields</b>	data table
<b>firstcharinbox</b>	function	<b>listcodes</b>	data table
<b>firstglyph</b>	function	<b>listtoutf</b>	function
<b>getattribute</b>	function	<b>load</b>	function
<b>gluecodes</b>	data table	<b>locate</b>	function
<b>glyphcodes</b>	data table	<b>mathcodes</b>	data table
<b>glyphdir_is_equal</b>	data table	<b>noadcodes</b>	data table
<b>glyphdir_is_opposite</b>	data table	<b>nodecodes</b>	data table
<b>glyphdir_is_orthogonal</b>	data table	<b>packlist</b>	function
<b>handlers</b>	table	<b>pardir_is_equal</b>	data table
F accessibility		<b>pardir_is_opposite</b>	data table
F backgrounds		<b>pardir_is_parallel</b>	data table
F characters		<b>partextdir_is_equal</b>	data table
F checkforleaks		<b>penaltycodes</b>	data table
F checkglyphs		<b>pool</b>	table
F cleanuppage		F baselineskip	
F export		F cleanup	
F finalize		F disc	
F graphicvadjust		F fontkern	
F migrate		F glue	
F protectglyphs		F gluespec	
F stripping		F glyph	
F unprotectglyphs		F kern	
<b>has_attribute</b>	function	F latelua	
<b>idstousing</b>	function	F leftmarginkern	
<b>ignorablefields</b>	data table	F leftskip	
<b>injections</b>	table	F lineskip	
F handler		F noad	
F setcursive		F pdfannotation	

F pdfdestination		setattributes	function
F pdfdirect		setunsetattributes	function
F pdfliteral		shifts	table
F pdfrestore		D data	
F pdfsave		F define	
F pdfsetmatrix		F enable	
F penalty		F handler	
F register		show	function
F rightmarginkern		showboxes	function
F rightskip		showcodes	function
F rule		showlist	function
F shrink		showsimplelist	function
F special		skipcodes	data table
F stretch		somepenalty	function
F temp		somespace	function
F textdir		stripping	table
F usage		F enable	
T userids		T glyphs	
N margins.inline		striprange	function
N splitters.one		tasks	table
N splitters.two		F actions	
F userlist		F appendaction	
F usernumber		F disableaction	
F userstring		F disablegroup	
F usertokens		F enableaction	
F zeroglue		F enablegroup	
print	function	F freeze	
processors	table	F freezegroup	
B enabled		F new	
F hpack_filter		F prependaction	
F post_linebreak_filter		F removeaction	
F pre_linebreak_filter		F restart	
F tracer		F showactions	
processwords	function	F table	
reference	function	textdir_is_equal	data table
references	table	textdir_is_is	data table
N attribute		textdir_is_opposite	data table
T done		textdir_is_parallel	data table
F handler		tonodes	function
T stack		tosequence	function
remove	function	totable	function
repackhlist	function	toutf	function
replace	function	tracers	table
report	function	T characters	
rightmarginwidth	function	F collect	
rules	table	F equal	
D data		F indices	
F define		F start	
F enable		F string	
F handler		F unicodes	
save	function	T colors	
serialize	function	F reset	
serializebox	function	F set	
setattribute	function	F fontchar	

F start	F reset	
T steppers	F start	
F check	F stop	
F codes	F stop	
F features	unsetattribute	function
F glyphs	unsetattributes	function
F message	visualizebox	function
F messages	whatcodes	data table
F nofsteps	whatsitcodes	data table
F register	writable_spec	function



## number (context)

	function		
basepoints	function	tociceros	function
bit	function	todidots	function
bits	function	todimen	function
clearbit	function	toevenhex	function
dimenfactors	data table	toinches	function
hasbit	function	tomillimeters	function
maxdimen	number	tonewciceros	function
nopts	function	tonewdidots	function
percent	function	tonumberf	function
points	function	tonumberg	function
pts	function	topicas	function
setbit	function	topoints	function
tobasepoints	function	toscaled	function
tobitstring	function	toscaledpoints	function
tocentimeters	function	toset	function

## os (basic lua)

<code>__getenv__</code>	function	<code>rename</code>	function
<code>__setenv__</code>	function	<code>resolvers</code>	table
<code>binsuffix</code>	string	<code>resultof</code>	function
<code>clock</code>	function	<code>runtime</code>	function
<code>date</code>	function	<code>selfdir</code>	string
<code>difftime</code>	function	<code>setenv</code>	overloaded function
<code>env</code>	data table	<code>setlocale</code>	overloaded function
<code>exec</code>	overloaded function	<code>sleep</code>	function
<code>execute</code>	overloaded function	<code>spawn</code>	overloaded function
<code>exit</code>	function	<code>time</code>	function
<code>getenv</code>	overloaded function	<code>times</code>	function
<code>gettimeofday</code>	function	<code>timezone</code>	function
<code>launch</code>	function	<code>tmpdir</code>	function
<code>libsuffix</code>	string	<code>tmpname</code>	function
<code>name</code>	string	<code>type</code>	string
<code>platform</code>	string	<code>uname</code>	function
<code>remove</code>	function	<code>uuid</code>	function

## package (basic lua)

<code>appendtolibpath</code>	function	<code>loaders</code>	table
<code>clibpaths</code>	function	<code>loadlib</code>	function
<code>config</code>	string	<code>path</code>	string
<code>cpath</code>	string	<code>preload</code>	table
<code>libpaths</code>	function	<code>prependtolibpath</code>	function
<code>loaded</code>	table	<code>seeall</code>	function

## pdf (basic tex)

<code>immediateobj</code>	<code>function</code>
<code>mapfile</code>	<code>function</code>
<code>mapline</code>	<code>function</code>
<code>maxobjnum</code>	<code>function</code>
<code>obj</code>	<code>function</code>
<code>objtype</code>	<code>function</code>
<code>pageattributes</code>	<code>string</code>
<code>pageref</code>	<code>function</code>

<code>pageresources</code>	<code>string</code>
<code>pagesattributes</code>	<code>string</code>
<code>pdfmapfile</code>	<code>function</code>
<code>pdfmapline</code>	<code>function</code>
<code>print</code>	<code>function</code>
<code>refobj</code>	<code>function</code>
<code>registerannot</code>	<code>function</code>
<code>reserveobj</code>	<code>function</code>

# physics (context)

units	table	S	Hz
T	tables	S	Litre
T	shortcuts	S	Metre
T	operators	S	W
S	*	S	b
S	.	S	g
S	/	S	h
S	:	S	hz
T	prefixes	S	l
S	E	S	lx
S	G	S	m
S	M	S	n
S	P	S	s
S	T	S	t
S	Y	S	u
S	Z	S	v
S	a	T	units
S	c	T	operators
S	d	S	OutOf
S	da	S	Per
S	f	S	Solidus
S	h	S	Times
S	k	T	packaged
S	m	S	Micron
S	n	T	prefixes
S	p	S	Atto
S	u	S	Centi
S	y	S	Deca
S	z	S	Deci
T	suffixes	S	Exa
S	+1	S	Exbi
S	+2	S	Femto
S	+3	S	Gibi
S	-1	S	Giga
S	-2	S	Hecto
S	-3	S	Kibi
S	1	S	Kilo
S	2	S	Mebi
S	3	S	Mega
S	^+1	S	Micro
S	^+2	S	Milli
S	^+3	S	Nano
S	^-1	S	Pebi
S	^-2	S	Peta
S	^-3	S	Pico
S	^1	S	Root
S	^2	S	Tebi
S	^3	S	Tera
T	units	S	Yobi
S	A	S	Yocto
S	B	S	Yotta

S Zebi	S Erlang
S Zepto	S Fahrenheit
S Zetta	S Farad
T suffixes	S Foot
S Cubic	S Force
S ICubic	S Gauss
S ILinear	S Gram
S ISquare	S Gray
S Inverse	S Henry
S Linear	S Hertz
S Square	S Hour
T symbols	S Inch
S ArcMinute	S Joule
S ArcSecond	S Katal
S Deg	S Kelvin
S Degree	S Liter
S Degrees	S Lux
S Percent	S Meter
S Per mille	S Metric Ton
S Promille	S Mol
S °	S Mole
T units	S Newton
S AC	S Ohm
S Ampere	S Pascal
S Angstrom	S RPM
S At	S RPS
S Atm	S Rad
S Atom	S RevPerMin
S Bar	S RevPerSec
S Baud	S Second
S Bel	S Siemens
S Bell	S Sievert
S Bequerel	S Sterant
S Bit	S Tesla
S Byte	S Tonne
S Cal	S Volt
S Candela	S VoltAC
S Celsius	S VoltDC
S Coulomb	S Watt
S DC	S Weber
S Dalton	S eV
S Electron Volt	S eVolt
S Equivalent	

## profiler (extra lua)

`pause`    `function`  
`resume`   `function`

`start`    `function`  
`stop`     `function`

# regimes (context)

<b>disable</b>	function	<b>process</b>	function
<b>enable</b>	function	<b>push</b>	function
<b>pop</b>	function	<b>translate</b>	function



# resolvers (context)

<b>allprefixes</b>	function	<b>getownpath</b>	function
<b>appendhash</b>	function	<b>getreadfilename</b>	function
<b>automount</b>	function	<b>hashers</b>	data table
<b>automounted</b>	table	<b>homedir</b>	string
<b>booleanvariable</b>	function	<b>installinputfilehandler</b>	function
<b>cacheversion</b>	string	<b>installinputlinehandler</b>	function
<b>checkedvariable</b>	function	<b>instance</b>	table
<b>cleanpath</b>	function	D data	
<b>cleanpathlist</b>	function	B diskcache	
<b>concatinators</b>	data table	D environment	
<b>configbanner</b>	string	D expansions	
<b>criticalvars</b>	data table	D fakepaths	
<b>dangerous</b>	data table	D files	
<b>datastate</b>	function	B force_suffixes	
<b>defaultsuffixes</b>	table	D found	
<b>dowithfilesandreport</b>	function	D foundintrees	
<b>dowithfilesintree</b>	function	D hashed	
<b>dowithpath</b>	function	D hashes	
<b>dowithvariable</b>	function	D lists	
<b>env</b>	function	B loadererror	
<b>executers</b>	table	D order	
F check		B remember	
F execute		B renewcache	
F finalize		B renewtree	
F register		B savelists	
<b>expandbraces</b>	function	D setups	
<b>expandedpathfromlist</b>	function	D specification	
<b>expandedpathlist</b>	function	D variables	
<b>expandedpathlistfromvariable</b>	function	<b>jobs</b>	table
<b>expandpath</b>	function	F currentcomponent	
<b>expandpathfromvariable</b>	function	F currentenvironment	
<b>expansion</b>	function	F currentproduct	
<b>extendtexmfvariable</b>	function	F currentproject	
<b>find_file</b>	function	F justacomponent	
<b>find_files</b>	function	D processors	
<b>findbinfile</b>	function	F productcomponent	
<b>findctxfile</b>	function	F usefile	
<b>finders</b>	data table	<b>joinpath</b>	function
<b>findfile</b>	function	<b>load</b>	function
<b>findfiles</b>	function	<b>loadbinfile</b>	function
<b>findgivenfile</b>	function	<b>loaders</b>	data table
<b>findgivenfiles</b>	function	<b>loadlualib</b>	function
<b>findpath</b>	function	<b>loadtexfile</b>	function
<b>findtexfile</b>	function	<b>loadtime</b>	function
<b>findwildcardfile</b>	function	<b>locateformat</b>	function
<b>findwildcardfiles</b>	function	<b>locators</b>	data table
<b>formatofsuffix</b>	function	<b>luacnfname</b>	string
<b>formatofvariable</b>	function	<b>luacnfspec</b>	string
<b>formats</b>	data table	<b>luacnfstate</b>	string
<b>generators</b>	data table	<b>macros</b>	table
<b>getenv</b>	function	F convertfile	

F decodecomment		schemes	table
F enablecomment		T cleaners	
F encodecomment		F md5	
F preprocessed		F none	
F processmkvi		F strip	
F version		F cleanname	
maxreadlevel	number	F install	
methodhandler	function	N threshold	
newinstance	function	setenv	function
openbinfile	function	setinstance	function
openers	data table	settrace	function
openfile	function	showpath	function
opentextfile	function	simplescanfiles	function
ownpath	string	splitconfigurationpath	function
prefixes	data table	splitexpansions	function
prependhash	function	splitmethod	function
registerextrapath	function	splitpath	function
registerfile	function	suffixes	data table
registerfilehash	function	suffixmap	data table
registerintrees	function	suffixofformat	function
registermethod	function	texdatablob	function
registerzipfile	function	unexpandedpath	function
relations	data table	unexpandedpathlist	function
renew	function	unresolve	function
repath	function	updaterelations	function
reset	function	updatescript	function
resetextrapath	function	usezipfile	function
resetresolve	function	validatedpath	function
resolve	function	variable	function
savers	data table	variableofformat	function
scandata	function	variableofformatorsuffix	function
scanfiles	function	wildcardpattern	function

# scripts (context)

categorytonumber	data table	numbertocategory	data table
colors	data table	numbertodataset	data table
handlers	data table	preprocess	function
hash	table	reset	function
installdataset	function	set	function
installmethod	function		

# set (context)

contains	function	tonumber	function
create	function	totable	function
tolist	function		

# socket (extra lua)

<b>BLOCKSIZE</b>	number		F keep-open
<b>_DEBUG</b>	boolean		<b>skip</b> function
<b>bind</b>	function		<b>sleep</b> function
<b>choose</b>	function		<b>smtp</b> table
<b>connect</b>	function		S DOMAIN
<b>dns</b>	table		N PORT
	F gethostname		S SERVER
	F tohostname		N TIMEOUT
	F toip		S ZONE
<b>ftp</b>	table		F message
	S PASSWORD		F open
	N PORT		F send
	N TIMEOUT		<b>source</b> function
	S USER		<b>sourcet</b> table
	F command		F by-length
	F get		F default
	F open		F http-chunked
	F put		F until-closed
<b>gettime</b>	function		<b>tcp</b> function
<b>http</b>	table		<b>tp</b> table
	N PORT		N TIMEOUT
	N TIMEOUT		F connect
	S USERAGENT		<b>try</b> function
	F open		<b>udp</b> function
	F request		<b>url</b> table
<b>newtry</b>	function		F absolute
<b>protect</b>	function		F build
<b>select</b>	function		F build_path
<b>sink</b>	function		F escape
<b>sinkt</b>	table		F parse
	F close-when-done		F parse_path
	F default		F unescape
	F http-chunked		

# sorters (context)

<b>comparers</b>	table	<b>definitions</b>	data table
F basic		<b>firstofsplit</b>	function
<b>constants</b>	table	<b>setlanguage</b>	function
S defaultdigits		<b>sort</b>	function
S defaultlanguage		<b>splitters</b>	table
S defaultmethod		F utf	
N digitmaximum		<b>strip</b>	function
N digitsoffset		<b>tracers</b>	data table
N ignoredoffset		<b>update</b>	function
N replacementoffset			

## statistics (context)

<code>checkfmtstatus</code>	function	<code>resettiming</code>	function
<code>elapsedindeed</code>	function	<code>runtime</code>	function
<code>elapsedseconds</code>	function	<code>savefmtstatus</code>	function
<code>elapsedtime</code>	function	<code>show</code>	function
<code>enable</code>	boolean	<code>showjobstat</code>	function
<code>formatruntime</code>	function	<code>starttiming</code>	function
<code>hastiming</code>	function	<code>stoptiming</code>	function
<code>memused</code>	function	<code>threshold</code>	number
<code>register</code>	function	<code>timed</code>	function
<code>reportstorage</code>	function		

status (basic tex)

list function



# storage (context)

allocate	function	min	number
data	table	nofmodules	number
evaluators	table	noftables	number
mark	function	register	function
marked	function	shared	data table
max	number		

## streams (context)

<code>collect</code>	function
<code>disable</code>	function
<code>enable</code>	function
<code>flush</code>	function
<code>initialize</code>	function

<code>push</code>	function
<code>start</code>	function
<code>stop</code>	function
<code>synchronize</code>	function

## string (basic lua)

<b>byte</b>	function	<b>match</b>	function
<b>bytepairs</b>	function	<b>quote</b>	function
<b>bytes</b>	function	<b>quoted</b>	function
<b>char</b>	function	<b>rep</b>	function
<b>characterpairs</b>	function	<b>reverse</b>	function
<b>characters</b>	function	<b>split</b>	function
<b>checkedsplit</b>	function	<b>splitlines</b>	function
<b>count</b>	function	<b>splitup</b>	function
<b>dump</b>	function	<b>strip</b>	function
<b>escapedpattern</b>	function	<b>sub</b>	function
<b>explode</b>	function	<b>toboolean</b>	function
<b>find</b>	function	<b>tocontext</b>	function
<b>format</b>	function	<b>todimen</b>	function
<b>gfind</b>	function	<b>topattern</b>	function
<b>gmatch</b>	function	<b>toutf</b>	function
<b>gsub</b>	function	<b>unquote</b>	function
<b>is_boolean</b>	function	<b>unquoted</b>	function
<b>is_empty</b>	function	<b>upper</b>	function
<b>len</b>	function	<b>utfcharacters</b>	function
<b>limit</b>	function	<b>utfsplitlines</b>	function
<b>lower</b>	function	<b>utfvalues</b>	function

# structures (context)

<b>atlocation</b>	function	F value	
<b>blocks</b>	table	<b>currentsectionnumber</b>	function
D collected		<b>descriptions</b>	table
F define		<b>documents</b>	table
F print		T data	
F save		S block	
F select		T blocks	
F setstate		T checkers	
D states		N depth	
D tobesaved		T forced	
<b>bookmarks</b>	table	T numbers	
F finalize		T ownnumbers	
F flatten		T status	
S method		F initialize	
F overload		F preset	
F place		F reset	
F register		<b>floats</b>	table
F setup		<b>formulas</b>	table
<b>counters</b>	table	F current	
F add		F simplify	
F analyze		F store	
F check		<b>helpers</b>	table
D collected		F analyze	
F compact		F formulanumber	
F converted		F merged	
F current		F page	
D data		F prefix	
F define		F prefixlastpage	
F first		F prefixpage	
F get		F simplify	
F last		F title	
F next		F touserdata	
F prev		<b>itemgroups</b>	table
F previous		F maxwidth	
F raw		F nofitems	
F record		F register	
F reset		<b>lists</b>	table
F restart		F analyze	
F restore		D cached	
F save		D collected	
F set		F doifstoredelse	
F setlevel		F enhance	
F setoffset		T enhancers	
F setown		F filter	
F setstate		F filtercollected	
F setvalue		F formulanumber	
F show		D internals	
T specials		F label	
F userpage		F location	
F subs		F number	
D tobesaved		D ordered	

- F page
- F popnesting
- F prefix
- F prefixednumber
- F prefixedpage
- F process
- F push
- D pushed
- F pushnesting
- F realpage
- T result
- F savednumber
- F savedprefixednumber
- F savedtitle
- F sectionnumber
- F size
- F title
- D tobesaved
- F userdata
- F uservalue

**marks**                      table

- D data
- F define
- F exists
- F fetch
- F fetchallmarks
- F fetched
- F fetchonemark
- F fetchtwomarks
- F get
- F number
- F relate
- F reset
- F set
- F show
- F synchronize
- F title
- T tracers
- F showtable

**notes**                      table

- F checkpagechange
- F define
- F deltapage
- F doifcontent
- F doifonsamepageasprevious
- F flush
- F flushpostponed
- F get
- F getn
- F getnumberpage
- F getstate
- F getsymbolpage
- F internal
- F internalid

- F listindex
- F number
- F ordered
- F postpone
- F resetpostponed
- F restore
- F save
- F setstate
- F setsymbolpage
- D states
- F store
- F title

**pages**                      table

- F analyze
- D collected
- F is\_odd
- F number
- F save
- D tobesaved

**processors**                      table

- F apply
- F register
- F reset
- F split
- F startapply
- F stopapply
- F stripped
- F tostring

**references**                      table

- F analyze
- F checkedfile
- F checkedfileorurl
- F checkedprogram
- F checkedrealpage
- F checkedurl
- D collected
- U componentsplitter
- F currentmetadata
- F currentorder
- D currentset
- F define
- D defined
- D derived
- F doifelse
- F enableinteraction
- F enhance
- D executers
- F expandcurrent
- F export
- T files
- T data
- F define
- F get
- F filter

D filters		F special operation with arguments
F from		T testspecials
F get		F deltapage
F getcurrentmetadata		F i
F getcurrentprefixspec		F internal
F getinnermethod		F page
F getinternalreference		F realpage
D handlers		F section
F identify		F userpage
F import		D tobereferred
F inject		D tobesaved
F injectcurrentset		T urls
D internals		T data
F load		F define
F loadpresets		F get
F mark		F whatfrom
D pages	<b>registers</b>	<b>table</b>
U prefixsplitter	F analyze	
T productdata	F analyzed	
T componentreferences	D collected	
T components	F compare	
T productreferences	F define	
T programs	F enhance	
T data	F extend	
F define	F filter	
F get	F filtercollected	
F realpageofpage	F finalize	
U referencesplitter	F flush	
D referred	F prepare	
F referredpage	F process	
F registerfinalizer	F sort	
F registerinitializer	F store	
F registerpage	D tobesaved	
F reportproblems	F unique	
F reset	F userdata	
T resolvers	<b>sections</b>	<b>table</b>
F reference	F autodepth	
F section	F cct	
D runners	T collected	
F set	F current	
F setandgetattribute	F currentblock	
F setcomponent	F currentid	
F setinnermethod	F currentlevel	
F setinternalreference	F defineautolevels	
F setnextinternal	F depthnumber	
F setnextorder	F finddata	
D specials	F findnumber	
F splitcomponent	F fullnumber	
F splitprefix	F getcurrentlevel	
F splitreference	F getlevel	
T testrunners	F getnumber	
F inner	F internalreference	
F special	D levelmap	
F special operation	D levels	

F load		F filter	
F matchingtilldepth		F finalize	
F numberatdepth		F flush	
F numbers		F meaning	
F popblock		F prepare	
F prefixedconverted		F process	
F pushblock		F register	
F register		F registerused	
D registered		F sort	
F reportstructure		F synonym	
F save		D tobesaved	
F set		<b>tags</b>	<b>table</b>
F setblock		T data	
F setchecker		F detailedtag	
F setlevel		F getid	
F setnumber		F handler	
F somelevel		D labels	
F startautolevel		F last	
F stopautolevel		F lastinchain	
F structuredata		T metadata	
F title		D properties	
D tobesaved		F registerdata	
F typesetnumber		F registermetadata	
F userdata		F restart	
B verbose		F setattributehash	
F way		F setcombination	
<b>sets</b>	<b>table</b>	F setdescription	
F define		F setdescriptionsymbol	
F get		F setfigure	
F getall		F sethighlight	
D setlist		F setitemgroup	
<b>specials</b>	<b>table</b>	F setproperty	
D collected		F setsorting	
F retrieve		F setsynonym	
F store		F settablecell	
D tobesaved		F settabulatecell	
<b>synonyms</b>	<b>table</b>	F start	
F analyzed		F stop	
D collected		D taglist	
F compare		T userdata	
F define			

## table (basic lua)

append	function	print	function
are_equal	function	remove	function
compact	function	reversed	function
concat	function	sequenced	function
contains	function	serialize	function
copy	function	setmetatablecall	function
count	function	setmetatableindex	function
derive	function	setmetatablekey	function
fastcopy	function	setmetatablenewindex	function
flattened	function	setn	function
foreach	function	sort	function
foreachi	function	sortedhash	function
fromhash	function	sortedhashkeys	function
getmetatablekey	function	sortedkeys	function
getn	function	sortedpairs	function
has_one_entry	function	strip	function
identical	function	sub	function
imerge	function	swapped	function
imerged	function	tocontext	function
insert	function	tofile	function
is_empty	function	tohandle	function
keys	function	tohash	function
loweredkeys	function	toxml	function
maxn	function	unique	function
merge	function	unnest	function
merged	function	unpack	function
prepend	function		



## tex (basic tex)

<b>attribute</b>	table	<b>pdffontname</b>	function
<b>badness</b>	function	<b>pdffontobjnum</b>	function
<b>box</b>	table	<b>pdffontsize</b>	function
<b>catcode</b>	table	<b>pdfpageref</b>	function
<b>conditionals</b>	data table	<b>pdfxformname</b>	function
<b>constants</b>	data table	<b>primitives</b>	function
<b>count</b>	table	<b>print</b>	function
<b>ctxcatcodes</b>	number	<b>printlist</b>	function
<b>definefont</b>	function	<b>prtcacodes</b>	number
<b>delcode</b>	table	<b>romannumeral</b>	function
<b>dimen</b>	table	<b>round</b>	function
<b>dummyscatcodes</b>	number	<b>run</b>	function
<b>enableprimitives</b>	function	<b>scale</b>	function
<b>error</b>	function	<b>scratchcatcodes</b>	number
<b>extraprimitives</b>	function	<b>set</b>	function
<b>finish</b>	function	<b>setAttribute</b>	function
<b>fontidentifier</b>	function	<b>setbox</b>	function
<b>fontname</b>	function	<b>setcatcode</b>	function
<b>fprint</b>	function	<b>setcount</b>	function
<b>get</b>	function	<b>setdelcode</b>	function
<b>getAttribute</b>	function	<b>setdimen</b>	function
<b>getbox</b>	function	<b>setfalse</b>	function
<b>getcatcode</b>	function	<b>setlccode</b>	function
<b>getcount</b>	function	<b>setlist</b>	function
<b>getdelcode</b>	function	<b>setmath</b>	function
<b>getdimen</b>	function	<b>setmathcode</b>	function
<b>getlccode</b>	function	<b>setnest</b>	function
<b>getlist</b>	function	<b>setsfcode</b>	function
<b>getmath</b>	function	<b>setskip</b>	function
<b>getmathcode</b>	function	<b>settoks</b>	function
<b>getnest</b>	function	<b>settrue</b>	function
<b>getsfcode</b>	function	<b>setuccode</b>	function
<b>getskip</b>	function	<b>sfcode</b>	table
<b>gettoks</b>	function	<b>shipout</b>	function
<b>getuccode</b>	function	<b>skip</b>	table
<b>hashtokens</b>	function	<b>sp</b>	function
<b>ifs</b>	data table	<b>sprint</b>	function
<b>iscount</b>	function	<b>systemmodes</b>	data table
<b>isdimen</b>	function	<b>texcatcodes</b>	number
<b>isskip</b>	function	<b>toks</b>	table
<b>istoken</b>	function	<b>tpacatcodes</b>	number
<b>lccode</b>	table	<b>tpbcatcodes</b>	number
<b>linebreak</b>	function	<b>tprint</b>	function
<b>lists</b>	table	<b>txtcatcodes</b>	number
<b>luacatcodes</b>	number	<b>type</b>	function
<b>mathcode</b>	table	<b>uccode</b>	table
<b>modes</b>	data table	<b>uniformdeviate</b>	function
<b>nest</b>	table	<b>uprint</b>	function
<b>nilcatcodes</b>	number	<b>vrbcacodes</b>	number
<b>notcatcodes</b>	number	<b>write</b>	function
<b>number</b>	function		

## texconfig (basic tex)

<code>error_line</code>	number	<code>max_print_line</code>	number
<code>expand_depth</code>	number	<code>max_strings</code>	number
<code>formatname</code>	string	<code>nest_size</code>	number
<code>half_error_line</code>	number	<code>param_size</code>	number
<code>hash_extra</code>	number	<code>save_size</code>	number
<code>init</code>	function	<code>shell_escape</code>	string
<code>kpse_init</code>	boolean	<code>stack_size</code>	number
<code>max_in_open</code>	number		

## texio (basic tex)

```
write      function  
write_nl  function
```

# token (basic tex)

<code>command_id</code>	function	<code>get_next</code>	function
<code>command_name</code>	function	<code>is_activechar</code>	function
<code>create</code>	function	<code>is_expandable</code>	function
<code>csname_id</code>	function	<code>is_protected</code>	function
<code>csname_name</code>	function	<code>lookup</code>	function
<code>expand</code>	function		

# tokens (context)

bgroup	table	T show_methods	
collectors	table	F a	
T data		F b	
F defaultwords		F c	
F dowithwords		F showtoken	
F flush		F test	
F handle		F trace	
F install		egroup	table
F register		hbox	table
T registered		letter	function
T remapper		letters	function
F convert		other	function
T data		vbox	table
F store		vtop	table
F show			

# tracers (context)

count	function	name	function
cs	function	primitive	function
dimen	function	printerror	function
knownlist	function	showlines	function
lists	table	strings	table
T context		S undefined	
T internals		toks	function
T scratch		type	function

# trackers (context)

data	data table	name	string
disable	function	register	function
dumphashtofile	function	report	function
enable	function	savehash	function
list	function	show	function

# typesetters (context)

**alignments** table

F handler

F set

**breakpoints** table

N attribute

F enable

F handler

D mapping

T methods

F set

F setreplacement

**cases** table

T actions

F handler

F set

**characters** table

F handler

**cleaners** table

F handler

F set

**digits** table

T actions

N attribute

F handler

F set

**directions** table

F handler

F process

F set

**hpack** function

**italics** table

F forcevariant

F handler

F reset

F set

**kerns** table

D factors

F handler

B keepligature

B keptogether

D mapping

F set

**margins** table

F finalhandler

F globalhandler

F ha

F localhandler

F save

**paragraphs** table

N attribute

T droppers

F freeze

F set

F handler

F set

**spacings** table

N attribute

F handler

D mapping

F set

F setup

**tonodes** function

**vpack** function

**xtables** table

F cleanup

F construct

F create

F flush

F initialize\_construct

F initialize\_reflow\_height

F initialize\_reflow\_width

F next\_row

F reflow\_height

F reflow\_width

F set\_construct

F set\_reflow\_height

F set\_reflow\_width



# unicode (extra lua)

<b>ascii</b>	<b>table</b>		
F byte		F gmatch	
F char		F gsub	
F dump		F len	
F find		F lower	
F format		F match	
F gfind		F rep	
F gmatch		F reverse	
F gsub		F sub	
F len		F upper	
F lower		<b>ustring</b>	<b>function</b>
F match		<b>utf16_to_utf8</b>	<b>function</b>
F rep		<b>utf16_to_utf8_be</b>	<b>function</b>
F reverse		<b>utf16_to_utf8_le</b>	<b>function</b>
F sub		<b>utf32_to_utf8</b>	<b>function</b>
F upper		<b>utf32_to_utf8_be</b>	<b>function</b>
<b>filetype</b>	<b>function</b>	<b>utf32_to_utf8_le</b>	<b>function</b>
<b>grapheme</b>	<b>table</b>	<b>utf8</b>	<b>table</b>
F byte		F byte	
F char		F char	
F dump		F dump	
F find		F find	
F format		F format	
F gfind		F gfind	
F gmatch		F gmatch	
F gsub		F gsub	
F len		F len	
F lower		F lower	
F match		F match	
F rep		F rep	
F reverse		F reverse	
F sub		F string	
F upper		F sub	
<b>latin1</b>	<b>table</b>	F toentities	
F byte		F upper	
F char		<b>utf8_to_utf16</b>	<b>function</b>
F dump		<b>utf8_to_utf8</b>	<b>function</b>
F find		<b>utfcodes</b>	<b>function</b>
F format		<b>utfname</b>	<b>table</b>
F gfind		<b>utftype</b>	<b>function</b>
		<b>xstring</b>	<b>function</b>

# url (context)

<code>addscheme</code>	function	<code>hasscheme</code>	function
<code>construct</code>	function	<code>query</code>	function
<code>filename</code>	function	<code>split</code>	function
<code>hashed</code>	function		

# utilities (context)

**debugger**                    table

F disable  
F enable  
F savestats  
F showstats

**formatters**                table

F formatcolumns  
F list  
F stripzeros

**garbagecollector**   table

F check  
N criterium  
B enabled

**lua**                        table

F compile

**packers**                   table

F hashed  
F new  
F pack  
F simplehashed  
F strip  
F unpack  
N version

**parsers**                   table

F add\_settings\_to\_array  
F arguments\_to\_table  
F array\_to\_string  
F getparameters  
F hash\_to\_string  
F listitem  
F make\_settings\_to\_hash\_pattern  
T patterns  
  U settings\_to\_array  
  U settings\_to\_hash\_a  
  U settings\_to\_hash\_b  
  U settings\_to\_hash\_c  
F settings\_to\_array  
F settings\_to\_hash  
F settings\_to\_hash\_strict  
F settings\_to\_hash\_tolerant  
F settings\_to\_set  
F simple\_hash\_to\_string

**report**                    function

**sequencers**               table

F appendaction

F appendgroup  
F autocompile  
F compile  
F disableaction  
F disablegroup  
F enableaction  
F enablegroup  
D functions  
F localize  
F nodeprocessor  
F prependaction  
F prependgroup  
F removeaction  
F reset  
F setkind  
F tostring

**setters**                   table

F disable  
F enable  
F initialize  
F list  
F new  
F register  
F reset  
F show

**storage**                   table

F allocate  
F checked  
F mark  
F marked  
F setinitializer  
F sparse

**strings**                   table

F collapseCrLf  
F newrepeater  
F striplong  
F tabtospace

**tables**                    table

F accesstable  
F definetable  
F encapsulate  
F insertaftervalue  
F insertbeforevalue  
F migratetable  
F removevalue

## visualizers (context)

escapepatterns	data table	signal	string
getvisualizer	function	signalpattern	userdata
load	function	specifications	data table
makenested	function	visualize	function
makepattern	function	visualizebuffer	function
newgrammar	function	visualizefile	function
newhandler	function	visualizestring	function
parsedxml	function	write	function
pattern	function	writeargument	function
register	function	writedefault	function
registerescapecommand	function	writeemptyline	function
registerescapeline	function	writenewline	function
registerescapepattern	function	writespace	function

## xml (context)

<b>addentitiesdoctype</b>	function	<b>erase</b>	function
<b>after</b>	function	<b>escaped</b>	function
<b>all</b>	function	<b>expressions</b>	table
<b>applylpath</b>	function	F boolean	
<b>assign</b>	function	F child	
<b>attribute</b>	function	F contains	
<b>before</b>	function	F count	
<b>body</b>	function	F error	
<b>builtinentities</b>	table	F find	
B amp		F lower	
B apos		F name	
B gt		F number	
B lt		F oneof	
B quot		F print	
<b>cdatatotext</b>	function	F quit	
<b>checkbom</b>	function	F tag	
<b>checkerror</b>	function	F text	
<b>checknamespace</b>	function	F undefined	
<b>checkns</b>	function	F upper	
<b>cleansed</b>	function	<b>fillin</b>	function
<b>collect</b>	function	<b>filter</b>	function
<b>collect_elements</b>	function	<b>finalizers</b>	table
<b>collect_tags</b>	function	T tex	
<b>collect_texts</b>	function	F all	
<b>collected</b>	function	F attribute	
<b>collecttexts</b>	function	F bibtexconcat	
<b>content</b>	function	F bibtexshort	
<b>convert</b>	function	F chainattribute	
<b>copy</b>	function	F command	
<b>count</b>	function	F concat	
<b>cprint</b>	function	F concatrange	
<b>css</b>	table	F context	
F colorspecification		F count	
F fontspecification		F ctxttext	
F padding		F default	
<b>defaulthandlers</b>	table	F first	
D file		F function	
D parsedxml		F index	
D string		F last	
D tex		F lettered	
D texline		F lower	
D texspace		F match	
D verbose		F name	
<b>defaultprotocol</b>	string	F position	
<b>delete</b>	function	F reverse	
<b>delete_element</b>	function	F stripped	
<b>each</b>	function	F tag	
<b>each_element</b>	function	F tags	
<b>elements</b>	function	F text	
<b>empty</b>	function	F upper	
<b>entities</b>	data table	T xml	

F all		newhandlers	function
F att		nodesettostring	function
F attribute		originalload	function
F attributes		package	function
F chainattribute		parent	function
F count		parsedentitylpeg	userdata
F default		pihandlers	table
F elements		placeholders	table
F empty		F unknown_any_entity	
F first		F unknown_dec_entity	
F function		F unknown_hex_entity	
F index		position	function
F last		privatecodes	table
F match		privatetoken	function
F name		process	function
F position		process_attributes	function
F reverse		process_elements	function
F table		processattributes	function
F tag		profiled	table
F tags		raw	function
F text		registerentity	function
F texts		registers	function
first	function	remap_name	function
found	function	remap_namespace	function
functions	table	remap_tag	function
getbuffer	function	remapname	function
gethandlers	function	remapnamespace	function
gethandlersfunction	function	remaptag	function
include	function	renamespace	function
index	function	replace	function
inheritedconvert	function	replace_element	function
inject	function	resolvens	function
inject_element	function	root	function
inject_element_after	function	save	function
inject_element_before	function	selection	function
injectafter	function	serialize	function
injectbefore	function	sethandlersfunction	function
insert	function	setproperty	function
insert_element	function	settings	function
insert_element_after	function	specialhandler	table
insert_element_before	function	sprint	function
insertafter	function	string	function
insertbefore	function	strip	function
inspect	function	strip_whitespace	function
is_valid	function	stripelement	function
last	function	stripleadingspaces	function
load	function	table	function
lpath	function	text	function
lpathcached	function	textonly	function
lpathcalls	function	tocdata	function
lshow	function	toelement	function
makestandalone	function	tostring	function
match	function	toxml	function
name	function	tprint	function

<code>traverse</code>	<code>function</code>	<code>withelements</code>	<code>function</code>
<code>unescaped</code>	<code>function</code>	<code>wrap</code>	<code>function</code>
<code>unprivatized</code>	<code>function</code>	<code>xmlns</code>	<code>table</code>
<code>withelement</code>	<code>function</code>		

## zip (extra lua)

<code>archives</code>	<code>table</code>	<code>openarchive</code>	<code>function</code>
<code>close</code>	<code>function</code>	<code>openfile</code>	<code>function</code>
<code>closearchive</code>	<code>function</code>	<code>registeredfiles</code>	<code>table</code>
<code>open</code>	<code>function</code>	<code>type</code>	<code>function</code>



## zlib (extra lua)

<b>adler32</b>	function	<b>decompress</b>	function
<b>compress</b>	function	<b>decompressobj</b>	function
<b>compressobj</b>	function	<b>version</b>	function
<b>crc32</b>	function		