



# ConTeXt

comenzile

# RO



# ConTeXt

## comenzile

ro / română  
29 august 2017



\AfterPar {...} * BEFEHL
\Alphabeticnumerals {...} * NUMMER
\AMSTEX
\AmSTeX
\And
\abjadnaivenumerals {...} * NUMMER
\abjadnodotnumerals {...} * NUMMER
\abjadnumerals {...} * NUMMER
\activatespacehandler {...} * on dezactivat da fixat
\acute {...} * CHARACTER
\adaptcollector [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 NAME OPT 2 inherits: \setupcollector
\adapteazaaspect [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 NUMMER OPT 2 inalttime = max DIMENSION linii = NUMMER
\adaptfontfeature [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 NAME 2 inherits: \definefontfeature
\adaptpapersize [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 inherits: \seteazadimensiunihartie OPT 2 inherits: \seteazadimensiunihartie
\addfeature [...] * NAME
\addfeature {...} * NAME
\addtocommalist {...} \ <sup>2</sup> .. 1 TEXT 2 CSNAME
\addtoJSreamble {...} {...} 1 NAME 2 CONTENT

\addvalue {...} {...} 1 NAME 2 TEXT
\adubuffer [...] * BUFFER OPT
\getBUFFER
\adumarcaje [...] [...] [...] 1 BESCHRIFTUNG OPT OPT 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\afiseazaaspect [...*,...] * pt bp cm mm dd cc pc $\mu$ nc sp in
\afiseazaculoare [...] * COLOR
\afiseazafonttext [...*,...] * inherits: \seteazafonttext
\afiseazagrid [...*,...] * reset subsol sus ni <sup>OPT</sup> unul tot linii incadrat nonumber dreapta stanga extern coloane
\afiseazagrupculoare [...] [...] 1 NAME OPT 2 orizontal vertical numar valoare nume
\afiseazamakeup [...] * marcaj tot boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math italic origin reset
\afiseazamediufonttext [...*,...] * inherits: \seteazafonttext
\afiseazapaleta [...] [...] 1 NAME OPT 2 orizontal vertical numar valoare nume
\afiseazarama [...] [...] 1 sus antet text sub <sup>OPT</sup> TI subsol 2 bordurastanga marginestanga text marginedreapta borduradreapta
\afiseazasetari [...*,...] * pt bp cm mm dd cc pc $\mu$ nc sp in
\afiseazasetsimboluri [...] * NAME
\afiseazastruts
\afiseazatiparire [...] [...] [...] 1 inherits: \seteazadimensi <sup>1</sup> unihartie OPT OPT 2 inherits: \seteazadimensiunihartie 3 inherits: \seteazaaspect

<code>\aftersplitstring ... \at ... \to ...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\aftertestandsplitstring ... \at ... \to ...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\aldin</code>
<code>\aldininclinat</code>
<code>\aldinitalic</code>
<code>\alignbottom</code>
<code>\aligned [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1 stanga centru dreapta sus subsol linie l c r m t b g 2 CONTENT
<code>\alignedbox [...<sup>1</sup>,...] ...<sup>2</sup> {...<sup>3</sup>}</code> 1 stanga centru dreapta sus subsol linie l c r m t b g 2 CSNAME 3 CONTENT
<code>\alignedline {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge spatiuspace cutspace marginestanga marginedreapta bordurastanga borduradreapta 2 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge spatiuspace cutspace marginestanga marginedreapta bordurastanga borduradreapta 3 CONTENT
<code>\alignmentcharacter</code>
<code>\aliniatcentru {...}</code> * CONTENT
<code>\aliniatdreapta {...}</code> * CONTENT
<code>\aliniatstanga {...}</code> * CONTENT
<code>\allinputpaths</code>
<code>\alphabeticnumerals {...}</code> * NUMMER
<code>\alwayscitation [...<sup>1</sup>...<sup>2</sup>...] [...<sup>2</sup>]</code> 1 referinta = REFERENCE <sup>OPT</sup> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE

`\alwayscitation [...]1 [...]2`

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

`\alwayscitation [...]1 [...]2`

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

`\alwayscite [...]1 [...]2`

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 REFERENCE

`\alwayscite [...]1 [...]2`

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

`\alwayscite [...]1 [...]2`

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

`\ampersand`

`\anchor [...]1 [...]2 [...]3 {...}4`

1 NAME OPT OPT  
2 inherits: \setuplayer  
3 inherits: \setuplayerinherits: \seteazainconjurat  
4 CONTENT

`\appendetoks ...1 \to ...2`

1 BEFEHL  
2 CSNAME

`\appendgvalue {...}1 {...}2`

1 NAME  
2 BEFEHL

`\appendtocommalist {...}1 ...2`

1 TEXT  
2 CSNAME

`\appendtoks ...1 \to ...2`

1 BEFEHL  
2 CSNAME



\appendtoksonce <sup>1</sup> ... \to \ <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\appendvalue { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\apply { <sup>1</sup> ...} { <sup>2</sup> ...} 1 CONTENT 2 CONTENT
\applyalternativestyle { <sup>*</sup> ...} * NAME
\applyprocessor { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 CONTENT
\applytocharacters \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytofirstcharacter \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringchar \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringcharspaced \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringline \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringlinespaced \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringword \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytosplitstringwordspaced \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\applytowords \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\arabicdecimals { <sup>*</sup> ...} * NUMMER
\arabicexnumerals { <sup>*</sup> ...} * NUMMER

\arabicnumerals {...} *   NUMBER
\arg {...} *   CONTENT
\asciistr {...} *   CONTENT
\ascundeblocuri [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] 1   NAME 2   NAME
\assignalfadimension {... <sup>1</sup> } \... <sup>2</sup> {... <sup>3</sup> } {... <sup>4</sup> } {... <sup>5</sup> } 1   mic mediu mare niciunul DIMENSION 2   CSNAME 3   DIMENSION 4   DIMENSION 5   DIMENSION
\assigndimen \... <sup>1</sup> {... <sup>2</sup> } 1   CSNAME 2   DIMENSION
\assigndimension {... <sup>1</sup> } \... <sup>2</sup> {... <sup>3</sup> } {... <sup>4</sup> } {... <sup>5</sup> } 1   [-+]mic [-+]mediu [-+]mare niciunul DIMENSION 2   CSNAME 3   DIMENSION 4   DIMENSION 5   DIMENSION
\assignifempty \... <sup>1</sup> {... <sup>2</sup> } 1   CSNAME 2   BEFEHL
\assigntranslation [... <sup>1</sup> ,... <sup>2</sup> ,...] \to \... 1   SPRACHE = TEXT 2   CSNAME
\assignvalue {... <sup>1</sup> } \... <sup>2</sup> {... <sup>3</sup> } {... <sup>4</sup> } {... <sup>5</sup> } 1   mic mediu mare TEXT 2   CSNAME 3   BEFEHL 4   BEFEHL 5   BEFEHL
\assignwidth {... <sup>1</sup> } \... <sup>2</sup> {... <sup>3</sup> } {... <sup>4</sup> } 1   ajustat broad DIMENSION 2   CSNAME 3   TEXT 4   DIMENSION
\assumelongusagecs \... <sup>1</sup> {... <sup>2</sup> } 1   CSNAME 2   CONTENT
\astype {...} *   CONTENT
\ATTACHMENT [... <sup>1</sup> ] [... <sup>2</sup> ,... <sup>3</sup> ,...] 1   NAME 2   inherits: \setupattachment instances: attachment

$\backslash\text{autocap} \{...\}$ * TEXT
$\backslash\text{autodirhbox} \overset{1}{...} \{...\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvbox} \overset{1}{...} \{...\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autodirvtop} \overset{1}{...} \{...\overset{2}{...}\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{autointegral} \{...\overset{1}{...}\} \{...\overset{2}{...}\} \{...\overset{3}{...}\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{automathematics} \{...\}$ * CONTENT
$\backslash\text{autosetups} \{...,*,...\}$ * NAME
$\backslash\text{autostarttext} \dots \backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar} \{...\}$ * BEFEHL
$\backslash\text{Big} \dots$ * CHARACTER
$\backslash\text{Bigg} \dots$ * CHARACTER
$\backslash\text{Biggl} \dots$ * CHARACTER
$\backslash\text{Biggm} \dots$ * CHARACTER
$\backslash\text{Biggr} \dots$ * CHARACTER
$\backslash\text{Bigl} \dots$ * CHARACTER
$\backslash\text{Bigm} \dots$ * CHARACTER

\Bigr {...} * CHARACTER
\backgroundimage {...} {...} {...} {...} 1 NUMMER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundimagefill {...} {...} {...} {...} 1 NUMMER 2 DIMENSION 3 DIMENSION 4 BEFEHL
\backgroundline [...] {...} 1 COLOR 2 CONTENT
\bar {...} * CHARACTER
\baraculoare [...,*...] * COLOR
\barainteractiune [...] <sup>1</sup> [...,... <sup>2</sup> ...,...] 1 NAME OPT OPT 2 inherits: \seteazabarainteractiune
\barasus {...} * TEXT
\BAR {...} * CONTENT instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar
\basegrid [...,... <sup>*</sup> ...,...] * nx = NUMMER ny = NUMMER dx = NUMMER dy = NUMMER factor = NUMMER scala = NUMMER xstep = NUMMER ystep = NUMMER offset = DIMENSION xoffset = DIMENSION yoffset = DIMENSION aliniere = centru unitate = cm mm in pc pt bp stil = STYLE BEFEHL culoare = COLOR
\baselinebottom
\baselineleftbox {...} * CONTENT
\baselinemiddlebox {...} * CONTENT

<code>\baselinerightbox {...}</code> *    CONTENT
<code>\bbox {...}</code> *    CONTENT
<code>\beforestrutstring ... \at ... \to ...</code> 1    TEXT 2    TEXT 3    CSNAME
<code>\beforetestandsplitstring ... \at ... \to ...</code> 1    TEXT 2    TEXT 3    CSNAME
<code>\beginBLOCK [...*,...] ... \endBLOCK</code> *    + - NAME            OPT
<code>\beginhbox ... \endhbox</code>
<code>\beginofshapebox ... \endofshapebox</code>
<code>\beginvbox ... \endvbox</code>
<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bigbodyfont</code>
<code>\bigg ...</code> *    CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> *    CHARACTER
<code>\biggm ...</code> *    CHARACTER
<code>\biggr ...</code> *    CHARACTER
<code>\bigl ...</code> *    CHARACTER
<code>\bigm ...</code> *    CHARACTER
<code>\bigr ...</code> *    CHARACTER
<code>\bigskip</code>

<p><code>\bitmapimage [...<sup>1</sup>...] {...<sup>2</sup>}</code></p> <p>1    culoare    =    rgb cmyk gri  latime        =    DIMENSION  inaltime     =    DIMENSION  x             =    NUMMER  y             =    NUMMER</p> <p>2    NUMMER</p>
<p><code>\blanc [...<sup>*</sup>...]</code></p> <p>*   inherits: <sup>OPT</sup>Vspacing</p>
<p><code>\blap {...}</code></p> <p>*   CONTENT</p>
<p><code>\bleed [...<sup>1</sup>...] {...<sup>2</sup>}</code></p> <p>1   inherits: <sup>OPT</sup>\setupbleeding  2   CONTENT</p>
<p><code>\bleedheight</code></p>
<p><code>\bleedwidth</code></p>
<p><code>\blockligatures [...<sup>*</sup>...]</code></p> <p>*   TEXT</p>
<p><code>\bodyfontenvironmentlist</code></p>
<p><code>\bodyfontsize</code></p>
<p><code>\boldface</code></p>
<p><code>\booleanmodevalue {...}</code></p> <p>*   NAME</p>
<p><code>\bottombox {...}</code></p> <p>*   CONTENT</p>
<p><code>\bottomleftbox {...}</code></p> <p>*   CONTENT</p>
<p><code>\bottomrightbox {...}</code></p> <p>*   CONTENT</p>
<p><code>\boxcursor</code></p>
<p><code>\boxmarker {...<sup>1</sup>} {...<sup>2</sup>}</code></p> <p>1   NAME  2   NUMMER</p>
<p><code>\boxofsize \...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> {...}</code></p> <p>1   CSNAME                    <sup>OPT</sup>  2   DIMENSION  3   CONTENT</p>
<p><code>\boxreference [...<sup>1</sup>...] \...<sup>2</sup> {...<sup>3</sup>}</code></p> <p>1   REFERENCE  2   CSNAME  3   CONTENT</p>

\bp ar ... \ep ar
\bp os {...} * NAME
\breve {...} * CHARACTER
\bTABLE [...,... <sup>*</sup> ...,...] ... \eTABLE * inherits: \setupTABLE <sup>OPT</sup>
\bTABLEbody [...,... <sup>*</sup> ...,...] ... \eTABLEbody * inherits: \setupTABLE <sup>OPT</sup>
\bTABLEfoot [...,... <sup>*</sup> ...,...] ... \eTABLEfoot * inherits: \setupTABLE <sup>OPT</sup>
\bTABLEhead [...,... <sup>*</sup> ...,...] ... \eTABLEhead * inherits: \setupTABLE <sup>OPT</sup>
\bTABLEnext [...,... <sup>*</sup> ...,...] ... \eTABLEnext * inherits: \setupTABLE <sup>OPT</sup>
\bTC [...,... <sup>*</sup> ...,...] ... \eTC * inherits: \PBD
\bTD [...,... <sup>*</sup> ...,...] ... \eTD * nx = <sup>OPT</sup> NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER actiune = REFERENCE inherits: \setupTABLE
\bTDs [...] ... \eTDs * NAME
\bTH [...,... <sup>*</sup> ...,...] ... \eTH * inherits: \PBD
\bTN [...,... <sup>*</sup> ...,...] ... \eTN * inherits: \PBD
\bTR [...,... <sup>*</sup> ...,...] ... \eTR * inherits: \PPTsetupTABLE
\bTRs [...] ... \eTRs * NAME
\bTX [...,... <sup>*</sup> ...,...] ... \eTX * inherits: \PBD
\bTY [...,... <sup>*</sup> ...,...] ... \eTY * inherits: \PPTsetupTABLE

\btthiddencitation [...] *   REFERENCE
\btxabbreviatedjournal {...} *   NAME
\btxaddjournal [...] <sup>1</sup> [...] <sup>2</sup> 1   NAME 2   NAME
\btxalwayscitation [...] <sup>1</sup> [...] <sup>2</sup> 1   referinta   = REFERENCE <sup>OPT</sup> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte    = BEFEHL dupa       = BEFEHL stanga     = BEFEHL dreapta    = BEFEHL inherits: \setupbtx 2   REFERENCE
\btxalwayscitation [...] <sup>1</sup> [...] <sup>2</sup> 1   implicit category entry <sup>OPT</sup> short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2   REFERENCE
\btxalwayscitation [...] <sup>1</sup> [...] <sup>2</sup> 1   referinta   = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte    = BEFEHL dupa       = BEFEHL stanga     = BEFEHL dreapta    = BEFEHL inherits: \setupbtx 2   KEY = VALUE
\btxauthorfield {...} *   initials firstnames vons surnames juniors
\btxdetail {...} *   address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxdirect {...} *   address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxdoif {...} <sup>1</sup> {...} <sup>2</sup> 1   address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME 2   TRUE
\btxdoifcombiinlistelse {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> 1   NAME 2   NAME 3   TRUE 4   FALSE



\btxdoifelse {...} {...} {...}

1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME  
2 TRUE  
3 FALSE

\btxdoifelsecombiinlist {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME  
2 TRUE  
3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

1 totdeauna douafete  
2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME  
3 TRUE  
4 FALSE

\btxdoifelseuservariable {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\btxdoifnot {...} {...}

1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME  
2 TRUE

\btxdoifsameaspreviouscheckedelse {...} {...} {...} {...}

1 totdeauna douafete  
2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME  
3 TRUE  
4 FALSE

\btxdoifsameaspreviouselse {...} {...} {...}

1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME  
2 TRUE  
3 FALSE

\btxdoifuservariableelse {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\btxexpandedjournal {...}

\* NAME

\btxfield {...}

\* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language  
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an  
yearfiled NAME

<p><code>\btxfielddname {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfielddtype {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfirstofrange {...}</code></p> <p>* volume pages</p>
<p><code>\btxflush {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxflushauthor [...<sup>1</sup>] {...<sup>2</sup>}</code></p> <p>1 num normal normalshort<sup>OPT</sup> inverted invertedshort</p> <p>2 autor editor</p>
<p><code>\btxflushauthorinverted {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorinvertedshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorname {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormal {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormalshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushsuffix</code></p>
<p><code>\btxfoundname {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfoundtype {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxhybridcite [...<sup>1</sup>...<sup>2</sup>]</code></p> <p>1 referinta = REFERENCE<sup>OPT</sup></p> <p>alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p>inainte = BEFEHL</p> <p>dupa = BEFEHL</p> <p>stanga = BEFEHL</p> <p>dreapta = BEFEHL</p> <p>inherits: \setupbtx</p> <p>2 REFERENCE</p>

\btxhybridcite [...<sup>1</sup>] [...<sup>2</sup>]

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

\btxhybridcite {...}

\* REFERENCE

\btxhybridcite [...<sup>1</sup>...] [...<sup>2</sup>...]

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

\btxlistcitation [...<sup>1</sup>...] [...<sup>2</sup>]

1 referinta = REFERENCE<sup>OPT</sup>  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 REFERENCE

\btxlistcitation [...<sup>1</sup>] [...<sup>2</sup>]

1 implicit category entry<sup>OPT</sup> short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

\btxlistcitation [...<sup>1</sup>...] [...<sup>2</sup>...]

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

\btxloadjournalist [...]

\* FILE

\btxoneorrange {...} {...} {...}

1 volume pages  
2 TRUE  
3 FALSE

\btxremapauthor [...<sup>1</sup>] [...<sup>2</sup>]

1 TEXT  
2 TEXT

\btxsavejournalist [...]

\* FILE

\btxsetup {...}

\* NAME

\btxsingularorplural {...} {...} {...}

1 editor producer director  
2 TRUE  
3 FALSE

`\btxsingularplural {...} {...} {...}`

1 editor producer director  
2 TRUE  
3 FALSE

`\btxttextcitation [...,\stackrel{1}{...},...] [...]`

1 referinta = REFERENCE<sup>OPT</sup>  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 REFERENCE

`\btxttextcitation [...]\stackrel{1}{...} [...]\stackrel{2}{...},...]`

1 implicit category entry<sup>OPT</sup> short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

`\btxttextcitation [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...]`

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

`\buildmathaccent {...} {...}`

1 CHARACTER  
2 CHARACTER

`\buildtextaccent {...} {...}`

1 CHARACTER  
2 CHARACTER

`\buildtextbottomcomma {...}`

\* CHARACTER

`\buildtextbottomdot {...}`

\* CHARACTER

`\buildtextcedilla {...}`

\* CHARACTER

`\buildtextgrave {...}`

\* CHARACTER

`\buildtextmacron {...}`

\* CHARACTER

`\buildtextognek {...}`

\* CHARACTER

`\butoaneinteractiune [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...]`

1 inherits: \seteazabarainteractiune<sup>OPT</sup>  
2 pagina subpagina REFERENCE

\buton [... <sup>1</sup> ... <sup>1</sup> ...] {... <sup>2</sup> } [... <sup>3</sup> ] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
\butonmeniu [... <sup>1</sup> ... <sup>1</sup> ...] {... <sup>2</sup> } {... <sup>3</sup> } 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
\butonmeniu [... <sup>1</sup> ...] [... <sup>2</sup> ... <sup>2</sup> ...] {... <sup>3</sup> } {... <sup>4</sup> } 1 NAME 2 inherits: \seteazameniuinteractiune 3 TEXT 4 REFERENCE
\BUTTON [... <sup>1</sup> ... <sup>1</sup> ...] {... <sup>2</sup> } [... <sup>3</sup> ] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
\Caps {...} * TEXT
\CONTEXT
\ConTeXt
\Context
\ConvertConstantAfter \... <sup>1</sup> {... <sup>2</sup> } {... <sup>3</sup> } 1 CSNAME 2 TEXT 3 TEXT
\ConvertToConstant \... <sup>1</sup> {... <sup>2</sup> } {... <sup>3</sup> } 1 CSNAME 2 TEXT 3 TEXT
\CUVANT {...} * TEXT
\CUVINTE {...} * TEXT
\Cuvant {...} * TEXT
\Cuvinte {...} * TEXT
\caligrafic
\camel {...} * TEXT

$\backslash\text{camp}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME OPT 2 TEXT
$\backslash\text{catcodetable}$ name
$\backslash\text{cbox}$ . <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{centeraligned}$ {.*...} * CONTENT
$\backslash\text{centerbox}$ . <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{centeredbox}$ . <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{centeredlastline}$
$\backslash\text{centerednextbox}$ . <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
$\backslash\text{centerline}$ {.*...} * CONTENT
$\backslash\text{centru}$ .*. * CHARACTER
$\backslash\text{cfrac}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} { <sup>3</sup> ...} 1 l c r l <sup>P</sup> <sub>P</sub> l <sup>c</sup> l <sup>r</sup> c <sup>l</sup> c <sup>c</sup> c <sup>r</sup> r <sup>l</sup> r <sup>c</sup> r <sup>r</sup> 2 CONTENT 3 CONTENT
$\backslash\text{CHARACTERKERNING}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 NUMBER OPT 2 TEXT
$\backslash\text{chardescription}$ {.*...} * NUMBER
$\backslash\text{charwidthlanguage}$
$\backslash\text{check}$ {.*...} * CHARACTER
$\backslash\text{checkcharacteralign}$ {.*...} * CONTENT
$\backslash\text{checkedchar}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NUMBER 2 CHARACTER

\checkedfiller {...} * sym simbol rigla latime spatiu NAME BEFEHL
\checkedstrippedcsname \*.. * CSNAME
\checkedstrippedcsname ... * TEXT
\checkinjector [...] * NAME
\checknextindentation [...] * da nu auto
\checknextinjector [...] * NAME
\checkpage [...] <sup>1</sup> [...,... <sup>2</sup> ...] <sup>OPT</sup> 1 NAME 2 inherits: \setuppagechecker
\checkparameters [...] * TEXT
\checkpreviousinjector [...] * NAME
\checksoundtrack {...} * NAME
\checktwopassdata {...} * NAME
\checkvariables [...] <sup>1</sup> [...,... <sup>2</sup> ...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
\chem {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 TEXT 2 TEXT 3 TEXT
\chemical [...] <sup>1</sup> [...,... <sup>2</sup> ...] <sup>OPT</sup> [...,... <sup>3</sup> ...] <sup>OPT</sup> 1 NAME 2 TEXT 3 TEXT
\chemicalbottext {...} * TEXT
\chemicalmidtext {...} * TEXT
\chemicalsymbol [...] * NAME

`\chemicaltext {...}`

\* TEXT

`\chemicaltoptext {...}`

\* TEXT

`\chineseallnumerals {...}`

\* NUMMER

`\chinesecapnumerals {...}`

\* NUMMER

`\chinesenumerals {...}`

\* NUMMER

`\citation [...1...2...] [...]`

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 REFERENCE

`\citation [...1...] [...2]`

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

`\citation {...}`

\* REFERENCE

`\citation [...1...2...] [...2...]`

1 referinta = REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 KEY = VALUE

`\cite [...1...2...] [...]`

1 referinta <sup>OR</sup> REFERENCE  
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum  
authoryear  
inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
inherits: \setupbtx  
2 REFERENCE

`\cite [...1...] [...2]`

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear  
2 REFERENCE

`\cite {...}`

\* REFERENCE



<pre> \cite [...,\sup{1}...,...] [...,\sup{2}...,...] 1  referinta = REFERENCE    alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                authoryear    inainte   = BEFEHL    dupa      = BEFEHL    stanga    = BEFEHL    dreapta   = BEFEHL    inherits: \setupbtx 2  KEY = VALUE </pre>
<pre> \clap {...} *  CONTENT </pre>
<pre> \classfont {...} {...} 1  NAME 2  FONT </pre>
<pre> \cldcommand {...} *  BEFEHL </pre>
<pre> \cldcontext {...} *  BEFEHL </pre>
<pre> \cldloadfile {...} *  FILE </pre>
<pre> \cldprocessfile {...} *  FILE </pre>
<pre> \cleftarrow {...} {...} 1  TEXT          OPT      OPT 2  TEXT </pre>
<pre> \clip [...,\sup{1}...,...] {...} 1  inherits: \seteazaclipping 2  CONTENT </pre>
<pre> \cloneazacamp [...]\sup{1} [...] [...]\sup{2} [...] [...]\sup{3} [...] [...]\sup{4},...] 1  NAME 2  NAME 3  NAME 4  NAME </pre>
<pre> \collect {...} *  CONTENT </pre>
<pre> \collectedtext [...,\sup{1}...,...] [...,\sup{2}...,...] {...}\sup{3} {...}\sup{4} 1  inherits: \setupcollectif OPT 2  stil      = STYLE BEFEHL    culoare   = COLOR    inherits: \seteazainconjurat 3  TEXT 4  CONTENT </pre>
<pre> \collectexpanded {...} *  CONTENT </pre>
<pre> \coloana [...,\sup{1},...] *  inherits: \columnbreak OPT </pre>

\colorcomponents {...} * COLOR
\colored [..., <sup>1</sup> ..., <sup>2</sup> ...] {...} 1 inherits: \definesteculoare 2 CONTENT
\colored [ <sup>1</sup> ...] {...} 1 COLOR 2 CONTENT
\coloronly [ <sup>1</sup> ...] {...} 1 COLOR 2 CONTENT
\columnbreak [..., <sup>1</sup> ...] * da nu preferinta local fortat primul ultim NUMBER NAME
\combinepages [ <sup>1</sup> ] [..., <sup>2</sup> ..., <sup>3</sup> ...] 1 FILE OPT 2 alternativ = a b c orizontal vertical n = NUMBER nx = NUMBER ny = NUMBER start = NUMBER stop = NUMBER distanta = DIMENSION sus = BEFEHL jos = BEFEHL stanga = BEFEHL dreapta = BEFEHL inainte = BEFEHL dupa = BEFEHL intre = BEFEHL frame = on dezactivat fundal = primplan culoare NAME culoarefundal = COLOR
\COMMENT [ <sup>1</sup> ] [..., <sup>2</sup> ..., <sup>3</sup> ...] {...} 1 TEXT OPT OPT 2 inherits: \seteazacommentariu 3 TEXT instances: comment
\commalistelement
\commalistsentence [..., <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 TEXT OPT 2 TEXT
\commalistsize
\comparagrupculoare [...] * NAME
\comparapaleta [...] * NAME
\comparedimension {...} {...} 1 DIMENSION 2 DIMENSION

1 DIMENSION  
2 DIMENSION

\completeazanumarpagina

```
1  NAME                                OPT          OPT
2  inherits: \setupbtxrendering
```

```
* inherits: \seteazalista      OPT
instances: content
```

```
1  LISTE
2  inherits: \seteazalista
```

```
* inherits: \seteazalista OPT
instances: chemicals figures tables intermezzi graphics
```

```
1 NAME OPT OPT
2 inherits: \setupbtxrendering
```

```
1 SINGULAR
2 inherits: \seteazasortare
```

```
* inherits: \seteazasortare      OPT
instances: logos
```

```

1 SINGULAR OPT
2 inherits: \seteazasinonime

```

```
* inherits: \seteazasinonime OPT
instances: abbreviations
```

```
1 NAME OPT
2 inherits: \seteazaregistru
```

```
* inherits: \seteazaregistruOPT
instances: index
```

```
1  NUMMER          OPT
2  inherits: \seteazaregistru
```

```
* CSNAME
```

\* CSNAME

\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple {...} * TEXT CSNAME
\componenta [...]
\componenta ... * FILE
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen \... * CSNAME
\constantdimenargument \... * CSNAME
\constantemptyargument \... * CSNAME
\constantnumber \... * CSNAME
\constantnumberargument \... * CSNAME
\contentreference [... <sup>1</sup> ,...] [... <sup>2</sup> ,... <sup>2</sup> ,...] {... <sup>3</sup> } 1 REFERENCE 2 inherits: \seteazainconjurat 3 CONTENT
\continuednumber {...} * NUMMER
\continueifinputfile {...} * FILE
\convertargument ... <sup>1</sup> \to ... <sup>2</sup> 1 TEXT 2 CSNAME
\convertcommand \... <sup>1</sup> \to ... <sup>2</sup> 1 CSNAME 2 CSNAME
\convertedcounter [... <sup>1</sup> ] [... <sup>2</sup> ,... <sup>2</sup> ,...] 1 NAME 2 inherits: \setupcounter

$\backslash$ converteddimen {...} {...} 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
$\backslash$ convertedsubcounter [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> ...,...] 1 NAME OPT OPT 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot 3 inherits: \setupcounter
$\backslash$ convertestenumar {...} <sup>1</sup> {...} <sup>2</sup> 1 gol implicit niciunul luna month:mnem caracter Caractere caractere Caractere a A Numere cuvant words Cuvant Cuvinte n N numereromane Numereromane i I r R KR RK grec Grec g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclednumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2 NUMBER
$\backslash$ convertmonth {...} * NUMBER
$\backslash$ convertvalue ... <sup>1</sup> \to ... <sup>2</sup> 1 NAME 2 CSNAME
$\backslash$ convertvboxtohbox
$\backslash$ copiazacamp [...] <sup>1</sup> [...] <sup>2</sup> 1 NAME 2 NAME
$\backslash$ copyboxfromcache {...} <sup>1</sup> {...} <sup>2</sup> ... <sup>3</sup> 1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
$\backslash$ copyLABELtext [...] <sup>1</sup> [...] <sup>2</sup> ...,...] 1 SPRACHE OPT 2 KEY = KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash$ copypages [...] <sup>1</sup> [...] <sup>2</sup> ...,...] <sup>3</sup> ...,...] 1 FILE OPT OPT 2 marcaje = on dezactivat offset = DIMENSION n = NUMBER 3 inherits: \setupexternalfigure
$\backslash$ copyparameters [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> ,...] 1 TEXT 2 TEXT 3 KEY
$\backslash$ copyposition {...} <sup>1</sup> {...} <sup>2</sup> 1 NAME 2 NAME
$\backslash$ corecteazaspatiualb {...} * CONTENT
$\backslash$ countersubs [...] <sup>1</sup> [...] <sup>2</sup> 1 NAME OPT 2 NUMBER

$\backslash\text{counttoken}$ <sup>1</sup> ... $\backslash\text{in}$ <sup>2</sup> ... $\backslash\text{to}$ $\backslash$ <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ <sup>1</sup> ... $\backslash\text{to}$ $\backslash$ <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ {...} * CONTENT
$\backslash\text{crampedclap}$ {...} * CONTENT
$\backslash\text{crampedllap}$ {...} * CONTENT
$\backslash\text{crampedrlap}$ {...} * CONTENT
$\backslash\text{crightarrow}$ {...} <sup>1</sup> {...} <sup>2</sup> {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{crightoverleftarrow}$ {...} <sup>1</sup> {...} <sup>2</sup> {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{ctop}$ <sup>1</sup> ... {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\backslash\text{ctxcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectlua}$ {...} * BEFEHL
$\backslash\text{ctxfunction}$ {...} * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$
$\backslash\text{ctxlatecommand}$ {...} * BEFEHL
$\backslash\text{ctxlatelua}$ {...} * BEFEHL
$\backslash\text{ctxloadluafile}$ {...} * FILE

\ctxlua {...} * BEFEHL
\ctxluabuffer [...] {...} * BUFFER <small>OPT</small>
\ctxluacode {...} * BEFEHL
\ctxreport {...} * BEFEHL
\ctxsprint {...} * BEFEHL
\culoare [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
\culoaregri [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 COLOR 2 CONTENT
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentETICHETA [... <sup>1</sup> ,...] { <sup>2</sup> ...} 1 REFERENCE <small>OPT</small> <small>OPT</small> 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber

\currentlistentryreferenceattribute {...} *    numar text numarpagina tot
\currentlistentrytitle
\currentlistentrytitlerendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} *    KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} *    KEY
\currentresponses
\currenttime [...*,...] *    h m TEXT                    OPT
\currentvalue
\currentxtablecolumn
\currentxtablerow
\cuvant {...} *    TEXT
\cuvantdreapta [... <sup>1</sup> ] {... <sup>2</sup> } 1    dreapta DIMENSION OPT 2    CONTENT
\d {...} *    CHARACTER
\data [..., <sup>1</sup> ...,... <sup>2</sup> ] [..., <sup>2</sup> ...] 1    d = NUMBER OPT                    OPT m = NUMBER y = NUMBER 2    inherits: \datacurrenta



<p><code>\datacurenta [...*,...]</code></p> <p>* an luna zi zisaptamana y yy Y m mm M d dd D w W spatiu \_ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT referinta day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</p>
<p><code>\datasetvariable {...} {...} {...}</code></p> <p>1 NAME 2 NAME NUMMER 3 KEY realpage</p>
<p><code>\dayoftheweek {...} {...} {...}</code></p> <p>1 NUMMER 2 NUMMER 3 NUMMER</p>
<p><code>\dayspermonth {...} {...}</code></p> <p>1 NUMMER 2 NUMMER</p>
<p><code>\ddot {...}</code></p> <p>* CHARACTER</p>
<p><code>\decrement \...</code></p> <p>* CSNAME</p>
<p><code>\decrementcounter [...] [...]</code></p> <p>1 NAME OPT 2 NUMMER</p>
<p><code>\decrementedcounter [...]</code></p> <p>* NAME</p>
<p><code>\decrementpagenumber</code></p>
<p><code>\decrementsubpagenumber</code></p>
<p><code>\decrementvalue {...}</code></p> <p>* NAME</p>
<p><code>\decrement cd:parentheses-1</code></p> <p>* CSNAME NUMMER</p>
<p><code>\defaultinterface</code></p>
<p><code>\defaultobjectpage</code></p>
<p><code>\defaultobjectreference</code></p>
<p><code>\defcatcodecommand \... .. {...}</code></p> <p>1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL</p>
<p><code>\defconvertedargument \... {...}</code></p> <p>1 CSNAME 2 TEXT</p>
<p><code>\defconvertedcommand \... \...</code></p> <p>1 CSNAME 2 CSNAME</p>

<pre> \defconvertedvalue \... {<sup>1</sup>... {<sup>2</sup>...} 1 CSNAME 2 NAME </pre>
<pre> \defineactivecharacter ... {<sup>1</sup>... {<sup>2</sup>...} 1 CHARACTER 2 BEFEHL </pre>
<pre> \definealternativestyle [...,<sup>1</sup>...] [...<sup>2</sup>] [...<sup>3</sup>] 1 NAME 2 BEFEHL 3 BEFEHL </pre>
<pre> \defineanchor [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] [...,<sup>4</sup>...<sup>4</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupplayer 4 inherits: \setupplayerinherits: \seteazainconjurat </pre>
<pre> \defineattachment [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupattachment </pre>
<pre> \defineattribute [...<sup>1</sup>] [...,<sup>2</sup>...] 1 NAME OPT 2 local global public private </pre>
<pre> \definebackground [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazafundal </pre>
<pre> \definebar [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupbar </pre>
<pre> \definebodyfontswitch [...<sup>1</sup>] [...,<sup>2</sup>...] 1 NAME 2 inherits: \seteazafonttext </pre>
<pre> \definebreakpoint [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] 1 NAME OPT 2 CHARACTER 3 type = 1 2 3 4 5 nstanga = NUMMER ndreapta = NUMMER stanga = BEFEHL mijloc = BEFEHL dreapta = BEFEHL range = da nu language = SPRACHE </pre>
<pre> \definebreakpoints [...<sup>*</sup>...] * NAME </pre>
<pre> \definebtx [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupbtx </pre>

```
\definebtxdataset [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxdataset
```

```
\definebtxregister [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxregister
```

```
\definebtxrendering [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbtxrendering
```

```
\definebutton [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbutton
```

```
\definecapitals [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazamazajuscule
```

```
\definecharacterkerning [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcharacterkerning
```

```
\definecharacterspacing [...]
* NAME
```

```
\definechemical [...] [...]
1 NAME
2 CONTENT
```

```
\definechemicals [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupchemical
```

```
\definechemicalsymbol [...] [...]
1 NAME
2 TEXT
```

```
\definecollector [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcollector
```

```
\definecolumnbreak [...] [...]
1 NAME
2 da nu preferinta local fortat primul ultim NUMBER
```

```
\definecombination [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcombination
```

<pre> \definecomment [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazacommentariu </pre>
<pre> \definecomplexorsimple \*... * CSNAME </pre>
<pre> \definecomplexorsimpleempty \*... * CSNAME </pre>
<pre> \definecomplexorsimpleempty {...} * TEXT CSNAME </pre>
<pre> \definecomplexorsimple {...} * TEXT CSNAME </pre>
<pre> \defineconversionset [...] [...] [...] 1 NAME SECTIONBLOCK:NAME OPT 2 NAME PROCESSOR-&gt;NAME 3 NAME PROCESSOR-&gt;NAME </pre>
<pre> \definecounter [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupcounter </pre>
<pre> \definedataset [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupdataset </pre>
<pre> \definedelimitedtext [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupdelimitedtext </pre>
<pre> \definedfont [...] * FONT OPT </pre>
<pre> \defineeffect [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupeffect </pre>
<pre> \defineexpandable [...] \^2... {...} 1 NUMMER OPT 2 CSNAME 3 CONTENT </pre>
<pre> \defineexternalfigure [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuexternalfigure </pre>

```

\definefallbackfamily [...] [...] [...] [...,..4...,...]
1 NAME OPT
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica caligrafic math
matematica
3 FONT
4 rscale = NUMBER
designsize = implicit auto
goodies = FILE
range = NUMBER NAME
offset = NUMBER NAME
check = da nu
fortat = da nu
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT

```

```

\definefallbackfamily [...] [...] [...] [...,..4...]
1 NAME OPT
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica caligrafic math
matematica
3 FONT
4 NAME

```

```

\definefieldbody [...] [2...] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfieldbody

```

```

\definefieldbodyset [1] [...,2...]
1 NAME
2 NAME

```

```

\definefieldcategory [1] [2...] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfieldcategory

```

```

\definefileconstant {1} {2}
1 NAME
2 NAME

```

```

\definefilefallback [1] [...,2...]
1 NAME
2 FILE

```

```

\definefilesynonym [1] [2]
1 NAME
2 FILE

```

```

\definefiller [1] [2...] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfiller

```

```

\definefirstline [1] [2...] [...,..3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupfirstline

```

```

1 NAME OPT OPT
2 NAME
3 inherits: \setupfittingpage

```

\* NAME

```

1  NAME                                OPT
2  FONT NAME
3  NAME NUMBER
4  rscale      =  NUMBER
   fortat      =  da nu
   check       =  da nu
   offset      =  NUMBER NAME
   features    =  NAME

```

```

1  NAME                                OPT
2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismannual caligrafic math
   matematica
3  FONT
4  rscale      =  NUMMER
   designsize  =  implicit auto
   goodies     =  FILE
   features    =  NAME
   tf          =  TEXT
   bf          =  TEXT
   it          =  TEXT
   sl          =  TEXT
   bi          =  TEXT
   bs          =  TEXT
   sc          =  TEXT

```

```
1 NAME
2 inherits: \definefontfamily
```

1	NAME
2	NAME

```

1  NAME                                     OPT
2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismanual caligrafic math
   matematica
3  FONT
4  NAME

```

`\definefontfeature` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

```
1 NAME
2 NAME
3 language = NAME
  script   = NAME auto
  mode     = node base auto niciunul
  liga     = da nu
  kern     = da nu
  extrakerns = da nu
  tlig     = da nu
  trep     = da nu
  missing  = da nu
  dummies  = da nu
  analyze  = da nu
  unicoding = da nu
  expansiune = NAME
  protrusion = NAME
  nostackmath = da nu
  realdimensions = da nu
  itlc     = da nu
  textitalics = da nu
  mathitalics = da nu
  slant     = NUMMER
  extend    = NUMMER
  dimensions = NUMMER
  boundingbox = da nu
  compose   = da nu
  char-ligatures = da nu
  compat-ligatures = da nu
  goodies   = FILE
  extrafeatures = da nu
  featureset = NAME
  colorscheme = NAME
  postprocessor = NAME
  mathdimensions = NAME
  keepligatures = da nu auto
  devanagari = da nu
  features     = da nu
  tcom         = da nu
  anum        = da nu
  mathsize     = da nu
  decomposehangul = da nu
  mathalternatives = da nu
  mathgaps     = da nu
  checkmarks   = da nu
  NAME         = da nu
  mathnolimitsmode = NUMMER
  blockligatures = da nu
```

`\definefontfile` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

```
1 NAME
2 FILE
3 features = NAME
  fallbacks = NAME
  goodies   = NAME
  designsize = auto implicit
```

`\definefontsize` [...]

```
* NAME
```

`\definefontsolution` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

```
1 NAME
2 NAME
3 inherits: \setupfontsolution
```

`\defineformula` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

```
1 NAME
2 NAME
3 inherits: \setupformula
```

`\defineformulaalternative` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 CSNAME
3 CSNAME
```

```
\defineformulaframed [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setupformulaframed
```

```
\defineframedcontent [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setupframedcontent
```

```
\definefrozenfont [...1] [...2]  
1 NAME  
2 FONT
```

```
\defineglobalcolor [...1] [...,...2...,...]  
1 NAME  
2 inherits: \definesteculoare
```

```
\defineglobalcolor [...1] [...2]  
1 NAME  
2 COLOR
```

```
\definegraphictypesynonym [...1] [...2]  
1 NAME  
2 NAME
```

```
\definegridsnapping [...1] [...,...2...,...]  
1 NAME  
2 local global noheight nodepth box max min niciunul linie jumatatelinie primul ultim inaltimeminima maxheight  
mindepth maxdepth sus subsol strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER  
box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER
```

```
\defineheadalternative [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setupheadalternative
```

```
\definehelp [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphelp
```

```
\definehigh [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphigh
```

```
\definehighlight [...1] [...2] [...,...3...,...]  
1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphighlight
```

```
\definehspace [...1] [...2] [...3]  
1 NAME OPT  
2 NAME  
3 DIMENSION
```



`\definehyphenationfeatures [...]1 [...,...2...,...]`

```
1 NAME
2 characters = TEXT
  hyphens   = da tot TEXT
  joiners    = da tot TEXT
  rightwords = NUMMER
  hyphenmin  = NUMMER
  lefthyphenmin = NUMMER
  righthyphenmin = NUMMER
  lefthyphenchar = NUMMER
  righthyphenchar = NUMMER
  alternativ  = original tex hyphenate expanded traditional niciunul
  borduradreapta = tex
  rightchars = cuvant NUMMER
```

`\defineindentedtext [...]1 [...]2 [...,...3...,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupindentedtext
```

`\defineindenting [...]1 [...,...2...,...]`

```
1 NAME
2 [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle
  DIMENSION
```

`\defineinitial [...]1 [...]2 [...,...3...,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupinitial
```

`\defineinsertion [...]1 [...]2 [...,...3...,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setupinsertion
```

`\defineinteraction [...]1 [...]2 [...,...3...,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setezainteractiunea
```

`\defineinteractionbar [...]1 [...]2 [...,...3...,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setezabarainteractiune
```

`\defineinterfaceconstant {...}1 {...}2`

```
1 NAME
2 NAME
```

`\defineinterfaceelement {...}1 {...}2`

```
1 NAME
2 NAME
```

`\defineinterfacevariable {...}1 {...}2`

```
1 NAME
2 NAME
```

`\defineinterlinespace [...]1 [...]2 [...,...3...,...]`

```
1 NAME OPT OPT
2 NAME
3 inherits: \setezaspatiuinterliniar
```

```

\defineintermediatecolor [1...] [2...] [3...OPT...]
1 NAME
2 COLOR NUMMER
3 a = NUMMER
  t = NUMMER

```

```

\defineitemgroup [1...] [2...] [3...OPT...]
1 NAME
2 NAME
3 inherits: \setupitemgroup

```

```

\defineitems [1...] [2...] [3...OPT...]
1 NAME
2 NAME
3 inherits: \seteazaelemente

```

```

\definelabelclass [1...] [2...]
1 NAME
2 NUMMER

```

```

\setarebtxlabeltext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setareheadtext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setarelabeltext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setaremathlabeltext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setareoperatorortext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setareprefixtext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setaresuffixtext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setaretaglabeltext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\setareunittext [1...] [2...OPT...]
1 SPRACHE
2 KEY = VALUE

```

```

\definelayer [1...] [2...] [3...OPT...]
1 NAME
2 NAME
3 inherits: \setuplayer

```

<pre> \definelaypreset [...] [...<sup>2</sup>...] 1 NAME 2 inherits: \setuplayer </pre>
<pre> \definelaypreset [...] [...<sup>2</sup>] 1 NAME 2 NAME </pre>
<pre> \definelayout [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazaaspect </pre>
<pre> \definelinefiller [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplinefiller </pre>
<pre> \definelinenote [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplinenote </pre>
<pre> \definelinenumbering [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazanumerotarelinii </pre>
<pre> \definelines [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazalinii </pre>
<pre> \definelistalternative [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplistalternative </pre>
<pre> \definelistextra [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplistextra </pre>
<pre> \definelow [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplow </pre>
<pre> \definelowhigh [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplowhigh </pre>
<pre> \definelowmidhigh [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplowmidhigh </pre>
<pre> \defineMPinstance [...] [...<sup>2</sup>] [...<sup>3</sup>...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupMPinstance </pre>

<pre> \definemarginblock [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmarginblock </pre>
<pre> \definemargindata [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmargindata </pre>
<pre> \definemarker [...] *  NAME </pre>
<pre> \definemathaccent ... .. 1  NAME 2  CHARACTER </pre>
<pre> \definemathalignment [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmathalignment </pre>
<pre> \definemathcases [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmathcases </pre>
<pre> \definemathcommand [...] [...] [...] [...] 1  NAME                      OPT      OPT      OPT 2  ord op bin rel open close punct alpha intern nothing limop nolog box 3  unu doi 4  BEFEHL \...##1 \...##1##2 </pre>
<pre> \definemathdoubleextensible [...] [...] [...] [...] 1  ambele vfenced          OPT 2  NAME 3  NUMMER 4  NUMMER </pre>
<pre> \definematematics [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmatematics </pre>
<pre> \definemathextensible [...] [...] [...] 1  reverse matematica text chemistry 2  NAME 3  NUMMER </pre>
<pre> \definemathfence [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmathfence </pre>
<pre> \definemathfraction [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmathfraction </pre>
<pre> \definemathframed [...] [...] [...] [...] 1  NAME                      OPT      OPT 2  NAME 3  inherits: \setupmathframed </pre>

<pre> \definemathmatrix [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupmathmatrix </pre>
<pre> \definemathornament [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupmathornament </pre>
<pre> \definemathoverextensible [...] [...] [...] 1 sus vfenced 2 NAME 3 NUMMER </pre>
<pre> \definemathovertextextensible [...] [...] [...] 1 bothtext 2 NAME 3 NUMMER </pre>
<pre> \definemathradical [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupmathradical </pre>
<pre> \definemathstackers [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupmathstackers </pre>
<pre> \definemathstyle [...] [...] 1 NAME 2 display text script scriptscript cramped uncramped normal impachetat mic mare </pre>
<pre> \definemathtriplet [...] [...] [...] 1 NAME 2 NAME 3 TEXT </pre>
<pre> \definemathunderextensible [...] [...] [...] 1 subsol vfenced 2 NAME 3 NUMMER </pre>
<pre> \definemathundertextextensible [...] [...] [...] 1 bothtext 2 NAME 3 NUMMER </pre>
<pre> \definemathunstacked [...] [...] [...] 1 larg 2 NAME 3 NUMMER </pre>
<pre> \definemeasure [...] [...] 1 NAME 2 DIMENSION </pre>
<pre> \definemessageconstant {...} * NAME </pre>

<pre> \definemixedcolumns [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupmixedcolumns </pre>
<pre> \definemode [...] [...] 1  NAME 2  da nu mentine </pre>
<pre> \definemultitonecolor [...] [...] [...] [...] 1  NAME 2  COLOR = NUMMER 3  inherits: \definesteculoare 4  inherits: \definespotcolor </pre>
<pre> \definenamecolor [...] [...] 1  NAME 2  inherits: \definesteculoare </pre>
<pre> \definenamecolor [...] [...] 1  NAME 2  COLOR </pre>
<pre> \definenamespace [...] [...] 1  NAME 2  nume = TEXT    parent = TEXT    stil = da nu    comanda = da nu lista    setup = da nu lista    set = da nu lista    frame = da nu </pre>
<pre> \definennarrower [...] [...] [...] 1  NAME 2  NAME 3  inherits: \seteazaingust </pre>
<pre> \definernote [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupnote </pre>
<pre> \defineornament [...] [...] [...] 1  NAME 2  alternativ = a b    inherits: \setupcollector 3  stil = STYLE BEFEHL    culoare = COLOR    inherits: \seteazainconjurat </pre>
<pre> \defineornament [...] [...] [...] 1  NAME 2  alternativ = a b    inherits: \setupplayer 3  inherits: \setuplayeredtext </pre>
<pre> \defineoutputroutine [...] [...] [...] 1  NAME 2  NAME 3  inherits: \setupoutputroutine </pre>
<pre> \defineoutputroutinecommand [...]*[...] *  KEY </pre>

<pre> \definepage [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definepagebreak [...] [...] 1 NAME 2 gol antet subsol dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadрупul ultim ultimpagina start stop </pre>
<pre> \definepagechecker [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagechecker </pre>
<pre> \definepagegrid [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagegrid </pre>
<pre> \definepagegridarea [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagegridarea </pre>
<pre> \definepagegridspan [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagegridspan </pre>
<pre> \definepageinjection [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppageinjection </pre>
<pre> \definepageinjectionalternative [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppageinjectionalternative </pre>
<pre> \definepageshift [...] [...] [...] 1 NAME 2 orizontal vertical 3 DIMENSION </pre>
<pre> \definepagestate [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppagestate </pre>
<pre> \definepairedbox [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setuppairedbox </pre>
<pre> \defineparagraph [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupparagraph </pre>
<pre> \defineparallel [...] [...] 1 NAME 2 NAME </pre>

<pre> \defineparbuilder [...] *   NAME </pre>
<pre> \defineplacement [...] [...] [...] [...] 1   NAME                OPT      OPT 2   NAME 3   inherits: \setupplacement </pre>
<pre> \definepositioning [...] [...] [...] 1   NAME                OPT      OPT 2   NAME 3   inherits: \setarepozitie </pre>
<pre> \defineprefixset [...] [...] [...] 1   NAME SECTIONBLOCK:NAME      OPT 2   ABSCHNITT 3   ABSCHNITT </pre>
<pre> \defineprocesscolor [...] [...] [...] 1   NAME                OPT 2   COLOR 3   inherits: \definesteculoare </pre>
<pre> \defineprocessor [...] [...] [...] 1   NAME                OPT      OPT 2   NAME 3   inherits: \setupprocessor </pre>
<pre> \definepushbutton [...] [...] 1   NAME                OPT 2   inherits: \setupfieldcontentframed </pre>
<pre> \definepushsymbol [...] [...] 1   NAME 2   n r d </pre>
<pre> \definerenderingwindow [...] [...] [...] 1   NAME                OPT      OPT 2   NAME 3   inherits: \setuprenderingwindow </pre>
<pre> \defineresetset [...] [...] [...] 1   NAME SECTIONBLOCK:NAME      OPT 2   NUMMER 3   NUMMER </pre>
<pre> \definescale [...] [...] [...] 1   NAME                OPT      OPT 2   NAME 3   inherits: \setupscale </pre>
<pre> \definescript [...] [...] [...] 1   NAME                OPT      OPT 2   NAME 3   inherits: \setupscript </pre>
<pre> \definesectionlevels [...] [...] 1   NAME 2   ABSCHNITT </pre>
<pre> \defineselector [...] [...] 1   NAME                OPT 2   inherits: \setupselector </pre>



```
\defineseparatorset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 BEFEHL PROCESSOR->BEFEHL
3 BEFEHL PROCESSOR->BEFEHL
```

```
\defineshift [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupshift
```

```
\definesidebar [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupsidebar
```

```
\definesort [...] [...] [...] {...}
1 da nu OPT
2 SINGULAR
3 NAME
4 CONTENT
```

```
\placelistoflogos [...] [...]
* inherits: \seteazasortare OPT
```

```
\definespotcolor [...] [...] [...]
1 NAME
2 COLOR
3 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
      difference exclusion hue saturation culoare luminosity
      t = NUMMER
      e = TEXT
      p = NUMMER
```

```
\defineste [...] \... {...}
1 NUMMER OPT
2 CSNAME
3 CONTENT
```

```
\definesteaccent ... ... ...
1 CHARACTER
2 CHARACTER
3 CHARACTER
```

```
\definesteantet [...] [...] [...]
1 NAME OPT OPT
2 ABSCHNITT
3 inherits: \seteazatitlu
```

```
\definestebloc [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \seteazabloc
```

```
\definesteblocsectione [...] [...] [...]
1 NAME OPT
2 NAME
3 inherits: \seteazablocsectione
```

```
\definestebuffer [...] [...] [...]
1 NAME OPT OPT
2 BUFFER
3 inherits: \seteazabuffer
```

```
\definestecamp [...] [...] [...] [...,4...] [...5]
1 NAME
2 radio sub text linie push check signature
3 NAME
4 NAME
5 NAME
```

```
\definestecaracter 1... 2...
1 CHARACTER
2 NUMMER
```

```
\definestecomanda 1... 2...
1 CHARACTER
2 BEFEHL
```

```
\definesteconversie [...] [2...] [3]
1 SPRACHE OPT
2 NAME
3 CSNAME
```

```
\definesteconversie [1...] [2...] [...,3...]
1 SPRACHE OPT
2 NAME
3 TEXT
```

```
\definesteculoare [1...] [...,2...,...]
1 NAME
2 r = NUMMER
g = NUMMER
b = NUMMER
c = NUMMER
m = NUMMER
y = NUMMER
k = NUMMER
h = NUMMER
s = NUMMER
v = NUMMER
x = NUMMER
a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
difference exclusion hue saturation culoare luminosity
t = NUMMER
```

```
\definesteculoare [1...] [2]
1 NAME
2 COLOR
```

```
\definestedescriere [1...] [2...] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupdescription
```

```
\definestedimensiunehartie [1...] [...,2...,...]
1 NAME
2 latime = DIMENSION
inaltime = DIMENSION
sus = BEFEHL
jos = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
distanta = DIMENSION
pagina = inherits: \seteazadimensiunihartie
hartie = inherits: \seteazadimensiunihartie
```

```
\definestedimensiunehartie [1...] [...,2...] [...,3...]
1 NAME OPT
2 inherits: \seteazadimensiunihartie
3 inherits: \seteazadimensiunihartie
```

```

\definesteenumerare [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupenumeration

```

```

\definesteeticheta [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplabel

```

```

\definestefloat [...] [...] [...]
1 SINGULAR OPT OPT
2 SINGULAR PLURAL
3 inherits: \seteazafloat
instances: chemical figure table intermezzo graphic

```

```

\definestefloat [...] [...] [...]
1 SINGULAR OPT OPT
2 PLURAL
3 SINGULAR
instances: chemical figure table intermezzo graphic

```

```

\definestefont [...] [...] [...]
1 NAME OPT
2 FONT
3 inherits: \seteazaspatiuinterliniar

```

```

\definestefonttext [...] [...] [...] [...]
1 NAME implicit OPT OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf = FILE
bf = FILE
it = FILE
sl = FILE
bi = FILE
bs = FILE
sc = FILE
mr = FILE
mrlr = FILE
mrrl = FILE
mb = FILE
mblr = FILE
mbrl = FILE

```

```

\definestefonttext [...] [...] [...] [...]
1 NAME implicit OPT OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME

```

```

\definestefont [...] [...] [...]
1 NAME OPT
2 FONT
3 NAME

```

```

\definesteformatreferinte [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupreferenceformat

```

```

\definestegrupculori [...] [...] [x:y:z,...]
1 NAME OPT
2 gri rgb cmyk spot
3 TRIPLET

```

<pre> \definestehbox [...] [...] 1  NAME 2  DIMENSION </pre>
<pre> \definesteinconjurare [...] [...] [...] [...] 1  NAME 2  NAME 3  inherits: \seteazainconjurat </pre>
<pre> \definestelista [...] [...] [...] 1  NAME 2  LISTE 3  inherits: \seteazalista </pre>
<pre> \definestelistacombinata [...] [...] [...] 1  NAME 2  LISTE 3  inherits: \seteazalista </pre>
<pre> \definestemakeup [...] [...] [...] 1  NAME 2  NAME 3  inherits: \seteazamakeup </pre>
<pre> \definestemarcaje [...] [...] [...] 1  NAME 2  BESCHRIFTUNG 3  inherits: \seteazamarcaje </pre>
<pre> \definestemediulfonttext [...] [...] [...] 1  NAME 2  implicit DIMENSION 3  mare = DIMENSION NUMMER    mic = DIMENSION NUMMER    a   = DIMENSION NUMMER    b   = DIMENSION NUMMER    c   = DIMENSION NUMMER    d   = DIMENSION NUMMER    text = DIMENSION NUMMER    x   = DIMENSION NUMMER    xx  = DIMENSION NUMMER    script = DIMENSION NUMMER    scriptscript = DIMENSION NUMMER    spatiereinterliniara = DIMENSION    em = inclinat italic STYLE BEFEHL    * = NUMMER </pre>
<pre> \definestemeniuinteractiune [...] [...] [...] 1  NAME 2  NAME 3  inherits: \seteazameniuinteractiune </pre>
<pre> \definesteoverlay [...] [...] [...] 1  NAME 2  NAME 3  BEFEHL </pre>
<pre> \definestepaleta [...] [...] 1  NAME 2  NAME = COLOR </pre>
<pre> \definestepaleta [...] [...] 1  NAME 2  NAME </pre>

<pre> \definesteparagraf [...] [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazaparafrage </pre>
<pre> \definesteprofil [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupprofile </pre>
<pre> \definesteprogram [...] [...] [...] 1 NAME OPT 2 TEXT 3 TEXT </pre>
<pre> \definestereferinte [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definesteregistru [...] [...] [...] 1 NAME OPT OPT 2 NAME 3 inherits: \seteazaregistru </pre>
<pre> \definestesablontabel [...] [ ... ] [...] [...] 1 NAME OPT OPT 2 TEMPLATE 3 NAME 4 NAME </pre>
<pre> \definestesectiune [...] * NAME </pre>
<pre> \definestesimbol [...] [...] [...] 1 NAME OPT 2 NAME 3 BEFEHL </pre>
<pre> \definestesimbolfigura [...] [...] [...] 1 NAME OPT 2 FILE NAME 3 inherits: \figuraexterna </pre>
<pre> \definestesinonim [...] [...] [...] [...] 1 SINGULAR OPT OPT 2 PLURAL 3 CSNAME 4 CSNAME </pre>
<pre> \definestesinonimfont [...] [...] [...] 1 NAME OPT 2 FONT 3 features = NAME   fallbacks = NAME   goodies = NAME   designsize = auto implicit </pre>
<pre> \definestesortare [...] [...] [...] 1 SINGULAR OPT 2 PLURAL 3 niciunul CSNAME </pre>

<pre> \definestestartstop [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupstartstop </pre>
<pre> \definestestil [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupstyle </pre>
<pre> \definestestilfont [...<sup>1</sup>,...] [...] 1 NAME 2 NAME </pre>
<pre> \definestestivacampuri [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupfieldcategory </pre>
<pre> \definestesubcamp [...] [...] [...] 1 NAME 2 NAME 3 NAME </pre>
<pre> \definestetabulatori [...] [...] [...] 1 NAME 2 NAME 3 TEMPLATE </pre>
<pre> \definestetext [...] [...] [...] [...] [...] [...] [...] 1 NAME 2 sus antet text subsol subsol 3 text margine bordura 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL 6 data numarpagina BESCHRIFTUNG TEXT BEFEHL 7 data numarpagina BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \definestetexteinconjugate [...<sup>1</sup>,...] [...] 1 NAME 2 inherits: \setupframedtext </pre>
<pre> \framedtext [...<sup>1</sup>,...] {...} 1 inherits: \setupframedtext 2 CONTENT </pre>
<pre> \definestetextinconjurat [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupframedtext </pre>
<pre> \definestetyping [...] [...] [...] 1 NAME 2 NAME 3 inherits: \seteazatyping </pre>
<pre> \definestyleinstance [...] [...] [...] [...] 1 NAME 2 rm ss tt mm hw cg 3 tf bf it sl bi bs sc 4 BEFEHL </pre>

<pre> \definesubformula [...] [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setupsbformula </pre>
<pre> \definesynonym [...] [...] [...] [...] 1 da nu 2 SINGULAR 3 NAME 4 TEXT 5 CONTENT </pre>
<pre> \placelistofabbreviations [...] [...] * inherits: \seteazasinonime </pre>
<pre> \definesystemattribute [...] [...] 1 NAME 2 local global public private </pre>
<pre> \definesystemconstant [...] * NAME </pre>
<pre> \definesystemvariable [...] * NAME </pre>
<pre> \defineTABLEsetup [...] [...] 1 NAME 2 inherits: \setupTABLE </pre>
<pre> \definetabulation [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptabulation </pre>
<pre> \definetextbackground [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptextflow </pre>
<pre> \definetooltip [...] [...] [...] 1 NAME 2 NAME 3 inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NUMBER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 a = NUMBER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten difference exclusion hue saturation culoare luminosity t = NUMBER </pre>
<pre> \definetransparency [...] [...] 1 NAME 2 NAME </pre>

`\definewopasslist {...}`

\* NAME

`\definetype [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \seteazatype

`\definetypeface [...1] [...2] [...3] [...4] [...5] [...6...]`

1 NAME

OPT

OPT

2 rm ss tt mm hw cg

3 serif sans mono math handwriting calligraphy

4 NAME

5 implicit dtp

6 rscale = auto NUMBER

features = NAME

fallbacks = NAME

goodies = NAME

designsize = auto implicit

directie = ambele

`\definetyescriptprefix [...1] [...2]`

1 NAME

2 TEXT

`\definetyescriptsynonym [...1] [...2]`

1 NAME

2 TEXT

`\definetyesetting [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 TEXT

3 inherits: \setupexternalfigure

`\defineunit [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \setupunit

`\defineviewerlayer [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \setupviewerlayer

`\definevspace [...1] [...2] [...3]`

1 NAME

OPT

2 NAME

3 DIMENSION

`\definevspacing [...1] [...2]`

1 NAME

2 inherits: \vspacing

`\definevspacingamount [...1] [...2] [...3]`

1 NAME

OPT

OPT

2 DIMENSION

3 DIMENSION

`\definetable [...1] [...2] [...3...]`

1 NAME

OPT

OPT

2 NAME

3 inherits: \setupxtable



<code>\delimited [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup></code> 1 NAME OPT 2 SPRACHE 3 CONTENT
<code>\delimitedtext [...]<sup>1</sup> [...]<sup>2</sup> {...}<sup>3</sup></code> 1 NAME OPT 2 SPRACHE 3 CONTENT
<code>\DELIMITEDTEXT [...]<sup>1</sup> {...}<sup>2</sup></code> 1 SPRACHE OPT 2 CONTENT instances: quotation quote blockquote speech aside
<code>\depthofstring {...}</code> * TEXT
<code>\depthonlybox {...}</code> * CONTENT
<code>\depthspanningtext {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1 TEXT 2 DIMENSION 3 FONT
<code>\DESCRIERE [...]<sup>1</sup>, [...] {...}<sup>2</sup> ...<sup>3</sup> \par</code> 1 REFERENCE OPT OPT 2 TEXT 3 CONTENT
<code>\despre [...]</code> * REFERENCE
<code>\determinacaracteristicilelistei [...]<sup>1</sup>, [...] [...]<sup>2</sup>, ..., [...]</code> 1 LISTE 2 inherits: \seteazalista OPT
<code>\determinacaracteristiciregistru [...]<sup>1</sup> [...]<sup>2</sup>, ..., [...]</code> 1 NAME OPT 2 language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc numberorder = numere compress = da nu tot criteriu = local text curent precedent tot ABSCHNITT
<code>\determinanumartitlu [...]</code> * ABSCHNITT
<code>\determinenoflines {...}</code> * CONTENT
<code>\devanagarinumerals {...}</code> * NUMMER
<code>\digits {...}</code> * NUMMER
<code>\digits ...</code> * NUMMER

<code>\dimensiontocount {<sup>1</sup>..} \<sup>2</sup>..</code> 1    DIMENSION 2    CSNAME
<code>\din [...]</code> *    REFERENCE
<code>\directboxfromcache {<sup>1</sup>..} {<sup>2</sup>..}</code> 1    NAME 2    NUMMER TEXT
<code>\directcolor [...]</code> *    COLOR
<code>\directcolored [...,<sup>*</sup>...,...]</code> *    inherits: \definesteculoare
<code>\directcolored [...]</code> *    COLOR
<code>\directconvertedcounter {<sup>1</sup>..} {<sup>2</sup>..}</code> 1    NAME 2    primul precedent urmatorul ultim numar
<code>\directcopyboxfromcache {<sup>1</sup>..} {<sup>2</sup>..}</code> 1    NAME 2    NUMMER TEXT
<code>\directdummysparameter {<sup>*</sup>..}</code> *    KEY
<code>\directgetboxllx ...</code> *    CSNAME NUMMER
<code>\directgetboxlly ...</code> *    CSNAME NUMMER
<code>\directhighlight {<sup>1</sup>..} {<sup>2</sup>..}</code> 1    NAME 2    TEXT
<code>\directlocalframed [...<sup>1</sup>..] {<sup>2</sup>..}</code> 1    NAME 2    CONTENT
<code>\directluacode {<sup>*</sup>..}</code> *    BEFEHL
<code>\directselect {<sup>1</sup>..} {<sup>2</sup>..} {<sup>3</sup>..} {<sup>4</sup>..} {<sup>5</sup>..} {<sup>6</sup>..}</code> 1    NAME 2    CONTENT 3    CONTENT 4    CONTENT 5    CONTENT 6    CONTENT
<code>\directsetbar {<sup>*</sup>..}</code> *    NAME

$\backslash\text{directsetup}$ {...} * NAME
$\backslash\text{directsymbol}$ {...} {...} 1 NAME 2 NAME
$\backslash\text{directvspacing}$ {...,*...} * inherits: \vspacing
$\backslash\text{dis}$ {...} * CONTENT
$\backslash\text{disabledirectives}$ [...,*...] * NAME
$\backslash\text{disableexperiments}$ [...,*...] * NAME
$\backslash\text{disablemode}$ [...,*...] * NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ [...,*...] * NAME
$\backslash\text{displaymath}$ {...} * CONTENT
$\backslash\text{displaymathematics}$ {...} * CONTENT
$\backslash\text{displaymessage}$ {...} * TEXT
$\backslash\text{distributedhsize}$ {...} {...} {...} 1 DIMENSION 2 DIMENSION 3 NUMMER
$\backslash\text{dividedsize}$ {...} {...} {...} 1 DIMENSION 2 DIMENSION 3 NUMMER
$\backslash\text{doadaptleftskip}$ {...} * da nu standard DIMENSION
$\backslash\text{doadaptrightskip}$ {...} * da nu standard DIMENSION

<code>\doaddfeature {...}</code> *    NAME
<code>\doassign [...]<sup>1</sup> [...]<sup>2</sup>...</code> 1    TEXT 2    KEY = VALUE
<code>\doassignempty [...]<sup>1</sup> [...]<sup>2</sup>...</code> 1    TEXT 2    KEY = VALUE
<code>\doboundtext {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    TEXT 2    DIMENSION 3    BEFEHL
<code>\docheckassignment {...}</code> *    TEXT
<code>\docheckedpagestate {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup> {...}<sup>6</sup> {...}<sup>7</sup></code> 1    REFERENCE 2    BEFEHL 3    BEFEHL 4    BEFEHL 5    BEFEHL 6    BEFEHL 7    BEFEHL
<code>\docheckedpair {...}<sup>*</sup>...</code> *    TEXT
<code>\documentvariable {...}</code> *    KEY
<code>\dodoubleargument \... [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1    CSNAME 2    TEXT 3    TEXT
<code>\dodoubleargumentwithset \... [...]<sup>1</sup> [...]<sup>2</sup>,... [...]<sup>3</sup></code> 1    CSNAME 2    TEXT 3    TEXT
<code>\dodoubleempty \... [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1    CSNAME                    OPT            OPT 2    TEXT 3    TEXT
<code>\dodoubleemptywithset \... [...]<sup>1</sup> [...]<sup>2</sup>,... [...]<sup>3</sup></code> 1    CSNAME                    OPT            OPT 2    TEXT 3    TEXT
<code>\dodoublegroupempty \... {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    CSNAME                    OPT            OPT 2    TEXT 3    TEXT
<code>\doeassign [...]<sup>1</sup> [...]<sup>2</sup>...</code> 1    TEXT 2    KEY = VALUE

\doexpandedrecurse {...} {...}

1 NUMMER  
2 BEFEHL

\dofastloopcs {...} \...

1 NUMMER  
2 CSNAME

\dogetattribute {...}

\* NAME

\dogetattributeid {...}

\* NAME

\dogetcommacommandelement ... \from ... \to ...

1 NUMMER  
2 TEXT  
3 CSNAME

\dogobbledoubleempty [...] [...]

1 TEXT  
2 TEXT

\dogobblesingleempty [...]

\* TEXT

\doif {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 TRUE

\doifallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifallcommonelse {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifalldefinedelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifallmodes {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifallmodeselse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifassignmentelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

`\doifblackelse {...} {...} {...}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifbothsides {...} {...} {...}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL

`\doifbothsidesoverruled {...} {...} {...}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL

`\doifboxelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifbufferelse {...} {...} {...}`

1 BUFFER  
2 TRUE  
3 FALSE

`\doifcolor {...} {...}`

1 COLOR  
2 TRUE

`\doifcolorelse {...} {...} {...}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifcommandhandler \... {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifcommon {...,1...} {...,2...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifcommonelse {...,1...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifcontent {...} {...} {...} \...4 {...5}`

1 BEFEHL  
2 BEFEHL  
3 BEFEHL  
4 CSNAME  
5 CONTENT

\doifconversiondefinedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifconversionnumberelse {...} {...} {...} {...}

1 NAME  
2 NUMBER  
3 TRUE  
4 FALSE

\doifcounter {...} {...}

1 NAME  
2 TRUE

\doifcounterelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifcurrentfonthasfeatureelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdefined {...} {...}

1 NAME  
2 TRUE

\doifdefinedcounter {...} {...}

1 NAME  
2 TRUE

\doifdefinedcounterelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdefinedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdimensionelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifdimenstringelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifdocumentargument {...} {...}

1 NAME  
2 TRUE

\doifdocumentargumentelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifdocumentfilename {...} {...}

1    NUMMER  
2    TRUE

\doifdocumentfilenameelse {...} {...} {...}

1    NUMMER  
2    TRUE  
3    FALSE

\doifdrawingblackelse {...} {...}

1    TRUE  
2    FALSE

\doifelse {...} {...} {...} {...}

1    CONTENT  
2    CONTENT  
3    TRUE  
4    FALSE

\doifelseallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>}

1    TEXT  
2    TEXT  
3    TRUE  
4    FALSE

\doifelsealldefined {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1    NAME  
2    TRUE  
3    FALSE

\doifelseallmodes {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1    NAME  
2    TRUE  
3    FALSE

\doifelseassignment {...} {...} {...}

1    TEXT  
2    TRUE  
3    FALSE

\doifelseblack {...} {...} {...}

1    COLOR  
2    TRUE  
3    FALSE

\doifelsebox {...} {...} {...} {...}

1    NAME  
2    NAME  
3    TRUE  
4    FALSE

\doifelseboxincache {...} {...} {...} {...}

1    NAME  
2    NUMMER TEXT  
3    TRUE  
4    FALSE

\doifelsebuffer {...} {...} {...}

1    BUFFER  
2    TRUE  
3    FALSE



\doifelsecolor {...} {...} {...}

1 COLOR  
2 TRUE  
3 FALSE

\doifelsecommandhandler {...} {...} {...} {...}

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelsecommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseconversiondefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsecounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsecurrentsortingused {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymshown {...} {...}

1 TRUE  
2 FALSE

\doifelsecurrentsynonymused {...} {...}

1 TRUE  
2 FALSE

\doifelsedefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedefinedcounter {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedimension {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsestring {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsedocumentargument {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsedocumentfilename {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

\doifelsedrawingblack {...} {...}

1 TRUE  
2 FALSE

\doifelseempty {...} {...} {...}

1 CONTENT  
2 TRUE  
3 FALSE

\doifelseemptyvalue {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

\doifelseenv {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\doifelsefastoptionalcheck {...} {...}

1 TRUE  
2 FALSE

\doifelsefastoptionalcheckcs \^1... \^2...

1 CSNAME  
2 CSNAME

\doifelsefieldbody {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefieldcategory {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefigure {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefiledefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefileexists {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefirstchar {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseflagged {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefontchar {...} {...} {...} {...}

1 FONT  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsefontpresent {...} {...} {...}

1 FONT  
2 TRUE  
3 FALSE

\doifelsefontsynonym {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsehasspace {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsehelp {...} {...}

1 TRUE  
2 FALSE

\doifelseincsname {...} {...} {...} {...}

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

\doifelseinelement {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinputfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseinsertion {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseinset {...} {...,<sup>2</sup>...} {...} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinstring {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseintoks {...} {...} {...} {...}

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseitalic {...} {...}

1 TRUE  
2 FALSE

\doifelselanguage {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifelselayerdata {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutdefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutsomeline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

`\doifelselayouttextline {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseleapyear {...} {...} {...}`

1 NUMMER  
2 TRUE  
3 FALSE

`\doifelselist {...} {...} {...}`

1 LISTE  
2 TRUE  
3 FALSE

`\doifelselocation {...} {...}`

1 TRUE  
2 FALSE

`\doifelselocfile {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsemainfloatbody {...} {...}`

1 TRUE  
2 FALSE

`\doifelsemarking {...} {...} {...}`

1 BESCHRIFTUNG  
2 TRUE  
3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

1 NAME  
2 NAME NUMMER  
3 TRUE  
4 FALSE

`\doifelsemode {...,1...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsenextbgroup {...} {...}`

1 TRUE  
2 FALSE

`\doifelsenextbgroupcs \1... \2...`

1 CSNAME  
2 CSNAME

`\doifelsenextchar {...} {...} {...}`

1 CHARACTER  
2 TRUE  
3 FALSE

`\doifelsenextoptional {...} {...}`

1 TRUE  
2 FALSE

`\doifelsenextoptionalcs \1... \2...`

1 CSNAME  
2 CSNAME

`\doifelsenextparenthesis {...} {...}`

1 TRUE  
2 FALSE

`\doifelsenonzeropositive {...} {...} {...}`

1 NUMMER  
2 TRUE  
3 FALSE

`\doifelsenoteonsamepage {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsenothing {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelsenumber {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelseobjectfound {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseobjectreferencefound {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseoddpage {...} {...}`

1 BEFEHL  
2 BEFEHL

`\doifelseoddpagefloat {...} {...}`

1 TRUE  
2 FALSE

`\doifelseoldercontext {...} {...} {...}`

1 NUMMER  
2 TRUE  
3 FALSE

\doifelseolderversion {...} {...} {...} {...}

1 NUMMER  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseoverlay {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseparallel {...} {...,<sup>2</sup>...} {...} {...}

1 NAME  
2 NAME tot  
3 TRUE  
4 FALSE

\doifelseparentfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsepath {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepathexists {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepatterns {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifelseposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositiononpage {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifelsepositionsonsamepage {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsonthispage {...<sup>1</sup>,...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsused {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserreferencefound {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelserightpagefloat {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserighttoleftinbox ... {...<sup>1</sup>} {...<sup>2</sup>}

1 CSNAME NUMBER  
2 TRUE  
3 FALSE

\doifelsesamelinereference {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelsesamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsesetups {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomebackground {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomespace {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesomething {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesometoks \... {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME  
2 TRUE  
3 FALSE

\doifelsestringinstring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE



\doifelsestructurelisthasnumber {...} {...}

1 TRUE  
2 FALSE

\doifelsestructurelisthaspage {...} {...}

1 TRUE  
2 FALSE

\doifelsesymboldefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesymbolset {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetext {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsetextflow {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetextflowcollector {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetypingfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseundefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseurldefined {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsevalue {...} {...} {...} {...}

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsevaluenothing {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsevariable {...} {...} {...} {...}

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

<pre> \doifempty {...} {...} 1  CONTENT 2  TRUE </pre>
<pre> \doifemptyelse {...} {...} {...} 1  CONTENT 2  TRUE 3  FALSE </pre>
<pre> \doifemptytoks \^1... {...} 1  CSNAME 2  TRUE </pre>
<pre> \doifemptyvalue {...} {...} 1  NAME 2  TRUE </pre>
<pre> \doifemptyvalueelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doifemptyvariable {...} {...} {...} 1  NAME 2  KEY 3  TRUE </pre>
<pre> \doifemptyvariableelse {...} {...} {...} {...} 1  NAME 2  KEY 3  TRUE 4  FALSE </pre>
<pre> \doifenv {...} {...} 1  KEY 2  TRUE </pre>
<pre> \doifenvelse {...} {...} {...} 1  KEY 2  TRUE 3  FALSE </pre>
<pre> \doiffastoptionalcheckcselse \^1... \^2... 1  CSNAME 2  CSNAME </pre>
<pre> \doiffastoptionalcheckelse {...} {...} 1  TRUE 2  FALSE </pre>
<pre> \doiffielddbodyelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>
<pre> \doiffielddcategoryelse {...} {...} {...} 1  NAME 2  TRUE 3  FALSE </pre>

`\doiffigureelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffile {...} {...}`

1 FILE  
2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffileexistseelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifflaggedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

1 FONT  
2 NUMMER  
3 TRUE  
4 FALSE

`\doiffontpresentelse {...} {...} {...}`

1 FONT  
2 TRUE  
3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifhasspaceelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifhelpelse {...} {...}`

1 TRUE  
2 FALSE

`\doifincsnameelse {...} {...} {...} {...}`

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

\doifinelementelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifinputfileelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifinsectionelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifinset {...} {...,<sup>2</sup>...} {...}

1 TEXT  
2 TEXT  
3 TRUE

\doifinsetelse {...} {...,<sup>2</sup>...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifinstring {...} {...<sup>2</sup>} {...}

1 TEXT  
2 TEXT  
3 TRUE

\doifinstringelse {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifinsymbolset {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifinsymbolsetelse {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifintokselse {...} {...} {...} {...}

1 BEFEHL  
2 BEFEHL  
3 TRUE  
4 FALSE

\doifintwopassdataelse {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifitalicelse {...} {...}

1 TRUE  
2 FALSE

\doiflanguageelse {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doiflayerdataelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiflayoutdefinedelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiflayoutsomelineelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doiflayouttextlineelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifleapyearelse {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doiflistelse {...} {...} {...}

1 LISTE  
2 TRUE  
3 FALSE

\doiflocationelse {...} {...}

1 TRUE  
2 FALSE

\doiflocfileelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifMPgraphicelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifmainfloatbodyelse {...} {...}

1 TRUE  
2 FALSE

\doifmarkingelse {...} {...} {...}

1 BESCHRIFTUNG  
2 TRUE  
3 FALSE

\doifmeaningelse \^1... \^2... {...} {...}

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

\doifmessageelse {...} {...} {...} {...}

1 NAME  
2 NAME NUMBER  
3 TRUE  
4 FALSE

\doifmode {...,<sup>1</sup>...} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifmodeelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifnextbgroupcselse \<sup>1</sup>... \<sup>2</sup>...

1 CSNAME  
2 CSNAME

\doifnextbgroupelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifnextcharelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CHARACTER  
2 TRUE  
3 FALSE

\doifnextoptionalcselse \<sup>1</sup>... \<sup>2</sup>...

1 CSNAME  
2 CSNAME

\doifnextoptionalelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifnextparenthesiselse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifnonzeropositiveelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NUMBER  
2 TRUE  
3 FALSE

\doifnot {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CONTENT  
2 CONTENT  
3 TRUE

\doifnotallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotallmodes {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

<pre> \doifnotcommandhandler \...<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> 1 CSNAME 2 NAME 3 TRUE </pre>
<pre> \doifnotcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...}<sup>3</sup> 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \doifnotcounter {...}<sup>1</sup> {...}<sup>2</sup> 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentargument {...}<sup>1</sup> {...}<sup>2</sup> 1 NAME 2 TRUE </pre>
<pre> \doifnotdocumentfilename {...}<sup>1</sup> {...}<sup>2</sup> 1 NUMBER 2 TRUE </pre>
<pre> \doifnotempty {...}<sup>1</sup> {...}<sup>2</sup> 1 CONTENT 2 TRUE </pre>
<pre> \doifnotemptyvalue {...}<sup>1</sup> {...}<sup>2</sup> 1 NAME 2 TRUE </pre>
<pre> \doifnotemptyvariable {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> 1 NAME 2 KEY 3 TRUE </pre>
<pre> \doifnotenv {...}<sup>1</sup> {...}<sup>2</sup> 1 KEY 2 TRUE </pre>
<pre> \doifnoteonsamepageelse {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotescollected {...}<sup>1</sup> {...}<sup>2</sup> 1 NAME 2 TRUE </pre>
<pre> \doifnotfile {...}<sup>1</sup> {...}<sup>2</sup> 1 FILE 2 TRUE </pre>
<pre> \doifnotflagged {...}<sup>1</sup> {...}<sup>2</sup> 1 NAME 2 TRUE </pre>
<pre> \doifnothing {...}<sup>1</sup> {...}<sup>2</sup> 1 TEXT 2 TRUE </pre>

`\doifnothingelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifnotinset {...} {...,2...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifnotinfloat {...}`

\* TRUE

`\doifnotinstring {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifnotmode {...,1...} {...}`

1 NAME  
2 TRUE

`\doifnotnumber {...} {...}`

1 TEXT  
2 TRUE

`\doifnotsamestring {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifnotsetups {...} {...}`

1 NAME  
2 TRUE

`\doifnotvalue {...} {...} {...}`

1 NAME  
2 TEXT  
3 TRUE

`\doifnotvariable {...} {...} {...}`

1 NAME  
2 KEY  
3 TRUE

`\doifnumber {...} {...}`

1 TEXT  
2 TRUE

`\doifnumberelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifobjectfoundelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE



\doifobjectreferencefoundelse {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifoddpagelse {...} {...}

1 BEFEHL  
2 BEFEHL

\doifoddpagefloatelse {...} {...}

1 TRUE  
2 FALSE

\doifoldercontextelse {...} {...} {...}

1 NUMMER  
2 TRUE  
3 FALSE

\doifolderversionelse {...} {...} {...} {...}

1 NUMMER  
2 NUMMER  
3 TRUE  
4 FALSE

\doifoverlappingelse {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifoverlayelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifparallelelse {...} {...,  
2,...} {...} {...}

1 NAME  
2 NAME tot  
3 TRUE  
4 FALSE

\doifparentfileelse {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifpathelse {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifpathexistseelse {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifpatternselse {...} {...} {...}

1 SPRACHE  
2 TRUE  
3 FALSE

\doifposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionactionelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME  
2 NUMMER  
3 TRUE  
4 FALSE

\doifpositionsonsamepageelse {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsonthispageelse {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsusedelse {...} {...}

1 TRUE  
2 FALSE

\doifreferencefoundelse {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifrightpagefloatelse {...} {...}

1 TRUE  
2 FALSE

\doifrighttoleftinboxelse <sup>1</sup>... {...} {...}

1 CSNAME NUMMER  
2 TRUE  
3 FALSE

\doifsamelinereferenceelse {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifsamestring {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE

\doifsamestringelse {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifsetups {...} {...}

1 NAME  
2 TRUE

\doifsetupselse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifsomebackground {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifsomebackgroundelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifsomespaceelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifsomething {...} {...}

1 TEXT  
2 TRUE

\doifsomethingelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifsometoks \... {...}

1 CSNAME  
2 TRUE

\doifsometokselse \... {...} {...}

1 CSNAME  
2 TRUE  
3 FALSE

\doifstringinstringelse {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifstructurelisthasnumberelse {...} {...}

1 TRUE  
2 FALSE

\doifstructurelisthaspageelse {...} {...}

1 TRUE  
2 FALSE

`\doifsymboldefinedelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doifsymbolsetelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftext {1.} {2.} {3.}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextelse {1.} {2.} {3.}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextflowcollectorelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftextflowelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftypingfileelse {1.} {2.} {3.}`

1 FILE  
2 TRUE  
3 FALSE

`\doifundefined {1.} {2.}`

1 NAME  
2 TRUE

`\doifundefinedcounter {1.} {2.}`

1 NAME  
2 TRUE

`\doifundefinedelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doifurldefinedelse {1.} {2.} {3.}`

1 NAME  
2 TRUE  
3 FALSE

`\doifvalue {1.} {2.} {3.}`

1 NAME  
2 TEXT  
3 TRUE

`\doifvalueelse {1.} {2.} {3.} {4.}`

1 NAME  
2 TEXT  
3 TRUE  
4 FALSE

<code>\doifvaluenothing {...} {...}</code> 1 NAME 2 TRUE
<code>\doifvaluenothingelse {...} {...} {...}</code> 1 NAME 2 TRUE 3 FALSE
<code>\doifvaluesomething {...} {...}</code> 1 NAME 2 TRUE
<code>\doifvariable {...} {...} {...}</code> 1 NAME 2 KEY 3 TRUE
<code>\doifvariableelse {...} {...} {...} {...}</code> 1 NAME 2 KEY 3 TRUE 4 FALSE
<code>\doindentation</code>
<code>\dollar</code>
<code>\doloop {...}</code> * BEFEHL
<code>\doloopoverlist {...,<sup>1</sup>...} {...}</code> 1 TEXT 2 BEFEHL
<code>\donothing</code>
<code>\dontconvertfont</code>
<code>\dontleavehmode</code>
<code>\dontpermitspacesbetweenegroups</code>
<code>\dopositionaction {...}</code> * NAME
<code>\doprocesslocalsetups {...,*...}</code> * NAME
<code>\doquadrupleargument \... [<sup>2</sup>...] [<sup>3</sup>] [<sup>4</sup>] [<sup>5</sup>]</code> 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT

`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`

1 CSNAME OPT OPT OPT OPT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`

1 CSNAME OPT OPT OPT OPT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`

1 CSNAME OPT OPT OPT OPT OPT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\doquintuplegroupempty \1... {2...} {3...} {4...} {5...} {6...}`

1 CSNAME OPT OPT OPT OPT OPT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\dorechecknextindentation`

`\dorecurse {1...} {2...}`

1 NUMMER  
2 BEFEHL

`\dorepeatwithcommand [1...] \2...`

1 TEXT NUMMER\*TEXT  
2 CSNAME

`\doreplacefeature {*...}`

\* NAME

`\doresetandafffeature {*...}`

\* NAME

`\doresetattribute {*...}`

\* NAME

`\dorotatebox {1...} \2... {3...}`

1 NUMMER  
2 CSNAME  
3 CONTENT

`\dosetattribute {1...} {2...}`

1 NAME  
2 NUMMER

`\dosetleftskipadaption {...}`

\* da nu standard DIMENSION

`\dosetrighskipadaption {...}`

\* da nu standard DIMENSION

`\dosetupcheckedinterlinespace {...,*=...}`

\* inherits: \seteazaspatiuinterliniar

`\dosetupcheckedinterlinespace {...,*...}`

\* on dezactivat reset auto mic mediu mare NUMMER DIMENSION

`\dosetupcheckedinterlinespace {...}`

\* NAME

`\doseventupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...] [8...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT

`\doseventupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...] [8...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT  
8 TEXT

`\dosingleargument \1... [2...]`

1 CSNAME  
2 TEXT

`\dosingleempty \1... [2...]`

1 CSNAME  
2 TEXT

`\dosinglegroupempty \1... {2...}`

1 CSNAME  
2 TEXT

`\dosixtupleargument \1... [2...] [3...] [4...] [5...] [6...] [7...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT

`\dosixtupleempty \1... [2...] [3...] [4...] [5...] [6...] [7...]`

1 CSNAME  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT  
7 TEXT

$\backslash\text{dostarttagged} \{.^1.\} \{.^2.\} \dots \backslash\text{dostoptagged}$ 1 NAME 2 NAME
$\backslash\text{dostepwiserecurse} \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 NUMBER 2 NUMBER 3 [-+]NUMBER 4 BEFEHL
$\backslash\text{dosubtractfeature} \{.^*.\}$ * NAME
$\backslash\text{dotfskip} \{.^*.\}$ * DIMENSION
$\backslash\text{dotoks} \backslash.^*.$ * CSNAME
$\backslash\text{dotripleargument} \backslash.^1. [.^2.] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleargumentwithset} \backslash.^1. [...,^2...] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleempty} \backslash.^1. [.^2.] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleemptywithset} \backslash.^1. [...,^2...] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotriplegroupempty} \backslash.^1. \{.^2.\} \{.^3.\} \{.^4.\}$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{doublebar} \{.^*.\}$ * TEXT
$\backslash\text{doublebond}$
$\backslash\text{doublebrace} \{.^*.\}$ * TEXT
$\backslash\text{doublebracket} \{.^*.\}$ * TEXT
$\backslash\text{doubleparent} \{.^*.\}$ * TEXT



<code>\dowith {...<sup>1</sup>,...} {...<sup>2</sup>}</code> 1 BEFEHL 2 BEFEHL
<code>\dowithnextbox {...<sup>1</sup>} \... {...<sup>3</sup>}</code> 1 BEFEHL 2 CSNAME 3 CONTENT
<code>\dowithnextboxcontent {...<sup>1</sup>} {...<sup>2</sup>} \... {...<sup>4</sup>}</code> 1 BEFEHL 2 BEFEHL 3 CSNAME 4 CONTENT
<code>\dowithnextboxcontentcs \... \... \... {...<sup>4</sup>}</code> 1 CSNAME 2 CSNAME 3 CSNAME 4 CONTENT
<code>\dowithnextboxcs \... \... {...<sup>3</sup>}</code> 1 CSNAME 2 CSNAME 3 CONTENT
<code>\dowithpargument \*...</code> * CSNAME
<code>\dowithrange {...<sup>1</sup>,...} \...<sup>2</sup></code> 1 NUMMER NUMMER:NUMMER 2 CSNAME
<code>\dowithwargument \*...</code> * CSNAME
<code>\dpofstring {...<sup>*</sup>}</code> * TEXT
<code>\dreapta ...<sup>*</sup></code> * CHARACTER
<code>\dummydigit</code>
<code>\dummyparameter {...<sup>*</sup>}</code> * KEY
<code>\dute {...<sup>1</sup>} [...<sup>2</sup>]</code> 1 CONTENT 2 REFERENCE
<code>\dutebox {...<sup>1</sup>} [...<sup>2</sup>]</code> 1 CONTENT 2 REFERENCE
<code>\dutepagina {...<sup>1</sup>} [...<sup>2</sup>]</code> 1 TEXT 2 REFERENCE
<code>\ETEX</code>

<code>\EveryLine {...}</code> *   BEFEHL
<code>\EveryPar {...}</code> *   BEFEHL
<code>\ecran [...,*,...]</code> *   inherits: <sup>OPT</sup> pagina
<code>\edefconvertedargument \<sup>1</sup>... {\<sup>2</sup>...}</code> 1   CSNAME 2   TEXT
<code>\efcmaxheight {...}</code> *   NAME
<code>\efcmaxwidth {...}</code> *   NAME
<code>\efcminheight {...}</code> *   NAME
<code>\efcminwidth {...}</code> *   NAME
<code>\efcparameter {\<sup>1</sup>...} {\<sup>2</sup>...}</code> 1   NAME 2   KEY
<code>\effect [\<sup>1</sup>...] {\<sup>2</sup>...}</code> 1   NAME 2   CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {\<sup>1</sup>...} {\<sup>2</sup>...}</code> 1   TEXT <sup>OPT</sup> <sup>OPT</sup> 2   TEXT
<code>\leftharpoondownfill {\<sup>1</sup>...} {\<sup>2</sup>...}</code> 1   TEXT <sup>OPT</sup> <sup>OPT</sup> 2   TEXT
<code>\leftharpoonupfill {\<sup>1</sup>...} {\<sup>2</sup>...}</code> 1   TEXT <sup>OPT</sup> <sup>OPT</sup> 2   TEXT
<code>\leftrightarrowfill {\<sup>1</sup>...} {\<sup>2</sup>...}</code> 1   TEXT <sup>OPT</sup> <sup>OPT</sup> 2   TEXT
<code>\element [...,*,...]</code> *   REFERENCE <sup>OPT</sup>
<code>\emphasisboldface</code>

<code>\emphasistypeface</code>
<code>\emptylines [...]</code> *    NUMMER            OPT
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code> *    NAME
<code>\enableexperiments [...,*,...]</code> *    NAME
<code>\enablemode [...,*,...]</code> *    NAME
<code>\enableoutputstream [...]</code> *    NAME
<code>\enableparpositions</code>
<code>\enableregime [...]</code> *    cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows
<code>\enabletrackers [...,*,...]</code> *    NAME
<code>\enskip</code>
<code>\enspace</code>
<code>\ENUMERARE [...,<sup>1</sup>...] {...<sup>2</sup>} ...<sup>3</sup> \par</code> 1    REFERENCE            OPT            OPT 2    TEXT 3    CONTENT
<code>\env {...}</code> *    KEY
<code>\envvar {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    KEY 2    BEFEHL
<code>\eoverbarfill {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    TEXT                    OPT            OPT 2    TEXT
<code>\eoverbracefill {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    TEXT                    OPT            OPT 2    TEXT
<code>\eoverbracketfill {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    TEXT                    OPT            OPT 2    TEXT

$\backslash\text{eoverparentfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{epos}$ $\{...\}^*$ *    NAME
$\backslash\text{equaldigits}$ $\{...\}^*$ *    TEXT
$\backslash\text{erightarrowfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{erightharpoondownfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{erightharpoonupfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eTeX}$
$\backslash\text{ETICHETA}$ $[...,\dots]^1 \{...\}^2$ 1    REFERENCE            OPT            OPT 2    TEXT
$\backslash\text{etwoheadrightarrowfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderbarfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderbracefill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderbracketfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{eunderparentfill}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{executeifdefined}$ $\{...\}^1 \{...\}^2$ 1    NAME 2    BEFEHL
$\backslash\text{exitloop}$
$\backslash\text{exitloopnow}$
$\backslash\text{expandcheckedcsname}$ $\backslash.^1 \{...\}^2 \{...\}^3$ 1    CSNAME 2    KEY 3    TEXT

<code>\expanded {...}</code> *    CONTENT
<code>\expandfontsynonym \<sup>1</sup>... {<sup>2</sup>...}</code> 1    CSNAME 2    NAME
<code>\expdoif {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1    CONTENT 2    CONTENT 3    TRUE
<code>\expdoifcommonelse {<sup>1</sup>...,<sup>1</sup>...} {<sup>2</sup>...,<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\expdoifelse {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1    CONTENT 2    CONTENT 3    TRUE 4    FALSE
<code>\expdoifelsecommon {<sup>1</sup>...,<sup>1</sup>...} {<sup>2</sup>...,<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\expdoifelseinset {<sup>1</sup>...} {<sup>2</sup>...,<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\expdoifinsetelse {<sup>1</sup>...} {<sup>2</sup>...,<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\expdoifnot {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1    CONTENT 2    CONTENT 3    TRUE
<code>\externalfigurecollectionmaxheight {...}</code> *    NAME
<code>\externalfigurecollectionmaxwidth {...}</code> *    NAME
<code>\externalfigurecollectionminheight {...}</code> *    NAME
<code>\externalfigurecollectionminwidth {...}</code> *    NAME
<code>\externalfigurecollectionparameter {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NAME 2    KEY

\fakebox ... * CSNAME NUMMER
\faraliniiantetsisubsol
\faraliniisussijos
\faraspatiu
\fastdecrement ... * CSNAME
\fastincrement ... * CSNAME
\fastlocalframed [...] [...] [...] {} 1 NAME 2 inherits: \seteazainconjurat 3 CONTENT
\fastloopfinal
\fastloopindex
\fastscale [...] {} 1 NUMMER 2 CONTENT
\fastsetup {} * NAME
\fastsetupwithargument [...] {} 1 NAME 2 CONTENT
\fastsetupwithargumentswapped [...] {} 1 CONTENT 2 NAME
\fastswitchtobodyfont {} * x xx mic mare script scriptscript
\fastsxsy [...] {} {} 1 NUMMER 2 NUMMER 3 CONTENT
\feature [...] [] 1 + - = ! > < more less nou reset implicit old local 2 NAME
\feature [...] {} 1 + - = ! > < more less nou reset implicit old local 2 NAME
\fence

<code>\fenced [...]{...}</code> 1 NAME 2 CONTENT
<code>\FENCE {...}</code> * CONTENT
<code>\fetchallmarkings [...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME
<code>\fetchallmarks [...]</code> * BESCHRIFTUNG
<code>\fetchmark [...][...]</code> 1 BESCHRIFTUNG OPT 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchmarking [...][...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchonemark [...][...]</code> 1 BESCHRIFTUNG OPT 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchonemarking [...][...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchruntimecommand \...{...}</code> 1 CSNAME 2 FILE
<code>\fetchtwomarkings [...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME
<code>\fetchtwomarks [...]</code> * BESCHRIFTUNG
<code>\fieldbody [...][...<sup>2</sup>...]</code> 1 NAME OPT 2 inherits: \setupfieldbody
<code>\fifthoffivearguments {...}{...}{...}{...}{...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT

```
\fifthofsixarguments {1...} {2...} {3...} {4...} {5...} {6...}
1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT
```

```
\figuraexterna [...] [...] [...] [...] [...]
1 FILE OPT OPT
2 NAME
3 inherits: \setupexternalfigure
```

<code>\figurefilename</code>
------------------------------

<code>\figurefilepath</code>
------------------------------

<code>\figurefiletype</code>
------------------------------

<code>\figurefullname</code>
------------------------------

<code>\figureheight</code>
----------------------------

<code>\figurenaturalheight</code>
-----------------------------------

<code>\figurenaturalwidth</code>
----------------------------------

```
\figuresymbol [..1.] [...2...]  
1 FILE NAME OPT  
2 inherits: \figuraexterna
```

```
\figurewidth
```

```
\filename {...}
* FILE
```

\filledhboxb ... {...}		
1	TEXT	OPT
2	CONTENT	

\filledhboxc ... {...}	
1	TEXT OPT
2	CONTENT

\filledhboxg <sup>1</sup> ... { <sup>2</sup> ...}	
1	TEXT OPT
2	CONTENT

<pre> \filledhboxk ... {...} 1  TEXT          OPT 2  CONTENT </pre>
---

<pre> \filledhboxm ... {...} 1  TEXT          OPT 2  CONTENT </pre>
---

\filledhboxr ... {...}	
1	TEXT OPT
2	CONTENT



\filledhboxy <sup>1</sup>... {<sup>2</sup>...}

1 TEXT OPT  
2 CONTENT

\filler [...]

\* sym simbol rigla latime spatiu NAME

\filterfromnext {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} {<sup>6</sup>...} {<sup>7</sup>...}

1 NUMBER OPT  
2 NUMBER OPT  
3 CONTENT OPT  
4 CONTENT OPT  
5 CONTENT OPT  
6 CONTENT OPT  
7 CONTENT OPT

\filterfromvalue {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 NUMMER  
3 NUMMER

\filterpages [<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...]  
OPT

1 FILE  
2 par impar NUMBER NUMBER:NUMBER  
3 latime = DIMENSION  
n = NUMMER  
category = NAME

\filterreference {<sup>\*</sup>...}

\* implicit text titlu numar pagina realpage

\findtwopassdata {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 NAME

\finishregisterentry [<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...]  
OPT

1 NAME  
2 eticheta = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
alternativ = TEXT  
3 KEY = VALUE

\firdepar

\firstcharacter

\firstcounter [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME OPT  
2 NUMMER

\firstcountervalue [<sup>\*</sup>...]

\* NAME

\firstoffivearguments {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

\firstoffourarguments {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\firstofoneargument {...} * TEXT
\firstofoneunexpanded {...} * TEXT
\firstofsixarguments {...} {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
\firstofthreearguments {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\firstofthreeunexpanded {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT
\firstoftwoarguments {...} {...} 1 TEXT 2 TEXT
\firstoftwounexpanded {...} {...} 1 TEXT 2 TEXT
\firstrealpage
\firstrealpagenumber
\firstsubcountervalue [...] [...] 1 NAME 2 NUMBER
\firstsubpagenumber
\firstuserpage
\firstuserpagenumber
\fitfieldframed [... <sup>1</sup> ...,...] {...} 1 inherits: \seteazainconjunctat 2 CONTENT
\fittopbaselinegrid {...} * CONTENT

\* NAME

```
* inherits: \seteazalista OPT
```

```
* inherits: \seteazalista
```

```
* inherits: \seteazalista OPT
```

```
* inherits: \seteazalista OPT
```

```
* inherits: \seteazalista OPT
```

\* KEY

\* CSNAME NUMMER

\* NAME

---

\* NAME

\* NAME

\_\_\_\_\_

\* NAME

\* NAME

\* CSNAME

```

1      NAME                                OPT                                OPT
2      NAME
3      criteriu = text ABSCHNITT

```

\* PATH

```

1  NAME
2  FILE
3  TEXT

```

```

1  NAME                                OPT          OPT
2  FILE
3  NAME
4  inherits: \setuexternalfigure

```

```
1  m p s x t          OPT                                OPT
2  FILE
3  KEY = VALUE
```

1	NAME
2	FILE

```

1  FILE                                OPT
2  NAME

```

\* FILE

1	NAME	OPT	OPT
2	URL		
3	FILE		
4	TEXT		

1	NAME	OPT	OPT
2	URL		
3	FILE		
4	TEXT		

\fontbody

\* NAME

\* NUMMER

```

1  NAME
2  FONT

```

96

<code>\fontfeaturelist [...]<sup>1</sup> [...]</code> 1 NAME 2 TEXT
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [...]<sup>1</sup>,...<sup>2</sup> {...}</code> 1 REFERENCE OPT 2 TEXT
<code>\footnotetext [...]<sup>*</sup>,...<sup>*</sup>,...]</code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [...]<sup>1</sup> [...]<sup>2</sup>,...]</code> 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\formula [...]<sup>1</sup>,...<sup>2</sup> {...}</code> 1 impachetat tight centru incadrat inherits: \seteazafonttext 2 CONTENT
<code>\foundbox {...}<sup>1</sup> {...}<sup>2</sup></code> 1 NAME 2 NAME
<code>\fourthoffivearguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fourthoffourarguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\fourthofsixarguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup> {...}<sup>6</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT

$\backslash FRACTION$ {...} {...} 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash framed$ [... $\frac{1}{2}$ ...] {...} 1 inherits: \seteazainconjurat <sup>OPT</sup> 2 CONTENT
$\backslash frameddimension$ {...} * KEY
$\backslash framedparameter$ {...} * KEY
$\backslash FRAMED$ [... $\frac{1}{2}$ ...] {...} 1 inherits: \seteazainconjurat <sup>OPT</sup> 2 CONTENT instances: unframed fitfieldframed
$\backslash fitfieldframed$ [... $\frac{1}{2}$ ...] {...} 1 inherits: \seteazainconjurat <sup>OPT</sup> 2 CONTENT
$\backslash unframed$ [... $\frac{1}{2}$ ...] {...} 1 inherits: \seteazainconjurat <sup>OPT</sup> 2 CONTENT
$\backslash freezedimenmacro$ \ <sup>1</sup> ... \ <sup>2</sup> ... 1 CSNAME 2 CSNAME
$\backslash freezemeasure$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 DIMENSION
$\backslash frenchspacing$
$\backslash fromlinenote$ [ <sup>1</sup> ...] {...} 1 REFERENCE 2 TEXT
$\backslash frozenhbox$ {...} * CONTENT
$\backslash fundal$ {...} * CONTENT
$\backslash FUNDAL$ {...} * CONTENT instances: fundal
$\backslash GetPar$
$\backslash GotoPar$
$\backslash Greeknumerals$ {...} * NUMMER

\gdefconvertedargument \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 TEXT
\gdefconvertedcommand \ <sup>1</sup> ... \ <sup>2</sup> ... 1 CSNAME 2 CSNAME
\getboxfromcache { <sup>1</sup> ...} { <sup>2</sup> ...} <sup>3</sup> ... 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER
\getboxllx <sup>*</sup> ... * CSNAME NUMMER
\getboxlly <sup>*</sup> ... * CSNAME NUMMER
\getbufferdata [ <sup>*</sup> ...] * BUFFER OPT
\getcommacommandsize [... <sup>*</sup> ,...] * BEFEHL
\getcommalistsize [... <sup>*</sup> ,...] * BEFEHL
\getdayoftheweek { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NUMMER 2 NUMMER 3 NUMMER
\getdayspermonth { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NUMMER 2 NUMMER
\getdefinedbuffer [ <sup>*</sup> ...] * BUFFER
\getdocumentargument { <sup>*</sup> ...} * NAME
\getdocumentargumentdefault { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 TEXT
\getdocumentfilename { <sup>*</sup> ...} * NUMMER
\getdummyparameters [... <sup>*</sup> ...=...,...] * KEY = VALUE
\getemptyparameters [ <sup>1</sup> ...] [... <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE

<code>\getparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getexpandedparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getfiguredimensions [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 FILE <span style="float: right;">OPT</span> 2 inherits: \setupexternalfigure
<code>\getfirstcharacter {...}</code> * TEXT
<code>\getfirsttwopassdata {...}</code> * NAME
<code>\getfromcommacommand [...]<sup>1</sup>,... [...]<sup>2</sup>]</code> 1 BEFEHL 2 NUMMER
<code>\getfromcommalist [...]<sup>1</sup>,... [...]<sup>2</sup>]</code> 1 BEFEHL 2 NUMMER
<code>\getfromtwopassdata {...}<sup>1</sup> {...}<sup>2</sup>]</code> 1 NAME 2 NAME
<code>\getglyphdirect {...}<sup>1</sup> {...}<sup>2</sup>]</code> 1 FONT 2 NUMMER CHARACTER
<code>\getglyphstyled {...}<sup>1</sup> {...}<sup>2</sup>]</code> 1 FONT 2 NUMMER CHARACTER
<code>\getgparameters [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getlasttwopassdata {...}</code> * NAME
<code>\getlocalfloat {...}</code> * NUMMER
<code>\getlocalfloats</code>
<code>\getMPdrawing</code>
<code>\getMPlayer [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>3</sup>]</code> 1 NAME <span style="float: right;">OPT</span> 2 inherits: \setezainconjurat 3 CONTENT



<pre> \getmessage {...} {...} 1  NAME 2  NAME NUMBER </pre>
<pre> \getnamedglyphdirect {...} {...} 1  FONT 2  NAME </pre>
<pre> \getnamedglyphstyled {...} {...} 1  FONT 2  NAME </pre>
<pre> \getnamedtwopassdatalist \... {...} 1  CSNAME 2  NAME </pre>
<pre> \getnaturaldimensions ... *  CSNAME NUMBER </pre>
<pre> \getnoflines {...} *  DIMENSION </pre>
<pre> \getobject {...} {...} 1  NAME 2  NAME </pre>
<pre> \getobjectdimensions {...} {...} 1  NAME 2  NAME </pre>
<pre> \getpaletsize [...] *  NAME </pre>
<pre> \getparameters [...] [..., ...<sup>2</sup>..., ...] 1  TEXT 2  KEY = VALUE </pre>
<pre> \getprivatechar {...} *  NAME </pre>
<pre> \getprivateslot {...} *  NAME </pre>
<pre> \getrandomcount \... {...} {...} 1  CSNAME 2  NUMMER 3  NUMMER </pre>
<pre> \getrandomdimen \... {...} {...} 1  CSNAME 2  DIMENSION 3  DIMENSION </pre>
<pre> \getrandomfloat \... {...} {...} 1  CSNAME 2  NUMMER 3  NUMMER </pre>

\getrandomnumber \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CSNAME 2 NUMMER 3 NUMMER
\getrandomseed \*.. * CSNAME
\getraweparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getrawgparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getrawnoflines {...} * DIMENSION
\getrawparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getrawxparameters [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
\getreference [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 implicit text titlu numar pagina realpage 2 REFERENCE
\getreferenceentry {...} * implicit text titlu numar pagina realpage
\getroundednoflines {...} * DIMENSION
\getsubstring { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NUMMER 2 NUMMER 3 TEXT
\gettwopassdata {...} * NAME
\gettwopassdatalist {...} * NAME
\getuvalue {...} * NAME
\getvalue {...} * NAME
\getvariable { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 KEY

<pre> \getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL </pre>
<pre> \getxparameters [...]<sup>1</sup> [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \globaldisablemode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalenablemode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalletempty \*... * CSNAME </pre>
<pre> \globalpopbox ... * CSNAME NUMBER </pre>
<pre> \globalpopmacro \*... * CSNAME </pre>
<pre> \globalpreventmode [...,<sup>*</sup>...] * NAME </pre>
<pre> \globalprocesscommalist [...]<sup>1</sup> \*...<sup>2</sup> 1 BEFEHL 2 CSNAME </pre>
<pre> \globalpushbox ... * CSNAME NUMBER </pre>
<pre> \globalpushmacro \*... * CSNAME </pre>
<pre> \globalpushreferenceprefix {...}<sup>*</sup> ... \globalpopreferenceprefix * + - TEXT </pre>
<pre> \globalswapcounts \*... \*...<sup>1</sup> \*...<sup>2</sup> 1 CSNAME 2 CSNAME </pre>
<pre> \globalswapdimens \*... \*...<sup>1</sup> \*...<sup>2</sup> 1 CSNAME 2 CSNAME </pre>
<pre> \globalswapmacros \*... \*...<sup>1</sup> \*...<sup>2</sup> 1 CSNAME 2 CSNAME </pre>
<pre> \globalundefine {...} * NAME </pre>
<pre> \glyphfontfile {...} * FONT </pre>

\gobbledoubleempty [...<sup>1</sup>] [...<sup>2</sup>]

1 TEXT OPT OPT  
2 TEXT

\gobbleeightarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>} {...<sup>8</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT

\gobblefivearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT

\gobblefiveoptionals [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>] [...<sup>5</sup>]

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

\gobblefourarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT

\gobblefouroptionals [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

\gobbleninearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>} {...<sup>8</sup>} {...<sup>9</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT

\gobbleoneargument {...<sup>\*</sup>}

\* CONTENT

\gobbleoneoptional [...<sup>\*</sup>]

\* TEXT

\gobblesevenarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} {...<sup>7</sup>}

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT

* TEXT	OPT
1. The first part of the report is a summary of the findings.	
2. The second part of the report is a detailed description of the methodology.	
3. The third part of the report is a discussion of the results.	
4. The fourth part of the report is a conclusion.	
5. The fifth part of the report is a list of references.	
6. The sixth part of the report is an appendix.	
7. The seventh part of the report is a glossary.	
8. The eighth part of the report is a bibliography.	
9. The ninth part of the report is a table of contents.	
10. The tenth part of the report is a list of figures.	

1	CONTENT
2	CONTENT
3	CONTENT
4	CONTENT
5	CONTENT
6	CONTENT

1	CONTENT
2	CONTENT
3	CONTENT
4	CONTENT
5	CONTENT
6	CONTENT
7	CONTENT
8	CONTENT
9	CONTENT
10	CONTENT

1 CONTENT  
2 CONTENT  
3 CONTENT

1	TEXT
2	TEXT
3	TEXT

1 CONTENT  
2 CONTENT

1	TEXT
2	TEXT

\* CSNAME

\* CONTENT

```

1  CATEGORY                                OPT
2  NAME
3  NAME
4  NAME

```

1	NAME
2	NAME
3	NAME

```

1  NAME
2  CSNAME

```

<code>\grave {...}</code> * CHARACTER
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring .<sup>1</sup> \at .<sup>2</sup> \to \.<sup>3</sup> \and \.<sup>4</sup></code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMBER
<code>\grid [...,<sup>*</sup>...,...]</code> * inherits: <del>base</del> grid
<code>\grosimelinie</code>
<code>\groupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\gsetboxllx .<sup>1</sup> {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gsetboxlly .<sup>1</sup> {...}</code> 1 CSNAME NUMBER 2 DIMENSION
<code>\gujaratinumerals {...}</code> * NUMBER
<code>\gurmukhinumerals {...}</code> * NUMBER
<code>\hairspace</code>
<code>\halfwaybox {...}</code> * CONTENT
<code>\handletokens .<sup>1</sup> \with \.<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1 REFERENCE 2 CONTENT

<code>\hboxBOX {...}</code> *   CONTENT
<code>\hdofstring {...}</code> *   TEXT
<code>\headhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT       OPT 2   CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox <sup>1</sup>... {<sup>2</sup>...}</code> 1   TEXT       OPT 2   CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring {...}</code> *   TEXT
<code>\heightofstring {...}</code> *   TEXT
<code>\heightspanningtext {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   TEXT 2   DIMENSION 3   FONT
<code>\HELP [<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...}</code> 1   REFERENCE 2   TEXT 3   TEXT instances: helptext
<code>\hglue ...</code> *   DIMENSION
<code>\hiddencitation [...]</code> *   REFERENCE

<code>\hiddencite [...]</code> *    REFERENCE
<code>\highlight [...]<sup>1</sup> {...}<sup>2</sup></code> 1    NAME 2    TEXT
<code>\HIGHLIGHT {...}</code> *    TEXT
<code>\highordinalstr {...}</code> *    TEXT
<code>\hilo [...]<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    stanga <sup>OPT</sup> dreapta 2    CONTENT 3    CONTENT
<code>\himilo {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup></code> 1    CONTENT 2    CONTENT 3    CONTENT
<code>\hl [...]</code> *    NUMBER
<code>\horizontalgrowingbar [...,..<sup>*</sup>...,...]</code> *    inherits: \setuppositionbar
<code>\horizontalpositionbar [...,..<sup>*</sup>...,...]</code> *    inherits: \setuppositionbar
<code>\hphantom {...}</code> *    CONTENT
<code>\hpos {...}<sup>1</sup> {...}<sup>2</sup></code> 1    NAME 2    CONTENT
<code>\hsizefraction {...}<sup>1</sup> {...}<sup>2</sup></code> 1    DIMENSION 2    NUMBER
<code>\hsmash {...}</code> *    CONTENT
<code>\hsmashbox ...</code> *    CSNAME NUMBER
<code>\hsmashed {...}</code> *    CONTENT
<code>\hspace [...]<sup>1</sup> [...]<sup>2</sup></code> 1    NAME        OPT        OPT 2    mic mediu mare normal implicit niciunul .5 1 2 3 speech minicitat interquotation citat sentence intersentence NAME
<code>\htdpofstring {...}</code> *    TEXT



<code>\htofstring {...}</code> * TEXT
<code>\hyphen</code>
<code>\hyphenatedcoloredword {...}</code> * TEXT
<code>\hyphenatedfile {...}</code> * FILE
<code>\hyphenatedfilename {...}</code> * TEXT
<code>\hyphenatedhbox {...}</code> * CONTENT
<code>\hyphenatedpar {...}</code> * TEXT
<code>\hyphenatedurl {...}</code> * TEXT
<code>\hyphenatedword {...}</code> * TEXT
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1 TRUE 2 FALSE
<code>\iftruetypeetting ...<sup>1</sup> \else ...<sup>2</sup> \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME

<code>\immediatesavetwopassdata {...} {...} {...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\impartefloat [...<sup>1</sup>...<sup>2</sup>...] {...} {...}</code> 1 inherits: \seteazaimpartefloat 2 BEFEHL 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in {...} {...<sup>2</sup>} [...<sup>3</sup>]</code> 1 TEXT <sup>PT</sup> OPT 2 TEXT 3 REFERENCE
<code>\inalt {...}</code> * CONTENT
<code>\HIGH {...}</code> * CONTENT instances: unitshigh
<code>\inclinat</code>
<code>\inclinataldin</code>
<code>\includemenu [...]</code> * NAME
<code>\includeversioninfo {...}</code> * NAME
<code>\increment \*...</code> * CSNAME
<code>\incrementcounter [...<sup>1</sup>] [...<sup>2</sup>]</code> 1 NAME OPT 2 NUMMER
<code>\incrementedcounter [...]</code> * NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> * NAME
<code>\increment cd:parentheses-1</code> * CSNAME NUMMER
<code>\indentation</code>

<code>\infofont</code>
<code>\infofontbold</code>
<code>\inframed [...<sup>1</sup>...<sup>2</sup>...] {...}</code> 1 inherits: \setea22inconjurat 2 CONTENT
<code>\inheritparameter [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</code> 1 TEXT 2 TEXT 3 KEY
<code>\inhibitblank</code>
<code>\initializeboxstack {...}</code> * NAME
<code>\injos [...]</code> * DIMENSION
<code>\inlinebuffer [...<sup>*</sup>...]</code> * BUFFER OPT
<code>\inlinedbox {...}</code> * CONTENT
<code>\inlinemath {...}</code> * CONTENT
<code>\inlinemathematics {...}</code> * CONTENT
<code>\inlinemessage {...}</code> * TEXT
<code>\inlineordisplaymath {...<sup>1</sup>} {...<sup>2</sup>}</code> 1 CONTENT 2 CONTENT
<code>\inlinerange [...]</code> * REFERENCE
<code>\inlinie {...<sup>1</sup>} [...<sup>2</sup>]</code> 1 TEXT OPT 2 REFERENCE
<code>\innerflushshapebox</code>
<code>\input {...}</code> * FILE
<code>\inputfilebarename</code>
<code>\inputfilename</code>

<code>\inputfilerealsuffix</code>
<code>\inputfilesuffix</code>
<code>\inputgivenfile {...}</code> <code>* FILE</code>
<code>\input ...</code> <code>* FILE</code>
<code>\insertpages [<sup>1</sup>...] [<sup>2</sup>...,...]<sub>OPT</sub> [<sup>3</sup>...,...]<sub>OPT</sub></code> <code>1 FILE</code> <code>2 NUMMER</code> <code>3 latime = DIMENSION</code> <code>n = NUMMER</code> <code>category = NAME</code>
<code>\instalarelimba [<sup>1</sup>...] [<sup>2</sup>...,...]</code> <code>1 NAME</code> <code>2 inherits: \setarelimba</code>
<code>\instalarelimba [<sup>1</sup>...] [<sup>2</sup>...]</code> <code>1 NAME</code> <code>2 SPRACHE</code>
<code>\installactionhandler {...}</code> <code>* NAME</code>
<code>\installactivecharacter ...</code> <code>* CHARACTER</code>
<code>\installanddefineactivecharacter <sup>1</sup>... {<sup>2</sup>...}</code> <code>1 CHARACTER</code> <code>2 BEFEHL</code>
<code>\installattributestack \*...</code> <code>* CSNAME</code>
<code>\installautocommandhandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...</code> <code>1 CSNAME</code> <code>2 NAME</code> <code>3 CSNAME</code>
<code>\installautosetuphandler \<sup>1</sup>... {<sup>2</sup>...}</code> <code>1 CSNAME</code> <code>2 NAME</code>
<code>\installbasicautosetuphandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...</code> <code>1 CSNAME</code> <code>2 NAME</code> <code>3 CSNAME</code>
<code>\installbasicparameterhandler \<sup>1</sup>... {<sup>2</sup>...}</code> <code>1 CSNAME</code> <code>2 NAME</code>
<code>\installbottomframerenderer {<sup>1</sup>...} {<sup>2</sup>...}</code> <code>1 NAME</code> <code>2 BEFEHL</code>

```
\installcommandhandler \... {...} \...
```

```
1 CSNAME  
2 NAME  
3 CSNAME
```

```
\installcorenamespace {...}
```

```
* NAME
```

```
\installdefinehandler \... {...} \...
```

```
1 CSNAME  
2 NAME  
3 CSNAME
```

```
\installdefinitionset \... {...}
```

```
1 CSNAME  
2 NAME
```

```
\installdefinitionsetmember \... {...} \... {...}
```

```
1 CSNAME  
2 NAME  
3 CSNAME  
4 NAME
```

```
\installdirectcommandhandler \... {...}
```

```
1 CSNAME  
2 NAME
```

```
\installdirectparameterhandler \... {...}
```

```
1 CSNAME  
2 NAME
```

```
\installdirectparametersethandler \... {...}
```

```
1 CSNAME  
2 NAME
```

```
\installdirectsetuphandler \... {...}
```

```
1 CSNAME  
2 NAME
```

```
\installdirectstyleandcolorhandler \... {...}
```

```
1 CSNAME  
2 NAME
```

```
\installframedautocommandhandler \... {...} \...
```

```
1 CSNAME  
2 NAME  
3 CSNAME
```

```
\installframedcommandhandler \... {...} \...
```

```
1 CSNAME  
2 NAME  
3 CSNAME
```

```
\installleftframerenderer {...} {...}
```

```
1 NAME  
2 BEFEHL
```

```
\installnamespace {...}
```

```
* NAME
```

\installoutputroutine \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 BEFEHL
\installpagearrangement <sup>1</sup> ... { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\installparameterhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installparameterhashhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installparametersethandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installparentinjector \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installrightframerenderer { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\installrootparameterhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installsetuphandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installsetupononlycommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installshipoutmethod { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 BEFEHL
\installsimplecommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} \ <sup>3</sup> ... 1 CSNAME 2 NAME 3 CSNAME
\installsimpleframedcommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} \ <sup>3</sup> ... 1 CSNAME 2 NAME 3 CSNAME
\installstyleandcolorhandler \ <sup>1</sup> ... { <sup>2</sup> ...} 1 CSNAME 2 NAME
\installswitchcommandhandler \ <sup>1</sup> ... { <sup>2</sup> ...} \ <sup>3</sup> ... 1 CSNAME 2 NAME 3 CSNAME

<code>\installswitchsetuphandler \.^ {^}</code> 1 CSNAME 2 NAME
<code>\installtexdirective {...} {...} {...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtexttracker {...} {...} {...}</code> 1 NAME 2 BEFEHL 3 BEFEHL
<code>\installtopframerenderer {...} {...}</code> 1 NAME 2 BEFEHL
<code>\installunitsseparator {...} {...}</code> 1 NAME 2 BEFEHL
<code>\installunitsspace {...} {...}</code> 1 NAME 2 BEFEHL
<code>\installversioninfo {...} {...}</code> 1 NAME 2 BEFEHL
<code>\integerrounding {...}</code> * NUMMER
<code>\intertext {...}</code> * TEXT
<code>\intins [..., ..., ^, ..., ...] {...}</code> 1 inherits: \setupstretched 2 TEXT
<code>\invokepagehandler {...} {...}</code> 1 normal niciunul NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italic</code>
<code>\italicaldin</code>
<code>\italiccorrection</code>
<code>\italicface</code>

$\backslash$ itemtag [...*...] *    REFERENCE <small>OPT</small>
$\backslash$ jobfilename
$\backslash$ jobfilesuffix
$\backslash$ jos {...} *    CONTENT
$\backslash$ jossus [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } 1    stanga dreapta 2    CONTENT 3    CONTENT
$\backslash$ LOW {...} *    CONTENT instances: unitslow
$\backslash$ Kap {...} *    TEXT
$\backslash$ kap {...} *    TEXT
$\backslash$ keeplinestogether {...} *    NUMMER
$\backslash$ keepunwantedspaces
$\backslash$ kerncharacters [... <sup>1</sup> ] {... <sup>2</sup> } 1    NUMMER <small>OPT</small> 2    TEXT
$\backslash$ koreancirclednumerals {...} *    NUMMER
$\backslash$ koreannumerals {...} *    NUMMER
$\backslash$ koreannumeralsc {...} *    NUMMER
$\backslash$ koreannumeralsp {...} *    NUMMER
$\backslash$ koreanparentnumerals {...} *    NUMMER
$\backslash$ LAMSTEX
$\backslash$ LATEX
$\backslash$ LamSTeX
$\backslash$ LaTeX



<code>\Litera {...}</code> *    NUMBER
<code>\Litere {...}</code> *    NUMBER
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\LUNA {...}</code> *    NUMBER
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\la {...} {...} [...]</code> 1    TEXT <sup>PPT</sup> OPT 2    TEXT 3    REFERENCE
<code>\LABELlimba</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabeltext {...}</code> *    KEY
<code>\headtext {...}</code> *    KEY
<code>\labeltext {...}</code> *    KEY
<code>\mathlabeltext {...}</code> *    KEY
<code>\operatorortext {...}</code> *    KEY
<code>\prefixtext {...}</code> *    KEY
<code>\suffixtext {...}</code> *    KEY
<code>\taglabeltext {...}</code> *    KEY
<code>\unittext {...}</code> *    KEY

$\backslash LABELtexts \{...\} \{...\}$ 1 KEY 2 TEXT instances: head label mathlabel
$\backslash leftheadtext \{...\}$ * KEY
$\backslash leftlabeltext \{...\}$ * KEY
$\backslash leftmathlabeltext \{...\}$ * KEY
$\backslash languageCharacters \{...\}$ * NUMMER
$\backslash languagecharacters \{...\}$ * NUMMER
$\backslash languagecharwidth \{...\}$ * SPRACHE
$\backslash lapagina [..]$ * REFERENCE
$\backslash lastcounter [..] [..]$ 1 NAME OPT 2 NUMMER
$\backslash lastcountervalue [..]$ * NAME
$\backslash lastdigit \{...\}$ * NUMMER
$\backslash lastlinewidth$
$\backslash lastnaturalboxdp$
$\backslash lastnaturalboxht$
$\backslash lastnaturalboxwd$
$\backslash lastpredefinedsymbol$
$\backslash lastrealpage$
$\backslash lastrealpagenumber$
$\backslash lastsubcountervalue [..] [..]$ 1 NAME 2 NUMMER
$\backslash lastsubpagenumber$

\* NUMMER

\lastuserpage

\lastuserpagenumber

\* BEFEHL

```

1 inherits: \setupplayerOPT
2 inherits: \setuplayeredtext
3 TEXT
4 CONTENT

```

\layerheight

\layerwidth

1	NAME
2	NUMMER
3	NAME
4	CONTENT

```

1  NAME
2  NUMMER
3  CONTENT

```

```

1  TEXT OPT
2  CONTENT

```

\* CONTENT

\* CONTENT

\* CONTENT

```
* KEY
instances: head label mathlabel
```

\* KEY

\* KEY

\* KEY

<code>\leftline {...}</code> *    CONTENT
<code>\lefttorrighthbox <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\lefttorrightvbox <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\lefttorrightvtop <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\leftskipadaption</code>
<code>\leftsubguillemot</code>
<code>\lefttopbox {...}</code> *    CONTENT
<code>\lefttoright</code>
<code>\lefttorrighthbox <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\lefttorrightvbox <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\lefttorrightvtop <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\letbeundefined {...}</code> *    NAME
<code>\letcatcodecommand \<sup>1</sup>... <sup>2</sup>... \<sup>3</sup>...</code> 1    CSNAME 2    CHARACTER NUMBER 3    CSNAME
<code>\letcscsname \<sup>1</sup>... \csname <sup>2</sup>... \endcsname</code> 1    CSNAME 2    NAME
<code>\letcsnamecs \csname <sup>1</sup>... \endcsname \<sup>2</sup>...</code> 1    NAME 2    CSNAME
<code>\letcsnamecsname \csname <sup>1</sup>... \endcsname \csname <sup>2</sup>... \endcsname</code> 1    NAME 2    NAME
<code>\letdummyparameter {...} \<sup>2</sup>...</code> 1    KEY 2    CSNAME

<code>\letempty \*...</code> <code>* CSNAME</code>
<code>\letgvalue {...} \*...</code> <code>1 NAME</code> <code>2 CSNAME</code>
<code>\letgvalueempty {...}</code> <code>* NAME</code>
<code>\letgvalurelax {...}</code> <code>* NAME</code>
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>

<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    NUMMER                    OPT 2    TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1    NAME 2    CSNAME
<code>\letvalueempty</code> { <sup>*</sup> ...} *    NAME
<code>\letvaluerelax</code> { <sup>*</sup> ...} *    NAME
<code>\lfence</code> { <sup>*</sup> ...} *    CHARACTER
<code>\lhbox</code> { <sup>*</sup> ...} *    CONTENT
<code>\limba</code> [ <sup>*</sup> ...] *    SPRACHE
<code>\limbapincipala</code> [ <sup>*</sup> ...] *    SPRACHE
<code>\LANGUAGE</code>
<code>\limitatelines</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1    NUMMER 2    BEFEHL 3    TEXT
<code>\limitatetext</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1    TEXT 2    [-+]DIMENSION 3    BEFEHL
<code>\limitatetext</code> { <sup>1</sup> ...} {... <sup>2</sup> ,...} { <sup>3</sup> ...} 1    TEXT 2    [-+]DIMENSION 3    BEFEHL
<code>\limtatefirstline</code> { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1    TEXT 2    DIMENSION 3    BEFEHL

\LINENOTE {...} * TEXT instances: linenote
\startlinenote [...] <sup>1</sup> {...} <sup>2</sup> 1 REFERENCE 2 TEXT
\linespanningtext {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 TEXT 2 DIMENSION 3 FONT
\linie {...} * CONTENT
\linieneagra [...] <sup>*</sup> [...] * inherits: \seteazaliniflinegre
\liniesubtire
\linieumplere [...] <sup>*</sup> [...] * inherits: \seteazaliniiumplere
\liniinegre [...] <sup>*</sup> [...] * inherits: \seteazaliniflinegre
\liniisubtiri [...] <sup>*</sup> [...] * inherits: \seteazalinifsubtire
\listcitation [...] <sup>1</sup> [...] <sup>2</sup> 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\listcitation [...] <sup>1</sup> [...] <sup>2</sup> 1 implicit category <sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE
\listcitation [...] <sup>1</sup> [...] <sup>2</sup> 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 KEY = VALUE

```

\listcite [...1...][..2]
1  referinta = REFERENCE
    alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                    authorityyear
    inainte    = BEFEHL
    dupa       = BEFEHL
    stanga     = BEFEHL
    dreapta    = BEFEHL
    inherits: \setupbtx
2  REFERENCE

```

```
\listcite [...][...]
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

```

\listcite [...,\sup{1}...,...] [...,\sup{2}...,...]
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authorityyear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE

```

\listnamespaces

```
\litera {...}
*   NUMMER
```

```
\literate {...}
*   NUMMER
```

\llap {...}  
\* CONTENT

```
\loadanyfile [...]
* FILE
```

```
\loadanyfileonce [...]
* FILE
```

```
\loadbtxdefinitionfile [..]
* FILE
```

```
\loadbtxreplacementfile [...]  
* FILE
```

```
\loadcldfile [...]
* FILE
```

```
\loadcldfileonce [...]
* FILE
```

```
\loadfontgoodies [...]
* FILE
```

```
\loadluafile [...]
* FILE
```



```
\loadluafileonce [...]
```

`\loadspellchecklist [...]1 [...]2`

`\loadtexfile [...]`

`\loadtexfileonce [...]`

`\loadtypescriptfile [...]`

$$\backslash\mathrm{localframed} \left[ \overset{.1}{\dots} \right] \left[ \dots, \overset{.2}{\dots} \dots, \dots \right] \{ \overset{.3}{\dots} \}$$
$$\backslash\mathrm{localframedwithsettings} \left[ \overset{1}{\dots} \right] \left[ \dots, \overset{2}{\dots}, \dots \right] \left\{ \overset{3}{\dots} \right\}$$

\localhsize

\localpopbox ...

\localpopmacro \.\*

\localpushbox ...

\localpushmacro \.\*...

```
\localundefine {...}
```

`\locatedfilepath`

```
\locatefilepath {...}
```

`\locfilename {.*}`

$$\backslash\mathrm{lomihi} \{...\} \{...\} \{...\}$$

$\backslash\lowerbox$ $\{...\}$ $\backslash^2...$ $\{...\}$ 1 DIMENSION 2 CSNAME 3 CONTENT
$\backslashlowercased$ $\{...\}$ * TEXT
$\backslashlowercasestring$ $^1...$ $\backslashto$ $\backslash^2...$ 1 TEXT 2 CSNAME
$\backslashlowerlefthdoubleninequote$
$\backslashlowerleftsingleninequote$
$\backslashlowerrighthdoubleninequote$
$\backslashlowerrightsingleninequote$
$\backslashLOWHIGH$ $[^1...]$ $\{^2...\}$ $\{^3...\}$ 1 stanga dreapta 2 CONTENT 3 CONTENT
$\backslashLOWMIDHIGH$ $\{^1...\}$ $\{^2...\}$ $\{^3...\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslashlrbbox$ $\{^1...\}$ $\{^2...\}$ $\{^3...\}$ $\{^4...\}$ $\{^5...\}$ 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
$\backslashltop$ $^1...$ $\{^2...\}$ 1 TEXT <sup>OPT</sup> 2 CONTENT
$\backslashluacode$ $\{...\}$ * BEFEHL
$\backslashluaconditional$ $\backslash^*...$ * CSNAME
$\backslashluaenvironment$ $^*...$ * FILE
$\backslashluaexpanded$ $\{...\}$ * BEFEHL
$\backslashluaexpr$ $\{...\}$ * CONTENT
$\backslashluafunction$ $\{...\}$ * BEFEHL

<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luaminorversion</code>
<code>\luaparameterset {<sup>1</sup>..} {<sup>2</sup>..}</code> 1    NAME 2    CONTENT
<code>\luasetup {<sup>*</sup>..}</code> *    NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\luna {<sup>*</sup>..}</code> *    NUMMER
<code>\lungimelista</code>
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {<sup>*</sup>..}</code> *    NUMMER
<code>\MONTHSHORT {<sup>*</sup>..}</code> *    NUMMER
<code>\MPanchor {<sup>*</sup>..}</code> *    NAME

\MPbetex {...} *   NAME
\MPc {...} *   NAME
\MPcode {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME <sup>OPT</sup> 2   CONTENT
\MPcolor {...} *   COLOR
\MPcoloronly {...} *   COLOR
\MPcolumn {...} *   NAME
\MPd {...} *   NAME
\MPdrawing {...} *   CONTENT
\MPfontsizehskip {...} *   FONT
\MPgetmultipars {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME 2   NAME
\MPgetmultishape {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME 2   NAME
\MPgetposboxes {... <sup>1</sup> ,... <sup>2</sup> } {... <sup>2</sup> } 1   NAME 2   NAME
\MPh {...} *   NAME
\MPII
\MPIV
\MPinclusions [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } 1   + <sup>OPT</sup> <sup>OPT</sup> 2   NAME 3   CONTENT
\MPleftskip {...} *   NAME
\MPll {...} *   NAME

\MPlr {...} * NAME
\MPIs {...} * NAME
\MPmenubuttons {...} * NAME
\MPn {...} * NAME
\MPoptions {...} * COLOR
\MPoverlayanchor {...} * NAME
\MPp {...} * NAME
\MPpage {...} * NAME
\MPpardata {...} * NAME
\MPplus {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\MPpos {...} * NAME
\MPpositiongraphic {...} {..., <u>...</u> ,...} 1 NAME OPT 2 KEY = VALUE
\MPposset {...} * NAME
\MPr {...} * NAME
\MPrawvar {...} {...} 1 NAME 2 KEY
\MPregion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME

\MPrs {...} *   NAME
\MPstring {...} *   NAME
\MPtext {...} *   NAME
\MPtransparency {...} *   COLOR
\MPul {...} *   NAME
\MPur {...} *   NAME
\MPVI
\MPv {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } 1   NAME 2   NUMMER 3   CONTENT
\MPvar {...} *   KEY
\MPvariable {...} *   KEY
\MPvv {... <sup>1</sup> } {... <sup>2</sup> } 1   NAME 2   CONTENT
\MPw {...} *   NAME
\MPwhd {...} *   NAME
\MPx {...} *   NAME
\MPxy {...} *   NAME
\MPxywhd {...} *   NAME
\MPy {...} *   NAME
\m [... <sup>1</sup> ] {... <sup>2</sup> } 1   NAME 2   CONTENT

<code>\makecharacteractive ...</code> <code>* CHARACTER</code>
<code>\makerawcommalist [...<sup>1</sup>,...] \<sup>2</sup>...</code> <code>1 BEFEHL</code> <code>2 CSNAME</code>
<code>\makestrutofbox ...</code> <code>* CSNAME NUMBER</code>
<code>\mapfontsize [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 DIMENSION</code> <code>2 DIMENSION</code>
<code>\marcaje (...<sup>1</sup>,...) (...<sup>2</sup>,...) [...<sup>3</sup>]</code> <code>1 POSITION</code> <code>2 POSITION</code> <code>3 REFERENCE</code>
<code>\mare ...</code> <code>* CHARACTER</code>
<code>\margindata [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] [...<sup>3</sup>,...<sup>3</sup>,...] {...<sup>4</sup>}</code> <code>1 NAME</code> <code>2 referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> <code>3 inherits: \setupmarginframed</code> <code>4 CONTENT</code>
<code>\MARGINDATA [...<sup>1</sup>,...<sup>1</sup>,...] [...<sup>2</sup>,...<sup>2</sup>,...] {...<sup>3</sup>}</code> <code>1 referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> <code>2 inherits: \setupmarginframed</code> <code>3 CONTENT</code> <code>instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge</code> <code>inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin</code> <code>inother margintext</code>
<code>\markcontent [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 reset tot NAME</code> <code>2 CONTENT</code>
<code>\markinjector [...<sup>1</sup>]</code> <code>* NAME</code>
<code>\mat {...<sup>1</sup>}</code> <code>* CONTENT</code>
<code>\matematica [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\math [...<sup>1</sup>] {...<sup>2</sup>}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\mathbf</code>
<code>\mathbi</code>

<code>\mathblackboard</code>
<code>\mathbs</code>
<code>\mathcommand {*.}</code> <code>* NAME</code>
<code>\MATHCOMMAND {<sup>1</sup>.} {<sup>2</sup>.}</code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\mathdefault</code>
<code>\MATHDOUBLEEXTENSIBLE {*.}</code> <code>* TEXT</code>
<code>\MATHEXTENSIBLE [<sup>1</sup>.] {<sup>2</sup>.} {<sup>3</sup>.}</code> <code>1 reverse matematica <math>\Psi</math> text chemistry OPT</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\mathfraktur</code>
<code>\MATHFRAMED [...<sup>1</sup>...] {<sup>2</sup>.}</code> <code>1 inherits: \setupmathframed</code> <code>2 CONTENT</code> <code>instances: mframed inmframed mcframed</code>
<code>\mathfunction {*.}</code> <code>* CONTENT</code>
<code>\mathit</code>
<code>\mathitalic</code>
<code>\mathop {*.}</code> <code>* CONTENT</code>
<code>\MATHORNAMENT {*.}</code> <code>* CONTENT</code>
<code>\MATHOVEREXTENSIBLE {*.}</code> <code>* TEXT</code>
<code>\MATHOVERTEXTEXTENSIBLE {<sup>1</sup>.} {<sup>2</sup>.}</code> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\MATHRADICAL [<sup>1</sup>.] {<sup>2</sup>.}</code> <code>1 TEXT OPT</code> <code>2 CONTENT</code>
<code>\mathrm</code>
<code>\mathscript</code>



<code>\mathsl</code>
<code>\mathss</code>
<code>\mathtext <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtextbf <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtextbi <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtextbs <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtextit <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtextsl <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtexttf <sup>1</sup>... {...}</code> 1    TEXT            OPT 2    TEXT
<code>\mathtf</code>
<code>\mathtripletp <sup>1</sup>... {...} <sup>2</sup>... {...} <sup>3</sup>... {...} <sup>4</sup>... {...}</code> 1    NAME            OPT        OPT        OPT        OPT 2    TEXT 3    TEXT 4    TEXT
<code>\MATHTRIPLET <sup>1</sup>... {...} <sup>2</sup>... {...} <sup>3</sup>... {...} <sup>4</sup>... {...}</code> 1    NAME            OPT        OPT        OPT        OPT 2    TEXT 3    TEXT 4    TEXT
<code>\mathtt</code>
<code>\MATHUNDEREXTENSIBLE {...}</code> *    TEXT
<code>\MATHUNDERTEXTEXTENSIBLE <sup>1</sup>... {...} <sup>2</sup>... {...}</code> 1    TEXT 2    TEXT
<code>\MATHUNSTACKED</code>
<code>\mathupright</code>

$\backslash\mathrm{mathword} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordbf} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordbi} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordbs} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordit} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordsl} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{mathwordtf} \mathrel{\mathop{\cdot}\limits^1} \dots \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathrm{maxaligned} \{\mathrel{\mathop{\cdot}\limits^*} \dots\}$ *    CONTENT
$\backslash\mathrm{mbox} \{\mathrel{\mathop{\cdot}\limits^*} \dots\}$ *    CONTENT
$\backslash\mathrm{measure} \{\mathrel{\mathop{\cdot}\limits^*} \dots\}$ *    NAME
$\backslash\mathrm{measured} \{\mathrel{\mathop{\cdot}\limits^*} \dots\}$ *    NAME
$\backslash\mathrm{mediu} [\mathrel{\mathop{\cdot}\limits^*} \dots]$ *    FILE
$\backslash\mathrm{mediu} \mathrel{\mathop{\cdot}\limits^*} \dots$ *    FILE
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{menuinteractiune} [\mathrel{\mathop{\cdot}\limits^1} \dots] [\dots\mathrel{\mathop{\cdot}\limits^2} \dots,\dots]$ 1    NAME                            OPT 2    inherits: $\backslash\mathrm{seteazameniuinteractiune}$
$\backslash\mathrm{mequal} \{\mathrel{\mathop{\cdot}\limits^1} \dots\} \{\mathrel{\mathop{\cdot}\limits^2} \dots\}$ 1    TEXT            OPT            OPT 2    TEXT

$\backslash\text{message}\{...\}$ * TEXT
$\backslash\text{metaTeX}$
$\backslash\text{mfence}\{...\}$ * CHARACTER
$\backslash\text{mfunction}\{...\}$ * CONTENT
$\backslash\text{mfunctionlabeltext}\{...\}$ * NAME
$\backslash\text{mhbox}\{...\}$ * CONTENT
$\backslash\text{mhookleftarrow}\{...\}^{1}\{...\}^{2}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mhookrightarrow}\{...\}^{1}\{...\}^{2}$ 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mic}$
$\backslash\text{micaldin}$
$\backslash\text{micaldininclinat}$
$\backslash\text{micinclinat}$
$\backslash\text{micinclinataldin}$
$\backslash\text{micitalicaldin}$
$\backslash\text{micnormal}$
$\backslash\text{mictype}$
$\backslash\text{middlealigned}\{...\}$ * CONTENT
$\backslash\text{middlebox}\{...\}$ * CONTENT
$\backslash\text{midhbox}\{...\}$ * CONTENT
$\backslash\text{minimalhbox}\{...\}^{1}\{...\}^{2}$ 1 TEXT OPT 2 CONTENT

$\backslash\text{mixedcaps}$ {...} * TEXT
$\backslash\text{mkvibuffer}$ [...] * BUFFER OPT
$\backslash\text{mLeftarrow}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mLeftrightarrow}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mleftarrow}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mleftharpoondown}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mleftharpoonup}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mleftrightarrow}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mleftrightharpoons}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mmapsto}$ {...} {...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{moduleparameter}$ {...} {...} 1 FILE 2 KEY
$\backslash\text{molecule}$ {...} * CONTENT
$\backslash\text{mono}$
$\backslash\text{monoaldin}$
$\backslash\text{mononormal}$
$\backslash\text{monthlong}$ {...} * NUMMER
$\backslash\text{monthshort}$ {...} * NUMMER
$\backslash\text{mprandomnumber}$

$\backslash\mathrm{mRightarrow} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mrel} \{...\} \{...\}$ 1    TEXT    OPT            OPT 2    TEXT
$\backslash\mathrm{mrightarrow} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mrightharpoondown} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mrightharpoonup} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mrightrightarpoons} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mrightoverleftarrow} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mtext} \{...\}$ *    CONTENT
$\backslash\mathrm{mtriplerel} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mtwoheadleftarrow} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{mtwoheadrightarrow} \{...\} \{...\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\mathrm{NormalizeFontHeight} \backslash^1... \{...\} \{...\} \{...\}$ 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
$\backslash\mathrm{NormalizeFontWidth} \backslash^1... \{...\} \{...\} \{...\}$ 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
$\backslash\mathrm{NormalizeTextHeight} \{...\} \{...\} \{...\}$ 1    FONT 2    DIMENSION 3    TEXT

<code>\NormalizeTextWidth {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\Numere {...}</code> * NUMMER
<code>\Numereromane {...}</code> * NUMMER
<code>\namedheadnumber {...}</code> * ABSCHNITT
<code>\namedstructureheadlocation {...}</code> * ABSCHNITT
<code>\namedstructureuservariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 ABSCHNITT 2 KEY
<code>\namedstructurevariable {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 ABSCHNITT 2 KEY
<code>\namedtaggedlabeltexts {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...}</code> 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
<code>\naturalhbox <sup>1</sup>... {<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\naturalhpack <sup>1</sup>... {<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\naturalvbox <sup>1</sup>... {<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\naturalvcenter <sup>1</sup>... {<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\naturalvpack <sup>1</sup>... {<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\naturalvtop <sup>1</sup>... {<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\naturalwd ...</code> * CSNAME NUMMER
<code>\necunoscute</code>

<code>\negatecolorbox ...</code> <code>* CSNAME NUMBER</code>
<code>\negated {...}</code> <code>* TEXT</code>
<code>\negthinspace</code>
<code>\newattribute \...</code> <code>* CSNAME</code>
<code>\newcatcodetable \...</code> <code>* CSNAME</code>
<code>\newcounter \...</code> <code>* CSNAME</code>
<code>\newevery \<sup>1</sup>... \<sup>2</sup>...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> <code>* NAME</code>
<code>\newsignal \...</code> <code>* CSNAME</code>
<code>\newsystemmode {...}</code> <code>* NAME</code>
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...] [<sup>2</sup>...]</code> <code>1 NAME OPT</code> <code>2 NUMBER</code>
<code>\nextcountervalue [...]</code> <code>* NAME</code>
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\urmatorulPARAGRAPHS</code>

<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...] [...]</code> 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE
<code>\nodetostring \.^... {...}</code> 1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,...<sup>1</sup>...,...] {...<sup>2</sup>}</code> 1 inherits: \setezainconjurat 2 CONTENT



<code>\normalitalicface</code>
<code>\normalizebodyfontsize \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontline \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontwidth \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizetextdepth {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextheight {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextline {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalizetextwidth {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\normalslantedface</code>
<code>\normaltypeface</code>
<code>\nota [<sup>1</sup>...] [<sup>2</sup>...]</code> 1 NAME OPT 2 REFERENCE

<p><code>\NOTE [...,<sup>1</sup>...] {...}</code></p> <p>1 REFERENCE<sup>PT</sup></p> <p>2 TEXT</p> <p>instances: footnote endnote</p>
<p><code>\NOTE [...,*=...,...]</code></p> <p>* titlu = TEXT</p> <p>semncarte = TEXT</p> <p>lista = TEXT</p> <p>referinta = REFERENCE</p> <p>instances: footnote endnote</p>
<p><code>\endnote [...,<sup>1</sup>...] {...}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\footnote [...,<sup>1</sup>...] {...}</code></p> <p>1 REFERENCE OPT</p> <p>2 TEXT</p>
<p><code>\notesymbol [...<sup>1</sup>] [...<sup>2</sup>]</code></p> <p>1 NAME OPT</p> <p>2 REFERENCE</p>
<p><code>\notragged</code></p>
<p><code>\ntimes {...} {...}</code></p> <p>1 TEXT</p> <p>2 NUMMER</p>
<p><code>\numarformula [...,*=...,...]</code></p> <p>* REFERENCE OPT</p>
<p><code>\numarpagina</code></p>
<p><code>\numartitlu [...<sup>1</sup>] [...<sup>2</sup>]</code></p> <p>1 ABSCHNITT OPT</p> <p>2 precedent curent urmatorul primul ultim</p>
<p><code>\numartitlucurent</code></p>
<p><code>\numberofpoints {...}</code></p> <p>* DIMENSION</p>
<p><code>\numere {...}</code></p> <p>* NUMMER</p>
<p><code>\numereromane {...}</code></p> <p>* NUMMER</p>
<p><code>\obeydepth</code></p>
<p><code>\objectdepth</code></p>
<p><code>\objectheight</code></p>
<p><code>\objectmargin</code></p>



<code>\outputstreamunvcopy [...]</code> *    NAME
<code>\over [...]</code> *    REFERENCE
<code>\overbartext {...} {...}</code> 1    TEXT 2    TEXT
<code>\overbarunderbar {...}</code> *    TEXT
<code>\overbrace {...}</code> *    TEXT
<code>\overbracetext {...} {...}</code> 1    TEXT 2    TEXT
<code>\overbraceunderbrace {...}</code> *    TEXT
<code>\overbracket {...}</code> *    TEXT
<code>\overbrackettext {...} {...}</code> 1    TEXT 2    TEXT
<code>\overbracketunderbracket {...}</code> *    TEXT
<code>\overlaybutton [...]</code> *    REFERENCE
<code>\overlaybutton {...}</code> *    REFERENCE
<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> *    FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>

$\backslash\mathrm{overlayrollbutton}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1    REFERENCE 2    REFERENCE
$\backslash\mathrm{overlaywidth}$
$\backslash\mathrm{overleftarrow}$ {...} *    TEXT
$\backslash\mathrm{overleftharpoonupdown}$ {...} *    TEXT
$\backslash\mathrm{overleftharpoonup}$ {...} *    TEXT
$\backslash\mathrm{overleftrightarrow}$ {...} *    TEXT
$\backslash\mathrm{overloaderror}$
$\backslash\mathrm{overparent}$ {...} *    TEXT
$\backslash\mathrm{overparenttext}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1    TEXT 2    TEXT
$\backslash\mathrm{overparentunderparent}$ {...} *    TEXT
$\backslash\mathrm{overrightarrow}$ {...} *    TEXT
$\backslash\mathrm{overrightharpoonupdown}$ {...} *    TEXT
$\backslash\mathrm{overrightharpoonup}$ {...} *    TEXT
$\backslash\mathrm{overset}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1    TEXT 2    TEXT
$\backslash\mathrm{overtwoheadleftarrow}$ {...} *    TEXT
$\backslash\mathrm{overtwoheadrightarrow}$ {...} *    TEXT
$\backslash\mathrm{PDFcolor}$ {...} *    NAME
$\backslash\mathrm{PDFETEX}$
$\backslash\mathrm{PDFTEX}$

<code>\PITEX</code>
<code>\PiTeX</code>
<code>\PointsToBigPoints {...} \^2.</code> 1 DIMENSION 2 CSNAME
<code>\PointsToReal {...} \^2.</code> 1 DIMENSION 2 CSNAME
<code>\PointsToWholeBigPoints {...} \^2.</code> 1 DIMENSION 2 CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>
<code>\PtToCm {...}</code> * DIMENSION
<code>\pagearea [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> 1 sus antet text subso <sup>OPT</sup> subso <sup>OPT</sup> 2 text margine bordura 3 stanga dreapta lefttext middletext righttext
<code>\pagebreak [...,*...]</code> * gol antet subso <sup>OPT</sup> dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadrupul ultim ultimapagina start stop NAME
<code>\pagefigure [...]<sup>1</sup> [...,...<sup>2</sup>...]<sup>OPT</sup></code> 1 FILE 2 inherits: \setupexternalfigure
<code>\pagegridspanwidth {...}</code> * NUMMER
<code>\pageinjection [...]<sup>1</sup> [...,...<sup>2</sup>...]<sup>OPT</sup></code> 1 NAME 2 KEY = VALUE
<code>\pageinjection [...,...<sup>1</sup>...]<sup>OPT</sup> [...,...<sup>2</sup>...]<sup>OPT</sup></code> 1 inherits: \setuppageinjection 2 KEY = VALUE
<code>\pagestaterealpage {...} {...}</code> 1 NAME 2 NAME NUMMER
<code>\pagina [...,*...]</code> * inherits: \pagebreak <sup>OPT</sup>
<code>\paletsize</code>

<code>\PARAGRAPHS</code>
<code>\pastreazablocuri [...<sup>1</sup>,...] [...<sup>2</sup>,...]</code> 1 NAME 2 NAME OPT
<code>\pdfactualtext {...} {...}</code> 1 CONTENT 2 TEXT
<code>\pdfbackendactualtext {...} {...}</code> 1 CONTENT 2 TEXT
<code>\pdfbackendcurrentresources</code>
<code>\pdfbackendsetcatalog {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetcolorspace {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsettextgstate {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetinfo {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetname {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageattribute {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageresource {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpagesattribute {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpattern {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetshade {...} {...}</code> 1 NAME 2 TEXT
<code>\pdfcolor {...}</code> * NAME
<code>\pdfTeX</code>

<code>\pdfTeX</code>
<code>\pelung {...}</code> * NAME
<code>\percent</code>
<code>\percentdimen {...} {...}</code> 1 DIMENSION CSNAME 2 DIMENSION NUMBER
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>
<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {...}</code> * NUMMER
<code>\persiannumerals {...}</code> * NUMMER
<code>\phantom {...}</code> * CONTENT
<code>\phantombox [...,...*...,...]</code> * latime = DIMENSION inaltme = DIMENSION inaltime = DIMENSION
<code>\pickupgroupedcommand {...} {...} {...}</code> 1 BEFEHL 2 BEFEHL 3 BEFEHL
<code>\placeattachments</code>
<code>\placebtxrendering [...] [...,...<sup>2</sup>...,...]</code> 1 NAME OPT OPT 2 inherits: \setupbtxrendering
<code>\placecitation [...]</code> * REFERENCE
<code>\placecomments</code>
<code>\placecurrentformulanumber</code>
<code>\placedbox {...}</code> * CONTENT



**\placefloat** [<sup>1</sup>...] [<sup>2</sup>...,...] [<sup>3</sup>...,...] {<sup>4</sup>...} {<sup>5</sup>...}

- 1 SINGULAR OPT OPT
- 2 split totdeauna stanga dreapta intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

**\placefloatwithsetups** [<sup>1</sup>...] [<sup>2</sup>...,...] [<sup>3</sup>...,...] {<sup>4</sup>...} {<sup>5</sup>...}

- 1 NAME OPT OPT
- 2 split totdeauna stanga dreapta intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol
- 3 REFERENCE
- 4 TEXT
- 5 CONTENT

**\puneFLOAT** [<sup>1</sup>...,...] [<sup>2</sup>...,...] {<sup>3</sup>...} {<sup>4</sup>...}

- 1 split totdeauna<sup>OPT</sup>stanga dreapta<sup>OPT</sup> intern extern spatiuspace cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

instances: chemical figure table intermezzo graphic

**\placeframed** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...] {<sup>3</sup>...}

- 1 NAME OPT
- 2 inherits: \seteazainconjurat
- 3 CONTENT

**\placeheadnumber** [...]

- \* ABSCHNITT

**\placeheadtext** [...]

- \* ABSCHNITT

**\placehelp**

**\placeinitial** [...]

- \* NAME OPT

**\placelayer** [...]

- \* NAME

**\placelayeredtext** [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...] [<sup>3</sup>...,...<sup>3</sup>...,...] {<sup>4</sup>...} {<sup>5</sup>...}

- 1 NAME OPT OPT
- 2 inherits: \setuplayer
- 3 inherits: \setuplayeredtext
- 4 TEXT
- 5 CONTENT

**\placelistofFLOATS** [...,<sup>\*</sup>...,...]

- \* inherits: \seteazalista OPT
- instances: chemicals figures tables intermezzi graphics

**\completelistofchemicals** [...,<sup>\*</sup>...,...]

- \* inherits: \seteazalista OPT

$\backslash\completelistoffigures$ [... <sup>*</sup> ...] * inherits: \seteazalista OPT
$\backslash\completelistofgraphics$ [... <sup>*</sup> ...] * inherits: \seteazalista OPT
$\backslash\completelistofintermezzi$ [... <sup>*</sup> ...] * inherits: \seteazalista OPT
$\backslash\completelistoftables$ [... <sup>*</sup> ...] * inherits: \seteazalista OPT
$\backslash\placelistofpublications$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 NAME OPT OPT 2 inherits: \setupbtxrendering
$\backslash\placelistofsorts$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 SINGULAR OPT 2 inherits: \seteazasortare
$\backslash\placelistofSORTS$ [... <sup>*</sup> ...] * inherits: \seteazasortare OPT instances: logos
$\backslash\completelistoflogos$ [... <sup>*</sup> ...] * inherits: \seteazasortare OPT
$\backslash\placelistofsynonyms$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 SINGULAR OPT 2 inherits: \seteazasinonime
$\backslash\placelistofSYNONYMS$ [... <sup>*</sup> ...] * inherits: \seteazasinonime OPT instances: abbreviations
$\backslash\completelistofabbreviations$ [... <sup>*</sup> ...] * inherits: \seteazasinonime OPT
$\backslash\placelocalnotes$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 NAME OPT 2 inherits: \setupnote
$\backslash\placement$ [... <sup>1</sup> ] [... <sup>2</sup> ...] {... <sup>3</sup> } 1 NAME OPT 2 inherits: \setupplacement 3 CONTENT
$\backslash\PLACEMENT$ [... <sup>1</sup> ...] {... <sup>2</sup> } 1 inherits: \setup <sup>OPT</sup> placement 2 CONTENT
$\backslash\placenamefloat$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME 2 REFERENCE
$\backslash\placenameformula$ [... <sup>1</sup> ...] {... <sup>2</sup> } 1 + - REFERENCE OPT 2 TEXT

<p><b>\placenotes</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p><b>\placepairedbox</b> [...<sup>1</sup>] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>} <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>
<p><b>\punePAIREDBOX</b> [...<sup>1</sup>,...] {...<sup>2</sup>} {...<sup>3</sup>} <small>OPT</small></p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances: legend</p>
<p><b>\setarelegend</b> [...<sup>*</sup>,...] <small>OPT</small></p> <p>* inherits: \setuppairedbox</p>
<p><b>\placeparallel</b> [...<sup>1</sup>] [...<sup>2</sup>,...] [...<sup>3</sup>,...] <small>OPT</small></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p><b>\placerawlist</b> [...<sup>1</sup>] [...<sup>2</sup>,...] <small>OPT</small></p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>
<p><b>\placereadingwindow</b> [...<sup>1</sup>] [...<sup>2</sup>] <small>OPT</small></p> <p>1 NAME</p> <p>2 NAME</p>
<p><b>\plaseazapegrid</b> [...<sup>1</sup>] {...<sup>2</sup>} <small>OPT</small></p> <p>1 normal standard da <small>OPT</small> Strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME</p> <p>2 CONTENT</p>
<p><b>\plaseazapegrid</b> [...<sup>1</sup>,...] {...<sup>2</sup>} <small>OPT</small></p> <p>1 inherits: \definegridsmapping</p> <p>2 CONTENT</p>
<p><b>\plaseazasemnecarte</b> [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...] <small>OPT OPT OPT</small></p> <p>1 ABSCHNITT LISTE</p> <p>2 ABSCHNITT LISTE</p> <p>3 inherits: \setupbookmark</p>
<p><b>\popattribute</b> \...</p> <p>* CSNAME</p>
<p><b>\popmacro</b> \...</p> <p>* CSNAME</p>
<p><b>\popmode</b> [...]</p> <p>* NAME</p>
<p><b>\popsystemmode</b> {...}</p> <p>* NAME</p>
<p><b>\positionoverlay</b> {...}</p> <p>* NAME</p>

<code>\positionregionoverlay {<sup>1</sup>.} {<sup>2</sup>.}</code> 1 NAME 2 NAME
<code>\postponenotes</code>
<code>\potrivestecamp [<sup>1</sup>.] [<sup>2</sup>...<sup>OPT</sup>...]</code> 1 NAME 2 inherits: \setupfieldbody
<code>\pozitie [<sup>1</sup>...<sup>OPT</sup>...<sup>2</sup>] (...<sup>2</sup>,...) {<sup>3</sup>.}</code> 1 inherits: \setarepozitie 2 POSITION 3 CONTENT
<code>\predefinedfont [<sup>*</sup>.]</code> * FONT
<code>\predefinefont [<sup>1</sup>.] [<sup>2</sup>.]</code> 1 NAME 2 FONT
<code>\predefinesymbol [<sup>*</sup>.]</code> * NAME
<code>\prefixedpagenumber</code>
<code>\prependetoks <sup>1</sup>... \to \<sup>2</sup>...</code> 1 BEFEHL 2 CSNAME
<code>\prependgvalue {<sup>1</sup>.} {<sup>2</sup>.}</code> 1 NAME 2 BEFEHL
<code>\prependtocommalist {<sup>1</sup>.} \<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\prependtoks <sup>1</sup>... \to \<sup>2</sup>...</code> 1 BEFEHL 2 CSNAME
<code>\prependtoksonce <sup>1</sup>... \to \<sup>2</sup>...</code> 1 BEFEHL 2 CSNAME
<code>\prependvalue {<sup>1</sup>.} {<sup>2</sup>.}</code> 1 NAME 2 BEFEHL
<code>\presetdocument [...<sup>*</sup>=...]</code> * inherits: \setupdocument
<code>\presetfieldsymbols [...<sup>*</sup>...]</code> * NAME

<pre> \presetLABELtext [...] [...] 1  SPRACHE          OPT 2  KEY  =  VALUE instances: head label mathlabel taglabel unit operator prefix suffix btxlabel </pre>
<pre> \copybtxlabeltext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copyheadtext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copylabeltext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copymathlabeltext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copyoperatortext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copyprefixtext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copysuffixtext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copytaglabeltext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \copyunittext [...] [...] 1  SPRACHE          OPT 2  KEY  =  KEY </pre>
<pre> \pretocommalist {...} \^2.. 1  TEXT 2  CSNAME </pre>
<pre> \prevcounter [...] [\^2..] 1  NAME          OPT 2  NUMMER </pre>
<pre> \prevcountervalue [...] *  NAME </pre>
<pre> \preventmode [...,*...] *  NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>

<pre> \prevsubcountervalue [...] [...] 1  NAME 2  NUMMER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>
<pre> \primasubpagina </pre>
<pre> \procent </pre>
<pre> \processezabloc [...] [...] [...] 1  NAME 2  NAME 3  criteriu = text ABSCHNITT </pre>
<pre> \processaction [...] [...] 1  BEFEHL 2  APPLY </pre>
<pre> \processallactionsinset [...] [...] 1  BEFEHL 2  APPLY </pre>
<pre> \processassignlist [...] \... 1  TEXT 2  CSNAME </pre>
<pre> \processassignmentcommand [...] \... 1  KEY = VALUE 2  CSNAME </pre>
<pre> \processassignmentlist [...] \... 1  KEY = VALUE 2  CSNAME </pre>
<pre> \processbetween {...} \... 1  NAME 2  CSNAME </pre>
<pre> \processbodyfontenvironmentlist \... *  CSNAME </pre>
<pre> \processcolorcomponents {...} *  COLOR </pre>
<pre> \processcommacommand [...] \... 1  BEFEHL 2  CSNAME </pre>
<pre> \processcommalist [...] \... 1  BEFEHL 2  CSNAME </pre>

<pre> \processcommalistwithparameters [...<sup>1</sup>,...] \<sup>2</sup>... 1  BEFEHL 2  CSNAME </pre>
<pre> \processcontent {...} \<sup>2</sup>... 1  NAME 2  CSNAME </pre>
<pre> \processfile {...} *  FILE </pre>
<pre> \processfilemany {...} *  FILE </pre>
<pre> \processfilenone {...} *  FILE </pre>
<pre> \processfileonce {...} *  FILE </pre>
<pre> \processfirstactioninset [...<sup>1</sup>] [...,<sup>2</sup>=&gt;...,...] 1  BEFEHL 2  APPLY </pre>
<pre> \processisolatedchars {...} \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \processisolatedwords {...} \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \processlinetablebuffer [...<sup>1</sup>] *  BUFFER OPT </pre>
<pre> \processlinetablefile {...} *  FILE </pre>
<pre> \processlist {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} \<sup>4</sup>... 1  CHARACTER 2  CHARACTER 3  TEXT 4  CSNAME </pre>
<pre> \processMPbuffer [...<sup>*</sup>,...] *  NAME OPT </pre>
<pre> \processMPfigurefile {...} *  FILE </pre>
<pre> \processmonth {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1  NUMMER 2  NUMMER 3  BEFEHL </pre>
<pre> \processranges [...<sup>1</sup>,...] \<sup>2</sup>... 1  NUMMER NUMMER:NUMMER 2  CSNAME </pre>

<pre> \processseparatedlist [...] [...] {...} 1 TEXT 2 TEXT 3 CSNAME BEFEHL </pre>
<pre> \processTeXbuffer [...] * BUFFER OPT </pre>
<pre> \processtokens {...} {...} {...} {...} {...} 1 BEFEHL 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 TEXT </pre>
<pre> \processuntil \*. * CSNAME </pre>
<pre> \processxtablebuffer [...] * NAME OPT </pre>
<pre> \processyear {...} {...} {...} {...} 1 NUMMER 2 BEFEHL 3 BEFEHL 4 BEFEHL </pre>
<pre> \produs [...] * FILE </pre>
<pre> \produs ... * FILE </pre>
<pre> \profiledbox [...] [...] [...] {...} 1 niciunul fixat strict halfixed quarterfixed eightsfixed NAME 2 inherits: \setupprofile 3 CONTENT </pre>
<pre> \profilegivenbox {...} ... 1 niciunul fixat strict halfixed quarterfixed eightsfixed NAME 2 CSNAME NUMMER </pre>
<pre> \program [...] * NAME </pre>
<pre> \proiect [...] * FILE </pre>
<pre> \proiect ... * FILE </pre>
<pre> \pseudoMixedCapped {...} * TEXT </pre>
<pre> \pseudoSmallCapped {...} * TEXT </pre>
<pre> \pseudoSmallcapped {...} * TEXT </pre>



<p><b>\pseudosmallcapped {...}</b></p> <p>* TEXT</p>
<p><b>\punct {...}</b></p> <p>* CHARACTER</p>
<p><b>\puncte [...]</b></p> <p>* NUMMER <small>OPT</small></p>
<p><b>\puncte [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \setupperiods <small>OPT</small></p>
<p><b>\punedeasuprafiecareia {...} {...}</b></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><b>\punefatainfata {...} {...}</b></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><b>\puneformula [...,*,...]</b></p> <p>* + - REFERENCE <small>OPT</small></p>
<p><b>\punelista [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]</b></p> <p>1 LISTE <small>OPT</small></p> <p>2 inherits: \seteazalista</p>
<p><b>\punelistacombinata [...]<sup>1</sup> [...,<sup>2</sup>...,...]</b></p> <p>1 LISTE <small>OPT</small></p> <p>2 inherits: \seteazalista</p>
<p><b>\puneCOMBINEDLIST [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazalista <small>OPT</small></p> <p>instances: content</p>
<p><b>\setarecontent [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazalista</p>
<p><b>\punenotesubsol [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \setupnote <small>OPT</small></p>
<p><b>\punenotesubsollocale [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \setupnote <small>OPT</small></p>
<p><b>\punenumarpagina</b></p>
<p><b>\puneregistru [...]<sup>1</sup> [...,<sup>2</sup>...,...]</b></p> <p>1 NAME <small>OPT</small></p> <p>2 inherits: \seteazaregistru</p>
<p><b>\puneREGISTER [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazaregistru <small>OPT</small></p> <p>instances: index</p>
<p><b>\completindex [...,..<sup>*</sup>...,...]</b></p> <p>* inherits: \seteazaregistru <small>OPT</small></p>

<p><code>\punesubformula [...<sup>2</sup>,...]</code></p> <p>* + - REFERENCE      OPT</p>
<p><code>\purenumber {...}</code></p> <p>* NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \*...</code></p> <p>* CSNAME</p>
<p><code>\pushbar [...<sup>1</sup>] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbutton [...<sup>1</sup>] [...<sup>2</sup>]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushculoare [...<sup>1</sup>] ... \popculoare</code></p> <p>* COLOR</p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushfundal [...<sup>1</sup>] ... \popfundal</code></p> <p>* NAME</p>
<p><code>\pushindentation ... \popindentation</code></p>
<p><code>\pushMPdrawing ... \popMPdrawing</code></p>
<p><code>\pushmacro \*...</code></p> <p>* CSNAME</p>
<p><code>\pushmathstyle ... \popmathstyle</code></p>
<p><code>\pushmode [...<sup>1</sup>]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...<sup>1</sup>]</code></p> <p>* NAME      OPT</p>
<p><code>\pushpath [...<sup>1</sup>] ... \poppath</code></p> <p>* PATH</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...<sup>1</sup>} ... \popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...<sup>1</sup>}</code></p> <p>* NAME</p>

<code>\putboxincache {<sup>1</sup>..} {<sup>2</sup>..} <sup>3</sup>..</code> 1 NAME 2 NUMMER TEXT 3 CSNAME NUMMER
<code>\putnextboxincache {<sup>1</sup>..} {<sup>2</sup>..} \<sup>3</sup>.. {<sup>4</sup>..}</code> 1 NAME 2 NUMMER TEXT 3 CSNAME 4 CONTENT
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [<sup>*</sup>..]</code> * NUMMER <small>OPT</small>
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {<sup>*</sup>..}</code> * FILE
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {<sup>1</sup>..} \<sup>2</sup>.. {<sup>3</sup>..}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {<sup>*</sup>..}</code> * TEXT
<code>\randomnumber {<sup>1</sup>..} {<sup>2</sup>..}</code> 1 NUMMER 2 NUMMER
<code>\rawcounter [<sup>1</sup>..] [<sup>2</sup>..]</code> 1 NAME <small>OPT</small> 2 NUMMER
<code>\rawcountervalue [<sup>*</sup>..]</code> * NAME

<pre> \rawdate [...] * inherits: \datacurenta </pre>
<pre> \rawdoifelseinset {...} {...,<sup>2</sup>...} {...} {...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \rawdoifinset {...} {...,<sup>2</sup>...} {...} 1 TEXT 2 TEXT 3 TRUE </pre>
<pre> \rawdoifinsetelse {...} {...,<sup>2</sup>...} {...} {...} 1 TEXT 2 TEXT 3 TRUE 4 FALSE </pre>
<pre> \rawgetparameters [...] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \rawprocessaction [...] [...,<sup>2</sup>=&gt;...,...] 1 BEFEHL 2 APPLY </pre>
<pre> \rawprocesscommacommand [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawprocesscommalist [...,<sup>1</sup>...] \<sup>2</sup>... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawstructurelistuservariable {...} * KEY </pre>
<pre> \rawsubcountervalue [...] [<sup>2</sup>...] 1 NAME 2 NUMMER </pre>
<pre> \rbox ... {<sup>2</sup>...} 1 TEXT <sup>OPT</sup> 2 CONTENT </pre>
<pre> \readfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>
<pre> \readfixfile {...} {...} {...} {...} 1 PATH 2 FILE 3 TRUE 4 FALSE </pre>
<pre> \readjobfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>

<code>\readlocfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readsetfile {...} {...} {...} {...}</code> 1 PATH 2 FILE 3 TRUE 4 FALSE
<code>\readsysfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readtexfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readxmlfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\realsmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...]<sup>1</sup> [...]<sup>2</sup></code> 1 implicit text titlu numar pagina realpage 2 REFERENCE
<code>\REFERENCEFORMAT {...}<sup>1</sup> {...}<sup>2</sup> [...]<sup>3</sup></code> 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referinta [...]<sup>1</sup>, [...] {...}<sup>2</sup></code> 1 REFERENCE 2 TEXT

\referintapagina [... <sup>*</sup> ...] *   REFERENCE
\referintatext [... <sup>1</sup> ...] {.. <sup>2</sup> .} 1   REFERENCE 2   TEXT
\referring (... <sup>1</sup> ...) (... <sup>2</sup> ...) [... <sup>3</sup> .] 1   POSITION 2   POSITION 3   REFERENCE
\reflexie {...} *   CONTENT
\registerattachment [... <sup>1</sup> .] [... <sup>2</sup> ...] 1   NAME 2   inherits: \setupattachment
\attachment [... <sup>1</sup> .] [... <sup>2</sup> ...] 1   NAME           OPT           OPT 2   inherits: \setupattachment
\registerctxluafile {... <sup>1</sup> .} {... <sup>2</sup> .} 1   FILE 2   NUMMER
\registerexternalfigure [... <sup>1</sup> .] [... <sup>2</sup> .] [... <sup>3</sup> ...] 1   FILE                   OPT           OPT 2   NAME 3   inherits: \setupexternalfigure
\registerfontclass {... <sup>*</sup> .} *   NAME
\registerhyphenationexception [... <sup>1</sup> .] [... <sup>2</sup> .] 1   SPRACHE                   OPT 2   TEXT
\registerhyphenationpattern [... <sup>1</sup> .] [... <sup>2</sup> .] 1   SPRACHE                   OPT 2   TEXT
\registermenubuttons [... <sup>1</sup> .] [... <sup>2</sup> .] 1   NAME 2   TEXT
\registersort [... <sup>1</sup> .] [... <sup>2</sup> .] 1   SINGULAR 2   NAME
\registersynonym [... <sup>1</sup> .] [... <sup>2</sup> .] 1   SINGULAR 2   NAME
\registerunit [... <sup>1</sup> .] [... <sup>2</sup> ...] 1   prefix unitate operator suffixe simbol packaged 2   KEY = VALUE

\REGISTER [...] [... <sup>2</sup> ...+...] 1 TEXT PROCESSOR->TEXT 2 INDEX instances: index
\veziindex [...] [... <sup>2</sup> ...+...] {... <sup>3</sup> } 1 TEXT PROCESSOR->TEXT 2 INDEX 3 TEXT PROCESSOR->TEXT
\REGISTER [...] {... <sup>2</sup> } [... <sup>3</sup> ...+...] 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: index
\regular
\relatemarking [...] [... <sup>2</sup> ] 1 BESCHRIFTUNG 2 BESCHRIFTUNG
\relateparameterhandlers {... <sup>1</sup> } {... <sup>2</sup> } {... <sup>3</sup> } {... <sup>4</sup> } 1 NAME 2 NAME 3 NAME 4 NAME
\relaxvalueifundefined {...} * NAME
\remainingcharacters
\remarca (... <sup>1</sup> ,...) (... <sup>2</sup> ,...) [... <sup>3</sup> ... <sup>3</sup> ...] <sup>OPT</sup> {... <sup>4</sup> } 1 POSITION 2 POSITION 3 inherits: \seteazainconjurat 4 TEXT
\removebottomthings
\removedepth
\removefromcommalist {... <sup>1</sup> } \... <sup>2</sup> ... 1 TEXT 2 CSNAME
\removelastskip
\removelastspace
\removemarkedcontent [... <sup>*</sup> ] * NAME
\removepunctuation
\removesubstring ... \from ... \to \... <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME

\removetoks <sup>1</sup> ... \from \ <sup>2</sup> ... 1 BEFEHL 2 CSNAME
\removeunwantedspaces
\replacefeature [...] * NAME
\replacefeature {...} * NAME
\replaceincommalist \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1 CSNAME 2 NUMMER
\replaceword [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 NAME 2 TEXT 3 TEXT
\rescan {...} * CONTENT
\rescanwithsetup {\ <sup>1</sup> ...} {\ <sup>2</sup> ...} 1 NAME 2 CONTENT
\resetallattributes
\resetandaddfeature [...] * NAME
\resetandaddfeature {...} * NAME
\resetbar
\resetboxesincache {...} * NAME
\resetbreakpoints
\resetbuffer [...] * BUFFER
\resetcharacteralign
\resetcharacterkerning
\resetcharacterspacing
\resetcharacterstripping
\resetcollector [...] * NAME



\resetcounter [...] [...] 1 NAME OPT 2 NUMMER
\resetdigitsmanipulation
\resetdirection
\reseteazamarcaje [...] * BESCHRIFTUNG
\resetfeature
\resetflag {...} * NAME
\resetfontcolorscheme
\resetfontfallback [...] [...] 1 NAME OPT 2 FONT
\resetfontsolution
\resethyphenationfeatures
\resetinjector [...] * NAME
\resetinteractionmenu [...] * NAME
\resetitaliccorrection
\resetlayer [...] * NAME
\resetlocalfloats
\resetMPdrawing
\resetMPenvironment
\resetMPinstance [...] * NAME
\resetmarker [...] * NAME
\resetmode {...} * NAME
\resetpagenumber

\resetparallel [...] <sup>1</sup> [...] <sup>2</sup> ,...] 1 NAME OPT 2 NAME tot
\resetpath
\resetpenalties \*... * CSNAME
\resetprofile
\resetrecurselevel
\resetreference [...] * NAME
\resetreplacement
\resetscript
\resetsetups [...] * NAME
\resetshownsynonyms [...] * SINGULAR
\resetsubpagenumber
\resetsymbolset
\resetssystemmode {...} * NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\reshapebox {...} * BEFEHL

<pre> \resolvedglyphdirect {...} {...} 1  FONT 2  e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME </pre>
<pre> \resolvedglyphstyled {...} {...} 1  FONT 2  e:NAME x:NUMMER d:NUMMER s:NUMMER i:NUMMER n:NAME c:NAME u:NAME a:NAME </pre>
<pre> \restartcounter [...] [...<sup>2</sup>] [...<sup>3</sup>] 1  NAME 2  NUMMER 3  NUMMER </pre>
<pre> \restorebox {...} {...<sup>2</sup>} 1  NAME 2  NAME </pre>
<pre> \restorecatcodes </pre>
<pre> \restorecounter [...] *  NAME </pre>
<pre> \restorecurrentattributes {...} *  NAME </pre>
<pre> \restoreendofline </pre>
<pre> \restoreglobalbodyfont </pre>
<pre> \reusableMPgraphic {...} {...<sup>2</sup>...} 1  NAME 2  KEY = VALUE </pre>
<pre> \reuseMPgraphic {...} {...<sup>2</sup>...} 1  NAME 2  KEY = VALUE </pre>
<pre> \reuserandomseed </pre>
<pre> \revivefeature </pre>
<pre> \rfence {...} *  CHARACTER </pre>
<pre> \rhbox {...} *  CONTENT </pre>
<pre> \rightbottombox {...} *  CONTENT </pre>
<pre> \rightbox {...} *  CONTENT </pre>
<pre> \righthbox {...} *  CONTENT </pre>

$\backslash right LABEL text \{...\}$ * KEY instances: head label mathlabel
$\backslash rightline \{...\}$ * CONTENT
$\backslash rightorleftpageaction \{.^1.\} \{.^2.\}$ 1 BEFEHL 2 BEFEHL
$\backslash rightskipadaption$
$\backslash rightsubguillemot$
$\backslash righttopleft$
$\backslash righttopleftthbox \{.^1.\} \{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash righttopleftvbox \{.^1.\} \{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash righttopleftvtop \{.^1.\} \{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash righttopbox \{...\}$ * CONTENT
$\backslash riglatext \{.^1.\} \{.^2.\}$ 1 sus centru sub <sup>OPT</sup> sol 2 TEXT
$\backslash rigleumplere \{...\} \{.^1.\} \{.^2.\} \{.^3.\}$ 1 inherits: \seteazarigleumplere OPT OPT 2 TEXT 3 TEXT
$\backslash rlap \{...\}$ * CONTENT
$\backslash robustaddtocommalist \{.^1.\} \{.^2.\}$ 1 TEXT 2 CSNAME
$\backslash robustdoifelseinset \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 TEXT 2 TEXT 3 TRUE 4 FALSE
$\backslash robustdoifinsetelse \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 TEXT 2 TEXT 3 TRUE 4 FALSE

<code>\robustpretocommalist {...} \<sup>1</sup>...</code> 1 TEXT 2 CSNAME
<code>\rollbutton [...,\<sup>1</sup>...,...] \<sup>2</sup>... [\<sup>3</sup>...]</code> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
<code>\rollbutton [\<sup>1</sup>...] [\<sup>2</sup>...,...\<sup>3</sup>...] \<sup>4</sup>... [\<sup>4</sup>...]</code> 1 NAME OPT OPT 2 inherits: \setezameniuinteractiune 3 TEXT 4 REFERENCE
<code>\roman</code>
<code>\roteste [...,\<sup>1</sup>...,...] {\<sup>2</sup>...}</code> 1 inherits: \setezarotare 2 CONTENT
<code>\rtop \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledhbox \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledhpack \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledmbox {...}</code> * CONTENT
<code>\ruledtopv \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledtpack \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledvbox \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledvpack \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\ruledvtop \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 TEXT OPT 2 CONTENT
<code>\runMPbuffer [...,\<sup>1</sup>*,...] \<sup>2</sup>...</code> * NAME OPT
<code>\runninghbox {...}</code> * CONTENT

<code>\ScaledPointsToBigPoints {...} \<sup>1</sup>...</code> 1    DIMENSION 2    CSNAME
<code>\ScaledPointsToWholeBigPoints {...} \<sup>2</sup>...</code> 1    DIMENSION 2    CSNAME
<code>\Smallcapped {...}</code> *    TEXT
<code>\safechar {...}</code> *    NUMMER
<code>\sans</code>
<code>\sansaldin</code>
<code>\sansnormal</code>
<code>\sansserif</code>
<code>\savebox {...} {...} {...}</code> 1    NAME 2    NAME 3    CONTENT
<code>\savebtxdataset [...]<sup>1</sup> [...]<sup>2</sup> [...,...]<sup>3</sup>...,...]</code> 1    NAME                    OPT            OPT            OPT 2    FILE 3    dataset    =    NAME type           =    bib lua xml fisier        =    FILE criteriu     =    tot text intro referinta curent aici precedent local componenta SECTIONBLOCK:tot SECTIONBLOCK:referinta SECTIONBLOCK:curent SECTIONBLOCK:precedent
<code>\savebuffer [...,...]<sup>*</sup>...,...]</code> *    lista    =    NAME fisier    =    FILE prefix    =    da nu
<code>\savebuffer [...]<sup>1</sup>,...]</code> <code>[...]<sup>2</sup>]</code> 1    BUFFER 2    FILE
<code>\savecounter [...]</code> *    NAME
<code>\saveculoare ... \restoreculoare</code>
<code>\savecurrentattributes {...}</code> *    NAME
<code>\savenormalmeaning \<sup>*</sup>...</code> *    CSNAME

\save tagged twopassdata { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} { <sup>4</sup> ...} 1 NAME 2 NUMMER 3 NAME 4 CONTENT
\save twopassdata { <sup>1</sup> ...} { <sup>2</sup> ...} { <sup>3</sup> ...} 1 NAME 2 NUMMER 3 CONTENT
\sbox { <sup>*</sup> ...} * CONTENT
\scala [ <sup>1</sup> ...] [..., <sup>2</sup> ... <sub>OPT</sub> ,... <sub>OPT</sub> ] { <sup>3</sup> ...} 1 NAME 2 inherits: \setupscale 3 CONTENT
\scriebuffer [..., <sup>1</sup> ... <sub>OPT</sub> ] [..., <sup>2</sup> ... <sub>OPT</sub> ,...] 1 BUFFER 2 inherits: \seteazatyping
\type <sup>BUFFER</sup> [..., <sup>*</sup> ... <sub>OPT</sub> ,...] * inherits: \seteazatyping
\scrieinlista [ <sup>1</sup> ...] [..., <sup>2</sup> ... <sub>OPT</sub> ,...] { <sup>3</sup> ...} { <sup>4</sup> ...} 1 LISTE 2 inherits: \seteazalista 3 NUMMER 4 TEXT
\scrieintreliste [ <sup>1</sup> ...] [..., <sup>2</sup> ... <sub>OPT</sub> ,...] { <sup>3</sup> ...} 1 LISTE 2 inherits: \seteazalista 3 BEFEHL
\SCRIPT instances: hangul hanzi nihongo ethiopic thai latin test
\ethiopic
\hangul
\hanzi
\latin
\nihongo
\test
\thai
\scrismanual

\secondoffivearguments {...} {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

\secondoffourarguments {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

\secondofsixarguments {...} {...} {...} {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

\secondofthreearguments {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT

\secondofthreeunexpanded {...} {...} {...}

1 TEXT  
2 TEXT  
3 TEXT

\secondoftwoarguments {...} {...}

1 TEXT  
2 TEXT

\secondoftwounexpanded {...} {...}

1 TEXT  
2 TEXT

\SECTION [...,<sup>1</sup>...] {...<sup>2</sup>}

1 REFERENCE OPT  
2 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

\SECTION [...,<sup>\*</sup>...] [...]

\* titlu = TEXT  
semncarte = TEXT  
marcaje = TEXT  
lista = TEXT  
referinta = REFERENCE  
numarpropriu = TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

\SECTION [...,<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE OPT  
2 NUMMER  
3 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject



```
\veziREGISTER [...]1 [...+...+...]2 {...}3
1 TEXT PROCESSOR->TEXT
2 INDEX
3 TEXT PROCESSOR->TEXT
instances: index
```

```
\puneindex [...,...*...,...]
* inherits: \seteazaOPTregistru
```

```
\select {...}1 {...}2 {...}3 {...}4 {...}5 {...}6
1 NAME OPT OPT OPT OPT OPT
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT
```

```
\selecteazablocuri [...,1...] [...,2...] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 criteriu = text ABSCHNITT
```

```
\semncarte [...]1 {...}2
1 ABSCHNITT LISTE
2 TEXT
```

```
\serializecommalist [...,*...]
* BEFEHL
```

```
\serializedcommalist
```

```
\serif
```

```
\serifbold
```

```
\serifnormal
```

```
\setare [...]*
* NAME
```

```
\setareitemization [...,1...] [...,2...,...]
1 NAME NAME:NUMMER OPT
2 inherits: \setupitemgroup
```

```
\setareitemize [...,1...] [...,2...] [...,3...,...]
1 fiecare NUMMER OPT OPT OPT
2 inherits: \setupitemgroup
3 inherits: \setupitemgroup
```

```

\setarelimba [...] [...]
1  SPRACHE implicitOPT
2  implicit      = SPRACHE
    stare       = start stop
    data        = inherits: \datacurenta
    patterns    = FILE
    lefthyphenmin = NUMBER
    righthyphenmin = NUMBER
    lefthyphenchar = NUMBER
    righthyphenchar = NUMBER
    setups      = NAME
    spatiere    = broad impachetat
    font        = auto
    text        = TEXT
    limittext   = TEXT
    hyphen      = TEXT
    compoundhyphen = TEXT
    leftcompoundhyphen = TEXT
    rightcompoundhyphen = TEXT
    minicitatstanga = BEFEHL
    minicitatdreapta = BEFEHL
    citatstanga = BEFEHL
    citatdreapta = BEFEHL
    leftspeech = BEFEHL
    rightspeech = BEFEHL
    propozitiestanga = BEFEHL
    middlespeech = BEFEHL
    propozitiedreapta = BEFEHL
    midsentence = BEFEHL
    subpropozitiestanga = BEFEHL
    subpropozitiedreapta = BEFEHL
    factor      = da nu

```

```

\setarepozitie [...] [...]
1  NAME          OPT
2  offset      = da nu
    unitate    = ex em pt in cm mm sp bp pc dd cc nc
    stare      = start overlay
    xoffset     = DIMENSION
    yoffset     = DIMENSION
    xstep      = absolut relativ
    ystep      = absolut relativ
    xscala     = NUMBER
    yscala     = NUMBER
    xfactor    = NUMBER
    yfactor    = NUMBER
    factor     = NUMBER
    scala     = NUMBER

```

```

\setare {...}
*  NAME

```

```

\setbar [...]
*  NAME

```

```

\setbigbodyfont

```

```

\setboxllx 1... {2...}
1  CSNAME NUMBER
2  DIMENSION

```

```

\setboxlly 1... {2...}
1  CSNAME NUMBER
2  DIMENSION

```

```

\setbreakpoints [...]
*  reset NAME

```

```

\setbuffer [...] ... \endbuffer
*  NAME

```

```
\setcapstrut
```

`\setcatcodetable \dots`

\* CSNAME

```
\setcharacteralign {...} {...}
```

1 NUMMER

2 TEXT number->TEXT text->TEXT

```
\setcharactercasing [..]
```

\* reset CUVANT cuvant Cuvant Cuvinte majuscula Majuscula niciunul aleator mixed camel cap Cap

```
\setcharactercleaning [..]
```

```
* reset 1
```

`\setcharacterkerning [...]`

```
* reset NAME
```

`\setcharacterspacing [...]`

```
*  reset NAME
```

`\setcharacterstripping [...]`

```
* reset 1
```

`\setcharstrut {...}`

\* TEXT

$$\backslash \text{setcollector} \left[ \overset{1}{\dots} \right] \left[ \dots, \overset{2}{\dots} = \dots, \dots \right] \left\{ \overset{3}{\dots} \right\}$$

1 NAME

OPT

```
2 inherits: \setupcollector
```

### 3 CONTENT

```
\setcolormodel [..]
```

```
*  black bw gri rgb cmyk tot niciunul
```

```
\setcounter [...] [.^2.] [...] [.^3.]
```

1 NAME

OPT

1	NAME
2	NUMMER

3 NUMMER

```
\setcounterown [...] [.^2.] [.^3.]
```

1 NAME

OPT

1	NAME
2	NUMMER

3 TEXT

```
\setcurrentfontclass {...}
```

\* NAME

```
\setdataset [...] [...] [...,...3...,...]
```

1 NAME

OPT

1	NAME
2	NAME

```

3  KEY  =  VALUE

```

```
\setdefaultpenalties
```

`\setdigitsmanipulation [...]`

```
* reset NUMMER
```

<pre>\setdirection [...]</pre> <pre>*   NUMMER</pre>
<pre>\setdocumentargument {...} {...}</pre> <pre>1   NAME</pre> <pre>2   TEXT</pre>
<pre>\setdocumentargumentdefault {...} {...}</pre> <pre>1   NAME</pre> <pre>2   TEXT</pre>
<pre>\setdocumentfilename {...} {...}</pre> <pre>1   NUMMER</pre> <pre>2   TEXT</pre>
<pre>\setdummyparameter {...} {...}</pre> <pre>1   KEY</pre> <pre>2   BEFEHL</pre>
<pre>\seteazaaliniat [...,*,...]</pre> <pre>*   [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle</pre> <pre>      DIMENSION NAME</pre>
<pre>\seteazaalinieria [...,*,...]</pre> <pre>*   broad larg subsol inaltime linie inalt jos lohi flushright flushleft centru da nu latime normal reset intern</pre> <pre>      extern flushinner flushouter stanga dreapta center dezactivat ultim end paragraf lefttoright righttoleft l2r</pre> <pre>      r2l tabelul lesshyphenation morehyphenation suspendat nothanging hz fullhz nohz despsilabe nedespsilabe tolerant</pre> <pre>      foartetolerant dilatat extremestretch final 2*final 3*final 4*final</pre>
<pre>\seteazaantet [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</pre> <pre>1   text margine bordura</pre> <pre>2   inherits: \setuplayoutelement</pre>
<pre>\seteazaaranjareapag [...,*,...]</pre> <pre>*   dezactivat oglindit douafete negativ 90 180 270 reset fundal normal 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP 2DOWN</pre> <pre>      2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW</pre> <pre>      1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME</pre>

\setezaaspect [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]

```

1  NAME OPT
2  stare = start stop normal repetat
   margine = DIMENSION
   bordura = DIMENSION
   distantamargine = DIMENSION
   distantabordura = DIMENSION
   distantabordurastanga = DIMENSION
   distantacoltdreapta = DIMENSION
   distantamarginestanga = DIMENSION
   distantamarginedreapta = DIMENSION
   distantasus = DIMENSION
   distantaantet = DIMENSION
   distantasubsol = DIMENSION
   distantajos = DIMENSION
   preset = NAME
   marginestanga = DIMENSION
   marginedreapta = DIMENSION
   bordurastanga = DIMENSION
   borduradreapta = DIMENSION
   antet = DIMENSION
   subsol = DIMENSION
   sus = DIMENSION
   jos = DIMENSION
   spatiuspate = DIMENSION
   spatiusus = DIMENSION
   setups = NAME
   cutspace = DIMENSION
   latime = DIMENSION centru ajustat
   spatiujos = DIMENSION
   linii = NUMMER
   inaltime = DIMENSION centru ajustat
   offsetoriz = DIMENSION
   veroffset = DIMENSION
   coloane = NUMMER
   distantacoloane = DIMENSION
   metoda = implicit normal NAME
   locatie = stanga centru dreapta sus subsol ofata douafete
   latimetext = DIMENSION
   inaltimetext = DIMENSION
   nx = NUMMER
   ny = NUMMER
   dx = DIMENSION
   dy = DIMENSION
   scala = NUMMER
   sx = NUMMER
   sy = NUMMER
   marcaje = on dezactivat pagina gol culoare unu doi patru
   grid = da nu dezactivat
   textdistance = DIMENSION
   alternativ = implicit normal marcaj NAME
   clipoffset = DIMENSION
   cropoffset = DIMENSION
   trimoffset = DIMENSION
   bleedoffset = DIMENSION
   artoffset = DIMENSION

```

\setezaaspect [...]

\* reset NAME

\seteazabarainteractiune [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]

```

1  NAME OPT
2  alternativ = a b c d e f g
   stare = start stop
   comanda = CSNAME
   latime = DIMENSION
   inaltime = DIMENSION max broad
   inaltime = DIMENSION max
   distanta = DIMENSION
   pas = mic mediu mare
   culoarefundal = COLOR
   stil = STYLE BEFEHL
   culoare = COLOR
   culoarecontrast = COLOR
   simbol = da nu
   inherits: \seteazainconjurat

```

**\seteazablanc** [...,\*,...]

\* inherits: \vspacing<sup>OPT</sup>

**\seteazabloc** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 inainte = BEFEHL  
dupa = BEFEHL  
intern = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

**\seteazablocsectiune** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 NAME <sup>OPT</sup>  
2 pagina = inherits: \pagina  
inainte = BEFEHL  
dupa = BEFEHL  
numar = da nu

**\seteazabuffer** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...]

1 BUFFER <sup>OPT</sup>  
2 inainte = BEFEHL  
dupa = BEFEHL

**\seteazacamp** [...<sup>1</sup>] [...,<sup>2</sup>,...] [...,..<sup>3</sup>...,...] [...,..<sup>4</sup>...,...] [...,..<sup>5</sup>...,...]

1 NAME <sup>OPT</sup>  
2 reset eticheta incadrat orizontal vertical  
3 inherits: \setupfieldtotalframed  
4 inherits: \setupfieldlabelframed  
5 inherits: \setupfieldcontentframed

**\seteazacampuri** [...,<sup>1</sup>,...] [...,..<sup>2</sup>...,...] [...,..<sup>3</sup>...,...] [...,..<sup>4</sup>...,...]

1 reset eticheta incadrat<sup>OPT</sup> orizontal vertical <sup>OPT</sup>  
2 inherits: \setupfieldtotalframed  
3 inherits: \setupfieldlabelframed  
4 inherits: \setupfieldcontentframed

**\seteazaclipping** [...,..<sup>\*</sup>...,...]

\* stare = start stop  
latime = DIMENSION  
inaltime = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
x = NUMMER  
y = NUMMER  
nx = NUMMER  
ny = NUMMER  
sx = NUMMER  
sy = NUMMER  
offsetstanga = DIMENSION  
offsetdreapta = DIMENSION  
offsetsus = DIMENSION  
offsetjos = DIMENSION  
mp = NAME  
n = NUMMER  
offset = DIMENSION

**\seteazacoloane** [...,..<sup>\*</sup>...,...]

\* n = NUMMER  
distanta = DIMENSION  
optiune = fundal  
offset = DIMENSION  
comanda = \...##1  
inaltime = DIMENSION  
directie = stanga dreapta  
balanta = da nu  
aliniere = setupalign  
toleranta = setuptolerance  
blanc = inherits: \blanc  
nsus = NUMMER  
rigla = on dezactivat BEFEHL

\seteazacommentariu [...<sup>1</sup>,...] [...<sup>2</sup>...,...]

```
1 NAME OPT
2 stare = start stop niciunul
metoda = normal ascuns
simbol = Comment Ajutor Insert Cheie Newparagraph Note Paragraf Default
latime = ajustat DIMENSION
inaltime = ajustat DIMENSION
inaltime = ajustat DIMENSION
titlu = TEXT
subtitlu = TEXT
autor = TEXT
nx = NUMMER
ny = NUMMER
culoare = COLOR
optiune = xml max
textlayer = NAME
locatie = bordurastanga borduradreaapta inmarginestanga marginedreaapta text inalt niciunul
distanta = DIMENSION
spatiu = da
buffer = BUFFER
```

\seteazacommentariupagina [...<sup>\*</sup>...,...]

```
* locatie = stanga dreapta sus subsol niciunul
stare = start stop niciunul
offset = DIMENSION
distanta = DIMENSION
latime = DIMENSION
inaltime = DIMENSION
```

\comment [...<sup>1</sup>] [...<sup>2</sup>...,...] {...<sup>3</sup>}

```
1 TEXT OPT OPT
2 inherits: \seteazacommentariu
3 TEXT
```

\seteazaculoare [...]

```
* FILE
```

\seteazaculori [...<sup>\*</sup>...,...]

```
* stare = start stop
spot = da nu
expansiune = da nu
factor = da nu
rgb = da nu
cmyk = da nu
conversie = da nu totdeauna
pagecolormodel = auto niciunul NAME
culoaretext = COLOR
intent = overprint knockout niciunul
```

\seteazadimensiunihartie [...<sup>1</sup>] [...<sup>2</sup>...,...]

```
1 NAME OPT
2 sus = BEFEHL
jos = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
metoda = normal niciunul NAME
scala = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
latime = DIMENSION
inaltime = DIMENSION
spatiusus = DIMENSION
spatiuspate = DIMENSION
offset = DIMENSION
pagina = reset vedere oglindit negativ rotat 90 180 270 NAME
hartie = reset vedere oglindit negativ rotat 90 180 270 NAME
optiune = ajustat max
distanta = DIMENSION
```

```

\seteazadimensiunihartie [...,1...] [...,2...]
1  reset vedere oglindit negativ rotatOPT 90 180 270OPTNAME
2  reset vedere oglindit negativ rotat 90 180 270 NAME

```

```

\seteazaecraninteractiune [...,*...]
*  latime      = ajustat max tight DIMENSION
   inaltime   = ajustat max tight DIMENSION
   spatiuspate = DIMENSION
   offsetoriz  = DIMENSION
   veroffset   = DIMENSION
   spatiusus   = DIMENSION
   optiune     = ajustat max ofata douafete semncarte auto niciunul implicit fixat vedere portrait pagina foaie
   copies      = NUMMER
   intarziere  = niciunul NUMMER

```

```

\seteazaelemente [...,1...] [...,2...]
1  NAMEOPT
2  alternativ  = stanga dreapta sus subsol inmarginie
   latimetext = DIMENSION
   latime     = DIMENSION
   distanta   = DIMENSION
   simbol     = niciunul NAME
   aliniere   = stanga centru dreapta flushleft flushright intern extern margine
   textalign  = stanga centru dreapta flushleft flushright intern extern
   n          = NUMMER
   inainte    = BEFEHL
   dupa       = BEFEHL
   intre      = BEFEHL

```

```

\seteazaenumerare [...,1...] [...,2...]
1  NAMEOPT
2  inherits: \setupenumeration

```



```

\seteazafloat [...1,...] [...2,...]
1 SINGULAR OPT
2 aliniaturmator = da nu auto
implicit = inherits: \placefloat
fallback = inherits: \placefloat
intern = BEFEHL
criteriu = DIMENSION
metoda = NUMMER
sidemethod = NUMMER
textmethod = NUMMER
sidealign = inalttime adancime linie jumatatelinie grila normal
grid = CD:STRING
local = da nu
comanda = \...#1
availablewidth = DIMENSION
availableheight = DIMENSION
latimeminima = DIMENSION
latimemaxima = DIMENSION
locatie = stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin
inneredge outeredge spatuspate cutspace marginestanga marginedreapta bordurastanga
borduradreapta
distantamarginestanga = DIMENSION
distantamarginedreapta = DIMENSION
marginestanga = DIMENSION
marginedreapta = DIMENSION
innermargin = DIMENSION
outermargin = DIMENSION
bottombefore = BEFEHL
bottomafter = BEFEHL
expansiune = da nu xml
referenceprefix = + - TEXT
xmlsetup = NAME
catcodes = NAME
freeregion = da nu
spatiuinainte = niciunul inherits: \blanc
spatiudupa = niciunul inherits: \blanc
latime = DIMENSION
inalttime = DIMENSION
offset = DIMENSION niciunul overlay
spatiulateralinainte = niciunul inherits: \blanc
spatiulateraldupa = niciunul inherits: \blanc
margine = DIMENSION
nsus = DIMENSION
njos = DIMENSION
pas = mic mediu mare linie adancime
nlinii = NUMMER
cache = da nu

```

```

\seteazafloats [...1,...] [...2,...]
1 SINGULAR OPT
2 inherits: \seteazafloat

```

```

\seteazafonttext [...*,...]
* DIMENSION NAME global reset x xx mic mare script scriptscript rm ss tt hw cg roman serif regular sans sansserif
suport type teletype mono scrismmanual caligrafic

```

```

\seteazaformulare [...*,...]
* metoda = XML HTML PDF
export = da nu

```

```

\seteazaformule [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setupformula

```

```

\seteazafundal [...1,...] [...2,...]
1 NAME OPT
2 stare = start stop
offsetstanga = DIMENSION
offsetdreapta = DIMENSION
offsetsus = DIMENSION
offsetjos = DIMENSION
inainte = BEFEHL
dupa = BEFEHL
inherits: \seteazainconjurat

```

```

\seteazafundaluri [...,1...] [...,2...] [...,3...,...]
1  sus antet text subsol subsol OPT
2  bordurastanga marginestanga text marginedreapta borduradreapta
3  inherits: \seteazainconjurat

```

```

\seteazafundaluri [...,1...] [...,2...,...]
1  foaie pagina paginastangaOPT paginadreapta text ascuns
2  stare = start stop
   inherits: \seteazainconjurat

```

```

\seteazagrosimelinie [...*]
*  mic mediu mare DIMENSION

```

```

\seteazaimpartireafloat [...,*...,...]
*  inainte = BEFEHL
   dupa    = BEFEHL
   intre   = BEFEHL
   linii   = auto NUMMER
   conversie = NAME

```

```

\seteazainconjurat [...,1...] [...,2...,...]
1  NAME OPT
2  colt          = rectangular rotund NUMMER
   coltframe     = rectangular rotund NUMMER
   coltfundal    = rectangular rotund NUMMER
   raza          = DIMENSION
   razaframe     = DIMENSION
   razafundal    = DIMENSION
   inaltime      = DIMENSION
   adancimeframe = DIMENSION
   adancimefundal = DIMENSION
   culoareframe  = COLOR
   framesus      = on dezactivat NAME
   framejos      = on dezactivat NAME
   framestanga   = on dezactivat NAME
   framedreapta  = on dezactivat NAME
   region        = da nu
   grosimerigla  = DIMENSION
   offsetframe   = DIMENSION
   frame         = on dezactivat overlay niciunul
   fundal        = primplan culoare NAME
   offsetfundal  = incadrat DIMENSION
   component     = NAME
   extras        = BEFEHL
   foregroundstyle = STYLE BEFEHL
   foregroundcolor = COLOR
   setups        = NAME
   offset        = implicit overlay niciunul DIMENSION
   latime        = local ajustat max broad fixat DIMENSION
   inaltime      = ajustat max broad DIMENSION
   aliniere      = inherits: \seteazaalinierea
   strut         = da nu niciunul local global
   autostrut     = da nu
   locatie       = inaltime adancime inalt jos sus centru subsol linie lohi suspendat mentine formula matematica
                  normal
   autolatime    = da nu fortat
   linii         = NUMMER
   sus          = BEFEHL
   jos          = BEFEHL
   blanc        = da nu
   profile       = NAME
   gol          = da nu
   loffset       = DIMENSION
   roffset       = DIMENSION
   toffset       = DIMENSION
   boffset       = DIMENSION
   orientation   = NUMMER

```

**\setezaingust** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
 2 stanga = DIMENSION  
 mijloc = DIMENSION  
 dreapta = DIMENSION  
 implicit = [-+]stanga [-+]centru [-+]dreapta NUMMER\*stanga NUMMER\*centru NUMMER\*dreapta reset  
 inainte = BEFEHL  
 dupa = BEFEHL

**\seteazainteractiunea** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
 2 stare = start stop  
 stil = STYLE BEFEHL  
 culoare = COLOR  
 culoarecontrast = COLOR  
 titlu = TEXT  
 subtitlu = COLOR  
 autor = TEXT  
 data = TEXT  
 keyword = TEXT  
 focus = standard incadrat latime latimeminima inaltime inaltime minima ajustat tight  
 meniu = on dezactivat  
 fieldlayer = auto NAME  
 calculeaza = REFERENCE  
 click = da nu  
 display = normal nou  
 pagina = da nu pagina nume auto  
 actiunedeschidere = REFERENCE  
 actiuneinchidere = REFERENCE  
 actiunedeschiderepagina = REFERENCE  
 actiuneinchiderepagina = REFERENCE  
 setsimbol = NAME  
 inaltime = DIMENSION  
 inaltime = DIMENSION  
 focusoffset = DIMENSION

**\seteazainteractiunea** [...]

\* NAME OPT

**\seteazajos** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 text margine b<sup>OT</sup>rdura  
 2 inherits: \setuplayoutelement

**\seteazalegenda** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
 2 inherits: \setupfloatcaption

**\seteazalegende** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
 2 inherits: \setupfloatcaption

**\punechemical** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmarginestanga  
 marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime  
 adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine  
 [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva  
 effective antet subsol  
 2 REFERENCE  
 3 TEXT  
 4 CONTENT

**\punefigure** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmarginestanga  
 marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime  
 adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine  
 [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva  
 effective antet subsol  
 2 REFERENCE  
 3 TEXT  
 4 CONTENT

**\punegraphic** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

1 split totdeauna<sup>OPT</sup> stanga<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspate cutspace instanga indreapta inmargine marginestanga  
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime  
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine  
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva  
effective antet subsol  
2 REFERENCE  
3 TEXT  
4 CONTENT

**\puneintermezzo** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

1 split totdeauna<sup>OPT</sup> stanga<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspate cutspace instanga indreapta inmargine marginestanga  
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime  
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine  
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva  
effective antet subsol  
2 REFERENCE  
3 TEXT  
4 CONTENT

**\punetable** [...<sup>1</sup>,...] [...<sup>2</sup>,...] {...<sup>3</sup>} {...<sup>4</sup>}

1 split totdeauna<sup>OPT</sup> stanga<sup>OPT</sup> dreapta<sup>OPT</sup> intern extern spatiuspate cutspace instanga indreapta inmargine marginestanga  
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime  
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine  
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva  
effective antet subsol  
2 REFERENCE  
3 TEXT  
4 CONTENT

**\seteazaliniesilabe** [...<sup>1</sup>,...<sup>\*</sup>,...] [...<sup>2</sup>,...<sup>\*</sup>,...]

\* semn = normal larg

**\seteazaliniesubtire** [...<sup>1</sup>,...<sup>\*</sup>,...] [...<sup>2</sup>,...<sup>\*</sup>,...]

\* inaltime = max DIMENSION  
inaltime = max DIMENSION  
fundal = culoare  
frame = on dezactivat  
grosimerigla = DIMENSION  
alternativ = a b c niciunul  
culoarefundal = COLOR  
culoare = COLOR  
spatiereinterliniara = mic mediu mare NUMBER  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
n = NUMBER

**\seteazalinii** [...<sup>1</sup>,...] [...<sup>2</sup>,...<sup>\*</sup>,...]

1 NAME<sup>OPT</sup>  
2 optiune = impachetat  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
aliniat = inherits: \seteazaaliniat  
aliniera = inherits: \seteazaalinierea  
spatiu = da on dezactivat fixat implicit  
comanda = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR  
stanga = BEFEHL  
dreapta = BEFEHL

**\seteazaliniimargine** [...<sup>1</sup>,...] [...<sup>2</sup>,...<sup>\*</sup>,...]

1 NUMBER<sup>OPT</sup>  
2 inherits: \setupmarginrule

```
\seteazaliniinegre [...,.*=...,...]
```

```
*   latime      = max DIMENSION
    inaltime    = max DIMENSION
    inaltime    = max DIMENSION
    distanta    = DIMENSION
    n           = NUMBER
    alternativ    = a b
    stil        = STYLE BEFEHL
    culoare     = COLOR
    type        = mp da nu
    mp          = NAME
```

```
\seteazaliniiumplere [...,.*=...,...]
```

```
*   inainte     = BEFEHL
    dupa        = BEFEHL
    margine     = DIMENSION
    latime      = DIMENSION
    distanta    = DIMENSION
    grosimerigla = DIMENSION
    culoare     = COLOR
```

**\seteazalista** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 LISTE
2 stare = start stop
   locatie = niciunul aici
   type = simple comanda userdata
   criteriu = local intro referinta SECTIONBLOCK:referinta tot SECTIONBLOCK:tot text SECTIONBLOCK:text
             curent SECTIONBLOCK:curent aici precedent SECTIONBLOCK:precedent componenta ABSCHNITT
             SECTIONBLOCK:ABSCHNITT

   lista = NAME
   latime = ajustat broad auto DIMENSION
   inaltime = ajustat broad DIMENSION
   inaltime = ajustat broad DIMENSION
   simbol = unu doi trei niciunul implicit
   eticheta = da nu niciunul NAME
   starter = BEFEHL
   stopper = BEFEHL
   comanda = \...#1#2#3
   comandanumar = \...#1
   comandatext = \...#1
   comandapagina = \...#1
   numarpagina = da nu totdeauna
   numartitlu = da nu totdeauna
   inainte = BEFEHL
   dupa = BEFEHL
   intre = BEFEHL
   margine = niciunul DIMENSION
   distanta = niciunul DIMENSION
   alinieretitlu = da nu
   numberalign = stanga dreapta centru flushleft flushright intern extern
   aliniere = inherits: \seteazaalinierea
   suspenda = da nu
   stanga = BEFEHL
   dreapta = BEFEHL
   interactiune = da nu tot numar text titlu pagina numarsetiune numarpagina
   limittext = da nu TEXT
   stil = STYLE BEFEHL
   culoare = COLOR
   stilnumar = STYLE BEFEHL
   culoarenumar = COLOR
   stiltext = STYLE BEFEHL
   culoaretex = COLOR
   stilpagina = STYLE BEFEHL
   culoarepagina = COLOR
   referinta = NUMMER
   extras = NAME
   order = comanda tot titlu
   alternativ = a b c d e f g stanga dreapta sus subsol comanda niciunul interactive paragraf orizontal
              vertical NAME

   latimemaxima = DIMENSION
   pageprefix = da nu
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset = NAME
   pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                       ABSCHNITT:tot

   pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
   pageconversionset = NAME
   pagestarter = BEFEHL PROCESSOR->BEFEHL
   pagestopper = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \seteazainconjurat
```

**\seteazalistacombinata** [...<sup>1</sup>] [...<sup>2</sup>,...]

```
1 LISTE
2 inherits: \seteazalista
```

**\setareCOMBINEDLIST** [...<sup>\*</sup>,...]

```
* inherits: \seteazalista
instances: content
```

**\punecontent** [...<sup>\*</sup>,...]

```
* inherits: \seteazalista
```

**\seteazamajuscule** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 titlu = da nu  
sc = da nu  
stil = STYLE BEFEHL

**\seteazamakeup** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 pagina = inherits: \pagina  
comanda = BEFEHL  
latime = DIMENSION  
inaltime = DIMENSION  
aliniera = inherits: \seteazaaliniera  
setups = NAME  
sus = BEFEHL  
jos = BEFEHL  
inainte = BEFEHL  
dupa = BEFEHL  
locatie = sus  
referinta = REFERENCE  
pagestate = start stop  
stareantet = start stop inalt gol niciunul normal  
staresubsol = start stop inalt gol niciunul normal  
staresus = start stop inalt gol niciunul normal  
starejos = start stop inalt gol niciunul normal  
staretext = start stop inalt gol niciunul normal  
douafete = da nu gol  
stil = inherits: \value-style  
culoare = COLOR

**\seteazamarcaje** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 BESCHRIFTUNG OPT  
2 stare = start stop  
expansiune = da nu  
separator = BEFEHL  
filtercommand = \...##1

**\seteazameniuiinteractiune** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 alternativ = vertical orizontal ascuns  
category = NAME  
offsetstanga = overlay incadrat niciunul implicit DIMENSION  
offsetdreapta = overlay incadrat niciunul implicit DIMENSION  
offsetsus = overlay incadrat niciunul implicit DIMENSION  
offsetjos = overlay incadrat niciunul implicit DIMENSION  
latimemaxima = DIMENSION  
inaltimemaxima = DIMENSION  
itemalign = stanga centru dreapta flushleft flushright jos inalt lohi  
stare = start gol local  
stanga = BEFEHL  
dreapta = BEFEHL  
distanta = overlay DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
pozitie = da nu  
mijloc = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR  
aceeasipagina = da nu gol niciunul normal implicit  
culoarecontrast = COLOR  
inherits: \seteazainconjurat

**\seteazaminicitat** [...,<sup>\*</sup>...,...]

\* inherits: \setupdelimitedtext

**\seteazanumarpagina** [...,<sup>\*</sup>...,...]

\* inherits: \setupuserpagenumber

**\seteazanumarsubpagina** [...,<sup>\*</sup>...,...]

\* inherits: \setupcounter

\seteazanumartitlu [...]<sup>1</sup> [...]<sup>2</sup>

1 ABSCHNITT  
2 [-+]NUMMER

\seteazanumerotarelinii [...]<sup>1</sup>,...<sup>2</sup> [...],...<sup>2</sup>,...]

1 NAME OPT  
2 start = NUMMER  
pas = NUMMER  
metoda = pagina primul urmatorul  
conversie = NAME  
continua = da nu  
locatie = text begin end implicit stanga dreapta intern extern instanga indreapta margine inmargine  
distanta = DIMENSION  
alinieri = intern extern flushleft flushright stanga dreapta centru auto  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
margine = DIMENSION  
latime = margine DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazanumerotarepagina [...],...<sup>\*</sup>,...]

\* alternativ = ofata douafete  
pagina = inherits: \pagina  
strut = da nu  
comanda = \...##1  
stanga = BEFEHL  
dreapta = BEFEHL  
stare = start stop  
latime = DIMENSION  
locatie = antet subsol stanga centru dreapta instanga indreapta margine inmargine lamargine marginebordura  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazanumerotareparagrafe [...],...<sup>\*</sup>,...]

\* stare = start stop linie reset  
distanta = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

\seteazapaleta [...]

\* NAME

\seteazaparagrafe [...]<sup>1</sup> [...],...<sup>2</sup> [...],...<sup>3</sup>,...]

1 NAME OPT OPT  
2 fiecare NUMMER  
3 n = NUMMER  
inainte = BEFEHL  
dupa = BEFEHL  
latime = DIMENSION  
distanta = DIMENSION  
inaltime = DIMENSION ajustat  
sus = BEFEHL  
jos = BEFEHL  
alinieri = inherits: \seteazaalinieria  
intern = BEFEHL  
comanda = BEFEHL  
rigla = on dezactivat  
grosimerigla = DIMENSION  
culoareringla = COLOR  
stil = STYLE BEFEHL  
culoare = COLOR



\seteazaparafrage [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 NAME:NUMBER OPT
2 n = NUMBER
  inainte = BEFEHL
  dupa = BEFEHL
  latime = DIMENSION
  distanta = DIMENSION
  inaltime = DIMENSION ajustat
  sus = BEFEHL
  jos = BEFEHL
  aliniere = inherits: \seteazaalinierea
  intern = BEFEHL
  comanda = BEFEHL
  rigla = on dezactivat
  grosimerigla = DIMENSION
  culoarerigla = COLOR
  stil = STYLE BEFEHL
  culoare = COLOR
```

\seteazaplasareaopozita [...,\*...]

```
* stare = start stop
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
```

\seteazaprograme [...,\*...]

```
* stil = STYLE BEFEHL
  culoare = COLOR
```

\seteazareferinte [...,\*...]

```
* stare = start stop
  expansiune = da nu xml
  autofile = da nu
  export = da nu
  stanga = BEFEHL
  dreapta = BEFEHL
  latime = DIMENSION
  douafete = da nu
  interactiune = eticheta text simbol tot
  separator = BEFEHL
  prefix = + - TEXT
```

\seteazaregistru [...] [...] <sup>1</sup> <sub>2</sub> [...]

```

1 NAME NAME:NUMMER OPT
2 referencemethod = avans
  expansiune = da nu xml
  numarpropriu = da nu
  xmlsetup = NAME
  alternativ = a b A B
  metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
  compress = da nu tot
  criteriu = local text curent precedent tot ABSCHNITT
  pageprefixseparatorset = BEFEHL
  pageprefixconversionset = NAME
  pageprefixstarter = BEFEHL PROCESSOR->BEFEHL
  pageprefixstopper = BEFEHL PROCESSOR->BEFEHL
  pageprefixset = NAME
  pageprefixsegments = NUMBER NUMBER:NUMMER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot

  pageprefixconnector = BEFEHL
  pageprefix = da nu
  pageseparatorset = NAME
  pageconversionset = NAME
  pagestarter = BEFEHL PROCESSOR->BEFEHL
  pagestopper = BEFEHL PROCESSOR->BEFEHL
  pagesegments = NUMBER NUMBER:NUMMER NUMBER:* NUMBER:tot
  latimemaxima = DIMENSION
  indicator = da nu
  inainte = BEFEHL
  dupa = BEFEHL
  comanda = \...##1
  comandatext = \...##1
  deeptextcommand = \...##1
  comandapagina = \...##1
  distanta = DIMENSION
  interactiune = text numarpagina
  numarpagina = da nu
  simbol = a n niciunul 1 2 BEFEHL
  language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
  stil = STYLE BEFEHL
  culoare = COLOR
  stiltext = STYLE BEFEHL
  culoaretext = COLOR
  stilpagina = STYLE BEFEHL
  culoarepagina = COLOR
  n = NUMBER
  balanta = da nu
  aliniere = inherits: \seteazaalinierea
  numberorder = numere

```

\seteazaregistru [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...]

```

1  NAME                      OPT          OPT
2  NUMMER
3  referencemethod          = avans
   expansiune                = da nu xml
   numarpropriu              = da nu
   xmlsetup                  = NAME
   alternativ                 = a b A B
   metoda                    = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress                  = da nu tot impachetat
   criteriu                  = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset    = BEFEHL
   pageprefixconversionset   = NAME
   pageprefixstarter         = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper         = BEFEHL PROCESSOR->BEFEHL
   pageprefixset             = NAME
   pageprefixsegments        = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                               ABSCHNITT:tot
   pageprefixconnector       = BEFEHL
   pageprefix                = da nu
   pageseparatorset          = NAME
   pageconversionset         = NAME
   pagestarter               = BEFEHL PROCESSOR->BEFEHL
   pagestopper               = BEFEHL PROCESSOR->BEFEHL
   pagesegments              = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
   latimemaxima              = DIMENSION
   indicator                 = da nu
   inainte                   = BEFEHL
   dupa                      = BEFEHL
   comanda                   = \...##1
   comandatext               = \...##1
   deeptextcommand           = \...##1
   comandapagina             = \...##1
   distanta                  = DIMENSION
   interactiune              = text numarpagina
   numarpagina               = da nu
   simbol                    = a n niciunul 1 2 BEFEHL
   language                  = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scen SPRACHE
   stil                      = STYLE BEFEHL
   culoare                   = COLOR
   stiltext                  = STYLE BEFEHL
   culoaretext               = COLOR
   stilpagina                = STYLE BEFEHL
   culoarepagina             = COLOR
   n                          = NUMMER
   balanta                   = da nu
   aliniere                   = inherits: \seteazaalinierea
   numberorder               = numere

```

\setareREGISTER [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NUMMER                      OPT
2  inherits: \seteazaregistru
instances: index

```

\seteazarigletext [...<sup>\*</sup>,...]

```

*  inainte                   = BEFEHL
   dupa                      = BEFEHL
   intre                     = BEFEHL
   grosimerigla              = DIMENSION
   locatie                   = stanga inmarginie
   stil                      = STYLE BEFEHL
   culoare                   = COLOR
   culoarerigla              = COLOR
   latime                    = DIMENSION
   inaltime                  = DIMENSION
   distanta                  = DIMENSION
   corectieadancime          = on dezactivat
   fonttext                  = inherits: \seteazafonttext

```

**\seteazarigleumplere** [...,..<sup>\*</sup>...,...]

\*    inainte                = BEFEHL  
     dupa                 = BEFEHL  
     n                     = NUMBER  
     spatiereinterliniara = mic mediu mare NUMBER  
     distanta              = DIMENSION  
     latime                = ajustat broad DIMENSION  
     separator            = BEFEHL  
     stil                  = STYLE BEFEHL  
     culoare              = COLOR

**\seteazarotare** [...,..<sup>\*</sup>...,...]

\*    locatie = ajustat broad adancime inalt centru implicit normal  
     rotatie = stanga dreapta intern extern NUMBER  
     inherits: \seteazainconjurat

**\seteazasimbol** [...]

\*    NAME

**\seteazasinonime** [...,..<sup>1</sup>...,...][...,..<sup>2</sup>...,...]

1    SINGULAR                OPT  
2    expansiune              = da nu xml  
     alternativ               = primul ultim normal NAME  
     urmatorul               = BEFEHL  
     comanda                = \...##1##2##3  
     comandatext            = \...##1  
     synonymcommand        = \...##1  
     language               = implicit DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE  
     metoda                 = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc  
     criteriu                = curent precedent local text tot ABSCHNITT  
     stil                    = STYLE BEFEHL  
     culoare                = COLOR  
     stiltext                = STYLE BEFEHL  
     culoaretext            = COLOR  
     stilsinonim            = STYLE BEFEHL  
     culoaresinonim        = COLOR

**\abbreviation** [...<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}

1    NAME                    OPT  
2    TEXT  
3    CONTENT

**\seteazasortare** [...,..<sup>1</sup>...,...][...,..<sup>2</sup>...,...]

1    SINGULAR                OPT  
2    expansiune              = da nu xml  
     alternativ               = primul ultim normal NAME  
     urmatorul               = BEFEHL  
     comanda                = \...##1##2##3  
     comandatext            = \...##1  
     synonymcommand        = \...##1  
     language               = implicit DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE  
     metoda                 = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc  
     criteriu                = curent precedent local text tot ABSCHNITT  
     stil                    = STYLE BEFEHL  
     culoare                = COLOR  
     stiltext                = STYLE BEFEHL  
     culoaretext            = COLOR  
     stilsinonim            = STYLE BEFEHL  
     culoaresinonim        = COLOR

**\logo** [...<sup>1</sup>...] {...<sup>2</sup>}

1    NAME                    OPT  
2    CONTENT

**\seteazaspatiu** [...]

\*    fixat impachetat <sup>OPT</sup>broad

**\seteazaspatiualb** [...,..<sup>\*</sup>...,...]

\*    fix fixat flexibil linie <sup>OPT</sup>jumatatelinie quarterline niciunul mic mediu mare implicit DIMENSION

```

\seteazaspatiuiinterliniar [...1,...2,...]
1 NAME OPT
2 linie = DIMENSION
  inaltime = NUMBER
  inaltime = NUMBER
  inaltime minima = NUMBER
  mindepth = NUMBER
  distanta = DIMENSION
  sus = NUMBER inaltime
  jos = NUMBER
  dilatata = NUMBER
  shrink = NUMBER

```

```

\seteazaspatiuiinterliniar [...*,...]
* on deactivat reset auto mic mediu mare NUMBER DIMENSION

```

```

\seteazaspatiuiinterliniar [...*]
* NAME

```

```

\seteazasubsol [...1,...2,...]
1 text margine bordura OPT
2 inherits: \setuplayoutelement

```

```

\seteazasus [...1,...2,...]
1 text margine bordura OPT
2 inherits: \setuplayoutelement

```

```

\seteazatabele [...*,...]
* text = DIMENSION max
  split = da nu repetat auto
  frame = on deactivat
  NL = inherits: \blanc
  VL = mic mediu mare niciunul NUMBER
  HL = mic mediu mare niciunul NUMBER
  distanta = mic mediu mare niciunul
  aliniere = stanga centru dreapta
  comenzi = BEFEHL
  fonttext = inherits: \seteazafonttext
  grosimerigla = DIMENSION
  inaltime = strut NUMBER
  inaltime = strut NUMBER
  openup = DIMENSION

```

```

\seteazatabulatori [...1,...2,...3,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuptabulation

```

```

\seteazatext [...1,...2,...]
1 text margine bordura OPT
2 inherits: \setuplayoutelement

```

```

\seteazatexteantet [...1,...2,...3,...4,...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

```

```

\seteazatextejos [...1,...2,...3,...4,...5]
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

```

```
\seteazatextesubsol [...]1 [...]2 [...]3 [...]4 [...]5
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\seteazatextesus [...]1 [...]2 [...]3 [...]4 [...]5
1 text margine borduraOPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\seteazatextetext [...]1 [...]2 [...]3 [...]4 [...]5
1 text margine bordura OPT OPT OPT OPT OPT
2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
```

```
\setareLABELtext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
```

```
\presetbtxlabeltext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetheadtext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetlabeltext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetmathlabeltext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetoperatortext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetprefixtext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetsuffixtext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presettaglabeltext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

```
\presetunittext [...]1 [...]2...
1 SPRACHE OPT
2 KEY = VALUE
```

**\seteazatitlu** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1  ABSCHNITT          OPT
2  frontpartlabel      = NAME
   bodypartlabel       = NAME
   appendixlabel       = NAME
   backpartlabel       = NAME
   expansiune          = da nu xml
   catcodes             = NAME
   sectionresetset     = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   conversie           = NAME
   sectionstarter      = BEFEHL PROCESSOR->BEFEHL
   sectionstopper       = BEFEHL PROCESSOR->BEFEHL
   sectionset          = NAME
   sectionsegments     = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   referenceprefix     = + - TEXT
   stil                = STYLE BEFEHL
   culoare             = COLOR
   stiltext            = STYLE BEFEHL
   culoaretext         = COLOR
   stilnumar           = STYLE BEFEHL
   culoarenumar        = COLOR
   cuplare             = ABSCHNITT
   numarpropriu        = da nu
   beforesection       = BEFEHL
   aftersection        = BEFEHL
   insidesection       = BEFEHL
   numarincrement      = da nu lista gol
   punetitlu           = da nu ascuns gol
   numar              = da nu
   pagina              = inherits: \pagina
   marcaje             = pagina reset
   antet              = start stop inalt niciunul normal gol faramarcare NAME
   text               = start stop inalt niciunul normal gol faramarcare NAME
   subsol             = start stop inalt niciunul normal gol faramarcare NAME
   inainte            = BEFEHL
   dupa               = BEFEHL
   intre              = BEFEHL
   continua           = da nu
   alinieretitlu       = da nu obiectmobil
   spatiereinterliniara = NAME
   interactiune        = lista referinta
   internalgrid        = NAME
   grid               = normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu
                        jos niciunul linie strut box min max centru NAME
   aliniere           = inherits: \seteazaalinierea
   toleranta          = inherits: \seteazatoleranta
   strut              = da nu
   suspenda           = linie broad ajustat niciunul NUMBER
   margine            = DIMENSION
   aliniaturmator      = da nu auto
   alternativ          = text paragraf normal margine inmargine sus centru subsol reverse textmarginal NAME
   latime             = DIMENSION
   numberwidth        = DIMENSION
   latimetext         = DIMENSION
   distanta           = DIMENSION
   textdistance       = DIMENSION
   comandainainte     = BEFEHL
   comandadupa        = BEFEHL
   comanda            = \...##1##2
   comandatext        = \...##1
   deeptextcommand    = \...##1
   comandanumar       = \...##1
   deepnumbercommand  = \...##1
   locatie            = NAME
```

**\seteazatitluri** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1  ABSCHNITT          OPT
2  inherits: \seteazatitlu
```

**\chapter** [...<sup>1</sup>,...] {...<sup>2</sup>...}

```
1  REFERENCE          OPT
2  TEXT
```

<pre> \part [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>PT</sup> 2  TEXT </pre>
<pre> \section [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subject [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsection [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubject [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsection [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubject [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsection [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubject [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsection [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsubject [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsubsection [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \subsubsubsubsubsubject [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \title [...,<sup>1</sup>...] {...} 1  REFERENCE<sup>OPT</sup> 2  TEXT </pre>
<pre> \seteazatoleranta [...,*...] *  orizontal vertical foarteststrict strict tolerant foartetolerant spatiu dilatat </pre>
<pre> \seteazatranzitiepagina [...*] *  reset auto start aleator NUMMER </pre>



**\seteazatype** [ $\dots^1, \dots$ ] [ $\dots, \dots^2, \dots$ ]

1 NAME OPT  
2 optiune = mp lua xml parsed-xml nested tex context niciunul NAME  
comanda = CSNAME  
stanga = BEFEHL  
dreapta = BEFEHL  
tab = da nu NUMBER  
compact = absolut ultim tot  
escape = da nu TEXT PROCESSOR->TEXT  
stil = STYLE BEFEHL  
culoare = COLOR  
linii = da nu normal despsilabe  
spatiu = on dezactivat normal fixat dilatat

**\seteazatyping** [ $\dots^1, \dots$ ] [ $\dots, \dots^2, \dots$ ]

1 NAME OPT  
2 margineimpara = DIMENSION  
marginepara = DIMENSION  
margine = da nu standard DIMENSION  
optiune = mp lua xml parsed-xml nested tex context niciunul NAME  
stil = STYLE BEFEHL  
culoare = COLOR  
aliniere = inherits: \seteazaalinierea  
linii = da nu normal despsilabe  
spatiu = on dezactivat normal fixat dilatat  
keeptogether = da nu  
inainte = BEFEHL  
dupa = BEFEHL  
strip = da nu NUMBER  
range = NUMBER NAME  
tab = da nu NUMBER  
escape = da nu TEXT PROCESSOR->TEXT  
aliniaturmator = da nu auto  
continua = da nu  
start = NUMBER  
stop = NUMBER  
pas = NUMBER  
numerotare = fisier linie nu  
blanc = inherits: \blanc

**\seteazaur1** [ $\dots, \dots^*, \dots$ ]

\* stil = STYLE BEFEHL  
culoare = COLOR

**\setelementexporttag** [ $\dots^1$ ] [ $\dots^2$ ] [ $\dots^3$ ]

1 NAME OPT  
2 export nature pdf  
3 inline display mixed

**\setemeasure**  $\{\dots^1\} \{\dots^2\}$

1 NAME  
2 DIMENSION

**\setevalue**  $\{\dots^1\} \{\dots^2\}$

1 NAME  
2 CONTENT

**\setevariable**  $\{\dots^1\} \{\dots^2\} \{\dots^3\}$

1 NAME  
2 KEY  
3 VALUE

**\setevariables** [ $\dots^1$ ] [ $\dots, \dots^2, \dots$ ]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

**\setfirstline** [ $\dots^*$ ]

\* NAME OPT

<pre>\setflag {...} * NAME</pre>
<pre>\setfont ... * FONT</pre>
<pre>\setfontcolorsheme [...] * NAME</pre>
<pre>\setfontfeature {...} * NAME</pre>
<pre>\setfontsolution [...] * NAME</pre>
<pre>\setfontstrut</pre>
<pre>\setgmeasure {...} {...} 1 NAME 2 DIMENSION</pre>
<pre>\setgvalue {...} {...} 1 NAME 2 CONTENT</pre>
<pre>\setgvariable {...} {...} {...} 1 NAME 2 KEY 3 VALUE</pre>
<pre>\setgvariables [...] [...<sup>2</sup>...,...] 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE</pre>
<pre>\sethboxregister ...<sup>1</sup> {...} 1 CSNAME NUMMER 2 CONTENT</pre>
<pre>\sethyphenatedurlafter {...} * TEXT</pre>
<pre>\sethyphenatedurlbefore {...} * TEXT</pre>
<pre>\sethyphenatedurlnormal {...} * TEXT</pre>
<pre>\sethyphenationfeatures [...,<sup>*</sup>...] * NAME reset OPT</pre>
<pre>\setinitial [...]<sup>1</sup> [...,<sup>2</sup>...,...] 1 NAME OPT OPT 2 inherits: \setupinitial</pre>

<pre> \setinjector [...] [...] [...] 1  NAME 2  NUMMER 3  BEFEHL </pre>
<pre> \setinteraction [...] *  ascuns NAME </pre>
<pre> \setinterfacecommand {...} {...} 1  NAME 2  NAME </pre>
<pre> \setinterfaceconstant {...} {...} 1  NAME 2  NAME </pre>
<pre> \setinterfaceelement {...} {...} 1  NAME 2  NAME </pre>
<pre> \setinterfacemessage {...} {...} {...} 1  NAME 2  titlu NAME NUMMER 3  TEXT </pre>
<pre> \setinterfacevariable {...} {...} 1  NAME 2  NAME </pre>
<pre> \setinternalrendering [...] [...] [...] 1  NAME 2  auto embed 3  CONTENT </pre>
<pre> \setitaliccorrection [...] *  reset 1 2 </pre>
<pre> \setJSreamble {...} {...} 1  NAME 2  CONTENT </pre>
<pre> \setlayer [...] [...] [...] [...] [...] 1  NAME          OPT          OPT 2  stanga dreapta par impar 3  inherits: \setuplayer 4  CONTENT </pre>
<pre> \setlayerframed [...] [...] [...] [...] [...] [...] 1  NAME          OPT          OPT 2  inherits: \setuplayer 3  inherits: \seteazainconjurat 4  CONTENT </pre>
<pre> \setlayerframed [...] [...] [...] [...] [...] 1  NAME          OPT 2  inherits: \setuplayerinherits: \seteazainconjurat 3  CONTENT </pre>

<pre> \setlayertext [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] [<sup>3</sup>...<sub>OPT</sub>...] {...} 1  NAME 2  inherits: \setuplayer 3  aliniere = inherits: \seteazaalinierea    latime  = DIMENSION    stil    = STYLE BEFEHL    culoare = COLOR 4  TEXT </pre>
<pre> \setlinefiller [...] *  filler NAME </pre>
<pre> \setlocalhsize [...] *  [-+]DIMENSION <sub>OPT</sub> </pre>
<pre> \setMPlayer [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sub>OPT</sub>...] {...} 1  NAME 2  NAME 3  inherits: \setuplayer 4  CONTENT </pre>
<pre> \setMPpositiongraphic {...} {...} {...<sub>OPT</sub>...} 1  NAME 2  NAME 3  KEY = VALUE </pre>
<pre> \setMPpositiongraphicrange {...} {...} {...} {...<sub>OPT</sub>...} 1  NAME 2  NAME 3  NAME 4  KEY = VALUE </pre>
<pre> \setMPtext {...} {...} 1  NAME 2  TEXT </pre>
<pre> \setMPvariable [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] 1  NAME 2  KEY = VALUE </pre>
<pre> \setMPvariables [<sup>1</sup>...] [<sup>2</sup>...<sub>OPT</sub>...] 1  NAME 2  KEY = VALUE </pre>
<pre> \setmainbodyfont </pre>
<pre> \setmainparbuilder [...<sup>*</sup>...] *  implicit oneline basic NAME </pre>
<pre> \setmarker [<sup>1</sup>...] [<sup>2</sup>...] 1  NAME 2  NUMMER </pre>
<pre> \setmarking [...<sup>1</sup>...] {...<sup>2</sup>...} 1  BESCHRIFTUNG 2  TEXT </pre>
<pre> \setmathstyle {...<sup>*</sup>...} *  display text script scriptscript cramped uncramped normal impachetat mic mare NAME </pre>

<pre> \setmeasure {...} {...} 1  NAME 2  DIMENSION </pre>
<pre> \setmessagetext {...} {...} 1  NAME 2  NAME NUMBER </pre>
<pre> \setmode {...} *  NAME </pre>
<pre> \setnostrut </pre>
<pre> \setnote [...<sup>1</sup>] [...<sup>2</sup>,...<sup>3</sup>] {...} 1  NAME 2  REFERENCE 3  TEXT </pre>
<pre> \setnotetext [...<sup>1</sup>] [...<sup>2</sup>,...<sup>3</sup>] {...} 1  NAME 2  REFERENCE 3  TEXT </pre>
<pre> \setnotetext [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] 1  NAME 2  titlu      = TEXT    semncarte = TEXT    lista     = TEXT    referinta = REFERENCE </pre>
<pre> \setnote [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] 1  NAME 2  titlu      = TEXT    semncarte = TEXT    lista     = TEXT    referinta = REFERENCE </pre>
<pre> \setobject {...<sup>1</sup>} {...<sup>2</sup>} \...<sup>3</sup> {...<sup>4</sup>} 1  NAME 2  NAME 3  CSNAME 4  CONTENT </pre>
<pre> \setoldstyle </pre>
<pre> \setpagegrid [...<sup>1</sup>,...<sup>1</sup>,...] {...<sup>2</sup>} 1  c      = NUMBER OPT    r      = NUMBER    optiune = niciunul 2  CONTENT </pre>
<pre> \setpagereference {...<sup>1</sup>} {...<sup>2</sup>,...} 1  NAME 2  REFERENCE </pre>
<pre> \setpagestate [...<sup>1</sup>] [...<sup>2</sup>] 1  NAME 2  NAME NUMBER </pre>
<pre> \setpagestaterealpageno {...<sup>1</sup>} {...<sup>2</sup>} 1  NAME 2  NAME NUMBER </pre>

<pre> \setpenalties \... {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1 CSNAME 2 NUMMER 3 NUMMER </pre>
<pre> \setpercentdimen {<sup>1</sup>...} {<sup>2</sup>...} 1 DIMENSION CSNAME 2 DIMENSION NUMMER </pre>
<pre> \setposition {<sup>*</sup>...} * NAME </pre>
<pre> \setpositionbox {<sup>1</sup>...} \... {<sup>3</sup>...} 1 NAME 2 CSNAME 3 CONTENT </pre>
<pre> \setpositiondata {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} 1 NAME 2 DIMENSION 3 DIMENSION 4 DIMENSION </pre>
<pre> \setpositiondataplus {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...,...} 1 NAME 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 TEXT </pre>
<pre> \setpositiononly {<sup>*</sup>...} * NAME </pre>
<pre> \setpositionplus {<sup>1</sup>...} {<sup>2</sup>...,...} \... {<sup>4</sup>...} 1 NAME 2 TEXT 3 CSNAME 4 CONTENT </pre>
<pre> \setpositionstrut {<sup>*</sup>...} * NAME </pre>
<pre> \setprofile [...<sup>*</sup>...] * niciunul fixat strict halfixed quarterfixed eightsfixed NAME </pre>
<pre> \setrandomseed {<sup>*</sup>...} * NUMMER </pre>
<pre> \setreference [...<sup>1</sup>,...] [...<sup>2</sup>...,...] 1 REFERENCE 2 KEY = VALUE </pre>
<pre> \setreferencedobject {<sup>1</sup>...} {<sup>2</sup>...} \... {<sup>4</sup>...} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>

**\setregisterentry** [<sup>1</sup>...] [<sup>2</sup>...<sub>...</sub>] [<sup>3</sup>...<sub>...</sub>]

1 NAME OPT  
2 eticheta = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternativ = TEXT  
3 KEY = VALUE

**\setreplacement** [...]

\* reset NAME

**\setrigidcolumnbalance** ...

\* CSNAME NUMMER

**\setrigidcolumnhsize** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 DIMENSION  
2 DIMENSION  
3 NUMMER

**\setscript** [...]

\* hangul hanzi nihongo ethiopic thai test NAME

**\setsectionblock** [<sup>1</sup>...] [<sup>2</sup>...<sub>...</sub>] OPT

1 NAME  
2 semncarte = TEXT

**\setsimplecolumnhsize** [...<sub>...</sub>]

\* n = NUMMER  
latime = DIMENSION  
distanta = DIMENSION  
linii = NUMMER

**\setsmallbodyfont**

**\setsmallcaps**

**\setstackbox** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 NAME  
3 CONTENT

**\setstructurepageregister** [<sup>1</sup>...] [<sup>2</sup>...<sub>...</sub>] [<sup>3</sup>...<sub>...</sub>] OPT

1 NAME  
2 eticheta = NAME  
keys = TEXT PROCESSOR->TEXT  
entries = TEXT PROCESSOR->TEXT  
keys:1 = TEXT  
keys:2 = TEXT  
keys:3 = TEXT  
entries:1 = TEXT  
entries:2 = TEXT  
entries:3 = TEXT  
alternativ = TEXT  
3 KEY = VALUE

**\setstrut**

**\setsuperiors**

<pre> \setssystemmode {...} *   NAME </pre>
<pre> \settabular </pre>
<pre> \settaggedmetadata [...,*...,...] *   KEY  =  VALUE </pre>
<pre> \settextcontent [...] [...] [...] [...] [...] 1   sus antet text subsol subsol      OPT      OPT 2   text margine bordura 3   stanga centru dreapta 4   data numarpagina BESCHRIFTUNG TEXT BEFEHL 5   data numarpagina BESCHRIFTUNG TEXT BEFEHL </pre>
<pre> \settightobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \settightreferencedobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \settightunreferencedobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>
<pre> \settrialtypesetting </pre>
<pre> \setuevalue {...} {...} 1   NAME 2   CONTENT </pre>
<pre> \setugvalue {...} {...} 1   NAME 2   CONTENT </pre>
<pre> \setunreferencedobject {...} {...} \... {...} 1   NAME 2   NAME 3   CSNAME 4   CONTENT </pre>



**\setupattachment** [...,<sup>1</sup>...] [...,<sup>2</sup>...]

```
1  NAME                      OPT
2  titlu                     = TEXT
   subtitlu                  = TEXT
   autor                     = TEXT
   fisier                    = FILE
   nume                      = NAME
   buffer                    = BUFFER
   stare                     = start stop
   metoda                    = normal ascuns
   simbol                    = Graph Paperclip Pushpin Default
   latime                    = ajustat DIMENSION
   inaltime                  = ajustat DIMENSION
   inaltime                  = ajustat DIMENSION
   culoare                   = COLOR
   textlayer                 = NAME
   locatie                   = bordurastanga borduradreaapta inmargine marginestanga marginedreaapta text inalt niciunul
   distanta                  = DIMENSION
```

**\setupattachments** [...,<sup>1</sup>...] [...,<sup>2</sup>...]

```
1  NAME                      OPT
2  inherits: \setupattachment
```

**\setupbackend** [...,<sup>\*</sup>...]

```
*  export                    = da FILE
   xhtml                     = FILE
   fisier                    = FILE
   intent                    = NAME
   spatiu                    = da nu
   xmpfile                   = FILE
   format                    = version implicit NAME
   nivel                     = NUMMER
   optiune                   = totdeauna niciodata
   profile                   = FILE
```

**\setupbar** [...,<sup>1</sup>...] [...,<sup>2</sup>...]

```
1  NAME                      OPT
2  culoare                   = COLOR
   continua                  = da nu tot
   gol                       = da nu
   unitate                   = ex em pt in cm mm sp bp pc dd cc nc
   order                     = primplan fundal
   grosimerigla              = DIMENSION
   metoda                    = NUMMER
   offset                    = NUMMER
   dy                        = NUMMER
   max                       = NUMMER
   foregroundstyle            = STYLE BEFEHL
   foregroundcolor            = COLOR
   mp                         = NAME
   stanga                     = TEXT
   dreapta                   = TEXT
```

**\setupbars** [...,<sup>1</sup>...] [...,<sup>2</sup>...]

```
1  NAME                      OPT
2  inherits: \setupbar
```

**\hiddenbar** {...}

```
*  CONTENT
```

**\nobar** {...}

```
*  CONTENT
```

**\overbar** {...}

```
*  CONTENT
```

**\overbars** {...}

```
*  CONTENT
```

<code>\overstrike {...}</code> *    CONTENT
<code>\overstrikes {...}</code> *    CONTENT
<code>\underbar {...}</code> *    CONTENT
<code>\underbars {...}</code> *    CONTENT
<code>\underdash {...}</code> *    CONTENT
<code>\underdashes {...}</code> *    CONTENT
<code>\underdot {...}</code> *    CONTENT
<code>\underdots {...}</code> *    CONTENT
<code>\underrandom {...}</code> *    CONTENT
<code>\underrandoms {...}</code> *    CONTENT
<code>\understrike {...}</code> *    CONTENT
<code>\understrikes {...}</code> *    CONTENT
<code>\setupbleeding [...,..<sup>*</sup>...,...]</code> *    latime     = DIMENSION *    inaltime  = DIMENSION *    offset    = DIMENSION *    hoffset   = DIMENSION *    voffset   = DIMENSION *    locatie   = t b l r bl lb br rb tl lt tr rt *    dilatata  = da nu *    pagina    = da nu
<code>\setupbookmark [...,..<sup>*</sup>...,...]</code> *    fortat         = da nu *    numar          = da nu *    numberseparatorset = NAME *    numberconversionset = NAME *    numberstarter    = BEFEHL *    numberstopper    = BEFEHL *    numbersegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot *    sectionblock     = da nu

\setupbtx [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 specification = implicit apa aps NAME
  dataset      = implicit NAME
  comanda       = \...##1
  stanga        = BEFEHL
  dreapta       = BEFEHL
  authorconversion = normal normalshort normalinverted invertedshort short
  etallimit     = NUMMER
  etaldisplay   = NUMMER
  etaloption    = ultim
  stopper       = initials
  interactiune  = start stop numar text pagina tot
  alternativ     = implicit category entry short pagina num textnum an index tag keywords autor authoryears
                  authornum authoryear
  sorttype      = normal reverse
  compress      = da nu
  implicit      = implicit NAME
  stil          = STYLE BEFEHL
  culoare       = COLOR
```

\setupbtxdataset [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 language = SPRACHE
```

\setupbtxlist [<sup>1</sup>...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 inherits: \seteazalista
```

\setupbtxregister [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 stare = start stop
  dataset = NAME
  field = keyword range numarpagina autor
  register = NAME
  metoda = once
  alternativ = normalshort invertedshort
  stil = STYLE BEFEHL
  culoare = COLOR
```

\setupbtxrendering [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 staretext = start stop
  pagestate = start stop
  separator = BEFEHL
  criteriu = precedent cite aici tot niciunul
  specification = NAME
  titlu = TEXT
  inainte = BEFEHL
  dupa = BEFEHL
  dataset = NAME
  metoda = dataset fortat local global niciunul
  sorttype = short dataset lista referinta folosit implicit cite index
  repeta = da nu
  group = NAME
  numerotare = da nu num index tag short pagina
```

\setupbtx [...]

```
* NAME
```

\setupbutton [<sup>1</sup>...,...] [<sup>2</sup>...,...]

```
1 NAME OPT
2 stare = start stop
  aceeasipagina = da nu gol niciunul normal implicit
  stil = STYLE BEFEHL
  culoare = COLOR
  culoarecontrast = COLOR
  alternativ = ascuns
  inherits: \seteazainconjurat
```

`\setupcharacterkerning [...1,...] [...2,...]`

1 NAME OPT  
2 factor = max NUMBER  
latime = DIMENSION  
features = NAME  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupcharacterspacing [...1] [...2] [...3,...]`

1 NAME OPT  
2 NUMBER  
3 stanga = NUMBER  
dreapta = NUMBER  
alternativ = 0 1

`\setupchemical [...1,...] [...2,...]`

1 NAME OPT  
2 strut = da nu auto cap ajustat linie implicit CHARACTER  
latime = ajustat niciunul NUMBER  
inaltime = ajustat niciunul NUMBER  
stanga = ajustat niciunul NUMBER  
dreapta = ajustat niciunul NUMBER  
sus = ajustat niciunul NUMBER  
jos = ajustat niciunul NUMBER  
scala = mic mediu mare normal NUMBER  
rotatie = NUMBER  
symalinie = auto  
axa = on dezactivat  
culoareframe = COLOR  
grosimerigla = DIMENSION  
offset = DIMENSION  
unitate = DIMENSION  
factor = NUMBER  
frame = on dezactivat  
culoarerigla = COLOR  
fonttext = inherits: \seteazafonttext  
dimensiune = mic mediu mare  
stil = STYLE BEFEHL  
culoare = COLOR

`\setupchemicalframed [...1,...] [...2,...]`

1 NAME OPT  
2 inherits: \seteazainconjurat

`\setupcollector [...1,...] [...2,...]`

1 NAME OPT  
2 rotatie = stanga dreapta intern extern NUMBER  
colt = stanga centru dreapta sus subsol  
x = DIMENSION  
y = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
locatie = stanga centru dreapta sus subsol linie l c r m t b g  
stare = start stop

`\setupcolumnspan [...*,...]`

\* n = NUMBER  
inherits: \seteazainconjurat

\setupcombination [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 nx = NUMBER  
ny = NUMBER  
latime = ajustat DIMENSION  
inaltime = ajustat DIMENSION  
locatie = stanga centru dreapta sus subsol  
distanta = DIMENSION  
alternativ = eticheta text  
aliniere = inherits: \seteazaalinierea  
continua = da nu  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR

\setupcounter [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 start = NUMBER  
counter = NAME  
metoda = pagina  
stare = start stop  
mod = bypagina byblock bytext byantet byABSCHNITT  
prefix = da nu  
prefixseparatorset = NAME  
prefixconversion = NAME  
prefixconversionset = NAME  
prefixstarter = BEFEHL PROCESSOR->BEFEHL  
prefixstopper = BEFEHL PROCESSOR->BEFEHL  
prefixset = NAME  
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:\* ABSCHNITT:tot  
numberorder = reverse  
numberseparatorset = NAME  
numberconversion = NAME  
numberconversionset = NAME  
numberstarter = BEFEHL PROCESSOR->BEFEHL  
numberstopper = BEFEHL PROCESSOR->BEFEHL  
numbersegments = NUMBER NUMBER:NUMBER NUMBER:\* NUMBER:tot  
type = primul precedent urmatorul ultim numar  
criteriu = strict pozitiv tot  
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupdataset [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 intarziere = da nu

\setupdelimitedtext [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
language = local global SPRACHE  
metoda = font  
repete = da nu  
locatie = text paragraf margine  
stanga = BEFEHL  
mijloc = BEFEHL  
dreapta = BEFEHL  
nextleft = BEFEHL  
nextright = BEFEHL  
spatiuinainte = inherits: \blanc  
spatiudupa = inherits: \blanc  
marginestanga = da nu standard DIMENSION  
marginedreapta = da nu standard DIMENSION  
aliniat = inherits: \seteazaaliniat  
aliniaturmator = da nu auto  
stil = STYLE BEFEHL  
culoare = COLOR  
stilsimbol = STYLE BEFEHL  
culoaresimbol = COLOR

\aside [...<sup>1</sup>] {...<sup>2</sup>}

1 SPRACHE OPT  
2 CONTENT

`\blockquote [...]1 {...}2`

1 SPRACHE OPT  
2 CONTENT

`\quotation [...]1 {...}2`

1 SPRACHE OPT  
2 CONTENT

`\quote [...]1 {...}2`

1 SPRACHE OPT  
2 CONTENT

`\speech [...]1 {...}2`

1 SPRACHE OPT  
2 CONTENT

`\setupdescription [...]1,...2 [...],...2,...]`

1 NAME OPT  
2 titlu = da nu  
nivel = NUMMER  
text = TEXT  
headcommand = \...##1  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
alternativ = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin  
outermargin serried suspendat sus comanda NAME  
alinie = inherits: \seteazaalinie  
headalign = inherits: \seteazaalinie  
aliniat = inherits: \seteazaaliniat  
display = da nu  
aliniaturmator = da nu auto  
latime = ajustat broad linie DIMENSION  
distanta = niciunul DIMENSION  
dilatata = NUMMER  
shrink = NUMMER  
suspenda = ajustat broad niciunul margine NUMMER  
closesymbol = BEFEHL  
closecommand = \...##1  
expansiune = da nu xml  
referenceprefix = + - TEXT  
exemplu = TEXT  
margine = da nu standard DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR  
stiltitlu = STYLE BEFEHL  
culoaretitlu = COLOR

`\setupdirections [...],...*,...]`

\* bidi = on dezactivat local global  
metoda = unu doi implicit  
fences = da nu  
break = ambele inainte

`\setupdocument [...],...*,...]`

\* inainte = BEFEHL  
dupa = BEFEHL  
metadata:author = TEXT  
metadata:title = TEXT  
metadata:subject = TEXT  
metadata:keywords = TEXT  
KEY = VALUE

`\setupeffect [...]1,...2 [...],...2,...]`

1 NAME OPT  
2 metoda = niciunul comanda  
dilatata = NUMMER  
grosimerigla = NUMMER  
alternativ = normal intern extern ambele ascuns dilatata

\setupenumeration [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                                OPT
2  titlu                               = da nu
   numar                               = da nu
   comandanumar                        = \...##1
   distantatitlu                       = DIMENSION
   stiltitlu                           = STYLE BEFEHL
   culoaretitlu                        = COLOR
   titlecommand                        = \...##1
   titleleft                           = BEFEHL
   titleright                          = BEFEHL
   stanga                              = BEFEHL
   dreapta                             = BEFEHL
   simbol                              = BEFEHL
   starter                             = BEFEHL
   stopper                             = BEFEHL
   cuplare                             = NAME
   counter                             = NAME
   nivel                               = NUMMER
   text                                = TEXT
   headcommand                         = \...##1
   inainte                             = BEFEHL
   dupa                                = BEFEHL
   intre                               = BEFEHL
   alternativ                           = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                                     outermargin serried suspendat sus comanda NAME

   aliniere                            = inherits: \seteazaalinierea
   headalign                           = inherits: \seteazaalinierea
   aliniat                             = inherits: \seteazaaliniat
   display                             = da nu
   aliniaturmator                      = da nu auto
   latime                              = ajustat broad linie DIMENSION
   distanta                            = niciunul DIMENSION
   dilatat                             = NUMMER
   shrink                              = NUMMER
   suspenda                            = ajustat broad niciunul margine NUMMER
   closesymbol                         = BEFEHL
   closecommand                        = \...##1
   expansiune                          = da nu xml
   referenceprefix                     = + - TEXT
   exemplu                             = TEXT
   margine                             = da nu standard DIMENSION
   stil                                = STYLE BEFEHL
   culoare                              = COLOR
   stiltitlu                           = STYLE BEFEHL
   culoaretitlu                        = COLOR
   inherits: \setupcounter

```

\setupenv [...<sup>\*</sup>,...]

```

*  set      = BEFEHL
   reset    = BEFEHL
   KEY      = VALUE

```

\setupexport [...<sup>\*</sup>,...]

```

*  aliniere    = flushleft centru flushright normal
   fonttext    = DIMENSION
   latime      = DIMENSION
   titlu       = TEXT
   subtitlu    = TEXT
   autor       = TEXT
   alternativ    = html div
   properties  = da nu
   hyphen      = da nu
   cssfile     = FILE
   primapagina = FILE
   ultimapagina = FILE

```

`\setupexternalfigure [...,1...] [...,2...,...]`

```

1  NAME                                OPT
2  latime                             = DIMENSION
   inaltime                           = DIMENSION
   eticheta                            = NAME
   pagina                             = NUMBER
   obiect                              = da nu
   prefix                             = TEXT
   metoda                             = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controale                          = da nu
   previzualizare                     = da nu
   mask                               = niciunul
   rezolutie                          = NUMBER
   culoare                             = COLOR
   arguments                          = TEXT
   repeta                             = da nu
   factor                             = ajustat broad max auto implicit
   hfactor                            = ajustat broad max auto implicit
   factorw                            = ajustat broad max auto implicit
   latimemaxima                       = DIMENSION
   inaltimemaxima                     = DIMENSION
   equalwidth                         = DIMENSION
   equalheight                        = DIMENSION
   scala                              = NUMBER
   xscala                             = NUMBER
   yscala                             = NUMBER
   s                                  = NUMBER
   sx                                 = NUMBER
   sy                                 = NUMBER
   linii                              = NUMBER
   locatie                            = local global implicit
   director                           = PATH
   optiune                            = test incadrat gol
   foregroundcolor                    = COLOR
   reset                              = da nu
   fundal                             = culoare primplan NAME
   frame                              = on dezactivat
   culoarefundal                      = COLOR
   aliniere                           = inherits: \seteazaalinierea
   xmax                               = NUMBER
   ymax                               = NUMBER
   frames                             = on dezactivat
   interactiune                       = da tot niciunul referinta layer semncarte
   fonttext                           = DIMENSION
   comment                            = BEFEHL TEXT
   dimensiune                         = niciunul media crop trim art
   cache                              = PATH
   resources                          = PATH
   display                            = FILE
   conversie                          = TEXT
   order                              = LISTE
   crossreference                     = da nu NUMBER

```

`\setupexternalsoundtracks [...,*...,...]`

`* optiune = repetat`

`\setupfieldbody [...,1...] [...,2...,...]`

```

1  NAME                                OPT
2  category = NAME
   inherits: \setupfieldcategory

```



**\setupfieldcategory** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 start = NUMBER
  stil = STYLE BEFEHL
  culoare = COLOR
  type = radio sub text linie push check signature
  values = TEXT
  implicit = TEXT
  culoareframecamp = COLOR
  culoarefundalcamp = COLOR
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = DIMENSION
  aliniere = stanga centru dreapta flushleft center flushright
  n = NUMBER
  simbol = NAME
  fieldlayer = NAME
  optiune = readonly obligatoriu protejat sortat nedisponibil nocheck fixat fisier ascuns tiparibil auto
  clickintru = REFERENCE
  clickies = REFERENCE
  regiuneintrare = REFERENCE
  regiuneiesire = REFERENCE
  dupatasta = REFERENCE
  format = REFERENCE
  verifica = REFERENCE
  calculeaza = REFERENCE
  focusin = REFERENCE
  focusout = REFERENCE
  openpage = REFERENCE
  closepage = REFERENCE
```

**\setupfieldcontentframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inherits: \seteazainconjuratinherits: \setupfieldcategory
```

**\setupfieldlabelframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inherits: \seteazainconjurat
```

**\setupfieldtotalframed** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  distanta = DIMENSION
  alternativ = reset eticheta incadrat orizontal vertical
  inherits: \seteazainconjurat
```

**\setupfiller** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 marginestanga = DIMENSION
  marginedreapta = DIMENSION
  stanga = BEFEHL
  dreapta = BEFEHL
  alternativ = simbol dilatat rigla spatiu
  metoda = local global centru broad
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = DIMENSION
  offset = DIMENSION
  distanta = DIMENSION
  aliniere = stanga dreapta centru flushleft flushright intern extern
  simbol = BEFEHL
  stil = STYLE BEFEHL
  culoare = COLOR
```

**\setupfirstline** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1 NAME OPT
2 n = NUMBER
  alternativ = implicit linie cuvant
  stil = STYLE BEFEHL
  culoare = COLOR
```

`\setupfittingpage [...1,...] [...2,...,...]`

```
1 NAME OPT
2 pagestate = start stop
  comanda = \...##1
  margine = pagina
  scala = NUMMER
  hartie = auto default NAME
inherits: \seteazainconjurat
```

`\setupfloatcaption [...1,...] [...2,...,...]`

```
1 NAME OPT
2 suffix = BEFEHL
  suffixseparator = BEFEHL
  suffixstopper = BEFEHL
  locatie = stanga dreapta centru jos inalt grila overlay intern extern innermargin outermargin marginestanga
            marginedreapta lefthanging righthanging suspenda sus subsol dilatat niciunul implicit
  comanda = \...##1
  comandanumar = \...##1
  comandatext = \...##1
  spatiuinainte = inherits: \blanc
  spaceinbetween = inherits: \blanc
  spatiudupa = inherits: \blanc
  distanta = DIMENSION
  intre = BEFEHL
  stil = STYLE BEFEHL
  culoare = COLOR
  offsetsus = DIMENSION
  offsetjos = DIMENSION
  numar = da nu niciunul
  group = TEXT
  marginestanga = DIMENSION
  marginedreapta = DIMENSION
  innermargin = DIMENSION
  outermargin = DIMENSION
  aliniere = inherits: \seteazaalinierea
  latime = ajustat max DIMENSION
  latimeminima = ajustat DIMENSION
  latimemaxima = DIMENSION
inherits: \setupcounter
```

`\setupfontexpansion [...1,...] [...2,...,...]`

```
1 NAME
2 vector = NAME
  factor = NUMMER
  dilatat = NUMMER
  shrink = NUMMER
  pas = NUMMER
```

`\setupfontprotrusion [...1,...] [...2,...,...]`

```
1 NAME
2 vector = NAME
  factor = NUMMER
  stanga = NUMMER
  dreapta = NUMMER
```

`\setupfonts [...*,...,...]`

```
* language = nu auto
```

`\setupfontsolution [...1,...] [...2,...,...]`

```
1 NAME OPT
2 goodies = FILE
  solution = NAME
  less = NAME
  more = NAME
  metoda = preroll split normal reverse aleator
  criteriu = NUMMER
```

```

\setupformula [...1,...] [...2...,...]
1  NAME                      OPT
2  locatie                   = stanga dreapta
    aliniere                 = stanga centru dreapta flushleft center flushright normal
    strut                    = da nu
    distanta                 = DIMENSION
    stanga                   = BEFEHL
    dreapta                  = BEFEHL
    spatiuinainte            = inherits: \blanc
    spatiudupa               = inherits: \blanc
    comandanumar             = \...##1
    culoare                  = COLOR
    stilnumar                = STYLE BEFEHL
    culoarenumar             = COLOR
    optiune                  = impachetat tight centru incadrat inherits: \seteazafonttext
    margine                  = da nu standard DIMENSION
    marginestanga            = DIMENSION
    marginedreapta          = DIMENSION
    alternativ                = NAME
    aliniaturmator           = da nu auto
    grid                     = inherits: \snaptogrid
    frame                    = numar
    expansiune               = da nu xml
    referenceprefix          = + - TEXT
    xmlsetup                 = NAME
    catcodes                 = NAME
    split                    = da nu
    inherits: \setupcounter

```

```

\setupformulaframed [...1,...] [...2...,...]
1  NAME                      OPT
2  inherits: \seteazainconjurat

```

```

\setupframedcontent [...1,...] [...2...,...]
1  NAME                      OPT
2  stanga                    = BEFEHL
    dreapta                  = BEFEHL
    leftoffser               = DIMENSION
    offsetdreapta            = DIMENSION
    offsetsus                = DIMENSION
    offsetjos                = DIMENSION
    corectielinie            = da nu
    inherits: \seteazainconjurat

```

```

\setupframedtext [...1,...] [...2...,...]
1  NAME                      OPT
2  stanga                    = BEFEHL
    dreapta                  = BEFEHL
    intern                   = BEFEHL
    locatie                  = stanga dreapta centru niciunul
    corectieadancime         = on dezactivat
    fonttext                 = inherits: \seteazafonttext
    aliniat                  = inherits: \seteazaaliniat
    stil                     = STYLE BEFEHL
    culoare                  = COLOR
    inherits: \seteazainconjuratinherits: \setupplacement

```

```

\setupglobalreferenceprefix [...]
*  + - TEXT

```

```

\setupheadalternative [...1,...] [...2...,...]
1  NAME                      OPT
2  alternativ                 = orizontal vertical undeva
    renderingsetup          = NAME

```

```

\setuphelp [...1,...] [...2...,...]
1  NAME                      OPT
2  inherits: \seteazainconjurat

```

`\helptext [...]1 {...}2 {...}3`

1 REFERENCE OPT  
2 TEXT  
3 TEXT

`\setuphigh [...]1,... [...]2,...]`

1 NAME OPT  
2 distanta = DIMENSION  
up = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

`\setuphighlight [...]1,... [...]2,...]`

1 NAME OPT  
2 comanda = da nu  
stil = STYLE BEFEHL  
culoare = COLOR

`\unitshigh {...}`

\* CONTENT

`\setuphyphenation [...]*,...]`

\* metoda = original tex implicit hyphenate expanded traditional niciunul

`\setupindentedtext [...]1,... [...]2,...]`

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
distanta = DIMENSION  
exemplu = TEXT  
text = TEXT  
latime = ajustat broad DIMENSION  
separator = BEFEHL  
stil = STYLE BEFEHL  
culoare = COLOR  
stiltitlu = STYLE BEFEHL  
culoaretitlu = COLOR

`\setupinitial [...]1,... [...]2,...]`

1 NAME OPT  
2 n = NUMBER  
m = NUMBER  
inainte = BEFEHL  
distanta = DIMENSION  
hoffset = DIMENSION  
voffset = linie DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR  
font = FONT  
text = TEXT  
locatie = margine text  
metoda = primul ultim auto niciunul

`\setupinsertion [...]1,... [...]2,...]`

1 NAME OPT  
2 locatie = pagina text coloane firstcolumn lastcolumn

`\setupitaliccorrection [...]*,...]`

\* text totdeauna global niciunul

```

\setupitemgroup [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT OPT
2 fiecare NUMMER
3 intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine lamargine intext
larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat reverse coloane unu doi trei patru
cinci six seven eight nine standard NUMMER*broad NUMMER*serried orizontal NAME
4 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
inaintetitlu = BEFEHL
dupatitlu = BEFEHL
textstanga = BEFEHL
textdreapta = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
factor = NUMMER
pas = DIMENSION
latime = DIMENSION
distanta = DIMENSION
margine = da nu standard DIMENSION
marginestanga = da nu standard DIMENSION
marginedreapta = da nu standard DIMENSION
aliniere = inherits: \seteazaalinierea
aliniat = inherits: \seteazaaliniat
start = NUMMER
symaliniere = stanga centru dreapta flushleft center flushright
simbol = NAME
n = NUMMER
aliniaturmator = da nu auto
intern = BEFEHL
comanda = CSNAME
elemente = NUMMER
latimemaxima = DIMENSION
itemalign = stanga dreapta centru flushleft flushright intern extern
alignsymbol = da nu
textdistance = mic mediu mare niciunul spatiu DIMENSION
punestopper = da nu
stil = STYLE BEFEHL
culoare = COLOR
stilititlu = STYLE BEFEHL
culoaretitlu = COLOR
stilmarcaj = STYLE BEFEHL
culoaremarcaj = COLOR
stilsimbol = STYLE BEFEHL
culoaresimbol = COLOR
grid = inherits: \definegridsnapping
inherits: \setupcounter

```

**\setupitemgroup** [...<sup>1</sup>...] [...<sup>2</sup>...]

```

1  NAME NAME:NUMMER      OPT
2  inainte      = BEFEHL
   dupa         = BEFEHL
   intre        = BEFEHL
   inaintetitlu = BEFEHL
   dupatitlu    = BEFEHL
   textstanga   = BEFEHL
   textdreapta  = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   factor       = NUMMER
   pas          = DIMENSION
   latime       = DIMENSION
   distanta     = DIMENSION
   optiune      = intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine
                  lamargine intext larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat
                  reverse coloane unu doi trei patru cinci six seven eight nine standard NUMMER*broad NUMMER*serried
                  orizontal NAME
   margine      = da nu standard DIMENSION
   marginestanga = da nu standard DIMENSION
   marginedreapta = da nu standard DIMENSION
   aliniere     = inherits: \seteazaalinierea
   aliniat      = inherits: \seteazaaliniat
   start        = NUMMER
   symaliniere  = stanga centru dreapta flushleft center flushright
   simbol       = NAME
   n            = NUMMER
   aliniaturmator = da nu auto
   intern       = BEFEHL
   comanda      = CSNAME
   elemente     = NUMMER
   latimemaxima = DIMENSION
   itemalign    = stanga dreapta centru flushleft flushright intern extern
   alignsymbol  = da nu
   textdistance = mic mediu mare niciunul spatiu DIMENSION
   punestopper  = da nu
   stil         = STYLE BEFEHL
   culoare      = COLOR
   stiltitlu    = STYLE BEFEHL
   culoaretitlu = COLOR
   stilmarcaj   = STYLE BEFEHL
   culoaremarcaj = COLOR
   stilsimbol   = STYLE BEFEHL
   culoaresimbol = COLOR
   grid         = inherits: \definegridsnapping
   inherits: \setupcounter

```

**\setareITEMGROUP** [...<sup>1</sup>...] [...<sup>2</sup>...] [...<sup>3</sup>...]

```

1  fiecare NUMMER      OPT
2  inherits: \setupitemgroup
3  inherits: \setupitemgroup
instances: itemize

```

\setuplabel [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 titlu = da nu
  numar = da nu
  comandanumar = \...##1
  distantatitlu = DIMENSION
  stiltitlu = STYLE BEFEHL
  culoaretitlu = COLOR
  titlecommand = \...##1
  titleleft = BEFEHL
  titleright = BEFEHL
  stanga = BEFEHL
  dreapta = BEFEHL
  simbol = BEFEHL
  starter = BEFEHL
  stopper = BEFEHL
  cuplare = NAME
  counter = NAME
  nivel = NUMMER
  text = TEXT
  headcommand = \...##1
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  alternativ = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
               outermargin serried suspendat sus comanda intext NAME

  aliniere = inherits: \seteazaalinierea
  headalign = inherits: \seteazaalinierea
  aliniat = inherits: \seteazaaliniat
  display = da nu
  aliniaturmator = da nu auto
  latime = ajustat broad linie DIMENSION
  distanta = niciunul DIMENSION
  suspenda = ajustat broad niciunul margine NUMMER
  closesymbol = BEFEHL
  closecommand = \...##1
  expansiune = da nu xml
  referenceprefix = + - TEXT
  exemplu = TEXT
  margine = da nu standard DIMENSION
  stil = STYLE BEFEHL
  culoare = COLOR
  stiltitlu = STYLE BEFEHL
  culoaretitlu = COLOR
  inherits: \setupcounter

```

\setuplayer [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1 NAME OPT
2 stare = start stop continuu urmatorul repetat
  optiune = test
  pagina = NUMMER
  latime = DIMENSION
  inaltime = DIMENSION
  region = NAME
  rotatie = stanga dreapta intern extern NUMMER
  pozitie = da nu overlay
  hoffset = max DIMENSION
  voffset = max DIMENSION
  offset = DIMENSION
  dx = DIMENSION
  dy = DIMENSION
  sx = NUMMER
  sy = NUMMER
  x = DIMENSION
  y = DIMENSION
  colt = stanga centru dreapta sus subsol
  locatie = grila stanga centru dreapta sus subsol linie l c r m t b g
  linie = NUMMER
  coloana = NUMMER
  directie = normal reverse
  douafete = da nu
  metoda = ajustat overlay
  repeta = da
  preset = lefttop righttop leftbottom rightbottom centru middletop middlebottom middleleft middleright lefttopleft
            lefttopright NAME

```

`\setuplayeredtext [...1,...] [...2,...]`

```
1 NAME OPT
2 stil = STYLE BEFEHL
  culoare = COLOR
  inherits: \seteazainconjurat
```

`\setuplayouttext [...1] [...2] [...3,...]`

```
1 sus antet text subso1 subso1OPT
2 text margine bordura
3 stare = start stop gol inalt niciunul normal faramarcare NAME
  stil = STYLE BEFEHL
  culoare = COLOR
  strut = da nu
  n = NUMMER
  inainte = BEFEHL
  dupa = BEFEHL
  stilstanga = STYLE BEFEHL
  stildreapta = STYLE BEFEHL
  culoarestanga = COLOR
  culoaredreapta = COLOR
  latime = DIMENSION
  latimestanga = DIMENSION
  marginedreapta = DIMENSION
```

`\setuplinefiller [...1,...] [...2,...]`

```
1 NAME OPT
2 locatie = stanga dreapta ambele
  scop = stanga dreapta local
  mp = NAME
  inaltime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  threshold = DIMENSION
  grosimerigla = DIMENSION
  inainte = BEFEHL
  dupa = BEFEHL
  culoare = COLOR
  stiltext = STYLE BEFEHL
  culoaretext = COLOR
  aliniere = inherits: \seteazaalinierea
```

`\setuplinefillers [...1,...] [...2,...]`

```
1 NAME OPT
2 inherits: \setuplinefiller
```

`\setuplinenote [...1,...] [...2,...]`

```
1 NAME OPT
2 compress = da nu
  compressmethod = separator stopper spatiu
  compressseparator = BEFEHL
  compressdistance = DIMENSION
  inherits: \setupnote
```

`\linenote {...}`

```
* TEXT
```



`\setuplinetable [...]1 [...]2 [...,...3...,...]`

```
1 r c OPT OPT
2 impar par antet NUMBER
3 linii = ajustat NUMBER
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  dilatat = da nu DIMENSION
  latimemaxima = ajustat DIMENSION
  nstanga = NUMBER
  n = NUMBER
  repeta = da nu
  nx = NUMBER
  latime = DIMENSION
  inaltime = ajustat linie DIMENSION
  distanta = DIMENSION
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  aliniere = inherits: \seteazaalinierea
  fundal = culoare
  culoarefundal = COLOR
  xheight = max DIMENSION
  xdepth = max DIMENSION
  stil = STYLE BEFEHL
  culoare = COLOR
```

`\setuplistalternative [...]1,... [...,...2...,...]`

```
1 NAME OPT
2 inainte = BEFEHL
  dupa = BEFEHL
  comanda = \...##1##2##3
  renderingsetup = NAME
  latime = DIMENSION
  distanta = DIMENSION
  dilatat = DIMENSION
  filler = BEFEHL
```

`\setuplistextra [...]1,... [...,...2...,...]`

```
1 NAME OPT
2 inainte = BEFEHL
  dupa = BEFEHL
```

`\setuplocalfloats [...,...*...,...]`

```
* inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
```

`\setuplocalinterlinespace [...]1,... [...,...2...,...]`

```
1 NAME OPT
2 inherits: \seteazaspatiuinterliniar
```

`\setuplocalinterlinespace [...]*,...`

```
* on dezactivat reset auto mic mediu mareOPT NUMBER DIMENSION
```

`\setuplocalinterlinespace [...]*`

```
* NAME
```

`\setuplow [...]1,... [...,...2...,...]`

```
1 NAME OPT
2 distanta = DIMENSION
  down = DIMENSION
  stil = STYLE BEFEHL
  culoare = COLOR
```

`\setuplowhigh [...1,...] [...2...,...]`

1 NAME OPT  
2 distanta = DIMENSION  
up = DIMENSION  
down = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

`\setuplowmidhigh [...1,...] [...2...,...]`

1 NAME OPT  
2 up = DIMENSION  
down = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

`\unitslow {...}`

\* CONTENT

`\setupMPgraphics [...*...,...]`

\* culoare = local global  
mpy = FILE

`\setupMPinstance [...1,...] [...2...,...]`

1 NAME OPT  
2 format = metafun mpost  
initializations = da nu  
setups = NAME  
stiltext = STYLE BEFEHL  
culoaretex = COLOR  
extensions = da nu  
metoda = binary decimal double scaled implicit

`\setupMPpage [...*...,...]`

\* inherits: \setupfittingpage

`\setupMPvariables [...1,...] [...2...,...]`

1 NAME OPT  
2 KEY = VALUE

`\setupmarginblock [...1,...] [...2...,...]`

1 NAME OPT  
2 stare = start stop  
latime = DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL  
alinieri = inherits: \seteazaaliniera  
stil = STYLE BEFEHL  
culoare = COLOR  
sus = BEFEHL  
jos = BEFEHL  
locatie = stanga dreapta centru inmargine  
stanga = BEFEHL  
dreapta = BEFEHL

```

\setupmargindata [...1...] [...2...]
1 NAME OPT
2 strut = da nu auto cap ajustat linie implicit CHARACTER
   comanda = \...##1
   latime = DIMENSION
   aliniere = inherits: \seteazaalinierea
   anchor = region text
   locatie = stanga dreapta intern extern
   metoda = sus linie primul adancime inaltime
   category = implicit bordura
   scop = local global
   optiune = text paragraf
   margine = local normal margine bordura
   distanta = DIMENSION
   hoffset = DIMENSION
   voffset = DIMENSION
   dy = DIMENSION
   spatiu jos = DIMENSION
   threshold = DIMENSION
   linie = NUMMER
   stack = da continuu
   stil = STYLE BEFEHL
   culoare = COLOR

```

```

\setupmarginframed [...1...] [...2...]
1 NAME OPT
2 inherits: \seteazainconjurat

```

```

\atleftmargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\atrighmargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininner [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininneredge [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\ininnermargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleft [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftedge [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT OPT
   inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inleftmargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inmargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inotherr [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouter [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouteredge [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inoutermargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inright [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightedge [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightmargin [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\margintext [...1...] [...2...] {...3}
1 referinta = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\setupmarginrule [1] [...2...]
1 NUMMEROPT
2 inherits: \setupsidebar

```

`\setupmathalignment [...1,...] [...2,...]`

```
1 NAME OPT
2 n = NUMMER
  m = NUMMER
  distanta = DIMENSION
  numar = auto
  separator = TEXT
  aliniere = stanga centru dreapta normal
  locatie = sus center subsol normal
  grid = math nu
```

`\setupmathcases [...1,...] [...2,...]`

```
1 NAME OPT
2 stanga = BEFEHL
  dreapta = BEFEHL
  strut = da nu
  stil = STYLE BEFEHL
  distanta = DIMENSION
  numberdistance = DIMENSION
```

`\setupmathematics [...1,...] [...2,...]`

```
1 NAME OPT
2 openup = da nu
  setsimbol = NAME
  functionstyle = STYLE BEFEHL
  compact = da nu
  aliniere = l2r r2l
  bidi = da nu
  sygreek = normal italic niciunul
  lcgreeek = normal italic niciunul
  ucgreeek = normal italic niciunul
  italics = 1 2 3 4 niciunul reset
  autopunctuation = da nu tot
  setups = NAME
  domain = NAME reset
  stiltext = STYLE BEFEHL
  culoaretext = COLOR
  functioncolor = COLOR
  integral = limits nolimits autolimits displaylimits niciunul
  stylealternative = NAME
  implicit = normal italic
  fraction = ams ctx
```

`\setupmathfence [...1,...] [...2,...]`

```
1 NAME OPT
2 comanda = da nu
  stanga = NUMMER
  mijloc = NUMMER
  dreapta = NUMMER
  mathstyle = display text script scriptscript cramped uncramped normal impachetat mic mare
  culoare = COLOR
  stare = auto
  factor = niciunul auto NUMMER
```

`\setupmathfraction [...1,...] [...2,...]`

```
1 NAME OPT
2 distantasus = DIMENSION
  distantajos = DIMENSION
  margine = DIMENSION
  culoare = COLOR
  strut = da nu math tight
  alternativ = intern extern ambele
  rigla = da nu auto
  stanga = NUMMER
  dreapta = NUMMER
  grosimerigla = DIMENSION
  mathstyle = STYLE BEFEHL
  distanta = nu niciunul overlay
```

`\setupmathfractions [...1,...] [...2,...]`

```
1 NAME OPT
2 inherits: \setupmathfraction
```

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

1    CONTENT  
2    CONTENT

```

1 NAME OPT
2 inherits: \seteazainconjurat

```

```

1 inherits: \setupmathframedOPST
2 CONTENT

```

```

1 inherits: \setupOPTmathframed
2 CONTENT

```

```

1 inherits: \setupOPTmathframed
2 CONTENT

```

```

1  NAME                                OPT
2  stanga      = BEFEHL
   dreapta    = BEFEHL
   strut       = da nu NUMMER
   aliniere    = stanga centru dreapta normal
   stil        = STYLE BEFEHL
   distanta    = DIMENSION
   locatie     = sus subsoal inalt jos lohi normal

```

```

\setupmathornament [...1,...] [...2,...]
1 NAME OPT
2 alternativ = mp
   culoare = COLOR
   mpoffset = DIMENSION
   mp      = NAME

```

```

\setupmathradical [...1,...] [...2,...]
1 NAME OPT
2 alternativ = implicit normal mp
   culoare = COLOR
   mpoffset = DIMENSION
   mp      = NAME

```

```

\setupmathstackers [...1,...] [...2,...]
1 NAME OPT
2 stanga      = BEFEHL
   dreapta    = BEFEHL
   topcommand = \...##1
   bottomcommand = \...##1
   middlecommand = \...##1
   mp         = NAME
   mpheight   = DIMENSION
   mpdepth    = DIMENSION
   mpoffset   = DIMENSION
   culoare    = COLOR
   hoffset    = DIMENSION
   voffset    = DIMENSION
   inaltimeminima = DIMENSION
   mindepth    = DIMENSION
   mathclass   = rel ord
   offset      = min max normal
   locatie     = sus subsol inalt jos centru NUMBER
   strut       = da nu
   alternativ   = normal implicit mp
   latimeminima = DIMENSION
   distanta    = DIMENSION
   moffset     = DIMENSION
   order       = normal reverse
   mathlimits  = da nu

```

```

\setupmathstyle [...*,...]
* display text script scriptscript cramped uncramped normal impachetat mic mare NAME

```

```

\setupmixedcolumns [...1,...] [...2,...]
1 NAME OPT
2 grid      = inherits: \definegridsnapping
   grosimerigla = DIMENSION
   metoda     = otr box
   inainte    = BEFEHL
   dupa       = BEFEHL
   distanta   = DIMENSION
   n          = NUMBER
   inaltimaxima = DIMENSION
   latimaxima = DIMENSION
   pas        = DIMENSION
   profile    = NAME
   aliniere   = inherits: \seteazaalinierea
   setups     = NAME
   balanta    = da nu
   splitmethod = niciunul fixat
   alternativ  = local global
   internalgrid = linie jumatatelinie
   separator  = rigla
   strut      = da nu
   culoare    = COLOR
   culoarerigla = COLOR
   directie   = normal reverse
   inherits: \seteazainconjurat

```

```

\setupmodule [...1] [...2,...]
1 FILE OPT
2 test = da nu
   KEY = VALUE

```

`\setupnotation [...1,...] [...2,...]`

```

1  NAME                OPT
2  titlu               = da nu
   numar              = da nu
   type               = note
   comandanumar       = \...##1
   distantatitlu      = DIMENSION
   stiltitlu          = STYLE BEFEHL
   culoaretitlu       = COLOR
   titlecommand       = \...##1
   titleleft          = BEFEHL
   titleright         = BEFEHL
   stanga             = BEFEHL
   dreapta            = BEFEHL
   simbol             = BEFEHL
   starter            = BEFEHL
   stopper            = BEFEHL
   cuplare            = NAME
   counter            = NAME
   nivel              = NUMMER
   text               = TEXT
   headcommand        = \...##1
   inainte            = BEFEHL
   dupa               = BEFEHL
   intre              = BEFEHL
   alternativ          = stanga dreapta inmargine instanga indreapta margine marginestanga marginedreapta innermargin
                        outermargin serried suspendat sus comanda note NAME
   aliniere           = inherits: \seteazaalinierea
   headalign          = inherits: \seteazaalinierea
   aliniat            = inherits: \seteazaaliniat
   display            = da nu
   aliniaturmator     = da nu auto
   latime             = ajustat broad linie DIMENSION
   distanta           = niciunul DIMENSION
   dilatat            = NUMMER
   shrink             = NUMMER
   suspenda           = ajustat broad niciunul margine NUMMER
   closesymbol        = BEFEHL
   closecommand       = \...##1
   expansiune         = da nu xml
   referenceprefix    = + - TEXT
   exemplu            = TEXT
   margine            = da nu standard DIMENSION
   stil               = STYLE BEFEHL
   culoare            = COLOR
   stiltitlu          = STYLE BEFEHL
   culoaretitlu       = COLOR
   inherits: \setupcounter

```

`\setupnotations [...1,...] [...2,...]`

```

1  NAME                OPT
2  inherits: \setupnotation

```



**\setupnote** [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup>, $\dots$ ]

```
1 NAME OPT
2 interactiune = da nu numar text tot
  symbolcommand = \...##1
  comandatext = \...##1
  indicator = da nu
  separatortext = BEFEHL
  latime = DIMENSION
  inaltime = DIMENSION
  distanta = DIMENSION
  rulecommand = BEFEHL
  rigla = on dezactivat normal stanga dreapta comanda paragraf
  split = tolerant strict foartestRICT NUMMER
  factor = NUMMER
  locatie = text pagina inalt subsol niciunul coloane firstcolumn lastcolumn
  urmatorul = BEFEHL
  n = NUMMER
  culoarerigla = COLOR
  grosimerigla = DIMENSION
  setups = NAME
  spatiereinterliniara = NAME
  paragraf = da nu
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  scop = pagina
  distantacoloane = DIMENSION
  continua = da nu
  alternativ = grila fixat coloane note niciunul
  criteriu = pagina
  fonttext = inherits: \seteazafonttext
  aliniere = inherits: \seteazaalinierea
  stiltext = STYLE BEFEHL
  culoaretex = COLOR
  anchor = urmatorul
  spatiuinainte = inherits: \blanc
  spaceinbetween = inherits: \blanc
  inherits: \seteazainconjurat
```

**\setupnotes** [ $\dots$ , $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup>, $\dots$ ]

```
1 NAME OPT
2 inherits: \setupnote
```

**\setupoffset** [ $\dots$ , $\dots$ ]<sup>\*</sup>, $\dots$ ]

```
* inherits: \setupoffsetbox
```

**\setupoffsetbox** [ $\dots$ , $\dots$ ]<sup>\*</sup>, $\dots$ ]

```
* x = DIMENSION
  y = DIMENSION
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  offsetsus = DIMENSION
  offsetjos = DIMENSION
  metoda = fixat
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = DIMENSION
  locatie = stanga centru dreapta sus subsol linie l c r m t b g
```

**\setupoutputroutine** [ $\dots$ ]<sup>1</sup> [ $\dots$ , $\dots$ ]<sup>2</sup>, $\dots$ ]

```
1 NAME OPT
2 KEY = CSNAME
```

**\setupoutputroutine** [ $\dots$ ]<sup>\*</sup>

```
* NAME
```

\setuppagechecker [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 linii = NUMMER  
offset = DIMENSION  
metoda = 0 1 2 3  
inainte = BEFEHL  
dupa = BEFEHL  
intre = BEFEHL

\setuppagegrid [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 n = NUMMER  
nstanga = NUMMER  
ndreapta = NUMMER  
latime = DIMENSION auto  
distanta = DIMENSION  
linii = NUMMER  
latimemaxima = DIMENSION  
inaltimemaxima = DIMENSION  
directie = normal reverse  
pagina = inherits: \pagina  
inherits: \seteazainconjurat

\setuppagegridarea [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 stare = start stop repetat  
x = NUMMER  
y = NUMMER  
nx = NUMMER  
ny = NUMMER  
stil = STYLE BEFEHL  
culoare = COLOR  
clipoffset = DIMENSION  
offsetdreapta = DIMENSION  
inherits: \seteazainconjurat

\setuppagegridareatext [...<sup>1</sup>] [...<sup>2</sup>]

1 NAME  
2 TEXT

\setuppagegridlines [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 NAME  
2 NUMMER  
3 NUMMER  
4 NUMMER

\setuppagegridspan [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 n = NUMMER  
stil = STYLE BEFEHL  
culoare = COLOR  
inainte = BEFEHL  
dupa = BEFEHL  
inherits: \seteazainconjurat

\setuppagegridstart [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>]

1 NAME  
2 NUMMER  
3 NUMMER  
4 NUMMER

\setuppageinjection [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 stare = precedent urmatorul NUMMER  
intarziere = da nu  
alternativ = figura buffer setups niciunul NAME  
pagina = inherits: \pagina  
pagestate = start stop  
n = NUMMER  
inherits: \seteazainconjurat

<pre> \setuppageinjectionalternative [...] [...] 1  NAME                                OPT 2  renderingsetup = NAME </pre>
<pre> \setuppageshift [...] [...] 1  pagina foaie      OPT      OPT 2  NAME 3  NAME </pre>
<pre> \setuppagestate [...] [...] 1  NAME                                OPT 2  intarziere = da nu </pre>
<pre> \setuppairedbox [...] [...] 1  NAME                                OPT 2  inainte      = BEFEHL    dupa         = BEFEHL    intre        = BEFEHL    locatie      = stanga centru dreapta sus subsol inalt jos    n            = NUMMER    distanta     = DIMENSION    fonttext     = inherits: \seteazafonttext    latime       = DIMENSION    inaltime     = DIMENSION    latimemaxima = DIMENSION    inaltime maxima = DIMENSION    aliniere     = inherits: \seteazaalinierea    stil         = STYLE BEFEHL    culoare      = COLOR </pre>
<pre> \setarePAIREDBOX [...] * inherits: \setuppairedbox instances: legend </pre>
<pre> \punellegend [...] [...] 1  inherits: \setuppairedbox 2  CONTENT 3  TEXT </pre>
<pre> \setuppaper [...] * inherits: \seteazadimensiunihartie </pre>
<pre> \setupparagraph [...] [...] 1  NAME                                OPT 2  stil      = STYLE BEFEHL    culoare   = COLOR    aliniere  = inherits: \seteazaalinierea    setups    = NAME </pre>
<pre> \setupparagraphintro [...] [...] 1  reset fiecare primul urmatorul 2  BEFEHL </pre>
<pre> \setupparallel [...] [...] 1  NAME 2  NAME 3  setups = NAME    start  = NUMMER    n      = NUMMER    criteriu = tot </pre>
<pre> \setupperiods [...] * n      = NUMMER    latime = DIMENSION ajustat    distanta = DIMENSION    simbol = BEFEHL </pre>

**\setupplacement** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 inainte = BEFEHL  
dupa = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
grid = inherits: \snaptogrid  
corectielinie = on dezactivat  
corectieadancime = on dezactivat  
margine = da nu standard

**\setuppositionbar** [...,<sup>\*</sup>...,...]

\* stil = STYLE BEFEHL  
culoare = COLOR  
n = NUMMER  
min = NUMMER  
max = NUMMER  
text = TEXT  
latime = DIMENSION  
inaltime = DIMENSION  
inaltime = DIMENSION

**\setupprocessor** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 stare = start stop  
stanga = BEFEHL  
dreapta = BEFEHL  
comanda = \...##1  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupprofile** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 inaltime = DIMENSION  
inaltime = DIMENSION  
distanta = DIMENSION  
factor = NUMMER  
linii = NUMMER  
metoda = strict fixat niciunul

**\setupquotation** [...,<sup>\*</sup>...,...]

\* inherits: \setupdelimitedtext

**\setuprealpagenumber** [...,<sup>\*</sup>...,...]

\* inherits: \setupcounter

**\setupreferenceformat** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 eticheta = \* NAME  
stanga = BEFEHL  
dreapta = BEFEHL  
type = implicit text titlu numar pagina realpage  
setups = NAME  
autocase = da nu  
text = TEXT  
stil = STYLE BEFEHL  
culoare = COLOR

**\setupreferenceprefix** [...]

\* + - TEXT

```

\setupreferencestructureprefix [...] [...] [...] [...]
1 NAME ABSCHNITT OPT OPT
2 implicit
3 prefix = da nu
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = BEFEHL PROCESSOR->BEFEHL
  prefixstopper = BEFEHL PROCESSOR->BEFEHL
  prefixset = NAME
  prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = BEFEHL PROCESSOR->BEFEHL
  numberstopper = BEFEHL PROCESSOR->BEFEHL
  numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
  numberseparatorset = NAME
  prefixconnector = BEFEHL PROCESSOR->BEFEHL

```

```

\setupregisters [...] [...]
1 NAME NAME:NUMBER OPT
2 inherits: \seteazaregistru

```

```

\setupregisters [...] [...] [...]
1 NAME OPT OPT
2 NUMMER
3 inherits: \seteazaregistru

```

```

\index [...] [...]
1 TEXT PROCESSOR->TEXT
2 INDEX

```

```

\setuprenderingwindow [...] [...]
1 NAME OPT
2 actiunedeschiderepagina = REFERENCE
  actiuneinchiderepagina = REFERENCE
  inherits: \seteazainconjurat

```

```

\setups [...]
* NAME

```

```

\setupscale [...] [...]
1 NAME OPT
2 scala = NUMMER
  xscala = NUMMER
  yscala = NUMMER
  latime = DIMENSION
  inaltime = DIMENSION
  inaltime = da nu
  linii = NUMMER
  factor = ajustat broad max auto implicit
  hfactor = ajustat broad max auto implicit
  factorw = ajustat broad max auto implicit
  latimemaxima = DIMENSION
  inaltimemaxima = DIMENSION
  s = NUMMER
  sx = NUMMER
  sy = NUMMER
  equalwidth = DIMENSION
  equalheight = DIMENSION
  grid = da ajustat inaltime adancime jumatatelinie

```

```

\setupscript [...] [...]
1 NAME OPT
2 metoda = hangul hanzi nihongo ethiopic thai test
  preset = NAME
  features = auto

```

**\setupscripts** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 NAME OPT
- 2 inherits: \setupscript

**\setupselector** [...<sup>1</sup>.] [...,<sup>2</sup>...,...]

- 1 NAME
- 2 n = NUMMER
- m = NUMMER

**\setupshift** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 NAME OPT
- 2 continua = da nu
- unitate = ex em pt in cm mm sp bp pc dd cc nc
- metoda = NUMMER
- dy = NUMMER
- aliniera = inherits: \seteazaalinieraa
- stil = STYLE BEFEHL
- culoare = COLOR

**\shiftdown** {...}

- \* CONTENT

**\shiftup** {...}

- \* CONTENT

**\setupsidebar** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 NAME OPT
- 2 grosimerigla = DIMENSION
- culoarerigla = COLOR
- alternativ = NUMMER
- offsetsus = DIMENSION
- offsetjos = DIMENSION
- distanta = DIMENSION
- distantamarginestanga = DIMENSION
- nivel = NUMMER

**\setupspellchecking** [...,<sup>\*</sup>...,...]

- \* stare = start stop
- metoda = 1 2 3
- lista = NAME

**\setupstartstop** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 NAME OPT
- 2 inainte = BEFEHL
- dupa = BEFEHL
- intre = BEFEHL
- setups = NAME
- stanga = BEFEHL
- dreapta = BEFEHL
- stil = STYLE BEFEHL
- culoare = COLOR

**\setupstretched** [...,<sup>\*</sup>...,...]

- \* inherits: \setupcharacterkerning

**\setupstruts** [...<sup>\*</sup>.]

- \* da nu auto cap OPTajustat linie implicit CHARACTER

**\setupstyle** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

- 1 NAME OPT
- 2 metoda = comanda
- stil = STYLE BEFEHL
- culoare = COLOR

`\setupsubformula [...1,...] [...2,...]`

1 NAME OPT  
2 aliniaturmator = da nu auto

`\setupsubformulas [...1,...] [...2,...]`

1 NAME OPT  
2 inherits: \setupsubformula

`\setups {...,*,...}`

\* NAME

`\setupTABLE [...1,...] [...2,...] [...3,...]`

1 r c x y rand colona primul ultim start antet fiecare impar par unu NUMBER -NUMBER  
2 primul least fiecare doi impar par NUMBER -NUMBER  
3 extras = BEFEHL  
stanga = BEFEHL  
dreapta = BEFEHL  
culoaretitlu = COLOR  
stiltitlu = STYLE BEFEHL  
distantamarginestanga = DIMENSION  
distantamarginedreapta = DIMENSION  
distantacoloane = DIMENSION  
latimemaxima = DIMENSION  
setups = NAME  
latimetext = DIMENSION local  
split = da nu repetat auto  
antet = repetat  
optiune = dilatat tight  
inainte = BEFEHL  
dupa = BEFEHL  
aceeasipagina = inainte dupa ambele  
spaceinbetween = inherits: \blanc  
splitoffset = DIMENSION  
aliniazacarakter = da nu  
alierecaracter = TEXT number->TEXT text->TEXT  
distanta = DIMENSION  
culoare = COLOR  
stil = math STYLE BEFEHL  
inherits: \seteazainconjurat

`\setupTEXpage [...,*,...]`

\* inherits: \setupfittingpage

`\setuptabulation [...1,...] [...2,...]`

1 NAME OPT  
2 format = TEMPLATE niciunul  
inainte = BEFEHL  
dupa = BEFEHL  
distanta = mic mediu mare niciunul blank adancime grila DIMENSION  
alinie = stanga centru dreapta dimension  
rigla = linie normal  
culoarerigla = COLOR  
grosimerigla = DIMENSION  
fonttext = inherits: \seteazafonttext  
aliniat = da nu  
split = da nu repetat auto  
unitate = DIMENSION  
margine = DIMENSION  
intern = BEFEHL  
EQ = BEFEHL  
antet = da repetat text  
frame = on dezactivat  
titlu = TEXT  
keeptogether = da nu

`\setuptagging [...,*,...]`

\* stare = start stop  
metoda = auto

**\setuptextbackground** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 stare = start stop  
locatie = text paragraf niciunul  
alternativ = NUMMER  
mp = NAME  
metoda = NAME  
fundal = culoare  
culoarefundal = COLOR  
colt = rectangular rotund  
nivel = NUMMER  
offsetfundal = DIMENSION  
inainte = BEFEHL  
dupa = BEFEHL  
alinieri = inherits: \seteazaalinieria  
dash = NUMMER  
raza = DIMENSION  
frame = on dezactivat  
culoareframe = COLOR  
grosimerigla = DIMENSION  
voffset = DIMENSION  
offsetframe = DIMENSION  
offsetstanga = da nu standard DIMENSION  
offsetdreapta = da nu standard DIMENSION  
offsetsus = mic mediu mare linie DIMENSION  
offsetjos = mic mediu mare linie DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

**\setuptextflow** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 latime = DIMENSION  
stil = STYLE BEFEHL  
culoare = COLOR

**\setuptooltip** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 locatie = stanga centru dreapta  
inherits: \seteazainconjurat

**\tooltip** [...,<sup>1</sup>...,...]{...<sup>2</sup>.}{...<sup>3</sup>.}

1 inherits: \setup<sup>OPT</sup>tooltip  
2 TEXT  
3 TEXT

**\setupunit** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 metoda = 1 2 3 4 5 6  
language = SPRACHE  
alternativ = text matematica  
order = reverse normal  
separator = mic mediu mare normal niciunul NAME  
spatiu = mic mediu mare normal niciunul NAME  
stil = STYLE BEFEHL  
culoare = COLOR

**\unit** {...}

\* CONTENT

**\setupuserpagenumber** [...,<sup>\*</sup>...,...]

\* viewerprefix = TEXT  
stare = start stop niciunul mentine gol  
inherits: \setupcounter

**\setupversion** [...]

\* concept fisier temporar final NAME



**\setupviewerlayer** [...,\*=...]

\* titlu = TEXT  
stare = start stop  
export = da nu  
tiparibil = da nu  
scop = local global  
metoda = niciunul comanda

**\setupvspacing** [...,\*=...]

\* inherits: \vspacing <sup>OPT</sup>

**\setupwithargument** {...} {...} <sup>1</sup> <sup>2</sup>

1 NAME  
2 CONTENT

**\setupwithargumentswapped** {...} {...} <sup>1</sup> <sup>2</sup>

1 CONTENT  
2 NAME

**\setupxml** [...,\*=...]

\* implicit = ascuns niciunul text  
compress = da nu

**\setupxtable** [...,<sup>1</sup>...] [...,<sup>2</sup>=...]

1 NAME <sup>OPT</sup>  
2 latimetext = DIMENSION local  
fonttext = inherits: \seteazafonttext  
spaceinbetween = inherits: \blanc  
optiune = tight max dilatat latime inaltime fixat  
inaltimetext = DIMENSION  
latimemaxima = DIMENSION  
distantacoloane = DIMENSION  
distantamarginestanga = DIMENSION  
distantamarginedreapta = DIMENSION  
antet = repetat  
subsol = repetat  
grosimerigla = DIMENSION  
split = da nu repetat auto  
splitoffset = DIMENSION  
aceeasipagina = inainte dupa ambele  
distanta = DIMENSION  
inherits: \seteazainconjurat

**\setuvalue** {...} {...} <sup>1</sup> <sup>2</sup>

1 NAME  
2 CONTENT

**\setuxvalue** {...} {...} <sup>1</sup> <sup>2</sup>

1 NAME  
2 CONTENT

**\setvalue** {...} {...} <sup>1</sup> <sup>2</sup>

1 NAME  
2 CONTENT

**\setvariable** {...} {...} {...} <sup>1</sup> <sup>2</sup> <sup>3</sup>

1 NAME  
2 KEY  
3 VALUE

**\setvariables** [...]<sup>1</sup> [...,<sup>2</sup>...]

1 NAME  
2 set = BEFEHL  
reset = BEFEHL  
KEY = VALUE

<pre> \setvboxregister ... {<sup>1</sup>...<sup>2</sup>} 1  CSNAME NUMBER 2  CONTENT </pre>
<pre> \setvisualizerfont [<sup>*</sup>...] *  FONT                      OPT </pre>
<pre> \setvtopregister ... {<sup>1</sup>...<sup>2</sup>} 1  CSNAME NUMBER 2  CONTENT </pre>
<pre> \setwidthof ... \to \<sup>1</sup>...<sup>2</sup> 1  TEXT 2  CSNAME </pre>
<pre> \setxmeasure {<sup>1</sup>...} {<sup>2</sup>...} 1  NAME 2  DIMENSION </pre>
<pre> \setxvalue {<sup>1</sup>...} {<sup>2</sup>...} 1  NAME 2  CONTENT </pre>
<pre> \setxvariable {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1  NAME 2  KEY 3  VALUE </pre>
<pre> \setxvariables [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...<sup>2</sup>...] 1  NAME 2  set      = BEFEHL    reset    = BEFEHL    KEY      = VALUE </pre>
<pre> \shapedhbox {<sup>*</sup>...} *  CONTENT </pre>
<pre> \SHIFT {<sup>*</sup>...} *  CONTENT instances: shiftup shiftdown </pre>
<pre> \showallmakeup </pre>
<pre> \showattributes </pre>
<pre> \showboxes </pre>
<pre> \showbtxdatasetauthors [<sup>*</sup>...<sup>*</sup>...<sup>*</sup>...] *  specification = NAME          OPT    dataset       = NAME    field         = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [<sup>*</sup>...] *  NAME                      OPT </pre>

<pre> \showbtxdatasetcompleteness [...,.*,...] *  specification = NAME          OPT    dataset       = NAME    field         = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...] *  NAME          OPT </pre>
<pre> \showbtxdatasetfields [...,.*,...] *  specification = NAME          OPT    dataset       = NAME    field         = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution                   journal language luna monthfiled nationality note numar unu doi organization pages publisher                   school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] *  NAME          OPT </pre>
<pre> \showbtxfields [...,.*,...] *  rotatie       = NUMBER      OPT    specification = NAME </pre>
<pre> \showbtxfields [...] *  NAME          OPT </pre>
<pre> \showbtxhashedauthors [...] *  TEXT          OPT </pre>
<pre> \showbtxtables [...] *  TEXT          OPT </pre>
<pre> \showchardata {...} *  TEXT </pre>
<pre> \showcharratio {...} *  TEXT </pre>
<pre> \showcolorbar [...] *  COLOR </pre>
<pre> \showcolorcomponents [...] *  COLOR </pre>
<pre> \showcolorset [...] *  COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] *  NAME </pre>
<pre> \showdirectives </pre>
<pre> \showdirlsinmargin </pre>
<pre> \showedebuginfo </pre>

<code>\showexperiments</code>
<code>\showfont [...] [...<sup>2</sup>,...]</code> 1 FONT OPT 2 NUMMER
<code>\showfontdata</code>
<code>\showfontitalics</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...*,...]</code> * inherits: \seteazafonttext
<code>\showfontstyle [...<sup>1</sup>,...][...<sup>2</sup>,...][...<sup>3</sup>,...][...<sup>4</sup>,...]</code> 1 inherits: \seteazafonttext OPT OPT OPT 2 rm ss tt mm hw cg 3 tf bf it sl bi bs 4 tot NUMMER
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...} [...<sup>2</sup>]</code> 1 TEXT 2 REFERENCE
<code>\showhyphenationtrace [...<sup>1</sup>][...<sup>2</sup>]</code> 1 SPRACHE OPT 2 TEXT
<code>\showhyphens {...}</code> * TEXT
<code>\showinjector [...*,...]</code> * NAME OPT
<code>\showjustification</code>
<code>\showkerning {...}</code> * TEXT
<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> * TEXT
<code>\showligatures [...]</code> * FONT
<code>\showlogcategories</code>

<code>\showmargins</code>
<code>\showmessage {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.,...}</code> 1 NAME 2 NAME NUMBER 3 TEXT
<code>\showminimalbaseline</code>
<code>\shownextbox \<sup>1</sup>. {<sup>2</sup>.}</code> 1 CSNAME 2 CONTENT
<code>\showotfcomposition {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code> 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
<code>\showparentchain \<sup>1</sup>. {<sup>2</sup>.}</code> 1 CSNAME 2 NAME
<code>\showsetupsdefinition [<sup>*</sup>.]</code> * NAME
<code>\showtimer {<sup>*</sup>.}</code> * TEXT
<code>\showtokens [<sup>*</sup>.]</code> * NAME
<code>\showtrackers</code>
<code>\showvalue {<sup>*</sup>.}</code> * NAME
<code>\showvariable {<sup>1</sup>.} {<sup>2</sup>.}</code> 1 NAME 2 KEY
<code>\showwarning {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.,...}</code> 1 NAME 2 NAME NUMBER 3 TEXT
<code>\simbol [<sup>1</sup>.] [<sup>2</sup>.]</code> 1 NAME <small>OPT</small> 2 NAME
<code>\simbol {<sup>*</sup>.}</code> * NAME
<code>\simplealignedbox {<sup>1</sup>.} {<sup>2</sup>.} {<sup>3</sup>.}</code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT

`\simplealignedboxplus {...} {...} {...} {...}`  
1 DIMENSION  
2 stanga dreapta centru flushleft flushright intern extern  
3 TEXT  
4 CONTENT

`\simplealignedspreadbox {...} {...} {...}`  
1 DIMENSION  
2 stanga dreapta centru flushleft flushright intern extern  
3 CONTENT

`\simplegroupedcommand {...} {...}`  
1 BEFEHL  
2 BEFEHL

`\simplereversealignedbox {...} {...} {...}`  
1 DIMENSION  
2 stanga dreapta centru flushleft flushright intern extern  
3 CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`  
1 DIMENSION  
2 stanga dreapta centru flushleft flushright intern extern  
3 TEXT  
4 CONTENT

`\singalcharacteralign {...} {...}`  
1 NUMMER  
2 NUMMER

`\singlebond`

`\sixthofsixarguments {...} {...} {...} {...} {...} {...}`  
1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\slantedface`

`\slicepages [...]1 [...,...2...,...]OPT [...,...3...,...]OPT`  
1 FILE  
2 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
latime = DIMENSION  
inaltime = DIMENSION  
n = NUMMER  
3 offset = DIMENSION  
hoffset = DIMENSION  
voffset = DIMENSION  
latime = DIMENSION  
inaltime = DIMENSION  
n = NUMMER

`\slovenianNumerals {...}`  
\* NUMMER

`\sloveniannumerals {...}`  
\* NUMMER

`\smallbodyfont`

$\backslash\text{smallcappedcharacters}$ {...} *    NUMBER
$\backslash\text{smallcappedromannumerals}$ {...} *    NUMBER
$\backslash\text{smaller}$
$\backslash\text{smallskip}$
$\backslash\text{smash}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    w h d t <sup>OPT</sup> 2    CONTENT
$\backslash\text{smashbox}$ ... *    CSNAME NUMBER
$\backslash\text{smashboxed}$ ... *    CSNAME NUMBER
$\backslash\text{smashedhbox}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    TEXT            OPT 2    CONTENT
$\backslash\text{smashedvbox}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    TEXT            OPT 2    CONTENT
$\backslash\text{snaptogrid}$ [ <sup>1</sup> ...] \^ <sup>2</sup> ... { <sup>3</sup> ...} 1    normal standard <sup>OPT</sup> da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME 2    CSNAME 3    CONTENT
$\backslash\text{snaptogrid}$ [..., <sup>1</sup> ...] \^ <sup>2</sup> ... { <sup>3</sup> ...} 1    inherits: \define <sup>OPT</sup> gridsnapping 2    CSNAME 3    CONTENT
$\backslash\text{someheadnumber}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1    ABSCHNITT 2    precedent curent urmatorul primul ultim
$\backslash\text{somekindoftab}$ [..., <sup>*</sup> ...,...] *    alternativ    =    orizonta <sup>OPT</sup> lvertical latime        =    DIMENSION inaltime      =    DIMENSION n             =    NUMBER m             =    NUMBER
$\backslash\text{somelocalfloat}$
$\backslash\text{somenamedheadnumber}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1    ABSCHNITT 2    precedent curent urmatorul primul ultim

$\backslash\text{someplace} \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\} \{.^5.\} \{.^6.\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 REFERENCE
$\backslash\text{SORTING} [.^1.] \{.^2.\}$ 1 NAME <small>OPT</small> 2 CONTENT instances: logo
$\backslash\text{spanishNumerals} \{.^*.\}$ * NUMBER
$\backslash\text{spanishnumerals} \{.^*.\}$ * NUMBER
$\backslash\text{spatiifixate}$
$\backslash\text{spatiu}$
$\backslash\text{spatiufixat}$
$\backslash\text{splitatasterisk} \dots \backslash.^2. \backslash.^3.$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolon} \dots \backslash.^2. \backslash.^3.$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolons} \dots \backslash.^2. \backslash.^3.$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcomma} \dots \backslash.^2. \backslash.^3.$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatperiod} \dots \backslash.^2. \backslash.^3.$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitdfrac} \{.^1.\} \{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{splitfilename} \{.^*.\}$ * FILE
$\backslash\text{splitfrac} \{.^1.\} \{.^2.\}$ 1 CONTENT 2 CONTENT



<code>\splitoffbase</code>
<code>\splitofffull</code>
<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens</code> <sup>1</sup> ... \from <sup>2</sup> ... \to \ <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> <sup>1</sup> ... \at <sup>2</sup> ... \to \ <sup>3</sup> ... \and \ <sup>4</sup> ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> ... * CSNAME NUMBER
<code>\sqrt</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 TEXT <sup>OPT</sup> 2 CONTENT
<code>\stackrel</code> { <sup>1</sup> ...} { <sup>2</sup> ...} 1 CONTENT 2 CONTENT
<code>\stanga</code> ... * CHARACTER
<code>\startalignment</code> [...*...] ... \stopalignment * inherits: \seteazaaliniea
<code>\startaliniatcentru</code> ... \stopaliniatcentru
<code>\startaliniatdreapta</code> ... \stopaliniatdreapta
<code>\startaliniatstanga</code> ... \stopaliniatstanga
<code>\startallmodes</code> [...*...] ... \stopallmodes * NAME
<code>\startantettabel</code> [...*] ... \stopantettabel * NAME

<pre> \startATTACHMENT [...] [...] ... \stopATTACHMENT 1  NAME          OPT          OPT 2  inherits: \setupattachment instances: attachment </pre>
<pre> \startattachment [...] [...] ... \stopattachment 1  NAME          OPT          OPT 2  inherits: \setupattachment </pre>
<pre> \startbar [...] ... \stopbar *  NAME </pre>
<pre> \startbitmapimage [..., ...=..., ...] ... \stopbitmapimage *  culoare      = rgb cmyk gri    latime       = DIMENSION    inaltime     = DIMENSION    x            = NUMMER    y            = NUMMER </pre>
<pre> \startblocsectioneambient [...] ... \stopblocsectioneambient *  NAME </pre>
<pre> \startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions *  NAME </pre>
<pre> \startbuffer [...] ... \stopbuffer *  NAME          OPT </pre>
<pre> \startBUFFER ... \stopBUFFER instances: hiding </pre>
<pre> \startcatcodetable \*... ... \stopcatcodetable *  CSNAME </pre>
<pre> \startcentraligned ... \stopcentraligned </pre>
<pre> \startcharacteralign [...] ... \stopcharacteralign *  TEXT number-&gt;TEXT text-&gt;TEXT </pre>
<pre> \startcheckedfences ... \stopcheckedfences </pre>
<pre> \startchemical [...] [...] ... \stopchemical 1  NAME          OPT          OPT 2  inherits: \setupchemical </pre>
<pre> \startcollect ... \stopcollect </pre>
<pre> \startcollecting ... \stopcollecting </pre>
<pre> \startcoloane [..., ...=..., ...] ... \stopcoloane *  inherits: \seteazacoloane<sup>OPT</sup> </pre>
<pre> \startcolorintent [...] ... \stopcolorintent *  knockout overprint niciunul </pre>
<pre> \startcoloronly [...] ... \stopcoloronly *  COLOR </pre>

$\backslash\text{startcolorset } [...]\dots\backslash\text{stopcolorset}$ $\ast$ NAME
$\backslash\text{startcolumnspan } [...]\overset{\ast}{=}\dots\backslash\text{stopcolumnspan}$ $\ast$ inherits: $\backslash\text{setupcolumnspan}^{\text{PT}}$
$\backslash\text{startcombination } [...]\overset{1}{\dots}\overset{2}{=}\dots\backslash\text{stopcombination}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupcombination}$
$\backslash\text{startcombination } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stopcombination}$ 1 NAME OPT OPT 2 N*M
$\backslash\text{startcomentariupagina}\dots\backslash\text{stopcomentariupagina}$
$\backslash\text{startCOMMENT } [...]\overset{1}{\dots}\overset{2}{=}\dots\backslash\text{stopCOMMENT}$ 1 TEXT OPT OPT 2 inherits: $\backslash\text{seteazacomentariu}$ instances: comment
$\backslash\text{startcomment } [...]\overset{1}{\dots}\overset{2}{=}\dots\backslash\text{stopcomment}$ 1 TEXT OPT OPT 2 inherits: $\backslash\text{seteazacomentariu}$
$\backslash\text{startcomponenta } [...]\dots\backslash\text{stopcomponenta}$ $\ast$ FILE $\ast$
$\backslash\text{startcomponenta } \dots\dots\backslash\text{stopcomponenta}$ $\ast$ FILE $\ast$
$\backslash\text{startcontextcode}\dots\backslash\text{stopcontextcode}$
$\backslash\text{startcontextdefinitioncode}\dots\backslash\text{stopcontextdefinitioncode}$
$\backslash\text{startbtxlabeltext } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stopbtxlabeltext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startheadtext } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stopheadtext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startlabeltext } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stoplabeltext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startmathlabeltext } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stopmathlabeltext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startoperatorortext } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stopoperatorortext}$ 1 SPRACHE OPT 2 KEY
$\backslash\text{startprefixtext } [...]\overset{1}{\dots}\overset{2}{\dots}\backslash\text{stopprefixtext}$ 1 SPRACHE OPT 2 KEY

$\backslash\text{startsuffixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ] ... $\backslash\text{stopsuffixtext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{starttaglabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ] ... $\backslash\text{stoptaglabeltext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startunittext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ] ... $\backslash\text{stopunittext}$ 1    SPRACHE                    OPT 2    KEY
$\backslash\text{startctxfunction}$ ... .. $\backslash\text{stopctxfunction}$ *    NAME
$\backslash\text{startctxfunctiondefinition}$ ... .. $\backslash\text{stopctxfunctiondefinition}$ *    NAME
$\backslash\text{startculoare}$ [ <sup>1</sup> ] ... $\backslash\text{stopculoare}$ *    COLOR
$\backslash\text{startcurrentcolor}$ ... $\backslash\text{stopcurrentcolor}$
$\backslash\text{startcurrentlistentrywrapper}$ ... $\backslash\text{stopcurrentlistentrywrapper}$
$\backslash\text{startdelimited}$ [ <sup>1</sup> ] [ <sup>2</sup> ] [ <sup>3</sup> ...,...] ... $\backslash\text{stopdelimited}$ 1    NAME                                    OPT                    OPT 2    SPRACHE 3    inherits: $\backslash\text{startingust}$
$\backslash\text{startdelimitedtext}$ [ <sup>1</sup> ] [ <sup>2</sup> ] [ <sup>3</sup> ...,...] ... $\backslash\text{stopdelimitedtext}$ 1    NAME                                    OPT                    OPT 2    SPRACHE 3    inherits: $\backslash\text{startingust}$
$\backslash\text{startDELIMITEDTEXT}$ [ <sup>1</sup> ] [ <sup>2</sup> ...,...] ... $\backslash\text{stopDELIMITEDTEXT}$ 1    SPRACHE                                    OPT                    OPT 2    inherits: $\backslash\text{startingust}$ <b>instances:</b> quotation quote blockquote speech aside
$\backslash\text{startaside}$ [ <sup>1</sup> ] [ <sup>2</sup> ...,...] ... $\backslash\text{stopaside}$ 1    SPRACHE                    OPT                    OPT 2    inherits: $\backslash\text{startingust}$
$\backslash\text{startblockquote}$ [ <sup>1</sup> ] [ <sup>2</sup> ...,...] ... $\backslash\text{stopblockquote}$ 1    SPRACHE                    OPT                    OPT 2    inherits: $\backslash\text{startingust}$
$\backslash\text{startquotation}$ [ <sup>1</sup> ] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquotation}$ 1    SPRACHE                    OPT                    OPT 2    inherits: $\backslash\text{startingust}$
$\backslash\text{startquote}$ [ <sup>1</sup> ] [ <sup>2</sup> ...,...] ... $\backslash\text{stopquote}$ 1    SPRACHE                    OPT                    OPT 2    inherits: $\backslash\text{startingust}$
$\backslash\text{startspeech}$ [ <sup>1</sup> ] [ <sup>2</sup> ...,...] ... $\backslash\text{stopspeech}$ 1    SPRACHE                    OPT                    OPT 2    inherits: $\backslash\text{startingust}$

$\backslash startDESCRIERE [...,\dots^*...]$ ... $\backslash stopDESCRIERE$ * titlu = TEXT <small>OPT</small> semncarte = TEXT lista = TEXT referinta = REFERENCE
$\backslash startDESCRIERE [...,\dots^1...] \{...\}^2$ ... $\backslash stopDESCRIERE$ 1 REFERENCE <small>OPT</small> <small>OPT</small> 2 TEXT
$\backslash startdespachetat$ ... $\backslash stopdespachetat$
$\backslash startdisplaymath$ ... $\backslash stopdisplaymath$
$\backslash startdmath$ ... $\backslash stopdmath$
$\backslash startdocument [...,\dots^*...]$ ... $\backslash stopdocument$ * inherits: $\backslash setupdocument$ <small>OPT</small>
$\backslash startdute [...]$ ... $\backslash stopdute$ * REFERENCE
$\backslash starteffect [...]$ ... $\backslash stopeffect$ * NAME
$\backslash startEFFECT$ ... $\backslash stopEFFECT$
$\backslash startelement [...,\dots^*...]$ ... $\backslash stopelement$ * REFERENCE <small>OPT</small>
$\backslash startembeddedxtable [...,\dots^*...]$ ... $\backstopembeddedxtable$ * inherits: $\backsetuptable$ <small>OPT</small>
$\backstartembeddedxtable [...]$ ... $\backstopembeddedxtable$ * NAME <small>OPT</small>
$\backstartENUMERARE [...,\dots^*...]$ ... $\backstopENUMERARE$ * titlu = TEXT <small>OPT</small> semncarte = TEXT lista = TEXT referinta = REFERENCE
$\backstartENUMERARE [...,\dots^1...] \{...\}^2$ ... $\backstopENUMERARE$ 1 REFERENCE <small>OPT</small> <small>OPT</small> 2 TEXT
$\backstartexceptions [...]$ ... $\backstopexceptions$ * SPRACHE
$\backstartexpanded$ ... $\backstopexpanded$
$\backstartexpandedcollect$ ... $\backstopexpandedcollect$
$\backstartextendedcatcodetable \backstart...$ ... $\backstopextendedcatcodetable$ * CSNAME

$\backslash\text{startexternalfigurecollection}$ [...] ... $\backslash\text{stopexternalfigurecollection}$ * NAME
$\backslash\text{startfigura}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [..., <sup>3</sup> ...,...] ... $\backslash\text{stopfigura}$ 1 NAME 2 FILE 3 inherits: \figuraexterna
$\backslash\text{startfittingpage}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] ... $\backslash\text{stopfittingpage}$ 1 NAME 2 inherits: \setupfittingpage
$\backslash\text{startFITTINGPAGE}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopFITTINGPAGE}$ * inherits: \setupfittingpage <sup>OPT</sup> instances: TEXpage MPpage
$\backslash\text{startMPpage}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopMPpage}$ * inherits: \setupfittingpage <sup>OPT</sup>
$\backslash\text{startTEXpage}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopTEXpage}$ * inherits: \setupfittingpage <sup>OPT</sup>
$\backslash\text{startfixat}$ [...] ... $\backslash\text{stopfixat}$ * jos centru in <sup>OPT</sup> alt lohi implicit
$\backslash\text{startfloatcombination}$ [..., <sup>*</sup> ...,...] ... $\backslash\text{stopfloatcombination}$ * inherits: \setupcombination <sup>OPT</sup>
$\backslash\text{startfloatcombination}$ [...] ... $\backslash\text{stopfloatcombination}$ * N*M NAME <sup>OPT</sup>
$\backslash\text{startFLOATtext}$ [..., <sup>1</sup> ...] [..., <sup>2</sup> ...] {... <sup>3</sup> } ... $\backslash\text{stopFLOATtext}$ 1 split totdeauna stanga <sup>P</sup> dreapta int <sup>OPT</sup> ern extern spatiuspate cutspace instanga indreapta inmargin <sup>e</sup> marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective antet subsol 2 REFERENCE 3 TEXT instances: chemical figure table intermezzo graphic
$\backslash\text{startfont}$ [...] ... $\backslash\text{stopfont}$ * FONT <sup>OPT</sup>
$\backslash\text{startfontclass}$ [...] ... $\backslash\text{stopfontclass}$ * fiecare NAME
$\backslash\text{startfontsolution}$ [...] ... $\backslash\text{stopfontsolution}$ * NAME
$\backslash\text{startformula}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopformula}$ * impachetat tight centru incadrat inherits: \seteazafonttext <sup>OPT</sup>
$\backslash\text{startFORMULAformula}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopFORMULAformula}$ * impachetat tight centru in <sup>OPT</sup> adrat inherits: \seteazafonttext <sup>OPT</sup> instances: sp sd mp md
$\backslash\text{startformule}$ [..., <sup>*</sup> ...] ... $\backslash\text{stopformule}$ * + - REFERENCE <sup>OPT</sup>

$\backslash\text{startframed}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash\text{stopframed}$ 1 NAME OPT OPT 2 inherits: \seteazainconjurat
$\backslash\text{startframedcontent}$ [...] ... $\backslash\text{stopframedcontent}$ * NAME dezactivat OPT
$\backslash\text{startfundal}$ [...] ... $\backslash\text{stopfundal}$ * inherits: \seteazafundal
$\backslash\text{startFUNDAL}$ [...] ... $\backslash\text{stopFUNDAL}$ * inherits: \seteazafundal instances: fundal
$\backslash\text{startgridsnapping}$ [...] ... $\backslash\text{stopgridsnapping}$ * normal standard da strict tolerant sus subsoi ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME
$\backslash\text{startgridsnapping}$ [...] ... $\backslash\text{stopgridsnapping}$ * inherits: \definegridsnapping
$\backslash\text{starthboxestohbox}$ ... $\backslash\text{stophboxestohbox}$
$\backslash\text{starthboxregister}$ ... $\backslash\text{stophboxregister}$ * CSNAME NUMMER
$\backslash\text{startHELP}$ [...] ... $\backslash\text{stopHELP}$ * REFERENCE OPT instances: helptext
$\backslash\text{starthelptext}$ [...] ... $\backslash\text{stophelptext}$ * REFERENCE OPT
$\backslash\text{starthighlight}$ [...] ... $\backslash\text{stophighlight}$ * NAME
$\backslash\text{starthyphenation}$ [...] ... $\backslash\text{stophyphenation}$ * original tex implicit hyphenate expanded traditional niciunul
$\backslash\text{startimath}$ ... $\backslash\text{stopimath}$
$\backslash\text{startimpachetat}$ [...] ... $\backslash\text{stopimpachetat}$ * blank OPT
$\backslash\text{startindentedtext}$ [...] ... $\backslash\text{stopindentedtext}$ * NAME
$\backslash\text{startINDENTEDTEXT}$ ... $\backslash\text{stopINDENTEDTEXT}$
$\backslash\text{startingust}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash\text{stopingust}$ 1 NAME OPT OPT 2 inherits: \seteazaingust
$\backslash\text{startingust}$ [...] [ <sup>1</sup> ...] [...] [ <sup>2</sup> ...] ... $\backslash\text{stopingust}$ 1 inherits: \seteazaingust OPT 2 [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset

<code>\startingust [...]<sup>1</sup> [...]<sup>2</sup>,...] ... \stoppingust</code> 1    NAME                    OPT                    OPT 2    [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
<code>\starthiding ... \stophiding</code>
<code>\startinteractiune [...]<sup>*</sup> ... \stopinteractiune</code> *    ascuns NAME
<code>\startinterface ... \stopinterface</code> *    tot SPRACHE
<code>\startintertext ... \stopintertext</code>
<code>\startitemgroup [...]<sup>1</sup> [...]<sup>2</sup>,...] [...]<sup>3</sup>,...,...] ... \stopitemgroup</code> 1    NAME                    OPT                    OPT 2    inherits: \setupitemgroup 3    inherits: \setupitemgroup
<code>\startITEMGROUP [...]<sup>1</sup>,...] [...]<sup>2</sup>,...,...] ... \stopITEMGROUP</code> 1    inherits: \setupitemgroup 2    inherits: \setupitemgroup instances: itemize
<code>\startJScode ...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> ... \stopJScode</code> 1    NAME 2    uses 3    NAME
<code>\startJSreamble ...<sup>1</sup> ...<sup>2</sup> ...<sup>3</sup> ... \stopJSreamble</code> 1    NAME 2    folosit 3    now later
<code>\startknockout ... \stopknockout</code>
<code>\startlayout [...]<sup>*</sup> ... \stoplayout</code> *    NAME
<code>\startlinealignment [...]<sup>*</sup> ... \stoplinealignment</code> *    stanga centru dreapta max
<code>\startlinecorrection [...]<sup>*</sup>,...] ... \stoplinecorrection</code> *    blank inherits: \blanc                    OPT
<code>\startlinefiller [...]<sup>1</sup> [...]<sup>2</sup>,...,...] ... \stoplinefiller</code> 1    filler NAME                    OPT 2    inherits: \setuplinefiller
<code>\startLINENOTE [...]<sup>1</sup> {...}<sup>2</sup></code> 1    REFERENCE 2    TEXT instances: linenote
<code>\stoplinenote [...]<sup>*</sup></code> *    REFERENCE



<pre> \startlinenumbering [...] [...] ... \stoplinenumbering 1  NAME                OPT      OPT 2  continua  = da nu     start    = NUMMER     pas      = NUMMER     metoda   = pagina primul urmatorul </pre>
<pre> \startlinenumbering [...] [...] ... \stoplinenumbering 1  NAME                OPT      OPT 2  continuu NUMMER </pre>
<pre> \startlinetable ... \stoplinetable </pre>
<pre> \startlinetablebody ... \stoplinetablebody </pre>
<pre> \startlinetablecell [...] [...] ... \stoplinetablecell * inherits: \setuplinetable OPT </pre>
<pre> \startlinetablehead ... \stoplinetablehead </pre>
<pre> \startlinie [...] * REFERENCE </pre>
<pre> \startliniemargine [...] ... \stopliniemargine * NUMMER                OPT </pre>
<pre> \startliniemargine [...] [...] ... \stopliniemargine * inherits: \setupmarginrule OPT </pre>
<pre> \startLINES [...] [...] ... \stopLINES * inherits: \seteazalini instances: lines </pre>
<pre> \startlocalfootnotes ... \stoplocalfootnotes </pre>
<pre> \startlocalheadsetup ... \stoplocalheadsetup </pre>
<pre> \startlocallinecorrection [...] [...] ... \stoplocallinecorrection * blank inherits: \blanc OPT </pre>
<pre> \startlocalnotes [...] [...] ... \stoplocalnotes * NAME </pre>
<pre> \startlocalsetups [...] [...] ... \stoplocalsetups 1  grila                OPT 2  NAME </pre>
<pre> \startlocalsetups ... ... \stoplocalsetups * NAME </pre>
<pre> \startlua ... \stoplua </pre>
<pre> \startluacode ... \stopluacode </pre>
<pre> \startluaparameterset [...] ... \stopluaparameterset * NAME </pre>

<pre> \startluasetups [...] [...] ... \stopluasetups 1  grila          OPT 2  NAME </pre>
<pre> \startluasetups ... .. \stopluasetups *  NAME </pre>
<pre> \startMPclip {...} ... \stopMPclip *  NAME </pre>
<pre> \startMPcode {...} ... \stopMPcode *  NAME          OPT </pre>
<pre> \startMPdefinitions {...} ... \stopMPdefinitions *  NAME          OPT </pre>
<pre> \startMPdrawing [...] ... \stopMPdrawing *  -             OPT </pre>
<pre> \startMPenvironment [...] ... \stopMPenvironment *  reset global + OPT </pre>
<pre> \startMPextensions {...,*...} ... \stopMPextensions *  NAME          OPT </pre>
<pre> \startMPinclusions [...] {...} [...] ... \stopMPinclusions 1  +             OPT  OPT 2  NAME </pre>
<pre> \startMPinitializations ... \stopMPinitializations </pre>
<pre> \startMPpositiongraphic {...} {...,*...} ... \stopMPpositiongraphic 1  NAME          OPT 2  KEY </pre>
<pre> \startMPpositionmethod {...} ... \stopMPpositionmethod *  NAME </pre>
<pre> \startMPrun {...} ... \stopMPrun *  NAME          OPT </pre>
<pre> \startmakeup [...] [...] [...] ... \stopmakeup 1  NAME          OPT 2  inherits: \seteazamakeup </pre>
<pre> \startMAKEUPmakeup [...] [...] [...] ... \stopMAKEUPmakeup *  inherits: \seteazamakeup OPT instances: standard page text middle </pre>
<pre> \startmiddlemakeup [...] [...] [...] ... \stopmiddlemakeup *  inherits: \seteazamakeup OPT </pre>
<pre> \startpagemakeup [...] [...] [...] ... \stoppagemakeup *  inherits: \seteazamakeup OPT </pre>
<pre> \startstandardmakeup [...] [...] [...] ... \stopstandardmakeup *  inherits: \seteazamakeup OPT </pre>

$\backslash starttextmakeup$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstoptextmakeup$ * inherits: \seteazamakeup <sup>OPT</sup>
$\backstartmarginblock$ [... <sup>*</sup> ] ... $\backstopmarginblock$ * NAME <sup>OPT</sup>
$\backstartmarkedcontent$ [... <sup>*</sup> ] ... $\backstopmarkedcontent$ * reset tot NAME <sup>OPT</sup>
$\backstartMATHALIGNMENT$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopMATHALIGNMENT$ * inherits: \setupmathalignment <sup>OPT</sup> instances: align mathalignment
$\backstartMATHCASES$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopMATHCASES$ * inherits: \setupmathcases <sup>OPT</sup> instances: cases mathcases
$\backstartMATHMATRIX$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopMATHMATRIX$ * inherits: \setupmathmatrix <sup>PT</sup> instances: matrix mathmatrix
$\backstartmathmode$ ... $\backstopmathmode$
$\backstartmathstyle$ [... <sup>*</sup> ...] ... $\backstopmathstyle$ * display text script scriptscript cramped uncramped normal impachetat mic mare NAME
$\backstartmatrices$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopmatrices$ * inherits: \setupmathmat <sup>PT</sup> fix
$\backstartmaxaligned$ ... $\backstopmaxaligned$
$\backstartmediu$ [... <sup>*</sup> ] ... $\backstopmediu$ * FILE *
$\backstartmediu$ . <sup>*</sup> ... $\backstopmediu$ * FILE *
$\backstartmenuinteractiune$ [... <sup>*</sup> ] ... $\backstopmenuinteractiune$ * NAME
$\backstartmiddlealigned$ ... $\backstopmiddlealigned$
$\backstartmixedcolumns$ [... <sup>1</sup> ...] [... <sup>2</sup> ... <sup>2</sup> ...] ... $\backstopmixedcolumns$ 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 inherits: \setupmixedcolumns
$\backstartMIXEDCOLUMNS$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopMIXEDCOLUMNS$ * inherits: \setupmixedcolumns <sup>OPT</sup> instances: itemgroupcolumns boxedcolumns
$\backstartboxedcolumns$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopboxedcolumns$ * inherits: \setupmixedcolumns <sup>OPT</sup>
$\backstartitemgroupcolumns$ [... <sup>*</sup> ... <sup>*</sup> ...] ... $\backstopitemgroupcolumns$ * inherits: \setupmixedcolumns <sup>OPT</sup>

$\backslash\text{startmode} [\dots,*,\dots] \dots \backslash\text{stopmode}$ $*$ NAME
$\backslash\text{startmodeset} [\dots,\overset{1}{\dots}] \{\dots\} \dots \backslash\text{stopmodeset}$ 1 NAME implicit 2 CONTENT
$\backslash\text{startmodule} [\dots] \dots \backslash\text{stopmodule}$ $*$ FILE
$\backslash\text{startmoduletestsection} \dots \backslash\text{stopmoduletestsection}$
$\backslash\text{startmodule} \dots \dots \backslash\text{stopmodule}$ $*$ FILE
$\backslash\text{startnamedsection} [\dots] [\dots,\dots,\overset{2}{\dots}] [\dots,\dots,\overset{3}{\dots}] \dots \backslash\text{stopnamedsection}$ 1 ABSCHNITT 2 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 3 KEY = VALUE
$\backslash\text{startnamedsubformulas} [\dots,\overset{1}{\dots}] \{\dots\} \dots \backslash\text{stopnamedsubformulas}$ 1 + - REFERENCE 2 TEXT
$\backslash\text{startnarrower} [\dots,*,\dots] \dots \backslash\text{stopnarrower}$ $*$ [-+]stanga [-+]centru <sup>PT</sup> [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
$\backslash\text{startNARROWER} [\dots,*,\dots] \dots \backslash\text{stopNARROWER}$ $*$ [-+]stanga [-+]centru <sup>PT</sup> [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
$\backslash\text{startnegativ} \dots \backslash\text{stopnegativ}$
$\backslash\text{startnicelyfilledbox} [\dots,\dots,\overset{*}{\dots}] \dots \backslash\text{stopnicelyfilledbox}$ $*$ latime = DIMENSION inaltime = DIMENSION offset = DIMENSION strut = da nu
$\backslash\text{startnointerference} \dots \backslash\text{stopnointerference}$
$\backslash\text{startnotallmodes} [\dots,*,\dots] \dots \backslash\text{stopnotallmodes}$ $*$ NAME
$\backslash\text{startNOTE} [\dots,*,\dots] \dots \backslash\text{stopNOTE}$ $*$ REFERENCE instances: footnote endnote
$\backslash\text{startNOTE} [\dots,\dots,\overset{*}{\dots}] \dots \backslash\text{stopNOTE}$ $*$ titlu = TEXT <sup>OPT</sup> semncarte = TEXT lista = TEXT referinta = REFERENCE instances: footnote endnote
$\backslash\text{startendnote} [\dots,*,\dots] \dots \backslash\text{stopendnote}$ $*$ REFERENCE

<code>\startfootnote [...*...] ... \stopfootnote</code> *    REFERENCE                      OPT
<code>\startnotext ... \stopnotext</code>
<code>\startnotmode [...*...] ... \stopnotmode</code> *    NAME
<code>\startopus ... \stopopus</code>
<code>\startoutputstream [...*] ... \stopoutputstream</code> *    NAME
<code>\startoverlay ... \stopoverlay</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startpagefigure [...<sup>1</sup>] [...,...<sup>2</sup>...,...] ... \stoppagefigure</code> 1    FILE                              OPT 2    inherits: \setupexternalfigure
<code>\startpagegrid [...<sup>1</sup>] [...,...<sup>2</sup>...,...] ... \stoppagegrid</code> 1    NAME                              OPT                      OPT 2    inherits: \setuppagegrid
<code>\startpagegridspan [...<sup>1</sup>] [...,...<sup>2</sup>...,...] ... \stoppagegridspan</code> 1    NAME                              OPT 2    inherits: \setuppagegridspan
<code>\startPAGEGRID [...,...*...,...] ... \stopPAGEGRID</code> *    inherits: \setuppagegrid <sup>OPT</sup>
<code>\startpagelayout [...*] ... \stoppagelayout</code> *    pagina paginastanga paginadreapta
<code>\startpar [...<sup>1</sup>] [...,...<sup>2</sup>...,...] ... \stoppar</code> 1    NAME                              OPT                      OPT 2    inherits: \setupparagraph
<code>\startparagraf [...<sup>1</sup>] [...,...<sup>2</sup>...,...] ... \stopparagraf</code> 1    NAME                              OPT                      OPT 2    inherits: \setupparagraph
<code>\startparagraphs [...*] ... \stopparagraphs</code> *    NAME
<code>\startparagraphscell ... \stopparagraphscell</code>
<code>\startPARAGRAPHS ... \stopPARAGRAPHS</code>
<code>\startPARALLEL ... \stopPARALLEL</code>
<code>\startparbuilder [...*] ... \stopparbuilder</code> *    implicit oneline basic NAME

```

\startplacefloat [...]1 [...]2 [...] [...] ... \stopplacefloat
1 SINGULAR
2 titlu = TEXT
  semncarte = TEXT
  marcaje = TEXT
  lista = TEXT
  locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
            marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
            text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
            niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
            pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
3 KEY = VALUE

```

```

\startpuneFLOAT [...]1 [...]2 [...] [...] ... \stoppuneFLOAT
1 titlu = TEXT
  semncarte = TEXT
  marcaje = TEXT
  lista = TEXT
  locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
            marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
            text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
            niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
            pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE
instances: chemical figure table intermezzo graphic

```

```

\startpunechemical [...]1 [...]2 [...] [...] ... \stoppunechemical
1 titlu = TEXT
  semncarte = TEXT
  marcaje = TEXT
  lista = TEXT
  locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
            marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
            text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
            niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
            pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startpunefigure [...]1 [...]2 [...] [...] ... \stoppunefigure
1 titlu = TEXT
  semncarte = TEXT
  marcaje = TEXT
  lista = TEXT
  locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
            marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
            text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
            niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
            pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startpunegraphic [...]1 [...]2 [...] [...] ... \stoppunegraphic
1 titlu = TEXT
  semncarte = TEXT
  marcaje = TEXT
  lista = TEXT
  locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
            marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
            text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
            niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
            pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startpuneintermezzo [...1...2...] ... \stoppuneintermezzo
1 titlu      = TEXT          OPT          OPT
  semncarte = TEXT
  marcaje   = TEXT
  lista     = TEXT
  locatie   = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startpunetable [...1...2...] ... \stoppunetable
1 titlu      = TEXT          OPT          OPT
  semncarte = TEXT
  marcaje   = TEXT
  lista     = TEXT
  locatie   = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
             marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
             text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
             niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
             pagina paginastanga paginadreapta undeva effective antet subsol
  referinta = REFERENCE
2 KEY = VALUE

```

```

\startplacepairedbox [...1...2...] ... \stopplacepairedbox
1 NAME          OPT
2 inherits: \setuppairedbox

```

```

\startpunePAIREDBOX [...*...] ... \stoppunePAIREDBOX
* inherits: \setuppairedbox OPT
instances: legend

```

```

\startpunelegend [...*...] ... \stoppunelegend
* inherits: \setuppairedbox OPT

```

```

\startpositioning [...1...2...] ... \stoppositioning
1 NAME          OPT          OPT
2 inherits: \setarepozitie

```

```

\startpositionoverlay {...} ... \stoppositionoverlay
* NAME

```

```

\startpositiv ... \stoppositiv

```

```

\startpostponing [...] ... \stoppostponing
* [-+]NUMBER OPT

```

```

\startprocessassignmentcommand [...*...] ... \stopprocessassignmentcommand
* KEY = VALUE

```

```

\startprocessassignmentlist [...*...] ... \stopprocessassignmentlist
* KEY = VALUE

```

```

\startprocesscommacommand [...*...] ... \stopprocesscommacommand
* BEFEHL

```

```

\startprocesscommalist [...*...] ... \stopprocesscommalist
* BEFEHL

```

```

\startprodus [...] ... \stopprodus
* FILE *

```

\startprodus ... \stopprodus * FILE *
\startproiect [...]\stopproiect * FILE *
\startproiect ... \stopproiect * FILE *
\startprotectedcolors ... \stopprotectedcolors
\startpublicatie [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>...</sub> ] ... \stoppublicatie 1 NAME OPT OPT 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT
\startpuneformula [... <sup>*</sup> ...] ... \stoppuneformula * titlu = TEXT OPT suffix = TEXT referinta = + - REFERENCE
\startpuneformula [... <sup>*</sup> ...] ... \stoppuneformula * + - REFERENCE OPT
\starandomized ... \stoprandomized
\starawsetups [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... \stoprawsetups 1 grila OPT 2 NAME
\starawsetups ... \stoprawsetups * NAME
\startreadingfile ... \stopreadingfile
\startregime [...]\stopregime * inherits: \enableregime
\startregister [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] [ <sup>4</sup> ...] [... <sup>5</sup> +...] 1 NAME OPT OPT 2 NAME 3 TEXT 4 TEXT PROCESSOR->TEXT 5 INDEX
\startreusableMPgraphic { <sup>1</sup> ...} { <sup>2</sup> ...} ... \stopreusableMPgraphic 1 NAME OPT 2 KEY
\stariglatext {...}\stopriglatext * TEXT
\startscript [...]\stopscrip * hangul hanzi nihongo ethiopic thai test NAME



<pre> \startsectionblock [...]<sup>1</sup> [...]<sup>2</sup>... [...] ... \stopsectionblock 1  NAME                                OPT 2  semncarte = TEXT     inherits: \seteazablocsectione </pre>
<pre> \startSECTIONBLOCK [...]<sup>*</sup>... [...] ... \stopSECTIONBLOCK *  semncarte = TEXT                                OPT     inherits: \seteazablocsectione instances: frontmatter bodymatter appendices backmatter </pre>
<pre> \startappendices [...]<sup>*</sup>... [...] ... \stopappendices *  semncarte = TEXT                                OPT     inherits: \seteazablocsectione </pre>
<pre> \startbackmatter [...]<sup>*</sup>... [...] ... \stopbackmatter *  semncarte = TEXT                                OPT     inherits: \seteazablocsectione </pre>
<pre> \startbodymatter [...]<sup>*</sup>... [...] ... \stopbodymatter *  semncarte = TEXT                                OPT     inherits: \seteazablocsectione </pre>
<pre> \startfrontmatter [...]<sup>*</sup>... [...] ... \stopfrontmatter *  semncarte = TEXT                                OPT     inherits: \seteazablocsectione </pre>
<pre> \startsectionlevel [...]<sup>1</sup> [...]<sup>2</sup>... [...] [...]<sup>3</sup>... [...] ... \stopsectionlevel 1  NAME                                OPT      OPT      OPT 2  titlu          = TEXT     semncarte     = TEXT     marcaje       = TEXT     lista         = TEXT     referinta     = REFERENCE     numarpropriu  = TEXT 3  KEY = VALUE </pre>
<pre> \startSECTION [...]<sup>1</sup>... [...] [...]<sup>2</sup>... [...] ... \stopSECTION 1  titlu          = TEXT OPT      OPT     semncarte     = TEXT     marcaje       = TEXT     lista         = TEXT     referinta     = REFERENCE     numarpropriu  = TEXT 2  KEY = VALUE instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \startchapter [...]<sup>1</sup>... [...] [...]<sup>2</sup>... [...] ... \stopchapter 1  titlu          = TEXT OPT      OPT     semncarte     = TEXT     marcaje       = TEXT     lista         = TEXT     referinta     = REFERENCE     numarpropriu  = TEXT 2  KEY = VALUE </pre>
<pre> \startpart [...]<sup>1</sup>... [...] [...]<sup>2</sup>... [...] ... \stoppart 1  titlu          = TEXT OPT      OPT     semncarte     = TEXT     marcaje       = TEXT     lista         = TEXT     referinta     = REFERENCE     numarpropriu  = TEXT 2  KEY = VALUE </pre>

```

\startsection [...,\sfrac{1}{...},...] [...,\sfrac{2}{...},...] ... \stopsection
1   titlu       = TEXTOPT
    semncarte   = TEXT
    marcaje     = TEXT
    lista       = TEXT
    referinta   = REFERENCE
    numarpropriu = TEXT
2   KEY = VALUE

```

```

\startsubject [...,\sfrac{1}{...},...] [...,\sfrac{2}{...},...] ... \stopsubject
1   titlu       = TEXTOPT
    semncarte   = TEXT
    marcaje     = TEXT
    lista       = TEXT
    referinta    = REFERENCE
    numarpropriu = TEXT
2   KEY = VALUE

```

```

\startsubsection [...,\frac{1}{2}...,...] [...,\frac{2}{2}...,...] ... \stopsubsection
1  titlu           = TEXT           OPT           OPT
   semncarte      = TEXT
   marcaje        = TEXT
   lista          = TEXT
   referinta      = REFERENCE
   numarpropriu   = TEXT
2  KEY = VALUE

```

```

\startsubsubject [...,\sub{...},...] [...,\sub{...},...] ... \stopsubsubject
1  titlu           = TEXT           OPT
   semncarte      = TEXT
   marcaje        = TEXT
   lista          = TEXT
   referinta      = REFERENCE
   numarpropriu   = TEXT
2  KEY = VALUE

```

```

\startsubsubsection [...,\sfrac{1}{2}...,...] [...,\sfrac{2}{2}...,...] ... \stopsubsubsection
1   titlu           = TEXT
    semncarte       = TEXT
    marcaje         = TEXT
    lista           = TEXT
    referinta       = REFERENCE
    numarpropriu    = TEXT
2   KEY = VALUE

```

```

\startsubsubsubject [...,\sup{1}...,...] [...,\sup{2}...,...] ... \stopsubsubsubject
1  titlu           = TEXT
   semncarte      = TEXT
   marcaje        = TEXT
   lista          = TEXT
   referinta      = REFERENCE
   numarpropriu   = TEXT
2  KEY = VALUE

```

```

\startsubsubsection [...1...] [...2...] ... \stopsubsubsection
1  titlu           = TEXT
   semncarte      = TEXT
   marcaje        = TEXT
   lista           = TEXT
   referinta      = REFERENCE
   numarpropriu   = TEXT
2  KEY = VALUE

```

```

\startsubsubsubsubject [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] ... \stopsubsubsubsubject
1  titlu           = TEXT
   semncarte      = TEXT
   marcaje        = TEXT
   lista          = TEXT
   referinta      = REFERENCE
   numarpropriu   = TEXT
2  KEY = VALUE

```

<pre> \startsubsubsubsubsection [...,\subsubsubsubsection<sup>1</sup>...] [...,\subsubsubsubsection<sup>2</sup>...] ... \stopsubsubsubsubsection 1  titlu           = TEXT    semncarte      = TEXT    marcaje       = TEXT    lista         = TEXT    referinta     = REFERENCE    numarpropriu  = TEXT 2  KEY = VALUE </pre>
<pre> \startsubsubsubsubsubject [...,\subsubsubsubsubject<sup>1</sup>...] [...,\subsubsubsubsubject<sup>2</sup>...] ... \stopsubsubsubsubsubject 1  titlu           = TEXT    semncarte      = TEXT    marcaje       = TEXT    lista         = TEXT    referinta     = REFERENCE    numarpropriu  = TEXT 2  KEY = VALUE </pre>
<pre> \starttitle [...,\title<sup>1</sup>...] [...,\title<sup>2</sup>...] ... \stoptitle 1  titlu           = TEXT    semncarte      = TEXT    marcaje       = TEXT    lista         = TEXT    referinta     = REFERENCE    numarpropriu  = TEXT 2  KEY = VALUE </pre>
<pre> \startlines [...,\lines<sup>*</sup>...] ... \stoplines * inherits: \seteazalines<sup>OPT</sup> </pre>
<pre> \startLUA [...,\LUA<sup>*</sup>...] ... \stopLUA * inherits: \seteazalua<sup>OPT</sup> </pre>
<pre> \startMP [...,\MP<sup>*</sup>...] ... \stopMP * inherits: \seteazamp<sup>OPT</sup> </pre>
<pre> \startPARSEDXML [...,\PARSEDXML<sup>*</sup>...] ... \stopPARSEDXML * inherits: \seteazaparsedxml<sup>OPT</sup> </pre>
<pre> \startTEX [...,\TEX<sup>*</sup>...] ... \stopTEX * inherits: \seteazatex<sup>OPT</sup> </pre>
<pre> \starttyping [...,\typing<sup>*</sup>...] ... \stoptyping * inherits: \seteazatyping<sup>OPT</sup> </pre>
<pre> \startXML [...,\XML<sup>*</sup>...] ... \stopXML * inherits: \seteazaxml<sup>OPT</sup> </pre>
<pre> \startitemize [...,\itemize<sup>1</sup>...] [...,\itemize<sup>2</sup>...] ... \stopitemize 1  inherits: \setupitemgroup<sup>OPT</sup> 2  inherits: \setupitemgroup </pre>
<pre> \startalign [...,\align<sup>*</sup>...] ... \stopalign * inherits: \setupmathalignment<sup>OPT</sup> </pre>
<pre> \startmathalignment [...,\mathalignment<sup>*</sup>...] ... \stopmathalignment * inherits: \setupmathalignment<sup>OPT</sup> </pre>
<pre> \startcases [...,\cases<sup>*</sup>...] ... \stopcases * inherits: \setupmathcases<sup>OPT</sup> </pre>

$\backslash\text{startmathcases}$ [...] $\backslash\text{stopmathcases}$ * inherits: $\backslash\text{setupmathcases}$ <sup>OPT</sup>
$\backslash\text{startmathmatrix}$ [...] $\backslash\text{stopmathmatrix}$ * inherits: $\backslash\text{setupmathmatrix}$ <sup>PT</sup>
$\backslash\text{startmatrix}$ [...] $\backslash\text{stopmatrix}$ * inherits: $\backslash\text{setupmatrix}$ <sup>OPT</sup>
$\backslash\text{startsetups}$ [...] $\backslash\text{stopsetups}$ 1 grila <sup>OPT</sup> 2 NAME
$\backslash\text{startmdformula}$ [...] $\backslash\text{stopmdformula}$ * impachetat tight centr <sup>OPT</sup> incadrat inherits: $\backslash\text{seteazafonttext}$
$\backslash\text{startmpformula}$ [...] $\backslash\text{stopmpformula}$ * impachetat tight centr <sup>OPT</sup> incadrat inherits: $\backslash\text{seteazafonttext}$
$\backslash\text{startsdfformula}$ [...] $\backslash\text{stopsdfformula}$ * impachetat tight centr <sup>OPT</sup> incadrat inherits: $\backslash\text{seteazafonttext}$
$\backslash\text{startspformula}$ [...] $\backslash\text{stopspformula}$ * impachetat tight centr <sup>OPT</sup> incadrat inherits: $\backslash\text{seteazafonttext}$
$\backslash\text{startsetups}$ ... $\backslash\text{stopsetups}$ * NAME
$\backslash\text{startshift}$ [...] $\backslash\text{stopshift}$ * NAME
$\backslash\text{startsidebar}$ [...] $\backslash\text{stopsidebar}$ 1 NAME <sup>OPT</sup> <sup>OPT</sup> 2 inherits: $\backslash\text{setupsidebar}$
$\backslash\text{startsimplecolumns}$ [...] $\backslash\text{stopsimplecolumns}$ * inherits: $\backslash\text{setsimplecolumnsize}$ <sup>OPT</sup>
$\backslash\text{startspecialitem}$ [...] $\backslash\text{stopspecialitem}$ 1 element <sup>OPT</sup> <sup>OPT</sup> 2 REFERENCE
$\backslash\text{startspecialitem}$ [...] $\backslash\text{stopspecialitem}$ * sub propriu
$\backslash\text{startspecialitem}$ [...] {...} $\backslash\text{stopspecialitem}$ 1 sym rulat mar 2 TEXT
$\backslash\text{startspread}$ ... $\backslash\text{stopspread}$
$\backslash\text{start}$ [...] $\backslash\text{stop}$ * NAME <sup>OPT</sup>
$\backslash\text{startSTARTSTOP}$ ... $\backslash\text{stopSTARTSTOP}$

<pre> \startstaticMPfigure {...} ... \stopstaticMPfigure *   NAME </pre>
<pre> \startstaticMPgraphic {...} {...,<sup>2</sup>...} ... \stopstaticMPgraphic 1   NAME                               OPT 2   KEY </pre>
<pre> \STARTSTOP {...} *   CONTENT </pre>
<pre> \startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter </pre>
<pre> \startstructurepageregister [...]<sup>1</sup> [...]<sup>2</sup> [...,<sup>3</sup>...,...] [...,<sup>4</sup>...,...] 1   NAME                               OPT 2   NAME 3   eticheta      = NAME    keys           = TEXT PROCESSOR-&gt;TEXT    entries        = TEXT PROCESSOR-&gt;TEXT    keys:1         = TEXT    keys:2         = TEXT    keys:3         = TEXT    entries:1      = TEXT    entries:2      = TEXT    entries:3      = TEXT    alternativ      = TEXT 4   KEY = VALUE </pre>
<pre> \startstyle [...,<sup>*</sup>...,...] ... \stopstyle *   inherits: \setupstyle </pre>
<pre> \startstyle [...]<sup>*</sup> ... \stopstyle *   NAME FONT </pre>
<pre> \startSTYLE ... \stopSTYLE </pre>
<pre> \startsubformulas [...,<sup>*</sup>...,...] ... \stopsubformulas *   + - REFERENCE          OPT </pre>
<pre> \startsubjectlevel [...]<sup>1</sup> [...,<sup>2</sup>...,...] [...,<sup>3</sup>...,...] ... \stopsubjectlevel 1   NAME                               OPT      OPT      OPT 2   titlu           = TEXT    semncarte       = TEXT    marcaje         = TEXT    lista           = TEXT    referinta       = REFERENCE    numarpropriu    = TEXT 3   KEY = VALUE </pre>
<pre> \startsubsentence ... \stopsubsentence </pre>
<pre> \startsubsoltabel [...]<sup>*</sup> ... \stopsubsoltabel *   NAME </pre>
<pre> \startsubstack ... \stopsubstack </pre>
<pre> \startsuspendat [...,<sup>1</sup>...,...] {...}<sup>2</sup> ... \stopsuspendat 1   distanta = DIMENSION  OPT    n         = NUMMER    locatie   = stanga dreapta 2   CONTENT </pre>

$\backslash$ startsuspendat [ <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash$ stopsuspendat 1    stanga dreapta    OPT 2    CONTENT
$\backslash$ startsymbolset [...] ... $\backslash$ stopsymbolset *    NAME
$\backslash$ startTABLE [... <sup>*</sup> ...] ... $\backslash$ stopTABLE *    inherits: $\backslash$ setupTABLE
$\backslash$ startTABLEbody [... <sup>*</sup> ...] ... $\backslash$ stopTABLEbody *    inherits: $\backslash$ setupTABLE    OPT
$\backslash$ startTABLEfoot [... <sup>*</sup> ...] ... $\backslash$ stopTABLEfoot *    inherits: $\backslash$ setupTABLE    OPT
$\backslash$ startTABLEhead [... <sup>*</sup> ...] ... $\backslash$ stopTABLEhead *    inherits: $\backslash$ setupTABLE    OPT
$\backslash$ startTABLEnext [... <sup>*</sup> ...] ... $\backslash$ stopTABLEnext *    inherits: $\backslash$ setupTABLE    OPT
$\backslash$ starttabellele [  <sup>*</sup> ...] ... $\backslash$ stoptabellele *    TEMPLATE
$\backslash$ starttabellele [...] ... $\backslash$ stoptabellele *    NAME
$\backslash$ starttabelul [  <sup>1</sup> ...] [... <sup>2</sup> ...] ... $\backslash$ stoptabelul 1    TEMPLATE    OPT 2    inherits: $\backslash$ seteazatabele
$\backslash$ starttabelul [...] [... <sup>2</sup> ...] ... $\backslash$ stoptabelul 1    NAME    OPT 2    inherits: $\backslash$ seteazatabele
$\backslash$ starttabulate [  <sup>1</sup> ...] [... <sup>2</sup> ...] ... $\backslash$ stoptabulate 1    TEMPLATE    OPT    OPT 2    inherits: $\backslash$ seteazatabulatori
$\backslash$ starttabulatehead [ <sup>*</sup> ...] ... $\backslash$ stoptabulatehead *    NAME    OPT
$\backslash$ starttabulatetail [ <sup>*</sup> ...] ... $\backslash$ stoptabulatetail *    NAME    OPT
$\backslash$ startTABULATE [ <sup>1</sup> ...] [... <sup>2</sup> ...] ... $\backslash$ stopTABULATE 1    NAME    OPT    OPT 2    inherits: $\backslash$ seteazatabulatori instances: legend fact
$\backslash$ startfact [ <sup>1</sup> ...] [... <sup>2</sup> ...] ... $\backslash$ stopfact 1    NAME    OPT    OPT 2    inherits: $\backslash$ seteazatabulatori
$\backslash$ startlegend [ <sup>1</sup> ...] [... <sup>2</sup> ...] ... $\backslash$ stoplegend 1    NAME    OPT    OPT 2    inherits: $\backslash$ seteazatabulatori

$\backslash startTABULATION$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash stopTABULATION$ 1 NAME OPT OPT 2 inherits: $\backslash setupstabulation$
$\backslash starttexcode$ ... $\backslash stoptexcode$
$\backslash starttexdefinition$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] [ <sup>4</sup> ...] [ <sup>5</sup> ...] [ <sup>6</sup> ...] [ <sup>7</sup> ...] ... $\backslash stoptexdefinition$ 1 spaces nospaces OPT OPT OPT OPT OPT OPT 2 global 3 unexpanded 4 expanded 5 singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument tripleargument quadrupleargument quintupleargument sextupleargument 6 NAME 7 TEMPLATE
$\backslash starttext$ ... $\backslash stoptext$
$\backslash starttextajutator$ [ <sup>*</sup> ...] ... $\backslash stoptextajutator$ * REFERENCE OPT
$\backslash starttextbackground$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash stoptextbackground$ 1 NAME OPT 2 inherits: $\backslash setuptextbackground$
$\backslash starttextbackgroundmanual$ ... $\backslash stoptextbackgroundmanual$
$\backslash startTEXTBACKGROUND$ [ <sup>*</sup> ...] ... $\backslash stopTEXTBACKGROUND$ * inherits: $\backslash setuptextbackground$ OPT
$\backslash starttextcolor$ [ <sup>*</sup> ...] ... $\backslash stoptextcolor$ * COLOR
$\backslash starttextcolorintent$ ... $\backslash stoptextcolorintent$
$\backslash startLABELtext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash stopLABELtext$ 1 SPRACHE OPT 2 KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash starttextflow$ [ <sup>*</sup> ...] ... $\backslash stoptextflow$ * NAME
$\backslash startFRAMEDTEXT$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash stopFRAMEDTEXT$ 1 stanga dreapta centr <sup>P</sup> iniunul OPT 2 inherits: $\backslash setupframedtext$ instances: framedtext
$\backslash startframedtext$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] ... $\backslash stopframedtext$ 1 stanga dreapta centr <sup>P</sup> iniunul OPT 2 inherits: $\backslash setupframedtext$
$\backslash starttitlu$ [ <sup>1</sup> ...] { <sup>2</sup> ...} ... $\backslash stoptitlu$ 1 REFERENCE OPT 2 TEXT
$\backslash starttokens$ [ <sup>*</sup> ...] ... $\backslash stoptokens$ * NAME

$\backslash\text{starttransparent}$ [...] ... $\backslash\text{stoptransparent}$ * COLOR
$\backslash\text{starttypescript}$ [... <sup>1</sup> ,...] [... <sup>2</sup> ,...] [... <sup>3</sup> ,...] ... $\backslash\text{stoptypescript}$ 1 serif sans mono math handwriting calligraphy <small>OPT</small> 2 NAME 3 size nume
$\backslash\text{starttypescriptcollection}$ [...] ... $\backslash\text{stoptypescriptcollection}$ * NAME
$\backslash\text{startTYPING}$ [...,*...,...] ... $\backslash\text{stopTYPING}$ * inherits: $\backslash\text{seteazatyping}$ <small>OPT</small> instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startTYPING}$ [...,*...,...] ... $\backslash\text{stopTYPING}$ * continuu <small>OPT</small> instances: typing LUA MP PARSEDXML TEX XML
$\backslash\text{startuniqueMPgraphic}$ {... <sup>1</sup> } {... <sup>2</sup> ,...} ... $\backslash\text{stopuniqueMPgraphic}$ 1 NAME <small>OPT</small> 2 KEY
$\backslash\text{startuniqueMPpagegraphic}$ {... <sup>1</sup> } {... <sup>2</sup> ,...} ... $\backslash\text{stopuniqueMPpagegraphic}$ 1 NAME <small>OPT</small> 2 KEY
$\backslash\text{startusableMPgraphic}$ {... <sup>1</sup> } {... <sup>2</sup> ,...} ... $\backslash\text{stopusableMPgraphic}$ 1 NAME <small>OPT</small> 2 KEY
$\backslash\text{startuseMPgraphic}$ {... <sup>1</sup> } {... <sup>2</sup> ,...} ... $\backslash\text{stopuseMPgraphic}$ 1 NAME <small>OPT</small> 2 KEY
$\backslash\text{startusemathstyleparameter}$ \.* ... $\backslash\text{stopusemathstyleparameter}$ * CSNAME
$\backslash\text{startusingbtxs specification}$ [...] ... $\backslash\text{stopusingbtxs specification}$ * NAME
$\backslash\text{startvboxregister}$ .* ... $\backslash\text{stopvboxregister}$ * CSNAME NUMBER
$\backslash\text{startvboxtohbox}$ ... $\backslash\text{stopvboxtohbox}$
$\backslash\text{startvboxtohboxseparator}$ ... $\backslash\text{stopvboxtohboxseparator}$
$\backslash\text{startviewerlayer}$ [...] ... $\backslash\text{stopviewerlayer}$ * NAME
$\backslash\text{startVIEWERLAYER}$ ... $\backslash\text{stopVIEWERLAYER}$
$\backslash\text{startvtopregister}$ .* ... $\backslash\text{stopvtopregister}$ * CSNAME NUMBER



<pre> \startxcell [...] [...] ... \stopxcell 1  NAME          OPT          OPT 2  nx  =  NUMBER     ny  =  NUMBER     nc  =  NUMBER     nr  =  NUMBER     inherits: \setupxtable </pre>
<pre> \startxcellgroup [...] [...] ... \stopxcellgroup 1  NAME          OPT          OPT 2  inherits: \setupxtable </pre>
<pre> \startxgroup [...] [...] ... \stopxgroup 1  NAME          OPT          OPT 2  inherits: \setupxtable </pre>
<pre> \startxmldisplayverbatim [...] ... \stopxmldisplayverbatim *  NAME </pre>
<pre> \startxmllineverbatim [...] ... \stopxmllineverbatim *  NAME </pre>
<pre> \startxmlraw ... \stopxmlraw </pre>
<pre> \startxmlsetups [...] [...] ... \stopxmlsetups 1  grila          OPT 2  NAME </pre>
<pre> \startxmlsetups ... ... \stopxmlsetups *  NAME </pre>
<pre> \startxrow [...] [...] ... \stopxrow 1  NAME          OPT          OPT 2  inherits: \setupxtable </pre>
<pre> \startxrowgroup [...] [...] ... \stopxrowgroup 1  NAME          OPT          OPT 2  inherits: \setupxtable </pre>
<pre> \startxtable [...] [...] ... \stopxtable *  inherits: \setupxtable </pre>
<pre> \startxtablebody [...] [...] ... \stopxtablebody *  inherits: \setupxtable </pre>
<pre> \startxtablebody [...] ... \stopxtablebody *  NAME </pre>
<pre> \startxtablefoot [...] [...] ... \stopxtablefoot *  inherits: \setupxtable </pre>
<pre> \startxtablefoot [...] ... \stopxtablefoot *  NAME </pre>
<pre> \startxtablehead [...] [...] ... \stopxtablehead *  inherits: \setupxtable </pre>
<pre> \startxtablehead [...] ... \stopxtablehead *  NAME </pre>

<code>\startxnext [...,..<sup>*</sup>...,...] ... \stopxnext</code> <code>* inherits: \setupxnext <sup>OPT</sup></code>
<code>\startxnext [...] ... \stopxnext</code> <code>* NAME <sup>OPT</sup></code>
<code>\startXTABLE [...,..<sup>*</sup>...,...] ... \stopXTABLE</code> <code>* inherits: \setupxtable <sup>OPT</sup></code>
<code>\startxtable [...] ... \stopxtable</code> <code>* NAME <sup>OPT</sup></code>
<code>\stivacampuri [...<sup>1</sup>] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]</code> <code>1 NAME <sup>OPT</sup></code> <code>2 NAME <sup>OPT</sup></code> <code>3 inherits: \setupfieldcategory</code>
<code>\stopLINENOTE [...]</code> <code>* REFERENCE</code> <code>instances: linenote</code>
<code>\stoplinie [...]</code> <code>* REFERENCE</code>
<code>\stopregister [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\stopstructurepageregister [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\strictdoifelsenextoptional {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 TRUE</code> <code>2 FALSE</code>
<code>\strictdoifnextoptionalelse {...<sup>1</sup>} {...<sup>2</sup>}</code> <code>1 TRUE</code> <code>2 FALSE</code>
<code>\stripcharacter ... \from ...<sup>2</sup> \to ...<sup>3</sup></code> <code>1 CHARACTER</code> <code>2 TEXT</code> <code>3 CSNAME</code>
<code>\strippedcsname \*...</code> <code>* CSNAME</code>
<code>\strippedcsname ...</code> <code>* TEXT</code>
<code>\stripspaces \from ...<sup>1</sup> \to ...<sup>2</sup></code> <code>1 TEXT</code> <code>2 CSNAME</code>
<code>\structurelistuservariable {...}</code> <code>* KEY</code>
<code>\structurenumber</code>

<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...<sup>1</sup>...<sup>2</sup>...] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [...<sup>1</sup>] {...<sup>2</sup>}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\sublinie {...}</code> * TEXT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...<sup>1</sup>} {...<sup>2</sup>} \<sup>3</sup>...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME

\swapcounts \... \... 1 CSNAME 2 CSNAME
\swapdimens \... \... 1 CSNAME 2 CSNAME
\swapface
\swapmacros \... \... 1 CSNAME 2 CSNAME
\swaptypesface
\switchstyleonly [...] * rm ss tt hw cg roman serif regular sans sansserif suport type teletype mono scrismanual caligrafic
\switchstyleonly \... * CSNAME
\switchtocolour [...] * COLOR
\switchtointerlinespace [...] [...] 1 NAME OPT 2 inherits: \seteazaspatiuinterliniar
\switchtointerlinespace [...] * on dezactivat reset auto mic mediu mare NUMMER DIMENSION
\switchtointerlinespace [...] * NAME
\symbolreference [...] * REFERENCE
\synchronizeblank
\synchronizeindenting
\synchronizemarking [...] [...] [...] 1 BESCHRIFTUNG OPT 2 NUMMER 3 mentine
\synchronizeoutputstreams [...] * NAME
\synchronizestrut {...} * da nu auto cap ajustat linie implicit CHARACTER
\synchronizewhitespace

<code>\SYNONYM [...]{...}{...}</code> 1 NAME OPT 2 TEXT 3 CONTENT instances: abbreviation
<code>\systemlog {...}{...}{...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemlogfirst {...}{...}{...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast {...}{...}{...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups {...}</code> * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {...}{...}{...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\tequal {...}{...}</code> 1 TEXT OPT OPT 2 TEXT

<pre> \testandsplitstring <sup>1</sup>... \at <sup>2</sup>... \to <sup>3</sup>... \and <sup>4</sup>... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME </pre>
<pre> \testcolumn [<sup>1</sup>...] [<sup>2</sup>...] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testfeature {...} {...} 1 NUMBER 2 CONTENT </pre>
<pre> \testfeatureonce {...} {...} 1 NUMBER 2 CONTENT </pre>
<pre> \testpage [<sup>1</sup>...] [<sup>2</sup>...] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testpageonly [<sup>1</sup>...] [<sup>2</sup>...] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testpagesync [<sup>1</sup>...] [<sup>2</sup>...] 1 NUMBER OPT 2 DIMENSION </pre>
<pre> \testtokens [...] * NAME </pre>
<pre> \tex {...} * CONTENT </pre>
<pre> \texdefinition {...} * NAME </pre>
<pre> \texsetup {...} * NAME </pre>
<pre> \textajutator [<sup>1</sup>...] {...} {...} 1 REFERENCE OPT 2 TEXT 3 TEXT </pre>
<pre> \TEXTBACKGROUND {...} * CONTENT </pre>
<pre> \textcitation [...,<sup>1</sup>...,...] [<sup>2</sup>...] 1 referinta = REFERENCE    alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                authoryear    inainte   = BEFEHL    dupa      = BEFEHL    stanga    = BEFEHL    dreapta   = BEFEHL    inherits: \setupbtx 2 REFERENCE </pre>

<pre> \textcitation [...] [...] 1  implicit category<sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2  REFERENCE </pre>
<pre> \textcitation [...,\overset{1}{...},...] [...,\overset{2}{...},...] 1  referinta    = REFERENCE     alternativ   = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                     authoryear     inainte     = BEFEHL     dupa        = BEFEHL     stanga      = BEFEHL     dreapta     = BEFEHL     inherits: \setupbtx 2  KEY = VALUE </pre>
<pre> \textcite [...,\overset{1}{...},...] [...] 1  referinta    = REFERENCE     alternativ   = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                     authoryear     inainte     = BEFEHL     dupa        = BEFEHL     stanga      = BEFEHL     dreapta     = BEFEHL     inherits: \setupbtx 2  REFERENCE </pre>
<pre> \textcite [...] [...] 1  implicit category<sup>OPT</sup> entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2  REFERENCE </pre>
<pre> \textcite [...,\overset{1}{...},...] [...,\overset{2}{...},...] 1  referinta    = REFERENCE     alternativ   = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum                     authoryear     inainte     = BEFEHL     dupa        = BEFEHL     stanga      = BEFEHL     dreapta     = BEFEHL     inherits: \setupbtx 2  KEY = VALUE </pre>
<pre> \textcontrolspace </pre>
<pre> \LABELtext {...} *  KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel </pre>
<pre> \btxlabellimba </pre>
<pre> \headlimba </pre>
<pre> \labellimba </pre>
<pre> \mathlabellimba </pre>
<pre> \operatorlimba </pre>
<pre> \prefixlimba </pre>
<pre> \suffixlimba </pre>
<pre> \taglabellimba </pre>

<code>\unitlimba</code>
<code>\textflowcollector {...}</code> <code>* NAME</code>
<code>\FRAMEDTEXT [...<sup>1</sup>...] {...<sup>2</sup>}</code> <code>1 inherits: \setupframedtext</code> <code>2 CONTENT</code> <code>instances: framedtext</code>
<code>\textmath {...}</code> <code>* CONTENT</code>
<code>\textminus</code>
<code>\textormathchar {...}</code> <code>* NUMMER</code>
<code>\textplus</code>
<code>\textumlere [...<sup>1</sup>...] {...<sup>2</sup>} {...<sup>3</sup>}</code> <code>1 inherits: \setezarigtextumlere OPT OPT</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\textvisiblespace</code>
<code>\thainumerals {...}</code> <code>* NUMMER</code>
<code>\thefirstcharacter {...}</code> <code>* TEXT</code>
<code>\thenormalizedbodyfontsize {...}</code> <code>* DIMENSION</code>
<code>\theremainingcharacters {...}</code> <code>* TEXT</code>
<code>\thickspace</code>
<code>\thinspace</code>
<code>\thirtoffivearguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>}</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code> <code>5 TEXT</code>
<code>\thirtoffourarguments {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 TEXT</code> <code>4 TEXT</code>



`\thirdofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\thirdofthreearguments {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT

`\thirdofthreeunexpanded {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT

`\thookleftarrow {...} {...}`

1 TEXT  
2 TEXT

OPT

OPT

`\thookrightarrow {...} {...}`

1 TEXT  
2 TEXT

OPT

OPT

`\threedigitrounding {...}`

\* NUMMER

`\tibetannumerals {...}`

\* NUMMER

`\tightlayer [...]`

\* NAME

`\tilde {...}`

\* CHARACTER

`\tinyfont`

`\tleftarrow {...} {...}`

1 TEXT  
2 TEXT

OPT

OPT

`\tleftrightarrow {...} {...}`

1 TEXT  
2 TEXT

OPT

OPT

`\tlap {...}`

\* CONTENT

`\tleftarrow {...} {...}`

1 TEXT  
2 TEXT

OPT

OPT

`\tleftharpoonup {...} {...}`

1 TEXT  
2 TEXT

OPT

OPT

$\backslash\text{tleftharpoonup}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{leftrightharpoonup}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{leftrightharpoons}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{tmapsto}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{tochar}$ $\{...\}$ *    e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
$\backslash\text{tolinenote}$ $[...]$ *    REFERENCE
$\backslash\text{TOOLTIP}$ $[...,\dots]^1,...] \{...\}^2 \{...\}^3$ 1    inherits: $\backslash\text{setupTOOLTIP}$ 2    TEXT 3    TEXT instances: tooltip
$\backslash\text{TOOLTIP}$ $[...]^1 \{...\}^2 \{...\}^3$ 1    stanga centru dreapta 2    TEXT 3    TEXT instances: tooltip
$\backslash\text{topbox}$ $\{...\}$ *    CONTENT
$\backslash\text{topleftbox}$ $\{...\}$ *    CONTENT
$\backslash\text{toplinebox}$ $\{...\}$ *    CONTENT
$\backslash\text{toprightbox}$ $\{...\}$ *    CONTENT
$\backslash\text{topskippedbox}$ $\{...\}$ *    CONTENT
$\backslash\text{tRightharpoonup}$ $\{...\}^1 \{...\}^2$ 1    TEXT                    OPT            OPT 2    TEXT
$\backslash\text{tracecatcodetables}$
$\backslash\text{tracedfontname}$ $\{...\}$ *    FONT
$\backslash\text{traceoutputroutines}$

<code>\tracepositions</code>
<code>\traduce [.,..*=.,..]</code> <code>* SPRACHE = TEXT<sup>PT</sup></code>
<code>\transparencycomponents {...}</code> <code>* COLOR</code>
<code>\transparent [...]<sup>1</sup> {...}<sup>2</sup></code> <code>1 COLOR</code> <code>2 CONTENT</code>
<code>\trecilafonttext [...]*...]</code> <code>* inherits: \seteazafonttext</code>
<code>\trel {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\trightarrow {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\trightharpoondown {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\trightharpoonup {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\trightleftharpoons {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\trightoverleftarrow {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\triplebond</code>
<code>\truefilename {...}</code> <code>* FILE</code>
<code>\truefontname {...}</code> <code>* FONT</code>
<code>\ttraggedright</code>
<code>\ttriplerel {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>
<code>\twoheadleftarrow {...}<sup>1</sup> {...}<sup>2</sup></code> <code>1 TEXT OPT OPT</code> <code>2 TEXT</code>

$\backslash$ twoheadrightarrow {...} {...} 1    TEXT                      OPT            OPT 2    TEXT
$\backslash$ twodigitrounding {...} *    NUMMER
$\backslash$ tx
$\backslash$ txx
$\backslash$ typ [...,\overset{1}{=},...] {...} 1    inherits: \seteazatype 2    CONTENT
$\backslash$ type [...,\overset{1}{=},...] {...} 1    inherits: \seteazatype 2    CONTENT
$\backslash$ typedefinedbuffer [...,\overset{1}{.}] [...,\overset{2}{=},...] 1    BUFFER                                      OPT 2    inherits: \seteazatyping
$\backslash$ typeface
$\backslash$ typefile [...,\overset{1}{.}] [...,\overset{2}{=},...] {...} 1    NAME                      OPT            OPT 2    inherits: \seteazatyping 3    FILE
$\backslash$ typeinlinebuffer [...,\overset{1}{.},...] [...,\overset{2}{=},...] 1    BUFFER                      OPT            OPT 2    inherits: \seteazatype
$\backslash$ typescriptone
$\backslash$ typescriptprefix {...} *    NAME
$\backslash$ typescriptthree
$\backslash$ typescripttwo
$\backslash$ typesetbuffer [...,\overset{1}{.}] [...,\overset{2}{=},...] 1    * BUFFER                      OPT            OPT 2    inherits: \setupexternalfigure
$\backslash$ typesetfile [...,\overset{1}{.}] [...,\overset{2}{.}] [...,\overset{3}{=},...] 1    NAME FILE                      OPT            OPT 2    FILE TEXT 3    inherits: \setupexternalfigure
$\backslash$ type [...,\overset{1}{=},...] <<\overset{2}{.}>> 1    inherits: \seteazatype 2    ANGLES
$\backslash$ TYPE [...,\overset{1}{=},...] {...} 1    inherits: \seteazatype 2    CONTENT

$\backslash TYPE [\dots, \dots, \dots] \langle \dots \rangle$ 1 inherits: $\backslash setezatype$ 2 ANGLES
$\backslash typ [\dots, \dots, \dots] \langle \dots \rangle$ 1 inherits: $\backslash setezatype$ 2 ANGLES
$\backslash uconvertnumber \{ \dots \} \{ \dots \}$ 1 inherits: $\backslash converttestenumar$ 2 NUMMER
$\backslash uedcatcodecommand \dots \{ \dots \}$ 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
$\backslash ultimasubpagina$
$\backslash undefinevalue \{ \dots \}$ * NAME
$\backslash undepthed \{ \dots \}$ * CONTENT
$\backslash underbartext \{ \dots \} \{ \dots \}$ 1 TEXT 2 TEXT
$\backslash underbrace \{ \dots \}$ * TEXT
$\backslash underbracetext \{ \dots \} \{ \dots \}$ 1 TEXT 2 TEXT
$\backslash underbracket \{ \dots \}$ * TEXT
$\backslash underbrackettext \{ \dots \} \{ \dots \}$ 1 TEXT 2 TEXT
$\backslash underleftarrow \{ \dots \}$ * TEXT
$\backslash underleftharpoonup \{ \dots \}$ * TEXT
$\backslash underleftharpoonup \{ \dots \}$ * TEXT
$\backslash underlefttrightharpoonup \{ \dots \}$ * TEXT
$\backslash underparent \{ \dots \}$ * TEXT

$\backslash$ underparenttext {...} {...} 1 TEXT 2 TEXT
$\backslash$ underrightarrow {...} * TEXT
$\backslash$ underrightharpoondown {...} * TEXT
$\backslash$ underrightharpoonup {...} * TEXT
$\backslash$ underset {...} {...} 1 TEXT 2 TEXT
$\backslash$ undertwoheadleftarrow {...} * TEXT
$\backslash$ undertwoheadrightarrow {...} * TEXT
$\backslash$ undeva {...} {...} [...] 1 TEXT 2 TEXT 3 REFERENCE
$\backslash$ undoassign [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
$\backslash$ unhhbox ... <sup>1</sup> \with {... <sup>2</sup> } 1 CSNAME NUMBER 2 BEFEHL
$\backslash$ unihex {...} * NUMMER
$\backslash$ uniqueMPgraphic {...} {..., <sup>2</sup> ... <sup>OPT</sup> ,...} 1 NAME 2 KEY = VALUE
$\backslash$ uniqueMPpagegraphic {...} {..., <sup>2</sup> ... <sup>OPT</sup> ,...} 1 NAME 2 KEY = VALUE
$\backslash$ UNIT {...} * CONTENT instances: unit
$\backslash$ unprotect ... \protect
$\backslash$ unprotected ... <sup>*</sup> \par * CONTENT
$\backslash$ unregisterhyphenationpattern [... <sup>1</sup> ] [... <sup>2</sup> ] 1 SPRACHE 2 TEXT

<code>\unspaceafter \<sup>1</sup> \{<sup>2</sup>...</code> 1 CSNAME 2 TEXT
<code>\unspaceargument ... \to \<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\unspaced {...}</code> * TEXT
<code>\unspacestring \<sup>1</sup> \to \<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\untexargument {...} \to \<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\untexcommand {...} \to \<sup>2</sup>...</code> 1 CSNAME 2 CSNAME
<code>\uppercased {...}</code> * TEXT
<code>\uppercasestring \<sup>1</sup> \to \<sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> * NAME
<code>\urmatoareasubpagina</code>
<code>\usealignparameter \*</code> * CSNAME
<code>\useblankparameter \*</code> * CSNAME

\usebodyfont [...] * inherits: \seteazafonttext
\usebodyfontparameter \*.. * CSNAME
\usebtxdataset [ <sup>1</sup> ...] [ <sup>2</sup> ] [ <sup>3</sup> ... <sub>OPT</sub> ...] 1 NAME OPT 2 FILE OPT 3 specification = NAME
\usebtxdefinitions [\*..] * FILE
\usecitation [...] * REFERENCE
\usecitation {\*..} * REFERENCE
\usecolors [...] * FILE
\usecomponent [\*..] * FILE
\usedummycolorparameter {\*..} * KEY
\usedummystyleandcolor {\ <sup>1</sup> ..} {\ <sup>2</sup> ..} 1 KEY 2 KEY
\usedummystyleparameter {\*..} * KEY
\useenvironment [\*..] * FILE
\useexternalrendering [ <sup>1</sup> ...] [ <sup>2</sup> ] [ <sup>3</sup> ] [ <sup>4</sup> ] 1 NAME 2 NAME 3 FILE 4 auto embed
\usefigurebase [\*..] * reset FILE
\usefile [ <sup>1</sup> ...] [ <sup>2</sup> ] [ <sup>3</sup> ... <sub>OPT</sub> ] 1 NAME OPT 2 FILE 3 TEXT
\usegridparameter \*.. * CSNAME
\useindentingparameter \*.. * CSNAME



<code>\useindentnextparameter \*...</code> <code>* CSNAME</code>
<code>\useinterlinespaceparameter \*...</code> <code>* CSNAME</code>
<code>\uselanguageparameter \*...</code> <code>* CSNAME</code>
<code>\uselua module [...]</code> <code>* FILE</code>
<code>\useMPenvironmentbuffer [...]</code> <code>* NAME</code>
<code>\useMPgraphic {...} {...,<sup>2</sup>...,...}</code> <code>1 NAME OPT</code> <code>2 KEY = VALUE</code>
<code>\useMPlibrary [...]</code> <code>* FILE</code>
<code>\useMPrun {...} {...}</code> <code>1 NAME</code> <code>2 NUMMER</code>
<code>\useMPvariables [...<sup>1</sup>] [...<sup>2</sup>,...]</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\usemathstyleparameter \*...</code> <code>* CSNAME</code>
<code>\useproduct [...]</code> <code>* FILE</code>
<code>\useprofileparameter \*...</code> <code>* CSNAME</code>
<code>\useproject [...]</code> <code>* FILE</code>
<code>\userreferenceparameter \*...</code> <code>* CSNAME</code>
<code>\userpagenumber</code>
<code>\usesetupsparameter \*...</code> <code>* CSNAME</code>
<code>\usestaticMPfigure [...,<sup>1</sup>...,...<sup>2</sup>] [...]</code> <code>1 inherits: \setupscale OPT</code> <code>2 NAME</code>
<code>\usesubpath [...,*,...]</code> <code>* PATH</code>

<pre> \usetexmodule [...] [...] [...] 1 m p s x t      OPT      OPT 2 FILE 3 KEY = VALUE </pre>
<pre> \usetypescript [...] [...] [...] 1 serif sans mono math handwriting calligraphy casual tot 2 NAME fallback implicit dtp simple 3 size nume </pre>
<pre> \usetypescriptfile [...] * reset FILE </pre>
<pre> \usezipfile [...] [...] 1 FILE      OPT 2 FILE </pre>
<pre> \utfchar {...} * NUMMER </pre>
<pre> \utflower {...} * TEXT </pre>
<pre> \utfupper {...} * TEXT </pre>
<pre> \utilityregisterlength </pre>
<pre> \VerboseNumber {...} * NUMMER </pre>
<pre> \valoareculoare {...} * COLOR </pre>
<pre> \vboxreference [...<sup>1</sup>,...] {..<sup>2</sup>.} 1 REFERENCE 2 CONTENT </pre>
<pre> \vec {..<sup>1</sup>.} * CHARACTER </pre>
<pre> \verbatim {...} * CONTENT </pre>
<pre> \verbatimstring {...} * CONTENT </pre>
<pre> \verbosenummer {...} * NUMMER </pre>
<pre> \versiune [...] * concept fisier temporar final NAME </pre>
<pre> \verticalgrowingbar [...<sup>1</sup>,...<sup>2</sup>,...] * inherits: \setuppositionbar </pre>
<pre> \verticalpositionbar [...<sup>1</sup>,...<sup>2</sup>,...] * inherits: \setuppositionbar </pre>

<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> <code>* DIMENSION</code>
<code>\viewerlayer [...]{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\vl [...]</code> <code>* NUMBER</code>
<code>\vphantom {...}</code> <code>* CONTENT</code>
<code>\vpos {...}{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\vsmash {...}</code> <code>* CONTENT</code>
<code>\vsmashbox ...</code> <code>* CSNAME NUMBER</code>
<code>\vsmashed {...}</code> <code>* CONTENT</code>
<code>\vspace [...]{...}</code> <code>1 NAME OPT OPT</code> <code>2 NAME</code>
<code>\vsparing [...]{...}</code> <code>* preferinta acesipagina max fortat enable dezactivat faraalb inapot overlay totdeauna weak strong implicit</code> <code>inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb inaltime</code> <code>adancime standard NUMBER*mic NUMBER*mediu NUMBER*mare NUMBER*linie NUMBER*jumatatelinie NUMBER*quarterline</code> <code>NUMBER*formula NUMBER*alb NUMBER*inaltime NUMBER*adancime category:NUMBER order:NUMBER penalty:NUMBER DIMENSION</code> <code>NAME</code>
<code>\WidthSpanningText {...}{...}{...}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>
<code>\wdofstring {...}</code> <code>* TEXT</code>
<code>\widthofstring {...}</code> <code>* TEXT</code>
<code>\widthspanningtext {...}{...}{...}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>

$\backslash$ withoutpt {...} *    DIMENSION
$\backslash$ words {...} *    TEXT
$\backslash$ wordtonumber {...} {...} 1    unu doi trei patru cinci 2    TEXT
$\backslash$ writedatatolist [...] [... <sup>2</sup> ... <sup>2</sup> ...] [... <sup>3</sup> ... <sup>3</sup> ...] 1    LISTE 2    inherits: \seteazalista 3    KEY = VALUE
$\backslash$ writestatus {...} {...} 1    TEXT 2    TEXT
$\backslash$ XETEX
$\backslash$ XeTeX
$\backslash$ xdefconvertedargument \ <sup>1</sup> ... {\ <sup>2</sup> ...} 1    CSNAME 2    TEXT
$\backslash$ xequal {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xhookleftarrow {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xhookrightarrow {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xLeftarrow {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xLeftrightarrow {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xleftarrow {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xleftharpoonup {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xleftharpoondown {...} {...} 1    TEXT    OPT    OPT 2    TEXT
$\backslash$ xleftharpoonup {...} {...} 1    TEXT    OPT    OPT 2    TEXT

`\xlefttrightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\xleftrightharpoons {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\xmapsto {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\xmladdindex {...}`

\* NODE

`\xmlafterdocumentsetup {...} {...} {...}`

1 NAME  
2 SETUP  
3 SETUP

`\xmlaftersetup {...} {...}`

1 SETUP  
2 SETUP

`\xmlall {...} {...}`

1 NODE  
2 LPATH

`\xmlappenddocumentsetup {...} {...}`

1 NAME  
2 SETUP

`\xmlappendsetup {...}`

\* SETUP

`\xmlapplyselectors {...}`

\* NODE

`\xmlatt {...} {...}`

1 NODE  
2 NAME

`\xmlattdef {...} {...} {...}`

1 NODE  
2 NAME  
3 TEXT

`\xmlattribute {...} {...} {...}`

1 NODE  
2 LPATH  
3 NAME

`\xmlattributedef {...} {...} {...} {...}`

1 NODE  
2 LPATH  
3 NAME  
4 TEXT

`\xmlbadinclusions {...}`

\* NODE

<pre> \xmlbeforedocumentsetup {...} {...} {...} 1  NAME 2  SETUP 3  SETUP </pre>
<pre> \xmlbeforesetup {...} {...} 1  SETUP 2  SETUP </pre>
<pre> \xmlchainatt {...} {...} 1  NODE 2  NAME </pre>
<pre> \xmlchainattdef {...} {...} {...} 1  NODE 2  NAME 3  TEXT </pre>
<pre> \xmlchecknamespace {...} {...} 1  NODE 2  NAME </pre>
<pre> \xmlcommand {...} {...} {...} 1  NODE 2  LPATH 3  XMLSETUP </pre>
<pre> \xmlconcat {...} {...} {...} 1  NODE 2  LPATH 3  TEXT </pre>
<pre> \xmlconcatrange {...} {...} {...} {...} {...} 1  NODE 2  LPATH 3  TEXT 4  FIRST 5  LAST </pre>
<pre> \xmlcontext {...} {...} 1  NODE 2  LPATH </pre>
<pre> \xmlcount {...} *  NODE </pre>
<pre> \xmldefaulttotext {...} *  NODE </pre>
<pre> \xmldirectives {...} *  NODE </pre>
<pre> \xmldirectivesafter {...} *  NODE </pre>
<pre> \xmldirectivesbefore {...} *  NODE </pre>
<pre> \xmldisplayverbatim {...} *  NODE </pre>

\xmldoif {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE

\xmldoifelse {...} {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE  
4 FALSE

\xmldoifelseempty {...} {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE  
4 FALSE

\xmldoifelseselfempty {...} {...} {...}

1 NODE  
2 TRUE  
3 FALSE

\xmldoifelsestext {...} {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE  
4 FALSE

\xmldoifelsevalue {...} {...} {...} {...}

1 CATEGORY  
2 NAME  
3 TRUE  
4 FALSE

\xmldoifnot {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE

\xmldoifnotselfempty {...} {...}

1 NODE  
2 TRUE

\xmldoifnottext {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE

\xmldoifselfempty {...} {...}

1 NODE  
2 TRUE

\xmldoiftext {...} {...} {...}

1 NODE  
2 LPATH  
3 TRUE

\xmlelement {...} {...}

1 NODE  
2 NUMMER

\xmlfilter {...} {...}

1 NODE  
2 LPATH

\xmlfirst {...} {...} 1    NODE 2    LPATH
\xmlflush {...} *    NODE
\xmlflushcontext {...} *    NODE
\xmlflushdocumentsetups {...} {...} 1    NAME 2    SETUP
\xmlflushlinewise {...} *    NODE
\xmlflushpure {...} *    NODE
\xmlflushspacewise {...} *    NODE
\xmlflushtext {...} *    NODE
\xmlinclude {...} {...} {...} 1    NODE 2    LPATH 3    NAME
\xmlinclusion {...} *    NODE
\xmlinclusions {...} *    NODE
\xmlinfo {...} *    NODE
\xmlinjector {...} *    NAME
\xmlinlineverbatim {...} *    NODE
\xmlinstalldirective {...} {...} 1    NAME 2    CSNAME
\xmllast {...} {...} 1    NODE 2    LPATH
\xmllastatt
\xmllastmatch



\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE
\xmlnonspace {...} {...} 1 NODE 2 LPATH
\xmlpath {...} * NODE
\xmlpos {...} * NODE
\xmlposition {...} {...} {...} 1 NODE 2 LPATH 3 NUMMER
\xmlprependdocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlprependsetup {...} * SETUP

<pre> \xmlprettyprint {...} {...} 1  NODE 2  NAME </pre>
<pre> \xmlprocessbuffer {...} {...} {...} 1  BUFFER 2  NAME 3  XMLSETUP </pre>
<pre> \xmlprocessdata {...} {...} {...} 1  NAME 2  TEXT 3  XMLSETUP </pre>
<pre> \xmlprocessfile {...} {...} {...} 1  NAME 2  FILE 3  XMLSETUP </pre>
<pre> \xmlpure {...} {...} 1  NODE 2  LPATH </pre>
<pre> \xmlraw {...} *  NODE </pre>
<pre> \xmlrefatt {...} {...} 1  NODE 2  NAME </pre>
<pre> \xmlregistereddokumentsetups {...} {...} 1  NAME 2  SETUP </pre>
<pre> \xmlregisteredsetups </pre>
<pre> \xmlregisterns {...} {...} 1  NAME 2  URL </pre>
<pre> \xmlremapname {...} {...} {...} {...} 1  NODE 2  LPATH 3  NAME 4  NAME </pre>
<pre> \xmlremapnamespace {...} {...} {...} 1  NODE 2  NAME 3  NAME </pre>
<pre> \xmlremoveddocumentsetup {...} {...} 1  NAME 2  SETUP </pre>
<pre> \xmlremovesetup {...} *  SETUP </pre>
<pre> \xmlresetdocumentsetups {...} *  NAME </pre>

<code>\xmlresetinjectors</code>
<code>\xmlresetsetups {...}</code> *    NAME
<code>\xmlsave {...} {...}</code> 1    NODE 2    FILE
<code>\xmlsetentity {...} {...}</code> 1    NAME 2    TEXT
<code>\xmlsetfunction {...} {...} {...}</code> 1    NODE 2    LPATH 3    LUAFUNCTION
<code>\xmlsetinjectors [...,*,...]</code> *    NAME
<code>\xmlsetsetup {...} {...} {...}</code> 1    NAME 2    LPATH 3    SETUP
<code>\xmlsetup {...} {...}</code> 1    NODE 2    SETUP
<code>\xmlshow {...}</code> *    NODE
<code>\xmlsnippet {...} {...}</code> 1    NODE 2    NUMMER
<code>\xmlstrip {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstripnolines {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstripped {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlstrippednolines {...} {...}</code> 1    NODE 2    LPATH
<code>\xmltag {...}</code> *    NODE
<code>\xmltexentity {...} {...}</code> 1    NAME 2    TEXT

$\backslash\text{xmltext} \{.^1.\} \{.^2.\}$ 1    NODE 2    LPATH
$\backslash\text{xmltobuffer} \{.^1.\} \{.^2.\} \{.^3.\}$ 1    NODE 2    LPATH 3    BUFFER
$\backslash\text{xmltobufferverbose} \{.^1.\} \{.^2.\} \{.^3.\}$ 1    NODE 2    LPATH 3    BUFFER
$\backslash\text{xmltofile} \{.^1.\} \{.^2.\} \{.^3.\}$ 1    NODE 2    LPATH 3    FILE
$\backslash\text{xmlvalue} \{.^1.\} \{.^2.\} \{.^3.\}$ 1    CATEGORY 2    NAME 3    TEXT
$\backslash\text{xmlverbatim} \{.^*.\}$ *    NODE
$\backslash\text{xRightarrow} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{xrel} \{.^1.\} \{.^2.\}$ 1    TEXT    OPT            OPT 2    TEXT
$\backslash\text{xrightarrow} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{xrightharpoondown} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{xrightharpoonup} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{xrightleftharpoons} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{xrightoverleftarrow} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT
$\backslash\text{xsplitstring} \backslash.^1. \{.^2.\}$ 1    CSNAME 2    TEXT
$\backslash\text{xtriplerel} \{.^1.\} \{.^2.\}$ 1    TEXT            OPT            OPT 2    TEXT

`\xtwoheadleftarrow {...} {...}`

1 TEXT

OPT OPT

2 TEXT

`\xtwoheadrightarrow {...} {...}`

1 TEXT

OPT OPT

2 TEXT

`\xypos {...}`

\* NAME

`\ZIDINSAPTAMANA {...}`

\* NUMMER

`\zidinsaptamana {...}`

\* NUMMER







**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**