



ConTExT

comenzile

RO

ConTeXt

comenzile

ro / română
25 octombrie 2016

<p><code>\AfterPar {...}</code></p> <p>* BEFEHL</p>
<p><code>\Alphabeticnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\AMSTEX</code></p>
<p><code>\AmSTeX</code></p>
<p><code>\And</code></p>
<p><code>\abjadnaivenumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\abjadnodotnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\abjadnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\abreviere [¹...] {²...} {³...}</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\activatespacehandler {...}</code></p> <p>* on dezactivat da fixat</p>
<p><code>\acute {...}</code></p> <p>* CHARACTER</p>
<p><code>\adaptcollector [¹...] [...,²...,...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupcollector</p>
<p><code>\adapteazaaspect [...,¹...] [...,²...,...]</code> <small>OPT</small></p> <p>1 NUMMER</p> <p>2 inaltime = max DIMENSION linii = NUMMER</p>
<p><code>\adaptfontfeature [¹...] [...,²...,...]</code></p> <p>1 NAME</p> <p>2 inherits: \definefontfeature</p>
<p><code>\adaptpapersize [...,¹...] [...,²...,...]</code> <small>OPT</small></p> <p>1 inherits: \seteazadimensiunihartie</p> <p>2 inherits: \seteazadimensiunihartie</p>

<p><code>\addfeature [...]</code></p> <p>* NAME</p>
<p><code>\addfeature {...}</code></p> <p>* NAME</p>
<p><code>\addtocommalist {...} \^{.2}.</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\addtoJSreamble {...} {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\addvalue {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\adubuffer [...]</code> OPT</p> <p>* BUFFER</p>
<p><code>\getBUFFER</code></p>
<p><code>\adumarcaje [...] [...²] [...³]</code> OPT OPT</p> <p>1 BESCHRIFTUNG</p> <p>2 pagina NAME</p> <p>3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\afiseazaaspect [...[*],...]</code> OPT</p> <p>* pt bp cm mm dd cc pc nd nc sp in</p>
<p><code>\afiseazaculoare [...]</code></p> <p>* COLOR</p>
<p><code>\afiseazafonttext [...[*],...]</code></p> <p>* inherits: \seteazafonttext</p>
<p><code>\afiseazagrid [...[*],...]</code> OPT</p> <p>* reset subsol sus niciunul tot linii incadrat nonumber dreapta stanga extern coloane</p>
<p><code>\afiseazagrupculoare [...¹] [...²,...]</code> OPT</p> <p>1 NAME</p> <p>2 orizontal vertical numar valoare nume</p>
<p><code>\afiseazamakeup [...]</code> OPT</p> <p>* marcaj tot boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math italic origin reset</p>

<p><code>\afiseazamediufonttext [...,*,...]</code></p> <p>* inherits: \seteazafonttext</p>
<p><code>\afiseazapaleta [...¹] [...²,...]</code> OPT</p> <p>1 NAME</p> <p>2 orizontal vertical numar valoare nume</p>
<p><code>\afiseazarama [...¹,...]² [...²,...]</code> OPT OPT</p> <p>1 sus antet text subsol subsol</p> <p>2 bordurastanga marginestanga text marginedreapta borduradreapta</p>
<p><code>\afiseazasetari [...,*,...]</code> OPT</p> <p>* pt bp cm mm dd cc pc nd nc sp in</p>
<p><code>\afiseazasetsimboluri [...]</code></p> <p>* NAME</p>
<p><code>\afiseazastruts</code></p>
<p><code>\afiseazatiparire [...¹,...]² [...²,...]³ [...³,...]</code> OPT OPT OPT</p> <p>1 inherits: \seteazadimensiunihartie</p> <p>2 inherits: \seteazadimensiunihartie</p> <p>3 inherits: \seteazaaspect</p>
<p><code>\aftersplitstring .¹. \at .². \to \³.</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring .¹. \at .². \to \³.</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aldin</code></p>
<p><code>\aldininclinat</code></p>
<p><code>\aldinitalic</code></p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...¹,...]{.².}</code></p> <p>1 stanga centru dreapta sus subsol linie l c r m t b g</p> <p>2 CONTENT</p>

`\alignedbox [...1,...] \...2 {...3}`

- 1 stanga dreapta sus subsol linie l c r m t b g
- 2 CSNAME
- 3 CONTENT

`\alignedline {...1} {...2} {...3}`

- 1 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge
spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta
- 2 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge
spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta
- 3 CONTENT

`\alignmentcharacter`

`\aliniatcentru {...}`

- * CONTENT

`\aliniatdreapta {...}`

- * CONTENT

`\aliniatstanga {...}`

- * CONTENT

`\allinputpaths`

`\alphabeticnumerals {...}`

- * NUMMER

`\alwayscitation [...1...1...]OPT [...2]`

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\alwayscitation [...1]OPT [...2]`

- 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\alwayscitation [...1...1...]OPT [...2...2...]OPT`

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

`\alwayscite [...1...2] [...]`

OPT

- 1 `referinta` = `REFERENCE`
 `alternativ` = `implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum`
 `authoryear`
 `inainte` = `BEFEHL`
 `dupa` = `BEFEHL`
 `stanga` = `BEFEHL`
 `dreapta` = `BEFEHL`
 `inherits:` `\setupbtx`
- 2 `REFERENCE`

`\alwayscite [...1] [...2]`

OPT

- 1 `implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear`
- 2 `REFERENCE`

`\alwayscite [...1...2] [...2...2]`

- 1 `referinta` = `REFERENCE`
 `alternativ` = `implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum`
 `authoryear`
 `inainte` = `BEFEHL`
 `dupa` = `BEFEHL`
 `stanga` = `BEFEHL`
 `dreapta` = `BEFEHL`
 `inherits:` `\setupbtx`
- 2 `KEY` = `VALUE`

`\ampersand`

`\anchor [...1] [...2...2] [...3...3] {...4}`

OPT

OPT

- 1 `NAME`
- 2 `inherits:` `\setuplayer`
- 3 `inherits:` `\setuplayerinherits:` `\seteazainconjurat`
- 4 `CONTENT`

`\appendetoks ... \to \...`

- 1 `BEFEHL`
- 2 `CSNAME`

`\appendgvalue {...1} {...2}`

- 1 `NAME`
- 2 `BEFEHL`

`\appendtocommalist {...1} \...`

- 1 `TEXT`
- 2 `CSNAME`

`\appendtoks ... \to \...`

- 1 `BEFEHL`
- 2 `CSNAME`

`\appendtoksonce ... \to \...`

- 1 `BEFEHL`
- 2 `CSNAME`

\appendvalue {...} {...}

- 1 NAME
- 2 BEFEHL

\apply {...} {...}

- 1 CONTENT
- 2 CONTENT

\applyalternativestyle {...}

- * NAME

\applyprocessor {...} {...}

- 1 NAME
- 2 CONTENT

\applytocharacters \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytofirstcharacter \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringchar \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringcharspaced \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringline \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringlinespaced \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringword \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringwordspaced \¹... {...}

- 1 CSNAME
- 2 TEXT

<p><code>\applytowords \...¹ {...²}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\arabicdecimals {...}</code></p> <p>* NUMMER</p>
<p><code>\arabicexnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\arabicnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\arg {...}</code></p> <p>* CONTENT</p>
<p><code>\asciistr {...}</code></p> <p>* CONTENT</p>
<p><code>\ascundeblocuri [...¹,...] [...²,...] <small>OPT</small></code></p> <p>1 NAME</p> <p>2 + -</p>
<p><code>\aside [...¹] {...²} <small>OPT</small></code></p> <p>1 SPRACHE</p> <p>2 CONTENT</p>
<p><code>\assignalfadimension {...¹} \...² {...³} {...⁴} {...⁵}</code></p> <p>1 mic mediu mare niciunul DIMENSION</p> <p>2 CSNAME</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 DIMENSION</p>
<p><code>\assigndimen \...¹ {...²}</code></p> <p>1 CSNAME</p> <p>2 DIMENSION</p>
<p><code>\assigndimension {...¹} \...² {...³} {...⁴} {...⁵}</code></p> <p>1 [-+]mic [-+]mediu [-+]mare niciunul DIMENSION</p> <p>2 CSNAME</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 DIMENSION</p>

<pre> \assignifempty \¹... {\²...} 1 CSNAME 2 BEFEHL </pre>
<pre> \assigntranslation [...,\¹...,...] \to \²... 1 SPRACHE = TEXT 2 CSNAME </pre>
<pre> \assignvalue {\¹...} \²... {\³...} {\⁴...} {\⁵...} 1 mic mediu mare TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL </pre>
<pre> \assignwidth {\¹...} \²... {\³...} {\⁴...} 1 ajustat broad DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION </pre>
<pre> \assumelongusagecs \¹... {\²...} 1 CSNAME 2 CONTENT </pre>
<pre> \astype {\[*]...} * CONTENT </pre>
<pre> \atleftmargin [...,\¹...,...] {\²...} ^{OPT} 1 referinta = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \atrightrightmargin [...,\¹...,...] {\²...} ^{OPT} 1 referinta = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \attachment [...\¹...] [...,\²...,...] ^{OPT} ^{OPT} 1 NAME 2 inherits: \setupattachment </pre>
<pre> \ATTACHMENT [...\¹...] [...,\²...,...] ^{OPT} ^{OPT} 1 NAME 2 inherits: \setupattachment instances: attachment </pre>

$\backslash\text{autocap} \{...\}$ * TEXT
$\backslash\text{autodirhbox} \overset{1}{...} \overset{2}{\{...\}}$ 1 TEXT 2 CONTENT
$\backslash\text{autodirvbox} \overset{1}{...} \overset{2}{\{...\}}$ 1 TEXT 2 CONTENT
$\backslash\text{autodirvtop} \overset{1}{...} \overset{2}{\{...\}}$ 1 TEXT 2 CONTENT
$\backslash\text{autoinsertnextspace}$
$\backslash\text{automathematics} \{...\}$ * CONTENT
$\backslash\text{autosetups} \{...,*,...\}$ * NAME
$\backslash\text{autostarttext} ... \backslash\text{autostoptext}$
$\backslash\text{availablehsize}$
$\backslash\text{averagecharwidth}$
$\backslash\text{BeforePar} \{...\}$ * BEFEHL
$\backslash\text{Big} ...$ * CHARACTER
$\backslash\text{Bigg} ...$ * CHARACTER
$\backslash\text{Biggl} ...$ * CHARACTER
$\backslash\text{Biggm} ...$ * CHARACTER
$\backslash\text{Biggr} ...$ * CHARACTER

<p><code>\Bigl ...</code></p> <p>* CHARACTER</p>
<p><code>\Bigr ...</code></p> <p>* CHARACTER</p>
<p><code>\backgroundimage {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 BEFEHL</p>
<p><code>\backgroundimagefill {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 BEFEHL</p>
<p><code>\backgroundline [...] {...}</code></p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\bar {...}</code></p> <p>* CHARACTER</p>
<p><code>\baraculoare [...,*,...]</code></p> <p>* COLOR</p>
<p><code>\barainteractiune [...]_{OPT} [...,...²...]_{OPT}</code></p> <p>1 NAME</p> <p>2 inherits: \seteazarainteractiune</p>
<p><code>\barasus {...}</code></p> <p>* CONTENT</p>
<p><code>\BAR {...}</code></p> <p>* CONTENT</p> <p>instances: barasus sublinie liniepeste understrike supralinie sublinii liniipeste understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar</p>

`\basegrid [...,*=...,...]`
OPT

* nx = NUMBER
ny = NUMBER
dx = NUMBER
dy = NUMBER
factor = NUMBER
scala = NUMBER
xstep = NUMBER
ystep = NUMBER
offset = DIMENSION
xoffset = DIMENSION
yoffset = DIMENSION
aliniere = centru
unitate = cm mm in pc pt bp
stil = STYLE BEFEHL
culoare = COLOR

`\baselinebottom`

`\baselineleftbox {...}`

* CONTENT

`\baselinemiddlebox {...}`

* CONTENT

`\baselinerrightbox {...}`

* CONTENT

`\bbox {...}`

* CONTENT

`\beforesplitstring 1.... \at 2.... \to 3....`

1 TEXT

2 TEXT

3 CSNAME

`\beforetestandsplitstring 1.... \at 2.... \to 3....`

1 TEXT

2 TEXT

3 CSNAME

`\beginBLOCK [...,*=...,...] ... \endBLOCK`
OPT

* + -

`\beginhbox ... \endhbox`

`\beginofshapebox ... \endofshapebox`

`\beginvbox ... \endvbox`

`\beginvtop ... \endvtop`

`\begstrut ... \endstrut`

<code>\bigbodyfont</code>
<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER
<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\binom {...}^{...}</code> 1 CONTENT 2 CONTENT
<code>\bitmapimage [...]{...}</code> 1 <ul style="list-style-type: none"> <code>culoare</code> = rgb cmyk gri <code>latime</code> = DIMENSION <code>inaltime</code> = DIMENSION <code>x</code> = NUMMER <code>y</code> = NUMMER 2 NUMMER
<code>\blanc [...]{...}</code> <small>OPT</small> * inherits: \vspacing
<code>\blap {...}</code> * CONTENT
<code>\bleed [...]{...}</code> <small>OPT</small> 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>

<code>\bleedwidth</code>
<code>\blockquote [...]¹ {...}²</code> <div> <div>OPT</div> <div> 1 SPRACHE 2 CONTENT </div> </div>
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>
<code>\booleanmodevalue {...}</code> * NAME
<code>\bottombox {...}</code> * CONTENT
<code>\bottomleftbox {...}</code> * CONTENT
<code>\bottomrightbox {...}</code> * CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...}¹ {...}²</code> <div> 1 NAME 2 NUMMER </div>
<code>\boxofsize \...¹ ...² ...³ {...}</code> <div> <div>OPT</div> <div> 1 CSNAME 2 DIMENSION 3 CONTENT </div> </div>
<code>\boxreference [...,¹...] \...² {...}³</code> <div> 1 REFERENCE 2 CSNAME 3 CONTENT </div>
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breve {...}</code> * CHARACTER

$\backslash\text{bTABLE} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTABLE}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTABLEbody} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTABLEbody}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTABLEfoot} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTABLEfoot}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTABLEhead} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTABLEhead}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTABLEnext} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTABLEnext}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTC} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTC}$ <small>OPT</small> * inherits: $\backslash\text{bTD}$
$\backslash\text{bTD} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTD}$ <small>OPT</small> * nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER actiune = REFERENCE inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTDs} [\dots] \dots \backslash\text{eTDs}$ * NAME
$\backslash\text{bTH} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTH}$ <small>OPT</small> * inherits: $\backslash\text{bTD}$
$\backslash\text{bTN} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTN}$ <small>OPT</small> * inherits: $\backslash\text{bTD}$
$\backslash\text{bTR} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTR}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bTRs} [\dots] \dots \backslash\text{eTRs}$ * NAME
$\backslash\text{bTX} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTX}$ <small>OPT</small> * inherits: $\backslash\text{bTD}$
$\backslash\text{bTY} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTY}$ <small>OPT</small> * inherits: $\backslash\text{setupTABLE}$
$\backslash\text{bthiddencitation} [\dots]$ * REFERENCE

* NAME

1 NAME

2 NAME

```

1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits:    \setupbtx

```

2 REFERENCE

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
```

2 REFERENCE

```

1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits:    \setupbtx

```

2 KEY = VALUE

```
* initials firstnames vons surnames juniors
```

```
* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
  luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
  yearfiled NAME
```

```
* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
yearfiled NAME
```

```
1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
```

2 TRUE

\btxdfcombiinlistelse {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdfotherwise {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfotherwisecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdfelsesameasprevious {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdfelsesameaspreviouschecked {...} {...} {...} {...}

- 1 totdeauna douafete
- 2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdfelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdfifnot {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE

\btxdfisameaspreviouscheckedelse {...} {...} {...} {...}

- 1 totdeauna douafete
- 2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 3 TRUE
- 4 FALSE

<p><code>\btxdfsameaspreviouselse {...} {...} {...}</code></p> <p>1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p> <p>2 TRUE</p> <p>3 FALSE</p>
<p><code>\btxdfuservariableelse {...} {...} {...}</code></p> <p>1 KEY</p> <p>2 TRUE</p> <p>3 FALSE</p>
<p><code>\btlexpandedjournal {...}</code></p> <p>* NAME</p>
<p><code>\btxdfield {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxdfieldname {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxdfieldtype {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfirstofrange {...}</code></p> <p>* volume pages</p>
<p><code>\btxflush {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxflushauthor [...¹...] {...²...}</code> OPT</p> <p>1 num normal normalshort inverted invertedshort</p> <p>2 autor editor</p>
<p><code>\btxflushauthorinverted {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorinvertedshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthorname {...}</code></p> <p>* autor editor</p>

<p><code>\btxflushauthornormal {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushauthornormalshort {...}</code></p> <p>* autor editor</p>
<p><code>\btxflushsuffix</code></p>
<p><code>\btxfoundname {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxfoundtype {...}</code></p> <p>* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME</p>
<p><code>\btxhybridcite [...¹..._{OPT}...] [...²...]</code></p> <p>1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite [...¹...] [...²...]</code> _{OPT}</p> <p>1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\btxhybridcite {...}</code></p> <p>* REFERENCE</p>
<p><code>\btxhybridcite [...¹..._{OPT}...] [...²..._{OPT}...]</code></p> <p>1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx</p> <p>2 KEY = VALUE</p>
<p><code>\btxlabellanguage</code></p>
<p><code>\btxlabeltext {...}</code></p> <p>* KEY</p>

\btxlistcitation [...¹...²...] [...]

OPT

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

\btxlistcitation [...¹] [...²]

OPT

- 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

\btxlistcitation [...¹...²...] [...²...¹...]

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

\btxloadjournalist [...]

- * FILE

\btxoneorrange {...¹} {...²} {...³}

- 1 volume pages
- 2 TRUE
- 3 FALSE

\btxremapauthor [...¹] [...²]

- 1 TEXT
- 2 TEXT

\btxsavejournalist [...]

- * FILE

\btxsetup {...}

- * NAME

\btxsingularorplural {...¹} {...²} {...³}

- 1 editor producer director
- 2 TRUE
- 3 FALSE

\btxsingularplural {...¹} {...²} {...³}

- 1 editor producer director
- 2 TRUE
- 3 FALSE

`\btxttextcitation [...,\u00b1...,\u00b2...]`
OPT

1 referinta = REFERENCE
 alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
 authoryear
 inainte = BEFEHL
 dupa = BEFEHL
 stanga = BEFEHL
 dreapta = BEFEHL
 inherits: \setupbtx
 2 REFERENCE

`\btxttextcitation [...]\u00b2...]`
OPT

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
 2 REFERENCE

`\btxttextcitation [...,\u00b1...,\u00b2...,\u00b3...]`

1 referinta = REFERENCE
 alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
 authoryear
 inainte = BEFEHL
 dupa = BEFEHL
 stanga = BEFEHL
 dreapta = BEFEHL
 inherits: \setupbtx
 2 KEY = VALUE

`\buildmathaccent {...}\u00b2...]`

1 CHARACTER
 2 CHARACTER

`\buildtextaccent {...}\u00b2...]`

1 CHARACTER
 2 CHARACTER

`\buildtextbottomcomma {...}`

* CHARACTER

`\buildtextbottomdot {...}`

* CHARACTER

`\buildtextcedilla {...}`

* CHARACTER

`\buildtextgrave {...}`

* CHARACTER

`\buildtextmacron {...}`

* CHARACTER

`\buildtextognek {...}`

* CHARACTER

<p><code>\butoaneinteractiune [...¹...¹...] [...²...]</code></p> <p><small>OPT</small></p> <p>1 inherits: \seteazabarainteractiune</p> <p>2 pagina subpagina REFERENCE</p>
<p><code>\buton [...¹...¹...] {...².} [...³.]</code></p> <p><small>OPT</small></p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\butonmeniu [...¹...¹...] {...².} {...³.}</code></p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p><code>\butonmeniu [...¹.] [...²...²...²...] {...³.} {...⁴.}</code></p> <p><small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \seteazameniuinteractiune</p> <p>3 TEXT</p> <p>4 REFERENCE</p>
<p><code>\BUTTON [...¹...¹...] {...².} [...³.]</code></p> <p><small>OPT</small></p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p> <p>instances: button</p>
<p><code>\Caps {...}</code></p> <p>* TEXT</p>
<p><code>\CONTEXT</code></p>
<p><code>\ConTeXt</code></p>
<p><code>\Context</code></p>
<p><code>\ConvertConstantAfter \... {...².} {...³.}</code></p> <p><small>1 CSNAME</small></p> <p><small>2 TEXT</small></p> <p><small>3 TEXT</small></p>
<p><code>\ConvertToConstant \... {...².} {...³.}</code></p> <p><small>1 CSNAME</small></p> <p><small>2 TEXT</small></p> <p><small>3 TEXT</small></p>
<p><code>\CUVANT {...}</code></p> <p>* TEXT</p>

$\backslash\text{CUVINTE} \{...\}$ * TEXT
$\backslash\text{Cuvant} \{...\}$ * TEXT
$\backslash\text{Cuvinte} \{...\}$ * TEXT
$\backslash\text{caligrafic}$
$\backslash\text{camel} \{...\}$ * TEXT
$\backslash\text{camp} [^{1..}] [^{2..}]$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 NAME 2 TEXT
$\backslash\text{capitol} [^{1..},^{2..}] \{...\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 REFERENCE 2 TEXT
$\backslash\text{catcodetablename}$
$\backslash\text{cbox} ^{1..} \{^{2..}\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
$\backslash\text{centeraligned} \{...\}$ * CONTENT
$\backslash\text{centerbox} ^{1..} \{^{2..}\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
$\backslash\text{centeredbox} ^{1..} \{^{2..}\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
$\backslash\text{centeredlastline}$
$\backslash\text{centerednextbox} ^{1..} \{^{2..}\}$ <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
$\backslash\text{centerline} \{...\}$ * CONTENT

$\backslash\text{centru } \dots$ * CHARACTER
$\backslash\text{cfrac } [\overset{1}{\dots}] \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$ <small>OPT</small> 1 l c r ll lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT
$\backslash\text{CHARACTERKERNING } [\overset{1}{\dots}] \{\overset{2}{\dots}\}$ <small>OPT</small> 1 NUMMER 2 TEXT
$\backslash\text{chardescription } \{\dots\}$ * NUMMER
$\backslash\text{charwidthlanguage}$
$\backslash\text{check } \{\dots\}$ * CHARACTER
$\backslash\text{checkcharacteralign } \{\dots\}$ * CONTENT
$\backslash\text{checkedchar } \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 NUMMER 2 CHARACTER
$\backslash\text{checkedfiller } \{\dots\}$ * sym simbol rigla latime spatiu NAME BEFEHL
$\backslash\text{checkedstrippedcsname } \backslash\dots$ * CSNAME
$\backslash\text{checkedstrippedcsname } \dots$ * TEXT
$\backslash\text{checkinjector } [\dots]$ * NAME
$\backslash\text{checknextindentation } [\dots]$ * da nu auto
$\backslash\text{checknextinjector } [\dots]$ * NAME
$\backslash\text{checkpage } [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots]$ <small>OPT</small> 1 NAME 2 inherits: \setuppagechecker

<code>\checkparameters [...]</code> * TEXT
<code>\checkpreviousinjector [...]</code> * NAME
<code>\checksoundtrack {...}</code> * NAME
<code>\checktwopassdata {...}</code> * NAME
<code>\checkvariables [...]¹ [...,...²...,...]</code> 1 NAME 2 set = BEFEHL reset = BEFEHL KEY = VALUE
<code>\chem {...}¹ {...}² {...}³</code> 1 TEXT 2 TEXT 3 TEXT
<code>\chemical [...]_{OPT} [...,...]² [...,...]_{OPT}³</code> 1 NAME 2 TEXT 3 TEXT
<code>\chemicalbottext {...}</code> * TEXT
<code>\chemicalmidtext {...}</code> * TEXT
<code>\chemicalsymbol [...]</code> * NAME
<code>\chemicaltext {...}</code> * TEXT
<code>\chemicaltoptext {...}</code> * TEXT
<code>\chineseallnumerals {...}</code> * NUMMER
<code>\chinesecapnumerals {...}</code> * NUMMER

<p><code>\chinesenumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\citat [¹...] {²...}</code></p> <p><small>OPT</small></p> <p>1 SPRACHE</p> <p>2 CONTENT</p>
<p><code>\citation [...,¹...,...] [²...]</code></p> <p><small>OPT</small></p> <p>1 referinta = REFERENCE</p> <p> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p> inainte = BEFEHL</p> <p> dupa = BEFEHL</p> <p> stanga = BEFEHL</p> <p> dreapta = BEFEHL</p> <p> inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\citation [¹...] [²...]</code></p> <p><small>OPT</small></p> <p>1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\citation {...}</code></p> <p>* REFERENCE</p>
<p><code>\citation [...,¹...,...] [...,²...,...]</code></p> <p>1 referinta = REFERENCE</p> <p> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p> inainte = BEFEHL</p> <p> dupa = BEFEHL</p> <p> stanga = BEFEHL</p> <p> dreapta = BEFEHL</p> <p> inherits: \setupbtx</p> <p>2 KEY = VALUE</p>
<p><code>\cite [...,¹...,...] [²...]</code></p> <p><small>OPT</small></p> <p>1 referinta = REFERENCE</p> <p> alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p> inainte = BEFEHL</p> <p> dupa = BEFEHL</p> <p> stanga = BEFEHL</p> <p> dreapta = BEFEHL</p> <p> inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\cite [¹...] [²...]</code></p> <p><small>OPT</small></p> <p>1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear</p> <p>2 REFERENCE</p>
<p><code>\cite {...}</code></p> <p>* REFERENCE</p>

`\cite [...,\sup{1}...,...] [...,\sup{2}...,...]`

```
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                   authoryear
   inainte     = BEFEHL
   dupa        = BEFEHL
   stanga      = BEFEHL
   dreapta     = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

`\clap {...}`

* CONTENT

`\classfont {\sup{1}.} {\sup{2}.}`

1 NAME

2 FONT

`\cldcommand {...}`

* BEFEHL

`\cldcontext {...}`

* BEFEHL

`\cldloadfile {...}`

* FILE

`\cldprocessfile {...}`

* FILE

`\cleftarrow {\sup{1}.} {\sup{2}.}`
 OPT OPT

1 TEXT

2 TEXT

`\clip [...,\sup{1}...,...] {\sup{2}.}`
 OPT

1 inherits: \seteazaclipping

2 CONTENT

`\cloneazacamp [\sup{1}.] [\sup{2}.] [\sup{3}.] [...,\sup{4}.,...]`

1 NAME

2 NAME

3 NAME

4 NAME

`\collect {...}`

* CONTENT

<p><code>\collectedtext</code> [\dots,\dots¹\dots,\dots] [\dots,\dots²\dots,\dots] {...} {...}</p> <p style="text-align: center;">OPT OPT</p> <p>1 inherits: \setupcollector</p> <p>2 stil = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\collectexpanded</code> {...}</p> <p>* CONTENT</p>
<p><code>\coloana</code> [\dots,\dots[*]\dots]</p> <p style="text-align: center;">OPT</p> <p>* inherits: \columnbreak</p>
<p><code>\colorcomponents</code> {...}</p> <p>* COLOR</p>
<p><code>\colored</code> [\dots,\dots¹\dots,\dots] {...²...}</p> <p>1 inherits: \definesteculoare</p> <p>2 CONTENT</p>
<p><code>\colored</code> [\dots¹] {...²...}</p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\coloronly</code> [\dots¹] {...²...}</p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\columnbreak</code> [\dots,\dots[*]\dots]</p> <p style="text-align: center;">OPT</p> <p>* da nu preferinta local fortat primul ultim NUMMER NAME</p>
<p><code>\combinepages</code> [\dots¹] [\dots,\dots²\dots,\dots]</p> <p style="text-align: center;">OPT</p> <p>1 FILE</p> <p>2 alternativ = a b c orizontal vertical n = NUMMER nx = NUMMER ny = NUMMER start = NUMMER stop = NUMMER distanta = DIMENSION sus = BEFEHL jos = BEFEHL stanga = BEFEHL dreapta = BEFEHL inainte = BEFEHL dupa = BEFEHL intre = BEFEHL frame = on dezactivat fundal = primplan culoare NAME culoarefundal = COLOR</p>

$\backslash\text{comentariu}$ $[\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots},\dots] \{\overset{3}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 inherits: \seteazacomentariu 3 TEXT
$\backslash\text{COMENTARIU}$ $[\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots},\dots] \{\overset{3}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 inherits: \seteazacomentariu 3 TEXT instances: comentariu
$\backslash\text{commalistelement}$
$\backslash\text{commalistsentence}$ $[\dots,\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots]$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{commalistsize}$
$\backslash\text{comparagrupculoare}$ $[\dots]$ * NAME
$\backslash\text{comparapaleta}$ $[\dots]$ * NAME
$\backslash\text{comparedimension}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 DIMENSION 2 DIMENSION
$\backslash\text{comparedimensioneps}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 DIMENSION 2 DIMENSION
$\backslash\text{completeazanumarpagina}$
$\backslash\text{completebtxrendering}$ $[\overset{1}{\dots}] [\dots,\dots,\overset{2}{\dots},\dots]$ <small>OPT OPT</small> 1 NAME 2 inherits: \setupbtxrendering
$\backslash\text{completCOMBINEDLIST}$ $[\dots,\dots,\overset{*}{\dots},\dots]$ <small>OPT</small> * inherits: \seteazalista instances: cuprins
$\backslash\text{completecontent}$ $[\dots,\dots,\overset{*}{\dots},\dots]$ <small>OPT</small> * inherits: \seteazalista

\completeindex [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazaregistru
\completelist [...] ¹ [...,.. ² ...,...] <small>OPT</small> 1 LISTE 2 inherits: \seteazalista
\completelistofabbreviations [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazasinonime
\completelistofFLOATS [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazalista
\completelistoflogos [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazasortare
\completelistofpublications [...] ¹ [...,.. ² ...,...] <small>OPT OPT</small> 1 NAME 2 inherits: \setupbt rendering
\completelistofsorts [...] ¹ [...,.. ² ...,...] <small>OPT</small> 1 SINGULAR 2 inherits: \seteazasortare
\completelistofSORTS [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazasortare instances: logos
\completelistofsynonyms [...] ¹ [...,.. ² ...,...] <small>OPT</small> 1 SINGULAR 2 inherits: \seteazasinonime
\completelistofSYNONYMS [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazasinonime instances: abbrevieri
\completere register [...] ¹ [...,.. ² ...,...] <small>OPT</small> 1 NAME 2 inherits: \seteazaregistru
\completeregISTRU [...,.. [*] ...,...] <small>OPT</small> * inherits: \seteazaregistru instances: index
\complexorsimple *.. * CSNAME

\complexorsimpleempty *.. * CSNAME
\complexorsimpleempty {...} * TEXT CSNAME
\complexorsimple {...} * TEXT CSNAME
\componenta [...] * FILE
\componenta ... * FILE
\composedcollector {...} * NAME
\composedlayer {...} * NAME
\compresult
\constantdimen *.. * CSNAME
\constantdimenargument *.. * CSNAME
\constantemptyargument *.. * CSNAME
\constantnumber *.. * CSNAME
\constantnumberargument *.. * CSNAME
\contentreference [..., ¹ ...] [..., ² _{OPT} ...,...] {... ³ } 1 REFERENCE 2 inherits: \setezainconjurat 3 CONTENT
\continuednumber {...} * NUMMER
\continueifinputfile {...} * FILE

$\backslash\text{convertargument}$ $\overset{1}{...}$ $\backslash\text{to}$ $\overset{2}{...}$ 1 TEXT 2 CSNAME
$\backslash\text{convertcommand}$ $\backslash\overset{1}{...}$ $\backslash\text{to}$ $\overset{2}{...}$ 1 CSNAME 2 CSNAME
$\backslash\text{convertedcounter}$ $[\overset{1}{...}]$ $[\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupcounter}$
$\backslash\text{convertedddimen}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
$\backslash\text{convertedsubcounter}$ $[\overset{1}{...}]$ $[\overset{2}{...}]$ $[\dots,\overset{3}{...},\dots]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot 3 inherits: $\backslash\text{setupcounter}$
$\backslash\text{converttestenunar}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ 1 gol implicit niciunul luna month:mnem character Carac ^{ter} caractere Caractere a A Numere cuv ^{ant} words Cuv ^{ant} Cuvinte n N numereromane Numereromane i I r R KR RK grec Grec g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirclemn ^{umerals} kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set ₀ set ₁ set ₂ set ₃ continued NAME 2 NUMMER
$\backslash\text{convertmonth}$ $\{\overset{*}{...}\}$ * NUMMER
$\backslash\text{convertvalue}$ $\overset{1}{...}$ $\backslash\text{to}$ $\overset{2}{...}$ 1 NAME 2 CSNAME
$\backslash\text{convertvboxtohbox}$
$\backslash\text{copiazacamp}$ $[\overset{1}{...}]$ $[\overset{2}{...}]$ 1 NAME 2 NAME
$\backslash\text{copybtxlabeltext}$ $[\overset{1}{...}]$ $[\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyheadtext}$ $[\overset{1}{...}]$ $[\dots,\overset{2}{...},\dots]$ <small>OPT</small> 1 SPRACHE 2 KEY = KEY

$\backslash\text{copylabeltext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyETICHETAtext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY instances: antet eticheta mathlabel taglabel unitate operator prefix suffix btxlabel
$\backslash\text{copymathlabeltext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyoperatortext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{coppages}$ [¹ ...] [² ...,...] <small>OPT</small> <small>OPT</small> 1 FILE 2 marcaje = on dezactivat offset = DIMENSION n = NUMMER 3 inherits: \setupexternalfigure
$\backslash\text{copyparameters}$ [¹ ...] [² ...] [³ ...,...] 1 TEXT 2 TEXT 3 KEY
$\backslash\text{copyposition}$ { ¹ ...} { ² ...} 1 NAME 2 NAME
$\backslash\text{copyprefixtext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{copyunittext}$ [¹ ...] [² ...,...] <small>OPT</small> 1 SPRACHE 2 KEY = KEY
$\backslash\text{corecteazaspatualb}$ {.*} * CONTENT

$\backslash\text{countersubs}$ [¹ ...] [² ...] <small>OPT</small> 1 NAME 2 NUMMER
$\backslash\text{counttoken}$ ¹ ... \in ² ... \to \^ ³ ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ ¹ ... \to \^ ² ... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ {...} * CONTENT
$\backslash\text{crampedclap}$ {...} * CONTENT
$\backslash\text{crampedllap}$ {...} * CONTENT
$\backslash\text{crampedrlap}$ {...} * CONTENT
$\backslash\text{crightarrow}$ { ¹ ...} { ² ...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{crightoverleftarrow}$ { ¹ ...} { ² ...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{ctop}$ ¹ ... { ² ...} <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ctxcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectcommand}$ {...} * BEFEHL
$\backslash\text{ctxdirectlua}$ {...} * BEFEHL
$\backslash\text{ctxfunction}$ {...} * NAME

<code>\CTXFUNCTIONDEFINITION</code>
<code>\CTXFUNCTION</code>
<code>\ctxlatecommand {...}</code> * BEFEHL
<code>\ctxlatelua {...}</code> * BEFEHL
<code>\ctxloadluafile {...}</code> * FILE
<code>\ctxlua {...}</code> * BEFEHL
<code>\ctxluabuffer [...]</code> <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div> * BUFFER
<code>\ctxluacode {...}</code> * BEFEHL
<code>\ctxreport {...}</code> * BEFEHL
<code>\ctxsprint {...}</code> * BEFEHL
<code>\culoare [...] {...}</code> 1 COLOR 2 CONTENT
<code>\culoaregri [...] {...}</code> 1 COLOR 2 CONTENT
<code>\currentassignmentlistkey</code>
<code>\currentassignmentlistvalue</code>
<code>\currentbtxuservariable {...}</code> * KEY
<code>\currentcommalistitem</code>
<code>\currentcomponent</code>
<code>\currentenvironment</code>

<code>\currentfeaturetest</code>
<code>\currentinterface</code>
$\backslash currentETICHETA \left[\dots, \overset{1}{\dots} \right] \left\{ \overset{2}{\dots} \right\}$ <div> <div>1</div> <div>REFERENCE</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
<code>\currentlanguage</code>
<code>\currentlistentrydestinationattribute</code>
<code>\currentlistentrylimitedtext {...}</code> * TEXT
<code>\currentlistentrynumber</code>
<code>\currentlistentrypagenumber</code>
<code>\currentlistentryreferenceattribute {...}</code> * numar text numarpagina tot
<code>\currentlistentrytitle</code>
<code>\currentlistentrytitlerendered</code>
<code>\currentlistsymbol</code>
<code>\currentmainlanguage</code>
<code>\currentmessagetext</code>
<code>\currentmoduleparameter {...}</code> * KEY
<code>\currentoutputstream</code>
<code>\currentproduct</code>
<code>\currentproject</code>
<code>\currentregime</code>
<code>\currentregisterpageuserdata {...}</code> * KEY
<code>\currentresponses</code>
<code>\currenttime \left[\dots, \overset{*}{\dots} \right]</code> <div> <div>*</div> <div>h m TEXT</div> </div>

<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\cuvant {...}</code> <code>* TEXT</code>
<code>\cuvantdreapta [...]¹ {...}²</code> <code> OPT</code> <code>1 dreapta DIMENSION</code> <code>2 CONTENT</code>
<code>\cuvantmarginal [...,¹...]² {...}</code> <code> OPT</code> <code>1 referinta = REFERENCE</code> <code> inherits: \setupmargindata</code> <code>2 CONTENT</code>
<code>\d {...}</code> <code>* CHARACTER</code>
<code>\data [...,¹...]² [...,²...]</code> <code> OPT OPT</code> <code>1 d = NUMBER</code> <code> m = NUMBER</code> <code> y = NUMBER</code> <code>2 inherits: \datacurenta</code>
<code>\datacurenta [...,[*]...]</code> <code> OPT</code> <code>* an luna zi zisaptamana y yy Y m mm M d dd D w W spatiu _ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT</code> <code> referinta day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</code>
<code>\datasetvariable {...}¹ {...}² {...}³</code> <code>1 NAME</code> <code>2 NAME NUMBER</code> <code>3 KEY realpage</code>
<code>\dayoftheweek {...}¹ {...}² {...}³</code> <code>1 NUMBER</code> <code>2 NUMBER</code> <code>3 NUMBER</code>
<code>\dayspermonth {...}¹ {...}²</code> <code>1 NUMBER</code> <code>2 NUMBER</code>
<code>\dbinom {...}¹ {...}²</code> <code>1 CONTENT</code> <code>2 CONTENT</code>

<code>\ddot {...}</code> * CHARACTER
<code>\decrement \...</code> * CSNAME
<code>\decrementcounter [...]¹ [...]²</code> <div> <div>1 NAME</div> <div>2 NUMMER</div> <div>OPT</div> </div>
<code>\decrementedcounter [...]</code> * NAME
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code> * NAME
<code>\decrement cd:parentheses-1</code> * CSNAME NUMBER
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \...¹ \...² {...}³</code> <div> <div>1 CSNAME</div> <div>2 CHARACTER NUMBER</div> <div>3 BEFEHL</div> </div>
<code>\defconvertedargument \...¹ {...}²</code> <div> <div>1 CSNAME</div> <div>2 TEXT</div> </div>
<code>\defconvertedcommand \...¹ \...²</code> <div> <div>1 CSNAME</div> <div>2 CSNAME</div> </div>
<code>\defconvertedvalue \...¹ {...}²</code> <div> <div>1 CSNAME</div> <div>2 NAME</div> </div>

`\defineactivecharacter 1... {2...}`

- 1 CHARACTER
- 2 BEFEHL

`\definealternativestyle [...,1...] [2...] [3...]`

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

`\defineanchor [1...] [2...] [...,3...OPT,...] [...,4...OPT,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupplayer
- 4 inherits: \setupplayerinherits: \seteazainconjurat

`\defineattachment [1...] [2...OPT] [...,3...OPT,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupattachment

`\defineattribute [1...] [...,2...OPT,...]`

- 1 NAME
- 2 local global public private

`\definebackground [1...] [2...OPT] [...,3...OPT,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \seteazafundal

`\definebar [1...] [2...OPT] [...,3...OPT,...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupbar

`\definebodyfontswitch [1...] [...,2...]`

- 1 NAME
- 2 inherits: \seteazafonttext

`\definebreakpoint [1...] [2...] [...,3...OPT,...]`

- 1 NAME
- 2 CHARACTER
- 3 type = 1 2 3 4 5
nstanga = NUMMER
ndreapta = NUMMER
stanga = BEFEHL
mijloc = BEFEHL
dreapta = BEFEHL
range = da nu
language = SPRACHE

<pre> \definebreakpoints [...] * NAME </pre>
<pre> \definebtx [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtx </pre>
<pre> \definebtxdataset [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxdataset </pre>
<pre> \definebtxregister [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxregister </pre>
<pre> \definebtxrendering [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxrendering </pre>
<pre> \definebutton [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbutton </pre>
<pre> \definecapitals [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazamajuscule </pre>
<pre> \definecharacterkerning [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupcharacterkerning </pre>
<pre> \definecharacterspacing [...] * NAME </pre>
<pre> \definechemical [...] {...} 1 NAME 2 CONTENT </pre>

```
\definechemicals [1...] [2...] [3...OPT...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupchemical

```
\definechemicalsymbol [1...] [2...]
```

- 1 NAME
- 2 TEXT

```
\definecollector [1...] [2...] [3...OPT...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupcollector

```
\definecolumnbreak [1...] [2...,...]
```

- 1 NAME
- 2 da nu preferinta local fortat primul ultim NUMBER

```
\definecombination [1...] [2...] [3...OPT...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupcombination

```
\definecomment [1...] [2...] [3...OPT...OPT...]
```

- 1 NAME
- 2 NAME
- 3 inherits: \seteazacommentariu

```
\definecomplexorsimple \*..
```

- * CSNAME

```
\definecomplexorsimpleempty \*..
```

- * CSNAME

```
\definecomplexorsimpleempty {*..}
```

- * TEXT CSNAME

```
\definecomplexorsimple {*..}
```

- * TEXT CSNAME

```
\defineconversionset [1...] [2...,...]OPT [3...]
```

- 1 NAME SECTIONBLOCK:NAME
- 2 NAME PROCESSOR->NAME
- 3 NAME PROCESSOR->NAME

`\definecounter` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupcounter

`\definedataset` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupdataset

`\definedelimitedtext` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupdelimitedtext

`\definedfont` [^{*}...]_{OPT}

- * FONT

`\defineeffect` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupeffect

`\defineexpandable` [¹...] [²..._{OPT}...] {³...}

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

`\defineexternalfigure` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupexternalfigure

`\definefallbackfamily` [¹...] [²...] [³...] [⁴..._{OPT}...]

- 1 NAME
- 2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica manual caligrafic math
- 3 FONT
- 4
 - rsize = NUMBER
 - designsize = implicit auto
 - goodies = FILE
 - range = NUMBER NAME
 - offset = NUMBER NAME
 - check = da nu
 - fortat = da nu
 - features = NAME
 - tf = TEXT
 - bf = TEXT
 - it = TEXT
 - sl = TEXT
 - bi = TEXT
 - bs = TEXT
 - sc = TEXT

`\definefallbackfamily` [¹...] [²...] [³...] [⁴...,...]
OPT

- 1 NAME
- 2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica caligrafic math
- 3 FONT
- 4 NAME

`\definefielddbody` [¹...] [²...] [³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfielddbody

`\definefielddbodyset` [¹...] [²...,...]

- 1 NAME
- 2 NAME

`\definefieldcategory` [¹...] [²...] [³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldcategory

`\definefileconstant` {¹...} {²...}

- 1 NAME
- 2 NAME

`\definefilefallback` [¹...] [²...,...]

- 1 NAME
- 2 FILE

`\definefilesynonym` [¹...] [²...]

- 1 NAME
- 2 FILE

`\definefiller` [¹...] [²...] [³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfiller

`\definefirstline` [¹...] [²...] [³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfirstline

`\definefittingpage` [¹...] [²...] [³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfittingpage

```
\definefontalternative [...]
```

```
* NAME
```

```
\definefontfallback [...]1 [...]2 [...,3...] [...,4...]
OPT
```

```
1 NAME
```

```
2 FONT NAME
```

```
3 NAME NUMBER
```

```
4 rscale = NUMBER
fortat = da nu
check = da nu
offset = NUMMER NAME
```

```
\definefontfamily [...]1 [...]2 [...]3 [...,4...]
OPT
```

```
1 NAME
```

```
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismanual caligrafic math
matematica
```

```
3 FONT
```

```
4 rscale = NUMBER
designsize = implicit auto
goodies = FILE
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT
```

```
\definefontfamilypreset [...]1 [...,2...]

```

```
1 NAME
```

```
2 inherits: \definefontfamily
```

```
\definefontfamilypreset [...]1 [...]2
```

```
1 NAME
```

```
2 NAME
```

```
\definefontfamily [...]1 [...]2 [...]3 [...,4...]
OPT
```

```
1 NAME
```

```
2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismanual caligrafic math
matematica
```

```
3 FONT
```

```
4 NAME
```

```
\definefontfeature [...]1 [...]2 [...,...]3...,...
```

OPT

1 NAME

2 NAME

3 language = NAME
script = NAME auto
mode = node base auto niciunul
liga = da nu
kern = da nu
extrakerns = da nu
tlig = da nu
trep = da nu
missing = da nu
dummies = da nu
analyze = da nu
unicoding = da nu
expansiune = NAME
protrusion = NAME
nostackmath = da nu
realdimensions = da nu
itlc = da nu
textitalics = da nu
mathitalics = da nu
slant = NUMMER
extend = NUMMER
dimensions = NUMMER
boundingbox = da nu
compose = da nu
char-ligatures = da nu
compat-ligatures = da nu
goodies = FILE
extrafeatures = da nu
featureset = NAME
colorscheme = NAME
postprocessor = NAME
mathdimensions = NAME
keepligatures = da nu auto
devanagari = da nu
features = da nu
tcom = da nu
anum = da nu
mathsize = da nu
decomposehangul = da nu
mathalternatives = da nu
mathgaps = da nu
checkmarks = da nu
NAME = da nu
mathnolimitsmode = NUMMER

```
\definefontfile [...]1 [...]2 [...,...]3...,...
```

OPT

1 NAME

2 FILE

3 features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicit

```
\definefontsize [...]
```

* NAME

```
\definefontsolution [...]1 [...]2 [...,...]3...,...
```

OPT

OPT

1 NAME

2 NAME

3 inherits: \setupfontsolution

`\defineformula` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformula

`\defineformulaalternative` [¹...] [²...] [³...]

- 1 NAME
- 2 CSNAME
- 3 CSNAME

`\defineformulaframed` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformulaframed

`\defineframedcontent` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupframedcontent

`\definefrozenfont` [¹...] [²...]

- 1 NAME
- 2 FONT

`\defineglobalcolor` [¹...] [²...₂...]

- 1 NAME
- 2 inherits: \definesteculoare

`\defineglobalcolor` [¹...] [²...]

- 1 NAME
- 2 COLOR

`\definegraphictypesynonym` [¹...] [²...]

- 1 NAME
- 2 NAME

`\definegridsnapping` [¹...] [²...,...]

- 1 NAME
- 2 local global noheight nodepth box max min niciunul linie jumatatelinie primul ultim inaltimeminima maxheight mindepth maxdepth sus subsol strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER

`\defineheadalternative` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupheadalternative

```
1  NAME
2  NAME
3  inherits: \setuphelp
```

```
1  NAME
2  NAME
3  inherits: \setuphigh
```

```
1  NAME
2  NAME
3  inherits: \setuphighlight
```

1	NAME
2	NAME
3	DIMENSION

```

1  NAME
2  characters      = TEXT
   hyphens        = da tot TEXT
   joiners        = da tot TEXT
   rightwords     = NUMBER
   hyphenmin      = NUMBER
   lefthyphenmin  = NUMBER
   righthyphenmin = NUMBER
   lefthyphenchar = NUMBER
   righthyphenchar = NUMBER
   alternativ      = original tex hyphenate expanded traditional niciunul
   borduradreapta = tex
   rightchars     = cuvant NUMBER

```

```
1  NAME
2  NAME
3  inherits: \setupindentedtext
```

```
1  NAME
2  [--]mic [--]mediu [--]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle
   DIMENSION
```

```
1  NAME
2  NAME
3  inherits: \setupinitial
```

```
1  NAME
2  NAME
3  inherits: \setupinsection
```

```
1  NAME
2  NAME
3  inherits: \seteazainteractiunea
```

```
1  NAME
2  NAME
3  inherits: \seteazabarainteractiune
```

1	NAME
2	NAME

1	NAME
2	NAME

1	NAME
2	NAME

```
1  NAME
2  NAME
3  inherits: \seteazaspatiuinterliniar
```

```

1  NAME
2  COLOR NUMBER
3  a  =  NUMBER
    t  =  NUMBER

```

```
1  NAME
2  NAME
3  inherits: \setupitemgroup
```

```
1  NAME
2  NAME
3  inherits: \seteazaelemente
```

<pre> \definelabelclass [...] [¹...] [²...] OPT 1 NAME 2 NUMMER </pre>
<pre> \definelayer [...] [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuplayer </pre>
<pre> \definelayerpreset [...] [...,¹...,...] 1 NAME 2 inherits: \setuplayer </pre>
<pre> \definelayerpreset [¹...] [²...] 1 NAME 2 NAME </pre>
<pre> \definelayout [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazaaspect </pre>
<pre> \definelinefiller [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuplinefiller </pre>
<pre> \definelinenote [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuplinenote </pre>
<pre> \definelinenumbering [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazanumerotarelinii </pre>
<pre> \definelines [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazalinii </pre>
<pre> \definelistalternative [¹...] [²...] [...,³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuplistalternative </pre>

`\definelistextra` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistextra

`\definelow` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplow

`\definelowhigh` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowhigh

`\definelowmidhigh` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowmidhigh

`\defineMPinstance` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupMPinstance

`\definemarginblock` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmarginblock

`\definemargindata` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmargindata

`\definemarker` [...]

- * NAME

`\definemathaccent` ...¹ ...²

- 1 NAME
- 2 CHARACTER

`\definemathalignment` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathalignment

`\definemathcases` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathcases

`\definemathcommand` [¹...] [²...] [³...] {⁴...}

- 1 NAME
- 2 ord op bin rel open close punct alpha intern nothing limop noloop box
- 3 unu doi
- 4 BEFEHL \...##1 \...##1##2

`\definemathdoubleextensible` [¹...] [²...] [³...] [⁴...]

- 1 ambele vfenced
- 2 NAME
- 3 NUMMER
- 4 NUMMER

`\definematematics` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathematics

`\definemathextensible` [¹...] [²...] [³...]

- 1 reverse matematica text chemistry
- 2 NAME
- 3 NUMMER

`\definemathfence` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathfence

`\definemathfraction` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathfraction

`\definemathframed` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathframed

`\definemathmatrix` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathmatrix

```
\definemathornament [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupmathornament
```

```
\definemathoverextensible [...] [...]
1 sus vfenced
2 NAME
3 NUMMER
```

```
\definemathovertextextensible [...] [...]
1 bothtext
2 NAME
3 NUMMER
```

```
\definemathradical [...] [...]
1 NAME
2 NAME
3 inherits: \setupmathradical
```

```
\definemathstackers [...] [...]
1 NAME
2 NAME
3 inherits: \setupmathstackers
```

```
\definemathstyle [...] [...]
1 NAME
2 display text script scriptscript cramped uncramped normal impachetat mic mare
```

```
\definemathtriplet [...] [...]
1 NAME
2 NAME
3 TEXT
```

```
\definemathunderextensible [...] [...]
1 subsol vfenced
2 NAME
3 NUMMER
```

```
\definemathundertextextensible [...] [...]
1 bothtext
2 NAME
3 NUMMER
```

```
\definemathunstacked [1...] [2...] [3...]
                        OPT
1 larg
2 NAME
3 NUMMER
```

```
\definemeasure [1...] [2...]
1 NAME
2 DIMENSION
```

```
\definemessageconstant {.*}
* NAME
```

```
\definemixedcolumns [1...] [2...] [3...,...,...]
                        OPT      OPT
1 NAME
2 NAME
3 inherits: \setupmixedcolumns
```

```
\definemode [...,1...] [2...]
                        OPT
1 NAME
2 da nu mentine
```

```
\definemultitonecolor [1...] [...,2...,...] [...,3...,...] [...,4...,...]
                                                OPT
1 NAME
2 COLOR = NUMMER
3 inherits: \definesteculoare
4 inherits: \definespotcolor
```

```
\definenamecolor [1...] [...,2...,...]
1 NAME
2 inherits: \definesteculoare
```

```
\definenamecolor [1...] [2...]
1 NAME
2 COLOR
```

```
\definenamespace [1...] [...,2...,...]
1 NAME
2 nume = TEXT
  parent = TEXT
  stil = da nu
  comanda = da nu lista
  setup = da nu lista
  set = da nu lista
  frame = da nu
```

```
\definenarrower [1...] [2...] [3...,...,...]
                        OPT      OPT
1 NAME
2 NAME
3 inherits: \seteazaingust
```


<pre> \definernote [...] [²...] [³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupnote </pre>
<pre> \defineornament [...] [²...,...] [³...,...] OPT 1 NAME 2 alternativ = a b inherits: \setupcollector 3 stil = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat </pre>
<pre> \defineornament [¹] [²...,...] [³...,...] OPT 1 NAME 2 alternativ = a b inherits: \setuplayer 3 inherits: \setuplayeredtext </pre>
<pre> \defineoutputroutine [¹] [²...] [³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupoutputroutine </pre>
<pre> \defineoutputroutinecommand [...,*...] * KEY </pre>
<pre> \definepage [¹] [²] 1 NAME 2 REFERENCE </pre>
<pre> \definepagebreak [¹] [²...,...] 1 NAME 2 gol antet subsol dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadрупul ultim ultimapagina start stop </pre>
<pre> \definepagechecker [¹] [²...] [³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuppagechecker </pre>
<pre> \definepagegrid [¹] [²...] [³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuppagegrid </pre>
<pre> \definepagegridarea [¹] [²...] [³...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setuppagegridarea </pre>

`\definepagegridspan [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppagegridspan

`\definepageinjection [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppageinjection

`\definepageinjectionalternative [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppageinjectionalternative

`\definepageshift [...]1 [...]2 [...,3...]`

1 NAME

2 orizontal vertical

3 DIMENSION

`\definepagestate [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppagestate

`\definepairedbox [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppairedbox

`\defineparagraph [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupparagraph

`\defineparallel [...]1 [...,2...]`

1 NAME

2 NAME

`\defineparbuilder [...]`

* NAME

`\defineplacement [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupplacement

```
1  NAME
2  NAME
3  inherits: \setarepozitie
```

```

1  NAME SECTIONBLOCK:NAME
2  ABSCHNITT
3  ABSCHNITT

```

```
1  NAME
2  COLOR
3  inherits: \definesteculoare
```

```
1  NAME
2  NAME
3  inherits: \setupprocessor
```

```
1  NAME
2  inherits: \setupfieldcontentframed
```

```
1  NAME
2  n r d
```

```
1  NAME
2  NAME
3  inherits: \setuprenderingwindow
```

```

1  NAME SECTIONBLOCK:NAME
2  NUMMER
3  NUMMER

```

```
1  NAME
2  NAME
3  inherits: \setupscale
```

```
1  NAME
2  NAME
3  inherits: \setupscript
```

`\definesectionlevels [...]1 [...,2...]`

- 1 NAME
- 2 ABSCHNITT

`\defineselector [...]1 [...,2...OPT...]`

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [...]1 [...,2...]OPT [...]3`

- 1 NAME SECTIONBLOCK:NAME
- 2 BEFEHL PROCESSOR->BEFEHL
- 3 BEFEHL PROCESSOR->BEFEHL

`\defineshift [...]1 [...]OPT2 [...,3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

`\definesidebar [...]1 [...]OPT2 [...,3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupsidebar

`\definesort [...]1 [...]2 [...]OPT3 {...}4`

- 1 da nu
- 2 SINGULAR
- 3 NAME
- 4 CONTENT

`\definespotcolor [...]1 [...]2 [...,3...OPT...]`

- 1 NAME
- 2 COLOR
- 3 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
difference exclusion hue saturation culoare luminosity
t = NUMMER
e = TEXT
p = NUMMER

`\defineste [...]1 \...OPT2 {...}3`

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

`\definesteaccent ...1 ...2 ...3`

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

\definesteantet [¹...] [²...] [³...,...³...,...]
 OPT OPT

- 1 NAME
- 2 ABSCHNITT
- 3 inherits: \seteazatitlu

\definestebloc [¹...] [²...] [³...,...³...,...]
 OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazabloc

\definesteblocsectione [¹...] [²...] [³...,...³...,...]
 OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazablocsectione

\definestebuffer [¹...] [²...] [³...,...³...,...]
 OPT OPT

- 1 NAME
- 2 BUFFER
- 3 inherits: \seteazabuffer

\definestecamp [¹...] [²...] [³...] [⁴...,...]⁵ [⁵...]

- 1 NAME
- 2 radio sub text linie push check signature
- 3 NAME
- 4 NAME
- 5 NAME

\definestecaracter ¹... ²...

- 1 CHARACTER
- 2 NUMMER

\definestecomanda ¹... ²...

- 1 CHARACTER
- 2 BEFEHL

\definesteconversie [¹...] [²...] [³...]
 OPT

- 1 SPRACHE
- 2 NAME
- 3 CSNAME

\definesteconversie [¹...] [²...] [³...,...]
 OPT

- 1 SPRACHE
- 2 NAME
- 3 TEXT

```

1  NAME
2  r  =  NUMBER
   g  =  NUMBER
   b  =  NUMBER
   c  =  NUMBER
   m  =  NUMBER
   y  =  NUMBER
   k  =  NUMBER
   h  =  NUMBER
   s  =  NUMBER
   v  =  NUMBER
   x  =  NUMBER
   a  =  NUMBER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
        difference exclusion hue saturation culoare luminosity
   t  =  NUMBER

```

```
1  NAME
2  COLOR
```

```
1  NAME
2  NAME
3  inherits: \setupdescription
```

```

1  NAME
2  latime      = DIMENSION
   inaltime   = DIMENSION
   sus        = BEFEHL
   jos        = BEFEHL
   stanga     = BEFEHL
   dreapta    = BEFEHL
   distanta   = DIMENSION
   pagina     = inherits: \seteazadimensiuniuhartie
   hartie     = inherits: \seteazadimensiuniuhartie

```

```
1  NAME
2  inherits: \seteazadimensiunihartie
3  inherits: \seteazadimensiunihartie
```

```
1  NAME
2  NAME
3  inherits: \setupenumeration
```

```
1  NAME
2  NAME
3  inherits: \setuplabel
```

```
\definestefloat [...]1 [...]2 [...,...3...]3
                        OPT      OPT

1  SINGULAR
2  PLURAL
3  inherits: \seteazafloat

instances: chemical figure table intermezzo graphic
```

```
\definestefloat [...]1 [...]2 [...]3
                        OPT      OPT

1  SINGULAR
2  PLURAL
3  SINGULAR

instances: chemical figure table intermezzo graphic
```

```
\definestefont [...]1 [...]2 [...,...3...]3
                                   OPT

1  NAME
2  FONT
3  inherits: \seteazaspatiuinterliniar
```

```
\definestefonttext [...]1,... [...]2,... [...]3,... [...,...4...]4
                        OPT      OPT

1  NAME implicit
2  NAME DIMENSION
3  rm ss tt hw cg

4  tf    = FILE
    bf    = FILE
    it    = FILE
    sl    = FILE
    bi    = FILE
    bs    = FILE
    sc    = FILE
    mr    = FILE
    mrlr  = FILE
    mrrl  = FILE
    mb    = FILE
    mblr  = FILE
    mbrl  = FILE
```

```
\definestefonttext [...]1,... [...]2,... [...]3,... [...]4
                        OPT      OPT

1  NAME implicit
2  NAME DIMENSION
3  rm ss tt hw cg
4  NAME
```

```
\definestefont [...]1 [...]2 [...]3
                                   OPT

1  NAME
2  FONT
3  NAME
```

```
\definesteformatreferinte [...]1 [...]2 [...,...3...]3
                                   OPT      OPT

1  NAME
2  NAME
3  inherits: \setupreferenceformat
```

\definestegrupculori [¹...] [²...] [x:y:³z,...]
OPT

- 1 NAME
- 2 gri rgb cmyk spot
- 3 TRIPLET

\definestehbox [¹...] [²...]

- 1 NAME
- 2 DIMENSION

\definesteinconjurare [¹...] [²...] [...,³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazainconjurat

\definestelista [¹...] [²...] [...,³...,...]
OPT OPT

- 1 NAME
- 2 LISTE
- 3 inherits: \seteazalista

\definestelistacombinata [¹...] [...,²...] [...,³...,...]
OPT

- 1 NAME
- 2 LISTE
- 3 inherits: \seteazalista

\definestemakeup [¹...] [²...] [...,³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazamakeup

\definestemarcaje [¹...] [²...] [...,³...,...]
OPT OPT

- 1 NAME
- 2 BESCHRIFTUNG
- 3 inherits: \seteazamarcaje

\definestemediulfonttext [¹...] [²...] [...,³...,...]
OPT OPT

- 1 NAME
- 2 implicit DIMENSION
- 3

mare	=	DIMENSION NUMMER
mic	=	DIMENSION NUMMER
a	=	DIMENSION NUMMER
b	=	DIMENSION NUMMER
c	=	DIMENSION NUMMER
d	=	DIMENSION NUMMER
text	=	DIMENSION NUMMER
x	=	DIMENSION NUMMER
xx	=	DIMENSION NUMMER
script	=	DIMENSION NUMMER
scriptscript	=	DIMENSION NUMMER
spatiereinterliniara	=	DIMENSION
em	=	inclinat italic STYLE BEFEHL
*	=	NUMMER

<pre> \definestemeniuiinteractiune [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazameniuiinteractiune </pre>
<pre> \definesteoverlay [...] [...] [...] OPT 1 NAME 2 NAME 3 BEFEHL </pre>
<pre> \definestepaleta [...] [...] [...] 1 NAME 2 NAME = COLOR </pre>
<pre> \definestepaleta [...] [...] 1 NAME 2 NAME </pre>
<pre> \definesteparagraf [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazaparafrage </pre>
<pre> \definesteprofil [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupprofile </pre>
<pre> \definesteprogram [...] [...] [...] OPT 1 NAME 2 TEXT 3 TEXT </pre>
<pre> \definestereferinte [...] [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definesteregistru [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazaregistru </pre>
<pre> \definestesablontabel [...] [...] [...] [...] OPT OPT 1 NAME 2 TEMPLATE 3 NAME 4 NAME </pre>

<pre> \definestesectione [...]</pre> <p>* NAME</p>
<pre> \definestesimbol [¹...] [²...] [³...] OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 BEFEHL</p>
<pre> \definestesimbolfigura [¹...] [²...] [³...,...³...,...] OPT</pre> <p>1 NAME</p> <p>2 FILE NAME</p> <p>3 inherits: \figuraexterna</p>
<pre> \definestesinonim [¹...] [²...] [³...] [⁴...] OPT OPT</pre> <p>1 SINGULAR</p> <p>2 PLURAL</p> <p>3 CSNAME</p> <p>4 CSNAME</p>
<pre> \definestesinonimfont [¹...] [²...] [³...,...³...,...] OPT</pre> <p>1 NAME</p> <p>2 FONT</p> <p>3 features = NAME fallbacks = NAME goodies = NAME designsize = auto implicit</p>
<pre> \definestesortare [¹...] [²...] [³...] OPT</pre> <p>1 SINGULAR</p> <p>2 PLURAL</p> <p>3 niciunul CSNAME</p>
<pre> \definestestartstop [¹...] [²...] [³...,...³...,...] OPT OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupstartstop</p>
<pre> \definestestil [¹...] [²...] [³...,...³...,...] OPT OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupstyle</p>
<pre> \definestestilfont [...,¹...] [²...]</pre> <p>1 NAME</p> <p>2 NAME</p>

`\definestestivacampuri` [¹...] [²...,...] [³...,..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldcategory

`\definestesubcamp` [¹...] [²...] [³...,...]

- 1 NAME
- 2 NAME
- 3 NAME

`\definestetabulatori` [¹...] [²...] [³.../]_{OPT}

- 1 NAME
- 2 NAME
- 3 TEMPLATE

`\definestetext` [¹...] [²...] [³...] [⁴...] [⁵...] [⁶...] [⁷...] _{OPT} _{OPT} _{OPT} _{OPT}

- 1 NAME
- 2 sus antet text subsol subsol
- 3 text margine bordura
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 6 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 7 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\definestetextinconjurat` [¹...] [²...] [³...,..._{OPT}...]_{OPT}

- 1 NAME
- 2 NAME
- 3 inherits: \setupframedtext

`\definestetyping` [¹...] [²...] [³...,..._{OPT}...]_{OPT}

- 1 NAME
- 2 NAME
- 3 inherits: \seteazatyping

`\definestyleinstance` [¹...] [²...] [³...] [⁴...] _{OPT} _{OPT}

- 1 NAME
- 2 rm ss tt mm hw cg
- 3 tf bf it sl bi bs sc
- 4 BEFEHL

`\definesubformula` [¹...] [²...] [³...,..._{OPT}...]_{OPT}

- 1 NAME
- 2 NAME
- 3 inherits: \setupsubformula

`\definesynonym [...]1 [...]2 [...]3 {...}4 {...}5`

OPT

- 1 da nu
- 2 SINGULAR
- 3 NAME
- 4 TEXT
- 5 CONTENT

`\definesystemattribute [...]1 [...]2,...]`

OPT

- 1 NAME
- 2 local global public private

`\definesystemconstant {...}`

- * NAME

`\definesystemvariable {...}`

- * NAME

`\defineTABLEsetup [...]1 [...]2,...]`

- 1 NAME
- 2 inherits: \setupTABLE

`\definetabulation [...]1 [...]2 [...]3,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptabulation

`\definetextbackground [...]1 [...]2 [...]3,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextbackground

`\definetextflow [...]1 [...]2 [...]3,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextflow

`\definetooltip [...]1 [...]2 [...]3,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptooltip

`\definetransparency [...]1 [...]2`

- 1 NAME
- 2 NUMMER

`\definetransparency [1...] [2...]`

1 NAME
2 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
difference exclusion hue saturation culoare luminosity
t = NUMMER

`\definetransparency [1...] [2...]`

1 NAME
2 NAME

`\definewopasslist {*.}`

* NAME

`\definetype [1...] [2...] [3...]`
OPT OPT

1 NAME
2 NAME
3 inherits: \seteazatype

`\definetypesface [1...] [2...] [3...] [4...] [5...] [6...]`
OPT OPT

1 NAME
2 rm ss tt mm hw cg
3 serif sans mono math handwriting calligraphy
4 NAME
5 implicit dtp
6 rscale = auto NUMMER
features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicit
directie = ambele

`\definetypescriptprefix [1...] [2...]`

1 NAME
2 TEXT

`\definetypescriptsynonym [1...] [2...]`

1 NAME
2 TEXT

`\definetypesetting [1...] [2...] [3...]`
OPT OPT

1 NAME
2 TEXT
3 inherits: \setupexternalfigure

`\defineunit [1...] [2...] [3...]`
OPT OPT

1 NAME
2 NAME
3 inherits: \setupunit

```
1  NAME
2  NAME
3  inherits: \setupviewerlayer
```

```

1  NAME
2  NAME
3  DIMENSION

```

```
1  NAME
2  inherits: \vspacing
```

```
1  NAME
2  DIMENSION
3  DIMENSION
```

```
1  NAME
2  NAME
3  inherits: \setupxtable
```

1	NAME
2	SPRACHE
3	CONTENT

1	NAME
2	SPRACHE
3	CONTENT

```
instances: citat minicitat blockquote speech aside
```

* TEXT

* CONTENT

$\backslash\text{depthspanningtext} \{\text{...}^1\} \{\text{...}^2\} \{\text{...}^3\}$ 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{DESCRIERE} [\text{...}^1, \text{...}^2] \{\text{...}^3\} \text{...} \backslash\text{par}$ <small>OPT OPT</small> 1 REFERENCE 2 TEXT 3 CONTENT
$\backslash\text{despre} [\text{...}^*]$ * REFERENCE
$\backslash\text{determinacaracteristicilelistei} [\text{...}^1, \text{...}^2] [\text{...}^2, \text{...}^2, \text{...}^2]$ <small>OPT</small> 1 LISTE 2 inherits: \seteazalista
$\backslash\text{determinacaracteristiciregistru} [\text{...}^1] [\text{...}^2, \text{...}^2, \text{...}^2]$ <small>OPT</small> 1 NAME 2 language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc numberorder = numere compress = da nu tot criteriu = local text curent precedent tot ABSCHNITT
$\backslash\text{determinanumartitlu} [\text{...}^*]$ * ABSCHNITT
$\backslash\text{determinenoflines} \{\text{...}^*\}$ * CONTENT
$\backslash\text{devanagarinumerals} \{\text{...}^*\}$ * NUMMER
$\backslash\text{dfrac} \{\text{...}^1\} \{\text{...}^2\}$ 1 CONTENT 2 CONTENT
$\backslash\text{digits} \{\text{...}^*\}$ * NUMMER
$\backslash\text{digits} \text{...}^*$ * NUMMER
$\backslash\text{dimensiontocount} \{\text{...}^1\} \backslash \text{...}^2$ 1 DIMENSION 2 CSNAME

<code>\din [...]</code> * REFERENCE
<code>\directcolor [...]</code> * COLOR
<code>\directcolored [...,...[*]...,...]</code> * inherits: \definesteculoare
<code>\directcolored [...]</code> * COLOR
<code>\directconvertedcounter {...¹} {...²}</code> 1 NAME 2 primul precedent urmatorul ultim numar
<code>\directdummyparameter {...}</code> * KEY
<code>\directgetboxllx ...</code> * CSNAME NUMBER
<code>\directgetboxlly ...</code> * CSNAME NUMBER
<code>\directhighlight {...¹} {...²}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...¹] {...²}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * BEFEHL
<code>\directselect {...¹} {...²} {...³} {...⁴} {...⁵} {...⁶}</code> <div style="display: flex; justify-content: space-around; margin: 0 100px;"> OPT OPT OPT OPT OPT </div> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME

$\backslash\text{directsetup}$ {...} * NAME
$\backslash\text{directsymbol}$ {... ¹ } {... ² } 1 NAME 2 NAME
$\backslash\text{directvspacing}$ {...,*...} * inherits: \vspacing
$\backslash\text{dis}$ {...} * CONTENT
$\backslash\text{disabledirectives}$ [...,*...]
* NAME
$\backslash\text{disableexperiments}$ [...,*...]
* NAME
$\backslash\text{disablemode}$ [...,*...]
* NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ [...,*...]
* NAME
$\backslash\text{displaymath}$ {...} * CONTENT
$\backslash\text{displaymathematics}$ {...} * CONTENT
$\backslash\text{displaymessage}$ {...} * TEXT
$\backslash\text{distributedhsize}$ {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 DIMENSION 3 NUMMER

<code>\dividedsize {...} {...} {...}</code> 1 DIMENSION 2 DIMENSION 3 NUMMER
<code>\doadaptleftskip {...}</code> * da nu standard DIMENSION
<code>\doadaptrightskip {...}</code> * da nu standard DIMENSION
<code>\doaddfeature {...}</code> * NAME
<code>\doassign [...¹] [...²...]</code> 1 TEXT 2 KEY = VALUE
<code>\doassignempty [...¹] [...²...]</code> 1 TEXT 2 KEY = VALUE
<code>\doboundtext {...¹} {...²} {...³}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\docheckassignment {...}</code> * TEXT
<code>\docheckedpagestate {...¹} {...²} {...³} {...⁴} {...⁵} {...⁶} {...⁷}</code> 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL
<code>\docheckedpair {...*,...}</code> * TEXT
<code>\documentvariable {...}</code> * KEY

\dodoubleargument \¹... [²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleargumentwithset \¹... [²...,²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleempty \¹... [²...] [³...]
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleemptywithset \¹... [²...,²...] [³...]
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoublegroupempty \¹... {²...} {³...}
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\doeassign [¹...] [²...]

- 1 TEXT
- 2 KEY = VALUE

\doexpandedrecurse {¹...} {²...}

- 1 NUMMER
- 2 BEFEHL

\dogetattribute {^{*}...}

- * NAME

\dogetattributeid {^{*}...}

- * NAME

\dogetcommacommandelement ¹... \from ²... \to ³...

- 1 NUMMER
- 2 TEXT
- 3 CSNAME

\dogobbledoubleempty [¹...] [²...]
OPT OPT

- 1 TEXT
- 2 TEXT

<pre> \dogobblesingleempty [...] OPT * TEXT </pre>
<pre> \doif {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifallcommon {...} * TRUE </pre>
<pre> \doifallcommonelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifalldefinedelse {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifallmodes {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifallmodeselse {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifassignmentelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifblackelse {...} {...} {...} 1 COLOR 2 TRUE 3 FALSE </pre>
<pre> \doifbothsides {...} {...} {...} 1 BEFEHL 2 BEFEHL 3 BEFEHL </pre>

`\doifbothsidesoverruled {...} {...} {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 BEFEHL

`\doifboxelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifbufferelse {...} {...} {...}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifcolor {...} {...}`

- 1 COLOR
- 2 TRUE

`\doifcolorelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifcommandhandler \... {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifcommon {...}`

- * TRUE

`\doifcommonelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifcontent {...} {...} {...} \... {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 BEFEHL
- 4 CSNAME
- 5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifconversionnumberelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifcurrentfonthasfeatureelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefined {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMMER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelse {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE
- 4 FALSE

`\doifelseallcommon {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsealldefined {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseallmodes {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseassignment {...1} {...2} {...3}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseblack {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsebox {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsebuffer {...1} {...2} {...3}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifelsecolor {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsecommandhandler \... {...1} {...2} {...3} {...4}`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsecommon {...1} {...2}`

- 1 TRUE
- 2 FALSE

\doifelseconversiondefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsecounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentsortingingused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymshown {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsedefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedefinedcounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedimension {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsedimenstring {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsedocumentargument {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedocumentfilename {...} {...} {...}

- 1 NUMMER
- 2 TRUE
- 3 FALSE

\doifelsedrawingblack {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseempty {...} {...} {...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifelseemptyvalue {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifelseenv {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\doifelsefastoptionalcheck {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsefastoptionalcheckcs \... \...

- 1 CSNAME
- 2 CSNAME

\doifelsefieldbody {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefieldcategory {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefigure {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefiledefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefileexists {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefirstchar {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseflagged {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefontchar {...} {...} {...} {...}

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsefontpresent {...} {...} {...}

- 1 FONT
- 2 TRUE
- 3 FALSE

\doifelsefontsynonym {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsehasspace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsehelp {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseincsname {...} {...} {...} {...}

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

\doifelseinelement {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinputfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseinsertion {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinset {...} {...} {...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifelseinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseintoks {...} {...} {...} {...}

- 1 BEFEHL
- 2 BEFEHL
- 3 TRUE
- 4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseitalic {...} {...}

- 1 TRUE
- 2 FALSE

\doifelselanguage {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doifelselayerdata {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutdefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutsomeline {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayouttextline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseleapyear {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelselist {...} {...} {...}`

- 1 LISTE
- 2 TRUE
- 3 FALSE

`\doifelselocation {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \... \...1 \...2`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \... \...1 \...2`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextparenthesis {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenonzeropositive {...1} {...2} {...3}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsenoteonsamepage {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenothing {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsenumber {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseobjectfound {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseobjectreferencefound {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoddpage {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\doifelseoddpagefloat {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseoldercontext {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelseolderversion {...} {...} {...} {...}`

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifelseoverlapping {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoverlay {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseparallel {...} {...,2...} {...} {...4}`

- 1 NAME
- 2 NAME tot
- 3 TRUE
- 4 FALSE

`\doifelseparentfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelsepath {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifelsepathexists {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifelsepatterns {...} {...} {...}`

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

`\doifelseposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsepositiononpage {...} {...} {...} {...4}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsepositionsonsamepage {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionsonthispage {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionsused {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifelserreferencefound {...¹} {...²} {...³}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelserightpagefloat {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifelserighttoleftinbox ...¹ {...²} {...³}

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

\doifelsesamelinereference {...¹} {...²} {...³}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelsesamestring {...¹} {...²} {...³} {...⁴}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsesetups {...¹} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomebackground {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomespace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesomething {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesometoks \... {...} {...}

- 1 CSNAME
- 2 TRUE
- 3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsestructurelisthasnumber {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsestructurelisthaspage {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsesymboldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesymbolset {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetext {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsetextflow {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetextflowcollector {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetypingfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseundefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseurldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsevalue {...} {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsevaluenothing {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsevariable {...} {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifempty $\{.^1.\} \{.^2.\}$

- 1 CONTENT
- 2 TRUE

\doifemptyelse $\{.^1.\} \{.^2.\} \{.^3.\}$

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifemptytoks $\backslash.^1.\ \{.^2.\}$

- 1 CSNAME
- 2 TRUE

\doifemptyvalue $\{.^1.\} \{.^2.\}$

- 1 NAME
- 2 TRUE

\doifemptyvalueelse $\{.^1.\} \{.^2.\} \{.^3.\}$

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifemptyvariable $\{.^1.\} \{.^2.\} \{.^3.\}$

- 1 NAME
- 2 KEY
- 3 TRUE

\doifemptyvariableelse $\{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifenv $\{.^1.\} \{.^2.\}$

- 1 KEY
- 2 TRUE

\doifenvelse $\{.^1.\} \{.^2.\} \{.^3.\}$

- 1 KEY
- 2 TRUE
- 3 FALSE

\doiffastoptionalcheckcselse $\backslash.^1.\ \backslash.^2.\$

- 1 CSNAME
- 2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiffieldbodyelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffieldcategoryelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffigureelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffile {...} {...}`

- 1 FILE
- 2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doiffflaggedelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doiffontcharelse {...} {...} {...} {...}

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doiffontpresentelse {...} {...} {...}

- 1 FONT
- 2 TRUE
- 3 FALSE

\doiffontsynonymelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifhasspaceelse {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifhelpelse {...} {...}

- 1 TRUE
- 2 FALSE

\doifincsnameelse {...} {...} {...} {...}

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

\doifinelementelse {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifinputfileelse {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifinsertionelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifinset {...} {...}`

1 CONTENT
2 TRUE

`\doifinsetelse {...} {...} {...}`

1 CONTENT
2 TRUE
3 FALSE

`\doifinstring {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifinstringelse {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifinsymbolset {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifinsymbolsetelse {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifintokselse {...} {...} {...} {...}`

1 BEFEHL
2 BEFEHL
3 TRUE
4 FALSE

`\doifintwopassdataelse {...} {...} {...} {...}`

1 NAME
2 NAME
3 TRUE
4 FALSE

`\doifitalicelse {...} {...}`

1 TRUE
2 FALSE

`\doiflanguageelse {...} {...} {...}`

1 SPRACHE
2 TRUE
3 FALSE

`\doiflayerdataelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMMER
2 TRUE
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LISTE
2 TRUE
3 FALSE

`\doiflocationelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflocfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifmainfloatbodyelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifmarkingelse {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifmeaningelse \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifmessageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMMER
- 3 TRUE
- 4 FALSE

`\doifmode {...,1...} {...2}`

- 1 NAME
- 2 TRUE

`\doifmodeelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnextbgroupcselse \1... \2...`

- 1 CSNAME
- 2 CSNAME

<pre> \doifnextbgroupelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifnextcharelse {...} {...} {...} 1 CHARACTER 2 TRUE 3 FALSE </pre>
<pre> \doifnextoptionalcselse \^1... \^2... 1 CSNAME 2 CSNAME </pre>
<pre> \doifnextoptionalelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifnextparenthesiselse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifnonzeropositiveelse {...} {...} {...} 1 NUMMER 2 TRUE 3 FALSE </pre>
<pre> \doifnot {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifnotallcommon {...} * TRUE </pre>
<pre> \doifnotallmodes {...,^1...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifnotcommandhandler \^1... {...} {...} 1 CSNAME 2 NAME 3 TRUE </pre>
<pre> \doifnotcommon {...} * TRUE </pre>

<pre>\doifnotcounter {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotdocumentargument {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotdocumentfilename {...} {...}</pre> <pre>1 NUMMER</pre> <pre>2 TRUE</pre>
<pre>\doifnotempty {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 TRUE</pre>
<pre>\doifnotemptyvalue {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotemptyvariable {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 TRUE</pre>
<pre>\doifnotenv {...} {...}</pre> <pre>1 KEY</pre> <pre>2 TRUE</pre>
<pre>\doifnoteonsamepageelse {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\doifnotescollected {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotfile {...} {...}</pre> <pre>1 FILE</pre> <pre>2 TRUE</pre>
<pre>\doifnotflagged {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>

`\doifnothing {...} {...}`

1 TEXT
2 TRUE

`\doifnothingelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifnotinset {...} {...}`

1 CONTENT
2 TRUE

`\doifnotinfloat {...}`

* TRUE

`\doifnotinstring {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifnotmode {...} {...}`

1 NAME
2 TRUE

`\doifnotnumber {...} {...}`

1 TEXT
2 TRUE

`\doifnotsamestring {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifnotsetups {...} {...}`

1 NAME
2 TRUE

`\doifnotvalue {...} {...} {...}`

1 NAME
2 TEXT
3 TRUE

`\doifnotvariable {...} {...} {...}`

1 NAME
2 KEY
3 TRUE

`\doifnumber {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnumberelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifobjectfoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifobjectreferencefoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoddpagelse {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\doifoddpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifoldercontextelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifolderversionelse {...} {...} {...} {...}`

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifoverlappingelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoverlayelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifparallelelse {...} {...,2...} {...} {...4}`

- 1 NAME
- 2 NAME tot
- 3 TRUE
- 4 FALSE

`\doifparentfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifpathelse {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifpathexistselse {...} {...} {...}`

- 1 PATH
- 2 TRUE
- 3 FALSE

`\doifpatternelse {...} {...} {...}`

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

`\doifposition {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionaction {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionactionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositiononpageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifpositionsonsamepageelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsonthispageelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsusedelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifreferencefoundelse {...1} {...2} {...3}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifrightpagefloatelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifrighttoleftinboxelse ...1 {...2} {...3}`

- 1 CSNAME NUMMER
- 2 TRUE
- 3 FALSE

`\doifsamelinereferenceelse {...1} {...2} {...3}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifsamestringelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifsetupself {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackground {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifsomespaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsomething {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifsomethingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifsometoks \... {...}`

- 1 CSNAME
- 2 TRUE

`\doifsometokselsetelse \... {...} {...}`

1 CSNAME
2 TRUE
3 FALSE

`\doifstringinstringelse {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

1 TRUE
2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

1 TRUE
2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsymbolsetelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiftext {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextflowcollectorelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doiftextflowelse {1...} {2...} {3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftypingfileelse {1...} {2...} {3...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifundefined {1...} {2...}`

- 1 NAME
- 2 TRUE

`\doifundefinedcounter {1...} {2...}`

- 1 NAME
- 2 TRUE

`\doifundefinedelse {1...} {2...} {3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifurldefinedelse {1...} {2...} {3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvalue {1...} {2...} {3...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifvalueelse {1...} {2...} {3...} {4...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifvaluenothing {1...} {2...}`

- 1 NAME
- 2 TRUE

`\doifvaluenothingelse {1...} {2...} {3...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvaluesomething {...} {...}`

1 NAME

2 TRUE

`\doifvariable {...} {...} {...}`

1 NAME

2 KEY

3 TRUE

`\doifvariableelse {...} {...} {...} {...}`

1 NAME

2 KEY

3 TRUE

4 FALSE

`\doindentation`

`\dollar`

`\doloop {...}`

* BEFEHL

`\doloopoverlist {...,1...} {...2}`

1 TEXT

2 BEFEHL

`\donothing`

`\dontconvertfont`

`\dontleavehmode`

`\dontpermitspacesbetweenegroups`

`\dopositionaction {...}`

* NAME

`\doprocesslocalsetups {...,*...}`

* NAME

`\doquadrupleargument \1... [2...] [3...] [4...] [5...]`

1 CSNAME

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`
OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`
OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintuplegroupempty \1... {2...} {3...} {4...} {5...} {6...}`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\dorechecknextindentation`

`\dorecurse {1...} {2...}`

- 1 NUMMER
- 2 BEFEHL

`\dorepeatwithcommand [1...] \2...`

- 1 TEXT NUMMER*TEXT
- 2 CSNAME

<p><code>\doreplacefeature {...}</code></p> <p>* NAME</p>
<p><code>\doresetandafffeature {...}</code></p> <p>* NAME</p>
<p><code>\doresetattribute {...}</code></p> <p>* NAME</p>
<p><code>\dorotatebox {...} \dots {...}</code></p> <p>1 NUMMER</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\dosetattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\dosetleftskipadaption {...}</code></p> <p>* da nu standard DIMENSION</p>
<p><code>\dosetrighskipadaption {...}</code></p> <p>* da nu standard DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* inherits: \seteazaspatiuinterliniar</p>
<p><code>\dosetupcheckedinterlinespace {...,*...}</code></p> <p>* on dezactivat reset auto mic mediu mare NUMMER DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace {...}</code></p> <p>* NAME</p>
<p><code>\doseventupleargument \dots [..] [..] [..] [..] [..] [..] [..] [..]</code></p> <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p> <p>7 TEXT</p> <p>8 TEXT</p>

\doseventupleempty \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷ ⁸
 OPT OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT
- 8 TEXT

\dosingleargument \... ¹ ²
 OPT

- 1 CSNAME
- 2 TEXT

\dosingleempty \... ¹ ²
 OPT

- 1 CSNAME
- 2 TEXT

\dosinglegroupempty \... ¹ { ² }
 OPT

- 1 CSNAME
- 2 TEXT

\dosixtupleargument \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷
 OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

\dosixtupleempty \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷
 OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

\dostarttagged { ¹ } { ² } ... \dostoptagged

- 1 NAME
- 2 NAME

`\dostepwiserecurse {...} {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 [-+]NUMBER
- 4 BEFEHL

`\dosubtractfeature {...}`

- * NAME

`\dotfskip {...}`

- * DIMENSION

`\dotoks \...`

- * CSNAME

`\dotripleargument \... [...] [...] [...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \... [...,2...] [...] [...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \... 2 [...] 3 [...] 4 [...]`
 OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleemptywithset \... [...,2...] [...] [...]`
 OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotriplegroupempty \... {2...} {3...} {4...}`
 OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\doublebar {...}`

- * TEXT

<code>\doublebond</code>
<code>\doublebrace {...}</code> * TEXT
<code>\doublebracket {...}</code> * TEXT
<code>\doubleparent {...}</code> * TEXT
<code>\dowith {...¹,...} {...²}</code> 1 BEFEHL 2 BEFEHL
<code>\dowithnextbox {...¹} \... {...³}</code> 1 BEFEHL 2 CSNAME 3 CONTENT
<code>\dowithnextboxcontent {...¹} {...²} \... {...⁴}</code> 1 BEFEHL 2 BEFEHL 3 CSNAME 4 CONTENT
<code>\dowithnextboxcontentcs \...¹ \...² \...³ {...⁴}</code> 1 CSNAME 2 CSNAME 3 CSNAME 4 CONTENT
<code>\dowithnextboxcs \...¹ \...² {...³}</code> 1 CSNAME 2 CSNAME 3 CONTENT
<code>\dowithpargument \...</code> * CSNAME
<code>\dowithrange {...¹,...} \...²</code> 1 NUMMER NUMMER:NUMMER 2 CSNAME
<code>\dowithwargument \...</code> * CSNAME

<p><code>\dpofstring {...}</code></p> <p>* TEXT</p>
<p><code>\dreapta ...</code></p> <p>* CHARACTER</p>
<p><code>\dummydigit</code></p>
<p><code>\dummyparameter {...}</code></p> <p>* KEY</p>
<p><code>\dute {...} [...]</code></p> <p>1 CONTENT</p> <p>2 REFERENCE</p>
<p><code>\dutebox {...} [...]</code></p> <p>1 CONTENT</p> <p>2 REFERENCE</p>
<p><code>\dutepagina {...} [...]</code></p> <p>1 TEXT</p> <p>2 REFERENCE</p>
<p><code>\ETEX</code></p>
<p><code>\EveryLine {...}</code></p> <p>* BEFEHL</p>
<p><code>\EveryPar {...}</code></p> <p>* BEFEHL</p>
<p><code>\ecran [...,*,...]</code> OPT</p> <p>* inherits: \pagina</p>
<p><code>\edefconvertedargument \¹... {²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\efcmaxheight {...}</code></p> <p>* NAME</p>
<p><code>\efcmaxwidth {...}</code></p> <p>* NAME</p>
<p><code>\efcminheight {...}</code></p> <p>* NAME</p>

<code>\efcminwidth {...}</code> <code>* NAME</code>
<code>\efcparameter {...} {...}</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\effect [...] {...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\leftharpoondownfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\leftharpoonupfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\leftrightarrowfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\element [...,*...]</code> <div> <div></div> <div>OPT</div> </div> <code>* REFERENCE</code>
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...,*...]</code> <div> <div></div> <div>OPT</div> </div> <code>* NUMMER</code>
<code>\emspace</code>
<code>\enabledirectives [...,*...]</code> <code>* NAME</code>
<code>\enableexperiments [...,*...]</code> <code>* NAME</code>

<p><code>\enablemode [...,*,...]</code></p> <p>* NAME</p>
<p><code>\enableoutputstream [...]</code></p> <p>* NAME</p>
<p><code>\enableparpositions</code></p>
<p><code>\enableregime [...]</code></p> <p>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</p>
<p><code>\enabletrackers [...,*,...]</code></p> <p>* NAME</p>
<p><code>\endnote [...,¹,...] {²...}</code> <small> OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\endnote [...,.*=.,...]</code></p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p>
<p><code>\enskip</code></p>
<p><code>\enspace</code></p>
<p><code>\ENUMERARE [...,¹,...] {²...} ³. \par</code> <small> OPT OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\env {...}</code></p> <p>* KEY</p>
<p><code>\envvar {...} {²...}</code> <small> ¹</small></p> <p>1 KEY</p> <p>2 BEFEHL</p>
<p><code>\eoverbarfill {¹...} {²...}</code> <small> OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\eoverbracefill {¹...} {²...}</code> <small> OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>

$\backslash\mathrm{eoverbracketfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eoverparentfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{epos}$ $\{*\}$ * NAME
$\backslash\mathrm{equaldigits}$ $\{*\}$ * TEXT
$\backslash\mathrm{erightarrowfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{erightharpoondownfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{erightharpoonupfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eTeX}$
$\backslash\mathrm{ethiopic}$
$\backslash\mathrm{ETICHETA}$ $[\overset{1}{\dots},\dots]\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 REFERENCE 2 TEXT
$\backslash\mathrm{etwoheadrightarrowfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eunderbarfill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{eunderbracefill}$ $\{\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ <small>OPT OPT</small> 1 TEXT 2 TEXT

$\backslash\mathrm{eunderbracketfill}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathrm{eunderparentfill}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <div> <div>1</div> <div>TEXT</div> </div> <div> <div>2</div> <div>TEXT</div> </div>
$\backslash\mathrm{executeifdefined}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>BEFEHL</div> </div>
$\backslash\mathrm{exitloop}$
$\backslash\mathrm{exitloopnow}$
$\backslash\mathrm{expandcheckedcsname}\ \overset{1}{\backslash}...\ \overset{2}{\{...\}}\ \overset{3}{\{...\}}$ <div> <div>1</div> <div>CSNAME</div> </div> <div> <div>2</div> <div>KEY</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
$\backslash\mathrm{expanded}\ \overset{*}{\{...\}}$ <div> <div>*</div> <div>CONTENT</div> </div>
$\backslash\mathrm{expandfontsynonym}\ \overset{1}{\backslash}...\ \overset{2}{\{...\}}$ <div> <div>1</div> <div>CSNAME</div> </div> <div> <div>2</div> <div>NAME</div> </div>
$\backslash\mathrm{externalfigurecollectionmaxheight}\ \overset{*}{\{...\}}$ <div> <div>*</div> <div>NAME</div> </div>
$\backslash\mathrm{externalfigurecollectionmaxwidth}\ \overset{*}{\{...\}}$ <div> <div>*</div> <div>NAME</div> </div>
$\backslash\mathrm{externalfigurecollectionminheight}\ \overset{*}{\{...\}}$ <div> <div>*</div> <div>NAME</div> </div>
$\backslash\mathrm{externalfigurecollectionminwidth}\ \overset{*}{\{...\}}$ <div> <div>*</div> <div>NAME</div> </div>
$\backslash\mathrm{externalfigurecollectionparameter}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>KEY</div> </div>
$\backslash\mathrm{fakebox}\ \overset{*}{...}$ <div> <div>*</div> <div>CSNAME NUMMER</div> </div>
$\backslash\mathrm{faraliniiantetsisubsol}$

<code>\faraliniisussijos</code>
<code>\faraspatiu</code>
<code>\fastdecrement \.*..</code> * CSNAME
<code>\fastincrement \.*..</code> * CSNAME
<code>\fastlocalframed [¹...] [²...<u>...</u>...] {³...}</code> 1 NAME 2 inherits: \seteazainconjurat 3 CONTENT
<code>\fastscale {¹...} {²...}</code> 1 NUMMER 2 CONTENT
<code>\fastsetup {.*..}</code> * NAME
<code>\fastsetupwithargument {¹...} {²...}</code> 1 NAME 2 CONTENT
<code>\fastsetupwithargumentswapped {¹...} {²...}</code> 1 CONTENT 2 NAME
<code>\fastswitchtobodyfont {.*..}</code> * x xx mic mare script scriptscript
<code>\fastxsxy {¹...} {²...} {³...}</code> 1 NUMMER 2 NUMMER 3 CONTENT
<code>\feature [¹...] [²...]</code> 1 + - = ! > < more less nou reset implicit old local 2 NAME
<code>\feature {¹...} {²...}</code> 1 + - = ! > < more less nou reset implicit old local 2 NAME
<code>\fence</code>

<code>\fenced [...]{...}</code> 1 NAME 2 CONTENT
<code>\FENCE {...}</code> * CONTENT
<code>\fetchallmarkings [...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME
<code>\fetchallmarks [...]</code> * BESCHRIFTUNG
<code>\fetchmark [...][...]</code> <small>OPT</small> 1 BESCHRIFTUNG 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchmarking [...][...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchonemark [...][...]</code> <small>OPT</small> 1 BESCHRIFTUNG 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchonemarking [...][...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchruntimecommand \...{...}</code> 1 CSNAME 2 FILE
<code>\fetchtwomarkings [...][...]</code> 1 BESCHRIFTUNG 2 pagina NAME
<code>\fetchtwomarks [...]</code> * BESCHRIFTUNG

<code>\fieldbody [...]¹ [...,...²...,...]</code> <small>OPT</small> 1 NAME 2 inherits: \setupfieldbody
<code>\fifthoffivearguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fifthofsixarguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\figuraexterna [...]¹ [...]² [...,...³...,...]</code> <small>OPT</small> <small>OPT</small> 1 FILE 2 NAME 3 inherits: \setupexternalfigure
<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<code>\figuresymbol [...]¹ [...,...²...,...]</code> <small>OPT</small> 1 FILE NAME 2 inherits: \figuraexterna
<code>\figurewidth</code>
<code>\filename {...}</code> * FILE

<pre> \filledhboxb ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxc ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxg ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxk ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxm ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxr ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxy ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filler [...] * sym simbol rigla latime spatiu NAME </pre>
<pre> \filterfromnext {¹...} {²...} 1 NUMMER 2 NUMMER </pre>
<pre> \filterfromvalue {¹...} {²...} {³...} 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \filterpages [...¹] [...²,...] [...³,...³...³,...] OPT 1 FILE 2 par impar NUMMER NUMMER:NUMMER 3 latime = DIMENSION n = NUMMER category = NAME </pre>

\filterreference {...} * implicit text titlu numar pagina realpage
\findtwopassdata {...} {...} 1 NAME 2 NAME
\finishregisterentry [...] ¹ [...,... ² ...,...] ² [...,... ³ ...,...] ³ <div style="text-align: right; margin-right: 100px;">OPT</div> 1 NAME 2 eticheta = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT alternativ = TEXT 3 KEY = VALUE
\firdepar
\firstcharacter
\firstcounter [...] ¹ [...] ² <div style="text-align: right; margin-right: 100px;">OPT</div> 1 NAME 2 NUMMER
\firstcountervalue [...] [*] * NAME
\firstoffivearguments {...} ¹ {...} ² {...} ³ {...} ⁴ {...} ⁵ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
\firstoffourarguments {...} ¹ {...} ² {...} ³ {...} ⁴ 1 TEXT 2 TEXT 3 TEXT 4 TEXT
\firstofoneargument {...} [*] * TEXT
\firstofoneunexpanded {...} [*] * TEXT

<p><code>\firstofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<p><code>\firstofthreearguments {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\firstofthreeunexpanded {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p><code>\firstoftwoarguments {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\firstoftwounexpanded {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\firstrealpage</code></p>
<p><code>\firstrealpagenumber</code></p>
<p><code>\firstsubcountervalue [...] [...]</code></p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\firstsubpagenumber</code></p>
<p><code>\firstuserpage</code></p>
<p><code>\firstuserpagenumber</code></p>
<p><code>\fitfieldframed [...^{$\frac{1}{2}$}...,...] {...}</code></p> <p style="text-align: center;"><small>OPT</small></p> <p>1 inherits: \setezainconjurat</p> <p>2 CONTENT</p>
<p><code>\fittopbaselinegrid {...}</code></p> <p>* CONTENT</p>

\flag {...} * NAME
\floatuserdataparameter {...} * KEY
\flushboxregister ... * CSNAME NUMBER
\flushcollector [...] * NAME
\flushedrightlastline
\flushlayer [...] * NAME
\flushlocalfloats
\flushnextbox
\flushnotes
\flushoutputstream [...] * NAME
\flushshapebox
\flushtextflow {...} * NAME
\flushtokens [...] * NAME
\flushtoks \... * CSNAME
\folosestebloc [..., ¹ ...] [..., ² ...] [..., ³ ...] 1 NAME 2 + - 3 criteriu = text ABSCHNITT
\folosestedirector [...,*...] * PATH

<p><code>\folosestedocumentextern</code> [¹...] [²...] [³...] <small>OPT</small></p> <p>1 NAME</p> <p>2 FILE</p> <p>3 TEXT</p>
<p><code>\folosestefiguraexterna</code> [¹...] [²...] [³...] [⁴...,..⁴...,...] <small>OPT</small> <small>OPT</small></p> <p>1 NAME</p> <p>2 FILE</p> <p>3 NAME</p> <p>4 inherits: \setuexternalfigure</p>
<p><code>\folosestemodul</code> [¹...] [²...,...] [³...,..³...,...] <small>OPT</small> <small>OPT</small></p> <p>1 m p s x t</p> <p>2 FILE</p> <p>3 KEY = VALUE</p>
<p><code>\folosestemuzicaexterna</code> [¹...] [²...]</p> <p>1 NAME</p> <p>2 FILE</p>
<p><code>\folosestescriptJS</code> [¹...] [²...,...] <small>OPT</small></p> <p>1 FILE</p> <p>2 NAME</p>
<p><code>\folosestesimboluri</code> [...]</p> <p>* FILE</p>
<p><code>\folosesteURL</code> [¹...] [²...] [³...] [⁴...] <small>OPT</small> <small>OPT</small></p> <p>1 NAME</p> <p>2 URL</p> <p>3 FILE</p> <p>4 TEXT</p>
<p><code>\folosesteurl</code> [¹...] [²...] [³...] [⁴...] <small>OPT</small> <small>OPT</small></p> <p>1 NAME</p> <p>2 URL</p> <p>3 FILE</p> <p>4 TEXT</p>
<p><code>\fontalternative</code></p>
<p><code>\fontbody</code></p>
<p><code>\fontchar</code> {...}</p> <p>* NAME</p>
<p><code>\fontcharbyindex</code> {...}</p> <p>* NUMMER</p>

<code>\fontclass</code>
<code>\fontclassname {¹...} {²...}</code> 1 NAME 2 FONT
<code>\fontface</code>
<code>\fontfeaturelist [¹...] [²...]</code> 1 NAME 2 TEXT
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [¹...,^{OPT}...] {²...}</code> 1 REFERENCE 2 TEXT
<code>\footnotetext [...,[*]...,...]</code> * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<code>\forgetparameters [¹...] [...,²...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\forgetragged</code>
<code>\formula [¹...,^{OPT}...] {²...}</code> 1 impachetat tight centru incadrat inherits: \seteazafonttext 2 CONTENT
<code>\foundbox {¹...} {²...}</code> 1 NAME 2 NAME

`\fourthoffivearguments {...} {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT

`\fourthoffourarguments {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT

`\fourthofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT

`\frac {...} {...}`

1 CONTENT
2 CONTENT

`\FRACTION {...} {...}`

1 CONTENT
2 CONTENT

instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom

`\framed [...,\stackrel{1}{=},...] {...}`
OPT

1 inherits: \seteazainconjurat
2 CONTENT

`\frameddimension {...}`

* KEY

`\framedparameter {...}`

* KEY

`\FRAMED [...,\stackrel{1}{=},...] {...}`
OPT

1 inherits: \seteazainconjurat
2 CONTENT

instances: unframed fitfieldframed

<code>\freezedimenmacro \¹ \²</code> 1 CSNAME 2 CSNAME
<code>\freezemeasure [...] [...]</code> 1 NAME 2 DIMENSION
<code>\frenchspacing</code>
<code>\fromlinenote [¹] {²}</code> 1 REFERENCE 2 TEXT
<code>\frozenhbox {*.}</code> * CONTENT
<code>\fundal {*.}</code> * CONTENT
<code>\FUNDAL {*.}</code> * CONTENT instances: fundal
<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumerals {*.}</code> * NUMMER
<code>\gdefconvertedargument \¹ {²}</code> 1 CSNAME 2 TEXT
<code>\gdefconvertedcommand \¹ \²</code> 1 CSNAME 2 CSNAME
<code>\getboxllx ...</code> * CSNAME NUMBER
<code>\getboxlly ...</code> * CSNAME NUMBER
<code>\getbufferdata [...]_{OPT}</code> * BUFFER

\getcommacommandsize [...,*...] * BEFEHL
\getcommalistsize [...,*...] * BEFEHL
\getdayoftheweek {... ¹ .} {... ² .} {... ³ .} 1 NUMMER 2 NUMMER 3 NUMMER
\getdayspermonth {... ¹ .} {... ² .} 1 NUMMER 2 NUMMER
\getdefinedbuffer [...*] * BUFFER
\getdocumentargument {...*} * NAME
\getdocumentargumentdefault {... ¹ .} {... ² .} 1 NAME 2 TEXT
\getdocumentfilename {...*} * NUMMER
\getdummyparameters [...,*=...] * KEY = VALUE
\getemptyparameters [... ¹ .] [...,* ² =...] 1 TEXT 2 KEY = VALUE
\getparameters [... ¹ .] [...,* ² =...] 1 TEXT 2 KEY = VALUE
\getexpandedparameters [... ¹ .] [...,* ² =...] 1 TEXT 2 KEY = VALUE
\getfiguredimensions [... ¹ .] [...,* ² _{OPT} =...] 1 FILE 2 inherits: \setupexternalfigure

\getfirstcharacter {...} * TEXT
\getfirsttwopassdata {...} * NAME
\getfromcommacommand [... ¹ ,...] [... ² .] 1 BEFEHL 2 NUMMER
\getfromcommalist [... ¹ ,...] [... ² .] 1 BEFEHL 2 NUMMER
\getfromtwopassdata {... ¹ } {... ² .} 1 NAME 2 NAME
\getglyphdirect {... ¹ } {... ² .} 1 FONT 2 NUMMER CHARACTER
\getglyphstyled {... ¹ } {... ² .} 1 FONT 2 NUMMER CHARACTER
\getgparameters [... ¹ .] [... ² ... ² ...] 1 TEXT 2 KEY = VALUE
\getlasttwopassdata {...} * NAME
\getlocalfloat {...} * NUMMER
\getlocalfloats
\getMPdrawing
\getMPlayer [... ¹ .] [... ² ... ² ... ³ .] <small>OPT</small> 1 NAME 2 inherits: \seteazainconjurat 3 CONTENT
\getmessage {... ¹ } {... ² .} 1 NAME 2 NAME NUMMER

<pre>\getnamedglyphdirect {...} {...}</pre> <pre>1 FONT</pre> <pre>2 NAME</pre>
<pre>\getnamedglyphstyled {...} {...}</pre> <pre>1 FONT</pre> <pre>2 NAME</pre>
<pre>\getnamedtwopassdatalist \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\getnaturaldimensions ...</pre> <pre>* CSNAME NUMMER</pre>
<pre>\getnoflines {...}</pre> <pre>* DIMENSION</pre>
<pre>\getobject {...} {...}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\getobjectdimensions {...} {...}</pre> <pre>1 NAME</pre> <pre>2 NAME</pre>
<pre>\getpaletsize [...]</pre> <pre>* NAME</pre>
<pre>\getparameters [...] [..., ...²..., ...]</pre> <pre>1 TEXT</pre> <pre>2 KEY = VALUE</pre>
<pre>\getprivatechar {...}</pre> <pre>* NAME</pre>
<pre>\getprivateslot {...}</pre> <pre>* NAME</pre>
<pre>\getrandomcount \... {...} {...}</pre> <pre>1 CSNAME</pre> <pre>2 NUMMER</pre> <pre>3 NUMMER</pre>

`\getrandomdimen \1... {2...} {3...}`

- 1 CSNAME
- 2 DIMENSION
- 3 DIMENSION

`\getrandomfloat \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMMER
- 3 NUMMER

`\getrandomnumber \1... {2...} {3...}`

- 1 CSNAME
- 2 NUMMER
- 3 NUMMER

`\getrandomseed *...`

- * CSNAME

`\getraweparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawgparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawnoflines {*...}`

- * DIMENSION

`\getrawparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getrawxparameters [1...] [...,2...,...]`

- 1 TEXT
- 2 KEY = VALUE

`\getreference [1...] [2...]`

- 1 implicit text titlu numar pagina realpage
- 2 REFERENCE

`\getreferenceentry {*...}`

- * implicit text titlu numar pagina realpage

`\getroundednoflines {*...}`

- * DIMENSION

<pre>\getsubstring {...} {...} {...}</pre> <pre>1 NUMMER</pre> <pre>2 NUMMER</pre> <pre>3 TEXT</pre>
<pre>\gettwopassdata {...}</pre> <pre>* NAME</pre>
<pre>\gettwopassdatalist {...}</pre> <pre>* NAME</pre>
<pre>\getuvalue {...}</pre> <pre>* NAME</pre>
<pre>\getvalue {...}</pre> <pre>* NAME</pre>
<pre>\getvariable {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre>
<pre>\getvariabledefault {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 BEFEHL</pre>
<pre>\getxparameters [...] [...,..²...,...]</pre> <pre>1 TEXT</pre> <pre>2 KEY = VALUE</pre>
<pre>\globaldisablemode [...,*,...]</pre> <pre>* NAME</pre>
<pre>\globalenablemode [...,*,...]</pre> <pre>* NAME</pre>
<pre>\globalletempty *...</pre> <pre>* CSNAME</pre>
<pre>\globalpopbox ...</pre> <pre>* CSNAME NUMMER</pre>
<pre>\globalpopmacro *...</pre> <pre>* CSNAME</pre>
<pre>\globalpreventmode [...,*,...]</pre> <pre>* NAME</pre>

<code>\globalprocesscommalist [...] \...</code> 1 BEFEHL 2 CSNAME
<code>\globalpushbox ...</code> * CSNAME NUMMER
<code>\globalpushmacro \...</code> * CSNAME
<code>\globalpushreferenceprefix {...} ... \globalpopreferenceprefix</code> * + - TEXT
<code>\globalswapcounts \... \...</code> 1 CSNAME 2 CSNAME
<code>\globalswapdimens \... \...</code> 1 CSNAME 2 CSNAME
<code>\globalswapmacros \... \...</code> 1 CSNAME 2 CSNAME
<code>\globalundefine {...}</code> * NAME
<code>\glyphfontfile {...}</code> * FONT
<code>\gobbledoubleempty [...]_{OPT} [...]_{OPT}</code> 1 TEXT 2 TEXT
<code>\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}</code> 1 CONTENT 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT 7 CONTENT 8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT

`\gobblefiveoptionals [...] [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT

`\gobblefouroptionals [...] [...] [...] [...]`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT

`\gobbleoneargument {...}`

- * CONTENT

`\gobbleoneoptional [...]`

- * TEXT

\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT

\gobblesingleempty [...]

OPT

- * TEXT

\gobblesixarguments {...} {...} {...} {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT

\gobblespacetokens

\gobbletenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT
- 10 CONTENT

\gobblethreearguments {...} {...} {...}

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT

\gobblethreeoptionals [...] [...] [...]

- 1 TEXT
- 2 TEXT
- 3 TEXT

\gobbletwoarguments {...} {...}

- 1 CONTENT
- 2 CONTENT

<p><code>\gobbletwooptionals [...] [...]</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\gobbleuntil \...</code></p> <p>* CSNAME</p>
<p><code>\gobbleuntilrelax ... \relax</code></p> <p>* CONTENT</p>
<p><code>\grabbufferdata [...] [...] [...] [...] [...]</code></p> <p><small>OPT</small></p> <p>1 CATEGORY</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p><code>\grabbufferdatadirect {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p>
<p><code>\grabuntil {...} \^2...</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\grave {...}</code></p> <p>* CHARACTER</p>
<p><code>\grayvalue {...}</code></p> <p>* COLOR</p>
<p><code>\greedystring \^1 \at \^2 \to \^3 \and \^4...</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p> <p>4 CSNAME</p>
<p><code>\greeknumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\grid [..., ...^..., ...]</code></p> <p><small>OPT</small></p> <p>* inherits: \basegrid</p>
<p><code>\grosimelinie</code></p>
<p><code>\groupedcommand {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p>

$\backslash\text{gsetboxllx}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 CSNAME NUMBER 2 DIMENSION
$\backslash\text{gsetboxlly}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 CSNAME NUMBER 2 DIMENSION
$\backslash\text{gujaratinumerals}$ $\{...\}$ * NUMBER
$\backslash\text{gurmurkhinumerals}$ $\{...\}$ * NUMBER
$\backslash\text{hairspace}$
$\backslash\text{halfwaybox}$ $\{...\}$ * CONTENT
$\backslash\text{handletokens}$ $\overset{1}{...}$ $\backslash\text{with}$ $\overset{2}{...}$ 1 TEXT 2 CSNAME
$\backslash\text{hangul}$
$\backslash\text{hanzi}$
$\backslash\text{hash}$
$\backslash\text{hat}$ $\{...\}$ * CHARACTER
$\backslash\text{hboxofvbox}$ $\overset{*}{...}$ * CSNAME NUMBER
$\backslash\text{hboxreference}$ $[...,\overset{1}{...}]$ $\{\overset{2}{...}\}$ 1 REFERENCE 2 CONTENT
$\backslash\text{hboxBOX}$ $\{...\}$ * CONTENT
$\backslash\text{hdofstring}$ $\{...\}$ * TEXT
$\backslash\text{headhbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ _{OPT} 1 TEXT 2 CONTENT

<code>\headlanguage</code>
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtexts {¹...} {²...}</code> 1 KEY 2 TEXT
<code>\headtextwidth</code>
<code>\headvbox ¹... {²...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\headwidth</code>
<code>\heightanddepthofstring {.*}</code> * TEXT
<code>\heightofstring {.*}</code> * TEXT
<code>\heightspanningtext {¹...} {²...} {³...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\HELP [¹...] {²...} {³...}</code> <small>OPT</small> 1 REFERENCE 2 TEXT 3 TEXT instances: textajutator
<code>\hglue ...</code> * DIMENSION
<code>\hiddenbar {.*}</code> * CONTENT

\backslash hiddencitation [...] * REFERENCE
\backslash hiddencite [...] * REFERENCE
\backslash highlight [...] ¹ {...} ² 1 NAME 2 TEXT
\backslash HIGHLIGHT {...} * TEXT
\backslash highordinalstr {...} * TEXT
\backslash hilo [...] ¹ {...} ² {...} ³ <small>OPT</small> 1 stanga dreapta 2 CONTENT 3 CONTENT
\backslash himilo {...} ¹ {...} ² {...} ³ 1 CONTENT 2 CONTENT 3 CONTENT
\backslash hl [...] <small>OPT</small> * NUMMER
\backslash horizontalgrowingbar [...,... [*] ...,...] * inherits: \setuppositionbar
\backslash horizontalpositionbar [...,... [*] ...,...] * inherits: \setuppositionbar
\backslash hphantom {...} * CONTENT
\backslash hpos {...} ¹ {...} ² 1 NAME 2 CONTENT
\backslash hsizedfraction {...} ¹ {...} ² 1 DIMENSION 2 NUMMER
\backslash hsmash {...} * CONTENT

<p><code>\hsmashbox ...</code></p> <p>* CSNAME NUMMER</p>
<p><code>\hsmashed {...}</code></p> <p>* CONTENT</p>
<p><code>\hspace [...]¹ [...]²</code></p> <p>OPT OPT</p> <p>1 NAME</p> <p>2 mic mediu mare normal implicit niciunul .5 1 2 3 speech minicitat interquotation citat sentence intersentence NAME</p>
<p><code>\htdpofstring {...}</code></p> <p>* TEXT</p>
<p><code>\htofstring {...}</code></p> <p>* TEXT</p>
<p><code>\hyphen</code></p>
<p><code>\hyphenatedcoloredword {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedfile {...}</code></p> <p>* FILE</p>
<p><code>\hyphenatedfilename {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedhbox {...}</code></p> <p>* CONTENT</p>
<p><code>\hyphenatedpar {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedurl {...}</code></p> <p>* TEXT</p>
<p><code>\hyphenatedword {...}</code></p> <p>* TEXT</p>
<p><code>\INRSTEX</code></p>
<p><code>\ibox {...}</code></p> <p>* CONTENT</p>
<p><code>\ifassignment ...¹ \else ...² \fi</code></p> <p>1 TRUE</p> <p>2 FALSE</p>

<code>\iff</code>
<code>\ifinobject ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\iftrialeasetting ¹... \else ²... \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {¹...} {²...} {³...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\impartefloat [...¹...²...³...] {²...} {³...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 inherits: \seteazaimpartireafloat 2 BEFEHL 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in {¹...} {²...} [...³...]</code> <div style="display: flex; justify-content: space-around; width: 100px; margin-left: 10px;"><small>OPT</small><small>OPT</small></div> 1 TEXT 2 TEXT 3 REFERENCE
<code>\inalt {...}</code> * CONTENT

<code>\INALT {...}</code> * CONTENT instances: unitshigh
<code>\inclinat</code>
<code>\inclinataldin</code>
<code>\includemenu [...]</code> * NAME
<code>\includeversioninfo {...}</code> * NAME
<code>\increment \...</code> * CSNAME
<code>\incrementcounter [...]¹ [...]²</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 NUMMER
<code>\incrementedcounter [...]</code> * NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> * NAME
<code>\increment cd:parentheses-1</code> * CSNAME NUMBER
<code>\indentation</code>
<code>\index [...]¹ [...+...+...]²</code> <div style="text-align: center;"><small>OPT</small></div> 1 TEXT PROCESSOR->TEXT 2 INDEX
<code>\index [...]¹ {...}² [...+...+...]³</code> <div style="text-align: center;"><small>OPT</small></div> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX

$\backslash\text{indreapta } [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \{\overset{3}{\dots}\}$ <small>OPT OPT</small> 1 <code>referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>
$\backslash\text{infofont}$
$\backslash\text{infofontbold}$
$\backslash\text{inframed } [\dots, \dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ <small>OPT</small> 1 <code>inherits: \setezainconjurat</code> 2 <code>CONTENT</code>
$\backslash\text{inheritparameter } [\overset{1}{\dots}] [\overset{2}{\dots}] [\overset{3}{\dots}]$ 1 <code>TEXT</code> 2 <code>TEXT</code> 3 <code>KEY</code>
$\backslash\text{inhibitblank}$
$\backslash\text{ininner } [\dots, \dots, \overset{1}{\dots}, \dots] [\dots, \dots, \overset{2}{\dots}, \dots] \{\overset{3}{\dots}\}$ <small>OPT OPT</small> 1 <code>referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>inherits: \setupmarginframed</code> 3 <code>CONTENT</code>
$\backslash\text{ininneredge } [\dots, \dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ <small>OPT</small> 1 <code>referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>CONTENT</code>
$\backslash\text{ininnermargin } [\dots, \dots, \overset{1}{\dots}, \dots] \{\overset{2}{\dots}\}$ <small>OPT</small> 1 <code>referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 <code>CONTENT</code>
$\backslash\text{initializeboxstack } \{\overset{*}{\dots}\}$ * <code>NAME</code>
$\backslash\text{injos } [\overset{*}{\dots}]$ * <code>DIMENSION</code>
$\backslash\text{inlinebuffer } [\dots, \overset{*}{\dots}]$ <small>OPT</small> * <code>BUFFER</code>
$\backslash\text{inlinedbox } \{\overset{*}{\dots}\}$ * <code>CONTENT</code>

$\backslash\mathrm{inlinemath}\{...\}$ * CONTENT
$\backslash\mathrm{inlinemathematics}\{...\}$ * CONTENT
$\backslash\mathrm{inlinemessage}\{...\}$ * TEXT
$\backslash\mathrm{inlineordisplaymath}\{...\}^1\{...\}^2$ 1 CONTENT 2 CONTENT
$\backslash\mathrm{inlinerange}\{...\}$ * REFERENCE
$\backslash\mathrm{inlinie}\{...\}^1\{...\}^2$ <small>OPT</small> 1 TEXT 2 REFERENCE
$\backslash\mathrm{inmaframed}\{...\}^1\{...\}^2$ <small>OPT</small> 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{inmargineadreapta}\{...\}^1\{...\}^2$ <small>OPT</small> 1 referinta = REFERENCE inherits: $\backslash\mathrm{setupmargindata}$ 2 CONTENT
$\backslash\mathrm{inmargineastanga}\{...\}^1\{...\}^2$ <small>OPT</small> 1 referinta = REFERENCE inherits: $\backslash\mathrm{setupmargindata}$ 2 CONTENT
$\backslash\mathrm{innerflushshapebox}$
$\backslash\mathrm{inothet}\{...\}^1\{...\}^2\{...\}^3$ <small>OPT</small> <small>OPT</small> 1 referinta = REFERENCE inherits: $\backslash\mathrm{setupmargindata}$ 2 inherits: $\backslash\mathrm{setupmarginframed}$ 3 CONTENT
$\backslash\mathrm{inouter}\{...\}^1\{...\}^2\{...\}^3$ <small>OPT</small> <small>OPT</small> 1 referinta = REFERENCE inherits: $\backslash\mathrm{setupmargindata}$ 2 inherits: $\backslash\mathrm{setupmarginframed}$ 3 CONTENT

<pre> \inouteredge [...,\stackrel{1}{=}\dots] {\stackrel{2}{.}} 1 referinta = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \inoutermargin [...,\stackrel{1}{=}\dots] {\stackrel{2}{.}} 1 referinta = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \inparteadreapta [...,\stackrel{1}{=}\dots] {\stackrel{2}{.}} 1 referinta = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \inparteastanga [...,\stackrel{1}{=}\dots] {\stackrel{2}{.}} 1 referinta = REFERENCE inherits: \setupmargindata 2 CONTENT </pre>
<pre> \input {...} * FILE </pre>
<pre> \inputfilebarename </pre>
<pre> \inputfilename </pre>
<pre> \inputfilerealsuffix </pre>
<pre> \inputfilesuffix </pre>
<pre> \inputgivenfile {...} * FILE </pre>
<pre> \input ... * FILE </pre>
<pre> \insertpages [...]\stackrel{2}{,}\dots\stackrel{3}{,}\dots 1 FILE 2 NUMMER 3 latime = DIMENSION n = NUMMER category = NAME </pre>
<pre> \instalarelimba [...]\stackrel{2}{,}\dots 1 NAME 2 inherits: \setarelimba </pre>
<pre> \instalarelimba [...]\stackrel{2}{,}\dots 1 NAME 2 SPRACHE </pre>

\installactionhandler {...} * NAME
\installactivecharacter ... * CHARACTER
\installanddefineactivecharacter ... ¹ {...} ² 1 CHARACTER 2 BEFEHL
\installattributestack *... * CSNAME
\installautocommandhandler \... ¹ {...} ² \... ³ 1 CSNAME 2 NAME 3 CSNAME
\installautosetuphandler \... ¹ {...} ² 1 CSNAME 2 NAME
\installbasicautosetuphandler \... ¹ {...} ² \... ³ 1 CSNAME 2 NAME 3 CSNAME
\installbasicparameterhandler \... ¹ {...} ² 1 CSNAME 2 NAME
\installbottomframerenderer {... ¹ } {... ² } 1 NAME 2 BEFEHL
\installcommandhandler \... ¹ {...} ² \... ³ 1 CSNAME 2 NAME 3 CSNAME
\installcorenamespace {...} * NAME
\installdefinehandler \... ¹ {...} ² \... ³ 1 CSNAME 2 NAME 3 CSNAME

<pre>\installdefinitionset \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdefinitionsetmember \... {...} \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre> <pre>4 NAME</pre>
<pre>\installdirectcommandhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectparameterhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectparametersethandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectsetuphandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installdirectstyleandcolorhandler \... {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre>
<pre>\installframedautocommandhandler \... {...} \...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installframedcommandhandler \... {...} \...</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 CSNAME</pre>
<pre>\installleftframerenderer {...} {...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\installnamespace {...}</pre> <pre>* NAME</pre>

<pre> \installoutputroutine \... {...} 1 CSNAME 2 BEFEHL </pre>
<pre> \installpagearrangement ... {...} 1 NAME 2 BEFEHL </pre>
<pre> \installparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparameterhashhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparametersethandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installparentinjector \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installrightframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installrootparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installsetuphandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installsetuponlycommandhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installshipoutmethod {...} {...} 1 NAME 2 BEFEHL </pre>

`\installsimplecommandhandler \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installsimpleframedcommandhandler \.^{.} \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installstyleandcolorhandler \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME

`\installswitchcommandhandler \.^{.} \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME
- 3 CSNAME

`\installswitchsetuphandler \.^{.} \.^{.}`

- 1 CSNAME
- 2 NAME

`\installtexdirective \.^{.} \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

`\installtextracker \.^{.} \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

`\installtopframerenderer \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL

`\installunitsseparator \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL

`\installunitsspace \.^{.} \.^{.}`

- 1 NAME
- 2 BEFEHL

<code>\installversioninfo {...} {...}</code> 1 NAME 2 BEFEHL
<code>\instanga [...,\overset{1}{=}{...},...] [...,\overset{2}{=}{...},...] {...}</code> <small>OPT</small> <small>OPT</small> 1 referinta = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT
<code>\integerrounding {...}</code> * NUMMER
<code>\intertext {...}</code> * TEXT
<code>\intins [...,\overset{1}{=}{...},...] {...}</code> <small>OPT</small> 1 inherits: \setupstretched 2 TEXT
<code>\invokepagehandler {...} {...}</code> 1 normal niciunul NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italic</code>
<code>\italicaldin</code>
<code>\italiccorrection</code>
<code>\itemtag [...,*,...]</code> <small>OPT</small> * REFERENCE
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\jos {...}</code> * CONTENT

\backslash jossus [¹ ...] { ² ...} { ³ ...} <small>OPT</small> 1 stanga dreapta 2 CONTENT 3 CONTENT
\backslash JOS {...} * CONTENT instances: unitslow
\backslash Kap {...} * TEXT
\backslash kap {...} * TEXT
\backslash keeplinestogether {...} * NUMMER
\backslash keepunwantedspaces
\backslash kerncharacters [¹ ...] { ² ...} <small>OPT</small> 1 NUMMER 2 TEXT
\backslash koreancirclenumerals {...} * NUMMER
\backslash koreannumerals {...} * NUMMER
\backslash koreannumeralsc {...} * NUMMER
\backslash koreannumeralsp {...} * NUMMER
\backslash koreanparentnumerals {...} * NUMMER
\backslash LAMSTEX
\backslash LATEX
\backslash LamSTeX
\backslash LaTeX

<code>\Litera {...}</code> * NUMMER
<code>\Litere {...}</code> * NUMMER
<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\LUNA {...}</code> * NUMMER
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\la {...} {...} [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> <small>OPT</small> </div> 1 TEXT 2 TEXT 3 REFERENCE
<code>\labellanguage</code>
<code>\ETICHETAlimba</code> instances: antet eticheta mathlabel taglabel unitate operator prefix suffix btxlabel
<code>\labeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\ETICHETAtexts {...} {...}</code> 1 KEY 2 TEXT instances: antet eticheta mathlabel
<code>\languageCharacters {...}</code> * NUMMER
<code>\languagecharacters {...}</code> * NUMMER
<code>\languagecharwidth {...}</code> * SPRACHE

\lapagina [...] * REFERENCE
\lastcounter [...] [¹ ...] [² ...] <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>NUMMER</div> </div>
\lastcountervalue [...] * NAME
\lastdigit {...} * NUMMER
\lastnaturalboxdp
\lastnaturalboxht
\lastnaturalboxwd
\lastpredefinedsymbol
\lastrealpage
\lastrealpagenumber
\lastsubcountervalue [...] [¹ ...] [² ...] <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>NUMMER</div> </div>
\lastsubpagenumber
\lasttwodigits {...} * NUMMER
\lastuserpage
\lastuserpagenumber
\lateluacode {...} * BEFEHL
\latin
\layeredtext [..., ¹ ...,...] [..., ² ...,...] {...} {...} <div> <div>1</div> <div>inherits: \setuplayer</div> </div> <div> <div>2</div> <div>inherits: \setuplayeredtext</div> </div> <div> <div>3</div> <div>TEXT</div> </div> <div> <div>4</div> <div>CONTENT</div> </div>

<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {...} {...} {...} {...}</code> 1 NAME 2 NUMMER 3 NAME 4 CONTENT
<code>\lazysavetwopassdata {...} {...} {...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\lbox ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\leftbottombox {...}</code> * CONTENT
<code>\leftbox {...}</code> * CONTENT
<code>\lefthbox {...}</code> * CONTENT
<code>\leftheadtext {...}</code> * KEY
<code>\leftlabeltext {...}</code> * KEY
<code>\leftETICHETAtext {...}</code> * KEY instances: antet eticheta mathlabel
<code>\leftline {...}</code> * CONTENT
<code>\leftmathlabeltext {...}</code> * KEY
<code>\lefttorrighthbox ...¹ {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT

$\backslash\text{lefttorrightvbox} \overset{.1}{\dots} \{ \overset{.2}{\dots} \}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorrightvtop} \overset{.1}{\dots} \{ \overset{.2}{\dots} \}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{leftskipadaption}$
$\backslash\text{leftsubguillemot}$
$\backslash\text{lefttopbox} \{ \overset{.*}{\dots} \}$ <p>* CONTENT</p>
$\backslash\text{lefttoright}$
$\backslash\text{lefttorighthbox} \overset{.1}{\dots} \{ \overset{.2}{\dots} \}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorightvbox} \overset{.1}{\dots} \{ \overset{.2}{\dots} \}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{lefttorightvtop} \overset{.1}{\dots} \{ \overset{.2}{\dots} \}$ <p>1 TEXT</p> <p>2 CONTENT</p>
$\backslash\text{letbeundefined} \{ \overset{.*}{\dots} \}$ <p>* NAME</p>
$\backslash\text{letcatcodecommand} \overset{.1}{\dots} \overset{.2}{\dots} \overset{.3}{\dots}$ <p>1 CSNAME</p> <p>2 CHARACTER NUMBER</p> <p>3 CSNAME</p>
$\backslash\text{letcscsname} \overset{.1}{\dots} \backslash\text{csname} \overset{.2}{\dots} \backslash\text{endcsname}$ <p>1 CSNAME</p> <p>2 NAME</p>
$\backslash\text{letcsnamecs} \backslash\text{csname} \overset{.1}{\dots} \backslash\text{endcsname} \overset{.2}{\dots}$ <p>1 NAME</p> <p>2 CSNAME</p>
$\backslash\text{letcsnamecsname} \backslash\text{csname} \overset{.1}{\dots} \backslash\text{endcsname} \backslash\text{csname} \overset{.2}{\dots} \backslash\text{endcsname}$ <p>1 NAME</p> <p>2 NAME</p>

<code>\letdummyparameter {...} \...</code> 1 KEY 2 CSNAME
<code>\letempty *...</code> * CSNAME
<code>\letgvalue {...} \...</code> 1 NAME 2 CSNAME
<code>\letgvalueempty {...}</code> * NAME
<code>\letgvalurelax {...}</code> * NAME
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>

<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> $[^{.1}]$ $\{^{.2}\}$ <small>OPT</small> 1 NUMMER 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> $\{^{.1}\}$ $\backslash^{.2}$ 1 NAME 2 CSNAME
<code>\letvalueempty</code> $\{^{.1}\}$ * NAME
<code>\letvaluerelax</code> $\{^{.1}\}$ * NAME
<code>\lfence</code> $\{^{.1}\}$ * CHARACTER
<code>\lhbox</code> $\{^{.1}\}$ * CONTENT
<code>\limba</code> $[^{.1}]$ * SPRACHE
<code>\limbapincipala</code> $[^{.1}]$ * SPRACHE
<code>\LANGUAGE</code>
<code>\limitatelines</code> $\{^{.1}\}$ $\{^{.2}\}$ $\{^{.3}\}$ 1 NUMMER 2 BEFEHL 3 TEXT

<p>\limitatetext {...¹} {...²} {...³}</p> <p>1 TEXT</p> <p>2 [-+]DIMENSION</p> <p>3 BEFEHL</p>
<p>\limitatetext {...¹} {...²,...³} {...³}</p> <p>1 TEXT</p> <p>2 [-+]DIMENSION</p> <p>3 BEFEHL</p>
<p>\limtatefirstline {...¹} {...²} {...³}</p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 BEFEHL</p>
<p>\linenote {...}</p> <p>* TEXT</p>
<p>\LINENOTE {...}</p> <p>* TEXT</p> <p>instances: linenote</p>
<p>\linespanningtext {...¹} {...²} {...³}</p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p>\linie {...}</p> <p>* CONTENT</p>
<p>\linieneagra [...[*]...[*]...]</p> <p><small>OPT</small></p> <p>* inherits: \seteazaliniinegre</p>
<p>\liniepeste {...}</p> <p>* CONTENT</p>
<p>\liniesubtire</p>
<p>\linieumplere [...[*]...[*]...]</p> <p>* inherits: \seteazaliniiumplere</p>
<p>\liniinegre [...[*]...[*]...]</p> <p><small>OPT</small></p> <p>* inherits: \seteazaliniinegre</p>
<p>\liniipeste {...}</p> <p>* CONTENT</p>

\liniisubtiri [...^{*}...]

OPT

* inherits: \seteazaliniesubtire

\listcitation [...¹...²...] [...]

OPT

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx

2 REFERENCE

\listcitation [...¹...] [...²]

OPT

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear

2 REFERENCE

\listcitation [...¹...²...] [...²...]

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx

2 KEY = VALUE

\listcite [...¹...²...] [...]

OPT

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx

2 REFERENCE

\listcite [...¹...] [...²]

OPT

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear

2 REFERENCE

\listcite [...¹...²...] [...²...]

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx

2 KEY = VALUE

\listnamespaces

\litera {...}

* NUMMER

\litere {...} * NUMMER
\llap {...} * CONTENT
\loadanyfile [...] * FILE
\loadanyfileonce [...] * FILE
\loadbtxdefinitionfile [...] * FILE
\loadbtxreplacementfile [...] * FILE
\loadcldfile [...] * FILE
\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [...] ¹ [...] ² 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE

<p><code>\localframed</code> [¹...] [_{OPT}...,...²...,...]² {...}³}</p> <p>1 NAME</p> <p>2 inherits: \seteazainconjurat</p> <p>3 CONTENT</p>
<p><code>\localframedwithsettings</code> [¹...] [_{OPT}...,...²...,...]² {...}³}</p> <p>1 NAME</p> <p>2 inherits: \seteazainconjurat</p> <p>3 CONTENT</p>
<p><code>\localhsize</code></p>
<p><code>\localpopbox</code> ...</p> <p>* CSNAME NUMBER</p>
<p><code>\localpopmacro</code> \...</p> <p>* CSNAME</p>
<p><code>\localpushbox</code> ...</p> <p>* CSNAME NUMBER</p>
<p><code>\localpushmacro</code> \...</p> <p>* CSNAME</p>
<p><code>\localundefine</code> {...}</p> <p>* NAME</p>
<p><code>\locatedfilepath</code></p>
<p><code>\locatefilepath</code> {...}</p> <p>* FILE</p>
<p><code>\locfilename</code> {...}</p> <p>* FILE</p>
<p><code>\logo</code> [_{OPT}...]¹ {...}²}</p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\lomihi</code> {...}¹ {...}² {...}³}</p> <p>1 CONTENT</p> <p>2 CONTENT</p> <p>3 CONTENT</p>
<p><code>\lowerbox</code> {...}¹ \...² {...}³}</p> <p>1 DIMENSION</p> <p>2 CSNAME</p> <p>3 CONTENT</p>

<p><code>\lowercased {...}</code></p> <p>* TEXT</p>
<p><code>\lowercasestring ¹... \to ²...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\lowerlefthdoubleninequote</code></p>
<p><code>\lowerleftsingleninequote</code></p>
<p><code>\lowerrighthdoubleninequote</code></p>
<p><code>\lowerrightsingleninequote</code></p>
<p><code>\LOWHIGH [¹...] {²...} {³...}</code></p> <p><small>OPT</small></p> <p>1 stanga dreapta</p> <p>2 CONTENT</p> <p>3 CONTENT</p>
<p><code>\LOWMIDHIGH {¹...} {²...} {³...}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p> <p>3 CONTENT</p>
<p><code>\lrbbox {¹...} {²...} {³...} {⁴...} {⁵...}</code></p> <p>1 DIMENSION</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 CONTENT</p>
<p><code>\ltop ¹... {²...}</code></p> <p><small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\luacode {...}</code></p> <p>* BEFEHL</p>
<p><code>\luaconditional *...</code></p> <p>* CSNAME</p>
<p><code>\luaenvironment ...</code></p> <p>* FILE</p>
<p><code>\luaexpanded {...}</code></p> <p>* BEFEHL</p>

<code>\luafunction {...}</code> * BEFEHL
<code>\luajitTeX</code>
<code>\luamajorversion</code>
<code>\luaminorversion</code>
<code>\luaparameterset {...} {...}</code> 1 NAME 2 CONTENT
<code>\luasetup {...}</code> * NAME
<code>\luaTeX</code>
<code>\luaversion</code>
<code>\luna {...}</code> * NUMMER
<code>\lungimelista</code>
<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {...}</code> * NUMMER

<code>\MONTHSHORT {...}</code> * NUMBER
<code>\MPanchor {...}</code> * NAME
<code>\MPbetex {...}</code> * NAME
<code>\MPc {...}</code> * NAME
<code>\MPcode {...} {...}</code> <div> <div>OPT</div> <div>1 NAME</div> <div>2 CONTENT</div> </div>
<code>\MPcolor {...}</code> * COLOR
<code>\MPcoloronly {...}</code> * COLOR
<code>\MPcolumn {...}</code> * NAME
<code>\MPd {...}</code> * NAME
<code>\MPdrawing {...}</code> * CONTENT
<code>\MPfontsizehskip {...}</code> * FONT
<code>\MPgetmultipars {...} {...}</code> <div> <div>1 NAME</div> <div>2 NAME</div> </div>
<code>\MPgetmultishape {...} {...}</code> <div> <div>1 NAME</div> <div>2 NAME</div> </div>
<code>\MPgetposboxes {...,¹...} {...²...}</code> <div> <div>1 NAME</div> <div>2 NAME</div> </div>
<code>\MPh {...}</code> * NAME

\MPII
\MPIV
\MPinclusions [¹ ...] { ² ...} { ³ ...} <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1</div> <div>+</div> </div> <div> <div>2</div> <div>NAME</div> </div> <div> <div>3</div> <div>CONTENT</div> </div>
\MPlleftskip {...} <div> <div>*</div> <div>NAME</div> </div>
\MPl1 {...} <div> <div>*</div> <div>NAME</div> </div>
\MPlr {...} <div> <div>*</div> <div>NAME</div> </div>
\MPls {...} <div> <div>*</div> <div>NAME</div> </div>
\MPmenubuttons {...} <div> <div>*</div> <div>NAME</div> </div>
\MPn {...} <div> <div>*</div> <div>NAME</div> </div>
\MPOptions {...} <div> <div>*</div> <div>COLOR</div> </div>
\MPOverlayanchor {...} <div> <div>*</div> <div>NAME</div> </div>
\MPP {...} <div> <div>*</div> <div>NAME</div> </div>
\MPPage {...} <div> <div>*</div> <div>NAME</div> </div>
\MPPardata {...} <div> <div>*</div> <div>NAME</div> </div>
\MPPplus {... ¹ } {... ² } {... ³ } <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>NUMMER</div> </div> <div> <div>3</div> <div>CONTENT</div> </div>

\MPpos {...} * NAME
\MPpositiongraphic {...} {... ¹ ... ² ...} <div> <div></div> <div>OPT</div> </div> 1 NAME 2 KEY = VALUE
\MPposset {...} * NAME
\MPpr {...} * NAME
\MPrawvar {...} {...} 1 NAME 2 KEY
\MPregion {...} * NAME
\MPrest {...} {...} 1 NAME 2 CONTENT
\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPstring {...} * NAME
\MPtext {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME
\MPur {...} * NAME
\MPVI

$\backslash\text{MPv}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 NAME 2 NUMMER 3 CONTENT
$\backslash\text{MPvar}$ $\{.^*\}$ * KEY
$\backslash\text{MPvariable}$ $\{.^*\}$ * KEY
$\backslash\text{MPvv}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 CONTENT
$\backslash\text{MPw}$ $\{.^*\}$ * NAME
$\backslash\text{MPwhd}$ $\{.^*\}$ * NAME
$\backslash\text{MPx}$ $\{.^*\}$ * NAME
$\backslash\text{MPxy}$ $\{.^*\}$ * NAME
$\backslash\text{MPxywhd}$ $\{.^*\}$ * NAME
$\backslash\text{MPy}$ $\{.^*\}$ * NAME
$\backslash\text{m}$ $[\text{OPT}.^1.]$ $\{.^2.\}$ 1 NAME 2 CONTENT
$\backslash\text{maframed}$ $[\text{OPT}.\text{inherits}=.^1.\text{setupmathframed}.\text{CONTENT}]\$ $\{.^2.\}$ 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT
$\backslash\text{makecharacteractive}$... * CHARACTER
$\backslash\text{makerawcommalist}$ $[\text{...}^1,\text{...}]\$ $\text{...}^2.$ 1 BEFEHL 2 CSNAME

<p><code>\makestrutofbox ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\mapfontsize [¹...] [²...]</code></p> <p>1 DIMENSION</p> <p>2 DIMENSION</p>
<p><code>\marcaje (...¹,...) (...²,...) [...³]</code></p> <p>1 POSITION</p> <p>2 POSITION</p> <p>3 REFERENCE</p>
<p><code>\mare ...</code></p> <p>* CHARACTER</p>
<p><code>\marginal [...¹...] [...²...] {...³}</code></p> <p style="text-align: center;">OPT OPT</p> <p>1 referinta = REFERENCE inherits: \setupmargindata</p> <p>2 inherits: \setupmarginframed</p> <p>3 CONTENT</p>
<p><code>\margindata [¹...] [...²...] [...³...] {...⁴}</code></p> <p style="text-align: center;"> OPT OPT</p> <p>1 NAME</p> <p>2 referinta = REFERENCE inherits: \setupmargindata</p> <p>3 inherits: \setupmarginframed</p> <p>4 CONTENT</p>
<p><code>\MARGINDATA [...¹...] [...²...] {...³}</code></p> <p style="text-align: center;"> OPT OPT</p> <p>1 referinta = REFERENCE inherits: \setupmargindata</p> <p>2 inherits: \setupmarginframed</p> <p>3 CONTENT</p> <p>instances: inmargin eastanga inmargin eadreapta inoutermargin ininnermargin inpart eastanga inpart eadreapta inouteredge ininneredge atleftmargin atrightmargin instanga indreapta inouter ininner inmargin inother textmarginal</p>
<p><code>\markcontent [¹...] {...²}</code></p> <p style="text-align: center;"> OPT</p> <p>1 reset tot NAME</p> <p>2 CONTENT</p>
<p><code>\markinjector [...]</code></p> <p>* NAME</p>
<p><code>\mat {...}</code></p> <p>* CONTENT</p>

$\backslash\mathrm{matematica}$ [¹ ...] { ² ...} <small>OPT</small> 1 NAME 2 CONTENT
$\backslash\mathrm{math}$ [¹ ...] { ² ...} <small>OPT</small> 1 NAME 2 CONTENT
$\backslash\mathrm{mathbf}$
$\backslash\mathrm{mathbi}$
$\backslash\mathrm{mathblackboard}$
$\backslash\mathrm{mathbs}$
$\backslash\mathrm{mathcommand}$ {...} * NAME
$\backslash\mathrm{MATHCOMMAND}$ { ¹ ...} { ² ...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathdefault}$
$\backslash\mathrm{MATHDOUBLEEXTENSIBLE}$ {...} * TEXT
$\backslash\mathrm{MATHEXTENSIBLE}$ [¹ ...] { ² ...} { ³ ...} <small>OPT</small> <small>OPT</small> <small>OPT</small> 1 reverse matematica text chemistry 2 TEXT 3 TEXT
$\backslash\mathrm{mathfraktur}$
$\backslash\mathrm{MATHFRAMED}$ [... ¹ ... ¹ ...] { ² ...} <small>OPT</small> 1 inherits: \setupmathframed 2 CONTENT instances: mframed inmframed mcframed
$\backslash\mathrm{mathfunction}$ {...} * CONTENT
$\backslash\mathrm{mathit}$
$\backslash\mathrm{mathitalic}$
$\backslash\mathrm{mathlabellanguage}$

$\backslash\mathrm{mathlabeltext}\{...\}$ * KEY
$\backslash\mathrm{mathlabeltexts}\{...\}\{...\}$ 1 KEY 2 TEXT
$\backslash\mathrm{mathop}\{...\}$ * CONTENT
$\backslash\mathrm{MATHORNAMENT}\{...\}$ * CONTENT
$\backslash\mathrm{MATHOVEREXTENSIBLE}\{...\}$ * TEXT
$\backslash\mathrm{MATHOVERTEXTTEXTENSIBLE}\{...\}\{...\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{MATHRADICAL}\left[...\right]\{...\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\mathrm{mathrm}$
$\backslash\mathrm{mathscript}$
$\backslash\mathrm{mathsl}$
$\backslash\mathrm{mathss}$
$\backslash\mathrm{mathtext}\overset{1}{...}\{...\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathtextbf}\overset{1}{...}\{...\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathtextbi}\overset{1}{...}\{...\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathtextbs}\overset{1}{...}\{...\}$ <small>OPT</small> 1 TEXT 2 TEXT

$\backslash\mathtextit$ $\overset{1}{\dots}\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathtextsl$ $\overset{1}{\dots}\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathtexttf$ $\overset{1}{\dots}\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathttf$
$\backslash\mathtripl$ $\overset{1}{[\dots]}\{\overset{2}{\dots}\}\{\overset{3}{\dots}\}\{\overset{4}{\dots}\}$ <small>OPT OPT OPT OPT</small> 1 NAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtriplet$ $\overset{1}{[\dots]}\{\overset{2}{\dots}\}\{\overset{3}{\dots}\}\{\overset{4}{\dots}\}$ <small>OPT OPT OPT OPT</small> 1 NAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtriplet$ $\overset{1}{[\dots]}\{\overset{2}{\dots}\}\{\overset{3}{\dots}\}\{\overset{4}{\dots}\}$ <small>OPT OPT OPT OPT</small> 1 NAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\mathtripl$
$\backslash\mathunderextensible$ $\{.\overset{*}{\dots}\}$ * TEXT
$\backslash\mathunderextextensible$ $\{.\overset{1}{\dots}\}\{\overset{2}{\dots}\}$ 1 TEXT 2 TEXT
$\backslash\mathunstacked$
$\backslash\mathupright$
$\backslash\mathword$ $\overset{1}{\dots}\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathwordbf$ $\overset{1}{\dots}\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 TEXT

$\backslash\mathrm{mathwordbi} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathwordbs} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathwordit} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathwordsl} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{mathwordtf} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{maxaligned} \{...\}$ * CONTENT
$\backslash\mathrm{mbox} \{...\}$ * CONTENT
$\backslash\mathrm{mcframed} [...,\overset{1}{...},...] \{\overset{2}{...}\}$ <small>OPT</small> 1 inherits: $\backslash\mathrm{setupmathframed}$ 2 CONTENT
$\backslash\mathrm{measure} \{...\}$ * NAME
$\backslash\mathrm{measured} \{...\}$ * NAME
$\backslash\mathrm{mediu} [...]$ * FILE
$\backslash\mathrm{mediu} ...$ * FILE
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$

$\backslash\text{menuinteractiune}$ [¹ ...] [\dots ,... ² ...] <small>OPT</small> 1 NAME 2 inherits: \seteazamenuinteractiune
$\backslash\text{mequal}$ { ¹ ...} { ² ...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{message}$ {.*} * TEXT
$\backslash\text{metaTeX}$
$\backslash\text{mfence}$ {.*} * CHARACTER
$\backslash\text{mfunction}$ {.*} * CONTENT
$\backslash\text{mfunctionlabeltext}$ {.*} * NAME
$\backslash\text{mhbox}$ {.*} * CONTENT
$\backslash\text{mhookleftarrow}$ { ¹ ...} { ² ...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mhookrightarrow}$ { ¹ ...} { ² ...} <small>OPT</small> <small>OPT</small> 1 TEXT 2 TEXT
$\backslash\text{mic}$
$\backslash\text{micaldin}$
$\backslash\text{micaldininclinat}$
$\backslash\text{micinclinat}$
$\backslash\text{micinclinataldin}$
$\backslash\text{micitalicaldin}$
$\backslash\text{micnormal}$
$\backslash\text{mictype}$

$\backslash\mathrm{middlealigned}\{...\}$ * CONTENT
$\backslash\mathrm{middlebox}\{...\}$ * CONTENT
$\backslash\mathrm{midhbox}\{...\}$ * CONTENT
$\backslash\mathrm{minicitat}\overset{1}{[...]}{\overset{2}{\{...\}}}$ 1 SPRACHE 2 CONTENT
$\backslash\mathrm{minimalhbox}\overset{1}{...}{\overset{2}{\{...\}}}$ 1 TEXT 2 CONTENT
$\backslash\mathrm{mixedcaps}\{...\}$ * TEXT
$\backslash\mathrm{mkvibuffer}\overset{*}{[...]}$ * BUFFER
$\backslash\mathrm{mLeftarrow}\overset{1}{\{...\}}{\overset{2}{\{...\}}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mLeftrightarrow}\overset{1}{\{...\}}{\overset{2}{\{...\}}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mleftarrow}\overset{1}{\{...\}}{\overset{2}{\{...\}}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mleftharpoondown}\overset{1}{\{...\}}{\overset{2}{\{...\}}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mleftharpoonup}\overset{1}{\{...\}}{\overset{2}{\{...\}}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mleftrightharpoonup}\overset{1}{\{...\}}{\overset{2}{\{...\}}}$ 1 TEXT 2 TEXT

\mleftrightharpoons $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mmapsto $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\moduleparameter $\{...\}^1 \{...\}^2$ 1 FILE 2 KEY
\molecule $\{...\}^*$ * CONTENT
\mono
\monoaldin
\mononormal
\monthlong $\{...\}^*$ * NUMMER
\monthshort $\{...\}^*$ * NUMMER
\mprandomnumber
\mRrightarrow $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrel $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrightarrow $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrightharpoondown $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrightharpoonup $\{...\}^1 \{...\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT

$\backslash\mathrm{mrightharpoonleft}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mrightharpoonoverleftarrow}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mtext}\{.*\}$ <div> <div>* CONTENT</div> </div>
$\backslash\mathrm{mtriplelrel}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mtwoheadleftarrow}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{mtwoheadrightarrow}\{\dots\}\{\dots\}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\backslash\mathrm{NormalizeFontHeight}\backslash\dots\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 CSNAME</div> <div>2 TEXT</div> <div>3 DIMENSION</div> <div>4 FONT</div> </div>
$\backslash\mathrm{NormalizeFontWidth}\backslash\dots\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 CSNAME</div> <div>2 TEXT</div> <div>3 DIMENSION</div> <div>4 FONT</div> </div>
$\backslash\mathrm{NormalizeTextHeight}\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 FONT</div> <div>2 DIMENSION</div> <div>3 TEXT</div> </div>
$\backslash\mathrm{NormalizeTextWidth}\{\dots\}\{\dots\}\{\dots\}$ <div> <div>1 FONT</div> <div>2 DIMENSION</div> <div>3 TEXT</div> </div>
$\backslash\mathrm{Numere}\{.*\}$ <div> <div>* NUMMER</div> </div>

<code>\Numereromane {...}</code> * NUMMER
<code>\namedheadnumber {...}</code> * ABSCHNITT
<code>\namedstructureheadlocation {...}</code> * ABSCHNITT
<code>\namedstructureuservariable {...} {...}</code> 1 ABSCHNITT 2 KEY
<code>\namedstructurevariable {...} {...}</code> 1 ABSCHNITT 2 KEY
<code>\namedtaggedlabeltexts {...} {...} {...} {...} {...}</code> 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
<code>\naturalhbox ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalhpack ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalvbox ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalvcenter ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalvpack ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalvtop ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT

<p><code>\naturalwd ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\necunoscut</code></p>
<p><code>\negatecolorbox ...</code></p> <p>* CSNAME NUMBER</p>
<p><code>\negated {...}</code></p> <p>* TEXT</p>
<p><code>\negthinspace</code></p>
<p><code>\newattribute \...</code></p> <p>* CSNAME</p>
<p><code>\newcatcodetable \...</code></p> <p>* CSNAME</p>
<p><code>\newcounter \...</code></p> <p>* CSNAME</p>
<p><code>\newevery \¹... \²...</code></p> <p>1 CSNAME</p> <p>2 CSNAME</p>
<p><code>\newfrenchspacing</code></p>
<p><code>\newmode {...}</code></p> <p>* NAME</p>
<p><code>\newsignal \...</code></p> <p>* CSNAME</p>
<p><code>\newsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\nextbox</code></p>
<p><code>\nextboxdp</code></p>
<p><code>\nextboxht</code></p>
<p><code>\nextboxhtdp</code></p>
<p><code>\nextboxwd</code></p>

<code>\nextcounter [...]</code> ¹ <code>[...]</code> ² <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>NUMMER</div> </div> <div>OPT</div>
<code>\nextcountervalue [...]</code> <div> <div>*</div> <div>NAME</div> </div>
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\urmatorulPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]</code> ¹ <code>[...]</code> ² <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>NUMMER</div> </div>
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nihongo</code>
<code>\nobar {...}</code> <div> <div>*</div> <div>CONTENT</div> </div>
<code>\nocitation [...]</code> <div> <div>*</div> <div>REFERENCE</div> </div>
<code>\nocitation {...}</code> <div> <div>*</div> <div>REFERENCE</div> </div>
<code>\nocite [...]</code> <div> <div>*</div> <div>REFERENCE</div> </div>
<code>\nocite {...}</code> <div> <div>*</div> <div>REFERENCE</div> </div>
<code>\nodetostring \... {...}</code> ¹ ² <div> <div>1</div> <div>CSNAME</div> </div> <div> <div>2</div> <div>CONTENT</div> </div>
<code>\nofigurepages</code>

<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {...}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> * CONTENT
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,\u005Cseteazainconjurat {...}</code> 1 inherits: \seteazainconjurat 2 CONTENT
<code>\normalizebodyfontsize \¹... {\²...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \¹... {\²...} {\³...} {\⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \¹... {\²...} {\³...} {\⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontline \¹... {\²...} {\³...} {\⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT

`\normalizefontwidth \...1 {...}2 {...}3 {...}4`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizetextdepth {...}1 {...}2 {...}3`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextheight {...}1 {...}2 {...}3`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextline {...}1 {...}2 {...}3`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {...}1 {...}2 {...}3`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normaltypeface`

`\nota [...]1 [...]2`
OPT

- 1 NAME
- 2 REFERENCE

`\notasubsol [...]1, [...]2`
OPT

- 1 REFERENCE
- 2 TEXT

`\notasubsol [...]*, [...]*`

***** `titlu` = TEXT
 `semncarte` = TEXT
 `lista` = TEXT
 `referinta` = REFERENCE

`\NOTE [...]1, [...]2`
OPT

- 1 REFERENCE
- 2 TEXT

`instances: notasubsol endnote`

<p><code>\NOTE [...,*...]</code></p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p> <p>instances: notasubsol endnote</p>
<p><code>\notesymbol [...¹.] [...².]</code></p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\notragged</code></p>
<p><code>\ntimes {...} {...}</code></p> <p>1 TEXT</p> <p>2 NUMMER</p>
<p><code>\numarformula [...,*...]</code></p> <p style="text-align: center;">OPT</p> <p>* REFERENCE</p>
<p><code>\numarpagina</code></p>
<p><code>\numartitlu [...¹.] [...².]</code></p> <p style="text-align: center;">OPT</p> <p>1 ABSCHNITT</p> <p>2 precedent curent urmatorul primul ultim</p>
<p><code>\numartitlucurent</code></p>
<p><code>\numberofpoints {...}</code></p> <p>* DIMENSION</p>
<p><code>\numere {...}</code></p> <p>* NUMMER</p>
<p><code>\numereromane {...}</code></p> <p>* NUMMER</p>
<p><code>\obeydepth</code></p>
<p><code>\objectdepth</code></p>
<p><code>\objectheight</code></p>
<p><code>\objectmargin</code></p>
<p><code>\objectwidth</code></p>
<p><code>\obox {...}</code></p> <p>* CONTENT</p>

<p><code>\offset [...,..¹...,...] {...}</code> <small>OPT</small></p> <p>1 inherits: \setupoffset</p> <p>2 CONTENT</p>
<p><code>\offsetbox [...,..¹...,...] \.² {...}</code> <small>OPT</small></p> <p>1 inherits: \setupoffsetbox</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\olinie [...]</code></p> <p>* REFERENCE</p>
<p><code>\onedigitrounding {...}</code></p> <p>* NUMMER</p>
<p><code>\operatorlanguage</code></p>
<p><code>\operatorortext {...}</code></p> <p>* KEY</p>
<p><code>\ordinaldaynumber {...}</code></p> <p>* NUMMER</p>
<p><code>\ordinalstr {...}</code></p> <p>* TEXT</p>
<p><code>\ornamenttext [...,..¹...,...] [...,..²...,...] {...³} {...⁴}</code> <small>OPT</small></p> <p>1 alternativ = a b inherits: \setupcollector</p> <p>2 stil = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p><code>\ornamenttext [...¹] {...²} {...³}</code></p> <p>1 NAME</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\ornamenttext [...,..¹...,...] [...,..²...,...] {...³} {...⁴}</code> <small>OPT</small></p> <p>1 alternativ = a b inherits: \setuplayer</p> <p>2 inherits: \setuplayeredtext</p> <p>3 TEXT</p> <p>4 CONTENT</p>

$\backslash ORNAMENT \{...\} \{...\}$ 1 TEXT 2 CONTENT
$\backslash outputfilename$
$\backslash outputstreambox [...]$ * NAME
$\backslash outputstreamcopy [...]$ * NAME
$\backslash outputstreamunvbox [...]$ * NAME
$\backslash outputstreamunvcopy [...]$ * NAME
$\backslash over [...]$ * REFERENCE
$\backslash overbartext \{...\} \{...\}$ 1 TEXT 2 TEXT
$\backslash overbarunderbar \{...\}$ * TEXT
$\backslash overbrace \{...\}$ * TEXT
$\backslash overbracetext \{...\} \{...\}$ 1 TEXT 2 TEXT
$\backslash overbraceunderbrace \{...\}$ * TEXT
$\backslash overbracket \{...\}$ * TEXT
$\backslash overbrackettext \{...\} \{...\}$ 1 TEXT 2 TEXT
$\backslash overbracketunderbracket \{...\}$ * TEXT

<code>\overlaybutton [...]</code> * REFERENCE
<code>\overlaybutton {...}</code> * REFERENCE
<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...¹] [...²]</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overleftarrow {...}</code> * TEXT
<code>\overleftharpoontdown {...}</code> * TEXT
<code>\overleftharpoonup {...}</code> * TEXT
<code>\overleftrightarrow {...}</code> * TEXT
<code>\overloaderror</code>
<code>\overparent {...}</code> * TEXT
<code>\overparenttext {...¹} {...²}</code> 1 TEXT 2 TEXT

\overparentunderparent {...} * TEXT
\overrightarrow {...} * TEXT
$\overrightarrow{\text{harpoon}}\downarrow$ {...} * TEXT
$\overrightarrow{\text{harpoon}}\uparrow$ {...} * TEXT
$\overset{.1.}{.2.}$ {...} 1 TEXT 2 TEXT
\overleftrightarrow {...} * TEXT
\overleftrightarrow {...} * TEXT
\textcolor {...} * NAME
PDFETEX
PDFTEX
PCTEX
PicTeX
PointsToBigPoints {...} \^2.. 1 DIMENSION 2 CSNAME
PointsToReal {...} \^2.. 1 DIMENSION 2 CSNAME
$\text{PointsToWholeBigPoints}$ {...} \^2.. 1 DIMENSION 2 CSNAME
PPCHTEX
PPCHTeX

<code>\PRAGMA</code>
<code>\PtToCm {...}</code> <code>* DIMENSION</code>
<code>\pagearea [...] [...] [...]</code> <div style="text-align: center;"><small>OPT OPT</small></div> <code>1 sus antet text subsol subsol</code> <code>2 text margine bordura</code> <code>3 stanga dreapta lefttext middletext righttext</code>
<code>\pagebreak [...;...]</code> <div style="text-align: center;"><small>OPT</small></div> <code>* gol antet subsol dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare</code> <code> stanga dreapta par impar cvadрупul ultim ultimpagina start stop NAME</code>
<code>\pagefigure [...] [...;...]</code> <div style="text-align: center;"><small> ²</small></div> <div style="text-align: center;"><small> OPT</small></div> <code>1 FILE</code> <code>2 inherits: \setupexternalfigure</code>
<code>\pagegridspanwidth {...}</code> <code>* NUMMER</code>
<code>\pageinjection [...] [...;...]</code> <div style="text-align: center;"><small> ²</small></div> <div style="text-align: center;"><small> OPT OPT</small></div> <code>1 NAME</code> <code>2 KEY = VALUE</code>
<code>\pageinjection [...;...;...] [...;...;...]</code> <div style="text-align: center;"><small> ¹</small></div> <div style="text-align: center;"><small> OPT OPT</small></div> <code>1 inherits: \setuppageinjection</code> <code>2 KEY = VALUE</code>
<code>\pagestaterealpage {...} {...}</code> <div style="text-align: center;"><small> ²</small></div> <code>1 NAME</code> <code>2 NAME NUMMER</code>
<code>\pagina [...;...]</code> <div style="text-align: center;"><small> OPT</small></div> <code>* inherits: \pagebreak</code>
<code>\paletsize</code>
<code>\PARAGRAPHS</code>
<code>\parte [...;...] {...}</code> <div style="text-align: center;"><small> ¹</small></div> <div style="text-align: center;"><small> OPT</small></div> <code>1 REFERENCE</code> <code>2 TEXT</code>
<code>\pastreazablocuri [...;...] [...;...]</code> <div style="text-align: center;"><small> ²</small></div> <div style="text-align: center;"><small> OPT</small></div> <code>1 NAME</code> <code>2 + -</code>

<p><code>\pdfactualtext {...} {...}</code></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendactualtext {...} {...}</code></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendcurrentresources</code></p>
<p><code>\pdfbackendsetcatalog {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetcolorspace {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsettextgstate {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetinfo {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>

<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>
<p><code>\pelung {...}</code></p> <p>* NAME</p>
<p><code>\percent</code></p>
<p><code>\percentdimen {...} {...}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMMER</p>
<p><code>\permitcaretescape</code></p>
<p><code>\permitcircumflexescape</code></p>
<p><code>\permitspacesbetweenegroups</code></p>
<p><code>\persiandecimals {...}</code></p> <p>* NUMMER</p>
<p><code>\persiannumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\phantom {...}</code></p> <p>* CONTENT</p>
<p><code>\phantombox [...,...*...,...]</code></p> <p>* latime = DIMENSION</p> <p>inaltime = DIMENSION</p> <p>inaltime = DIMENSION</p>
<p><code>\pickupgroupedcommand {...} {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p>
<p><code>\placeattachments</code></p>

<p><code>\placebtxrendering</code> $\overset{1}{[...]} \overset{2}{[...,...]}$</p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placecitation</code> [...]</p> <p>* REFERENCE</p>
<p><code>\placecomments</code></p>
<p><code>\placecontent</code> $\overset{*}{[...,...]}$</p> <p>* inherits: \seteeazalista</p>
<p><code>\placecurrentformulanumber</code></p>
<p><code>\placedbox</code> {...}</p> <p>* CONTENT</p>
<p><code>\placefloat</code> $\overset{1}{[...]} \overset{2}{[...,...]} \overset{3}{[...,...]} \overset{4}{\{...\}} \overset{5}{\{...\}}$</p> <p>1 SINGULAR</p> <p>2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placefloatwithsetups</code> $\overset{1}{[...]} \overset{2}{[...,...]} \overset{3}{[...,...]} \overset{4}{\{...\}} \overset{5}{\{...\}}$</p> <p>1 NAME</p> <p>2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\puneFLOAT</code> $\overset{1}{[...,...]} \overset{2}{[...,...]} \overset{3}{\{...\}} \overset{4}{\{...\}}$</p> <p>1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p> <p>instances: chemical figure table intermezzo graphic</p>

<p><code>\placeframed</code> [¹...] [²..._{OPT}] {...³}</p> <p>1 NAME</p> <p>2 inherits: \seteazainconjurat</p> <p>3 CONTENT</p>
<p><code>\placeheadnumber</code> [...]</p> <p>* ABSCHNITT</p>
<p><code>\placeheadtext</code> [...]</p> <p>* ABSCHNITT</p>
<p><code>\placehelp</code></p>
<p><code>\placeindex</code> [...[*]..._{OPT}]</p> <p>* inherits: \seteazaregistru</p>
<p><code>\placeinitial</code> [..._{OPT}]</p> <p>* NAME</p>
<p><code>\placelayer</code> [...]</p> <p>* NAME</p>
<p><code>\placelayeredtext</code> [¹] [...²..._{OPT}] [...³..._{OPT}] {...⁴} {...⁵}</p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placelistofabbreviations</code> [...[*]..._{OPT}]</p> <p>* inherits: \seteazasinonime</p>
<p><code>\placelistofFLOATS</code> [...[*]..._{OPT}]</p> <p>* inherits: \seteazalista</p>
<p><code>\placelistoflogos</code> [...[*]..._{OPT}]</p> <p>* inherits: \seteazasortare</p>
<p><code>\placelistofpublications</code> [...¹...] [...²..._{OPT}]</p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placelistofsorts</code> [...¹] [...²..._{OPT}]</p> <p>1 SINGULAR</p> <p>2 inherits: \seteazasortare</p>

<p><code>\placelistofSORTS [...,\overset{*}{=}\dots]</code> <small>OPT</small></p> <p>* inherits: \seteazasortare</p> <p>instances: logos</p>
<p><code>\placelistofsynonyms [...]\dots\overset{2}{=}\dots]</code> <small>OPT</small></p> <p>1 SINGULAR</p> <p>2 inherits: \seteazasinonime</p>
<p><code>\placelistofSYNONYMS [...,\overset{*}{=}\dots]</code> <small>OPT</small></p> <p>* inherits: \seteazasinonime</p> <p>instances: abrevieri</p>
<p><code>\placelocalnotes [...]\dots\overset{2}{=}\dots]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p><code>\placement [...]\dots\overset{2}{=}\dots]{\dots}</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupplacement</p> <p>3 CONTENT</p>
<p><code>\PLACEMENT [...,\overset{1}{=}\dots]{\dots}</code> <small>OPT</small></p> <p>1 inherits: \setupplacement</p> <p>2 CONTENT</p>
<p><code>\placenamefloat [...]\dots]</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\placenameformula [...,\overset{1}{=}\dots]{\dots}</code> <small>OPT</small></p> <p>1 + - REFERENCE</p> <p>2 TEXT</p>
<p><code>\placenotes [...,\overset{1}{=}\dots]\dots\overset{2}{=}\dots]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p><code>\placepairedbox [...]\dots\overset{2}{=}\dots]{\dots}{\dots}</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>

<p><code>\punePAIREDBOX [...,¹...,^{OPT}...] {...} {...}</code></p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances: legenda</p>
<p><code>\placeparallel [...,¹] [...,²,...] [...,³...,^{OPT}...]</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p><code>\placerawlist [...,¹] [...,²...,^{OPT}...]</code></p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>
<p><code>\placereadingwindow [...,¹] [...,²...]^{OPT}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\plaseazapegid [...,¹] {...,²...}^{OPT}</code></p> <p>1 normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME</p> <p>2 CONTENT</p>
<p><code>\plaseazapegid [...,¹...,^{OPT}...] {...,²...}</code></p> <p>1 inherits: \definegridsnapping</p> <p>2 CONTENT</p>
<p><code>\plaseazasemnecarte [...,¹...,^{OPT}...] [...,²...,^{OPT}...] [...,³...,^{OPT}...,^{OPT}...]</code></p> <p>1 ABSCHNITT LISTE</p> <p>2 ABSCHNITT LISTE</p> <p>3 inherits: \setupbookmark</p>
<p><code>\popattribute *...</code></p> <p>* CSNAME</p>
<p><code>\popmacro *...</code></p> <p>* CSNAME</p>
<p><code>\popmode [...,¹...]</code></p> <p>* NAME</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>

<p><code>\positionregionoverlay {¹...} {²...}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\postponenotes</code></p>
<p><code>\potrivestecamp [...]¹ [...,²...,...]_{OPT}</code></p> <p>1 NAME</p> <p>2 inherits: \setupfieldbody</p>
<p><code>\pozitie [...,¹...,...] (...,²...) {³...}_{OPT}</code></p> <p>1 inherits: \setarepozitie</p> <p>2 POSITION</p> <p>3 CONTENT</p>
<p><code>\predefinedfont [...]</code></p> <p>* FONT</p>
<p><code>\predefinefont [¹...] [²...]</code></p> <p>1 NAME</p> <p>2 FONT</p>
<p><code>\predefinesymbol [...]</code></p> <p>* NAME</p>
<p><code>\prefixedpagenumber</code></p>
<p><code>\prefixlanguage</code></p>
<p><code>\prefixtext {[*]...}</code></p> <p>* KEY</p>
<p><code>\prependetoks ¹... \to \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\prependgvalue {¹...} {²...}</code></p> <p>1 NAME</p> <p>2 BEFEHL</p>
<p><code>\prependtocommalist {¹...} \²...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\prependtoks ¹... \to \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>

<pre>\prependtoksonce ¹... \to \²...</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\prependvalue {\¹...} {\²...}</pre> <pre>1 NAME</pre> <pre>2 BEFEHL</pre>
<pre>\presetbtxlabeltext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presetdocument [...[*]...]</pre> <pre>* inherits: \setupdocument</pre>
<pre>\presetfieldsymbols [...[*]...]</pre> <pre>* NAME</pre>
<pre>\presetheadtext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presetlabeltext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presetETICHETAtext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre> <pre>instances: antet eticheta mathlabel taglabel unitate operator prefix suffix btxlabel</pre>
<pre>\presetmathlabeltext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presetoperatortext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presetprefixtext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\presettaglabeltext [¹...] [²..._{OPT}...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>

<pre>\presetunittext [...] [¹...]_{OPT} [²...=>...]</pre> <pre>1 SPRACHE</pre> <pre>2 KEY = VALUE</pre>
<pre>\pretocommalist {...} \¹...²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\prevcounter [...] [¹...]_{OPT} [²...]</pre> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\prevcountervalue [...]</pre> <pre>* NAME</pre>
<pre>\preventmode [...,*...]</pre> <pre>* NAME</pre>
<pre>\prevrealpage</pre>
<pre>\prevrealpagenumber</pre>
<pre>\prevsubcountervalue [¹...]_{OPT} [²...]</pre> <pre>1 NAME</pre> <pre>2 NUMMER</pre>
<pre>\prevsubpage</pre>
<pre>\prevsubpagenumber</pre>
<pre>\prevuserpage</pre>
<pre>\prevuserpagenumber</pre>
<pre>\primasubpagina</pre>
<pre>\procent</pre>
<pre>\proceseazabloc [...,¹...]_{OPT} [...,²...]_{OPT} [...,³...=>...]_{OPT}</pre> <pre>1 NAME</pre> <pre>2 + -</pre> <pre>3 criteriu = text ABSCHNITT</pre>
<pre>\processaction [¹...]_{OPT} [...,²...=>...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>

<pre>\processallactionsinset [...¹] [...²=>...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>
<pre>\processassignlist [...¹,...] \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processassignmentcommand [...¹,...] \...²</pre> <pre>1 KEY = VALUE</pre> <pre>2 CSNAME</pre>
<pre>\processassignmentlist [...¹,...] \...²</pre> <pre>1 KEY = VALUE</pre> <pre>2 CSNAME</pre>
<pre>\processbetween {...¹} \...²</pre> <pre>1 NAME</pre> <pre>2 CSNAME</pre>
<pre>\processbodyfontenvironmentlist \...[*]</pre> <pre>* CSNAME</pre>
<pre>\processcolorcomponents {...[*]}</pre> <pre>* COLOR</pre>
<pre>\processcommacommand [...¹,...] \...²</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\processcommalist [...¹,...] \...²</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\processcommalistwithparameters [...¹,...] \...²</pre> <pre>1 BEFEHL</pre> <pre>2 CSNAME</pre>
<pre>\processcontent {...¹} \...²</pre> <pre>1 NAME</pre> <pre>2 CSNAME</pre>
<pre>\processfile {...[*]}</pre> <pre>* FILE</pre>
<pre>\processfilemany {...[*]}</pre> <pre>* FILE</pre>

<pre>\processfilenone {...}</pre> <pre>* FILE</pre>
<pre>\processfileonce {...}</pre> <pre>* FILE</pre>
<pre>\processfirstactioninset [...]¹ [...,²...=>...]</pre> <pre>1 BEFEHL</pre> <pre>2 APPLY</pre>
<pre>\processisolatedchars {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processisolatedwords {...}¹ \...²</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\processlinetablebuffer [...]^{OPT}</pre> <pre>* BUFFER</pre>
<pre>\processlinetablefile {...}</pre> <pre>* FILE</pre>
<pre>\processlist {...}¹ {...}² {...}³ \...⁴</pre> <pre>1 CHARACTER</pre> <pre>2 CHARACTER</pre> <pre>3 TEXT</pre> <pre>4 CSNAME</pre>
<pre>\processMPbuffer [...]^{OPT}</pre> <pre>* NAME</pre>
<pre>\processMPfigurefile {...}</pre> <pre>* FILE</pre>
<pre>\processmonth {...}¹ {...}² {...}³</pre> <pre>1 NUMMER</pre> <pre>2 NUMMER</pre> <pre>3 BEFEHL</pre>
<pre>\processranges [...]¹,...²</pre> <pre>1 NUMMER NUMMER:NUMMER</pre> <pre>2 CSNAME</pre>

<p><code>\processseparatedlist [...]¹ [...]² {...}³</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME BEFEHL</p>
<p><code>\processTeXbuffer [...]^{OPT}</code></p> <p>* BUFFER</p>
<p><code>\processtokens {...}¹ {...}² {...}³ {...}⁴ {...}⁵</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p> <p>4 BEFEHL</p> <p>5 TEXT</p>
<p><code>\processuntil *..</code></p> <p>* CSNAME</p>
<p><code>\processxtablebuffer [...]^{OPT}</code></p> <p>* NAME</p>
<p><code>\processyear {...}¹ {...}² {...}³ {...}⁴</code></p> <p>1 NUMMER</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p> <p>4 BEFEHL</p>
<p><code>\produs [...]</code></p> <p>* FILE</p>
<p><code>\produs ...</code></p> <p>* FILE</p>
<p><code>\profiledbox [...]¹ [...,...²...,...]^{OPT} {...}³</code></p> <p>1 niciunul fixat strict halffixed quarterfixed eightsfixed NAME</p> <p>2 inherits: \setupprofile</p> <p>3 CONTENT</p>
<p><code>\profilegivenbox {...}¹ ...²</code></p> <p>1 niciunul fixat strict halffixed quarterfixed eightsfixed NAME</p> <p>2 CSNAME NUMMER</p>
<p><code>\program [...]</code></p> <p>* NAME</p>
<p><code>\proiect [...]</code></p> <p>* FILE</p>

<p>\proiect .*.</p> <p>* FILE</p>
<p>\pseudoMixedCapped {...}</p> <p>* TEXT</p>
<p>\pseudoSmallCapped {...}</p> <p>* TEXT</p>
<p>\pseudoSmallcapped {...}</p> <p>* TEXT</p>
<p>\pseudosmallcapped {...}</p> <p>* TEXT</p>
<p>\punct {...}</p> <p>* CHARACTER</p>
<p>\puncte [...] OPT</p> <p>* NUMMER</p>
<p>\puncte [...[*]...] OPT</p> <p>* inherits: \setupperiods</p>
<p>\punedeasuprafiecareia {...¹} {...²}</p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p>\punefatainfata {...¹} {...²}</p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p>\puneformula [...[*]...] OPT</p> <p>* + - REFERENCE</p>
<p>\punelegenda [...¹...] {...²} {...³} OPT</p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p>
<p>\punelista [...¹...] [...²...] OPT</p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>
<p>\punelistacombinata [...¹] [...²...] OPT</p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>

<p><code>\puneCOMBINEDLIST [...,..[*]...]</code> <small>OPT</small></p> <p>* inherits: \seteazalista</p> <p>instances: cuprins</p>
<p><code>\punenotesubsol [...,..[*]...]</code> <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p><code>\punenotesubsollocale [...,..[*]...]</code> <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p><code>\punenumarpagina</code></p>
<p><code>\puneregistru [...]¹ [...,..²...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \seteazaregistru</p>
<p><code>\puneREGISTRU [...,..[*]...]</code> <small>OPT</small></p> <p>* inherits: \seteazaregistru</p> <p>instances: index</p>
<p><code>\punesubformula [...,[*]...]</code> <small>OPT</small></p> <p>* + - REFERENCE</p>
<p><code>\purenumber {...}</code></p> <p>* NUMMER</p>
<p><code>\pusharrangedpages ... \poparrangedpages</code></p>
<p><code>\pushattribute \...</code></p> <p>* CSNAME</p>
<p><code>\pushbar [...][*] ... \popbar</code></p> <p>* NAME</p>
<p><code>\pushbutton [...]¹ [...]²</code></p> <p>1 NAME</p> <p>2 REFERENCE</p>
<p><code>\pushcatcodetable ... \popcatcodetable</code></p>
<p><code>\pushculoare [...][*] ... \popculoare</code></p> <p>* COLOR</p>
<p><code>\pushendofline ... \popendofline</code></p>
<p><code>\pushfundal [...][*] ... \popfundal</code></p> <p>* NAME</p>

<code>\pushindentation ... \popindentation</code>
<code>\pushMPdrawing ... \popMPdrawing</code>
<code>\pushmacro *..</code> <code>* CSNAME</code>
<code>\pushmathstyle ... \popmathstyle</code>
<code>\pushmode [...]</code> <code>* NAME</code>
<code>\pushoutputstream [...]</code> <small>OPT</small> <code>* NAME</code>
<code>\pushpath [...] ... \poppath</code> <code>* PATH</code>
<code>\pushpunctuation ... \poppunctuation</code>
<code>\pushrandomseed ... \poprandomseed</code>
<code>\pushreferenceprefix {...} ... \popreferenceprefix</code> <code>* + - TEXT</code>
<code>\pushsystemmode {...}</code> <code>* NAME</code>
<code>\qqquad</code>
<code>\quad</code>
<code>\quads [...]</code> <small>OPT</small> <code>* NUMMER</code>
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {...}</code> <code>* FILE</code>
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>

<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {¹.} \². {³.}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {.*}</code> * TEXT
<code>\randomnumber {¹.} {².}</code> 1 NUMMER 2 NUMMER
<code>\rawcounter [¹.] [².]_{OPT}</code> 1 NAME 2 NUMMER
<code>\rawcountervalue [.*]</code> * NAME
<code>\rawdate [...,*,...]</code> * inherits: \datacurenta
<code>\rawdoifelseinset {¹.} {².} {³.}</code> 1 CONTENT 2 TRUE 3 FALSE
<code>\rawdoifinset {¹.} {².}</code> 1 CONTENT 2 TRUE
<code>\rawdoifinsetelse {¹.} {².} {³.}</code> 1 CONTENT 2 TRUE 3 FALSE
<code>\rawgetparameters [¹.] [...,²=...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\rawprocessaction [¹.] [...,²=>...,...]</code> 1 BEFEHL 2 APPLY

`\rawprocesscommacommmand [...1,...] \2...`

1 BEFEHL

2 CSNAME

`\rawprocesscommalist [...1,...] \2...`

1 BEFEHL

2 CSNAME

`\rawstructurelistuservariable {...}`

* KEY

`\rawsubcountervalue [...1] [...2]`

1 NAME

2 NUMMER

`\rbox ...1 {...2}`
OPT

1 TEXT

2 CONTENT

`\readfile {...1} {...2} {...3}`

1 FILE

2 TRUE

3 FALSE

`\readfixfile {...1} {...2} {...3} {...4}`

1 PATH

2 FILE

3 TRUE

4 FALSE

`\readjobfile {...1} {...2} {...3}`

1 FILE

2 TRUE

3 FALSE

`\readlocfile {...1} {...2} {...3}`

1 FILE

2 TRUE

3 FALSE

`\readsetfile {...1} {...2} {...3} {...4}`

1 PATH

2 FILE

3 TRUE

4 FALSE

<code>\readsysfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readtexfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\readxmlfile {...} {...} {...}</code> 1 FILE 2 TRUE 3 FALSE
<code>\realpagenumber</code>
<code>\realSmallCapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\realSmallcapped {...}</code> * TEXT
<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...] [...]</code> 1 implicit text titlu numar pagina realpage 2 REFERENCE
<code>\REFERENCEFORMAT {...} {...} [...]</code> <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referinta [...¹,...] {...²}</code> 1 REFERENCE 2 TEXT

<pre>\referintapagina [...*...]</pre> <p>* REFERENCE</p>
<pre>\referintatext [...¹...] {...²}</pre> <p>1 REFERENCE</p> <p>2 TEXT</p>
<pre>\referring (...¹,...) (...²,...) [...³]</pre> <p>1 POSITION</p> <p>2 POSITION</p> <p>3 REFERENCE</p>
<pre>\reflexie {...}</pre> <p>* CONTENT</p>
<pre>\registerattachment [...¹] [...²...,...]</pre> <p>1 NAME</p> <p>2 inherits: \setupattachment</p>
<pre>\registerctxluafile {...¹} {...²}</pre> <p>1 FILE</p> <p>2 NUMMER</p>
<pre>\registerexternalfigure [...¹] [...²]_{OPT} [...³..._{OPT}...]</pre> <p>1 FILE</p> <p>2 NAME</p> <p>3 inherits: \setupexternalfigure</p>
<pre>\registerfontclass {...}</pre> <p>* NAME</p>
<pre>\registerhyphenationexception [...¹]_{OPT} [...²]</pre> <p>1 SPRACHE</p> <p>2 TEXT</p>
<pre>\registerhyphenationpattern [...¹]_{OPT} [...²]</pre> <p>1 SPRACHE</p> <p>2 TEXT</p>
<pre>\registermenubuttons [...¹] [...²]</pre> <p>1 NAME</p> <p>2 TEXT</p>
<pre>\registersort [...¹] [...²]</pre> <p>1 SINGULAR</p> <p>2 NAME</p>

<code>\registersynonym [...]¹ [...]²</code> 1 SINGULAR 2 NAME
<code>\registerunit [...]¹ [...,...²...,...]</code> <small>OPT</small> 1 prefix unitate operator suffixe simbol packaged 2 KEY = VALUE
<code>\REGISTRU [...]¹ [...+...²+...]</code> <small>OPT</small> 1 TEXT PROCESSOR->TEXT 2 INDEX instances: index
<code>\REGISTRU [...]¹ {...}² [...+...³+...]</code> <small>OPT</small> 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: index
<code>\regular</code>
<code>\relatemarking [...]¹ [...]²</code> 1 BESCHRIFTUNG 2 BESCHRIFTUNG
<code>\relateparameterhandlers {...}¹ {...}² {...}³ {...}⁴</code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\relaxvalueifundefined {...}[*]</code> * NAME
<code>\remainingcharacters</code>
<code>\remarca (...,¹...) (...,²...) [...,...³...,...]⁴ {...}</code> <small>OPT</small> 1 POSITION 2 POSITION 3 inherits: \seteazainconjurat 4 TEXT
<code>\removebottomthings</code>
<code>\removedepth</code>

\removefromcommalist {...} \ ² .. 1 TEXT 2 CSNAME
\removelastskip
\removelastspace
\removemarkedcontent [...] * NAME
\removepunctuation
\removesubstring . ¹ .. \from . ² .. \to \ ³ .. 1 TEXT 2 TEXT 3 CSNAME
\removetoks . ¹ .. \from \ ² .. 1 BEFEHL 2 CSNAME
\removeunwantedspaces
\replacefeature [...] * NAME
\replacefeature {...} * NAME
\replaceincommalist \ ¹ .. {...} 1 CSNAME 2 NUMMER
\replaceword [...] [...] ² [...] [...] ³ 1 NAME 2 TEXT 3 TEXT
\rescan {...} * CONTENT
\rescanwithsetup {...} {...} ² 1 NAME 2 CONTENT
\resetallattributes

\resetandaddfeature [...] * NAME
\resetandaddfeature {...} * NAME
\resetbar
\resetbreakpoints
\resetbuffer [...] * BUFFER
\resetcharacteralign
\resetcharacterkerning
\resetcharacterspacing
\resetcharacterstripping
\resetcollector [...] * NAME
\resetcounter [...] [¹ ...] [² ...] OPT 1 NAME 2 NUMMER
\resetdigitsmanipulation
\resetdirection
\reseteazamarcaje [...] * BESCHRIFTUNG
\resetfeature
\resetflag {...} * NAME
\resetfontcolorscheme
\resetfontfallback [...] [¹ ...] [² ...] OPT 1 NAME 2 FONT
\resetfontsolution
\resethyphenationfeatures

\resetinjector [...] * NAME
\resetinteractionmenu [...] * NAME
\resetitaliccorrection
\resetlayer [...] * NAME
\resetlocalfloats
\resetMPdrawing
\resetMPenvironment
\resetMPinstance [...] * NAME
\resetmarker [...] * NAME
\resetmode {...} * NAME
\resetpagenumber
\resetparallel [...] ¹ [...] ² _{OPT} 1 NAME 2 NAME tot
\resetpath
\resetpenalties *... * CSNAME
\resetprofile
\resetreference [...] * NAME
\resetreplacement
\resetscript
\resetsetups [...] * NAME

\resetshownsynonyms [...] * SINGULAR
\resetsubpagenumber
\resetsymbolset
\resetsystemmode {...} * NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\reshapebox {...} * BEFEHL
\restartcounter [...] ¹ [...] ² [...] ³ <small>OPT</small> 1 NAME 2 NUMMER 3 NUMMER
\restorebox {...} ¹ {...} ² 1 NAME 2 NAME
\restorecatcodes
\restorecounter [...] * NAME
\restorecurrentattributes {...} * NAME

<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
$\backslash reusableMPgraphic \{...\} \{...\overset{2}{...}\}$ OPT <p>1 NAME</p> <p>2 KEY = VALUE</p>
$\backslash reuseMPgraphic \{...\} \{...\overset{2}{...}\}$ OPT <p>1 NAME</p> <p>2 KEY = VALUE</p>
<code>\reuserandomseed</code>
<code>\revivefeature</code>
$\backslash rfence \{...\}$ <p>* CHARACTER</p>
$\backslash rhbox \{...\}$ <p>* CONTENT</p>
$\backslash rightbottombox \{...\}$ <p>* CONTENT</p>
$\backslash rightbox \{...\}$ <p>* CONTENT</p>
$\backslash righthbox \{...\}$ <p>* CONTENT</p>
$\backslash rightheadtext \{...\}$ <p>* KEY</p>
$\backslash rightlabeltext \{...\}$ <p>* KEY</p>
$\backslash rightETICHETAtext \{...\}$ <p>* KEY</p> <p>instances: antet eticheta mathlabel</p>
$\backslash rightline \{...\}$ <p>* CONTENT</p>
$\backslash rightmathlabeltext \{...\}$ <p>* KEY</p>

$\backslash\mathrm{rightorleftpageaction}\ \{.^1.\}\ \{.^2.\}$ 1 BEFEHL 2 BEFEHL
$\backslash\mathrm{rightskipadaption}$
$\backslash\mathrm{rightsubguillemot}$
$\backslash\mathrm{righttopleft}$
$\backslash\mathrm{righttopleftthbox}\ \overset{.1}{...}\ \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopleftvbox}\ \overset{.1}{...}\ \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopleftvtop}\ \overset{.1}{...}\ \{.^2.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\mathrm{righttopbox}\ \{.^*.\}$ * CONTENT
$\backslash\mathrm{riglatext}\ [\overset{.1}{...}]\ \overset{.2}{\{.^{...}\}}$ <small>OPT</small> <small>OPT</small> 1 sus centru subsol 2 TEXT
$\backslash\mathrm{rigleumplere}\ [\overset{.1}{...}\overset{.1}{...}\overset{.1}{...}]\ \overset{.2}{\{.^{...}\}}\ \overset{.3}{\{.^{...}\}}$ <small>OPT</small> <small>OPT</small> <small>OPT</small> 1 inherits: \seteazarigleumplere 2 TEXT 3 TEXT
$\backslash\mathrm{rlap}\ \{.^*.\}$ * CONTENT
$\backslash\mathrm{robustaddtocommalist}\ \{.^1.\}\ \backslash.^2..$ 1 TEXT 2 CSNAME
$\backslash\mathrm{robustdoifelseinset}\ \{.^1.\}\ \{.^2.\}$ 1 TRUE 2 FALSE
$\backslash\mathrm{robustdoifinsetelse}\ \{.^1.\}\ \{.^2.\}$ 1 TRUE 2 FALSE

$\backslash\text{robustpretocommalist}$ $\{...\} \backslash^{.2}.$ 1 TEXT 2 CSNAME
$\backslash\text{rollbutton}$ $[...,\overset{.1}{...},...] \overset{.2}{...} [\overset{.3}{...}]$ 1 inherits: $\backslash\text{setupbutton}$ 2 TEXT 3 REFERENCE
$\backslash\text{rollbutton}$ $[\overset{.1}{...}] [\dots,\overset{.2}{...},...] \overset{.3}{...} [\overset{.4}{...}]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{seteazameniuiinteractiune}$ 3 TEXT 4 REFERENCE
$\backslash\text{roman}$
$\backslash\text{roteste}$ $[...,\overset{.1}{...},...] \{...\}^{.2}$ <small>OPT</small> 1 inherits: $\backslash\text{seteazarotare}$ 2 CONTENT
$\backslash\text{rtop}$ $\overset{.1}{...} \{...\}^{.2}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledhbox}$ $\overset{.1}{...} \{...\}^{.2}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledhpack}$ $\overset{.1}{...} \{...\}^{.2}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledmbox} \{...\}$ * CONTENT
$\backslash\text{ruledtopv}$ $\overset{.1}{...} \{...\}^{.2}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledtpack}$ $\overset{.1}{...} \{...\}^{.2}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{ruledvbox}$ $\overset{.1}{...} \{...\}^{.2}$ <small>OPT</small> 1 TEXT 2 CONTENT

<pre> \ruledvpack ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvtop ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \runMPbuffer [...¹*,...] OPT * NAME </pre>
<pre> \runninghbox {...} * CONTENT </pre>
<pre> \ScaledPointsToBigPoints {¹...} \²... 1 DIMENSION 2 CSNAME </pre>
<pre> \ScaledPointsToWholeBigPoints {¹...} \²... 1 DIMENSION 2 CSNAME </pre>
<pre> \Smallcapped {...} * TEXT </pre>
<pre> \safechar {...} * NUMMER </pre>
<pre> \sans </pre>
<pre> \sansaldin </pre>
<pre> \sansnormal </pre>
<pre> \sansserif </pre>
<pre> \savebox {¹...} {²...} {³...} 1 NAME 2 NAME 3 CONTENT </pre>
<pre> \savebtxdataset [...¹] [...²] [...³...=...,...] OPT OPT OPT 1 NAME 2 FILE 3 dataset = NAME type = bib lua xml fisier = FILE criteriu = tot text intro referinta curent aici precedent local componenta SECTIONBLOCK:tot SECTIONBLOCK:referinta SECTIONBLOCK:curent SECTIONBLOCK:precedent </pre>

<pre> \savebuffer [...,..[*]...,...] * lista = NAME fisier = FILE prefix = da nu </pre>
<pre> \savebuffer [...,¹...] [²...] 1 BUFFER 2 FILE </pre>
<pre> \savecounter [...] * NAME </pre>
<pre> \saveculoare ... \restoreculoare </pre>
<pre> \savecurrentattributes {...} * NAME </pre>
<pre> \savenormalmeaning *... * CSNAME </pre>
<pre> \savetaggedtwopassdata {...} {...} {...} {...} 1 NAME 2 NUMMER 3 NAME 4 CONTENT </pre>
<pre> \savetwopassdata {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT </pre>
<pre> \sbox {...} * CONTENT </pre>
<pre> \scala [¹...] [...,²...,...] {...³} OPT OPT 1 NAME 2 inherits: \setupscale 3 CONTENT </pre>
<pre> \scriebuffer [...,¹...] [...,²...,...] OPT OPT 1 BUFFER 2 inherits: \seteazatyping </pre>
<pre> \typeBUFFER [...,..[*]...,...] OPT * inherits: \seteazatyping </pre>

```
\scrieinlista [...] [...,..2...,...] {...} {...}
                        OPT
```

```
1  LISTE
2  inherits: \seteazalista
3  NUMMER
4  TEXT
```

```
\scrientreliste [...] [...,..2...,...] {...}
                        OPT
```

```
1  LISTE
2  inherits: \seteazalista
3  BEFEHL
```

```
\SCRIPT
instances: hangul hanzi nihongo ethiopic thai latin test
```

```
\scrismanual
```

```
\secondoffivearguments {...} {...} {...} {...} {...}
```

```
1  TEXT
2  TEXT
3  TEXT
4  TEXT
5  TEXT
```

```
\secondoffourarguments {...} {...} {...} {...}
```

```
1  TEXT
2  TEXT
3  TEXT
4  TEXT
```

```
\secondofsixarguments {...} {...} {...} {...} {...} {...}
```

```
1  TEXT
2  TEXT
3  TEXT
4  TEXT
5  TEXT
6  TEXT
```

```
\secondofthreearguments {...} {...} {...}
```

```
1  TEXT
2  TEXT
3  TEXT
```

```
\secondofthreeunexpanded {...} {...} {...}
```

```
1  TEXT
2  TEXT
3  TEXT
```

<p><code>\secondoftwoarguments {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\secondoftwounexpanded {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\sectione [...¹,...] {...}</code> OPT</p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\SECTIONUNE [...¹,...] {...}</code> OPT</p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>instances: parte capitol sectiune subsectiune subsubsectiune subsubsubsectiune subsubsubsubsectiune titlu subiect subsubiect subsubsubiect subsubsubsubiect subsubsubsubsubiect</p>
<p><code>\SECTIONUNE [...[*],...=...,...]</code></p> <p>* titlu = TEXT</p> <p>semncarte = TEXT</p> <p>marcaje = TEXT</p> <p>lista = TEXT</p> <p>referinta = REFERENCE</p> <p>numarpropriu = TEXT</p> <p>instances: parte capitol sectiune subsectiune subsubsectiune subsubsubsectiune subsubsubsubsectiune titlu subiect subsubiect subsubsubiect subsubsubsubiect subsubsubsubsubiect</p>
<p><code>\SECTIONUNE [...¹,...] {...} {...}</code> OPT</p> <p>1 REFERENCE</p> <p>2 NUMMER</p> <p>3 TEXT</p> <p>instances: parte capitol sectiune subsectiune subsubsectiune subsubsubsectiune subsubsubsubsectiune titlu subiect subsubiect subsubsubiect subsubsubsubiect subsubsubsubsubiect</p>
<p><code>\seeindex [...¹] [...²+...+...] {...}</code> OPT</p> <p>1 TEXT PROCESSOR->TEXT</p> <p>2 INDEX</p> <p>3 TEXT PROCESSOR->TEXT</p>
<p><code>\veziREGISTRU [...¹] [...²+...+...] {...}</code> OPT</p> <p>1 TEXT PROCESSOR->TEXT</p> <p>2 INDEX</p> <p>3 TEXT PROCESSOR->TEXT</p> <p>instances: index</p>

`\select {...} {...} {...} {...} {...} {...}`
 ¹ ² ³ ⁴ ⁵ ⁶
 OPT OPT OPT OPT OPT OPT

1 NAME
2 CONTENT
3 CONTENT
4 CONTENT
5 CONTENT
6 CONTENT

`\selecteazablocuri [...,1...] [...,2...] [...,3...,...]`
 ¹ ² ³
 OPT OPT OPT

1 NAME
2 + -
3 criteriu = text ABSCHNITT

`\semncarte [...]1 {...}2`
 ¹ ²
 OPT

1 ABSCHNITT LISTE
2 TEXT

`\serializecommalist [...,*...]`

* BEFEHL

`\serializedcommalist`

`\serif`

`\serifbold`

`\serifnormal`

`\setare [...]`

* NAME

`\setareitemization [...,1...] [...,2...,...]`
 ¹ ²
 OPT

1 NAME NAME:NUMMER
2 inherits: \setupitemgroup

\setarelimba [...]¹ [...]²...

OPT

```
1  SPRACHE implicit
2  implicit          = SPRACHE
   stare            = start stop
   data             = inherits: \datacurenta
   patterns         = FILE
   lefthyphenmin    = NUMBER
   righthyphenmin   = NUMBER
   lefthyphenchar   = NUMBER
   righthyphenchar  = NUMBER
   setups           = NAME
   spatiere         = broad impachetat
   font             = auto
   text            = TEXT
   limitttext       = TEXT
   hyphen           = TEXT
   compoundhyphen   = TEXT
   leftcompoundhyphen = TEXT
   rightcompoundhyphen = TEXT
   minicitatstanga  = BEFEHL
   minicitatdreapta = BEFEHL
   citatstanga      = BEFEHL
   citatdreapta     = BEFEHL
   leftspeech       = BEFEHL
   rightspeech      = BEFEHL
   propozitiestanga = BEFEHL
   middlespeech     = BEFEHL
   propozitiedreapta = BEFEHL
   midsentence      = BEFEHL
   subpropozitiestanga = BEFEHL
   subpropozitiedreapta = BEFEHL
   factor           = da nu
```

\setarepozitie [...]¹ [...]²...

OPT

```
1  NAME
2  offset = da nu
   unitate = ex em pt in cm mm sp bp pc dd cc nc
   stare   = start overlay
   xoffset = DIMENSION
   yoffset = DIMENSION
   xstep   = absolut relativ
   ystep   = absolut relativ
   xscala  = NUMMER
   yscala  = NUMMER
   xfactor = NUMMER
   yfactor = NUMMER
   factor  = NUMMER
   scala   = NUMMER
```

\setare {...}

* NAME

\setbar [...]

* NAME

\setbigbodyfont

\setboxllx ... {...}¹ {...}²

```
1  CSNAME NUMBER
2  DIMENSION
```

\setboxlly ... {...}¹ {...}²

```
1  CSNAME NUMBER
2  DIMENSION
```

\setbreakpoints [...] * reset NAME
\setbuffer [...] ... \endbuffer * NAME
\setcapstrut
\setcatcodetable *... * CSNAME
\setcharacteralign { ¹ ...} { ² ...} 1 NUMMER 2 TEXT number->TEXT text->TEXT
\setcharactercasing [...] * reset CUVANT cuvant Cuvant Cuvinte majuscula Majuscula niciunul aleator mixed camel cap Cap
\setcharactercleaning [...] * reset 1
\setcharacterkerning [...] * reset NAME
\setcharacterspacing [...] * reset NAME
\setcharacterstripping [...] * reset 1
\setcharstrut {...} * TEXT
\setcollector [¹ ...] [..., ² ... _{OPT} ,...] { ³ ...} 1 NAME 2 inherits: \setupcollector 3 CONTENT
\setcolormodel1 [...] * black bw gri rgb cmyk tot niciunul
\setcounter [¹ ...] [² ... _{OPT}] [³ ...] 1 NAME 2 NUMMER 3 NUMMER

<code>\setcounterown [...]¹ [...]² [...]³</code> <div> <div>OPT</div> <div> 1 NAME 2 NUMMER 3 TEXT </div> </div>
<code>\setcurrentfontclass {...}</code> <div> <div>*</div> <div>NAME</div> </div>
<code>\setdataset [...]¹ [...]² [...]³...,...</code> <div> <div>OPT</div> <div> 1 NAME 2 NAME 3 KEY = VALUE </div> </div>
<code>\setdefaultpenalties</code>
<code>\setdigitsmanipulation [...]</code> <div> <div>*</div> <div>reset NUMMER</div> </div>
<code>\setdirection [...]</code> <div> <div>*</div> <div>NUMMER</div> </div>
<code>\setdocumentargument {...}¹ {...}²</code> <div> <div>1 NAME</div> <div>2 TEXT</div> </div>
<code>\setdocumentargumentdefault {...}¹ {...}²</code> <div> <div>1 NAME</div> <div>2 TEXT</div> </div>
<code>\setdocumentfilename {...}¹ {...}²</code> <div> <div>1 NUMMER</div> <div>2 TEXT</div> </div>
<code>\setdummyparameter {...}¹ {...}²</code> <div> <div>1 KEY</div> <div>2 BEFEHL</div> </div>
<code>\setezaaliniat [...][*],...</code> <div> <div>OPT</div> <div> <div> * [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle </div> <div>DIMENSION NAME</div> </div> </div>
<code>\setezaalinieria [...][*],...</code> <div> <div> * broad larg subsol inaltime linie inalt jos lohi flushright flushleft centru da nu latime normal reset intern extern flushinner flushouter stanga dreapta center dezactivat ultim end paragraf lefttoright righttoleft l2r r2l tabelul lesshyphenation morehyphenation suspendat nothanging hz fullhz nohz despsilabe nedespsilabe tolerant foartetolerant dilatat extremestretch final 2*final 3*final 4*final </div> </div>
<code>\setezaantet [...]¹ [...]²...,...</code> <div> <div>OPT</div> <div> 1 text margine bordura 2 inherits: \setuplayoutelement </div> </div>

\setezaaranjareapag [...,*,...]

* dezactivat oglindit douafete negativ 90 180 270 reset fundal normal 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP 2DOWN
2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW
1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME

\setezaaspect [¹...] [²..._{OPT}...]

1 NAME

2 stare = start stop normal repetat
margine = DIMENSION
bordura = DIMENSION
distantamargine = DIMENSION
distantabordura = DIMENSION
distantabordurastanga = DIMENSION
distantacoltdreapta = DIMENSION
distantamarginestanga = DIMENSION
distantamarginedreapta = DIMENSION
distantasus = DIMENSION
distantaantet = DIMENSION
distantasubsol = DIMENSION
distantajos = DIMENSION
preset = NAME
marginestanga = DIMENSION
marginedreapta = DIMENSION
bordurastanga = DIMENSION
borduradreapta = DIMENSION
antet = DIMENSION
subsol = DIMENSION
sus = DIMENSION
jos = DIMENSION
spatiuspate = DIMENSION
spatiusus = DIMENSION
setups = NAME
cutspace = DIMENSION
latime = DIMENSION centru ajustat
spatiujos = DIMENSION
linii = NUMMER
inaltime = DIMENSION centru ajustat
offsetoriz = DIMENSION
veroffset = DIMENSION
coloane = NUMMER
distantacoloane = DIMENSION
metoda = implicit normal NAME
locatie = stanga centru dreapta sus subsol ofata douafete
latimetext = DIMENSION
inaltimetext = DIMENSION
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
scala = NUMMER
sx = NUMMER
sy = NUMMER
marcaje = on dezactivat pagina gol culoare unu doi patru
grid = da nu dezactivat
textdistance = DIMENSION
alternativ = implicit normal marcaj NAME
clipoffset = DIMENSION
cropoffset = DIMENSION
trimoffset = DIMENSION
bleedoffset = DIMENSION
artoffset = DIMENSION

\setezaaspect [...]

* reset NAME

`\seteazabarainteractiune [...,1...] [...,2...,...]`
OPT

1 NAME

2 alternativ = a b c d e f g
stare = start stop
comanda = CSNAME
latime = DIMENSION
inaltime = DIMENSION max broad
inaltime = DIMENSION max
distanta = DIMENSION
pas = mic mediu mare
culoarefundal = COLOR
stil = STYLE BEFEHL
culoare = COLOR
culoarecontrast = COLOR
simbol = da nu
inherits: \seteazainconjurat

`\seteazablanc [...,*...]`
OPT

* inherits: \vspacing

`\seteazabloc [...,1...] [...,2...,...]`
OPT

1 NAME

2 inainte = BEFEHL
dupa = BEFEHL
intern = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR

`\seteazablocsectiune [...,1...] [...,2...,...]`
OPT

1 NAME

2 pagina = inherits: \pagina
inainte = BEFEHL
dupa = BEFEHL
numar = da nu

`\seteazabuffer [...,1...] [...,2...,...]`
OPT

1 BUFFER

2 inainte = BEFEHL
dupa = BEFEHL

`\seteazacamp [...,1...] [...,2...,...]
OPT OPT` `[...,3...,...]
OPT` `[...,4...,...]
OPT` `[...,5...,...]`

1 NAME

2 reset eticheta incadrat orizontal vertical

3 inherits: \setupfieldtotalframed

4 inherits: \setupfieldlabelframed

5 inherits: \setupfieldcontentframed

`\seteazacampuri [...,1...] [...,2...,...]
OPT OPT` `[...,3...,...]
OPT` `[...,4...,...]`

1 reset eticheta incadrat orizontal vertical

2 inherits: \setupfieldtotalframed

3 inherits: \setupfieldlabelframed

4 inherits: \setupfieldcontentframed

\seteazaclipping [...,*=...,...]

```
*  stare      = start stop
   latime     = DIMENSION
   inaltime   = DIMENSION
   hoffset    = DIMENSION
   voffset    = DIMENSION
   x          = NUMMER
   y          = NUMMER
   nx         = NUMMER
   ny         = NUMMER
   sx         = NUMMER
   sy         = NUMMER
   offsetstanga = DIMENSION
   offsetdreapta = DIMENSION
   offsetsus  = DIMENSION
   offsetjos   = DIMENSION
   mp         = NAME
   n          = NUMMER
   offset     = DIMENSION
```

\seteazacoloane [...,*=...,...]

```
*  n          = NUMMER
   distanta   = DIMENSION
   optiune    = fundal
   offset     = DIMENSION
   comanda    = \...##1
   inaltime   = DIMENSION
   directie   = stanga dreapta
   balanta    = da nu
   aliniere   = setupalign
   toleranta  = setuptolerance
   blanc      = inherits: \blanc
   nsus       = NUMMER
   rigla      = on dezactivat BEFEHL
```

\seteazacomentariu [...,¹...,...]
OPT [...,²...,...]

```
1  NAME
2  stare      = start stop niciunul
   metoda     = normal ascuns
   simbol     = Comment Ajutor Insert Cheie Newparagraph Note Paragraf Default
   latime     = ajustat DIMENSION
   inaltime   = ajustat DIMENSION
   inaltime   = ajustat DIMENSION
   titlu      = TEXT
   subtitlu   = TEXT
   autor      = TEXT
   nx         = NUMMER
   ny         = NUMMER
   culoare    = COLOR
   optiune    = xml max
   textlayer  = NAME
   locatie    = bordurastanga borduradreapta inmarginestanga marginedreapta text inalt niciunul
   distanta   = DIMENSION
```

\seteazacomentariupagina [...,*=...,...]

```
*  locatie    = stanga dreapta sus subsol niciunul
   stare      = start stop niciunul
   offset     = DIMENSION
   distanta   = DIMENSION
   latime     = DIMENSION
   inaltime   = DIMENSION
```

\seteazaculoare [...]

```
*  FILE
```

\seteazaculori [...,*...]

* stare = start stop
spot = da nu
expansiune = da nu
factor = da nu
rgb = da nu
cmyk = da nu
conversie = da nu totdeauna
pagecolormodel = auto niciunul NAME
culoaretext = COLOR
intent = overprint knockout niciunul

\seteazadimensiunihartie [...]¹ [...]²...]

OPT

1 NAME
2 sus = BEFEHL
jos = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
metoda = normal niciunul NAME
scala = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
latime = DIMENSION
inaltime = DIMENSION
spatiusus = DIMENSION
spatiuspate = DIMENSION
offset = DIMENSION
pagina = reset vedere oglindit negativ rotat 90 180 270 NAME
hartie = reset vedere oglindit negativ rotat 90 180 270 NAME
optiune = ajustat max
distanta = DIMENSION

\seteazadimensiunihartie [...]¹ [...]²...]

OPT

OPT

1 reset vedere oglindit negativ rotat 90 180 270 NAME
2 reset vedere oglindit negativ rotat 90 180 270 NAME

\seteazaecraninteractiune [...,*...]

* latime = ajustat max tight DIMENSION
inaltime = ajustat max tight DIMENSION
spatiuspate = DIMENSION
offsetoriz = DIMENSION
veroffset = DIMENSION
spatiusus = DIMENSION
optiune = ajustat max ofata douafete semncarte auto niciunul implicit fixat vedere portrait pagina foaie
copies = NUMMER
intarziere = niciunul NUMMER

\seteazaelemente [...]¹ [...]²...]

OPT

1 NAME
2 alternativ = stanga dreapta sus subsol inmarginie
latimetext = DIMENSION
latime = DIMENSION
distanta = DIMENSION
simbol = niciunul NAME
aliniere = stanga centru dreapta flushleft flushright intern extern marginie
textalign = stanga centru dreapta flushleft flushright intern extern
n = NUMMER
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL

`\seteazafloat [...1,...] [...2,...]`
OPT

```

1  SINGULAR

2  aliniaturmator      = da nu auto
   implicit            = inherits: \placefloat
   fallback            = inherits: \placefloat
   intern              = BEFEHL
   criteriu            = DIMENSION
   metoda              = NUMMER
   sidemethod          = NUMMER
   textmethod          = NUMMER
   sidealign           = inaltime adancime linie jumatatelinie grila normal
   local               = da nu
   comanda              = \...##1
   availablewidth      = DIMENSION
   availableheight     = DIMENSION
   latimeminima        = DIMENSION
   latimemaxima        = DIMENSION
   locatie              = stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin
                        inneredge outeredge spatiuspate cutspace marginestanga marginedreapta bordurastanga
                        borduradreapta

   distantamarginestanga = DIMENSION
   distantamarginedreapta = DIMENSION
   marginestanga         = DIMENSION
   marginedreapta        = DIMENSION
   innermargin           = DIMENSION
   outermargin           = DIMENSION
   bottombefore          = BEFEHL
   bottomafter           = BEFEHL
   spatiuinainte         = niciunul inherits: \blanc
   spatiudupa            = niciunul inherits: \blanc
   latime                = DIMENSION
   inaltime              = DIMENSION
   offset                = DIMENSION niciunul overlay
   spatiulateralinainte  = niciunul inherits: \blanc
   spatiulateraldupa     = niciunul inherits: \blanc
   margine                = DIMENSION
   nsus                  = DIMENSION
   njos                  = DIMENSION
   pas                   = mic mediu mare linie adancime
   nlinii                 = NUMMER
   cache                  = da nu

```

`\seteazafonttext [...*,...]`
OPT

* DIMENSION NAME global reset x xx mic mare script scriptscript rm ss tt hw cg roman serif regular sans sansserif
 suport type teletype mono scrismmanual caligrafic

`\seteazaformulare [...*,...]`

* metoda = XML HTML PDF
 export = da nu

`\seteazafundal [...1,...] [...2,...]`
OPT

```

1  NAME

2  stare              = start stop
   offsetstanga       = DIMENSION
   offsetdreapta      = DIMENSION
   offsetsus          = DIMENSION
   offsetjos          = DIMENSION
   inainte            = BEFEHL
   dupa                = BEFEHL
   inherits: \seteazainconjurat

```

`\seteazafundaluri [...1,...] [...2,...] [...3,...]`
OPT

```

1  sus antet text subsol subsol

2  bordurastanga marginestanga text marginedreapta borduradreapta

3  inherits: \seteazainconjurat

```

\seteazafundaluri [...,¹...] [...,²...,...]
OPT

1 foaie pagina paginastanga paginadreapta text ascuns
 2 stare = start stop
 inherits: \seteazainconjurat

\seteazagrosimelinie [...]

* mic mediu mare DIMENSION

\seteazaimpartireafloat [...,^{*}...,...]

* inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 linii = auto NUMMER
 conversie = NAME

\seteazainconjurat [...,¹...] [...,²...,...]
OPT

1 NAME
 2 colt = rectangular rotund NUMMER
 coltframe = rectangular rotund NUMMER
 coltfundal = rectangular rotund NUMMER
 raza = DIMENSION
 razaframe = DIMENSION
 razafundal = DIMENSION
 inaltime = DIMENSION
 adancimeframe = DIMENSION
 adancimefundal = DIMENSION
 culoareframe = COLOR
 framesus = on dezactivat NAME
 framejos = on dezactivat NAME
 framestanga = on dezactivat NAME
 framedreapta = on dezactivat NAME
 region = da nu
 grosimerigla = DIMENSION
 offsetframe = DIMENSION
 frame = on dezactivat overlay niciunul
 fundal = primplan culoare NAME
 offsetfundal = incadrat DIMENSION
 component = NAME
 extras = BEFEHL
 foregroundstyle = STYLE BEFEHL
 foregroundcolor = COLOR
 setups = NAME
 offset = implicit overlay niciunul DIMENSION
 latime = local ajustat max broad fixat DIMENSION
 inaltime = ajustat max broad DIMENSION
 aliniere = inherits: \seteazaalinierea
 strut = da nu niciunul local global
 autostrut = da nu
 locatie = inaltime adancime inalt jos sus centru subsol linie lohi suspendat mentine formula matematica
 normal
 autolatime = da nu fortat
 linii = NUMMER
 sus = BEFEHL
 jos = BEFEHL
 blanc = da nu
 profile = NAME
 gol = da nu
 loffset = DIMENSION
 roffset = DIMENSION
 toffset = DIMENSION
 boffset = DIMENSION
 orientation = NUMMER

\seteazaingust [...¹,...] [...²,...] OPT

1 NAME

2 stanga = DIMENSION
mijloc = DIMENSION
dreapta = DIMENSION
implicit = [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
inainte = BEFEHL
dupa = BEFEHL

\seteazainteractiunea [...¹,...] [...²,...] OPT

1 NAME

2 stare = start stop
stil = STYLE BEFEHL
culoare = COLOR
culoarecontrast = COLOR
titlu = TEXT
subtitlu = COLOR
autor = TEXT
data = TEXT
keyword = TEXT
focus = standard incadrat latime latimeminima inaltime inaltimeminima ajustat tight
menu = on dezactivat
fieldlayer = auto NAME
calculeaza = REFERENCE
click = da nu
display = normal nou
pagina = da nu pagina nume auto
actiunedeschidere = REFERENCE
actiuneinchidere = REFERENCE
actiunedeschiderepagina = REFERENCE
actiuneinchiderepagina = REFERENCE
setsimbol = NAME
inaltime = DIMENSION
inaltime = DIMENSION
focusoffset = DIMENSION

\seteazainteractiunea [...¹,...] OPT

* NAME

\seteazajos [...¹,...] [...²,...] OPT

1 text margine bordura

2 inherits: \setuplayoutelement

\seteazalegenda [...¹,...] [...²,...] OPT

1 NAME

2 inherits: \setupfloatcaption

\punechemical [...¹,...] [...²,...] {...³} {...⁴} OPT

1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga
marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
[-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
effective

2 REFERENCE

3 TEXT

4 CONTENT

`\punefigure [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\punegraphic [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\puneintermezzo [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\punetable [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\seteazaliniesilabe [...*,...]`

* semn = normal larg

`\seteazaliniesubtire [...*,...]`

* inaltime = max DIMENSION
 inaltime = max DIMENSION
 fundal = culoare
 frame = on dezactivat
 grosimerigla = DIMENSION
 alternativ = a b c niciunul
 culoarefundal = COLOR
 culoare = COLOR
 spatiereinterliniara = mic mediu mare NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 n = NUMMER

`\seteazalinii [...1,...] [...2...,...]`
OPT

```
1  NAME
2  optiune   = impachetat
   inainte  = BEFEHL
   dupa     = BEFEHL
   intre    = BEFEHL
   aliniat   = inherits: \seteazaaliniat
   aliniere  = inherits: \seteazaalinierea
   spatiu   = da on dezactivat fixat implicit
   comanda  = BEFEHL
   stil     = STYLE BEFEHL
   culoare  = COLOR
   stanga   = BEFEHL
   dreapta  = BEFEHL
```

`\seteazaliniimargine [...1] [...2...,...]`
OPT

```
1  NUMMER
2  inherits: \setupmarginrule
```

`\seteazaliniinegre [...*...,...]`

```
*  latime    = max DIMENSION
   inaltime  = max DIMENSION
   inaltime  = max DIMENSION
   distanta  = DIMENSION
   n         = NUMMER
   alternativ = a b
   stil      = STYLE BEFEHL
   culoare   = COLOR
   type      = mp da nu
   mp        = NAME
```

`\seteazaliniiumplere [...*...,...]`

```
*  inainte   = BEFEHL
   dupa      = BEFEHL
   margine   = DIMENSION
   latime    = DIMENSION
   distanta  = DIMENSION
   grosimerigla = DIMENSION
   culoare   = COLOR
```

\seteazalista [...,¹...] [...,²...,...]
OPT

```

1  LISTE
2  stare                = start stop
   locatie              = niciunul aici
   type                 = simple comanda userdata
   criteriu             = local intro referinta SECTIONBLOCK:referinta tot SECTIONBLOCK:tot text SECTIONBLOCK:text
                        = curent SECTIONBLOCK:curent aici precedent SECTIONBLOCK:precedent componenta ABSCHNITT
                        = SECTIONBLOCK:ABSCHNITT
   lista                = NAME
   latime               = ajustat broad auto DIMENSION
   inaltime             = ajustat broad DIMENSION
   inaltime             = ajustat broad DIMENSION
   simbol              = unu doi trei niciunul implicit
   eticheta             = da nu niciunul NAME
   starter              = BEFEHL
   stopper              = BEFEHL
   comanda              = \...#1#2#3
   comandanumar         = \...#1
   comandatext          = \...#1
   comandapagina       = \...#1
   numarpagina         = da nu totdeauna
   numartitlu          = da nu totdeauna
   inainte              = BEFEHL
   dupa                 = BEFEHL
   intre                = BEFEHL
   margine              = niciunul DIMENSION
   distanta             = niciunul DIMENSION
   alinieretitlu       = da nu
   numberalign          = stanga dreapta centru flushleft flushright intern extern
   aliniere             = inherits: \seteazaalinierea
   suspenda            = da nu
   stanga               = BEFEHL
   dreapta              = BEFEHL
   interactiune         = da nu tot numar text titlu pagina numarsetiune numarpagina
   limittext           = da nu TEXT
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stilnumar            = STYLE BEFEHL
   culoarenumar         = COLOR
   stiltext             = STYLE BEFEHL
   culoaretex          = COLOR
   stilpagina           = STYLE BEFEHL
   culoarepagina       = COLOR
   referinta           = NUMMER
   extras               = NAME
   order                = comanda tot titlu
   alternativ            = a b c d e f g stanga dreapta sus subsol comanda niciunul interactive paragraf orizontal
                        = vertical NAME
   latimemaxima         = DIMENSION
   pageprefix           = da nu
   pageprefixseparatorset = NAME
   pageprefixconversionset = NAME
   pageprefixset        = NAME
   pageprefixsegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        = ABSCHNITT:tot
   pageprefixconnector  = BEFEHL PROCESSOR->BEFEHL
   pageconversionset     = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   inherits: \setupcounterinherits: \seteazainconjurat

```

\seteazalistacombinata [...,¹] [...,²...,...]

```

1  LISTE
2  inherits: \seteazalista

```

\setareCOMBINEDLIST [...,^{*}...,...]

* inherits: \seteazalista

instances: cuprins

`\seteazamajuscul` [...,¹...] [...,²...,...]
OPT

1 NAME
 2 titlu = da nu
 sc = da nu
 stil = STYLE BEFEHL

`\seteazamakeup` [...,¹...] [...,²...,...]
OPT

1 NAME
 2 pagina = inherits: \pagina
 comanda = BEFEHL
 latime = DIMENSION
 inaltime = DIMENSION
 aliniera = inherits: \seteazaaliniera
 setups = NAME
 sus = BEFEHL
 jos = BEFEHL
 inainte = BEFEHL
 dupa = BEFEHL
 locatie = sus
 referinta = REFERENCE
 pagestate = start stop
 stareantet = start stop inalt gol niciunul normal
 staresubsol = start stop inalt gol niciunul normal
 staresus = start stop inalt gol niciunul normal
 starejos = start stop inalt gol niciunul normal
 staretext = start stop inalt gol niciunul normal
 douafete = da nu gol
 stil = inherits: \value-style
 culoare = COLOR

`\seteazamarcaje` [...,¹...] [...,²...,...]
OPT

1 BESCHRIFTUNG
 2 stare = start stop
 expansiune = da nu
 separator = BEFEHL
 filtercommand = \...##1

`\seteazameniuiinteractiune` [...,¹...] [...,²...,...]
OPT

1 NAME
 2 alternativ = vertical orizontal ascuns
 category = NAME
 offsetstanga = overlay incadrat niciunul implicit DIMENSION
 offsetdreapta = overlay incadrat niciunul implicit DIMENSION
 offsetsus = overlay incadrat niciunul implicit DIMENSION
 offsetjos = overlay incadrat niciunul implicit DIMENSION
 latimemaxima = DIMENSION
 inaltimemaxima = DIMENSION
 itemalign = stanga centru dreapta flushleft flushright jos inalt lohi
 stare = start gol local
 stanga = BEFEHL
 dreapta = BEFEHL
 distanta = overlay DIMENSION
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 pozitie = da nu
 mijloc = BEFEHL
 stil = STYLE BEFEHL
 culoare = COLOR
 aceeasipagina = da nu gol niciunul normal implicit
 culoarecontrast = COLOR
 inherits: \seteazainconjurat

`\seteazaminicitat` [...,^{*}...,...]

* inherits: \setupdelimitedtext

\seteazanumarpagina [...,..^{*}...,...]

* inherits: \setupuserpagenumber

\seteazanumarsubpagina [...,..^{*}...,...]

* inherits: \setupcounter

\seteazanumartitlu [...¹.] [...².]

1 ABSCHNITT

2 [-+]NUMMER

\seteazanumerotarelinii [...,¹...] [...,²...] OPT

1 NAME

2 start = NUMMER
pas = NUMMER
metoda = pagina primul urmatorul
conversie = NAME
continua = da nu
locatie = text begin end implicit stanga dreapta intern extern instanga indreapta margine inmargin
distanta = DIMENSION
alinie = intern extern flushleft flushright stanga dreapta centru auto
comanda = \...##1
stanga = BEFEHL
dreapta = BEFEHL
margine = DIMENSION
latime = margine DIMENSION
stil = STYLE BEFEHL
culoare = COLOR

\seteazanumerotarepagina [...,..^{*}...,...]

* alternativ = ofata douafete
pagina = inherits: \pagina
strut = da nu
comanda = \...##1
stanga = BEFEHL
dreapta = BEFEHL
stare = start stop
latime = DIMENSION
locatie = antet subsol stanga centru dreapta instanga indreapta margine inmargin lamargine marginebordura
stil = STYLE BEFEHL
culoare = COLOR

\seteazanumerotareparagrafe [...,..^{*}...,...]

* stare = start stop linie reset
distanta = DIMENSION
stil = STYLE BEFEHL
culoare = COLOR

\seteazapaleta [...]

* NAME

\seteazaparafrage [¹...] [²...,...]
OPT OPT

1 NAME
 2 fiecare NUMMER
 3 n = NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 latime = DIMENSION
 distanta = DIMENSION
 inaltime = DIMENSION ajustat
 sus = BEFEHL
 jos = BEFEHL
 aliniere = inherits: \seteazaalinierea
 intern = BEFEHL
 comanda = BEFEHL
 rigla = on dezactivat
 grosimerigla = DIMENSION
 culoarerigla = COLOR
 stil = STYLE BEFEHL
 culoare = COLOR

\seteazaparafrage [¹...] [²...,...]
OPT

1 NAME:NUMMER
 2 n = NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 latime = DIMENSION
 distanta = DIMENSION
 inaltime = DIMENSION ajustat
 sus = BEFEHL
 jos = BEFEHL
 aliniere = inherits: \seteazaalinierea
 intern = BEFEHL
 comanda = BEFEHL
 rigla = on dezactivat
 grosimerigla = DIMENSION
 culoarerigla = COLOR
 stil = STYLE BEFEHL
 culoare = COLOR

\seteazaplasareaopozita [...,...*...]

* stare = start stop
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL

\seteazaprograme [...,...*...]

* stil = STYLE BEFEHL
 culoare = COLOR

\seteazareferinte [...,...*...]

* stare = start stop
 expansiune = da nu xml
 autofile = da nu
 export = da nu
 stanga = BEFEHL
 dreapta = BEFEHL
 latime = DIMENSION
 douafete = da nu
 interactiune = eticheta text simbol tot
 separator = BEFEHL
 prefix = + - TEXT

\seteazaregistru [¹...] [²...,...]

OPT

```

1  NAME NAME:NUMMER

2  referencemethod      = avans
   expansiune           = da nu xml
   numarpropriu         = da nu
   xmlsetup             = NAME
   alternativ            = a b A B
   metoda               = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress             = da nu tot
   criteriu             = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   pageprefixconnector  = BEFEHL
   pageprefix           = da nu
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
   latimemaxima         = DIMENSION
   indicator            = da nu
   inainte              = BEFEHL
   dupa                 = BEFEHL
   comanda              = \...##1
   comandatext          = \...##1
   deeptextcommand      = \...##1
   comandapagina        = \...##1
   distanta             = DIMENSION
   interactiune         = text numarpagina
   numarpagina          = da nu
   simbol              = a n niciunul 1 2 BEFEHL
   language             = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stiltext             = STYLE BEFEHL
   culoaretext          = COLOR
   stilpagina           = STYLE BEFEHL
   culoarepagina        = COLOR
   n                    = NUMMER
   balanta              = da nu
   aliniere             = inherits: \seteazaalinierea
   numberorder          = numere

```

\seteazaregistru [...,¹...] [...,²...] [...,³...,...]
OPT OPT

```

1  NAME
2  NUMMER
3  referencemethod      = avans
   expansiune           = da nu xml
   numarpropriu         = da nu
   xmlsetup             = NAME
   alternativ            = a b A B
   metoda               = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress             = da nu tot
   criteriu             = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   pageprefixconnector  = BEFEHL
   pageprefix           = da nu
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
   latimemaxima         = DIMENSION
   indicator            = da nu
   inainte              = BEFEHL
   dupa                 = BEFEHL
   comanda              = \...##1
   comandatext          = \...##1
   deeptextcommand      = \...##1
   comandapagina        = \...##1
   distanta             = DIMENSION
   interactiune         = text numarpagina
   numarpagina          = da nu
   simbol               = a n niciunul 1 2 BEFEHL
   language             = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stiltext             = STYLE BEFEHL
   culoaretext          = COLOR
   stilpagina           = STYLE BEFEHL
   culoarepagina        = COLOR
   n                    = NUMBER
   balanta              = da nu
   aliniere             = inherits: \seteazaalinierea
   numberorder          = numere

```

\setareREGISTRU [...,¹...] [...,²...,...]
OPT

```

1  NUMMER
2  inherits: \seteazaregistru

```

instances: index

\seteazarigletext [...,^{*}...,...]

```

*  inainte             = BEFEHL
   dupa                = BEFEHL
   intre               = BEFEHL
   grosimerigla        = DIMENSION
   locatie             = stanga inmarginie
   stil                = STYLE BEFEHL
   culoare             = COLOR
   culoarerigla        = COLOR
   latime              = DIMENSION
   inaltime            = DIMENSION
   distanta            = DIMENSION
   corectieadancime    = on dezactivat
   fonttext            = inherits: \seteazafonttext

```

\seteazarigleumplere [...,*...]

* inainte = BEFEHL
dupa = BEFEHL
n = NUMMER
spatiereinterliniara = mic mediu mare NUMMER
distanta = DIMENSION
latime = ajustat broad DIMENSION
separator = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR

\seteazarotare [...,*...]

* locatie = ajustat broad adancime inalt centru implicit normal
rotatie = stanga dreapta intern extern NUMMER
inherits: \seteazainconjurat

\seteazasimbol [...]

* NAME

\seteazasinonime [...,¹...] [...,*²...]
OPT

1 SINGULAR
2 expansiune = da nu xml
alternativ = primul ultim normal NAME
urmatorul = BEFEHL
comanda = \...##1##2##3
comandatext = \...##1
synonymcommand = \...##1
language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
criteriu = curent precedent local text tot ABSCHNITT
stil = STYLE BEFEHL
culoare = COLOR
stiltext = STYLE BEFEHL
culoaretext = COLOR
stilsinonim = STYLE BEFEHL
culoaresinonim = COLOR

\seteazasortare [...,¹...] [...,*²...]
OPT

1 SINGULAR
2 expansiune = da nu xml
alternativ = primul ultim normal NAME
urmatorul = BEFEHL
comanda = \...##1##2##3
comandatext = \...##1
synonymcommand = \...##1
language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
criteriu = curent precedent local text tot ABSCHNITT
stil = STYLE BEFEHL
culoare = COLOR
stiltext = STYLE BEFEHL
culoaretext = COLOR
stilsinonim = STYLE BEFEHL
culoaresinonim = COLOR

\seteazaspatiu [...]
OPT

* fixat impachetat broad

\seteazaspatialb [...,*...]
OPT

* fix fixat flexibil linie jumatatelinie quarterline niciunul mic mediu mare implicit DIMENSION

`\seteazaspatiuinterliniar [...1,...] [...2,...]`
OPT

```
1  NAME

2  linie          = DIMENSION
   inaltime       = NUMMER
   inaltime       = NUMMER
   inaltime        = NUMMER
   inaltime        = NUMMER
   mindepth       = NUMMER
   distanta       = DIMENSION
   sus            = NUMMER inaltime
   jos            = NUMMER
   dilatata       = NUMMER
   shrink         = NUMMER
```

`\seteazaspatiuinterliniar [...*,...]`
OPT

* on dezactivat reset auto mic mediu mare NUMMER DIMENSION

`\seteazaspatiuinterliniar [...*]`

* NAME

`\seteazasubsol [...1] [...2,...]`
OPT

```
1  text margine bordura

2  inherits: \setuplayoutelement
```

`\seteazasus [...1] [...2,...]`
OPT

```
1  text margine bordura

2  inherits: \setuplayoutelement
```

`\seteazatabele [...*,...]`

```
*  text          = DIMENSION max
   split         = da nu repetat auto
   frame         = on dezactivat
   NL            = inherits: \blanc
   VL            = mic mediu mare niciunul NUMMER
   HL            = mic mediu mare niciunul NUMMER
   distanta      = mic mediu mare niciunul
   aliniere      = stanga centru dreapta
   comenzi       = BEFEHL
   fonttext      = inherits: \seteazafonttext
   grosimerigla  = DIMENSION
   inaltime      = strut NUMMER
   inaltime      = strut NUMMER
```

`\seteazatabulatori [...1] [...2] [...3,...]`
OPT OPT

```
1  NAME

2  NAME

3  inherits: \setuptabulation
```

`\seteazatext [...1] [...2,...]`
OPT

```
1  text margine bordura

2  inherits: \setuplayoutelement
```

`\seteazatexteantet` $\left[\overset{1}{\dots} \right]$ $\left[\overset{2}{\dots} \right]$ $\left[\overset{3}{\dots} \right]$ $\left[\overset{4}{\dots} \right]$ $\left[\overset{5}{\dots} \right]$
OPT OPT OPT OPT OPT

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextejos` $\left[\overset{1}{\dots} \right]$ $\left[\overset{2}{\dots} \right]$ $\left[\overset{3}{\dots} \right]$ $\left[\overset{4}{\dots} \right]$ $\left[\overset{5}{\dots} \right]$
OPT OPT OPT OPT OPT

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextesubsol` $\left[\overset{1}{\dots} \right]$ $\left[\overset{2}{\dots} \right]$ $\left[\overset{3}{\dots} \right]$ $\left[\overset{4}{\dots} \right]$ $\left[\overset{5}{\dots} \right]$
OPT OPT OPT OPT OPT

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextesus` $\left[\overset{1}{\dots} \right]$ $\left[\overset{2}{\dots} \right]$ $\left[\overset{3}{\dots} \right]$ $\left[\overset{4}{\dots} \right]$ $\left[\overset{5}{\dots} \right]$
OPT OPT OPT OPT OPT

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextetext` $\left[\overset{1}{\dots} \right]$ $\left[\overset{2}{\dots} \right]$ $\left[\overset{3}{\dots} \right]$ $\left[\overset{4}{\dots} \right]$ $\left[\overset{5}{\dots} \right]$
OPT OPT OPT OPT OPT

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatexteticheta` $\left[\overset{1}{\dots} \right]$ $\left[\dots, \dots, \overset{2}{\dots}, \dots \right]$
OPT

- 1 SPRACHE
- 2 KEY = VALUE

`\setareETICHETAtext` $\left[\overset{1}{\dots} \right]$ $\left[\dots, \dots, \overset{2}{\dots}, \dots \right]$
OPT

- 1 SPRACHE
- 2 KEY = VALUE

instances: antet eticheta mathlabel taglabel unitate operator prefix suffix btxlabel

\seteazatexttitlu [...]¹ [...,...²...,...]
OPT

- 1 SPRACHE
- 2 KEY = VALUE

\seteazatitlu [...]¹,... [...,...²...,...]
OPT

- 1 ABSCHNITT
- 2

frontpartlabel	=	NAME
bodypartlabel	=	NAME
appendixlabel	=	NAME
backpartlabel	=	NAME
expansiune	=	da nu xml
catcodes	=	NAME
sectionresetset	=	NAME
sectionseparatorset	=	NAME
sectionconversionset	=	NAME
conversie	=	NAME
sectionstarter	=	BEFEHL PROCESSOR->BEFEHL
sectionstopper	=	BEFEHL PROCESSOR->BEFEHL
sectionset	=	NAME
sectionsegments	=	NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
referenceprefix	=	+ - TEXT
stil	=	STYLE BEFEHL
culoare	=	COLOR
stiltext	=	STYLE BEFEHL
culoaretex	=	COLOR
stilnumar	=	STYLE BEFEHL
culoarenumar	=	COLOR
cuplare	=	ABSCHNITT
numarpropriu	=	da nu
beforesection	=	BEFEHL
aftersection	=	BEFEHL
insidection	=	BEFEHL
numarincrement	=	da nu lista gol
punetitlu	=	da nu ascuns gol
numar	=	da nu
pagina	=	inherits: \pagina
marcaje	=	pagina reset
antet	=	start stop inalt niciunul normal gol faramarcare NAME
text	=	start stop inalt niciunul normal gol faramarcare NAME
subsol	=	start stop inalt niciunul normal gol faramarcare NAME
inainte	=	BEFEHL
dupa	=	BEFEHL
intre	=	BEFEHL
continua	=	da nu
alinieretitlu	=	da nu obiectmobil
spatiereinterliniara	=	NAME
interactiune	=	lista referinta
internalgrid	=	NAME
grid	=	normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME
alinie	=	inherits: \seteazaalinie
toleranta	=	inherits: \seteazatoleranta
strut	=	da nu
suspenda	=	linie broad ajustat niciunul NUMMER
margine	=	DIMENSION
aliniaturmator	=	da nu auto
alternativ	=	text paragraf normal margine inmargine sus centru subsol reverse NAME
latime	=	DIMENSION
numberwidth	=	DIMENSION
latimetext	=	DIMENSION
distanta	=	DIMENSION
comandainainte	=	BEFEHL
comandadupa	=	BEFEHL
comanda	=	\...##1##2
comandatext	=	\...##1
deeptextcommand	=	\...##1
comandanumar	=	\...##1
deepnumbercommand	=	\...##1

\seteazatoleranta [...,*...]

- * orizontal vertical foartestrict strict tolerant foartetolerant spatiu dilatat

`\seteazatranzitiepagina [...]`

* reset auto start aleator NUMBER

`\seteazatype [...1,...] [...2,...]`
OPT

1 NAME

2 optiune = mp lua xml parsed-xml nested tex context niciunul NAME
comanda = CSNAME
stanga = BEFEHL
dreapta = BEFEHL
tab = da nu NUMBER
compact = absolut ultim tot
escape = da nu TEXT PROCESSOR->TEXT
stil = STYLE BEFEHL
culoare = COLOR
linii = da nu normal despsilabe
spatiu = on dezactivat normal fixat dilatat

`\seteazatyping [...*,...]`

* margineimpara = DIMENSION
marginepara = DIMENSION
margine = da nu standard DIMENSION
optiune = mp lua xml parsed-xml nested tex context niciunul NAME
stil = STYLE BEFEHL
culoare = COLOR
alinie = inherits: \seteazaalinie
linii = da nu normal despsilabe
spatiu = on dezactivat normal fixat dilatat
keepttogether = da nu
inainte = BEFEHL
dupa = BEFEHL
strip = da nu NUMBER
range = NUMBER NAME
tab = da nu NUMBER
escape = da nu TEXT PROCESSOR->TEXT
aliniaturmator = da nu auto
continua = da nu
start = NUMBER
stop = NUMBER
pas = NUMBER
numerotare = fisier linie nu
blanc = inherits: \blanc

`\seteazaurl [...*,...]`

* stil = STYLE BEFEHL
culoare = COLOR

`\setelementexporttag [...1] [...2] [...3]`
OPT

1 NAME

2 export nature pdf

3 inline display mixed

`\setemeasure {...1} {...2}`

1 NAME

2 DIMENSION

`\setevalue {...1} {...2}`

1 NAME

2 CONTENT

`\setevariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setevariables [...][...2...]`

- 1 NAME
- 2 `set` = BEFEHL
`reset` = BEFEHL
`KEY` = VALUE

`\setfirstline [...]`
OPT

- * NAME

`\setflag {...}`

- * NAME

`\setfont ...`

- * FONT

`\setfontcolorsheme [...]`

- * NAME

`\setfontfeature {...}`

- * NAME

`\setfontsolution [...]`

- * NAME

`\setfontstrut`

`\setgmeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setgvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setgvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setgvariables [...][...2...]`

- 1 NAME
- 2 `set` = BEFEHL
`reset` = BEFEHL
`KEY` = VALUE

<pre> \setboxregister ¹... {²...} 1 CSNAME NUMMER 2 CONTENT </pre>
<pre> \sethyphenatedurlafter {...} * TEXT </pre>
<pre> \sethyphenatedurlbefore {...} * TEXT </pre>
<pre> \sethyphenatedurlnormal {...} * TEXT </pre>
<pre> \sethyphenationfeatures [...,[*]...] OPT * NAME reset </pre>
<pre> \setinitial [¹...] [²...²...,...] OPT OPT 1 NAME 2 inherits: \setupinitial </pre>
<pre> \setinjector [¹...] [...,²...] [³...] 1 NAME 2 NUMMER 3 BEFEHL </pre>
<pre> \setinteraction [...] * ascuns NAME </pre>
<pre> \setinterfacecommand {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceconstant {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceelements {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \setinterfacemessage {¹...} {²...} {³...} 1 NAME 2 titlu NAME NUMMER 3 TEXT </pre>

1	NAME
2	NAME

```
1  NAME
2  auto embed
3  CONTENT
```

```
* reset 1 2
```

```

1  NAME
2  CONTENT

```

```
1  NAME
2  stanga dreapta par impar
3  inherits: \setupplayer
4  CONTENT
```

```
1  NAME
2  inherits: \setupplayer
3  inherits: \seteazainconjurat
4  CONTENT
```

```

1  NAME
2  inherits: \setupplayerinherits: \seteazainconjurat
3  CONTENT

```

```

1  NAME
2  inherits: \setupplayer
3  aliniere = inherits: \seteazaalinierea
   latime   = DIMENSION
   stil     = STYLE BEFEHL
   culoare  = COLOR
4  TEXT

```

```
*  filler NAME
```

* [-+] DIMENSION

`\setMPlayer [...]1 [...]2 [...,...3...,...]OPT {...}4`

- 1 NAME
- 2 NAME
- 3 inherits: \setupplayer
- 4 CONTENT

`\setMPpositiongraphic {...}1 {...}2 {...,...3...,...}OPT`

- 1 NAME
- 2 NAME
- 3 KEY = VALUE

`\setMPpositiongraphicrange {...}1 {...}2 {...}3 {...,...4...,...}OPT`

- 1 NAME
- 2 NAME
- 3 NAME
- 4 KEY = VALUE

`\setMPtext {...}1 {...}2`

- 1 NAME
- 2 TEXT

`\setMPvariable [...]1 [...]2`

- 1 NAME
- 2 KEY = VALUE

`\setMPvariables [...]1 [...,...2...,...]OPT`

- 1 NAME
- 2 KEY = VALUE

`\setmainbodyfont`

`\setmainparbuilder [...]*`

- * implicit oneline basic NAME

`\setmarker [...]1 [...]2`

- 1 NAME
- 2 NUMMER

`\setmarking [...]1 {...}2`

- 1 BESCHRIFTUNG
- 2 TEXT

`\setmathstyle {...,*...}`

- * display text script scriptscript cramped uncramped normal impachetat mic mare NAME

<pre> \setmeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setmessagetext {...} {...} 1 NAME 2 NAME NUMBER </pre>
<pre> \setmode {...} * NAME </pre>
<pre> \setnostrut </pre>
<pre> \setnote [...]¹ [...,²...] {...}³ OPT 1 NAME 2 REFERENCE 3 TEXT </pre>
<pre> \setnotetext [...]¹ [...,²...] {...}³ OPT 1 NAME 2 REFERENCE 3 TEXT </pre>
<pre> \setnotetext [...]¹ [...,²...,...] 1 NAME 2 titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE </pre>
<pre> \setnote [...]¹ [...,²...,...] 1 NAME 2 titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE </pre>
<pre> \setobject {...}¹ {...}² \...³ {...}⁴ 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>
<pre> \setoldstyle </pre>
<pre> \setpagegrid [...]¹ [...,²...,...] {...} OPT 1 c = NUMBER r = NUMBER optiune = niciunul 2 CONTENT </pre>

\setpagereference {...} {...,²...}

1 NAME

2 REFERENCE

\setpagestate [...]¹ [...]²
OPT

1 NAME

2 NAME NUMBER

\setpagestaterealpageno {...} {...¹} {...²}

1 NAME

2 NAME NUMBER

\setpenalties \... {...¹} {...²} {...³}

1 CSNAME

2 NUMBER

3 NUMBER

\setpercentdimen {...} {...¹} {...²}

1 DIMENSION CSNAME

2 DIMENSION NUMBER

\setposition {...}

* NAME

\setpositionbox {...} \... {...¹} {...²} {...³}

1 NAME

2 CSNAME

3 CONTENT

\setpositiondata {...} {...¹} {...²} {...³} {...⁴}

1 NAME

2 DIMENSION

3 DIMENSION

4 DIMENSION

\setpositiondataplus {...} {...¹} {...²} {...³} {...⁴} {...,⁵...}

1 NAME

2 DIMENSION

3 DIMENSION

4 DIMENSION

5 TEXT

\setpositiononly {...}

* NAME

\setpositionplus {...} {...,²...} \... {...⁴}

- 1 NAME
- 2 TEXT
- 3 CSNAME
- 4 CONTENT

\setpositionstrut {...}

- * NAME

\setprofile [...]

- * niciunul fixat strict halffixed quarterfixed eightsfixed NAME

\setrandomseed {...}

- * NUMMER

\setreference [...,¹...] [...,²...,...]

- 1 REFERENCE
- 2 KEY = VALUE

\setreferencedobject {...} {...} \... {...⁴}

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setregisterentry [...¹] [...,²...,...]^{OPT} [...,³...,...]

- 1 NAME
- 2 eticheta = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternativ = TEXT
- 3 KEY = VALUE

\setreplacement [...]

- * reset NAME

\setrigidcolumnbalance ...

- * CSNAME NUMMER

\setrigidcolumnhsize {...} {...} {...³}

- 1 DIMENSION
- 2 DIMENSION
- 3 NUMMER

<p><code>\setscript [...]</code></p> <p>* hangul hanzi nihongo ethiopic thai test NAME</p>
<p><code>\setsectionblock [...]¹ [...,...²...,...]²</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 semncarte = TEXT</p>
<p><code>\setsimplecolumnhsize [...,...[*]...,...]</code></p> <p>* n = NUMMER</p> <p> latime = DIMENSION</p> <p> distante = DIMENSION</p> <p> linii = NUMMER</p>
<p><code>\setsmallbodyfont</code></p>
<p><code>\setsmallcaps</code></p>
<p><code>\setstackbox {...}¹ {...}² {...}³</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 CONTENT</p>
<p><code>\setstructurepageregister [...]¹ [...,...²...,...]² [...,...³...,...]³</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 eticheta = NAME</p> <p> keys = TEXT PROCESSOR->TEXT</p> <p> entries = TEXT PROCESSOR->TEXT</p> <p> keys:1 = TEXT</p> <p> keys:2 = TEXT</p> <p> keys:3 = TEXT</p> <p> entries:1 = TEXT</p> <p> entries:2 = TEXT</p> <p> entries:3 = TEXT</p> <p> alternativ = TEXT</p> <p>3 KEY = VALUE</p>
<p><code>\setstrut</code></p>
<p><code>\setsuperiors</code></p>
<p><code>\setsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\settabular</code></p>
<p><code>\settaggedmetadata [...,...[*]...,...]</code></p> <p>* KEY = VALUE</p>

`\setttextcontent [...]1 [...]2 [...]3 [...]4 [...]5`

OPT OPT

- 1 sus antet text subsol subsol
- 2 text margine bordura
- 3 stanga centru dreapta
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\settightobject {...}1 {...}2 \...3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightreferencedobject {...}1 {...}2 \...3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightunreferencedobject {...}1 {...}2 \...3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settrialtypesetting`

`\setuevalue {...}1 {...}2`

- 1 NAME
- 2 CONTENT

`\setugvalue {...}1 {...}2`

- 1 NAME
- 2 CONTENT

`\setunreferencedobject {...}1 {...}2 \...3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setupattachment [...,¹...] [...,²...]
OPT

```
1  NAME

2  titlu      = TEXT
   subtitlu   = TEXT
   autor      = TEXT
   fisier     = FILE
   nume       = NAME
   buffer     = BUFFER
   stare      = start stop
   metoda     = normal ascuns
   simbol     = Graph Paperclip Pushpin Default
   latime     = ajustat DIMENSION
   inaltime   = ajustat DIMENSION
   inaltime   = ajustat DIMENSION
   culoare    = COLOR
   textlayer  = NAME
   locatie    = bordurastanga borduradreaapta inmarginestanga marginedreaapta text inalt niciunul
   distanta   = DIMENSION
```

\setupbackend [...,*...]

```
*  export     = da FILE
   xhtml      = FILE
   fisier     = FILE
   intent     = NAME
   spatiu     = da nu
   xmpfile    = FILE
   format     = version implicit NAME
   nivel      = NUMMER
   optiune    = totdeauna niciodata
   profile    = FILE
```

\setupbar [...,¹...] [...,²...]
OPT

```
1  NAME

2  culoare      = COLOR
   continua     = da nu tot
   gol          = da nu
   unitate      = ex em pt in cm mm sp bp pc dd cc nc
   order        = primplan fundal
   grosimerigla = DIMENSION
   metoda       = NUMMER
   offset       = NUMMER
   dy           = NUMMER
   max          = NUMMER
   foregroundstyle = STYLE BEFEHL
   foregroundcolor = COLOR
   mp           = NAME
   stanga       = TEXT
   dreapta      = TEXT
```

\setupbleeding [...,*...]

```
*  latime      = DIMENSION
   inaltime    = DIMENSION
   offset      = DIMENSION
   hoffset     = DIMENSION
   voffset     = DIMENSION
   locatie     = t b l r bl lb br rb tl lt tr rt
   dilatata    = da nu
   pagina      = da nu
```

\setupbookmark [...,*...]

```
*  fortat      = da nu
   numar       = da nu
   numberseparatorset = NAME
   numberconversionset = NAME
   numberstarter = BEFEHL
   numberstopper = BEFEHL
   numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
   sectionblock = da nu
```

\setupbtx [¹...] [²...,...]

OPT

```
1  NAME

2  specification = implicit apa aps NAME
   dataset      = implicit NAME
   comanda      = \...##1
   stanga       = BEFEHL
   dreapta      = BEFEHL
   authorconversion = normal normalshort normalinverted invertedshort short
   etallimit     = NUMMER
   etaldisplay   = NUMMER
   etaloption    = ultim
   stopper       = initials
   interactiune  = start stop tot
   alternativ     = implicit category entry short pagina num textnum an index tag keywords autor authoryears
                  authornum authoryear
   sorttype      = normal reverse
   compress      = da nu
   implicit      = implicit NAME
   stil          = STYLE BEFEHL
   culoare       = COLOR
```

\setupbtxdataset [¹...,...] [²...,...]

OPT

```
1  NAME

2  language = SPRACHE
```

\setupbtxlabeltext [¹...] [²...,...]

OPT

```
1  SPRACHE

2  KEY = VALUE
```

\setupbtxlist [¹...] [²...,...]

OPT

```
1  NAME

2  inherits: \seteazalista
```

\setupbtxregister [¹...,...] [²...,...]

OPT

```
1  NAME

2  stare      = start stop
   dataset    = NAME
   field      = keyword range numarpagina autor
   register   = NAME
   metoda     = once
   alternativ  = normalshort invertedshort
   stil       = STYLE BEFEHL
   culoare    = COLOR
```

\setupbtxrendering [¹...,...] [²...,...]

OPT

```
1  NAME

2  staretext   = start stop
   pagestate   = start stop
   separator   = BEFEHL
   criteriu    = precedent cite aici tot niciunul
   specification = NAME
   titlu       = TEXT
   inainte     = BEFEHL
   dupa        = BEFEHL
   dataset     = NAME
   metoda      = dataset fortat local global niciunul
   sorttype    = short dataset lista referinta folosit implicit cite index
   repeta      = da nu
   group       = NAME
   numerotare  = da nu num index tag short pagina
```

\setupbtx [...]

```
*  NAME
```

`\setupbutton [...1,...] [...2,...]`
OPT

```
1 NAME

2 stare          = start stop
  aceeasipagina  = da nu gol niciunul normal implicit
  stil           = STYLE BEFEHL
  culoare        = COLOR
  culoarecontrast = COLOR
  alternativ      = ascuns
  inherits: \seteazainconjurat
```

`\setupcharacterkerning [...1,...] [...2,...]`
OPT

```
1 NAME

2 factor      = max NUMBER
  latime      = DIMENSION
  features    = NAME
  stil        = STYLE BEFEHL
  culoare     = COLOR
```

`\setupcharacterspacing [...1] [...2] [...3,...]`
OPT

```
1 NAME

2 NUMMER

3 stanga      = NUMBER
  dreapta     = NUMBER
  alternativ    = 0 1
```

`\setupchemical [...1,...] [...2,...]`
OPT

```
1 NAME

2 strut        = inherits: \value-strut
  latime       = ajustat niciunul NUMBER
  inaltime     = ajustat niciunul NUMBER
  stanga       = ajustat niciunul NUMBER
  dreapta      = ajustat niciunul NUMBER
  sus         = ajustat niciunul NUMBER
  jos          = ajustat niciunul NUMBER
  scala        = mic mediu mare normal NUMBER
  rotatie      = NUMBER
  symalinie    = auto
  axa          = on dezactivat
  culoareframe = COLOR
  grosimerigla = DIMENSION
  offset       = DIMENSION
  unitate      = DIMENSION
  factor       = NUMBER
  frame        = on dezactivat
  culoarerigla = COLOR
  fonttext     = inherits: \seteazafonttext
  dimensiune   = mic mediu mare
  stil         = STYLE BEFEHL
  culoare      = COLOR
```

`\setupchemicalframed [...1,...] [...2,...]`
OPT

```
1 NAME

2 inherits: \seteazainconjurat
```

`\setupcollector [...1,...] [...2,...]`
OPT

```
1 NAME

2 rotatie = stanga dreapta intern extern NUMBER
  colt    = stanga centru dreapta sus subsol
  x       = DIMENSION
  y       = DIMENSION
  hoffset = DIMENSION
  voffset = DIMENSION
  locatie = stanga centru dreapta sus subsol linie l c r m t b g
  stare   = start stop
```


\setupcolumnspan [...,..^{*}...,...]

* n = NUMMER
inherits: \seteazainconjurat

\setupcombination [...,..¹...] [...,..²...,...]
OPT

1 NAME
2 nx = NUMMER
ny = NUMMER
latime = ajustat DIMENSION
inaltime = ajustat DIMENSION
locatie = stanga centru dreapta sus subsol
distanta = DIMENSION
alternativ = eticheta text
alinie = inherits: \seteazaalinie
continua = da nu
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR

\setupcontent [...,..^{*}...,...]

* inherits: \seteazalista

\setupcounter [...,..¹...] [...,..²...,...]
OPT

1 NAME
2 start = NUMMER
counter = NAME
metoda = pagina
stare = start stop
mod = bypagina byblock bytext byantet byABSCHNITT
prefix = da nu
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
numberorder = reverse
numberseparatorset = NAME
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
type = primul precedent urmatorul ultim numar
criteriu = strict positiv tot
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupdataset [...,..^{*}...,...]

* intarziere = da nu

`\setupdelimitedtext [...1,...] [...2...]`
OPT

```
1  NAME

2  inainte      = BEFEHL
   dupa         = BEFEHL
   language     = local global SPRACHE
   metoda       = font
   repeta       = da nu
   locatie      = text paragraf margine
   stanga       = BEFEHL
   mijloc       = BEFEHL
   dreapta      = BEFEHL
   nextleft     = BEFEHL
   nextright    = BEFEHL
   spatiuinainte = inherits: \blanc
   spatiudupa   = inherits: \blanc
   marginestanga = da nu standard DIMENSION
   marginedreapta = da nu standard DIMENSION
   aliniat      = inherits: \seteazaaliniat
   aliniaturmator = da nu auto
   stil         = STYLE BEFEHL
   culoare      = COLOR
   stilsimbol   = STYLE BEFEHL
   culoaresimbol = COLOR
```

`\setupdescription [...1,...] [...2...]`
OPT

```
1  NAME

2  titlu        = da nu
   nivel        = NUMMER
   text         = TEXT
   headcommand  = \...##1
   inainte      = BEFEHL
   dupa         = BEFEHL
   intre        = BEFEHL
   alternativ    = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                  outermargin serried suspendat sus comanda NAME
   aliniere     = inherits: \seteazaalinierea
   headalign    = inherits: \seteazaalinierea
   aliniat      = inherits: \seteazaaliniat
   display      = da nu
   aliniaturmator = da nu auto
   latime       = ajustat broad linie DIMENSION
   distanta     = niciunul DIMENSION
   suspenda     = ajustat broad niciunul margine NUMMER
   closesymbol  = BEFEHL
   closecommand = \...##1
   expansiune   = da nu xml
   exemplu      = TEXT
   margine      = da nu standard DIMENSION
   stil         = STYLE BEFEHL
   culoare      = COLOR
   stiltitlu    = STYLE BEFEHL
   culoaretitlu = COLOR
```

`\setupdirections [...*...]`

```
*  bidi    = on dezactivat local global
   metoda  = unu doi implicit
   fences  = da nu
```

`\setupdocument [...*...]`

```
*  inainte      = BEFEHL
   dupa         = BEFEHL
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY          = VALUE
```

\setupeffect [...,¹...] [...,²...,...]
OPT

1 NAME

2 metoda = niciunul comanda
dilatata = NUMMER
grosimerigla = NUMMER
alternativ = normal intern extern ambele ascuns dilatata

\setupenumeration [...,¹...] [...,²...,...]
OPT

1 NAME

2 titlu = da nu
numar = da nu
comandanumar = \...##1
distantatitlu = DIMENSION
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
titlecommand = \...##1
titleleft = BEFEHL
titleright = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
simbol = BEFEHL
starter = BEFEHL
stopper = BEFEHL
cuplare = NAME
counter = NAME
nivel = NUMMER
text = TEXT
headcommand = \...##1
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
alternativ = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
outermargin serried suspendat sus comanda NAME

alinieri = inherits: \seteazaalinieri
headalign = inherits: \seteazaalinieri
aliniat = inherits: \seteazaaliniat
display = da nu
aliniaturmator = da nu auto
latime = ajustat broad linie DIMENSION
distanta = niciunul DIMENSION
suspenda = ajustat broad niciunul margine NUMMER
closesymbol = BEFEHL
closecommand = \...##1
expansiune = da nu xml
exemplu = TEXT
margine = da nu standard DIMENSION
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
inherits: \setupcounter

\setupenv [...,*...,...]

* set = BEFEHL
reset = BEFEHL
KEY = VALUE

\setupexport [...,*...,...]

* alinieri = flushleft centru flushright normal
fonttext = DIMENSION
latime = DIMENSION
titlu = TEXT
subtitlu = TEXT
autor = TEXT
alternativ = html div
properties = da nu
hyphen = da nu
cssfile = FILE
primapagina = FILE
ultimpagina = FILE

`\setupexternalfigure [...1,...] [...2,...]`
OPT

```

1  NAME

2  latime           = DIMENSION
   inaltime        = DIMENSION
   eticheta        = NAME
   pagina          = NUMMER
   obiect          = da nu
   prefix          = TEXT
   metoda          = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controale       = da nu
   previzualizare  = da nu
   mask            = niciunul
   rezolutie       = NUMMER
   culoare         = COLOR
   arguments       = TEXT
   repeta         = da nu
   factor          = ajustat broad max auto implicit
   hfactor         = ajustat broad max auto implicit
   factorw         = ajustat broad max auto implicit
   latimemaxima    = DIMENSION
   inaltimemaxima  = DIMENSION
   equalwidth      = DIMENSION
   equalheight     = DIMENSION
   scala           = NUMMER
   xscala          = NUMMER
   yscala          = NUMMER
   s               = NUMMER
   sx              = NUMMER
   sy              = NUMMER
   linii           = NUMMER
   locatie         = local global implicit
   director        = PATH
   optiune         = test incadrat gol
   foregroundcolor = COLOR
   reset           = da nu
   fundal          = culoare primplan NAME
   frame           = on dezactivat
   culoarefundal   = COLOR
   aliniere        = inherits: \seteazaalinierea
   xmax            = NUMMER
   ymax            = NUMMER
   frames          = on dezactivat
   interactiune    = da tot niciunul referinta layer semncarte
   fonttext        = DIMENSION
   comment         = BEFEHL TEXT
   dimensiune      = niciunul media crop trim art
   cache           = PATH
   resources       = PATH
   display         = FILE
   conversie       = TEXT
   order           = LISTE
   crossreference  = da nu NUMMER

```

`\setupexternalsoundtracks [...*,...]`

* optiune = repetat

`\setupfieldbody [...1,...] [...2,...]`
OPT

```

1  NAME

2  category = NAME
   inherits: \setupfieldcategory

```

`\setupfieldcategory [...,1...] [...,2...]`
OPT

```

1  NAME

2  start      = NUMBER
   stil       = STYLE BEFEHL
   culoare    = COLOR
   type       = radio sub text linie push check signature
   values     = TEXT
   implicit   = TEXT
   culoareframecamp = COLOR
   culoarefundalcamp = COLOR
   latime     = DIMENSION
   inaltime   = DIMENSION
   inaltime   = DIMENSION
   aliniere   = stanga centru dreapta flushleft center flushright
   n          = NUMBER
   simbol     = NAME
   fieldlayer = NAME
   optiune    = readonly obligatoriu protejat sortat nedisponibil nocheck fixat fisier ascuns tiparibil auto
   clickintru = REFERENCE
   clickies   = REFERENCE
   regiuneintrare = REFERENCE
   regiuneiesire = REFERENCE
   dupatasta  = REFERENCE
   format     = REFERENCE
   verifica   = REFERENCE
   calculeaza = REFERENCE
   focusin    = REFERENCE
   focusout   = REFERENCE
   openpage   = REFERENCE
   closepage  = REFERENCE

```

`\setupfieldcontentframed [...,1...] [...,2...]`
OPT

```

1  NAME

2  inherits: \seteazainconjuratinherits: \setupfieldcategory

```

`\setupfieldlabelframed [...,1...] [...,2...]`
OPT

```

1  NAME

2  inherits: \seteazainconjurat

```

`\setupfieldtotalframed [...,1...] [...,2...]`
OPT

```

1  NAME

2  inainte    = BEFEHL
   dupa       = BEFEHL
   intre      = BEFEHL
   distanta   = DIMENSION
   alternativ  = reset eticheta incadrat orizontal vertical
   inherits: \seteazainconjurat

```

`\setupfiller [...,1...] [...,2...]`
OPT

```

1  NAME

2  marginestanga = DIMENSION
   marginedreapta = DIMENSION
   stanga        = BEFEHL
   dreapta       = BEFEHL
   alternativ     = simbol dilatat rigla spatiu
   metoda        = local global centru broad
   latime        = DIMENSION
   inaltime      = DIMENSION
   inaltime      = DIMENSION
   offset        = DIMENSION
   distanta      = DIMENSION
   aliniere      = stanga dreapta centru flushleft flushright intern extern
   simbol        = BEFEHL
   stil          = STYLE BEFEHL
   culoare       = COLOR

```

`\setupfirstline [...1,...] [...2,...]`
OPT

1 NAME
2 n = NUMMER
alternativ = implicit linie cuvant
stil = STYLE BEFEHL
culoare = COLOR

`\setupfittingpage [...1,...] [...2,...]`
OPT

1 NAME
2 pagestate = start stop
comanda = \...##1
margine = pagina
scala = NUMMER
hartie = auto default NAME
inherits: \seteazainconjurat

`\setupfloatcaption [...1,...] [...2,...]`
OPT

1 NAME
2 suffix = BEFEHL
suffixseparator = BEFEHL
suffixstopper = BEFEHL
locatie = stanga dreapta centru jos inalt grila overlay intern extern innermargin outermargin marginestanga
marginedreapta lefthanging righthanging suspenda sus subsol dilatat niciunul implicit
comanda = \...##1
comandanumar = \...##1
comandatext = \...##1
spatiuinainte = inherits: \blanc
spaceinbetween = inherits: \blanc
spatiudupa = inherits: \blanc
distanta = DIMENSION
intre = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR
offsetsus = DIMENSION
offsetjos = DIMENSION
numar = da nu niciunul
group = TEXT
marginestanga = DIMENSION
marginedreapta = DIMENSION
innermargin = DIMENSION
outermargin = DIMENSION
aliniere = inherits: \seteazaalinierea
latime = ajustat max DIMENSION
latimeminima = ajustat DIMENSION
latimemaxima = DIMENSION
inherits: \setupcounter

`\setupfontexpansion [...1] [...2,...]`

1 NAME
2 vector = NAME
factor = NUMMER
dilatat = NUMMER
shrink = NUMMER
pas = NUMMER

`\setupfontprotrusion [...1] [...2,...]`

1 NAME
2 vector = NAME
factor = NUMMER
stanga = NUMMER
dreapta = NUMMER

`\setupfonts [...*,...]`

* language = nu auto

`\setupfontsolution [...1,...] [...2,...]`
OPT

1 NAME

2 goodies = FILE
 solution = NAME
 less = NAME
 more = NAME
 metoda = preroll split normal reverse aleator
 criteriu = NUMMER

`\setupformula [...1,...] [...2,...]`
OPT

1 NAME

2 locatie = stanga dreapta
 aliniere = stanga centru dreapta flushleft center flushright normal
 strut = da nu
 distanta = DIMENSION
 stanga = BEFEHL
 dreapta = BEFEHL
 spatiuinainte = inherits: \blanc
 spatiudupa = inherits: \blanc
 comandanumar = \...##1
 culoare = COLOR
 stilnumar = STYLE BEFEHL
 culoarenumar = COLOR
 optiune = impachetat tight centru incadrat inherits: \seteazafonttext
 margine = da nu standard DIMENSION
 marginestanga = DIMENSION
 marginedreapta = DIMENSION
 alternativ = NAME
 aliniaturmator = da nu auto
 grid = inherits: \snaptogrid
 frame = numar
 inherits: \setupcounter

`\setupformulaframed [...1,...] [...2,...]`
OPT

1 NAME

2 inherits: \seteazainconjurat

`\setupframedcontent [...1,...] [...2,...]`
OPT

1 NAME

2 stanga = BEFEHL
 dreapta = BEFEHL
 leftoffser = DIMENSION
 offsetdreapta = DIMENSION
 offsetsus = DIMENSION
 offsetjos = DIMENSION
 corectielinie = da nu
 inherits: \seteazainconjurat

`\setupframedtext [...1,...] [...2,...]`
OPT

1 NAME

2 stanga = BEFEHL
 dreapta = BEFEHL
 intern = BEFEHL
 locatie = stanga dreapta centru niciunul
 corectieadancime = on dezactivat
 fonttext = inherits: \seteazafonttext
 aliniat = inherits: \seteazaaliniat
 stil = STYLE BEFEHL
 culoare = COLOR
 inherits: \seteazainconjuratinherits: \setupplacement

`\setupglobalreferenceprefix [...]`

* + - TEXT

`\setupheadalternative [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 alternativ = orizontal vertical
renderingsetup = NAME

`\setuphelp [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 inherits: \seteazainconjurat

`\setuphigh [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 distanta = DIMENSION
up = DIMENSION
stil = STYLE BEFEHL
culoare = COLOR

`\setuphighlight [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 comanda = da nu
stil = STYLE BEFEHL
culoare = COLOR

`\setuphyphenation [...,*...]`

- * metoda = original tex implicit hyphenate expanded traditional niciunul

`\setupindentedtext [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 inainte = BEFEHL
dupa = BEFEHL
distanta = DIMENSION
exemplu = TEXT
text = TEXT
latime = ajustat broad DIMENSION
separator = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR

`\setupindex [...,1...] [...,2...]`
OPT

- 1 NUMMER
- 2 inherits: \seteazaregistru

`\setupinitial [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 n = NUMMER
m = NUMMER
inainte = BEFEHL
distanta = DIMENSION
hoffset = DIMENSION
voffset = linie DIMENSION
stil = STYLE BEFEHL
culoare = COLOR
font = FONT
text = TEXT
locatie = margine text
metoda = primul ultim auto niciunul

\setupinsertion [...,¹...] [...,²...] OPT

1 NAME

2 locatie = pagina text coloane firstcolumn lastcolumn

\setupitaliccorrection [...,*...]

* text totdeauna global niciunul

\setupitemgroup [...¹] [...²,...] [...³,...] [...⁴,...] OPT OPT OPT OPT

1 NAME

2 fiecare NUMMER

3 intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine lamargine intext larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat reverse coloane unu doi trei patru cinci six seven eight nine standard NUMMER*broad NUMMER*serried orizontal NAME

4 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
inaintetitlu = BEFEHL
dupatitlu = BEFEHL
textstanga = BEFEHL
textdreapta = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
factor = NUMMER
pas = DIMENSION
latime = DIMENSION
distanta = DIMENSION
margine = da nu standard DIMENSION
marginestanga = da nu standard DIMENSION
marginedreapta = da nu standard DIMENSION
aliniere = inherits: \seteazaalinierea
aliniat = inherits: \seteazaaliniat
start = NUMMER
symaliniere = stanga centru dreapta flushleft center flushright
simbol = NAME
n = NUMMER
aliniaturmator = da nu auto
intern = BEFEHL
comanda = CSNAME
elemente = NUMMER
latimemaxima = DIMENSION
itemalign = stanga dreapta centru flushleft flushright intern extern
alignsymbol = da nu
textdistance = mic mediu mare niciunul spatiu DIMENSION
punestopper = da nu
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
stilmarcaj = STYLE BEFEHL
culoaremarcaj = COLOR
stilsimbol = STYLE BEFEHL
culoaresimbol = COLOR
inherits: \setupcounter

OPT

2	inainte	=	BEFEHL
	dupa	=	BEFEHL
	intre	=	BEFEHL
	inaintetitlu	=	BEFEHL
	dupatitlu	=	BEFEHL
	textstanga	=	BEFEHL
	textdreapta	=	BEFEHL
	stanga	=	BEFEHL
	dreapta	=	BEFEHL
	factor	=	NUMMER
	pas	=	DIMENSION
	latime	=	DIMENSION
	distanța	=	DIMENSION
	optiune	=	intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine lamargine intext larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat reverse coloane unu doi trei patru cinci six seven eight nine standard NUMMER*broad NUMMER*serried orizontal NAME
	margine	=	da nu standard DIMENSION
	marginestanga	=	da nu standard DIMENSION
	marginedreapta	=	da nu standard DIMENSION
	alinieri	=	inherits: \seteazaalinieria
	aliniat	=	inherits: \seteazaaliniat
	start	=	NUMMER
	symaliniere	=	stanga centru dreapta flushleft center flushright
	simbol	=	NAME
	n	=	NUMMER
	aliniaturmator	=	da nu auto
	intern	=	BEFEHL
	comanda	=	CSNAME
	elemente	=	NUMMER
	latimemaxima	=	DIMENSION
	itemalign	=	stanga dreapta centru flushleft flushright intern extern
	alignsymbol	=	da nu
	textdistance	=	mic mediu mare niciunul spatiu DIMENSION
	punestopper	=	da nu
	stil	=	STYLE BEFEHL
	culoare	=	COLOR
	stiltitlu	=	STYLE BEFEHL
	culoaretitlu	=	COLOR
	stilmarcaj	=	STYLE BEFEHL
	culoaremarcaj	=	COLOR
	stilsimbol	=	STYLE BEFEHL
	culoaresimbol	=	COLOR
	inherits:	=	\setupcounter

OPT

OPT

OPT

```
instances: enumerate
```

OPT

OPT

OPT

```
3 inherits: \setupitemgroup
```

\setuplabel [...¹,...] [...²,...]

OPT

```

1  NAME

2  titlu           = da nu
   numar          = da nu
   comandanumar   = \...##1
   distantatitlu  = DIMENSION
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   stanga         = BEFEHL
   dreapta        = BEFEHL
   simbol         = BEFEHL
   starter        = BEFEHL
   stopper        = BEFEHL
   cuplare        = NAME
   counter        = NAME
   nivel          = NUMMER
   text           = TEXT
   headcommand    = \...##1
   inainte        = BEFEHL
   dupa           = BEFEHL
   intre          = BEFEHL
   alternativ      = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                   outermargin serried suspendat sus comanda intext NAME

   aliniere       = inherits: \seteazaalinierea
   headalign      = inherits: \seteazaalinierea
   aliniat        = inherits: \seteazaaliniat
   display        = da nu
   aliniaturmator = da nu auto
   latime         = ajustat broad linie DIMENSION
   distanta       = niciunul DIMENSION
   suspenda       = ajustat broad niciunul margine NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expansiune     = da nu xml
   exemplu        = TEXT
   margine        = da nu standard DIMENSION
   stil           = STYLE BEFEHL
   culoare        = COLOR
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   inherits: \setupcounter

```

\setuplayer [...¹,...] [...²,...]

OPT

```

1  NAME

2  stare          = start stop continuu urmatorul repetat
   optiune        = test
   pagina         = NUMMER
   latime         = DIMENSION
   inaltime       = DIMENSION
   region         = NAME
   rotatie        = stanga dreapta intern extern NUMMER
   pozitie        = da nu overlay
   hoffset        = max DIMENSION
   voffset        = max DIMENSION
   offset         = DIMENSION
   dx             = DIMENSION
   dy             = DIMENSION
   sx             = NUMMER
   sy             = NUMMER
   x              = DIMENSION
   y              = DIMENSION
   colt           = stanga centru dreapta sus subsol
   locatie        = grila stanga centru dreapta sus subsol linie l c r m t b g
   linie          = NUMMER
   coloana        = NUMMER
   directie       = normal reverse
   douafete       = da nu
   metoda         = ajustat overlay
   repeta         = da
   preset         = lefttop righttop leftbottom rightbottom centru middletop middlebottom middleleft middleright lefttoleft
                   lefttopright NAME

```

`\setuplayeredtext [...1,...] [...2,...]`
OPT

1 NAME
 2 stil = STYLE BEFEHL
 culoare = COLOR
 inherits: \seteazainconjurat

`\setuplayouttext [...1] [...2] [...3,...]`
OPT

1 sus antet text subsol subsol
 2 text margine bordura
 3 stare = start stop gol inalt niciunul normal faramarcare NAME
 stil = STYLE BEFEHL
 culoare = COLOR
 strut = da nu
 n = NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 stilstanga = STYLE BEFEHL
 stildreapta = STYLE BEFEHL
 culoarestanga = COLOR
 culoaredreapta = COLOR
 latime = DIMENSION
 latimestanga = DIMENSION
 marginedreapta = DIMENSION

`\setuplinefiller [...1,...] [...2,...]`
OPT

1 NAME
 2 locatie = stanga dreapta ambele
 scop = stanga dreapta local
 mp = NAME
 inaltime = DIMENSION
 inaltime = DIMENSION
 distanta = DIMENSION
 threshold = DIMENSION
 grosimerigla = DIMENSION
 inainte = BEFEHL
 dupa = BEFEHL
 culoare = COLOR
 stiltext = STYLE BEFEHL
 culoaretext = COLOR
 aliniere = inherits: \seteazaalinierea

`\setuplinefillers [...1,...] [...2,...]`
OPT

1 NAME
 2 inherits: \setuplinefiller

`\setuplinenote [...1,...] [...2,...]`
OPT

1 NAME
 2 compress = da nu
 compressmethod = separator stopper spatiu
 compressseparator = BEFEHL
 compressdistance = DIMENSION
 inherits: \setupnote

`\setuplinetable [...]1 [...]2 [...,...]3 [...,...]`

OPT OPT

```
1 r c
2 impar par antet NUMMER
3 linii      = ajustat NUMMER
  inainte    = BEFEHL
  dupa       = BEFEHL
  intre      = BEFEHL
  dilatata   = da nu DIMENSION
  latimemaxima = ajustat DIMENSION
  nstanga    = NUMMER
  n          = NUMMER
  repeta     = da nu
  nx         = NUMMER
  latime     = DIMENSION
  inaltime   = ajustat linie DIMENSION
  distanta   = DIMENSION
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  aliniere    = inherits: \seteazaalinierea
  fundal     = culoare
  culoarefundal = COLOR
  xheight    = max DIMENSION
  xdepth     = max DIMENSION
  stil       = STYLE BEFEHL
  culoare    = COLOR
```

`\setuplistalternative [...]1 [...,...]2 [...,...]`

OPT

```
1 NAME
2 inainte = BEFEHL
  dupa    = BEFEHL
  comanda = \...##1##2##3
  renderingsetup = NAME
  latime       = DIMENSION
  distanta     = DIMENSION
  dilatata     = DIMENSION
  filler       = BEFEHL
```

`\setuplistextra [...]1 [...,...]2 [...,...]`

OPT

```
1 NAME
2 inainte = BEFEHL
  dupa    = BEFEHL
```

`\setuplocalfloats [...,...]* [...,...]`

```
* inainte = BEFEHL
  dupa    = BEFEHL
  intre   = BEFEHL
```

`\setuplocalinterlinespace [...]1 [...,...]2 [...,...]`

OPT

```
1 NAME
2 inherits: \seteazaspatiuinterliniar
```

`\setuplocalinterlinespace [...]* [...]`

OPT

```
* on dezactivat reset auto mic mediu mare NUMMER DIMENSION
```

`\setuplocalinterlinespace [...]*`

```
* NAME
```

`\setuplow [...,1...] [...,2...,...]`
OPT

1 NAME
 2 distanta = DIMENSION
 down = DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 distanta = DIMENSION
 up = DIMENSION
 down = DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 up = DIMENSION
 down = DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupMPgraphics [...,*...,...]`

* culoare = local global
 mpy = FILE

`\setupMPinstance [...,1...] [...,2...,...]`
OPT

1 NAME
 2 format = metafun mpost
 initializations = da nu
 setups = NAME
 stiltext = STYLE BEFEHL
 culoaretext = COLOR
 extensions = da nu
 metoda = binary decimal double scaled implicit

`\setupMPpage [...,*...,...]`

* inherits: \setupfittingpage

`\setupMPvariables [1...] [...,2...,...]`
OPT

1 NAME
 2 KEY = VALUE

`\setupmarginblock [...,1...] [...,2...,...]`
OPT

1 NAME
 2 stare = start stop
 latime = DIMENSION
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 aliniere = inherits: \seteazaalinierea
 stil = STYLE BEFEHL
 culoare = COLOR
 sus = BEFEHL
 jos = BEFEHL
 locatie = stanga dreapta centru inmarginie
 stanga = BEFEHL
 dreapta = BEFEHL

`\setupmargindata [...1,...] [...2,...]`
OPT

```

1  NAME

2  strut      = da nu auto cap ajustat linie implicit CHARACTER
   comanda    = \...##1
   latime     = DIMENSION
   aliniere   = inherits: \seteazaalinierea
   anchor     = region text
   locatie    = stanga dreapta intern extern
   metoda     = sus linie primul adancime inaltime
   category   = implicit bordura
   scop       = local global
   optiune    = text paragraf
   margine    = local normal margine bordura
   distanta   = DIMENSION
   hoffset    = DIMENSION
   voffset    = DIMENSION
   dy         = DIMENSION
   spatiujos  = DIMENSION
   threshold  = DIMENSION
   linie      = NUMMER
   stack      = da continuu
   stil       = STYLE BEFEHL
   culoare    = COLOR

```

`\setupmarginframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \seteazainconjurat

```

`\setupmarginrule [...1] [...2,...]`
OPT

```

1  NUMMER

2  inherits: \setupsidebar

```

`\setupmathalignment [...1,...] [...2,...]`
OPT

```

1  NAME

2  n          = NUMMER
   m          = NUMMER
   distanta   = DIMENSION
   aliniere   = stanga centru dreapta normal

```

`\setupmathcases [...1,...] [...2,...]`
OPT

```

1  NAME

2  stanga      = BEFEHL
   dreapta    = BEFEHL
   strut      = da nu
   stil       = STYLE BEFEHL
   distanta   = DIMENSION
   numberdistance = DIMENSION

```

`\setupmathematics [...1,...] [...2,...]`
OPT

```
1 NAME

2 openup          = da nu
  setsimbol       = NAME
  functionstyle   = STYLE BEFEHL
  compact         = da nu
  aliniere        = l2r r2l
  bidi           = da nu
  sygreek         = normal italic niciunul
  lcgreek         = normal italic niciunul
  ucgreek         = normal italic niciunul
  italics         = 1 2 3 4 niciunul reset
  autopunctuation = da nu tot
  setups          = NAME
  domain         = NAME reset
  stiltext        = STYLE BEFEHL
  culoaretext     = COLOR
  functioncolor   = COLOR
  integral        = limits nolimits autolimits displaylimits niciunul
  stylealternative = NAME
  implicit        = normal italic
  fraction        = ams ctx
```

`\setupmathfence [...1,...] [...2,...]`
OPT

```
1 NAME

2 comanda = da nu
  stanga  = NUMMER
  mijloc  = NUMMER
  dreapta = NUMMER
  mathstyle = display text script scriptscript cramped uncramped normal impachetat mic mare
  culoare  = COLOR
  stare    = auto
```

`\setupmathfraction [...1,...] [...2,...]`
OPT

```
1 NAME

2 distantasus = DIMENSION
  distantajos = DIMENSION
  margine     = DIMENSION
  culoare     = COLOR
  strut       = da nu math tight
  alternativ   = intern extern ambele
  rigla       = da nu auto
  stanga      = NUMMER
  dreapta     = NUMMER
  grosimerigla = DIMENSION
  mathstyle   = STYLE BEFEHL
  distanta    = nu niciunul overlay
```

`\setupmathframed [...1,...] [...2,...]`
OPT

```
1 NAME

2 inherits: \seteazainconjurat
```

`\setupmathlabeltext [...1,...] [...2,...]`
OPT

```
1 SPRACHE

2 KEY = VALUE
```

`\setupmathmatrix [...1,...] [...2,...]`
OPT

```
1 NAME

2 stanga = BEFEHL
  dreapta = BEFEHL
  strut   = da nu NUMMER
  aliniere = stanga centru dreapta normal
  stil     = STYLE BEFEHL
  distanta = DIMENSION
  locatie  = sus subsol inalt jos lohi normal
```


`\setupmathornament [...1,...] [...2...,...]`
OPT

1 NAME
 2 alternativ = mp
 culoare = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathradical [...1,...] [...2...,...]`
OPT

1 NAME
 2 alternativ = implicit normal mp
 culoare = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathstackers [...1,...] [...2...,...]`
OPT

1 NAME
 2 stanga = BEFEHL
 dreapta = BEFEHL
 topcommand = \...##1
 bottomcommand = \...##1
 middlecommand = \...##1
 mp = NAME
 mpheight = DIMENSION
 mpdepth = DIMENSION
 mpoffset = DIMENSION
 culoare = COLOR
 hoffset = DIMENSION
 voffset = DIMENSION
 inaltimeminima = DIMENSION
 mindepth = DIMENSION
 mathclass = rel ord
 offset = min max normal
 locatie = sus subsol inalt jos centru NUMMER
 strut = da nu
 alternativ = normal implicit mp
 latimeminima = DIMENSION
 distanta = DIMENSION
 moffset = DIMENSION
 order = normal reverse
 mathlimits = da nu

`\setupmathstyle [...*,...]`

* display text script scriptscript cramped uncramped normal impachetat mic mare NAME

`\setupmixedcolumns [...1,...] [...2...,...]`
OPT

1 NAME
 2 grid = inherits: \definegridsnapping
 grosimerigla = DIMENSION
 metoda = otr box
 inainte = BEFEHL
 dupa = BEFEHL
 distanta = DIMENSION
 n = NUMMER
 inaltimemaxima = DIMENSION
 latimemaxima = DIMENSION
 pas = DIMENSION
 profile = NAME
 aliniere = inherits: \seteazaalinierea
 setups = NAME
 balanta = da nu
 splitmethod = niciunul fixat
 alternativ = local global
 internalgrid = linie jumatatelinie
 separator = rigla
 strut = da nu
 culoare = COLOR
 culoarerigla = COLOR
 directie = normal reverse
 inherits: \seteazainconjurat

`\setupmodule [...]1 [...]2...`
OPT

1 FILE
 2 test = da nu
 KEY = VALUE

`\setupnotation [...]1 [...]2...`
OPT

1 NAME
 2 titlu = da nu
 numar = da nu
 type = note
 comandanumar = \...##1
 distantatitlu = DIMENSION
 stiltitlu = STYLE BEFEHL
 culoaretitlu = COLOR
 titlecommand = \...##1
 titleleft = BEFEHL
 titleright = BEFEHL
 stanga = BEFEHL
 dreapta = BEFEHL
 simbol = BEFEHL
 starter = BEFEHL
 stopper = BEFEHL
 cuplare = NAME
 counter = NAME
 nivel = NUMMER
 text = TEXT
 headcommand = \...##1
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 alternativ = stanga dreapta inmargine instanga indreapta margine marginestanga marginedreapta innermargin
 outermargin serried suspendat sus comanda note NAME
 aliniere = inherits: \seteazaalinierea
 headalign = inherits: \seteazaalinierea
 aliniat = inherits: \seteazaaliniat
 display = da nu
 aliniaturmator = da nu auto
 latime = ajustat broad linie DIMENSION
 distanta = niciunul DIMENSION
 suspenda = ajustat broad niciunul margine NUMMER
 closesymbol = BEFEHL
 closecommand = \...##1
 expansiune = da nu xml
 exemplu = TEXT
 margine = da nu standard DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR
 stiltitlu = STYLE BEFEHL
 culoaretitlu = COLOR
 inherits: \setupcounter

`\setupnote [...1,...] [...2,...]`
OPT

```

1  NAME

2  interactiune      = da nu numar text tot
   symbolcommand    = \...##1
   comandatext      = \...##1
   indicator        = da nu
   separatorstext    = BEFEHL
   latime           = DIMENSION
   inaltime         = DIMENSION
   distanta        = DIMENSION
   rulecommand      = BEFEHL
   rigla            = on dezactivat normal stanga dreapta comanda paragraf
   split            = tolerant strict foartestRICT NUMMER
   factor           = NUMMER
   locatie          = text pagina inalt subsol niciunul coloane firstcolumn lastcolumn
   urmatorul        = BEFEHL
   n                = NUMMER
   culoarerigla     = COLOR
   grosimerigla     = DIMENSION
   setups           = NAME
   spatiereinterliniara = NAME
   paragraf         = da nu
   inainte          = BEFEHL
   dupa             = BEFEHL
   intre            = BEFEHL
   scop             = pagina
   distantacoloane  = DIMENSION
   continua         = da nu
   alternativ        = grila fixat coloane note niciunul
   criteriu         = pagina
   fonttext         = inherits: \seteazafonttext
   aliniere         = inherits: \seteazaaliniere
   stiltext         = STYLE BEFEHL
   culoaretext      = COLOR
   anchor           = urmatorul
   inherits: \seteazainconjurat

```

`\setupoffset [...*,...]`

* inherits: \setupoffsetbox

`\setupoffsetbox [...*,...]`

```

*  x                = DIMENSION
   y                = DIMENSION
   offsetstanga     = DIMENSION
   offsetdreapta    = DIMENSION
   offsetsus        = DIMENSION
   offsetjos        = DIMENSION
   metoda          = fixat
   latime           = DIMENSION
   inaltime         = DIMENSION
   inaltime         = DIMENSION
   locatie          = stanga centru dreapta sus subsol linie l c r m t b g

```

`\setupoperatorstext [...1] [...2,...]`
OPT

```

1  SPRACHE

2  KEY = VALUE

```

`\setupoutputroutine [...1] [...2,...]`
OPT

```

1  NAME

2  KEY = CSNAME

```

`\setupoutputroutine [...*]`

* NAME

\setuppagechecker [...,¹...] [...,²...] OPT

1 NAME
2 linii = NUMMER
offset = DIMENSION
metoda = 0 1 2 3
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL

\setuppagegrid [...,¹...] [...,²...] OPT

1 NAME
2 n = NUMMER
nstanga = NUMMER
ndreapta = NUMMER
latime = DIMENSION auto
distanta = DIMENSION
linii = NUMMER
latimemaxima = DIMENSION
inaltimemaxima = DIMENSION
directie = normal reverse
pagina = inherits: \pagina
inherits: \seteazainconjurat

\setuppagegridarea [...,¹...] [...,²...] OPT

1 NAME
2 stare = start stop repetat
x = NUMMER
y = NUMMER
nx = NUMMER
ny = NUMMER
stil = STYLE BEFEHL
culoare = COLOR
clipoffset = DIMENSION
offsetdreapta = DIMENSION
inherits: \seteazainconjurat

\setuppagegridareatext [...¹] [...²]

1 NAME
2 TEXT

\setuppagegridlines [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppagegridspan [...,¹...] [...,²...] OPT

1 NAME
2 n = NUMMER
stil = STYLE BEFEHL
culoare = COLOR
inainte = BEFEHL
dupa = BEFEHL
inherits: \seteazainconjurat

\setuppagegridstart [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppageinjection [...,¹...] [...,²...,...]
OPT

1 NAME
2 stare = precedent urmatorul NUMMER
intarziere = da nu
alternativ = figura buffer setups niciunul NAME
pagina = inherits: \pagina
pagestate = start stop
n = NUMMER
inherits: \seteazainconjurat

\setuppageinjectionalternative [...,¹...] [...,²...,...]
OPT

1 NAME
2 renderingsetup = NAME

\setuppageshift [...¹...] [...²...] [...³...]
OPT OPT

1 pagina foaie
2 NAME
3 NAME

\setuppagestate [...,^{*}...,...]

* intarziere = da nu

\setuppairedbox [...,¹...] [...,²...,...]
OPT

1 NAME
2 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
locatie = stanga centru dreapta sus subsol inalt jos
n = NUMMER
distanta = DIMENSION
fonttext = inherits: \seteazafonttext
latime = DIMENSION
inaltime = DIMENSION
latimemaxima = DIMENSION
inaltimemaxima = DIMENSION
aliniere = inherits: \seteazaalinieria
stil = STYLE BEFEHL
culoare = COLOR

\setarePAIREDBOX [...,^{*}...,...]

* inherits: \setuppairedbox

instances: legenda

\setuppaper [...,^{*}...,...]

* inherits: \seteazadimensiunihartie

\setupparagraph [...,¹...] [...,²...,...]
OPT

1 NAME
2 stil = STYLE BEFEHL
culoare = COLOR
aliniere = inherits: \seteazaalinieria
setups = NAME

\setupparagraphintro [...,¹...] [...²...]

1 reset fiecare primul urmatorul
2 BEFEHL

`\setupparallel [...]1 [...]2,... [...]3,...]`

1 NAME
2 NAME
3 setups = NAME
start = NUMBER
n = NUMBER
criteriu = tot

`\setupperiods [...]*,...]`

* n = NUMBER
latime = DIMENSION ajustat
distanta = DIMENSION
simbol = BEFEHL

`\setupplacement [...]1,... [...]2,...]`
OPT

1 NAME
2 inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
grid = inherits: \snaptogrid
corectielinie = on dezactivat
corectieadancime = on dezactivat
margine = da nu standard

`\setuppositionbar [...]*,...]`

* stil = STYLE BEFEHL
culoare = COLOR
n = NUMBER
min = NUMBER
max = NUMBER
text = TEXT
latime = DIMENSION
inaltime = DIMENSION
inaltime = DIMENSION

`\setupprefixtext [...]1,... [...]2,...]`
OPT

1 SPRACHE
2 KEY = VALUE

`\setupprocessor [...]1,... [...]2,...]`
OPT

1 NAME
2 stare = start stop
stanga = BEFEHL
dreapta = BEFEHL
comanda = \...##1
stil = STYLE BEFEHL
culoare = COLOR

`\setupprofile [...]1,... [...]2,...]`
OPT

1 NAME
2 inaltime = DIMENSION
inaltime = DIMENSION
distanta = DIMENSION
factor = NUMBER
linii = NUMBER
metoda = strict fixat niciunul

`\setupquotation [...]*,...]`

* inherits: \setupdelimitedtext

\setuprealpagenumber [...,*...]

* inherits: \setupcounter

\setupreferenceformat [...,¹...] [...,²...] OPT

1 NAME

2 eticheta = * NAME
stanga = BEFEHL
dreapta = BEFEHL
type = implicit text titlu numar pagina realpage
setups = NAME
autocase = da nu
text = TEXT
stil = STYLE BEFEHL
culoare = COLOR

\setupreferenceprefix [...]

* + - TEXT

\setupreferencestructureprefix [...,¹...] [...,²...] [...,³...] OPT OPT

1 NAME ABSCHNITT

2 implicit

3 prefix = da nu
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
numberseparatorset = NAME
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setuprenderingwindow [...,¹...] [...,²...] OPT

1 NAME

2 actiunedeschiderepagina = REFERENCE
actiuneinchiderepagina = REFERENCE
inherits: \seteazainconjurat

\setups [...,*...]

* NAME

`\setupscale [...,1...] [...,2...]`
OPT

```
1  NAME

2  scala      =  NUMBER
   xscala     =  NUMBER
   yscala     =  NUMBER
   latime     =  DIMENSION
   inaltime   =  DIMENSION
   inaltime   =  da nu
   linii      =  NUMBER
   factor     =  ajustat broad max auto implicit
   hfactor    =  ajustat broad max auto implicit
   factorw    =  ajustat broad max auto implicit
   latimemaxima =  DIMENSION
   inaltime maxima =  DIMENSION
   s          =  NUMBER
   sx         =  NUMBER
   sy         =  NUMBER
   equalwidth  =  DIMENSION
   equalheight =  DIMENSION
   grid       =  da ajustat inaltime adancime jumatatelinie
```

`\setupscrip [...,1...] [...,2...]`
OPT

```
1  NAME

2  metoda    =  hangul hanzi nihongo ethiopic thai test
   preset    =  NAME
   features   =  auto
```

`\setupselector [...,1...] [...,2...]`

```
1  NAME

2  n  =  NUMBER
   m  =  NUMBER
```

`\setupshift [...,1...] [...,2...]`
OPT

```
1  NAME

2  continua  =  da nu
   unitate   =  ex em pt in cm mm sp bp pc dd cc nc
   metoda    =  NUMBER
   dy        =  NUMBER
   aliniere  =  inherits: \setezaalinierea
   stil      =  STYLE BEFEHL
   culoare   =  COLOR
```

`\setupsidebar [...,1...] [...,2...]`
OPT

```
1  NAME

2  grosimerigla      =  DIMENSION
   culoarerigla      =  COLOR
   alternativ          =  NUMBER
   offsetsus          =  DIMENSION
   offsetjos          =  DIMENSION
   distanta           =  DIMENSION
   distantamarginestanga =  DIMENSION
   nivel              =  NUMBER
```

`\setupspellchecking [...,*...]`

```
*  stare  =  start stop
   metoda =  1 2 3
   lista  =  NAME
```


`\setupstartstop [...,1...] [...,2...,...]`
OPT

1 NAME
 2 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 setups = NAME
 stanga = BEFEHL
 dreapta = BEFEHL
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupstretched [...,*...,...]`

* inherits: \setupcharacterkerning

`\setupstruts [...*...]`
OPT

* da nu auto cap ajustat linie implicit CHARACTER

`\setupstyle [...,1...] [...,2...,...]`
OPT

1 NAME
 2 metoda = comanda
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupsbformula [...,1...] [...,2...,...]`
OPT

1 NAME
 2 aliniaturmator = da nu auto

`\setups {...,*...}`

* NAME

`\setupTABLE [...,1...] [...,2...] [...,3...,...]`
OPT OPT

1 r c x y rand coloana primul ultim start antet fiecare impar par unu NUMMER -NUMMER
 2 primul least fiecare doi impar par NUMMER -NUMMER
 3 extras = BEFEHL
 stanga = BEFEHL
 dreapta = BEFEHL
 culoaretitlu = COLOR
 stiltitlu = STYLE BEFEHL
 distantamarginestanga = DIMENSION
 distantamarginedreapta = DIMENSION
 distantacoloane = DIMENSION
 latimemaxima = DIMENSION
 setups = NAME
 latimetext = DIMENSION local
 split = da nu repetat auto
 antet = repetat
 optiune = dilatat tight
 inainte = BEFEHL
 dupa = BEFEHL
 aceeasipagina = inainte dupa ambele
 spaceinbetween = inherits: \blanc
 splitoffset = DIMENSION
 aliniazacaracter = da nu
 alierecaracter = TEXT number->TEXT text->TEXT
 distanta = DIMENSION
 culoare = COLOR
 stil = math STYLE BEFEHL
 inherits: \setezainconjurat

`\setupTEXpage [...,*...,...]`

* inherits: \setupfittingpage

`\setuptabulation [...1,...] [...2,...]`
OPT

```
1 NAME

2 format      = TEMPLATE niciunul
  inainte     = BEFEHL
  dupa        = BEFEHL
  distanta    = mic mediu mare niciunul blank adancime grila DIMENSION
  aliniere     = stanga centru dreapta dimension
  rigla       = linie normal
  culoarerigla = COLOR
  grosimerigla = DIMENSION
  fonttext    = inherits: \seteazafonttext
  aliniat     = da nu
  split       = da nu repetat auto
  unitate     = DIMENSION
  margine     = DIMENSION
  intern      = BEFEHL
  EQ          = BEFEHL
  antet       = da repetat text
  frame       = on dezactivat
  titlu       = TEXT
  keeptogether = da nu
```

`\setuptagging [...*,...]`

```
* stare = start stop
metoda = auto
```

`\setuptaglabeltext [...1,...] [...2,...]`
OPT

```
1 SPRACHE

2 KEY = VALUE
```

`\setuptextbackground [...1,...] [...2,...]`
OPT

```
1 NAME

2 stare      = start stop
  locatie    = text paragraf niciunul
  alternativ  = NUMMER
  mp         = NAME
  metoda     = NAME
  fundal     = culoare
  culoarefundal = COLOR
  colt       = rectangular rotund
  nivel      = NUMMER
  offsetfundal = DIMENSION
  inainte    = BEFEHL
  dupa       = BEFEHL
  aliniere   = inherits: \seteazaalinierea
  dash       = NUMMER
  raza       = DIMENSION
  frame      = on dezactivat
  culoareframe = COLOR
  grosimerigla = DIMENSION
  voffset    = DIMENSION
  offsetframe = DIMENSION
  offsetstanga = da nu standard DIMENSION
  offsetdreapta = da nu standard DIMENSION
  offsetsus   = mic mediu mare linie DIMENSION
  offsetjos   = mic mediu mare linie DIMENSION
  stil       = STYLE BEFEHL
  culoare     = COLOR
```

`\setuptextflow [...1,...] [...2,...]`
OPT

```
1 NAME

2 latime = DIMENSION
  stil   = STYLE BEFEHL
  culoare = COLOR
```

`\setuptooltip [...,1...] [...,2...,...]`
OPT

1 NAME
2 locatie = stanga centru dreapta
inherits: \seteazainconjurat

`\setupunit [...,1...] [...,2...,...]`
OPT

1 NAME
2 metoda = 1 2 3 4 5 6
language = SPRACHE
alternativ = text matematica
order = reverse normal
separator = mic mediu mare normal niciunul NAME
spatiu = mic mediu mare normal niciunul NAME
stil = STYLE BEFEHL
culoare = COLOR

`\setupunittext [...1] [...,2...,...]`
OPT

1 SPRACHE
2 KEY = VALUE

`\setupuserpagenumber [...,*...,...]`

* viewerprefix = TEXT
stare = start stop niciunul mentine gol
inherits: \setupcounter

`\setupversion [...*]`

* concept fisier temporar final NAME

`\setupviewerlayer [...,*...,...]`

* titlu = TEXT
stare = start stop
export = da nu
tiparibil = da nu
scop = local global
metoda = niciunul comanda

`\setupvspacing [...,*...]`
OPT

* inherits: \vspacing

`\setupwithargument {...1} {...2}`

1 NAME
2 CONTENT

`\setupwithargumentswapped {...1} {...2}`

1 CONTENT
2 NAME

`\setupxml [...,*...,...]`

* implicit = ascuns niciunul text
compress = da nu

`\setupxtable [...1,...2] [...2,...1,...]`
OPT

1 NAME

2 latimetext = DIMENSION local
fonttext = inherits: \seteazafonttext
spaceinbetween = inherits: \blanc
optiune = tight max dilatat latime inaltime fixat
inaltimetext = DIMENSION
latimemaxima = DIMENSION
distantacoloane = DIMENSION
distantamarginestanga = DIMENSION
distantamarginedreapta = DIMENSION
antet = repetat
subsol = repetat
grosimerigla = DIMENSION
split = da nu repetat auto
splitoffset = DIMENSION
aceeasipagina = inainte dupa ambele
distanta = DIMENSION
inherits: \seteazainconjurat

`\setuvalue {...1} {...2}`

1 NAME

2 CONTENT

`\setuxvalue {...1} {...2}`

1 NAME

2 CONTENT

`\setvalue {...1} {...2}`

1 NAME

2 CONTENT

`\setvariable {...1} {...2} {...3}`

1 NAME

2 KEY

3 VALUE

`\setvariables [...1] [...2,...1,...]`

1 NAME

2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\setvboxregister ...1 {...2}`

1 CSNAME NUMBER

2 CONTENT

`\setvisualizerfont [...*]`
OPT

* FONT

`\setvtopregister ...1 {...2}`

1 CSNAME NUMBER

2 CONTENT

<pre>\setwidthof ¹... \to ²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\setxmeasure {...} {...}</pre> <pre>1 NAME</pre> <pre>2 DIMENSION</pre>
<pre>\setxvalue ¹ {...} ² {...}</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\setxvariable ¹ {...} ² {...} ³ {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 VALUE</pre>
<pre>\setxvariables [¹...] [²...,...]</pre> <pre>1 NAME</pre> <pre>2 set = BEFEHL</pre> <pre>reset = BEFEHL</pre> <pre>KEY = VALUE</pre>
<pre>\sfrac {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 CONTENT</pre>
<pre>\shapedhbox {...}</pre> <pre>* CONTENT</pre>
<pre>\shiftdown {...}</pre> <pre>* CONTENT</pre>
<pre>\shiftup {...}</pre> <pre>* CONTENT</pre>
<pre>\SHIFT {...}</pre> <pre>* CONTENT</pre> <pre>instances: shiftup shiftdown</pre>
<pre>\showallmakeup</pre>
<pre>\showattributes</pre>
<pre>\showboxes</pre>

<pre> \showbtxdatasetauthors [...,..[*]...,...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [...*] OPT * NAME </pre>
<pre> \showbtxdatasetcompleteness [...,..[*]...,...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...*] OPT * NAME </pre>
<pre> \showbtxdatasetfields [...,..[*]...,...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...*] OPT * NAME </pre>
<pre> \showbtxfields [...,..[*]...,...] OPT * rotatie = NUMBER specification = NAME </pre>
<pre> \showbtxfields [...*] OPT * NAME </pre>
<pre> \showbtxhashedauthors [...*] OPT * TEXT </pre>
<pre> \showbtxtables [...*] OPT * TEXT </pre>
<pre> \showchardata {...} * TEXT </pre>
<pre> \showcharratio {...} * TEXT </pre>
<pre> \showcolorbar [...*] * COLOR </pre>

\showcolorcomponents [...] * COLOR
\showcolorset [...] * COLOR
\showcolorstruts
\showcounter [...] * NAME
\showdirectives
\showdirlsinmargin
\showedebuginfo
\showexperiments
\showfont [...] ¹ [...] ² OPT 1 FONT 2 NUMMER
\showfontdata
\showfontkerns
\showfontparameters
\showfontstrip [...]*[...] * inherits: \seteazafonttext
\showfontstyle [...] ¹ , [...] ² [...] ³ , [...] ⁴ [...] ⁵ OPT OPT OPT OPT 1 inherits: \seteazafonttext 2 rm ss tt mm hw cg 3 tf bf it sl bi bs 4 tot NUMMER
\showglyphs
\showgridsnapping
\showhelp {...} ¹ {...} ² 1 TEXT 2 REFERENCE
\showhyphenationtrace [...] ¹ [...] ² OPT 1 SPRACHE 2 TEXT

\showhyphens {...} * TEXT
\showinjector [...,*,...] <div> <div></div> <div>OPT</div> </div> * NAME
\showjustification
\showkerning {...} * TEXT
\showlayoutcomponents
\showligature {...} * TEXT
\showligatures [...] * FONT
\showlogcategories
\showmargins
\showmessage { ¹ .} { ² .} { ³ ...,...} 1 NAME 2 NAME NUMBER 3 TEXT
\showminimalbaseline
\shownextbox \ ¹ ... { ² .} 1 CSNAME 2 CONTENT
\showotfcomposition { ¹ .} { ² .} { ³ .} 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
\showparentchain \ ¹ ... { ² .} 1 CSNAME 2 NAME
\showsetupsdefinition [...] * NAME
\showtimer {...} * TEXT

<code>\showtokens [...]</code> * NAME
<code>\showtrackers</code>
<code>\showvalue {...}</code> * NAME
<code>\showvariable {...} {...}</code> 1 NAME 2 KEY
<code>\showwarning {...} {...} {..., 1 NAME 2 NAME NUMBER 3 TEXT </code>
<code>\simbol [...] [...]</code> <div style="margin-left: 100px;">OPT</div> 1 NAME 2 NAME
<code>\simbol {...}</code> * NAME
<code>\simplealignedbox {...} {...} {...}</code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
<code>\simplealignedboxplus {...} {...} {...} {...}</code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 TEXT 4 CONTENT
<code>\simplealignedspreadbox {...} {...} {...}</code> 1 DIMENSION 2 stanga dreapta centru flushleft flushright intern extern 3 CONTENT
<code>\simplegroupedcommand {...} {...}</code> 1 BEFEHL 2 BEFEHL

`\simplereversealignedbox {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 TEXT
- 4 CONTENT

`\singalcharacteralign {...} {...}`

- 1 NUMMER
- 2 NUMMER

`\singlebond`

`\sixthofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\slicepages [...]1 [...,2...,...]2 [...,3...,...]3`
OPT OPT

- 1 FILE
- 2 offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
latime = DIMENSION
inaltime = DIMENSION
n = NUMMER
- 3 offset = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
latime = DIMENSION
inaltime = DIMENSION
n = NUMMER

`\slovenianNumerals {...}`

- * NUMMER

`\sloveniannumerals {...}`

- * NUMMER

`\smallbodyfont`

`\smallcappedcharacters {...}`

- * NUMMER

$\backslash\text{smallcappedromannumerals} \{...\}$ * NUMBER
$\backslash\text{smaller}$
$\backslash\text{smallskip}$
$\backslash\text{smash} [^{1.}] \{^{2.}...\}$ <small>OPT</small> 1 w h d t b 2 CONTENT
$\backslash\text{smashbox} ...$ * CSNAME NUMBER
$\backslash\text{smashboxed} ...$ * CSNAME NUMBER
$\backslash\text{smashedhbox} ^{1.}... \{^{2.}...\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{smashedvbox} ^{1.}... \{^{2.}...\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{snaptogrid} [^{1.}] \backslash^{2.}... \{^{3.}...\}$ <small>OPT</small> 1 normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME 2 CSNAME 3 CONTENT
$\backslash\text{snaptogrid} [...,^{1.}...] \backslash^{2.}... \{^{3.}...\}$ <small>OPT</small> 1 inherits: \definegridsnapping 2 CSNAME 3 CONTENT
$\backslash\text{someheadnumber} [^{1.}] [^{2.}]$ 1 ABSCHNITT 2 precedent curent urmatorul primul ultim
$\backslash\text{somekindoftab} [...,^{*}...,...]$ <small>OPT</small> * alternativ = orizontal vertical latime = DIMENSION inaltime = DIMENSION n = NUMBER m = NUMBER
$\backslash\text{somelocalfloat}$

$\backslash\text{somenamedheadnumber} \{.^1.\} \{.^2.\}$ 1 ABSCHNITT 2 precedent curent urmatorul primul ultim
$\backslash\text{someplace} \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\} \{.^5.\} [.^6.]$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 REFERENCE
$\backslash\text{SORTING} [.^1.] \{.^2.\}$ <small>OPT</small> 1 NAME 2 CONTENT instances: logo
$\backslash\text{spanishNumerals} \{.*.\}$ * NUMMER
$\backslash\text{spanishnumerals} \{.*.\}$ * NUMMER
$\backslash\text{spatiifixate}$
$\backslash\text{spatiu}$
$\backslash\text{spatiufixat}$
$\backslash\text{speech} [.^1.] \{.^2.\}$ <small>OPT</small> 1 SPRACHE 2 CONTENT
$\backslash\text{splitdfrac} \{.^1.\} \{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{splitfilename} \{.*.\}$ * FILE
$\backslash\text{splitfrac} \{.^1.\} \{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{splitoffbase}$
$\backslash\text{splitofffull}$

<code>\splitoffkind</code>
<code>\splitoffname</code>
<code>\splitoffpath</code>
<code>\splitoffroot</code>
<code>\splitofftokens</code> ¹ ... \from ² ... \to \ ³ ... 1 TEXT 2 TEXT 3 CSNAME
<code>\splitofftype</code>
<code>\splitstring</code> ¹ ... \at ² ... \to \ ³ ... \and \ ⁴ ... 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox</code> ... * CSNAME NUMBER
<code>\sqrt</code> [¹ ...] { ² ...} _{OPT} 1 TEXT 2 CONTENT
<code>\stackrel</code> { ¹ ...} { ² ...} 1 CONTENT 2 CONTENT
<code>\stanga</code> ... * CHARACTER
<code>\startalign</code> [..., [*] ...,...] ... \stopalign _{OPT} * inherits: \setupmathalignment
<code>\startalignment</code> [..., [*] ...] ... \stopalignment * inherits: \seteazaalinierea
<code>\startaliniatcentru</code> ... \stopaliniatcentru
<code>\startaliniatdreapta</code> ... \stopaliniatdreapta
<code>\startaliniatstanga</code> ... \stopaliniatstanga
<code>\startallmodes</code> [..., [*] ...] ... \stopallmodes * NAME

<code>\startantettabel [...] ... \stopantettabel</code> <code>* NAME</code>
<code>\startapendixuri [...,..[*]...,...] ... \stopapendixuri</code> <div>OPT</div> <code>* semncarte = TEXT</code> <code> inherits: \seteazablocsectiune</code>
<code>\startascundere ... \stopascundere</code>
<code>\startaside [...]¹ [...,..²...,...] ... \stopaside</code> <div>OPT OPT</div> <code>1 SPRACHE</code> <code>2 inherits: \startingust</code>
<code>\startattachment [...]¹ [...,..²...,...] ... \stopattachment</code> <div>OPT OPT</div> <code>1 NAME</code> <code>2 inherits: \setupattachment</code>
<code>\startATTACHMENT [...]¹ [...,..²...,...] ... \stopATTACHMENT</code> <div>OPT OPT</div> <code>1 NAME</code> <code>2 inherits: \setupattachment</code> <code>instances: attachment</code>
<code>\startbar [...] ... \stopbar</code> <code>* NAME</code>
<code>\startbitmapimage [...,..[*]...,...] ... \stopbitmapimage</code> <code>* culoare = rgb cmyk gri</code> <code> latime = DIMENSION</code> <code> inaltime = DIMENSION</code> <code> x = NUMMER</code> <code> y = NUMMER</code>
<code>\startblockquote [...]¹ [...,..²...,...] ... \stopblockquote</code> <div>OPT OPT</div> <code>1 SPRACHE</code> <code>2 inherits: \startingust</code>
<code>\startblocsectiuneambient [...] ... \stopblocsectiuneambient</code> <code>* NAME</code>
<code>\startboxedcolumns [...,..[*]...,...] ... \stopboxedcolumns</code> <div>OPT</div> <code>* inherits: \setupmixedcolumns</code>
<code>\startbtxlabeltext [...]¹ [...]² ... \stopbtxlabeltext</code> <div>OPT</div> <code>1 SPRACHE</code> <code>2 KEY</code>
<code>\startbtxrenderingdefinitions [...] ... \stopbtxrenderingdefinitions</code> <code>* NAME</code>

$\backslash\text{startbuffer}$ [\dots] \dots $\backslash\text{stopbuffer}$ <small>OPT</small> * NAME
$\backslash\text{startBUFFER}$ \dots $\backslash\text{stopBUFFER}$ instances: ascundere
$\backslash\text{startcapitol}$ [$\dots,\dots,\overset{1}{=}\dots,\dots$] [$\dots,\dots,\overset{2}{=}\dots,\dots$] \dots $\backslash\text{stopcapitol}$ <small>OPT</small> <small>OPT</small> 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 2 KEY = VALUE
$\backslash\text{startcases}$ [$\dots,\dots,\overset{*}{=}\dots,\dots$] \dots $\backslash\text{stopcases}$ <small>OPT</small> * inherits: $\backslash\text{setupmathcases}$
$\backslash\text{startcatcodetable}$ $\backslash\dots$ \dots $\backslash\text{stopcatcodetable}$ * CSNAME
$\backslash\text{startcenteraligned}$ \dots $\backslash\text{stopcenteraligned}$
$\backslash\text{startcharacteralign}$ [\dots] \dots $\backslash\text{stopcharacteralign}$ <small>OPT</small> * TEXT number->TEXT text->TEXT
$\backslash\text{startcheckedfences}$ \dots $\backslash\text{stopcheckedfences}$
$\backslash\text{startchemical}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{=}\dots,\dots$] \dots $\backslash\text{stopchemical}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupchemical}$
$\backslash\text{startcitat}$ [$\overset{1}{\dots}$] [$\dots,\overset{2}{\dots},\dots$] \dots $\backslash\text{stopcitat}$ <small>OPT</small> <small>OPT</small> 1 SPRACHE 2 inherits: $\backslash\text{startingust}$
$\backslash\text{startcollect}$ \dots $\backslash\text{stopcollect}$
$\backslash\text{startcollecting}$ \dots $\backslash\text{stopcollecting}$
$\backslash\text{startcoloane}$ [$\dots,\dots,\overset{*}{=}\dots,\dots$] \dots $\backslash\text{stopcoloane}$ <small>OPT</small> * inherits: $\backslash\text{seteazacoloane}$
$\backslash\text{startcolorintent}$ [\dots] \dots $\backslash\text{stopcolorintent}$ * knockout overprint niciunul
$\backslash\text{startcoloronly}$ [\dots] \dots $\backslash\text{stopcoloronly}$ * COLOR

$\backslash\text{startcolorset}$ [...] ... $\backslash\text{stopcolorset}$ * NAME
$\backslash\text{startcolumnspan}$ [..., $\overset{*}{\text{=}}$...,...] ... $\backslash\text{stopcolumnspan}$ <small>OPT</small> * inherits: $\backslash\text{setupcolumnspan}$
$\backslash\text{startcombination}$ [$\overset{1}{\text{...}}$] [..., $\overset{2}{\text{=}}$...,...] ... $\backslash\text{stopcombination}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupcombination}$
$\backslash\text{startcombination}$ [$\overset{1}{\text{...}}$] [$\overset{2}{\text{...}}$] ... $\backslash\text{stopcombination}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 N*M
$\backslash\text{startcomentariu}$ [$\overset{1}{\text{...}}$] [..., $\overset{2}{\text{=}}$...,...] ... $\backslash\text{stopcomentariu}$ <small>OPT</small> <small>OPT</small> 1 TEXT 2 inherits: $\backslash\text{seteazacomentariu}$
$\backslash\text{startcomentariupagina}$... $\backslash\text{stopcomentariupagina}$
$\backslash\text{startCOMENTARIU}$ [$\overset{1}{\text{...}}$] [..., $\overset{2}{\text{=}}$...,...] ... $\backslash\text{stopCOMENTARIU}$ <small>OPT</small> <small>OPT</small> 1 TEXT 2 inherits: $\backslash\text{seteazacomentariu}$ instances: comentariu
$\backslash\text{startcomponenta}$ [...] ... $\backslash\text{stopcomponenta}$ * FILE *
$\backslash\text{startcomponenta}$.* ... $\backslash\text{stopcomponenta}$ * FILE *
$\backslash\text{startcontextcode}$... $\backslash\text{stopcontextcode}$
$\backslash\text{startcontextdefinitioncode}$... $\backslash\text{stopcontextdefinitioncode}$
$\backslash\text{startctxfunction}$.* ... $\backslash\text{stopctxfunction}$ * NAME
$\backslash\text{startctxfunctiondefinition}$.* ... $\backslash\text{stopctxfunctiondefinition}$ * NAME
$\backslash\text{startculoare}$ [...] ... $\backslash\text{stopculoare}$ * COLOR
$\backslash\text{startcurrentcolor}$... $\backslash\text{stopcurrentcolor}$
$\backslash\text{startcurrentlistentrywrapper}$... $\backslash\text{stopcurrentlistentrywrapper}$

$\backslash\mathrm{startdelimited} [\overset{1}{...}] [\overset{2}{...}] [\overset{3}{...},...] \dots \backslash\mathrm{stopdelimited}$ $\text{OPT} \qquad \text{OPT}$ 1 NAME 2 SPRACHE 3 inherits: \startingust
$\backslash\mathrm{startdelimitedtext} [\overset{1}{...}] [\overset{2}{...}] [\overset{3}{...},...] \dots \backslash\mathrm{stopdelimitedtext}$ $\text{OPT} \qquad \text{OPT}$ 1 NAME 2 SPRACHE 3 inherits: \startingust
$\backslash\mathrm{startDELIMITEDTEXT} [\overset{1}{...}] [\overset{2}{...},...] \dots \backslash\mathrm{stopDELIMITEDTEXT}$ $\text{OPT} \qquad \text{OPT}$ 1 SPRACHE 2 inherits: \startingust instances: citat minicitat blockquote speech aside
$\backslash\mathrm{startDESCRIERE} [...,\overset{*}{...},...] \dots \backslash\mathrm{stopDESCRIERE}$ OPT * titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE
$\backslash\mathrm{startDESCRIERE} [...,\overset{1}{...}] \{\overset{2}{...}\} \dots \backslash\mathrm{stopDESCRIERE}$ $\text{OPT} \qquad \text{OPT}$ 1 REFERENCE 2 TEXT
$\backslash\mathrm{startdespachetat} \dots \backslash\mathrm{stopdespachetat}$
$\backslash\mathrm{startdisplaymath} \dots \backslash\mathrm{stopdisplaymath}$
$\backslash\mathrm{startdmath} \dots \backslash\mathrm{stopdmath}$
$\backslash\mathrm{startdocument} [...,\overset{*}{...},...] \dots \backslash\mathrm{stopdocument}$ OPT * inherits: \setupdocument
$\backslash\mathrm{startdute} [\overset{*}{...}] \dots \backslash\mathrm{stopdute}$ * REFERENCE
$\backslash\mathrm{starteffect} [\overset{*}{...}] \dots \backslash\mathrm{stopeffect}$ * NAME
$\backslash\mathrm{startEFFECT} \dots \backslash\mathrm{stopEFFECT}$
$\backslash\mathrm{startelement} [...,\overset{*}{...}] \dots \backslash\mathrm{stopelement}$ OPT * REFERENCE
$\backslash\mathrm{startembeddedxtable} [...,\overset{*}{...},...] \dots \backslash\mathrm{stopembeddedxtable}$ OPT * inherits: \setupxtable

<p><code>\startembeddedxtable [...]^{OPT} ... \stopembeddedxtable</code></p> <p>* NAME</p>
<p><code>\startendnote [...]^{OPT} ... \stopendnote</code></p> <p>* REFERENCE</p>
<p><code>\startendnote [...]^{OPT} ... \stopendnote</code></p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p>
<p><code>\startenumerare [...]¹ [...]² ... \stopenumerare</code></p> <p>1 inherits: \setupitemgroup 2 inherits: \setupitemgroup</p>
<p><code>\startENUMERARE [...]^{OPT} ... \stopENUMERARE</code></p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p>
<p><code>\startENUMERARE [...]¹ {...}² ... \stopENUMERARE</code></p> <p>1 REFERENCE 2 TEXT</p>
<p><code>\startepilogul [...]^{OPT} ... \stopepilogul</code></p> <p>* semncarte = TEXT inherits: \seteazablocsectione</p>
<p><code>\startexceptions [...] ... \stopexceptions</code></p> <p>* SPRACHE</p>
<p><code>\startexpanded ... \stopexpanded</code></p>
<p><code>\startexpandedcollect ... \stopexpandedcollect</code></p>
<p><code>\startextendedcatcodetable \.* ... \stopextendedcatcodetable</code></p> <p>* CSNAME</p>
<p><code>\startexternalfigurecollection [...] ... \stopexternalfigurecollection</code></p> <p>* NAME</p>
<p><code>\startfact [...]¹ [...]² ... \stopfact</code></p> <p>1 NAME 2 inherits: \seteazatabulatori</p>
<p><code>\startfigura [...]¹ [...]² [...]³ ... \stopfigura</code></p> <p>1 NAME 2 FILE 3 inherits: \figuraexterna</p>

<p><code>\startfittingpage [...]¹ [...,...²...,...]</code> ... <code>\stopfittingpage</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \setupfittingpage</p>
<p><code>\startFITTINGPAGE [...,...[*]...,...]</code> ... <code>\stopFITTINGPAGE</code> <small>OPT</small></p> <p>* inherits: \setupfittingpage</p> <p>instances: TEXpage MPpage</p>
<p><code>\startfloatcombination [...,...[*]...,...]</code> ... <code>\stopfloatcombination</code> <small>OPT</small></p> <p>* inherits: \setupcombination</p>
<p><code>\startfloatcombination [...][*]</code> ... <code>\stopfloatcombination</code> <small>OPT</small></p> <p>* N*M NAME</p>
<p><code>\startOBJECTMOBILtext [...]¹,...]</code> [...,...²,...] {...³.} ... <code>\stopOBJECTMOBILtext</code> <small>OPT OPT</small></p> <p>1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmarginemarginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startfont [...][*]</code> ... <code>\stopfont</code> <small>OPT</small></p> <p>* FONT</p>
<p><code>\startfontclass [...][*]</code> ... <code>\stopfontclass</code></p> <p>* fiecare NAME</p>
<p><code>\startfontsolution [...][*]</code> ... <code>\stopfontsolution</code></p> <p>* NAME</p>
<p><code>\startformula [...][*],...]</code> ... <code>\stopformula</code> <small>OPT</small></p> <p>* impachetat tight centru incadrat inherits: \seteazafonttext</p>
<p><code>\startFORMULAformula [...][*],...]</code> ... <code>\stopFORMULAformula</code> <small>OPT</small></p> <p>* impachetat tight centru incadrat inherits: \seteazafonttext</p> <p>instances: sp sd mp md</p>
<p><code>\startformule [...][*],...]</code> ... <code>\stopformule</code> <small>OPT</small></p> <p>* + - REFERENCE</p>
<p><code>\startframed [...]¹ [...,...²...,...]</code> ... <code>\stopframed</code> <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \seteazainconjurat</p>
<p><code>\startframedcontent [...][*]</code> ... <code>\stopframedcontent</code> <small>OPT</small></p> <p>* NAME dezactivat</p>

$\backslash\text{startfundal}$ [\dots , \dots , $\overset{\text{OPT}}{=}\dots$, \dots] ... $\backslash\text{stopfundal}$ * inherits: $\backslash\text{seteazafundal}$
$\backslash\text{startFUNDAL}$ [\dots , \dots , $\overset{\text{OPT}}{=}\dots$, \dots] ... $\backslash\text{stopFUNDAL}$ * inherits: $\backslash\text{seteazafundal}$ instances: fundal
$\backslash\text{startgridsnapping}$ [$\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stopgridsnapping}$ * normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME
$\backslash\text{startgridsnapping}$ [\dots , $\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stopgridsnapping}$ * inherits: $\backslash\text{definegridsnapping}$
$\backslash\text{starthboxestohbox}$... $\backslash\text{stophboxestohbox}$
$\backslash\text{starthboxregister}$ $\overset{\text{OPT}}{.}$... $\backslash\text{stophboxregister}$ * CSNAME NUMBER
$\backslash\text{starthHELP}$ [$\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stopHELP}$ * REFERENCE instances: textajutator
$\backslash\text{starthhighlight}$ [$\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stophhighlight}$ * NAME
$\backslash\text{starthyphenation}$ [\dots , $\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stophyphenation}$ * original tex implicit hyphenate expanded traditional niciunul
$\backslash\text{startimath}$... $\backslash\text{stopimath}$
$\backslash\text{startimpachetat}$ [$\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stopimpachetat}$ * blank
$\backslash\text{startindentedtext}$ [$\overset{\text{OPT}}{.}\dots$] ... $\backslash\text{stopindentedtext}$ * NAME
$\backslash\text{startINDENTEDTEXT}$... $\backslash\text{stopINDENTEDTEXT}$
$\backslash\text{startingust}$ [$\overset{1}{.}\dots$] [\dots , \dots , $\overset{2}{=}\dots$, \dots] ... $\backslash\text{stopingust}$ 1 NAME 2 inherits: $\backslash\text{seteazaingust}$
$\backslash\text{startingust}$ [\dots , \dots , $\overset{1}{=}\dots$, \dots] [\dots , $\overset{2}{.}\dots$] ... $\backslash\text{stopingust}$ 1 inherits: $\backslash\text{seteazaingust}$ 2 [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset

<p><code>\startingust</code> ¹<code>[...]</code> ²<code>[...,...]</code> ... <code>\stoppingust</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 <code>[--]stanga [--]centru [--]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset</code></p>
<p><code>\startinteractiune</code> [*]<code>[...]</code> ... <code>\stopinteractiune</code></p> <p>* ascuns NAME</p>
<p><code>\startinterface</code> [*] ... <code>\stopinterface</code></p> <p>* tot SPRACHE</p>
<p><code>\startintertext</code> ... <code>\stopintertext</code></p>
<p><code>\startitemgroup</code> ¹<code>[...]</code> ²<code>[...,...]</code> ³<code>[...,...]</code> ... <code>\stopitemgroup</code></p> <p><small>OPT OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: <code>\setupitemgroup</code></p> <p>3 inherits: <code>\setupitemgroup</code></p>
<p><code>\startITEMGROUP</code> ¹<code>[...,...]</code> ²<code>[...,...]</code> ... <code>\stopITEMGROUP</code></p> <p><small>OPT OPT</small></p> <p>1 inherits: <code>\setupitemgroup</code></p> <p>2 inherits: <code>\setupitemgroup</code></p> <p>instances: enumerare</p>
<p><code>\startJScode</code> ¹ ... ² ... ³ ... <code>\stopJScode</code></p> <p>1 NAME</p> <p>2 uses</p> <p>3 NAME</p>
<p><code>\startJSreamble</code> ¹ ... ² ... ³ ... <code>\stopJSreamble</code></p> <p>1 NAME</p> <p>2 folositi</p> <p>3 now later</p>
<p><code>\startknockout</code> ... <code>\stopknockout</code></p>
<p><code>\startLUA</code> [*]<code>[...,...]</code> ... <code>\stopLUA</code></p> <p><small>OPT</small></p> <p>* inherits: <code>\seteazatyping</code></p>
<p><code>\startLUA</code> [*]<code>[...,...]</code> ... <code>\stopLUA</code></p> <p><small>OPT</small></p> <p>* continuu</p>
<p><code>\startlayout</code> [*]<code>[...]</code> ... <code>\stoplayout</code></p> <p>* NAME</p>
<p><code>\startlegenda</code> ¹<code>[...]</code> ²<code>[...,...]</code> ... <code>\stoplegenda</code></p> <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: <code>\seteazatabulatori</code></p>

<code>\startlinealignment [...] ... \stoplinealignment</code> * stanga centru dreapta max
<code>\startlinecorrection [...,*...] ... \stoplinecorrection</code> <div style="text-align: center;"><small>OPT</small></div> * blank inherits: \blanc
<code>\startlinefiller [...] [...,*...] ... \stoplinefiller</code> <div style="text-align: center;"><small>OPT</small></div> 1 filler NAME 2 inherits: \setuplinefiller
<code>\startlinenote [...] {...}</code> 1 REFERENCE 2 TEXT
<code>\startLINENOTE [...] {...}</code> 1 REFERENCE 2 TEXT instances: linenote
<code>\startlinenumbering [...,*...] ... \stoplinenumbering</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> 1 NAME 2 inherits: \seteazanumerotarelinii
<code>\startlinenumbering [...] [...,*] ... \stoplinenumbering</code> <div style="display: flex; justify-content: space-around;"><div><small>OPT</small></div><div><small>OPT</small></div></div> 1 NAME 2 continuu NUMMER
<code>\startlinetable ... \stoplinetable</code>
<code>\startlinetablebody ... \stoplinetablebody</code>
<code>\startlinetablecell [...,*...] ... \stoplinetablecell</code> <div style="text-align: center;"><small>OPT</small></div> * inherits: \setuplinetable
<code>\startlinetablehead ... \stoplinetablehead</code>
<code>\startlinie [...]</code> * REFERENCE
<code>\startliniemargine [...,*] ... \stopliniemargine</code> <div style="text-align: center;"><small>OPT</small></div> * NUMMER
<code>\startliniemargine [...,*...] ... \stopliniemargine</code> <div style="text-align: center;"><small>OPT</small></div> * inherits: \setupmarginrule
<code>\startlinii [...,*...] ... \stoplinii</code> <div style="text-align: center;"><small>OPT</small></div> * inherits: \seteazalinii

<pre> \startLINII [...,*=...,...] ... \stopLINII OPT * inherits: \seteazalinii instances: linii </pre>
<pre> \startlocalfootnotes ... \stoplocalfootnotes </pre>
<pre> \startlocalheadsetup ... \stoplocalheadsetup </pre>
<pre> \startlocallinecorrection [...,*=...,...] ... \stoplocallinecorrection OPT * blank inherits: \blanc </pre>
<pre> \startlocalnotes [...,*=...,...] ... \stoplocalnotes * NAME </pre>
<pre> \startlocalsetups [...¹,...] [...²,...] ... \stoplocalsetups OPT 1 grila 2 NAME </pre>
<pre> \startlocalsetups .* ... \stoplocalsetups * NAME </pre>
<pre> \startlua ... \stoplua </pre>
<pre> \startluacode ... \stopluacode </pre>
<pre> \startluaparameterset [...,*=...,...] ... \stopluaparameterset * NAME </pre>
<pre> \startluasetups [...¹,...] [...²,...] ... \stopluasetups OPT 1 grila 2 NAME </pre>
<pre> \startluasetups .* ... \stopluasetups * NAME </pre>
<pre> \startMP [...,*=...,...] ... \stopMP OPT * inherits: \seteazatyping </pre>
<pre> \startMPclip {...,*=...,...} ... \stopMPclip * NAME </pre>
<pre> \startMPcode {...,*=...,...} ... \stopMPcode OPT * NAME </pre>
<pre> \startMPdefinitions {...,*=...,...} ... \stopMPdefinitions OPT * NAME </pre>

$\backslash\text{startMPdrawing}$ [\dots] \dots $\backslash\text{stopMPdrawing}$ <small>OPT</small> $*$ $-$
$\backslash\text{startMPenvironment}$ [\dots] \dots $\backslash\text{stopMPenvironment}$ <small>OPT</small> $*$ reset global +
$\backslash\text{startMPextensions}$ [\dots, \ast, \dots] \dots $\backslash\text{stopMPextensions}$ <small>OPT</small> $*$ NAME
$\backslash\text{startMPinclusions}$ [\dots^1] [\dots^2] \dots $\backslash\text{stopMPinclusions}$ <small>OPT OPT</small> 1 $+$ 2 NAME
$\backslash\text{startMPinitializations}$ \dots $\backslash\text{stopMPinitializations}$
$\backslash\text{startMPpage}$ [$\dots, \ast, \dots, \dots$] \dots $\backslash\text{stopMPpage}$ <small>OPT</small> $*$ $\text{inherits: } \backslash\text{setupfittingpage}$
$\backslash\text{startMPpositiongraphic}$ [\dots^1] [\dots^2, \dots] \dots $\backslash\text{stopMPpositiongraphic}$ <small> OPT</small> 1 NAME 2 KEY
$\backslash\text{startMPpositionmethod}$ [\dots] \dots $\backslash\text{stopMPpositionmethod}$ $*$ NAME
$\backslash\text{startMPrun}$ [\dots] \dots $\backslash\text{stopMPrun}$ <small>OPT</small> $*$ NAME
$\backslash\text{startMP}$ [\dots, \ast, \dots] \dots $\backslash\text{stopMP}$ <small>OPT</small> $*$ continuu
$\backslash\text{startmakeup}$ [\dots^1] [$\dots, \ast, \dots, \dots$] \dots $\backslash\text{stopmakeup}$ <small> OPT</small> 1 NAME 2 $\text{inherits: } \backslash\text{seteazamakeup}$
$\backslash\text{startMARCAJmakeup}$ [$\dots, \ast, \dots, \dots$] \dots $\backslash\text{stopMARCAJmakeup}$ <small> OPT</small> $*$ $\text{inherits: } \backslash\text{seteazamakeup}$ $\text{instances: standard pagina text centru}$
$\backslash\text{startmarginblock}$ [\dots] \dots $\backslash\text{stopmarginblock}$ <small>OPT</small> $*$ NAME
$\backslash\text{startmarkedcontent}$ [\dots] \dots $\backslash\text{stopmarkedcontent}$ <small>OPT</small> $*$ reset tot NAME
$\backslash\text{startmathalignment}$ [$\dots, \ast, \dots, \dots$] \dots $\backslash\text{stopmathalignment}$ <small> OPT</small> $*$ $\text{inherits: } \backslash\text{setupmathalignment}$

$\backslash startMATHALIGNMENT [\dots \overset{*}{=} \dots] \dots \backslash stopMATHALIGNMENT$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathalignment</p> <p>instances: align mathalignment</p>
$\backslash startmathcases [\dots \overset{*}{=} \dots] \dots \backslash stopmathcases$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathcases</p>
$\backslash startMATHCASES [\dots \overset{*}{=} \dots] \dots \backslash stopMATHCASES$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathcases</p> <p>instances: cases mathcases</p>
$\backslash startmathlabeltext [\overset{1}{\dots}] [\overset{2}{\dots}] \dots \backslash stopmathlabeltext$ <p> <small>OPT</small> </p> <p>1 SPRACHE</p> <p>2 KEY</p>
$\backslash startmathmatrix [\dots \overset{*}{=} \dots] \dots \backslash stopmathmatrix$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathmatrix</p>
$\backslash startMATHMATRIX [\dots \overset{*}{=} \dots] \dots \backslash stopMATHMATRIX$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathmatrix</p> <p>instances: matrix mathmatrix</p>
$\backslash startmathmode \dots \backslash stopmathmode$
$\backslash startmathstyle [\dots \overset{*}{=} \dots] \dots \backslash stopmathstyle$ <p>* display text script scriptscript cramped uncramped normal impachetat mic mare NAME</p>
$\backslash startmatrices [\dots \overset{*}{=} \dots] \dots \backslash stopmatrices$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathmatrix</p>
$\backslash startmatrix [\dots \overset{*}{=} \dots] \dots \backslash stopmatrix$ <p> <small>OPT</small> </p> <p>* inherits: \setupmathmatrix</p>
$\backslash startmaxaligned \dots \backslash stopmaxaligned$
$\backslash startmdformula [\dots \overset{*}{=} \dots] \dots \backslash stopmdformula$ <p> <small>OPT</small> </p> <p>* impachetat tight centru incadrat inherits: \seteazafonttext</p>
$\backslash startmediu [\overset{*}{\dots}] \dots \backslash stopmediu$ <p>* FILE *</p>
$\backslash startmediu \overset{*}{\dots} \dots \backslash stopmediu$ <p>* FILE *</p>
$\backslash startmeniuinteractiune [\overset{*}{\dots}] \dots \backslash stopmeniuinteractiune$ <p>* NAME</p>

<code>\startmiddlealigned ... \stopmiddlealigned</code>
<code>\startmiddlemakeup [...,\stackrel{*}{...}] ... \stopmiddlemakeup</code> <small>OPT</small> <code>* inherits: \seteazamakeup</code>
<code>\startminicitat [...]\stopminicitat</code> <small>OPT</small> <code>* SPRACHE</code>
<code>\startmixedcolumns [...,\stackrel{1}{...}] [...,\stackrel{2}{...}] ... \stopmixedcolumns</code> <small>OPT OPT</small> <code>1 NAME</code> <code>2 inherits: \setupmixedcolumns</code>
<code>\startMIXEDCOLUMNS [...,\stackrel{*}{...}] ... \stopMIXEDCOLUMNS</code> <small>OPT</small> <code>* inherits: \setupmixedcolumns</code> <code>instances: itemgroupcolumns boxedcolumns</code>
<code>\startmode [...,*...] ... \stopmode</code> <code>* NAME</code>
<code>\startmodeset [...,\stackrel{1}{...}] {\stackrel{2}{...}} ... \stopmodeset</code> <code>1 NAME implicit</code> <code>2 CONTENT</code>
<code>\startmodule [...]\stopmodule</code> <code>* FILE</code>
<code>\startmoduletestsection ... \stopmoduletestsection</code>
<code>\startmodule * ... \stopmodule</code> <code>* FILE</code>
<code>\startmpformula [...,*...] ... \stopmpformula</code> <small>OPT</small> <code>* impachetat tight centru incadrat inherits: \seteazafonttext</code>
<code>\startnamedsection [...]\stackrel{1}{...} [...,\stackrel{2}{...}] [...,\stackrel{3}{...}] ... \stopnamedsection</code> <small>OPT OPT</small> <code>1 ABSCHNITT</code> <code>2 titlu = TEXT</code> <code>semncarte = TEXT</code> <code>marcaje = TEXT</code> <code>lista = TEXT</code> <code>referinta = REFERENCE</code> <code>numarpropriu = TEXT</code> <code>3 KEY = VALUE</code>
<code>\startnamedsubformulas [...,\stackrel{1}{...}] {\stackrel{2}{...}} ... \stopnamedsubformulas</code> <small>OPT</small> <code>1 + - REFERENCE</code> <code>2 TEXT</code>

<p><code>\startnarrower [...,*...] ... \stopnarrower</code></p> <p style="text-align: center;">OPT</p> <p>* [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset</p>
<p><code>\startNARROWER [...,*...] ... \stopNARROWER</code></p> <p style="text-align: center;">OPT</p> <p>* [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset</p>
<p><code>\startnegativ ... \stopnegativ</code></p>
<p><code>\startnicelyfilledbox [...,*=...,...] ... \stopnicelyfilledbox</code></p> <p style="text-align: center;">OPT</p> <p>* latime = DIMENSION inaltime = DIMENSION offset = DIMENSION strut = da nu</p>
<p><code>\startnointerference ... \stopnointerference</code></p>
<p><code>\startnotallmodes [...,*...] ... \stopnotallmodes</code></p> <p>* NAME</p>
<p><code>\startnotasubsol [...,*...] ... \stopnotasubsol</code></p> <p style="text-align: center;">OPT</p> <p>* REFERENCE</p>
<p><code>\startnotasubsol [...,*=...,...] ... \stopnotasubsol</code></p> <p style="text-align: center;">OPT</p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p>
<p><code>\startNOTE [...,*...] ... \stopNOTE</code></p> <p style="text-align: center;">OPT</p> <p>* REFERENCE</p> <p>instances: notasubsol endnote</p>
<p><code>\startNOTE [...,*=...,...] ... \stopNOTE</code></p> <p style="text-align: center;">OPT</p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p> <p>instances: notasubsol endnote</p>
<p><code>\startnotext ... \stopnotext</code></p>
<p><code>\startnotmode [...,*...] ... \stopnotmode</code></p> <p>* NAME</p>
<p><code>\startoperator¹text [...²] [...] ... \stopoperator¹text</code></p> <p style="text-align: center;">OPT</p> <p>1 SPRACHE</p> <p>2 KEY</p>
<p><code>\startopus ... \stopopus</code></p>

<code>\startoutputstream [...] ... \stopoutputstream</code> * NAME
<code>\startoverlay ... \stopoverlay</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startPARSEDXML [...,..¹...,..²...,...] ... \stopPARSEDXML</code> <small>OPT</small> * inherits: \seteazatyping
<code>\startPARSEDXML [...,..¹...,..²...,...] ... \stopPARSEDXML</code> <small>OPT</small> * continuu
<code>\startpagefigure [...,..¹...,..²...,...] ... \stoppagefigure</code> <small>OPT</small> 1 FILE 2 inherits: \setupexternalfigure
<code>\startpagegrid [...,..¹...,..²...,...] ... \stoppagegrid</code> <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setuppagegrid
<code>\startpagegridspan [...,..¹...,..²...,...] ... \stoppagegridspan</code> <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setuppagegridspan
<code>\startPAGEGRID [...,..¹...,..²...,...] ... \stopPAGEGRID</code> <small>OPT</small> * inherits: \setuppagegrid
<code>\startpagelayout [...] ... \stoppagelayout</code> * pagina paginastanga paginadreapta
<code>\startpagemakeup [...,..¹...,..²...,...] ... \stoppagemakeup</code> <small>OPT</small> * inherits: \seteazamakeup
<code>\startpar [...,..¹...,..²...,...] ... \stoppar</code> <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupparagraph
<code>\startparagraf [...,..¹...,..²...,...] ... \stopparagraf</code> <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: \setupparagraph
<code>\startparagraphs [...] ... \stopparagraphs</code> * NAME
<code>\startparagraphscell ... \stopparagraphscell</code>
<code>\startPARAGRAPHS ... \stopPARAGRAPHS</code>

```
\startPARALLEL ... \stopPARALLEL
```

```
\startparbuilder [...] ... \stopparbuilder
```

```
* implicit oneline basic NAME
```

```
\startparte [...1...1...] [...2...2...] ... \stopparte
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  referinta  = REFERENCE
  numarpropriu = TEXT
```

```
2 KEY = VALUE
```

```
\startpuneFLOAT [...1...1...] [...2...2...] ... \stoppuneFLOAT
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE
```

```
2 KEY = VALUE
```

instances: chemical figure table intermezzo graphic

```
\startpunechemical [...1...1...] [...2...2...] ... \stoppunechemical
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE
```

```
2 KEY = VALUE
```

```
\startpunefigure [...1...1...] [...2...2...] ... \stoppunefigure
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin
marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE
```

```
2 KEY = VALUE
```

<pre> \startpunegraphic [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppunegraphic 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective referinta = REFERENCE 2 KEY = VALUE </pre>
<pre> \startpuneintermezzo [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppuneintermezzo 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective referinta = REFERENCE 2 KEY = VALUE </pre>
<pre> \startpunetable [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppunetable 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective referinta = REFERENCE 2 KEY = VALUE </pre>
<pre> \startplacepairedbox [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplacepairedbox 1 NAME 2 inherits: \setuppairedbox </pre>
<pre> \startpunePAIREDBOX [...,\stackrel{*}{=},...] ... \stoppunePAIREDBOX * inherits: \setuppairedbox instances: legenda </pre>
<pre> \startpositioning [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppositioning 1 NAME 2 inherits: \setarepozitie </pre>
<pre> \startpositionoverlay {...} ... \stoppositionoverlay * NAME </pre>
<pre> \startpositiv ... \stoppositiv </pre>
<pre> \startpostponing [...,\stackrel{*}{=},...] ... \stoppostponing * [-+]NUMBER </pre>

<pre> \startprefixtext [...] [...] ... \stopprefixtext OPT 1 SPRACHE 2 KEY </pre>
<pre> \startprincipalul [...,...[*]...,...] ... \stopprincipalul OPT * semncarte = TEXT inherits: \seteazablocsectiune </pre>
<pre> \startprocessassignmentcommand [...,...[*]...,...] ... \stopprocessassignmentcommand * KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,...[*]...,...] ... \stopprocessassignmentlist * KEY = VALUE </pre>
<pre> \startprocesscommacommand [...,[*]...] ... \stopprocesscommacommand * BEFEHL </pre>
<pre> \startprocesscommalist [...,[*]...] ... \stopprocesscommalist * BEFEHL </pre>
<pre> \startprodus [...] ... \stopprodus * FILE * </pre>
<pre> \startprodus ...[*] ... \stopprodus * FILE * </pre>
<pre> \startproiect [...] ... \stopproiect * FILE * </pre>
<pre> \startproiect ...[*] ... \stopproiect * FILE * </pre>
<pre> \startprologul [...,...[*]...,...] ... \stopprologul OPT * semncarte = TEXT inherits: \seteazablocsectiune </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpublicatie [¹...] [...,...²...,...] ... \stoppublicatie OPT OPT 1 NAME 2 tag = REFERENCE category = TEXT k = REFERENCE t = TEXT </pre>
<pre> \startpuneformula [...,...[*]...,...] ... \stoppuneformula OPT * titlu = TEXT suffix = TEXT referinta = + - REFERENCE </pre>

$\backslash\mathrm{startpuneformula} [\dots,\overset{\ast}{\dots}] \dots \backslash\mathrm{stoppuneformula}$ <p><small>OPT</small></p> <p>* + - REFERENCE</p>
$\backslash\mathrm{startpunelegenda} [\dots,\overset{\ast}{\dots},\dots] \dots \backslash\mathrm{stoppunelegenda}$ <p><small>OPT</small></p> <p>* inherits: \setuppairedbox</p>
$\backslash\mathrm{startrandomized} \dots \backslash\mathrm{stoprandomized}$
$\backslash\mathrm{startrawsetups} [\overset{1}{\dots}] [\overset{2}{\dots}] \dots \backslash\mathrm{stoprawsetups}$ <p><small>OPT</small></p> <p>1 grila</p> <p>2 NAME</p>
$\backslash\mathrm{startrawsetups} \overset{\ast}{\dots} \dots \backslash\mathrm{stoprawsetups}$ <p>* NAME</p>
$\backslash\mathrm{startreadingfile} \dots \backslash\mathrm{stopreadingfile}$
$\backslash\mathrm{startregime} [\overset{\ast}{\dots}] \dots \backslash\mathrm{stopregime}$ <p>* inherits: \enableregime</p>
$\backslash\mathrm{startregister} [\overset{1}{\dots}] [\overset{2}{\dots}] [\overset{3}{\dots}] [\overset{4}{\dots}] [\dots\overset{5}{+}\dots]$ <p><small>OPT OPT</small></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 TEXT</p> <p>4 TEXT PROCESSOR->TEXT</p> <p>5 INDEX</p>
$\backslash\mathrm{startreusableMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots},\dots\} \dots \backslash\mathrm{stopreusableMPgraphic}$ <p><small>OPT</small></p> <p>1 NAME</p> <p>2 KEY</p>
$\backslash\mathrm{startriglatext} \{\overset{\ast}{\dots}\} \dots \backslash\mathrm{stopriglatext}$ <p>* TEXT</p>
$\backslash\mathrm{startscript} [\overset{\ast}{\dots}] \dots \backslash\mathrm{stopscript}$ <p>* hangul hanzi nihongo ethiopic thai test NAME</p>
$\backslash\mathrm{startsdformula} [\dots,\overset{\ast}{\dots}] \dots \backslash\mathrm{stopsdformula}$ <p><small>OPT</small></p> <p>* impachetat tight centru incadrat inherits: \seteazafonttext</p>
$\backslash\mathrm{startsectionblock} [\overset{1}{\dots}] [\dots,\overset{2}{\dots},\dots] \dots \backslash\mathrm{stopsectionblock}$ <p><small>OPT</small></p> <p>1 NAME</p> <p>2 semncarte = TEXT inherits: \seteazablocsectiune</p>

<pre> \startSECTIONBLOCK [...[*]...] ... \stopSECTIONBLOCK OPT * semncarte = TEXT inherits: \seteazablocsectione instances: prologul principalul apendixuri epilogul </pre>
<pre> \startsectionlevel [...¹...] [...²...] [...³...] ... \stopsectionlevel OPT OPT OPT 1 NAME 2 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 3 KEY = VALUE </pre>
<pre> \startsectione [...¹...] [...²...] ... \stopsectione OPT OPT 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 2 KEY = VALUE </pre>
<pre> \startSECTIUNE [...¹...] [...²...] ... \stopSECTIUNE OPT OPT 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 2 KEY = VALUE instances: parte capitol sectiune subsectiune subsubsectiune subsubsubsectiune subsubsubsubsectiune titlu subiect subsubiect subsubsubiect subsubsubsubiect subsubsubsubsubiect </pre>
<pre> \startsetups [...¹...] [...²...] ... \stopsetups OPT OPT 1 grila 2 NAME </pre>
<pre> \startsetups \stopsetups * NAME </pre>
<pre> \startshift [...] ... \stopshift * NAME </pre>
<pre> \startsidebar [...¹...] [...²...] ... \stopsidebar OPT OPT 1 NAME 2 inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...[*]...] ... \stopsimplecolumns OPT * inherits: \setsimplecolumnhsize </pre>

$\backslash\text{startspecialitem}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] ... $\backslash\text{stopspecialitem}$ <small>OPT OPT</small> 1 element 2 REFERENCE
$\backslash\text{startspecialitem}$ [\dots] ... $\backslash\text{stopspecialitem}$ * sub propriu
$\backslash\text{startspecialitem}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stopspecialitem}$ 1 sym rulat mar 2 TEXT
$\backslash\text{startspeech}$ [$\dots,\overset{*}{\dots}$] ... $\backslash\text{stopspeech}$ <small>OPT</small> * inherits: $\backslash\text{startingust}$
$\backslash\text{startspformula}$ [$\dots,\overset{*}{\dots}$] ... $\backslash\text{stopspformula}$ <small>OPT</small> * impachetat tight centru incadrat inherits: $\backslash\text{seteazafonttext}$
$\backslash\text{startspread}$... $\backslash\text{stopspread}$
$\backslash\text{startstandardmakeup}$ [$\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopstandardmakeup}$ <small>OPT</small> * inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{start}$ [$\overset{*}{\dots}$] ... $\backslash\text{stop}$ <small>OPT</small> * NAME
$\backslash\text{startSTARTSTOP}$... $\backslash\text{stopSTARTSTOP}$
$\backslash\text{startstaticMPfigure}$ [$\overset{*}{\dots}$] ... $\backslash\text{stopstaticMPfigure}$ * NAME
$\backslash\text{startstaticMPgraphic}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots},\dots$] ... $\backslash\text{stopstaticMPgraphic}$ <small>OPT</small> 1 NAME 2 KEY
$\backslash\text{STARTSTOP}$ [$\overset{*}{\dots}$] * CONTENT
$\backslash\text{startstrictinspectnextcharacter}$... $\backslash\text{stopstrictinspectnextcharacter}$

`\startstructurepageregister [...]1 [...]2 [...]3 [...]4 ...`
OPT

1 NAME
 2 NAME
 3 eticheta = NAME
 keys = TEXT PROCESSOR->TEXT
 entries = TEXT PROCESSOR->TEXT
 keys:1 = TEXT
 keys:2 = TEXT
 keys:3 = TEXT
 entries:1 = TEXT
 entries:2 = TEXT
 entries:3 = TEXT
 alternativ = TEXT
 4 KEY = VALUE

`\startstyle [...]*... \stopstyle`

* inherits: \setupstyle

`\startstyle [...]*... \stopstyle`

* NAME FONT

`\startSTYLE ... \stopSTYLE`

`\startsubformulas [...]*... \stopsubformulas`
OPT

* + - REFERENCE

`\startsubiect [...]1 [...]2 ... \stopsubiect`
OPT OPT

1 titlu = TEXT
 semncarte = TEXT
 marcaje = TEXT
 lista = TEXT
 referinta = REFERENCE
 numarpropriu = TEXT
 2 KEY = VALUE

`\startsubjectlevel [...]1 [...]2 [...]3 ... \stopsubjectlevel`
OPT OPT OPT

1 NAME
 2 titlu = TEXT
 semncarte = TEXT
 marcaje = TEXT
 lista = TEXT
 referinta = REFERENCE
 numarpropriu = TEXT
 3 KEY = VALUE

`\startsubsectiune [...]1 [...]2 ... \stopsubsectiune`
OPT OPT

1 titlu = TEXT
 semncarte = TEXT
 marcaje = TEXT
 lista = TEXT
 referinta = REFERENCE
 numarpropriu = TEXT
 2 KEY = VALUE

`\startsubsentence ... \stopsubsentence`

`\startsubsoltabel [...]*... \stopsubsoltabel`

* NAME

\startsubstack ... \stopsubstack

\startsubsubject [...,\overset{1}{=},...,\overset{2}{=},...] ... \stopsubsubject

1 titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

2 KEY = VALUE

\startsubsubsection [...,\overset{1}{=},...,\overset{2}{=},...] ... \stopsubsubsection

1 titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

2 KEY = VALUE

\startsubsubsubject [...,\overset{1}{=},...,\overset{2}{=},...] ... \stopsubsubsubject

1 titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

2 KEY = VALUE

\startsubsubsubsection [...,\overset{1}{=},...,\overset{2}{=},...] ... \stopsubsubsubsection

1 titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

2 KEY = VALUE

\startsubsubsubsubject [...,\overset{1}{=},...,\overset{2}{=},...] ... \stopsubsubsubsubject

1 titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

2 KEY = VALUE

\startsubsubsubsubsection [...,\overset{1}{=},...,\overset{2}{=},...] ... \stopsubsubsubsubsection

1 titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

2 KEY = VALUE

$\backslash\text{startsubsubsubsubsubject} [\dots, \overset{1}{\underset{\text{OPT}}{=}} \dots, \dots] [\dots, \overset{2}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopsubsubsubsubsubject}$ <pre> 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 2 KEY = VALUE </pre>
$\backslash\text{startsymbolset} [\dots] \dots \backslash\text{stopsymbolset}$ <pre> * NAME </pre>
$\backslash\text{startTABLE} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTABLE}$ <pre> * inherits: \setupTABLE </pre>
$\backslash\text{startTABLEbody} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTABLEbody}$ <pre> * inherits: \setupTABLE </pre>
$\backslash\text{startTABLEfoot} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTABLEfoot}$ <pre> * inherits: \setupTABLE </pre>
$\backslash\text{startTABLEhead} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTABLEhead}$ <pre> * inherits: \setupTABLE </pre>
$\backslash\text{startTABLEnext} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTABLEnext}$ <pre> * inherits: \setupTABLE </pre>
$\backslash\text{startTEX} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTEX}$ <pre> * inherits: \seteazatyping </pre>
$\backslash\text{startTEXpage} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTEXpage}$ <pre> * inherits: \setupfittingpage </pre>
$\backslash\text{startTEX} [\dots, \overset{*}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stopTEX}$ <pre> * continuu </pre>
$\backslash\text{starttabelele} [\dots] \dots \backslash\text{stoptabelele}$ <pre> * TEMPLATE </pre>
$\backslash\text{starttabelele} [\dots] \dots \backslash\text{stoptabelele}$ <pre> * NAME </pre>
$\backslash\text{starttabelul} [\overset{1}{\dots}] [\dots, \overset{2}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stoptabelul}$ <pre> 1 TEMPLATE 2 inherits: \seteazatabele </pre>
$\backslash\text{starttabelul} [\overset{1}{\dots}] [\dots, \overset{2}{\underset{\text{OPT}}{=}} \dots, \dots] \dots \backslash\text{stoptabelul}$ <pre> 1 NAME 2 inherits: \seteazatabele </pre>

$\backslash\text{starttabulate}$ $[/\overset{1}{...}/]$ $[\dots,\dots\overset{2}{=}\dots,]\dots\backslash\text{stoptabulate}$ <small>OPT</small> <small>OPT</small> 1 <code>TEMPLATE</code> 2 <code>inherits: \seteazatabulatori</code>
$\backslash\text{starttabulatehead}$ $[\overset{*}{...}] \dots\backslash\text{stoptabulatehead}$ <small>OPT</small> * <code>NAME</code>
$\backslash\text{starttabulatetail}$ $[\overset{*}{...}] \dots\backslash\text{stoptabulatetail}$ <small>OPT</small> * <code>NAME</code>
$\backslash\text{startTABULATE}$ $[\overset{1}{...}] [\dots,\dots\overset{2}{=}\dots,]\dots\backslash\text{stopTABULATE}$ <small>OPT</small> <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \seteazatabulatori</code> <code>instances: legenda fapt</code>
$\backslash\text{startTABULATION}$ $[\overset{1}{...}] [\dots,\dots\overset{2}{=}\dots,]\dots\backslash\text{stopTABULATION}$ <small>OPT</small> <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \setuptabulation</code>
$\backslash\text{starttaglabeltext}$ $[\overset{1}{...}] [\overset{2}{...}] \dots\backslash\text{stoptaglabeltext}$ <small>OPT</small> 1 <code>SPRACHE</code> 2 <code>KEY</code>
$\backslash\text{starttexcode} \dots\backslash\text{stoptexcode}$
$\backslash\text{starttexdefinition}$ $\overset{1}{...} \overset{2}{...} \overset{3}{...} \overset{4}{...} \overset{5}{...} \overset{6}{...} \dots\backslash\text{stoptexdefinition}$ <small>OPT</small> <small>OPT</small> <small>OPT</small> <small>OPT</small> <small>OPT</small> <small>OPT</small> 1 <code>spaces nospaces</code> 2 <code>global</code> 3 <code>unexpanded</code> 4 <code>expanded</code> 5 <code>NAME</code> 6 <code>TEMPLATE</code>
$\backslash\text{starttext} \dots\backslash\text{stoptext}$
$\backslash\text{starttextajutator}$ $[\overset{*}{...}] \dots\backslash\text{stoptextajutator}$ <small>OPT</small> * <code>REFERENCE</code>
$\backslash\text{starttextbackground}$ $[\overset{1}{...}] [\dots,\dots\overset{2}{=}\dots,]\dots\backslash\text{stoptextbackground}$ <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \setuptextbackground</code>
$\backslash\text{starttextbackgroundmanual} \dots\backslash\text{stoptextbackgroundmanual}$
$\backslash\text{startTEXTBACKGROUND}$ $[\dots,\dots\overset{*}{=}\dots,]\dots\backslash\text{stopTEXTBACKGROUND}$ <small>OPT</small> * <code>inherits: \setuptextbackground</code>

$\backslash\text{starttextcolor}$ [...] ... $\backslash\text{stoptextcolor}$ * COLOR
$\backslash\text{starttextcolorintent}$... $\backslash\text{stoptextcolorintent}$
$\backslash\text{starttexteticheta}$ [¹ ...] [²] ... $\backslash\text{stoptexteticheta}$ <small>OPT</small> 1 SPRACHE 2 KEY
$\backslash\text{startETICHETAtext}$ [¹ ...] [²] ... $\backslash\text{stopETICHETAtext}$ <small>OPT</small> 1 SPRACHE 2 KEY instances: antet eticheta mathlabel taglabel unitate operator prefix suffix btxlabel
$\backslash\text{starttextflow}$ [...] ... $\backslash\text{stoptextflow}$ * NAME
$\backslash\text{starttextinconjurat}$ [¹] [..., ² ...,...] ... $\backslash\text{stoptextinconjurat}$ <small>OPT</small> <small>OPT</small> 1 stanga dreapta centru niciunul 2 inherits: $\backslash\text{setupframedtext}$
$\backslash\text{startTEXTINCONJURAT}$ [¹] [..., ² ...,...] ... $\backslash\text{stopTEXTINCONJURAT}$ <small>OPT</small> <small>OPT</small> 1 stanga dreapta centru niciunul 2 inherits: $\backslash\text{setupframedtext}$ instances: textinconjurat
$\backslash\text{starttextmakeup}$ [..., [*] ...,...] ... $\backslash\text{stoptextmakeup}$ <small>OPT</small> * inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{starttexttitlu}$ [¹] [...] ... $\backslash\text{stoptexttitlu}$ <small>OPT</small> 1 SPRACHE 2 KEY
$\backslash\text{starttitlu}$ [..., ¹ ...] { ² } ... $\backslash\text{stoptitlu}$ <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{starttokens}$ [...] ... $\backslash\text{stoptokens}$ * NAME
$\backslash\text{starttransparent}$ [...] ... $\backslash\text{stoptransparent}$ * COLOR

$\backslash\text{starttypescript} [\overset{1}{\dots}, \dots] [\overset{2}{\dots}, \dots] [\overset{3}{\dots}, \dots] \dots \backslash\text{stoptypescript}$ $\text{1 serif sans mono math handwriting calligraphy}$ 2 NAME 3 size nume
$\backslash\text{starttypescriptcollection} [\dots] \dots \backslash\text{stoptypescriptcollection}$ $\ast \text{ NAME}$
$\backslash\text{starttyping} [\dots, \overset{\ast}{\dots}, \dots] \dots \backslash\text{stoptyping}$ $\ast \text{ inherits: \seteazatyping}$
$\backslash\text{starttyping} [\dots, \overset{\ast}{\dots}, \dots] \dots \backslash\text{stoptyping}$ $\ast \text{ continuu}$
$\backslash\text{startTYPING} [\dots, \overset{\ast}{\dots}, \dots] \dots \backslash\text{stopTYPING}$ $\ast \text{ inherits: \seteazatyping}$ $\text{instances: typing LUA MP PARSEDXML TEX XML}$
$\backslash\text{startTYPING} [\dots, \overset{\ast}{\dots}, \dots] \dots \backslash\text{stopTYPING}$ $\ast \text{ continuu}$ $\text{instances: typing LUA MP PARSEDXML TEX XML}$
$\backslash\text{startuniqueMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots}, \dots\} \dots \backslash\text{stopuniqueMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuniqueMPpagegraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots}, \dots\} \dots \backslash\text{stopuniqueMPpagegraphic}$ 1 NAME 2 KEY
$\backslash\text{startunittext} [\overset{1}{\dots}] [\overset{2}{\dots}] \dots \backslash\text{stopunittext}$ 1 SPRACHE 2 KEY
$\backslash\text{startusableMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots}, \dots\} \dots \backslash\text{stopusableMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startuseMPgraphic} \{\overset{1}{\dots}\} \{\overset{2}{\dots}, \dots\} \dots \backslash\text{stopuseMPgraphic}$ 1 NAME 2 KEY
$\backslash\text{startusemathstyleparameter} \backslash\ast \dots \backslash\text{stopusemathstyleparameter}$ $\ast \text{ CSNAME}$

$\backslash\text{startusingbtxspecification}$ [...] ... $\backslash\text{stopusingbtxspecification}$ * NAME
$\backslash\text{startvboxregister}$... $\backslash\text{stopvboxregister}$ * CSNAME NUMBER
$\backslash\text{startvboxtohbox}$... $\backslash\text{stopvboxtohbox}$
$\backslash\text{startvboxtohboxseparator}$... $\backslash\text{stopvboxtohboxseparator}$
$\backslash\text{startviewerlayer}$ [...] ... $\backslash\text{stopviewerlayer}$ * NAME
$\backslash\text{startVIEWERLAYER}$... $\backslash\text{stopVIEWERLAYER}$
$\backslash\text{startvtopregister}$... $\backslash\text{stopvtopregister}$ * CSNAME NUMBER
$\backslash\text{startXML}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopXML}$ * inherits: $\backslash\text{seteazatyping}$
$\backslash\text{startXML}$ [... [*] ... ^{OPT} ...] ... $\backslash\text{stopXML}$ * continuu
$\backslash\text{startxcell}$ [... ¹ ... ^{OPT}] [... ² ... ^{OPT} ...] ... $\backslash\text{stopxcell}$ 1 NAME 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxcellgroup}$ [... ¹ ... ^{OPT}] [... ² ... ^{OPT} ...] ... $\backslash\text{stopxcellgroup}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxgroup}$ [... ¹ ... ^{OPT}] [... ² ... ^{OPT} ...] ... $\backslash\text{stopxgroup}$ 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxmldisplayverbatim}$ [...] ... $\backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmlinlineverbatim}$ [...] ... $\backslash\text{stopxmlinlineverbatim}$ * NAME
$\backslash\text{startxmlraw}$... $\backslash\text{stopxmlraw}$

$\backslash\text{startxmlsetups}$ $[\overset{1}{\dots}]$ $[\overset{2}{\dots}]$... $\backslash\text{stopxmlsetups}$ <small>OPT</small> 1 grila 2 NAME
$\backslash\text{startxmlsetups}$ \dots ... $\backslash\text{stopxmlsetups}$ * NAME
$\backslash\text{startxrow}$ $[\overset{1}{\dots}]$ $[\dots, \overset{2}{\dots}, \dots]$... $\backslash\text{stopxrow}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxrowgroup}$ $[\overset{1}{\dots}]$ $[\dots, \overset{2}{\dots}, \dots]$... $\backslash\text{stopxrowgroup}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ $[\dots, \overset{*}{\dots}, \dots]$... $\backslash\text{stopxtable}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablebody}$ $[\dots, \overset{*}{\dots}, \dots]$... $\backslash\text{stopxtablebody}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablebody}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxtablebody}$ <small>OPT</small> * NAME
$\backslash\text{startxtablefoot}$ $[\dots, \overset{*}{\dots}, \dots]$... $\backslash\text{stopxtablefoot}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablefoot}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxtablefoot}$ <small>OPT</small> * NAME
$\backslash\text{startxtablehead}$ $[\dots, \overset{*}{\dots}, \dots]$... $\backslash\text{stopxtablehead}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablehead}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxtablehead}$ <small>OPT</small> * NAME
$\backslash\text{startxtablenext}$ $[\dots, \overset{*}{\dots}, \dots]$... $\backslash\text{stopxtablenext}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablenext}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxtablenext}$ <small>OPT</small> * NAME
$\backslash\text{startXTABLE}$ $[\dots, \overset{*}{\dots}, \dots]$... $\backslash\text{stopXTABLE}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ $[\overset{*}{\dots}]$... $\backslash\text{stopxtable}$ <small>OPT</small> * NAME

<code>\stivacampuri [...]</code> <div> $[...,\overset{2}{...}]$ $[...,\overset{3}{...},...]$ </div> <div> <div>OPT</div> <div>OPT</div> </div> <div> 1 NAME 2 NAME 3 inherits: \setupfieldcategory </div>
<code>\stoplinenote [...]</code> <div> * REFERENCE </div>
<code>\stopLINENOTE [...]</code> <div> * REFERENCE </div> <div> instances: linenote </div>
<code>\stoplinie [...]</code> <div> * REFERENCE </div>
<code>\stopregister [...]</code> <div> $[...]$ $[...]$ </div> <div> 1 NAME 2 NAME </div>
<code>\stopstructurepageregister [...]</code> <div> $[...]$ $[...]$ </div> <div> 1 NAME 2 NAME </div>
<code>\strictdoifelsenextoptional {...}</code> <div> $\{...\}$ $\{...\}$ </div> <div> 1 TRUE 2 FALSE </div>
<code>\strictdoifnextoptionalelse {...}</code> <div> $\{...\}$ $\{...\}$ </div> <div> 1 TRUE 2 FALSE </div>
<code>\stripcharacter ... \from ... \to ...</code> <div> $...$ $...$ $...$ </div> <div> 1 CHARACTER 2 TEXT 3 CSNAME </div>
<code>\strippedcsname *</code> <div> * CSNAME </div>
<code>\strippedcsname ...</code> <div> * TEXT </div>
<code>\stripspaces \from ... \to ...</code> <div> $...$ $...$ </div> <div> 1 TEXT 2 CSNAME </div>

<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...,¹...,²...] {...}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [¹...] {...}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {...}</code> * TEXT
<code>\subject [...,¹...,²...] {...}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\sublinie {...}</code> * CONTENT
<code>\sublinii {...}</code> * CONTENT

<code>\subpagenumber</code>
<code>\subsectionone [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...¹} {...²} \...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subsubject [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsectionone [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubject [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubsectionone [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubsubject [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubsubsectionone [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubsubsubject [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubsubsubsectionone [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subsubsubsubsubsubject [...¹,...] {...²}</code> <small>OPT</small> 1 REFERENCE 2 TEXT
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME

<code>\supralinie {...}</code> * CONTENT
<code>\swapcounts \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swapdimens \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \¹... \²...</code> 1 CSNAME 2 CSNAME
<code>\swaptypeface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg roman serif regular sans sansserif suport type teletype mono scrismannual caligrafic
<code>\switchstyleonly *</code> * CSNAME
<code>\switchtocolour [...]</code> * COLOR
<code>\switchtointerlinespace [...,¹...] [...,²..._{OPT},...]</code> 1 NAME 2 inherits: \seteazaspatiuinterliniar
<code>\switchtointerlinespace [...,¹...] [...,²..._{OPT},...]</code> * on dezactivat reset auto mic mediu mare NUMMER DIMENSION
<code>\switchtointerlinespace [...]</code> * NAME
<code>\symbolreference [...]</code> * REFERENCE
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>

\synchro ¹ nizemarking [...] [² ...] [³ ...] <div> <div>1</div> <div>BESCHRIFTUNG</div> </div> <div> <div>2</div> <div>NUMMER</div> </div> <div> <div>3</div> <div>mentine</div> </div> <div>OPT</div>
\synthesizeoutputstreams [...*,...] <div> <div>*</div> <div>NAME</div> </div>
\synchro [*] nizestrut {...} <div> <div>*</div> <div>da nu auto cap ajustat linie implicit CHARACTER</div> </div>
\synchronizewhitespace
\SYNONYM [¹ ...] { ² ...} { ³ ...} <div>OPT</div> <div> <div>1</div> <div>NAME</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>CONTENT</div> </div> <div>instances: abreviere</div>
\systemlog {...} {...} {...} <div> <div>1</div> <div>FILE</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
\systemlogfirst {...} {...} {...} <div> <div>1</div> <div>FILE</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
\systemloglast {...} {...} {...} <div> <div>1</div> <div>FILE</div> </div> <div> <div>2</div> <div>TEXT</div> </div> <div> <div>3</div> <div>TEXT</div> </div>
\systemsetups {...} <div> <div>*</div> <div>NAME</div> </div>
\TABLE
\TaBlE
\TEX
\TeX
\TheNormalizedFontSize
\TransparencyHack

<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\taglabellanguage</code>
<code>\taglabeltext {...}</code> * KEY
<code>\tbinom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\tequal {...} {...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\testandsplitstring ... \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\testcolumn [...] [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT </div> 1 NUMMER 2 DIMENSION
<code>\testfeature {...}</code> * NUMMER
<code>\testfeatureonce {...}</code> * NUMMER

\backslash testpage [...] [...] ² <small>OPT</small> 1 NUMMER 2 DIMENSION
\backslash testpageonly [...] [...] ² <small>OPT</small> 1 NUMMER 2 DIMENSION
\backslash testpagesync [...] [...] ² <small>OPT</small> 1 NUMMER 2 DIMENSION
\backslash testtokens [...] * NAME
\backslash tex {...} * CONTENT
\backslash texdefinition {...} * NAME
\backslash texsetup {...} * NAME
\backslash textajutator [...] ¹ {...} ² {...} ³ <small>OPT</small> 1 REFERENCE 2 TEXT 3 TEXT
\backslash TEXTBACKGROUND {...} * CONTENT
\backslash textcitation [...] ¹ [...] ² <small>OPT</small> 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\backslash textcitation [...] ¹ [...] ² <small>OPT</small> 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear 2 REFERENCE

`\textcitation [...1...] [...2...]`

```
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits: \setupbtx

2  KEY = VALUE
```

`\textcite [...1...] [...2...]`
OPT

```
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits: \setupbtx

2  REFERENCE
```

`\textcite [...1...] [...2...]`
OPT

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear

2  REFERENCE
```

`\textcite [...1...] [...2...]`

```
1  referinta    = REFERENCE
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
                  authoryear
   inainte      = BEFEHL
   dupa         = BEFEHL
   stanga       = BEFEHL
   dreapta      = BEFEHL
   inherits: \setupbtx

2  KEY = VALUE
```

`\textcontrolspace`

`\texteticheta {...}`

* KEY

`\ETICHETAtext {...}`

* KEY

instances: antet eticheta mathlabel taglabel unitate operator prefix suffix btxlabel

`\textflowcollector {...}`

* NAME

`\textinconjurat [...1...] {...2...}`
OPT

```
1  inherits: \setupframedtext

2  CONTENT
```

$\backslash\text{TEXTINCONJURAT}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 inherits: $\backslash\text{setupframedtext}$ 2 CONTENT instances: textinconjurat
$\backslash\text{texmarginal}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 referinta = REFERENCE inherits: $\backslash\text{setupmargindata}$ 2 CONTENT
$\backslash\text{texmath}$ $\{\dots\}$ * CONTENT
$\backslash\text{textminus}$
$\backslash\text{texormathchar}$ $\{\dots\}$ * NUMMER
$\backslash\text{textplus}$
$\backslash\text{texittitlu}$ $\{\dots\}$ * KEY
$\backslash\text{textumplere}$ [$\dots\overset{1}{=}\dots$] $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ <small>OPT OPT OPT</small> 1 inherits: $\backslash\text{seteazarigleumplere}$ 2 TEXT 3 TEXT
$\backslash\text{textvisiblespace}$
$\backslash\text{tfrac}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ 1 CONTENT 2 CONTENT
$\backslash\text{thai}$
$\backslash\text{thainumerals}$ $\{\dots\}$ * NUMMER
$\backslash\text{thefirstcharacter}$ $\{\dots\}$ * TEXT
$\backslash\text{thenormalizedbodyfontsize}$ $\{\dots\}$ * DIMENSION
$\backslash\text{theremainingcharacters}$ $\{\dots\}$ * TEXT

<code>\thickspace</code>
<code>\thinspace</code>
<code>\thirddoffivearguments {¹.} {².} {³.} {⁴.} {⁵.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\thirddoffourarguments {¹.} {².} {³.} {⁴.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\thirddofsixarguments {¹.} {².} {³.} {⁴.} {⁵.} {⁶.}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\thirddofthreearguments {¹.} {².} {³.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thirddofthreeunexpanded {¹.} {².} {³.}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\thookleftarrow {¹.} {².}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\thookrightarrow {¹.} {².}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
<code>\threedigitrounding {[*].}</code> * NUMMER

$\backslash\text{tibetan}\text{numerals}\{\dots\}$ * NUMBER
$\backslash\text{tightlayer}[\dots]$ * NAME
$\backslash\text{tilde}\{\dots\}$ * CHARACTER
$\backslash\text{tinyfont}$
$\backslash\text{titlu}[\dots,\dots]^{1}\{\dots\}^{2}$ <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{titlumarginal}[\dots,\dots]^{1}\{\dots\}^{2}$ <small>OPT</small> 1 <code>referinta = REFERENCE</code> <code>inherits: \setupmargindata</code> 2 CONTENT
$\backslash\text{tLeftarrow}\{\dots\}^{1}\{\dots\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tLeftrightarrow}\{\dots\}^{1}\{\dots\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tlap}\{\dots\}$ * CONTENT
$\backslash\text{tleftarrow}\{\dots\}^{1}\{\dots\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tlefttharpoondown}\{\dots\}^{1}\{\dots\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tlefttharpoonup}\{\dots\}^{1}\{\dots\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tleftrightarrow}\{\dots\}^{1}\{\dots\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT

$\backslash\text{tleftrightharpoons}$ $\overset{1}{\{...\}}$ $\overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tmapsto}$ $\overset{1}{\{...\}}$ $\overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\text{tochar}$ $\{...\}$ * NAME
$\backslash\text{tolinenote}$ $[...\]$ * REFERENCE
$\backslash\text{tooltip}$ $[...,...\overset{1}{=},...]$ $\overset{2}{\{...\}}$ $\overset{3}{\{...\}}$ <small>OPT</small> 1 inherits: $\backslash\text{setuptooltip}$ 2 TEXT 3 TEXT
$\backslash\text{tooltip}$ $[\overset{1}{...}]$ $\overset{2}{\{...\}}$ $\overset{3}{\{...\}}$ <small>OPT</small> 1 stanga centru dreapta 2 TEXT 3 TEXT
$\backslash\text{TOOLTIP}$ $[...,...\overset{1}{=},...]$ $\overset{2}{\{...\}}$ $\overset{3}{\{...\}}$ <small>OPT</small> 1 inherits: $\backslash\text{setuptooltip}$ 2 TEXT 3 TEXT instances: tooltip
$\backslash\text{TOOLTIP}$ $[\overset{1}{...}]$ $\overset{2}{\{...\}}$ $\overset{3}{\{...\}}$ <small>OPT</small> 1 stanga centru dreapta 2 TEXT 3 TEXT instances: tooltip
$\backslash\text{topbox}$ $\{...\}$ * CONTENT
$\backslash\text{topleftbox}$ $\{...\}$ * CONTENT
$\backslash\text{toplinebox}$ $\{...\}$ * CONTENT

$\backslash\mathrm{toprightbox}\{\ldots\}$ * CONTENT
$\backslash\mathrm{topskippedbox}\{\ldots\}$ * CONTENT
$\backslash\mathrm{tRightarrow}\overset{1}{\{\ldots\}}\overset{2}{\{\ldots\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{tracecatcodetables}$
$\backslash\mathrm{tracedfontname}\{\ldots\}$ * FONT
$\backslash\mathrm{traceoutputroutines}$
$\backslash\mathrm{tracepositions}$
$\backslash\mathrm{traduce}\left[\ldots,\overset{*}{\ldots}=\overset{1}{\ldots},\overset{2}{\ldots}\right]$ * SPRACHE = TEXT
$\backslash\mathrm{transparencycomponents}\{\ldots\}$ * COLOR
$\backslash\mathrm{transparent}\overset{1}{[\ldots]}\overset{2}{\{\ldots\}}$ 1 COLOR 2 CONTENT
$\backslash\mathrm{trecilafonttext}\left[\ldots,\overset{*}{\ldots}\right]$ * inherits: $\backslash\mathrm{seteazafonttext}$
$\backslash\mathrm{trel}\overset{1}{\{\ldots\}}\overset{2}{\{\ldots\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{trightarrow}\overset{1}{\{\ldots\}}\overset{2}{\{\ldots\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{trightharpoondown}\overset{1}{\{\ldots\}}\overset{2}{\{\ldots\}}$ 1 TEXT 2 TEXT
$\backslash\mathrm{trightharpoonup}\overset{1}{\{\ldots\}}\overset{2}{\{\ldots\}}$ 1 TEXT 2 TEXT

$\backslash\mathrm{trig}\mathrm{ht}\mathrm{lef}\mathrm{tharp}\mathrm{oons}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{trig}\mathrm{ht}\mathrm{over}\mathrm{lef}\mathrm{tar}\mathrm{row}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{triple}\mathrm{bond}$
$\backslash\mathrm{true}\mathrm{fil}\mathrm{e}\mathrm{na}\mathrm{me}\ \{...\}$ * FILE
$\backslash\mathrm{true}\mathrm{font}\mathrm{na}\mathrm{me}\ \{...\}$ * FONT
$\backslash\mathrm{ttr}\mathrm{ag}\mathrm{ged}\mathrm{right}$
$\backslash\mathrm{ttri}\mathrm{pl}\mathrm{er}\mathrm{el}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{ttwo}\mathrm{head}\mathrm{lef}\mathrm{tar}\mathrm{row}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{ttwo}\mathrm{head}\mathrm{right}\mathrm{ar}\mathrm{row}\ \overset{1}{\{...\}}\ \overset{2}{\{...\}}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{two}\mathrm{dig}\mathrm{it}\mathrm{rou}\mathrm{nd}\mathrm{ing}\ \{...\}$ * NUMBER
$\backslash\mathrm{tx}$
$\backslash\mathrm{txx}$
$\backslash\mathrm{typ}\ [\dots\overset{1}{=}\dots]\ \overset{2}{\{...\}}$ <small>OPT</small> 1 inherits: $\backslash\mathrm{seteazatype}$ 2 CONTENT
$\backslash\mathrm{type}\ [\dots\overset{1}{=}\dots]\ \overset{2}{\{...\}}$ <small>OPT</small> 1 inherits: $\backslash\mathrm{seteazatype}$ 2 CONTENT
$\backslash\mathrm{typed}\mathrm{e}\mathrm{f}\mathrm{i}\mathrm{n}\mathrm{e}\mathrm{d}\mathrm{b}\mathrm{u}\mathrm{f}\mathrm{f}\mathrm{e}\mathrm{r}\ [\overset{1}{...}]\ [\dots\overset{2}{=}\dots]$ <small>OPT</small> 1 BUFFER 2 inherits: $\backslash\mathrm{seteazatyping}$

<code>\typeface</code>
<code>\typefile</code> ¹ _{OPT} [...] ² _{OPT} [...,.. _{OPT} ...,...] { ³ ...} 1 NAME 2 inherits: \seteazatyping 3 FILE
<code>\typescriptone</code>
<code>\typescriptprefix</code> {.*} * NAME
<code>\typescriptthree</code>
<code>\typescripttwo</code>
<code>\typesetbuffer</code> ¹ _{OPT} [...] ² _{OPT} [...,.. _{OPT} ...,...] 1 * BUFFER 2 inherits: \setupexternalfigure
<code>\typesetfile</code> ¹ [...] ² _{OPT} [...] ³ _{OPT} [...,.. _{OPT} ...,...] 1 NAME FILE 2 FILE TEXT 3 inherits: \setupexternalfigure
<code>\type</code> [...,.. _{OPT} ...,...] << ² ...>> 1 inherits: \seteazatype 2 ANGLES
<code>\TYPE</code> [...,.. _{OPT} ...,...] { ² ...} 1 inherits: \seteazatype 2 CONTENT
<code>\TYPE</code> [...,.. _{OPT} ...,...] << ² ...>> 1 inherits: \seteazatype 2 ANGLES
<code>\typ</code> [...,.. _{OPT} ...,...] << ² ...>> 1 inherits: \seteazatype 2 ANGLES
<code>\uconvertnumber</code> { ¹ ...} { ² ...} 1 inherits: \converttestenumar 2 NUMMER

$\backslash\mathrm{uedcatcodecommand} \backslash^1 \dots^2 \{ \dots^3 \}$ 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
$\backslash\mathrm{ultimasubpagina}$
$\backslash\mathrm{undefinevalue} \{ \dots \}$ * NAME
$\backslash\mathrm{undepthed} \{ \dots \}$ * CONTENT
$\backslash\mathrm{underbartext} \{ \dots^1 \} \{ \dots^2 \}$ 1 TEXT 2 TEXT
$\backslash\mathrm{underbrace} \{ \dots^* \}$ * TEXT
$\backslash\mathrm{underbracetext} \{ \dots^1 \} \{ \dots^2 \}$ 1 TEXT 2 TEXT
$\backslash\mathrm{underbracket} \{ \dots^* \}$ * TEXT
$\backslash\mathrm{underbrackettext} \{ \dots^1 \} \{ \dots^2 \}$ 1 TEXT 2 TEXT
$\backslash\mathrm{underdash} \{ \dots \}$ * CONTENT
$\backslash\mathrm{underdashes} \{ \dots \}$ * CONTENT
$\backslash\mathrm{underdot} \{ \dots \}$ * CONTENT
$\backslash\mathrm{underdots} \{ \dots \}$ * CONTENT
$\backslash\mathrm{underleftarrow} \{ \dots \}$ * TEXT
$\backslash\mathrm{underleftharpoonupdown} \{ \dots \}$ * TEXT

$\underleftharpoonup \{...\}$ * TEXT
$\underleftrightharpoonup \{...\}$ * TEXT
$\underparent \{...\}$ * TEXT
$\underparenttext \{...\} \{...\}$ 1 TEXT 2 TEXT
$\underrandom \{...\}$ * CONTENT
$\underrandoms \{...\}$ * CONTENT
$\underrightharpoonup \{...\}$ * TEXT
$\underrightharpoonupdown \{...\}$ * TEXT
$\underrightharpoonupup \{...\}$ * TEXT
$\underset \{...\} \{...\}$ 1 TEXT 2 TEXT
$\understrike \{...\}$ * CONTENT
$\understrikes \{...\}$ * CONTENT
$\undertwoheadleftarrow \{...\}$ * TEXT
$\undertwoheadrightarrow \{...\}$ * TEXT
$\undeva \{...\} \{...\} [...] \{...\}$ 1 TEXT 2 TEXT 3 REFERENCE

<code>\undoassign [...]¹ [...]²...</code> 1 TEXT 2 KEY = VALUE
<code>\unframed [...]¹...²...] {...}</code> <small>OPT</small> 1 inherits: \seteazainconjurat 2 CONTENT
<code>\unhhbox ...¹ \with {...}</code> 1 CSNAME NUMMER 2 BEFEHL
<code>\unihex {...}</code> * NUMMER
<code>\uniqueMPgraphic {...}¹ {...]²...]</code> <small>OPT</small> 1 NAME 2 KEY = VALUE
<code>\uniqueMPpagegraphic {...}¹ {...]²...]</code> <small>OPT</small> 1 NAME 2 KEY = VALUE
<code>\unitate {...}</code> * CONTENT
<code>\UNITATE {...}</code> * CONTENT instances: unitate
<code>\unitlanguage</code>
<code>\unittext {...}</code> * KEY
<code>\unprotect ... \protect</code>
<code>\unprotected ...[*] \par</code> * CONTENT
<code>\unregisterhyphenationpattern [...]¹ [...]²]</code> <small>OPT</small> 1 SPRACHE 2 TEXT
<code>\unspaceafter \...¹ {...}</code> 1 CSNAME 2 TEXT

<code>\unspaceargument ... \to \^2...</code> 1 TEXT 2 CSNAME
<code>\unspaced {...}</code> * TEXT
<code>\unspacestring ... \to \^2...</code> 1 TEXT 2 CSNAME
<code>\untexargument {...} \to \^2...</code> 1 TEXT 2 CSNAME
<code>\untexcommand {...} \to \^2...</code> 1 CSNAME 2 CSNAME
<code>\uppercased {...}</code> * TEXT
<code>\uppercasestring ... \to \^2...</code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> * NAME
<code>\urmatoareasubpagina</code>
<code>\usealignparameter \^2...</code> * CSNAME

\useblankparameter *.. * CSNAME
\usebodyfont [...*,...] * inherits: \seteazafonttext
\usebodyfontparameter *.. * CSNAME
\usebtxdataset ¹ [...] ² [...] ³ [...] ³ [...] <div> <div>OPT</div> <div>OPT</div> </div> 1 NAME 2 FILE 3 specification = NAME
\usebtxdefinitions [...*] * FILE
\usecolors [...*] * FILE
\usecomponent [...*] * FILE
\usedummycolorparameter {...*} * KEY
\usedummystyleandcolor {... ¹ } {... ² } 1 KEY 2 KEY
\usedummystyleparameter {...*} * KEY
\useenvironment [...*] * FILE
\useexternalrendering [... ¹] [... ²] [... ³] [... ⁴] 1 NAME 2 NAME 3 FILE 4 auto embed
\usefigurebase [...*] * reset FILE

<pre> \usefile [...] [...] [...] OPT 1 NAME 2 FILE 3 TEXT </pre>
<pre> \usegridparameter *... * CSNAME </pre>
<pre> \useindentingparameter *... * CSNAME </pre>
<pre> \useindentnextparameter *... * CSNAME </pre>
<pre> \useinterlinespaceparameter *... * CSNAME </pre>
<pre> \uselanguageparameter *... * CSNAME </pre>
<pre> \uselua module [...] * FILE </pre>
<pre> \useMPenvironmentbuffer [...] * NAME </pre>
<pre> \useMPgraphic {...} {..., ...²..., ...} OPT 1 NAME 2 KEY = VALUE </pre>
<pre> \useMPlibrary [...] * FILE </pre>
<pre> \useMPrun {...} {...} 1 NAME 2 NUMMER </pre>
<pre> \useMPvariables [...] [...] 1 NAME 2 KEY </pre>
<pre> \usemathstyleparameter *... * CSNAME </pre>
<pre> \useproduct [...] * FILE </pre>

<code>\useprofileparameter \...</code> * CSNAME
<code>\useproject [...]</code> * FILE
<code>\userreferenceparameter \...</code> * CSNAME
<code>\userpagenumber</code>
<code>\usesetupparameter \...</code> * CSNAME
<code>\usestaticMPfigure [...¹..._{OPT}...] [...²...]</code> 1 inherits: \setupscale 2 NAME
<code>\usesubpath [...*,...]</code> * PATH
<code>\usetexmodule [...¹..._{OPT}] [...²..._{OPT}] [...³..._{OPT}...]</code> 1 m p s x t 2 FILE 3 KEY = VALUE
<code>\usetypescript [...¹..._{OPT}] [...²..._{OPT}] [...³...]</code> 1 serif sans mono math handwriting calligraphy casual tot 2 NAME fallback implicit dtp simple 3 size nume
<code>\usetypescriptfile [...]</code> * reset FILE
<code>\usezipfile [...¹..._{OPT}] [...²...]</code> 1 FILE 2 FILE
<code>\utfchar {...}</code> * NUMMER
<code>\utflower {...}</code> * TEXT
<code>\utfupper {...}</code> * TEXT
<code>\utilityregisterlength</code>

<code>\VerboseNumber {...}</code> * NUMMER
<code>\valoareculoare {...}</code> * COLOR
<code>\vboxreference [...¹,...²] {...}</code> 1 REFERENCE 2 CONTENT
<code>\vec {...}</code> * CHARACTER
<code>\verbatim {...}</code> * CONTENT
<code>\verbatimstring {...}</code> * CONTENT
<code>\verbosenummer {...}</code> * NUMMER
<code>\versiune [...]</code> * concept fisier temporar final NAME
<code>\verticalgrowingbar [...[*]...]</code> * inherits: \setuppositionbar
<code>\verticalpositionbar [...[*]...]</code> * inherits: \setuppositionbar
<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> * DIMENSION
<code>\viewerlayer [...¹] {...²}</code> 1 NAME 2 CONTENT
<code>\vl [...]</code> ^{OPT} * NUMMER

<code>\vphantom {...}</code> * CONTENT
<code>\vpos {...} {...}</code> 1 NAME 2 CONTENT
<code>\vsmash {...}</code> * CONTENT
<code>\vsmashbox ...</code> * CSNAME NUMMER
<code>\vsmashed {...}</code> * CONTENT
<code>\vspace [...] [...]</code> <small>OPT OPT</small> 1 NAME 2 NAME
<code>\vspacing [...]*...]</code> <small>OPT</small> * preferinta aceeasipagina max fortat enable dezactivat faraalb inapot overlay totdeauna weak strong implicit inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb inaltime adancime standard NUMMER*mic NUMMER*mediu NUMMER*mare NUMMER*linie NUMMER*jumatatelinie NUMMER*quarterline NUMMER*formula NUMMER*alb NUMMER*inaltime NUMMER*adancime category:NUMMER order:NUMMER penalty:NUMMER DIMENSION NAME
<code>\WidthSpanningText {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\wdofstring {...}</code> * TEXT
<code>\widthhofstring {...}</code> * TEXT
<code>\widthspanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\withoutpt {...}</code> * DIMENSION
<code>\words {...}</code> * TEXT

$\backslash\text{wordtonumber}$ $\{.^1.\}$ $\{.^2.\}$ 1 unu doi trei patru cinci 2 TEXT
$\backslash\text{writedatatolist}$ $[.^1.]$ $[.^2.^3.^4.^5.^6.^7.^8.^9.^{10}.]$ $[.^3.^4.^5.^6.^7.^8.^9.^{10}.]$ 1 LISTE 2 inherits: \seteazalista 3 KEY = VALUE
$\backslash\text{writestatus}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{XETEX}$
$\backslash\text{XeTeX}$
$\backslash\text{xdefconvertedargument}$ $\backslash.^1.\{.^2.\}$ 1 CSNAME 2 TEXT
$\backslash\text{xequal}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{xfrac}$ $\{.^1.\}$ $\{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{xhookleftarrow}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{xhookrightarrow}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{xLeftarrow}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{xLeftrightarrow}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT
$\backslash\text{xleftarrow}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT 2 TEXT

$\backslash\mathrm{xleftharpoondown}$ $\{\dots\}^1 \{\dots\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xleftharpoonup}$ $\{\dots\}^1 \{\dots\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xleftrightharpoonup}$ $\{\dots\}^1 \{\dots\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xleftrightharpoons}$ $\{\dots\}^1 \{\dots\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xmapsto}$ $\{\dots\}^1 \{\dots\}^2$ <small>OPT OPT</small> 1 TEXT 2 TEXT
$\backslash\mathrm{xmlladdindex}$ $\{.\}^*$ * NODE
$\backslash\mathrm{xmllafterdocumentsetup}$ $\{\dots\}^1 \{\dots\}^2 \{\dots\}^3$ 1 NAME 2 SETUP 3 SETUP
$\backslash\mathrm{xmllaftersetup}$ $\{\dots\}^1 \{\dots\}^2$ 1 SETUP 2 SETUP
$\backslash\mathrm{xmllall}$ $\{\dots\}^1 \{\dots\}^2$ 1 NODE 2 LPATH
$\backslash\mathrm{xmllappenddocumentsetup}$ $\{\dots\}^1 \{\dots\}^2$ 1 NAME 2 SETUP
$\backslash\mathrm{xmllappendsetup}$ $\{.\}^*$ * SETUP
$\backslash\mathrm{xmllapplyselectors}$ $\{.\}^*$ * NODE

\xmlatt {...} {...}

- 1 NODE
- 2 NAME

\xmlattdef {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 TEXT

\xmlattribute {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME

\xmlattributedef {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 TEXT

\xmlbadinclusions {...}

- * NODE

\xmlbeforedocumentsetup {...} {...} {...}

- 1 NAME
- 2 SETUP
- 3 SETUP

\xmlbeforesetup {...} {...}

- 1 SETUP
- 2 SETUP

\xmlchainatt {...} {...}

- 1 NODE
- 2 NAME

\xmlchainattdef {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 TEXT

\xmlchecknamespace {...} {...}

- 1 NODE
- 2 NAME

`\xmlcommand {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 XMLSETUP

`\xmlconcat {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT
- 4 FIRST
- 5 LAST

`\xmlcontext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlcount {...}`

- * NODE

`\xmldefaulttotext {...}`

- * NODE

`\xmldirectives {...}`

- * NODE

`\xmldirectivesafter {...}`

- * NODE

`\xmldirectivesbefore {...}`

- * NODE

`\xmldisplayverbatim {...}`

- * NODE

`\xmldoif {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmldoifelse {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

\xmldoifelseempty {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

\xmldoifelseselfempty {...} {...} {...}

- 1 NODE
- 2 TRUE
- 3 FALSE

\xmldoifelsetext {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE
- 4 FALSE

\xmldoifelsevalue {...} {...} {...} {...}

- 1 CATEGORY
- 2 NAME
- 3 TRUE
- 4 FALSE

\xmldoifnot {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmldoifnotselfempty {...} {...}

- 1 NODE
- 2 TRUE

\xmldoifnottext {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 TRUE

\xmldoifselfempty {...} {...}

- 1 NODE
- 2 TRUE

<pre>\xmldoiftext {...} {...} {...}</pre> <pre>1 NODE</pre> <pre>2 LPATH</pre> <pre>3 TRUE</pre>
<pre>\xmlelement {...} {...}</pre> <pre>1 NODE</pre> <pre>2 NUMMER</pre>
<pre>\xmlfilter {...} {...}</pre> <pre>1 NODE</pre> <pre>2 LPATH</pre>
<pre>\xmlfirst {...} {...}</pre> <pre>1 NODE</pre> <pre>2 LPATH</pre>
<pre>\xmlflush {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushcontext {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushdocumentsetups {...} {...}</pre> <pre>1 NAME</pre> <pre>2 SETUP</pre>
<pre>\xmlflushlinewise {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushpure {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushspacewise {...}</pre> <pre>* NODE</pre>
<pre>\xmlflushtext {...}</pre> <pre>* NODE</pre>
<pre>\xmlinclude {...} {...} {...}</pre> <pre>1 NODE</pre> <pre>2 LPATH</pre> <pre>3 NAME</pre>
<pre>\xmlinclusion {...}</pre> <pre>* NODE</pre>

\xmlinclusions {...} * NODE
\xmlinfo {...} * NODE
\xmlinjector {...} * NAME
\xmlinlineverbatim {...} * NODE
\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP
\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP

\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE
\xmlnonspace {...} {...} 1 NODE 2 LPATH
\xmlpath {...} * NODE
\xmlpos {...} * NODE
\xmlposition {...} {...} {...} 1 NODE 2 LPATH 3 NUMMER
\xmlprependdocumentsetup {...} {...} 1 NAME 2 SETUP
\xmlprependsetup {...} * SETUP
\xmlprettyprint {...} {...} 1 NODE 2 NAME
\xmlprocessbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP

\xmlprocessdata {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 XMLSETUP

\xmlprocessfile {...} {...} {...}

- 1 NAME
- 2 FILE
- 3 XMLSETUP

\xmlpure {...} {...}

- 1 NODE
- 2 LPATH

\xmlraw {...}

- * NODE

\xmlrefatt {...} {...}

- 1 NODE
- 2 NAME

\xmlregisterddocumentsetups {...} {...}

- 1 NAME
- 2 SETUP

\xmlregisteredsetups

\xmlregisterns {...} {...}

- 1 NAME
- 2 URL

\xmlremapname {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

\xmlremapnamespace {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 NAME

\xmlremoveddocumentsetup {...} {...}

- 1 NAME
- 2 SETUP

<pre>\xmlremovesetup {...} * SETUP</pre>
<pre>\xmlresetdocumentsetups {...} * NAME</pre>
<pre>\xmlresetinjectors</pre>
<pre>\xmlresetsetups {...} * NAME</pre>
<pre>\xmlsave {...} {...} 1 NODE 2 FILE</pre>
<pre>\xmlsetentity {...} {...} 1 NAME 2 TEXT</pre>
<pre>\xmlsetfunction {...} {...} {...} 1 NODE 2 LPATH 3 LUAFUNCTION</pre>
<pre>\xmlsetinjectors [...,*,...] * NAME</pre>
<pre>\xmlsetsetup {...} {...} {...} 1 NAME 2 LPATH 3 SETUP</pre>
<pre>\xmlsetup {...} {...} 1 NODE 2 SETUP</pre>
<pre>\xmlshow {...} * NODE</pre>
<pre>\xmlsnippet {...} {...} 1 NODE 2 NUMMER</pre>
<pre>\xmlstrip {...} {...} 1 NODE 2 LPATH</pre>

<pre> \xmlstripnolines {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlstripped {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlstrippednolines {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmltag {...} * NODE </pre>
<pre> \xmltexentity {...} {...} 1 NAME 2 TEXT </pre>
<pre> \xmltext {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmltobuffer {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER </pre>
<pre> \xmltobufferverbose {...} {...} {...} 1 NODE 2 LPATH 3 BUFFER </pre>
<pre> \xmltofile {...} {...} {...} 1 NODE 2 LPATH 3 FILE </pre>
<pre> \xmlvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT </pre>
<pre> \xmlverbatim {...} * NODE </pre>

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 TEXT

2 CONTENT

\xypos {...}

* NAME

\ZIDINSAPTAMANA {...}

* NUMMER

\zidinsaptamana {...}

* NUMMER



PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com