



ConTExT

comenzile

RO

ConTeXt

comenzile

ro / română

17 ianuarie 2017

<code>\AfterPar {...}</code> * BEFEHL
<code>\Alphabeticnumerals {...}</code> * NUMMER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abjadnaivenumerals {...}</code> * NUMMER
<code>\abjadnodotnumerals {...}</code> * NUMMER
<code>\abjadnumerals {...}</code> * NUMMER
<code>\activatespacehandler {...}</code> * on dezactivat da fixat
<code>\acute {...}</code> * CHARACTER
<code>\adaptcollector [...]¹ [...,...²...,...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 NAME 2 inherits: \setupcollector
<code>\adapteazaaspect [...]¹,... [...,...²...,...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 NUMMER 2 inalttime = max DIMENSION linii = NUMMER
<code>\adaptfontfeature [...]¹ [...,...²...,...]</code> 1 NAME 2 inherits: \definefontfeature
<code>\adaptpapersize [...]¹,... [...,...²...,...]</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 inherits: \seteazadimensiunihartie 2 inherits: \seteazadimensiunihartie
<code>\addfeature [...]</code> * NAME

<p><code>\addfeature {...}</code></p> <p>* NAME</p>
<p><code>\addtocommalist {...} \^{2}...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\addtoJSreamble {...} {...}</code></p> <p>1 NAME</p> <p>2 CONTENT</p>
<p><code>\addvalue {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\adubuffer [...]</code> OPT</p> <p>* BUFFER</p>
<p><code>\getBUFFER</code></p>
<p><code>\adumarcaje [...] [...]_{OPT} [...]_{OPT}</code></p> <p>1 BESCHRIFTUNG</p> <p>2 pagina NAME</p> <p>3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck</p>
<p><code>\afiseazaaspect [...]*...]</code> OPT</p> <p>* pt bp cm mm dd cc pc nd nc sp in</p>
<p><code>\afiseazaculoare [...]</code></p> <p>* COLOR</p>
<p><code>\afiseazafonttext [...]*...]</code></p> <p>* inherits: \seteazafonttext</p>
<p><code>\afiseazagrid [...]*...]</code> OPT</p> <p>* reset subsol sus niciunul tot linii incadrat nonumber dreapta stanga extern coloane</p>
<p><code>\afiseazagrupculoare [...]₁ [...]₂...]</code> OPT</p> <p>1 NAME</p> <p>2 orizontal vertical numar valoare nume</p>
<p><code>\afiseazamakeup [...]</code> OPT</p> <p>* marcaj tot boxes glyph fontkern hbox vbox vtop kern glue penalty strut whatsit simple simplehbox simplevbox simplevtop user math italic origin reset</p>
<p><code>\afiseazamediufonttext [...]*...]</code></p> <p>* inherits: \seteazafonttext</p>

<p><code>\afiseazapaleta [...]¹ [...]²,...]</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 orizontal vertical numar valoare nume</p>
<p><code>\afiseazarama [...]¹,...]</code> <small>OPT</small> <code>² [...],...</code> <small>OPT</small></p> <p>1 sus antet text subsol subsol</p> <p>2 bordurastanga marginestanga text marginedreapta borduradreapta</p>
<p><code>\afiseazasetari [...][*],...]</code> <small>OPT</small></p> <p>* pt bp cm mm dd cc pc nd nc sp in</p>
<p><code>\afiseazasetsimboluri [...][*]]</code></p> <p>* NAME</p>
<p><code>\afiseazastruts</code></p>
<p><code>\afiseazatiparire [...]¹,...]</code> <small>OPT</small> <code>² [...],...</code> <small>OPT</small> <code>³ [...],...]</code> <small>OPT</small></p> <p>1 inherits: \seteazadimensiunihartie</p> <p>2 inherits: \seteazadimensiunihartie</p> <p>3 inherits: \seteazaaspect</p>
<p><code>\aftersplitstring ...¹ \at ...² \to ...³</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aftertestandsplitstring ...¹ \at ...² \to ...³</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\aldin</code></p>
<p><code>\aldininclinat</code></p>
<p><code>\aldinitalic</code></p>
<p><code>\alignbottom</code></p>
<p><code>\aligned [...]¹,...]</code> <code>{...²}</code></p> <p>1 stanga centru dreapta sus subsol linie l c r m t b g</p> <p>2 CONTENT</p>
<p><code>\alignedbox [...]¹,...]</code> <code>\...² {...³}</code></p> <p>1 stanga centru dreapta sus subsol linie l c r m t b g</p> <p>2 CSNAME</p> <p>3 CONTENT</p>

`\alignedline {1...} {2...} {3...}`

1 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge
spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta

2 stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin inneredge outeredge
spatiuspate cutspace marginestanga marginedreapta bordurastanga borduradreapta

3 CONTENT

`\alignmentcharacter`

`\aliniatcentru {...}`

* CONTENT

`\aliniatdreapta {...}`

* CONTENT

`\aliniatstanga {...}`

* CONTENT

`\allinputpaths`

`\alphabeticnumerals {...}`

* NUMMER

`\alwayscitation [...,1...OPT...]2 [...]`

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx

2 REFERENCE

`\alwayscitation [...]1 [...]OPT2`

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear

2 REFERENCE

`\alwayscitation [...,1...1...]2 [...,2...2...]`

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx

2 KEY = VALUE

`\alwayscite [...1...2] [...]`

OPT

- 1 `referinta` = `REFERENCE`
 `alternativ` = `implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum`
 `authoryear`
 `inainte` = `BEFEHL`
 `dupa` = `BEFEHL`
 `stanga` = `BEFEHL`
 `dreapta` = `BEFEHL`
 `inherits:` `\setupbtx`
- 2 `REFERENCE`

`\alwayscite [...1] [...2]`

OPT

- 1 `implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear`
- 2 `REFERENCE`

`\alwayscite [...1...2] [...2...2]`

- 1 `referinta` = `REFERENCE`
 `alternativ` = `implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum`
 `authoryear`
 `inainte` = `BEFEHL`
 `dupa` = `BEFEHL`
 `stanga` = `BEFEHL`
 `dreapta` = `BEFEHL`
 `inherits:` `\setupbtx`
- 2 `KEY = VALUE`

`\ampersand`

`\anchor [...1] [...2...2] [...3...3] {...4}`

OPT

OPT

- 1 `NAME`
- 2 `inherits:` `\setuplayer`
- 3 `inherits:` `\setuplayerinherits:` `\seteazainconjurat`
- 4 `CONTENT`

`\appendetoks ... \to \...2`

- 1 `BEFEHL`
- 2 `CSNAME`

`\appendgvalue {...1} {...2}`

- 1 `NAME`
- 2 `BEFEHL`

`\appendtocommalist {...1} \...2`

- 1 `TEXT`
- 2 `CSNAME`

`\appendtoks ... \to \...2`

- 1 `BEFEHL`
- 2 `CSNAME`

`\appendtoksonce ... \to \...2`

- 1 `BEFEHL`
- 2 `CSNAME`

\appendvalue {...} {...}

- 1 NAME
- 2 BEFEHL

\apply {...} {...}

- 1 CONTENT
- 2 CONTENT

\applyalternativestyle {...}

- * NAME

\applyprocessor {...} {...}

- 1 NAME
- 2 CONTENT

\applytocharacters \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytofirstcharacter \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringchar \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringcharspaced \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringline \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringlinespaced \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringword \¹... {...}

- 1 CSNAME
- 2 TEXT

\applytosplitstringwordspaced \¹... {...}

- 1 CSNAME
- 2 TEXT

<p><code>\applytowords \... {¹... {²...}}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\arabicdecimals {...}</code></p> <p>* NUMMER</p>
<p><code>\arabicexnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\arabicnumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\arg {...}</code></p> <p>* CONTENT</p>
<p><code>\asciistr {...}</code></p> <p>* CONTENT</p>
<p><code>\ascundeblocuri [...,¹...] [...,²...] <small>OPT</small></code></p> <p>1 NAME</p> <p>2 + -</p>
<p><code>\aside [¹...] {²...} <small>OPT</small></code></p> <p>1 SPRACHE</p> <p>2 CONTENT</p>
<p><code>\assignalfadimension {¹...} \... {²...} {³...} {⁴...} {⁵...}</code></p> <p>1 mic mediu mare niciunul DIMENSION</p> <p>2 CSNAME</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 DIMENSION</p>
<p><code>\assigndimen \... {¹... {²...}}</code></p> <p>1 CSNAME</p> <p>2 DIMENSION</p>
<p><code>\assigndimension {¹...} \... {²...} {³...} {⁴...} {⁵...}</code></p> <p>1 [-+]mic [-+]mediu [-+]mare niciunul DIMENSION</p> <p>2 CSNAME</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 DIMENSION</p>

<pre> \assignifempty \... {^2.} 1 CSNAME 2 BEFEHL </pre>
<pre> \assigntranslation [...,^1...,...] \to \... 1 SPRACHE = TEXT 2 CSNAME </pre>
<pre> \assignvalue {^1.} \... {^3.} {^4.} {^5.} 1 mic mediu mare TEXT 2 CSNAME 3 BEFEHL 4 BEFEHL 5 BEFEHL </pre>
<pre> \assignwidth {^1.} \... {^3.} {^4.} 1 ajustat broad DIMENSION 2 CSNAME 3 TEXT 4 DIMENSION </pre>
<pre> \assumelongusagecs \... {^2.} 1 CSNAME 2 CONTENT </pre>
<pre> \astype {...} * CONTENT </pre>
<pre> \attachment [...^1.] [...,^2...,...] OPT OPT 1 NAME 2 inherits: \setupattachment </pre>
<pre> \ATTACHMENT [...^1.] [...,^2...,...] OPT OPT 1 NAME 2 inherits: \setupattachment instances: attachment </pre>
<pre> \autocap {...} * TEXT </pre>
<pre> \autodirhbox ...^1. {...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \autodirvbox ...^1. {...} OPT 1 TEXT 2 CONTENT </pre>

$\backslash\autodirvtop$ $\overset{1}{\dots} \overset{2}{\{\dots\}}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\autoinsertnextspace$
$\backslash\automathematics \{...\}$ * CONTENT
$\backslash\autosetups \{...,...\}$ * NAME
$\backslash\autostarttext \dots \backslash\autostoptext$
$\backslash\availablehsize$
$\backslash\averagecharwidth$
$\backslash\BeforePar \{...\}$ * BEFEHL
$\backslash\Big \dots$ * CHARACTER
$\backslash\Bigg \dots$ * CHARACTER
$\backslash\Biggl \dots$ * CHARACTER
$\backslash\Biggm \dots$ * CHARACTER
$\backslash\Biggr \dots$ * CHARACTER
$\backslash\Bigl \dots$ * CHARACTER
$\backslash\Bigm \dots$ * CHARACTER
$\backslash\Bigr \dots$ * CHARACTER

<p><code>\backgroundimage {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 BEFEHL</p>
<p><code>\backgroundimagefill {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 BEFEHL</p>
<p><code>\backgroundline [...] {...}</code></p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p><code>\bar {...}</code></p> <p>* CHARACTER</p>
<p><code>\baraculoare [...;...]</code></p> <p>* COLOR</p>
<p><code>\barainteractiune [...]_{OPT} [...,...²...]_{OPT}</code></p> <p>1 NAME</p> <p>2 inherits: \seteazarainteractiune</p>
<p><code>\barasus {...}</code></p> <p>* CONTENT</p>
<p><code>\BAR {...}</code></p> <p>* CONTENT</p> <p>instances: barasus sublinie liniepeste understrike supralinie sublinii liniipeste understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar</p>
<p><code>\basegrid [...,...[*]...]_{OPT}</code></p> <p>* nx = NUMMER</p> <p> ny = NUMMER</p> <p> dx = NUMMER</p> <p> dy = NUMMER</p> <p> factor = NUMMER</p> <p> scala = NUMMER</p> <p> xstep = NUMMER</p> <p> ystep = NUMMER</p> <p> offset = DIMENSION</p> <p> xoffset = DIMENSION</p> <p> yoffset = DIMENSION</p> <p> aliniere = centru</p> <p> unitate = cm mm in pc pt bp</p> <p> stil = STYLE BEFEHL</p> <p> culoare = COLOR</p>
<p><code>\baselinebottom</code></p>

<code>\baselineleftbox {...}</code> * CONTENT
<code>\baselinemiddlebox {...}</code> * CONTENT
<code>\baselinerightbox {...}</code> * CONTENT
<code>\bbox {...}</code> * CONTENT
<code>\beforesplitstring ...¹ \at ...² \to ...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\beforetestandsplitstring ...¹ \at ...² \to ...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\beginBLOCK [...[*]...] ... \endBLOCK</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * + -
<code>\beginhbox ... \endhbox</code>
<code>\beginofshapebox ... \endofshapebox</code>
<code>\beginvbox ... \endvbox</code>
<code>\beginvtop ... \endvtop</code>
<code>\begstrut ... \endstrut</code>
<code>\bigbodyfont</code>
<code>\bigg ...</code> * CHARACTER
<code>\bigger</code>
<code>\biggl ...</code> * CHARACTER
<code>\biggm ...</code> * CHARACTER

<code>\biggr ...</code> * CHARACTER
<code>\bigl ...</code> * CHARACTER
<code>\bigm ...</code> * CHARACTER
<code>\bigr ...</code> * CHARACTER
<code>\bigskip</code>
<code>\binom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\bitmapimage [...,¹...,...] {...}</code> 1 culoare = rgb cmyk gri latime = DIMENSION inaltime = DIMENSION x = NUMMER y = NUMMER 2 NUMMER
<code>\blanc [...,^{OPT}...]</code> * inherits: \vspacing
<code>\blap {...}</code> * CONTENT
<code>\bleed [...,¹...,...] {...}</code> ^{OPT} 1 inherits: \setupbleeding 2 CONTENT
<code>\bleedheight</code>
<code>\bleedwidth</code>
<code>\blockquote [...,¹...] {...}</code> ^{OPT} 1 SPRACHE 2 CONTENT
<code>\bodyfontenvironmentlist</code>
<code>\bodyfontsize</code>
<code>\boldface</code>

<code>\booleanmodevalue {...}</code> * NAME
<code>\bottombox {...}</code> * CONTENT
<code>\bottomleftbox {...}</code> * CONTENT
<code>\bottomrightbox {...}</code> * CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...} {...}</code> 1 NAME 2 NUMMER
<code>\boxofsize \... ..²... .. {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 CSNAME 2 DIMENSION 3 CONTENT
<code>\boxreference [...,¹...] \...² {...³}</code> 1 REFERENCE 2 CSNAME 3 CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> * NAME
<code>\breve {...}</code> * CHARACTER
<code>\bTABLE [...,[*]...,...] ... \eTABLE</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * inherits: \setupTABLE
<code>\bTABLEbody [...,[*]...,...] ... \eTABLEbody</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * inherits: \setupTABLE
<code>\bTABLEfoot [...,[*]...,...] ... \eTABLEfoot</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * inherits: \setupTABLE
<code>\bTABLEhead [...,[*]...,...] ... \eTABLEhead</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * inherits: \setupTABLE

$\backslash\text{bTABLEnext} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTABLEnext}$ <small>OPT</small> * inherits: \setupTABLE
$\backslash\text{bTC} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTC}$ <small>OPT</small> * inherits: \bTD
$\backslash\text{bTD} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTD}$ <small>OPT</small> * nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER n = NUMBER m = NUMBER actiune = REFERENCE inherits: \setupTABLE
$\backslash\text{bTDs} [\dots] \dots \backslash\text{eTDs}$ * NAME
$\backslash\text{bTH} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTH}$ <small>OPT</small> * inherits: \bTD
$\backslash\text{bTN} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTN}$ <small>OPT</small> * inherits: \bTD
$\backslash\text{bTR} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTR}$ <small>OPT</small> * inherits: \setupTABLE
$\backslash\text{bTRs} [\dots] \dots \backslash\text{eTRs}$ * NAME
$\backslash\text{bTX} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTX}$ <small>OPT</small> * inherits: \bTD
$\backslash\text{bTY} [\dots\overset{*}{=}\dots] \dots \backslash\text{eTY}$ <small>OPT</small> * inherits: \setupTABLE
$\backslash\text{bthiddencitation} [\dots]$ * REFERENCE
$\backslash\text{btxabbreviatedjournal} \{\dots\}$ * NAME
$\backslash\text{btxaddjournal} [\dots^1] [\dots^2]$ 1 NAME 2 NAME

\btxalwayscitation [...¹...] [...²]
OPT

```
1  referinta  = REFERENCE
   alternativ  = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte    = BEFEHL
   dupa       = BEFEHL
   stanga     = BEFEHL
   dreapta    = BEFEHL
   inherits: \setupbtx
2  REFERENCE
```

\btxalwayscitation [...¹...] [...²]
OPT

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2  REFERENCE
```

\btxalwayscitation [...¹...] [...²...]

```
1  referinta  = REFERENCE
   alternativ  = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte    = BEFEHL
   dupa       = BEFEHL
   stanga     = BEFEHL
   dreapta    = BEFEHL
   inherits: \setupbtx
2  KEY = VALUE
```

\btxauthorfield {...}

* initials firstnames vons surnames juniors

\btxdetail {...}

* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
yearfiled NAME

\btxdirect {...}

* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
yearfiled NAME

\btxdoif {...} {...}

```
1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
2  TRUE
```

\btxdoifcombiinlistelse {...} {...} {...} {...}

```
1  NAME
2  NAME
3  TRUE
4  FALSE
```

\btxdoifelse {...} {...} {...}

```
1  address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language
   luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an
   yearfiled NAME
2  TRUE
3  FALSE
```

\btxdoifelsecombiinlist {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\btxdoifelsesameasprevious {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifelsesameaspreviouschecked {...} {...} {...} {...}

- 1 totdeauna douafete
- 2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifelseuservariable {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btxdoifnot {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE

\btxdoifsameaspreviouscheckedelse {...} {...} {...} {...}

- 1 totdeauna douafete
- 2 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 3 TRUE
- 4 FALSE

\btxdoifsameaspreviouselse {...} {...} {...}

- 1 address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
- 2 TRUE
- 3 FALSE

\btxdoifuservariableelse {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\btsexpandedjournal {...} * NAME
\btxfield {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxfieldname {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxfieldtype {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxfirstofrange {...} * volume pages
\btxflush {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME
\btxflushauthor [... ¹ ...] {... ² } <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 num normal normalshort inverted invertedshort 2 autor editor
\btxflushauthorinverted {...} * autor editor
\btxflushauthorinvertedshort {...} * autor editor
\btxflushauthorname {...} * autor editor
\btxflushauthornormal {...} * autor editor
\btxflushauthornormalshort {...} * autor editor
\btxflushsuffix
\btxfoundname {...} * address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME

`\btxfoundtype {...}`

* address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME

`\btxhybridcite [...1...] [...2]`
OPT

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
2 REFERENCE

`\btxhybridcite [...1...] [...2]`
OPT

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2 REFERENCE

`\btxhybridcite {...}`

* REFERENCE

`\btxhybridcite [...1...] [...2...]`

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
2 KEY = VALUE

`\btxlistcitation [...1...] [...2]`
OPT

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
2 REFERENCE

`\btxlistcitation [...1...] [...2]`
OPT

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2 REFERENCE

`\btxlistcitation [...1...] [...2...]`

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
2 KEY = VALUE

\btloadjournalist [...] * FILE
\btoneorrange {...} {...} {...} 1 volume pages 2 TRUE 3 FALSE
\btremapauthor [...] [...] 1 TEXT 2 TEXT
\btssavejournalist [...] * FILE
\btsetup {...} * NAME
\btsingularorplural {...} {...} {...} 1 editor producer director 2 TRUE 3 FALSE
\btsingularplural {...} {...} {...} 1 editor producer director 2 TRUE 3 FALSE
\bttextcitation [...,... ¹ ...,...] ^{OPT} [...] ² 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE
\bttextcitation [...] ¹ [...] ² ^{OPT} 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear 2 REFERENCE
\bttextcitation [...,... ¹ ...,...] ¹ [...,... ² ...,...] ² 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 KEY = VALUE

$\backslash\text{buildmathaccent} \{.^1.\} \{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextaccent} \{.^1.\} \{.^2.\}$ 1 CHARACTER 2 CHARACTER
$\backslash\text{buildtextbottomcomma} \{.*.\}$ * CHARACTER
$\backslash\text{buildtextbottomdot} \{.*.\}$ * CHARACTER
$\backslash\text{buildtextcedilla} \{.*.\}$ * CHARACTER
$\backslash\text{buildtextgrave} \{.*.\}$ * CHARACTER
$\backslash\text{buildtextmacron} \{.*.\}$ * CHARACTER
$\backslash\text{buildtextognek} \{.*.\}$ * CHARACTER
$\backslash\text{butoaneinteractiune} [.,.,.\overset{1}{=}.,.,.] [.,.,.\overset{2}{,}.,.,.]$ <small>OPT</small> 1 inherits: \seteazabarainteractiune 2 pagina subpagina REFERENCE
$\backslash\text{buton} [.,.,.\overset{1}{=}.,.,.] \{.^2.\} [.^3.]$ <small>OPT</small> 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{butonmeniu} [.,.,.\overset{1}{=}.,.,.] \{.^2.\} \{.^3.\}$ 1 inherits: \setupbutton 2 TEXT 3 REFERENCE
$\backslash\text{butonmeniu} [.^1.] [.,.,.\overset{2}{=}.,.,.] \{.^3.\} \{.^4.\}$ <small>OPT</small> 1 NAME 2 inherits: \seteazameniuinteractiune 3 TEXT 4 REFERENCE

\backslash <i>BUTTON</i> [..., ¹ ... _{OPT} ...] {...} [...] 1 inherits: \setupbutton 2 TEXT 3 REFERENCE instances: button
\backslash Caps {...} * TEXT
\backslash CONTEXT
\backslash ConTeXt
\backslash Context
\backslash ConvertConstantAfter \. ¹ ... {...} {...} 1 CSNAME 2 TEXT 3 TEXT
\backslash ConvertToConstant \. ¹ ... {...} {...} 1 CSNAME 2 TEXT 3 TEXT
\backslash CUVANT {...} * TEXT
\backslash CUVINTE {...} * TEXT
\backslash Cuvant {...} * TEXT
\backslash Cuvinte {...} * TEXT
\backslash caligrafic
\backslash camel {...} * TEXT
\backslash camp [...] _{OPT} [...] ² 1 NAME 2 TEXT
\backslash catcodetablename

$\backslash\text{cbox} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeraligned} \{...\}$ * CONTENT
$\backslash\text{centerbox} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeredbox} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centeredlastline}$
$\backslash\text{centerednextbox} \overset{1}{...} \{\overset{2}{...}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{centerline} \{...\}$ * CONTENT
$\backslash\text{centru} ...$ * CHARACTER
$\backslash\text{cfrac} [\overset{1}{...}] \{\overset{2}{...}\} \{\overset{3}{...}\}$ <small>OPT</small> 1 l c r ll lc lr cl cc cr rl rc rr 2 CONTENT 3 CONTENT
$\backslash\text{CHARACTERKERNING} [\overset{1}{...}] \{\overset{2}{...}\}$ <small>OPT</small> 1 NUMMER 2 TEXT
$\backslash\text{chardescription} \{...\}$ * NUMMER
$\backslash\text{charwidthlanguage}$
$\backslash\text{check} \{...\}$ * CHARACTER
$\backslash\text{checkcharacteralign} \{...\}$ * CONTENT

<pre>\checkedchar {...} {...}</pre> <pre>1 NUMMER</pre> <pre>2 CHARACTER</pre>
<pre>\checkedfiller {...}</pre> <pre>* sym simbol rigla latime spatiu NAME BEFEHL</pre>
<pre>\checkedstrippedcsname \...</pre> <pre>* CSNAME</pre>
<pre>\checkedstrippedcsname ...</pre> <pre>* TEXT</pre>
<pre>\checkinjector [...]</pre> <pre>* NAME</pre>
<pre>\checknextindentation [...]</pre> <pre>* da nu auto</pre>
<pre>\checknextinjector [...]</pre> <pre>* NAME</pre>
<pre>\checkpage [...]¹ [...,...²...]_{OPT}</pre> <pre>1 NAME</pre> <pre>2 inherits: \setuppagechecker</pre>
<pre>\checkparameters [...]</pre> <pre>* TEXT</pre>
<pre>\checkpreviousinjector [...]</pre> <pre>* NAME</pre>
<pre>\checksoundtrack {...}</pre> <pre>* NAME</pre>
<pre>\checktwopassdata {...}</pre> <pre>* NAME</pre>
<pre>\checkvariables [...]¹ [...,...²...]</pre> <pre>1 NAME</pre> <pre>2 set = BEFEHL</pre> <pre> reset = BEFEHL</pre> <pre> KEY = VALUE</pre>
<pre>\chem {...}¹ {...}² {...}³</pre> <pre>1 TEXT</pre> <pre>2 TEXT</pre> <pre>3 TEXT</pre>

<pre> \chemical [...]¹ [...]² [...]³ [...] OPT OPT 1 NAME 2 TEXT 3 TEXT </pre>
<pre> \chemicalbottext {...} * TEXT </pre>
<pre> \chemicalmidtext {...} * TEXT </pre>
<pre> \chemicalsymbol [...] * NAME </pre>
<pre> \chemicaltext {...} * TEXT </pre>
<pre> \chemicaltoptext {...} * TEXT </pre>
<pre> \chineseallnumerals {...} * NUMMER </pre>
<pre> \chinesecapnumerals {...} * NUMMER </pre>
<pre> \chinesenumerals {...} * NUMMER </pre>
<pre> \citat [...]¹ {...}² OPT 1 SPRACHE 2 CONTENT </pre>
<pre> \citation [...]¹ [...]² OPT 1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx 2 REFERENCE </pre>
<pre> \citation [...]¹ [...]² OPT 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear 2 REFERENCE </pre>
<pre> \citation {...} * REFERENCE </pre>

`\citation [...,\sup{1}...,...]` `[...,\sup{2}...,...]`

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx

2  KEY = VALUE
```

`\cite [...,\sup{1}...,...]` `[...]\sup{2}...`

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx

2  REFERENCE
```

`\cite [...]\sup{1}...` `[...]\sup{2}...`

```
1  implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear

2  REFERENCE
```

`\cite {...}`

* REFERENCE

`\cite [...,\sup{1}...,...]` `[...,\sup{2}...,...]`

```
1  referinta = REFERENCE
   alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
               authoryear
   inainte   = BEFEHL
   dupa      = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   inherits: \setupbtx

2  KEY = VALUE
```

`\clap {...}`

* CONTENT

`\classfont {...}\sup{1}...` `{...}\sup{2}...`

```
1  NAME
2  FONT
```

`\cldcommand {...}`

* BEFEHL

`\cldcontext {...}`

* BEFEHL

`\cldloadfile {...}`

* FILE

<p>\cldprocessfile {...}</p> <p>* FILE</p>
<p>\cleftarrow {...¹} {...²}</p> <p> OPT OPT</p> <p>1 TEXT</p> <p>2 TEXT</p>
<p>\clip [...¹...] {...²}</p> <p> OPT</p> <p>1 inherits: \seteazaclipping</p> <p>2 CONTENT</p>
<p>\cloneazacamp [...¹] [...²] [...³] [...⁴,...]</p> <p>1 NAME</p> <p>2 NAME</p> <p>3 NAME</p> <p>4 NAME</p>
<p>\collect {...}</p> <p>* CONTENT</p>
<p>\collectedtext [...¹...] [...²...] {...³} {...⁴}</p> <p> OPT OPT</p> <p>1 inherits: \setupcollector</p> <p>2 stil = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat</p> <p>3 TEXT</p> <p>4 CONTENT</p>
<p>\collectexpanded {...}</p> <p>* CONTENT</p>
<p>\coloana [...[*]...]</p> <p> OPT</p> <p>* inherits: \columnbreak</p>
<p>\colorcomponents {...}</p> <p>* COLOR</p>
<p>\colored [...¹...] {...²}</p> <p>1 inherits: \definesteculoare</p> <p>2 CONTENT</p>
<p>\colored [...¹] {...²}</p> <p>1 COLOR</p> <p>2 CONTENT</p>
<p>\coloronly [...¹] {...²}</p> <p>1 COLOR</p> <p>2 CONTENT</p>

<p><code>\columnbreak [...[*]...]</code> <small>OPT</small></p> <p>* da nu preferinta local fortat primul ultim NUMMER NAME</p>
<p><code>\combinepages [...¹] [...²...²...]</code> <small>OPT</small></p> <p>1 FILE</p> <p>2 alternativ = a b c orizontal vertical n = NUMBER nx = NUMBER ny = NUMBER start = NUMBER stop = NUMBER distanta = DIMENSION sus = BEFEHL jos = BEFEHL stanga = BEFEHL dreapta = BEFEHL inainte = BEFEHL dupa = BEFEHL intre = BEFEHL frame = on dezactivat fundal = primplan culoare NAME culoarefundal = COLOR</p>
<p><code>\comentariu [...¹] [...²...²...] {...³}</code> <small>OPT</small> <small>OPT</small></p> <p>1 TEXT</p> <p>2 inherits: \seteazacomentariu</p> <p>3 TEXT</p>
<p><code>\COMENTARIU [...¹] [...²...²...] {...³}</code> <small>OPT</small> <small>OPT</small></p> <p>1 TEXT</p> <p>2 inherits: \seteazacomentariu</p> <p>3 TEXT</p> <p>instances: comentariu</p>
<p><code>\commalistelement</code></p>
<p><code>\commalistsentence [...¹,...] [...²,...] [...²,...]</code> <small>OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\commalistsize</code></p>
<p><code>\comparagrupculoare [...]</code></p> <p>* NAME</p>
<p><code>\comparapaleta [...]</code></p> <p>* NAME</p>
<p><code>\comparedimension {...¹} {...²}</code></p> <p>1 DIMENSION</p> <p>2 DIMENSION</p>

$\backslash\text{comparedimensione}\text{pns } \{...\}^1 \{...\}^2$ 1 DIMENSION 2 DIMENSION
$\backslash\text{completeazanumarpagina}$
$\backslash\text{completebtxrendering } [...\]^{1}_{\text{OPT}} [...\]^{2}_{\text{OPT}}$ 1 NAME 2 inherits: \setupbtxrendering
$\backslash\text{complet}\text{COMBINEDLIST } [...\]^{*}_{\text{OPT}}$ * inherits: \seteazalista instances:
$\backslash\text{completelist } [...\] [...\]^{2}_{\text{OPT}}$ 1 LISTE 2 inherits: \seteazalista
$\backslash\text{completelistof}\text{FLOATS } [...\]^{*}_{\text{OPT}}$ * inherits: \seteazalista
$\backslash\text{completelistofpublications } [...\]^{1}_{\text{OPT}} [...\]^{2}_{\text{OPT}}$ 1 NAME 2 inherits: \setupbtxrendering
$\backslash\text{completelistofsorts } [...\] [...\]^{2}_{\text{OPT}}$ 1 SINGULAR 2 inherits: \seteazasortare
$\backslash\text{completelistof}\text{SORTS } [...\]^{*}_{\text{OPT}}$ * inherits: \seteazasortare instances:
$\backslash\text{completelistofsynonyms } [...\] [...\]^{2}_{\text{OPT}}$ 1 SINGULAR 2 inherits: \seteazasinonime
$\backslash\text{completelistof}\text{SYNONYMS } [...\]^{*}_{\text{OPT}}$ * inherits: \seteazasinonime instances:
$\backslash\text{completeregister } [...\] [...\]^{2}_{\text{OPT}}$ 1 NAME 2 inherits: \seteazaregistru

<code>\completREGISTER [...,..^{OPT}...,...]</code> <code>* inherits: \seteazaregistru</code> <code>instances:</code>
<code>\complexorsimple *..</code> <code>* CSNAME</code>
<code>\complexorsimpleempty *..</code> <code>* CSNAME</code>
<code>\complexorsimpleempty {...}</code> <code>* TEXT CSNAME</code>
<code>\complexorsimple {...}</code> <code>* TEXT CSNAME</code>
<code>\componenta [...]</code> <code>* FILE</code>
<code>\componenta ...</code> <code>* FILE</code>
<code>\composedcollector {...}</code> <code>* NAME</code>
<code>\composedlayer {...}</code> <code>* NAME</code>
<code>\compresult</code>
<code>\constantdimen *..</code> <code>* CSNAME</code>
<code>\constantdimenargument *..</code> <code>* CSNAME</code>
<code>\constantemptyargument *..</code> <code>* CSNAME</code>
<code>\constantnumber *..</code> <code>* CSNAME</code>
<code>\constantnumberargument *..</code> <code>* CSNAME</code>

$\backslash\text{contentreference}$ [... ¹ ,...] [... ² _{OPT} ,...] {... ³ } 1 REFERENCE 2 inherits: \setezainconjurat 3 CONTENT
$\backslash\text{continuednumber}$ {...} * NUMMER
$\backslash\text{continueifinputfile}$ {...} * FILE
$\backslash\text{convertargument}$... \to ... ² 1 TEXT 2 CSNAME
$\backslash\text{convertcommand}$ \... \to ... ² 1 CSNAME 2 CSNAME
$\backslash\text{convertedcounter}$ [... ¹] [... ² _{OPT} ,...] 1 NAME 2 inherits: \setupcounter
$\backslash\text{convertedddimen}$ {... ¹ } {... ² } 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc
$\backslash\text{convertedsubcounter}$ [... ¹] [... ² _{OPT}] [... ³ _{OPT} ,...] 1 NAME 2 NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot 3 inherits: \setupcounter
$\backslash\text{converttestenumar}$ {... ¹ } {... ² } 1 gol implicit niciunul luna month:mnem caracter Caractere caractere Caractere a A Numere cuvant words Cuvant Cuvinte n N numereromane Numereromane i I r R KR RK grec Grec g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmurkhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirlenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued NAME 2 NUMMER
$\backslash\text{convertmonth}$ {...} * NUMMER
$\backslash\text{convertvalue}$... \to ... ² 1 NAME 2 CSNAME
$\backslash\text{convertvboxtohbox}$

<p><code>\copiazacamp</code> [¹...] [²...]</p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\copyLABELtext</code> [¹...] [²..._{OPT}...]</p> <p>1 SPRACHE</p> <p>2 KEY = KEY</p> <p>instances:</p>
<p><code>\coppages</code> [¹...] [²..._{OPT}...] [³..._{OPT}...]</p> <p>1 FILE</p> <p>2 marcaje = on dezactivat offset = DIMENSION n = NUMMER</p> <p>3 inherits: \setupexternalfigure</p>
<p><code>\copyparameters</code> [¹...] [²...] [³...,...]</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 KEY</p>
<p><code>\copyposition</code> {¹...} {²...}</p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\corectezaspatialb</code> {.*...}</p> <p>* CONTENT</p>
<p><code>\countersubs</code> [¹...] [²..._{OPT}]</p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\counttoken</code> ¹... \in ²... \to \³...</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME</p>
<p><code>\counttokens</code> ¹... \to \²...</p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\cramped</code> {.*...}</p> <p>* CONTENT</p>
<p><code>\crampedclap</code> {.*...}</p> <p>* CONTENT</p>

$\backslash\text{crampedllap} \{...\}$ * CONTENT
$\backslash\text{crampedrlap} \{...\}$ * CONTENT
$\backslash\text{crightarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\text{crightoverleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ 1 TEXT 2 TEXT
$\backslash\text{ctop} \overset{1}{...} \overset{2}{\{...\}}$ 1 TEXT 2 CONTENT
$\backslash\text{ctxcommand} \{...\}$ * BEFEHL
$\backslash\text{ctxdirectcommand} \{...\}$ * BEFEHL
$\backslash\text{ctxdirectlua} \{...\}$ * BEFEHL
$\backslash\text{ctxfunction} \{...\}$ * NAME
$\backslash\text{CTXFUNCTIONDEFINITION}$
$\backslash\text{CTXFUNCTION}$
$\backslash\text{ctxlatecommand} \{...\}$ * BEFEHL
$\backslash\text{ctxlatelua} \{...\}$ * BEFEHL
$\backslash\text{ctxloadluafile} \{...\}$ * FILE
$\backslash\text{ctxlua} \{...\}$ * BEFEHL
$\backslash\text{ctxluabuffer} [\overset{*}{...}]$ * BUFFER

\ctxluacode {...} * BEFEHL
\ctxreport {...} * BEFEHL
\ctxsprint {...} * BEFEHL
\culoare [...] {...} 1 COLOR 2 CONTENT
\culoaregri [...] {...} 1 COLOR 2 CONTENT
\currentassignmentlistkey
\currentassignmentlistvalue
\currentbtxuservariable {...} * KEY
\currentcommalistitem
\currentcomponent
\currentenvironment
\currentfeaturetest
\currentinterface
\currentETICHETA [...] ¹ [...] ² {...} OPT OPT 1 REFERENCE 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber

\currentlistentryreferenceattribute {...} * numar text numarpagina tot
\currentlistentrytitle
\currentlistentrytitlrendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY
\currentresponses
\currenttime [...*,...] <div style="text-align: center; margin-left: 100px;">OPT</div> * h m TEXT
\currentvalue
\currentxtablecolumn
\currentxtablerow
\cuvant {...} * TEXT
\cuvantdreapta [... ¹]{... ² } <div style="text-align: center; margin-left: 100px;">OPT</div> 1 dreapta DIMENSION 2 CONTENT
\d {...} * CHARACTER

<p><code>\data [...,¹...,...] [...,²...,...]</code></p> <p style="text-align: center;">OPT OPT</p> <p>1 d = NUMMER m = NUMMER y = NUMMER</p> <p>2 inherits: \datacurenta</p>
<p><code>\datacurenta [...,*,...]</code></p> <p style="text-align: center;">OPT</p> <p>* an luna zi zisaptamana y yy Y m mm M d dd D w W spatiu _ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT referinta day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from</p>
<p><code>\datasetvariable {...} {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME NUMMER</p> <p>3 KEY realpage</p>
<p><code>\dayoftheweek {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 NUMMER</p>
<p><code>\dayspermonth {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p>
<p><code>\dbinom {...} {...}</code></p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p><code>\ddot {...}</code></p> <p>* CHARACTER</p>
<p><code>\decrement \...</code></p> <p>* CSNAME</p>
<p><code>\decrementcounter [...]¹ [...]²</code></p> <p style="text-align: center;">OPT</p> <p>1 NAME</p> <p>2 NUMMER</p>
<p><code>\decrementedcounter [...]</code></p> <p>* NAME</p>
<p><code>\decrementpagenumber</code></p>
<p><code>\decrementsubpagenumber</code></p>
<p><code>\decrementvalue {...}</code></p> <p>* NAME</p>

\decrement cd:parentheses-1 * CSNAME NUMMER
\defaultinterface
\defaultobjectpage
\defaultobjectreference
\defcatcodecommand \ ¹ ... \ ² ... {\ ³ ...} 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
\defconvertedargument \ ¹ ... {\ ² ...} 1 CSNAME 2 TEXT
\defconvertedcommand \ ¹ ... \ ² ... 1 CSNAME 2 CSNAME
\defconvertedvalue \ ¹ ... {\ ² ...} 1 CSNAME 2 NAME
\defineactivecharacter \ ¹ ... {\ ² ...} 1 CHARACTER 2 BEFEHL
\definealternativestyle [...,\ ¹ ...] [...,\ ² ...] [...,\ ³ ...] 1 NAME 2 BEFEHL 3 BEFEHL
\defineanchor [...,\ ¹ ...] [...,\ ² ...] [...,\ ³ ...,\ ³ ...] [...,\ ⁴ ...,\ ⁴ ...] <small>OPT OPT</small> 1 NAME 2 NAME 3 inherits: \setupplayer 4 inherits: \setupplayerinherits: \seteazainconjurat
\defineattachment [...,\ ¹ ...] [...,\ ² ...] [...,\ ³ ...,\ ³ ...] <small>OPT OPT</small> 1 NAME 2 NAME 3 inherits: \setupattachment

<pre> \defineattribute [...] [¹...][²...³...] OPT 1 NAME 2 local global public private </pre>
<pre> \definebackground [¹...][²...][³...⁴...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazafundal </pre>
<pre> \definebar [¹...][²...][³...⁴...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbar </pre>
<pre> \definebodyfontswitch [¹...][²...³...] 1 NAME 2 inherits: \seteazafonttext </pre>
<pre> \definebreakpoint [¹...][²...][³...⁴...] OPT 1 NAME 2 CHARACTER 3 type = 1 2 3 4 5 nstanga = NUMMER ndreapta = NUMMER stanga = BEFEHL mijloc = BEFEHL dreapta = BEFEHL range = da nu language = SPRACHE </pre>
<pre> \definebreakpoints [...] * NAME </pre>
<pre> \definebtx [¹...][²...][³...⁴...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtx </pre>
<pre> \definebtxdataset [¹...][²...][³...⁴...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxdataset </pre>
<pre> \definebtxregister [¹...][²...][³...⁴...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupbtxregister </pre>

`\definebtxrendering [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupbtxrendering

`\definebutton [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupbutton

`\definecapitals [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setezamazajuscule

`\definecharacterkerning [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupcharacterkerning

`\definecharacterspacing [...]`

* NAME

`\definechemical [...]1 {...}2`

1 NAME

2 CONTENT

`\definechemicals [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupchemical

`\definechemicalsymbol [...]1 [...]2`

1 NAME

2 TEXT

`\definecollector [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupcollector

`\definecolumnbreak [...]1 [...]2,...`

1 NAME

2 da nu preferinta local fortat primul ultim NUMMER

```
\definecombination [...]1 [...]2 [...,...]3...OPT...OPT

1 NAME
2 NAME
3 inherits: \setupcombination
```

```
\definecomment [...]1 [...]2 [...,...]3...OPT...OPT

1 NAME
2 NAME
3 inherits: \seteazacomentariu
```

```
\definecomplexorsimple \...

* CSNAME
```

```
\definecomplexorsimpleempty \...

* CSNAME
```

```
\definecomplexorsimpleempty {...}

* TEXT CSNAME
```

```
\definecomplexorsimple {...}

* TEXT CSNAME
```

```
\defineconversionset [...]1 [...,2...] [...]3OPT

1 NAME SECTIONBLOCK:NAME
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\definecounter [...]1 [...]2 [...,...]3...OPT...OPT

1 NAME
2 NAME
3 inherits: \setupcounter
```

```
\definedataset [...]1 [...]2 [...,...]3...OPT...OPT

1 NAME
2 NAME
3 inherits: \setupdataset
```

```
\definedelimitedtext [...]1 [...]2 [...,...]3...OPT...OPT

1 NAME
2 NAME
3 inherits: \setupdelimitedtext
```

```
\definedfont [...]OPT

* FONT
```

```
\defineeffect [...] [1...] [2...] [3...OPT...OPT]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupeffect

```
\defineexpandable [1...] [2...] \{3...\}
```

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

```
\defineexternalfigure [1...] [2...] [3...OPT...OPT]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupexternalfigure

```
\definefallbackfamily [1...] [2...] [3...] [4...OPT...]
```

- 1 NAME
- 2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica manual caligrafic math
- 3 FONT
- 4

rscale	=	NUMMER
designsize	=	implicit auto
goodies	=	FILE
range	=	NUMMER NAME
offset	=	NUMMER NAME
check	=	da nu
fortat	=	da nu
features	=	NAME
tf	=	TEXT
bf	=	TEXT
it	=	TEXT
sl	=	TEXT
bi	=	TEXT
bs	=	TEXT
sc	=	TEXT

```
\definefallbackfamily [1...] [2...] [3...] [4...OPT...]
```

- 1 NAME
- 2 rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismatematica manual caligrafic math
- 3 FONT
- 4 NAME

```
\definefieldbody [1...] [2...] [3...OPT...OPT]
```

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldbody

```
\definefieldbodyset [1...] [2...]
```

- 1 NAME
- 2 NAME

`\definefieldcategory [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfieldcategory

`\definefileconstant {...}1 {...}2`

- 1 NAME
- 2 NAME

`\definefilefallback [...]1 [...,2...]`

- 1 NAME
- 2 FILE

`\definefilesynonym [...]1 [...]2`

- 1 NAME
- 2 FILE

`\definefiller [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfiller

`\definefirstline [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfirstline

`\definefittingpage [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupfittingpage

`\definefontalternative [...]*`

- * NAME

`\definefontfallback [...]1 [...]2 [...,3...] [...,...4...,...]`
OPT

- 1 NAME
- 2 FONT NAME
- 3 NAME NUMMER
- 4 rscale = NUMMER
fortat = da nu
check = da nu
offset = NUMMER NAME

`\definefontfamily` [¹...] [²...] [³...] [⁴..._{OPT}...]

```
1  NAME

2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismanual caligrafic math
   matematica

3  FONT

4  rscale      =  NUMMER
   designsizes =  implicit auto
   goodies     =  FILE
   features    =  NAME
   tf          =  TEXT
   bf          =  TEXT
   it          =  TEXT
   sl          =  TEXT
   bi          =  TEXT
   bs          =  TEXT
   sc          =  TEXT
```

`\definefontfamilypreset` [¹...] [²...]

```
1  NAME

2  inherits: \definefontfamily
```

`\definefontfamilypreset` [¹...] [²...]

```
1  NAME

2  NAME
```

`\definefontfamily` [¹...] [²...] [³...] [⁴..._{OPT}...]

```
1  NAME

2  rm ss tt mm hw cg roman serif regular sansserif sans suport teletype type mono scrismanual caligrafic math
   matematica

3  FONT

4  NAME
```

```
\definefontfeature [...]1 [...]2 [...,...3...,...]
```

OPT

1 NAME

2 NAME

3 language = NAME
script = NAME auto
mode = node base auto niciunul
liga = da nu
kern = da nu
extrakerns = da nu
tlig = da nu
trep = da nu
missing = da nu
dummies = da nu
analyze = da nu
unicoding = da nu
expansiune = NAME
protrusion = NAME
nostackmath = da nu
realdimensions = da nu
itlc = da nu
textitalics = da nu
mathitalics = da nu
slant = NUMMER
extend = NUMMER
dimensions = NUMMER
boundingbox = da nu
compose = da nu
char-ligatures = da nu
compat-ligatures = da nu
goodies = FILE
extrafeatures = da nu
featureset = NAME
colorscheme = NAME
postprocessor = NAME
mathdimensions = NAME
keepligatures = da nu auto
devanagari = da nu
features = da nu
tcom = da nu
anum = da nu
mathsize = da nu
decomposehangul = da nu
mathalternatives = da nu
mathgaps = da nu
checkmarks = da nu
NAME = da nu
mathnolimitsmode = NUMMER

```
\definefontfile [...]1 [...]2 [...,...3...,...]
```

OPT

1 NAME

2 FILE

3 features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicit

```
\definefontsize [...]
```

* NAME

```
\definefontsolution [...]1 [...]2 [...,...3...,...]
```

OPT

OPT

1 NAME

2 NAME

3 inherits: \setupfontsolution

`\defineformula` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformula

`\defineformulaalternative` [¹...] [²...] [³...]

- 1 NAME
- 2 CSNAME
- 3 CSNAME

`\defineformulaframed` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupformulaframed

`\defineframedcontent` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupframedcontent

`\definefrozenfont` [¹...] [²...]

- 1 NAME
- 2 FONT

`\defineglobalcolor` [¹...] [²...₂...]

- 1 NAME
- 2 inherits: \definesteculoare

`\defineglobalcolor` [¹...] [²...]

- 1 NAME
- 2 COLOR

`\definegraphictypesynonym` [¹...] [²...]

- 1 NAME
- 2 NAME

`\definegridsnapping` [¹...] [²...,...]

- 1 NAME
- 2 local global noheight nodepth box max min niciunul linie jumatatelinie primul ultim inaltimeminima maxheight mindepth maxdepth sus subsol strut NUMMER minheight:NUMMER maxheight:NUMMER mindepth:NUMMER maxdepth:NUMMER box:NUMMER top:NUMMER bottom:NUMMER offset:NUMMER

`\defineheadalternative` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupheadalternative

`\definehelp [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphelp

`\definehigh [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphigh

`\definehighlight [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuphighlight

`\definehspace [...]1 [...]2 [...]3`
OPT

- 1 NAME
- 2 NAME
- 3 DIMENSION

`\definehyphenationfeatures [...]1 [...,...2...,...]`

- 1 NAME
- 2 characters = TEXT
hyphens = da tot TEXT
joiners = da tot TEXT
rightwords = NUMMER
hyphenmin = NUMMER
lefthyphenmin = NUMMER
righthyphenmin = NUMMER
lefthyphenchar = NUMMER
righthyphenchar = NUMMER
alternativ = original tex hyphenate expanded traditional niciunul
borduradreapta = tex
rightchars = cuvant NUMMER

`\defineindentedtext [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupindentedtext

`\defineindenting [...]1 [...,...2...,...]`

- 1 NAME
- 2 [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle
DIMENSION

`\defineinitial [...]1 [...]2 [...,...3...,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupinitial

\defineinsertion [¹...] [²...] [³...,...³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupinsertion

\defineinteraction [¹...] [²...] [³...,...³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazainteractiunea

\defineinteractionbar [¹...] [²...] [³...,...³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazabarainteractiune

\defineinterfaceconstant {¹...} {²...}

- 1 NAME
- 2 NAME

\defineinterfaceelement {¹...} {²...}

- 1 NAME
- 2 NAME

\defineinterfacevariable {¹...} {²...}

- 1 NAME
- 2 NAME

\defineinterlinespace [¹...] [²...] [³...,...³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazaspatiuinterliniar

\defineintermediatecolor [¹...] [²...,...]³ [³...,...³...,...]
OPT

- 1 NAME
- 2 COLOR NUMMER
- 3 a = NUMMER
t = NUMMER

\defineitemgroup [¹...] [²...] [³...,...³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setupitemgroup

\defineitems [¹...] [²...] [³...,...³...,...]
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazaelemente

```
\definelabelclass [...]1 [...]2  
                                OPT
```

- 1 NAME
- 2 NUMMER

```
\definelayer [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuplayer

```
\definelayerpreset [...]1 [...,...2...,...]
```

- 1 NAME
- 2 inherits: \setuplayer

```
\definelayerpreset [...]1 [...]2
```

- 1 NAME
- 2 NAME

```
\definelayout [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \seteazaaspect

```
\definelinefiller [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinefiller

```
\definelinenote [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuplinenote

```
\definelinenumbering [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \seteazanumerotarelinii

```
\definelines [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \seteazalinii

```
\definelistalternative [...]1 [...]2 [...,...3...,...]  
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistalternative

`\definelistextra` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplistextra

`\definelow` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplow

`\definelowhigh` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowhigh

`\definelowmidhigh` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setuplowmidhigh

`\defineMPinstance` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupMPinstance

`\definemarginblock` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmarginblock

`\definemargindata` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmargindata

`\definemarker` [...]

- * NAME

`\definemathaccent` ...¹ ...²

- 1 NAME
- 2 CHARACTER

`\definemathalignment` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathalignment

`\definemathcases` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathcases

`\definemathcommand` [¹...] [²...] [³...] {⁴...}

- 1 NAME
- 2 ord op bin rel open close punct alpha intern nothing limop nolong box
- 3 unu doi
- 4 BEFEHL \...##1 \...##1##2

`\definemathdoubleextensible` [¹...] [²...] [³...] [⁴...]

- 1 ambele vfenced
- 2 NAME
- 3 NUMMER
- 4 NUMMER

`\definematematics` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathematics

`\definemathextensible` [¹...] [²...] [³...]

- 1 reverse matematica text chemistry
- 2 NAME
- 3 NUMMER

`\definemathfence` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathfence

`\definemathfraction` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathfraction

`\definemathframed` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathframed

`\definemathmatrix` [¹...] [²...] [³..._{OPT}..._{OPT}...]

- 1 NAME
- 2 NAME
- 3 inherits: \setupmathmatrix

```

\definemathornament [...] [...] [...]
                                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathornament

```

```

\definemathoverextensible [...] [...] [...]
                                OPT
1  sus vfenced
2  NAME
3  NUMMER

```

```

\definemathovertextextensible [...] [...] [...]
                                OPT
1  bothtext
2  NAME
3  NUMMER

```

```

\definemathradical [...] [...] [...]
                                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathradical

```

```

\definemathstackers [...] [...] [...]
                                OPT      OPT
1  NAME
2  NAME
3  inherits: \setupmathstackers

```

```

\definemathstyle [...] [...]
1  NAME
2  display text script scriptscript cramped uncramped normal impachetat mic mare

```

```

\definemathtriplet [...] [...] [...]
                    OPT      OPT
1  NAME
2  NAME
3  TEXT

```

```

\definemathunderextensible [...] [...] [...]
                                OPT
1  subsol vfenced
2  NAME
3  NUMMER

```

```

\definemathundertextextensible [...] [...] [...]
                                OPT
1  bothtext
2  NAME
3  NUMMER

```

<pre> \definemathunstacked [¹...] [²...] [³...] OPT 1 larg 2 NAME 3 NUMMER </pre>
<pre> \definemeasure [¹...] [²...] 1 NAME 2 DIMENSION </pre>
<pre> \definemessageconstant {.*} * NAME </pre>
<pre> \definemixedcolumns [¹...] [²...] [³...,...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupmixedcolumns </pre>
<pre> \definemode [...,¹...] [²...] OPT 1 NAME 2 da nu mentine </pre>
<pre> \definemultitonecolor [¹...] [...,²...,...] [...,³...,...] [...,⁴...,...] OPT 1 NAME 2 COLOR = NUMMER 3 inherits: \definesteculoare 4 inherits: \definespotcolor </pre>
<pre> \definenamecolor [¹...] [...,²...,...] 1 NAME 2 inherits: \definesteculoare </pre>
<pre> \definenamecolor [¹...] [²...] 1 NAME 2 COLOR </pre>
<pre> \definenamespace [¹...] [...,²...,...] 1 NAME 2 nume = TEXT parent = TEXT stil = da nu comanda = da nu lista setup = da nu lista set = da nu lista frame = da nu </pre>
<pre> \definennarrower [¹...] [²...] [³...,...,...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazaingust </pre>

```
1  NAME
2  NAME
3  inherits: \setupnote
```

```

1  NAME
2  alternativ = a b
   inherits: \setupcollector
3  stil      = STYLE BEFEHL
   culoare   = COLOR
   inherits: \seteazainconjurat

```

```
1  NAME
2  alternativ = a b
   inherits: \setupplayer
3  inherits: \setupplayeredtext
```

```
1  NAME
2  NAME
3  inherits: \setupoutputroutine
```

* KEY

1	NAME
2	REFERENCE

1	NAME
2	gol antet subsol dummy incadrat NUMMER +NUMBER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadrupul ultim ultimapagina start stop

```
1  NAME
2  NAME
3  inherits: \setuptoolspagechecker
```

```
1  NAME
2  NAME
3  inherits: \setuptoolspagegrid
```

```
1  NAME
2  NAME
3  inherits: \setuppagegridarea
```


`\definepagegridspan [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppagegridspan

`\definepageinjection [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppageinjection

`\definepageinjectionalternative [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppageinjectionalternative

`\definepageshift [...]1 [...]2 [...,3...]`

1 NAME

2 orizontal vertical

3 DIMENSION

`\definepagestate [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppagestate

`\definepairedbox [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuppairedbox

`\defineparagraph [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupparagraph

`\defineparallel [...]1 [...,2...]`

1 NAME

2 NAME

`\defineparbuilder [...]`

* NAME

`\defineplacement [...]1 [...]2 [...,...3...,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupplacement

```
1  NAME
2  NAME
3  inherits: \setarepozitie
```

```

1  NAME SECTIONBLOCK:NAME
2  ABSCHNITT
3  ABSCHNITT

```

```
1  NAME
2  COLOR
3  inherits: \definesteculoare
```

```
1  NAME
2  NAME
3  inherits: \setupprocessor
```

```
1  NAME
2  inherits: \setupfieldcontentframed
```

```
1  NAME
2  n r d
```

```
1  NAME
2  NAME
3  inherits: \setuprenderingwindow
```

```

1  NAME SECTIONBLOCK:NAME
2  NUMBER
3  NUMBER

```

```
1  NAME
2  NAME
3  inherits: \setupscale
```

```
1  NAME
2  NAME
3  inherits: \setupscript
```

`\definesectionlevels [...]1 [...,2...]`

- 1 NAME
- 2 ABSCHNITT

`\defineselector [...]1 [...,2...OPT...]`

- 1 NAME
- 2 inherits: \setupselector

`\defineseparatorset [...]1 [...,2...]OPT [...]3`

- 1 NAME SECTIONBLOCK:NAME
- 2 BEFEHL PROCESSOR->BEFEHL
- 3 BEFEHL PROCESSOR->BEFEHL

`\defineshift [...]1 [...]2OPT [...,3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupshift

`\definesidebar [...]1 [...]2OPT [...,3...OPT...]`

- 1 NAME
- 2 NAME
- 3 inherits: \setupsidebar

`\definesort [...]1 [...]2 [...]3 {...}4OPT`

- 1 da nu
- 2 SINGULAR
- 3 NAME
- 4 CONTENT

`\definespotcolor [...]1 [...]2 [...,3...3...]`

- 1 NAME
- 2 COLOR
- 3 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
difference exclusion hue saturation culoare luminosity
t = NUMMER
e = TEXT
p = NUMMER

`\defineste [...]1 [...]2OPT {...}3`

- 1 NUMMER
- 2 CSNAME
- 3 CONTENT

`\definesteaccent ...1 ...2 ...3`

- 1 CHARACTER
- 2 CHARACTER
- 3 CHARACTER

```
\definesteanetet [...] [...] [...] [...] [...]
                                OPT      OPT
```

- 1 NAME
- 2 ABSCHNITT
- 3 inherits: \seteazatitlu

```
\definestebloc [...] [...] [...] [...] [...]
                                OPT      OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \seteazabloc

```
\definesteblocsectione [...] [...] [...] [...] [...]
                                OPT
```

- 1 NAME
- 2 NAME
- 3 inherits: \seteazablocsectione

```
\definestebuffer [...] [...] [...] [...] [...]
                                OPT      OPT
```

- 1 NAME
- 2 BUFFER
- 3 inherits: \seteazabuffer

```
\definestecamp [...] [...] [...] [...] [...] [...]
                                OPT      OPT
```

- 1 NAME
- 2 radio sub text linie push check signature
- 3 NAME
- 4 NAME
- 5 NAME

```
\definestecaracter ... ...
```

- 1 CHARACTER
- 2 NUMMER

```
\definestecomanda ... ...
```

- 1 CHARACTER
- 2 BEFEHL

```
\definesteconversie [...] [...] [...]
                                OPT
```

- 1 SPRACHE
- 2 NAME
- 3 CSNAME

```
\definesteconversie [...] [...] [...]
                                OPT
```

- 1 SPRACHE
- 2 NAME
- 3 TEXT

`\definesteculoare [1...] [2...,...]`

```
1  NAME
2  r  = NUMBER
   g  = NUMBER
   b  = NUMBER
   c  = NUMBER
   m  = NUMBER
   y  = NUMBER
   k  = NUMBER
   h  = NUMBER
   s  = NUMBER
   v  = NUMBER
   x  = NUMBER
   a  = NUMBER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
       difference exclusion hue saturation culoare luminosity
   t  = NUMBER
```

`\definesteculoare [1...] [2...]`

```
1  NAME
2  COLOR
```

`\definestedescriere [1...] [2...] [3...,...3...,...]`
OPT OPT

```
1  NAME
2  NAME
3  inherits: \setupdescription
```

`\definestedimensiunehartie [1...] [2...,...]`

```
1  NAME
2  latime    = DIMENSION
   inaltime  = DIMENSION
   sus       = BEFEHL
   jos       = BEFEHL
   stanga    = BEFEHL
   dreapta   = BEFEHL
   distanta  = DIMENSION
   pagina    = inherits: \seteazadimensiunihartie
   hartie    = inherits: \seteazadimensiunihartie
```

`\definestedimensiunehartie [1...] [2...,...]3 [3...,...]`
OPT

```
1  NAME
2  inherits: \seteazadimensiunihartie
3  inherits: \seteazadimensiunihartie
```

`\definesteenumerare [1...] [2...] [3...,...3...,...]`
OPT OPT

```
1  NAME
2  NAME
3  inherits: \setupenumeration
```

`\definesteeticheta [1...] [2...] [3...,...3...,...]`
OPT OPT

```
1  NAME
2  NAME
3  inherits: \setuplabel
```

```
\definestefloat [...]1 [...]2 [...,...3...]3
                        OPT      OPT

1  SINGULAR
2  PLURAL
3  inherits: \seteazafloat

instances: chemical figure table intermezzo graphic
```

```
\definestefloat [...]1 [...]2 [...]3
                        OPT      OPT

1  SINGULAR
2  PLURAL
3  SINGULAR

instances: chemical figure table intermezzo graphic
```

```
\definestefont [...]1 [...]2 [...,...3...]3
                                   OPT

1  NAME
2  FONT
3  inherits: \seteazaspatiuinterliniar
```

```
\definestefonttext [...]1,... [...]2,... [...]3,... [...]4,...]4
                        OPT      OPT

1  NAME implicit
2  NAME DIMENSION
3  rm ss tt hw cg

4  tf    = FILE
    bf    = FILE
    it    = FILE
    sl    = FILE
    bi    = FILE
    bs    = FILE
    sc    = FILE
    mr    = FILE
    mrlr  = FILE
    mrrl  = FILE
    mb    = FILE
    mblr  = FILE
    mbrl  = FILE
```

```
\definestefonttext [...]1,... [...]2,... [...]3,... [...]4
                        OPT      OPT

1  NAME implicit
2  NAME DIMENSION
3  rm ss tt hw cg
4  NAME
```

```
\definestefont [...]1 [...]2 [...]3
                        OPT

1  NAME
2  FONT
3  NAME
```

```
\definesteformatreferinte [...]1 [...]2 [...,...3...]3
                                   OPT      OPT

1  NAME
2  NAME
3  inherits: \setupreferenceformat
```

`\definestegrupculori [...]1 [...]2 [x:y:z,...]3`
OPT

- 1 NAME
- 2 gri rgb cmyk spot
- 3 TRIPLET

`\definestehbox [...]1 [...]2`

- 1 NAME
- 2 DIMENSION

`\definesteinconjurare [...]1 [...]2 [...,...]3,,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazainconjurat

`\definestelista [...]1 [...]2 [...,...]3,,...]`
OPT OPT

- 1 NAME
- 2 LISTE
- 3 inherits: \seteazalista

`\definestelistacombinata [...]1 [...,2,...] [...,...]3,,...]`
OPT

- 1 NAME
- 2 LISTE
- 3 inherits: \seteazalista

`\definestemakeup [...]1 [...]2 [...,...]3,,...]`
OPT OPT

- 1 NAME
- 2 NAME
- 3 inherits: \seteazamakeup

`\definestemarcaje [...]1 [...]2 [...,...]3,,...]`
OPT OPT

- 1 NAME
- 2 BESCHRIFTUNG
- 3 inherits: \seteazamarcaje

`\definestemediulfonttext [...]1 [...]2 [...,...]3,,...]`
OPT OPT

- 1 NAME
- 2 implicit DIMENSION
- 3

mare	=	DIMENSION NUMMER
mic	=	DIMENSION NUMMER
a	=	DIMENSION NUMMER
b	=	DIMENSION NUMMER
c	=	DIMENSION NUMMER
d	=	DIMENSION NUMMER
text	=	DIMENSION NUMMER
x	=	DIMENSION NUMMER
xx	=	DIMENSION NUMMER
script	=	DIMENSION NUMMER
scriptscript	=	DIMENSION NUMMER
spatiereinterliniara	=	DIMENSION
em	=	inclinat italic STYLE BEFEHL
*	=	NUMMER

<pre> \definestemeniuiinteractiune [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazameniuiinteractiune </pre>
<pre> \definesteoverlay [...] [...] [...] OPT 1 NAME 2 NAME 3 BEFEHL </pre>
<pre> \definestepaleta [...] [...] [...] 1 NAME 2 NAME = COLOR </pre>
<pre> \definestepaleta [...] [...] 1 NAME 2 NAME </pre>
<pre> \definesteparagraf [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazaparagrafe </pre>
<pre> \definesteprofil [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \setupprofile </pre>
<pre> \definesteprogram [...] [...] [...] OPT 1 NAME 2 TEXT 3 TEXT </pre>
<pre> \definestereferinte [...] [...] [...] 1 NAME 2 REFERENCE </pre>
<pre> \definesteregistru [...] [...] [...] [...] OPT OPT 1 NAME 2 NAME 3 inherits: \seteazaregistru </pre>
<pre> \definestesablontabel [...] [...] [...] [...] OPT OPT 1 NAME 2 TEMPLATE 3 NAME 4 NAME </pre>

<pre> \definestesectione [...]</pre> <p>* NAME</p>
<pre> \definestesimbol [¹...] [²...] [³...] OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 BEFEHL</p>
<pre> \definestesimbolfigura [¹...] [²...] [³...,...³...,...] OPT</pre> <p>1 NAME</p> <p>2 FILE NAME</p> <p>3 inherits: \figuraexterna</p>
<pre> \definestesinonim [¹...] [²...] [³...] [⁴...] OPT OPT</pre> <p>1 SINGULAR</p> <p>2 PLURAL</p> <p>3 CSNAME</p> <p>4 CSNAME</p>
<pre> \definestesinonimfont [¹...] [²...] [³...,...³...,...] OPT</pre> <p>1 NAME</p> <p>2 FONT</p> <p>3 features = NAME fallbacks = NAME goodies = NAME designsize = auto implicit</p>
<pre> \definestesortare [¹...] [²...] [³...] OPT</pre> <p>1 SINGULAR</p> <p>2 PLURAL</p> <p>3 niciunul CSNAME</p>
<pre> \definestestartstop [¹...] [²...] [³...,...³...,...] OPT OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupstartstop</p>
<pre> \definestestil [¹...] [²...] [³...,...³...,...] OPT OPT</pre> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupstyle</p>
<pre> \definestestilfont [...,¹...] [²...]</pre> <p>1 NAME</p> <p>2 NAME</p>

`\definestestivacampuri [...1] [...2,...] [...3,...]
OPT`

1 NAME

2 NAME

3 inherits: \setupfieldcategory

`\definestesubcamp [...1] [...2] [...3,...]`

1 NAME

2 NAME

3 NAME

`\definestetabulatori [...1] [...2] [...3/]
OPT OPT`

1 NAME

2 NAME

3 TEMPLATE

`\definestetext [...1] [...2] [...3] [...4] [...5] [...6] [...7]
OPT OPT OPT OPT`

1 NAME

2 sus antet text subsol subsol

3 text margine bordura

4 data numarpagina BESCHRIFTUNG TEXT BEFEHL

5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

6 data numarpagina BESCHRIFTUNG TEXT BEFEHL

7 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\definestetextinconjurat [...1] [...2] [...3,...]
OPT OPT`

1 NAME

2 NAME

3 inherits: \setupframedtext

`\definestetyping [...1] [...2] [...3,...]
OPT OPT`

1 NAME

2 NAME

3 inherits: \seteazatyping

`\definestyleinstance [...1] [...2] [...3] [...4]
OPT OPT`

1 NAME

2 rm ss tt mm hw cg

3 tf bf it sl bi bs sc

4 BEFEHL

`\definesubformula [...1] [...2] [...3,...]
OPT OPT`

1 NAME

2 NAME

3 inherits: \setupsubformula

`\definesynonym [1...] [2...] [3...] {4...} {5...}`

OPT

- 1 da nu
- 2 SINGULAR
- 3 NAME
- 4 TEXT
- 5 CONTENT

`\definesystemattribute [1...] [2...,...]`

OPT

- 1 NAME
- 2 local global public private

`\definesystemconstant {*...}`

- * NAME

`\definesystemvariable {*...}`

- * NAME

`\defineTABLEsetup [1...] [2...,...]`

- 1 NAME
- 2 inherits: \setupTABLE

`\definetabulation [1...] [2...] [3...,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptabulation

`\definetextbackground [1...] [2...] [3...,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextbackground

`\definetextflow [1...] [2...] [3...,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptextflow

`\definetooltip [1...] [2...] [3...,...]`

OPT

OPT

- 1 NAME
- 2 NAME
- 3 inherits: \setuptooltip

`\definetransparency [1...] [2...]`

- 1 NAME
- 2 NUMMER

`\definetransparency [...]1 [...]2...`

1 NAME

2 a = NUMMER niciunul normal multiply ecran overlay softlight hardlight colordodge colorburn darken lighten
difference exclusion hue saturation culoare luminosity

t = NUMMER

`\definetransparency [...]1 [...]2`

1 NAME

2 NAME

`\definewopasslist {...}`

* NAME

`\definetype [...]1 [...]2 [...]3...`
OPT OPT

1 NAME

2 NAME

3 inherits: \seteazatype

`\definetypesface [...]1 [...]2 [...]3 [...]4 [...]5 [...]6...`
OPT OPT

1 NAME

2 rm ss tt mm hw cg

3 serif sans mono math handwriting calligraphy

4 NAME

5 implicit dtp

6 rscale = auto NUMMER
features = NAME
fallbacks = NAME
goodies = NAME
designsize = auto implicit
directie = ambele

`\definetypescriptprefix [...]1 [...]2`

1 NAME

2 TEXT

`\definetypescriptsynonym [...]1 [...]2`

1 NAME

2 TEXT

`\definetypesetting [...]1 [...]2 [...]3...`
OPT OPT

1 NAME

2 TEXT

3 inherits: \setupexternalfigure

`\defineunit [...]1 [...]2 [...]3...`
OPT OPT

1 NAME

2 NAME

3 inherits: \setupunit

`\defineviewerlayer [...]1 [...]2 [...]3...`

- 1 NAME
- 2 NAME
- 3 inherits: \setupviewerlayer

`\definevspace [...]1 [...]2 [...]3`

- 1 NAME
- 2 NAME
- 3 DIMENSION

`\definevspacing [...]1 [...]2`

- 1 NAME
- 2 inherits: \vspacing

`\definevspacingamount [...]1 [...]2 [...]3`

- 1 NAME
- 2 DIMENSION
- 3 DIMENSION

`\definextable [...]1 [...]2 [...]3...`

- 1 NAME
- 2 NAME
- 3 inherits: \setupxtable

`\delimited [...]1 [...]2 {...}3`

- 1 NAME
- 2 SPRACHE
- 3 CONTENT

`\delimitedtext [...]1 [...]2 {...}3`

- 1 NAME
- 2 SPRACHE
- 3 CONTENT

`\DELIMITEDTEXT [...]1 {...}2`

- 1 SPRACHE
- 2 CONTENT

`instances: citat minicitat blockquote speech aside`

`\depthofstring {...}`

- * TEXT

`\depthonlybox {...}`

- * CONTENT

$\backslash\text{depthspanningtext} \{...\}^1 \{...\}^2 \{...\}^3$ 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{DESCRIERE} [...,\dots]^1 \{...\}^2 \dots \backslash\text{par}$ <small>OPT</small> <small>OPT</small> 1 REFERENCE 2 TEXT 3 CONTENT
$\backslash\text{despre} [..*]$ * REFERENCE
$\backslash\text{determinacaracteristicilelistei} [...,\dots]^1 [...,\dots]^2 [...,\dots]^3$ <small>OPT</small> 1 LISTE 2 inherits: \seteazalista
$\backslash\text{determinacaracteristiciregistru} [...,\dots]^1 [...,\dots]^2 [...,\dots]^3$ <small>OPT</small> 1 NAME 2 language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc numberorder = numere compress = da nu tot criteriu = local text curent precedent tot ABSCHNITT
$\backslash\text{determinanumartitlu} [..*]$ * ABSCHNITT
$\backslash\text{determinenoflines} \{...\}$ * CONTENT
$\backslash\text{devanagarinumerals} \{...\}$ * NUMMER
$\backslash\text{dfrac} \{...\}^1 \{...\}^2$ 1 CONTENT 2 CONTENT
$\backslash\text{digits} \{...\}$ * NUMMER
$\backslash\text{digits} ..*$ * NUMMER
$\backslash\text{dimensiontocount} \{...\}^1 \backslash\{...\}^2$ 1 DIMENSION 2 CSNAME

<code>\din [...]</code> * REFERENCE
<code>\directcolor [...]</code> * COLOR
<code>\directcolored [...,...[*]...,...]</code> * inherits: \definesteculoare
<code>\directcolored [...]</code> * COLOR
<code>\directconvertedcounter {...¹} {...²}</code> 1 NAME 2 primul precedent urmatorul ultim numar
<code>\directdummyparameter {...}</code> * KEY
<code>\directgetboxllx ...</code> * CSNAME NUMBER
<code>\directgetboxlly ...</code> * CSNAME NUMBER
<code>\directhighlight {...¹} {...²}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...¹] {...²}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * BEFEHL
<code>\directselect {...¹} {...²} {...³} {...⁴} {...⁵} {...⁶}</code> <div style="display: flex; justify-content: space-around; margin: 0 100px;"> OPT OPT OPT OPT OPT </div> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME

$\backslash\text{directsetup}$ {...} * NAME
$\backslash\text{directsymbol}$ {... ¹ } {... ² } 1 NAME 2 NAME
$\backslash\text{directvspacing}$ {...,*...} * inherits: \vspacing
$\backslash\text{dis}$ {...} * CONTENT
$\backslash\text{disabledirectives}$ [...,*...]
* NAME
$\backslash\text{disableexperiments}$ [...,*...]
* NAME
$\backslash\text{disablemode}$ [...,*...]
* NAME
$\backslash\text{disableoutputstream}$
$\backslash\text{disableparpositions}$
$\backslash\text{disableregime}$
$\backslash\text{disabletrackers}$ [...,*...]
* NAME
$\backslash\text{displaymath}$ {...} * CONTENT
$\backslash\text{displaymathematics}$ {...} * CONTENT
$\backslash\text{displaymessage}$ {...} * TEXT
$\backslash\text{distributedhsize}$ {... ¹ } {... ² } {... ³ } 1 DIMENSION 2 DIMENSION 3 NUMMER

<code>\dividedsize {...} {...} {...}</code> 1 DIMENSION 2 DIMENSION 3 NUMMER
<code>\doadaptleftskip {...}</code> * da nu standard DIMENSION
<code>\doadaptrightskip {...}</code> * da nu standard DIMENSION
<code>\doaddfeature {...}</code> * NAME
<code>\doassign [...¹] [...²...]</code> 1 TEXT 2 KEY = VALUE
<code>\doassignempty [...¹] [...²...]</code> 1 TEXT 2 KEY = VALUE
<code>\doboundtext {...¹} {...²} {...³}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\docheckassignment {...}</code> * TEXT
<code>\docheckedpagestate {...¹} {...²} {...³} {...⁴} {...⁵} {...⁶} {...⁷}</code> 1 REFERENCE 2 BEFEHL 3 BEFEHL 4 BEFEHL 5 BEFEHL 6 BEFEHL 7 BEFEHL
<code>\docheckedpair {...*,...}</code> * TEXT
<code>\documentvariable {...}</code> * KEY

\dodoubleargument \¹... [²...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleargumentwithset \¹... [²...,³...] [³...]

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleempty \¹... [²...] [³...]
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoubleemptywithset \¹... [²...,³...] [³...]
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\dodoublegroupempty \¹... {²...} {³...}
OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT

\doeassign [¹...] [²...]

- 1 TEXT
- 2 KEY = VALUE

\doexpandedrecurse {¹...} {²...}

- 1 NUMMER
- 2 BEFEHL

\dogetattribute {^{*}...}

- * NAME

\dogetattributeid {^{*}...}

- * NAME

\dogetcommacommandelement ¹... \from ²... \to ³...

- 1 NUMMER
- 2 TEXT
- 3 CSNAME

\dogobbledoubleempty [¹...] [²...]
OPT OPT

- 1 TEXT
- 2 TEXT

<pre> \dogobblesingleempty [...] OPT * TEXT </pre>
<pre> \doif {...} {...} {...} 1 CONTENT 2 CONTENT 3 TRUE </pre>
<pre> \doifallcommon {...} * TRUE </pre>
<pre> \doifallcommonelse {...} {...} 1 TRUE 2 FALSE </pre>
<pre> \doifalldefinedelse {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifallmodes {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifallmodeselse {...,¹...} {...} {...} 1 NAME 2 TRUE 3 FALSE </pre>
<pre> \doifassignmentelse {...} {...} {...} 1 TEXT 2 TRUE 3 FALSE </pre>
<pre> \doifblackelse {...} {...} {...} 1 COLOR 2 TRUE 3 FALSE </pre>
<pre> \doifbothsides {...} {...} {...} 1 BEFEHL 2 BEFEHL 3 BEFEHL </pre>

`\doifbothsidesoverruled {...} {...} {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 BEFEHL

`\doifboxelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifbufferelse {...} {...} {...}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifcolor {...} {...}`

- 1 COLOR
- 2 TRUE

`\doifcolorelse {...} {...} {...}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifcommandhandler \... {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifcommon {...}`

- * TRUE

`\doifcommonelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifcontent {...} {...} {...} \... {...}`

- 1 BEFEHL
- 2 BEFEHL
- 3 BEFEHL
- 4 CSNAME
- 5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifconversionnumberelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifcurrentfonthasfeatureelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefined {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdimensionelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdimenstringelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifdocumentargument {...} {...}`

- 1 NAME
- 2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifdocumentfilename {...} {...}`

- 1 NUMMER
- 2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifdrawingblackelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelse {...} {...} {...} {...}`

- 1 CONTENT
- 2 CONTENT
- 3 TRUE
- 4 FALSE

`\doifelseallcommon {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsealldefined {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseallmodes {...1,...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseassignment {...1} {...2} {...3}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseblack {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsebox {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsebuffer {...1} {...2} {...3}`

- 1 BUFFER
- 2 TRUE
- 3 FALSE

`\doifelsecolor {...1} {...2} {...3}`

- 1 COLOR
- 2 TRUE
- 3 FALSE

`\doifelsecommandhandler \... {...1} {...2} {...3} {...4}`

- 1 CSNAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelsecommon {...1} {...2}`

- 1 TRUE
- 2 FALSE

\doifelseconversiondefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseconversionnumber {...} {...} {...} {...}

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsecounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentfonthasfeature {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsecurrentsortingingused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymshown {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsecurrentsynonymused {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsedefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedefinedcounter {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedimension {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsedimenstring {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsedocumentargument {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsedocumentfilename {...} {...} {...}

- 1 NUMMER
- 2 TRUE
- 3 FALSE

\doifelsedrawingblack {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseempty {...} {...} {...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifelseemptyvalue {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifelseenv {...} {...} {...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\doifelsefastoptionalcheck {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsefastoptionalcheckcs \... \...

- 1 CSNAME
- 2 CSNAME

\doifelsefieldbody {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefieldcategory {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefigure {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefiledefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefileexists {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsefirstchar {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseflagged {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsefontchar {...} {...} {...} {...}

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsefontpresent {...} {...} {...}

- 1 FONT
- 2 TRUE
- 3 FALSE

\doifelsefontsynonym {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsehasspace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsehelp {...} {...}

- 1 TRUE
- 2 FALSE

\doifelseincsname {...} {...} {...} {...}

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

\doifelseinelement {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinputfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseinsertion {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseinset {...} {...} {...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifelseinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelseinsymbolset {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseintoks {...} {...} {...} {...}

- 1 BEFEHL
- 2 BEFEHL
- 3 TRUE
- 4 FALSE

\doifelseintwopassdata {...} {...} {...} {...}

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseitalic {...} {...}

- 1 TRUE
- 2 FALSE

\doifelselanguage {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doifelselayerdata {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutdefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelselayoutsomeline {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelselayouttextline {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelseleapyear {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelselist {...} {...} {...}`

- 1 LISTE
- 2 TRUE
- 3 FALSE

`\doifelselocation {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelselocfile {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifelseMPgraphic {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsemainfloatbody {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelsemarking {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifelsemeaning \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifelsemessage {...} {...} {...} {...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TRUE
- 4 FALSE

`\doifelsemode {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenextbgroup {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextbgroupcs \... \...1 \...2`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextchar {...1} {...2} {...3}`

- 1 CHARACTER
- 2 TRUE
- 3 FALSE

`\doifelsenextoptional {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenextoptionalcs \... \...1 \...2`

- 1 CSNAME
- 2 CSNAME

`\doifelsenextparenthesis {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifelsenonzeropositive {...1} {...2} {...3}`

- 1 NUMBER
- 2 TRUE
- 3 FALSE

`\doifelsenoteonsamepage {...1} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifelsenothing {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelsenumber {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifelseobjectfound {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseobjectreferencefound {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifelseoddpage {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\doifelseoddpagefloat {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifelseoldercontext {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifelseolderversion {...} {...} {...} {...}`

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifelseoverlapping {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

\doifelseoverlay {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseparallel {...} {...,²...} {...} {...⁴}

- 1 NAME
- 2 NAME tot
- 3 TRUE
- 4 FALSE

\doifelseparentfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelsepath {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifelsepathexists {...} {...} {...}

- 1 PATH
- 2 TRUE
- 3 FALSE

\doifelsepatterns {...} {...} {...}

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

\doifelseposition {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionaction {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositiononpage {...} {...} {...} {...⁴}

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

\doifelsepositionsonsamepage {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionsonthispage {...,¹...} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsepositionsused {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifelserreferencefound {...¹} {...²} {...³}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelserightpagefloat {...¹} {...²}

- 1 TRUE
- 2 FALSE

\doifelserighttoleftinbox ...¹ {...²} {...³}

- 1 CSNAME NUMBER
- 2 TRUE
- 3 FALSE

\doifelsesamelinereference {...¹} {...²} {...³}

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

\doifelsesamestring {...¹} {...²} {...³} {...⁴}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsesetups {...¹} {...²} {...³}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomebackground {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesomespace {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesomething {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsesometoks \... {...} {...}

- 1 CSNAME
- 2 TRUE
- 3 FALSE

\doifelsestringinstring {...} {...} {...} {...}

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsestructurelisthasnumber {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsestructurelisthaspage {...} {...}

- 1 TRUE
- 2 FALSE

\doifelsesymboldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsesymbolset {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetext {...} {...} {...}

- 1 TEXT
- 2 TRUE
- 3 FALSE

\doifelsetextflow {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetextflowcollector {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsetypingfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\doifelseundefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelseurldefined {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsevalue {...} {...} {...} {...}

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

\doifelsevaluenothing {...} {...} {...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifelsevariable {...} {...} {...} {...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifempty ¹{...} ²{...}

- 1 CONTENT
- 2 TRUE

\doifemptyelse ¹{...} ²{...} ³{...}

- 1 CONTENT
- 2 TRUE
- 3 FALSE

\doifemptytoks \¹... ²{...}

- 1 CSNAME
- 2 TRUE

\doifemptyvalue ¹{...} ²{...}

- 1 NAME
- 2 TRUE

\doifemptyvalueelse ¹{...} ²{...} ³{...}

- 1 NAME
- 2 TRUE
- 3 FALSE

\doifemptyvariable ¹{...} ²{...} ³{...}

- 1 NAME
- 2 KEY
- 3 TRUE

\doifemptyvariableelse ¹{...} ²{...} ³{...} ⁴{...}

- 1 NAME
- 2 KEY
- 3 TRUE
- 4 FALSE

\doifenv ¹{...} ²{...}

- 1 KEY
- 2 TRUE

\doifenvelse ¹{...} ²{...} ³{...}

- 1 KEY
- 2 TRUE
- 3 FALSE

\doiffastoptionalcheckcselse \¹... \²...

- 1 CSNAME
- 2 CSNAME

`\doiffastoptionalcheckelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiffieldbodyelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffieldcategoryelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffigureelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffile {...} {...}`

- 1 FILE
- 2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffileexistselse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifflaggedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

- 1 FONT
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doiffontpresentelse {...} {...} {...}`

- 1 FONT
- 2 TRUE
- 3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifhasspaceelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifhelpelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifincsnameelse {...} {...} {...} {...}`

- 1 TEXT
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifinelementelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifinputfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

```
\doifinsectionelse {...} {...} {...}
```

```
1  NAME  
2  TRUE  
3  FALSE
```

```
\doifinset {...} {...}
```

```
1  CONTENT  
2  TRUE
```

```
\doifinsetelse {...} {...} {...}
```

```
1  CONTENT  
2  TRUE  
3  FALSE
```

```
\doifinstring {...} {...} {...}
```

```
1  TEXT  
2  TEXT  
3  TRUE
```

```
\doifinstringelse {...} {...} {...} {...}
```

```
1  TEXT  
2  TEXT  
3  TRUE  
4  FALSE
```

```
\doifinsymbolset {...} {...} {...} {...}
```

```
1  NAME  
2  NAME  
3  TRUE  
4  FALSE
```

```
\doifinsymbolsetelse {...} {...} {...} {...}
```

```
1  NAME  
2  NAME  
3  TRUE  
4  FALSE
```

```
\doifintokselse {...} {...} {...} {...}
```

```
1  BEFEHL  
2  BEFEHL  
3  TRUE  
4  FALSE
```

`\doifintwopassdataelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifitalicelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflanguageelse {...} {...} {...}`

- 1 SPRACHE
- 2 TRUE
- 3 FALSE

`\doiflayerdataelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifleapyearelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doiflistelse {...} {...} {...}`

- 1 LISTE
- 2 TRUE
- 3 FALSE

`\doiflocationelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doiflocfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifMPgraphicelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifmainfloatbodyelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifmarkingelse {...} {...} {...}`

- 1 BESCHRIFTUNG
- 2 TRUE
- 3 FALSE

`\doifmeaningelse \1... \2... {...} {...}`

- 1 CSNAME
- 2 CSNAME
- 3 TRUE
- 4 FALSE

`\doifmessageelse {...1} {...2} {...3} {...4}`

- 1 NAME
- 2 NAME NUMMER
- 3 TRUE
- 4 FALSE

`\doifmode {...,1...} {...2}`

- 1 NAME
- 2 TRUE

`\doifmodeelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifnextbgroupcselse \1... \2...`

- 1 CSNAME
- 2 CSNAME

<pre>\doifnextbgroupelse {...} {...}</pre> <pre>1 TRUE</pre> <pre>2 FALSE</pre>
<pre>\doifnextcharelse {...} {...} {...}</pre> <pre>1 CHARACTER</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\doifnextoptionalcselse \^1... \^2...</pre> <pre>1 CSNAME</pre> <pre>2 CSNAME</pre>
<pre>\doifnextoptionalelse {...} {...}</pre> <pre>1 TRUE</pre> <pre>2 FALSE</pre>
<pre>\doifnextparenthesiselse {...} {...}</pre> <pre>1 TRUE</pre> <pre>2 FALSE</pre>
<pre>\doifnonzeropositiveelse {...} {...} {...}</pre> <pre>1 NUMMER</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\doifnot {...} {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 CONTENT</pre> <pre>3 TRUE</pre>
<pre>\doifnotallcommon {...}</pre> <pre>* TRUE</pre>
<pre>\doifnotallmodes {...,^1...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\doifnotcommandhandler \^1... {...} {...}</pre> <pre>1 CSNAME</pre> <pre>2 NAME</pre> <pre>3 TRUE</pre>
<pre>\doifnotcommon {...}</pre> <pre>* TRUE</pre>

<pre>\doifnotcounter {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotdocumentargument {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotdocumentfilename {...} {...}</pre> <pre>1 NUMMER</pre> <pre>2 TRUE</pre>
<pre>\doifnotempty {...} {...}</pre> <pre>1 CONTENT</pre> <pre>2 TRUE</pre>
<pre>\doifnotemptyvalue {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotemptyvariable {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 TRUE</pre>
<pre>\doifnotenv {...} {...}</pre> <pre>1 KEY</pre> <pre>2 TRUE</pre>
<pre>\doifnoteonsamepageelse {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre> <pre>3 FALSE</pre>
<pre>\doifnotescollected {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifnotfile {...} {...}</pre> <pre>1 FILE</pre> <pre>2 TRUE</pre>
<pre>\doifnotflagged {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>

`\doifnothing {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnothingelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifnotinset {...} {...}`

- 1 CONTENT
- 2 TRUE

`\doifnotinfloat {...}`

- * TRUE

`\doifnotinstring {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotmode {...,1...} {...}`

- 1 NAME
- 2 TRUE

`\doifnotnumber {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnotsamestring {...1} {...2} {...3}`

- 1 TEXT
- 2 TEXT
- 3 TRUE

`\doifnotsetups {...} {...}`

- 1 NAME
- 2 TRUE

`\doifnotvalue {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifnotvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 TRUE

`\doifnumber {...} {...}`

- 1 TEXT
- 2 TRUE

`\doifnumberelse {...} {...} {...}`

- 1 TEXT
- 2 TRUE
- 3 FALSE

`\doifobjectfoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifobjectreferencefoundelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoddpagelse {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\doifoddpagefloatelse {...} {...}`

- 1 TRUE
- 2 FALSE

`\doifoldercontextelse {...} {...} {...}`

- 1 NUMMER
- 2 TRUE
- 3 FALSE

`\doifolderversionelse {...} {...} {...} {...}`

- 1 NUMMER
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifoverlappingelse {...} {...} {...} {...}`

- 1 NAME
- 2 NAME
- 3 TRUE
- 4 FALSE

`\doifoverlayelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifparallelelse {...} {...,2...} {...} {...4}`

1 NAME
2 NAME tot
3 TRUE
4 FALSE

`\doifparentfileelse {...} {...} {...}`

1 FILE
2 TRUE
3 FALSE

`\doifpathelse {...} {...} {...}`

1 PATH
2 TRUE
3 FALSE

`\doifpathexistselse {...} {...} {...}`

1 PATH
2 TRUE
3 FALSE

`\doifpatternself {...} {...} {...}`

1 SPRACHE
2 TRUE
3 FALSE

`\doifposition {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifpositionaction {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifpositionactionelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifpositionelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositiononpageelse {...} {...} {...} {...}`

- 1 NAME
- 2 NUMMER
- 3 TRUE
- 4 FALSE

`\doifpositionsonsamepageelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsonthispageelse {...,1...} {...2} {...3}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifpositionsusedelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifreferencefoundelse {...1} {...2} {...3}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifrightpagefloatelse {...1} {...2}`

- 1 TRUE
- 2 FALSE

`\doifrighttoleftinboxedelse ...1 {...2} {...3}`

- 1 CSNAME NUMMER
- 2 TRUE
- 3 FALSE

`\doifsamelinereferenceelse {...1} {...2} {...3}`

- 1 REFERENCE
- 2 TRUE
- 3 FALSE

`\doifsamestring {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE

`\doifsamestringelse {...} {...} {...} {...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifsetups {...} {...}`

1 NAME
2 TRUE

`\doifsetupself {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsomebackground {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsomebackgroundelse {...} {...} {...}`

1 NAME
2 TRUE
3 FALSE

`\doifsomespaceelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifsomething {...} {...}`

1 TEXT
2 TRUE

`\doifsomethingelse {...} {...} {...}`

1 TEXT
2 TRUE
3 FALSE

`\doifsometoks \... {...}`

1 CSNAME
2 TRUE

`\doifsometokselsetelse \1... {\2...} {\3...}`

1 CSNAME
2 TRUE
3 FALSE

`\doifstringinstringelse {\1...} {\2...} {\3...} {\4...}`

1 TEXT
2 TEXT
3 TRUE
4 FALSE

`\doifstructurelisthasnumberelse {\1...} {\2...}`

1 TRUE
2 FALSE

`\doifstructurelisthaspageelse {\1...} {\2...}`

1 TRUE
2 FALSE

`\doifsymboldefinedelse {\1...} {\2...} {\3...}`

1 NAME
2 TRUE
3 FALSE

`\doifsymbolsetelse {\1...} {\2...} {\3...}`

1 NAME
2 TRUE
3 FALSE

`\doiftext {\1...} {\2...} {\3...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextelse {\1...} {\2...} {\3...}`

1 TEXT
2 TRUE
3 FALSE

`\doiftextflowcollectorelse {\1...} {\2...} {\3...}`

1 NAME
2 TRUE
3 FALSE

`\doiftextflowelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doiftypingfileelse {...} {...} {...}`

- 1 FILE
- 2 TRUE
- 3 FALSE

`\doifundefined {...} {...}`

- 1 NAME
- 2 TRUE

`\doifundefinedcounter {...} {...}`

- 1 NAME
- 2 TRUE

`\doifundefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifurldefinedelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

`\doifvalue {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE

`\doifvalueelse {...} {...} {...} {...}`

- 1 NAME
- 2 TEXT
- 3 TRUE
- 4 FALSE

`\doifvaluenothing {...} {...}`

- 1 NAME
- 2 TRUE

`\doifvaluenothingelse {...} {...} {...}`

- 1 NAME
- 2 TRUE
- 3 FALSE

<pre>\doifvaluesomething {...} {...}</pre> <pre>1 NAME</pre> <pre>2 TRUE</pre>
<pre>\doifvariable {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 TRUE</pre>
<pre>\doifvariableelse {...} {...} {...} {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 TRUE</pre> <pre>4 FALSE</pre>
<pre>\doindentation</pre>
<pre>\dollar</pre>
<pre>\doloop {...}</pre> <pre>* BEFEHL</pre>
<pre>\doloopoverlist {...,¹...} {...²}</pre> <pre>1 TEXT</pre> <pre>2 BEFEHL</pre>
<pre>\donothing</pre>
<pre>\dontconvertfont</pre>
<pre>\dontleavehmode</pre>
<pre>\dontpermitspacesbetweenegroups</pre>
<pre>\dopositionaction {...}</pre> <pre>* NAME</pre>
<pre>\doprocesslocalsetups {...,*...}</pre> <pre>* NAME</pre>
<pre>\doquadrupleargument \¹... [²...] [³...] [⁴...] [⁵...]</pre> <pre>1 CSNAME</pre> <pre>2 TEXT</pre> <pre>3 TEXT</pre> <pre>4 TEXT</pre> <pre>5 TEXT</pre>

`\doquadrupleempty \1... [2...] [3...] [4...] [5...]`
OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\doquadruplegroupempty \1... {2...} {3...} {4...} {5...}`
OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\doquintupleargument \1... [2...] [3...] [4...] [5...] [6...]`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintupleempty \1... [2...] [3...] [4...] [5...] [6...]`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\doquintuplegroupempty \1... {2...} {3...} {4...} {5...} {6...}`
OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\dorechecknextindentation`

`\dorecurse {1...} {2...}`

- 1 NUMMER
- 2 BEFEHL

`\dorepeatwithcommand [1...] \2...`

- 1 TEXT NUMMER*TEXT
- 2 CSNAME

\doreplacefeature {...} * NAME
\doresetandafffeature {...} * NAME
\doresetattribute {...} * NAME
\dorotatebox {...} \dots {...} 1 NUMMER 2 CSNAME 3 CONTENT
\dosetattribute {...} {...} 1 NAME 2 NUMMER
\dosetleftskipadaption {...} * da nu standard DIMENSION
\dosetrighskipadaption {...} * da nu standard DIMENSION
\dosetupcheckedinterlinespace {...,*...} * inherits: \seteazaspatiuinterliniar
\dosetupcheckedinterlinespace {...,*...} * on dezactivat reset auto mic mediu mare NUMMER DIMENSION
\dosetupcheckedinterlinespace {...} * NAME
\doseventupleargument \dots [1] [2] [3] [4] [5] [6] [7] [8] 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT 8 TEXT

\doseventupleempty \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷ ⁸
 OPT OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT
- 8 TEXT

\dosingleargument \... ¹ ²
 OPT

- 1 CSNAME
- 2 TEXT

\dosingleempty \... ¹ ²
 OPT

- 1 CSNAME
- 2 TEXT

\dosinglegroupempty \... ¹ { ² }
 OPT

- 1 CSNAME
- 2 TEXT

\dosixtupleargument \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷
 OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

\dosixtupleempty \... ¹ ² ³ ⁴ ⁵ ⁶ ⁷
 OPT OPT OPT OPT OPT OPT OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT
- 7 TEXT

\dostarttagged { ¹ } { ² } ... \dostoptagged

- 1 NAME
- 2 NAME

`\dostepwiserecurse {...} {...} {...} {...}`

- 1 NUMBER
- 2 NUMBER
- 3 [-+]NUMBER
- 4 BEFEHL

`\dosubtractfeature {...}`

- * NAME

`\dotfskip {...}`

- * DIMENSION

`\dotoks \...`

- * CSNAME

`\dotripleargument \... [...]1 [...]2 [...]3 [...]4`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleargumentwithset \... [...]1 [...]2, [...]3 [...]4`

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleempty \... [...]1 [...]2 [...]3 [...]4`

OPT

OPT

OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotripleemptywithset \... [...]1 [...]2, [...]3 [...]4`

OPT

OPT

OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\dotriplegroupempty \... {...}1 {...}2 {...}3 {...}4`

OPT

OPT

OPT

- 1 CSNAME
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\doublebar {...}`

- * TEXT

<code>\doublebond</code>
<code>\doublebrace {...}</code> * TEXT
<code>\doublebracket {...}</code> * TEXT
<code>\doubleparent {...}</code> * TEXT
<code>\dowith {...¹,...} {...²}</code> 1 BEFEHL 2 BEFEHL
<code>\dowithnextbox {...¹} \... {...³}</code> 1 BEFEHL 2 CSNAME 3 CONTENT
<code>\dowithnextboxcontent {...¹} {...²} \... {...⁴}</code> 1 BEFEHL 2 BEFEHL 3 CSNAME 4 CONTENT
<code>\dowithnextboxcontentcs \...¹ \...² \...³ {...⁴}</code> 1 CSNAME 2 CSNAME 3 CSNAME 4 CONTENT
<code>\dowithnextboxcs \...¹ \...² {...³}</code> 1 CSNAME 2 CSNAME 3 CONTENT
<code>\dowithpargument \...</code> * CSNAME
<code>\dowithrange {...¹,...} \...²</code> 1 NUMMER NUMMER:NUMMER 2 CSNAME
<code>\dowithwargument \...</code> * CSNAME

\dpofstring {...} * TEXT
\dreapta ... * CHARACTER
\dummydigit
\dummysparameter {...} * KEY
\dute {...} [...] 1 CONTENT 2 REFERENCE
\dutebox {...} [...] 1 CONTENT 2 REFERENCE
\dutepagina {...} [...] 1 TEXT 2 REFERENCE
\ETEX
\EveryLine {...} * BEFEHL
\EveryPar {...} * BEFEHL
\ecran [...,*...] <div>OPT</div> * inherits: \pagina
\edefconvertedargument \ ¹ ... { ² ...} 1 CSNAME 2 TEXT
\efcmaxheight {...} * NAME
\efcmaxwidth {...} * NAME
\efcminheight {...} * NAME

<code>\efcminwidth {...}</code> <code>* NAME</code>
<code>\efcparameter {...} {...}</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\effect [...] {...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\leftarrowfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\leftharpoondownfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\leftharpoonupfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\leftrightarrowfill {...} {...}</code> <div> <div></div> <div>OPT</div> <div></div> <div>OPT</div> </div> <code>1 TEXT</code> <code>2 TEXT</code>
<code>\element [...,*...]</code> <div> <div></div> <div>OPT</div> </div> <code>* REFERENCE</code>
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...,*...]</code> <div> <div></div> <div>OPT</div> </div> <code>* NUMMER</code>
<code>\emspace</code>
<code>\enabledirectives [...,*...]</code> <code>* NAME</code>
<code>\enableexperiments [...,*...]</code> <code>* NAME</code>

<p><code>\enablemode [...,*,...]</code></p> <p>* NAME</p>
<p><code>\enableoutputstream [...]</code></p> <p>* NAME</p>
<p><code>\enableparpositions</code></p>
<p><code>\enableregime [...]</code></p> <p>* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows</p>
<p><code>\enabletrackers [...,*,...]</code></p> <p>* NAME</p>
<p><code>\enskip</code></p>
<p><code>\enspace</code></p>
<p><code>\ENUMERARE [...,¹...] {..².} ..³. \par</code> <small>OPT OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 CONTENT</p>
<p><code>\env {...}</code></p> <p>* KEY</p>
<p><code>\envvar {..¹.} {..².}</code></p> <p>1 KEY</p> <p>2 BEFEHL</p>
<p><code>\eoverbarfill {..¹.} {..².}</code> <small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\eoverbracefill {..¹.} {..².}</code> <small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\eoverbracketfill {..¹.} {..².}</code> <small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>
<p><code>\eoverparentfill {..¹.} {..².}</code> <small>OPT OPT</small></p> <p>1 TEXT</p> <p>2 TEXT</p>

$\backslash\text{epos}$ {...} * NAME
$\backslash\text{equaldigits}$ {...} * TEXT
$\backslash\text{erightarrowfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{erightharpoondownfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{erightharpoonupfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eTeX}$
$\backslash\text{ETICHETA}$ [..., ¹ ...] {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 REFERENCE 2 TEXT
$\backslash\text{etwoheadrightarrowfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderbarfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderbracefill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderbracketfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{eunderparentfill}$ {...} {...} <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 TEXT 2 TEXT
$\backslash\text{executeifdefined}$ {...} {...} 1 NAME 2 BEFEHL

<code>\exitloop</code>
<code>\exitloopnow</code>
<code>\expandcheckedcsname \¹..²..³..</code> 1 CSNAME 2 KEY 3 TEXT
<code>\expanded {..[*]..}</code> * CONTENT
<code>\expandfontsynonym \¹..²..</code> 1 CSNAME 2 NAME
<code>\externalfigurecollectionmaxheight {..[*]..}</code> * NAME
<code>\externalfigurecollectionmaxwidth {..[*]..}</code> * NAME
<code>\externalfigurecollectionminheight {..[*]..}</code> * NAME
<code>\externalfigurecollectionminwidth {..[*]..}</code> * NAME
<code>\externalfigurecollectionparameter {..¹..²..}</code> 1 NAME 2 KEY
<code>\fakebox ..[*]..</code> * CSNAME NUMBER
<code>\faraliniiantetsisubsol</code>
<code>\faraliniisussijos</code>
<code>\faraspatiu</code>
<code>\fastdecrement \..[*]..</code> * CSNAME
<code>\fastincrement \..[*]..</code> * CSNAME

<p>\fastlocalframed [¹...] [²...₂...] {³...}</p> <p>1 NAME</p> <p>2 inherits: \seteazainconjurat</p> <p>3 CONTENT</p>
<p>\fastscale {¹...} {²...}</p> <p>1 NUMMER</p> <p>2 CONTENT</p>
<p>\fastsetup {[*]...}</p> <p>* NAME</p>
<p>\fastsetupwithargument {¹...} {²...}</p> <p>1 NAME</p> <p>2 CONTENT</p>
<p>\fastsetupwithargumentswapped {¹...} {²...}</p> <p>1 CONTENT</p> <p>2 NAME</p>
<p>\fastswitchtobodyfont {[*]...}</p> <p>* x xx mic mare script scriptscript</p>
<p>\fastxsxy {¹...} {²...} {³...}</p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 CONTENT</p>
<p>\feature [¹...] [²...]</p> <p>1 + - = ! > < more less nou reset implicit old local</p> <p>2 NAME</p>
<p>\feature {¹...} {²...}</p> <p>1 + - = ! > < more less nou reset implicit old local</p> <p>2 NAME</p>
<p>\fence</p>
<p>\fenced [¹...] {²...}</p> <p>1 NAME</p> <p>2 CONTENT</p>
<p>\FENCE {[*]...}</p> <p>* CONTENT</p>
<p>\fetchallmarkings [¹...] [²...]</p> <p>1 BESCHRIFTUNG</p> <p>2 pagina NAME</p>

\fetchallmarks [...] * BESCHRIFTUNG
\fetchmark [...] [² ...] <div>OPT</div> 1 BESCHRIFTUNG 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchmarking [¹] [²] [³] 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchonemark [¹] [² ...] <div>OPT</div> 1 BESCHRIFTUNG 2 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchonemarking [¹] [²] [³] 1 BESCHRIFTUNG 2 pagina NAME 3 primul ultim curent precedent urmatorul sus subsol implicit ambele tot first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
\fetchruntimecommand \ ¹ {...} 1 CSNAME 2 FILE
\fetchtwomarkings [¹] [²] 1 BESCHRIFTUNG 2 pagina NAME
\fetchtwomarks [...] * BESCHRIFTUNG
\fieldbody [...] [² ...] <div>OPT</div> 1 NAME 2 inherits: \setupfieldbody
\fifthoffivearguments {...} {...} {...} {...} {...} 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT

`\fifthofsixarguments` $\{\dots\}^1 \{\dots\}^2 \{\dots\}^3 \{\dots\}^4 \{\dots\}^5 \{\dots\}^6$

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

6 TEXT

$$\backslash\text{figuraexterna} \begin{matrix} [\dots] & [\dots] & [\dots, \dots = \dots, \dots] \\ & \text{OPT} & \text{OPT} \end{matrix}$$

1 FILE

2 NAME

```
3 inherits: \setupexternalfigure
```

\figurefilename

\figurefilepath

\figurefiletype

`\figurefullname`

\figureheight

\figurenaturalheight

\figurenaturalwidth

```
\figuresymbol [...] [..1..] [..2..OPT..]
```

1 FILE NAME

```
2 inherits: \figuraexterna
```

\figurewidth

`\filename {...}`

* FILE

`\filledhboxb` ¹... {²...}
OPT

1 TEXT

2 CONTENT

`\filledhboxc` ¹... {²...}
OPT

1 TEXT

2 CONTENT

`\filledhboxg` ¹... {²...}
OPT

1 TEXT

2 CONTENT

<pre> \filledhboxk ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxm ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxr ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filledhboxy ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \filler [...]</pre> <p>* sym simbol rigla latime spatiu NAME</p>
<pre> \filterfromnext {¹...} {²...} 1 NUMMER 2 NUMMER </pre>
<pre> \filterfromvalue {¹...} {²...} {³...} 1 NAME 2 NUMMER 3 NUMMER </pre>
<pre> \filterpages [...]¹ [...,²...] [...,³...,...]_{OPT} 1 FILE 2 par impar NUMMER NUMMER:NUMMER 3 latime = DIMENSION n = NUMMER category = NAME </pre>
<pre> \filterreference {[*]...} * implicit text titlu numar pagina realpage </pre>
<pre> \findtwopassdata {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \finishregisterentry [...]¹ [...,²...,...]_{OPT} [...,³...,...]_{OPT} 1 NAME 2 eticheta = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT alternativ = TEXT 3 KEY = VALUE </pre>

<code>\firdepar</code>
<code>\firstcharacter</code>
<code>\firstcounter [...]</code> <div> <div>¹</div> <div>²</div> <div>OPT</div> </div>
1 NAME 2 NUMMER
<code>\firstcountervalue [...]</code> * NAME
<code>\firstoffivearguments {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\firstoffourarguments {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
<code>\firstofoneargument {...}</code> * TEXT
<code>\firstofoneunexpanded {...}</code> * TEXT
<code>\firstofsixarguments {...} {...} {...} {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\firstofthreearguments {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT
<code>\firstofthreeunexpanded {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT

<code>\firstoftwoarguments {...} {...}</code> 1 TEXT 2 TEXT
<code>\firstoftwounexpanded {...} {...}</code> 1 TEXT 2 TEXT
<code>\firstrealpage</code>
<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue [...] [...]</code> 1 NAME 2 NUMMER
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfieldframed [...,\stackrel{.1}{\text{OPT}},...] {...}</code> 1 inherits: \seteazainconjurat 2 CONTENT
<code>\fittopbaselinegrid {...}</code> * CONTENT
<code>\flag {...}</code> * NAME
<code>\floatuserdataparameter {...}</code> * KEY
<code>\flushboxregister ...</code> * CSNAME NUMBER
<code>\flushcollector [...]</code> * NAME
<code>\flushedrightlastline</code>
<code>\flushlayer [...]</code> * NAME
<code>\flushlocalfloats</code>
<code>\flushnextbox</code>

<code>\flushnotes</code>
<code>\flushoutputstream [...]</code> * NAME
<code>\flushshapebox</code>
<code>\flushtextflow {...}</code> * NAME
<code>\flushtokens [...]</code> * NAME
<code>\flushtoks *..</code> * CSNAME
<code>\folosestebloc [...¹,...] [...²,...] [...³,...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 NAME 2 + - 3 criteriu = text ABSCHNITT
<code>\folosestedirector [...*,...]</code> * PATH
<code>\folosestedocumentextern [...¹] [...²] [...³]</code> <div style="display: flex; justify-content: flex-end; width: 100%;"> OPT </div> 1 NAME 2 FILE 3 TEXT
<code>\folosestefiguraexterna [...¹] [...²] [...³] [...⁴,...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 NAME 2 FILE 3 NAME 4 inherits: \setupexternalfigure
<code>\folosestemodul [...¹] [...²,...] [...³,...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 m p s x t 2 FILE 3 KEY = VALUE
<code>\folosestemuzicaexterna [...¹] [...²]</code> 1 NAME 2 FILE
<code>\folosestescriptJS [...¹] [...²,...]</code> <div style="display: flex; justify-content: flex-end; width: 100%;"> OPT </div> 1 FILE 2 NAME

\folosestesimboluri [...] * FILE
\folosesteURL [...] [...] [...] [...] 1 NAME 2 URL 3 FILE 4 TEXT
\folosesteurl [...] [...] [...] [...] 1 NAME 2 URL 3 FILE 4 TEXT
\fontalternative
\fontbody
\fontchar {...} * NAME
\fontcharbyindex {...} * NUMMER
\fontclass
\fontclassname {...} {...} 1 NAME 2 FONT
\fontface
\fontfeaturelist [...] [...] 1 NAME 2 TEXT
\fontsize
\fontstyle
\footnotetext [...] [...] [...] [...] 1 REFERENCE 2 TEXT

<p><code>\footnotetext [...[*]...]</code></p> <p>* titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE</p>
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>
<p><code>\forgetparameters [...¹] [...²...]</code></p> <p>1 TEXT</p> <p>2 KEY = VALUE</p>
<code>\forgetragged</code>
<p><code>\formula [...¹;...] {..²..}</code></p> <p> OPT</p> <p>1 impachetat tight centru incadrat inherits: \seteazafonttext</p> <p>2 CONTENT</p>
<p><code>\foundbox {..¹} {..²..}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\fourthoffivearguments {..¹} {..²} {..³} {..⁴} {..⁵}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p>
<p><code>\fourthoffourarguments {..¹} {..²} {..³} {..⁴}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p>
<p><code>\fourthofsixarguments {..¹} {..²} {..³} {..⁴} {..⁵} {..⁶}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>

$\frac{\dots}{\dots}$ 1 CONTENT 2 CONTENT
$\frac{\dots}{\dots}$ 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\boxed{\dots}$ 1 inherits: \seteazainconjurat 2 CONTENT
$\boxed{\dots}$ * KEY
$\boxed{\dots}$ * KEY
$\boxed{\dots}$ 1 inherits: \seteazainconjurat 2 CONTENT instances: unframed fitfieldframed
\dots 1 CSNAME 2 CSNAME
\dots 1 NAME 2 DIMENSION
\dots
\dots 1 REFERENCE 2 TEXT
\dots * CONTENT
\dots * CONTENT

<p><code>\FUNDAL {...}</code></p> <p>* CONTENT</p> <p>instances: fundal</p>
<code>\GetPar</code>
<code>\GotoPar</code>
<p><code>\Greeknumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\gdefconvertedargument \¹... {\²...}</code></p> <p>1 CSNAME</p> <p>2 TEXT</p>
<p><code>\gdefconvertedcommand \¹... \²...</code></p> <p>1 CSNAME</p> <p>2 CSNAME</p>
<p><code>\getboxllx ...</code></p> <p>* CSNAME NUMMER</p>
<p><code>\getboxlly ...</code></p> <p>* CSNAME NUMMER</p>
<p><code>\getbufferdata [...]_{OPT}</code></p> <p>* BUFFER</p>
<p><code>\getcommacommandsize [...,*,...]</code></p> <p>* BEFEHL</p>
<p><code>\getcommalistsize [...,*,...]</code></p> <p>* BEFEHL</p>
<p><code>\getdayoftheweek {\¹...} {\²...} {\³...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 NUMMER</p>
<p><code>\getdayspermonth {\¹...} {\²...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p>
<p><code>\getdefinedbuffer [...]</code></p> <p>* BUFFER</p>

\getdocumentargument {...} * NAME
\getdocumentargumentdefault {...} {...} 1 NAME 2 TEXT
\getdocumentfilename {...} * NUMMER
\getdummyparameters [...,.. ¹ ...,...] * KEY = VALUE
\getemptyparameters [...] ¹ [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getparameters [...] ¹ [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getexpandedparameters [...] ¹ [...,.. ² ...,...] 1 TEXT 2 KEY = VALUE
\getfiguredimensions [...] ¹ [...,.. ² ...,...] <div style="text-align: center;"><small>OPT</small></div> 1 FILE 2 inherits: \setupexternalfigure
\getfirstcharacter {...} * TEXT
\getfirsttwopassdata {...} * NAME
\getfromcommacommand [..., ¹ ...] [...] ² 1 BEFEHL 2 NUMMER
\getfromcommalist [..., ¹ ...] [...] ² 1 BEFEHL 2 NUMMER
\getfromtwopassdata {...} ¹ {...} ² 1 NAME 2 NAME

<code>\getglyphdirect {...} {...}</code> 1 FONT 2 NUMMER CHARACTER
<code>\getglyphstyled {...} {...}</code> 1 FONT 2 NUMMER CHARACTER
<code>\getgparameters [...] [...,²...,...]</code> 1 TEXT 2 KEY = VALUE
<code>\getlasttwopassdata {...}</code> * NAME
<code>\getlocalfloat {...}</code> * NUMMER
<code>\getlocalfloats</code>
<code>\getMPdrawing</code>
<code>\getMPlayer [...] [...,²...,...]_{OPT} {...}</code> 1 NAME 2 inherits: \setezainconjurat 3 CONTENT
<code>\getmessage {...} {...}</code> 1 NAME 2 NAME NUMMER
<code>\getnamedglyphdirect {...} {...}</code> 1 FONT 2 NAME
<code>\getnamedglyphstyled {...} {...}</code> 1 FONT 2 NAME
<code>\getnamedtwopassdatalist \¹... {...}</code> 1 CSNAME 2 NAME
<code>\getnaturaldimensions ...</code> * CSNAME NUMMER
<code>\getnoflines {...}</code> * DIMENSION

\getobject {...} {...}

1 NAME

2 NAME

\getobjectdimensions {...} {...}

1 NAME

2 NAME

\getpaletsize [...]

* NAME

\getparameters [...]¹ [...,...²...,...]

1 TEXT

2 KEY = VALUE

\getprivatechar {...}

* NAME

\getprivateslot {...}

* NAME

\getrandomcount \... {...}¹ {...}² {...}³

1 CSNAME

2 NUMMER

3 NUMMER

\getrandomdimen \... {...}¹ {...}² {...}³

1 CSNAME

2 DIMENSION

3 DIMENSION

\getrandomfloat \... {...}¹ {...}² {...}³

1 CSNAME

2 NUMMER

3 NUMMER

\getrandomnumber \... {...}¹ {...}² {...}³

1 CSNAME

2 NUMMER

3 NUMMER

\getrandomseed \...

* CSNAME

\getraweparameters [...]¹ [...,...²...,...]

1 TEXT

2 KEY = VALUE

<pre> \getrawgparameters [...] [...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawnoflines {...} * DIMENSION </pre>
<pre> \getrawparameters [...] [...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawxparameters [...] [...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getreference [...] [...] 1 implicit text titlu numar pagina realpage 2 REFERENCE </pre>
<pre> \getreferenceentry {...} * implicit text titlu numar pagina realpage </pre>
<pre> \getroundednoflines {...} * DIMENSION </pre>
<pre> \getsubstring {...} {...} {...} 1 NUMMER 2 NUMMER 3 TEXT </pre>
<pre> \gettwopassdata {...} * NAME </pre>
<pre> \gettwopassdatalist {...} * NAME </pre>
<pre> \getuvalue {...} * NAME </pre>
<pre> \getvalue {...} * NAME </pre>
<pre> \getvariable {...} {...} 1 NAME 2 KEY </pre>

<pre> \getvariabledefault {...} {...} {...} 1 NAME 2 KEY 3 BEFEHL </pre>
<pre> \getxparameters [...] [...,..<u>2</u>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \globaldisablemode [...,*...] * NAME </pre>
<pre> \globalenablemode [...,*...] * NAME </pre>
<pre> \globalletempty *... * CSNAME </pre>
<pre> \globalpopbox ... * CSNAME NUMMER </pre>
<pre> \globalpopmacro *... * CSNAME </pre>
<pre> \globalpreventmode [...,*...] * NAME </pre>
<pre> \globalprocesscommalist [...] *... 1 BEFEHL 2 CSNAME </pre>
<pre> \globalpushbox ... * CSNAME NUMMER </pre>
<pre> \globalpushmacro *... * CSNAME </pre>
<pre> \globalpushreferenceprefix {...} ... \globalpopreferenceprefix * + - TEXT </pre>
<pre> \globalswapcounts *... *... 1 CSNAME 2 CSNAME </pre>
<pre> \globalswapdimens *... *... 1 CSNAME 2 CSNAME </pre>

`\globalswapmacros \1... \2...`

1 CSNAME

2 CSNAME

`\globalundefine {...}`

* NAME

`\glyphfontfile {...}`

* FONT

`\gobbledoubleempty [1...] [2...]`
 OPT OPT

1 TEXT

2 TEXT

`\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

7 CONTENT

8 CONTENT

`\gobblefivearguments {...} {...} {...} {...} {...}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

`\gobblefiveoptionals [1...] [2...] [3...] [4...] [5...]`

1 TEXT

2 TEXT

3 TEXT

4 TEXT

5 TEXT

`\gobblefourarguments {...} {...} {...} {...}`

1 CONTENT

2 CONTENT

3 CONTENT

4 CONTENT

\gobblefouroptionals [...]¹ [...]² [...]³ [...]⁴

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT

\gobbleninearguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶ {...}⁷ {...}⁸ {...}⁹

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT

\gobbleoneargument {...}^{*}

- * CONTENT

\gobbleoneoptional [...]^{*}

- * TEXT

\gobblesevenarguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶ {...}⁷

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT

\gobblesingleempty [...]^{*}
OPT

- * TEXT

\gobblesixarguments {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT

\gobblespacetokens

`\gobbletenarguments {1.} {2.} {3.} {4.} {5.} {6.} {7.} {8.} {9.} {10.}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT
- 4 CONTENT
- 5 CONTENT
- 6 CONTENT
- 7 CONTENT
- 8 CONTENT
- 9 CONTENT
- 10 CONTENT

`\gobblethreearguments {1.} {2.} {3.}`

- 1 CONTENT
- 2 CONTENT
- 3 CONTENT

`\gobblethreeoptionals [1.] [2.] [3.]`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\gobbletwoarguments {1.} {2.}`

- 1 CONTENT
- 2 CONTENT

`\gobbletwooptionals [1.] [2.]`

- 1 TEXT
- 2 TEXT

`\gobbleuntil \...`

- * CSNAME

`\gobbleuntilrelax ... \relax`

- * CONTENT

`\grabbufferdata [1.] [2.] [3.] [4.]`
OPT

- 1 CATEGORY
- 2 NAME
- 3 NAME
- 4 NAME

`\grabbufferdatadirect {1.} {2.} {3.}`

- 1 NAME
- 2 NAME
- 3 NAME

<code>\grabuntil {...} \²...</code> 1 NAME 2 CSNAME
<code>\grave {...}</code> * CHARACTER
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring ... \at ¹... \to \³... \and \⁴...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMMER
<code>\grid [...,[*]...,...]</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> * inherits: \basegrid
<code>\grosimlinie</code>
<code>\groupedcommand {.¹...} {.²...}</code> 1 BEFEHL 2 BEFEHL
<code>\gsetboxllx ¹... {.²...}</code> 1 CSNAME NUMMER 2 DIMENSION
<code>\gsetboxlly ¹... {.²...}</code> 1 CSNAME NUMMER 2 DIMENSION
<code>\gujaratinumerals {.*...}</code> * NUMMER
<code>\gurmukhinumerals {.*...}</code> * NUMMER
<code>\hairspace</code>
<code>\halfwaybox {.*...}</code> * CONTENT

<code>\handletokens ... \with ...</code> 1 TEXT 2 CSNAME
<code>\hash</code>
<code>\hat {...}</code> * CHARACTER
<code>\hboxofvbox ...</code> * CSNAME NUMBER
<code>\hboxreference [...¹,...] {...²}</code> 1 REFERENCE 2 CONTENT
<code>\hboxBOX {...}</code> * CONTENT
<code>\hdofstring {...}</code> * TEXT
<code>\headhbox ...¹ {...²}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\headnumbercontent</code>
<code>\headnumberdistance</code>
<code>\headnumberwidth</code>
<code>\headreferenceattributes</code>
<code>\headsetupspacing</code>
<code>\headtextcontent</code>
<code>\headtextdistance</code>
<code>\headtextwidth</code>
<code>\headvbox ...¹ {...²}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\headwidth</code>

<p><code>\heightanddepthofstring {...}</code></p> <p>* TEXT</p>
<p><code>\heightofstring {...}</code></p> <p>* TEXT</p>
<p><code>\heightspanningtext {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\HELP [...]_{OPT} {...} {...}</code></p> <p>1 REFERENCE</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>instances: textajutator</p>
<p><code>\hglue ...</code></p> <p>* DIMENSION</p>
<p><code>\hiddenbar {...}</code></p> <p>* CONTENT</p>
<p><code>\hiddencitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\hiddencite [...]</code></p> <p>* REFERENCE</p>
<p><code>\highlight [...]¹ {...}²</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\HIGHLIGHT {...}</code></p> <p>* TEXT</p>
<p><code>\highordinalstr {...}</code></p> <p>* TEXT</p>
<p><code>\hilo [...]¹ {...}² {...}³</code> <small>OPT</small></p> <p>1 stanga dreapta</p> <p>2 CONTENT</p> <p>3 CONTENT</p>

$\backslash\mathrm{himilo}\{\ldots\}\{\ldots\}\{\ldots\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\mathrm{hl}\left[\ldots\right]$ <small>OPT</small> * NUMMER
$\backslash\mathrm{horizontalgrowingbar}\left[\ldots,\ldots\overset{*}{=}\ldots,\ldots\right]$ * inherits: $\backslash\mathrm{setuppositionbar}$
$\backslash\mathrm{horizontalpositionbar}\left[\ldots,\ldots\overset{*}{=}\ldots,\ldots\right]$ * inherits: $\backslash\mathrm{setuppositionbar}$
$\backslash\mathrm{hphantom}\{\ldots\}$ * CONTENT
$\backslash\mathrm{hpos}\{\ldots\}^1\{\ldots\}^2$ 1 NAME 2 CONTENT
$\backslash\mathrm{hsizefraction}\{\ldots\}^1\{\ldots\}^2$ 1 DIMENSION 2 NUMMER
$\backslash\mathrm{hsmash}\{\ldots\}$ * CONTENT
$\backslash\mathrm{hsmashbox}\ldots$ * CSNAME NUMMER
$\backslash\mathrm{hsmashed}\{\ldots\}$ * CONTENT
$\backslash\mathrm{hspace}\left[\ldots\right]^1\left[\ldots\right]^2$ <small>OPT OPT</small> 1 NAME 2 mic mediu mare normal implicit niciunul .5 1 2 3 speech minicitat interquotation citat sentence intersentence NAME
$\backslash\mathrm{htdpofstring}\{\ldots\}$ * TEXT
$\backslash\mathrm{htofstring}\{\ldots\}$ * TEXT
$\backslash\mathrm{hyphen}$
$\backslash\mathrm{hyphenatedcoloredword}\{\ldots\}$ * TEXT

<code>\hyphenatedfile {...}</code> * FILE
<code>\hyphenatedfilename {...}</code> * TEXT
<code>\hyphenatedhbox {...}</code> * CONTENT
<code>\hyphenatedpar {...}</code> * TEXT
<code>\hyphenatedurl {...}</code> * TEXT
<code>\hyphenatedword {...}</code> * TEXT
<code>\INRSTEX</code>
<code>\ibox {...}</code> * CONTENT
<code>\ifassignment ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iff</code>
<code>\ifinobject ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifinoutputstream ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ifparameters ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\iftrialsypesetting ...¹ \else ...² \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>

\ignorevalue {...} * NAME
\immediatesavetwopassdata {...} {...} {...} 1 NAME 2 NUMMER 3 CONTENT
\impartefloat [... ¹ ... _{OPT} ...] {...} {...} 1 inherits: \setezaimpartireafloat 2 BEFEHL 3 CONTENT
\impliedby
\implies
\in {... _{OPT} } {... _{OPT} } [...] 1 TEXT 2 TEXT 3 REFERENCE
\inalt {...} * CONTENT
\HIGH {...} * CONTENT instances:
\inclinat
\inclinataldin
\includemenu [...] * NAME
\includeversioninfo {...} * NAME
\increment *... * CSNAME
\incrementcounter [... ¹] [... _{OPT} ²] 1 NAME 2 NUMMER

$\backslash\text{incrementedcounter}$ [...] * NAME
$\backslash\text{incrementpagenumber}$
$\backslash\text{incrementsubpagenumber}$
$\backslash\text{incrementvalue}$ {...} * NAME
$\backslash\text{increment}$ cd:parentheses-1 * CSNAME NUMBER
$\backslash\text{indentation}$
$\backslash\text{infofont}$
$\backslash\text{infofontbold}$
$\backslash\text{inframed}$ [..., ¹ ... _{OPT} ...] {... ² } 1 inherits: \seteazainconjurat 2 CONTENT
$\backslash\text{inheritparameter}$ [... ¹] [... ²] [... ³] 1 TEXT 2 TEXT 3 KEY
$\backslash\text{inhibitblank}$
$\backslash\text{initializeboxstack}$ {...} * NAME
$\backslash\text{injos}$ [...] * DIMENSION
$\backslash\text{inlinebuffer}$ [... [*] ...] * BUFFER
$\backslash\text{inlinedbox}$ {...} * CONTENT
$\backslash\text{inlinemath}$ {...} * CONTENT
$\backslash\text{inlinemathematics}$ {...} * CONTENT

$\backslash\text{inlinemessage } \{...\}$ * TEXT
$\backslash\text{inlineordisplaymath } \{.^1.\} \{.^2.\}$ 1 CONTENT 2 CONTENT
$\backslash\text{inlinerange } [...]$ * REFERENCE
$\backslash\text{inlinie } \{.^1.\} [.^2.]$ <small>OPT</small> 1 TEXT 2 REFERENCE
$\backslash\text{inmaframed } [...,\dots.^1\dots] \{.^2.\}$ <small>OPT</small> 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT
$\backslash\text{innerflushshapebox}$
$\backslash\text{input } \{...\}$ * FILE
$\backslash\text{inputfilebarename}$
$\backslash\text{inputfilename}$
$\backslash\text{inputfilerealsuffix}$
$\backslash\text{inputfilesuffix}$
$\backslash\text{inputgivenfile } \{...\}$ * FILE
$\backslash\text{input } ...$ * FILE
$\backslash\text{insertpages } [...]\ [...,\dots.^2\dots] [...,\dots.^3\dots]$ <small>OPT</small> <small>OPT</small> 1 FILE 2 NUMMER 3 latime = DIMENSION n = NUMMER category = NAME
$\backslash\text{instalarelimba } [.^1.] [...,\dots.^2\dots]$ 1 NAME 2 inherits: $\backslash\text{setarelimba}$

<pre> \instalarelimba [...] [...] 1 NAME 2 SPRACHE </pre>
<pre> \installactionhandler {...} * NAME </pre>
<pre> \installactivecharacter ... * CHARACTER </pre>
<pre> \installanddefineactivecharacter ... {...} 1 CHARACTER 2 BEFEHL </pre>
<pre> \installattributestack \... * CSNAME </pre>
<pre> \installautocommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installautosetuphandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbasicautosetuphandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installbasicparameterhandler \... {...} 1 CSNAME 2 NAME </pre>
<pre> \installbottomframerenderer {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \installcommandhandler \... {...} \... 1 CSNAME 2 NAME 3 CSNAME </pre>
<pre> \installcorenamespace {...} * NAME </pre>

\installdefinehandler \¹... {²...} \³...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installdefinitionset \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdefinitionsetmember \¹... {²...} \³... {⁴...}

- 1 CSNAME
- 2 NAME
- 3 CSNAME
- 4 NAME

\installdirectcommandhandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectparameterhandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectparametersethandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectsetuphandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installdirectstyleandcolorhandler \¹... {²...}

- 1 CSNAME
- 2 NAME

\installframedautocommandhandler \¹... {²...} \³...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installframedcommandhandler \¹... {²...} \³...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installleftframerenderer {...} {...}

- 1 NAME
- 2 BEFEHL

\installnamespace {...}

- * NAME

\installoutputroutine \... {...}

- 1 CSNAME
- 2 BEFEHL

\installpagearrangement ... {...}

- 1 NAME
- 2 BEFEHL

\installparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installparameterhashhandler \... {...}

- 1 CSNAME
- 2 NAME

\installparametersethandler \... {...}

- 1 CSNAME
- 2 NAME

\installparentinjector \... {...}

- 1 CSNAME
- 2 NAME

\installrightframerenderer {...} {...}

- 1 NAME
- 2 BEFEHL

\installrootparameterhandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuphandler \... {...}

- 1 CSNAME
- 2 NAME

\installsetuponlycommandhandler \... {...}

- 1 CSNAME
- 2 NAME

\installshipoutmethod {...} {...}

- 1 NAME
- 2 BEFEHL

\installsimplecommandhandler \.^... {...} \.^...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installsimpleframedcommandhandler \.^... {...} \.^...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installstyleandcolorhandler \.^... {...}

- 1 CSNAME
- 2 NAME

\installswitchcommandhandler \.^... {...} \.^...

- 1 CSNAME
- 2 NAME
- 3 CSNAME

\installswitchsetuphandler \.^... {...}

- 1 CSNAME
- 2 NAME

\installtexdirective {...} {...} {...}

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

\installtextracker {...} {...} {...}

- 1 NAME
- 2 BEFEHL
- 3 BEFEHL

\installtopframerenderer {...} {...}

- 1 NAME
- 2 BEFEHL

\installunitsseparator {...} {...}

- 1 NAME
- 2 BEFEHL

<code>\installunitsspace {...} {...}</code> 1 NAME 2 BEFEHL
<code>\installversioninfo {...} {...}</code> 1 NAME 2 BEFEHL
<code>\integerrounding {...}</code> * NUMMER
<code>\intertext {...}</code> * TEXT
<code>\intins [...,¹...,_{OPT}...] {...}</code> 1 inherits: \setupstretched 2 TEXT
<code>\invokepagehandler {...} {...}</code> 1 normal niciunul NAME 2 CONTENT
<code>\istltdir ...</code> * TLT TRT
<code>\istrtdir ...</code> * TLT TRT
<code>\italic</code>
<code>\italicaldin</code>
<code>\italiccorrection</code>
<code>\itemtag [...,¹*,...]_{OPT}</code> * REFERENCE
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\jos {...}</code> * CONTENT
<code>\jossus [...¹...]_{OPT} {...} {...³...}</code> 1 stanga dreapta 2 CONTENT 3 CONTENT

$\backslash LOW \{...\}$ * CONTENT instances:
$\backslash Kap \{...\}$ * TEXT
$\backslash kap \{...\}$ * TEXT
$\backslash keeplinestogether \{...\}$ * NUMMER
$\backslash keepunwantedspaces$
$\backslash kerncharacters \left[\overset{1}{...} \right] \overset{2}{\{...\}}$ <div>1 NUMMER</div> <div>2 TEXT</div> <div>OPT</div>
$\backslash koreancirclenumerals \{...\}$ * NUMMER
$\backslash koreannumerals \{...\}$ * NUMMER
$\backslash koreannumeralsc \{...\}$ * NUMMER
$\backslash koreannumeralsp \{...\}$ * NUMMER
$\backslash koreanparentnumerals \{...\}$ * NUMMER
$\backslash LAMSTEX$
$\backslash LATEX$
$\backslash LamSTeX$
$\backslash LaTeX$
$\backslash Litera \{...\}$ * NUMMER
$\backslash Litere \{...\}$ * NUMMER

<code>\LUAJITTEX</code>
<code>\LUATEX</code>
<code>\LUNA {...}</code> * NUMMER
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaTeX</code>
<code>\la {...} {...} [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> <small>OPT</small> </div> 1 TEXT 2 TEXT 3 REFERENCE
<code>\LABELlimba</code> instances:
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances:
<code>\languageCharacters {...}</code> * NUMMER
<code>\languagecharacters {...}</code> * NUMMER
<code>\languagecharwidth {...}</code> * SPRACHE
<code>\lapagina [...]</code> * REFERENCE
<code>\lastcounter [...] [...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> </div> 1 NAME 2 NUMMER
<code>\lastcountervalue [...]</code> * NAME
<code>\lastdigit {...}</code> * NUMMER

<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [.¹.] [.².]</code> 1 NAME 2 NUMMER
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {.*}</code> * NUMMER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {.*}</code> * BEFEHL
<code>\layeredtext [..._{OPT}¹..._{OPT}²...] {.³.} {.⁴.}</code> 1 inherits: \setuplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {.¹.} {.².} {.³.} {.⁴.}</code> 1 NAME 2 NUMMER 3 NAME 4 CONTENT
<code>\lazysavetwopassdata {.¹.} {.².} {.³.}</code> 1 NAME 2 NUMMER 3 CONTENT

$\backslash\text{box} \overset{1}{...} \{\overset{2}{...}\}$ OPT 1 TEXT 2 CONTENT
$\backslash\text{leftbottombox} \{...\}$ * CONTENT
$\backslash\text{leftbox} \{...\}$ * CONTENT
$\backslash\text{lefthbox} \{...\}$ * CONTENT
$\backslash\text{leftLABELtext} \{...\}$ * KEY instances:
$\backslash\text{leftline} \{...\}$ * CONTENT
$\backslash\text{lefttorrighthbox} \overset{1}{...} \{\overset{2}{...}\}$ OPT 1 TEXT 2 CONTENT
$\backslash\text{lefttorrightvbox} \overset{1}{...} \{\overset{2}{...}\}$ OPT 1 TEXT 2 CONTENT
$\backslash\text{lefttorrightvtop} \overset{1}{...} \{\overset{2}{...}\}$ OPT 1 TEXT 2 CONTENT
$\backslash\text{leftskipadaption}$
$\backslash\text{leftsubguillemot}$
$\backslash\text{lefttopbox} \{...\}$ * CONTENT
$\backslash\text{lefttright}$
$\backslash\text{lefttorrighthbox} \overset{1}{...} \{\overset{2}{...}\}$ OPT 1 TEXT 2 CONTENT

$\backslash\text{lefttorightvbox}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{lefttorightvtop}$ $\overset{1}{\dots}$ $\{\overset{2}{\dots}\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{letbeundefined}$ $\{.*\}$ * NAME
$\backslash\text{letcatcodecommand}$ $\overset{1}{\dots}$ $\overset{2}{\dots}$ $\overset{3}{\dots}$ 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
$\backslash\text{letcscsname}$ $\overset{1}{\dots}$ $\backslash\text{csname}$ $\overset{2}{\dots}$ $\backslash\text{endcsname}$ 1 CSNAME 2 NAME
$\backslash\text{letcsnamecs}$ $\backslash\text{csname}$ $\overset{1}{\dots}$ $\backslash\text{endcsname}$ $\overset{2}{\dots}$ 1 NAME 2 CSNAME
$\backslash\text{letcsnamecsname}$ $\backslash\text{csname}$ $\overset{1}{\dots}$ $\backslash\text{endcsname}$ $\backslash\text{csname}$ $\overset{2}{\dots}$ $\backslash\text{endcsname}$ 1 NAME 2 NAME
$\backslash\text{letdummyparameter}$ $\{\overset{1}{\dots}\}$ $\overset{2}{\dots}$ 1 KEY 2 CSNAME
$\backslash\text{letempty}$ $\overset{*}{\dots}$ * CSNAME
$\backslash\text{letgvalue}$ $\{\overset{1}{\dots}\}$ $\overset{2}{\dots}$ 1 NAME 2 CSNAME
$\backslash\text{letgvalueempty}$ $\{.*\}$ * NAME
$\backslash\text{letgvalurelax}$ $\{.*\}$ * NAME
$\backslash\text{letterampersand}$
$\backslash\text{letterat}$

<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>
<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\letteregroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> $[\overset{1}{...}] \{\overset{2}{...}\}$ <small>OPT</small> 1 NUMMER 2 TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>

<code>\letvalue {¹.} \².</code> 1 NAME 2 CSNAME
<code>\letvalueempty {.*}</code> * NAME
<code>\letvaluerelax {.*}</code> * NAME
<code>\lfence {.*}</code> * CHARACTER
<code>\lhbox {.*}</code> * CONTENT
<code>\limba [...]</code> * SPRACHE
<code>\limbapincipala [...]</code> * SPRACHE
<code>\LANGUAGE</code>
<code>\limitatelines {¹.} {².} {³.}</code> 1 NUMMER 2 BEFEHL 3 TEXT
<code>\limitatetext {¹.} {².} {³.}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limitatetext {¹.} {...²,...} {³.}</code> 1 TEXT 2 [-+]DIMENSION 3 BEFEHL
<code>\limtatefirstline {¹.} {².} {³.}</code> 1 TEXT 2 DIMENSION 3 BEFEHL
<code>\LINENOTE {.*}</code> * TEXT instances:

<p><code>\linespanningtext {¹...} {²...} {³...}</code></p> <p>1 TEXT</p> <p>2 DIMENSION</p> <p>3 FONT</p>
<p><code>\linie {.*.}</code></p> <p>* CONTENT</p>
<p><code>\linieneagra [...[*]...]</code> OPT</p> <p>* inherits: \seteazaliniinegre</p>
<p><code>\liniepeste {.*.}</code></p> <p>* CONTENT</p>
<p><code>\liniesubtire</code></p>
<p><code>\linieumplere [...[*]...]</code></p> <p>* inherits: \seteazaliniiumplere</p>
<p><code>\liniinegre [...[*]...]</code> OPT</p> <p>* inherits: \seteazaliniinegre</p>
<p><code>\liniipeste {.*.}</code></p> <p>* CONTENT</p>
<p><code>\liniisubtiri [...[*]...]</code> OPT</p> <p>* inherits: \seteazalinesubtire</p>
<p><code>\listcitation [...¹...²...] [...]</code> OPT</p> <p>1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx</p> <p>2 REFERENCE</p>
<p><code>\listcitation [¹...] [²...]</code> OPT</p> <p>1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear</p> <p>2 REFERENCE</p>
<p><code>\listcitation [...¹...²...] [...²...]</code></p> <p>1 referinta = REFERENCE alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authorityyear inainte = BEFEHL dupa = BEFEHL stanga = BEFEHL dreapta = BEFEHL inherits: \setupbtx</p> <p>2 KEY = VALUE</p>

`\listcite [...,\1...,...]\2...]`
OPT

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
2 REFERENCE

`\listcite [...]\1...]\2...`
OPT

1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
2 REFERENCE

`\listcite [...,\1...,...]\2...,...]`

1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
2 KEY = VALUE

`\listnamespaces`

`\litera {...}`

* NUMMER

`\litere {...}`

* NUMMER

`\llap {...}`

* CONTENT

`\loadanyfile [...]`

* FILE

`\loadanyfileonce [...]`

* FILE

`\loadbtxdefinitionfile [...]`

* FILE

`\loadbtxreplacementfile [...]`

* FILE

`\loadcldfile [...]`

* FILE

`\loadcldfileonce [...]`

* FILE

\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [¹ ...] [² ...] 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localframed [¹] [..., ² ..., ³ ...] {...} <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 NAME 2 inherits: \seteazainconjurat 3 CONTENT
\localframedwithsettings [¹] [..., ² ..., ³ ...] {...} 1 NAME 2 inherits: \seteazainconjurat 3 CONTENT
\localhsize
\localpopbox ... * CSNAME NUMBER
\localpopmacro \... * CSNAME
\localpushbox ... * CSNAME NUMBER
\localpushmacro \... * CSNAME
\localundefine {...} * NAME

<code>\locatedfilepath</code>
<code>\locatefilepath {...}</code> * FILE
<code>\locfilename {...}</code> * FILE
<code>\lomihi {.¹.} {.².} {.³.}</code> 1 CONTENT 2 CONTENT 3 CONTENT
<code>\lowerbox {.¹.} \.². {.³.}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\lowercased {...}</code> * TEXT
<code>\lowercasestring .¹. \to \.².</code> 1 TEXT 2 CSNAME
<code>\lowerlefthdoubleninequote</code>
<code>\lowerleftsingleninequote</code>
<code>\lowerrighthdoubleninequote</code>
<code>\lowerrightsingleninequote</code>
<code>\LOWHIGH [.¹.] {.².} {.³.}</code> <small>OPT</small> 1 stanga dreapta 2 CONTENT 3 CONTENT
<code>\LOWMIDHIGH {.¹.} {.².} {.³.}</code> 1 CONTENT 2 CONTENT 3 CONTENT

$\backslash\text{lrtb}\text{box}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT
$\backslash\text{top}$ $\overset{1}{.}\dots\overset{2}{.}\{.^3.\}$ <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{luacode}$ $\{.^*.\}$ * BEFEHL
$\backslash\text{luaconditional}$ $\backslash.^*.$ * CSNAME
$\backslash\text{luaenvironment}$ \dots * FILE
$\backslash\text{luaexpanded}$ $\{.^*.\}$ * BEFEHL
$\backslash\text{luafunction}$ $\{.^*.\}$ * BEFEHL
$\backslash\text{lua}\text{jit}\text{TeX}$
$\backslash\text{luamajorversion}$
$\backslash\text{luaminorversion}$
$\backslash\text{luaparameterset}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 CONTENT
$\backslash\text{luasetup}$ $\{.^*.\}$ * NAME
$\backslash\text{lua}\text{TeX}$
$\backslash\text{lua}\text{version}$
$\backslash\text{luna}$ $\{.^*.\}$ * NUMMER
$\backslash\text{lungimelista}$

<code>\METAFONT</code>
<code>\METAFUN</code>
<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTHLONG {...}</code> * NUMBER
<code>\MONTHSHORT {...}</code> * NUMBER
<code>\MPanchor {...}</code> * NAME
<code>\MPbetex {...}</code> * NAME
<code>\MPc {...}</code> * NAME
<code>\MPcode {...¹} {...²}</code> <div>OPT</div> 1 NAME 2 CONTENT
<code>\MPcolor {...}</code> * COLOR
<code>\MPcoloronly {...}</code> * COLOR
<code>\MPcolumn {...}</code> * NAME

<code>\MPd {...}</code> * NAME
<code>\MPdrawing {...}</code> * CONTENT
<code>\MPfontsizehskip {...}</code> * FONT
<code>\MPgetmultipars {...} {...}</code> 1 NAME 2 NAME
<code>\MPgetmultishape {...} {...}</code> 1 NAME 2 NAME
<code>\MPgetposboxes {...,¹...} {...²}</code> 1 NAME 2 NAME
<code>\MPh {...}</code> * NAME
<code>\MPII</code>
<code>\MPIV</code>
<code>\MPinclusions [¹...] {²...} {³...}</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 + 2 NAME 3 CONTENT
<code>\MPleftskip {...}</code> * NAME
<code>\MPll {...}</code> * NAME
<code>\MPlr {...}</code> * NAME
<code>\MPls {...}</code> * NAME
<code>\MPmenubuttons {...}</code> * NAME

<code>\MPn {...}</code> * NAME
<code>\MPoptions {...}</code> * COLOR
<code>\MPoverlayanchor {...}</code> * NAME
<code>\MPp {...}</code> * NAME
<code>\MPpage {...}</code> * NAME
<code>\MPpardata {...}</code> * NAME
<code>\MPplus {...} {...} {...}</code> 1 NAME 2 NUMMER 3 CONTENT
<code>\MPpos {...}</code> * NAME
<code>\MPpositiongraphic {...} {...,²...}</code> <div style="text-align: center; margin-left: 150px;"><small>OPT</small></div> 1 NAME 2 KEY = VALUE
<code>\MPposset {...}</code> * NAME
<code>\MPr {...}</code> * NAME
<code>\MPrawvar {...} {...}</code> 1 NAME 2 KEY
<code>\MPregion {...}</code> * NAME
<code>\MPrest {...} {...}</code> 1 NAME 2 CONTENT

\MPrightskip {...} * NAME
\MPrs {...} * NAME
\MPstring {...} * NAME
\MPtext {...} * NAME
\MPtransparency {...} * COLOR
\MPul {...} * NAME
\MPur {...} * NAME
\MPVI
\MPv {... ¹ } {... ² } {... ³ } 1 NAME 2 NUMMER 3 CONTENT
\MPvar {...} * KEY
\MPvariable {...} * KEY
\MPvv {... ¹ } {... ² } 1 NAME 2 CONTENT
\MPw {...} * NAME
\MPwhd {...} * NAME
\MPx {...} * NAME

\backslash MPxy {...} * NAME
\backslash MPxywhd {...} * NAME
\backslash MPy {...} * NAME
\backslash m [...] ¹ {...} <small>OPT</small> 1 NAME 2 CONTENT
\backslash maframed [...,...] ¹ {...} <small>OPT</small> 1 inherits: \setupmathframed 2 CONTENT
\backslash makecharacteractive ... * CHARACTER
\backslash makerawcommalist [...] ¹ ,... \^2... 1 BEFEHL 2 CSNAME
\backslash makestrutofbox ... * CSNAME NUMMER
\backslash mapfontsize [...] ¹ [...] ² 1 DIMENSION 2 DIMENSION
\backslash marcaje (...) ¹ ,... (...) ² ,... [...] ³ 1 POSITION 2 POSITION 3 REFERENCE
\backslash mare ... * CHARACTER
\backslash margindata [...] ¹ [...,...] ² [...,...] ³ {...} ⁴ <small>OPT</small> <small>OPT</small> 1 NAME 2 referinta = REFERENCE inherits: \setupmargindata 3 inherits: \setupmarginframed 4 CONTENT

\backslash MARGINDATA [..., $\overset{1}{=}$...,...] [..., $\overset{2}{=}$...,...] {...} 1 referinta = REFERENCE inherits: \setupmargindata 2 inherits: \setupmarginframed 3 CONTENT instances:
\backslash markcontent [...] $\overset{1}{}$ {...} 1 reset tot NAME 2 CONTENT
\backslash markinjector [...*] * NAME
\backslash mat {...*} * CONTENT
\backslash matematica [...] $\overset{1}{}$ {...} 1 NAME 2 CONTENT
\backslash math [...] $\overset{1}{}$ {...} 1 NAME 2 CONTENT
\backslash mathbf
\backslash mathbi
\backslash mathblackboard
\backslash mathbs
\backslash mathcommand {...*} * NAME
\backslash MATHCOMMAND {...} $\overset{1}{}$ {...} 1 TEXT 2 TEXT
\backslash mathdefault
\backslash MATHDOUBLEEXTENSIBLE {...*} * TEXT

$\backslash\text{MATHEXTENSIBLE}$ [¹ ...] { ² ...} { ³ ...} <small>OPT OPT OPT</small> 1 reverse matematica text chemistry 2 TEXT 3 TEXT
$\backslash\text{mathfraktur}$
$\backslash\text{MATHFRAMED}$ [... ¹ ...] { ² ...} <small>OPT</small> 1 inherits: \setupmathframed 2 CONTENT instances: mframed inmframed mcframed
$\backslash\text{mathfunction}$ {.*.} * CONTENT
$\backslash\text{mathit}$
$\backslash\text{mathitalic}$
$\backslash\text{mathop}$ {.*.} * CONTENT
$\backslash\text{MATHORNAMENT}$ {.*.} * CONTENT
$\backslash\text{MATHOVEREXTENSIBLE}$ {.*.} * TEXT
$\backslash\text{MATHOVERTEXTEXTENSIBLE}$ { ¹ ...} { ² ...} 1 TEXT 2 TEXT
$\backslash\text{MATHRADICAL}$ [¹ ...] { ² ...} <small>OPT</small> 1 TEXT 2 CONTENT
$\backslash\text{mathrm}$
$\backslash\text{mathscript}$
$\backslash\text{mathsl}$
$\backslash\text{mathss}$
$\backslash\text{mathtext}$ ¹ ... { ² ...} <small>OPT</small> 1 TEXT 2 TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

1	TEXT
2	TEXT

```
1  TEXT
2  TEXT
```

1	NAME
2	TEXT
3	TEXT
4	TEXT

1	NAME
2	TEXT
3	TEXT
4	TEXT

* TEXT

1	TEXT
2	TEXT

165

$\backslash\mathrm{mediu} \dots$ \ast FILE
$\backslash\mathrm{medskip}$
$\backslash\mathrm{medspace}$
$\backslash\mathrm{menuinteractiune} [\dots] [\dots,\dots,\overset{2}{\dots},\dots]$ $\phantom{\backslash\mathrm{menuinteractiune} [\dots] [\dots,\dots,\dots,\dots]} \text{OPT}$ 1 NAME 2 inherits: $\backslash\mathrm{seteazamenuinteractiune}$
$\backslash\mathrm{mequal} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\phantom{\backslash\mathrm{mequal} \{\dots\} \{\dots\}} \text{OPT} \quad \text{OPT}$ 1 TEXT 2 TEXT
$\backslash\mathrm{message} \{\dots\}$ \ast TEXT
$\backslash\mathrm{metaTeX}$
$\backslash\mathrm{mfence} \{\dots\}$ \ast CHARACTER
$\backslash\mathrm{mfunction} \{\dots\}$ \ast CONTENT
$\backslash\mathrm{mfunctionlabeltext} \{\dots\}$ \ast NAME
$\backslash\mathrm{mhbox} \{\dots\}$ \ast CONTENT
$\backslash\mathrm{mhookleftarrow} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\phantom{\backslash\mathrm{mhookleftarrow} \{\dots\} \{\dots\}} \text{OPT} \quad \text{OPT}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mhookrightarrow} \{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ $\phantom{\backslash\mathrm{mhookrightarrow} \{\dots\} \{\dots\}} \text{OPT} \quad \text{OPT}$ 1 TEXT 2 TEXT
$\backslash\mathrm{mic}$
$\backslash\mathrm{micaldin}$
$\backslash\mathrm{micaldininclinat}$
$\backslash\mathrm{micinclinat}$
$\backslash\mathrm{micinclinataldin}$

<code>\micriticaldin</code>
<code>\micnormal</code>
<code>\mictype</code>
<code>\middlealigned {...}</code> * CONTENT
<code>\middlebox {...}</code> * CONTENT
<code>\midhbox {...}</code> * CONTENT
<code>\minicitat [...]</code> <div style="text-align: center;"><small>¹</small> OPT</div> 1 SPRACHE 2 CONTENT
<code>\minimalhbox ... [...]</code> <div style="text-align: center;"><small>¹</small> OPT</div> 1 TEXT 2 CONTENT
<code>\mixedcaps {...}</code> * TEXT
<code>\mkvibuffer [...]</code> <div style="text-align: center;"><small>¹</small> OPT</div> * BUFFER
<code>\mLeftarrow {...} [...]</code> <div style="text-align: center;"><small>¹</small> OPT <small>²</small> OPT</div> 1 TEXT 2 TEXT
<code>\mLeftrightarrow {...} [...]</code> <div style="text-align: center;"><small>¹</small> OPT <small>²</small> OPT</div> 1 TEXT 2 TEXT
<code>\mleftarrow {...} [...]</code> <div style="text-align: center;"><small>¹</small> OPT <small>²</small> OPT</div> 1 TEXT 2 TEXT
<code>\mleftharpoondown {...} [...]</code> <div style="text-align: center;"><small>¹</small> OPT <small>²</small> OPT</div> 1 TEXT 2 TEXT
<code>\mleftharpoonup {...} [...]</code> <div style="text-align: center;"><small>¹</small> OPT <small>²</small> OPT</div> 1 TEXT 2 TEXT

\leftrightsquigarrow $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\leftrightharpoons $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mapsto $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\moduleparameter $\{...\}^{1}\{...\}^{2}$ 1 FILE 2 KEY
\molecule $\{...\}^{*}$ * CONTENT
\mono
\monoaldin
\mononormal
\monthlong $\{...\}^{*}$ * NUMMER
\monthshort $\{...\}^{*}$ * NUMMER
\mprandomnumber
\mrightarrow $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrel $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrightarrow $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT
\mrightharpoondown $\{...\}^{1}\{...\}^{2}$ <small>OPT OPT</small> 1 TEXT 2 TEXT

$\backslash\mathrm{mrightharpoonup} \overset{1}{\{...\}} \overset{2}{\{...\}}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\mathrm{mrightharpoonleft} \overset{1}{\{...\}} \overset{2}{\{...\}}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\mathrm{mrightharpoonoverleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\mathrm{mtext} \{...\}$ <p>* CONTENT</p>
$\backslash\mathrm{mtriplelrel} \overset{1}{\{...\}} \overset{2}{\{...\}}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\mathrm{mtwoheadleftarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\mathrm{mtwoheadrightarrow} \overset{1}{\{...\}} \overset{2}{\{...\}}$ <p>1 TEXT</p> <p>2 TEXT</p>
$\backslash\mathrm{NormalizeFontHeight} \backslash^{1}\{...\} \overset{2}{\{...\}} \overset{3}{\{...\}} \overset{4}{\{...\}}$ <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 DIMENSION</p> <p>4 FONT</p>
$\backslash\mathrm{NormalizeFontWidth} \backslash^{1}\{...\} \overset{2}{\{...\}} \overset{3}{\{...\}} \overset{4}{\{...\}}$ <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 DIMENSION</p> <p>4 FONT</p>
$\backslash\mathrm{NormalizeTextHeight} \overset{1}{\{...\}} \overset{2}{\{...\}} \overset{3}{\{...\}}$ <p>1 FONT</p> <p>2 DIMENSION</p> <p>3 TEXT</p>

<code>\NormalizeTextWidth {...} {...} {...}</code> 1 FONT 2 DIMENSION 3 TEXT
<code>\Numere {...}</code> * NUMMER
<code>\Numereromane {...}</code> * NUMMER
<code>\namedheadnumber {...}</code> * ABSCHNITT
<code>\namedstructureheadlocation {...}</code> * ABSCHNITT
<code>\namedstructureuservariable {...} {...}</code> 1 ABSCHNITT 2 KEY
<code>\namedstructurevariable {...} {...}</code> 1 ABSCHNITT 2 KEY
<code>\namedtaggedlabeltexts {...} {...} {...} {...} {...}</code> 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
<code>\naturalhbox ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalhpack ...¹ {...²}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalvbox ...¹ {...}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT
<code>\naturalvcenter ...¹ {...²}</code> <div style="text-align: center; margin-left: 100px;"><small>OPT</small></div> 1 TEXT 2 CONTENT

<p><code>\naturalvpack</code> $\overset{1}{\dots} \{\overset{2}{\dots}\}$ <small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalvtop</code> $\overset{1}{\dots} \{\overset{2}{\dots}\}$ <small>OPT</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\naturalwd</code> \dots</p> <p>* CSNAME NUMBER</p>
<code>\necunoscut</code>
<p><code>\negatecolorbox</code> \dots</p> <p>* CSNAME NUMBER</p>
<p><code>\negated</code> $\{\dots\}$</p> <p>* TEXT</p>
<code>\negthinspace</code>
<p><code>\newattribute</code> \dots</p> <p>* CSNAME</p>
<p><code>\newcatcodetable</code> \dots</p> <p>* CSNAME</p>
<p><code>\newcounter</code> \dots</p> <p>* CSNAME</p>
<p><code>\newevery</code> $\overset{1}{\dots} \overset{2}{\dots}$</p> <p>1 CSNAME</p> <p>2 CSNAME</p>
<code>\newfrenchspacing</code>
<p><code>\newmode</code> $\{\dots\}$</p> <p>* NAME</p>
<p><code>\newsignal</code> \dots</p> <p>* CSNAME</p>
<p><code>\newsystemmode</code> $\{\dots\}$</p> <p>* NAME</p>
<code>\nextbox</code>
<code>\nextboxdp</code>

<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...]</code> ¹ <code>[...]</code> ² <small>OPT</small> 1 NAME 2 NUMMER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\urmatoru1PARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...]</code> ¹ <code>[...]</code> ² 1 NAME 2 NUMMER
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nobar {...}</code> * CONTENT
<code>\nocitation [...]</code> * REFERENCE
<code>\nocitation {...}</code> * REFERENCE
<code>\nocite [...]</code> * REFERENCE
<code>\nocite {...}</code> * REFERENCE

<code>\nodetostring \¹... {²...}</code> 1 CSNAME 2 CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nokap {.*.}</code> * TEXT
<code>\nonfrenchspacing</code>
<code>\nonmathematics {.*.}</code> * CONTENT
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,¹...,²...] {.*.}</code> 1 inherits: \seteazainconjurat 2 CONTENT
<code>\normalizebodyfontsize \¹... {²...}</code> 1 CSNAME 2 DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT
<code>\normalizefontheight \¹... {²...} {³...} {⁴...}</code> 1 CSNAME 2 TEXT 3 DIMENSION 4 FONT

`\normalizefontline \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizefontwidth \1... {\2...} {\3...} {\4...}`

- 1 CSNAME
- 2 TEXT
- 3 DIMENSION
- 4 FONT

`\normalizetextdepth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextheight {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextline {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normalizetextwidth {\1...} {\2...} {\3...}`

- 1 FONT
- 2 DIMENSION
- 3 TEXT

`\normaltypeface`

`\nota [1...] [2...]`
OPT

- 1 NAME
- 2 REFERENCE

`\NOTE [1...,...]2...`
OPT

- 1 REFERENCE
- 2 TEXT

instances:

\NOTE [...,..^{*}..,..^{*}..]

```
*   titlu      = TEXT
    semncarte  = TEXT
    lista      = TEXT
    referinta  = REFERENCE
```

```
instances:
```

`\notesymbol [...1...] [...2...]`
OPT

1 NAME

2 REFERENCE

\notragged

$$\backslash ntimes \{.^1..\} \{.^2..\}$$

1 TEXT

2 NUMMER

`\numarformula [...,*,...]`
OPT

* REFERENCE

\numarpagina

`\numartitlu [...1...] [...2...]`
OPT

1 ABSCHNITT

2 precedent curent urmatorul primul ultim

\numartitlucurent

$$\backslash \text{numberofpoints} \{...\}$$

* DIMENSION

$$\backslash \mathrm{numere} \{.\ast.\}$$

* NUMMER

`\numereromane {...}`

* NUMMER

\obeydepth

\objectdepth

\objectheight

\objectmargin

\objectwidth

$$\backslash\text{obox} \{.\!.\!.\}$$

* CONTENT

$\backslash\text{offset}$ [$\dots,\dots,\overset{1}{=}\dots,\dots$] $\{\dots\}$ <small>OPT</small> 1 inherits: \setupoffset 2 CONTENT
$\backslash\text{offsetbox}$ [$\dots,\dots,\overset{1}{=}\dots,\dots$] $\backslash\overset{2}{\dots}$ $\{\overset{3}{\dots}\}$ <small>OPT</small> 1 inherits: \setupoffsetbox 2 CSNAME 3 CONTENT
$\backslash\text{oline}$ [\dots] * REFERENCE
$\backslash\text{onedigitrounding}$ $\{\dots\}$ * NUMMER
$\backslash\text{ordinaldaynumber}$ $\{\dots\}$ * NUMMER
$\backslash\text{ordinalstr}$ $\{\dots\}$ * TEXT
$\backslash\text{ornamenttext}$ [$\dots,\dots,\overset{1}{=}\dots,\dots$] [$\dots,\dots,\overset{2}{=}\dots,\dots$] $\{\overset{3}{\dots}\}$ $\{\overset{4}{\dots}\}$ <small>OPT</small> 1 alternativ = a b inherits: \setupcollector 2 stil = STYLE BEFEHL culoare = COLOR inherits: \seteazainconjurat 3 TEXT 4 CONTENT
$\backslash\text{ornamenttext}$ [$\overset{1}{\dots}$] $\{\overset{2}{\dots}\}$ $\{\overset{3}{\dots}\}$ 1 NAME 2 TEXT 3 CONTENT
$\backslash\text{ornamenttext}$ [$\dots,\dots,\overset{1}{=}\dots,\dots$] [$\dots,\dots,\overset{2}{=}\dots,\dots$] $\{\overset{3}{\dots}\}$ $\{\overset{4}{\dots}\}$ <small>OPT</small> 1 alternativ = a b inherits: \setuplayer 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
$\backslash\text{ORNAMENT}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ 1 TEXT 2 CONTENT
$\backslash\text{outputfilename}$

$\backslash\text{outputstreambox}$ [...] * NAME
$\backslash\text{outputstreamcopy}$ [...] * NAME
$\backslash\text{outputstreamunvbox}$ [...] * NAME
$\backslash\text{outputstreamunvcopy}$ [...] * NAME
$\backslash\text{over}$ [...] * REFERENCE
$\backslash\text{overbartext}$ { ¹ .} { ² .} 1 TEXT 2 TEXT
$\backslash\text{overbarunderbar}$ {...} * TEXT
$\backslash\text{overbrace}$ {...} * TEXT
$\backslash\text{overbracetext}$ { ¹ .} { ² .} 1 TEXT 2 TEXT
$\backslash\text{overbraceunderbrace}$ {...} * TEXT
$\backslash\text{overbracket}$ {...} * TEXT
$\backslash\text{overbrackettext}$ { ¹ .} { ² .} 1 TEXT 2 TEXT
$\backslash\text{overbracketunderbracket}$ {...} * TEXT
$\backslash\text{overlaybutton}$ [...] * REFERENCE
$\backslash\text{overlaybutton}$ {...} * REFERENCE

<code>\overlaycolor</code>
<code>\overlaydepth</code>
<code>\overlayfigure {...}</code> * FILE
<code>\overlayheight</code>
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [.¹..] [.²..]</code> 1 REFERENCE 2 REFERENCE
<code>\overlaywidth</code>
<code>\overleftarrow {...}</code> * TEXT
<code>\overleftharpoontdown {...}</code> * TEXT
<code>\overleftharpoonup {...}</code> * TEXT
<code>\overleftrightarrow {...}</code> * TEXT
<code>\overloaderror</code>
<code>\overparent {...}</code> * TEXT
<code>\overparenttext {.¹..} {.²..}</code> 1 TEXT 2 TEXT
<code>\overparentunderparent {...}</code> * TEXT
<code>\overrightarrow {...}</code> * TEXT

$\backslash\overrightharpoonpoondown \{...\}$ * TEXT
$\backslash\overrightharpoonup \{...\}$ * TEXT
$\backslashoverset {^{.1.}} {^{.2.}}$ 1 TEXT 2 TEXT
$\backslashovertwoheadleftarrow \{...\}$ * TEXT
$\backslashovertwoheadrightarrow \{...\}$ * TEXT
$\backslashPDFcolor \{...\}$ * NAME
\backslashPDFETEX
\backslashPDFTEX
\backslashPCTEX
\backslashPiCTeX
$\backslashPointsToBigPoints \{...\} \backslash^{.2.}$ 1 DIMENSION 2 CSNAME
$\backslashPointsToReal \{...\} \backslash^{.2.}$ 1 DIMENSION 2 CSNAME
$\backslashPointsToWholeBigPoints \{...\} \backslash^{.2.}$ 1 DIMENSION 2 CSNAME
\backslashPPCHTEX
\backslashPPCHTeX
\backslashPRAGMA
$\backslashPtToCm \{...\}$ * DIMENSION

<p><code>\pagearea</code> [¹...] [²...] [³...] <small>OPT OPT</small></p> <p>1 sus antet text subsol subsol</p> <p>2 text margine bordura</p> <p>3 stanga dreapta lefttext middletext righttext</p>
<p><code>\pagebreak</code> [...,*...] <small>OPT</small></p> <p>* gol antet subsol dummy incadrat NUMMER +NUMMER implicit reset dezactivat da nu marcaj blank preferinta preferintamare stanga dreapta par impar cvadрупul ultim ultimapagina start stop NAME</p>
<p><code>\pagefigure</code> [¹...] [...,²...,...] <small>OPT</small></p> <p>1 FILE</p> <p>2 inherits: \setupexternalfigure</p>
<p><code>\pagegridspanwidth</code> {.*.}</p> <p>* NUMMER</p>
<p><code>\pageinjection</code> [¹...] [...,²...,...] <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 KEY = VALUE</p>
<p><code>\pageinjection</code> [...,¹...,...] [...,²...,...] <small>OPT OPT</small></p> <p>1 inherits: \setuppageinjection</p> <p>2 KEY = VALUE</p>
<p><code>\pagestaterealpage</code> {¹.} {².}</p> <p>1 NAME</p> <p>2 NAME NUMMER</p>
<p><code>\pagina</code> [...,*...] <small>OPT</small></p> <p>* inherits: \pagebreak</p>
<p><code>\paletsize</code></p>
<p><code>\PARAGRAPHS</code></p>
<p><code>\pastreazablocuri</code> [...,¹...] [...,²...,...] <small>OPT</small></p> <p>1 NAME</p> <p>2 + -</p>
<p><code>\pdfactualtext</code> {¹.} {².}</p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendactualtext</code> {¹.} {².}</p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><code>\pdfbackendcurrentresources</code></p>

<p><code>\pdfbackendsetcatalog {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetcolorspace {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsettextgstate {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetinfo {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetname {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpageresource {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpagesattribute {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetpattern {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfbackendsetshade {...} {...}</code></p> <p>1 NAME</p> <p>2 TEXT</p>
<p><code>\pdfcolor {...}</code></p> <p>* NAME</p>
<p><code>\pdfeTeX</code></p>
<p><code>\pdfTeX</code></p>

<p><code>\pelung {...}</code></p> <p>* NAME</p>
<p><code>\percent</code></p>
<p><code>\percentdimen {...} {...}</code></p> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMMER</p>
<p><code>\permitcaretescape</code></p>
<p><code>\permitcircumflexescape</code></p>
<p><code>\permitspacesbetweengroups</code></p>
<p><code>\persiandecimals {...}</code></p> <p>* NUMMER</p>
<p><code>\persiannumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\phantom {...}</code></p> <p>* CONTENT</p>
<p><code>\phantombox [...,...[*]...,...]</code></p> <p>* latime = DIMENSION</p> <p>inalttime = DIMENSION</p> <p>inaltime = DIMENSION</p>
<p><code>\pickupgroupedcommand {...} {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p>
<p><code>\placeattachments</code></p>
<p><code>\placebtxrendering [...]_{OPT} [...,...²...,...]_{OPT}</code></p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p><code>\placecitation [...]</code></p> <p>* REFERENCE</p>
<p><code>\placecomments</code></p>
<p><code>\placecurrentformulanumber</code></p>
<p><code>\placedbox {...}</code></p> <p>* CONTENT</p>

<p><code>\placefloat</code> [¹...] [²...,...] [³...,...] {⁴...} {⁵...}</p> <p style="text-align: center;">OPT OPT</p> <p>1 SINGULAR</p> <p>2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\placefloatwithsetups</code> [¹...] [²...,...] [³...,...] {⁴...} {⁵...}</p> <p style="text-align: center;">OPT OPT</p> <p>1 NAME</p> <p>2 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>3 REFERENCE</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p><code>\puneFLOAT</code> [¹...,...] [²...,...] {³...} {⁴...}</p> <p style="text-align: center;">OPT OPT</p> <p>1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p> <p>4 CONTENT</p> <p>instances: chemical figure table intermezzo graphic</p>
<p><code>\placeframed</code> [¹...] [²...,..._{OPT}...] {³...}</p> <p>1 NAME</p> <p>2 inherits: \setezainconjurat</p> <p>3 CONTENT</p>
<p><code>\placeheadnumber</code> [...]</p> <p>* ABSCHNITT</p>
<p><code>\placeheadtext</code> [...]</p> <p>* ABSCHNITT</p>
<p><code>\placehelp</code></p>
<p><code>\placeinitial</code> [¹...,..._{OPT}]</p> <p>* NAME</p>
<p><code>\placelayer</code> [...]</p> <p>* NAME</p>

<p>\placelayeredtext [¹...] [²..._{OPT}...] [³..._{OPT}...] {⁴...} {⁵...}</p> <p>1 NAME</p> <p>2 inherits: \setuplayer</p> <p>3 inherits: \setuplayeredtext</p> <p>4 TEXT</p> <p>5 CONTENT</p>
<p>\placelistofFLOATS [[*]..._{OPT}...]</p> <p>* inherits: \seteazalista</p>
<p>\placelistofpublications [¹...] [²..._{OPT}...]</p> <p>1 NAME</p> <p>2 inherits: \setupbtxrendering</p>
<p>\placelistofsorts [¹...] [²..._{OPT}...]</p> <p>1 SINGULAR</p> <p>2 inherits: \seteazasortare</p>
<p>\placelistofSORTS [[*]..._{OPT}...]</p> <p>* inherits: \seteazasortare</p> <p>instances:</p>
<p>\placelistofsynonyms [¹...] [²..._{OPT}...]</p> <p>1 SINGULAR</p> <p>2 inherits: \seteazasinonime</p>
<p>\placelistofSYNONYMS [[*]..._{OPT}...]</p> <p>* inherits: \seteazasinonime</p> <p>instances:</p>
<p>\placelocalnotes [¹...] [²..._{OPT}...]</p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p>\placement [¹...] [²..._{OPT}...] {³...}</p> <p>1 NAME</p> <p>2 inherits: \setupplacement</p> <p>3 CONTENT</p>
<p>\PLACEMENT [¹..._{OPT}...] {²...}</p> <p>1 inherits: \setupplacement</p> <p>2 CONTENT</p>
<p>\placenamedfloat [¹...] [²...]</p> <p>1 NAME</p> <p>2 REFERENCE</p>

<p>\placenedformula [...¹,...] {².}</p> <p>1 + - REFERENCE</p> <p>2 TEXT</p>
<p>\placenames [...¹,...] [...².,...]</p> <p>1 NAME</p> <p>2 inherits: \setupnote</p>
<p>\placepairedbox [...¹] [...².,...] {³.} {⁴.}</p> <p>1 NAME</p> <p>2 inherits: \setuppairedbox</p> <p>3 CONTENT</p> <p>4 TEXT</p>
<p>\punePAIREDBOX [...¹.,...] {².} {³.}</p> <p>1 inherits: \setuppairedbox</p> <p>2 CONTENT</p> <p>3 TEXT</p> <p>instances:</p>
<p>\placeparallel [...¹] [...²,...] [...³.,...]</p> <p>1 NAME</p> <p>2 NAME</p> <p>3 inherits: \setupparallel</p>
<p>\placerawlist [...¹] [...².,...]</p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>
<p>\placereadingwindow [...¹] [...².]</p> <p>1 NAME</p> <p>2 NAME</p>
<p>\plaseazapegrid [...¹] {².}</p> <p>1 normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME</p> <p>2 CONTENT</p>
<p>\plaseazapegrid [...¹,...] {².}</p> <p>1 inherits: \definegridsnapping</p> <p>2 CONTENT</p>
<p>\plaseazasemnecarte [...¹,...] [...².,...] [...³.,...]</p> <p>1 ABSCHNITT LISTE</p> <p>2 ABSCHNITT LISTE</p> <p>3 inherits: \setupbookmark</p>

<p><code>\popattribute \...</code></p> <p>* CSNAME</p>
<p><code>\popmacro \...</code></p> <p>* CSNAME</p>
<p><code>\popmode [...]</code></p> <p>* NAME</p>
<p><code>\popsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\positionoverlay {...}</code></p> <p>* NAME</p>
<p><code>\positionregionoverlay {...} {...}</code></p> <p>1 NAME</p> <p>2 NAME</p>
<p><code>\postponenotes</code></p>
<p><code>\potrivestecamp [...]¹ [...,...²...,...]_{OPT}</code></p> <p>1 NAME</p> <p>2 inherits: \setupfieldbody</p>
<p><code>\pozitie [...,...¹...,...]_{OPT} (...,...²...) {...³}</code></p> <p>1 inherits: \setarepozitie</p> <p>2 POSITION</p> <p>3 CONTENT</p>
<p><code>\predefinedfont [...]</code></p> <p>* FONT</p>
<p><code>\predefinefont [...]¹ [...]²</code></p> <p>1 NAME</p> <p>2 FONT</p>
<p><code>\predefinesymbol [...]</code></p> <p>* NAME</p>
<p><code>\prefixedpagenumber</code></p>
<p><code>\prependetoks ... \to \...¹ \to \...²</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>

<pre> \prependgvalue {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \prependtocommalist {...} \^2... 1 TEXT 2 CSNAME </pre>
<pre> \prependtoks ^1... \to \^2... 1 BEFEHL 2 CSNAME </pre>
<pre> \prependtoksonce ^1... \to \^2... 1 BEFEHL 2 CSNAME </pre>
<pre> \prependvalue {...} {...} 1 NAME 2 BEFEHL </pre>
<pre> \presetdocument [..., ...^*..., ...] * inherits: \setupdocument </pre>
<pre> \presetfieldsymbols [..., ^*...] * NAME </pre>
<pre> \presetLABELtext [...^1...] [..., ...^2..., ...] OPT 1 SPRACHE 2 KEY = VALUE instances: </pre>
<pre> \pretocommalist {...} \^2... 1 TEXT 2 CSNAME </pre>
<pre> \prevcounter [...^1...] [...^2...] OPT 1 NAME 2 NUMMER </pre>
<pre> \prevcountervalue [...^*] * NAME </pre>
<pre> \preventmode [..., ^*...] * NAME </pre>
<pre> \prevrealpage </pre>

<code>\prevrealpagenumber</code>
<code>\prevsubcountervalue [...]¹ [...]²</code> 1 NAME 2 NUMMER
<code>\prevsubpage</code>
<code>\prevsubpagenumber</code>
<code>\prevuserpage</code>
<code>\prevuserpagenumber</code>
<code>\primasubpagina</code>
<code>\procent</code>
<code>\proceseazabloc [...]¹ [...]² [...]³</code> <small>OPT OPT</small> 1 NAME 2 + - 3 criteriu = text ABSCHNITT
<code>\processaction [...]¹ [...]²</code> 1 BEFEHL 2 APPLY
<code>\processallactionsinset [...]¹ [...]²</code> 1 BEFEHL 2 APPLY
<code>\processassignlist [...]¹ \^²</code> 1 TEXT 2 CSNAME
<code>\processassignmentcommand [...]¹ \^²</code> 1 KEY = VALUE 2 CSNAME
<code>\processassignmentlist [...]¹ \^²</code> 1 KEY = VALUE 2 CSNAME
<code>\processbetween {...}¹ \^²</code> 1 NAME 2 CSNAME

<p><code>\processbodyfontenvironmentlist *</code></p> <p>* CSNAME</p>
<p><code>\processcolorcomponents {...}</code></p> <p>* COLOR</p>
<p><code>\processcommacommand [...¹,...] \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\processcommalist [...¹,...] \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\processcommalistwithparameters [...¹,...] \²...</code></p> <p>1 BEFEHL</p> <p>2 CSNAME</p>
<p><code>\processcontent {...¹} \²...</code></p> <p>1 NAME</p> <p>2 CSNAME</p>
<p><code>\processfile {...}</code></p> <p>* FILE</p>
<p><code>\processfilemany {...}</code></p> <p>* FILE</p>
<p><code>\processfilenone {...}</code></p> <p>* FILE</p>
<p><code>\processfileonce {...}</code></p> <p>* FILE</p>
<p><code>\processfirstactioninset [...¹] [...²,...=>...]</code></p> <p>1 BEFEHL</p> <p>2 APPLY</p>
<p><code>\processisolatedchars {...¹} \²...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\processisolatedwords {...¹} \²...</code></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p><code>\processlinetablebuffer [...¹]_{OPT}</code></p> <p>* BUFFER</p>

<p><code>\processlinetablefile {...}</code></p> <p>* FILE</p>
<p><code>\processlist {...} {...} {...} \...</code></p> <p>1 CHARACTER</p> <p>2 CHARACTER</p> <p>3 TEXT</p> <p>4 CSNAME</p>
<p><code>\processMPbuffer [...[*]...]</code> OPT</p> <p>* NAME</p>
<p><code>\processMPfigurefile {...}</code></p> <p>* FILE</p>
<p><code>\processmonth {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p> <p>3 BEFEHL</p>
<p><code>\processranges [...¹,...] \...²</code></p> <p>1 NUMMER NUMMER:NUMMER</p> <p>2 CSNAME</p>
<p><code>\processseparatedlist [...¹] [...²] {...³}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 CSNAME BEFEHL</p>
<p><code>\processTEXbuffer [...[*]...]</code> OPT</p> <p>* BUFFER</p>
<p><code>\processtokens {...} {...} {...} {...} {...}</code></p> <p>1 BEFEHL</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p> <p>4 BEFEHL</p> <p>5 TEXT</p>
<p><code>\processuntil \...</code></p> <p>* CSNAME</p>
<p><code>\processxtablebuffer [...[*]...]</code> OPT</p> <p>* NAME</p>

<p><code>\processyear {...} {...} {...} {...}</code></p> <p>1 NUMMER</p> <p>2 BEFEHL</p> <p>3 BEFEHL</p> <p>4 BEFEHL</p>
<p><code>\produs [...]</code></p> <p>* FILE</p>
<p><code>\produs ...</code></p> <p>* FILE</p>
<p><code>\profiledbox ¹ [...] ² [...] ³ {...}</code> <small>OPT OPT</small></p> <p>1 niciunul fixat strict halffixed quarterfixed eightsfixed NAME</p> <p>2 inherits: \setupprofile</p> <p>3 CONTENT</p>
<p><code>\profilegivenbox ¹ ² ³ [...]</code> <small> OPT</small></p> <p>1 niciunul fixat strict halffixed quarterfixed eightsfixed NAME</p> <p>2 CSNAME NUMMER</p>
<p><code>\program [...]</code></p> <p>* NAME</p>
<p><code>\proiect [...]</code></p> <p>* FILE</p>
<p><code>\proiect ...</code></p> <p>* FILE</p>
<p><code>\pseudoMixedCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallCapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudoSmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\pseudosmallcapped {...}</code></p> <p>* TEXT</p>
<p><code>\punct {...}</code></p> <p>* CHARACTER</p>
<p><code>\puncte ¹ [...]</code> <small> OPT</small></p> <p>* NUMMER</p>

<p>\puncte $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* inherits: \setupperiods</p>
<p>\punedeasuprafiecareia $\{...\}^1 \{...\}^2$</p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p>\punefatalinfata $\{...\}^1 \{...\}^2$</p> <p>1 CONTENT</p> <p>2 CONTENT</p>
<p>\puneformula $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* + - REFERENCE</p>
<p>\punelista $[...,\overset{1}{=},...]$ $[...,\overset{2}{=},...]$ <small>OPT</small></p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>
<p>\punelistacombinata $[...]\overset{1}{=}$ $[...,\overset{2}{=},...]$ <small>OPT</small></p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p>
<p>\puneCOMBINEDLIST $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* inherits: \seteazalista</p> <p>instances:</p>
<p>\punenotesubsol $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p>\punenotesubsollocale $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* inherits: \setupnote</p>
<p>\punenumarpagina</p>
<p>\puneregistru $[...]\overset{1}{=}$ $[...,\overset{2}{=},...]$ <small>OPT</small></p> <p>1 NAME</p> <p>2 inherits: \seteazaregistru</p>
<p>\puneREGISTER $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* inherits: \seteazaregistru</p> <p>instances:</p>
<p>\punesubformula $[...,\overset{*}{=},...]$ <small>OPT</small></p> <p>* + - REFERENCE</p>
<p>\purenumber $\{...\}^*$</p> <p>* NUMMER</p>

<code>\pusharrangedpages ... \poparrangedpages</code>
<code>\pushattribute *...</code> <code>* CSNAME</code>
<code>\pushbar [...] ... \popbar</code> <code>* NAME</code>
<code>\pushbutton [¹...] [²...]</code> <code>1 NAME</code> <code>2 REFERENCE</code>
<code>\pushcatcodetable ... \popcatcodetable</code>
<code>\pushculoare [...] ... \popculoare</code> <code>* COLOR</code>
<code>\pushendofline ... \popendofline</code>
<code>\pushfundal [...] ... \popfundal</code> <code>* NAME</code>
<code>\pushindentation ... \popindentation</code>
<code>\pushMPdrawing ... \popMPdrawing</code>
<code>\pushmacro *...</code> <code>* CSNAME</code>
<code>\pushmathstyle ... \popmathstyle</code>
<code>\pushmode [...] ...</code> <code>* NAME</code>
<code>\pushoutputstream [^{OPT}...]</code> <code>* NAME</code>
<code>\pushpath [...] ... \poppath</code> <code>* PATH</code>
<code>\pushpunctuation ... \poppunctuation</code>
<code>\pushrandomseed ... \poprandomseed</code>
<code>\pushreferenceprefix {...} ... \popreferenceprefix</code> <code>* + - TEXT</code>
<code>\pushsystemmode {...}</code> <code>* NAME</code>

<code>\quad</code>
<code>\quad</code>
<code>\quads [...]</code> <small>OPT</small> * NUMBER
<code>\quitcommalist</code>
<code>\quitprevcommalist</code>
<code>\quittypescriptscanning</code>
<code>\ReadFile {...}</code> * FILE
<code>\raggedbottom</code>
<code>\raggedcenter</code>
<code>\raggedleft</code>
<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {...} \² {...}</code> 1 DIMENSION 2 CSNAME 3 CONTENT
<code>\randomizetext {...}</code> * TEXT
<code>\randomnumber {\¹ {...} {\² {...}}</code> 1 NUMBER 2 NUMBER
<code>\rawcounter [...] [...]</code> <small>OPT</small> 1 NAME 2 NUMBER
<code>\rawcountervalue [...]</code> * NAME
<code>\rawdate [...,*,...]</code> * inherits: \datacurenta

<pre> \rawdoifelseinset {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \rawdoifinset {...} {...} 1 CONTENT 2 TRUE </pre>
<pre> \rawdoifinsetelse {...} {...} {...} 1 CONTENT 2 TRUE 3 FALSE </pre>
<pre> \rawgetparameters [...]¹ [...,²...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \rawprocessaction [...]¹ [...,²⇒...,...] 1 BEFEHL 2 APPLY </pre>
<pre> \rawprocesscommacommand [...]¹,... \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawprocesscommalist [...]¹,... \²... 1 BEFEHL 2 CSNAME </pre>
<pre> \rawstructurelistuservariable {...} * KEY </pre>
<pre> \rawsubcountervalue [...]¹ [...]² 1 NAME 2 NUMMER </pre>
<pre> \abox ¹... {...}² OPT 1 TEXT 2 CONTENT </pre>
<pre> \readfile {...} {...} {...} 1 FILE 2 TRUE 3 FALSE </pre>

\readfixfile {...} {...} {...} {...}

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

\readjobfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readlocfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readsetfile {...} {...} {...} {...}

- 1 PATH
- 2 FILE
- 3 TRUE
- 4 FALSE

\readsysfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readtexfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\readxmlfile {...} {...} {...}

- 1 FILE
- 2 TRUE
- 3 FALSE

\realpagenumber

\realSmallCapped {...}

- * TEXT

\realSmallcapped {...}

- * TEXT

\realSmallcapped {...}

- * TEXT

<code>\recursedepth</code>
<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...]¹ [...]²</code> 1 implicit text titlu numar pagina realpage 2 REFERENCE
<code>\REFERENCEFORMAT {...}¹ {...}² [...]³</code> <div style="display: flex; justify-content: space-around; width: 100%;"> <small>OPT</small> <small>OPT</small> </div> 1 TEXT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referinta [...]¹, [...] {...}²</code> 1 REFERENCE 2 TEXT
<code>\referintapagina [...][*], [...]</code> * REFERENCE
<code>\referintatext [...]¹, [...] {...}²</code> 1 REFERENCE 2 TEXT
<code>\referring (...)¹, (...) (...)², [...] [...]³</code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\reflexie {...}[*]</code> * CONTENT
<code>\registerattachment [...]¹ [...]², [...], [...]</code> 1 NAME 2 inherits: \setupattachment
<code>\registerctxluafile {...}¹ {...}²</code> 1 FILE 2 NUMMER

<pre> \registerexternalfigure [...] [...] [...] [...] OPT OPT 1 FILE 2 NAME 3 inherits: \setupexternalfigure </pre>
<pre> \registerfontclass {...} * NAME </pre>
<pre> \registerhyphenationexception [...] [...] OPT 1 SPRACHE 2 TEXT </pre>
<pre> \registerhyphenationpattern [...] [...] OPT 1 SPRACHE 2 TEXT </pre>
<pre> \registermenubuttons [...] [...] 1 NAME 2 TEXT </pre>
<pre> \registersort [...] [...] 1 SINGULAR 2 NAME </pre>
<pre> \registersynonym [...] [...] 1 SINGULAR 2 NAME </pre>
<pre> \registerunit [...] [...] OPT 1 prefix unitate operator suffixe simbol packaged 2 KEY = VALUE </pre>
<pre> \REGISTER [...] [...] OPT 1 TEXT PROCESSOR->TEXT 2 INDEX instances: </pre>
<pre> \REGISTER [...] {...} [...] OPT 1 TEXT PROCESSOR->TEXT 2 TEXT 3 INDEX instances: </pre>
<pre> \regular </pre>

<code>\relatemarking [...]¹ [...]²</code> 1 BESCHRIFTUNG 2 BESCHRIFTUNG
<code>\relateparameterhandlers {...}¹ {...}² {...}³ {...}⁴</code> 1 NAME 2 NAME 3 NAME 4 NAME
<code>\relaxvalueifundefined {...}</code> * NAME
<code>\remainingcharacters</code>
<code>\remarca (...¹,...) (...²,...) [...³_{OPT}...]⁴ {...}</code> 1 POSITION 2 POSITION 3 inherits: \seteazainconjurat 4 TEXT
<code>\removebottomthings</code>
<code>\removedepth</code>
<code>\removefromcommalist {...}¹ \...²</code> 1 TEXT 2 CSNAME
<code>\removelastskip</code>
<code>\removelastspace</code>
<code>\removemarkedcontent [...][*]</code> * NAME
<code>\removepunctuation</code>
<code>\removesubstring ... \from ...¹ \to ...² \...³</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\removetoks ... \from ...¹ \...²</code> 1 BEFEHL 2 CSNAME
<code>\removeunwantedspaces</code>

<pre>\replacefeature [...]</pre> <pre>* NAME</pre>
<pre>\replacefeature {...}</pre> <pre>* NAME</pre>
<pre>\replaceincommalist \.^{.2.} {...}</pre> <pre>1 CSNAME</pre> <pre>2 NUMMER</pre>
<pre>\replaceword [.^{.2.}] [.^{.3.}] [...]</pre> <pre>1 NAME</pre> <pre>2 TEXT</pre> <pre>3 TEXT</pre>
<pre>\rescan {...}</pre> <pre>* CONTENT</pre>
<pre>\rescanwithsetup {.^{.2.}} {...}</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\resetallattributes</pre>
<pre>\resetandaddfeature [...]</pre> <pre>* NAME</pre>
<pre>\resetandaddfeature {...}</pre> <pre>* NAME</pre>
<pre>\resetbar</pre>
<pre>\resetbreakpoints</pre>
<pre>\resetbuffer [...]</pre> <pre>* BUFFER</pre>
<pre>\resetcharacteralign</pre>
<pre>\resetcharacterkerning</pre>
<pre>\resetcharacterspacing</pre>
<pre>\resetcharacterstripping</pre>
<pre>\resetcollector [...]</pre> <pre>* NAME</pre>

\resetcounter [...] [¹ ...] [² ...] <small>OPT</small> 1 NAME 2 NUMMER
\resetdigitsmanipulation
\resetdirection
\reseteazamarcaje [...] * BESCHRIFTUNG
\resetfeature
\resetflag {...} * NAME
\resetfontcolorsheme
\resetfontfallback [¹ ...] [² ...] <small>OPT</small> 1 NAME 2 FONT
\resetfontsolution
\resethyphenationfeatures
\resetinjector [...] * NAME
\resetinteractionmenu [...] * NAME
\resetitaliccorrection
\resetlayer [...] * NAME
\resetlocalfloats
\resetMPdrawing
\resetMPenvironment
\resetMPinstance [...] * NAME
\resetmarker [...] * NAME

\resetmode {...} * NAME
\resetpagenumber
\resetparallel [...] ¹ [...] ² ... <small>OPT</small> 1 NAME 2 NAME tot
\resetpath
\resetpenalties *.. * CSNAME
\resetprofile
\resetreference [...] * NAME
\resetreplacement
\resetscript
\resetsetups [...] * NAME
\resetshownsynonyms [...] * SINGULAR
\resetsubpagenumber
\resetsymbolset
\resetssystemmode {...} * NAME
\resettimer
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR
\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber

<code>\resetvalue {...}</code> * NAME
<code>\resetvisualizers</code>
<code>\reshapebox {...}</code> * BEFEHL
<code>\restartcounter [...]</code> $[...]$ $[...]$ <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 NUMMER 3 NUMMER
<code>\restorebox {...} {...}</code> 1 NAME 2 NAME
<code>\restorecatcodes</code>
<code>\restorecounter [...]</code> * NAME
<code>\restorecurrentattributes {...}</code> * NAME
<code>\restoreendofline</code>
<code>\restoreglobalbodyfont</code>
<code>\reusableMPgraphic {...} {...,$\stackrel{2}{=}$...,...}</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 KEY = VALUE
<code>\reuseMPgraphic {...} {...,$\stackrel{2}{=}$...,...}</code> <div style="text-align: center;"><small>OPT</small></div> 1 NAME 2 KEY = VALUE
<code>\reuserandomseed</code>
<code>\revivefeature</code>
<code>\rfence {...}</code> * CHARACTER
<code>\rhbox {...}</code> * CONTENT

<code>\rightbottombox {...}</code> * CONTENT
<code>\rightbox {...}</code> * CONTENT
<code>\righthbox {...}</code> * CONTENT
<code>\rightLABELtext {...}</code> * KEY instances:
<code>\rightline {...}</code> * CONTENT
<code>\rightorleftpageaction {...} {...}</code> 1 BEFEHL 2 BEFEHL
<code>\rightskipadaption</code>
<code>\rightsubguillemot</code>
<code>\righttopleft</code>
<code>\righttopleftthbox ¹... {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\righttoplefttvbox ¹... {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\righttopleftvtop ¹... {...}</code> <small>OPT</small> 1 TEXT 2 CONTENT
<code>\righttopbox {...}</code> * CONTENT
<code>\riglertext [¹...][²...]</code> <small>OPT OPT</small> 1 sus centru subsol 2 TEXT

<p>\rigleumplere [<small>¹</small>...,...<small>_{OPT}</small>] {<small>²</small>...} {<small>³</small>...}</p> <p>1 inherits: \seteazarigleumplere</p> <p>2 TEXT</p> <p>3 TEXT</p>
<p>\rlap {...}</p> <p>* CONTENT</p>
<p>\robustaddtocommalist {<small>¹</small>...} \...<small>²</small></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p>\robustdoifelseinset {<small>¹</small>...} {<small>²</small>...}</p> <p>1 TRUE</p> <p>2 FALSE</p>
<p>\robustdoifinsetelse {<small>¹</small>...} {<small>²</small>...}</p> <p>1 TRUE</p> <p>2 FALSE</p>
<p>\robustpretocommalist {<small>¹</small>...} \...<small>²</small></p> <p>1 TEXT</p> <p>2 CSNAME</p>
<p>\rollbutton [<small>¹</small>...,...<small>_{OPT}</small>] ...<small>²</small> [<small>³</small>...]</p> <p>1 inherits: \setupbutton</p> <p>2 TEXT</p> <p>3 REFERENCE</p>
<p>\rollbutton [<small>¹</small>...]<small>_{OPT}</small> [<small>²</small>...,...<small>_{OPT}</small>] ...<small>³</small> [<small>⁴</small>...]</p> <p>1 NAME</p> <p>2 inherits: \seteazameniuiinteractiune</p> <p>3 TEXT</p> <p>4 REFERENCE</p>
<p>\roman</p>
<p>\roteste [<small>¹</small>...,...<small>_{OPT}</small>] {<small>²</small>...}</p> <p>1 inherits: \seteazarotare</p> <p>2 CONTENT</p>
<p>\rtop ...<small>¹</small> {<small>²</small>...}<small>_{OPT}</small></p> <p>1 TEXT</p> <p>2 CONTENT</p>

<pre> \ruledhbox ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledhpack ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledmbox {...} * CONTENT </pre>
<pre> \ruledtopv ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledtpack ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvbox ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvpack ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \ruledvtop ¹... {²...} OPT 1 TEXT 2 CONTENT </pre>
<pre> \runMPbuffer [...[*]...] OPT * NAME </pre>
<pre> \runninghbox {...} * CONTENT </pre>
<pre> \ScaledPointsToBigPoints {...} \²... 1 DIMENSION 2 CSNAME </pre>
<pre> \ScaledPointsToWholeBigPoints {...} \²... 1 DIMENSION 2 CSNAME </pre>
<pre> \Smallcapped {...} * TEXT </pre>

```
\safechar {...}
```

* NUMMER

\sans

\sansaldin

\sansnormal

\sansserif

$$\backslash\mathrm{savebox}\ \{.\!.\!.\}^1\ \{.\!.\!.\}^2\ \{.\!.\!.\}^3$$

1 NAME

2 NAME

3 CONTENT

$$\backslash \text{savebtxdataset} \quad \underset{\text{OPT}}{[...]} \quad \underset{\text{OPT}}{[...]} \quad \underset{\text{OPT}}{[...,\dots^3,...,\dots]}$$

1 NAME

2 FILE

```
3 dataset = NAME
```

```
type      = bib lua xml
```

```
fichier = FILE
```

```
criteriu = tot text intro referinta curent aici precedent local componenta SECTIONBLOCK:tot SECTIONBLOCK:referinta
SECTIONBLOCK:curent SECTIONBLOCK:precedent
```

```
\savebuffer [...=*...]
```

```
* lista = NAME
  fisier = FILE
  prefix = da nu
```

```
\savebuffer [...1,...] [...2]
```

1 BUFFER

2 FILE

```
\savecounter [...]
```

* NAME

```
\saveculoare ... \restoreculoare
```

```
\savecurrentattributes {...}
```

* NAME

\savenormalmeaning \.*...

* CSNAME

$$\backslash \text{savetaggedtwopassdata} \{ \dots \}^1 \{ \dots \}^2 \{ \dots \}^3 \{ \dots \}^4$$

1 NAME

2 NUMMER.

3 NAME

4 CONTENT

<p>\savetwopassdata ¹{...} ²{...} ³{...}</p> <p>1 NAME</p> <p>2 NUMMER</p> <p>3 CONTENT</p>
<p>\sbox {...}</p> <p>* CONTENT</p>
<p>\scala [¹...] [²...,...²...,...] ³{...}</p> <p>1 NAME</p> <p>2 inherits: \setupscale</p> <p>3 CONTENT</p>
<p>\scriebuffer [¹...,...¹] [²...,...²...,...²] ³{...}</p> <p>1 BUFFER</p> <p>2 inherits: \seteazatyping</p>
<p>\typeBUFFER [[*]...,...[*]...,...[*]] ^{OPT}</p> <p>* inherits: \seteazatyping</p>
<p>\scrieinlista [¹...] [²...,...²...,...²] ³{...} ⁴{...}</p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p> <p>3 NUMMER</p> <p>4 TEXT</p>
<p>\scrieintreliste [¹...] [²...,...²...,...²] ³{...}</p> <p>1 LISTE</p> <p>2 inherits: \seteazalista</p> <p>3 BEFEHL</p>
<p>\SCRIPT</p> <p>instances:</p>
<p>\scrismanual</p>
<p>\secondoffivearguments ¹{...} ²{...} ³{...} ⁴{...} ⁵{...}</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p>
<p>\secondoffourarguments ¹{...} ²{...} ³{...} ⁴{...}</p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p>

`\secondofsixarguments {...} {...} {...} {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT
- 4 TEXT
- 5 TEXT
- 6 TEXT

`\secondofthreearguments {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondofthreeunexpanded {...} {...} {...}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\secondoftwoarguments {...} {...}`

- 1 TEXT
- 2 TEXT

`\secondoftwounexpanded {...} {...}`

- 1 TEXT
- 2 TEXT

`\SECTION [...,1...] {...2...}`
OPT

- 1 REFERENCE
- 2 TEXT

instances:

`\SECTION [...,*...,...]`

***** titlu = TEXT
semncarte = TEXT
marcaje = TEXT
lista = TEXT
referinta = REFERENCE
numarpropriu = TEXT

instances:

`\SECTION [...,1...] {...2...} {...3...}`
OPT

- 1 REFERENCE
- 2 NUMMER
- 3 TEXT

instances:

\veziREGISTER [...]¹ [...+...+...]² {...}³

OPT

1 TEXT PROCESSOR->TEXT

2 INDEX

3 TEXT PROCESSOR->TEXT

instances:

\select {...}¹ {...}² {...}³ {...}⁴ {...}⁵ {...}⁶

OPT

OPT

OPT

OPT

OPT

1 NAME

2 CONTENT

3 CONTENT

4 CONTENT

5 CONTENT

6 CONTENT

\selecteazablocuri [...]¹,...² [...]³,...⁴ [...]⁵,...⁶,...⁷

OPT

OPT

1 NAME

2 + -

3 criteriu = text ABSCHNITT

\semncarte [...]¹ {...}²

OPT

1 ABSCHNITT LISTE

2 TEXT

\serializecommalist [...]^{*},...]

* BEFEHL

\serializedcommalist

\serif

\serifbold

\serifnormal

\setare [...]^{*}

* NAME

\setareitemization [...]¹,...² [...]³,...⁴,...⁵

OPT

1 NAME NAME:NUMMER

2 inherits: \setupitemgroup

\setarelimba [...] [...] ¹ _{OPT} [...] ² [...] [...]

```
1  SPRACHE implicit

2  implicit      = SPRACHE
   stare        = start stop
   data         = inherits: \datacurenta
   patterns     = FILE
   lefthyphenmin = NUMBER
   righthyphenmin = NUMBER
   lefthyphenchar = NUMBER
   righthyphenchar = NUMBER
   setups       = NAME
   spatiere     = broad impachetat
   font         = auto
   text         = TEXT
   limitttext   = TEXT
   hyphen       = TEXT
   compoundhyphen = TEXT
   leftcompoundhyphen = TEXT
   rightcompoundhyphen = TEXT
   minicitatstanga = BEFEHL
   minicitatdreapta = BEFEHL
   citatstanga = BEFEHL
   citatdreapta = BEFEHL
   leftspeech = BEFEHL
   rightspeech = BEFEHL
   propozitiestanga = BEFEHL
   middlespeech = BEFEHL
   propozitiedreapta = BEFEHL
   midsentence = BEFEHL
   subpropozitiestanga = BEFEHL
   subpropozitiedreapta = BEFEHL
   factor       = da nu
```

\setarepozitie [...] ¹ [...] [...] ² [...] [...]

```
1  NAME

2  offset = da nu
   unitate = ex em pt in cm mm sp bp pc dd cc nc
   stare = start overlay
   xoffset = DIMENSION
   yoffset = DIMENSION
   xstep = absolut relativ
   ystep = absolut relativ
   xscala = NUMMER
   yscala = NUMMER
   xfactor = NUMMER
   yfactor = NUMMER
   factor = NUMMER
   scala = NUMMER
```

\setare {...}

* NAME

\setbar [...] [...]

* NAME

\setbigbodyfont

\setboxllx ¹ [...] {² [...] [...]}

```
1  CSNAME NUMMER
2  DIMENSION
```

\setboxlly ¹ [...] {² [...] [...]}

```
1  CSNAME NUMMER
2  DIMENSION
```


\setbreakpoints [...] * reset NAME
\setbuffer [...] ... \endbuffer * NAME
\setcapstrut
\setcatcodetable *... * CSNAME
\setcharacteralign { ¹ ...} { ² ...} 1 NUMMER 2 TEXT number->TEXT text->TEXT
\setcharactercasing [...] * reset CUVANT cuvant Cuvant Cuvinte majuscula Majuscula niciunul aleator mixed camel cap Cap
\setcharactercleaning [...] * reset 1
\setcharacterkerning [...] * reset NAME
\setcharacterspacing [...] * reset NAME
\setcharacterstripping [...] * reset 1
\setcharstrut {...} * TEXT
\setcollector [¹ ...] [..., ² ... _{OPT} ,...] { ³ ...} 1 NAME 2 inherits: \setupcollector 3 CONTENT
\setcolormodel1 [...] * black bw gri rgb cmyk tot niciunul
\setcounter [¹ ...] [² ... _{OPT}] [³ ...] 1 NAME 2 NUMMER 3 NUMMER

<pre> \setcounterown [...] [¹...] [²...] [³...] OPT 1 NAME 2 NUMMER 3 TEXT </pre>
<pre> \setcurrentfontclass {...} * NAME </pre>
<pre> \setdataset [¹...] [²...] [³...,...] OPT 1 NAME 2 NAME 3 KEY = VALUE </pre>
<pre> \setdefaultpenalties </pre>
<pre> \setdigitsmanipulation [...] * reset NUMMER </pre>
<pre> \setdirection [...] * NUMMER </pre>
<pre> \setdocumentargument {...} {...} 1 NAME 2 TEXT </pre>
<pre> \setdocumentargumentdefault {...} {...} 1 NAME 2 TEXT </pre>
<pre> \setdocumentfilename {...} {...} 1 NUMMER 2 TEXT </pre>
<pre> \setdummyparameter {...} {...} 1 KEY 2 BEFEHL </pre>
<pre> \setezaaliniat [...,*...] OPT * [-+]mic [-+]mediu [-+]mare niciunul nu nu primul urmatorul da totdeauna niciodata impar par normal reset toggle DIMENSION NAME </pre>
<pre> \setezaalinieria [...,*...] * broad larg subsol inaltime linie inalt jos lohi flushright flushleft centru da nu latime normal reset intern extern flushinner flushouter stanga dreapta center dezactivat ultim end paragraf lefttoright righttoleft l2r r2l tabelul lesshyphenation morehyphenation suspendat nothanging hz fullhz nohz despsilabe nedespsilabe tolerant foartetolerant dilatat extremestretch final 2*final 3*final 4*final </pre>
<pre> \setezaantet [¹...] [²...,...] OPT 1 text margine bordura 2 inherits: \setuplayoutelement </pre>

\setezaaranjareapag [...,*,...]

* dezactivat oglindit douafete negativ 90 180 270 reset fundal normal 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP 2DOWN
2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW
1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME

\setezaaspect [¹...] [²..._{OPT}...]

1 NAME

2 stare = start stop normal repetat
margine = DIMENSION
bordura = DIMENSION
distantamargine = DIMENSION
distantabordura = DIMENSION
distantabordurastanga = DIMENSION
distantacoltdreapta = DIMENSION
distantamarginestanga = DIMENSION
distantamarginedreapta = DIMENSION
distantasus = DIMENSION
distantaantet = DIMENSION
distantasubsol = DIMENSION
distantajos = DIMENSION
preset = NAME
marginestanga = DIMENSION
marginedreapta = DIMENSION
bordurastanga = DIMENSION
borduradreapta = DIMENSION
antet = DIMENSION
subsol = DIMENSION
sus = DIMENSION
jos = DIMENSION
spatiuspate = DIMENSION
spatiusus = DIMENSION
setups = NAME
cutspace = DIMENSION
latime = DIMENSION centru ajustat
spatiujos = DIMENSION
linii = NUMMER
inaltime = DIMENSION centru ajustat
offsetoriz = DIMENSION
veroffset = DIMENSION
coloane = NUMMER
distantacoloane = DIMENSION
metoda = implicit normal NAME
locatie = stanga centru dreapta sus subsol ofata douafete
latimetext = DIMENSION
inaltimetext = DIMENSION
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
scala = NUMMER
sx = NUMMER
sy = NUMMER
marcaje = on dezactivat pagina gol culoare unu doi patru
grid = da nu dezactivat
textdistance = DIMENSION
alternativ = implicit normal marcaj NAME
clipoffset = DIMENSION
cropoffset = DIMENSION
trimoffset = DIMENSION
bleedoffset = DIMENSION
artoffset = DIMENSION

\setezaaspect [...]

* reset NAME

`\seteazabarainteractiune [...,1...] [...,2...,...]`
OPT

1 NAME

2 alternativ = a b c d e f g
stare = start stop
comanda = CSNAME
latime = DIMENSION
inaltime = DIMENSION max broad
inaltime = DIMENSION max
distanta = DIMENSION
pas = mic mediu mare
culoarefundal = COLOR
stil = STYLE BEFEHL
culoare = COLOR
culoarecontrast = COLOR
simbol = da nu
inherits: \seteazainconjurat

`\seteazablanc [...,*...]`
OPT

* inherits: \vspacing

`\seteazabloc [...,1...] [...,2...,...]`
OPT

1 NAME

2 inainte = BEFEHL
dupa = BEFEHL
intern = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR

`\seteazablocsectiune [...,1...] [...,2...,...]`
OPT

1 NAME

2 pagina = inherits: \pagina
inainte = BEFEHL
dupa = BEFEHL
numar = da nu

`\seteazabuffer [...,1...] [...,2...,...]`
OPT

1 BUFFER

2 inainte = BEFEHL
dupa = BEFEHL

`\seteazacamp [...,1...] [...,2...,...] [...,3...,...] [...,4...,...] [...,5...,...]`
OPT OPT OPT OPT

1 NAME

2 reset eticheta incadrat orizontal vertical

3 inherits: \setupfieldtotalframed

4 inherits: \setupfieldlabelframed

5 inherits: \setupfieldcontentframed

`\seteazacampuri [...,1...] [...,2...,...] [...,3...,...] [...,4...,...]`
OPT OPT OPT OPT

1 reset eticheta incadrat orizontal vertical

2 inherits: \setupfieldtotalframed

3 inherits: \setupfieldlabelframed

4 inherits: \setupfieldcontentframed

\seteazaclipping [...,*=...,...]

```
* stare      = start stop
  latime     = DIMENSION
  inaltime   = DIMENSION
  hoffset    = DIMENSION
  voffset    = DIMENSION
  x          = NUMMER
  y          = NUMMER
  nx         = NUMMER
  ny         = NUMMER
  sx         = NUMMER
  sy         = NUMMER
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  offsetsus  = DIMENSION
  offsetjos  = DIMENSION
  mp         = NAME
  n          = NUMMER
  offset     = DIMENSION
```

\seteazacoloane [...,*=...,...]

```
* n          = NUMMER
  distanta   = DIMENSION
  optiune    = fundal
  offset     = DIMENSION
  comanda    = \...##1
  inaltime   = DIMENSION
  directie   = stanga dreapta
  balanta    = da nu
  aliniere   = setupalign
  toleranta  = setuptolerance
  blanc      = inherits: \blanc
  nsus       = NUMMER
  rigla      = on dezactivat BEFEHL
```

\seteazacommentariu [...,¹...,...]_{OPT} [...,²...,...]

```
1 NAME
2 stare      = start stop niciunul
  metoda     = normal ascuns
  simbol      = Comment Ajutor Insert Cheie Newparagraph Note Paragraf Default
  latime      = ajustat DIMENSION
  inaltime    = ajustat DIMENSION
  inaltime    = ajustat DIMENSION
  titlu       = TEXT
  subtitlu    = TEXT
  autor       = TEXT
  nx          = NUMMER
  ny          = NUMMER
  culoare     = COLOR
  optiune     = xml max
  textlayer   = NAME
  locatie     = bordurastanga borduradreapta inmarginemarginestangamarginedreapta text inalt niciunul
  distanta    = DIMENSION
```

\seteazacommentariupagina [...,*=...,...]

```
* locatie    = stanga dreapta sus subsol niciunul
  stare      = start stop niciunul
  offset     = DIMENSION
  distanta   = DIMENSION
  latime     = DIMENSION
  inaltime   = DIMENSION
```

\seteazaculoare [...]

```
* FILE
```

\seteazaculori [...,*...]

* stare = start stop
spot = da nu
expansiune = da nu
factor = da nu
rgb = da nu
cmyk = da nu
conversie = da nu totdeauna
pagecolormodel = auto niciunul NAME
culoaretext = COLOR
intent = overprint knockout niciunul

\seteazadimensiunihartie [...]¹ [...]²...]

OPT

1 NAME
2 sus = BEFEHL
jos = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
metoda = normal niciunul NAME
scala = NUMMER
nx = NUMMER
ny = NUMMER
dx = DIMENSION
dy = DIMENSION
latime = DIMENSION
inaltime = DIMENSION
spatiusus = DIMENSION
spatiuspate = DIMENSION
offset = DIMENSION
pagina = reset vedere oglindit negativ rotat 90 180 270 NAME
hartie = reset vedere oglindit negativ rotat 90 180 270 NAME
optiune = ajustat max
distanta = DIMENSION

\seteazadimensiunihartie [...]¹ [...]²...]

OPT

OPT

1 reset vedere oglindit negativ rotat 90 180 270 NAME
2 reset vedere oglindit negativ rotat 90 180 270 NAME

\seteazaecraninteractiune [...,*...]

* latime = ajustat max tight DIMENSION
inaltime = ajustat max tight DIMENSION
spatiuspate = DIMENSION
offsetoriz = DIMENSION
veroffset = DIMENSION
spatiusus = DIMENSION
optiune = ajustat max ofata douafete semncarte auto niciunul implicit fixat vedere portrait pagina foaie
copies = NUMMER
intarziere = niciunul NUMMER

\seteazaelemente [...]¹ [...]²...]

OPT

1 NAME
2 alternativ = stanga dreapta sus subsol inmarginie
latimetext = DIMENSION
latime = DIMENSION
distanta = DIMENSION
simbol = niciunul NAME
alinieri = stanga centru dreapta flushleft flushright intern extern marginie
textalign = stanga centru dreapta flushleft flushright intern extern
n = NUMMER
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL

\seteazafloat [...¹,...] [...²,...]

OPT

```

1 SINGULAR

2 aliniaturmator      = da nu auto
  implicit            = inherits: \placefloat
  fallback             = inherits: \placefloat
  intern              = BEFEHL
  criteriu             = DIMENSION
  metoda              = NUMMER
  sidemethod           = NUMMER
  textmethod          = NUMMER
  sidealign            = inaltime adancime linie jumatatelinie grila normal
  grid                = CD:STRING
  local               = da nu
  comanda              = \...##1
  availablewidth       = DIMENSION
  availableheight      = DIMENSION
  latimeminima         = DIMENSION
  latimemaxima         = DIMENSION
  locatie              = stanga dreapta centru flushleft flushright center max intern extern innermargin outermargin
                        inneredge outeredge spatuspate cutspace marginestanga marginedreapta bordurastanga
                        borduradreapta
  distantamarginestanga = DIMENSION
  distantamarginedreapta = DIMENSION
  marginestanga        = DIMENSION
  marginedreapta       = DIMENSION
  innermargin          = DIMENSION
  outermargin          = DIMENSION
  bottombefore         = BEFEHL
  bottomafter          = BEFEHL
  spatiuinainte        = niciunul inherits: \blanc
  spatiudupa           = niciunul inherits: \blanc
  latime               = DIMENSION
  inaltime             = DIMENSION
  offset              = DIMENSION niciunul overlay
  spatiulateralinainte = niciunul inherits: \blanc
  spatiulateraldupa    = niciunul inherits: \blanc
  margine              = DIMENSION
  nsus                 = DIMENSION
  njos                 = DIMENSION
  pas                  = mic mediu mare linie adancime
  nlinii               = NUMMER
  cache                = da nu

```

\seteazafonttext [...^{*},...]

OPT

* DIMENSION NAME global reset x xx mic mare script scriptscript rm ss tt hw cg roman serif regular sans sansserif suport type teletype mono scrismmanual caligrafic

\seteazaformulare [...^{*},...]

* metoda = XML HTML PDF
export = da nu

\seteazafundal [...¹,...] [...²,...]

OPT

```

1 NAME

2 stare      = start stop
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  offsetsus    = DIMENSION
  offsetjos    = DIMENSION
  inainte      = BEFEHL
  dupa         = BEFEHL
  inherits: \seteazainconjurat

```

\seteazafundaluri [...¹,...] [...²,...] [...³,...]

OPT

```

1 sus antet text subsol subsol

2 bordurastanga marginestanga text marginedreapta borduradreapta

3 inherits: \seteazainconjurat

```

\seteazafundaluri [...,¹...] [...,²...,...]
OPT

1 foaie pagina paginastanga paginadreapta text ascuns
2 stare = start stop
inherits: \seteazainconjurat

\seteazagrosimelinie [...]

* mic mediu mare DIMENSION

\seteazaimpartireafloat [...,^{*}...,...]

* inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
linii = auto NUMMER
conversie = NAME

\seteazainconjurat [...,¹...] [...,²...,...]
OPT

1 NAME
2 colt = rectangular rotund NUMMER
coltframe = rectangular rotund NUMMER
coltfundal = rectangular rotund NUMMER
raza = DIMENSION
razaframe = DIMENSION
razafundal = DIMENSION
inaltime = DIMENSION
adancimeframe = DIMENSION
adancimefundal = DIMENSION
culoareframe = COLOR
framesus = on dezactivat NAME
framejos = on dezactivat NAME
framestanga = on dezactivat NAME
framedreapta = on dezactivat NAME
region = da nu
grosimerigla = DIMENSION
offsetframe = DIMENSION
frame = on dezactivat overlay niciunul
fundal = primplan culoare NAME
offsetfundal = incadrat DIMENSION
component = NAME
extras = BEFEHL
foregroundstyle = STYLE BEFEHL
foregroundcolor = COLOR
setups = NAME
offset = implicit overlay niciunul DIMENSION
latime = local ajustat max broad fixat DIMENSION
inaltime = ajustat max broad DIMENSION
aliniere = inherits: \seteazaalinierea
strut = da nu niciunul local global
autostrut = da nu
locatie = inaltime adancime inalt jos sus centru subsol linie lohi suspendat mentine formula matematica
normal
autolatime = da nu fortat
linii = NUMMER
sus = BEFEHL
jos = BEFEHL
blanc = da nu
profile = NAME
gol = da nu
loffset = DIMENSION
roffset = DIMENSION
toffset = DIMENSION
boffset = DIMENSION
orientation = NUMMER

\seteazaingust [...¹,...] [...²,...]
OPT

1 NAME

2 stanga = DIMENSION
 mijloc = DIMENSION
 dreapta = DIMENSION
 implicit = [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
 inainte = BEFEHL
 dupa = BEFEHL

\seteazainteractiunea [...¹,...] [...²,...]
OPT

1 NAME

2 stare = start stop
 stil = STYLE BEFEHL
 culoare = COLOR
 culoarecontrast = COLOR
 titlu = TEXT
 subtitlu = COLOR
 autor = TEXT
 data = TEXT
 keyword = TEXT
 focus = standard incadrat latime latimeminima inaltime inaltimeminima ajustat tight
 meniu = on dezactivat
 fieldlayer = auto NAME
 calculeaza = REFERENCE
 click = da nu
 display = normal nou
 pagina = da nu pagina nume auto
 actiunedeschidere = REFERENCE
 actiuneinchidere = REFERENCE
 actiunedeschiderepagina = REFERENCE
 actiuneinchiderepagina = REFERENCE
 setsimbol = NAME
 inaltime = DIMENSION
 inaltime = DIMENSION
 focusoffset = DIMENSION

\seteazainteractiunea [...]
OPT

* NAME

\seteazajos [...¹,...] [...²,...]
OPT

1 text margine bordura

2 inherits: \setuplayoutelement

\seteazalegenda [...¹,...] [...²,...]
OPT

1 NAME

2 inherits: \setupfloatcaption

\punechemical [...¹,...] [...²,...] {...³} {...⁴}
OPT OPT

1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga
 marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime
 adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine
 [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva
 effective

2 REFERENCE

3 TEXT

4 CONTENT

`\punefigure [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\punegraphic [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\puneintermezzo [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\punetable [...1,...] [...2,...] {...3} {...4}`

- 1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective
- 2 REFERENCE
- 3 TEXT
- 4 CONTENT

`\seteazaliniesilabe [...*,...]`

* semn = normal larg

`\seteazaliniesubtire [...*,...]`

* inaltime = max DIMENSION
 inaltime = max DIMENSION
 fundal = culoare
 frame = on dezactivat
 grosimerigla = DIMENSION
 alternativ = a b c niciunul
 culoarefundal = COLOR
 culoare = COLOR
 spatiereinterliniara = mic mediu mare NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 n = NUMMER

`\seteazalinii [...,1...] [...,2...,...]`

OPT

```
1 NAME
2 optiune = impachetat
  inainte = BEFEHL
  dupa    = BEFEHL
  intre   = BEFEHL
  aliniat = inherits: \seteazaaliniat
  aliniere = inherits: \seteazaalinierea
  spatiu  = da on dezactivat fixat implicit
  comanda = BEFEHL
  stil    = STYLE BEFEHL
  culoare = COLOR
  stanga  = BEFEHL
  dreapta = BEFEHL
```

`\seteazaliniimargine [...,1] [...,2...,...]`

OPT

```
1 NUMMER
2 inherits: \setupmarginrule
```

`\seteazaliniinegre [...,*...,...]`

```
* latime      = max DIMENSION
  inaltime    = max DIMENSION
  inaltime    = max DIMENSION
  distanta    = DIMENSION
  n           = NUMMER
  alternativ    = a b
  stil        = STYLE BEFEHL
  culoare     = COLOR
  type        = mp da nu
  mp          = NAME
```

`\seteazaliniiumplere [...,*...,...]`

```
* inainte     = BEFEHL
  dupa        = BEFEHL
  margine     = DIMENSION
  latime      = DIMENSION
  distanta    = DIMENSION
  grosimerigla = DIMENSION
  culoare     = COLOR
```

\seteazalista [...,¹...] [...,²...,...]
OPT

```
1 LISTE
2 stare = start stop
  locatie = niciunul aici
  type = simple comanda userdata
  criteriu = local intro referinta SECTIONBLOCK:referinta tot SECTIONBLOCK:tot text SECTIONBLOCK:text
            curent SECTIONBLOCK:curent aici precedent SECTIONBLOCK:precedent componenta ABSCHNITT
            SECTIONBLOCK:ABSCHNITT
  lista = NAME
  latime = ajustat broad auto DIMENSION
  inaltime = ajustat broad DIMENSION
  inaltime = ajustat broad DIMENSION
  simbol = unu doi trei niciunul implicit
  eticheta = da nu niciunul NAME
  starter = BEFEHL
  stopper = BEFEHL
  comanda = \...#1#2#3
  comandanumar = \...#1
  comandatext = \...#1
  comandapagina = \...#1
  numarpagina = da nu totdeauna
  numartitlu = da nu totdeauna
  inainte = BEFEHL
  dupa = BEFEHL
  intre = BEFEHL
  margine = niciunul DIMENSION
  distanta = niciunul DIMENSION
  alinieretitlu = da nu
  numberalign = stanga dreapta centru flushleft flushright intern extern
  aliniere = inherits: \seteazaalinierea
  suspenda = da nu
  stanga = BEFEHL
  dreapta = BEFEHL
  interactiune = da nu tot numar text titlu pagina numarsetiune numarpagina
  limittext = da nu TEXT
  stil = STYLE BEFEHL
  culoare = COLOR
  stilnumar = STYLE BEFEHL
  culoarenumar = COLOR
  stiltext = STYLE BEFEHL
  culoaretex = COLOR
  stilpagina = STYLE BEFEHL
  culoarepagina = COLOR
  referinta = NUMMER
  extras = NAME
  order = comanda tot titlu
  alternativ = a b c d e f g stanga dreapta sus subsol comanda niciunul interactive paragraf orizontal
              vertical NAME
  latimemaxima = DIMENSION
  pageprefix = da nu
  pageprefixseparatorset = NAME
  pageprefixconversionset = NAME
  pageprefixset = NAME
  pageprefixsegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                      ABSCHNITT:tot
  pageprefixconnector = BEFEHL PROCESSOR->BEFEHL
  pageconversionset = NAME
  pagestarter = BEFEHL PROCESSOR->BEFEHL
  pagestopper = BEFEHL PROCESSOR->BEFEHL
  inherits: \setupcounterinherits: \seteazainconjurat
```

\seteazalistacombinata [...,¹] [...,²...,...]

```
1 LISTE
2 inherits: \seteazalista
```

\setareCOMBINEDLIST [...,^{*}...,...]

```
* inherits: \seteazalista
```

instances:

`\seteazamajuscul` [...,¹...] [...,²...,...]
OPT

1 NAME
 2 titlu = da nu
 sc = da nu
 stil = STYLE BEFEHL

`\seteazamakeup` [...,¹...] [...,²...,...]
OPT

1 NAME
 2 pagina = inherits: \pagina
 comanda = BEFEHL
 latime = DIMENSION
 inaltime = DIMENSION
 alinieare = inherits: \seteazaalinieria
 setups = NAME
 sus = BEFEHL
 jos = BEFEHL
 inainte = BEFEHL
 dupa = BEFEHL
 locatie = sus
 referinta = REFERENCE
 pagestate = start stop
 stareantet = start stop inalt gol niciunul normal
 staresubsol = start stop inalt gol niciunul normal
 staresus = start stop inalt gol niciunul normal
 starejos = start stop inalt gol niciunul normal
 staretext = start stop inalt gol niciunul normal
 douafete = da nu gol
 stil = inherits: \value-style
 culoare = COLOR

`\seteazamarcaje` [...,¹...] [...,²...,...]
OPT

1 BESCHRIFTUNG
 2 stare = start stop
 expansiune = da nu
 separator = BEFEHL
 filtercommand = \...##1

`\seteazameniuiinteractiune` [...,¹...] [...,²...,...]
OPT

1 NAME
 2 alternativ = vertical orizontal ascuns
 category = NAME
 offsetstanga = overlay incadrat niciunul implicit DIMENSION
 offsetdreapta = overlay incadrat niciunul implicit DIMENSION
 offsetsus = overlay incadrat niciunul implicit DIMENSION
 offsetjos = overlay incadrat niciunul implicit DIMENSION
 latimemaxima = DIMENSION
 inaltimemaxima = DIMENSION
 itemalign = stanga centru dreapta flushleft flushright jos inalt lohi
 stare = start gol local
 stanga = BEFEHL
 dreapta = BEFEHL
 distanta = overlay DIMENSION
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 pozitie = da nu
 mijloc = BEFEHL
 stil = STYLE BEFEHL
 culoare = COLOR
 aceeasipagina = da nu gol niciunul normal implicit
 culoarecontrast = COLOR
 inherits: \seteazainconjurat

`\seteazaminicitat` [...,^{*}...,...]

* inherits: \setupdelimitedtext

\seteazanumarpagina [...,..^{*}...,...]

* inherits: \setupuserpagenumber

\seteazanumarsubpagina [...,..^{*}...,...]

* inherits: \setupcounter

\seteazanumartitlu [...¹.] [...².]

1 ABSCHNITT

2 [-+]NUMMER

\seteazanumerotarelinii [...,¹...] [...,²...] OPT

1 NAME

2 start = NUMMER
pas = NUMMER
metoda = pagina primul urmatorul
conversie = NAME
continua = da nu
locatie = text begin end implicit stanga dreapta intern extern instanga indreapta margine inmargin
distanta = DIMENSION
alinie = intern extern flushleft flushright stanga dreapta centru auto
comanda = \...##1
stanga = BEFEHL
dreapta = BEFEHL
margine = DIMENSION
latime = margine DIMENSION
stil = STYLE BEFEHL
culoare = COLOR

\seteazanumerotarepagina [...,..^{*}...,...]

* alternativ = ofata douafete
pagina = inherits: \pagina
strut = da nu
comanda = \...##1
stanga = BEFEHL
dreapta = BEFEHL
stare = start stop
latime = DIMENSION
locatie = antet subsol stanga centru dreapta instanga indreapta margine inmargin lamargine marginebordura
stil = STYLE BEFEHL
culoare = COLOR

\seteazanumerotareparagrafe [...,..^{*}...,...]

* stare = start stop linie reset
distanta = DIMENSION
stil = STYLE BEFEHL
culoare = COLOR

\seteazapaleta [...]

* NAME

\seteazaparafrage [¹...] [²...,...]
OPT OPT

1 NAME
 2 fiecare NUMMER
 3 n = NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 latime = DIMENSION
 distanta = DIMENSION
 inaltime = DIMENSION ajustat
 sus = BEFEHL
 jos = BEFEHL
 aliniere = inherits: \seteazaalinierea
 intern = BEFEHL
 comanda = BEFEHL
 rigla = on dezactivat
 grosimerigla = DIMENSION
 culoarerigla = COLOR
 stil = STYLE BEFEHL
 culoare = COLOR

\seteazaparafrage [¹...] [²...,...]
OPT

1 NAME:NUMMER
 2 n = NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 latime = DIMENSION
 distanta = DIMENSION
 inaltime = DIMENSION ajustat
 sus = BEFEHL
 jos = BEFEHL
 aliniere = inherits: \seteazaalinierea
 intern = BEFEHL
 comanda = BEFEHL
 rigla = on dezactivat
 grosimerigla = DIMENSION
 culoarerigla = COLOR
 stil = STYLE BEFEHL
 culoare = COLOR

\seteazaplasareaopozita [...,...*...]

* stare = start stop
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL

\seteazaprograme [...,...*...]

* stil = STYLE BEFEHL
 culoare = COLOR

\seteazareferinte [...,...*...]

* stare = start stop
 expansiune = da nu xml
 autofile = da nu
 export = da nu
 stanga = BEFEHL
 dreapta = BEFEHL
 latime = DIMENSION
 douafete = da nu
 interactiune = eticheta text simbol tot
 separator = BEFEHL
 prefix = + - TEXT

\seteazaregistru [¹...] [²...,...]

OPT

```

1  NAME NAME:NUMBER

2  referencemethod      = avans
   expansiune           = da nu xml
   numarpropriu         = da nu
   xmlsetup             = NAME
   alternativ            = a b A B
   metoda               = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress             = da nu tot
   criteriu             = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   pageprefixconnector  = BEFEHL
   pageprefix           = da nu
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot
   latimemaxima         = DIMENSION
   indicator            = da nu
   inainte              = BEFEHL
   dupa                 = BEFEHL
   comanda              = \...##1
   comandatext          = \...##1
   deeptextcommand      = \...##1
   comandapagina        = \...##1
   distanta             = DIMENSION
   interactiune         = text numarpagina
   numarpagina          = da nu
   simbol               = a n niciunul 1 2 BEFEHL
   language             = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stiltext             = STYLE BEFEHL
   culoaretext          = COLOR
   stilpagina           = STYLE BEFEHL
   culoarepagina        = COLOR
   n                    = NUMMER
   balanta              = da nu
   aliniere             = inherits: \seteazaalinierea
   numberorder          = numere

```


\seteazaregistru [...,¹...] [...,²...] [...,³...,...]
OPT OPT

```

1  NAME
2  NUMMER
3  referencemethod      = avans
   expansiune           = da nu xml
   numarpropriu         = da nu
   xmlsetup             = NAME
   alternativ            = a b A B
   metoda               = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
   compress             = da nu tot
   criteriu             = local text curent precedent tot ABSCHNITT
   pageprefixseparatorset = BEFEHL
   pageprefixconversionset = NAME
   pageprefixstarter    = BEFEHL PROCESSOR->BEFEHL
   pageprefixstopper    = BEFEHL PROCESSOR->BEFEHL
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   pageprefixconnector  = BEFEHL
   pageprefix           = da nu
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = BEFEHL PROCESSOR->BEFEHL
   pagestopper          = BEFEHL PROCESSOR->BEFEHL
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
   latimemaxima         = DIMENSION
   indicator            = da nu
   inainte              = BEFEHL
   dupa                 = BEFEHL
   comanda              = \...##1
   comandatext          = \...##1
   deeptextcommand      = \...##1
   comandapagina        = \...##1
   distanta             = DIMENSION
   interactiune         = text numarpagina
   numarpagina          = da nu
   simbol               = a n niciunul 1 2 BEFEHL
   language             = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn SPRACHE
   stil                 = STYLE BEFEHL
   culoare              = COLOR
   stiltext             = STYLE BEFEHL
   culoaretext          = COLOR
   stilpagina           = STYLE BEFEHL
   culoarepagina        = COLOR
   n                    = NUMBER
   balanta              = da nu
   aliniere             = inherits: \seteazaalinierea
   numberorder          = numere

```

\setareREGISTER [...,¹...] [...,²...,...]
OPT

```

1  NUMMER
2  inherits: \seteazaregistru

```

instances:

\seteazarigletext [...,^{*}...,...]

```

*  inainte             = BEFEHL
   dupa                 = BEFEHL
   intre               = BEFEHL
   grosimerigla        = DIMENSION
   locatie             = stanga inmarginie
   stil                = STYLE BEFEHL
   culoare              = COLOR
   culoarerigla        = COLOR
   latime              = DIMENSION
   inaltime            = DIMENSION
   distanta            = DIMENSION
   corectieadancime    = on dezactivat
   fonttext            = inherits: \seteazafonttext

```

\seteazarigleumplere [...,*...]

* inainte = BEFEHL
dupa = BEFEHL
n = NUMMER
spatiereinterliniara = mic mediu mare NUMMER
distanta = DIMENSION
latime = ajustat broad DIMENSION
separator = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR

\seteazarotare [...,*...]

* locatie = ajustat broad adancime inalt centru implicit normal
rotatie = stanga dreapta intern extern NUMMER
inherits: \seteazainconjurat

\seteazasimbol [...]

* NAME

\seteazasinonime [...,¹...] [...,*²...]
OPT

1 SINGULAR
2 expansiune = da nu xml
alternativ = primul ultim normal NAME
urmatorul = BEFEHL
comanda = \...##1##2##3
comandatext = \...##1
synonymcommand = \...##1
language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
criteriu = curent precedent local text tot ABSCHNITT
stil = STYLE BEFEHL
culoare = COLOR
stiltext = STYLE BEFEHL
culoarettext = COLOR
stilsinonim = STYLE BEFEHL
culoaresinonim = COLOR

\seteazasortare [...,¹...] [...,*²...]
OPT

1 SINGULAR
2 expansiune = da nu xml
alternativ = primul ultim normal NAME
urmatorul = BEFEHL
comanda = \...##1##2##3
comandatext = \...##1
synonymcommand = \...##1
language = implicit DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scن SPRACHE
metoda = implicit inainte dupa primul ultim ch mm zm pm mc zc pc uc
criteriu = curent precedent local text tot ABSCHNITT
stil = STYLE BEFEHL
culoare = COLOR
stiltext = STYLE BEFEHL
culoarettext = COLOR
stilsinonim = STYLE BEFEHL
culoaresinonim = COLOR

\seteazaspatiu [...]
OPT

* fixat impachetat broad

\seteazaspatualb [...,*...]
OPT

* fix fixat flexibil linie jumatatelinie quarterline niciunul mic mediu mare implicit DIMENSION

`\seteazaspatiinterliniar [...1,...] [...2,...]`
OPT

1 NAME

2 linie = DIMENSION
 inaltime = NUMMER
 inaltime = NUMMER
 inaltime minima = NUMMER
 mindepth = NUMMER
 distanta = DIMENSION
 sus = NUMMER inaltime
 jos = NUMMER
 dilatat = NUMMER
 shrink = NUMMER

`\seteazaspatiinterliniar [...*,...]`
OPT

* on dezactivat reset auto mic mediu mare NUMMER DIMENSION

`\seteazaspatiinterliniar [...*]`

* NAME

`\seteazasubsol [...1] [...2,...]`
OPT

1 text margine bordura

2 inherits: \setuplayoutelement

`\seteazasus [...1] [...2,...]`
OPT

1 text margine bordura

2 inherits: \setuplayoutelement

`\seteazatabele [...*,...]`

* text = DIMENSION max
 split = da nu repetat auto
 frame = on dezactivat
 NL = inherits: \blanc
 VL = mic mediu mare niciunul NUMMER
 HL = mic mediu mare niciunul NUMMER
 distanta = mic mediu mare niciunul
 aliniere = stanga centru dreapta
 comenzi = BEFEHL
 fonttext = inherits: \seteazafonttext
 grosimerigla = DIMENSION
 inaltime = strut NUMMER
 inaltime = strut NUMMER
 openup = DIMENSION

`\seteazatabulatori [...1] [...2] [...3,...]`
OPT OPT

1 NAME

2 NAME

3 inherits: \setuptabulation

`\seteazatext [...1] [...2,...]`
OPT

1 text margine bordura

2 inherits: \setuplayoutelement

`\seteazatexteantet` $\begin{smallmatrix} [\dots]^1 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^2 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^3 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^4 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^5 \\ \text{OPT} \end{smallmatrix}$

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextejos` $\begin{smallmatrix} [\dots]^1 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^2 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^3 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^4 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^5 \\ \text{OPT} \end{smallmatrix}$

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextesubsol` $\begin{smallmatrix} [\dots]^1 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^2 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^3 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^4 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^5 \\ \text{OPT} \end{smallmatrix}$

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextesus` $\begin{smallmatrix} [\dots]^1 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^2 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^3 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^4 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^5 \\ \text{OPT} \end{smallmatrix}$

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\seteazatextetext` $\begin{smallmatrix} [\dots]^1 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^2 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^3 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^4 \\ \text{OPT} \end{smallmatrix}$ $\begin{smallmatrix} [\dots]^5 \\ \text{OPT} \end{smallmatrix}$

- 1 text margine bordura
- 2 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 3 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\setareLABELtext` $\begin{smallmatrix} [\dots]^1 \\ \text{OPT} \end{smallmatrix}$ $[\dots, \dots \overset{2}{=} \dots, \dots]$

- 1 SPRACHE
- 2 KEY = VALUE

instances:

\seteazatitlu [...¹,...] [...²,...]

OPT

```

1  ABSCHNITT

2  frontpartlabel      = NAME
   bodypartlabel       = NAME
   appendixlabel       = NAME
   backpartlabel       = NAME
   expansiune          = da nu xml
   catcodes             = NAME
   sectionresetset     = NAME
   sectionseparatorset = NAME
   sectionconversionset = NAME
   conversie           = NAME
   sectionstarter      = BEFEHL PROCESSOR->BEFEHL
   sectionstopper      = BEFEHL PROCESSOR->BEFEHL
   sectionset          = NAME
   sectionsegments     = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:*
                        ABSCHNITT:tot
   referenceprefix     = + - TEXT
   stil                = STYLE BEFEHL
   culoare             = COLOR
   stiltext            = STYLE BEFEHL
   culoaretext         = COLOR
   stilnumar           = STYLE BEFEHL
   culoarenumar        = COLOR
   cuplare             = ABSCHNITT
   numarpropriu        = da nu
   beforesection       = BEFEHL
   aftersection        = BEFEHL
   insidesection       = BEFEHL
   numarincrement      = da nu lista gol
   punetitlu           = da nu ascuns gol
   numar              = da nu
   pagina              = inherits: \pagina
   marcaje             = pagina reset
   antet               = start stop inalt niciunul normal gol faramarcare NAME
   text                = start stop inalt niciunul normal gol faramarcare NAME
   subsol              = start stop inalt niciunul normal gol faramarcare NAME
   inainte             = BEFEHL
   dupa                = BEFEHL
   intre               = BEFEHL
   continua            = da nu
   alinieretitlu       = da nu obiectmobil
   spatiereinterliniara = NAME
   interactiune        = lista referinta
   internalgrid         = NAME
   grid               = normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu
                        jos niciunul linie strut box min max centru NAME
   aliniere            = inherits: \seteazaalinierea
   toleranta           = inherits: \seteazatoleranta
   strut               = da nu
   suspenda            = linie broad ajustat niciunul NUMMER
   margine             = DIMENSION
   aliniaturmator      = da nu auto
   alternativ           = text paragraf normal margine inmargine sus centru subsol reverse textmarginal NAME
   latime              = DIMENSION
   numberwidth         = DIMENSION
   latimetext          = DIMENSION
   distanta            = DIMENSION
   textdistance        = DIMENSION
   comandainainte      = BEFEHL
   comandadupa         = BEFEHL
   comanda             = \...##1##2
   comandatext         = \...##1
   deeptextcommand     = \...##1
   comandanumar        = \...##1
   deepnumbercommand   = \...##1

```

\seteazatitluri [...¹,...] [...²,...]

OPT

```

1  ABSCHNITT

2  inherits: \seteazatitlu

```

\seteazatoleranta [...*,...]

* orizontal vertical foartestRICT strict tolerant foartetolerant spatiu dilatat

```
* reset auto start aleator NUMMER
```

1 NAME

```

2      optiune = mp lua xml parsed-xml nested tex context niciunul NAME
      comanda = CSNAME
      stanga  = BEFEHL
      dreapta = BEFEHL
      tab     = da nu NUMMER
      compact = absolut ultim tot
      escape  = da nu TEXT PROCESSOR->TEXT
      stil    = STYLE BEFEHL
      culoare = COLOR
      linii   = da nu normal despsilabe
      spatiu  = on dezactivat normal fixat dilatat

```

```
*
margineimpara = DIMENSION
marginepara   = DIMENSION
margine       = da nu standard DIMENSION
optiune       = mp lua xml parsed-xml nested tex context niciunul NAME
stil          = STYLE BEFEHL
culoare       = COLOR
alinierere    = inherits: \seteazaalinierere
linii         = da nu normal despsilabe
spatiu        = on dezactivat normal fixat dilatat
keepetogether = da nu
inainte       = BEFEHL
dupa          = BEFEHL
strip         = da nu NUMMER
range         = NUMMER NAME
tab           = da nu NUMMER
escape        = da nu TEXT PROCESSOR->TEXT
aliniaturmator = da nu auto
continua      = da nu
start         = NUMMER
stop          = NUMMER
pas           = NUMMER
numerotare    = fisier linie nu
blanc         = inherits: \blanc
```

```
* stil      = STYLE BEFEHL
  culoare  = COLOR
```

1 NAME

2 export nature pdf

3 inline display mixed

1 NAME

2 DIMENSION

1 NAME

2 CONTENT

`\setevariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setevariables [...][...2...]`

- 1 NAME
- 2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\setfirstline [...]`
OPT

- * NAME

`\setflag {...}`

- * NAME

`\setfont ...`

- * FONT

`\setfontcolorsheme [...]`

- * NAME

`\setfontfeature {...}`

- * NAME

`\setfontsolution [...]`

- * NAME

`\setfontstrut`

`\setgmeasure {...} {...}`

- 1 NAME
- 2 DIMENSION

`\setgvalue {...} {...}`

- 1 NAME
- 2 CONTENT

`\setgvariable {...} {...} {...}`

- 1 NAME
- 2 KEY
- 3 VALUE

`\setgvariables [...][...2...]`

- 1 NAME
- 2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

<pre> \setboxregister ¹... {²...} 1 CSNAME NUMMER 2 CONTENT </pre>
<pre> \sethyphenatedurlafter {...} * TEXT </pre>
<pre> \sethyphenatedurlbefore {...} * TEXT </pre>
<pre> \sethyphenatedurlnormal {...} * TEXT </pre>
<pre> \sethyphenationfeatures [...,[*]...] OPT * NAME reset </pre>
<pre> \setinitial [¹...] [²..._{OPT}...] OPT 1 NAME 2 inherits: \setupinitial </pre>
<pre> \setinjector [¹...] [...²,...] [³...] 1 NAME 2 NUMMER 3 BEFEHL </pre>
<pre> \setinteraction [...] * ascuns NAME </pre>
<pre> \setinterfacecommand {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceconstant {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \setinterfaceelements {¹...} {²...} 1 NAME 2 NAME </pre>
<pre> \setinterfacemessage {¹...} {²...} {³...} 1 NAME 2 titlu NAME NUMMER 3 TEXT </pre>

<pre> \setinterfacevariable {...} {...} 1 NAME 2 NAME </pre>
<pre> \setinternalrendering [...] [...] {...} 1 NAME 2 auto embed 3 CONTENT </pre>
<pre> \setitaliccorrection [...] * reset 1 2 </pre>
<pre> \setJSreamble {...} {...} 1 NAME 2 CONTENT </pre>
<pre> \setlayer [...] [...²_{OPT}] [...,³_{OPT}...,...] {...⁴} 1 NAME 2 stanga dreapta par impar 3 inherits: \setuplayer 4 CONTENT </pre>
<pre> \setlayerframed [...] [...,²_{OPT}...,...] [...,³_{OPT}...,...] {...⁴} 1 NAME 2 inherits: \setuplayer 3 inherits: \seteazainconjurat 4 CONTENT </pre>
<pre> \setlayerframed [...] [...,²_{OPT}...,...] {...³} 1 NAME 2 inherits: \setuplayerinherits: \seteazainconjurat 3 CONTENT </pre>
<pre> \setlayertext [...] [...,²_{OPT}...,...] [...,³_{OPT}...,...] {...⁴} 1 NAME 2 inherits: \setuplayer 3 aliniere = inherits: \seteazaalinierea latime = DIMENSION stil = STYLE BEFEHL culoare = COLOR 4 TEXT </pre>
<pre> \setlinefiller [...] * filler NAME </pre>
<pre> \setlocalhsize [..._{OPT}] * [-+]DIMENSION </pre>

`\setMPlayer [...]1 [...]2 [...,...3...,...]OPT {...}4`

- 1 NAME
- 2 NAME
- 3 inherits: \setupplayer
- 4 CONTENT

`\setMPpositiongraphic {...}1 {...}2 {...,...3...,...}OPT`

- 1 NAME
- 2 NAME
- 3 KEY = VALUE

`\setMPpositiongraphicrange {...}1 {...}2 {...}3 {...,...4...,...}OPT`

- 1 NAME
- 2 NAME
- 3 NAME
- 4 KEY = VALUE

`\setMPtext {...}1 {...}2`

- 1 NAME
- 2 TEXT

`\setMPvariable [...]1 [...]2`

- 1 NAME
- 2 KEY = VALUE

`\setMPvariables [...]1 [...,...2...,...]OPT`

- 1 NAME
- 2 KEY = VALUE

`\setmainbodyfont`

`\setmainparbuilder [...]*`

- * implicit oneline basic NAME

`\setmarker [...]1 [...]2`

- 1 NAME
- 2 NUMMER

`\setmarking [...]1 {...}2`

- 1 BESCHRIFTUNG
- 2 TEXT

`\setmathstyle {...,*...}`

- * display text script scriptscript cramped uncramped normal impachetat mic mare NAME

<pre> \setmeasure {...} {...} 1 NAME 2 DIMENSION </pre>
<pre> \setmessagetext {...} {...} 1 NAME 2 NAME NUMBER </pre>
<pre> \setmode {...} * NAME </pre>
<pre> \setnostrut </pre>
<pre> \setnote [...]¹ [...,²...] {...}³ OPT 1 NAME 2 REFERENCE 3 TEXT </pre>
<pre> \setnotetext [...]¹ [...,²...] {...}³ OPT 1 NAME 2 REFERENCE 3 TEXT </pre>
<pre> \setnotetext [...]¹ [...,²...,...] 1 NAME 2 titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE </pre>
<pre> \setnote [...]¹ [...,²...,...] 1 NAME 2 titlu = TEXT semncarte = TEXT lista = TEXT referinta = REFERENCE </pre>
<pre> \setobject {...}¹ {...}² \...³ {...}⁴ 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>
<pre> \setoldstyle </pre>
<pre> \setpagegrid [...,¹...,²...] {...} OPT 1 c = NUMBER r = NUMBER optiune = niciunul 2 CONTENT </pre>

<pre>\setpagereference {...} {...,²...}</pre> <p>1 NAME</p> <p>2 REFERENCE</p>
<pre>\setpagestate [...]¹ [...]² OPT</pre> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<pre>\setpagestaterealpageno {...} {...}¹ {...}²</pre> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<pre>\setpenalties \... {...}¹ {...}² {...}³</pre> <p>1 CSNAME</p> <p>2 NUMBER</p> <p>3 NUMBER</p>
<pre>\setpercentdimen {...} {...}¹ {...}²</pre> <p>1 DIMENSION CSNAME</p> <p>2 DIMENSION NUMBER</p>
<pre>\setposition {...}</pre> <p>* NAME</p>
<pre>\setpositionbox {...} \... {...}¹ \... {...}² {...}³</pre> <p>1 NAME</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<pre>\setpositiondata {...} {...}¹ {...}² {...}³ {...}⁴</pre> <p>1 NAME</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p>
<pre>\setpositiondataplus {...} {...}¹ {...}² {...}³ {...}⁴ {...,⁵...}</pre> <p>1 NAME</p> <p>2 DIMENSION</p> <p>3 DIMENSION</p> <p>4 DIMENSION</p> <p>5 TEXT</p>
<pre>\setpositiononly {...}</pre> <p>* NAME</p>

<pre> \setpositionplus {...} {...,²...} \... {⁴...} 1 NAME 2 TEXT 3 CSNAME 4 CONTENT </pre>
<pre> \setpositionstrut {...} * NAME </pre>
<pre> \setprofile [...] * niciunul fixat strict halffixed quarterfixed eightsfixed NAME </pre>
<pre> \setrandomseed {...} * NUMMER </pre>
<pre> \setreference [...,¹...] [...,²...,...] 1 REFERENCE 2 KEY = VALUE </pre>
<pre> \setreferencedobject {¹...} {²...} \... {⁴...} 1 NAME 2 NAME 3 CSNAME 4 CONTENT </pre>
<pre> \setregisterentry [...¹] [...,²...,...] [...,³...,...] OPT 1 NAME 2 eticheta = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativ = TEXT 3 KEY = VALUE </pre>
<pre> \setreplacement [...] * reset NAME </pre>
<pre> \setrigidcolumnbalance ... * CSNAME NUMMER </pre>
<pre> \setrigidcolumnhsize {¹...} {²...} {³...} 1 DIMENSION 2 DIMENSION 3 NUMMER </pre>

<p><code>\setscript [...]</code></p> <p>* hangul hanzi nihongo ethiopic thai test NAME</p>
<p><code>\setsectionblock [...]¹ [...,...²...,...]²</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 semncarte = TEXT</p>
<p><code>\setsimplecolumnhsize [...,...[*]...,...]</code></p> <p>* n = NUMMER latime = DIMENSION distanta = DIMENSION linii = NUMMER</p>
<p><code>\setsmallbodyfont</code></p>
<p><code>\setsmallcaps</code></p>
<p><code>\setstackbox {...}¹ {...}² {...}³</code></p> <p>1 NAME</p> <p>2 NAME</p> <p>3 CONTENT</p>
<p><code>\setstructurepageregister [...]¹ [...,...²...,...]² [...,...³...,...]³</code> <small>OPT</small></p> <p>1 NAME</p> <p>2 eticheta = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativ = TEXT</p> <p>3 KEY = VALUE</p>
<p><code>\setstrut</code></p>
<p><code>\setsuperiors</code></p>
<p><code>\setsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\settabular</code></p>
<p><code>\settaggedmetadata [...,...[*]...,...]</code></p> <p>* KEY = VALUE</p>

`\setttextcontent [...]1 [...]2 [...]3 [...]4 [...]5`

OPT OPT

- 1 sus antet text subsol subsol
- 2 text margine bordura
- 3 stanga centru dreapta
- 4 data numarpagina BESCHRIFTUNG TEXT BEFEHL
- 5 data numarpagina BESCHRIFTUNG TEXT BEFEHL

`\settightobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightreferencedobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settightunreferencedobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

`\settrialtypesetting`

`\setuevalue {...}1 {...}2`

- 1 NAME
- 2 CONTENT

`\setugvalue {...}1 {...}2`

- 1 NAME
- 2 CONTENT

`\setunreferencedobject {...}1 {...}2 \... {...}3 {...}4`

- 1 NAME
- 2 NAME
- 3 CSNAME
- 4 CONTENT

\setupattachment [...,¹...] [...,²...]
OPT

```

1  NAME

2  titlu      = TEXT
   subtitlu   = TEXT
   autor      = TEXT
   fisier     = FILE
   nume       = NAME
   buffer     = BUFFER
   stare      = start stop
   metoda     = normal ascuns
   simbol     = Graph Paperclip Pushpin Default
   latime     = ajustat DIMENSION
   inaltime   = ajustat DIMENSION
   inaltime   = ajustat DIMENSION
   culoare    = COLOR
   textlayer  = NAME
   locatie    = bordurastanga borduradreaapta inmarginestanga marginedreaapta text inalt niciunul
   distanta   = DIMENSION

```

\setupbackend [...,*...]

```

*  export     = da FILE
   xhtml      = FILE
   fisier     = FILE
   intent     = NAME
   spatiu     = da nu
   xmpfile    = FILE
   format     = version implicit NAME
   nivel      = NUMMER
   optiune    = totdeauna niciodata
   profile    = FILE

```

\setupbar [...,¹...] [...,²...]
OPT

```

1  NAME

2  culoare      = COLOR
   continua     = da nu tot
   gol          = da nu
   unitate      = ex em pt in cm mm sp bp pc dd cc nc
   order        = primplan fundal
   grosimerigla = DIMENSION
   metoda       = NUMMER
   offset       = NUMMER
   dy           = NUMMER
   max          = NUMMER
   foregroundstyle = STYLE BEFEHL
   foregroundcolor = COLOR
   mp           = NAME
   stanga       = TEXT
   dreapta      = TEXT

```

\setupbleeding [...,*...]

```

*  latime      = DIMENSION
   inaltime    = DIMENSION
   offset      = DIMENSION
   hoffset     = DIMENSION
   voffset     = DIMENSION
   locatie     = t b l r bl lb br rb tl lt tr rt
   dilatata    = da nu
   pagina      = da nu

```

\setupbookmark [...,*...]

```

*  fortat      = da nu
   numar       = da nu
   numberseparatorset = NAME
   numberconversionset = NAME
   numberstarter = BEFEHL
   numberstopper = BEFEHL
   numbersegments = NUMMER NUMMER:NUMMER NUMMER:* NUMMER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
   sectionblock = da nu

```


\setupbtx [¹...] [²...,...]

OPT

```
1  NAME

2  specification = implicit apa aps NAME
   dataset      = implicit NAME
   comanda      = \...##1
   stanga       = BEFEHL
   dreapta      = BEFEHL
   authorconversion = normal normalshort normalinverted invertedshort short
   etallimit    = NUMMER
   etaldisplay  = NUMMER
   etaloption   = ultim
   stopper      = initials
   interactiune = start stop tot
   alternativ    = implicit category entry short pagina num textnum an index tag keywords autor authoryears
                  authornum authoryear
   sorttype     = normal reverse
   compress     = da nu
   implicit     = implicit NAME
   stil         = STYLE BEFEHL
   culoare      = COLOR
```

\setupbtxdataset [¹...,...] [²...,...]

OPT

```
1  NAME

2  language = SPRACHE
```

\setupbtxlist [¹...] [²...,...]

OPT

```
1  NAME

2  inherits: \setezalista
```

\setupbtxregister [¹...,...] [²...,...]

OPT

```
1  NAME

2  stare      = start stop
   dataset    = NAME
   field      = keyword range numarpagina autor
   register   = NAME
   metoda     = once
   alternativ  = normalshort invertedshort
   stil       = STYLE BEFEHL
   culoare    = COLOR
```

\setupbtxrendering [¹...,...] [²...,...]

OPT

```
1  NAME

2  staretext   = start stop
   pagestate   = start stop
   separator    = BEFEHL
   criteriu    = precedent cite aici tot niciunul
   specification = NAME
   titlu       = TEXT
   inainte     = BEFEHL
   dupa        = BEFEHL
   dataset     = NAME
   metoda      = dataset fortat local global niciunul
   sorttype    = short dataset lista referinta folosit implicit cite index
   repeta      = da nu
   group       = NAME
   numerotare  = da nu num index tag short pagina
```

\setupbtx [...]

```
*  NAME
```

`\setupbutton [...1,...] [...2,...]`
OPT

1 NAME

2 stare = start stop
 aceeasipagina = da nu gol niciunul normal implicit
 stil = STYLE BEFEHL
 culoare = COLOR
 culoarecontrast = COLOR
 alternativ = ascuns
 inherits: \seteazainconjurat

`\setupcharacterkerning [...1,...] [...2,...]`
OPT

1 NAME

2 factor = max NUMBER
 latime = DIMENSION
 features = NAME
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupcharacterspacing [...1] [...2] [...3,...]`
OPT

1 NAME

2 NUMMER

3 stanga = NUMBER
 dreapta = NUMBER
 alternativ = 0 1

`\setupchemical [...1,...] [...2,...]`
OPT

1 NAME

2 strut = inherits: \value-strut
 latime = ajustat niciunul NUMBER
 inaltime = ajustat niciunul NUMBER
 stanga = ajustat niciunul NUMBER
 dreapta = ajustat niciunul NUMBER
 sus = ajustat niciunul NUMBER
 jos = ajustat niciunul NUMBER
 scala = mic mediu mare normal NUMBER
 rotatie = NUMBER
 symalinie = auto
 axa = on dezactivat
 culoareframe = COLOR
 grosimerigla = DIMENSION
 offset = DIMENSION
 unitate = DIMENSION
 factor = NUMBER
 frame = on dezactivat
 culoarerigla = COLOR
 fonttext = inherits: \seteazafonttext
 dimensiune = mic mediu mare
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupchemicalframed [...1,...] [...2,...]`
OPT

1 NAME

2 inherits: \seteazainconjurat

`\setupcollector [...1,...] [...2,...]`
OPT

1 NAME

2 rotatie = stanga dreapta intern extern NUMBER
 colt = stanga centru dreapta sus subsol
 x = DIMENSION
 y = DIMENSION
 hoffset = DIMENSION
 voffset = DIMENSION
 locatie = stanga centru dreapta sus subsol linie l c r m t b g
 stare = start stop

\setupcolumnspan [...,^{*}...]

* n = NUMBER
inherits: \seteazainconjurat

\setupcombination [...,¹...] [...,²...]
OPT

1 NAME
2 nx = NUMBER
ny = NUMBER
latime = ajustat DIMENSION
inaltime = ajustat DIMENSION
locatie = stanga centru dreapta sus subsol
distanta = DIMENSION
alternativ = eticheta text
alinie = inherits: \seteazaalinie
continua = da nu
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR

\setupcounter [...,¹...] [...,²...]
OPT

1 NAME
2 start = NUMBER
counter = NAME
metoda = pagina
stare = start stop
mod = bypagina byblock bytext byantet byABSCHNITT
prefix = da nu
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
numberorder = reverse
numberseparatorset = NAME
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
type = primul precedent urmatorul ultim numar
criteriu = strict positiv tot
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupdataset [...,^{*}...]

* intarziere = da nu

`\setupdelimitedtext [...1,...] [...2...]`
OPT

```
1  NAME

2  inainte      = BEFEHL
   dupa         = BEFEHL
   language     = local global SPRACHE
   metoda       = font
   repeta       = da nu
   locatie      = text paragraf margine
   stanga       = BEFEHL
   mijloc       = BEFEHL
   dreapta      = BEFEHL
   nextleft     = BEFEHL
   nextright    = BEFEHL
   spatiuinainte = inherits: \blanc
   spatiudupa   = inherits: \blanc
   marginestanga = da nu standard DIMENSION
   marginedreapta = da nu standard DIMENSION
   aliniat      = inherits: \seteazaaliniat
   aliniaturmator = da nu auto
   stil         = STYLE BEFEHL
   culoare      = COLOR
   stilsimbol   = STYLE BEFEHL
   culoaresimbol = COLOR
```

`\setupdescription [...1,...] [...2...]`
OPT

```
1  NAME

2  titlu        = da nu
   nivel        = NUMMER
   text         = TEXT
   headcommand  = \...##1
   inainte      = BEFEHL
   dupa         = BEFEHL
   intre        = BEFEHL
   alternativ    = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                  outermargin serried suspendat sus comanda NAME
   aliniere     = inherits: \seteazaalinierea
   headalign    = inherits: \seteazaalinierea
   aliniat      = inherits: \seteazaaliniat
   display      = da nu
   aliniaturmator = da nu auto
   latime       = ajustat broad linie DIMENSION
   distanta     = niciunul DIMENSION
   suspenda     = ajustat broad niciunul margine NUMMER
   closesymbol  = BEFEHL
   closecommand = \...##1
   expansiune   = da nu xml
   exemplu      = TEXT
   margine      = da nu standard DIMENSION
   stil         = STYLE BEFEHL
   culoare      = COLOR
   stiltitlu    = STYLE BEFEHL
   culoaretitlu = COLOR
```

`\setupdirections [...*...]`

```
*  bidi    = on dezactivat local global
   metoda  = unu doi implicit
   fences  = da nu
```

`\setupdocument [...*...]`

```
*  inainte      = BEFEHL
   dupa         = BEFEHL
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY          = VALUE
```

`\setupeffect [...,1...] [...,2...,...]`
OPT

1 NAME

2 metoda = niciunul comanda
dilatata = NUMMER
grosimerigla = NUMMER
alternativ = normal intern extern ambele ascuns dilatata

`\setupenumeration [...,1...] [...,2...,...]`
OPT

1 NAME

2 titlu = da nu
numar = da nu
comandanumar = \...##1
distantatitlu = DIMENSION
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
titlecommand = \...##1
titleleft = BEFEHL
titleright = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
simbol = BEFEHL
starter = BEFEHL
stopper = BEFEHL
cuplare = NAME
counter = NAME
nivel = NUMMER
text = TEXT
headcommand = \...##1
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
alternativ = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
outermargin serried suspendat sus comanda NAME

alinieri = inherits: \seteazaalinieria
headalign = inherits: \seteazaalinieria
aliniat = inherits: \seteazaaliniat
display = da nu
aliniaturmator = da nu auto
latime = ajustat broad linie DIMENSION
distanta = niciunul DIMENSION
suspenda = ajustat broad niciunul margine NUMMER
closesymbol = BEFEHL
closecommand = \...##1
expansiune = da nu xml
exemplu = TEXT
margine = da nu standard DIMENSION
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
inherits: \setupcounter

`\setupenv [...,*...,...]`

* set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\setupexport [...,*...,...]`

* alinieri = flushleft centru flushright normal
fonttext = DIMENSION
latime = DIMENSION
titlu = TEXT
subtitlu = TEXT
autor = TEXT
alternativ = html div
properties = da nu
hyphen = da nu
cssfile = FILE
primapagina = FILE
ultimpagina = FILE

`\setupexternalfigure [...,1...] [...,2...,...]`
OPT

```

1  NAME

2  latime           = DIMENSION
   inalttime        = DIMENSION
   eticheta         = NAME
   pagina           = NUMMER
   obiect           = da nu
   prefix           = TEXT
   metoda           = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
   controale        = da nu
   previzualizare   = da nu
   mask             = niciunul
   rezolutie        = NUMMER
   culoare          = COLOR
   arguments        = TEXT
   repeta           = da nu
   factor           = ajustat broad max auto implicit
   hfactor          = ajustat broad max auto implicit
   factorw          = ajustat broad max auto implicit
   latimemaxima     = DIMENSION
   inaltimemaxima   = DIMENSION
   equalwidth       = DIMENSION
   equalheight      = DIMENSION
   scala            = NUMMER
   xscala           = NUMMER
   yscala           = NUMMER
   s                = NUMMER
   sx               = NUMMER
   sy               = NUMMER
   linii            = NUMMER
   locatie          = local global implicit
   director         = PATH
   optiune          = test incadrat gol
   foregroundcolor   = COLOR
   reset            = da nu
   fundal           = culoare primplan NAME
   frame            = on dezactivat
   culoarefundal    = COLOR
   aliniere         = inherits: \setezaalinierea
   xmax             = NUMMER
   ymax             = NUMMER
   frames           = on dezactivat
   interactiune     = da tot niciunul referinta layer semncarte
   fonttext         = DIMENSION
   comment          = BEFEHL TEXT
   dimensiune       = niciunul media crop trim art
   cache            = PATH
   resources        = PATH
   display          = FILE
   conversie        = TEXT
   order            = LISTE
   crossreference    = da nu NUMMER

```

`\setupexternalsoundtracks [...,*...,...]`

* optiune = repetat

`\setupfieldbody [...,1...] [...,2...,...]`
OPT

```

1  NAME

2  category = NAME
   inherits: \setupfieldcategory

```

`\setupfieldcategory [...,1...] [...,2...]`
OPT

```

1  NAME

2  start          = NUMBER
   stil           = STYLE BEFEHL
   culoare        = COLOR
   type           = radio sub text linie push check signature
   values         = TEXT
   implicit       = TEXT
   culoareframecamp = COLOR
   culoarefundalcamp = COLOR
   latime         = DIMENSION
   inaltime       = DIMENSION
   inaltime       = DIMENSION
   aliniere       = stanga centru dreapta flushleft center flushright
   n              = NUMBER
   simbol         = NAME
   fieldlayer     = NAME
   optiune        = readonly obligatoriu protejat sortat nedisponibil nocheck fixat fisier ascuns tiparibil auto
   clickintru     = REFERENCE
   clickies       = REFERENCE
   regiuneintrare = REFERENCE
   regiuneiesire  = REFERENCE
   dupatasta      = REFERENCE
   format         = REFERENCE
   verifica       = REFERENCE
   calculeaza     = REFERENCE
   focusin        = REFERENCE
   focusout       = REFERENCE
   openpage       = REFERENCE
   closepage      = REFERENCE

```

`\setupfieldcontentframed [...,1...] [...,2...]`
OPT

```

1  NAME

2  inherits: \seteazainconjuratinherits: \setupfieldcategory

```

`\setupfieldlabelframed [...,1...] [...,2...]`
OPT

```

1  NAME

2  inherits: \seteazainconjurat

```

`\setupfieldtotalframed [...,1...] [...,2...]`
OPT

```

1  NAME

2  inainte      = BEFEHL
   dupa         = BEFEHL
   intre        = BEFEHL
   distanta     = DIMENSION
   alternativ    = reset eticheta incadrat orizontal vertical
   inherits: \seteazainconjurat

```

`\setupfiller [...,1...] [...,2...]`
OPT

```

1  NAME

2  marginestanga = DIMENSION
   marginedreapta = DIMENSION
   stanga        = BEFEHL
   dreapta       = BEFEHL
   alternativ     = simbol dilatat rigla spatiu
   metoda        = local global centru broad
   latime        = DIMENSION
   inaltime      = DIMENSION
   inaltime      = DIMENSION
   offset        = DIMENSION
   distanta      = DIMENSION
   aliniere       = stanga dreapta centru flushleft flushright intern extern
   simbol        = BEFEHL
   stil          = STYLE BEFEHL
   culoare        = COLOR

```

`\setupfirstline [...1,...] [...2,...]`
OPT

1 NAME

2 n = NUMMER
 alternativ = implicit linie cuvant
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupfittingpage [...1,...] [...2,...]`
OPT

1 NAME

2 pagestate = start stop
 comanda = \...##1
 margine = pagina
 scala = NUMMER
 hartie = auto default NAME
 inherits: \seteazainconjurat

`\setupfloatcaption [...1,...] [...2,...]`
OPT

1 NAME

2 suffix = BEFEHL
 suffixseparator = BEFEHL
 suffixstopper = BEFEHL
 locatie = stanga dreapta centru jos inalt grila overlay intern extern innermargin outermargin marginestanga
 marginedreapta lefthanging righthanging suspenda sus subsol dilatat niciunul implicit

comanda = \...##1
 comandanumar = \...##1
 comandatext = \...##1
 spatiuinainte = inherits: \blanc
 spaceinbetween = inherits: \blanc
 spatiudupa = inherits: \blanc
 distanta = DIMENSION
 intre = BEFEHL
 stil = STYLE BEFEHL
 culoare = COLOR
 offsetsus = DIMENSION
 offsetjos = DIMENSION
 numar = da nu niciunul
 group = TEXT
 marginestanga = DIMENSION
 marginedreapta = DIMENSION
 innermargin = DIMENSION
 outermargin = DIMENSION
 aliniere = inherits: \seteazaalinierea
 latime = ajustat max DIMENSION
 latimeminima = ajustat DIMENSION
 latimemaxima = DIMENSION
 inherits: \setupcounter

`\setupfontexpansion [...1] [...2,...]`

1 NAME

2 vector = NAME
 factor = NUMMER
 dilatata = NUMMER
 shrink = NUMMER
 pas = NUMMER

`\setupfontprotrusion [...1] [...2,...]`

1 NAME

2 vector = NAME
 factor = NUMMER
 stanga = NUMMER
 dreapta = NUMMER

`\setupfonts [...*,...]`

* language = nu auto

`\setupfontsolution [...1,...] [...2,...]`
OPT

1 NAME

2 goodies = FILE
 solution = NAME
 less = NAME
 more = NAME
 metoda = preroll split normal reverse aleator
 criteriu = NUMMER

`\setupformula [...1,...] [...2,...]`
OPT

1 NAME

2 locatie = stanga dreapta
 aliniere = stanga centru dreapta flushleft center flushright normal
 strut = da nu
 distanta = DIMENSION
 stanga = BEFEHL
 dreapta = BEFEHL
 spatiuinainte = inherits: \blanc
 spatiudupa = inherits: \blanc
 comandanumar = \...##1
 culoare = COLOR
 stilnumar = STYLE BEFEHL
 culoarenumar = COLOR
 optiune = impachetat tight centru incadrat inherits: \seteazafonttext
 margine = da nu standard DIMENSION
 marginestanga = DIMENSION
 marginedreapta = DIMENSION
 alternativ = NAME
 aliniaturmator = da nu auto
 grid = inherits: \snaptogrid
 frame = numar
 inherits: \setupcounter

`\setupformulaframed [...1,...] [...2,...]`
OPT

1 NAME

2 inherits: \seteazainconjurat

`\setupframedcontent [...1,...] [...2,...]`
OPT

1 NAME

2 stanga = BEFEHL
 dreapta = BEFEHL
 leftoffser = DIMENSION
 offsetdreapta = DIMENSION
 offsetsus = DIMENSION
 offsetjos = DIMENSION
 corectielinie = da nu
 inherits: \seteazainconjurat

`\setupframedtext [...1,...] [...2,...]`
OPT

1 NAME

2 stanga = BEFEHL
 dreapta = BEFEHL
 intern = BEFEHL
 locatie = stanga dreapta centru niciunul
 corectieadancime = on dezactivat
 fonttext = inherits: \seteazafonttext
 aliniat = inherits: \seteazaaliniat
 stil = STYLE BEFEHL
 culoare = COLOR
 inherits: \seteazainconjuratinherits: \setupplacement

`\setupglobalreferenceprefix [...]`

* + - TEXT

`\setupheadalternative [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 alternativ = orizontal vertical undeva
renderingsetup = NAME

`\setuphelp [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 inherits: \seteazainconjurat

`\setuphigh [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 distanta = DIMENSION
up = DIMENSION
stil = STYLE BEFEHL
culoare = COLOR

`\setuphighlight [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 comanda = da nu
stil = STYLE BEFEHL
culoare = COLOR

`\setuphyphenation [...,*...]`

- * metoda = original tex implicit hyphenate expanded traditional niciunul

`\setupindentedtext [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 inainte = BEFEHL
dupa = BEFEHL
distanta = DIMENSION
exemplu = TEXT
text = TEXT
latime = ajustat broad DIMENSION
separator = BEFEHL
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR

`\setupinitial [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 n = NUMMER
m = NUMMER
inainte = BEFEHL
distanta = DIMENSION
hoffset = DIMENSION
voffset = linie DIMENSION
stil = STYLE BEFEHL
culoare = COLOR
font = FONT
text = TEXT
locatie = margine text
metoda = primul ultim auto niciunul

`\setupinsertion [...,1...] [...,2...]`
OPT

- 1 NAME
- 2 locatie = pagina text coloane firstcolumn lastcolumn

\setupitaliccorrection [...,*,...]

* text totdeauna global niciunul

\setupitemgroup [...]¹ [...]² [...]³ [...]⁴ [...]⁵

OPT

OPT

OPT

1 NAME

2 fiecare NUMMER

3 intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine lamargine intext
larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat reverse coloane unu doi trei patru
cinci six seven eight nine standard NUMMER*broad NUMMER*serried orizontal NAME

4 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
inaintetitlu = BEFEHL
dupatitlu = BEFEHL
textstanga = BEFEHL
textdreapta = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
factor = NUMMER
pas = DIMENSION
latime = DIMENSION
distanta = DIMENSION
margine = da nu standard DIMENSION
marginestanga = da nu standard DIMENSION
marginedreapta = da nu standard DIMENSION
aliniere = inherits: \seteazaalinierea
aliniaat = inherits: \seteazaaliniat
start = NUMMER
symaliniere = stanga centru dreapta flushleft center flushright
simbol = NAME
n = NUMMER
aliniaturmator = da nu auto
intern = BEFEHL
comanda = CSNAME
elemente = NUMMER
latimemaxima = DIMENSION
itemalign = stanga dreapta centru flushleft flushright intern extern
alignsymbol = da nu
textdistance = mic mediu mare niciunul spatiu DIMENSION
punestopper = da nu
stil = STYLE BEFEHL
culoare = COLOR
stiltitlu = STYLE BEFEHL
culoaretitlu = COLOR
stilmarcaj = STYLE BEFEHL
culoaremarcaj = COLOR
stilsimbol = STYLE BEFEHL
culoaresimbol = COLOR
inherits: \setupcounter

OPT

2	inainte	=	BEFEHL
	dupa	=	BEFEHL
	intre	=	BEFEHL
	inaintetitlu	=	BEFEHL
	dupatitlu	=	BEFEHL
	textstanga	=	BEFEHL
	textdreapta	=	BEFEHL
	stanga	=	BEFEHL
	dreapta	=	BEFEHL
	factor	=	NUMMER
	pas	=	DIMENSION
	latime	=	DIMENSION
	distanța	=	DIMENSION
	optiune	=	intro aleator continuu impachetat autointro broad text inainte dupa faraalb margine inmargine lamargine intext larg ajustat nofit paragraf unit serried stopper despachetat repetat norepeat reverse coloane unu doi trei patru cinci six seven eight nine standard NUMMER*broad NUMMER*serried orizontal NAME
	margine	=	da nu standard DIMENSION
	marginestanga	=	da nu standard DIMENSION
	marginedreapta	=	da nu standard DIMENSION
	alinieri	=	inherits: \seteazaalinieria
	aliniat	=	inherits: \seteazaaliniat
	start	=	NUMMER
	symaliniere	=	stanga centru dreapta flushleft flushright
	simbol	=	NAME
	n	=	NUMMER
	aliniaturmator	=	da nu auto
	intern	=	BEFEHL
	comanda	=	CSNAME
	elemente	=	NUMMER
	latimemaxima	=	DIMENSION
	itemalign	=	stanga dreapta centru flushleft flushright intern extern
	alignsymbol	=	da nu
	textdistance	=	mic mediu mare niciunul spatiu DIMENSION
	punestopper	=	da nu
	stil	=	STYLE BEFEHL
	culoare	=	COLOR
	stiltitlu	=	STYLE BEFEHL
	culoaretitlu	=	COLOR
	stilmarcaj	=	STYLE BEFEHL
	culoaremarcaj	=	COLOR
	stilsimbol	=	STYLE BEFEHL
	culoaresimbol	=	COLOR
	inherits:	=	\setupcounter

OPT

OPT

OPT

```
instances:
```

\setuplabel [...¹,...] [...²,...]

OPT

```

1  NAME

2  titlu           = da nu
   numar          = da nu
   comandanumar   = \...##1
   distantatitlu  = DIMENSION
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   titlecommand   = \...##1
   titleleft      = BEFEHL
   titleright     = BEFEHL
   stanga         = BEFEHL
   dreapta        = BEFEHL
   simbol         = BEFEHL
   starter        = BEFEHL
   stopper        = BEFEHL
   cuplare        = NAME
   counter        = NAME
   nivel          = NUMMER
   text           = TEXT
   headcommand    = \...##1
   inainte        = BEFEHL
   dupa           = BEFEHL
   intre          = BEFEHL
   alternativ      = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
                   outermargin serried suspendat sus comanda intext NAME

   aliniere       = inherits: \seteazaalinierea
   headalign      = inherits: \seteazaalinierea
   aliniat        = inherits: \seteazaaliniat
   display        = da nu
   aliniaturmator = da nu auto
   latime         = ajustat broad linie DIMENSION
   distanta       = niciunul DIMENSION
   suspenda       = ajustat broad niciunul margine NUMMER
   closesymbol    = BEFEHL
   closecommand   = \...##1
   expansiune     = da nu xml
   referenceprefix = + - TEXT
   exemplu        = TEXT
   margine        = da nu standard DIMENSION
   stil           = STYLE BEFEHL
   culoare        = COLOR
   stiltitlu      = STYLE BEFEHL
   culoaretitlu   = COLOR
   inherits: \setupcounter

```

\setuplayer [...¹,...] [...²,...]

OPT

```

1  NAME

2  stare          = start stop continuu urmatorul repetat
   optiune        = test
   pagina         = NUMMER
   latime         = DIMENSION
   inaltime       = DIMENSION
   region         = NAME
   rotatie        = stanga dreapta intern extern NUMMER
   pozitie        = da nu overlay
   hoffset        = max DIMENSION
   voffset        = max DIMENSION
   offset         = DIMENSION
   dx             = DIMENSION
   dy             = DIMENSION
   sx             = NUMMER
   sy             = NUMMER
   x              = DIMENSION
   y              = DIMENSION
   colt           = stanga centru dreapta sus subsol
   locatie        = grila stanga centru dreapta sus subsol linie l c r m t b g
   linie          = NUMMER
   coloana        = NUMMER
   directie       = normal reverse
   douafete       = da nu
   metoda         = ajustat overlay
   repeta         = da
   preset         = lefttop righttop leftbottom rightbottom centru middletop middlebottom middleleft middleright lefttopleft
                   lefttopright NAME

```

`\setuplayeredtext [...1,...] [...2,...]`
OPT

1 NAME
 2 stil = STYLE BEFEHL
 culoare = COLOR
 inherits: \seteazainconjurat

`\setuplayouttext [...1] [...2] [...3,...]`
OPT

1 sus antet text subsol subsol
 2 text margine bordura
 3 stare = start stop gol inalt niciunul normal faramarcare NAME
 stil = STYLE BEFEHL
 culoare = COLOR
 strut = da nu
 n = NUMMER
 inainte = BEFEHL
 dupa = BEFEHL
 stilstanga = STYLE BEFEHL
 stildreapta = STYLE BEFEHL
 culoarestanga = COLOR
 culoaredreapta = COLOR
 latime = DIMENSION
 latimestanga = DIMENSION
 marginedreapta = DIMENSION

`\setuplinefiller [...1,...] [...2,...]`
OPT

1 NAME
 2 locatie = stanga dreapta ambele
 scop = stanga dreapta local
 mp = NAME
 inaltime = DIMENSION
 inaltime = DIMENSION
 distanta = DIMENSION
 threshold = DIMENSION
 grosimerigla = DIMENSION
 inainte = BEFEHL
 dupa = BEFEHL
 culoare = COLOR
 stiltext = STYLE BEFEHL
 culoaretext = COLOR
 aliniere = inherits: \seteazaalinierea

`\setuplinefillers [...1,...] [...2,...]`
OPT

1 NAME
 2 inherits: \setuplinefiller

`\setuplinenote [...1,...] [...2,...]`
OPT

1 NAME
 2 compress = da nu
 compressmethod = separator stopper spatiu
 compressseparator = BEFEHL
 compressdistance = DIMENSION
 inherits: \setupnote

`\setuplinetable [...]1 [...]2 [...,...3...,...]`

OPT OPT

```
1 r c
2 impar par antet NUMMER
3 linii      = ajustat NUMMER
  inainte    = BEFEHL
  dupa       = BEFEHL
  intre      = BEFEHL
  dilatata   = da nu DIMENSION
  latimemaxima = ajustat DIMENSION
  nstanga    = NUMMER
  n          = NUMMER
  repeta     = da nu
  nx         = NUMMER
  latime     = DIMENSION
  inaltime   = ajustat linie DIMENSION
  distanta   = DIMENSION
  offsetstanga = DIMENSION
  offsetdreapta = DIMENSION
  aliniere    = inherits: \seteazaalinierea
  fundal     = culoare
  culoarefundal = COLOR
  xheight    = max DIMENSION
  xdepth     = max DIMENSION
  stil       = STYLE BEFEHL
  culoare    = COLOR
```

`\setuplistalternative [...]1,... [-,...,2...,...]`

OPT

```
1 NAME
2 inainte = BEFEHL
  dupa    = BEFEHL
  comanda = \...##1##2##3
  renderingsetup = NAME
  latime       = DIMENSION
  distanta     = DIMENSION
  dilatata     = DIMENSION
  filler       = BEFEHL
```

`\setuplistextra [...]1,... [-,...,2...,...]`

OPT

```
1 NAME
2 inainte = BEFEHL
  dupa    = BEFEHL
```

`\setuplocalfloats [...,...*...,...]`

```
* inainte = BEFEHL
  dupa    = BEFEHL
  intre    = BEFEHL
```

`\setuplocalinterlinespace [...]1,... [-,...,2...,...]`

OPT

```
1 NAME
2 inherits: \seteazaspatiuinterliniar
```

`\setuplocalinterlinespace [...]*,...`

OPT

```
* on dezactivat reset auto mic mediu mare NUMMER DIMENSION
```

`\setuplocalinterlinespace [...]*`

```
* NAME
```

`\setuplow [...,1...] [...,2...,...]`
OPT

1 NAME
 2 distanta = DIMENSION
 down = DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR

`\setuplowhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 distanta = DIMENSION
 up = DIMENSION
 down = DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR

`\setuplowmidhigh [...,1...] [...,2...,...]`
OPT

1 NAME
 2 up = DIMENSION
 down = DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupMPgraphics [...,*...,...]`

* culoare = local global
 mpy = FILE

`\setupMPinstance [...,1...] [...,2...,...]`
OPT

1 NAME
 2 format = metafun mpost
 initializations = da nu
 setups = NAME
 stiltext = STYLE BEFEHL
 culoaretext = COLOR
 extensions = da nu
 metoda = binary decimal double scaled implicit

`\setupMPpage [...,*...,...]`

* inherits: \setupfittingpage

`\setupMPvariables [...,1] [...,2...,...]`
OPT

1 NAME
 2 KEY = VALUE

`\setupmarginblock [...,1...] [...,2...,...]`
OPT

1 NAME
 2 stare = start stop
 latime = DIMENSION
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 aliniere = inherits: \seteazaalinierea
 stil = STYLE BEFEHL
 culoare = COLOR
 sus = BEFEHL
 jos = BEFEHL
 locatie = stanga dreapta centru inmargine
 stanga = BEFEHL
 dreapta = BEFEHL

`\setupmargindata [...1,...] [...2,...]`
OPT

```

1  NAME

2  strut      = da nu auto cap ajustat linie implicit CHARACTER
   comanda    = \...##1
   latime     = DIMENSION
   aliniere   = inherits: \seteazaalinierea
   anchor     = region text
   locatie    = stanga dreapta intern extern
   metoda    = sus linie primul adancime inaltime
   category   = implicit bordura
   scop       = local global
   optiune    = text paragraf
   margine    = local normal margine bordura
   distanta   = DIMENSION
   hoffset    = DIMENSION
   voffset    = DIMENSION
   dy         = DIMENSION
   spatiujos  = DIMENSION
   threshold  = DIMENSION
   linie      = NUMMER
   stack      = da continuu
   stil       = STYLE BEFEHL
   culoare    = COLOR

```

`\setupmarginframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \seteazainconjurat

```

`\setupmarginrule [...1] [...2,...]`
OPT

```

1  NUMMER

2  inherits: \setupsidebar

```

`\setupmathalignment [...1,...] [...2,...]`
OPT

```

1  NAME

2  n          = NUMMER
   m          = NUMMER
   distanta   = DIMENSION
   aliniere   = stanga centru dreapta normal

```

`\setupmathcases [...1,...] [...2,...]`
OPT

```

1  NAME

2  stanga      = BEFEHL
   dreapta    = BEFEHL
   strut      = da nu
   stil       = STYLE BEFEHL
   distanta   = DIMENSION
   numberdistance = DIMENSION

```

`\setupmathematics [...1,...] [...2,...]`
OPT

```

1  NAME

2  openup           = da nu
   setsimbol       = NAME
   functionstyle    = STYLE BEFEHL
   compact          = da nu
   aliniere         = l2r r2l
   bidi            = da nu
   sygreek          = normal italic niciunul
   lcgreek          = normal italic niciunul
   ucgreek          = normal italic niciunul
   italics          = 1 2 3 4 niciunul reset
   autopunctuation = da nu tot
   setups          = NAME
   domain           = NAME reset
   stiltext         = STYLE BEFEHL
   culoaretext      = COLOR
   functioncolor    = COLOR
   integral         = limits nolimits autolimits displaylimits niciunul
   stylealternative = NAME
   implicit         = normal italic
   fraction         = ams ctx

```

`\setupmathfence [...1,...] [...2,...]`
OPT

```

1  NAME

2  comanda    = da nu
   stanga     = NUMMER
   mijloc     = NUMMER
   dreapta    = NUMMER
   mathstyle  = display text script scriptscript cramped uncramped normal impachetat mic mare
   culoare    = COLOR
   stare     = auto

```

`\setupmathfraction [...1,...] [...2,...]`
OPT

```

1  NAME

2  distantasus = DIMENSION
   distantajos = DIMENSION
   margine     = DIMENSION
   culoare     = COLOR
   strut       = da nu math tight
   alternativ   = intern extern ambele
   rigla       = da nu auto
   stanga      = NUMMER
   dreapta     = NUMMER
   grosimerigla = DIMENSION
   mathstyle   = STYLE BEFEHL
   distanta    = nu niciunul overlay

```

`\setupmathframed [...1,...] [...2,...]`
OPT

```

1  NAME

2  inherits: \seteazainconjurat

```

`\setupmathmatrix [...1,...] [...2,...]`
OPT

```

1  NAME

2  stanga    = BEFEHL
   dreapta   = BEFEHL
   strut     = da nu NUMMER
   aliniere  = stanga centru dreapta normal
   stil      = STYLE BEFEHL
   distanta  = DIMENSION
   locatie   = sus subsol inalt jos lohi normal

```

`\setupmathornament [...,1...] [...,2...,...]`
OPT

1 NAME
 2 alternativ = mp
 culoare = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathradical [...,1...] [...,2...,...]`
OPT

1 NAME
 2 alternativ = implicit normal mp
 culoare = COLOR
 mpoffset = DIMENSION
 mp = NAME

`\setupmathstackers [...,1...] [...,2...,...]`
OPT

1 NAME
 2 stanga = BEFEHL
 dreapta = BEFEHL
 topcommand = \...##1
 bottomcommand = \...##1
 middlecommand = \...##1
 mp = NAME
 mpheight = DIMENSION
 mpdepth = DIMENSION
 mpoffset = DIMENSION
 culoare = COLOR
 hoffset = DIMENSION
 voffset = DIMENSION
 inaltimeminima = DIMENSION
 mindepth = DIMENSION
 mathclass = rel ord
 offset = min max normal
 locatie = sus subsol inalt jos centru NUMMER
 strut = da nu
 alternativ = normal implicit mp
 latimeminima = DIMENSION
 distanta = DIMENSION
 moffset = DIMENSION
 order = normal reverse
 mathlimits = da nu

`\setupmathstyle [...,*,...]`

* display text script scriptscript cramped uncramped normal impachetat mic mare NAME

`\setupmixedcolumns [...,1...] [...,2...,...]`
OPT

1 NAME
 2 grid = inherits: \definegridsnapping
 grosimerigla = DIMENSION
 metoda = otr box
 inainte = BEFEHL
 dupa = BEFEHL
 distanta = DIMENSION
 n = NUMMER
 inaltimemaxima = DIMENSION
 latimemaxima = DIMENSION
 pas = DIMENSION
 profile = NAME
 aliniere = inherits: \seteazaalinierea
 setups = NAME
 balanta = da nu
 splitmethod = niciunul fixat
 alternativ = local global
 internalgrid = linie jumatatelinie
 separator = rigla
 strut = da nu
 culoare = COLOR
 culoarerigla = COLOR
 directie = normal reverse
 inherits: \seteazainconjurat

`\setupmodule [...]1 [...]2...`
OPT

1 FILE
 2 test = da nu
 KEY = VALUE

`\setupnotation [...]1 [...]2...`
OPT

1 NAME
 2 titlu = da nu
 numar = da nu
 type = note
 comandanumar = \...##1
 distantatitlu = DIMENSION
 stiltitlu = STYLE BEFEHL
 culoaretitlu = COLOR
 titlecommand = \...##1
 titleleft = BEFEHL
 titleright = BEFEHL
 stanga = BEFEHL
 dreapta = BEFEHL
 simbol = BEFEHL
 starter = BEFEHL
 stopper = BEFEHL
 cuplare = NAME
 counter = NAME
 nivel = NUMMER
 text = TEXT
 headcommand = \...##1
 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 alternativ = stanga dreapta inmargin instanga indreapta margine marginestanga marginedreapta innermargin
 outermargin serried suspendat sus comanda note NAME
 aliniere = inherits: \seteazaalinierea
 headalign = inherits: \seteazaalinierea
 aliniat = inherits: \seteazaaliniat
 display = da nu
 aliniaturmator = da nu auto
 latime = ajustat broad linie DIMENSION
 distanta = niciunul DIMENSION
 suspenda = ajustat broad niciunul margine NUMMER
 closesymbol = BEFEHL
 closecommand = \...##1
 expansiune = da nu xml
 referenceprefix = + - TEXT
 exemplu = TEXT
 margine = da nu standard DIMENSION
 stil = STYLE BEFEHL
 culoare = COLOR
 stiltitlu = STYLE BEFEHL
 culoaretitlu = COLOR
 inherits: \setupcounter

`\setupnotations [...]1 [...]2...`
OPT

1 NAME
 2 inherits: \setupnotation

\setupnote [\dots , \dots]¹ [\dots , \dots]²_{OPT}

```

1  NAME

2  interactiune      = da nu numar text tot
   symbolcommand     = \...##1
   comandatext       = \...##1
   indicator         = da nu
   separatorstext    = BEFEHL
   latime            = DIMENSION
   inaltime          = DIMENSION
   distanta          = DIMENSION
   rulecommand       = BEFEHL
   rigla             = on dezactivat normal stanga dreapta comanda paragraf
   split             = tolerant strict foarteststrict NUMMER
   factor            = NUMMER
   locatie           = text pagina inalt subsol niciunul coloane firstcolumn lastcolumn
   urmatorul         = BEFEHL
   n                 = NUMMER
   culoarerigla      = COLOR
   grosimerigla      = DIMENSION
   setups            = NAME
   spatiereinterliniara = NAME
   paragraf          = da nu
   inainte           = BEFEHL
   dupa              = BEFEHL
   intre             = BEFEHL
   scop              = pagina
   distantacoloane   = DIMENSION
   continua          = da nu
   alternativ         = grila fixat coloane note niciunul
   criteriu          = pagina
   fonttext          = inherits: \seteazafonttext
   aliniere          = inherits: \seteazaalinierea
   stiltext          = STYLE BEFEHL
   culoaretext       = COLOR
   anchor            = urmatorul
   inherits: \seteazainconjurat

```

\setupnotes [\dots , \dots]¹ [\dots , \dots]²_{OPT}

```

1  NAME

2  inherits: \setupnote

```

\setupoffset [\dots , \dots]^{*}

```

*  inherits: \setupoffsetbox

```

\setupoffsetbox [\dots , \dots]^{*}

```

*  x                = DIMENSION
   y                = DIMENSION
   offsetstanga     = DIMENSION
   offsetdreapta    = DIMENSION
   offsetsus        = DIMENSION
   offsetjos        = DIMENSION
   metoda          = fixat
   latime           = DIMENSION
   inaltime         = DIMENSION
   inaltime         = DIMENSION
   locatie          = stanga centru dreapta sus subsol linie l c r m t b g

```

\setupoutputroutine [\dots]¹ [\dots , \dots]²_{OPT}

```

1  NAME

2  KEY = CSNAME

```

\setupoutputroutine [\dots]^{*}

```

*  NAME

```

\setuppagechecker [...,¹...] [...,²...] OPT

1 NAME
2 linii = NUMMER
offset = DIMENSION
metoda = 0 1 2 3
inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL

\setuppagegrid [...,¹...] [...,²...] OPT

1 NAME
2 n = NUMMER
nstanga = NUMMER
ndreapta = NUMMER
latime = DIMENSION auto
distanta = DIMENSION
linii = NUMMER
latimemaxima = DIMENSION
inaltimemaxima = DIMENSION
directie = normal reverse
pagina = inherits: \pagina
inherits: \seteazainconjurat

\setuppagegridarea [...,¹...] [...,²...] OPT

1 NAME
2 stare = start stop repetat
x = NUMMER
y = NUMMER
nx = NUMMER
ny = NUMMER
stil = STYLE BEFEHL
culoare = COLOR
clipoffset = DIMENSION
offsetdreapta = DIMENSION
inherits: \seteazainconjurat

\setuppagegridareatext [...¹] [...²]

1 NAME
2 TEXT

\setuppagegridlines [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppagegridspan [...,¹...] [...,²...] OPT

1 NAME
2 n = NUMMER
stil = STYLE BEFEHL
culoare = COLOR
inainte = BEFEHL
dupa = BEFEHL
inherits: \seteazainconjurat

\setuppagegridstart [...¹] [...²] [...³] [...⁴]

1 NAME
2 NUMMER
3 NUMMER
4 NUMMER

\setuppageinjection [...,¹...] [...,²...,...]
OPT

1 NAME
2 stare = precedent urmatorul NUMMER
intarziere = da nu
alternativ = figura buffer setups niciunul NAME
pagina = inherits: \pagina
pagestate = start stop
n = NUMMER
inherits: \seteazainconjurat

\setuppageinjectionalternative [...,¹...] [...,²...,...]
OPT

1 NAME
2 renderingsetup = NAME

\setuppageshift [...¹...] [...²...] [...³...]
OPT OPT

1 pagina foaie
2 NAME
3 NAME

\setuppagestate [...,^{*}...,...]

* intarziere = da nu

\setuppairedbox [...,¹...] [...,²...,...]
OPT

1 NAME
2 inainte = BEFEHL
dupa = BEFEHL
intre = BEFEHL
locatie = stanga centru dreapta sus subsol inalt jos
n = NUMMER
distanta = DIMENSION
fonttext = inherits: \seteazafonttext
latime = DIMENSION
inaltime = DIMENSION
latimemaxima = DIMENSION
inaltimemaxima = DIMENSION
aliniere = inherits: \seteazaalinieria
stil = STYLE BEFEHL
culoare = COLOR

\setarePAIREDBOX [...,^{*}...,...]

* inherits: \setuppairedbox

instances:

\setuppaper [...,^{*}...,...]

* inherits: \seteazadimensiunihartie

\setupparagraph [...,¹...] [...,²...,...]
OPT

1 NAME
2 stil = STYLE BEFEHL
culoare = COLOR
aliniere = inherits: \seteazaalinieria
setups = NAME

\setupparagraphintro [...,¹...] [...²...]

1 reset fiecare primul urmatorul
2 BEFEHL

`\setupparallel [...]1 [...]2,...] [...]3,...,...`

```
1 NAME
2 NAME
3 setups    = NAME
  start     = NUMBER
  n         = NUMBER
  criteriu  = tot
```

`\setupperiods [...]*,...,...`

```
* n         = NUMBER
  latime    = DIMENSION ajustat
  distanta  = DIMENSION
  simbol    = BEFEHL
```

`\setupplacement [...]1,...] [...]2,...,...`
OPT

```
1 NAME
2 inainte   = BEFEHL
  dupa      = BEFEHL
  stanga    = BEFEHL
  dreapta   = BEFEHL
  grid      = inherits: \snaptogrid
  corectielinie = on dezactivat
  corectieadancime = on dezactivat
  margine   = da nu standard
```

`\setuppositionbar [...]*,...,...`

```
* stil      = STYLE BEFEHL
  culoare   = COLOR
  n         = NUMBER
  min       = NUMBER
  max       = NUMBER
  text      = TEXT
  latime    = DIMENSION
  inaltime  = DIMENSION
  inaltime  = DIMENSION
```

`\setupprocessor [...]1,...] [...]2,...,...`
OPT

```
1 NAME
2 stare     = start stop
  stanga    = BEFEHL
  dreapta   = BEFEHL
  comanda   = \...##1
  stil      = STYLE BEFEHL
  culoare   = COLOR
```

`\setupprofile [...]1,...] [...]2,...,...`
OPT

```
1 NAME
2 inaltime  = DIMENSION
  distanta  = DIMENSION
  distanta  = DIMENSION
  factor    = NUMBER
  linii     = NUMBER
  metoda    = strict fixat niciunul
```

`\setupquotation [...]*,...,...`

```
* inherits: \setupdelimitedtext
```

`\setuprealpagenumber [...]*,...,...`

```
* inherits: \setupcounter
```


\setupreferenceformat [...¹,...] [...²,...] OPT

1 NAME
2 eticheta = * NAME
stanga = BEFEHL
dreapta = BEFEHL
type = implicit text titlu numar pagina realpage
setups = NAME
autocase = da nu
text = TEXT
stil = STYLE BEFEHL
culoare = COLOR

\setupreferenceprefix [...]

* + - TEXT

\setupreferencestructureprefix [...¹] [...²] [...³,...,...] OPT OPT

1 NAME ABSCHNITT
2 implicit
3 prefix = da nu
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = BEFEHL PROCESSOR->BEFEHL
prefixstopper = BEFEHL PROCESSOR->BEFEHL
prefixset = NAME
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot ABSCHNITT ABSCHNITT:ABSCHNITT ABSCHNITT:* ABSCHNITT:tot
numberconversion = NAME
numberconversionset = NAME
numberstarter = BEFEHL PROCESSOR->BEFEHL
numberstopper = BEFEHL PROCESSOR->BEFEHL
numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:tot
numberseparatorset = NAME
prefixconnector = BEFEHL PROCESSOR->BEFEHL

\setupregisters [...¹] [...²,...,...] OPT

1 NAME NAME:NUMBER
2 inherits: \seteazaregistru

\setupregisters [...¹,...] [...²,...] [...³,...,...] OPT OPT

1 NAME
2 NUMMER
3 inherits: \seteazaregistru

\setuprenderingwindow [...¹,...] [...²,...] OPT

1 NAME
2 actiunedeschiderepagina = REFERENCE
actiuneinchiderepagina = REFERENCE
inherits: \seteazainconjurat

\setups [...*,...]

* NAME

\setupscale [...,¹...] [...,²...] OPT

```
1  NAME

2  scala      =  NUMBER
   xscala     =  NUMBER
   yscala     =  NUMBER
   latime     =  DIMENSION
   inaltime   =  DIMENSION
   inaltime   =  da nu
   linii      =  NUMBER
   factor     =  ajustat broad max auto implicit
   hfactor    =  ajustat broad max auto implicit
   factorw    =  ajustat broad max auto implicit
   latimemaxima =  DIMENSION
   inaltimemaxima =  DIMENSION
   s          =  NUMBER
   sx         =  NUMBER
   sy         =  NUMBER
   equalwidth =  DIMENSION
   equalheight =  DIMENSION
   grid       =  da ajustat inaltime adancime jumatatelinie
```

\setupsript [...,¹...] [...,²...] OPT

```
1  NAME

2  metoda     =  hangul hanzi nihongo ethiopic thai test
   preset     =  NAME
   features    =  auto
```

\setupscripts [...,¹...] [...,²...] OPT

```
1  NAME

2  inherits: \setupsript
```

\setupselector [...¹...] [...,²...] OPT

```
1  NAME

2  n =  NUMBER
   m =  NUMBER
```

\setupshift [...,¹...] [...,²...] OPT

```
1  NAME

2  continua   =  da nu
   unitate    =  ex em pt in cm mm sp bp pc dd cc nc
   metoda     =  NUMBER
   dy         =  NUMBER
   aliniere   =  inherits: \seteazaalinierea
   stil       =  STYLE BEFEHL
   culoare    =  COLOR
```

\setupsidebar [...,¹...] [...,²...] OPT

```
1  NAME

2  grosimerigla      =  DIMENSION
   culoarerigla      =  COLOR
   alternativ          =  NUMBER
   offsetsus         =  DIMENSION
   offsetjos          =  DIMENSION
   distanta           =  DIMENSION
   distantamarginestanga =  DIMENSION
   nivel              =  NUMBER
```

\setupspellchecking [...,^{*}...] [...,^{*}...] OPT

```
*  stare =  start stop
   metoda =  1 2 3
   lista  =  NAME
```

`\setupstartstop [...,1...] [...,2...,...]`
OPT

1 NAME
 2 inainte = BEFEHL
 dupa = BEFEHL
 intre = BEFEHL
 setups = NAME
 stanga = BEFEHL
 dreapta = BEFEHL
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupstretched [...,*...,...]`

* inherits: \setupcharacterkerning

`\setupstruts [...*...]`
OPT

* da nu auto cap ajustat linie implicit CHARACTER

`\setupstyle [...,1...] [...,2...,...]`
OPT

1 NAME
 2 metoda = comanda
 stil = STYLE BEFEHL
 culoare = COLOR

`\setupsbformula [...,1...] [...,2...,...]`
OPT

1 NAME
 2 aliniaturmator = da nu auto

`\setups {...,*...}`

* NAME

`\setupTABLE [...,1...] [...,2...] [...,3...,...]`
OPT OPT

1 r c x y rand coloana primul ultim start antet fiecare impar par unu NUMMER -NUMMER
 2 primul least fiecare doi impar par NUMMER -NUMMER
 3 extras = BEFEHL
 stanga = BEFEHL
 dreapta = BEFEHL
 culoaretitlu = COLOR
 stiltitlu = STYLE BEFEHL
 distantamarginestanga = DIMENSION
 distantamarginedreapta = DIMENSION
 distantacoloane = DIMENSION
 latimemaxima = DIMENSION
 setups = NAME
 latimetext = DIMENSION local
 split = da nu repetat auto
 antet = repetat
 optiune = dilatat tight
 inainte = BEFEHL
 dupa = BEFEHL
 aceeasipagina = inainte dupa ambele
 spaceinbetween = inherits: \blanc
 splitoffset = DIMENSION
 aliniazacaracter = da nu
 alierecaracter = TEXT number->TEXT text->TEXT
 distanta = DIMENSION
 culoare = COLOR
 stil = math STYLE BEFEHL
 inherits: \setezainconjurat

`\setupTEXpage [...,*...,...]`

* inherits: \setupfittingpage

`\setuptabulation [...1,...] [...2,...]`
OPT

```

1  NAME

2  format      =  TEMPLATE niciunul
   inainte     =  BEFEHL
   dupa        =  BEFEHL
   distanta    =  mic mediu mare niciunul blank adancime grila DIMENSION
   aliniere    =  stanga centru dreapta dimension
   rigla       =  linie normal
   culoarerigla =  COLOR
   grosimerigla =  DIMENSION
   fonttext    =  inherits: \seteazafonttext
   aliniat     =  da nu
   split       =  da nu repetat auto
   unitate     =  DIMENSION
   margine     =  DIMENSION
   intern      =  BEFEHL
   EQ          =  BEFEHL
   antet       =  da repetat text
   frame       =  on dezactivat
   titlu       =  TEXT
   keeptogether =  da nu

```

`\setuptagging [...*,...]`

```

*  stare  =  start stop
   metoda =  auto

```

`\setuptextbackground [...1,...] [...2,...]`
OPT

```

1  NAME

2  stare      =  start stop
   locatie    =  text paragraf niciunul
   alternativ  =  NUMMER
   mp         =  NAME
   metoda     =  NAME
   fundal     =  culoare
   culoarefundal =  COLOR
   colt       =  rectangular rotund
   nivel      =  NUMMER
   offsetfundal =  DIMENSION
   inainte    =  BEFEHL
   dupa       =  BEFEHL
   aliniere   =  inherits: \seteazaalinierea
   dash       =  NUMMER
   raza       =  DIMENSION
   frame      =  on dezactivat
   culoareframe =  COLOR
   grosimerigla =  DIMENSION
   voffset    =  DIMENSION
   offsetframe =  DIMENSION
   offsetstanga =  da nu standard DIMENSION
   offsetdreapta =  da nu standard DIMENSION
   offsetsus   =  mic mediu mare linie DIMENSION
   offsetjos   =  mic mediu mare linie DIMENSION
   stil        =  STYLE BEFEHL
   culoare     =  COLOR

```

`\setuptextflow [...1,...] [...2,...]`
OPT

```

1  NAME

2  latime  =  DIMENSION
   stil    =  STYLE BEFEHL
   culoare =  COLOR

```

`\setuptooltip [...1,...] [...2,...]`
OPT

```

1  NAME

2  locatie =  stanga centru dreapta
   inherits: \seteazainconjurat

```

`\setupunit [...,1...] [...,2...,...]`
OPT

1 NAME

2 metoda = 1 2 3 4 5 6
language = SPRACHE
alternativ = text matematica
order = reverse normal
separator = mic mediu mare normal niciunul NAME
spatiu = mic mediu mare normal niciunul NAME
stil = STYLE BEFEHL
culoare = COLOR

`\setupuserpagenumber [...,*...,...]`

* viewerprefix = TEXT
stare = start stop niciunul mentine gol
inherits: \setupcounter

`\setupversion [...*...]`

* concept fisier temporar final NAME

`\setupviewerlayer [...,*...,...]`

* titlu = TEXT
stare = start stop
export = da nu
tiparibil = da nu
scop = local global
metoda = niciunul comanda

`\setupvspacing [...,*...]`
OPT

* inherits: \vspacing

`\setupwithargument {...1} {...2}`

1 NAME

2 CONTENT

`\setupwithargumentswapped {...1} {...2}`

1 CONTENT

2 NAME

`\setupxml [...,*...,...]`

* implicit = ascuns niciunul text
compress = da nu

`\setupxtable [...1,...] [...2...]`
OPT

1 NAME

2 latimetext = DIMENSION local
fonttext = inherits: \seteazafonttext
spaceinbetween = inherits: \blanc
optiune = tight max dilatat latime inalttime fixat
inaltimetext = DIMENSION
latimemaxima = DIMENSION
distantacoloane = DIMENSION
distantamarginestanga = DIMENSION
distantamarginedreapta = DIMENSION
antet = repetat
subsol = repetat
grosimerigla = DIMENSION
split = da nu repetat auto
splitoffset = DIMENSION
aceeasipagina = inainte dupa ambele
distanta = DIMENSION
inherits: \seteazainconjurat

`\setuvalue {...1} {...2}`

1 NAME

2 CONTENT

`\setuxvalue {...1} {...2}`

1 NAME

2 CONTENT

`\setvalue {...1} {...2}`

1 NAME

2 CONTENT

`\setvariable {...1} {...2} {...3}`

1 NAME

2 KEY

3 VALUE

`\setvariables [...1] [...2...]`

1 NAME

2 set = BEFEHL
reset = BEFEHL
KEY = VALUE

`\setvboxregister ...1 {...2}`

1 CSNAME NUMBER

2 CONTENT

`\setvisualizerfont [...*]`
OPT

* FONT

`\setvtopregister ...1 {...2}`

1 CSNAME NUMBER

2 CONTENT

<pre>\setwidthof ¹... \to \²...</pre> <pre>1 TEXT</pre> <pre>2 CSNAME</pre>
<pre>\setxmeasure {...} {...}</pre> <pre>1 NAME</pre> <pre>2 DIMENSION</pre>
<pre>\setxvalue ¹ {...} ² {...}</pre> <pre>1 NAME</pre> <pre>2 CONTENT</pre>
<pre>\setxvariable {...} {...} ³ {...}</pre> <pre>1 NAME</pre> <pre>2 KEY</pre> <pre>3 VALUE</pre>
<pre>\setxvariables [¹...] [²...,...]</pre> <pre>1 NAME</pre> <pre>2 set = BEFEHL</pre> <pre> reset = BEFEHL</pre> <pre> KEY = VALUE</pre>
<pre>\sfrac ¹ {...} ² {...}</pre> <pre>1 CONTENT</pre> <pre>2 CONTENT</pre>
<pre>\shapedhbox {...}</pre> <pre>* CONTENT</pre>
<pre>\SHIFT {...}</pre> <pre>* CONTENT</pre> <p>instances:</p>
<pre>\showallmakeup</pre>
<pre>\showattributes</pre>
<pre>\showboxes</pre>
<pre>\showbtxdatasetauthors [[*]...,...]</pre> <pre> OPT</pre> <pre>* specification = NAME</pre> <pre> dataset = NAME</pre> <pre> field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution</pre> <pre> journal language luna monthfiled nationality note numar unu doi organization pages publisher</pre> <pre> school series titlu type volume an yearfiled NAME</pre>
<pre>\showbtxdatasetauthors [[*]...] OPT</pre> <pre>* NAME</pre>

<pre> \showbtxdatasetcompleteness [...,..[*]...,...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...*] OPT * NAME </pre>
<pre> \showbtxdatasetfields [...,..[*]...,...] OPT * specification = NAME dataset = NAME field = address assignee autor booktitle capitol zi dayfiled edition editor howpublished institution journal language luna monthfiled nationality note numar unu doi organization pages publisher school series titlu type volume an yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...*] OPT * NAME </pre>
<pre> \showbtxfields [...,..[*]...,...] OPT * rotatie = NUMMER specification = NAME </pre>
<pre> \showbtxfields [...*] OPT * NAME </pre>
<pre> \showbtxhashedauthors [...*] OPT * TEXT </pre>
<pre> \showbtxtables [...*] OPT * TEXT </pre>
<pre> \showchardata {...} * TEXT </pre>
<pre> \showcharratio {...} * TEXT </pre>
<pre> \showcolorbar [...] * COLOR </pre>
<pre> \showcolorcomponents [...] * COLOR </pre>
<pre> \showcolorset [...] * COLOR </pre>
<pre> \showcolorstruts </pre>
<pre> \showcounter [...] * NAME </pre>

<code>\showdirectives</code>
<code>\showdirlsinmargin</code>
<code>\showedebuginfo</code>
<code>\showexperiments</code>
<code>\showfont [...]¹ [...]²,...]</code> <small>OPT</small> 1 FONT 2 NUMMER
<code>\showfontdata</code>
<code>\showfontkerns</code>
<code>\showfontparameters</code>
<code>\showfontstrip [...]*,...]</code> * inherits: \seteazafonttext
<code>\showfontstyle [...]¹,...]² [...]³,...]⁴ [...]⁴,...]</code> <small>OPT OPT OPT OPT</small> 1 inherits: \seteazafonttext 2 rm ss tt mm hw cg 3 tf bf it sl bi bs 4 tot NUMMER
<code>\showglyphs</code>
<code>\showgridsnapping</code>
<code>\showhelp {...}¹ [...]²]</code> 1 TEXT 2 REFERENCE
<code>\showhyphenationtrace [...]¹ [...]²]</code> <small>OPT</small> 1 SPRACHE 2 TEXT
<code>\showhyphens {...}</code> * TEXT
<code>\showinjector [...]*,...]</code> <small>OPT</small> * NAME
<code>\showjustification</code>
<code>\showkerning {...}</code> * TEXT

<code>\showlayoutcomponents</code>
<code>\showligature {...}</code> * TEXT
<code>\showligatures [...]</code> * FONT
<code>\showlogcategories</code>
<code>\showmargins</code>
<code>\showmessage {...} {...} {..., 1 NAME 2 NAME NUMBER 3 TEXT </code>
<code>\showminimalbaseline</code>
<code>\shownextbox \... {...}</code> 1 CSNAME 2 CONTENT
<code>\showotfcomposition {...} {...} {...}</code> 1 FONT 2 -1 1 +1 l2r r2l 3 TEXT
<code>\showparentchain \... {...}</code> 1 CSNAME 2 NAME
<code>\showsetupsdefinition [...]</code> * NAME
<code>\showtimer {...}</code> * TEXT
<code>\showtokens [...]</code> * NAME
<code>\showtrackers</code>
<code>\showvalue {...}</code> * NAME

`\showvariable {...} {...}`

- 1 NAME
- 2 KEY

`\showwarning {...} {...} {...,3...}`

- 1 NAME
- 2 NAME NUMBER
- 3 TEXT

`\simbol [1...] [2...]`
OPT

- 1 NAME
- 2 NAME

`\simbol {...}`

- * NAME

`\simplealignedbox {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 CONTENT

`\simplealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 TEXT
- 4 CONTENT

`\simplealignedspreadbox {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 CONTENT

`\simplegroupedcommand {...} {...}`

- 1 BEFEHL
- 2 BEFEHL

`\simplereversealignedbox {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 CONTENT

`\simplereversealignedboxplus {...} {...} {...} {...}`

- 1 DIMENSION
- 2 stanga dreapta centru flushleft flushright intern extern
- 3 TEXT
- 4 CONTENT

<p><code>\singalcharacteralign {...} {...}</code></p> <p>1 NUMMER</p> <p>2 NUMMER</p>
<p><code>\singlebond</code></p>
<p><code>\sixthofsixarguments {...} {...} {...} {...} {...} {...}</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p>
<p><code>\slicepages [...]¹ [...,...²...,...]_{OPT} [...,...³...,...]_{OPT}</code></p> <p>1 FILE</p> <p>2 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION latime = DIMENSION inaltime = DIMENSION n = NUMMER</p> <p>3 offset = DIMENSION hoffset = DIMENSION voffset = DIMENSION latime = DIMENSION inaltime = DIMENSION n = NUMMER</p>
<p><code>\slovenianNumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\sloveniannumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\smallbodyfont</code></p>
<p><code>\smallcappedcharacters {...}</code></p> <p>* NUMMER</p>
<p><code>\smallcappedromannumerals {...}</code></p> <p>* NUMMER</p>
<p><code>\smaller</code></p>
<p><code>\smallskip</code></p>
<p><code>\smash [...]¹ {...}_{OPT}</code></p> <p>1 w h d t b</p> <p>2 CONTENT</p>

<p><code>\smashbox ...</code></p> <p>* CSNAME NUMMER</p>
<p><code>\smashboxed ...</code></p> <p>* CSNAME NUMMER</p>
<p><code>\smashedhbox ¹... {²...}</code> OPT</p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\smashedvbox ¹... {²...}</code> OPT</p> <p>1 TEXT</p> <p>2 CONTENT</p>
<p><code>\snaptogrid [¹...] \²... {³...}</code> OPT</p> <p>1 normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\snaptogrid [¹...,...]¹ \²... {³...}</code> OPT</p> <p>1 inherits: \definegridsnapping</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\someheadnumber [¹] [²]</code></p> <p>1 ABSCHNITT</p> <p>2 precedent curent urmatorul primul ultim</p>
<p><code>\somekindoftab [[*]...,...][*]</code> OPT</p> <p>* alternativ = orizontal vertical</p> <p>latime = DIMENSION</p> <p>inaltime = DIMENSION</p> <p>n = NUMMER</p> <p>m = NUMMER</p>
<p><code>\somalocalfloat</code></p>
<p><code>\somenamedheadnumber {¹...} {²...}</code></p> <p>1 ABSCHNITT</p> <p>2 precedent curent urmatorul primul ultim</p>
<p><code>\someplace {¹...} {²...} {³...} {⁴...} {⁵...} [⁶]</code></p> <p>1 TEXT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 REFERENCE</p>

$\backslash \textit{SORTING} [1] \{2\}$ <small>OPT</small> 1 NAME 2 CONTENT instances:
$\backslash \textit{spanishNumerals} \{\dots\}$ * NUMMER
$\backslash \textit{spanishnumerals} \{\dots\}$ * NUMMER
$\backslash \textit{spatiifixate}$
$\backslash \textit{spatiu}$
$\backslash \textit{spatiufixat}$
$\backslash \textit{speech} [1] \{2\}$ <small>OPT</small> 1 SPRACHE 2 CONTENT
$\backslash \textit{splitdfrac} \{1\} \{2\}$ 1 CONTENT 2 CONTENT
$\backslash \textit{splitfilename} \{\dots\}$ * FILE
$\backslash \textit{splitfrac} \{1\} \{2\}$ 1 CONTENT 2 CONTENT
$\backslash \textit{splitoffbase}$
$\backslash \textit{splitofffull}$
$\backslash \textit{splitoffkind}$
$\backslash \textit{splitoffname}$
$\backslash \textit{splitoffpath}$
$\backslash \textit{splitoffroot}$
$\backslash \textit{splitofftokens} 1 \backslash \textit{from} 2 \backslash \textit{to} 3$ 1 TEXT 2 TEXT 3 CSNAME

<code>\splitofftype</code>
<code>\splitstring ¹... \at ²... \to ³... \and ⁴...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\spreadhbox ...</code> * CSNAME NUMBER
<code>\sqrt [¹...] {²...}</code> _{OPT} 1 TEXT 2 CONTENT
<code>\stackrel{1}{rel} {¹...} {²...}</code> 1 CONTENT 2 CONTENT
<code>\stanga ...</code> * CHARACTER
<code>\startalignment [...,*...] ... \stopalignment</code> * inherits: \seteazaalinierea
<code>\startaliniatcentru ... \stopaliniatcentru</code>
<code>\startaliniatdreapta ... \stopaliniatdreapta</code>
<code>\startaliniatstanga ... \stopaliniatstanga</code>
<code>\startallmodes [...,*...] ... \stopallmodes</code> * NAME
<code>\startantettabel [...] ... \stopantettabel</code> * NAME
<code>\startascundere ... \stopascundere</code>
<code>\startaside [¹...] [²...,...]</code> ... <code>\stopaside</code> _{OPT} _{OPT} 1 SPRACHE 2 inherits: \startingust
<code>\startattachment [¹...] [²...,...]</code> ... <code>\stopattachment</code> _{OPT} _{OPT} 1 NAME 2 inherits: \setupattachment

$\backslash\text{startATTACHMENT}$ [¹ ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopATTACHMENT}$ $\backslash\text{startATTACHMENT}$ [<small>OPT</small> ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopATTACHMENT}$ 1 NAME 2 inherits: \setupattachment instances: attachment
$\backslash\text{startbar}$ [...] ... $\backslash\text{stopbar}$ * NAME
$\backslash\text{startbitmapimage}$ [..., [*] ...,...] ... $\backslash\text{stopbitmapimage}$ * culoare = rgb cmyk gri latime = DIMENSION inaltime = DIMENSION x = NUMMER y = NUMMER
$\backslash\text{startblockquote}$ [¹ ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopblockquote}$ $\backslash\text{startblockquote}$ [<small>OPT</small> ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopblockquote}$ 1 SPRACHE 2 inherits: \startingust
$\backslash\text{startblocsectioneambient}$ [...] ... $\backslash\text{stopblocsectioneambient}$ * NAME
$\backslash\text{startbtxrenderingdefinitions}$ [...] ... $\backslash\text{stopbtxrenderingdefinitions}$ * NAME
$\backslash\text{startbuffer}$ [[*] ...] ... $\backslash\text{stopbuffer}$ $\backslash\text{startbuffer}$ [<small>OPT</small> ...] ... $\backslash\text{stopbuffer}$ * NAME
$\backslash\text{startBUFFER}$... $\backslash\text{stopBUFFER}$ instances: ascundere
$\backslash\text{startcatcodetable}$ *... ... $\backslash\text{stopcatcodetable}$ * CSNAME
$\backslash\text{startcenteraligned}$... $\backslash\text{stopcenteraligned}$
$\backslash\text{startcharacteralign}$ [[*] ...] ... $\backslash\text{stopcharacteralign}$ $\backslash\text{startcharacteralign}$ [<small>OPT</small> ...] ... $\backslash\text{stopcharacteralign}$ * TEXT number->TEXT text->TEXT
$\backslash\text{startcheckedfences}$... $\backslash\text{stopcheckedfences}$
$\backslash\text{startchemical}$ [¹ ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopchemical}$ $\backslash\text{startchemical}$ [<small>OPT</small> ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopchemical}$ 1 NAME 2 inherits: \setupchemical
$\backslash\text{startcitat}$ [¹ ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopcitat}$ $\backslash\text{startcitat}$ [<small>OPT</small> ...] [<small>OPT</small> ...,... ² ...,...] ... $\backslash\text{stopcitat}$ 1 SPRACHE 2 inherits: \startingust

<code>\startcollect ... \stopcollect</code>
<code>\startcollecting ... \stopcollecting</code>
<code>\startcoloane [...,\overset{*}{=},...] ... \stopcoloane</code> <small>OPT</small> <code>* inherits: \seteazacoloane</code>
<code>\startcolorintent [...] ... \stopcolorintent</code> <code>* knockout overprint niciunul</code>
<code>\startcoloronly [...] ... \stopcoloronly</code> <code>* COLOR</code>
<code>\startcolorset [...] ... \stopcolorset</code> <code>* NAME</code>
<code>\startcolumnspan [...,\overset{*}{=},...] ... \stopcolumnspan</code> <small>OPT</small> <code>* inherits: \setupcolumnspan</code>
<code>\startcombination [...]\overset{1}{...} [...,\overset{2}{=},...] ... \stopcombination</code> <small>OPT</small> <small>OPT</small> <code>1 NAME</code> <code>2 inherits: \setupcombination</code>
<code>\startcombination [...]\overset{1}{...} [...]\overset{2}{...} ... \stopcombination</code> <small>OPT</small> <small>OPT</small> <code>1 NAME</code> <code>2 N*M</code>
<code>\startcomentariu [...]\overset{1}{...} [...,\overset{2}{=},...] ... \stopcomentariu</code> <small>OPT</small> <small>OPT</small> <code>1 TEXT</code> <code>2 inherits: \seteazacomentariu</code>
<code>\startcomentariupagina ... \stopcomentariupagina</code>
<code>\startCOMENTARIU [...]\overset{1}{...} [...,\overset{2}{=},...] ... \stopCOMENTARIU</code> <small>OPT</small> <small>OPT</small> <code>1 TEXT</code> <code>2 inherits: \seteazacomentariu</code> <code>instances: comentariu</code>
<code>\startcomponenta [...] ... \stopcomponenta</code> <code>* FILE *</code>
<code>\startcomponenta \stopcomponenta</code> <code>* FILE *</code>
<code>\startcontextcode ... \stopcontextcode</code>
<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>

* NAME

* NAME

* COLOR

$$\backslash\mathrm{startdelimited} \left[\overset{1}{\dots} \right] \left[\overset{2}{\dots} \right] \left[\overset{3}{\dots}, \dots \right] \dots \backslash\mathrm{stopdelimited}$$

1 NAME

2 SPRACHE

```
3 inherits: \startingust
```

`\startdelimitedtext` [¹...] [²...] [³...,...] ... `\stopdelimitedtext`

1 NAME

2 SPRACHE

```
3 inherits: \startingust
```

$$\backslash\textit{startDELIMITEDTEXT} \underset{\text{OPT}}{[...]} \underset{\text{OPT}}{[...;...]} \dots \backslash\textit{stopDELIMITEDTEXT}$$

1 SPRACHE

```
2 inherits: \startingust
```

```
instances: citat minicitat blockquote speech aside
```

$$\backslash\textit{startDESCRIERE} [\dots, \underset{\text{OPT}}{..=..}, \dots] \dots \backslash\textit{stopDESCRIERE}$$

```
*   titlu      = TEXT
    semncarte  = TEXT
    lista      = TEXT
    referinta  = REFERENCE
```

$$\backslash\textit{startDESCRIERE} [\dots^1, \dots] \{\dots\}^2 \dots \backslash\textit{stopDESCRIERE}$$

1 REFERENCE

2 TEXT

$$\backslash\mathrm{startdmath} \dots \backslash\mathrm{stopdmath}$$
$$\backslash\mathrm{startdocument} \left[\dots \underset{\mathrm{OPT}}{..=} .., \dots \right] \dots \backslash\mathrm{stopdocument}$$

```
* inherits: \setupdocument
```

* REFERENCE

$\backslash\text{starteffect} [\dots] \dots \backslash\text{stopeffect}$ * NAME
$\backslash\text{startEFFECT} \dots \backslash\text{stopEFFECT}$
$\backslash\text{startelement} [\dots, \dots] \dots \backslash\text{stopelement}$ <small>OPT</small> * REFERENCE
$\backslash\text{startembeddedxtable} [\dots, \dots, \dots] \dots \backslash\text{stopembeddedxtable}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startembeddedxtable} [\dots] \dots \backslash\text{stopembeddedxtable}$ <small>OPT</small> * NAME
$\backslash\text{startENUMERARE} [\dots, \dots, \dots] \dots \backslash\text{stopENUMERARE}$ <small>OPT</small> * titlu = TEXT * semncarte = TEXT * lista = TEXT * referinta = REFERENCE
$\backslash\text{startENUMERARE} [\dots, \dots] \{ \dots \} \dots \backslash\text{stopENUMERARE}$ <small>OPT</small> <small>OPT</small> 1 REFERENCE 2 TEXT
$\backslash\text{startexceptions} [\dots] \dots \backslash\text{stopexceptions}$ * SPRACHE
$\backslash\text{startexpanded} \dots \backslash\text{stopexpanded}$
$\backslash\text{startexpandedcollect} \dots \backslash\text{stopexpandedcollect}$
$\backslash\text{startextendedcatcodetable} \backslash\dots \dots \backslash\text{stopextendedcatcodetable}$ * CSNAME
$\backslash\text{startexternalfigurecollection} [\dots] \dots \backslash\text{stopexternalfigurecollection}$ * NAME
$\backslash\text{startfigura} [\dots] [\dots] [\dots, \dots, \dots] \dots \backslash\text{stopfigura}$ <small>OPT</small> 1 NAME 2 FILE 3 inherits: $\backslash\text{figuraexterna}$
$\backslash\text{startfittingpage} [\dots] [\dots, \dots, \dots] \dots \backslash\text{stopfittingpage}$ <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{setupfittingpage}$
$\backslash\text{startFITTINGPAGE} [\dots, \dots, \dots] \dots \backslash\text{stopFITTINGPAGE}$ <small>OPT</small> * inherits: $\backslash\text{setupfittingpage}$ instances: TEXpage MPpage

<p><code>\startfloatcombination [...[*]...] ... \stopfloatcombination</code> <small>OPT</small></p> <p>* inherits: \setupcombination</p>
<p><code>\startfloatcombination [...[*]] ... \stopfloatcombination</code> <small>OPT</small></p> <p>* N*M NAME</p>
<p><code>\startOBJECTMOBILtext [...¹,...²] {...³} ... \stopOBJECTMOBILtext</code> <small>OPT OPT</small></p> <p>1 split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective</p> <p>2 REFERENCE</p> <p>3 TEXT</p>
<p><code>\startfont [...[*]] ... \stopfont</code> <small>OPT</small></p> <p>* FONT</p>
<p><code>\startfontclass [...[*]] ... \stopfontclass</code></p> <p>* fiecare NAME</p>
<p><code>\startfontsolution [...[*]] ... \stopfontsolution</code></p> <p>* NAME</p>
<p><code>\startformula [...[*],...] ... \stopformula</code> <small>OPT</small></p> <p>* impachetat tight centru incadrat inherits: \seteazafonttext</p>
<p><code>\startFORMULAformula [...[*],...] ... \stopFORMULAformula</code> <small>OPT</small></p> <p>* impachetat tight centru incadrat inherits: \seteazafonttext</p> <p>instances: sp sd mp md</p>
<p><code>\startformule [...[*],...] ... \stopformule</code> <small>OPT</small></p> <p>* + - REFERENCE</p>
<p><code>\startframed [...¹] [...²,...²,...] ... \stopframed</code> <small>OPT OPT</small></p> <p>1 NAME</p> <p>2 inherits: \seteazainconjurat</p>
<p><code>\startframedcontent [...[*]] ... \stopframedcontent</code> <small>OPT</small></p> <p>* NAME dezactivat</p>
<p><code>\startfundal [...[*],...] ... \stopfundal</code> <small>OPT</small></p> <p>* inherits: \seteazafundal</p>
<p><code>\startFUNDAL [...[*],...] ... \stopFUNDAL</code> <small>OPT</small></p> <p>* inherits: \seteazafundal</p> <p>instances: fundal</p>

$\backslash\text{startgridsnapping}$ [...] ... $\backslash\text{stopgridsnapping}$ <small>OPT</small> * normal standard da strict tolerant sus subsol ambele broad ajustat primul ultim inalt unu jos niciunul linie strut box min max centru NAME
$\backslash\text{startgridsnapping}$ [...,*...] ... $\backslash\text{stopgridsnapping}$ <small>OPT</small> * inherits: $\backslash\text{definegridsnapping}$
$\backslash\text{starthboxestohbox}$... $\backslash\text{stophboxestohbox}$
$\backslash\text{starthboxregister}$... $\backslash\text{stophboxregister}$ * CSNAME NUMMER
$\backslash\text{startHELP}$ [...] ... $\backslash\text{stopHELP}$ <small>OPT</small> * REFERENCE instances: textajutator
$\backslash\text{starthhighlight}$ [...] ... $\backslash\text{stophighlight}$ * NAME
$\backslash\text{starthyphenation}$ [...,*...] ... $\backslash\text{stophyphenation}$ * original tex implicit hyphenate expanded traditional niciunul
$\backslash\text{startimath}$... $\backslash\text{stopimath}$
$\backslash\text{startimpachetat}$ [...] ... $\backslash\text{stopimpachetat}$ <small>OPT</small> * blank
$\backslash\text{startindentedtext}$ [...] ... $\backslash\text{stopindentedtext}$ * NAME
$\backslash\text{startINDENTEDTEXT}$... $\backslash\text{stopINDENTEDTEXT}$
$\backslash\text{startingust}$ [¹ ...] [..., ² ...,...] ... $\backslash\text{stopingust}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 inherits: $\backslash\text{seteazaingust}$
$\backslash\text{startingust}$ [..., ¹ ...,...] [..., ² ...,] ... $\backslash\text{stopingust}$ <small>OPT</small> <small>OPT</small> 1 inherits: $\backslash\text{seteazaingust}$ 2 [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
$\backslash\text{startingust}$ [¹ ...] [..., ² ...,] ... $\backslash\text{stopingust}$ <small>OPT</small> <small>OPT</small> 1 NAME 2 [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset
$\backslash\text{startinteractiune}$ [...] ... $\backslash\text{stopinteractiune}$ * ascuns NAME

<pre> \startinterface ... \stopinterface * tot SPRACHE </pre>
<pre> \startintertext ... \stopintertext </pre>
<pre> \startitemgroup [...] [...] [...] ... \stopitemgroup OPT OPT 1 NAME 2 inherits: \setupitemgroup 3 inherits: \setupitemgroup </pre>
<pre> \startITEMGROUP [...] [...] ... \stopITEMGROUP OPT OPT 1 inherits: \setupitemgroup 2 inherits: \setupitemgroup instances: </pre>
<pre> \startJScode \stopJScode 1 2 3 1 NAME 2 uses 3 NAME </pre>
<pre> \startJSreamble \stopJSreamble 1 2 3 1 NAME 2 folosit 3 now later </pre>
<pre> \startknockout ... \stopknockout </pre>
<pre> \startlayout [...] ... \stoplayout * NAME </pre>
<pre> \startlinealignment [...] ... \stoplinealignment * stanga centru dreapta max </pre>
<pre> \startlinecorrection [...] [...] ... \stoplinecorrection OPT * blank inherits: \blanc </pre>
<pre> \startlinefiller [...] [...] [...] ... \stoplinefiller OPT 1 filler NAME 2 inherits: \setuplinefiller </pre>
<pre> \startLINENOTE [...] {...} 1 REFERENCE 2 TEXT instances: </pre>

$\backslash\text{startlinenumbering}$ [$\overset{1}{\dots}$] [$\dots,\dots,\overset{2}{\dots},\dots$] ... $\backslash\text{stoplinenumbering}$ <small>OPT OPT</small> 1 NAME 2 continua = da nu start = NUMMER pas = NUMMER metoda = pagina primul urmatorul
$\backslash\text{startlinenumbering}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stoplinenumbering}$ <small>OPT OPT</small> 1 NAME 2 continuu NUMMER
$\backslash\text{startlinetable}$... $\backslash\text{stoplinetable}$
$\backslash\text{startlinetablebody}$... $\backslash\text{stoplinetablebody}$
$\backslash\text{startlinetablecell}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stoplinetablecell}$ <small>OPT</small> * inherits: $\backslash\text{setuplinetable}$
$\backslash\text{startlinetablehead}$... $\backslash\text{stoplinetablehead}$
$\backslash\text{startlinie}$ [$\overset{*}{\dots}$] * REFERENCE
$\backslash\text{startliniemargine}$ [$\overset{*}{\dots}$] ... $\backslash\text{stopliniemargine}$ <small>OPT</small> * NUMMER
$\backslash\text{startliniemargine}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopliniemargine}$ <small>OPT</small> * inherits: $\backslash\text{setupmarginrule}$
$\backslash\text{startLINES}$ [$\dots,\dots,\overset{*}{\dots},\dots$] ... $\backslash\text{stopLINES}$ <small>OPT</small> * inherits: $\backslash\text{seteazalinii}$ instances:
$\backslash\text{startlocalfootnotes}$... $\backslash\text{stoplocalfootnotes}$
$\backslash\text{startlocalheadsetup}$... $\backslash\text{stoplocalheadsetup}$
$\backslash\text{startlocallinecorrection}$ [$\dots,\overset{*}{\dots}$] ... $\backslash\text{stoplocallinecorrection}$ <small>OPT</small> * blank inherits: $\backslash\text{blanc}$
$\backslash\text{startlocalnotes}$ [$\dots,\overset{*}{\dots}$] ... $\backslash\text{stoplocalnotes}$ * NAME
$\backslash\text{startlocalsetups}$ [$\overset{1}{\dots}$] [$\overset{2}{\dots}$] ... $\backslash\text{stoplocalsetups}$ <small>OPT</small> 1 grila 2 NAME
$\backslash\text{startlocalsetups}$ $\overset{*}{\dots}$... $\backslash\text{stoplocalsetups}$ * NAME

<code>\startlua ... \stoplua</code>
<code>\startluacode ... \stopluacode</code>
<code>\startluaparameterset [...] ... \stopluaparameterset</code> <code>* NAME</code>
<code>\startluasetups [¹...] [²] ... \stopluasetups</code> <code> OPT</code> <code>1 grila</code> <code>2 NAME</code>
<code>\startluasetups \stopluasetups</code> <code>* NAME</code>
<code>\startMPclip {...} ... \stopMPclip</code> <code>* NAME</code>
<code>\startMPcode {...} ... \stopMPcode</code> <code> OPT</code> <code>* NAME</code>
<code>\startMPdefinitions {...} ... \stopMPdefinitions</code> <code> OPT</code> <code>* NAME</code>
<code>\startMPdrawing [¹] ... \stopMPdrawing</code> <code> OPT</code> <code>* -</code>
<code>\startMPenvironment [¹] ... \stopMPenvironment</code> <code> OPT</code> <code>* reset global +</code>
<code>\startMPextensions {...,[*]...} ... \stopMPextensions</code> <code> OPT</code> <code>* NAME</code>
<code>\startMPinclusions [¹] {²} ... \stopMPinclusions</code> <code> OPT OPT</code> <code>1 +</code> <code>2 NAME</code>
<code>\startMPinitializations ... \stopMPinitializations</code>
<code>\startMPpage [...,[*]...,...] ... \stopMPpage</code> <code> OPT</code> <code>* inherits: \setupfittingpage</code>
<code>\startMPpositiongraphic {...} {²,...} ... \stopMPpositiongraphic</code> <code> OPT</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\startMPpositionmethod {...} ... \stopMPpositionmethod</code> <code>* NAME</code>

$\backslash\text{startMPrun}$ $\{...\}$ \dots $\backslash\text{stopMPrun}$ <small>OPT</small> * NAME
$\backslash\text{startmakeup}$ $[...]$ $[...,\dots]$ \dots $\backslash\text{stopmakeup}$ <small>1 OPT</small> 1 NAME 2 inherits: $\backslash\text{seteazamakeup}$
$\backslash\text{startMAKEUPmakeup}$ $[...,\dots]$ \dots $\backslash\text{stopMAKEUPmakeup}$ <small>OPT</small> * inherits: $\backslash\text{seteazamakeup}$ instances:
$\backslash\text{startmarginblock}$ $[...]$ \dots $\backslash\text{stopmarginblock}$ <small>OPT</small> * NAME
$\backslash\text{startmarkedcontent}$ $[...]$ \dots $\backslash\text{stopmarkedcontent}$ <small>OPT</small> * reset tot NAME
$\backslash\text{startMATHALIGNMENT}$ $[...,\dots]$ \dots $\backslash\text{stopMATHALIGNMENT}$ <small>OPT</small> * inherits: $\backslash\text{setupmathalignment}$ instances:
$\backslash\text{startMATHCASES}$ $[...,\dots]$ \dots $\backslash\text{stopMATHCASES}$ <small>OPT</small> * inherits: $\backslash\text{setupmathcases}$ instances:
$\backslash\text{startMATHMATRIX}$ $[...,\dots]$ \dots $\backslash\text{stopMATHMATRIX}$ <small>OPT</small> * inherits: $\backslash\text{setupmathmatrix}$ instances:
$\backslash\text{startmathmode}$ \dots $\backslash\text{stopmathmode}$
$\backslash\text{startmathstyle}$ $[...,\dots]$ \dots $\backslash\text{stopmathstyle}$ * display text script scriptscript cramped uncramped normal impachetat mic mare NAME
$\backslash\text{startmatrices}$ $[...,\dots]$ \dots $\backslash\text{stopmatrices}$ <small>OPT</small> * inherits: $\backslash\text{setupmathmatrix}$
$\backslash\text{startmaxaligned}$ \dots $\backslash\text{stopmaxaligned}$
$\backslash\text{startmdformula}$ $[...,\dots]$ \dots $\backslash\text{stopmdformula}$ <small>OPT</small> * impachetat tight centru incadrat inherits: $\backslash\text{seteazafonttext}$
$\backslash\text{startmediu}$ $[...]$ \dots $\backslash\text{stopmediu}$ * FILE *

<pre> \startmediu ... \stopmediu * FILE </pre>
<pre> \startmenuinteractiune [...] ... \stopmenuinteractiune * NAME </pre>
<pre> \startmiddlealigned ... \stopmiddlealigned </pre>
<pre> \startminicitat [...] ... \stopminicitat OPT * SPRACHE </pre>
<pre> \startmixedcolumns [...] [...] ... \stopmixedcolumns OPT OPT 1 NAME 2 inherits: \setupmixedcolumns </pre>
<pre> \startMIXEDCOLUMNS [...] [...] ... \stopMIXEDCOLUMNS OPT * inherits: \setupmixedcolumns instances: </pre>
<pre> \startmode [...,*...] ... \stopmode * NAME </pre>
<pre> \startmodeset [...,¹...] {²...} ... \stopmodeset 1 NAME implicit 2 CONTENT </pre>
<pre> \startmodule [...] ... \stopmodule * FILE </pre>
<pre> \startmoduletestsection ... \stopmoduletestsection </pre>
<pre> \startmodule ... \stopmodule * FILE </pre>
<pre> \startmpformula [...,[*]...] ... \stopmpformula OPT * impachetat tight centru incadrat inherits: \seteazafonttext </pre>
<pre> \startnamedsection [...] [...] [...] ... \stopnamedsection OPT OPT OPT 1 ABSCHNITT 2 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 3 KEY = VALUE </pre>

<p><code>\startnamedsubformulas [...,¹...] {²...} ... \stopnamedsubformulas</code></p> <p><small>OPT</small></p> <p>1 + - REFERENCE</p> <p>2 TEXT</p>
<p><code>\startnarrower [...,*...] ... \stopnarrower</code></p> <p><small>OPT</small></p> <p>* [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset</p>
<p><code>\startNARROWER [...,*...] ... \stopNARROWER</code></p> <p><small>OPT</small></p> <p>* [-+]stanga [-+]centru [-+]dreapta NUMMER*stanga NUMMER*centru NUMMER*dreapta reset</p>
<p><code>\startnegativ ... \stopnegativ</code></p>
<p><code>\startnicelyfilledbox [...,*=...,...] ... \stopnicelyfilledbox</code></p> <p><small>OPT</small></p> <p>* latime = DIMENSION</p> <p> inaltime = DIMENSION</p> <p> offset = DIMENSION</p> <p> strut = da nu</p>
<p><code>\startnointerference ... \stopnointerference</code></p>
<p><code>\startnotallmodes [...,*...] ... \stopnotallmodes</code></p> <p>* NAME</p>
<p><code>\startNOTE [...,*...] ... \stopNOTE</code></p> <p><small>OPT</small></p> <p>* REFERENCE</p> <p>instances:</p>
<p><code>\startNOTE [...,*=...,...] ... \stopNOTE</code></p> <p><small>OPT</small></p> <p>* titlu = TEXT</p> <p> semncarte = TEXT</p> <p> lista = TEXT</p> <p> referinta = REFERENCE</p> <p>instances:</p>
<p><code>\startnotext ... \stopnotext</code></p>
<p><code>\startnotmode [...,*...] ... \stopnotmode</code></p> <p>* NAME</p>
<p><code>\startopus ... \stopopus</code></p>
<p><code>\startoutputstream [...*...] ... \stopoutputstream</code></p> <p>* NAME</p>
<p><code>\startoverlay ... \stopoverlay</code></p>
<p><code>\startoverprint ... \stopoverprint</code></p>

$\backslash\text{startpagefigure}$ [¹ ...] [_{OPT} ...,... ² ...,...] ... $\backslash\text{stoppagefigure}$ 1 FILE 2 inherits: $\backslash\text{setuexternalfigure}$
$\backslash\text{startpagegrid}$ [_{OPT} ¹ ...] [_{OPT} ...,... ² ...,...] ... $\backslash\text{stoppagegrid}$ 1 NAME 2 inherits: $\backslash\text{setuppagegrid}$
$\backslash\text{startpagegridspan}$ [¹ ...] [_{OPT} ...,... ² ...,...] ... $\backslash\text{stoppagegridspan}$ 1 NAME 2 inherits: $\backslash\text{setuppagegridspan}$
$\backslash\text{startPAGEGRID}$ [_{OPT} ...,... [*] ...,...] ... $\backslash\text{stopPAGEGRID}$ * inherits: $\backslash\text{setuppagegrid}$
$\backslash\text{startpagelayout}$ [...] ... $\backslash\text{stoppagelayout}$ * pagina paginastanga paginadreapta
$\backslash\text{startpar}$ [_{OPT} ¹ ...] [_{OPT} ...,... ² ...,...] ... $\backslash\text{stoppar}$ 1 NAME 2 inherits: $\backslash\text{setupparagraph}$
$\backslash\text{startparagraf}$ [_{OPT} ¹ ...] [_{OPT} ...,... ² ...,...] ... $\backslash\text{stopparagraf}$ 1 NAME 2 inherits: $\backslash\text{setupparagraph}$
$\backslash\text{startparagraphs}$ [...] ... $\backslash\text{stopparagraphs}$ * NAME
$\backslash\text{startparagraphscell}$... $\backslash\text{stopparagraphscell}$
$\backslash\text{startPARAGRAPHS}$... $\backslash\text{stopPARAGRAPHS}$
$\backslash\text{startPARALLEL}$... $\backslash\text{stopPARALLEL}$
$\backslash\text{startparbuilder}$ [...] ... $\backslash\text{stopparbuilder}$ * implicit oneline basic NAME
$\backslash\text{startpuneFLOAT}$ [_{OPT} ...,... ¹ ...,...] [_{OPT} ...,... ² ...,...] ... $\backslash\text{stoppuneFLOAT}$ 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT locatie = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargin marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto pagina paginastanga paginadreapta undeva effective referinta = REFERENCE 2 KEY = VALUE instances: chemical figure table intermezzo graphic

```
\startpunechemical [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stoppunechemical
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargine
               marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
               text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
               niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
               pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE

2 KEY = VALUE
```

```
\startpunefigure [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stoppunefigure
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargine
               marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
               text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
               niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
               pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE

2 KEY = VALUE
```

```
\startpunegraphic [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stoppunegraphic
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargine
               marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
               text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
               niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
               pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE

2 KEY = VALUE
```

```
\startpuneintermezzo [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stoppuneintermezzo
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargine
               marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
               text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
               niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
               pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE

2 KEY = VALUE
```

```
\startpunetable [...,\stackrel{1}{...},...] [...,\stackrel{2}{...},...] ... \stoppunetable
```

```
1 titlu      = TEXT
  semncarte  = TEXT
  marcaje    = TEXT
  lista      = TEXT
  locatie    = split totdeauna stanga dreapta intern extern spatiuspate cutspace instanga indreapta inmargine
               marginestanga marginedreapta bordurastanga borduradreapta innermargin outermargin inneredge outeredge
               text opus reset inaltime adancime [-+]linie jumatatelinie grila inalt jos ajustat 90 180 270 nonumber
               niciunul local aici fortat margine [-+]suspenda suspendat inalt ambele centru offset sus subsol auto
               pagina paginastanga paginadreapta undeva effective
  referinta  = REFERENCE

2 KEY = VALUE
```

<pre> \startplacepairedbox [...]¹ [...,...²...,...]_{OPT} ... \stopplacepairedbox 1 NAME 2 inherits: \setuppairedbox </pre>
<pre> \startpunePAIREDBOX [...,...[*]...,...]_{OPT} ... \stoppunePAIREDBOX * inherits: \setuppairedbox instances: </pre>
<pre> \startpositioning [...]_{OPT} [...,...²...,...]_{OPT} ... \stoppositioning 1 NAME 2 inherits: \setarepozitie </pre>
<pre> \startpositionoverlay {...} ... \stoppositionoverlay * NAME </pre>
<pre> \startpositiv ... \stoppositiv </pre>
<pre> \startpostponing [...]_{OPT} ... \stoppostponing * [-+]NUMBER </pre>
<pre> \startprocessassignmentcommand [...,...[*]...,...]_{OPT} ... \stopprocessassignmentcommand * KEY = VALUE </pre>
<pre> \startprocessassignmentlist [...,...[*]...,...]_{OPT} ... \stopprocessassignmentlist * KEY = VALUE </pre>
<pre> \startprocesscommaccommand [...,[*]...] ... \stopprocesscommaccommand * BEFEHL </pre>
<pre> \startprocesscommalist [...,[*]...] ... \stopprocesscommalist * BEFEHL </pre>
<pre> \startprodus [...]_{OPT} ... \stopprodus * FILE * </pre>
<pre> \startprodus ..._{OPT} ... \stopprodus * FILE * </pre>
<pre> \startproiect [...]_{OPT} ... \stopproiect * FILE * </pre>
<pre> \startproiect ..._{OPT} ... \stopproiect * FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>

```

1  NAME
2  tag      = REFERENCE
   category = TEXT
   k        = REFERENCE
   t        = TEXT

```

```
*  titlu      = TEXT
   suffix     = TEXT
   referinta  = + - REFERENCE
```

* + - REFERENCE

```
1  grila
2  NAME
```

* NAME

```
* inherits: \enableregime
```

```

1  NAME
2  NAME
3  TEXT
4  TEXT PROCESSOR->TEXT
5  INDEX

```

```
1  NAME
2  KEY
```

* TEXT

```
* hangul hanzi nihongo ethiopic thai test NAME
```

* impachetat tight centru incadrat inherits: \seteazafonttext

<pre> \startsectionblock [...]¹ [...,...²...,...]^{OPT} ... \stopsectionblock 1 NAME 2 semncarte = TEXT inherits: \seteazablocsectione </pre>
<pre> \startSECTIONBLOCK [...,...[*]...,...]^{OPT} ... \stopSECTIONBLOCK * semncarte = TEXT inherits: \seteazablocsectione instances: </pre>
<pre> \startsectionlevel [...]¹_{OPT} [...,...²...,...]_{OPT} [...,...³...,...]_{OPT} ... \stopsectionlevel 1 NAME 2 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 3 KEY = VALUE </pre>
<pre> \startSECTION [...,...¹...,...]_{OPT} [...,...²...,...]_{OPT} ... \stopSECTION 1 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 2 KEY = VALUE instances: </pre>
<pre> \startsetups [...]¹_{OPT} [...]² ... \stopsetups 1 grila 2 NAME </pre>
<pre> \startsetups \stopsetups * NAME </pre>
<pre> \startshift [...][*] ... \stopshift * NAME </pre>
<pre> \startsidebar [...]¹_{OPT} [...,...²...,...]_{OPT} ... \stopsidebar 1 NAME 2 inherits: \setupsidebar </pre>
<pre> \startsimplecolumns [...,...[*]...,...]_{OPT} ... \stopsimplecolumns * inherits: \setsimplecolumnhsize </pre>
<pre> \startspecialitem [...]¹_{OPT} [...,...²...,...]_{OPT} ... \stopspecialitem 1 element 2 REFERENCE </pre>

<pre> \startspecialitem [...] ... \stopspecialitem * sub propriu </pre>
<pre> \startspecialitem [...] {¹...} {²...} ... \stopspecialitem 1 sym rulat mar 2 TEXT </pre>
<pre> \startspeech [...[*],...] ... \stopspeech OPT * inherits: \startingust </pre>
<pre> \startspformula [...[*],...] ... \stopspformula OPT * impachetat tight centru incadrat inherits: \seteazafonttext </pre>
<pre> \startspread ... \stopspread </pre>
<pre> \start [[*]...] ... \stop OPT * NAME </pre>
<pre> \startSTARTSTOP ... \stopSTARTSTOP </pre>
<pre> \startstaticMPfigure {[*]...} ... \stopstaticMPfigure * NAME </pre>
<pre> \startstaticMPgraphic {¹...} {²...,³...} ... \stopstaticMPgraphic OPT 1 NAME 2 KEY </pre>
<pre> \STARTSTOP {[*]...} * CONTENT </pre>
<pre> \startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter </pre>
<pre> \startstructurepageregister [¹...] [²...] [...³,...³,...] [...⁴,...⁴,...] OPT 1 NAME 2 NAME 3 eticheta = NAME keys = TEXT PROCESSOR->TEXT entries = TEXT PROCESSOR->TEXT keys:1 = TEXT keys:2 = TEXT keys:3 = TEXT entries:1 = TEXT entries:2 = TEXT entries:3 = TEXT alternativ = TEXT 4 KEY = VALUE </pre>
<pre> \startstyle [...[*],...[*],...] ... \stopstyle * inherits: \setupstyle </pre>
<pre> \startstyle [...] ... \stopstyle * NAME FONT </pre>

<code>\startSTYLE ... \stopSTYLE</code>
<code>\startsubformulas [...[*]...] ... \stopsubformulas</code> <small>OPT</small> <code>* + - REFERENCE</code>
<code>\startsubjectlevel [...¹...] [...²...] [...³...] ... \stopsubjectlevel</code> <small>OPT OPT OPT</small> 1 NAME 2 titlu = TEXT semncarte = TEXT marcaje = TEXT lista = TEXT referinta = REFERENCE numarpropriu = TEXT 3 KEY = VALUE
<code>\startsubsentence ... \stopsubsentence</code>
<code>\startsubsoltabel [...[*]] ... \stopsubsoltabel</code> <code>* NAME</code>
<code>\startsubstack ... \stopsubstack</code>
<code>\startsymbolset [...[*]] ... \stopsymbolset</code> <code>* NAME</code>
<code>\startTABLE [...[*]...] ... \stopTABLE</code> <small>OPT</small> <code>* inherits: \setupTABLE</code>
<code>\startTABLEbody [...[*]...] ... \stopTABLEbody</code> <small>OPT</small> <code>* inherits: \setupTABLE</code>
<code>\startTABLEfoot [...[*]...] ... \stopTABLEfoot</code> <small>OPT</small> <code>* inherits: \setupTABLE</code>
<code>\startTABLEhead [...[*]...] ... \stopTABLEhead</code> <small>OPT</small> <code>* inherits: \setupTABLE</code>
<code>\startTABLEnext [...[*]...] ... \stopTABLEnext</code> <small>OPT</small> <code>* inherits: \setupTABLE</code>
<code>\startTEXpage [...[*]...] ... \stopTEXpage</code> <small>OPT</small> <code>* inherits: \setupfittingpage</code>
<code>\starttabelele [...[*]] ... \stoptabelele</code> <code>* TEMPLATE</code>
<code>\starttabelele [...[*]] ... \stoptabelele</code> <code>* NAME</code>

$\backslash\text{starttabelul}$ [$\overset{1}{ \dots }$] [$\dots, \dots, \overset{2}{=} \dots, \dots$] ... $\backslash\text{stoptabelul}$ <small>OPT</small> 1 <code>TEMPLATE</code> 2 <code>inherits: \seteazatabele</code>
$\backslash\text{starttabelul}$ [$\overset{1}{\dots}$] [$\dots, \dots, \overset{2}{=} \dots, \dots$] ... $\backslash\text{stoptabelul}$ <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \seteazatabele</code>
$\backslash\text{starttabulate}$ [$\overset{1}{/ \dots /}$] [$\dots, \dots, \overset{2}{=} \dots, \dots$] ... $\backslash\text{stoptabulate}$ <small>OPT</small> <small>OPT</small> 1 <code>TEMPLATE</code> 2 <code>inherits: \seteazatabulatori</code>
$\backslash\text{starttabulatehead}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptabulatehead}$ <small>OPT</small> * <code>NAME</code>
$\backslash\text{starttabulatetail}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptabulatetail}$ <small>OPT</small> * <code>NAME</code>
$\backslash\text{startTABULATE}$ [$\overset{1}{\dots}$] [$\dots, \dots, \overset{2}{=} \dots, \dots$] ... $\backslash\text{stopTABULATE}$ <small>OPT</small> <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \seteazatabulatori</code> instances:
$\backslash\text{startTABULATION}$ [$\overset{1}{\dots}$] [$\dots, \dots, \overset{2}{=} \dots, \dots$] ... $\backslash\text{stopTABULATION}$ <small>OPT</small> <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \setuptabulation</code>
$\backslash\text{starttexcode}$... $\backslash\text{stoptexcode}$
$\backslash\text{starttexdefinition}$ $\overset{1}{\dots}$ $\overset{2}{\dots}$ $\overset{3}{\dots}$ $\overset{4}{\dots}$ $\overset{5}{\dots}$ $\overset{6}{\dots}$... $\backslash\text{stoptexdefinition}$ <small>OPT</small> <small>OPT</small> <small>OPT</small> <small>OPT</small> <small>OPT</small> 1 <code>spaces nospaces</code> 2 <code>global</code> 3 <code>unexpanded</code> 4 <code>expanded</code> 5 <code>NAME</code> 6 <code>TEMPLATE</code>
$\backslash\text{starttext}$... $\backslash\text{stoptext}$
$\backslash\text{starttextajutator}$ [$\overset{*}{\dots}$] ... $\backslash\text{stoptextajutator}$ <small>OPT</small> * <code>REFERENCE</code>
$\backslash\text{starttextbackground}$ [$\overset{1}{\dots}$] [$\dots, \dots, \overset{2}{=} \dots, \dots$] ... $\backslash\text{stoptextbackground}$ <small>OPT</small> 1 <code>NAME</code> 2 <code>inherits: \setuptextbackground</code>
$\backslash\text{starttextbackgroundmanual}$... $\backslash\text{stoptextbackgroundmanual}$

<p><code>\startTEXTBACKGROUND [...,[*]...,...] ... \stopTEXTBACKGROUND</code> <small>OPT</small></p> <p>* inherits: \setuptextbackground</p>
<p><code>\starttextcolor [...] ... \stoptextcolor</code></p> <p>* COLOR</p>
<p><code>\starttextcolorintent ... \stoptextcolorintent</code></p>
<p><code>\startLABELtext [...¹] [...²] ... \stopLABELtext</code> <small>OPT</small></p> <p>1 SPRACHE</p> <p>2 KEY</p> <p>instances:</p>
<p><code>\starttextflow [...] ... \stoptextflow</code></p> <p>* NAME</p>
<p><code>\starttextinconjurat [...¹] [...,²...,...] ... \stoptextinconjurat</code> <small>OPT</small> <small>OPT</small></p> <p>1 stanga dreapta centru niciunul</p> <p>2 inherits: \setupframedtext</p>
<p><code>\startTEXTINCONJURAT [...¹] [...,²...,...] ... \stopTEXTINCONJURAT</code> <small>OPT</small> <small>OPT</small></p> <p>1 stanga dreapta centru niciunul</p> <p>2 inherits: \setupframedtext</p> <p>instances: textinconjurat</p>
<p><code>\starttitlu [...,¹...] {²...} ... \stoptitlu</code> <small>OPT</small></p> <p>1 REFERENCE</p> <p>2 TEXT</p>
<p><code>\starttokens [...] ... \stoptokens</code></p> <p>* NAME</p>
<p><code>\starttransparent [...] ... \stoptransparent</code></p> <p>* COLOR</p>
<p><code>\starttypescript [...,¹...] [...,²...] [...,³...] ... \stoptypescript</code> <small>OPT</small> <small>OPT</small> <small>OPT</small></p> <p>1 serif sans mono math handwriting calligraphy</p> <p>2 NAME</p> <p>3 size nume</p>
<p><code>\starttypescriptcollection [...] ... \stoptypescriptcollection</code></p> <p>* NAME</p>
<p><code>\startTYPING [...,[*]...,...] ... \stopTYPING</code> <small>OPT</small></p> <p>* inherits: \seteazatyping</p> <p>instances:</p>

<pre> \startTYPING [...[*]...] ... \stopTYPING OPT * continuu instances: </pre>
<pre> \startuniqueMPgraphic {...¹} {...²;} ... \stopuniqueMPgraphic OPT 1 NAME 2 KEY </pre>
<pre> \startuniqueMPpagegraphic {...¹} {...²;} ... \stopuniqueMPpagegraphic OPT 1 NAME 2 KEY </pre>
<pre> \startusableMPgraphic {...¹} {...²;} ... \stopusableMPgraphic OPT 1 NAME 2 KEY </pre>
<pre> \startuseMPgraphic {...¹} {...²;} ... \stopuseMPgraphic OPT 1 NAME 2 KEY </pre>
<pre> \startusemathstyleparameter \.* ... \stopusemathstyleparameter * CSNAME </pre>
<pre> \startusingbtxspefication [...[*]] ... \stopusingbtxspefication * NAME </pre>
<pre> \startvboxregister .[*] ... \stopvboxregister * CSNAME NUMBER </pre>
<pre> \startvboxtohbox ... \stopvboxtohbox </pre>
<pre> \startvboxtohboxseparator ... \stopvboxtohboxseparator </pre>
<pre> \startviewerlayer [...[*]] ... \stopviewerlayer * NAME </pre>
<pre> \startVIEWERLAYER ... \stopVIEWERLAYER </pre>
<pre> \startvtopregister .[*] ... \stopvtopregister * CSNAME NUMBER </pre>
<pre> \startxcell [...¹] [...²...] ... \stopxcell OPT OPT 1 NAME 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: \setupxtable </pre>

$\backslash\text{startxcellgroup} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopxcellgroup}$ $\text{OPT} \qquad \qquad \text{OPT}$ 1 NAME 2 inherits: \setupxtable
$\backslash\text{startxgroup} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopxgroup}$ $\text{OPT} \qquad \qquad \text{OPT}$ 1 NAME 2 inherits: \setupxtable
$\backslash\text{startxmldisplayverbatim} [\dots] \dots \backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmllineverbatim} [\dots] \dots \backslash\text{stopxmllineverbatim}$ * NAME
$\backslash\text{startxmlraw} \dots \backslash\text{stopxmlraw}$
$\backslash\text{startxmlsetups} [\overset{1}{\dots}] [\overset{2}{\dots}] \dots \backslash\text{stopxmlsetups}$ $\text{OPT} \qquad \qquad \text{OPT}$ 1 grila 2 NAME
$\backslash\text{startxmlsetups} \dots \dots \backslash\text{stopxmlsetups}$ * NAME
$\backslash\text{startxrow} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopxrow}$ $\text{OPT} \qquad \qquad \text{OPT}$ 1 NAME 2 inherits: \setupxtable
$\backslash\text{startxrowgroup} [\overset{1}{\dots}] [\dots, \dots, \overset{2}{\dots}, \dots] \dots \backslash\text{stopxrowgroup}$ $\text{OPT} \qquad \qquad \text{OPT}$ 1 NAME 2 inherits: \setupxtable
$\backslash\text{startxtable} [\dots, \dots, \overset{*}{\dots}, \dots] \dots \backslash\text{stopxtable}$ OPT * inherits: \setupxtable
$\backslash\text{startxtablebody} [\dots, \dots, \overset{*}{\dots}, \dots] \dots \backslash\text{stopxtablebody}$ OPT * inherits: \setupxtable
$\backslash\text{startxtablebody} [\dots] \dots \backslash\text{stopxtablebody}$ OPT * NAME
$\backslash\text{startxtablefoot} [\dots, \dots, \overset{*}{\dots}, \dots] \dots \backslash\text{stopxtablefoot}$ OPT * inherits: \setupxtable
$\backslash\text{startxtablefoot} [\dots] \dots \backslash\text{stopxtablefoot}$ OPT * NAME
$\backslash\text{startxtablehead} [\dots, \dots, \overset{*}{\dots}, \dots] \dots \backslash\text{stopxtablehead}$ OPT * inherits: \setupxtable

$\backslash\text{startxtablehead}$ $[\overset{*}{\dots}] \dots \backslash\text{stopxtablehead}$ <small>OPT</small> * NAME
$\backslash\text{startxtablenext}$ $[\dots,\overset{*}{\dots},\dots] \dots \backslash\text{stopxtablenext}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtablenext}$ $[\overset{*}{\dots}] \dots \backslash\text{stopxtablenext}$ <small>OPT</small> * NAME
$\backslash\text{startXTABLE}$ $[\dots,\overset{*}{\dots},\dots] \dots \backslash\text{stopXTABLE}$ <small>OPT</small> * inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxtable}$ $[\overset{*}{\dots}] \dots \backslash\text{stopxtable}$ <small>OPT</small> * NAME
$\backslash\text{stivacampuri}$ $[\overset{1}{\dots}] [\dots,\overset{2}{\dots}] [\dots,\overset{3}{\dots},\dots]$ <small>OPT</small> <small>OPT</small> 1 NAME 2 NAME 3 inherits: $\backslash\text{setupfieldcategory}$
$\backslash\text{stopLINENOTE}$ $[\overset{*}{\dots}]$ * REFERENCE instances:
$\backslash\text{stoplinie}$ $[\overset{*}{\dots}]$ * REFERENCE
$\backslash\text{stopregister}$ $[\overset{1}{\dots}] [\overset{2}{\dots}]$ 1 NAME 2 NAME
$\backslash\text{stopstructurepageregister}$ $[\overset{1}{\dots}] [\overset{2}{\dots}]$ 1 NAME 2 NAME
$\backslash\text{strictdoifelsenextoptional}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 TRUE 2 FALSE
$\backslash\text{strictdoifnextoptionalelse}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 TRUE 2 FALSE
$\backslash\text{stripcharacter}$ $\overset{1}{\dots} \backslash\text{from } \overset{2}{\dots} \backslash\text{to } \overset{3}{\dots}$ 1 CHARACTER 2 TEXT 3 CSNAME

<code>\strippedcsname *..</code> * CSNAME
<code>\strippedcsname ..</code> * TEXT
<code>\stripspaces \from ¹.. \to ²..</code> 1 TEXT 2 CSNAME
<code>\structurelistuservariable {*..}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {*..}</code> * KEY
<code>\structurevariable {*..}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {*..}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...¹...²...] {*..}</code> 1 inherits: \setupstyle 2 TEXT
<code>\styleinstance [...]</code> * NAME
<code>\style [¹...] {*²..}</code> 1 NAME FONT 2 TEXT
<code>\STYLE {*..}</code> * TEXT

<code>\sublinie {...}</code> * CONTENT
<code>\sublinii {...}</code> * CONTENT
<code>\subpagenumber</code>
<code>\subsentence {...}</code> * CONTENT
<code>\substituteincommalist {...} {...} \^3...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\subtractfeature [...]</code> * NAME
<code>\subtractfeature {...}</code> * NAME
<code>\supralinie {...}</code> * CONTENT
<code>\swapcounts \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\swapdimens \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\swapface</code>
<code>\swapmacros \^1... \^2...</code> 1 CSNAME 2 CSNAME
<code>\swapttypeface</code>
<code>\switchstyleonly [...]</code> * rm ss tt hw cg roman serif regular sans sansserif suport type teletype mono scrismanual caligrafic
<code>\switchstyleonly \^*...</code> * CSNAME

\switchtocolour [...] * COLOR
\switchtointerlinespace [..., ¹ ...] [..., ² ...,...] <div>OPT</div> 1 NAME 2 inherits: \seteazaspatiuinterliniar
\switchtointerlinespace [..., [*] ...] <div>OPT</div> * on dezactivat reset auto mic mediu mare NUMMER DIMENSION
\switchtointerlinespace [...] * NAME
\symbolreference [...] * REFERENCE
\synchronizeblank
\synchronizeindenting
\synchronizemarking [...] ¹ [...] ² [...] ³ <div>OPT</div> 1 BESCHRIFTUNG 2 NUMMER 3 mentine
\synchronizeoutputstreams [..., [*] ...] * NAME
\synchronizestrut {...} * da nu auto cap ajustat linie implicit CHARACTER
\synchronizewhitespace
\SYNONYM [...] ¹ {...} ² {...} ³ <div>OPT</div> 1 NAME 2 TEXT 3 CONTENT instances:
\systemlog {...} ¹ {...} ² {...} ³ 1 FILE 2 TEXT 3 TEXT

<code>\systemlogfirst {...} {...} {...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast {...} {...} {...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups {...}</code> * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * BEFEHL
<code>\taggedlabeltexts {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbinom {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\tbox {...}</code> * CONTENT

$\backslash\mathrm{tequal}\ \overset{1}{\mathrm{OPT}}\{\dots\}\ \overset{2}{\mathrm{OPT}}\{\dots\}$ 1 TEXT 2 TEXT
$\backslash\mathrm{testandsplitstring}\ \overset{1}{\dots}\ \backslash\mathrm{at}\ \overset{2}{\dots}\ \backslash\mathrm{to}\ \overset{3}{\dots}\ \backslash\mathrm{and}\ \overset{4}{\dots}$ 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
$\backslash\mathrm{testcolumn}\ [\overset{1}{\dots}]\ [\overset{2}{\dots}]$ OPT 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testfeature}\ \{\dots\}$ * NUMMER
$\backslash\mathrm{testfeatureonce}\ \{\dots\}$ * NUMMER
$\backslash\mathrm{testpage}\ [\overset{1}{\dots}]\ [\overset{2}{\dots}]$ OPT 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testpageonly}\ [\overset{1}{\dots}]\ [\overset{2}{\dots}]$ OPT 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testpagesync}\ [\overset{1}{\dots}]\ [\overset{2}{\dots}]$ OPT 1 NUMMER 2 DIMENSION
$\backslash\mathrm{testtokens}\ [\dots]$ * NAME
$\backslash\mathrm{tex}\ \{\dots\}$ * CONTENT
$\backslash\mathrm{texdefinition}\ \{\dots\}$ * NAME
$\backslash\mathrm{texsetup}\ \{\dots\}$ * NAME

`\textajutator` [¹...] {²...} {³...}
OPT

- 1 REFERENCE
- 2 TEXT
- 3 TEXT

`\TEXTBACKGROUND` {.*}

- * CONTENT

`\textcitation` [¹...¹...] [²...]
OPT

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\textcitation` [¹...] [²...]
OPT

- 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\textcitation` [¹...¹...] [²...²...]

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

`\textcite` [¹...¹...] [²...]
OPT

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 REFERENCE

`\textcite` [¹...] [²...]
OPT

- 1 implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum authoryear
- 2 REFERENCE

`\textcite` [¹...¹...] [²...²...]

- 1 referinta = REFERENCE
alternativ = implicit category entry short pagina num textnum an index tag keywords autor authoryears authornum
authoryear
inainte = BEFEHL
dupa = BEFEHL
stanga = BEFEHL
dreapta = BEFEHL
inherits: \setupbtx
- 2 KEY = VALUE

<code>\textcontrolspace</code>
<code>\LABELtext {...}</code> <code>* KEY</code> <code>instances:</code>
<code>\textflowcollector {...}</code> <code>* NAME</code>
<code>\textinconjurat [...,\overset{1}{=},...] {...}</code> <code>1 inherits: \setupframedtext</code> <code>2 CONTENT</code>
<code>\TEXTINCONJURAT [...,\overset{1}{=},...] {...}</code> <code>1 inherits: \setupframedtext</code> <code>2 CONTENT</code> <code>instances: textinconjurat</code>
<code>\textmath {...}</code> <code>* CONTENT</code>
<code>\textminus</code>
<code>\textormathchar {...}</code> <code>* NUMMER</code>
<code>\textplus</code>
<code>\textumlere [...,\overset{1}{=},...] {...} {...}</code> <code>1 inherits: \seteazarigleumlere</code> <code>2 TEXT</code> <code>3 TEXT</code>
<code>\textvisiblespace</code>
<code>\tfrac {...} {...}</code> <code>1 CONTENT</code> <code>2 CONTENT</code>
<code>\thainumerals {...}</code> <code>* NUMMER</code>
<code>\thefirstcharacter {...}</code> <code>* TEXT</code>
<code>\thenormalizedbodyfontsize {...}</code> <code>* DIMENSION</code>

$\backslash\text{theremainingcharacters}\{\dots\}$ \ast TEXT
$\backslash\text{thickspace}$
$\backslash\text{thinspace}$
$\backslash\text{thirtoffivearguments}\{\dots\}\{\dots\}\{\dots\}\{\dots\}\{\dots\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
$\backslash\text{thirtoffourarguments}\{\dots\}\{\dots\}\{\dots\}\{\dots\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{thirdofsixarguments}\{\dots\}\{\dots\}\{\dots\}\{\dots\}\{\dots\}\{\dots\}$ 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash\text{thirdofthreearguments}\{\dots\}\{\dots\}\{\dots\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{thirdofthreeunexpanded}\{\dots\}\{\dots\}\{\dots\}$ 1 TEXT 2 TEXT 3 TEXT
$\backslash\text{thookleftarrow}\overset{\scriptstyle 1}{\underset{\scriptstyle \text{OPT}}{\dots}}\overset{\scriptstyle 2}{\underset{\scriptstyle \text{OPT}}{\dots}}$ 1 TEXT 2 TEXT
$\backslash\text{thookrightarrow}\overset{\scriptstyle 1}{\underset{\scriptstyle \text{OPT}}{\dots}}\overset{\scriptstyle 2}{\underset{\scriptstyle \text{OPT}}{\dots}}$ 1 TEXT 2 TEXT

$\backslash\text{threedigitrounding}$ {...} * NUMBER
$\backslash\text{tibetannumerals}$ {...} * NUMBER
$\backslash\text{tightlayer}$ [...] * NAME
$\backslash\text{tilde}$ {...} * CHARACTER
$\backslash\text{tinyfont}$
$\backslash\text{tLeftarrow}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tLeftrightarrow}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tlap}$ {...} * CONTENT
$\backslash\text{tleftarrow}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tlefttharpoondown}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tlefttharpoonup}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tleftrightarrow}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tleftrightharpoons}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT
$\backslash\text{tmapsto}$ {... ¹ } {... ² } OPT OPT 1 TEXT 2 TEXT

<code>\tochar {...}</code> * NAME
<code>\tolinenote [...]</code> * REFERENCE
<code>\TOOLTIP [...¹...²...³] {...} {...}</code> <div>OPT</div> 1 inherits: \setuptooltip 2 TEXT 3 TEXT instances:
<code>\TOOLTIP [...¹] {...²} {...³}</code> <div>OPT</div> 1 stanga centru dreapta 2 TEXT 3 TEXT instances:
<code>\topbox {...}</code> * CONTENT
<code>\topleftbox {...}</code> * CONTENT
<code>\toplinebox {...}</code> * CONTENT
<code>\toprightbox {...}</code> * CONTENT
<code>\topskippedbox {...}</code> * CONTENT
<code>\tRightarrow {...¹} {...²}</code> <div>OPT OPT</div> 1 TEXT 2 TEXT
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code> * FONT
<code>\traceoutputroutines</code>
<code>\tracepositions</code>

$\backslash\text{traduce}$ [\dots $\overset{*}{=}\dots$] <ul style="list-style-type: none"> * <code>SPRACHE = TEXT</code>
$\backslash\text{transparencycomponents}$ {...} <ul style="list-style-type: none"> * <code>COLOR</code>
$\backslash\text{transparent}$ [$\overset{1}{\dots}$] $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>COLOR</code> 2 <code>CONTENT</code>
$\backslash\text{trecilafonttext}$ [\dots $\overset{*}{\dots}$] <ul style="list-style-type: none"> * <code>inherits: \seteazafonttext</code>
$\backslash\text{trel}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{trightarrow}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{trightharpoondown}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{trightharpoonup}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{trightleftharpoons}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{trightoverleftarrow}$ $\{\overset{1}{\dots}\}$ $\{\overset{2}{\dots}\}$ <ul style="list-style-type: none"> 1 <code>TEXT</code> 2 <code>TEXT</code>
$\backslash\text{triplebond}$
$\backslash\text{truefilename}$ {...} <ul style="list-style-type: none"> * <code>FILE</code>
$\backslash\text{truefontname}$ {...} <ul style="list-style-type: none"> * <code>FONT</code>
$\backslash\text{ttraggedright}$

\backslash tttriplerel $\{\overset{1}{...}\}\{\overset{2}{...}\}$ 1 TEXT 2 TEXT
\backslash twoheadleftarrow $\{\overset{1}{...}\}\{\overset{2}{...}\}$ 1 TEXT 2 TEXT
\backslash twoheadrightarrow $\{\overset{1}{...}\}\{\overset{2}{...}\}$ 1 TEXT 2 TEXT
\backslash twodigitrounding $\{.*\}$ * NUMMER
\backslash tx
\backslash txx
\backslash typ $[...,\overset{1}{...},...]\{\overset{2}{...}\}$ 1 inherits: \seteazatype 2 CONTENT
\backslash type $[...,\overset{1}{...},...]\{\overset{2}{...}\}$ 1 inherits: \seteazatype 2 CONTENT
\backslash typedefinedbuffer $[...]\overset{2}{[...,\overset{1}{...},...]}$ 1 BUFFER 2 inherits: \seteazatyping
\backslash typeface
\backslash typefile $\overset{1}{[...]}[\overset{2}{...,\overset{3}{...}},...]\{\overset{3}{...}\}$ 1 NAME 2 inherits: \seteazatyping 3 FILE
\backslash typescriptone
\backslash typescriptprefix $\{.*\}$ * NAME
\backslash typescriptthree
\backslash typescripttwo

$\backslash\text{typesetbuffer}$ $\overset{1}{[...]} \overset{2}{[...,...]}$ <small>OPT OPT</small> 1 * BUFFER 2 inherits: \setuexternalfigure
$\backslash\text{typesetfile}$ $\overset{1}{[...]} \overset{2}{[...]} \overset{3}{[...,...]}$ <small>OPT OPT</small> 1 NAME FILE 2 FILE TEXT 3 inherits: \setuexternalfigure
$\backslash\text{type}$ $\overset{1}{[...,...]} \ll\overset{2}{...}\gg$ <small>OPT</small> 1 inherits: \seteazatype 2 ANGLES
$\backslash\text{TYPE}$ $\overset{1}{[...,...]} \{\overset{2}{...}\}$ <small>OPT</small> 1 inherits: \seteazatype 2 CONTENT
$\backslash\text{TYPE}$ $\overset{1}{[...,...]} \ll\overset{2}{...}\gg$ <small>OPT</small> 1 inherits: \seteazatype 2 ANGLES
$\backslash\text{typ}$ $\overset{1}{[...,...]} \ll\overset{2}{...}\gg$ <small>OPT</small> 1 inherits: \seteazatype 2 ANGLES
$\backslash\text{uconvertnumber}$ $\{\overset{1}{...}\} \{\overset{2}{...}\}$ 1 inherits: \converttestenumar 2 NUMMER
$\backslash\text{uedcatcodecommand}$ $\overset{1}{...} \overset{2}{...} \{\overset{3}{...}\}$ 1 CSNAME 2 CHARACTER NUMMER 3 BEFEHL
$\backslash\text{ultimasubpagina}$
$\backslash\text{undefinevalue}$ $\{\overset{*}{...}\}$ * NAME
$\backslash\text{undepthed}$ $\{\overset{*}{...}\}$ * CONTENT
$\backslash\text{underbartext}$ $\{\overset{1}{...}\} \{\overset{2}{...}\}$ 1 TEXT 2 TEXT
$\backslash\text{underbrace}$ $\{\overset{*}{...}\}$ * TEXT

$\underbracket{\text{TEXT}}^1$ $\underbracket{\text{TEXT}}^2$
$\underbrace{\text{TEXT}}$
$\underbracket{\text{TEXT}}^1$ $\underbracket{\text{TEXT}}^2$
$\underdash{\text{CONTENT}}$
$\underdashes{\text{CONTENT}}$
$\underdot{\text{CONTENT}}$
$\underdotes{\text{CONTENT}}$
$\underleftarrow{\text{TEXT}}$
$\underleftharpoonup{\text{TEXT}}$
$\underleftharpoonup{\text{TEXT}}$
$\underleftrightarrow{\text{TEXT}}$
$\underparent{\text{TEXT}}$
$\underparent{\text{TEXT}}^1$ $\underparent{\text{TEXT}}^2$
$\underparent{\text{TEXT}}$
$\underparent{\text{TEXT}}$
$\underparent{\text{TEXT}}$

\underrightarrow {...} * TEXT
\underrightharpoonowdown {...} * TEXT
\underrightharpoonup {...} * TEXT
\underset {...} {...} 1 TEXT 2 TEXT
$\underline{\hspace{1cm}}$ * CONTENT
$\underline{\hspace{1cm}}$ * CONTENT
\undertwoheadleftarrow {...} * TEXT
\undertwoheadrightarrow {...} * TEXT
\undeva {...} {...} [...] 1 TEXT 2 TEXT 3 REFERENCE
\undoassign [...] [...] 1 TEXT 2 KEY = VALUE
\unframed [... ¹ ...] {...} _{OPT} 1 inherits: \seteazainconjurat 2 CONTENT
\unhhbox ... \with {...} 1 CSNAME NUMBER 2 BEFEHL
\unihex {...} * NUMMER
\uniqueMPgraphic {...} {... ² ...] _{OPT} 1 NAME 2 KEY = VALUE

$\backslash\text{uniqueMPpagegraphic}$ $\{...\} \{...\overset{2}{=}\dots\}$ <small>OPT</small> 1 NAME 2 KEY = VALUE
$\backslash\text{UNIT}$ $\{...\}$ * CONTENT instances:
$\backslash\text{unprotect}$... $\backslash\text{protect}$
$\backslash\text{unprotected}$ $\overset{*}{...}$ $\backslash\text{par}$ * CONTENT
$\backslash\text{unregisterhyphenationpattern}$ $[\overset{1}{...}] [\overset{2}{...}]$ <small>OPT</small> 1 SPRACHE 2 TEXT
$\backslash\text{unspaceafter}$ $\overset{1}{...} \{\overset{2}{...}\}$ 1 CSNAME 2 TEXT
$\backslash\text{unspaceargument}$ $\overset{1}{...} \backslash\text{to} \overset{2}{...}$ 1 TEXT 2 CSNAME
$\backslash\text{unspaced}$ $\{...\}$ * TEXT
$\backslash\text{unspacestring}$ $\overset{1}{...} \backslash\text{to} \overset{2}{...}$ 1 TEXT 2 CSNAME
$\backslash\text{untexargument}$ $\{...\} \backslash\text{to} \overset{2}{...}$ 1 TEXT 2 CSNAME
$\backslash\text{untexcommand}$ $\{...\} \backslash\text{to} \overset{2}{...}$ 1 CSNAME 2 CSNAME
$\backslash\text{uppercased}$ $\{...\}$ * TEXT
$\backslash\text{uppercasestring}$ $\overset{1}{...} \backslash\text{to} \overset{2}{...}$ 1 TEXT 2 CSNAME

<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [.*.]</code> * NAME
<code>\urmatoareasubpagina</code>
<code>\usealignparameter *..</code> * CSNAME
<code>\useblankparameter *..</code> * CSNAME
<code>\usebodyfont [...,*,...]</code> * inherits: \seteazafonttext
<code>\usebodyfontparameter *..</code> * CSNAME
<code>\usebtxdataset [...¹...] [...²...] [...,...³...,...]</code> <div style="display: flex; justify-content: space-around; width: 100%;"> OPT OPT </div> 1 NAME 2 FILE 3 specification = NAME
<code>\usebtxdefinitions [.*.]</code> * FILE
<code>\usecolors [.*.]</code> * FILE
<code>\usecomponent [.*.]</code> * FILE
<code>\usedummycolorparameter {.*.}</code> * KEY

<code>\usedummystyleandcolor {...} {...}</code> 1 KEY 2 KEY
<code>\usedummystyleparameter {...}</code> * KEY
<code>\useenvironment [...]</code> * FILE
<code>\useexternalrendering [...¹] [...²] [...³] [...⁴]</code> 1 NAME 2 NAME 3 FILE 4 auto embed
<code>\usefigurebase [...]</code> * reset FILE
<code>\usefile [...¹] [...²] [...³]_{OPT}</code> 1 NAME 2 FILE 3 TEXT
<code>\usegridparameter *...</code> * CSNAME
<code>\useindentingparameter *...</code> * CSNAME
<code>\useindentnextparameter *...</code> * CSNAME
<code>\useinterlinespaceparameter *...</code> * CSNAME
<code>\uselanguageparameter *...</code> * CSNAME
<code>\uselua module [...]</code> * FILE
<code>\useMPenvironmentbuffer [...]</code> * NAME
<code>\useMPgraphic {...} {...,²..._{OPT},...}</code> 1 NAME 2 KEY = VALUE

<code>\useMPlibrary [...]</code> * FILE
<code>\useMPrun {...} {...}</code> 1 NAME 2 NUMMER
<code>\useMPvariables [...]¹ [...,²...]</code> 1 NAME 2 KEY
<code>\usemathstyleparameter *..</code> * CSNAME
<code>\useproduct [...]</code> * FILE
<code>\useprofileparameter *..</code> * CSNAME
<code>\useproject [...]</code> * FILE
<code>\userferenceparameter *..</code> * CSNAME
<code>\userpagenumber</code>
<code>\usesetupsparameter *..</code> * CSNAME
<code>\usestaticMPfigure [...,¹_{OPT}...]² [...]</code> 1 inherits: \setupscale 2 NAME
<code>\usesubpath [...,[*]...]</code> * PATH
<code>\usetexmodule [...]_{OPT} [...,²...]_{OPT} [...,³_{OPT}...]_{OPT}</code> 1 m p s x t 2 FILE 3 KEY = VALUE
<code>\usetypescript [...]_{OPT} [...]_{OPT} [...]_{OPT}</code> 1 serif sans mono math handwriting calligraphy casual tot 2 NAME fallback implicit dtp simple 3 size nume

\usetypescriptfile [...] * reset FILE
\usezipfile [...] ¹ [...] ² <div>OPT</div> 1 FILE 2 FILE
\utfchar {...} * NUMMER
\utflower {...} * TEXT
\utfupper {...} * TEXT
\utilityregisterlength
\VerboseNumber {...} * NUMMER
\valoareculoare {...} * COLOR
\vboxreference [...] ¹ [...] ² {...} 1 REFERENCE 2 CONTENT
\vec {...} * CHARACTER
\verbatim {...} * CONTENT
\verbatimstring {...} * CONTENT
\verbosenummer {...} * NUMMER
\versiune [...] * concept fisier temporar final NAME
\verticalgrowingbar [...] [*] [...] * inherits: \setuppositionbar
\verticalpositionbar [...] [*] [...] * inherits: \setuppositionbar

<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> <code>* DIMENSION</code>
<code>\viewerlayer [...]{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\vl [...]</code> <code> OPT</code> <code>* NUMMER</code>
<code>\vphantom {...}</code> <code>* CONTENT</code>
<code>\vpos {...}{...}</code> <code>1 NAME</code> <code>2 CONTENT</code>
<code>\vsmash {...}</code> <code>* CONTENT</code>
<code>\vsmashbox ...</code> <code>* CSNAME NUMMER</code>
<code>\vsmashed {...}</code> <code>* CONTENT</code>
<code>\vspace [...]{...}</code> <code> OPT OPT</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\vspacing [...]*...]</code> <code> OPT</code> <code>* preferinta aceeasipagina max fortat enable dezactivat faraalb inapot overlay totdeauna weak strong implicit</code> <code> inainte intre dupa fixat flexibil niciunul mic mediu mare linie jumatatelinie quarterline formula alb inaltime</code> <code> adancime standard NUMMER*mic NUMMER*mediu NUMMER*mare NUMMER*linie NUMMER*jumatatelinie NUMMER*quarterline</code> <code> NUMMER*formula NUMMER*alb NUMMER*inaltime NUMMER*adancime category:NUMMER order:NUMMER penalty:NUMMER DIMENSION</code> <code> NAME</code>
<code>\WidthSpanningText {...}{...}{...}</code> <code>1 TEXT</code> <code>2 DIMENSION</code> <code>3 FONT</code>
<code>\wdofstring {...}</code> <code>* TEXT</code>

$\backslash\text{widthofstring}$ {...} * TEXT
$\backslash\text{widthspanningtext}$ {... ¹ } {... ² } {... ³ } 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{withoutpt}$ {...} * DIMENSION
$\backslash\text{words}$ {...} * TEXT
$\backslash\text{wordtonumber}$ {... ¹ } {... ² } 1 unu doi trei patru cinci 2 TEXT
$\backslash\text{writadatolist}$ [... ¹] [... ² ... _{OPT} ...] [... ³ ...] 1 LISTE 2 inherits: \seteazalista 3 KEY = VALUE
$\backslash\text{writestatus}$ {... ¹ } {... ² } 1 TEXT 2 TEXT
$\backslash\text{XETEX}$
$\backslash\text{XeTeX}$
$\backslash\text{xdefconvertedargument}$ \... {... ¹ } {... ² } 1 CSNAME 2 TEXT
$\backslash\text{xequal}$ {... ¹ } {... ² } _{OPT} _{OPT} 1 TEXT 2 TEXT
$\backslash\text{xfrac}$ {... ¹ } {... ² } 1 CONTENT 2 CONTENT
$\backslash\text{xhookleftarrow}$ {... ¹ } {... ² } _{OPT} _{OPT} 1 TEXT 2 TEXT

$\xhookrightarrow{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xLeftarrow{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xLeftrightarrow{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xleftarrow{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xleftharpoonowdown{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xleftharpoonoup{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xleftrightharpoonow{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xleftrightharpoons{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xmapsto{\dots}{\dots}$ <div> <div>OPT</div> <div>OPT</div> </div> <div> <div>1 TEXT</div> <div>2 TEXT</div> </div>
$\xmladdindex{\dots}$ <div> <div>* NODE</div> </div>
$\xmلاfterdocumentsetup{\dots}{\dots}{\dots}$ <div> <div>1 NAME</div> <div>2 SETUP</div> <div>3 SETUP</div> </div>
$\xmلاftersetup{\dots}{\dots}$ <div> <div>1 SETUP</div> <div>2 SETUP</div> </div>

\xmlall {¹.} {².}

- 1 NODE
- 2 LPATH

\xmlappenddocumentsetup {¹.} {².}

- 1 NAME
- 2 SETUP

\xmlappendsetup {^{*}.}

- * SETUP

\xmlapplyselectors {^{*}.}

- * NODE

\xmlatt {¹.} {².}

- 1 NODE
- 2 NAME

\xmlattdef {¹.} {².} {³.}

- 1 NODE
- 2 NAME
- 3 TEXT

\xmlattribute {¹.} {².} {³.}

- 1 NODE
- 2 LPATH
- 3 NAME

\xmlattributedef {¹.} {².} {³.} {⁴.}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 TEXT

\xmlbadinclusions {^{*}.}

- * NODE

\xmlbeforedocumentsetup {¹.} {².} {³.}

- 1 NAME
- 2 SETUP
- 3 SETUP

\xmlbeforesetup {¹.} {².}

- 1 SETUP
- 2 SETUP

`\xmlchainatt {...} {...}`

- 1 NODE
- 2 NAME

`\xmlchainattdef {...} {...} {...}`

- 1 NODE
- 2 NAME
- 3 TEXT

`\xmlchecknamespace {...} {...}`

- 1 NODE
- 2 NAME

`\xmlcommand {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 XMLSETUP

`\xmlconcat {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT

`\xmlconcatrange {...} {...} {...} {...} {...}`

- 1 NODE
- 2 LPATH
- 3 TEXT
- 4 FIRST
- 5 LAST

`\xmlcontext {...} {...}`

- 1 NODE
- 2 LPATH

`\xmlcount {...}`

- * NODE

`\xmldefaulttotext {...}`

- * NODE

`\xmldirectives {...}`

- * NODE

`\xmldirectivesafter {...}`

- * NODE

\xmldirectivesbefore {...}

* NODE

\xmldisplayverbatim {...}

* NODE

\xmldoif {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

\xmldoifelse {...} {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

4 FALSE

\xmldoifelseempty {...} {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

4 FALSE

\xmldoifelseselfempty {...} {...} {...}

1 NODE

2 TRUE

3 FALSE

\xmldoifelsetext {...} {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

4 FALSE

\xmldoifelsevalue {...} {...} {...} {...}

1 CATEGORY

2 NAME

3 TRUE

4 FALSE

\xmldoifnot {...} {...} {...}

1 NODE

2 LPATH

3 TRUE

<pre> \xmldoifnotselfempty {...} {...} 1 NODE 2 TRUE </pre>
<pre> \xmldoifnottext {...} {...} {...} 1 NODE 2 LPATH 3 TRUE </pre>
<pre> \xmldoifselfempty {...} {...} 1 NODE 2 TRUE </pre>
<pre> \xmldoiftext {...} {...} {...} 1 NODE 2 LPATH 3 TRUE </pre>
<pre> \xmlelement {...} {...} 1 NODE 2 NUMMER </pre>
<pre> \xmlfilter {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlfirst {...} {...} 1 NODE 2 LPATH </pre>
<pre> \xmlflush {...} * NODE </pre>
<pre> \xmlflushcontext {...} * NODE </pre>
<pre> \xmlflushdocumentsetups {...} {...} 1 NAME 2 SETUP </pre>
<pre> \xmlflushlinewise {...} * NODE </pre>
<pre> \xmlflushpure {...} * NODE </pre>

\xmlflushspacewise {...} * NODE
\xmlflushtext {...} * NODE
\xmlinclude {...} {...} {...} 1 NODE 2 LPATH 3 NAME
\xmlinclusion {...} * NODE
\xmlinclusions {...} * NODE
\xmlinfo {...} * NODE
\xmlinjector {...} * NAME
\xmlinlineverbatim {...} * NODE
\xmlinstalldirective {...} {...} 1 NAME 2 CSNAME
\xmllast {...} {...} 1 NODE 2 LPATH
\xmllastatt
\xmllastmatch
\xmlloadbuffer {...} {...} {...} 1 BUFFER 2 NAME 3 XMLSETUP
\xmlloaddata {...} {...} {...} 1 NAME 2 TEXT 3 XMLSETUP

\xmlloaddirectives {...} * FILE
\xmlloadfile {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlloadonly {...} {...} {...} 1 NAME 2 FILE 3 XMLSETUP
\xmlmain {...} * NAME
\xmlmapvalue {...} {...} {...} 1 CATEGORY 2 NAME 3 TEXT
\xmlname {...} * NODE
\xmlnamespace {...} * NODE
\xmlnonspace {...} {...} 1 NODE 2 LPATH
\xmlpath {...} * NODE
\xmlpos {...} * NODE
\xmlposition {...} {...} {...} 1 NODE 2 LPATH 3 NUMMER
\xmlprependdocumentsetup {...} {...} 1 NAME 2 SETUP

<pre>\xmlprependsetup {...}</pre> <p>* SETUP</p>
<pre>\xmlprettyprint {...} {...}</pre> <p>1 NODE</p> <p>2 NAME</p>
<pre>\xmlprocessbuffer {...} {...} {...}</pre> <p>1 BUFFER</p> <p>2 NAME</p> <p>3 XMLSETUP</p>
<pre>\xmlprocessdata {...} {...} {...}</pre> <p>1 NAME</p> <p>2 TEXT</p> <p>3 XMLSETUP</p>
<pre>\xmlprocessfile {...} {...} {...}</pre> <p>1 NAME</p> <p>2 FILE</p> <p>3 XMLSETUP</p>
<pre>\xmlpure {...} {...}</pre> <p>1 NODE</p> <p>2 LPATH</p>
<pre>\xmlraw {...}</pre> <p>* NODE</p>
<pre>\xmlrefatt {...} {...}</pre> <p>1 NODE</p> <p>2 NAME</p>
<pre>\xmlregistereddokumentsetups {...} {...}</pre> <p>1 NAME</p> <p>2 SETUP</p>
<pre>\xmlregisteredsetups</pre>
<pre>\xmlregisterns {...} {...}</pre> <p>1 NAME</p> <p>2 URL</p>

\xmlremapname {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

\xmlremapnamespace {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 NAME

\xmlremovedocumentsetup {...} {...}

- 1 NAME
- 2 SETUP

\xmlremovesetup {...}

- * SETUP

\xmlresetdocumentsetups {...}

- * NAME

\xmlresetinjectors

\xmlresetsetups {...}

- * NAME

\xmlsave {...} {...}

- 1 NODE
- 2 FILE

\xmlsetentity {...} {...}

- 1 NAME
- 2 TEXT

\xmlsetfunction {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 LUAFUNCTION

\xmlsetinjectors [...;...]

- * NAME

\xmlsetsetup {...} {...} {...}

- 1 NAME
- 2 LPATH
- 3 SETUP

\xmlsetup {...} {...}

- 1 NODE
- 2 SETUP

\xmlshow {...}

- * NODE

\xmlsnippet {...} {...}

- 1 NODE
- 2 NUMMER

\xmlstrip {...} {...}

- 1 NODE
- 2 LPATH

\xmlstripnolines {...} {...}

- 1 NODE
- 2 LPATH

\xmlstripped {...} {...}

- 1 NODE
- 2 LPATH

\xmlstrippednolines {...} {...}

- 1 NODE
- 2 LPATH

\xmltag {...}

- * NODE

\xmltexentity {...} {...}

- 1 NAME
- 2 TEXT

\xmltext {...} {...}

- 1 NODE
- 2 LPATH

\xmltobuffer {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 BUFFER

\xmltobufferverbose {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 BUFFER

$\backslash\text{xmltofile}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 NODE 2 LPATH 3 FILE
$\backslash\text{xmlvalue}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ $\{\overset{3}{...}\}$ 1 CATEGORY 2 NAME 3 TEXT
$\backslash\text{xmlverbatim}$ $\{...\}$ * NODE
$\backslash\text{xRightarrow}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xrel}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xrightarrow}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xrightharpoondown}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xrightharpoonup}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xrightleftharpoons}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xrightoverleftarrow}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ <div> <div>OPT</div> <div>OPT</div> </div> 1 TEXT 2 TEXT
$\backslash\text{xsplitstring}$ $\backslash\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 CSNAME 2 TEXT

`\xtriplerel {...} {...}`
 ¹ ²
 OPT OPT

1 TEXT

2 TEXT

`\xtwoheadleftarrow {...} {...}`
 ¹ ²
 OPT OPT

1 TEXT

2 TEXT

`\xtwoheadrightarrow {...} {...}`
 ¹ ²
 OPT OPT

1 TEXT

2 TEXT

`\xxfrac {...} {...}`

1 CONTENT

2 CONTENT

`\xypos {...}`

* NAME

`\ZIDINSAPTAMANA {...}`

* NUMMER

`\zidinsaptamana {...}`

* NUMMER



PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com