attributes backends bibtex bit32 blobs boolean buffers builders caches callbacks catcodes characters chemistry commands containers context converters coroutine ctxrunner debug dir directives document documentdata environment epdf experiments figures file floats for fontloader fonts functions global graphics gzip img interactions interfaces io job lamo languages layouts libraries lmx logs lpdf lpeg ltn12 luatex lxml math mathematics mbox md5 metapost mime moduledata modules mplib noads node nodes number os package pagebuilders parametersets pdfscanner physics profiler regimes resolvers scripts set socket sorters statistics status storage streams string structures table tex thirddata token tokens tracers trackers typesetters unicode url userdata utilities vf visualizers xml zip zlib

ConT_EXt MkIV

global (alias: _G)

| LUAVERSION | number | floats | table |
|----------------|----------|-----------------|----------|
| MAJORVERSION | number | font | table |
| MINORVERSION | number | fontloader | table |
| arg | table | fonts | table |
| assert | function | frozen | boolean |
| attributes | table | functions | table |
| backends | table | getmetatable | function |
| beginpage | function | getreadfilename | function |
| bibtex | table | global | table |
| bit32 | table | graphics | table |
| blobs | table | gzip | table |
| boolean | table | img | table |
| buffers | table | inspect | function |
| builders | table | interactions | table |
| caches | table | interfaces | table |
| callback | table | io | table |
| callbacks | table | ipairs | function |
| catcodes | table | job | table |
| characters | table | lang | table |
| chemistry | table | languages | table |
| collectgarbage | function | layouts | table |
| commands | table | lfs | table |
| containers | table | libraries | table |
| context | function | lmx | table |
| converters | table | lmxconvert | function |
| coroutine | table | lmxnew | function |
| ctxrunner | table | load | function |
| debug | table | loadfile | function |
| dimen | function | loadstring | function |
| dir | table | logs | table |
| directives | table | lp_fastpos_n | userdata |
| document | table | lp_fastpos_p | userdata |
| documentdata | table | lpdf | table |
| dofile | function | lpeg | table |
| endpage | function | ltn12 | table |
| environment | table | lua | table |
| epdf | table | luatex | table |
| error | function | lxml | table |
| experiments | table | math | table |
| figures | table | mathematics | table |
| file | table | mbox | table |

| metapost table socket table mime table function statistics table module function statistics table moduledata table strange table strange table moduleds table strange table modules table strange table modules table strange table mplib table streams table newline function string table newline function string table newt function string table node table swiglib function noads table swiglib function nodes table table table table table number table table table table table optional require function texconfig table outputpagestree function thirddata table package table toboolean function pagebuilders table token table parametersets table tonumber function profile table table trace_characters boolean pdf table trace_characters boolean pdfscanner table trace_characters table traceps table traceps function trackers table print function trackers table process function type function profiler table table traceps function rawget function unloade table rawequal function unpack function rawget function unpack function unpac | md5 | table | setmetatable | function |
|--|-------------------|----------|------------------|----------|
| mime table sorters table module function statistics table moduledata table status table modules table storage table mplib table streams table newline function string table next function string table node table swiglib function nodes table swiglib function nodes table table table table number table tex table number table tex table optional require function texconfig table outputpagestree function thirddata table package table toboolean function pagebuilders table token table pairs function tokens table parametersets table tonumber function pcall function tostring function pdf table trace_characters boolean pdfscanner table traceback function physics table traceback function physics table traceback function profiler table typesetters table print function trackers table process function unjock function rawequal function unpack function rawequal function unpack function rawet function unserdat table regimes table utilities table regimes table xml table resolvers table xml table | | | | |
| moduledata table status table modules table storage table mplib table streams table newline function string table next function stripath function noads table swiglib function node table swiglib function nodes table table table number table tex table optionalrequire function texconfig table outputpagestree function thirddata table package table token table pairs function tokens table parametersets table tonumber function pdf table trace_characters boolean pdfscanner table trace_characters table print function trackers table protect function unicode table protect function unpack function prowled function unpack function rawget | • | | | table |
| moduledata table status table modules table storage table mplib table streams table newline function string table next function stripath function noads table swiglib function node table swiglib function nodes table table table number table tex table optionalrequire function texconfig table outputpagestree function thirddata table package table token table pairs function tokens table parametersets table tonumber function pdf table trace_characters boolean pdfscanner table trace_characters table print function trackers table protect function unicode table protect function unpack function prowled function unpack function rawget | module | function | statistics | table |
| modules table streams table mplib table streams table newline function string table next function stripmath function noads table swiglib function node table swiglib function nodes table tex table number table tex table optional require function texconfig table outputpagestree function thirddata table package table toboolean function pagebuilders table token table pairs function tokens table parametersets table tonumber function pdf table traceback function pdf table traceback function pdf table traceback function physics table traceback function profiler table type function profiler table type function profiler table typesetters table protect function unicode table rawequal function unpack function profiler table typesetters table protect function unpack function rawequal function unpack function rawet function userdata table rawet function userdata table regimes table utilities table regimes table xml table regimes table xml table scripts table xml table | | | | |
| mplib table streams table newline function string table next function stripmath function noads table structures table node table swiglib function nodes table table table number table tex table optionalrequire function texconfig table os table texio table outputpagestree function thirddata table package table token table pagebuilders table token table parametersets table tonumber function pcall function tostring function pdf table trace_characters boolean pdfscanner table trace_characters boolean physics table tracers table print function type function profiler table typesetters table process function unicode table protect function unpack function profiler table tupesetters table protect function unpack function profiler table typesetters table protect function unpack function rawget function userdata table rawset function userdata table regimes table utilities table regimes table xml table regimes table xml table regimes function visualizers table regimes function visualizers table regolvers table xml table scripts table xml table | | | | |
| newline function string table next function stripmath function noads table structures table node table swiglib function nodes table table table table number table tex table optionalrequire function texconfig table os table texio table outputpagestree function thirddata table package table toboolean function pagebuilders table token table pairs function tokens table parametersets table tonumber function pdf table trace_characters boolean pdfscanner table trace_characters boolean pdfscanner table traces table print function trackers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function unpack function rawget function unpack function rawget function unpack table rawenal function unpack table rawenal function unpack table raweter function unicode table raweter function unpack function rawget function unpack table raweter function unpack table report_characters function visualizers table report_characters function visualizers table resolvers table xmlconvert function select function xpcall function | | | _ | |
| nextfunctionstripmathfunctionnoadstablestructurestablenodetableswiglibfunctionnodestabletabletablenumbertabletextableoptionalrequirefunctiontexconfigtableostabletexiotableoutputpagestreefunctionthirddatatablepackagetabletobooleanfunctionpagebuilderstabletokentablepairsfunctiontokenstableparametersetstabletonumberfunctionpcallfunctiontostringfunctionpdftabletrace_charactersbooleanpdfscannertabletrace_charactersbooleanpdfscannertabletrace_charactersbooleanpdfscannertabletrace_charactersbooleanpdfscannertabletrace_charactersbooleanpdfscannertabletrace_characterstableprintfunctiontrace_characterstableprintfunctiontrace_characterstableprocessfunctionunicodetableprocessfunctionunpackfunctionrawgealfunctionurltablerawgealfunctionurltablerawgealfunctionvisualizerstablerepuirefunctionvisualizerstableresolvers <th>•</th> <th>function</th> <th></th> <th></th> | • | function | | |
| noadstablestructurestablenodetableswiglibfunctionnodestabletabletablenumbertabletextableoptionalrequirefunctiontexconfigtableostabletexiotableoutputpagestreefunctionthirddatatablepackagetabletokentablepagebuilderstabletokentablepairsfunctiontokenstableparametersetstabletonumberfunctionpcallfunctiontostringfunctionpdftabletrace_charactersbooleanpdfscannertabletracebackfunctionphysicstabletracerstableprintfunctiontrackerstableprocessfunctiontypefunctionprofilertabletypesetterstableprotectfunctionunicodetablerawequalfunctionunpackfunctionrawgetfunctionurltablerawsetfunctionuserdatatableregimestableutilitiestableregimestableutilitiestablereport_charactersfunctionvisualizerstablerequirefunctionvisualizerstableresolverstablexmltableselectfunctionxpcallfunctionselect | | | • | |
| node table swiglib function nodes table table table table table optional require function texconfig table os table texio table texio table outputpagestree function thirddata table package table token table token table pairs function tokens table tonumber function pagebuilders table tonumber function pageluilders table tonumber function podf table trace_characters boolean pdfscanner table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function utf table table report_characters function vf table report_characters function visualizers table regort_characters function visualizers table scripts table xml table xml table scripts table xml table function set table xml function set | | | • | |
| nodestabletabletablenumbertabletextableoptionalrequirefunctiontexconfigtableostabletexiotableoutputpagestreefunctionthirddatatablepackagetabletobooleanfunctionpagebuilderstabletokentablepairsfunctiontokenstableparametersetstabletonumberfunctionpcallfunctiontostringfunctionpdftabletrace_charactersbooleanpdfscannertabletracebackfunctionphysicstabletracerstableprintfunctiontrackerstableprocessfunctiontypefunctionprofilertabletypesetterstableprotectfunctionunicodetablerawequalfunctionunpackfunctionrawgetfunctionurltablerawlenfunctionuserdatatableregimestableutilitiestableregimestableutilitiestablerequirefunctionvisualizerstablerequirefunctionvisualizerstableresolverstablexml convertfunctionselectfunctionxpcallfunctionsettableziptable | node | table | swialib | function |
| numbertabletextableoptionalrequirefunctiontexconfigtableostabletexiotableoutputpagestreefunctionthirddatatablepackagetabletobooleanfunctionpagebuilderstabletokentablepairsfunctiontokenstableparametersetstabletonumberfunctionpcallfunctiontostringfunctionpdftabletrace_charactersbooleanpdfscannertabletracebackfunctionphysicstabletracerstableprintfunctiontrackerstableprocessfunctiontypefunctionprofilertabletypesetterstableprotectfunctionunicodetablerawequalfunctionunpackfunctionrawgetfunctionurltablerawsetfunctionuserdatatableregimestableutilitiestableregimestableutilitiestablerequirefunctionvisualizerstablerequirefunctionvisualizerstableresolverstablexml convertfunctionselectfunctionxpcallfunctionsettableziptable | nodes | table | - | table |
| optional require function table texio table outputpagestree function thirddata table package table toboolean function pagebuilders table token table pairs function tokens table parameter sets table tonumber function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawet function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xml table scripts table xmlconvert function set table zip table function | number | | tex | |
| os table texio table outputpagestree function thirddata table package table toboolean function pagebuilders table token table pairs function tokens table parametersets table tonumber function pcall function tostring function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table print function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table regimes table xml table require function visualizers table resolvers table xml table scripts table xmlconvert function set table zip table | optionalrequire | function | | table |
| package table token table pairs function tokens table parametersets table tonumber function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawset function userdata table regimes table utilities table regimes table xml table resolvers table xml table resolvers table xml table resolvers table xml table resolvers table xml table rection xpcall function set table zip table | | table | • | table |
| package table token table pairs function tokens table parametersets table tonumber function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function type function profiler table typesetters table protect function unicode table rawequal function url table rawet function url table rawset function userdata table regimes table utilities table require function visualizers table resolvers table xml table scripts table xml table scripts table xml table scripts table xml table scripts table xml table script table xml table script table xml table script table xml table script table xml table | outputpagestree | function | thirddata | table |
| pagebuilders table token table pairs function tokens table parametersets table tonumber function pcall function tostring function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function set table zip table | | table | toboolean | function |
| pairs function tokens table parametersets table tonumber function pcall function tostring function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table scripts table xml table scripts table xmlconvert function set table zip table | | table | token | table |
| pcall function tostring function pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table report_characters function vf table require function visualizers table scripts table xml table xml table scripts table xml table function set table zip table | | function | tokens | table |
| pdf table trace_characters boolean pdfscanner table traceback function physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function set table zip table | parametersets | table | tonumber | function |
| pdfscanner physics table tracers table print function process function profiler table protect function rawequal function rawget function tunl table rawlen function tune table tunction tune table tunction tune tunl table regimes table tunction vf table require function visualizers table scripts table tracers table trackers table type function type function unicode table tunction unpack function unpack function url table table table table visualizers table scripts table xml table table scripts table xml table | pcall | function | tostring | function |
| physics table tracers table print function trackers table process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xml table select function xpcall function set table | pdf | table | trace_characters | boolean |
| print function type function process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function select function xpcall function set table | pdfscanner | table | traceback | function |
| process function type function profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table require function vf table resolvers table xml table scripts table xml table scripts table xmlconvert function set table zip table | physics | table | tracers | table |
| profiler table typesetters table protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function set table zip table | print | function | trackers | table |
| protect function unicode table rawequal function unpack function rawget function url table rawlen function userdata table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xml table xml table select function xpcall function set table | process | function | type | function |
| rawequal function unpack function rawget function url table rawlen function userdata table rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function select function xpcall function set table | profiler | table | typesetters | table |
| rawget function url table rawlen function userdata table rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function set table zip table | protect | function | unicode | table |
| rawlen function userdata table rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function select function xpcall function set table zip table | rawequal | function | unpack | function |
| rawset function utf table regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function select function xpcall function set table zip table | rawget | function | url | table |
| regimes table utilities table report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function select function xpcall function set table zip table | rawlen | function | userdata | table |
| report_characters function vf table require function visualizers table resolvers table xml table scripts table xmlconvert function select function xpcall function set table zip table | rawset | function | utf | table |
| requirefunctionvisualizerstableresolverstablexmltablescriptstablexmlconvertfunctionselectfunctionxpcallfunctionsettableziptable | regimes | table | utilities | table |
| resolvers table xml table scripts table xmlconvert function select function table zip table | report_characters | function | vf | table |
| scriptstablexmlconvertfunctionselectfunctionxpcallfunctionsettableziptable | require | function | visualizers | table |
| selectfunctionxpcallfunctionsettableziptable | resolvers | table | xml | table |
| set table zip table | scripts | table | xmlconvert | function |
| | select | function | xpcall | function |
| setinspector function zlib table | set | table | zip | table |
| | setinspector | function | zlib | table |

attributes (context)

| colorintents | table | | F mpoptions | |
|------------------|------------|-----|-----------------|------------|
| N attribute | | | U none | |
| D data | | | F popset | |
| F enable | | | F pushset | |
| F handler | | | F register | |
| F register | | | D registered | |
| D registered | | | F registerspoto | color |
| colors | table | | F rgb | |
| N attribute | | | F rgbtocmyk | |
| F cmyk | | | F rgbtogray | |
| F cmyktogray | | | F rgbtohsv | |
| F cmyktorgb | | | N selector | |
| F colorcomponent | CS | | F setlist | |
| B couple | | | F setmodel | |
| D data | | | D sets | |
| N default | | | F spec | |
| F defineintermed | Hiatecolor | | F spot | |
| F definemixcolor | - | | F spotcolorname | 2 |
| F definemultiton | necolor | | F spotcolorpare | ent |
| F defineprocesso | color | | F spotcolorvalu | ie |
| F definesimplegr | ay | | B supported | |
| F definespotcolo | or | | F transparency | components |
| F definetranspar | rency | | B triggering | |
| F enable | | | F usecolors | |
| F filter | | | F value | |
| F forcedmodel | | | D values | |
| F forcesupport | | | B weightgray | |
| F formatcolor | | det | fine | function |
| F formatgray | | ef1 | fects | table |
| F gray | | | N attribute | |
| F graytohsv | | | D data | |
| F handler | | | F enable | |
| F hsvtogray | | | F handler | |
| F hsvtorgb | | | F register | |
| F iccprofile | | | D registered | |
| F isblack | | | D values | |
| N main | | | ndlers | table |
| S model | | lis | | data table |
| D models | | nan | | data table |
| F mpcolor | | neg | gatives | table |
| F mpnamedcolor | | | N attribute | |

D data D registered
F enable B supported
F handler B triggering
F register F value
D registered D values

numbers data table
ofnode function
private function
showcurrent function
states table

F disabletriggering
F enabletriggering

F finalize
F initialize
F process
F selective
F stacked
F stacker

transparencies table

N attribute
D data
F enable
F forcesupport
F handler
U none
F register

> N attribute D data F define F enable F forcesupport F handler B hasorder D listwise F register D registered F resolve begin F resolve end F resolve_step D scopes F setfeatures F start F stop

B supported D values

backends (context)

F registerdocumentcloseaction

codeinjections table F registerdocumentopenaction F synchronizecolormodel F registeredsymbol current strina F registerpagecloseaction table defaults F registerpageopenaction T codeinjections F registersymbol T nodeiniections F setfieldcalculationset T registrations F setfigurealternative D tables F setfigurecolorspace install function F setfiguremask nodeinjections table F setformat F setformsmethod F restore F save F setpagetransition F transform F setupcanvas function nothina F setupidentity pdf table F setxmpfile T codeinjections F startlayer F addbookmarks F stoplayer F attachmentid F supportedformats F clonefield F useviewerlaver F definefield F validfield E definefieldset F validfieldcategory F defineviewerlaver F validfieldset F embedfile S comment F enabletags T nodeinjections F exportformdata F addtags F finalizepage F attachfile F finishreference F changestackedlayer F getdefaultfieldvalue F cmykcolor F getfieldcategory F comment F getfieldset F destination F getformatoption F effect F getoutputfilename F graycolor F getpreviewfigure F injectbitmap F insertrenderingwindow F insertmovie F mergereferences F insertsound F insertswf F mergeviewerlayers F prerollreference F insertu3d F knockout F presetsymbol F presetsymbollist F negative F processrendering F overprint

F positive

F reference F rgbcolor F spotcolor F startlayer F startstackedlayer

F stoplayer

F stopstackedlayer F transparency

F typesetfield T registrations

F cmykindexcolor F cmykspotcolor

F getspotcolorreference

F grayindexcolor F grayspotcolor F rgbindexcolor F rgbspotcolor F spotcolorname F transparency

T tables

D vfspecials

registrations table tables table

bibtex (context)

F filterall

| authorref authors | function table | F flush F nofregistered | |
|----------------------|-------------------|----------------------------|----------|
| F concat | | F process | |
| F inverted | | F register | |
| F invertedshort | | F registerplaced | |
| F normal | | F reset | |
| F normalshort | | F resolve | |
| F setsettings | | load | function |
| F short | | new | function |
| authoryearref | function | singularorplural | function |
| authoryearsref | function | statistics | table |
| convert | function | N nofbytes | |
| hacks | table | N nofdefinitions | |
| F add | | N nofshortcuts | |
| F doifalreadyplace | d | toxml | function |

bit32 (basic lua)

| arshift | function | extract | function |
|---------|----------|---------|----------|
| band | function | lrotate | function |
| bnot | function | lshift | function |
| bor | function | replace | function |
| btest | function | rrotate | function |
| bxor | function | rshift | function |

blobs (context)

| append | function | new | function |
|------------|----------|-------|----------|
| dimensions | function | pack | function |
| dispose | function | write | function |

boolean (context)

tocontext function

tonumber function

buffers (context)

| append | function | parallel | table |
|----------------|----------|------------------|----------|
| assign | function | F define | |
| collectcontent | function | F hassomecontent | i . |
| erase | function | F next | |
| exists | function | F place | |
| getcontent | function | F reset | |
| getlines | function | F save | |
| loadcontent | function | raw | function |

builders (context)

| kernel | table | F optimize |
|-----------|-----------------|-----------------------|
| F hypher | nation | T registered |
| F kernin | ng | F reset |
| F ligatu | uring | F set |
| F mlist_ | _to_hlist | F split |
| paragraph | ıs table | F start |
| T consti | ructors | F stop |
| N attr | ribute | F tag |
| F defi | .ne | vspacing table |
| F disa | ble | F analyze |
| F enab | ole | D categories |
| F hand | ller | F collapsevbox |
| T meth | nods | T data |
| F de | fault | D map |
| F on | eline | D skip |
| D name | es | D snapmethods |
| D numb | pers | F definesnapmethod |
| F set | | B fixed |
| F star | t | F pagehandler |
| F stop | | F setmap |
| F keepto | ogether | F setskip |
| F regist | tertogether | F snapbox |
| T solut: | ions | F tocategories |
| T spli | tters | F tocategory |
| F de | fine | F vboxhandler |
| | | |

caches (context)

| ask | boolean |
|----------------------|----------|
| base | string |
| collapsecontent | function |
| configfiles | function |
| contentstate | function |
| defaults | table |
| define | function |
| direct | boolean |
| force | boolean |
| getfirstreadablefile | function |
| getreadablepaths | function |
| getwritablepath | function |
| hashed | function |

| is_writable | function |
|----------------------|----------|
| loadcontent | function |
| loaddata | function |
| more | string |
| relocate | boolean |
| savecontent | function |
| savedata | function |
| setfirstwritablefile | function |
| setluanames | function |
| tree | string |
| treehash | function |
| usedpaths | function |

callback (basic tex)

find function
list function

register overloaded function

callbacks (context)

| freeze | function | |
|--------|------------|--|
| known | function | |
| list | data table | |
| рор | function | |

push function
register function
report function

catcodes (context)

names data table
numbers data table

register function

characters (context)

| activeoffset | number | lcchars | data table |
|--------------|------------|----------------------|------------|
| adobename | function | lccode | function |
| bidi | data table | lccodes | data table |
| blockrange | function | lettered | function |
| blocks | data table | lower | function |
| casemap | table | math | table |
| categories | data table | mathpairs | data table |
| category | function | otfscripts | data table |
| categorytags | data table | ranges | data table |
| combined | data table | registerentities | function |
| contextname | function | remap_hangul_syllabe | function |
| data | data table | safechar | function |
| decomposed | data table | setcodes | function |
| define | function | shape | function |
| description | function | shaped | function |
| descriptions | data table | shchars | data table |
| directions | table | shcodes | data table |
| enccodes | data table | specialchars | data table |
| entities | data table | specials | data table |
| fallbacks | data table | subscripts | table |
| filters | data table | superscripts | table |
| fromnumber | function | synonyms | data table |
| fschars | data table | tex | table |
| fscodes | data table | D accentmapping | |
| getrange | function | F defineaccents | |
| graphemes | data table | F toutf | |
| hangul | data table | tonumber | function |
| initialize | function | ucchars | data table |
| is_character | data table | uccode | function |
| is_command | data table | uccodes | data table |
| is_letter | data table | unicodechar | function |
| is_mark | data table | upper | function |
| is_spacing | data table | | |
| | | | |

chemistry (context)

component
define function
definitions data table
format string
instance string
molecule function

moleculeparser userdata
start function
stop function
structures number
undefine function

commands (context)

| Al mhahati a | £ | | £ |
|---------------------------|----------------------|-------------------------|----------|
| Alphabetic | function function | autonextstructurelevel | function |
| Character | | autosetups | function |
| Characters | function | autostarttext | function |
| MPC | function | autostoptext | function |
| MPd | function | averagecharwidth | function |
| MPh | function | bcolumn | function |
| MPll | function | boolcase | function |
| MPlr | function | character | function |
| MPls | function | characters | function |
| MPn | function | checkcharactersinfont | function |
| MPp | function | checkcountersetup | function |
| MPpardata | function | checkedconversion | function |
| MPplus | function | checkedpagefloat | function |
| MPpos | function | checktwopassdata | function |
| MPposset | function | chemicalcomponent | function |
| MPr | function | chineseallnumerals | function |
| MPrest | function | chinesecapnumerals | function |
| MPrs | function | chinesenumerals | function |
| MPul | function | cleanfontname | function |
| MPur | function | cleanuplayers | function |
| MPw | function | clonefield | function |
| MPx | function | collectfloat | function |
| MPxy | function | collecthelp | function |
| MPxywhd | function | colorcomponents | function |
| MPy | function | concatcommalist | function |
| Romannumerals | function | consultfloat | function |
| abjadnodotnumerals | function | copyposition | function |
| abjadnumerals | function | cos | function |
| addcounter | function | cosd | function |
| addlinklistelement | function | countervalue | function |
| addtojavascriptpreamble | function | counttwopassdata | function |
| addtolist | function | currentcomponent | function |
| allinputpaths | function | currentdate | function |
| alphabetic | function | currentenvironment | function |
| analysefloatmethod | function | currentproduct | function |
| analyzelist | function | currentproject | function |
| applytochars | function | currentreferencedefault | function |
| applytowords | function | currentreferenceorder | function |
| assignbuffer | function | currentregime | function |
| autofinishstructurelevels | function | datasetvariable | function |
| autonextspace | function | dayname | function |
| | | | |

| defineattribute | function | doanalyzeframedbox | function |
|-------------------------|----------|-------------------------------|----------|
| definebibtexsession | function | doif | function |
| definebreakpoint | function | doifblackelse | function |
| definebreakpoints | function | doifcommonelse | function |
| definecharacterspacing | function | doifcounter | function |
| definechemical | function | doifdimenstringelse | function |
| defineconversion | function | doifdrawingblackelse | function |
| definecounter | function | doifelse | function |
| definedviewerlayer | function | doifelsebuffer | function |
| definefield | function | doifelsecontinuewithfile | function |
| definefieldset | function | doifelsecounter | function |
| definefilefallback | function | doifelsecurrentfonthasfeature | function |
| definefilesynonym | function | doifelseintwopassdata | function |
| definefont_one | function | doifelsemarking | function |
| definefont_two | function | doifelsemessage | function |
| definefontfeature | function | doifelsemultipar | function |
| definefontsolution | function | doifelseparallel | function |
| defineinsertion | function | doifelsepositionsused | function |
| defineintermediatecolor | function | doifelserangeonpage | function |
| definelabels | function | doifelsereference | function |
| definelanguage | function | doifelsesavedfloat | function |
| definelinkedlist | function | doifelsespaces | function |
| definemarking | function | doifelseutfmathaccent | function |
| definemultitonecolor | function | doifelsevisualizer | function |
| definenote | function | doiffieldcategoryelse | function |
| defineparallel | function | doiffieldelse | function |
| defineparbuilder | function | doiffieldsetelse | function |
| defineprocesscolor | function | doiffiledefinedelse | function |
| defineprogram | function | doiffileexistelse | function |
| definereference | function | doiffirstcharelse | function |
| definesectionlevels | function | doifinputfileelse | function |
| definespotcolor | function | doifinsetelse | function |
| definestructureblock | function | doifleapyearelse | function |
| definestructureset | function | doiflisthasentry | function |
| definetransparency | function | doiflisthasnumberelse | function |
| definetwopasslist | function | doiflisthaspageelse | function |
| defineviewerlayer | function | doiflisthastitleelse | function |
| defrostrandomseed | function | doiflocfileelse | function |
| digits | function | doifnot | function |
| disableautofontscript | function | doifnotcounter | function |
| disableparbuilder | function | doifnotecontent | function |
| disableregime | function | doifnoteonsamepageasprevious | function |
| disablespellchecking | function | doifobjectreferencefoundelse | function |
| discardfromlist | function | doifolderversionelse | function |

| doifoverlappingelse | function | figurestatus | function |
|-----------------------------|----------|-----------------------------|----------|
| doifparentfileelse | function | figureused | function |
| doifposition | function | figurevariable | function |
| doifpositionelse | function | filterdefaultreference | function |
| doifpositiononpage | function | filterreference | function |
| doifpositionsonsamepageelse | function | finalizebox | function |
| doifpositionsonthispageelse | function | findtwopassdata | function |
| doifurldefinedelse | function | firstcountervalue | function |
| doprocesstypescriptfile | function | firstinset | function |
| doreshapeframedbox | function | flushfloat | function |
| dostarttextfile | function | flushnotes | function |
| dostoptextfile | function | flushpostponedblocks | function |
| ecolumn | function | flushpostponednotes | function |
| elapsedtime | function | fontchar | function |
| enableautofontscript | function | fontcollectionclone | function |
| enablecolor | function | fontcollectiondefine | function |
| enablecolorintents | function | fontcollectionprepare | function |
| enablefontcolorschemes | function | fontcollectionregister | function |
| enableparbuilder | function | fontcollectionreport | function |
| enableregime | function | fontcollectionreset | function |
| enablespellchecking | function | fontlookupgetkey | function |
| enabletransparency | function | fontlookupgetkeyofindex | function |
| enhancelinkedlist | function | fontlookupinitialize | function |
| enhancelist | function | fontlookupnoffound | function |
| enhancereference | function | forceendjob | function |
| erasebuffer | function | forcequitjob | function |
| expandcurrentreference | function | format | function |
| exportformdata | function | formatcolor | function |
| exportreferences | function | formatgray | function |
| extensiblecode | function | freezerandomseed | function |
| feature | function | from | function |
| featureattribute | function | getbuffer | function |
| featurelist | function | getbufferctxlua | function |
| feedback | function | getbuffermkvi | function |
| fetchallmarks | function | getcommandline | function |
| fetchmultipar | function | getctxfile | function |
| fetchmultishape | function | getcurrentprefixspec | function |
| fetchonemark | function | getcurrentreferencemetadata | function |
| fetchposboxes | function | getdefaultfieldvalue | function |
| fetchtwomarks | function | getfieldcategory | function |
| figurefilename | function | getfirstcharacter | function |
| figurefilepath | function | getfirsttwopassdata | function |
| figurefiletype | function | getfloatvariable | function |
| figurerequest | function | getinternalreference | function |

| getlasttwopassdata | function | installtexdirective | function |
|-------------------------|----------|---------------------|----------|
| getmarking | function | installtextracker | function |
| getmessage | function | languagenumber | function |
| getmpextensions | function | lastcountervalue | function |
| getnotestate | function | lchexnumber | function |
| getplaceholderchar | function | lchexnumbers | function |
| getprivateattribute | function | leapyear | function |
| getprivatechar | function | linenumbersstageone | function |
| getprogram | function | linenumbersstagetwo | function |
| getrandomcounta | function | listgroupindex | function |
| getrandomcountb | function | listlabel | function |
| getrandomseed | function | listlocation | function |
| getreadfilename | function | listprefixednumber | function |
| getsubstring | function | listprefixedpage | function |
| gettexbuffer | function | listrealpage | function |
| gettwopassdata | function | listsize | function |
| gettwopassdatalist | function | listtitle | function |
| geturl | function | listuserdata | function |
| grabbuffer | function | loadexamodes | function |
| helpaction | function | loadfontgoodies | function |
| helpreference | function | loadspellchecklist | function |
| hexstringtonumber | function | loadtypescriptfile | function |
| horizontalcode | function | loadvisualizer | function |
| hour | function | locatefilepath | function |
| hyphenatedlist | function | locfilename | function |
| hyphenatedurl | function | makeactive | function |
| D characters | | markfonts | function |
| N lefthyphenmin | | markregionbox | function |
| D mapping | | math_frac | function |
| N righthyphenmin | | mathrenderset | function |
| F setcharacters | | maxitemwidth | function |
| incrementedcounter | function | minute | function |
| initializetexdirectives | function | mixcleanup | function |
| initializetextrackers | function | mixfinalize | function |
| injectcurrentreference | function | mixflushlist | function |
| injectreference | function | mixflushrest | function |
| inlinechemical | function | mixgetsplit | function |
| insertattachment | function | mixsetsplit | function |
| insertcomment | function | mixstate | function |
| insertfield | function | molecule | function |
| insertionnumber | function | month | function |
| insertrenderingwindow | function | monthmnem | function |
| insertsoundclip | function | monthname | function |
| installedlanguages | function | mpcolor | function |

| mpoptions | function | prepareMPvariable | function |
|---|----------|----------------------------|----------|
| namedstructureuservariable | function | preparebibtexsession | function |
| namedstructurevariable | function | preparedfile | function |
| nbfs | function | presetsymbollist | function |
| nextcountervalue | function | presettabulate | function |
| nextparallel | function | prevcountervalue | function |
| nofdays | function | processbuffer | function |
| nofitems | function | processedfile | function |
| nofstackedfloats | function | processedfiles | function |
| notedeltapage | function | processfile | function |
| notelistindex | function | processfilemany | function |
| notenumberpage | function | processfilenone | function |
| noteprefixednumber | function | processfileonce | function |
| notesymbolpage | function | processlist | function |
| notetitle | function | pushfloat | function |
| ntimes | function | pushitaliccorrection | function |
| number | function | pushlist | function |
| numbers | function | pushregime | function |
| objectnumber | function | pushsectionblock | function |
| objectpage | function | rawcharacter | function |
| octnumber | function | rawcountervalue | function |
| octstringtonumber | function | rawdate | function |
| ordinal | function | referencepagestate | function |
| overloadbookmark | function | referencerealpage | function |
| <pre>page_injections_flush_after</pre> | function | registerattachment | function |
| <pre>page_injections_flush_before</pre> | function | registerbibtexentry | function |
| page_injections_save | function | registerbibtexfile | function |
| pagestaterealpage | function | registerbookmark | function |
| parpos | function | registerbuttons | function |
| pdfrotation | function | registercolor | function |
| percentageof | function | registercolorintent | function |
| pgfxcolorspec | function | registeredviewerlayer | function |
| placeparallel | function | registerhelp | function |
| popfloat | function | registeritemgroup | function |
| popitaliccorrection | function | registerlanguagefeatures | function |
| poplist | function | registerlinenumbering | function |
| popregime | function | registermaintextcolor | function |
| popsectionblock | function | registernamespace | function |
| pos | function | registerpostponedblock | function |
| posplus | function | registerrendering | function |
| posstrut | function | registersoundclip | function |
| postponenotes | function | registerstructureprocessor | function |
| poswhd | function | registertransparency | function |
| posxy | function | registerunit | function |

| relatemarking | function | setcharacterstripping | function |
|--------------------------|----------|--------------------------|----------|
| remapentity | function | setclosedocumentaction | function |
| removemissingcharacters | function | setclosepageaction | function |
| renderingvar | function | setcolormodel | function |
| replacemissingcharacters | function | setcounter | function |
| replacepospxywhd | function | setdataset | function |
| resavefloat | function | setdigitsmanipulation | function |
| resetcounter | function | setdirection | function |
| resetfontfeature | function | setdocumentenvironments | function |
| resetfontsolution | function | setdocumentfilenames | function |
| resetmarking | function | setdocumentmodes | function |
| resetmathitalics | function | setdocumentmodules | function |
| resetnullfont | function | setfigurelookuporder | function |
| resetparallel | function | setfontfeature | function |
| resetreference | function | setfontofid | function |
| resetstructureprocessor | function | setfontsolution | function |
| resettimer | function | setformat | function |
| restartcounter | function | setformsmethod | function |
| restorecounter | function | setinsertionlocation | function |
| restorecurrentattributes | function | setinterfaceconstant | function |
| restorenote | function | setinterfaceelement | function |
| romannumerals | function | setinterfacemessage | function |
| runbuffer | function | setinterfacemessages | function |
| safechar | function | setinterfacevariable | function |
| savebuffer | function | setinternalreference | function |
| savecounter | function | setlanguageexceptions | function |
| savecurrentattributes | function | setlanguagesynonym | function |
| savedlistnumber | function | setlayer | function |
| savedlistprefixednumber | function | setmarking | function |
| savedlisttitle | function | setmathalphabet | function |
| savefloat | function | setmathalternate | function |
| savenote | function | setmathattribute | function |
| saveobject | function | setmathitalics | function |
| saveparallel | function | setmathstyle | function |
| savestructureblock | function | setnextinternalreference | function |
| savetaggedtwopassdata | function | setnotestate | function |
| savetwopassdata | function | setnotesymbolpage | function |
| second | function | setobject | function |
| selectstructureblock | function | setopendocumentaction | function |
| setbreakpoints | function | setopenpageaction | function |
| setcharactercasing | function | setowncounter | function |
| setcharactercleaning | function | setpagestate | function |
| setcharacterkerning | function | setpagestaterealpageno | function |
| setcharacterspacing | function | setpagetransition | function |

| The second secon | unction |
|--|---------|
| setrandomsood function spetcoloryalue f | |
| section spoced random spoced value | unction |
| setrealign function startchemical f | unction |
| setreferencearguments function startcolorset f | unction |
| <pre>setreferenceattribute function startcomponent f</pre> | unction |
| <pre>setreferenceoperation function startenvironment f</pre> | unction |
| setsectionblock function startfontsolution f | unction |
| setstructureblockstate function startparbuilder f | unction |
| settagcombination function startproduct f | unction |
| settagdescription function startproject f | unction |
| <pre>settagdescriptionsymbol function startregime f</pre> | unction |
| settagfigure function startsectionlevel f | unction |
| settaghighlight function starttag f | unction |
| settagitemgroup function starttext f | unction |
| settagproperty function startviewerlayer f | unction |
| settagsorting function stopchemical f | unction |
| settagsynonym function stopcolorset f | unction |
| settagtablecellfunctionstopcomponentf | unction |
| <pre>settagtabulatecell function stopenvironment f</pre> | unction |
| setupbookmarksfunctionstopfontsolutionf | unction |
| setupcanvasfunctionstopparbuilderf | unction |
| setupcharacterspacing function stopproduct f | unction |
| <pre>setupexport function stopproject f</pre> | unction |
| <pre>setupfontexpansion function stopregime f</pre> | unction |
| setupfontprotrusion function stopsectionlevel f | unction |
| setupidentity function stoptag f | unction |
| and the second s | unction |
| setupitaliccorrectionfunctionstopviewerlayerf | unction |
| <pre>setuplinenumbering function storejavascriptcode f</pre> | unction |
| setvisual function storejavascriptpreamble f | unction |
| • | unction |
| | unction |
| - | unction |
| 5 | unction |
| showchardata function structurenumber f | unction |
| | unction |
| · | unction |
| 21 | unction |
| • | unction |
| · | unction |
| • | unction |
| <pre>sind function taggedmathfunction f</pre> | unction |
| | unction |

| tand | function | useurl | function |
|------------------------|----------|---------------------------------|----------|
| testcase | function | usexmlfile | function |
| textime | function | usezipfile | function |
| transparencycomponents | function | utfchar | function |
| triggereffect | function | utfmathclass | function |
| triggernegative | function | utfmathcommand | function |
| truefilename | function | utfmathfiller | function |
| typebuffer | function | utfmathstretch | function |
| typefile | function | verbose | function |
| typestring | function | visual | function |
| uchexnumber | function | vspacing | function |
| uchexnumbers | function | vspacingcollapse | function |
| undefinechemical | function | vspacingdefine | function |
| unicodechar | function | vspacingsetamount | function |
| unit | function | vspacingsnap | function |
| unloadlanguage | function | way | function |
| useMPlibrary | function | weekday | function |
| useanyfile | function | weekdayname | function |
| usecldfile | function | widthofstring | function |
| usecolors | function | writestatus | function |
| usecomponent | function | x_table_cleanup | function |
| useenvironment | function | x_table_construct | function |
| usefile | function | x_table_create | function |
| usejavascriptpreamble | function | x_table_flush | function |
| usejavascriptscripts | function | x_table_init_construct | function |
| uselibrary | function | x_table_init_reflow_height | function |
| useluafile | function | x_table_init_reflow_width | function |
| useluamodule | function | x_table_next_row | function |
| usemodules | function | x_table_reflow_height | function |
| usepath | function | x_table_reflow_width | function |
| useproduct | function | x_table_set_construct | function |
| useproject | function | x_table_set_reflow_height | function |
| usesubpath | function | x_table_set_reflow_width | function |
| usesymbols | function | year | function |

function

usetexfile

containers (context)

| cleanname | function | is_valid | function |
|-----------|----------|----------|----------|
| content | function | read | function |
| define | function | usecache | boolean |
| is_usable | function | write | function |

converters (context)

| Alphabetic | function | minute | function |
|--------------------|----------|-------------------|------------|
| Character | function | month | function |
| Characters | function | nofdays | function |
| Romannumerals | function | number | function |
| abjadnodotnumerals | function | numbers | function |
| abjadnumerals | function | octnumber | function |
| alphabetic | function | octstringtonumber | function |
| character | function | ordinal | function |
| characters | function | rawcharacter | function |
| chineseallnumerals | function | romannumerals | function |
| chinesecapnumerals | function | second | function |
| chinesenumerals | function | sequences | data table |
| chr | function | textime | function |
| chrs | function | toabjad | function |
| convert | function | tochinese | function |
| define | function | toroman | function |
| hexstringtonumber | function | uchexnumber | function |
| hour | function | uchexnumbers | function |
| isleapyear | function | verbose | table |
| lchexnumber | function | D data | |
| lchexnumbers | function | F translate | |
| leapyear | function | weekday | function |
| maxchrs | function | year | function |
| | | | |

coroutine (basic lua)

| create | function | status | function |
|---------|----------|--------|----------|
| resume | function | wrap | function |
| running | function | yield | function |

ctxrunner (context)

load function
prepfiles data table

resolve function

debug (basic lua)

| debug | function | sethook | function |
|--------------|----------|--------------|----------|
| gethook | function | setlocal | function |
| getinfo | function | setmetatable | function |
| getlocal | function | setupvalue | function |
| getmetatable | function | setuservalue | function |
| getregistry | function | traceback | function |
| getupvalue | function | upvalueid | function |
| getuservalue | function | upvaluejoin | function |

dir (context)

| collectpattern | function | globpattern | function |
|----------------|----------|-------------|----------|
| current | function | ls | function |
| expandname | function | makedirs | function |
| found | function | mkdirs | function |
| glob | function | pop | function |
| globfiles | function | push | function |

directives (context)

| data | data table | name | string |
|---------|------------|----------|----------|
| default | function | register | function |
| disable | function | report | function |
| enable | function | show | function |
| list | function | value | function |

document (context)

arguments files getargument getfilename options data table table function function table T ctxfile

D environments

D modes

D modules

setargument function
setdefaultargument function
setfilename function
variables data table

T commandline
D environments

D modes
D modules

environment (context)

| argument | function | luafile | function |
|---------------------|------------|------------------------|------------|
| arguments | data table | luafilechunk | function |
| basicengines | data table | maxnofruns | number |
| currentrun | number | originalarguments | data table |
| default_texmfcnf | string | outputfilename | string |
| engineflags | data table | ownbin | string |
| filename | string | ownmain | string |
| files | table | ownname | string |
| filesynonyms | data table | ownpath | string |
| getargument | function | rawarguments | data table |
| homedir | string | reconstructcommandline | function |
| initex | boolean | relativepath | function |
| initializearguments | function | setargument | function |
| initializefilenames | function | splitarguments | function |
| inputfilebarename | string | suffix | string |
| inputfilename | string | texfile | function |
| inputfilesuffix | string | texmfos | string |
| jobfilename | string | texos | string |
| jobfilesuffix | string | texroot | string |
| kindofrun | number | truefilename | function |
| loadluafile | function | validengines | data table |
| | | | |

epdf (extra tex)

ArrayfunctionPDFRectanglefunctionDictfunctionopenfunctionObjectfunctiontypefunction

experiments (context)

| data | data table | name | string |
|---------|------------|----------|----------|
| default | function | register | function |
| disable | function | report | function |
| enable | function | show | function |
| list | function | value | function |

figures (context)

applyratio function bases data table function bitmapimage boxnumber number cachepaths data table check function checkers data table data table converters function current defaultdepth number defaultheight number defaultsearch boolean defaultwidth number function done dummy function existers data table exists function formats data table found data table function get auess function hash function identifiers data table identify function include function

includers data table initialize function loaded data table localpaths data table magics data table mergegoodies function nofprocessed number order data table data table paths data table patterns pop function preferguality boolean data table programs function push registerpattern function registerresource function registersuffix function resources data table scale function setlookups function setorder function function setpaths suffixes data table data table used

file (basic lua)

| addsuffix | function |
|------------------------------|----------|
| basename | function |
| checksum | function |
| collapsepath | function |
| сору | function |
| dirname | function |
| expandname | function |
| extname | function |
| <pre>is_qualified_path</pre> | function |
| is_readable | function |
| is_rootbased_path | function |
| is_writable | function |
| isreadable | function |
| iswritable | function |
| join | function |
| joinpath | function |
| loadchecksum | function |
| nameonly | function |
| nametotable | function |

| needs_updating | function |
|----------------|----------|
| needsupdating | function |
| pathpart | function |
| readdata | function |
| removesuffix | function |
| replacesuffix | function |
| reslash | function |
| robustname | function |
| savechecksum | function |
| savedata | function |
| size | function |
| splitbase | function |
| splitname | function |
| splitpath | function |
| strip | function |
| suffix | function |
| suffixonly | function |
| syncmtimes | function |
| | |

floats (context)

| analysemethod | function | nofstacked | function |
|------------------|----------|------------|----------|
| checkedpagefloat | function | pop | function |
| collect | function | push | function |
| consult | function | resave | function |
| flush | function | save | function |
| getvariable | function | stacked | function |

font (basic tex)

| current | function | id | function |
|---------|---------------------|----------|----------|
| define | function | max | function |
| each | function | nextid | function |
| fonts | table | read_tfm | function |
| frozen | function | read_vf | function |
| getfont | overloaded function | setfont | function |

fontloader (extra tex)

| apply_afmfile | function | info | function |
|-------------------|----------|----------|----------|
| apply_featurefile | function | open | function |
| close | function | to_table | function |
| fields | function | totable | function |
| fullinfo | function | | |

fonts (context)

| analyzers | table | F assignmathparameters |
|---------------------------|------------|---------------------------|
| T features | | B autocleanup |
| N fina | | F beforecopyingcharacters |
| N init | | D cache |
| N isol | | F calculatescale |
| N medi | | F checkedfeatures |
| D initializers | | F checkedfilename |
| D methods | | F checkvirtualids |
| F setstate | | F cleanuptable |
| T states | | F collectprocessors |
| N blwf | | D designsizes |
| N fina | | D dontembed |
| N half | | F enhanceparameters |
| N init | | N factor |
| N isol | | F finalize |
| N mark | | F getfeatureaction |
| N medi | | F hashfeatures |
| N pref | | F hashinstance |
| N pstf | | T hashmethods |
| N rest | | F normal |
| N rphf | | F virtual |
| B useunicodemar | ks | F initializefeatures |
| checkers | table | T keys |
| F getmissing | | T character |
| F missing | | S depth |
| cid | table | S height |
| F getmap | | S italic |
| F loadfile | | S width |
| collections | table | T description |
| F clonevector | | T boundingbox |
| F define | | S depth |
| T definitions | | S height |
| F prepare | | S width |
| F process | | T parameters |
| F registermain | | S ascender |
| F report | | S descender |
| F reset | | S designsize |
| T vectors constructors | table | T expansion S auto |
| | | S auto S shrink |
| F aftercopyingc | lar acters | 2 SULTUK |
| F applymanipula | to so | S step |

| Catastal | C besitelies | |
|--|--|---------------|
| S stretch | S hasitalics | |
| S extendfactor | S hasmath | |
| S factor | S mathitalics | |
| S hfactor | S mode | |
| S mathsize | S name | |
| T protrusion | S noglyphnames | |
| S auto | S nostackmath | |
| S quad | S psname | |
| S scaledpoints | S textitalics | |
| S scriptpercentage | S virtualized | |
| S scriptscriptpercentage | D loadedfonts | |
| S size | S namemode | |
| S slantfactor | F newfeatures | |
| S slantperpoint | F newhandler | |
| T spacing | N privateoffset | |
| S extra | F readanddefine | |
| S shrink | F registerfeature | |
| S stretch | B resolvevirtualtoo | |
| S width | F scale | |
| T synonyms | F scaled | |
| S em | F setfactor | |
| | | |
| S ex | F setname | |
| S ex S extra_space | N version | |
| | N version current fu | nction |
| S extra_space | N version current fun currentid fun | nction |
| S extra_space S extraspace | N version current fun currentid fun | |
| S extra_space S extraspace S slant | N version current fun currentid fun | nction |
| S extra_space S extraspace S slant S space | N version current fur currentid fur definers tal | nction |
| S extra_space S extraspace S slant S space S space_shrink | N version current fur currentid fur definers tal F addlookup | nction ble |
| <pre>S extra_space S extraspace S slant S space S space_shrink S space_stretch</pre> | N version current fur currentid fur definers tal F addlookup F analyze | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink | N version current fur currentid fur definers tal F addlookup F analyze F applypostprocessor | nction ble |
| <pre>S extra_space S extraspace S slant S space S space_shrink S space_stretch S spacestretch S spacestretch</pre> | N version current funcurrentid funcurrentid funcurrentid definers tall F addlookup F analyze F applypostprocessor F checkedmode | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height | N version current funcurrentid funcurrentid funcurrentid definers tal F addlookup F analyze F applypostprocessor F checkedmode F checkedscript | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units | N version current fur currentid fur definers tal F addlookup F analyze F applypostprocessor F checkedmode F checkedscript F current | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S vacestretch S x_height S units S vfactor | N version current funcurrentid function fu | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S vacestretch S x_height S units S vfactor S xheight | N version current fur currentid fur definers tal F addlookup F analyze F applypostprocessor F checkedmode F checkedscript F current S defaultlookup F define | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties | N version current funcurrentid function fu | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties S autoitalicamount | N version current funcurrentid function fun | nction ble |
| S extra_space S extraspace S slant S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties S autoitalicamount T cidinfo | N version current funcurrentid funcurrentid funcurrentid funcurrentid funcurrentid funcurrential function func | nction ble |
| S extra_space S extraspace S slant S space S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties S autoitalicamount T cidinfo S embedding | N version current fur currentid fur definers tal F addlookup F analyze F applypostprocessor F checkedmode F checkedscript F current S defaultlookup F define F getspecification F loadfont F makespecification T methods | nction ble |
| S extra_space S extraspace S slant S space S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties S autoitalicamount T cidinfo S embedding S encodingbytes S filename S finalized | N version current funcurrentid funcurrentid funcurrentid funcurrentid funcurrentid funcurrential function func | nction ble |
| S extra_space S extraspace S slant S space S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties S autoitalicamount T cidinfo S embedding S encodingbytes S filename | N version current funcurrentid funcurrentid funcurrentid funcurrentid funcurrent funcurrent function | nction ble |
| S extra_space S extraspace S slant S space S space S space_shrink S space_stretch S spaceshrink S spacestretch S x_height S units S vfactor S xheight T properties S autoitalicamount T cidinfo S embedding S encodingbytes S filename S finalized | N version current funcurrentid funcurrentid funcurrentid funcurrentid funcurrentid funcurrential funcurrential funcurrential function fun | nction ble |

F resetnullfont B addligatures F resolve B addtexligatures T resolvers B autoprefixed F file D cache F name D features F spec T helpdata definetypeface function D bothkerned table encodings D leftkerned T agl D ligatures D cache D rightkerned F is known D texligatures F load D known F load F setfeatures F make unicode vector B syncspace D math N version N version T otf expansions data table F addfeature formats data table D cache goodies table T chainhandlers F normal D colorschemes D data F verbose D designsizes F collectlookups D filenames F dataset F getcompositions S defaultbasealternate T list S defaultnodealternate F compositions D enhancers D features F designsizes F expansions F getalternate F featureset T glists F filenames T handlers F files F contextchain F mathematics F devanagari remove joiners F protrusions F devanagari reorder matras F solutions F devanagari_reorder_pre_base_reordering_consonants F treatments F devanagari_reorder_reph F typefaces F gpos context F load F gpos_contextchain F prepare_features F gpos_cursive F register F gpos_mark2base F registerpostprocessor F gpos_mark2ligature F report F gpos_mark2mark handlers table F gpos_pair Tafm F gpos single B addkerns F gsub_alternate

| C south contout | D. marks |
|----------------------------|---------------------------|
| F gsub_context | D marks |
| F gsub_contextchain | D parameters |
| F gsub_ligature | T processes |
| F gsub_multiple | D properties |
| F gsub_reversecontextchain | D quads |
| F gsub_single | D resources |
| Fload | T setdynamics |
| F scriptandlanguage | D spaces |
| F setcontextchain | D spacings |
| F setdynamics | D xheights |
| F setfeatures | helpers table |
| T statistics | F addprivate |
| D usedfeatures | F dimenfactor |
| T tables | F fontpatternhassize |
| D baselines | F getdigitwidth |
| D features | F getparameters |
| D languages | F getprivatenode |
| D scripts | F hasprivate |
| N version | F nametoslot |
| T pfb | F setdigitwidth |
| T tfm | F splitfontpattern |
| D features | iterators table |
| F setfeatures | F characters |
| T vf | F descriptions |
| T combinations | F glyphs |
| F combine | loggers table |
| T combiner | F add_placeholders |
| D commands | T category_to_placeholder |
| F find | s 11 |
| D helpers | S lm |
| D math | S lo |
| D predefined | S lt |
| D whatever | S lu |
| hashes table | S mc |
| D characters | S me |
| D csnames | S mn |
| D descriptions | S nd |
| D dynamics | S nl |
| D emwidths | S no |
| D exheights | S pc |
| D extensibles | S pd |
| D identifiers | S pe |
| D italics | S pf |
| D lastmathids | S pi |
| | |

| S po | | F lu | a | |
|------------------|------------|--------|----------------------|----|
| S ps | | F op | entype | |
| S sc | | F ot | f | |
| S sk | | F pf | b | |
| S sm | | D se | quence | |
| S so | | F tf | m | |
| F format | | F tt | С | |
| F onetimemessage | e | F tt | f | |
| F register | | specif | iers table | |
| F reportdefined | fonts | D co | ntextmerged | |
| F reportusedfea | | F co | ntextnumber | |
| mappings | table | D co | ntextnumbers | |
| F addtounicode | | D co | ntextsetups | |
| F fromunicode16 | | | ntexttostring | |
| F loadfile | | F de | finecontext | |
| F loadline | | F me | rgecontext | |
| F loadlumtable | | F pr | resetcontext | |
| F makenameparse | r | F re | gistercontext | |
| F reset | | | owcontext | |
| F tounicode16 | | · | litcontext | |
| F tounicode16se | • | | rnonyms | |
| names | data table | | riants | |
| nulldata | data table | symbol | | |
| protrusions | data table | | elibrary | |
| readers | table | tables | | |
| F afm | | tracer | | |
| F check_lua | | treatm | ents data tab | Le |

F check_tfm F dfont

functions (context)

dummy function

graphics (context)

backgrounds table

F calculatemultipar

F fetchmultipar

F pair

F path

F point

gzip (extra lua)

close function
lines function

open function

img (basic tex)

| boxes | function | ofindex | function |
|----------------|----------|-----------|----------|
| check | function | package | function |
| checksize | function | print | function |
| clone | function | scan | function |
| сору | function | serialize | function |
| immediatewrite | function | totable | function |
| keys | function | types | function |
| new | function | write | function |
| node | function | | |

interactions (context)

D functions

D preambles

attachments table F setpreamble F insert F storecode F register F storepreamble fields table F usepreamblenow F clone F usescripts linkedlists table F define F defineset pages table F insert F setpagetransition general table F setupcanvas F getidentity references table F setupidentity F setclosedocument help table F setclosepage F collect F setopendocument F reference F setopenpage renderings table F register javascripts table F register F addtopreamble F rendering F code F var soundclips D codes table F flushpreambles F insert

F register

interfaces (context)

| addvalidkeys | function | namespaces | table |
|-------------------------------|------------|-------------------|------------|
| cachedsetups | data table | F define | |
| cachesetup | function | F list | |
| ${\it checked specification}$ | function | registernamespace | function |
| complete | data table | setconstant | function |
| constants | data table | setelement | function |
| corenamespaces | data table | setformat | function |
| definecommand | function | setmessage | function |
| doifelsemessage | function | setmessages | function |
| elements | data table | settranslation | function |
| formats | data table | setuserinterface | function |
| getcheckedparameters | function | setvalidkeys | function |
| getmessage | function | setvariable | function |
| hashedsetups | data table | showmessage | function |
| interfacedcommand | function | syntax | data table |
| interfaces | table | tolist | function |
| invalidkey | function | translations | data table |
| is_command | function | variables | data table |

io (basic lua)

| ask | function | o_limiters | table |
|-------------------|----------|---------------|---------------------|
| bytes | function | T paranoid | |
| characters | function | open | overloaded function |
| close | function | output | function |
| exists | function | pathseparator | string |
| fileseparator | string | popen | overloaded function |
| flush | function | read | function |
| i_limiter | function | readall | function |
| i_limiters | table | readnumber | function |
| T paranoid | | readstring | function |
| input | function | savedata | function |
| limiter | function | size | function |
| lines | function | stderr | userdata |
| loadchunk | function | stdin | userdata |
| loaddata | function | stdout | userdata |
| loadlines | function | tmpfile | function |
| noflines | function | type | function |
| o_limiter | function | write | function |
| | | | |

job (context)

| comment | function | F | getcollected | |
|-------------|----------|------|----------------------|--|
| datasets | table | F | getdata | |
| D collected | | F | getfield | |
| F extend | | F | gettobesaved | |
| F getdata | | F | inlist | |
| F setdata | | F | last | |
| D tobesaved | | F | list | |
| disablesave | function | F | save | |
| files | table | F | savetagged | |
| D collected | | D | tobesaved | |
| F context | | posi | . tions table | |
| B forcerun | | F | b_col | |
| F run | | F | b_region | |
| D tobesaved | | F | С | |
| initialize | function | D | collected | |
| load | function | F | column | |
| loadother | function | F | сору | |
| objects | table | F | depth | |
| D collected | | F | e_col | |
| F get | | F | e_region | |
| F number | | F | enhance | |
| F page | | F | extra | |
| F save | | F | get | |
| F set | | F | getreserved | |
| D tobesaved | | F | hangafter | |
| pack | boolean | F | hangindent | |
| packversion | number | F | height | |
| pagestates | table | F | hsize | |
| D collected | | F | leftskip | |
| F extend | | F | lowerleft | |
| F realpage | | F | lowerright | |
| F setstate | | F | markregionbox | |
| D tobesaved | | F | n | |
| passes | table | F | onsamepage | |
| F check | | F | overlapping | |
| D collected | | F | p | |
| F count | | F | page | |
| F define | | F | paragraph | |
| F find | | F | F parindent | |
| F first | | F | position | |
| F get | | F | r | |
| | | | | |

| F region | | save | function |
|--------------|----------|--------------|----------|
| F replace | | structure | table |
| F rightskip | | D collected | |
| F set | | T components | |
| F setall | | T tobesaved | |
| F setdim | | T branches | |
| D tobesaved | | S name | |
| F upperleft | | S type | |
| F upperright | t . | variables | table |
| F width | | D checksums | |
| Fx | | D collected | |
| F xy | | F save | |
| Fy | | D tobesaved | |
| register | function | version | number |

lang (basic tex)

| clean | function |
|-------------------|----------|
| clear_hyphenation | function |
| clear_patterns | function |
| exceptions | function |
| hyphenate | function |
| hyphenation | function |
| id | function |

| new | function |
|------------------|----------|
| patterns | function |
| postexhyphenchar | function |
| posthyphenchar | function |
| preexhyphenchar | function |
| prehyphenchar | function |

languages (context)

associate function associated data table association function counters data table function current data data table define function table frequencies

F averagecharwidth

F getdata

getnumber function hyphenate function installed function labels table

> F define F split

lefthyphenmin function loadable function loadwords function table logger

F report

numbers posthyphenchar function prehyphenchar registered righthyphenmin function setexceptions setsynonym unload version words

data table function data table function function function number table

F check T data F disable F enable T enablers B enables F found F load T methods N threshold

layouts (context)

status table
 F isleftpage

F leftorrightpagection

lfs (extra lua)

| attributes chdir currentdir dir | function function function function |
|--|--|
| isdir | ${\tt overloaded} \ {\tt function}$ |
| isfile | function |
| lock | function |
| lock_dir | function |
| mkdir | function |

| mkdirs | function |
|-------------------|----------|
| readlink | function |
| rmdir | function |
| setmode | function |
| shortname | function |
| symlinkattributes | function |
| touch | function |
| unlock | function |

libraries (context)

basiclua data table
basictex data table
builtin data table
extralua data table

extratex data table
functions data table
globals data table

lmx (context)

| color | function |
|---------------|----------|
| convert | function |
| convertfile | function |
| convertstring | function |
| einject | function |
| eprint | function |
| escape | function |
| finalized | function |
| finject | function |
| fprint | function |
| get | function |
| getvariables | function |
| htmfile | function |
| html | table |
| | |

F a F td F th

include function
inherited table

- S color-background-four
- S color-background-one
- S color-background-three
- S color-background-two
- S title

initialize function
inject function
lmxfile function

| loadedfile | function |
|---------------|----------|
| new | function |
| overloaderror | function |
| popupfile | function |
| print | function |
| pv | function |
| report | function |
| reset | function |
| result | function |
| set | function |
| show | function |
| showdebuginfo | function |
| showerror | function |
| stripcss | function |
| tv | function |
| type | function |
| urlescape | function |
| variable | function |
| variables | table |

- S color-background-blue
- S color-background-body
- S color-background-green
- S color-background-main
- S color-background-purple
- S color-background-yellow
- S title-default

logs (context)

| application | function | F version | |
|--------------|----------|-------------------|----------|
| categories | function | reportline | function |
| direct | function | reportlines | function |
| disable | function | setformats | function |
| enable | function | setmessenger | function |
| exporters | table | setprogram | function |
| extendbanner | function | settarget | function |
| flush | function | settranslations | function |
| help | function | show | function |
| messenger | function | show_close | function |
| new | function | show_load | function |
| newline | function | show_open | function |
| poptarget | function | simple | function |
| pushtarget | function | simpleline | function |
| report | function | simplelines | function |
| reportbanner | function | start_page_number | function |
| reporter | function | status | function |
| reporters | table | stop_page_number | function |
| F banner | | subdirect | function |
| F export | | subreport | function |
| F help | | system | function |
| F info | | texerrormessage | function |
| F lines | | writer | function |

lpdf (context)

| action | function | id | function |
|------------------------|------------|---------------------------|----------|
| adddocumentcolorspace | function | injectxmpinfo | function |
| adddocumentextgstate | function | insertxmpinfo | function |
| adddocumentpattern | function | javascript | function |
| adddocumentshade | function | launch | function |
| addtocatalog | function | layerreference | function |
| addtoinfo | function | limited | function |
| addtonames | function | linearshade | function |
| addtopageattributes | function | link | function |
| addtopageresources | function | null | function |
| addtopagesattributes | function | number | function |
| addxmpinfo | function | pagedestination | function |
| array | function | pagereference | function |
| boolean | function | pdfcolor | function |
| checkedkey | function | pdftimestamp | function |
| checkedvalue | function | protectresources | boolean |
| circularshade | function | reference | function |
| cmykcode | function | registerannotation | function |
| collectedresources | function | registerdocumentfinalizer | function |
| color | function | registerpagefinalizer | function |
| colorspace | function | reserveannotation | function |
| colorspaceconstants | data table | reserveobject | function |
| colorspec | function | rgbcode | function |
| colorvalue | function | rotationcm | function |
| colorvalues | function | shareobject | function |
| constant | function | shareobjectreference | function |
| delayedobject | function | spotcode | function |
| dictionary | function | stream | function |
| epdf | table | string | function |
| F expand | | timestamp | function |
| F load | | toeight | function |
| finalizedocument | function | tosixteen | function |
| finalizepage | function | transparency | function |
| finishtransparencycode | function | transparencycode | function |
| flushobject | function | transparencygroups | table |
| flushstreamfileobject | function | B none | |
| flushstreamobject | function | transparencyvalue | function |
| formats | data table | unicode | function |
| graycode | function | verbose | function |

lpeg (basic lua)

| В | function | finder | function |
|--------------|----------|-----------------------|------------|
| C | function | firstofsplit | function |
| Carg | function | frontstripper | function |
| Cb | function | instringchecker | function |
| Cc | function | is_lpeg | function |
| Cf | function | keeper | function |
| Cg | function | locale | function |
| Cmt | function | match | function |
| Ср | function | oneof | function |
| Cs | function | patterns | data table |
| Ct | function | print | function |
| P | function | replacer | function |
| R | function | secondofsplit | function |
| S | function | setmaxstack | function |
| UP | function | split | function |
| UR | function | splitat | function |
| US | function | splitter | function |
| V | function | stripper | function |
| anywhere | function | times | function |
| append | function | tsplitat | function |
| balancer | function | tsplitter | function |
| checkedsplit | function | type | function |
| counter | function | utfchartabletopattern | function |
| endstripper | function | version | function |
| | | | |

ltn12 (extra lua)

F null

| BLOCKSIZE filter | number table | F simplify F table | |
|---------------------|-----------------|-----------------------|---|
| F chain | | source table | Э |
| F cycle | | F cat | |
| pump | table | F chain | |
| F all | | F empty | |
| F step | | F error | |
| sink | table | F file | |
| F chain | | F rewind | |
| F error | | F simplify | |
| F file | | F string | |

lua (basic tex)

| bytecode | table |
|----------------|------------|
| bytedata | data table |
| bytedone | table |
| collectgarbage | function |
| delay | function |
| finalize | function |
| firstbytecode | number |
| flush | function |
| flushdelayed | function |
| getbytecode | function |
| getluaname | function |
| lastbytecode | number |

| messages | data table |
|-------------------|------------|
| name | table |
| numbers | data table |
| registercode | function |
| registeredcodes | function |
| registerfinalizer | function |
| registername | function |
| setbytecode | function |
| setluaname | function |
| startupfile | string |
| version | string |
| | |

luatex (context)

cleanuptempfiles function
registerstartactions function
registerstopactions

registertempfile starttime

function number

lxml (context)

| addindex | function | getid | function |
|-------------------|----------------------|--------------------|-------------------|
| all | function | getindex | function |
| applyfunction | function | id | function |
| att | function | idsplitter | userdata |
| attribute | function | include | function |
| chainattribute | function | index | function |
| checkindex | function | info | function |
| collected | function | inlineverbatim | function |
| command | function | installsetup | function |
| concat | function | last | function |
| concatrange | function | load | function |
| content | function | loadbuffer | function |
| context | function | loaddata | function |
| convert | function | loaded | table |
| count | function | loadregistered | function |
| delete | function | main | function |
| direct | function | match | function |
| directives | table | name | function |
| F after | | namespace | function |
| F before | | nonspace | function |
| F handle | | pos | function |
| F load | | position | function |
| F setup | | raw | function |
| displayverbatim | function | rawroot | function |
| doif | function | register | function |
| doifelse | function | registerentity | function |
| doifelsetext | function | removesetup | function |
| doifnot | function | resetcdata | function |
| doifnottext | function | resetsetups | function |
| doiftext | function | resolvedentity | function |
| element | function | root | function |
| elements | function | serialize | function |
| entities | data table | setaction | function |
| filter | function | setcdata | function |
| filterlist | function | setcommandtonone | function |
| first | function | setcommandtotext | function |
| flush | function | setsetup | function |
| flushlinewise | function function | snippet sorters | function table |
| flushsetups | function function | | rante |
| flushspacewise | function function | F add | |
| get_id | TUNC CIUN | F compare | |

| F flush | | stripped | function |
|----------|----------|---------------|------------|
| F reset | | tag | function |
| F show | | text | function |
| F sort | | tofile | function |
| splitid | function | toparameters | function |
| startraw | function | toverbatim | function |
| stopraw | function | verbatim | function |
| store | function | withindex | function |
| strip | function | xmltexhandler | data table |

math (basic lua)

| abs | function |
|-------------|----------|
| acos | function |
| asin | function |
| atan | function |
| atan2 | function |
| ceil | function |
| cos | function |
| cosd | function |
| cosh | function |
| deg | function |
| div | function |
| even | function |
| exp | function |
| floor | function |
| fmod | function |
| frexp | function |
| huge | number |
| initialseed | number |
| ldexp | function |
| log | function |
| | |

| max | function |
|----------------|----------|
| min | function |
| mod | function |
| modf | function |
| odd | function |
| pi | number |
| pow | function |
| rad | function |
| random | function |
| randomseed | function |
| round | function |
| setrandomseedi | function |
| sin | function |
| sind | function |
| sinh | function |
| sqrt | function |
| tan | function |
| tand | function |
| tanh | function |

mathematics (context)

| addfallbacks | function | mapremap | data table |
|------------------------|------------|------------------------|------------|
| alphabets | data table | overloaddimensions | function |
| big | function | overloadparameters | function |
| boldmap | table | privatebase | number |
| categories | table | remapalphabets | function |
| D functions | | renderings | table |
| checkaccentbaseheight | function | D mappings | |
| checkprivateparameters | function | D numbers | |
| classes | data table | D sets | |
| codes | data table | renderset | function |
| define | function | resetitalics | function |
| dimensions | function | scaleparameters | function |
| extensiblecode | function | setalternate | function |
| extensibles | data table | setitalics | function |
| extrabase | number | syncboth | function |
| extras | table | syncname | function |
| F add | | syncstyle | function |
| F copy | | toname | function |
| fallbacks | table | tostyle | function |
| F apply | | tweakaftercopyingfont | function |
| F install | | tweakbeforecopyingfont | function |
| fallbackstyleattr | function | tweaks | table |
| families | data table | F fixbadprime | |
| gaps | table | utfmathclass | function |
| getboth | function | utfmathcommand | function |
| getstyle | function | utfmathfiller | function |
| initializeparameters | function | utfmathstretch | function |
| makefont | function | | |

mbox (context)

| parse | function | parse_message | function |
|---------------|----------|---------------|----------|
| parse_from | function | split_headers | function |
| parse_header | function | split_mbox | function |
| parse_headers | function | split_message | function |

md5 (extra lua)

| function | exor | function |
|----------|----------|---------------------------|
| function | hex | function |
| function | sum | function |
| function | sumhexa | function |
| | function | function hex function sum |

metapost (context)

| analyzeplugins | function | F makempy | |
|-------------------------------|------------------|---------------------------------------|--------------------|
| checkformat | function | B needed | |
| checktexts | function | lastlog | string |
| collapse | boolean | load | string function |
| colorinitializer | function | makempy | table |
| convert | function | N nofconverted | cable |
| defaultformat | string | | |
| defaultinstance | J | F processgraphics metafun | table |
| defaultmethod | string string | F interpolate | table |
| directrun | function | | |
| edefsxsy | function | F topath method | number |
| • | function | multipass | boolean |
| escaped exectime | table | · · · · · · · · · · · · · · · · · · · | number |
| extensiondata | data table | n optimize | boolean |
| filterclippath | function | • | function |
| finder | function | parse pdfliterals | function |
| flush | function | pluginactions | function |
| flushers | table | process | function |
| | table | • | function |
| T pdf F comment | | processplugins reducetogray | boolean |
| F comment F flushfigure | | reporterror | function |
| F startfigure | | reset | function |
| F startfigure F stopfigure | | resetlastlog | function |
| F textfigure | | resetplugins | function |
| flushliteral | function | resettextexts | function |
| flushnormalpath | function | setextensions | function |
| flushreset | function | setoutercolor | function |
| format | function | settext | function |
| formatnumber | function | showlog | boolean |
| getclippath | function | tex | table |
| getextensions | function | F get | cabte |
| gettext | function | F reset | |
| graphic | function | F set | |
| graphic_base_pass | function | texerrors | boolean |
| graphic_extra_pass | function | textextsdata | function |
| instance | function | theclippath | function |
| intermediate | table | totable | function |
| T actions | | unload | function |
| 1 0001000 | | uncoau | Tunction |

mime (extra lua)

| b64 | function | qp | function |
|-----------|-------------|---------|-------------|
| decode | function | qpwrp | function |
| decodet | table | stuff | function |
| F base64 | ı | unb64 | function |
| F quoted | d-printable | unqp | function |
| dot | function | wrap | function |
| encode | function | wrapt | table |
| encodet | table | F base6 | 4 |
| F base64 | 1 | F defau | lt |
| F quoted | d-printable | F quote | d-printable |
| eol | function | F text | |
| normalize | e function | wrp | function |

mplib (extra tex)

fields function
finders table

F file

new function

pen_info function
preprocessed function
version function

noads (context)

| handlers | table |
|------------|-------|
| F check | |
| F collapse | |
| F families | |
| F italics | |
| F relocate | |
| F render | |
| F resize | |
| F tags | |

F unscript

F variants

process function

processors table

T collapse

F mlist_to_hlist

T relocate

T render

T resize

T unscript

node (basic tex)

| сору | function | ligat |
|-----------------|----------|-------|
| copy_list | function | mlist |
| count | function | new |
| current_attr | function | next |
| dimensions | function | prev |
| do_ligature_n | function | prote |
| end_of_math | function | protr |
| family_font | function | remov |
| fields | function | set_a |
| first_character | function | slide |
| first_glyph | function | subty |
| flush_list | function | tail |
| free | function | trave |
| has_attribute | function | trave |
| has_field | function | type |
| hpack | function | types |
| id | function | unpro |
| insert_after | function | unset |
| insert_before | function | usedl |
| is_node | function | vpack |
| kerning | function | whats |
| last_node | function | write |
| length | function | |
| | | |

| ligaturing | function |
|----------------------|----------|
| mlist_to_hlist | function |
| new | function |
| next | function |
| prev | function |
| protect_glyphs | function |
| protrusion_skippable | function |
| remove | function |
| set_attribute | function |
| slide | function |
| subtype | function |
| tail | function |
| traverse | function |
| traverse_id | function |
| type | function |
| types | function |
| unprotect_glyphs | function |
| unset_attribute | function |
| usedlist | function |
| vpack | function |
| whatsits | function |
| write | function |
| | |

nodes (context)

| after | function | E cleanunnage | |
|------------------------|------------|--|------------|
| aligned | function | F cleanuppage F export | |
| astable | function | F finalize | |
| before | function | F migrate | |
| builders | table | , and the second | |
| F buildpage filter | table | F protectglyphs F stripping | |
| F vpack_filter | | F unprotectglyphs | |
| codes | data table | has attribute | function |
| concat | function | idstostring | function |
| count | function | ignorablefields | data table |
| delete | function | injections | table |
| destinations | table | F handler | cabic |
| N attribute | | F installnewkern | |
| T done | | F setcursive | |
| F handler | | F setkern | |
| T stack | | F setmark | |
| dimensionfields | data table | F setpair | |
| dir is pop | data table | installattributehandler | function |
| dir negation | data table | is display math | function |
| disccodes | data table | is_mirrored | data table |
| discretionarycodes | data table | is_rotated | data table |
| endofmath | function | kerncodes | data table |
| fasthpack | function | leftmarginwidth | function |
| fields | function | lines | table |
| fillcodes | data table | T boxed | |
| firstcharacter | function | F register | |
| firstcharinbox | function | F setup | |
| firstglyph | function | F stage_one | |
| getattribute | function | F stage_two | |
| gluecodes | data table | F stage_zero | |
| glyphcodes | data table | D data | |
| glyphdir_is_equal | data table | F finalize | |
| glyphdir_is_opposite | data table | F number | |
| glyphdir_is_orthogonal | data table | N scratchbox | |
| handlers | table | link | function |
| F accessibility | | list | function |
| F alignbackgrounds | | listablefields | data table |
| F backgrounds | | listcodes | data table |
| F characters | | listtoutf | function |
| F checkforleaks | | load | function |
| F checkglyphs | | locate | function |

| margincodes | data table | F penalty | |
|--|------------|---|---|
| markers | table | F register | |
| F get | | F rightmarginkern | |
| mathcodes | data table | F rightskip | |
| noadcodes | data table | F rule | |
| nodecodes | data table | F shrink | |
| packlist | function | F special | |
| pardir_is_equal | data table | F stretch | |
| pardir_is_opposite | data table | F temp | |
| pardir_is_parallel | data table | F textdir | |
| partextdir_is_equal | data table | F usage | |
| penaltycodes | data table | T userids | |
| plugindata | table | N margins.inline | |
| S name | | N splitters.one | |
| T namespace | | N splitters.two | |
| N attribute | | F userlist | |
| T droppers | | F usernumber | |
| F freeze | | F userstring | |
| F set | | F usertokens | |
| F handler | | F vlist | |
| F set | | F zeroglue | |
| F processor | | print | function |
| | | • | |
| pool | table | processors | table |
| <pre>pool F baselineskip</pre> | table | • | table |
| • | table | processors | table |
| F baselineskip | table | processors B enabled | table |
| F baselineskip | table | <pre>processors B enabled F hpack_filter</pre> | table |
| F baselineskip F cleanup F disc | table | processors B enabled F hpack_filter F post_linebreak_filter | |
| F baselineskip F cleanup F disc F fontkern | table | <pre>processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords</pre> | function |
| F baselineskip F cleanup F disc F fontkern F glue | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference | function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec | table | <pre>processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords</pre> | function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference | function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references | function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references N attribute | function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references N attribute T done | function function table |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference reference T done F handler T stack remove | function function table function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F noad | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references N attribute T done F handler T stack remove repackhlist | function function table function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F noad F pdfannotation | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references N attribute T done F handler T stack remove repackhlist replace | function function table function function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F lineskip F noad F pdfannotation F pdfdestination | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references N attribute T done F handler T stack remove repackhlist replace report | function function table function function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F lineskip F noad F pdfannotation F pdfdestination F pdfdirect | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference references N attribute T done F handler T stack remove repackhlist replace report rightmarginwidth | function function table function function function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F lineskip F noad F pdfannotation F pdfdestination F pdfdirect F pdfliteral | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference reference T done F handler T stack remove repackhlist replace report rightmarginwidth rules | function function table function function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F lineskip F noad F pdfannotation F pdfdestination F pdfdirect F pdfliteral F pdfrestore | table | Processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference reference T done F handler T stack remove repackhlist replace report rightmarginwidth rules D data | function function table function function function function |
| F baselineskip F cleanup F disc F fontkern F glue F gluespec F glyph F hlist F kern F latelua F leftmarginkern F leftskip F lineskip F noad F pdfannotation F pdfdestination F pdfdirect F pdfliteral | table | processors B enabled F hpack_filter F post_linebreak_filter F pre_linebreak_filter F tracer processwords reference reference T done F handler T stack remove repackhlist replace report rightmarginwidth rules | function function table function function function function |

| F handler | | textdir_is_equal | data table |
|--------------------|------------|---------------------|------------|
| save | function | textdir_is_is | data table |
| serialize | function | textdir_is_opposite | data table |
| serializebox | function | textdir_is_parallel | data table |
| setattribute | function | tonodes | function |
| setattributes | function | tosequence | function |
| setunsetattributes | function | totable | function |
| shifts | table | toutf | function |
| D data | | tracers | table |
| F define | | T characters | |
| F enable | | F collect | |
| F handler | | F equal | |
| show | function | F indices | |
| showboxes | function | F start | |
| showcodes | function | F string | |
| showlist | function | F unicodes | |
| showsimplelist | function | T colors | |
| skipcodes | data table | F reset | |
| snapshots | table | F set | |
| F getparameters | | F setlist | |
| F getsamples | | F fontchar | |
| F resetsamples | | T frequencies | |
| F takesample | | F register | |
| somepenalty | function | F start | |
| somespace | function | T steppers | |
| stripping | table | F check | |
| T glyphs | | F codes | |
| F set | | F features | |
| striprange | function | F font | |
| tasks | table | F glyphs | |
| F actions | | F message | |
| F appendaction | | F messages | |
| F disableaction | | F nofsteps | |
| F disablegroup | | F register | |
| F enableaction | | F reset | |
| F enablegroup | | F start | |
| F freeze | | F stop | |
| F freezegroup | | F stop | |
| F new | | T transparencies | |
| F prependaction | | F reset | |
| F removeaction | | F set | |
| F restart | | F setlist | |
| F showactions | | unsetattribute | function |
| F table | | unsetattributes | function |

visualizebox visualizers

function table

F setlayer
F setvisual

F box F handler tabl

F markfonts F setfont

previous 83 next

number (context)

| | function | tocentimeters | function |
|--------------|------------|----------------|----------|
| basepoints | function | tociceros | function |
| bit | function | todidots | function |
| bits | function | todimen | function |
| clearbit | function | toevenhex | function |
| dimenfactors | data table | toinches | function |
| hasbit | function | tomillimeters | function |
| maxdimen | number | tonewciceros | function |
| nopts | function | tonewdidots | function |
| percent | function | tonumberf | function |
| points | function | tonumberg | function |
| pts | function | topicas | function |
| setbit | function | topoints | function |
| signed | function | toscaled | function |
| splitdimen | function | toscaledpoints | function |
| tobasepoints | function | toset | function |
| tobitstring | function | valid | function |
| | | | |

os (basic lua)

| getenv | function | remove | function |
|--------------|---------------------|-----------|---------------------|
| setenv | function | rename | function |
| binsuffix | string | resolvers | table |
| binsuffixes | table | resultof | function |
| clock | function | runtime | function |
| converttime | function | selfdir | string |
| date | function | setenv | overloaded function |
| difftime | function | setlocale | overloaded function |
| env | data table | sleep | function |
| exec | overloaded function | spawn | overloaded function |
| execute | overloaded function | time | function |
| exit | function | times | function |
| fulltime | function | timezone | function |
| getenv | overloaded function | tmpdir | function |
| gettimeofday | function | tmpname | function |
| launch | function | today | function |
| libsuffix | string | type | string |
| localtime | function | uname | function |
| name | string | uuid | function |
| now | function | where | function |
| platform | string | which | function |
| | | | |

package (basic lua)

| config | string |
|---------------|----------|
| cpath | string |
| extralibpath | function |
| extralibpaths | function |
| extraluapath | function |
| extraluapaths | function |
| helpers | table |
| libpaths | function |
| loaded | table |
| | |

| loaders | table |
|------------|----------|
| loadlib | function |
| luapaths | function |
| path | string |
| preload | table |
| searchers | table |
| searchpath | function |
| seeall | function |

pagebuilders (context)

F cleanup

pdf (basic tex)

| immediateobj | function |
|----------------|----------|
| mapfile | function |
| mapline | function |
| maxobjnum | function |
| obj | function |
| objtype | function |
| pageattributes | string |
| nageref | function |

| pageresources | string |
|-----------------|----------|
| pagesattributes | string |
| pdfmapfile | function |
| pdfmapline | function |
| print | function |
| refobj | function |
| registerannot | function |
| reserveobj | function |

pdfscanner (context)

scan function

physics (context)

units table

D tables

profiler (extra lua)

pause function
resume function
stop function

regimes (context)

| cleanup | function | process | function |
|---------|----------|-----------|----------|
| disable | function | push | function |
| enable | function | toregime | function |
| рор | function | translate | function |

resolvers (context)

finders

| 33 6' | | 61 1613 |
|---|--|---|
| allprefixes | function | findfile |
| appendhash | function | findfiles |
| automount | function | findgivenfile |
| automounted | table | findgivenfiles |
| booleanvariable | function | findpath |
| cacheversion | string | findtexfile |
| checkedvariable | function | findwildcardfile |
| cleanpath | function | findwildcardfiles |
| cleanpathlist | function | formatofsuffix |
| concatinators | data table | formatofvariable |
| configbanner | string | formats |
| criticalvars | data table | generators |
| dangerous | data table | getenv |
| datastate | function | getownpath |
| defaultsuffixes | table | getreadfilename |
| dowithfilesandreport | function | hashers |
| dowithfilesintree | function | homedir |
| dowithpath | function | inputstack |
| dowithvariable | function | installinputfilehandler |
| env | function | installinputlinehandler |
| | | • |
| executers | table | instance |
| executers F check | table | |
| | table | instance |
| F check | table | instance D data |
| F check F exec | table | <pre>instance D data B diskcache</pre> |
| F check F exec F execute | table | <pre>instance D data B diskcache D environment</pre> |
| F check F exec F execute F finalize | table | <pre>instance D data B diskcache D environment D expansions</pre> |
| F check F exec F execute F finalize F popen | table | <pre>instance D data B diskcache D environment D expansions D fakepaths</pre> |
| F check F exec F execute F finalize F popen F register | table function | <pre>instance D data B diskcache D environment D expansions D fakepaths D files</pre> |
| F check F exec F execute F finalize F popen F register F spawn | | <pre>instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes</pre> |
| F check F exec F execute F finalize F popen F register F spawn expandbraces | function | <pre>instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found</pre> |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist | function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist | function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlist | function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable expandpath | function function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlistfromvariable expandpath expandpath | function function function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlist expandedpathlistfromvariable expandpath expandpathfromvariable expansion | function function function function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror D order |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlist expandedpathlistfromvariable expandpath expandpath expandpathfromvariable expansion extendtexmfvariable | function function function function function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror D order B remember |
| F check F exec F execute F finalize F popen F register F spawn expandbraces expandedpathfromlist expandedpathlist expandedpathlist expandpath expandpath expandpath expandpath expandpathfromvariable expansion extendtexmfvariable find_file | function function function function function function function function | Instance D data B diskcache D environment D expansions D fakepaths D files B force_suffixes D found D foundintrees D hashed D hashes D lists B loaderror D order B remember B renewcache |

function data table data table function function function data table string table function function table

D specification

data table

| D variables | | registerintrees | function |
|----------------------|------------|------------------------|------------|
| jobs | table | registermethod | function |
| F currentcomponent | | registerzipfile | function |
| F currentenvironment | | relations | data table |
| F currentproduct | | renew | function |
| F currentproject | | repath | function |
| F justacomponent | | reset | function |
| D processors | | resetextrapath | function |
| F productcomponent | | resetresolve | function |
| F usefile | | resolve | function |
| joinpath | function | savers | data table |
| load | function | scandata | function |
| loadbinfile | function | scanfiles | function |
| loaders | data table | schemes | table |
| loadlualib | function | T cleaners | |
| loadtexfile | function | F md5 | |
| loadtime | function | F none | |
| locateformat | function | F strip | |
| locators | data table | F cleanname | |
| luacnfname | string | F fetchstring | |
| luacnfspec | string | F fetchtable | |
| luacnfstate | string | F install | |
| macros | table | setenv | function |
| F convertfile | | setinstance | function |
| F decodecomment | | showpath | function |
| F enablecomment | | simplescanfiles | function |
| F encodecomment | | splitconfigurationpath | function |
| F preprocessed | | splitexpansions | function |
| F processmk | | splitmethod | function |
| F processmkvi | | splitpath | function |
| F version | | suffixes | data table |
| maxreadlevel | number | suffixmap | data table |
| methodhandler | function | suffixofformat | function |
| newinstance | function | texdatablob | function |
| openbinfile | function | toppath | function |
| openers | data table | unexpandedpath | function |
| openfile | function | unexpandedpathlist | function |
| opentexfile | function | unresolve | function |
| ownpath | string | updaterelations | function |
| prefixes | data table | updatescript | function |
| prependhash | function | usezipfile | function |
| registerextrapath | function | validatedpath | function |
| registerfile | function | variable | function |
| registerfilehash | function | variableofformat | function |

variableofformatorsuffix function wildcardpattern

function

scripts (context)

autofontfeature table

F disable

F enable

F handler

categorytonumber data table
colors data table
defaults table

N inter_char_half_shrink_factor

N inter_char_half_stretch_factor

N $inter_char_hangul_penalty$

N inter_char_quarter_shrink_factor

N inter_char_quarter_stretch_factor

N inter_char_shrink_factor

N inter_char_stretch_factor

N inter_word_stretch_factor

handlers data table

hash table
injectors data table
installdataset function
numbertocategory
numbertodataset data table
numbertohandler data table
reset function

set splitters function data table

set (context)

contains function
create function
tolist function

tonumber function
totable function

socket (extra lua)

S comments

BLOCKSIZE number S connection DEBUG boolean S content-description SETSIZE number S content-disposition bind function S content-encoding choose function S content-id connect function S content-language connect4 function S content-length function connect6 S content-location dns table S content-md5 F getaddrinfo S content-range F gethostname S content-transfer-encoding F getnameinfo S content-type F tohostname S date F toip S diagnostic-code ftp table S dsn-gateway S PASSWORD S etag N PORT S expect N TIMEOUT S expires S USER S final-log-id F command S final-recipient F get S from S host F open S if-match F put gettime function S if-modified-since headers table S if-none-match S if-range T canonic S accept S if-unmodified-since S accept-charset S in-reply-to S accept-encoding S keywords S accept-language S last-attempt-date S last-modified S accept-ranges S action S location S age S max-forwards S allow S message-id S alternate-recipient S mime-version S original-envelope-id S arrival-date S authorization S original-recipient S bcc S pragma S cache-control S proxy-authenticate S cc S proxy-authorization

S range

| S received | protect | function |
|-------------------------|------------------------|-----------|
| S received-from-mta | select | function |
| S references | sink | function |
| S referer | sinkt | table |
| S remote-mta | F close- | when-done |
| S reply-to | F defaul | t |
| S reporting-mta | F http-cl | hunked |
| S resent-bcc | F keep-o | pen |
| S resent-cc | skip | function |
| S resent-date | sleep | function |
| S resent-from | smtp | table |
| S resent-message-id | S DOMAIN | |
| S resent-reply-to | N PORT | |
| S resent-sender | S SERVER | |
| S resent-to | N TIMEOU | Т |
| S retry-after | S ZONE | |
| S return-path | F message | е |
| S sender | F open | |
| S server | F send | |
| S smtp-remote-recipient | source | function |
| S status | sourcet | table |
| S subject | F by-leng | gth |
| S te | F defaul | t |
| S to | F http-cl | hunked |
| S trailer | F until- | closed |
| S transfer-encoding | tcp | function |
| S upgrade | tcp6 | function |
| S user-agent | tp | table |
| S vary | N TIMEOU | Т |
| S via | F connect | |
| S warning | try | function |
| S will-retry-until | udp | function |
| S www-authenticate | udp6 | function |
| S x-mailer | url | table |
| http table | F absolu | te |
| N PORT | F build | |
| N TIMEOUT | F build_µ | path |
| S USERAGENT | F escape | |
| F open | F parse | |
| F request | | |
| newtry function | F parse_p F unescap | |

sorters (context)

comparers table

F basic

constants table

S defaultdigits

S defaultlanguage

S defaultmethod

N digitsmaximum

 ${\sf N}$ digitsoffset

 ${\sf N}$ ignoredoffset

N replacementoffset

definitions data table firstofsplit function setlanguage function

sort function splitters table

F utf

strip function
tracers data table
update function

statistics (context)

| checkfmtstatus | function | register | function |
|----------------|----------|---------------|----------|
| elapsed | function | resettiming | function |
| elapsedindeed | function | runtime | function |
| elapsedseconds | function | savefmtstatus | function |
| elapsedtime | function | show | function |
| enable | boolean | starttiming | function |
| formatruntime | function | stoptiming | function |
| hastiming | function | threshold | number |
| memused | function | timed | function |

status (basic tex)

list function

storage (context)

allocate function
data table
mark function
marked function
max number
min number
nofmodules number

noftables number
register function
shared data table
strip boolean
tofmodules number
toftables number

streams (context)

| collect | function | push | function |
|------------|----------|-------------|----------|
| disable | function | start | function |
| enable | function | stop | function |
| flush | function | synchronize | function |
| initialize | function | | |

string (basic lua)

| autodouble | function | F %s %s %s %t |
|------------------|-------------------------|---|
| autosingle | function | F %s %s %s %s |
| booleanstring | function | F %s Tc %s w %s Tr |
| byte | function | F %s mul |
| bytepairs | function | F %s%s |
| bytes | function | F %s->%s->%s |
| char | function | F %s->%s->%s->%s->%s->%s |
| characterpairs | function | F %s:%s |
| characters | function | F %s:%s:%s |
| checkedsplit | function | F (%p,%p) |
| collapsespaces | function | F /%s %s |
| count | function | F /%s << %t >> |
| dump | function | F /%s [%t] |
| escapedpattern | function | F /%s cs /%s CS %s SCN %s scn |
| explode | function | F /Tr%s gs |
| find | function | F << %t >> |
| format | function | F << /Type /Annot %s /Rect [%0.3f %0.3f %0.3f %0.3f] >> |
| formatter | function | F MpSh%s |
| formatters | function | F Tr%s |
| F %t (%t) | | F U+%04X:%s |
| F %tcycle | | F [%t] |
| F %-15s : | | F [%s][%s] |
| F %-15s : %s | | <pre>F \convertnumber{%s}{%s}</pre> |
| F %-15s > | | F _bpnf_(%s,%s,%s,'%s') |
| F %-15s > | | T _extensions_ |
| F %-15s > %s | | S chruni |
| F %-15s > %s | | S font:features |
| F %-15s > %s > | | S font:name |
| F %-15s > %s > | | S tex |
| F %-15s > %s > % | s | S unichr |
| F %-15s > %s > % | s | S xml |
| F %.3f %.3f %.3f | %.3f k %.3f %.3f %.3f K | F _plibb_col(%q) |
| F %.3f %.3f %.3f | rg %.3f %.3f %.3f RG | <pre>F _plibb_region(%q)</pre> |
| F %.3f g %.3f G | | <pre>F _plibe_col()</pre> |
| F %U | | <pre>F _plibe_region(%s)</pre> |
| F %U (%s) | | <pre>F _plibenhance(%q)</pre> |
| F %a loaded | | S _preamble_ |
| F %p | | S _type_ |
| F %s | | F b:%s |
| F %s %s | | F buffer.%s |
| F %s %s %s | | F c:%s:%s:%s |
| | | |

```
F chem %s%s(%s,%s,"\chemicaltext{%s}");
                                                                                                               F w:%s
F chem %s%s(%s,%s,%s,%s,%s);
                                                                                                        amatch
                                                                                                                                               function
                                                                                                                                               function
F chem %s(%s,%s,"");
                                                                                                        asub
                                                                                                        is boolean
                                                                                                                                               function
F chem %s(%s,%s,%s);
                                                                                                        is empty
                                                                                                                                               function
F chem c%s(%s,%s,"");
                                                                                                        itself
                                                                                                                                               function
F chem set(%s);
function
F chem symbol("\chemicalsymbol[equilibrium]{%s}{%s}"); limit
                                                                                                                                               function
                                                                                                        longtostring
                                                                                                                                               function
F chem symbol("\chemicalsymbol[gives]{%s}{%s}");
F chem symbol("\chemicalsymbol[mesomeric]{%s}{%s}");
                                                                                                        lower
                                                                                                                                               function
                                                                                                                                               function
                                                                                                        match
F chem symbol("\chemicaltext{%s}");
                                                                                                                                               table
F chem trace boundingbox := %l;
                                                                                                        nspaces
                                                                                                                                               function
F dup %s mul exch dup %s mul exch %s mul
                                                                                                        quote
                                                                                                                                               function
F dup %s mul exch dup %s mul exch dup %s mul exch %s mul quoted
                                                                                                                                               function
                                                                                                        rep
Fe:%s
                                                                                                                                               function
F flushing realpage %s, userpage %s
                                                                                                        reverse
                                                                                                                                               function
F jobname %a, input %a, result %a
                                                                                                        split
                                                                                                        splitlines
                                                                                                                                               function
F lang-frq-%s.lua
                                                                                                        splitup
                                                                                                                                               function
F language %a is active
F mfun tt w[%i] := %f; mfun tt h[%i] := %f; mfun tt d[%ttrip%f;
                                                                                                                                               function
F multilocs[%s] := %s : multikind[%s] := "%s" : multipar snub) := (%--t--cycle function (%p.%p) :
                                                                                                        tformat
                                                                                                                                               function
F multireas[%s] := (%--t--cvcle) shifted - %s :
                                                                                                                                               function
                                                                                                        toboolean
F p:%s
                                                                                                        tocontext
                                                                                                                                               function
F p:%s:%s:%s:%s
F path multiregs[], multipars[], multibox ; string multikbodimenumeric multfluns[tionofmultipars ; nofmultipars :=
F path posboxes[], posregions[]; numeric pospages[]; numapattemposboxes; កាំក្រោលទាំងសំណាះ := %s; %t;
                                                                                                                                               function
F pdf: q 1 0 %f 1 0 0 cm
                                                                                                        totable
F pospages[%s] := %s; posboxes[%s] := (%p,%p) - -(%p,%p) - + (%p, %p) - - (%p,%p) - - (xp, xp) - - - (xp, xp) - - (xp, xp
F processed mkvi file %a, delta %s
                                                                                                        tracedchar
                                                                                                                                               function
                                                                                                        tracedchars
                                                                                                                                               table
F q %f %f %f %f %f cm
                                                                                                                                               function
F r:%s:%s:%s
                                                                                                        unquote
                                                                                                                                               function
F region:%s
                                                                                                        unquoted
                                                                                                        upper
                                                                                                                                               function
F 5:%5
                                                                                                        utfcharacters
                                                                                                                                               function
F setbounds currentpicture to multibox;
                                                                                                        utfvalues
                                                                                                                                               function
F unknown reference %a
                                                                                                        valid
                                                                                                                                               function
F using file %a
```

F visualizers.%s

structures (context)

| atlocation | function | F setlevel | |
|----------------|----------|----------------------|----------|
| blocks | table | F setoffset | |
| D collected | | F setown | |
| F define | | F setstate | |
| F print | | F setvalue | |
| F save | | T specials | |
| F select | | F userpage | |
| F setstate | | F subs | |
| D states | | D tobesaved | |
| D tobesaved | | F value | |
| bookmarks | table | currentsectionnumber | function |
| F finalize | | descriptions | table |
| F flatten | | documents | table |
| S method | | D data | |
| F overload | | F initialize | |
| F place | | F preset | |
| F register | | F reset | |
| F setup | | floats | table |
| counters | table | formulas | table |
| F add | | F current | |
| F analyze | | F simplify | |
| F check | | F store | |
| D collected | | helpers | table |
| F compact | | F analyze | |
| F converted | | F formulanumber | |
| F currentvalue | | F merged | |
| D data | | F page | |
| F define | | F prefix | |
| F first | | F prefixlastpage | |
| F get | | F prefixpage | |
| F last | | F simplify | |
| F next | | F title | |
| F prev | | F touserdata | |
| F previous | | inserts | table |
| F raw | | D data | |
| F record | | F define | |
| F reset | | F getdata | |
| F restart | | F getlocation | |
| F restore | | F getname | |
| F save | | F getnumber | |
| F set | | F setlocation | |

| F setup | | F uservalue | |
|-------------------|-------|--------------------------|-------|
| D stored | | marks | table |
| itemgroups | table | D data | |
| F maxwidth | | F define | |
| F nofitems | | F exists | |
| F register | | F fetch | |
| lists | table | F fetchallmarks | |
| F addto | | F fetched | |
| F analyze | | F fetchonemark | |
| B autoreorder | | F fetchtwomarks | |
| D cached | | F get | |
| D collected | | F number | |
| F discard | | F relate | |
| F enhance | | F reset | |
| T enhancers | | F set | |
| F filter | | F show | |
| F filtercollected | | F synchronize | |
| F formulanumber | | F title | |
| F groupindex | | T tracers | |
| F hasnumberdata | | F showtable | |
| F haspagedata | | notes | table |
| F hastitledata | | F checkpagechange | |
| D internals | | F define | |
| F iscached | | F doifonsamepageasprevio | us |
| F label | | F get | |
| F location | | F getdeltapage | |
| F number | | F getn | |
| D ordered | | F getnumberpage | |
| F page | | F getstate | |
| F popnesting | | F getsymbolpage | |
| F prefix | | F hascontent | |
| F prefixednumber | | F internal | |
| F prefixedpage | | F internalid | |
| F process | | F listindex | |
| D pushed | | F ordered | |
| F pushnesting | | F postpone | |
| F realpage | | F resetpostponed | |
| F reordered | | F restore | |
| T result | | F save | |
| F sectionnumber | | F setstate | |
| F size | | F setsymbolpage | |
| F title | | D states | |
| D tobesaved | | F store | |
| F userdata | | pages | table |

F analyze D internals D collected F load F is_odd F loadpresets F number F mark F save D pages D tobesaved U prefixsplitter references table D productdata F analvze T programs T data F checkedfile F checkedfileorurl F define F checkedprogram F aet F checkedrealpage F realpageofpage F checkedurl U referencesplitter D collected D referred U componentsplitter F referredpage F currentmetadata F registerfinalizer F currentorder F registerinitializer D currentset F registerpage F define F reportproblems D defined F reset D derived T resolvers F enableinteraction F reference F enhance F section D executers D runners F expandcurrent F set F export F setandgetattribute T files F setcomponent T data F setinnermethod F define F setinternalreference F setnextinternal F get F filter F setnextorder F filterdefault D specials D filters F splitcomponent F splitprefix F from F splitreference F get F getcurrentmetadata T testrunners Finner F getcurrentprefixspec F getinnermethod F special F getinternalreference F special operation D handlers F special operation with arguments F identify T testspecials F import F deltapage Εí F inject F injectcurrentset F internal

| F page | | F getlevel | |
|-------------------|-------|---------------------|-------|
| F realpage | | F getnumber | |
| F section | | F internalreference | |
| F userpage | | D levelmap | |
| D tobereferred | | D levels | |
| D tobesaved | | F load | |
| T urls | | F matchingtilldepth | |
| T data | | F numberatdepth | |
| F define | | F numbers | |
| F get | | F popblock | |
| F valid | | F prefixedconverted | |
| F whatfrom | | F pushblock | |
| registers | table | F register | |
| F analyze | | D registered | |
| F analyzed | | F reportstructure | |
| D collected | | F save | |
| F compare | | F set | |
| F define | | F setblock | |
| F enhance | | F setchecker | |
| F extend | | F setlevel | |
| F filter | | F setnumber | |
| F filtercollected | | F somelevel | |
| F finalize | | F structuredata | |
| F flush | | F title | |
| F prepare | | D tobesaved | |
| F process | | F typesetnumber | |
| F sort | | F userdata | |
| F store | | B verbose | |
| D tobesaved | | sets | table |
| F unique | | F define | |
| F userdata | | F get | |
| sections | table | F getall | |
| F autodepth | | D setlist | |
| F cct | | specials | table |
| D collected | | D collected | |
| F current | | F retrieve | |
| F currentblock | | F store | |
| F currentid | | D tobesaved | |
| F currentlevel | | synonyms | table |
| F depthnumber | | F analyzed | |
| F finddata | | D collected | |
| F findnumber | | F compare | |
| F fullnumber | | F define | |
| F getcurrentlevel | | F filter | |

F finalize F flush F meaning F prepare F process F register F registerused F sort F synonym D tobesaved table

F registermetadata F restart F setattributehash F setcombination F setdescription F setdescriptionsymbol F setfigure F sethighlight F setitemgroup F setproperty F setsorting F setsynonym F settablecell F settabulatecell F start

F registerdata

tags

T data F detailedtag F getid F handler D labels F last F lastinchain T metadata D properties

table (basic lua)

| allkeys | function | print | function |
|-----------------|----------|----------------------|----------|
| append | function | remove | function |
| are_equal | function | reverse | function |
| autokey | function | reversed | function |
| compact | function | save | function |
| concat | function | sequenced | function |
| contains | function | serialize | function |
| сору | function | setmetatablecall | function |
| count | function | setmetatableindex | function |
| derive | function | setmetatablekey | function |
| deserialize | function | setmetatablenewindex | function |
| drop | function | sort | function |
| fastcopy | function | sorted | function |
| fastserialize | function | sortedhash | function |
| flattened | function | sortedhashkeys | function |
| fromhash | function | sortedkeys | function |
| getmetatablekey | function | sortedpairs | function |
| has_one_entry | function | strip | function |
| identical | function | sub | function |
| imerge | function | swapped | function |
| imerged | function | tocontext | function |
| insert | function | tocsv | function |
| is_empty | function | tofile | function |
| keys | function | tohandle | function |
| load | function | tohash | function |
| loweredkeys | function | toxml | function |
| merge | function | twowaymapper | function |
| merged | function | unique | function |
| mirrored | function | unnest | function |
| pack | function | unpack | function |
| prepend | function | | |
| | | | |

tex (basic tex)

| attribute | table | istoken | function |
|------------------|------------|---------------|------------|
| badness | function | lccode | table |
| box | table | linebreak | function |
| catcode | table | lists | table |
| conditionals | data table | luacatcodes | number |
| constants | data table | mathcode | table |
| count | table | modes | data table |
| ctxcatcodes | number | nest | table |
| definefont | function | nilcatcodes | number |
| delcode | table | notcatcodes | number |
| dimen | table | number | function |
| directives | data table | pdffontname | function |
| enableprimitives | function | pdffontobjnum | function |
| error | function | pdffontsize | function |
| extraprimitives | function | pdfpageref | function |
| finish | function | pdfxformname | function |
| fontidentifier | function | primitives | function |
| fontname | function | print | function |
| fprint | function | printlist | function |
| get | function | prtcatcodes | number |
| getattribute | function | romannumeral | function |
| getbox | function | round | function |
| getcatcode | function | run | function |
| getcount | function | scale | function |
| getdelcode | function | set | function |
| getdimen | function | setattribute | function |
| getlccode | function | setbox | function |
| getlist | function | setcatcode | function |
| getmath | function | setcount | function |
| getmathcode | function | setdelcode | function |
| getnest | function | setdimen | function |
| getsfcode | function | setlccode | function |
| getskip | function | setlist | function |
| gettoks | function | setmath | function |
| getuccode | function | setmathcode | function |
| hashtokens | function | setnest | function |
| ifs | data table | setsfcode | function |
| inicatcodes | number | setskip | function |
| iscount | function | settoks | function |
| isdimen | function | setuccode | function |
| isskip | function | sfcode | table |

shipout function skip table sp function sprint function systemmodes data table texcatcodes number toks table tpacatcodes number tpbcatcodes number

tprint function data table trackers txtcatcodes number function type uccode table uniformdeviate function uprint function vrbcatcodes number write function

texconfig (basic tex)

| error_line | number |
|-----------------|----------|
| expand_depth | number |
| formatname | string |
| half_error_line | number |
| hash_extra | number |
| init | function |
| kpse_init | boolean |
| max in open | number |

| max_print_line | number |
|----------------|--------|
| max_strings | number |
| nest_size | number |
| param_size | number |
| save_size | number |
| shell_escape | string |
| stack_size | number |

texio (basic tex)

write function

write_nl function

token (basic tex)

| command_id | function |
|--------------|----------|
| command_name | function |
| create | function |
| csname_id | function |
| csname_name | function |
| expand | function |

get_next function
is_activechar function
is_expandable function
is_protected function
lookup function

tokens (context)

bgroup table
collectors table

T data

F defaultwords

F dowithwords

F flush

F handle

F install

F register
T registered

T remapper

F convert

T data

F store

F show

T show_methods

Fa

F b

Fc

F showtoken

F test

F trace

egroup table

hbox table

letter function
letters function

letters function
other function

vbox table

vtop table

tracers (context)

count function
cs function
dimen function
knownlist function
lists table

T context
T internals
T scratch

name function
primitive function
printerror function
showlines function
strings table

S undefined

toks function
type function

trackers (context)

| data | data table | name | string |
|----------------|------------|----------|----------|
| default | function | register | function |
| disable | function | report | function |
| dumphashtofile | function | savehash | function |
| enable | function | show | function |
| list | function | value | function |

typesetters (context)

| -1: | +ahla | | |
|------------------------|----------|------------------------|------------|
| alignments | table | F set kerns | table |
| F handler | | | table |
| F set breakpoints | table | D factors F handler | |
| N attribute | table | | |
| F define | | B keepligat | |
| F derine F handler | | B keeptoget | ner |
| | | D mapping F set | |
| D mapping T methods | | margins | table |
| T numbers | | F finalhand | |
| F set | | F globalhar | |
| F setreplace | ment | F ha | iutei |
| cases | table | F localhand | ller |
| T actions | Cabic | F save | ittei |
| F handler | | paragraphs | table |
| F register | | N attribute | |
| F set | | T droppers | |
| characters | table | F freeze | |
| F handler | | F set | |
| checkers | table | F handler | |
| F handler | | F set | |
| F reset | | processors | table |
| F set | | • F apply | |
| cleaners | table | F register | |
| F handler | | F reset | |
| F set | | F split | |
| digits | table | F startappl | .y |
| T actions | | F stopapply | , |
| N attribute | | F stripped | |
| F handler | | F tostring | |
| F set | | spacings | table |
| directions | table | N attribute | : |
| F handler | | F define | |
| F process | | F handler | |
| F set | | D mapping | |
| fast_hpack | function | T numbers | |
| hpack | function | T frenchp | unctuation |
| italics | table | T chara | cters |
| F forcevaria | nt | S name | |
| F handler | | N numbe | r |
| F reset | | F reset | |

F set F setup

tonodes function
vpack function
xtables table

F cleanup
F construct
F create
F flush

F initialize_construct
F initialize_reflow_height
F initialize_reflow_width

F next_row
F reflow_height
F reflow_width
F set_construct
F set_reflow_height
F set_reflow_width

unicode (extra lua)

| asci | i | table F | len |
|------|---------|---------|------------------|
| F | byte | F | lower |
| F | char | F | match |
| F | dump | F | rep |
| F | find | F | reverse |
| F | format | F | sub |
| F | gfind | F | upper |
| F | gmatch | utf8 | table |
| F | gsub | F | byte |
| F | len | F | char |
| F | lower | F | characters |
| F | match | F | count |
| F | rep | F | dump |
| F | reverse | F | filetype |
| F | sub | F | find |
| F | upper | F | format |
| grap | heme | table F | gfind |
| F | byte | F | gmatch |
| F | char | F | gsub |
| F | dump | F | is_valid |
| F | find | F | len |
| F | format | F | length |
| F | gfind | F | lower |
| F | gmatch | F | magic |
| F | gsub | F | match |
| F | len | F | remapper |
| F | lower | F | rep |
| F | match | F | replacer |
| F | rep | F | reverse |
| F | reverse | F | split |
| F | sub | F | splitlines |
| F | upper | F | sub |
| lati | n1 | table F | subtituter |
| F | byte | F | tocodes |
| F | char | F | toentities |
| F | dump | F | tostring |
| F | find | F | totable |
| F | format | F | upper |
| F | gfind | F | ustring |
| F | gmatch | F | utf16_to_utf8 |
| F | gsub | F | utf16_to_utf8_be |
| | | | |

F utf16_to_utf8_le
F utf32_to_utf8
F utf32_to_utf8_be
F utf32_to_utf8_le

F utf8_to_utf16
F utf8_to_utf8
F values
F xstring

url (context)

| addscheme | function | hashed | function |
|-----------|----------|-----------|----------|
| barepath | function | hasscheme | function |
| construct | function | query | function |
| escape | function | split | function |
| filename | function | toquery | function |

utilities (context)

| debugger | table | parsers | table |
|--------------------|-------|-----------------|--------------------|
| F disable | | F add_settings | |
| F enable | | F arguments_to | |
| F savestats | | F array_to_str | |
| F showstats | | F csvsplitter | |
| formatters | table | F getparameter | ^s |
| F formatcolumns | | F hash_to_stri | ing |
| F list | | F iterator | |
| F stripzeros | | F keq_to_hash | |
| garbagecollector | table | F listitem | |
| F check | | F make_setting | js_to_hash_pattern |
| N criterium | | F mergehashes | |
| B enabled | | T patterns | |
| lua | table | U keq_to_has | h_c |
| B alwaysstripcode | | U settings_t | o_array |
| F compile | | U settings_t | o_hash_a |
| F loadedluacode | | U settings_t | o_hash_b |
| F loadstripped | | U settings_t | o_hash_c |
| N nofstrippedbytes | | U unittotex | |
| N nofstrippedchunk | s | F rfc4180split | ter |
| B stripcode | | F settings_to_ | _array |
| T strippedchunks | | F settings_to_ | _array_with_repeat |
| F strippedloadstri | ng | F settings_to_ | hash |
| T suffixes | | F settings_to_ | _hash_strict |
| S lua | | F settings_to_ | _hash_tolerant |
| S luc | | F settings_to_ | _set |
| S lui | | F simple_hash_ | _to_string |
| S luj | | F splitthousar | nds |
| S luv | | F stepper | |
| S tma | | F unittotex | |
| S tmc | | F unittoxml | |
| S tua | | report | function |
| S tuc | | sequencers | table |
| packers | table | F appendaction | 1 |
| F hashed | | F appendgroup | |
| F new | | F compile | |
| F pack | | F disableaction | on |
| F simplehashed | | F disablegroup | |
| F strip | | F enableaction | 1 |
| F unpack | | F enablegroup | |
| N version | | D functions | |

F localize F setinitializer F new F sparse strings table F nodeprocessor F collapsecrlf F prependaction F prependgroup T formatters F removeaction F add F setkind F new F tostrina F newrepeater setters table F nice F disable F striplong F enable F tabtospace F initialize T tracers tables F list table F accesstable F new F definedtable F register F report F definetable F reset F encapsulate F show F insertaftervalue stacker table F insertbeforevalue F new F migratetable table storage F removevalue templates table F allocate F checked F load

F mark

F marked

F replace

F resolve

vf (context)

| char | function |
|--------|----------|
| down | function |
| fontid | function |
| image | function |
| node | function |
| nop | function |

pop function
push function
right function
rule function
special function

visualizers (context)

| escapepatterns | data table | signal | string |
|-----------------------|------------|-----------------|------------|
| getvisualizer | function | signalpattern | userdata |
| load | function | specifications | data table |
| makenested | function | visualize | function |
| makepattern | function | visualizebuffer | function |
| newgrammar | function | visualizefile | function |
| newhandler | function | visualizestring | function |
| parsedxml | function | write | function |
| pattern | function | writeargument | function |
| register | function | writedefault | function |
| registerescapecommand | function | writeemptyline | function |
| registerescapeline | function | writenewline | function |
| registerescapepattern | function | writespace | function |

xml (context)

| addentitiesdoctype | function | D tex | |
|----------------------|---------------------|---------------------------|---------------------|
| after | function | D texline | |
| all | function | D texspace | |
| applylpath | function | D verbose | |
| assign | function | defaultprotocol | string |
| attribute | function | delete | function |
| before | function | delete element | function |
| body | function | each | function |
| builtinentities | table | each_element | function |
| B amp | | elements | function |
| B apos | | elementtocdata | function |
| B gt | | empty | function |
| B lt | | entities | data table |
| B quot | | erase | function |
| cdata | function | errorhandler | function |
| cdatatotext | function | escaped | function |
| checkbom | function | expressions | table |
| checkerror | function | F boolean | |
| checknamespace | function | F child | |
| checkns | function | F contains | |
| cleansed | function | F count | |
| collect | function | F error | |
| collect_elements | function | F find | |
| collect_tags | function | F lower | |
| collect_texts | function | F name | |
| collected | function | F number | |
| collecttexts | function | F oneof | |
| content | function | F print | |
| convert | function | F quit | |
| сору | function | F tag | |
| count | function | F text | |
| cprint | function | F undefined | |
| CSS | table | F upper | |
| F colorspecification | | fillin | function |
| F dimension | | filter | function |
| F fontspecification | | finalizers | table |
| F padding | | F paragraphs | |
| defaulthandlers | table | T tex | |
| D file | | F all | |
| D parsedxml | | F attribute | |
| D string | | F bibtexconcat | |

| F | bibtexshort | F position | |
|----|----------------|----------------------------------|-----------------|
| F | chainattribute | F reverse | |
| F | command | F table | |
| F | concat | F tag | |
| F | concatrange | F tags | |
| F | context | F text | |
| F | count | F texts | |
| F | ctxtext | F upperall | |
| F | default | first | function |
| F | first | found | function |
| F | function | functions | table |
| F | index | getbuffer | function |
| F | last | gethandlers | function |
| F | lettered | gethandlersfunction | function |
| F | lower | helpers | table |
| F | lowerall | F recursetext | |
| F | match | include | function |
| F | name | index | function |
| F | position | inheritedconvert | function |
| F | reverse | inject | function |
| F | stripped | <pre>inject_element</pre> | function |
| F | tag | <pre>inject_element_after</pre> | function |
| F | tags | <pre>inject_element_before</pre> | function |
| F | text | injectafter | function |
| F | upper | injectbefore | function |
| F | upperall | insert | function |
| Тх | ml | insert_element | function |
| F | all | <pre>insert_element_after</pre> | function |
| F | att | <pre>insert_element_before</pre> | function |
| F | attribute | insertafter | function |
| F | attributes | insertbefore | function |
| F | cdata | insertcomment | function |
| F | chainattribute | inspect | function |
| F | count | is_valid | function |
| F | default | kind | function |
| F | elements | last | function |
| F | empty | load | function |
| F | first | lpath | function |
| F | function | lpathcached | function |
| F | index | lpathcalls | function |
| F | last | lshow | function |
| F | lowerall | makestandalone | function |
| F | match | match | function |
| F | name | name | function |
| | | | |

Т

| newhandlers | function | root | function |
|-------------------------------|---------------------|---------------------|-----------------|
| nodesettostring | function | save | function |
| originalload | function | selection | function |
| package | function | separate | function |
| parent | function | serialize | function |
| parsedentitylpeg | userdata | setcdata | function |
| pihandlers | table | sethandlersfunction | function |
| placeholders | table | setproperty | function |
| F unknown_any_entity | | settings | function |
| F unknown_dec_entity | | specialhandler | table |
| F unknown_hex_entity | | sprint | function |
| position | function | string | function |
| privatecodes | table | strip | function |
| privatetoken | function | strip_whitespace | function |
| process | function | stripelement | function |
| <pre>process_attributes</pre> | function | stripleadingspaces | function |
| process_elements | function | table | function |
| processattributes | function | text | function |
| profiled | table | textonly | function |
| raw | function | texttocdata | function |
| registerentity | function | tocdata | function |
| registerns | function | toelement | function |
| remap_name | function | tostring | function |
| remap_namespace | function | toxml | function |
| remap_tag | function | tprint | function |
| remapname | function | traverse | function |
| remapnamespace | function | unescaped | function |
| remaptag | function | unprivatized | function |
| renamespace | function | withelement | function |
| replace | function | withelements | function |
| replace_element | function | wrap | function |
| resolvens | function | xmlns | table |
| | | | |

zip (extra lua)

| archives | table | openarchive | function |
|--------------|----------|-----------------|----------|
| close | function | openfile | function |
| closearchive | function | registeredfiles | table |
| open | function | type | function |

zlib (extra lua)

adler32 function
compress function
compressobj function
crc32 function

decompress function
decompressobj function
version function