bitset blobs boolean buffers builders bytemap caches callback callbacks catcodes characters chemistry client commands containers context converters coroutine ctxrunner debug dir directives document documentdata drivers effects environment experiments figures file fio floats font fonts functions globaldata globals graphics gzip helper images interactions interfaces io job kdtree kpse language languages layouts lfs libraries lmx loaders logs lpdf lpeg lua luac luatex lxml math mathematics md5 metapost moduledata modules mp mplib nanojpeg noads node nodes number objects optional os package pagebuilders parametersets pdf pdfdecode pdfe physics pngdecode posit potrace process publications qrcodegen regimes resolvers sandbox scripts security sequencer serial server set sha2 sio sorters sparse statistics status storage streams string structures table tex texconditionals texconfig texconstants texifs texio texisdefined texmodes texsystemmodes thirddata timer token tokens tracers trackers typesetters updaters url userdata utf8 utilities vector visualizers xcomplex xdecimal xinterval xmath xml xzip zbuffer zip zlib

ConTeXt LMTX

global (alias: _G)

CONTEXTLMTXMODE	number	**ctxrunner**	table
JITSUPPORTED	boolean	**debug**	table
LUAFORMAT	number	**dimen**	function
LUAMAJORVERSION	number	**dir**	table
LUAMINORVERSION	number	**directives**	table
LUATEXENGINE	string	**document**	table
LUATEXFORMATID	number	**documentdata**	table
LUATEXFUNCTIONALITY	number	**dofile**	function
LUATEXVERBOSE	string	**drivers**	table
LUATEXVERSION	number	**effects**	table
LUAVERSION	number	**environment**	table
MP	function	**error**	function
SAVEDREQUIRE	function	**experiments**	table
aes	table	**figures**	table
arg	table	**file**	table
assert	function	**fio**	table
attributes	table	**floats**	table
backends	table	**font**	table
basexx	table	**fonts**	table
bibtex	table	**functions**	table
bit32	table	**getmetatable**	function
bitset	table	**globaldata**	table
blobs	table	**globals**	table
boolean	table	**graphics**	table
buffers	table	**gzip**	table
builders	table	**helper**	table
bytemap	table	**images**	table
caches	table	**inspect**	function
callback	table	**interactions**	table
callbacks	table	**interfaces**	table
catcodes	table	**io**	table
characterkern	function	**ipairs**	function
characters	table	**job**	table
chemistry	table	**kdtree**	table
client	table	**kpse**	table
collectgarbage	function	**language**	table
commands	table	**languages**	table
containers	table	**layouts**	table
context	function	**lfs**	table
converters	table	**libraries**	table
coroutine	table	**lmx**	table

load	function	publications	table
loaders	data table	qrcodegen	table
loadfile	function	rawequal	function
loadstring	function	rawget	function
logs	table	rawlen	function
lpdf	table	rawset	function
lpeg	table	regimes	table
lua	table	require	function
luac	table	resolvers	table
luatex	table	sandbox	table
lxml	table	scripts	table
math	table	security	table
mathematics	table	select	function
md5	table	sequencer	table
metapost	table	serial	table
moduledata	table	server	table
modules	table	set	table
mp	function	setinspector	function
mplib	table	setmathparameters	function
nanojpeg	table	setmetatable	function
next	function	sha2	table
noads	table	sio	table
node	table	sorters	table
nodes	table	sparse	table
number	table	statistics	table
objects	table	status	table
optional	table	storage	table
optionalrequire	function	streams	table
os	table	string	table
package	table	structures	table
pagebuilders	table	table	table
pairs	function	tabstr_boolean	function
parametersets	table	tabstr_flat	function
pcall	function	tabstr_mixed	function
pdf	table	tabstr_normal	function
pdfdecode	table	tex	table
pdfe	table	texconditionals	data table
pdfembeddedlink	function	texconfig	table
physics	table	texconstants	data table
pngdecode	table	texifs	data table
posit	table	texio	table
potrace	table	texisdefined	data table
print	function	texmodes	data table
process	table	texsystemmodes	data table

thirddata	table	**userdata**	table
timer	table	**utf**	table
toboolean	function	**utf8**	table
todecimal	function	**utilities**	table
token	table	**vector**	table
tokens	table	**visualizers**	table
tonumber	function	**warn**	function
tostring	function	**xcomplex**	table
tostring_u1	function	**xdecimal**	table
tostring_u2	function	**xinterval**	table
tracers	table	**xmath**	table
trackers	table	**xml**	table
type	function	**xpcall**	function
typesetters	table	**xzip**	table
unpack	function	**zbuffer**	table
updaters	table	**zip**	table
url	table	**zlib**	table

aes (extra lua)

decode function
encode function
random function

attributes (context)

alternates table
- N attribute
- D data
- F enable
- F handler
- F register
- D registered
- D values

applyoverloads function

checkvalues function

colorintents table
- N attribute
- D data
- F enable
- F handler
- F register
- D registered

colors table
- N attribute
- F cmyk
- F cmyktogray
- F cmyktorgb
- F colorcomponents
- D counts
- B couple
- F currentmodel
- F currentnamedmodel
- D data
- N default
- F defineintermediatecolor
- F definemultitonecolor
- F defineprocesscolor
- F defineprocesscolordirect
- F definesimplegray
- F definespotcolor
- F definetransparency
- F enable
- F filter
- N forced
- F forcedmodel
- F forcesupport
- F formatcolor
- F formatgray
- F formatluminance
- F formatluminanceratio
- F getpagecolormodel
- F gray
- F graytohsv
- F handler
- T helpers
  - F complement
  - F inbetween
  - F justone
- F hsvtogray
- F hsvtorgb
- F hwbtorgb
- F iccprofile
- F isblack
- F labtolch
- F labtorgb
- F labtoxyz
- F lchtolab
- F lchtorgb
- N main
- S model
- D models
- F mpcolor
- F mpnamedcolor
- F mpoptions
- F mprgbcolor
- F namedcolorattributes
- N none
- F popset
- F processcolorcomponents
- F pushset
- F register
- D registered
- F registerspotcolor
- F rgb
- F rgbbytes
- F rgbtocmyk
- F rgbtogray

F rgbtohsv
F rgbtoxyz
N selector
F setlist
F setmodel
F setpagecolormodel
D sets
F spec
F spot
F spotcolorname
F spotcolorparent
F spotcolorvalue
B supported
F toattributes
F transparencycomponents
B triggering
F usecolors
D valid
F value
D values
B weightgray
F xyztolab
F xyztorgb

counts data table
define function
effects table
N attribute
D data
F enable
F handler
F register
D registered
D values
getvalue function
getvalues function
handlers table
hasvalues function
list data table
markasoverload function
names data table
negatives table
N attribute
D data
F enable
F handler
F register
D registered
F set
numbers data table
ofnode function
private function
public function
registervalue function
restore function
save function
setcleaner function
showcurrent function
states table
F finalize
F initialize
F process
F selective
F simple
F stacked
F stacker
system function
tooverloads function
transparencies table
N attribute
D data
F enable
F forcesupport
F handler
T names
N color
N colorburn
N colordodge
N darken
N difference
N exclusion
N hardlight
N hue
N lighten
N luminosity
N multiply
N none
N normal
N overlay

N saturation
N screen
N softlight
N none
F register
D registered
B supported
F toattribute
B triggering
F value
D values

unsetvalue number

values data table

viewerlayers table

N attribute
F cleanup
D data
F define
F definedlayoutcomponent
F enable
F forcesupport
F handler
B hasorder
D listwise
F register
D registered
F resolve_begin
F resolve_end
F resolve_reset
F resolve_step
D scopes
F setfeatures
F setup
F start
F stop
B supported
D values

backends (context)

closeout function
codeinjections table
F registerboxresource
F registerfont
F restoreboxresource
current string
defaults table
T codeinjections
F prerollreference
F setautoprefix
F vfstartcolor
F vfstopcolor
T nodeinjections
F cmykcolor
F destination
F graycolor
F knockout
F overprint
F reference
F rgbcolor
F spotcolor
F transparency
T registrations
F transparency
D tables
getcallbackstate function
included table
B context
B date
B id
B metadata
B pdf
initialize function
latelua function
nodeinjections table
nothing function
openout function
registered table
T pdf
T codeinjections
F addbookmarks
F analyzenormalsymbol
F analyzesymbol
F attachmentid
F bitmap
F clonefield
F copyimage
F defaultprofile
F definefield
F definefieldset
F defineviewerlayer
F discardpages
F embedfile
F embedimage
F enabletags
F exportformdata
F fieldsurrounding
F flushmergelayer
F getbookmarks
F getboxresourcebox
F getdefaultfieldvalue
F getfieldcategory
F getfieldset
F getformatoption
F getinfo
F getlinkstructureparent
F getreferencestructureobject
F getrefobj
F insertrenderingwindow
F jp2
F jpg
F maptag
F mergebookmarks
F mergecomments
F mergefields
F mergereferences
F mergerenditions
F mergeviewerlayers
F newimage
F png
F prerollreference
F presetsymbol

F presetsymbollist
F processrendering
F registerdocumentcloseaction
F registerdocumentopenaction
F registeredsymbol
F registerfiguremask
F registerfigurerange
F registerpagecloseaction
F registerpageopenaction
F registerpattern
F registersymbol
F ruleactionbox
F ruleactiondraw
F ruleactionfill
F ruleactionmp
F ruleactionstroke
F saveboxresource
F scanimage
F setattachmentsupport
F setautoprefix
F setencryption
F setfieldcalculationset
F setfigurecolorspace
F setfiguremask
F setformat
F setformsmethod
F setjobcomment
F setpagetransition
F settaggingsupport
F setupviewerlayer
F setuserdata
F setxmpfile
F startactualtext
F startalternativetext
F startlayer
F startunicodetoactualtext
F startunicodetoactualtextdirect
F stopactualtext
F stopalternativetext
F stoplayer
F stopunicodetoactualtext
F stopunicodetoactualtextdirect
F supportedformats
F unicodetoactualtext
F useviewerlayer
F validcompactor
F validfield
F validfieldcategory
F validfieldset
F vfstartcolor
F vfstopcolor
F wrapimage
S name
T nodeinjections
F addtags
F annotation
F attachfile
F changestackedlayer
F cmykcolor
F comment
F destination
F effect
F getboxresourcedimensions
F graycolor
F injectbitmap
F insertu3d
F knockout
F negative
F overprint
F positive
F reference
F rgbcolor
F spotcolor
F startalternate
F startlayer
F startstackedlayer
F stopalternate
F stoplayer
F stopstackedlayer
F transparency
F typesetfield
F useboxresource
T registrations
F cmykindexcolor
F cmykspotcolor
F getspotcolorreference
F grayindexcolor
F grayspotcolor

```
  F rgbindexcolor
  F rgbspotcolor
  F spotcolorname
  F transparency
T tables
```

registrations	table
setencryption	function
tables	table
writeout	function

basexx (extra lua)

decode16	function	**encode16**	function
decode64	function	**encode64**	function
decode85	function	**encode85**	function
decodeLZW	function	**encodeLZW**	function
decodeRL	function	**encodeRL**	function

bit32 (context)

arshift	function	**extract**	function
band	function	**lrotate**	function
bnot	function	**lshift**	function
bor	function	**replace**	function
btest	function	**rrotate**	function
bxor	function	**rshift**	function

bitset (context)

assign	function	**newzerobased**	function
asstring	function	**reset**	function
band	function	**set**	function
bnot	function	**shl**	function
bor	function	**shr**	function
bxor	function	**tostring**	function
get	function	**totable**	function
len	function	**traverse**	function
new	function	**wipe**	function
newonebased	function		

blobs (context)

append	function	**strht**	function
dimensions	function	**strwd**	function
dispose	function	**tohpack**	function
new	function	**tonodes**	function
pack	function	**tovpack**	function
strdp	function	**write**	function
strhd	function		

boolean (context)

tocontext function
tonumber function

buffers (context)

append	function	**parallel**	table
assign	function	F define	
collectcontent	function	F hassomecontent	
empty	function	F next	
erase	function	F place	
exists	function	F reset	
get	function	F save	
getcontent	function	**prepend**	function
getctxlua	function	**raw**	function
getlines	function	**run**	function
getmkvi	function	**samplefile**	function
gettex	function	**splitsamplefile**	function
loadcontent	function	**undent**	function

builders (context)

checkparcontext function
checksidefloat function
hpack table
F qualityactions
F report
F show
kernel table
F collapsing
F hyphenating
F kerning
F ligaturing
F mlisttohlist
paragraphs table
T constructors
N attribute
F define
F disable
F enable
F handler
T methods
F basic
F default
F hpack
F oneline
D names
D numbers
F set
F start
F stop
T expansion
F trace
F keeptogether
F registertogether
T solutions
T splitters
F define
F optimize
T registered
F reset
F set
F split
F start
F stop
F tag
parpassidentifier function
passnames data table
profiling table
F add
F addrivers
F boxlinehandler
F distance
F fixedprofile
F get
F getrivers
F list
F pagehandler
F pagelinehandler
F profilebox
F profilelines
F set
F setlines
registerpaspasscallback function
vpack table
F qualityactions
F report
vspacing table
D categories
F checkstrutdepth
F collapsevbox
T data
D map
D skip
D snapmethods
F definesnapmethod
B fixed
F flushcontributions
F forcepageflush
F forcestrutdepth
F getnofpreviouslines
F inject
F injectdisable
F injectnowhite

F injectpenalty
F injectskip
F interceptsamepagecontent
F pagehandler
F pageoverflow
F popatsame
F pushatsame
F setmap
F setskip
F snapbox
F synchronizepage
F tocategories
F tocategory
F vboxhandler

bytemap (context)

bounds	function
clip	function
copy	function
dimensions	function
domain	function
downgrade	function
downsample	function
fillgray	function
fillrgb	function
filter	function
getbyte	function
getbytes	function
getluminance	function
getvalue	function
hasbytegray	function
hasbyterange	function
hasbytergb	function
new	function
newdomain	function
overlay	function
process	function
reduce	function
reset	function
setgray	function
setgrayadd	function
setgraymin	function
setrgb	function
slicegray	function
slicerange	function
slicergb	function
totable	function

caches (context)

base	string	**loadcontent**	function
collapsecontent	function	**loaddata**	function
configfiles	function	**more**	string
contentstate	function	**savecontent**	function
defaults	table	**savedata**	function
getfirstreadablefile	function	**setfirstwritablefile**	function
getreadablepaths	function	**setluanames**	function
getwritablepath	function	**treehash**	function
hashed	function	**usedpaths**	function
is_writable	function		

callback (basic tex)

find	function	**known**	function
getcontracts	function	**list**	function
getcontractvalues	function	**names**	function
getindex	function	**register**	overloaded function
getoptions	function	**setoptions**	function
getoptionvalues	function	**setstate**	function
getstate	function	**testonly**	function
getstatevalues	function	**usage**	function

callbacks (context)

freeze function
functions table
F start_page_number
F stop_page_number
getcomment function
getstates function
known function
list table
N alignment
N append_adjust
N append_line
N append_migrate
N append_to_vlist
N balance_boundary
N balance_check
N balance_insert
N begin_paragraph
N buildpage
N define_font
N find_format_file
N find_log_file
N get_attribute
N get_math_dictionary
N get_noad_class
N glyph_run
N handle_overload
N handle_uinsert
N handle_uleader
N hpack
N hpack_quality
N hyphenate
N insert_boundary
N insert_check_split
N insert_distance
N insert_par
N intercept_lua_error
N intercept_tex_error
N italic_correction
N kerning
N ligaturing
N linebreak
N linebreak_check
N linebreak_quality
N local_box
N make_extensible
N math_rule
N missing_character
N mlist_to_hlist
N open_data_file
N packed_vbox
N page_boundary
N paragraph_context
N paragraph_pass
N post_linebreak
N pre_dump
N pre_linebreak
N pre_output
N process_character
N process_jobname
N quality_font
N register_extensible
N show_build
N show_error_message
N show_loners
N show_lua_call
N show_vsplit
N show_warning_message
N show_whatsit
N start_file
N start_run
N stop_file
N stop_run
N tail_append
N test_only
N trace_memory
N vpack
N vpack_quality
N wrapup_run
names table
optimizer function
optionbits table
optioncodes table

N direct
N trace

pop function
push function
register function
report function
statebits table
statecodes table
N disabled
N frozen
N fundamental
N private
N selective
N set
N touched
N tracing

catcodes (context)

names data table
numbers data table
register function

characters (context)

addcharacternames function
adobename function
bidi data table
blockrange function
blocks data table
can_have_space data table
casemap table
categories data table
category function
categorytags data table
classifiers table
collapsed data table
combined data table
contextname function
csletters data table
data data table
decomposed data table
description function
descriptions data table
detailtags data table
directions table
emoji table
F compact
F known
F resolve
emojized function
enccodes data table
entities data table
fallbacks data table
filters data table
fractions table
fromnumber function
fschars data table
fscodes data table
getrange function
graphemes data table
hangul data table
indicgroups table
T above_mark
T after_half
T after_main
T after_postscript
T after_subscript
T anudatta
T before_half
T before_main
T before_postscript
T before_subscript
T below_mark
T consonant
T dependent_vowel
T halant
T independent_vowel
T nukta
T post_mark
T pre_mark
T ra
T stress_tone_mark
T twopart_mark
T vowel_modifier
initialize function
is_character data table
is_command data table
is_hyphenator data table
is_letter data table
is_mark data table
is_nothing data table
is_punctuation data table
is_spacing data table
is_symbol data table
lcchars data table
lccode function
lccodes data table
lettered function
lhash data table
linebreaks data table
lower function
mathlists data table
mirrors table
otfscripts data table
packdata table
N luasize

N newsize
N oldsize
N version

ranges data table
registerentities function
remap_hangul_syllabe function
scripthash table
setactivecatcodes function
setlettercatcodes function
setothercatcodes function
shape function
shaped function
shash data table
shchars data table
shcodes data table
showstring function
specialchars data table
specials data table
splits table
T char
T compat
subscripts table
superscripts table
synonyms data table
tex table
D accentmapping
D commandmapping
F defineaccents
F safechar
F strtextoutf
F strtoutfpattern
F toutf
F toutfpattern
textclasses table
tonumber function
ucchars data table
uccode function
uccodes data table
uhash data table
unicodechar function
upper function
verbosemarks data table

chemistry (context)

component function
define function
definitions data table
format string
inlinechemical function
instance string
method string
molecule function
moleculeparser userdata
start function
stop function
syntax table

```
T alkyl
 S category
 T keys
  S ad
  S adj
  S arrow
  S au
  S b
  S bb
  S bd
  S bw
  S c
  S cc
  S ccd
  S cd
  S cz
  S dash
  S db
  S diff
  S dir
  S dr
  S ed
  S ep
  S es
  S et
  S hb
  S label
  S ldb
  S ldd
  S line
  S lrn
  S lrt
  S mark
  S mir
  S mov
  S move
  S number
  S oe
  S off
  S r
  S rb
  S rbd
  S rd
  S rdb
  S rdd
  S rh
  S rm
  S rn
  S rot
  S rrn
  S rrt
  S rt
  S rz
  S sb
  S sd
  S sr
  S sub
  S tb
  S z
  S zln
  S zlt
  S zn
  S zrn
  S zrt
  S zt
 S keyword
 N max
T boat
 S category
 T keys
```

```
S adj
S arrow
S b
S bb
S c
S cc
S ccd
S cd
S dash
S diff
S eb
S label
S line
S lr
S lrb
S lrbd
S lrd
S lrh
S lrn
S lrt
S lrz
S lsr
S lsub
S mark
S mov
S move
S number
S off
S r
S rb
S rbd
S rd
S rh
S rn
S rr
S rrb
S rrbd
S rrd
S rrh
S rrn
S rrt
S rrz
S rsr
S rsub
  S rt
  S rz
  S sb
  S sr
  S sub
  S z
  S zln
  S zlt
  S zn
  S zrn
  S zrt
  S zt
 S keyword
 N max
T carbon
 S category
 S keyword
 N max
T chair
 S category
 S keyword
 N max
T chem
 N arguments
 F direct
T closecomplex
 S direct
T eight
 S category
 T keys
  S ad
  S adj
  S arrow
  S au
  S b
  S c
  S cc
  S ccd
  S cd
  S crz
  S dash
  S db
  S diff
  S dr
```

S eb
S ed
S er
S hb
S label
S line
S lr
S lrb
S lrbd
S lrd
S lrh
S lrn
S lrt
S lrz
S lsr
S lsub
S mark
S mid
S mids
S midz
S mir
S mov
S move
S number
S off
S r
S rb
S rbd
S rd
S rh
S rm
S rn
S rot
S rr
S rrb
S rrbd
S rrd
S rrh
S rrn
S rrt
S rrz
S rsr
S rsub
S rt
S rz
S s
S sb
S sr
S ss
S sub
S z
S zln
S zlt
S zn
S zrn
S zrt
S zt
S keyword
N max
T equals
S direct
T equilibrium
N arguments
F direct
T five
S category
S keyword
N max
T fivefront
S category
S keyword
N max
T four
S category
S keyword
N max
T gives
N arguments
F direct
T mesomeric
N arguments
F direct
T minus
S direct
T mp
N arguments
F direct
T newmaneclipsed

```
  S category
  S keyword
  N max
T newmanstagger
  S category
  S keyword
  N max
T nine
  S category
  S keyword
  N max
T one
  S category
  S keyword
  N max
T opencomplex
  S direct
T pb
  S direct
T pe
  S direct
T plus
  S direct
T reset
  S direct
T restore
  S direct
T save
  S direct
T seven
  S category
  S keyword
  N max
T six
  S category
  S keyword
  N max
T sixfront
  S category
  S keyword
  N max
T space
  S direct
T three
  S category
  S keyword
  N max
```

undefine function

client (context)

httprequest function
supported function

containers (context)

cleanname	function	**is_valid**	function
content	function	**read**	function
define	function	**usecache**	boolean
is_usable	function	**write**	function

converters (context)

A	function	**cn-a**	function
A:es	function	**cn-c**	function
A:ru	function	**cn-d**	function
A:sl	function	**convert**	function
AK	function	**decimals**	function
Alphabetic	function	**define**	function
Alphabetic:es	function	**gregorian_to_hebrew**	function
Alphabetic:ru	function	**gregorian_to_jalali**	function
Alphabetic:sl	function	**hebrewnumerals**	function
Character	function	**helpers**	table
Characters	function	**hexstringtonumber**	function
I	function	**i**	function
KA	function	**isleapyear**	function
KR	function	**jalali_to_gregorian**	function
R	function	**lchexnumber**	function
RK	function	**lchexnumbers**	function
Romannumerals	function	**leapyear**	function
Russiannumerals	function	**lower**	function
Sloveniannumerals	function	**max**	function
Spanishnumerals	function	**maxchrs**	function
Word	function	**nicenumber**	function
Words	function	**nofdays**	function
a	function	**number**	function
a:es	function	**numbers**	function
a:ru	function	**octnumber**	function
a:sl	function	**octstringtonumber**	function
abjadnodotnumerals	function	**ordinal**	function
abjadnumerals	function	**r**	function
alphabetic	function	**romannumerals**	function
alphabetic:es	function	**russiannumerals**	function
alphabetic:ru	function	**sequences**	data table
alphabetic:sl	function	**settime**	function
character	function	**sloveniannumerals**	function
characters	function	**spaceddigits**	function
chineseallnumerals	function	**spanishnumerals**	function
chinesecapnumerals	function	**textime**	function
chinesedatenumerals	function	**toabjad**	function
chinesenumerals	function	**tochinese**	function
chr	function	**tohebrew**	function
chrs	function	**toroman**	function
cn	function	**totime**	function

uchexnumber	function	F translate	
uchexnumbers	function	**weekday**	function
upper	function	**word**	function
verbose	table	**words**	function

D data

coroutine (basic lua)

close	function	**running**	function
create	function	**status**	function
isyieldable	function	**wrap**	function
resume	function	**yield**	function

ctxrunner (context)

load	function	**prepfiles**	data table
preparedfile	function	**resolve**	function

debug (basic lua)

getinfo	function	**traceback**	function
sethook	function		

dir (context)

collectpattern	function	**globfiles**	function
current	function	**globpattern**	function
expandlink	function	**ls**	function
expandname	function	**makedirs**	function
found	function	**mkdirs**	function
glob	function	**pop**	function
globdirs	function	**push**	function

directives (context)

data	data table	**register**	function
default	function	**report**	function
disable	function	**reset**	function
done	table	**set**	function
enable	function	**show**	function
list	function	**value**	function
name	string	**values**	function

document (context)

arguments	data table	**pdf_cleanup_procsets**	function
files	table	**pdf_identify_content**	function
functions	table	**pdf_serialize_content**	function
getargument	function	**pdf_strip_content**	function
getfilename	function	**pdf_strip_page**	function
options	table	**setargument**	function
T commandline		**setcommandline**	function
D environments		**setdefaultargument**	function
D modes		**setenvironments**	function
D modules		**setfilename**	function
T ctxfile		**setfilenames**	function
D environments		**setmodes**	function
D modes		**setmodules**	function
D modules		**variables**	data table
pdf_cleanup_cidsets	function		

documentdata (context)

variable function

drivers (context)

applyanchor function
applyorientation function
convert function
converters table
F analyze
F engine
F lmtx
F resyncbox
enable function
finalize function
gethpos function
gethvrpos function
getpos function
getrpos function
getvpos function
helpers table
initialize function
install function
instances table
T empty
T actions
F convert
F prepare
T flushers
F popleaderlevel
F pushleaderlevel
T whatsit
S name
T js
T actions
F cleanup
F convert
F finalize
F initialize
F outputfilename
F prepare
F wrapup
T flushers
F character
F popleaderlevel
F pushleaderlevel
F rule
F simplerule
F specialrule
F updatefontstate
T whatsit
S name
T json
T actions
F cleanup
F convert
F finalize
F initialize
F outputfilename
F prepare
F wrapup
T flushers
F character
F popleaderlevel
F pushleaderlevel
F rule
F simplerule
F specialrule
F updatefontstate
T whatsit
S name
T lua
T actions
F cleanup
F convert
F finalize
F initialize
F outputfilename
F prepare
F wrapup
T flushers
F character
F popleaderlevel
F pushleaderlevel
F rule
F simplerule

```
    F specialrule
    F updatefontstate
    T whatsit
  S name
T mpo
  T actions
    F finalize
    F initialize
  T flushers
    F character
    F popleaderlevel
    F pushleaderlevel
    F rule
    F simplerule
    F specialrule
    T whatsit
  S name
T mps
  T actions
    F cleanup
    F convert
    F finalize
    F initialize
    F outputfilename
    F prepare
    F wrapup
  T flushers
    F character
    F popleaderlevel
    F pushleaderlevel
    F rule
    F simplerule
    F specialrule
    F updatefontstate
    T whatsit
  S name
T none
  T actions
  T flushers
    F popleaderlevel
    F pushleaderlevel
    T whatsit
  S name
T pdf
  T actions
    F cleanup
    F convert
    F finalize
    F initialize
    F outputfilename
    F prepare
    F wrapup
  T flushers
    F character
    F flushimage
    F fontchar
    F group
    F literal
    F popgroup
    F popleaderlevel
    F poporientation
    F pushgroup
    F pushleaderlevel
    F pushorientation
    F restore
    F rule
    F save
    F setmatrix
    F setstate
    F simplerule
    F space
    F specialrule
    F startclipping
    F startmatrix
    F startmirroring
    F startrotation
    F startscaling
    F stopclipping
    F stopmatrix
    F stopmirroring
    F stoprotation
    F stopscaling
    F updatefontstate
    T whatsit
  S name
```

lmtxversion number
outputfilename function
report function

effects (context)

brownianmotion	function	**perlinmotion**	function
browniannoise	function	**perlinnoise**	function
getoctaveloops	function	**simplexangle**	function
getoctavemethods	function	**simplexdetail**	function
getoctavestatus	function	**simplexnoise**	function
getoctavevariants	function	**stepoctave**	function
newoctave	function	**worleybounds**	function
octave	function	**worleymotion**	function
octavebytemap	function	**worleynoise**	function

environment (context)

argument	function	**luafilechunk**	function
arguments	data table	**luatexengine**	string
basicengines	data table	**luatexfunctionality**	number
currentrun	number	**luatexverbose**	string
definefilefallback	function	**luatexversion**	number
definefilesynonym	function	**maxnofruns**	number
engineflags	data table	**oldhome**	string
filename	string	**originalarguments**	data table
filenames	table	**outputfilename**	string
files	table	**ownbin**	string
filesynonyms	data table	**ownmain**	string
forcedruns	number	**ownname**	string
getargument	function	**ownpath**	string
globfiles	function	**prerollrun**	boolean
homedir	string	**rawarguments**	data table
initex	boolean	**reconstructcommandline**	function
initexmode	boolean	**relativepath**	function
initializearguments	function	**setargument**	function
initializefilenames	function	**splitarguments**	function
inputfilebarename	string	**suffix**	string
inputfilename	string	**texfile**	function
inputfilesuffix	string	**texmfos**	string
jobfilefullname	string	**texos**	string
jobfilename	string	**texroot**	string
jobfilesuffix	string	**truefilename**	function
kindofrun	number	**useluamodule**	function
lmtxmode	number	**usemodules**	function
loadexamodes	function	**validengines**	data table
loadluafile	function	**version**	string
luafile	function		

experiments (context)

data	data table	**report**	function
default	function	**reset**	function
disable	function	**set**	function
enable	function	**show**	function
list	function	**value**	function
name	string	**values**	function
register	function		

figures (context)

applyratio function
badname function
bases data table
bitmapimage function
boxnumber number
bytepalette function
cachepaths data table
check function
checkers data table
conversions data table
converters data table
current function
defaultdepth number
defaultheight number
defaultsearch boolean
defaultwidth number
done function
dummy function
existers data table
exists function
formats data table
found data table
get function
getinfo function
getpdfinfo function
getrealpage function
guess function
guessfromstring function
hash function
identifiers data table
identify function
images table
- F check
- F checksize
- F copy
- F create
- F embed
- F embedfromstore
- F fetchdata
- T keys
- F print
- F resetdata
- F resetstore
- F scan
- F serialize
- T sizes
  - B art
  - B bleed
  - B crop
  - B media
  - B none
  - B trim
- F storedata
- F totable
- T types
  - N jbig2
  - N jp2
  - N jpg
  - N none
  - N pdf
  - N png
  - N stream
- F wrap

include function
includers data table
initialize function
loaded data table
localpaths data table
magics data table
mergegoodies function
nofmissing number
nofprocessed number
order data table
palettes table
paths data table
patterns data table
pop function
preferquality boolean
programs data table
push function
qrcode function
registerpattern function

registerresource	function	**setconversion**	function
registersuffix	function	**setlookups**	function
remappers	data table	**setorder**	function
resources	data table	**setpaths**	function
scale	function	**suffixes**	data table
set	function	**used**	data table

file (basic lua)

addsuffix	function	**needsupdating**	function
basename	function	**pathpart**	function
checksum	function	**readdata**	function
collapsepath	function	**removesuffix**	function
copy	function	**replacesuffix**	function
dirname	function	**reslash**	function
expandname	function	**robustname**	function
extname	function	**savechecksum**	function
is_qualified_path	function	**savedata**	function
is_readable	function	**size**	function
is_rootbased_path	function	**splitbase**	function
is_writable	function	**splitname**	function
isreadable	function	**splitpath**	function
iswritable	function	**suffix**	function
join	function	**suffixes**	function
joinpath	function	**suffixesonly**	function
loadchecksum	function	**suffixonly**	function
nameonly	function	**syncmtimes**	function
nametotable	function	**withinbase**	function
needs_updating	function		

fio (extra lua)

getposition	function	**readinteger1le**	function
read2dot14	function	**readinteger2**	function
readbytes	function	**readinteger2le**	function
readbytetable	function	**readinteger3**	function
readcardinal1	function	**readinteger3le**	function
readcardinal1le	function	**readinteger4**	function
readcardinal2	function	**readinteger4le**	function
readcardinal2le	function	**readintegertable**	function
readcardinal3	function	**setposition**	function
readcardinal3le	function	**skipposition**	function
readcardinal4	function	**writecardinal1**	function
readcardinal4le	function	**writecardinal1le**	function
readcardinaltable	function	**writecardinal2**	function
readcline	function	**writecardinal2le**	function
readcstring	function	**writecardinal3**	function
readdouble	function	**writecardinal3le**	function
readdoublele	function	**writecardinal4**	function
readfixed2	function	**writecardinal4le**	function
readfixed4	function	**writedouble**	function
readfloat	function	**writedoublele**	function
readfloatle	function	**writefloat**	function
readinteger1	function	**writefloatle**	function

floats (context)

analysemethod	function	**nofstacked**	function
checkedpagefloat	function	**pop**	function
collect	function	**push**	function
consult	function	**resave**	function
flush	function	**save**	function
getvariable	function	**stacked**	function
hasstacked	function		

font (basic tex)

addcharacters	function	**getmathspec**	function
addquality	function	**getparameterfields**	function
current	function	**gettextcharacterfields**	function
define	function	**id**	function
getfont	function	**max**	function
getfontdimen	function	**nextid**	function
getfontfields	function	**setfont**	function
getfontspec	function	**setfontdimen**	function
getmathcharacterfields	function	**xscaled**	function
getmathindex	function	**yscaled**	function

fonts (context)

analyzers table
- D features
- D initializers
- D methods
- F setstate
- D states
- B useunicodemarks

callbacks table
- F compile
- F devirtualize

checkers table
- F getmissing
- D mapping
- F missing
- F placeholder

cid table
- F getmap
- F loadfile

collections table
- F checkenabled
- F clonevector
- F define
- T definitions
- F direct
- F found
- F prepare
- F process
- F register
- F registermain
- F report
- F reset
- T rscales
- T vectors

constructors table
- F addcharacters
- F addcoreunicodes
- F aftercopyingcharacters
- F applyfinalizers
- F applymanipulators
- F assignmathparameters
- F beforecopyingcharacters
- F beforepassingfonttotex
- D cache
- F calculatescale
- F checkedfeatures
- F checkedfilename
- F collectprocessors
- F currentfonthasfeature
- D designsizes
- F enhanceparameters
- T enhancers
  - T afm
    - F apply
    - F patch
    - T patches
      - F register
      - F report
    - F register
    - F report
  - T otf
    - F addfeature
    - F apply
    - F enhance
    - F patch
    - T patches
      - F register
      - F report
    - F register
    - F report
  - T tfm
    - F apply
    - F patch
    - T patches
      - F register
      - F report
    - F register
    - F report
- N factor
- T features
  - D afm
  - D otf
  - D tfm

```
F finalize
F getfeatureaction
F getmathparameter
F getprivate
T handlers
  T afm
    B autoprefixed
    D cache
    D features
    F getkern
    T helpdata
      D bothkerned
      D leftkerned
      D ligatures
      D rightkerned
      D texligatures
    F load
    T readers
      F getinfo
      F loadfont
      F loadshapes
    F setfeatures
    B syncspace
    N version
  T otf
    F addfeature
    F basemodeinitializer
    D cache
    F collectlookups
    T coverup
      T actions
        F alternate
        F chainposition
        F chainsubstitution
        F kern
        F ligature
        F multiple
        F pair
        F single
        F substitution
      F register
      S stepkey
    F dataset
    F datasetpositionprocessor
    S defaultbasealternate
    S defaultnodealternate
    D features
    F featuresinitializer
    F featuresprocessor
    T fixers
    F getactualtext
    F getalternate
    F getgsub
    F getkern
    F getmultiple
    F getstreamhash
    F getsubstitution
    T handlers
      F ctx_camelcasing
      F devanagari_remove_joiners
      F devanagari_reorder_matras
      F devanagari_reorder_pre_base_reordering_consonants
      F devanagari_reorder_reph
      F gpos_context
      F gpos_contextchain
      F gpos_cursive
      F gpos_mark2base
      F gpos_mark2ligature
      F gpos_mark2mark
      F gpos_pair
      F gpos_single
      F gsub_alternate
      F gsub_context
      F gsub_contextchain
      F gsub_ligature
      F gsub_multiple
      F gsub_reversecontextchain
      F gsub_single
      F trigger_space_kerns
    T helpers
      F blockligatures
      F pardirstate
      F txtdirstate
    F load
    F loadoutlinedata
    F loadstreamdata
    F modeinitializer
    D mpscache
```

```
D pdfcache
F plugininitializer
F pluginprocessor
T plugins
  T text
D pngcache
B pngenabled
T readers
  F addunicodetable
  F avar
  F cbdt
  F cblc
  F cff
  F cff2
  T cffencoder
  F checkhash
  F cmap
  F colr
  F compact
  F condense
  F cpal
  F cvar
  F dsig
  F ebdt
  F eblc
  F ebsc
  F expand
  F extend
  F fvar
  F gasp
  F gdef
  F getcomponents
  F getinfo
  F glyf
  F gpos
  T gposhandlers
    F chainedcontext
    F context
    F cursive
    F extension
    F marktobase
    F marktoligature
    F marktomark
    F pair
    F single
  F gsub
  T gsubhandlers
    F alternate
    F chainedcontext
    F context
    F extension
    F ligature
    F multiple
    F reversechainedcontextsingle
    F single
  F gvar
  F head
  T helpers
    F axistofactors
    F cleanname
    F getaxisscale
    F getfactors
    F getscales
    F gotodatatable
    F normalizedaxis
    T normalizedaxishash
    F readdevice
    F readvariationdata
    F reportskippedtable
    F setvariabledata
  F hhea
  F hmtx
  F hvar
  F kern
  F loadfont
  F loadshapes
  F loca
  F math
  F maxp
  F mvar
  F name
  F os/2
  F pack
  F parsecharstrings
  F post
  F potracetocff
  F registerextender
  F rehash
```

F sbix
F stat
T streamreader
F close
F getposition
F getsize
F look
F open
F read2dot14
F readbyte
F readbytes
F readbytetable
F readcardinal
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable
F readchar
F readcline
F readcstring
F readfixed2
F readfixed4
F readinteger
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F readsignedbyte
F readstring
F readtag
F setposition
F size
F skip
F skiplong
F skipposition
F skipshort
F writebyte
F writecardinal1
F writecardinal1le
F writecardinal2
F writecardinal2le
F writecardinal3
F writecardinal3le
F writecardinal4
F writecardinal4le
F writeinteger1
F writeinteger1le
F writeinteger2
F writeinteger2le
F writeinteger3
F writeinteger3le
F writeinteger4
F writeinteger4le
F writestring
F stripredundant
F svg
N tableversion
F unifymissing
F unpack
F vhea
F vmtx
F vorg
F vvar
F woff2otf
F registerpalette
F registerplugin
F reorderlookups
F scriptandlanguage
F setdynamics
F setfeatures
T statistics
D usedfeatures
D svgcache
B svgenabled
T tables
D baselines
D features
D featuretypes

```
    D languages
    D scripts
  F texthandler
  T vectors
    T arab
      T gpos
        N curs
        N kern
        N mark
        N mkmk
      T gsub
        N calt
        N ccmp
        N cswh
        N dlig
        N fina
        N init
        N isol
        N liga
        N medi
        N mset
        N rclt
        N rlig
  N version
T pfb
  F filterencoding
  F filtermetadata
  F loadvector
  N version
T tfm
  D cache
  D features
  N maxnestingdepth
  N maxnestingsize
  T readers
    F loadpk
    F loadtfm
    F loadtfmvf
    F loadvf
    F pktopdf
    F potracedtopdf
    F showpk
  F reencode
  F setfeatures
    N version
  T vf
    T combinations
    F combine
    T combiner
      D commands
    D helpers
    D math
    D predefined
    N version
    D whatever
F hashfeatures
F hashinstance
T hashmethods
  F normal
  F virtual
F initializefeatures
D loadedfonts
N noffontsloaded
N nofsharedfonts
N nofsharedhashes
N nofsharedvectors
N privateoffset
D privateslots
F readanddefine
F registerfeature
F registerscriptset
F resetfeature
B resolvevirtualtoo
F scale
F scaled
F setfactor
F setfeature
F setmathparameter
F setname
B sharefonts
F trytosharefont
N version
current            function
currentid          function
definers           table
  F addlookup
  F analyze
  F applypostprocessors
```

F checkedmode
F checkedscript
S defaultlookup
F define
F getspecification
F internal
F loadfont
F makespecification
T methods
F install
D variants
F read
F register
F registered
F registerfallbackfont
F registersplit
F resetnullfont
F resolve
T resolvers
F file
F name
F spec

definetypeface function

dropins table

F clone
F getshape
F getshapes
F nextid
F provide
F registerglyph
F registerglyphs
F swap
F swapone

effects table

encodings table

T agl
D ctxcodes
D extras
D synonyms
D unicodes
D cache
F is_known
D known
F load
F make_unicode_vector
D math
N version

enhanceid function

expansions data table

formats data table

getalternate function

getindices function

getkern function

getmultiple function

getsubstitution function

getters table

T alternate
F opentype
T kern
F opentype
F type1
F type3
T multiple
F opentype
T substitution
F opentype

goodies table

D colorschemes
T data
T common-math.lfg
S author
S comment
S copyright
B initialized
T mathematics
T tweaks
T presets
F addmathkerns
F braille
F eulertocalligraphic
F fallbacks
F moderntocalligraphic
F moveintegrals
F moveitalics
F pagellaradical
F rsfstoscript
F rsfsuprighttoscript
F scripttocalligraphic

```
      F smalldigits
      F wipeanchors
      F wipeitalics
      F xitsarabic
  S name
  S version
T dejavu-math
  S author
  S comment
  S copyright
  B initialized
  T mathematics
    T alternates
      T dotless
        S comment
        S feature
        N value
    T bigslots
    T parameters
      N AccentBaseDepth
      N AccentTopShiftUp
      N DelimiterDisplayPercent
      N DelimiterDisplayShortfall
      N DelimiterPercent
      N DelimiterShortfall
      N DisplayOperatorMinHeight
      N FlattenedAccentTopShiftUp
      N FractionRuleThickness
      S PrimeBaselineDropMax
      S PrimeShiftUp
      S PrimeShiftUpCramped
      N SubscriptShiftDown
      S SubscriptShiftDownWithSuperscript
      N SuperscriptShiftUp
    T tweaks
      T aftercopying
  S name
  S version
T dejavu-text
  S author
  S comment
  S copyright
  T extensions
  B initialized
      S name
      S version
    D designsizes
    D filenames
    F getcompositions
    T list
    F load
    F prepare_features
    F register
    F registerpostprocessor
    F report
    T suffixes
handlers          table
hashes            table
    D characters
    D classes
    D csnames
    D descriptions
    D dynamics
    D emwidths
    D exheights
    D features
    D identifiers
    D italics
    D lastmathids
    D marks
    D mathparameters
    D modes
    D originals
    D parameters
    T processes
    D properties
    D quads
    D resources
    T setdynamics
    T shapes
    D spaces
    D spacings
    T streams
    D unicodes
    D unislots
    D variants
    D xheights
helpers           table
```

F addextraprivate
F addprivate
F appendcommands
F appendcommandtable
F checkflags
F checkmerge
F checksteps
F collectanchors
F combineglyphs
D commands
F composecharacters
F descriptiontoslot
F dimenfactor
F expandglyph
D extraprivates
F fontpatternhassize
F getcoloredglyphs
F getdigitwidth
F getinstancespec
F getparameters
F getprivatecharornode
F getprivatenode
F getprivates
F getprivateslot
F glyphdimenfactor
F hasprivate
F indextoslot
F isprivate
F mathscriptslots
F name
F nametoslot
F newprivateslot
F prependcommands
F prependcommandtable
F privateslot
F registerglyphbox
F scalecommands
F setboxdirectly
F setboxglyph
F setboxglyphs
F setdigitwidth
F setmetaglyph
F setmetaglyphs
D sharedprivates
F splitfontpattern
F tochar
T vfinjectors
F startcolor
F stopcolor
T vfspecials
T backgrounds
T outlines

infofont function

iterators table

F characters
F descriptions
F glyphs

loggers table

F format
F onetimemessage
F register
F reportdefinedfonts
F reportusedfeatures

mappings table

F addtounicode
F fromunicode16
F getentry
F loadfile
F loadline
F makenameparser
D overloads
F reset
F tounicode

metapost table

F baseline
F boundingbox
F boxtomp
F boxtompdimensions
F boxtompposition
F draw
F fill
F glyph
F maxbounds
F paths
F widthline
F zeroline

mode function

names data table

nulldata data table
privateoffsets table
B keepnames
N mathbase
N mathextrabase
N textbase
N textextrabase
protrusions data table
readers table
F afm
F check_lua
F check_tfm
F lua
F ofm
F opentype
F otf
F pfb
D sequence
F tfm
F ttc
F ttf
F woff
F woff2
registersanitizer function
reserveid function
select table
D alternatives
F bodyfont
D data
F default
D defaults
F definefallbackfamily
F definefontfamily
F definefontfamilypreset
D extras
F fallback
D fallbacks
F features
F filefallback
F fontdata
F fontfallback
F fontsynonym
F goodies
F mathfallback
D methods
D presets
F registerfallback
F registerfiles
F registerfontalternative
F registerfontfamily
F textfallback
F typeface
F typescript
F userdata
specifiers table
D contextmerged
F contextnumber
D contextnumbers
D contextsetups
F contexttostring
F definecontext
F mergecontext
F presetcontext
F registercontext
T scriptsets
T af
S language
N number
S script
T always
S autolanguage
S autoscript
B checkmissing
B compoundhyphen
B curs
B kern
B mark
B mkmk
S mode
N number
S script
S textcontrol
B wipemath
T arabic
B analyze
S autolanguage
S autoscript
B calt

```
  B ccmp
  B clig
  B curs
  B dlig
  B fina
  B init
  B isol
  B kern
  S language
  B liga
  B mark
  B medi
  B mkmk
  S mode
  N number
  B rlig
  S script
T ba
  S language
  N number
  S script
T bandw:overlay
  B ccmp
  B dist
  N number
T bengali-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B init
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B pstf
  B psts
  B rphf
  S script
  B vatu
T bengali-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B init
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B pstf
  B psts
  B rphf
  S script
  B vatu
T boldened
  S effect
  N number
T boldened-10
  S effect
  N number
T boldened-15
  S effect
  N number
T boldened-20
  S effect
```

```
  N number
T boldened-25
  S effect
  N number
T boldened-30
  S effect
  N number
T ca
  S language
  N number
  S script
T camelcasing
  B camelcasing
  N number
T cn
  S language
  N number
  S script
T color
  B ccmp
  S color
  B dist
  N number
T color:bitmap
  B ccmp
  B dist
  N number
  B sbix
T color:overlay
  B ccmp
  B colr
  B dist
  N number
T color:svg
  B ccmp
  B dist
  N number
  B svg
T complete
  S autolanguage
  S autoscript
  B checkmissing
  B compose
  B compoundhyphen
  B curs
  B kern
  B liga
  B mark
  B mkmk
  S mode
  N number
  S script
  S textcontrol
  B wipemath
T cy
  S language
  N number
  S script
T cz
  S language
  N number
  S script
T de
  S language
  N number
  S script
T default
  S autolanguage
  S autoscript
  B checkmissing
  B compoundhyphen
  B curs
  B itlc
  B kern
  B liga
  B mark
  B mkmk
  S mode
  N number
  B rvrn
  S script
  S textcontrol
  B wipemath
T deo
  S language
  N number
  S script
T devanagari-one
```

```
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B psts
  B rkrf
  B rphf
  S script
  B vatu
T devanagari-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B psts
  B rkrf
  B rphf
  S script
  B vatu
T dingbats
  S goodies
  S mode
  N number
  B unicoding
T es
  S language
  N number
  S script
T et
  S language
  N number
  S script
T f:fractions
  B frac
  N number
T f:inferiors
  N number
  B subs
T f:kern
  B kern
  N number
T f:kerns
  B kern
  N number
T f:oldstyle
  N number
  B onum
T f:smallcaps
  N number
  B smcp
T f:superiors
  N number
  B sups
T f:tabular
  N number
  B tnum
T fi
  S language
```

```
  N number
  S script
T followtext
  B liga
  N number
T fr
  S language
  N number
  S script
T fullprotrusion
  N number
  S protrusion
T gr
  S language
  N number
  S script
T grek
  N number
  S script
T gujarati-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B psts
  B rkrf
  B rphf
  S script
  B vatu
T gujarati-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B psts
  B rkrf
  B rphf
  S script
  B vatu
T gurmukhi-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
```

```
  B pres
  B pstf
  B psts
  B rphf
  S script
  B vatu
T gurmukhi-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B pstf
  B psts
  B rphf
  S script
  B vatu
T hebrew
  B analyze
  S autolanguage
  S autoscript
  B calt
  B ccmp
  B clig
  B curs
  B dlig
  B fina
  B init
  B isol
  B kern
  S language
  B liga
  B mark
  B medi
  B mkmk
  S mode
  N number
  B reordercombining
  B rlig
  S script
T hr
  S language
  N number
  S script
T hu
  S language
  N number
  S script
T indic-common
  B abvm
  B abvs
  B akhn
  B blwm
  B blws
  B calt
  B dist
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B psts
  B rphf
T inlinenumbers
  N number
  B pnum
  B tnum
T is
  S language
  N number
```

```
  S script
T it
  S language
  N number
  S script
T ja
  S language
  N number
  S script
T jamoforms
  B ljmo
  N number
  B tjmo
  B vjmo
T just-os
  S mode
  N number
  B onum
T kannada-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B pstf
  B psts
  B rphf
  S script
T kannada-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B pstf
  B psts
  B rphf
  S script
T la
  S language
  N number
  S script
T latn
  N number
  S script
T letterspacing
  B ccmp
  B clig
  B dlig
  S keepligatures
  B liga
  N number
  B rlig
T ligatures
  S autolanguage
  S autoscript
  B checkmissing
  B compoundhyphen
```

```
  B curs
  B kern
  B liga
  B mark
  B mkmk
  S mode
  N number
  S script
  S textcontrol
  B wipemath
T lm-math-bold
  S effect
  N number
T lowercasing
  B lowercasing
  N number
T malayalam-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B pstf
  B psts
  B rphf
  S script
T malayalam-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B pstf
  B psts
  B rphf
  S script
T math
  B compactmath
  B flattenaccents
  B kern
  S language
  B mathalternates
  S mathexpansion
  S mode
  N number
  B rvrn
  S script
  B ssty
  B wipemath
T math-script
  B compactmath
  B flattenaccents
  B kern
  S language
  B mathalternates
  S mathexpansion
  S mode
  N number
```

```
  B rvrn
  S script
  N ssty
  B wipemath
T math-scriptscript
  B compactmath
  B flattenaccents
  B kern
  S language
  B mathalternates
  S mathexpansion
  S mode
  N number
  B rvrn
  S script
  N ssty
  B wipemath
T math-text
  B compactmath
  B flattenaccents
  B kern
  S language
  B mathalternates
  S mathexpansion
  S mode
  N number
  B rvrn
  S script
  B ssty
  B wipemath
T mathematics
  B compactmath
  B flattenaccents
  B kern
  S language
  B mathalternates
  S mathexpansion
  S mode
  N number
  S script
  B wipemath
T mixed
T mongolian
  S autolanguage
  S autoscript
  B calt
  B checkmissing
  B compoundhyphen
  B curs
  B fina
  B init
  B isol
  B itlc
  B kern
  B liga
  B mark
  B medi
  B mkmk
  S mode
  B mset
  N number
  B rclt
  B rlig
  B rvrn
  S script
  S textcontrol
  B wipemath
T nl
  S language
  N number
  S script
T none
  B features
  S mode
  N number
T oldstyle
  S autolanguage
  S autoscript
  B checkmissing
  B compoundhyphen
  B curs
  B kern
  B liga
  B mark
  B mkmk
  S mode
  N number
  B onum
```

```
  S script
  S textcontrol
  B wipemath
T oldstylenumbers
  N number
  B onum
T original
  S autolanguage
  S autoscript
  B checkmissing
  B compoundhyphen
  B curs
  B itlc
  B kern
  B liga
  B mark
  B mkmk
  S mode
  N number
  B rvrn
  S script
  S textcontrol
  B wipemath
T oriya-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B pstf
  B psts
  B rphf
  S script
T oriya-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pres
  B pstf
  B psts
  B rphf
  S script
T pl
  S language
  N number
  S script
T primes
  N number
  B primes
T pt
  S language
  N number
  S script
T quality
  S expansion
  N number
  S protrusion
T recommended
  S autolanguage
  S autoscript
  B calt
```

```
  B checkmissing
  B clig
  B compoundhyphen
  B curs
  B itlc
  B kern
  B liga
  B mark
  B mkmk
  S mode
  N number
  B rlig
  S script
  S textcontrol
  B wipemath
T reordercombining
  N number
  B reordercombining
T ro
  S language
  N number
  S script
T ru
  S language
  N number
  S script
T semitic-complete
  B analyze
  S autolanguage
  S autoscript
  B calt
  B ccmp
  B clig
  B curs
  B dlig
  B fina
  B init
  B isol
  B kern
  S language
  B liga
  B mark
  B medi
  B mkmk
  S mode
  N number
  B rlig
T semitic-simple
  B analyze
  S autolanguage
  S autoscript
  B calt
  B ccmp
  B curs
  B fina
  B init
  B isol
  B kern
  S language
  B mark
  B medi
  B mkmk
  S mode
  N number
  B rlig
T simplearabic
  B analyze
  S autolanguage
  S autoscript
  B calt
  B ccmp
  B curs
  B fina
  B init
  B isol
  B kern
  S language
  B mark
  B medi
  B mkmk
  S mode
  N number
  B rlig
  S script
T simplehebrew
  B analyze
  S autolanguage
  S autoscript
```

```
  B calt
  B ccmp
  B curs
  B fina
  B init
  B isol
  B kern
  S language
  B mark
  B medi
  B mkmk
  S mode
  N number
  B rlig
  S script
T sk
  S language
  N number
  S script
T sl
  S language
  N number
  S script
T slanted
  N number
  N slant
T smallcaps
  S autolanguage
  S autoscript
  B checkmissing
  B compoundhyphen
  B curs
  B kern
  B mark
  B mkmk
  S mode
  N number
  S script
  B smcp
  S textcontrol
  B wipemath
T sv
  S language
  N number
  S script
T syriac
  B analyze
  S autolanguage
  S autoscript
  B calt
  B ccmp
  B clig
  B curs
  B dlig
  B fin2
  B fin3
  B fina
  B init
  B isol
  B kern
  S language
  B liga
  B mark
  B med2
  B medi
  B mkmk
  S mode
  N number
  B rlig
  S script
T system:tabnum
  B lnum
  N number
  B tnum
T tabledigits
  N number
  B tabledigits
  B tnum
T tabularnumbers
  N number
  B pnum
  B tnum
T tamil-one
  B abvm
  B abvs
  B akhn
  B blwm
  B blws
```

```
  B calt
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B psts
  B rphf
  S script
T tamil-two
  B abvm
  B abvs
  B akhn
  B blwm
  B blws
  B calt
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B psts
  B rphf
  S script
T telugu-one
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B pstf
  B psts
  B rphf
  S script
T telugu-two
  B abvm
  B abvs
  B akhn
  B blwf
  B blwm
  B blws
  B calt
  B cjct
  B dist
  B half
  B haln
  S indic
  B kern
  S language
  B locl
  S mode
  B nukt
  N number
  B pref
  B pres
  B pstf
  B psts
  B rphf
  S script
```

```
T th
  S language
  N number
  S script
T tibetan
  B abvm
  B abvs
  S autolanguage
  S autoscript
  B blwm
  B blws
  B calt
  B ccmp
  B checkmissing
  B compoundhyphen
  B curs
  B kern
  S language
  B liga
  B locl
  B mark
  B mkmk
  S mode
  N number
  S script
  S textcontrol
  B wipemath
T tr
  S language
  N number
  S script
T uk
  S language
  N number
  S script
T uppercasing
  N number
  B uppercasing
T us
  S language
  N number
  S script
T virtualmath
  B compactmath
  B flattenaccents
  B kern
  S language
  B mathalternates
  S mathexpansion
  S mode
  N number
  S script
  B wipemath
T vn
  S language
  N number
  S script
T zero
  N number
  B zero
F showcontext
F splitcontext
D synonyms
D variants
symbols            table
T emoji
  F checked
  F resolved
F uselibrary
tables             table
toeffect           function
tracers            table
treatments         table
F applyfixes
D data
S filename
F ignoredfile
F report
F trace
typefaces          table
```

functions (context)

dummy function

globaldata (context)

CONTEXTLMTXMODE number
JITSUPPORTED boolean
LUAFORMAT number
LUAMAJORVERSION number
LUAMINORVERSION number
LUATEXENGINE string
LUATEXFORMATID number
LUATEXFUNCTIONALITY number
LUATEXVERBOSE string
LUATEXVERSION number
LUAVERSION number
MP function
SAVEDREQUIRE function
aes table
- F decode
- F encode
- F random

arg table
assert function
attributes table
- T alternates
  - N attribute
  - D data
  - F enable
  - F handler
  - F register
  - D registered
  - D values
- F applyoverloads
- F checkvalues
- T colorintents
  - N attribute
  - D data
  - F enable
  - F handler
  - F register
  - D registered
- T colors
  - N attribute
  - F cmyk
  - F cmyktogray
  - F cmyktorgb
  - F colorcomponents
  - D counts
  - B couple
  - F currentmodel
  - F currentnamedmodel
  - D data
  - N default
  - F defineintermediatecolor
  - F definemultitonecolor
  - F defineprocesscolor
  - F defineprocesscolordirect
  - F definesimplegray
  - F definespotcolor
  - F definetransparency
  - F enable
  - F filter
  - N forced
  - F forcedmodel
  - F forcesupport
  - F formatcolor
  - F formatgray
  - F formatluminance
  - F formatluminanceratio
  - F getpagecolormodel
  - F gray
  - F graytohsv
  - F handler
  - F hsvtogray
  - F hsvtorgb
  - F hwbtorgb
  - F iccprofile
  - F isblack
  - F labtolch
  - F labtorgb
  - F labtoxyz
  - F lchtolab
  - F lchtorgb
  - N main
  - S model
  - D models

```
  F mpcolor
  F mpnamedcolor
  F mpoptions
  F mprgbcolor
  F namedcolorattributes
  N none
  F popset
  F processcolorcomponents
  F pushset
  F register
  D registered
  F registerspotcolor
  F rgb
  F rgbbytes
  F rgbtocmyk
  F rgbtogray
  F rgbtohsv
  F rgbtoxyz
  N selector
  F setlist
  F setmodel
  F setpagecolormodel
  D sets
  F spec
  F spot
  F spotcolorname
  F spotcolorparent
  F spotcolorvalue
  B supported
  F toattributes
  F transparencycomponents
  B triggering
  F usecolors
  D valid
  F value
  D values
  B weightgray
  F xyztolab
  F xyztorgb
D counts
F define
T effects
  N attribute
  D data
  F enable
  F handler
  F register
  D registered
  D values
F getvalue
F getvalues
T handlers
F hasvalues
D list
F markasoverload
D names
T negatives
  N attribute
  D data
  F enable
  F handler
  F register
  D registered
  F set
D numbers
F ofnode
F private
F public
F registervalue
F restore
F save
F setcleaner
F showcurrent
T states
  F finalize
  F initialize
  F process
  F selective
  F simple
  F stacked
  F stacker
F system
F tooverloads
T transparencies
  N attribute
  D data
  F enable
  F forcesupport
```

F handler
N none
F register
D registered
B supported
F toattribute
B triggering
F value
D values
N unsetvalue
D values
T viewerlayers
N attribute
F cleanup
D data
F define
F definedlayoutcomponent
F enable
F forcesupport
F handler
B hasorder
D listwise
F register
D registered
F resolve_begin
F resolve_end
F resolve_reset
F resolve_step
D scopes
F setfeatures
F setup
F start
F stop
B supported
D values

backends table

F closeout
T codeinjections
F registerboxresource
F registerfont
F restoreboxresource
S current
T defaults
D tables
F getcallbackstate
T included
B context
B date
B id
B metadata
B pdf
F initialize
F latelua
T nodeinjections
F nothing
F openout
T registered
T registrations
F setencryption
T tables
F writeout

basexx table

F decode16
F decode64
F decode85
F decodeLZW
F decodeRL
F encode16
F encode64
F encode85
F encodeLZW
F encodeRL

bibtex table

bit32 table

F arshift
F band
F bnot
F bor
F btest
F bxor
F extract
F lrotate
F lshift
F replace
F rrotate
F rshift

bitset table

F assign

F asstring
F band
F bnot
F bor
F bxor
F get
F len
F new
F newonebased
F newzerobased
F reset
F set
F shl
F shr
F tostring
F totable
F traverse
F wipe

blobs table

F append
F dimensions
F dispose
F new
F pack
F strdp
F strhd
F strht
F strwd
F tohpack
F tonodes
F tovpack
F write

boolean table

F tocontext
F tonumber

buffers table

F append
F assign
F collectcontent
F empty
F erase
F exists
F get
F getcontent
F getctxlua
F getlines
F getmkvi
F gettex
F loadcontent
T parallel
  F define
  F hassomecontent
  F next
  F place
  F reset
  F save
F prepend
F raw
F run
F samplefile
F splitsamplefile
F undent

builders table

F checkparcontext
F checksidefloat
T hpack
  F qualityactions
  F report
  F show
T kernel
  F collapsing
  F hyphenating
  F kerning
  F ligaturing
  F mlisttohlist
T paragraphs
  F keeptogether
  F registertogether
  F tag
F parpassidentifier
D passnames
T profiling
  F add
  F addrivers
  F boxlinehandler
  F distance
  F fixedprofile
  F get

F getrivers
F list
F pagehandler
F pagelinehandler
F profilebox
F profilelines
F set
F setlines
F registerpaspasscallback
T vpack
F qualityactions
F report
T vspacing
D categories
F checkstrutdepth
F collapsevbox
F definesnapmethod
B fixed
F flushcontributions
F forcepageflush
F forcestrutdepth
F getnofpreviouslines
F inject
F injectdisable
F injectnowhite
F injectpenalty
F injectskip
F interceptsamepagecontent
F pagehandler
F pageoverflow
F popatsame
F pushatsame
F setmap
F setskip
F snapbox
F synchronizepage
F tocategories
F tocategory
F vboxhandler

bytemap table

F bounds
F clip
F copy
F dimensions
F domain
F downgrade
F downsample
F fillgray
F fillrgb
F filter
F getbyte
F getbytes
F getluminance
F getvalue
F hasbytegray
F hasbyterange
F hasbytergb
F new
F newdomain
F overlay
F process
F reduce
F reset
F setgray
F setgrayadd
F setgraymin
F setrgb
F slicegray
F slicerange
F slicergb
F totable

caches table

S base
F collapsecontent
F configfiles
F contentstate
T defaults
F getfirstreadablefile
F getreadablepaths
F getwritablepath
F hashed
F is_writable
F loadcontent
F loaddata
S more
F savecontent
F savedata
F setfirstwritablefile

F setluanames
F treehash
F usedpaths

callback table

F find
F getcontracts
F getcontractvalues
F getindex
F getoptions
F getoptionvalues
F getstate
F getstatevalues
F known
F list
F names
F register
F setoptions
F setstate
F testonly
F usage

callbacks table

F freeze
T functions
F start_page_number
F stop_page_number
F getcomment
F getstates
F known
T list
N alignment
N append_adjust
N append_line
N append_migrate
N append_to_vlist
N balance_boundary
N balance_check
N balance_insert
N begin_paragraph
N buildpage
N define_font
N find_format_file
N find_log_file
N get_attribute
N get_math_dictionary
N get_noad_class
N glyph_run
N handle_overload
N handle_uinsert
N handle_uleader
N hpack
N hpack_quality
N hyphenate
N insert_boundary
N insert_check_split
N insert_distance
N insert_par
N intercept_lua_error
N intercept_tex_error
N italic_correction
N kerning
N ligaturing
N linebreak
N linebreak_check
N linebreak_quality
N local_box
N make_extensible
N math_rule
N missing_character
N mlist_to_hlist
N open_data_file
N packed_vbox
N page_boundary
N paragraph_context
N paragraph_pass
N post_linebreak
N pre_dump
N pre_linebreak
N pre_output
N process_character
N process_jobname
N quality_font
N register_extensible
N show_build
N show_error_message
N show_loners
N show_lua_call
N show_vsplit
N show_warning_message

N show_whatsit
N start_file
N start_run
N stop_file
N stop_run
N tail_append
N test_only
N trace_memory
N vpack
N vpack_quality
N wrapup_run
T names
F optimizer
T optionbits
T optioncodes
N direct
N trace
F pop
F push
F register
F report
T statebits
T statecodes
N disabled
N frozen
N fundamental
N private
N selective
N set
N touched
N tracing

catcodes table
D names
D numbers
F register

characterkern function

characters table
F addcharacternames
F adobename
D bidi
F blockrange
D blocks
D can_have_space
T casemap
D categories
F category
D categorytags
T classifiers
D collapsed
D combined
F contextname
D csletters
D data
D decomposed
F description
D descriptions
D detailtags
T directions
T emoji
F compact
F known
F resolve
F emojized
D enccodes
D entities
D fallbacks
D filters
T fractions
F fromnumber
D fschars
D fscodes
F getrange
D graphemes
D hangul
T indicgroups
F initialize
D is_character
D is_command
D is_hyphenator
D is_letter
D is_mark
D is_nothing
D is_punctuation
D is_spacing
D is_symbol
D lcchars
F lccode
D lccodes

F lettered
D lhash
D linebreaks
F lower
D mathlists
T mirrors
D otfscripts
T packdata
N luasize
N newsize
N oldsize
N version
D ranges
F registerentities
F remap_hangul_syllabe
T scripthash
F setactivecatcodes
F setlettercatcodes
F setothercatcodes
F shape
F shaped
D shash
D shchars
D shcodes
F showstring
D specialchars
D specials
T splits
T subscripts
T superscripts
D synonyms
T tex
D accentmapping
D commandmapping
F defineaccents
F safechar
F strtextoutf
F strtoutfpattern
F toutf
F toutfpattern
T textclasses
F tonumber
D ucchars
F uccode
D uccodes
D uhash
F unicodechar
F upper
D verbosemarks

chemistry table
F component
F define
D definitions
S format
F inlinechemical
S instance
S method
F molecule
U moleculeparser
F start
F stop
T syntax
F undefine

client table
F httprequest
F supported

collectgarbage function

commands table
F Alphabetic
F MPLIBconvertfollowtext
F MPLIBconvertoutlinetext
F MPc
F MPd
F MPfromhash
F MPh
F MPll
F MPlr
F MPls
F MPn
F MPp
F MPpardata
F MPplus
F MPpos
F MPr
F MPrest
F MPrs
F MPul
F MPur

F MPw
F MPwhd
F MPx
F MPxy
F MPxywhd
F MPy
F Romannumerals
F actualday
F actualmonth
F actualyear
F adaptfontfeature
F adaptivecheckbox
F addbtxentry
F addcounter
F adddefaultsuffix
F addfeature
F addfontpath
F addgrapheme
F addlinenumbers
F addlinklistelement
F addreplacements
F addreplacementslist
F addrivers
F addtocolumnset
F addtocolumnsetmvl
F addtojavascriptpreamble
F addtolist
F align_point_delta
F allinputpaths
F alphabetic
F analysefloatmethod
F analyzeitemgroup
F analyzelist
F analyzelocalanchors
F analyzeregister
F analyzerotate
F analyzeupcomingitemgroup
F applypattern
F applytobox
F applytofirstcharacter
F arraycompare
F arrayequals
F arraymaxvalue
F arrayminvalue
F arraysize
F arrayvalue
F ascender
F askedreference
F assignbuffer
F async
F attachinsertion
F attachinsertions
F atwordboundary
F autofinishstructurelevels
F autoinsertnextspace
F automigrationcodestring
F autonextstructurelevel
F autorule
F autosetups
F autostarttext
F autostoptext
F badnessmodecodestring
F balanceshapeextra
F benchmarktimer
F bf
F bi
F bitmapimage
F bitwise
F bitwiseand
F bitwiseflip
F bitwisenil
F bitwisenot
F bitwiseor
F bitwiseset
F bitwiseshift
F bitwisexor
F blockcolumnset
F blockligatures
F boolcase
F boxdir
F boxline
F boxlinedp
F boxlineht
F boxlineil
F boxlinein
F boxlineir
F boxlinelh
F boxlinelp

F boxlinels
F boxlinemaxdp
F boxlinemaxht
F boxlinemaxwd
F boxlinend
F boxlinenh
F boxlinenw
F boxlinerh
F boxlinerp
F boxliners
F boxlines
F boxlinewd
F boxoptioncodestring
F boxrangedp
F boxrangeht
F boxrangewd
F boxtostring
F bposcolumn
F bposcolumnregistered
F bs
F btxabbreviatedjournal
F btxaddentry
F btxaddjournal
F btxauthor
F btxauthorfield
F btxauthortoregister
F btxcmdstring
F btxcollectlistentries
F btxcurrentfirstnames
F btxcurrentinitials
F btxcurrentjuniors
F btxcurrentsurnames
F btxcurrentvons
F btxdetail
F btxdirect
F btxdoif
F btxdoifelse
F btxdoifelsecitedone
F btxdoifelsecombiinlist
F btxdoifelsematches
F btxdoifelsesameasprevious
F btxdoifelseuservariable
F btxdoifnot
F btxentrytobuffer
F btxentrytostring
F btxexpandedjournal
F btxfetchlistentries
F btxfield
F btxfirstofrange
F btxflush
F btxflushlistcombi
F btxflushlistentry
F btxflushlisttag
F btxflushmarked
F btxflushpages
F btxhandlecite
F btxhandlenocite
F btxlastofrange
F btxlistvariant
F btxloaddefinitionfile
F btxloadjournallist
F btxloadreplacementfile
F btxmissing
F btxoneorrange
F btxpreparelistentries
F btxremapauthor
F btxsavedataset
F btxsavejournallist
F btxsetdataset
F btxsetentry
F btxsetregister
F btxsetspecification
F btxshortcut
F btxshowauthorremapping
F btxsingularorplural
F btxtoregister
F btxusedataset
F btxuservariable
F build_page_after_shipout
F build_page_before_shipout
F build_page_setup
F capheight
F charactercontrolcodestring
F chardescription
F checkcolumnset
F checkcolumnsetmvl
F checkcountersetup
F checkedconversion

F checkedemoji
F checkedpagefloat
F checkinjector
F checkinterfacechain
F checkmarkedpages
F checknesting
F checkspacingavailable
F checkstrutdepth
F chemicalcomponent
F chinesenumerals
F chr
F classoptioncodestring
F cleancolumnset
F cleanfontname
F cleanupattributes
F cleanupbox
F cleanuplayers
F clonefield
F closein
F closeout
F codedef
F collectedmath
F collectfloat
F collecthelp
F columnsetbalancefirst
F columnsetbalancelast
F columnsetbalancepage
F columnsetcolumnwidth
F columnsetdisablewide
F columnsetenablewide
F columnsetgoto
F columnsethascontent
F columnsethspan
F columnsetlastfuture
F columnsetlastmvl
F columnsetlimit
F columnsetnoto
F columnsetresetdirect
F columnsetresetshapeextra
F columnsetreshape
F columnsetsblockrows
F columnsetsetshapeextra
F columnsetshape
F columnsetshapebalancecheck
F columnsetshapebalanceextend
F columnsetshapecolumn
F columnsetshapecount
F columnsetshapeindex
F columnsetshapepage
F columnsetshapesetbalancerange
F columnsetshapeslots
F columnsetshapespread
F columnsetshapevsize
F columnsetshapeworst
F columnsetshowgrid
F columnsetshowshape
F columnsetshowtracedgrid
F columnsetstate
F columnsetstatus
F combineglyphs
F component
F concatcommalist
F consultfloat
F continueifinputfile
F convertbtxdatasettoxml
F converteddimen
F convertmpstopdf
F copyboxfromcache
F copyboxline
F copyposition
F cos
F cosd
F ctxfunction
F ctxluamatch
F ctxluamatchfile
F ctxresetter
F ctxscanner
F currentcomponent
F currentdate
F currentdesignsize
F currentenvironment
F currentfontinstancespec
F currentposthyphenchar
F currentprehyphenchar
F currentproduct
F currentproject
F currentsectiontolist
F datasetsize

F datasetvariable
F day
F daymnem
F dayname
F decimals
F decrementcounter
F decrementsubcounter
F deferredenhancelist
F deferredenhancereference
F deferredenhanceregister
F defineaccents
F defineattribute
F defineboundary
F definebreakpoint
F definebreakpoints
F definecharacterspacing
F definechemical
F definecolumnset
F defineconversion
F definecounter
F definedlayoutcomponent
F definefallbackfamily
F definefield
F definefieldset
F definefilefallback
F definefilesynonym
F definefont_one
F definefont_two
F definefontcolorpalette
F definefontfamily
F definefontfamilypreset
F definefontfeature
F definefontscriptset
F definefontsolution
F definehyphenationfeatures
F defineinsertion
F defineintermediatecolor
F definelabcolorglobal
F definelabcolorlocal
F definelabels
F definelanguage
F definelinkedlist
F definemathpreset
F definemultitonecolorglobal
F definenamespace
F definenote
F defineparallel
F defineparbuilder
F defineprocesscolordummy
F defineprocesscolorglobal
F defineprocesscolorlocal
F defineprogram
F definereference
F defineregister
F definesectionlevels
F definespotcolorglobal
F definestructureblock
F definestructureset
F definesubcolumnset
F definetransparency
F definetransparencyglobal
F definetypeface
F defineviewerlayer
F delayedcolumnsetsheet
F depthnumber
F depthofstring
F descender
F detachinsertions
F diagnostic
F digits_normal
F digits_reverse
F directboxfromcache
F disableautofontscript
F disablecollectingmath
F disabledirectives
F disableexperiments
F disablejobsave
F disableparbuilder
F disableregime
F disablespellchecking
F disablestream
F disabletrackers
F discardfromlist
F discoptioncodestring
F disposeboxesincache
F disposeluatable
F doanalyzeframedbox
F doif

F doifcounter
F doifelse
F doifelseblack
F doifelseboxincache
F doifelsebuffer
F doifelsebufferempty
F doifelsecharinfont
F doifelseconverter
F doifelsecounter
F doifelsecounteractive
F doifelsecurrentfonthasfeature
F doifelsedimenstring
F doifelsedrawingblack
F doifelsefieldcategory
F doifelsefieldset
F doifelsefiledefined
F doifelsefileexist
F doifelsefirstchar
F doifelsefirstsectionpage
F doifelsefontfeature
F doifelsefontpresent
F doifelseindented
F doifelseinelement
F doifelseinputfile
F doifelseleapyear
F doifelselisthasentry
F doifelselisthasnumber
F doifelselisthaspage
F doifelselisthastitle
F doifelsemarkedcontent
F doifelsemarkedpage
F doifelsemessage
F doifelsenoteonsamepage
F doifelseobjectfound
F doifelseobjectreferencefound
F doifelseolderversion
F doifelseoverlapping
F doifelseparallel
F doifelseparentfile
F doifelsepathexist
F doifelsependingpagecontent
F doifelseposition
F doifelsepositiononpage
F doifelsepositionsonsamepage
F doifelsepositionsonthispage
F doifelsepositionsused
F doifelserangeonpage
F doifelsereference
F doifelsereferencechecked
F doifelsereferenced
F doifelserighttoleftinbox
F doifelsesame
F doifelsesomething
F doifelsespaces
F doifelsestackedfloats
F doifelsestructureblocksempty
F doifelsesynonymshown
F doifelsesynonymused
F doifelsetaggednoteonsamepage
F doifelseurldefined
F doifelseutfmathaccent
F doifelseutfmathfiller
F doifelseutfmathlimop
F doifelsevalidhashedfiles
F doifelsevisualizer
F doifmarkedpage
F doifnot
F doifnotcounter
F doifnotecontent
F doifnotsame
F doifnotthing
F doifposition
F doifsame
F doifsomething
F doifunknownfontfeature
F domainattribute
F doreshapeframedbox
F doresyncframedbox
F dosaveposition
F dosavepositionplus
F dosavepositionwhd
F dosetposition
F dosetpositionbox
F dosetpositionplus
F dosetpositionstrut
F dosetpositionstrutkind
F dosetpositionwhd
F dostarttextfile

F dostoptextfile
F doublescriptmodecodestring
F droptablegroup
F elapsedsteptime
F elapsedtime
F embedimagefromstore
F enablealignmentcharacter
F enablealignskips
F enableasciimode
F enableautofences
F enableautofontscript
F enablebackgroundalign
F enablebackgroundboxes
F enablecollectingmath
F enablecolor
F enablecolorintents
F enablecrlf
F enabledirectives
F enabledriver
F enableexperiments
F enablefontcolorschemes
F enablehidecontent
F enablemathalignrelocate
F enablematrixornaments
F enablematrixrules
F enableparbuilder
F enableregime
F enablescriptunstacking
F enablesidefloatchecker
F enablespellchecking
F enablestacking
F enablestream
F enableswapping
F enabletighten
F enabletrackers
F enabletransparency
F enableutf
F enhancelinkedlist
F enhancelist
F enhanceregister
F enhancesynonym
F environment
F eposcolumn
F eposcolumnregistered
F erasebuffer
F execute
F exportbox
F exportformdata
F exportreferences
F expression
F extendregister
F extendregisterlate
F extensiblecode
F fakeword
F featureattribute
F feedback
F fetchlanguagetext
F fetchmultipar
F fetchposboxes
F fetchterminaldata
F figure_flush_registered_pages
F figure_mergegoodies
F figure_nof_registered_pages
F figure_register_page
F figuresetdimensions
F filebasename
F filedirname
F filenameonly
F filesuffix
F filterdefaultreference
F filterreference
F finalizeobjectbox
F finalizeshipoutbox
F findregisterinternal
F finishcolumnsetflush
F finishexport
F firstinset
F firstsectionpage
F firstsubcountervalue
F flagcodestring
F flushcolumnsetareas
F flushcolumnsetcolumn
F flushfloat
F flushlabeledfloat
F flushnoterange
F flushnotes
F flushpageblocks
F flushpageinjectionsafter

F flushpageinjectionsbefore
F flushpostponedblocks
F flushpostponednotes
F flushstream
F flushstreamcopy
F fontchar
F fontcharbyindex
F fontcollectionclone
F fontcollectiondefine
F fontcollectionprepare
F fontcollectionregister
F fontcollectionreport
F fontcollectionreset
F fontlookupgetkey
F fontlookupgetkeyofindex
F fontlookupinitialize
F fontlookupnoffound
F forceendjob
F forcepageflush
F forcequitjob
F forcestrutdepth
F format
F formatcolor
F formatgray
F formatluminance
F formatluminanceratio
F formatone
F framedoutline
F from
F frozenparcodestring
F frule
F getMPdata
F getbidimode
F getbodyfontsizes
F getboxcountfromcache
F getboxdpfromcache
F getboxfromcache
F getboxhtdpfromcache
F getboxhtfromcache
F getboxwdfromcache
F getbuffer
F getbuffercontent
F getbufferctxlua
F getbuffermkvi
F getbuffertex
F getcharactercasingcategory
F getclubpenalties
F getcurrentprefixspec
F getcurrentreferencelabel
F getcurrentreferencemetadata
F getdefaultfieldvalue
F getdisplaywidowpenalties
F getdocumentargument
F getdocumentfilename
F getfieldcategory
F getfile
F getfirstcharacter
F getfloatvariable
F getfromluatable
F getfullstructurenumber
F getinterlinepenalties
F getinternalcachedlistreference
F getinternallistreference
F getinternalorderreference
F getmathblobindex
F getmathblobmapping
F getmathcharone
F getmathchartwo
F getmathmathblob
F getmathtextblob
F getmathvariant
F getmessage
F getmpextensions
F getnaturaldimensions
F getnaturalwd
F getnofpreviouslines
F getnotestate
F getnotestorecount
F getnotestoreflushed
F getobjectdimensions
F getobjectreference
F getobjectreferencepage
F getparshape
F getparwrapper
F getprivatechar
F getprivateglyphslot
F getprivatemathchar
F getprivateslot

F getprogram
F getrandomdimen
F getrandomfloat
F getrandomnumber
F getrandomseed
F getreadfilename
F getreferencesectionnumber
F getrivers
F getsetupstring
F getshapeparameter
F getsomefullstructurenumber
F getsomestructurenumber
F getspecificstructuretitle
F getstructurelevel
F getstructurenumber
F getsubstring
F getsynchronizemarking
F geturl
F getvisual
F getwidowpenalties
F globalpopmacro
F globalpushmacro
F gluetolinesinbox
F glyphoptioncodestring
F gobblenested
F gotocolumnsetslot
F grabbuffer
F groupcodestring
F groupsetgroup
F grph_nodes_initialize
F grph_nodes_register
F grph_nodes_reset
F grph_nodes_resolve
F handlemathhang
F hboxtovbox
F heightofstring
F helpaction
F helpreference
F hour
F hpackbox
F hpackedbox
F hsplit
F hyphenateddigits
F hyphenatedlist
F hyphenationcodestring
F ic
F idxfromluatable
F if_common
F ifallmodes
F ifbitwiseand
F ifblobindexdone
F ifboxhaslist
F ifcommon
F ifeof
F ifgluelineinbox
F ifinset
F iflua
F ifmode
F ifmodes
F ifmvl
F ifpositunum
F ifsetups
F ifsystemmode
F iftext
F ifxml
F ifxmlatt
F ifxmlattempty
F ifxmlempty
F ifxmlselfempty
F ifxmltext
F ignorefile
F ignoretagsinexport
F immediatemessage
F includesvgbuffer
F includesvgfile
F incrementcounter
F incrementsubcounter
F inhibitprimitive
F initializeexport
F initializejob
F initializemathcollapsing
F initializemathfencing
F initializemathitalics
F initializemathkernpairs
F initializemathnumbers
F initializemathspacing
F initializestream
F initializetexdirectives

F initializetexexperiments
F initializetextrackers
F injectcurrentreference
F injectcurrentreferencehtdp
F injectdisable
F injectnowhite
F injectreference
F injectvpenalty
F injectvskip
F injectvspacing
F injectzerobaselineskip
F inlinechemical
F inputfilebarename
F inputfilename
F inputfilerealsuffix
F inputfilesuffix
F insertattachment
F insertcategorycodestring
F insertcomment
F insertfield
F insertionnumber
F insertoptioncodestring
F insertrenderingwindow
F inspectluatable
F installedlanguages
F installtexdirective
F installtexexperiment
F installtextracker
F interceptsamepagecontent
F it
F jobfilefullname
F jobfilename
F jobfilesuffix
F jobposd
F jobposh
F jobposp
F jobposw
F jobposx
F jobposy
F languagecharwidth
F languagenumber
F lastblobindex
F lastnodeequals
F lastnodeid
F lastnodeidstring
F lastnodesubtypestring
F lastparwrapper
F lastrpos
F lastsavedboxresourceindex
F lastsavedimageresourceindex
F lastsavedimageresourcepages
F lastsectionpage
F lastsubcountervalue
F lastunitstring
F lastxpos
F lastypos
F lateindent
F latelua
F lateundent
F lchexnumber
F lchexnumbers
F leapyear
F limitated
F linebuffering
F linedir
F lineprofilebox
F linesegment
F listanchorcodestring
F listbookmark
F listexternal
F listgroupindex
F listlabel
F listlocation
F listnamespaces
F listprefixednumber
F listprefixedpage
F listrawnumber
F listrawrealpage
F listrawuserpage
F listsigncodestring
F listsize
F listtitle
F listuserdata
F lmt_parameters_define
F lmt_parameters_preset
F lmt_parameters_reset
F loadcldfile
F loadcldfileonce

F loadexamodes
F loadfontgoodies
F loadlibrary
F loadluafile
F loadluafileonce
F loadluamodule
F loadmapfile
F loadmapline
F loadspellchecklist
F loadtexfile
F loadtexfileonce
F loadtypescriptfile
F loadvisualizer
F loadxmlfile
F loadxmlfileonce
F localanchorx
F localanchory
F localboxindent
F localboxindex
F localboxlefthang
F localboxleftoffset
F localboxleftskip
F localboxlinenumber
F localboxlinewidth
F localboxlocalwidth
F localboxmarkonce
F localboxovershoot
F localboxparfillleftskip
F localboxparfillrightskip
F localboxparinitleftskip
F localboxparinitrightskip
F localboxprogress
F localboxrighthang
F localboxrightoffset
F localboxrightskip
F localpopmacro
F localpushmacro
F locatefilepath
F loopcs
F loopcsn
F lousiness
F luacardinal
F luacount
F luadimen
F luaexpression
F luafloat
F luainteger
F luanumber
F luarandom
F luascript
F luathread
F lxmlid
F manipulated
F markblobindexdone
F markcontent
F markedpageparameter
F markedpages
F markingnumber
F markingtitle
F markinjector
F markpage
F markregionbox
F markregionboxcorrected
F markregionboxtagged
F markregionboxtaggedkind
F markregionboxtaggedn
F markvisualfonts
F mathclassvalue
F mathcontrolcodestring
F mathhorizontalcode
F mathoptioncodestring
F mathrenderset
F mathstrutcode
F mathvariantcode
F mathvariantcount
F mathvariantslot
F maxbufferwidth
F message
F metapostescaped
F metapostformatted
F metapostgraphformat
F minute
F mixcleanup
F mixfinalize
F mixflushlist
F mixflushrest
F mixgetsplit
F mixsetsplit

F mixstate
F modecodestring
F molecule
F month
F monthmnem
F monthname
F mpblobtext
F mpcolor
F mpgetblob
F mpgettext
F mpgraphic
F mpgraphictexttoks
F mpoptions
F mpoutlinetoks
F mppopvariables
F mppushvariables
F mprunset
F mpruntab
F mprunvar
F mpsetclippath
F mpsetoutercolor
F mpsetsxsy
F mpsettext
F mptexget
F mptexreset
F mptexset
F mptexsetfrombuffer
F mptexttoks
F mvloptioncodestring
F namedstructureuservariable
F namedstructurevariable
F naturalwd
F negatedcolorcomponent
F newarray
F newhashedtable
F newindexedtable
F newluatable
F newparwrapper
F newrepeatablerandom
F newstacking
F nextparallel
F nextsubcountervalue
F nodimen
F nofbufferlines
F nofconversions
F nofdays
F nofdetachedinsertions
F noflinesinbox
F nofmathvariants
F nofstackedfloats
F nologbuffering
F normalizecodestring
F normalizedbodyfontsize
F normalizeparcodestring
F nospacesmodecodestring
F notedeltapage
F noteinternal
F notelistindex
F noteprefixednumber
F notetitle
F ntb_split_section_check
F ntb_split_section_fetch
F ntb_split_section_locate
F ntb_split_section_reset
F ntimes
F number
F numbers
F objectreference
F objectreferencepage
F octnumber
F openin
F openout
F operatingsystem
F ordinal
F outputfilename
F overloadbookmark
F overloadlowercase
F overloadsattribute
F overloaduppercase
F pageblockrealpage
F pageofinternal
F pageoverflow
F pagestaterealpage
F pagestaterealpageorder
F paragraphfillmodecodestring
F paragraphoptioncodestring
F parcontextcodestring
F pardir

F parpasscallback
F parpassidentifier
F parpos
F partriggercodestring
F pdfbackendcurrentresources
F pdfbackendsetcatalog
F pdfbackendsetcolorspace
F pdfbackendsetextgstate
F pdfbackendsetinfo
F pdfbackendsetname
F pdfbackendsetpageattribute
F pdfbackendsetpageresource
F pdfbackendsetpagesattribute
F pdfbackendsetpattern
F pdfbackendsetshade
F pdfcolor
F pdfextension
F pdffeedback
F pdflastobj
F pdfliteral
F pdfobj
F pdfrefobj
F pdfsetuserdata
F pdfvariable
F percentageof
F pfabs
F pfacos
F pfacosh
F pfasin
F pfasinh
F pfatan
F pfatanh
F pfatantwo
F pfceil
F pfcos
F pfcosh
F pfdeg
F pfexp
F pffloor
F pflog
F pfmod
F pfpow
F pfrad
F pfrem
F pfround
F pfsin
F pfsinh
F pfsqrt
F pftan
F pftanh
F pgfxcolorspec
F pickupbuffer
F pickupmarkedcontent
F pickuppunctuation
F placeparallel
F popfloat
F pophyphenation
F poplist
F poplocalanchors
F poplogfile
F popparagraphtweak
F poppath
F poprandomseed
F popreferenceprefix
F popregime
F poprunstate
F popsectionblock
F positunum
F positunumdef
F postlistbox
F postlistcopy
F postponenotes
F prefixedconverted
F prelistbox
F prelistcopy
F preparecolumnsetflush
F prerolledpages
F presetcolumnsetsheets
F presetcolumnsetspreadsheets
F presetmathematics
F presetmathfontalternate
F presetsymbollist
F previoussubcountervalue
F privatecharacter
F privatecharactercode
F processbodyfontsizes
F processbuffer
F processcollectedmath

F processedfile
F processedfiles
F processfile
F processfilemany
F processfilenone
F processfileonce
F processjob
F processlist
F processregister
F processsplit
F processsynonyms
F product
F profilebox
F profilemacro
F project
F pruneboxesincache
F purefontname
F pushfloat
F pushhyphenation
F pushlist
F pushlocalanchors
F pushlogfile
F pushparagraphtweak
F pushpath
F pushrandomseed
F pushreferenceprefix
F pushregime
F pushrunstate
F pushsectionblock
F pushstream
F putboxincache
F putincolumnset
F putincolumnsetdirect
F putnextboxincache
F qrcodebuffer
F qrcodestring
F rawMPdata
F rawcharacter
F rawsetupstring
F rawsubcountervalue
F read
F readfromterminal
F readline
F readlinedirect
F recolorbox
F referencecolumn
F referencepagedetail
F referencepagestate
F referenceposx
F referenceposy
F referencerealpage
F registeranchorbox
F registerattachment
F registerbackendsymbol
F registerbackground
F registerbodyfontsize
F registerbookmark
F registerboxglyph
F registerbuttons
F registercolorintent
F registercolumnsetarea
F registercolumnsetsheet
F registercolumnsetspreadsheets
F registerengineclass
F registerfallbackfont
F registerfiguremask
F registerfigurepattern
F registerfigurerange
F registerfiguresuffix
F registerfilescheme
F registerfontalternative
F registerfontfamily
F registerforcedbreak
F registergroupset
F registerhashedfiles
F registerhelp
F registerhyphenationexception
F registerhyphenationpattern
F registeritemgroup
F registerlabel
F registerlanguagefeatures
F registerlinenumbering
F registermaintextcolor
F registermpextensible
F registernamedlua
F registernamespace
F registerobject
F registerpattern

F registerpostponedblock
F registerreferencedobject
F registerrendering
F registersection
F registershownsynonym
F registersnaprange
F registerstructureprocessor
F registersynchronize
F registersynonym
F registertransliteration
F registerunit
F registerunitshortcut
F registerunknownbodysize
F registerusedsynonym
F registeruserdata
F registerverbosemathlabel
F removelastline
F renderingvar
F reorderfloats
F replacefeature
F replacepospxywhd
F replacewildcard
F reportstructure
F resavefloat
F reservedautoregiontag
F resetMPinstance
F resetalternate
F resetbackgroundrowdata
F resetboxesincache
F resetcharacteralign
F resetcolumnset
F resetcomparingtext
F resetcounter
F reseteffect
F resetfeature
F resetfontfeature
F resetfontsolution
F resetforcedbreak
F resetinjector
F resetlogfile
F resetmapfiles
F resetmathattributes
F resetnullfont
F resetparallel
F resetpath
F resetreference
F resetscript
F resetstructureprocessor
F resetsubcounter
F resetsynchronizemarking
F resetsynonyms
F resettimer
F resettrackers
F resolvedemoji
F restartcounter
F restartsubcounter
F restorecounter
F restorecurrentattributes
F restorenote
F restoreobject
F reuserandomseed
F reversevboxcontent
F revivefeature
F rightmathkern
F romannumerals
F rotateparshape
F rounded
F roundedfill
F roundedoutline
F ruby
F ruleoptioncodestring
F runcontextjob
F safechar
F samplefile
F saveboxresource
F savebuffer
F savecounter
F savecurrentattributes
F savecurrentvalue
F savedlistnumber
F savedlistprefixednumber
F savedlisttitle
F savefloat
F saveimageresource
F savemargindata
F savenote
F savepagedata
F savepageinjections

F saveparallel
F savepos
F savespecificfloat
F savestructureblock
F scangivendimensions
F scriptsmodecodestring
F second
F selectstructureblock
F set_extensible_data
F setadaptive
F setalternate
F setautoprefix
F setbackgroundrowdata
F setboxglyph
F setboxline
F setbreakpoints
F setcharacteralign
F setcharacteraligndetail
F setcharactercasing
F setcharactercleaning
F setcharacterkerning
F setcharacterspacing
F setcharacterstripping
F setclosedocumentaction
F setclosepageaction
F setcolormodel
F setcolumnsetarea
F setcolumnsetlines
F setcolumnsetmvl
F setcolumnsetpresent
F setcolumnsetproperties
F setcolumnsetstart
F setcomparetext
F setcomparingtext
F setcounter
F setdataset
F setdestinationattribute
F setdigitsmanipulation
F setdirection
F setdocumentargument
F setdocumentcommandline
F setdocumentctxfile
F setdocumentdefaultargument
F setdocumentenvironments
F setdocumentfilename
F setdocumentfilenames
F setdocumentmodes
F setdocumentmodules
F seteffect
F setelementbackendtag
F setelementnature
F setextrafontkerns
F setfieldcalculationset
F setfigureconversion
F setfigurelookuporder
F setfigurepaths
F setfirstline
F setfontfeature
F setfontofid
F setfontsolution
F setformat
F setformsmethod
F sethsizecolumnset
F sethsizecolumnspan
F sethyphenatedurlcharacters
F sethyphenationfeatures
F sethyphenationmethod
F setidentityvariable
F setinitial
F setinitialsectionblock
F setinjector
F setinsertionlocation
F setinsertmigration
F setinterfaceconstant
F setinterfaceelement
F setinterfacemessage
F setinterfacemessages
F setinterfacevariable
F setinternalreference
F setitaliccorrection
F setjavascriptpreamble
F setjobcomment
F setlanguageexceptions
F setlanguageoptions
F setlanguagepatterns
F setlanguagesynonym
F setlinefiller
F setlineprofile

F setlocalalignanchor
F setlocalmarkanchor
F setlocalsyncanchor
F setluatable
F setmathalphabet
F setmathattribute
F setmathfontalternate
F setmathfontstyle
F setmathsnapping
F setmathvariant
F setmetaglyph
F setmpextensions
F setnaturalwd
F setnegative
F setnextinternalreferences
F setnextreferenceorder
F setnotestate
F setopendocumentaction
F setopenpageaction
F setowncounter
F setownsubcounter
F setpagecolormodel
F setpagestate
F setpagesterealpageno
F setpagetransition
F setparagraphmetashape
F setparagraphshape
F setparbuilder
F setparwrapper
F setpdfcompression
F setperiodkerning
F setpostlistbox
F setprelistbox
F setprofile
F setrandomseed
F setrealign
F setrealspaces
F setreferencelinkmethod
F setregionbox
F setregionboxtagged
F setregistermethod
F setreplacements
F setruby
F setrule
F setscript
F setsectionblock
F setsectionentry
F setshadow
F setshift
F setsofthyphens
F setsplitlisthtdp
F setstacking
F setstructureblockstate
F setstructurelevel
F setstructurenumber
F setsubcounter
F settagcodepoint
F settagcombination
F settagcombinationpair
F settagconstruct
F settagdelimitedsymbol
F settagdescriptionindex
F settagfigure
F settagfloat
F settagformulacontent
F settaggedmetadata
F settaggingcomment
F settaggingoption
F settaggingpresets
F settaghighlight
F settagitem
F settagitemgroup
F settaglist
F settagmarginanchor
F settagmargintext
F settagmpgraphic
F settagnotation
F settagnotationsymbol
F settagparagraph
F settagproperty
F settagpublication
F settagregister
F settagsetreferencedescription
F settagsorting
F settagsubsentencesymbol
F settagsynonym
F settagtablecell
F settagtabulatecell

F settransliteration
F setupbookmarks
F setupcanvas
F setupcharacterspacing
F setupcomparingtext
F setupexport
F setupfontexpansion
F setupfontprotrusion
F setupinsertion
F setuplinenumbering
F setupsynctex
F setupusermetadata
F setupviewerlayer
F setvisual
F setvisualfont
F setvisuallayer
F setvisuals
F setvsizecolumnset
F setxmpfile
F shiftmatrixornaments
F shiftparshape
F shipoutpage
F showarray
F showassignerror
F showattributes
F showbits
F showboxinbuffer
F showbtxdatasetauthors
F showbtxdatasetcompleteness
F showbtxdatasetfields
F showbtxentry
F showbtxfields
F showbtxhashedauthors
F showbtxtables
F showbtxvariants
F showchardata
F showcounter
F showdirectives
F showdiscretionaries
F showexperiments
F showfontparameters
F showhyphenatedinlist
F showhyphenationtrace
F showinjector
F showjustification
F showlogcategories
F showluatables
F showluatokens
F showmacrostack
F showmessage
F showpagelist
F showparagraphshape
F showprofiledmacros
F showstructure
F showtrackers
F silliness
F simplealign
F simplecases
F simplematrix
F sin
F sind
F sl
F spaceddigits
F spacefactorcodestring
F spaceskipcodestring
F special
F specificationoptioncodestring
F specifiedfont
F specifiedfontsize
F specifiedfontspec
F splitfilename
F splitsamplefile
F spotcolorname
F spotcolorparent
F spotcolorvalue
F squid_check
F startactualtext
F startalternativetext
F startchemical
F startclipping
F startcollectingmath
F startcolorset
F startcomponent
F startenvironment
F startfontsolution
F startgraphicgroup
F startlocalcomponent
F startmarkpages

F startmatrix
F startmirroring
F startpageblock
F startparbuilder
F startprerollpageblock
F startproduct
F startproject
F startregime
F startrotation
F startruby
F startscaling
F startsectionlevel
F startstream
F starttext
F startviewerlayer
F step
F stopactualtext
F stopalternativetext
F stopchemical
F stopclipping
F stopcollectingmath
F stopcolorset
F stopcomponent
F stopenvironment
F stopfontsolution
F stopgraphicgroup
F stoplocalcomponent
F stopmarkpages
F stopmatrix
F stopmirroring
F stoppageblock
F stopparbuilder
F stopprerollpageblock
F stopproduct
F stopproject
F stopregime
F stoprotation
F stopscaling
F stopsectionlevel
F stopstream
F stoptext
F stopviewerlayer
F storejavascriptcode
F storejavascriptpreamble
F storenote
F storeregister
F strc_tags_document_pop
F strc_tags_document_push
F strc_tags_get_element_tag
F strc_tags_parcounter_pop
F strc_tags_parcounter_push
F strc_tags_set_aspect
F strc_tags_set_element_user_properties
F strc_tags_start
F strc_tags_start_chained
F strc_tags_start_detail
F strc_tags_start_ignore
F strc_tags_start_userdata
F strc_tags_stop
F stringtoorientation
F stripinserts
F structureautocatcodedget
F structureblockuservariable
F structurecatcodedget
F structuregivencatcodedget
F structurenumber
F structuretitle
F structureuservariable
F structurevariable
F subcountervalue
F subsubcountervalues
F subtocolumnsetmvl
F subtocolumnsetmvlbalance
F subtractfeature
F svghashed
F sync
F synccolor
F synccolorclone
F synccolorcount
F synchronizelocalanchors
F synchronizemarking
F synchronizesteps
F synchronizestream
F synctexblockfilename
F synctexdisable
F synctexpause
F synctexpopline
F synctexpushline

F synctexresetfilename
F synctexresume
F synctexsetfilename
F synonymfirstuserpage
F synonymmeaning
F synonymname
F synonympages
F synonymuserpages
F systemlog
F tabl_ntb_get_sec
F tabl_ntb_set_sec
F tagmfunctionlab
F tagmfunctionlabattribute
F tan
F tand
F textdir
F textime
F tf
F thebox
F thefirstcharacter
F themaxboxwidth
F theremainingcharacters
F tightfitcompensation
F timestring
F tobigpoints
F tobit
F tobits
F tochar
F tohexa
F toorientation
F totalofstring
F tounicharnum
F towholebigpoints
F transliterate
F transliteratebuffer
F transliterated
F transliteratedbuffer
F transliterationexception
F traverseblock
F traversemath
F triggerpagebuilder
F truefilename
F truefontname
F type
F typebuffer
F typefile
F uchar
F uchexnumber
F uchexnumbers
F undefinechemical
F unicodechar
F unihex
F unit
F unloadlanguage
F unstripinserts
F unsupportedcs
F useMPlibrary
F useanyfile
F useanyfileonce
F useboxresource
F usecolors
F usecomponent
F useenvironment
F usefigurebase
F usefile
F useimageresource
F usejavascriptpreamble
F usejavascriptscripts
F uselibrary
F uselist
F useluamodule
F useluatable
F usemathpluginlibrary
F usemodules
F usepath
F useproduct
F useproject
F usereferences
F useregister
F usesubpath
F usesymbols
F usetransliteration
F useurl
F usezipfile
F utfchar
F utflower
F utfmathclass
F utfmathcommand

F utfmathcommandfiller
F utfmathfiller
F utfmathstretch
F utfshape
F utfstrip
F utfupper
F uuid
F vboxlisttohbox
F verbose
F vpackbox
F vpackedbox
F way
F weekday
F weekdayname
F widthofstring
F widthuptohere
F write
F writeline
F writestatus
F writestring
F x_table_c
F x_table_cleanup
F x_table_construct
F x_table_create
F x_table_finish_row
F x_table_flush
F x_table_init_construct
F x_table_init_reflow_height
F x_table_init_reflow_height_option
F x_table_init_reflow_width
F x_table_init_reflow_width_option
F x_table_next_row
F x_table_next_row_option
F x_table_r
F x_table_reflow_height
F x_table_reflow_width
F x_table_set_construct
F x_table_set_reflow_height
F x_table_set_reflow_width
F xmladdindex
F xmlaftersetup
F xmlall
F xmlappendsetup
F xmlapplyselectors
F xmlatt
F xmlattdef
F xmlattribute
F xmlattributedef
F xmlbadinclusions
F xmlbeforesetup
F xmlchainatt
F xmlchainattdef
F xmlchecknamespace
F xmlcommand
F xmlconcat
F xmlconcatrange
F xmlcontext
F xmlcount
F xmlcssmappedstylevalue
F xmlcssstylevalue
F xmldelete
F xmldepth
F xmldirect
F xmldirectives
F xmldirectivesafter
F xmldirectivesbefore
F xmldisplayverbatim
F xmldoif
F xmldoifatt
F xmldoifelse
F xmldoifelseatt
F xmldoifelseempty
F xmldoifelseselfempty
F xmldoifelsetext
F xmldoifempty
F xmldoifnot
F xmldoifnotatt
F xmldoifnotempty
F xmldoifnotselfempty
F xmldoifnottext
F xmldoifselfempty
F xmldoiftext
F xmlelement
F xmlfileline
F xmlfilename
F xmlfilter
F xmlfilterlist
F xmlfirst

F xmlflush
F xmlflushcontext
F xmlflushlinewise
F xmlflushpure
F xmlflushsetups
F xmlflushspacewise
F xmlflushtext
F xmlformulatobuffer
F xmlfunction
F xmlgetindex
F xmlinclude
F xmlincludeoptions
F xmlinclusion
F xmlinclusionbase
F xmlinclusions
F xmlindex
F xmlinlineverbatim
F xmlinstalldirective
F xmllast
F xmllastatt
F xmllastmatch
F xmllastpar
F xmlloadbuffer
F xmlloaddata
F xmlloaddirectives
F xmlloadentities
F xmlloadfile
F xmlmain
F xmlmatch
F xmlname
F xmlnamespace
F xmlnonspace
F xmlpar
F xmlparam
F xmlpath
F xmlpopmatch
F xmlpos
F xmlprependsetup
F xmlpure
F xmlpushmatch
F xmlraw
F xmlrawtex
F xmlrefatt
F xmlregisterns
F xmlremapname
F xmlremapnamespace
F xmlremovesetup
F xmlresetinjectors
F xmlresetsetups
F xmlsave
F xmlsetatt
F xmlsetattribute
F xmlsetcommandtonone
F xmlsetcommandtotext
F xmlsetentity
F xmlsetinjectors
F xmlsetpar
F xmlsetparam
F xmlsetsetup
F xmlsnippet
F xmlstartraw
F xmlstarttiming
F xmlstopraw
F xmlstoptiming
F xmlstrip
F xmlstripanywhere
F xmlstripeverything
F xmlstripnolines
F xmlstripped
F xmlstrippednolines
F xmltag
F xmltexatt
F xmltexentity
F xmltext
F xmltobuffer
F xmltobuffertextonly
F xmltobufferverbose
F xmltofile
F xmltoparameters
F xmlverbatim
F xmlwithindex
F year

containers table

F cleanname
F content
F define
F is_usable
F is_valid

F read
B usecache
F write

context function

F bc
F bgroup
T catcodes
N context
N ctx
N ctxcatcodes
N plain
N protect
N prt
N prtcatcodes
N tex
N texcatcodes
N text
N txt
N txtcatcodes
N verbatim
N vrb
N vrbcatcodes
F char
F concat
D conditionals
T core
F BC
F EQ
F FL
F HL
F LABELTEXT
F LL
F LuaSnippet
F LuaSnippetBoundary
F LuaSnippetComment
F LuaSnippetCommentText
F LuaSnippetName
F LuaSnippetNameBase
F LuaSnippetNameCore
F LuaSnippetNameLibraries
F LuaSnippetQuote
F LuaSnippetSpecial
F LuaSnippetString
F ML
F MPLIBsetCtextX
F MPLIBsetNtextX
F MPLIBsettextX
F MetapostSnippet
F MetapostSnippetBoundary
F MetapostSnippetComment
F MetapostSnippetCommentText
F MetapostSnippetConstructor
F MetapostSnippetName
F MetapostSnippetNameMetafun
F MetapostSnippetNamePlain
F MetapostSnippetNamePrimitive
F MetapostSnippetQuote
F MetapostSnippetSpecial
F MetapostSnippetString
F NC
F NR
F ParsedXmlSnippetCdata
F ParsedXmlSnippetComment
F ParsedXmlSnippetDoctype
F ParsedXmlSnippetElement
F ParsedXmlSnippetInstruction
F ParsedXmlSnippetKey
F ParsedXmlSnippetValue
F TexSnippet
F TexSnippetBoundary
F TexSnippetComment
F TexSnippetCommentText
F TexSnippetGroup
F TexSnippetName
F TexSnippetSpecial
F VL
F XmlSnippet
F XmlSnippetBoundary
F XmlSnippetCdata
F XmlSnippetComment
F XmlSnippetEntity
F XmlSnippetEqual
F XmlSnippetKey
F XmlSnippetName
F XmlSnippetString
F applyprocessor
F beginhbox
F beginvbox

F beginvtop
F bf
F bgroup
F blank
F btxchecklistentry
F btxciteauthorsetup
F btxcitesetup
F btxflushauthor
F btxhandlecombientry
F btxhandlelistentry
F btxlistauthorsetup
F btxlistsetup
F btxnumberingsetup
F btxpagesetup
F btxsetafter
F btxsetauthorfield
F btxsetauthorvariant
F btxsetbacklink
F btxsetbefore
F btxsetcategory
F btxsetcombis
F btxsetconcat
F btxsetcount
F btxsetcurrentlistentry
F btxsetcurrentlistindex
F btxsetdataset
F btxsetfirst
F btxsetfirstinternal
F btxsetfirstnames
F btxsetfirstpage
F btxsetinitials
F btxsetinternal
F btxsetjuniors
F btxsetlanguage
F btxsetlastinternal
F btxsetlastpage
F btxsetlefttext
F btxsetnoflistentries
F btxsetnumber
F btxsetoverflow
F btxsetrighttext
F btxsetsecond
F btxsetsuffix
F btxsetsurnames
F btxsettag
F btxsetvons
F btxstartauthor
F btxstartcite
F btxstartciteauthor
F btxstartcombientry
F btxstartlistentry
F btxstartsubcite
F btxstopauthor
F btxstopcite
F btxstopciteauthor
F btxstopcombientry
F btxstoplistentry
F btxstopsubcite
F btxsubcitesetup
F buff_finish
F chemicalinline
F chemicalspecial
F color
F colordefagc
F colordefagt
F colordefalc
F colordefalt
F colordeffgc
F colordeffgt
F colordefflc
F colordefflt
F colordefrgc
F colordefrgt
F colordefrlc
F colordefrlt
F convertnumber
T cs
  F atendofgroup
  F bgroup
  F clf_step
  F droptablegroup
  F egroup
  F firstofoneargument
  F firstoftwoarguments
  F gobbleoneargument
  F hbox
  F par
  F secondoftwoarguments

F space
F vbox
F vtop
F ctxreport
F definebodyfont
F definefontfallback
F definefontsynonym
F definetypeface
F digitsdigit
F digitsfinalcomma
F digitsfinalperiod
F digitshighspace
F digitsintermediatecomma
F digitsintermediateperiod
F digitsminus
F digitsnegative
F digitsplus
F digitsplusminus
F digitspositive
F digitspower
F digitspowerminus
F digitspowerplus
F digitsseparatorspace
F digitssignspace
F digitsspace
F digitszeropadding
F doactivateinjector
F doboxfigureobject
F docheckfigurebuffer
F docheckfigurecld
F docheckfiguremprun
F docheckfiguremps
F docheckfiguretex
F dodisplayverbatimbeginline
F dodisplayverbatimemptyline
F dodisplayverbatiminitialize
F dodisplayverbatimnewline
F dodisplayverbatimstart
F dodisplayverbatimstop
F doexternalfigurerepeat
F dofastdefinetypeface
F dofinishreference
F doflushparallel
F dofromfiledescription
F dofromfileliteral
F dofromurldescription
F dofromurlliteral
F doinlineverbatimbeginline
F doinlineverbatimemptyline
F doinlineverbatimnewline
F doinlineverbatimstart
F doinlineverbatimstop
F domarkinjector
F donestedtypingstart
F donestedtypingstop
F doscalefigure
F dosetfastregisterentry
F dosetfigureobject
F dostarthead
F dostarttexdefinition
F dostarttext
F dostophead
F doverbatimspace
F dummyxcell
F egroup
F emptyreference
F enablemode
F endhbox
F endvbox
F endvtop
F environment
F errmessage
F expandreferencearguments
F expandreferenceoperation
F finalizeautostructurelevel
F finishjob
F flushboxregister
F getbuffer
F getvalue
F gobbletwoarguments
F goto
F highordinalstr
F ignoreparskip
F input
F labeltext
F loadfontgoodies
F loadfoundtypescriptfile
F luasetup

F m
F makelinenumber
F mathematics
F mathord
F mathrel
F nointerlineskip
F nostarthead
F nostophead
F overstrike
F page
F page_mvl_set_area
F par
F pdfliteral
F popcatcodetable
F processfilemany
F processfilenone
F processfileonce
F pushcatcodetable
F registerentry
F registeronepage
F registerpacked
F registerpagerange
F registersection
F registerseeword
F relocateexternalfigure
F resetfontfallback
F rlap
F rotate
F setcatcodetable
F setfalsevalue
F sethboxregister
F setruby
F setsectionblock
F settabulateentry
F settabulatelastentry
F setupsystem
F setupwithargument
F setvboxregister
F setvtopregister
F space
F startLuaSnippet
F startMetapostSnippet
F startParsedXmlSnippet
F startTexSnippet
F startXmlSnippet
F startbuffer
F startcolumns
F startfontclass
F startfoundexternalfigure
F starthboxregister
F startreadingfile
F startregisterentries
F startregisterentry
F startregisteroutput
F startregisterpages
F startregistersection
F startregisterseewords
F starttabulate
F starttext
F starttitle
F startuserdata
F startvboxregister
F startvtopregister
F startxtable
F startxtitle
F stopLuaSnippet
F stopMetapostSnippet
F stopParsedXmlSnippet
F stopTexSnippet
F stopXmlSnippet
F stopbuffer
F stopcolumns
F stopfontclass
F stopfoundexternalfigure
F stophboxregister
F stopreadingfile
F stopregisterentries
F stopregisterentry
F stopregisteroutput
F stopregisterpages
F stopregistersection
F stopregisterseewords
F stoptabulate
F stoptext
F stoptitle
F stopuserdata
F stopvboxregister
F stopvtopregister

```
  F stopxtable
  F stopxtitle
  F synonymentry
  F tabulaterow
  F tabulaterowbold
  F tabulaterowtyp
  F tabulaterowtype
  F texsetup
  F typ
  F unitsC
  F unitsN
  F unitsNspace
  F unitsNstart
  F unitsNstop
  F unitsO
  F unitsP
  F unitsPS
  F unitsPU
  F unitsPUS
  F unitsPclose
  F unitsPopen
  F unitsQ
  F unitsRPM
  F unitsRTO
  F unitsRabout
  F unitsS
  F unitsU
  F unitsUS
  F usemodule
  F validtext
  F xmlcdataafter
  F xmlcdatabefore
  F xmlcdataobeyedline
  F xmlcdataobeyedspace
  F xmlinjector
  F xmlprocessbuffer
  F xmlsetup
  F xmltexcommand
  F xmlvalue
F cssdimension
F ctxescape
F ctxescaped
T delayed
F direct
F egroup
F escape
F escaped
F firstofoneargument
F firstoftwoarguments
T formatted
  F monobold
  F verbatim
F fprint
T functions
  F callonce
  T known
  F register
  F reserve
  F unregister
F getlogger
F glyph
F gobbleoneargument
T hashedtables
F latelua
F loadfile
F loadviafile
T luatables
  F dispose
  F get
  F getfrom
  F idxfrom
  F inspect
  F new
  F set
  F show
  F use
T metafun
  F color
  T delayed
  F start
  F stop
D modes
T nc
F newindexer
F newtexthandler
F newverbosehandler
T nodes
  F flush
```

```
  F store
F nr
T nuts
  F flush
  F store
F par
F popcatcodes
F poplogger
F printlines
F printtable
F protect
T protected
T puretext
F pushcatcodes
F pushlogger
T registers
  F newbox
  F newchar
  F newcount
  F newdimen
  F newmuskip
  F newskip
  F newtoks
F rule
F runfile
F runstring
F safechar
F secondoftwoarguments
F setconditional
F setfontid
F setmode
F setsystemmode
F settracing
F settrialtypesettingmethod
F space
F sprint
F startcollecting
F step
F stepwise
F stopcollecting
D systemmodes
T templates
F tobuffer
T tocontext
  F boolean
  F function
  F nil
  F number
  F string
  F table
D tokenizedcs
F tolines
F trialtypesetting
F unprotect
F utfchar
T verbatim
  F LuaSnippetBoundary
  F LuaSnippetComment
  F LuaSnippetCommentText
  F LuaSnippetName
  F LuaSnippetNameBase
  F LuaSnippetNameCore
  F LuaSnippetNameLibraries
  F LuaSnippetQuote
  F LuaSnippetSpecial
  F LuaSnippetString
  F MetapostSnippetBoundary
  F MetapostSnippetComment
  F MetapostSnippetCommentText
  F MetapostSnippetConstructor
  F MetapostSnippetName
  F MetapostSnippetNameMetafun
  F MetapostSnippetNamePlain
  F MetapostSnippetNamePrimitive
  F MetapostSnippetQuote
  F MetapostSnippetSpecial
  F MetapostSnippetString
  F ParsedXmlSnippetCdata
  F ParsedXmlSnippetComment
  F ParsedXmlSnippetDoctype
  F ParsedXmlSnippetElement
  F ParsedXmlSnippetInstruction
  F TexSnippetBoundary
  F TexSnippetComment
  F TexSnippetCommentText
  F TexSnippetGroup
  F TexSnippetName
  F TexSnippetSpecial
```

F XmlSnippetBoundary
F XmlSnippetCdata
F XmlSnippetComment
F XmlSnippetEntity
F XmlSnippetEqual
F XmlSnippetKey
F XmlSnippetName
F XmlSnippetString
F ctxreport
F viafile

converters table

F A
F A:es
F A:ru
F A:sl
F AK
F Alphabetic
F Alphabetic:es
F Alphabetic:ru
F Alphabetic:sl
F Character
F Characters
F I
F KA
F KR
F R
F RK
F Romannumerals
F Russiannumerals
F Sloveniannumerals
F Spanishnumerals
F Word
F Words
F a
F a:es
F a:ru
F a:sl
F abjadnodotnumerals
F abjadnumerals
F alphabetic
F alphabetic:es
F alphabetic:ru
F alphabetic:sl
F character
F characters
F chineseallnumerals
F chinesecapnumerals
F chinesedatenumerals
F chinesenumerals
F chr
F chrs
F cn
F cn-a
F cn-c
F cn-d
F convert
F decimals
F define
F gregorian_to_hebrew
F gregorian_to_jalali
F hebrewnumerals
T helpers
F hexstringtonumber
F i
F isleapyear
F jalali_to_gregorian
F lchexnumber
F lchexnumbers
F leapyear
F lower
F max
F maxchrs
F nicenumber
F nofdays
F number
F numbers
F octnumber
F octstringtonumber
F ordinal
F r
F romannumerals
F russiannumerals
D sequences
F settime
F sloveniannumerals
F spaceddigits
F spanishnumerals
F textime

F toabjad
F tochinese
F tohebrew
F toroman
F totime
F uchexnumber
F uchexnumbers
F upper
T verbose
D data
F translate
F weekday
F word
F words

coroutine table
F close
F create
F isyieldable
F resume
F running
F status
F wrap
F yield

ctxrunner table
F load
F preparedfile
D prepfiles
F resolve

debug table
F getinfo
F sethook
F traceback

dimen function

dir table
F collectpattern
F current
F expandlink
F expandname
F found
F glob
F globdirs
F globfiles
F globpattern
F ls
F makedirs
F mkdirs
F pop
F push

directives table
D data
F default
F disable
T done
F enable
F list
S name
F register
F report
F reset
F set
F show
F value
F values

document table
D arguments
T files
T functions
F getargument
F getfilename
T options
F pdf_cleanup_cidsets
F pdf_cleanup_procsets
F pdf_identify_content
F pdf_serialize_content
F pdf_strip_content
F pdf_strip_page
F setargument
F setcommandline
F setdefaultargument
F setenvironments
F setfilename
F setfilenames
F setmodes
F setmodules
D variables

documentdata table
F variable

dofile function

drivers table

F applyanchor
F applyorientation
F convert
T converters
F analyze
F engine
F lmtx
F resyncbox
F enable
F finalize
F gethpos
F gethvrpos
F getpos
F getrpos
F getvpos
T helpers
F initialize
F install
T instances
N lmtxversion
F outputfilename
F report

effects table

F brownianmotion
F browniannoise
F getoctaveloops
F getoctavemethods
F getoctavestatus
F getoctavevariants
F newoctave
F octave
F octavebytemap
F perlinmotion
F perlinnoise
F simplexangle
F simplexdetail
F simplexnoise
F stepoctave
F worleybounds
F worleymotion
F worleynoise

environment table

F argument
D arguments
D basicengines
N currentrun
F definefilefallback
F definefilesynonym
D engineflags
S filename
T filenames
T files
D filesynonyms
N forcedruns
F getargument
F globfiles
S homedir
B initex
B initexmode
F initializearguments
F initializefilenames
S inputfilebarename
S inputfilename
S inputfilesuffix
S jobfilefullname
S jobfilename
S jobfilesuffix
N kindofrun
N lmtxmode
F loadexamodes
F loadluafile
F luafile
F luafilechunk
S luatexengine
N luatexfunctionality
S luatexverbose
N luatexversion
N maxnofruns
S oldhome
D originalarguments
S outputfilename
S ownbin
S ownmain
S ownname
S ownpath
B prerollrun
D rawarguments

F reconstructcommandline
F relativepath
F setargument
F splitarguments
S suffix
F texfile
S texmfos
S texos
S texroot
F truefilename
F useluamodule
F usemodules
D validengines
S version

error function

experiments table

D data
F default
F disable
F enable
F list
S name
F register
F report
F reset
F set
F show
F value
F values

figures table

F applyratio
F badname
D bases
F bitmapimage
N boxnumber
F bytepalette
D cachepaths
F check
D checkers
D conversions
D converters
F current
N defaultdepth
N defaultheight
B defaultsearch
N defaultwidth
F done
F dummy
D existers
F exists
D formats
D found
F get
F getinfo
F getpdfinfo
F getrealpage
F guess
F guessfromstring
F hash
D identifiers
F identify
T images
  F check
  F checksize
  F copy
  F create
  F embed
  F embedfromstore
  F fetchdata
  F print
  F resetdata
  F resetstore
  F scan
  F serialize
  F storedata
  F totable
  F wrap
F include
D includers
F initialize
D loaded
D localpaths
D magics
F mergegoodies
N nofmissing
N nofprocessed
D order
T palettes

D paths
D patterns
F pop
B preferquality
D programs
F push
F qrcode
F registerpattern
F registerresource
F registersuffix
D remappers
D resources
F scale
F set
F setconversion
F setlookups
F setorder
F setpaths
D suffixes
D used

file table

F addsuffix
F basename
F checksum
F collapsepath
F copy
F dirname
F expandname
F extname
F is_qualified_path
F is_readable
F is_rootbased_path
F is_writable
F isreadable
F iswritable
F join
F joinpath
F loadchecksum
F nameonly
F nametotable
F needs_updating
F needsupdating
F pathpart
F readdata
F removesuffix
F replacesuffix
F reslash
F robustname
F savechecksum
F savedata
F size
F splitbase
F splitname
F splitpath
F suffix
F suffixes
F suffixesonly
F suffixonly
F syncmtimes
F withinbase

fio table

F getposition
F read2dot14
F readbytes
F readbytetable
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable
F readcline
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat
F readfloatle
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le

F readinteger4
F readinteger4le
F readintegertable
F setposition
F skipposition
F writecardinal1
F writecardinal1le
F writecardinal2
F writecardinal2le
F writecardinal3
F writecardinal3le
F writecardinal4
F writecardinal4le
F writedouble
F writedoublele
F writefloat
F writefloatle

floats table

F analysemethod
F checkedpagefloat
F collect
F consult
F flush
F getvariable
F hasstacked
F nofstacked
F pop
F push
F resave
F save
F stacked

font table

F addcharacters
F addquality
F current
F define
F getfont
F getfontdimen
F getfontfields
F getfontspec
F getmathcharacterfields
F getmathindex
F getmathspec
F getparameterfields
F gettextcharacterfields
F id
F max
F nextid
F setfont
F setfontdimen
F xscaled
F yscaled

fonts table

T analyzers
D features
D initializers
D methods
F setstate
D states
B useunicodemarks
T callbacks
F compile
F devirtualize
T checkers
F getmissing
D mapping
F missing
F placeholder
T cid
F getmap
F loadfile
T collections
F checkenabled
F clonevector
F define
F direct
F found
F prepare
F process
F register
F registermain
F report
F reset
T constructors
F addcharacters
F addcoreunicodes
F aftercopyingcharacters
F applyfinalizers

F applymanipulators
F assignmathparameters
F beforecopyingcharacters
F beforepassingfonttotex
D cache
F calculatescale
F checkedfeatures
F checkedfilename
F collectprocessors
F currentfonthasfeature
D designsizes
F enhanceparameters
N factor
F finalize
F getfeatureaction
F getmathparameter
F getprivate
F hashfeatures
F hashinstance
F initializefeatures
D loadedfonts
N noffontsloaded
N nofsharedfonts
N nofsharedhashes
N nofsharedvectors
N privateoffset
D privateslots
F readanddefine
F registerfeature
F registerscriptset
F resetfeature
B resolvevirtualtoo
F scale
F scaled
F setfactor
F setfeature
F setmathparameter
F setname
B sharefonts
F trytosharefont
N version
F current
F currentid
T definers
F addlookup
F analyze
F applypostprocessors
F checkedmode
F checkedscript
S defaultlookup
F define
F getspecification
F internal
F loadfont
F makespecification
F read
F register
F registered
F registerfallbackfont
F registersplit
F resetnullfont
F resolve
F definetypeface
T dropins
F clone
F getshape
F getshapes
F nextid
F provide
F registerglyph
F registerglyphs
F swap
F swapone
T effects
T encodings
D cache
F is_known
D known
F load
F make_unicode_vector
D math
N version
F enhanceid
D expansions
D formats
F getalternate
F getindices
F getkern

F getmultiple
F getsubstitution
T getters
T goodies
  D colorschemes
  D designsizes
  D filenames
  F getcompositions
  F load
  F prepare_features
  F register
  F registerpostprocessor
  F report
T handlers
T hashes
  D characters
  D classes
  D csnames
  D descriptions
  D dynamics
  D emwidths
  D exheights
  D features
  D identifiers
  D italics
  D lastmathids
  D marks
  D mathparameters
  D modes
  D originals
  D parameters
  D properties
  D quads
  D resources
  D spaces
  D spacings
  D unicodes
  D unislots
  D variants
  D xheights
T helpers
  F addextraprivate
  F addprivate
  F appendcommands
  F appendcommandtable
  F checkflags
  F checkmerge
  F checksteps
  F collectanchors
  F combineglyphs
  D commands
  F composecharacters
  F descriptiontoslot
  F dimenfactor
  F expandglyph
  D extraprivates
  F fontpatternhassize
  F getcoloredglyphs
  F getdigitwidth
  F getinstancespec
  F getparameters
  F getprivatecharornode
  F getprivatenode
  F getprivates
  F getprivateslot
  F glyphdimenfactor
  F hasprivate
  F indextoslot
  F isprivate
  F mathscriptslots
  F name
  F nametoslot
  F newprivateslot
  F prependcommands
  F prependcommandtable
  F privateslot
  F registerglyphbox
  F scalecommands
  F setboxdirectly
  F setboxglyph
  F setboxglyphs
  F setdigitwidth
  F setmetaglyph
  F setmetaglyphs
  D sharedprivates
  F splitfontpattern
  F tochar
F infofont

T iterators
F characters
F descriptions
F glyphs
T loggers
F format
F onetimemessage
F register
F reportdefinedfonts
F reportusedfeatures
T mappings
F addtounicode
F fromunicode16
F getentry
F loadfile
F loadline
F makenameparser
D overloads
F reset
F tounicode
T metapost
F baseline
F boundingbox
F boxtomp
F boxtompdimensions
F boxtompposition
F draw
F fill
F glyph
F maxbounds
F paths
F widthline
F zeroline
F mode
D names
D nulldata
T privateoffsets
B keepnames
N mathbase
N mathextrabase
N textbase
N textextrabase
D protrusions
T readers
F afm
F check_lua
F check_tfm
F lua
F ofm
F opentype
F otf
F pfb
D sequence
F tfm
F ttc
F ttf
F woff
F woff2
F registersanitizer
F reserveid
T select
D alternatives
F bodyfont
D data
F default
D defaults
F definefallbackfamily
F definefontfamily
F definefontfamilypreset
D extras
F fallback
D fallbacks
F features
F filefallback
F fontdata
F fontfallback
F fontsynonym
F goodies
F mathfallback
D methods
D presets
F registerfallback
F registerfiles
F registerfontalternative
F registerfontfamily
F textfallback
F typeface
F typescript

F userdata
T specifiers
D contextmerged
F contextnumber
D contextnumbers
D contextsetups
F contexttostring
F definecontext
F mergecontext
F presetcontext
F registercontext
F showcontext
F splitcontext
D synonyms
D variants
T symbols
F uselibrary
T tables
F toeffect
T tracers
T treatments
F applyfixes
D data
S filename
F ignoredfile
F report
F trace
T typefaces

functions table

F dummy

getmetatable function

globaldata table

N CONTEXTLMTXMODE
B JITSUPPORTED
N LUAFORMAT
N LUAMAJORVERSION
N LUAMINORVERSION
S LUATEXENGINE
N LUATEXFORMATID
N LUATEXFUNCTIONALITY
S LUATEXVERBOSE
N LUATEXVERSION
N LUAVERSION
T MP
F SAVEDREQUIRE
T aes
F decode
F encode
F random
T arg
F assert
T attributes
F applyoverloads
F checkvalues
D counts
F define
F getvalue
F getvalues
F hasvalues
D list
F markasoverload
D names
D numbers
F ofnode
F private
F public
F registervalue
F restore
F save
F setcleaner
F showcurrent
F system
F tooverloads
N unsetvalue
D values
T backends
F closeout
S current
F getcallbackstate
F initialize
F latelua
F nothing
F openout
F setencryption
F writeout
T basexx
F decode16
F decode64

F decode85
F decodeLZW
F decodeRL
F encode16
F encode64
F encode85
F encodeLZW
F encodeRL
T bibtex
T bit32
F arshift
F band
F bnot
F bor
F btest
F bxor
F extract
F lrotate
F lshift
F replace
F rrotate
F rshift
T bitset
F assign
F asstring
F band
F bnot
F bor
F bxor
F get
F len
F new
F newonebased
F newzerobased
F reset
F set
F shl
F shr
F tostring
F totable
F traverse
F wipe
T blobs
F append
F dimensions
F dispose
F new
F pack
F strdp
F strhd
F strht
F strwd
F tohpack
F tonodes
F tovpack
F write
T boolean
F tocontext
F tonumber
T buffers
F append
F assign
F collectcontent
F empty
F erase
F exists
F get
F getcontent
F getctxlua
F getlines
F getmkvi
F gettex
F loadcontent
F prepend
F raw
F run
F samplefile
F splitsamplefile
F undent
T builders
F checkparcontext
F checksidefloat
F parpassidentifier
D passnames
F registerpaspasscallback
T bytemap
F bounds
F clip

F copy
F dimensions
F domain
F downgrade
F downsample
F fillgray
F fillrgb
F filter
F getbyte
F getbytes
F getluminance
F getvalue
F hasbytegray
F hasbyterange
F hasbytergb
F new
F newdomain
F overlay
F process
F reduce
F reset
F setgray
F setgrayadd
F setgraymin
F setrgb
F slicegray
F slicerange
F slicergb
F totable
T caches
S base
F collapsecontent
F configfiles
F contentstate
F getfirstreadablefile
F getreadablepaths
F getwritablepath
F hashed
F is_writable
F loadcontent
F loaddata
S more
F savecontent
F savedata
F setfirstwritablefile
F setluanames
F treehash
F usedpaths
T callback
F find
F getcontracts
F getcontractvalues
F getindex
F getoptions
F getoptionvalues
F getstate
F getstatevalues
F known
F list
F names
F register
F setoptions
F setstate
F testonly
F usage
T callbacks
F freeze
F getcomment
F getstates
F known
F optimizer
F pop
F push
F register
F report
T catcodes
D names
D numbers
F register
F characterkern
T characters
F addcharacternames
F adobename
D bidi
F blockrange
D blocks
D can_have_space
D categories

F category
D categorytags
D collapsed
D combined
F contextname
D csletters
D data
D decomposed
F description
D descriptions
D detailtags
F emojized
D enccodes
D entities
D fallbacks
D filters
F fromnumber
D fschars
D fscodes
F getrange
D graphemes
D hangul
F initialize
D is_character
D is_command
D is_hyphenator
D is_letter
D is_mark
D is_nothing
D is_punctuation
D is_spacing
D is_symbol
D lcchars
F lccode
D lccodes
F lettered
D lhash
D linebreaks
F lower
D mathlists
D otfscripts
D ranges
F registerentities
F remap_hangul_syllabe
F setactivecatcodes
F setlettercatcodes
F setothercatcodes
F shape
F shaped
D shash
D shchars
D shcodes
F showstring
D specialchars
D specials
D synonyms
F tonumber
D ucchars
F uccode
D uccodes
D uhash
F unicodechar
F upper
D verbosemarks
T chemistry
F component
F define
D definitions
S format
F inlinechemical
S instance
S method
F molecule
U moleculeparser
F start
F stop
F undefine
T client
F httprequest
F supported
F collectgarbage
T commands
F Alphabetic
F MPLIBconvertfollowtext
F MPLIBconvertoutlinetext
F MPc
F MPd
F MPfromhash

F MPh
F MPll
F MPlr
F MPls
F MPn
F MPp
F MPpardata
F MPplus
F MPpos
F MPr
F MPrest
F MPrs
F MPul
F MPur
F MPw
F MPwhd
F MPx
F MPxy
F MPxywhd
F MPy
F Romannumerals
F actualday
F actualmonth
F actualyear
F adaptfontfeature
F adaptivecheckbox
F addbtxentry
F addcounter
F adddefaultsuffix
F addfeature
F addfontpath
F addgrapheme
F addlinenumbers
F addlinklistelement
F addreplacements
F addreplacementslist
F addrivers
F addtocolumnset
F addtocolumnsetmvl
F addtojavascriptpreamble
F addtolist
F align_point_delta
F allinputpaths
F alphabetic
F analysefloatmethod
F analyzeitemgroup
F analyzelist
F analyzelocalanchors
F analyzeregister
F analyzerotate
F analyzeupcomingitemgroup
F applypattern
F applytobox
F applytofirstcharacter
F arraycompare
F arrayequals
F arraymaxvalue
F arrayminvalue
F arraysize
F arrayvalue
F ascender
F askedreference
F assignbuffer
F async
F attachinsertion
F attachinsertions
F atwordboundary
F autofinishstructurelevels
F autoinsertnextspace
F automigrationcodestring
F autonextstructurelevel
F autorule
F autosetups
F autostarttext
F autostoptext
F badnessmodecodestring
F balanceshapeextra
F benchmarktimer
F bf
F bi
F bitmapimage
F bitwise
F bitwiseand
F bitwiseflip
F bitwisenil
F bitwisenot
F bitwiseor
F bitwiseset

F bitwiseshift
F bitwisexor
F blockcolumnset
F blockligatures
F boolcase
F boxdir
F boxline
F boxlinedp
F boxlineht
F boxlineil
F boxlinein
F boxlineir
F boxlinelh
F boxlinelp
F boxlinels
F boxlinemaxdp
F boxlinemaxht
F boxlinemaxwd
F boxlinend
F boxlinenh
F boxlinenw
F boxlinerh
F boxlinerp
F boxliners
F boxlines
F boxlinewd
F boxoptioncodestring
F boxrangedp
F boxrangeht
F boxrangewd
F boxtostring
F bposcolumn
F bposcolumnregistered
F bs
F btxabbreviatedjournal
F btxaddentry
F btxaddjournal
F btxauthor
F btxauthorfield
F btxauthortoregister
F btxcmdstring
F btxcollectlistentries
F btxcurrentfirstnames
F btxcurrentinitials
F btxcurrentjuniors
F btxcurrentsurnames
F btxcurrentvons
F btxdetail
F btxdirect
F btxdoif
F btxdoifelse
F btxdoifelsecitedone
F btxdoifelsecombiinlist
F btxdoifelsematches
F btxdoifelsesameasprevious
F btxdoifelseuservariable
F btxdoifnot
F btxentrytobuffer
F btxentrytostring
F btxexpandedjournal
F btxfetchlistentries
F btxfield
F btxfirstofrange
F btxflush
F btxflushlistcombi
F btxflushlistentry
F btxflushlisttag
F btxflushmarked
F btxflushpages
F btxhandlecite
F btxhandlenocite
F btxlastofrange
F btxlistvariant
F btxloaddefinitionfile
F btxloadjournallist
F btxloadreplacementfile
F btxmissing
F btxoneorrange
F btxpreparelistentries
F btxremapauthor
F btxsavedataset
F btxsavejournallist
F btxsetdataset
F btxsetentry
F btxsetregister
F btxsetspecification
F btxshortcut
F btxshowauthorremapping

F btxsingularorplural
F btxtoregister
F btxusedataset
F btxuservariable
F build_page_after_shipout
F build_page_before_shipout
F build_page_setup
F capheight
F charactercontrolcodestring
F chardescription
F checkcolumnset
F checkcolumnsetmvl
F checkcountersetup
F checkedconversion
F checkedemoji
F checkedpagefloat
F checkinjector
F checkinterfacechain
F checkmarkedpages
F checknesting
F checkspacingavailable
F checkstrutdepth
F chemicalcomponent
F chinesenumerals
F chr
F classoptioncodestring
F cleancolumnset
F cleanfontname
F cleanupattributes
F cleanupbox
F cleanuplayers
F clonefield
F closein
F closeout
F codedef
F collectedmath
F collectfloat
F collecthelp
F columnsetbalancefirst
F columnsetbalancelast
F columnsetbalancepage
F columnsetcolumnwidth
F columnsetdisablewide
F columnsetenablewide
F columnsetgoto
F columnsethascontent
F columnsethspan
F columnsetlastfuture
F columnsetlastmvl
F columnsetlimit
F columnsetnoto
F columnsetresetdirect
F columnsetresetshapeextra
F columnsetreshape
F columnsetsblockrows
F columnsetsetshapeextra
F columnsetshape
F columnsetshapebalancecheck
F columnsetshapebalanceextend
F columnsetshapecolumn
F columnsetshapecount
F columnsetshapeindex
F columnsetshapepage
F columnsetshapesetbalancerange
F columnsetshapeslots
F columnsetshapespread
F columnsetshapevsize
F columnsetshapeworst
F columnsetshowgrid
F columnsetshowshape
F columnsetshowtracedgrid
F columnsetstate
F columnsetstatus
F combineglyphs
F component
F concatcommalist
F consultfloat
F continueifinputfile
F convertbtxdatasettoxml
F converteddimen
F convertmpstopdf
F copyboxfromcache
F copyboxline
F copyposition
F cos
F cosd
F ctxfunction
F ctxluamatch

F ctxluamatchfile
F ctxresetter
F ctxscanner
F currentcomponent
F currentdate
F currentdesignsize
F currentenvironment
F currentfontinstancespec
F currentposthyphenchar
F currentprehyphenchar
F currentproduct
F currentproject
F currentsectiontolist
F datasetsize
F datasetvariable
F day
F daymnem
F dayname
F decimals
F decrementcounter
F decrementsubcounter
F deferredenhancelist
F deferredenhancereference
F deferredenhanceregister
F defineaccents
F defineattribute
F defineboundary
F definebreakpoint
F definebreakpoints
F definecharacterspacing
F definechemical
F definecolumnset
F defineconversion
F definecounter
F definedlayoutcomponent
F definefallbackfamily
F definefield
F definefieldset
F definefilefallback
F definefilesynonym
F definefont_one
F definefont_two
F definefontcolorpalette
F definefontfamily
F definefontfamilypreset
F definefontfeature
F definefontscriptset
F definefontsolution
F definehyphenationfeatures
F defineinsertion
F defineintermediatecolor
F definelabcolorglobal
F definelabcolorlocal
F definelabels
F definelanguage
F definelinkedlist
F definemathpreset
F definemultitonecolorglobal
F definenamespace
F definenote
F defineparallel
F defineparbuilder
F defineprocesscolordummy
F defineprocesscolorglobal
F defineprocesscolorlocal
F defineprogram
F definereference
F defineregister
F definesectionlevels
F definespotcolorglobal
F definestructureblock
F definestructureset
F definesubcolumnset
F definetransparency
F definetransparencyglobal
F definetypeface
F defineviewerlayer
F delayedcolumnsetsheet
F depthnumber
F depthofstring
F descender
F detachinsertions
F diagnostic
F digits_normal
F digits_reverse
F directboxfromcache
F disableautofontscript
F disablecollectingmath

F disabledirectives
F disableexperiments
F disablejobsave
F disableparbuilder
F disableregime
F disablespellchecking
F disablestream
F disabletrackers
F discardfromlist
F discoptioncodestring
F disposeboxesincache
F disposeluatable
F doanalyzeframedbox
F doif
F doifcounter
F doifelse
F doifelseblack
F doifelseboxincache
F doifelsebuffer
F doifelsebufferempty
F doifelsecharinfont
F doifelseconverter
F doifelsecounter
F doifelsecounteractive
F doifelsecurrentfonthasfeature
F doifelsedimenstring
F doifelsedrawingblack
F doifelsefieldcategory
F doifelsefieldset
F doifelsefiledefined
F doifelsefileexist
F doifelsefirstchar
F doifelsefirstsectionpage
F doifelsefontfeature
F doifelsefontpresent
F doifelseindented
F doifelseinelement
F doifelseinputfile
F doifelseleapyear
F doifelselisthasentry
F doifelselisthasnumber
F doifelselisthaspage
F doifelselisthastitle
F doifelsemarkedcontent
F doifelsemarkedpage
F doifelsemessage
F doifelsenoteonsamepage
F doifelseobjectfound
F doifelseobjectreferencefound
F doifelseolderversion
F doifelseoverlapping
F doifelseparallel
F doifelseparentfile
F doifelsepathexist
F doifelsependingpagecontent
F doifelseposition
F doifelsepositiononpage
F doifelsepositionsonsamepage
F doifelsepositionsonthispage
F doifelsepositionsused
F doifelserangeonpage
F doifelsereference
F doifelsereferencechecked
F doifelsereferenced
F doifelserighttoleftinbox
F doifelsesame
F doifelsesomething
F doifelsespaces
F doifelsestackedfloats
F doifelsestructureblocksempty
F doifelsesynonymshown
F doifelsesynonymused
F doifelsetaggednoteonsamepage
F doifelseurldefined
F doifelseutfmathaccent
F doifelseutfmathfiller
F doifelseutfmathlimop
F doifelsevalidhashedfiles
F doifelsevisualizer
F doifmarkedpage
F doifnot
F doifnotcounter
F doifnotecontent
F doifnotsame
F doifnotthing
F doifposition
F doifsame
F doifsomething

F doifunknownfontfeature
F domainattribute
F doreshapeframedbox
F doresyncframedbox
F dosaveposition
F dosavepositionplus
F dosavepositionwhd
F dosetposition
F dosetpositionbox
F dosetpositionplus
F dosetpositionstrut
F dosetpositionstrutkind
F dosetpositionwhd
F dostarttextfile
F dostoptextfile
F doublescriptmodecodestring
F droptablegroup
F elapsedsteptime
F elapsedtime
F embedimagefromstore
F enablealignmentcharacter
F enablealignskips
F enableasciimode
F enableautofences
F enableautofontscript
F enablebackgroundalign
F enablebackgroundboxes
F enablecollectingmath
F enablecolor
F enablecolorintents
F enablecrlf
F enabledirectives
F enabledriver
F enableexperiments
F enablefontcolorschemes
F enablehidecontent
F enablemathalignrelocate
F enablematrixornaments
F enablematrixrules
F enableparbuilder
F enableregime
F enablescriptunstacking
F enablesidefloatchecker
F enablespellchecking
F enablestacking
F enablestream
F enableswapping
F enabletighten
F enabletrackers
F enabletransparency
F enableutf
F enhancelinkedlist
F enhancelist
F enhanceregister
F enhancesynonym
F environment
F eposcolumn
F eposcolumnregistered
F erasebuffer
F execute
F exportbox
F exportformdata
F exportreferences
F expression
F extendregister
F extendregisterlate
F extensiblecode
F fakeword
F featureattribute
F feedback
F fetchlanguagetext
F fetchmultipar
F fetchposboxes
F fetchterminaldata
F figure_flush_registered_pages
F figure_mergegoodies
F figure_nof_registered_pages
F figure_register_page
F figuresetdimensions
F filebasename
F filedirname
F filenameonly
F filesuffix
F filterdefaultreference
F filterreference
F finalizeobjectbox
F finalizeshipoutbox
F findregisterinternal

F finishcolumnsetflush
F finishexport
F firstinset
F firstsectionpage
F firstsubcountervalue
F flagcodestring
F flushcolumnsetareas
F flushcolumnsetcolumn
F flushfloat
F flushlabeledfloat
F flushnoterange
F flushnotes
F flushpageblocks
F flushpageinjectionsafter
F flushpageinjectionsbefore
F flushpostponedblocks
F flushpostponednotes
F flushstream
F flushstreamcopy
F fontchar
F fontcharbyindex
F fontcollectionclone
F fontcollectiondefine
F fontcollectionprepare
F fontcollectionregister
F fontcollectionreport
F fontcollectionreset
F fontlookupgetkey
F fontlookupgetkeyofindex
F fontlookupinitialize
F fontlookupnoffound
F forceendjob
F forcepageflush
F forcequitjob
F forcestrutdepth
F format
F formatcolor
F formatgray
F formatluminance
F formatluminanceratio
F formatone
F framedoutline
F from
F frozenparcodestring
F frule
F getMPdata
F getbidimode
F getbodyfontsizes
F getboxcountfromcache
F getboxdpfromcache
F getboxfromcache
F getboxhtdpfromcache
F getboxhtfromcache
F getboxwdfromcache
F getbuffer
F getbuffercontent
F getbufferctxlua
F getbuffermkvi
F getbuffertex
F getcharactercasingcategory
F getclubpenalties
F getcurrentprefixspec
F getcurrentreferencelabel
F getcurrentreferencemetadata
F getdefaultfieldvalue
F getdisplaywidowpenalties
F getdocumentargument
F getdocumentfilename
F getfieldcategory
F getfile
F getfirstcharacter
F getfloatvariable
F getfromluatable
F getfullstructurenumber
F getinterlinepenalties
F getinternalcachedlistreference
F getinternallistreference
F getinternalorderreference
F getmathblobindex
F getmathblobmapping
F getmathcharone
F getmathchartwo
F getmathmathblob
F getmathtextblob
F getmathvariant
F getmessage
F getmpextensions
F getnaturaldimensions

F getnaturalwd
F getnofpreviouslines
F getnotestate
F getnotestorecount
F getnotestoreflushed
F getobjectdimensions
F getobjectreference
F getobjectreferencepage
F getparshape
F getparwrapper
F getprivatechar
F getprivateglyphslot
F getprivatemathchar
F getprivateslot
F getprogram
F getrandomdimen
F getrandomfloat
F getrandomnumber
F getrandomseed
F getreadfilename
F getreferencesectionnumber
F getrivers
F getsetupstring
F getshapeparameter
F getsomefullstructurenumber
F getsomestructurenumber
F getspecificstructuretitle
F getstructurelevel
F getstructurenumber
F getsubstring
F getsynchronizemarking
F geturl
F getvisual
F getwidowpenalties
F globalpopmacro
F globalpushmacro
F gluetolinesinbox
F glyphoptioncodestring
F gobblenested
F gotocolumnsetslot
F grabbuffer
F groupcodestring
F groupsetgroup
F grph_nodes_initialize
F grph_nodes_register
F grph_nodes_reset
F grph_nodes_resolve
F handlemathhang
F hboxtovbox
F heightofstring
F helpaction
F helpreference
F hour
F hpackbox
F hpackedbox
F hsplit
F hyphenateddigits
F hyphenatedlist
F hyphenationcodestring
F ic
F idxfromluatable
F if_common
F ifallmodes
F ifbitwiseand
F ifblobindexdone
F ifboxhaslist
F ifcommon
F ifeof
F ifgluelineinbox
F ifinset
F iflua
F ifmode
F ifmodes
F ifmvl
F ifpositunum
F ifsetups
F ifsystemmode
F iftext
F ifxml
F ifxmlatt
F ifxmlattempty
F ifxmlempty
F ifxmlselfempty
F ifxmltext
F ignorefile
F ignoretagsinexport
F immediatemessage
F includesvgbuffer

F includesvgfile
F incrementcounter
F incrementsubcounter
F inhibitprimitive
F initializeexport
F initializejob
F initializemathcollapsing
F initializemathfencing
F initializemathitalics
F initializemathkernpairs
F initializemathnumbers
F initializemathspacing
F initializestream
F initializetexdirectives
F initializetexexperiments
F initializetextrackers
F injectcurrentreference
F injectcurrentreferencehtdp
F injectdisable
F injectnowhite
F injectreference
F injectvpenalty
F injectvskip
F injectvspacing
F injectzerobaselineskip
F inlinechemical
F inputfilebarename
F inputfilename
F inputfilerealsuffix
F inputfilesuffix
F insertattachment
F insertcategorycodestring
F insertcomment
F insertfield
F insertionnumber
F insertoptioncodestring
F insertrenderingwindow
F inspectluatable
F installedlanguages
F installtexdirective
F installtexexperiment
F installtextracker
F interceptsamepagecontent
F it
F jobfilefullname
F jobfilename
F jobfilesuffix
F jobposd
F jobposh
F jobposp
F jobposw
F jobposx
F jobposy
F languagecharwidth
F languagenumber
F lastblobindex
F lastnodeequals
F lastnodeid
F lastnodeidstring
F lastnodesubtypestring
F lastparwrapper
F lastrpos
F lastsavedboxresourceindex
F lastsavedimageresourceindex
F lastsavedimageresourcepages
F lastsectionpage
F lastsubcountervalue
F lastunitstring
F lastxpos
F lastypos
F lateindent
F latelua
F lateundent
F lchexnumber
F lchexnumbers
F leapyear
F limitated
F linebuffering
F linedir
F lineprofilebox
F linesegment
F listanchorcodestring
F listbookmark
F listexternal
F listgroupindex
F listlabel
F listlocation
F listnamespaces

F listprefixednumber
F listprefixedpage
F listrawnumber
F listrawrealpage
F listrawuserpage
F listsigncodestring
F listsize
F listtitle
F listuserdata
F lmt_parameters_define
F lmt_parameters_preset
F lmt_parameters_reset
F loadcldfile
F loadcldfileonce
F loadexamodes
F loadfontgoodies
F loadlibrary
F loadluafile
F loadluafileonce
F loadluamodule
F loadmapfile
F loadmapline
F loadspellchecklist
F loadtexfile
F loadtexfileonce
F loadtypescriptfile
F loadvisualizer
F loadxmlfile
F loadxmlfileonce
F localanchorx
F localanchory
F localboxindent
F localboxindex
F localboxlefthang
F localboxleftoffset
F localboxleftskip
F localboxlinenumber
F localboxlinewidth
F localboxlocalwidth
F localboxmarkonce
F localboxovershoot
F localboxparfillleftskip
F localboxparfillrightskip
F localboxparinitleftskip
F localboxparinitrightskip
F localboxprogress
F localboxrighthang
F localboxrightoffset
F localboxrightskip
F localpopmacro
F localpushmacro
F locatefilepath
F loopcs
F loopcsn
F lousiness
F luacardinal
F luacount
F luadimen
F luaexpression
F luafloat
F luainteger
F luanumber
F luarandom
F luascript
F luathread
F lxmlid
F manipulated
F markblobindexdone
F markcontent
F markedpageparameter
F markedpages
F markingnumber
F markingtitle
F markinjector
F markpage
F markregionbox
F markregionboxcorrected
F markregionboxtagged
F markregionboxtaggedkind
F markregionboxtaggedn
F markvisualfonts
F mathclassvalue
F mathcontrolcodestring
F mathhorizontalcode
F mathoptioncodestring
F mathrenderset
F mathstrutcode
F mathvariantcode

F mathvariantcount
F mathvariantslot
F maxbufferwidth
F message
F metapostescaped
F metapostformatted
F metapostgraphformat
F minute
F mixcleanup
F mixfinalize
F mixflushlist
F mixflushrest
F mixgetsplit
F mixsetsplit
F mixstate
F modecodestring
F molecule
F month
F monthmnem
F monthname
F mpblobtext
F mpcolor
F mpgetblob
F mpgettext
F mpgraphic
F mpgraphictexttoks
F mpoptions
F mpoutlinetoks
F mppopvariables
F mppushvariables
F mprunset
F mpruntab
F mprunvar
F mpsetclippath
F mpsetoutercolor
F mpsetsxsy
F mpsettext
F mptexget
F mptexreset
F mptexset
F mptexsetfrombuffer
F mptexttoks
F mvloptioncodestring
F namedstructureuservariable
F namedstructurevariable
F naturalwd
F negatedcolorcomponent
F newarray
F newhashedtable
F newindexedtable
F newluatable
F newparwrapper
F newrepeatablerandom
F newstacking
F nextparallel
F nextsubcountervalue
F nodimen
F nofbufferlines
F nofconversions
F nofdays
F nofdetachedinsertions
F noflinesinbox
F nofmathvariants
F nofstackedfloats
F nologbuffering
F normalizecodestring
F normalizedbodyfontsize
F normalizeparcodestring
F nospacesmodecodestring
F notedeltapage
F noteinternal
F notelistindex
F noteprefixednumber
F notetitle
F ntb_split_section_check
F ntb_split_section_fetch
F ntb_split_section_locate
F ntb_split_section_reset
F ntimes
F number
F numbers
F objectreference
F objectreferencepage
F octnumber
F openin
F openout
F operatingsystem
F ordinal

F outputfilename
F overloadbookmark
F overloadlowercase
F overloadsattribute
F overloaduppercase
F pageblockrealpage
F pageofinternal
F pageoverflow
F pagestaterealpage
F pagestaterealpageorder
F paragraphfillmodecodestring
F paragraphoptioncodestring
F parcontextcodestring
F pardir
F parpasscallback
F parpassidentifier
F parpos
F partriggercodestring
F pdfbackendcurrentresources
F pdfbackendsetcatalog
F pdfbackendsetcolorspace
F pdfbackendsetextgstate
F pdfbackendsetinfo
F pdfbackendsetname
F pdfbackendsetpageattribute
F pdfbackendsetpageresource
F pdfbackendsetpagesattribute
F pdfbackendsetpattern
F pdfbackendsetshade
F pdfcolor
F pdfextension
F pdffeedback
F pdflastobj
F pdfliteral
F pdfobj
F pdfrefobj
F pdfsetuserdata
F pdfvariable
F percentageof
F pfabs
F pfacos
F pfacosh
F pfasin
F pfasinh
F pfatan
F pfatanh
F pfatantwo
F pfceil
F pfcos
F pfcosh
F pfdeg
F pfexp
F pffloor
F pflog
F pfmod
F pfpow
F pfrad
F pfrem
F pfround
F pfsin
F pfsinh
F pfsqrt
F pftan
F pftanh
F pgfxcolorspec
F pickupbuffer
F pickupmarkedcontent
F pickuppunctuation
F placeparallel
F popfloat
F pophyphenation
F poplist
F poplocalanchors
F poplogfile
F popparagraphtweak
F poppath
F poprandomseed
F popreferenceprefix
F popregime
F poprunstate
F popsectionblock
F positunum
F positunumdef
F postlistbox
F postlistcopy
F postponenotes
F prefixedconverted
F prelistbox

F prelistcopy
F preparecolumnsetflush
F prerolledpages
F presetcolumnsetsheets
F presetcolumnsetspreadsheets
F presetmathematics
F presetmathfontalternate
F presetsymbollist
F previoussubcountervalue
F privatecharacter
F privatecharactercode
F processbodyfontsizes
F processbuffer
F processcollectedmath
F processedfile
F processedfiles
F processfile
F processfilemany
F processfilenone
F processfileonce
F processjob
F processlist
F processregister
F processsplit
F processsynonyms
F product
F profilebox
F profilemacro
F project
F pruneboxesincache
F purefontname
F pushfloat
F pushhyphenation
F pushlist
F pushlocalanchors
F pushlogfile
F pushparagraphtweak
F pushpath
F pushrandomseed
F pushreferenceprefix
F pushregime
F pushrunstate
F pushsectionblock
F pushstream
F putboxincache
F putincolumnset
F putincolumnsetdirect
F putnextboxincache
F qrcodebuffer
F qrcodestring
F rawMPdata
F rawcharacter
F rawsetupstring
F rawsubcountervalue
F read
F readfromterminal
F readline
F readlinedirect
F recolorbox
F referencecolumn
F referencepagedetail
F referencepagestate
F referenceposx
F referenceposy
F referencerealpage
F registeranchorbox
F registerattachment
F registerbackendsymbol
F registerbackground
F registerbodyfontsize
F registerbookmark
F registerboxglyph
F registerbuttons
F registercolorintent
F registercolumnsetarea
F registercolumnsetsheet
F registercolumnsetspreadsheets
F registerengineclass
F registerfallbackfont
F registerfiguremask
F registerfigurepattern
F registerfigurerange
F registerfiguresuffix
F registerfilescheme
F registerfontalternative
F registerfontfamily
F registerforcedbreak
F registergroupset

F registerhashedfiles
F registerhelp
F registerhyphenationexception
F registerhyphenationpattern
F registeritemgroup
F registerlabel
F registerlanguagefeatures
F registerlinenumbering
F registermaintextcolor
F registermpextensible
F registernamedlua
F registernamespace
F registerobject
F registerpattern
F registerpostponedblock
F registerreferencedobject
F registerrendering
F registersection
F registershownsynonym
F registersnaprange
F registerstructureprocessor
F registersynchronize
F registersynonym
F registertransliteration
F registerunit
F registerunitshortcut
F registerunknownbodysize
F registerusedsynonym
F registeruserdata
F registerverbosemathlabel
F removelastline
F renderingvar
F reorderfloats
F replacefeature
F replacepospxywhd
F replacewildcard
F reportstructure
F resavefloat
F reservedautoregiontag
F resetMPinstance
F resetalternate
F resetbackgroundrowdata
F resetboxesincache
F resetcharacteralign
F resetcolumnset
F resetcomparingtext
F resetcounter
F reseteffect
F resetfeature
F resetfontfeature
F resetfontsolution
F resetforcedbreak
F resetinjector
F resetlogfile
F resetmapfiles
F resetmathattributes
F resetnullfont
F resetparallel
F resetpath
F resetreference
F resetscript
F resetstructureprocessor
F resetsubcounter
F resetsynchronizemarking
F resetsynonyms
F resettimer
F resettrackers
F resolvedemoji
F restartcounter
F restartsubcounter
F restorecounter
F restorecurrentattributes
F restorenote
F restoreobject
F reuserandomseed
F reversevboxcontent
F revivefeature
F rightmathkern
F romannumerals
F rotateparshape
F rounded
F roundedfill
F roundedoutline
F ruby
F ruleoptioncodestring
F runcontextjob
F safechar
F samplefile

F saveboxresource
F savebuffer
F savecounter
F savecurrentattributes
F savecurrentvalue
F savedlistnumber
F savedlistprefixednumber
F savedlisttitle
F savefloat
F saveimageresource
F savemargindata
F savenote
F savepagedata
F savepageinjections
F saveparallel
F savepos
F savespecificfloat
F savestructureblock
F scangivendimensions
F scriptsmodecodestring
F second
F selectstructureblock
F set_extensible_data
F setadaptive
F setalternate
F setautoprefix
F setbackgroundrowdata
F setboxglyph
F setboxline
F setbreakpoints
F setcharacteralign
F setcharacteraligndetail
F setcharactercasing
F setcharactercleaning
F setcharacterkerning
F setcharacterspacing
F setcharacterstripping
F setclosedocumentaction
F setclosepageaction
F setcolormodel
F setcolumnsetarea
F setcolumnsetlines
F setcolumnsetmvl
F setcolumnsetpresent
F setcolumnsetproperties
F setcolumnsetstart
F setcomparetext
F setcomparingtext
F setcounter
F setdataset
F setdestinationattribute
F setdigitsmanipulation
F setdirection
F setdocumentargument
F setdocumentcommandline
F setdocumentctxfile
F setdocumentdefaultargument
F setdocumentenvironments
F setdocumentfilename
F setdocumentfilenames
F setdocumentmodes
F setdocumentmodules
F seteffect
F setelementbackendtag
F setelementnature
F setextrafontkerns
F setfieldcalculationset
F setfigureconversion
F setfigurelookuporder
F setfigurepaths
F setfirstline
F setfontfeature
F setfontofid
F setfontsolution
F setformat
F setformsmethod
F sethsizecolumnset
F sethsizecolumnspan
F sethyphenatedurlcharacters
F sethyphenationfeatures
F sethyphenationmethod
F setidentityvariable
F setinitial
F setinitialsectionblock
F setinjector
F setinsertionlocation
F setinsertmigration
F setinterfaceconstant

F setinterfaceelement
F setinterfacemessage
F setinterfacemessages
F setinterfacevariable
F setinternalreference
F setitaliccorrection
F setjavascriptpreamble
F setjobcomment
F setlanguageexceptions
F setlanguageoptions
F setlanguagepatterns
F setlanguagesynonym
F setlinefiller
F setlineprofile
F setlocalalignanchor
F setlocalmarkanchor
F setlocalsyncanchor
F setluatable
F setmathalphabet
F setmathattribute
F setmathfontalternate
F setmathfontstyle
F setmathsnapping
F setmathvariant
F setmetaglyph
F setmpextensions
F setnaturalwd
F setnegative
F setnextinternalreferences
F setnextreferenceorder
F setnotestate
F setopendocumentaction
F setopenpageaction
F setowncounter
F setownsubcounter
F setpagecolormodel
F setpagestate
F setpagestaterealpageno
F setpagetransition
F setparagraphmetashape
F setparagraphshape
F setparbuilder
F setparwrapper
F setpdfcompression
F setperiodkerning
F setpostlistbox
F setprelistbox
F setprofile
F setrandomseed
F setrealign
F setrealspaces
F setreferencelinkmethod
F setregionbox
F setregionboxtagged
F setregistermethod
F setreplacements
F setruby
F setrule
F setscript
F setsectionblock
F setsectionentry
F setshadow
F setshift
F setsofthyphens
F setsplitlisthtdp
F setstacking
F setstructureblockstate
F setstructurelevel
F setstructurenumber
F setsubcounter
F settagcodepoint
F settagcombination
F settagcombinationpair
F settagconstruct
F settagdelimitedsymbol
F settagdescriptionindex
F settagfigure
F settagfloat
F settagformulacontent
F settaggedmetadata
F settaggingcomment
F settaggingoption
F settaggingpresets
F settaghighlight
F settagitem
F settagitemgroup
F settaglist
F settagmarginanchor

F settagmargintext
F settagmpgraphic
F settagnotation
F settagnotationsymbol
F settagparagraph
F settagproperty
F settagpublication
F settagregister
F settagsetreferencedescription
F settagsorting
F settagsubsentencesymbol
F settagsynonym
F settagtablecell
F settagtabulatecell
F settransliteration
F setupbookmarks
F setupcanvas
F setupcharacterspacing
F setupcomparingtext
F setupexport
F setupfontexpansion
F setupfontprotrusion
F setupinsertion
F setuplinenumbering
F setupsynctex
F setupusermetadata
F setupviewerlayer
F setvisual
F setvisualfont
F setvisuallayer
F setvisuals
F setvsizecolumnset
F setxmpfile
F shiftmatrixornaments
F shiftparshape
F shipoutpage
F showarray
F showassignerror
F showattributes
F showbits
F showboxinbuffer
F showbtxdatasetauthors
F showbtxdatasetcompleteness
F showbtxdatasetfields
F showbtxentry
F showbtxfields
F showbtxhashedauthors
F showbtxtables
F showbtxvariants
F showchardata
F showcounter
F showdirectives
F showdiscretionaries
F showexperiments
F showfontparameters
F showhyphenatedinlist
F showhyphenationtrace
F showinjector
F showjustification
F showlogcategories
F showluatables
F showluatokens
F showmacrostack
F showmessage
F showpagelist
F showparagraphshape
F showprofiledmacros
F showstructure
F showtrackers
F silliness
F simplealign
F simplecases
F simplematrix
F sin
F sind
F sl
F spaceddigits
F spacefactorcodestring
F spaceskipcodestring
F special
F specificationoptioncodestring
F specifiedfont
F specifiedfontsize
F specifiedfontspec
F splitfilename
F splitsamplefile
F spotcolorname
F spotcolorparent

F spotcolorvalue
F squid_check
F startactualtext
F startalternativetext
F startchemical
F startclipping
F startcollectingmath
F startcolorset
F startcomponent
F startenvironment
F startfontsolution
F startgraphicgroup
F startlocalcomponent
F startmarkpages
F startmatrix
F startmirroring
F startpageblock
F startparbuilder
F startprerollpageblock
F startproduct
F startproject
F startregime
F startrotation
F startruby
F startscaling
F startsectionlevel
F startstream
F starttext
F startviewerlayer
F step
F stopactualtext
F stopalternativetext
F stopchemical
F stopclipping
F stopcollectingmath
F stopcolorset
F stopcomponent
F stopenvironment
F stopfontsolution
F stopgraphicgroup
F stoplocalcomponent
F stopmarkpages
F stopmatrix
F stopmirroring
F stoppageblock
F stopparbuilder
F stopprerollpageblock
F stopproduct
F stopproject
F stopregime
F stoprotation
F stopscaling
F stopsectionlevel
F stopstream
F stoptext
F stopviewerlayer
F storejavascriptcode
F storejavascriptpreamble
F storenote
F storeregister
F strc_tags_document_pop
F strc_tags_document_push
F strc_tags_get_element_tag
F strc_tags_parcounter_pop
F strc_tags_parcounter_push
F strc_tags_set_aspect
F strc_tags_set_element_user_properties
F strc_tags_start
F strc_tags_start_chained
F strc_tags_start_detail
F strc_tags_start_ignore
F strc_tags_start_userdata
F strc_tags_stop
F stringtoorientation
F stripinserts
F structureautocatcodedget
F structureblockuservariable
F structurecatcodedget
F structuregivencatcodedget
F structurenumber
F structuretitle
F structureuservariable
F structurevariable
F subcountervalue
F subsubcountervalues
F subtocolumnsetmvl
F subtocolumnsetmvlbalance
F subtractfeature

F svghashed
F sync
F synccolor
F synccolorclone
F synccolorcount
F synchronizelocalanchors
F synchronizemarking
F synchronizesteps
F synchronizestream
F synctexblockfilename
F synctexdisable
F synctexpause
F synctexpopline
F synctexpushline
F synctexresetfilename
F synctexresume
F synctexsetfilename
F synonymfirstuserpage
F synonymmeaning
F synonymname
F synonympages
F synonymuserpages
F systemlog
F tabl_ntb_get_sec
F tabl_ntb_set_sec
F tagmfunctionlab
F tagmfunctionlabattribute
F tan
F tand
F textdir
F textime
F tf
F thebox
F thefirstcharacter
F themaxboxwidth
F theremainingcharacters
F tightfitcompensation
F timestring
F tobigpoints
F tobit
F tobits
F tochar
F tohexa
F toorientation
F totalofstring
F tounicharnum
F towholebigpoints
F transliterate
F transliteratebuffer
F transliterated
F transliteratedbuffer
F transliterationexception
F traverseblock
F traversemath
F triggerpagebuilder
F truefilename
F truefontname
F type
F typebuffer
F typefile
F uchar
F uchexnumber
F uchexnumbers
F undefinechemical
F unicodechar
F unihex
F unit
F unloadlanguage
F unstripinserts
F unsupportedcs
F useMPlibrary
F useanyfile
F useanyfileonce
F useboxresource
F usecolors
F usecomponent
F useenvironment
F usefigurebase
F usefile
F useimageresource
F usejavascriptpreamble
F usejavascriptscripts
F uselibrary
F uselist
F useluamodule
F useluatable
F usemathpluginlibrary
F usemodules

F usepath
F useproduct
F useproject
F usereferences
F useregister
F usesubpath
F usesymbols
F usetransliteration
F useurl
F usezipfile
F utfchar
F utflower
F utfmathclass
F utfmathcommand
F utfmathcommandfiller
F utfmathfiller
F utfmathstretch
F utfshape
F utfstrip
F utfupper
F uuid
F vboxlisttohbox
F verbose
F vpackbox
F vpackedbox
F way
F weekday
F weekdayname
F widthofstring
F widthuptohere
F write
F writeline
F writestatus
F writestring
F x_table_c
F x_table_cleanup
F x_table_construct
F x_table_create
F x_table_finish_row
F x_table_flush
F x_table_init_construct
F x_table_init_reflow_height
F x_table_init_reflow_height_option
F x_table_init_reflow_width
F x_table_init_reflow_width_option
F x_table_next_row
F x_table_next_row_option
F x_table_r
F x_table_reflow_height
F x_table_reflow_width
F x_table_set_construct
F x_table_set_reflow_height
F x_table_set_reflow_width
F xmladdindex
F xmlaftersetup
F xmlall
F xmlappendsetup
F xmlapplyselectors
F xmlatt
F xmlattdef
F xmlattribute
F xmlattributedef
F xmlbadinclusions
F xmlbeforesetup
F xmlchainatt
F xmlchainattdef
F xmlchecknamespace
F xmlcommand
F xmlconcat
F xmlconcatrange
F xmlcontext
F xmlcount
F xmlcssmappedstylevalue
F xmlcssstylevalue
F xmldelete
F xmldepth
F xmldirect
F xmldirectives
F xmldirectivesafter
F xmldirectivesbefore
F xmldisplayverbatim
F xmldoif
F xmldoifatt
F xmldoifelse
F xmldoifelseatt
F xmldoifelseempty
F xmldoifelseselfempty
F xmldoifelsetext

F xmldoifempty
F xmldoifnot
F xmldoifnotatt
F xmldoifnotempty
F xmldoifnotselfempty
F xmldoifnottext
F xmldoifselfempty
F xmldoiftext
F xmlelement
F xmlfileline
F xmlfilename
F xmlfilter
F xmlfilterlist
F xmlfirst
F xmlflush
F xmlflushcontext
F xmlflushlinewise
F xmlflushpure
F xmlflushsetups
F xmlflushspacewise
F xmlflushtext
F xmlformulatobuffer
F xmlfunction
F xmlgetindex
F xmlinclude
F xmlincludeoptions
F xmlinclusion
F xmlinclusionbase
F xmlinclusions
F xmlindex
F xmlinlineverbatim
F xmlinstalldirective
F xmllast
F xmllastatt
F xmllastmatch
F xmllastpar
F xmlloadbuffer
F xmlloaddata
F xmlloaddirectives
F xmlloadentities
F xmlloadfile
F xmlmain
F xmlmatch
F xmlname
F xmlnamespace
F xmlnonspace
F xmlpar
F xmlparam
F xmlpath
F xmlpopmatch
F xmlpos
F xmlprependsetup
F xmlpure
F xmlpushmatch
F xmlraw
F xmlrawtex
F xmlrefatt
F xmlregisterns
F xmlremapname
F xmlremapnamespace
F xmlremovesetup
F xmlresetinjectors
F xmlresetsetups
F xmlsave
F xmlsetatt
F xmlsetattribute
F xmlsetcommandtonone
F xmlsetcommandtotext
F xmlsetentity
F xmlsetinjectors
F xmlsetpar
F xmlsetparam
F xmlsetsetup
F xmlsnippet
F xmlstartraw
F xmlstarttiming
F xmlstopraw
F xmlstoptiming
F xmlstrip
F xmlstripanywhere
F xmlstripeverything
F xmlstripnolines
F xmlstripped
F xmlstrippednolines
F xmltag
F xmltexatt
F xmltexentity
F xmltext

F xmltobuffer
F xmltobuffertextonly
F xmltobufferverbose
F xmltofile
F xmltoparameters
F xmlverbatim
F xmlwithindex
F year
T containers
F cleanname
F content
F define
F is_usable
F is_valid
F read
B usecache
F write
T context
F bc
F bgroup
F char
F concat
D conditionals
F cssdimension
F ctxescape
F ctxescaped
F direct
F egroup
F escape
F escaped
F firstofoneargument
F firstoftwoarguments
F fprint
F getlogger
F glyph
F gobbleoneargument
F latelua
F loadfile
F loadviafile
D modes
F newindexer
F newtexthandler
F newverbosehandler
F nr
F par
F popcatcodes
F poplogger
F printlines
F printtable
F protect
F pushcatcodes
F pushlogger
F rule
F runfile
F runstring
F safechar
F secondoftwoarguments
F setconditional
F setfontid
F setmode
F setsystemmode
F settracing
F settrialtypesettingmethod
F space
F sprint
F startcollecting
F step
F stepwise
F stopcollecting
D systemmodes
F tobuffer
D tokenizedcs
F tolines
F trialtypesetting
F unprotect
F utfchar
F viafile
T converters
F A
F A:es
F A:ru
F A:sl
F AK
F Alphabetic
F Alphabetic:es
F Alphabetic:ru
F Alphabetic:sl
F Character

F Characters
F I
F KA
F KR
F R
F RK
F Romannumerals
F Russiannumerals
F Sloveniannumerals
F Spanishnumerals
F Word
F Words
F a
F a:es
F a:ru
F a:sl
F abjadnodotnumerals
F abjadnumerals
F alphabetic
F alphabetic:es
F alphabetic:ru
F alphabetic:sl
F character
F characters
F chineseallnumerals
F chinesecapnumerals
F chinesedatenumerals
F chinesenumerals
F chr
F chrs
F cn
F cn-a
F cn-c
F cn-d
F convert
F decimals
F define
F gregorian_to_hebrew
F gregorian_to_jalali
F hebrewnumerals
F hexstringtonumber
F i
F isleapyear
F jalali_to_gregorian
F lchexnumber
F lchexnumbers
F leapyear
F lower
F max
F maxchrs
F nicenumber
F nofdays
F number
F numbers
F octnumber
F octstringtonumber
F ordinal
F r
F romannumerals
F russiannumerals
D sequences
F settime
F sloveniannumerals
F spaceddigits
F spanishnumerals
F textime
F toabjad
F tochinese
F tohebrew
F toroman
F totime
F uchexnumber
F uchexnumbers
F upper
F weekday
F word
F words
T coroutine
F close
F create
F isyieldable
F resume
F running
F status
F wrap
F yield
T ctxrunner
F load

F preparedfile
D prepfiles
F resolve
T debug
F getinfo
F sethook
F traceback
F dimen
T dir
F collectpattern
F current
F expandlink
F expandname
F found
F glob
F globdirs
F globfiles
F globpattern
F ls
F makedirs
F mkdirs
F pop
F push
T directives
D data
F default
F disable
F enable
F list
S name
F register
F report
F reset
F set
F show
F value
F values
T document
D arguments
F getargument
F getfilename
F pdf_cleanup_cidsets
F pdf_cleanup_procsets
F pdf_identify_content
F pdf_serialize_content
F pdf_strip_content
F pdf_strip_page
F setargument
F setcommandline
F setdefaultargument
F setenvironments
F setfilename
F setfilenames
F setmodes
F setmodules
D variables
T documentdata
F variable
F dofile
T drivers
F applyanchor
F applyorientation
F convert
F enable
F finalize
F gethpos
F gethvrpos
F getpos
F getrpos
F getvpos
F initialize
F install
N lmtxversion
F outputfilename
F report
T effects
F brownianmotion
F browniannoise
F getoctaveloops
F getoctavemethods
F getoctavestatus
F getoctavevariants
F newoctave
F octave
F octavebytemap
F perlinmotion
F perlinnoise
F simplexangle

F simplexdetail
F simplexnoise
F stepoctave
F worleybounds
F worleymotion
F worleynoise
T environment
F argument
D arguments
D basicengines
N currentrun
F definefilefallback
F definefilesynonym
D engineflags
S filename
D filesynonyms
N forcedruns
F getargument
F globfiles
S homedir
B initex
B initexmode
F initializearguments
F initializefilenames
S inputfilebarename
S inputfilename
S inputfilesuffix
S jobfilefullname
S jobfilename
S jobfilesuffix
N kindofrun
N lmtxmode
F loadexamodes
F loadluafile
F luafile
F luafilechunk
S luatexengine
N luatexfunctionality
S luatexverbose
N luatexversion
N maxnofruns
S oldhome
D originalarguments
S outputfilename
S ownbin
S ownmain
S ownname
S ownpath
B prerollrun
D rawarguments
F reconstructcommandline
F relativepath
F setargument
F splitarguments
S suffix
F texfile
S texmfos
S texos
S texroot
F truefilename
F useluamodule
F usemodules
D validengines
S version
F error
T experiments
D data
F default
F disable
F enable
F list
S name
F register
F report
F reset
F set
F show
F value
F values
T figures
F applyratio
F badname
D bases
F bitmapimage
N boxnumber
F bytepalette
D cachepaths
F check

D checkers
D conversions
D converters
F current
N defaultdepth
N defaultheight
B defaultsearch
N defaultwidth
F done
F dummy
D existers
F exists
D formats
D found
F get
F getinfo
F getpdfinfo
F getrealpage
F guess
F guessfromstring
F hash
D identifiers
F identify
F include
D includers
F initialize
D loaded
D localpaths
D magics
F mergegoodies
N nofmissing
N nofprocessed
D order
D paths
D patterns
F pop
B preferquality
D programs
F push
F qrcode
F registerpattern
F registerresource
F registersuffix
D remappers
D resources
F scale
F set
F setconversion
F setlookups
F setorder
F setpaths
D suffixes
D used
T file
F addsuffix
F basename
F checksum
F collapsepath
F copy
F dirname
F expandname
F extname
F is_qualified_path
F is_readable
F is_rootbased_path
F is_writable
F isreadable
F iswritable
F join
F joinpath
F loadchecksum
F nameonly
F nametotable
F needs_updating
F needsupdating
F pathpart
F readdata
F removesuffix
F replacesuffix
F reslash
F robustname
F savechecksum
F savedata
F size
F splitbase
F splitname
F splitpath
F suffix

F suffixes
F suffixesonly
F suffixonly
F syncmtimes
F withinbase
T fio
F getposition
F read2dot14
F readbytes
F readbytetable
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable
F readcline
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat
F readfloatle
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F setposition
F skipposition
F writecardinal1
F writecardinal1le
F writecardinal2
F writecardinal2le
F writecardinal3
F writecardinal3le
F writecardinal4
F writecardinal4le
F writedouble
F writedoublele
F writefloat
F writefloatle
T floats
F analysemethod
F checkedpagefloat
F collect
F consult
F flush
F getvariable
F hasstacked
F nofstacked
F pop
F push
F resave
F save
F stacked
T font
F addcharacters
F addquality
F current
F define
F getfont
F getfontdimen
F getfontfields
F getfontspec
F getmathcharacterfields
F getmathindex
F getmathspec
F getparameterfields
F gettextcharacterfields
F id
F max
F nextid
F setfont
F setfontdimen
F xscaled
F yscaled
T fonts
F current
F currentid

```
  F definetypeface
  F enhanceid
  D expansions
  D formats
  F getalternate
  F getindices
  F getkern
  F getmultiple
  F getsubstitution
  F infofont
  F mode
  D names
  D nulldata
  D protrusions
  F registersanitizer
  F reserveid
  F toeffect
T functions
  F dummy
F getmetatable
T globaldata
  N CONTEXTLMTXMODE
  B JITSUPPORTED
  N LUAFORMAT
  N LUAMAJORVERSION
  N LUAMINORVERSION
  S LUATEXENGINE
  N LUATEXFORMATID
  N LUATEXFUNCTIONALITY
  S LUATEXVERBOSE
  N LUATEXVERSION
  N LUAVERSION
  F SAVEDREQUIRE
  F assert
  F characterkern
  F collectgarbage
  F dimen
  F dofile
  F error
  F getmetatable
  T graphics
    T backgrounds
      F fetchmultipar
    T bitmaps
      F flush
      F load
      T loaders
        F jpeg
        F jpg
        F png
      F new
      F placeholder
      F tocontext
    F bpsize
    T colorspaces
    T identifiers
      F bitmap
      F jp2
      F jpeg
      F jpg
      F png
    F identify
    F registerpdfcompactor
    F registerpdffont
    T synchronizers
      F collapse
      F collect
      F extend
      F getbottom
      F getd
      F geth
      F getkind
      F getsize
      F gettask
      F gettop
      F getw
      F getx
      F gety
      F prune
  T gzip
    F compress
    F compressed
    F decompress
    F load
    F save
    F suffix
  T helper
    F getprofile
```

F mathnested
F mathprocess
F mathstep
F snapindeed
F snaplist
F traversecharmethod
F traverseglyphmethod
F traversehorizontal
F traversevertical
F inspect
T interactions
D attachments
T fields
F clone
F define
F defineset
F insert
T general
F getidentity
F getidentityvariable
T help
F collect
F reference
F register
T javascripts
F addtopreamble
F code
D codes
F flushpreambles
D functions
D preambles
F setpreamble
F storecode
F storepreamble
F usepreamblenow
F usescripts
D linkedlists
T pages
F setpagetransition
F setupcanvas
T references
F setclosedocumentaction
F setclosepageaction
F setopendocumentaction
F setopenpageaction
D renderings
T interfaces
T arrays
D cachedsetups
F cachesetup
T cardinals
F checkedspecification
D complete
D constants
D corenamespaces
S currentinterface
S currentresponse
F definecommand
F defined
F doifelsemessage
D elements
T floats
D formats
F getmessage
F getnamespace
F getsetupstring
D hashedsetups
F implement
T integers
F interfacedcommand
T interfaces
F knownscanner
F message
F nameofscanner
T namesofscanners
T namespaces
F define
F list
T numbers
F registernamespace
F registerscanner
D scanners
F setconstant
F setcount
F setdimen
F setelement
F setformat
F setmacro

```
  F setmessage
  F setmessages
  F settranslation
  D setupstrings
  F setvariable
  F showmessage
  D storedscanners
  F tolist
  D translations
  D usednamespaces
  D variables
  F writestatus
T io
  F ask
  F bytes
  F characters
  F close
  F copydata
  F exists
  S fileseparator
  F flush
  F gobble
  F input
  F lines
  F loadchunk
  F loaddata
  F loadlines
  F newreader
  F noflines
  F open
  F output
  S pathseparator
  F popen
  F read
  F readall
  F readnumber
  F readstring
  F savedata
  F size
  U stderr
  U stdin
  U stdout
  F tmpfile
  F type
  F write
F ipairs
T job
  F comment
  T datasets
    D collected
    F extend
    F getdata
    F setdata
    D tobesaved
  F disablesave
  T embedded
    D collected
    D tobesaved
  T fileobjreferences
    D collected
    D tobesaved
  T files
    D collected
    F context
    B forcerun
    F run
    D tobesaved
  F getrandomseed
  F initialize
  T linkedlists
    D collected
    D tobesaved
  F load
  F loadother
  T meshedup
    D collected
    D tobesaved
  T objects
    D collected
    F get
    F number
    F page
    F save
    F set
    D tobesaved
  B pack
  N packversion
  T pagestates
```

```
  D collected
  F countervalue
  F extend
  F realpage
  F realpageorder
  F setstate
  D tobesaved
T parwrappers
  D collected
  D tobesaved
T positions
  F b_column
  F b_region
  F c
  D collected
  F column
  F columnofpos
  F copy
  F depth
  F e_column
  F e_region
  F enhance
  F extra
  F get
  F getcolumndata
  F getfree
  F gethpos
  F gethvrpos
  F getpos
  F getreserved
  F getrpos
  F getsync
  F gettobesaved
  F getvpos
  F hangafter
  F hangindent
  F height
  F hsize
  N lastr
  N lastx
  N lasty
  F leftskip
  F lowerleft
  F lowerright
  F markregionbox
  F n
  F onsamepage
  F overlapping
  F p
  F page
  F paragraph
  F parindent
  F position
  F r
  F region
  F registerhandlers
  F replace
  F rightskip
  F set
  F setall
  F setregionbox
  F setspec
  F settobesaved
  D tobesaved
  F upperleft
  F upperright
  F used
  F whd
  F width
  F x
  F xy
  F y
F register
F save
T structure
  D collected
  T components
  T namestack
  T tobesaved
    T branches
    S name
    S type
T variables
  D checksums
  D collected
  F getchecksum
  F makechecksum
  F restore
```

```
    F save
    F setchecksum
    D tobesaved
  N version
T kdtree
  F delete
  F found
  F insert
  F nearest
  F nearestindex
  F new
  F newweighted
  F reset
  F totable
  F traverse
T kpse
T language
  F clean
  F clearhyphenation
  F clearpatterns
  F current
  F gethjcode
  F haslanguage
  F hyphenate
  F hyphenation
  F hyphenationmin
  F id
  F new
  F patterns
  F postexhyphenchar
  F posthyphenchar
  F preexhyphenchar
  F prehyphenchar
  F sethjcode
  F setwordhandler
T languages
  F addgoodiesdata
  F addgoodiesfile
  T appliedoptions
  F associate
  D associated
  F association
  D counters
  F current
D data
D decimals
F define
F explicithyphen
F exportlanguage
F flatten
T frequencies
  F averagecharwidth
  F getdata
F getdata
F getmetadata
F getnumber
F goodiefiles
T hjcounts
F hyphenate
T hyphenators
  T dictionaries
  D featuresets
  F handler
  T methods
    F expanded
    B none
    F original
    F tex
    F traditional
  F popmethod
  F pushmethod
  F setmethod
  F setup
  F showhyphenationtrace
  T traditional
    F definefeatures
    F gettrace
    F hyphenate
    F injecthyphens
    F installmethod
    F lasttrace
    F loadpatterns
    F registerexception
    F registerpattern
    F setfeatures
F installed
F installhandler
T labels
```

```
  F define
  F split
F loadable
F loadwords
T logger
  F report
F nofflattened
D numbers
F pdflanguage
F postexhyphenchar
F posthyphenchar
F preexhyphenchar
F prehyphenchar
D registered
T registeredactions
T replacements
  F add
  F addlist
  F handler
  F set
F serializediscretionary
F setexceptions
F setgoodieshandler
F setoptions
F setpatterns
F setsynonym
F setwordhandler
F showdiscretionaries
F strippedgoodiewords
F tolang
T transliteration
  F exception
  F handler
  F register
  F set
  F use
F unload
T urls
  D characters
  N lefthyphenmin
  D mapping
  B packslashes
  N righthyphenmin
  F setcharacters
  N version
  F visualizediscretionaries
  T words
    F check
    T data
    F disable
    F enable
    T enablers
    B enables
    F found
    F load
    T methods
    N threshold
T layouts
  F getcanvas
  F getpagedimensions
  F setupcanvas
  T status
    F isleftpage
    F leftorrightpageaction
T lfs
  F attributes
  F canonicalize
  F chdir
  F currentdir
  F dir
  F expandpath
  F isdir
  F isfile
  F isfound
  F isreadabledir
  F isreadablefile
  F iswriteabledir
  F iswriteablefile
  F lessweird
  F link
  F mkdir
  F mkdirs
  F modification
  F moreweird
  F readlink
  F rmdir
  F setexecutable
  F setloadshebang
```

```
  F symlink
  F symlinktarget
  F touch
  F walkdir
T libraries
  D basiclua
  D basictex
  D builtin
  D extralua
  D extratex
  D functions
  D globals
  D obsolete
  D optional
T lmx
  F color
  F convert
  F convertfile
  F convertstring
  F einject
  F eprint
  F escape
  F finalized
  F finject
  F fprint
  F get
  F getvariables
  F htmfile
  T html
    F a
    F td
    F th
  F include
  T inherited
    S color-background-four
    S color-background-one
    S color-background-three
    S color-background-two
    S title
  F initialize
  F inject
  F lmxfile
  F loadedfile
  F make
  F new
  F popupfile
  F print
  F pv
  F report
  F reset
  F result
  F set
  F show
  F stripcss
  F tv
  F type
  F urlescape
  F variable
  T variables
    S color-background-blue
    S color-background-body
    S color-background-green
    S color-background-main
    S color-background-purple
    S color-background-yellow
    S title-default
F load
D loaders
F loadfile
F loadstring
T logs
  F application
  F categories
  F direct
  F disable
  F enable
  F finalactions
  F flush
  F format
  F formatted
  F loggingerrors
  F messenger
  F new
  F newline
  F poplogfile
  F poptarget
  T private
    F enablepagetiming
```

```
    F getpagetiming
  F pushlogfile
  F pushtarget
  F registerfinalactions
  F report
  F reporter
  F resetlogfile
  F setformatters
  F setlogfile
  F setmessenger
  F setprocessor
  F settarget
  F settimedlog
  F settranslations
  F show
  F start_page_number
  F start_run
  F starterrorlogging
  F startfilelogging
  F status
  F stop_page_number
  F stoperrorlogging
  F stopfilelogging
  F subdirect
  F subreport
  F system
  F texerrormessage
  F writer
T lpdf
  F action
  F adddocumentcolorspace
  F adddocumentextgstate
  F adddocumentpattern
  F adddocumentshade
  F addtocatalog
  F addtoinfo
  F addtonames
  F addtopageattributes
  F addtopageresources
  F addtopagesattributes
  F addxmpinfo
  F annotationspecification
  F array
  F attachmentsymbols
  F boolean
  F border
  F checkedkey
  F checkedresources
  F checkedvalue
  F circularshade
  F close
  F cmykcode
  F collectedresources
  F color
  F colorspace
D colorspaceconstants
  F colorspec
  F colorvalue
  F colorvalues
  F commentsymbols
  F compressdata
  F compresslevel
  F constant
  F copyarray
  F copyboolean
  F copyconstant
  F copydictionary
  F copyfloat
  F copyinteger
  F copynumber
  F copystring
  F copyunicode
  F deferredobject
  F delayedobject
  F destinationspecification
  F dictionary
  F docstring
  T encodingvalues
    N base16
    N base85
    N decoded
    N encoded
    N plain
    N utf16be
    N utf16le
  T endpoints
    S Div
    S Part
```

```
  S Sect
T epdf
  F allcontent
  F analyzefonts
  F contentplugin
  F contenttostring
  F contenttotext
  D encryptioncodes
  F expanded
  F expandwidths
  F fontplugin
  F getpagecontent
  F getstructure
  T helpers
    F tounicodetable
  T image
    F close
    F copy
    F new
    F open
    F query
  F load
  F mergewidths
  D objectcodes
  F objectrange
  F objecttype
  F pageplugin
  F parsecontent
  F producer
  T resolvers
    F destinations
    F embeddedfiles
    F javascripts
    F layers
    F pages
    F structure
    F widgets
  F unload
  F verboseobject
F escaped
F finalizedocument
F finalizepage
F finalizesignature
F finishtransparencycode
T flags
  T annotations
    N AutoView
    N Hidden
    N Invisible
    N Locked
    N LockedContents
    N NoRotate
    N NoView
    N NoZoom
    N Print
    N Printable
    N ReadOnly
    N ToggleNoView
    N auto
    N hidden
    N printable
  T widgets
    N Comb
    N CommitOnSelChange
    N DoNotScroll
    N DoNotSpellCheck
    N Edit
    N FileSelect
    N MultiLine
    N NoExport
    N NoToggleToOff
    N Password
    N PopUp
    N PushButton
    N Radio
    N RadiosInUnison
    N ReadOnly
    N Required
    N RichText
    N Sort
    N file
    N fixed
    N nocheck
    N protected
    N readonly
    N required
    N sorted
    N unavailable
```

F flushfonts
F flushgroup
F flushobject
F flushstreamfileobject
F flushstreamobject
T fonts
  F color_direct
  F color_indirect
D formats
F frombytes
F fromeight
F frompdfdoc
F fromsixteen
F getcatalog
F getcompression
F getfontname
F getfontobjectnumber
F getformatoption
F getinfo
F getmatrix
F getnofpages
F getpageproperties
F getpagereference
F getpagetags
F getpos
F gettaggingstatus
F gettrailerid
F getversion
F getxformname
F graycode
T h_hex_2
  S
  S
  S
  S
  S
  S (
  S)
  S \
T h_hex_4
F hasmatrix
F immediateobject
F includeimage
F initialize
T injectors
  F bitmap
  F jp2
  F jpg
  F png
F injectxmpinfo
F insertxmpinfo
F lastreferredpage
F layerreference
F limited
F linearshade
F literal
F majorversion
F makenametree
F minorversion
F noffontregistries
F nofpages
F null
F number
F object
F objectcompresslevel
F pagereference
F patternstream
F pdfcolor
F pdftimestamp
T permissions
  N access
  N add
  N assemble
  N extract
  N fillin
  N modify
  N print
  N quality
F preparesignature
F print
F procset
B protectresources
F quads
F rectangle
F reference
F registerannotation
F registerdestination
F registerdocumentfinalizer

F registerfontmethod
F registerinitializer
F registerpagefinalizer
F registerpattern
F registersignature
F replacexmpinfo
F reserveobject
F rgbcode
F rotationcm
F setcompression
F setencryption
F setpageorder
F setpagestate
F setpagetag
F setutfstringmode
F setversion
F sharedobject
F shareobject
F shareobjectreference
F splitsixteen
F spotcode
F stream
F string
F supportedformats
F tocidset
F toeight
F topdfdoc
F topermissions
F tosixteen
F transparency
F transparencycode
T transparencygroups
  B none
F transparencyvalue
F unicode
T usedcharacters
T usedfontnames
  N dejavusansmonoboldttf-1-0-0
T usedfontobjects
  N dejavusansmonoboldttf-1-0-0
D usedfontstreams
T usedindices
  T dejavusansmonoboldttf-1-0-0
  T dejavusansmonottf-1-0-0
  F verbose
T lpeg
  F B
  F C
  F Carg
  F Cb
  F Cc
  F Cf
  F Cg
  F Cmt
  F Cp
  F Cs
  F Ct
  F P
  F R
  F S
  F UP
  F UR
  F US
  F V
  F afterprefix
  F anywhere
  F append
  F balancer
  F beforesuffix
  F checkedsplit
  F containsws
  F counter
  F endstripper
  F finder
  F firstofsplit
  F frontstripper
  F instringchecker
  F is_lpeg
  F keeper
  F locale
  F match
  F oneof
  D patterns
  F pcode
  F print
  F ptree
  F replacer
  F secondofsplit

```
  F setmaxstack
  F setutfcasers
  F split
  F splitat
  F splitter
  F stripper
  F times
  F tsplitat
  F tsplitter
  F type
  F utfR
  F utfchartabletopattern
  F utfreplacer
  S version
T lua
  F addnibble
  T bytecode
  D bytedata
  T bytedone
  F callbytecode
  F comparekeys
  F finalizeinitex
  N firstbytecode
  F get_functions_table
  F getallkeys
  F getbytecode
  F getcheckedkeys
  F getcurrenttime
  F getdebuginfo
  F getexitcode
  F getfunctionstable
  F getnibble
  F getnumerickeys
  F getpreciseseconds
  F getpreciseticks
  F getruntime
  F getstacktop
  F getstartupfile
  F getstringkeys
  F getversion
  N lastbytecode
  F luastringcall
  D messages
  F mpsstringcall
  F newindex
  F newtable
  D numbers
  F protectglobal
  F registercode
  F registeredcodes
  F registerglobal
  F registerinitexfinalizer
  F registername
  F setbytecode
  F setexitcode
  F setnibble
  S startupfile
  F subnibble
  F usestringcall
  S version
T luac
  F inspect
  F print
T luatex
  F abort
  F cleanup
  F cleanuptempfiles
  F currentfile
  F currentlevel
  F currenttotal
  F poprunstate
  F pushrunstate
  F registerdumpactions
  F registerpageactions
  F registerstartactions
  F registerstopactions
  F registertempfile
  N starttime
  T synctex
    F blockfilename
    F collect
    F disable
    F enable
    F finish
    F isenabled
    F pause
    F popline
    F pushline
```

```
    F registerdisabler
    F registerenabler
    F resetfilename
    F resume
    F setfilename
    F setup
    F start
    F stop
    F wrapup
  F wrapup
T lxml
  F addindex
  F all
  F applyfunction
  F applyselectors
  F att
  F attribute
  F badinclusions
  F chainattribute
  F checkindex
  F collected
  F command
  F concat
  F concatrange
  F content
  F context
  F convert
  F count
  F delete
  F depth
  F direct
  T directives
    F after
    F before
    F handle
    F load
    F setup
  F displayverbatim
  F doif
  F doifelse
  F doifelseempty
  F doifelsetext
  F doifempty
  F doifnot
  F doifnotempty
  F doifnottext
  F doiftext
  F element
  F elements
  D entities
  F fileline
  F filename
  F filter
  F filterlist
  F first
  F flush
  F flushlinewise
  F flushsetups
  F flushspacewise
  F get_id
  F getid
  F getindex
  F id
  U idsplitter
  F ifatt
  F ifattempty
  F include
  F inclusion
  F inclusions
  F index
  F inlineverbatim
  F installsetup
  F last
  F lastatt
  F lastmatch
  F lastpar
  F load
  F loadbuffer
  F loaddata
  T loaded
  F main
  F match
  F name
  F namespace
  F nonspace
  T obsolete
    F get_id
  F par
```

F param
F parameter
F path
F popmatch
F pos
F position
F pure
F pushmatch
F raw
F rawroot
F rawtex
F refatt
F register
F registerentity
F removesetup
F replace
F resetcdata
F resetsetups
F resolvedentity
F root
F save
F serialize
F setaction
F setatt
F setattribute
F setcdata
F setcommandtonone
F setcommandtotext
F setpar
F setparam
F setparameter
F setsetup
F snippet
T sorters
  F add
  F compare
  F flush
  F reset
  F show
  F sort
F splitid
F startraw
F startunescaped
F stopraw
F stopunescaped
F store
F strip
F stripped
F tag
F texatt
F text
F tobuffer
F tofile
F toparameters
F toverbatim
F verbatim
F withindex
D xmltexhandler
T math
F abs
F acos
F asin
F atan
F atan2
F ceil
F ceiling
F cos
F cosd
F cosh
F deg
F div
F even
F exp
F floor
F fmod
F frexp
N huge
N initialseed
F ldexp
F log
F log10
F max
N maxinteger
F min
N mininteger
F mod
F modf
F odd

N pi
F pow
F rad
F random
F randomseed
F round
F setrandomseedi
F sin
F sind
F sinh
F sqrt
F tan
F tand
F tanh
F tointeger
F type
F ult
T mathematics
F addfallbacks
F addvariant
D alphabets
D alternatives
F beforepassingfonttotex
F big
D boldmap
T categories
D functions
D charactersets
F checkaftercopyingfont
D classes
D classnames
D codes
F define
T dictionaries
D data
D defaults
D groups
F groupset
F groupsetgroup
F name
D names
F registercharacter
F registergroup
F registergroupset
D sets
D variants
F dimensions
F disablecollecting
T domainlabels
T domainnames
N default
F enablecollecting
F extensiblecode
D extensibles
N extrabase
T fallbacks
F apply
F install
F fallbackstyleattr
F familyname
F functiontype
D gaps
F getblobindex
F getboth
F getdomainname
F getextensibledata
F getmathblob
F getoptionallabel
F getstyle
F gettextblob
F getverboselabel
F horizontalcode
F initializeparameters
F makefont
D mapremap
F markblobindexdone
F overloadparameters
F preset
T presets
T less
T more
T zero
N privatebase
F registerextensible
F registersimplematrix
F registerverboselabel
F remapalphabets
F renderextensible

T renderings
D mappings
D numbers
D sets
F renderset
F resetattributes
F scaleparameters
F setextensibledata
F setmathsymbol
D sets
F setsnapping
F setvariant
F strutcode
D styles
F syncboth
F syncname
F syncstyle
T tagging
B mfenced
F toengineclass
F toname
F tostyle
F tweakaftercopyingfont
F tweakbeforecopyingfont
T tweaks
F accentdimensions
F action
F addactuarian
F addarrows
F addbars
F addcomposites
F addequals
F addfourier
F addmirrors
F addparts
F addprivates
F addrules
F addscripts
F bigslots
F checkaccents
F checkspacing
F copyaccents
T datasets
T accentdimensions
T accent
T over
T under
T addarrows
T addscripts
T checkspacing
T copyaccents
T fixprimes
T fixslashes
T wipecues
F dimensions
F extendaccents
F fallbacks
F fixaccents
F fixellipses
F fixintegrals
F fixoldschool
F fixprimes
F fixradicals
F fixslashes
F fixvariants
F flattenaccents
F fontname
F inspect
F keepbases
F kernpairs
F kerns
T kernsets
T .,
F margins
F message
F moveitalics
F movelimits
F parameters
F radicalbodymargins
F radicaldegreeanchors
F replace
F replacealphabets
F replacerules
F setoptions
F setovershoots
F showinfo
F simplifykerns
F sortvariants

```
    F strut
    T subsets
      T acenorsuvxz
      T bhklt
      T d
      T dotless
      T f
      T gjqy
      T horizontalfences
      T i
      T integrals
      T letterlike
      T mw
      T p
    F substitute
    F topanchors
    F tweaks
    F version
    F wipeanchors
    F wipecues
    F wipeitalics
    F wipevariants
  F utfmathaccent
  F utfmathclass
  F utfmathcommand
  F utfmathfiller
  F utfmathstretch
  F variantcode
  F variantcount
  F virtualize
  D virtualized
T md5
  F HEX
  F dec
  F hex
  F sum
  F sumHEXA
  F sumhexa
T metapost
  F checkformat
  F checktracingonline
  F cm
  T codes
    N addto
    N ampersand
    N and
    N assignment
    N atleast
    N begingroup
    N btex
    N capsule
    N colon
    N comma
    N controls
    N curl
    N cycle
    N definedmacro
    N delimiters
    N endgroup
    N equals
    N etex
    N everyjob
    N exittest
    N expandafter
    N fiorelse
    N if
    N input
    N interim
    N internal
    N iteration
    N leftbrace
    N leftbracket
    N leftdelimiter
    N let
    N macrodef
    N macrospecial
    N maketext
    N message
    N mode
    N newbytemap
    N newinternal
    N nullary
    N numeric
    N of
    N ofbinary
    N onlyset
    N parametertype
    N pathconnect
```

```
  N pathjoin
  N plusorminus
  N primarybinary
  N primarydef
  N property
  N protection
  N relax
  N repeatloop
  N rightbrace
  N rightbracket
  N rightdelimiter
  N runscript
  N save
  N scantokens
  N secondarybinary
  N secondarydef
  N semicolon
  N setbounds
  N shipout
  N show
  N slash
  N step
  N stop
  N str
  N string
  N tag
  N tension
  N tertiarybinary
  N tertiarydef
  N thingstoadd
  N to
  N typename
  N unary
  N undefinedcs
  N until
  N void
  N with
  N within
  N write
F colorinitializer
F convert
F currentmpx
F currentmpxstatus
S defaultformat
S defaultinstance
S defaultmethod
F directrun
F escaped
T exectime
D extensiondata
F filter
F filterclippath
F flush
T flushers
  T pdf
    F flushfigure
    F startfigure
    F stopfigure
    F textfigure
    F tocomment
F flushnormalpath
T fonts
  F define
F format_number
F format_string
F formatnumber
F getbackendoption
F getbendtolerance
F getbuffer
F getclippath
F getextensions
F getextradata
F gethashentries
F getinstancebyname
F getinstanceinfo
F getinstancenames
F getjobdata
F getmovetolerance
F getparameter
F getparameterpreset
F getparameterset
F getrecord
F getstatistics
F gettext
F gettolerance
F graphic
F graphic_base_pass
F hascurvature
```

F includesvgbuffer
F includesvgfile
F installplugin
F isobject
T knownparameters
S lastlog
F load
F maketext
F mesh
F mesher
F meshupper
T metafonts
T metafun
  F interpolate
  F topath
T mptopdf
  F convertmpstopdf
  N nofconverted
N n
F newlogger
N nofruns
F nofscriptruns
F nvformat
F pdfliterals
F pluginactions
F points
F pointset
F popformat
F popscriptrunner
F popvariable
F popvariables
F preparetextextsdata
F process
F processing
F processplugins
T properties
F pushformat
F pushscriptrunner
F pushvariable
F pushvariables
B quitonerror
B reducetogray
F registerdirect
F registerfilter
F registermesher
F registermeshupper
F registerpointset
F registerscript
F registertokens
F remappedtext
F remaptext
F reporterror
F reportsvgfonts
F reset
F resetbackendoptions
F resetlastlog
F resetplugins
F run
F runinternal
F runscript
F scanparameters
F scriptindex
F setbendtolerance
F setbuffer
F setextensions
F setlogging
F setmovetolerance
F setoutercolor
F setparameter
F setparameterset
F setrecord
F settext
F settolerance
F setvariable
B showlog
F showsvgpage
F simple
F splitprescript
F startgraphic
F startsvghashing
F stopgraphic
F stopsvghashing
F svformat
B svgcachefile
F svgcolorremapper
T svgfactors
  N %
  N bp

N cm
N em
N ex
N in
N mm
N pc
N pt
N px
F svgglyphtomp
F svgshapestomp
F svgshapestopdf
F svgsplitcolor
F svgtomp
F svgtopdf
F sxsy
T tex
F get
F reset
F set
F setfrombuffer
B texerrors
F texexp
F theclippath
F tographic
F totable
T types
N boolean
N cmykcolor
N color
N dependent
N independent
N known
N nep
N numeric
N pair
N path
N pen
N picture
N protodependent
N string
N structured
N suffixedmacro
N tokenlist
N transform
N unknownboolean
N unknownnep
N unknownpath
N unknownpen
N unknownpicture
N unknownstring
N unsuffixedmacro
N vacuous
F typesvgpage
F unload
F untagvariable
T variables
T moduledata
T modules
D anch-loc
D anch-pgr
D anch-snc
D back-exp
D back-exp-imp-fnt
D back-exp-imp-mth
D back-exp-imp-ref
D back-exp-imp-tag
D back-imp-lua
D back-imp-mps
D back-imp-pdf
D back-imp-pdp
D blob-ini
D buff-imp-default
D buff-imp-escaped
D buff-imp-lua
D buff-imp-mp
D buff-imp-nested
D buff-imp-parsed-xml
D buff-imp-tex
D buff-imp-xml
D buff-ini
D buff-par
D buff-ver
D char-enc
D chem-ini
D chem-str
D cldf-com
D cldf-ver
D colo-icc

D colo-ini
D cont-run
D core-con
D core-ctx
D core-dat
D core-sys
D driv-shp
D file-mod
D file-syn
D font-afk
D font-agl
D font-aux
D font-cff
D font-chk
D font-cid
D font-col
D font-con
D font-ctx
D font-def
D font-dsp
D font-enc
D font-enh
D font-fbk
D font-fmp
D font-hsh
D font-imp-checks
D font-imp-combining
D font-imp-compound
D font-imp-digits
D font-imp-dimensions
D font-imp-effects
D font-imp-italics
D font-imp-ligatures
D font-imp-math
D font-imp-notused
D font-imp-properties
D font-imp-quality
D font-imp-reorder
D font-imp-scripts
D font-imp-spacekerns
D font-imp-tex
D font-imp-text
D font-imp-tracing
D font-imp-tweaks
D font-imp-unicode
D font-ini
D font-lig
D font-log
D font-lua
D font-map
D font-mpf
D font-mps
D font-nod
D font-ogr
D font-one
D font-onr
D font-osd
D font-ota
D font-otc
D font-otd
D font-oth
D font-oti
D font-otj
D font-otl
D font-oto
D font-otr
D font-ots
D font-ott
D font-oup
D font-pat
D font-prv
D font-san
D font-sel
D font-shp
D font-sol
D font-syn
D font-tfm
D font-tpk
D font-trt
D font-ttf
D font-txt
D font-vfc
D font-vir
D good-ctx
D good-gen
D good-ini
D good-mth
D grph-bmp

D grph-con
D grph-epd
D grph-fil
D grph-img
D grph-inc
D grph-pat
D grph-raw
D grph-rul
D grph-trf
D grph-u3d
D java-ini
D lang-cnt
D lang-def
D lang-dis
D lang-exc
D lang-hup
D lang-hyp
D lang-ini
D lang-lab
D lang-rep
D lang-tra
D lang-txt
D lang-url
D lang-wrd
D libs-imp-curl
D libs-imp-ghostscript
D libs-imp-graphicsmagick
D libs-ini
D lpdf-ano
D lpdf-col
D lpdf-epa
D lpdf-epd
D lpdf-fix
D lpdf-fix-imp-contents
D lpdf-fix-imp-fonts
D lpdf-fld
D lpdf-fmt
D lpdf-grp
D lpdf-img
D lpdf-ini
D lpdf-lmt
D lpdf-mis
D lpdf-ren
D lpdf-rul
D lpdf-sig
D lpdf-tag
D lpdf-u3d
D lpdf-wid
D lpdf-xmp
D lxml-css
D lxml-dir
D lxml-ent
D lxml-ini
D lxml-mms
D lxml-sor
D lxml-tex
D math-act
D math-ali
D math-dim
D math-ext
D math-fbk
D math-fnt
D math-frc
D math-inc
D math-ini
D math-map
D math-mps
D math-noa
D math-pre
D math-rad
D math-ren
D math-spa
D math-tag
D math-txt
D math-vfu
D meta-blb
D meta-fnt
D meta-fun
D meta-imp-txt
D meta-ini
D meta-lua
D meta-nod
D meta-pdf
D meta-tex
D mlib-ctx
D mlib-fio
D mlib-int
D mlib-lmp

D mlib-lmt
D mlib-lua
D mlib-mat
D mlib-mpf
D mlib-msh
D mlib-pdf
D mlib-pos
D mlib-pps
D mlib-ptr
D mlib-pts
D mlib-ran
D mlib-run
D mlib-scn
D mlib-snc
D mlib-svg
D node-ali
D node-bck
D node-fnt
D node-par
D node-ref
D node-rul
D node-tra
D node-typ
D pack-obj
D pack-ori
D pack-rul
D page-blk
D page-cst
D page-flt
D page-ini
D page-inj
D page-ins
D page-lin
D page-mix
D page-otr
D page-pst
D page-sel
D page-str
D phys-dim
D publ-aut
D publ-dat
D publ-fnd
D publ-inc
D publ-ini
D publ-jrn
D publ-oth
D publ-reg
D publ-sor
D publ-tra
D publ-usr
D regi-ini
D scrn-but
D scrn-fld
D scrn-hlp
D scrn-ini
D scrn-pag
D scrn-ref
D scrn-wid
D scrp-cjk
D scrp-eth
D scrp-ini
D scrp-tha
D scrp-tib
D sort-ini
D sort-lan
D spac-ali
D spac-brk
D spac-chr
D spac-hor
D spac-ovl
D spac-par
D spac-pas
D spac-prf
D spac-twi
D spac-ver
D strc-bkm
D strc-blk
D strc-con
D strc-doc
D strc-flt
D strc-ini
D strc-itm
D strc-lev
D strc-lst
D strc-mar
D strc-mat
D strc-not
D strc-num

```
D strc-pag
D strc-ref
D strc-reg
D strc-rsc
D strc-syn
D strc-tag
D strc-usr
D symb-emj
D symb-ini
D syst-cmp
D tabl-ali
D tabl-ntb
D tabl-tbl
D tabl-xtb
D task-ini
D trac-bld
D trac-jus
D trac-par
D trac-riv
D trac-sig
D trac-vis
D type-ini
D typo-adj
D typo-bld
D typo-brk
D typo-cap
D typo-chr
D typo-cln
D typo-dha
D typo-dif
D typo-dig
D typo-dir
D typo-drp
D typo-duc
D typo-fkr
D typo-fln
D typo-hid
D typo-inj
D typo-itc
D typo-krn
D typo-lan
D typo-lbx
D typo-man
D typo-mar
D typo-ovl
D typo-pag
D typo-par
D typo-pnc
D typo-prc
D typo-rep
D typo-rub
D typo-spa
D typo-stc
D typo-sus
D typo-syn
D typo-tal
D typo-wrp
D unic-ini
T mp
  F autoinject
  T aux
    F boolean
    F color
    F direct
    F draw
    F fill
    F flush
    F fprint
    F integer
    F number
    F numeric
    F pair
    F pairpoints
    F path
    F pathpoints
    F points
    F print
    F quadruple
    F quadruplepoints
    F quoted
    F size
    F string
    F transform
    F triplet
    F tripletpoints
    F vprint
  F boolean
  F bytemap_load_from_file
```

F cleaned
F color
F dataset
T datasets
  F load
F direct
F downgradebytemap
F downsamplebytemap
F draw
F expandtex
F fill
F fillbytemap
F flatten
F flush
F format
F formatted
F fprint
T get
  F hashentry
F getbytemap
F getbytemapdata
F getbytemapdirect
F getlastaddtype
F graphformat
T inject
  F boolean
  F cmykcolor
  F color
  F integer
  F number
  F numeric
  F pair
  F path
  F points
  F pt
  F quadruplet
  F string
  F tokens
  F transform
  F triplet
  F vector
  F vectors
  F whatever
  F whd
  F xy
F integer
F lmt_function_x
F lmt_glyphshape_accent
F lmt_glyphshape_baseline
F lmt_glyphshape_boundingbox
F lmt_glyphshape_depth
F lmt_glyphshape_height
F lmt_glyphshape_italic
F lmt_glyphshape_llx
F lmt_glyphshape_n
F lmt_glyphshape_path
F lmt_glyphshape_start
F lmt_glyphshape_stop
F lmt_glyphshape_usedbox
F lmt_glyphshape_usedline
F lmt_glyphshape_width
F lmt_mesh_set
F lmt_mesh_update
F lmt_poisson_generate
F lmt_start_potrace
F lmt_step_potrace
F lmt_stop_potrace
F lmt_svg_include
F loadbytemap
F loadbytemapfile
F mesh_register
F mf_blob_add
F mf_blob_dimensions
F mf_blob_index
F mf_blob_new
F mf_blob_raw_content
F mf_blob_raw_dimensions
F mf_blob_raw_reset
F mf_blob_raw_toutf
F mf_blob_raw_wipe
F mf_blob_size
F mf_blob_width
F mf_external_figure
F mf_finish_saving_data
F mf_formatted_text
F mf_get_outline_text
F mf_graphic_text
F mf_inject_blob

F mf_map_move
F mf_map_text
F mf_named_color
F mf_outline_text
F mf_save_data
F mf_script_index
F mf_start_saving_data
F mf_stop_saving_data
F mode
F n
F newbytemap
F number
F numeric
F pair
F pairpoints
F path
F pathpoints
F points
F points_register
F processbytemap
F processingmode
F quadruple
F quadruplepoints
F quoted
F report
T scan
  F boolean
  F cmykcolor
  F color
  F expression
  F integer
  F next
  F number
  F numeric
  F pair
  F path
  F pen
  F property
  F string
  F symbol
  F token
  T tokenscanners
  F transform
  T typescanners
    F whatever
  T set
  F setbytemap
  F setbytemapoctave
  F size
  T skip
    F token
  F solve
  F string
  F systemmode
  F transform
  F triplet
  F tripletpoints
  F vprint
T mplib
  F downgradebytemap
  F downsamplebytemap
  F execute
  F expandtex
  F fillbytemap
  F finder
  T finders
    F file
    F mpstemplate
  F finish
  F getbytemap
  F getbytemapdata
  F getbytemapdirect
  F getcallbackstate
  F getcodes
  F getcolormodels
  F getfields
  F gethashentries
  F gethashentry
  F getinternalactions
  F getknotstates
  F getlastaddtype
  F getlogtargets
  F getobjectdata
  F getobjectpeninfo
  F getobjectstacking
  F getobjecttypes
  F getprimitivelegacies
  F getprimitiveorigins

F getprimitives
F getpruneoptions
F getresultstates
F getscaledbits
F getscantypes
F getstates
F getstatistics
F getstatus
F gettolerance
F gettype
F gettypes
F injectboolean
F injectcmykcolor
F injectcolor
F injectinteger
F injectnumber
F injectnumeric
F injectpair
F injectpath
F injectpoints
F injectstring
F injecttokens
F injecttransform
F injectvector
F injectvectors
F injectwhatever
F new
F newbytemap
F peninfo
F processbytemap
T propertycodes
B realtimelogging
F scanboolean
F scancmykcolor
F scancolor
F scanexpression
F scaninteger
F scannext
F scannumber
F scannumeric
F scanpair
F scanpath
F scanpen
F scanproperty
F scanstring
F scansymbol
F scantoken
F scantransform
F setbytemap
F setbytemapoctave
F settolerance
F showcontext
F skiptoken
F solvepath
F version
T nanojpeg
F decode
F next
T noads
F getmathmode
T handlers
F alternates
F autofences
F classes
F collapse
F dictionaries
F export
F families
F fencing
F intervals
F kernpairs
F makeup
F normalize
F numbers
F relocate
F render
F showtree
F snap
F spacing
F suspicious
F tags
F unscript
F unstack
F variants
F process
F processnested
T processors
T dictionaries

```
    T intervals
    T suspicious
    T unscript
    T unstack
  F processouter
T node
  F checkdiscretionaries
  F checkdiscretionary
  F copy
  F copylist
  F count
  F currentattributes
  F dimensions
  T direct
    F addmargins
    F addxoffset
    F addxymargins
    F addyoffset
    F appendaftertail
    F appendcurrenttail
    F beginofmath
    F checkdiscretionaries
    F checkdiscretionary
    F collapsing
    F copy
    F copylist
    F copyonly
    F count
    F currentattributes
    F dimensions
    F effectiveglue
    F endofmath
    F exchange
    F fields
    F findattribute
    F findattributerange
    F findnode
    F firstchar
    F firstglyph
    F firstglyphnode
    F firstitalicglyph
    F flattendiscretionaries
    F flattenleaders
    F flushlist
    F flushnode
    F free
    F freeze
    F getanchors
    F getattribute
    F getattributelist
    F getattributes
    F getboth
    F getbottom
    F getbottomdelimiter
    F getbox
    F getcachestate
    F getchar
    F getchardict
    F getcharspec
    F getchoice
    F getclass
    F getcontinuation
    F getcontrol
    F getcornerkerns
    F getcurrenttail
    F getdata
    F getdegree
    F getdelimiter
    F getdenominator
    F getdepth
    F getdirection
    F getdisc
    F getdiscpart
    F getexcept
    F getexpansion
    F getfam
    F getfield
    F getfielderror
    F getfirstdirectioninlist
    F getfont
    F getfontcheck
    F getgeometry
    F getglue
    F getglyphdata
    F getglyphdimensions
    F getheight
    F getid
    F getidsubtype
```

F getidsubtypenext
F getindex
F getinputfields
F getkern
F getkerndimension
F getlanguage
F getleader
F getleftdelimiter
F getlist
F getlistdimensions
F getlocalparboxstate
F getmvllist
F getnaturalwhd
F getnext
F getnodeerrorvalues
F getnodes
F getnormalizedline
F getnucleus
F getnumerator
F getoffsets
F getoptions
F getorientation
F getparstate
F getpenalty
F getpost
F getpre
F getprev
F getprime
F getpropertiestable
F getproperty
F getreplace
F getrightdelimiter
F getruledimensions
F getscale
F getscales
F getscript
F getscripts
F getshift
F getshort
F getslant
F getspeciallist
F getstate
F getsub
F getsubpre
F getsubtype
F getsup
F getsuppre
F gettop
F gettopdelimiter
F gettotal
F getusage
F getusedattributes
F getweight
F getwhd
F getwidth
F getwordrange
F getxscale
F getxyscales
F getyscale
F gluetostring
F hasattribute
F hasdimensions
F hasdiscoption
F hasfield
F hasgeometry
F hasglyph
F hasglyphoption
F hasidsubtype
F hasoptions
F hasusage
F hpack
F hyphenating
F id
F ignoremathskip
F insertafter
F insertbefore
F insertcurrenthead
F isboth
F ischar
F ischarcheck
F ischardisc
F ischardiscsetcheck
F isdirect
F isfontcheck
F isglyph
F isitalicglyph
F isloop
F isnext

F isnextchar
F isnextcharcheck
F isnextcharsetcheck
F isnextglyph
F isnode
F isprev
F isprevchar
F isprevcharcheck
F isprevcharsetcheck
F isprevglyph
F issimilarglyph
F issnapped
F isspeciallist
F isvalid
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F makeextensible
F markglyphprocessing
F migrate
F mlisttohlist
F naturalhsize
F naturalwidth
F new
F newcontinuationatom
F newfontcheck
F newmathglyph
F newtextglyph
F patchattributes
F patchparshape
F prependbeforehead
F prependcurrenttail
F protectglyph
F protectglyphs
F protectglyphsbase
F protectglyphsnone
F protrusionskippable
F rangedimensions
F remove
F removefromlist
F repack
F reverse
F samefontcheck
F serialized
F setanchors
F setattribute
F setattributelist
F setattributes
F setattributesinlist
F setboth
F setbottom
F setbottomdelimiter
F setbox
F setchar
F setchardict
F setchoice
F setclass
F setcontinuation
F setcontrol
F setcurrenttail
F setdata
F setdegree
F setdelimiter
F setdenominator
F setdepth
F setdirection
F setdisc
F setdiscpart
F setexcept
F setexpansion
F setfam
F setfield
F setfielderror
F setfont
F setfontcheck
F setgeometry
F setglue
F setglyphdata
F setheight
F setindex
F setinputfields
F setkern
F setlanguage
F setleader
F setleftdelimiter
F setlink

F setlist
F setnext
F setnucleus
F setnumerator
F setoffsets
F setoptions
F setorientation
F setpenalty
F setpost
F setpre
F setprev
F setprime
F setproperty
F setreplace
F setrightdelimiter
F setruledimensions
F setscale
F setscales
F setscript
F setscripts
F setshift
F setslant
F setsnapped
F setspeciallist
F setsplit
F setstate
F setsub
F setsubpre
F setsubtype
F setsup
F setsuppre
F settop
F settopdelimiter
F settotal
F setweight
F setwhd
F setwidth
F show
F size
F slide
F softenhyphens
F startofpar
F subtypes
F tail
F todirect
F tonode
F tostring
F tovaliddirect
F traverse
F traversechar
F traversecontent
F traverseglyph
F traverseid
F traverseitalic
F traverseleader
F traverselist
F traversepossible
F type
F types
F unprotectglyph
F unprotectglyphs
F unsetattribute
F unsetattributes
F updatefirstandbotmark
F updatefirstmarks
F updatemarks
F updatetopmarks
F usedlist
F usesfont
F vbalance
F verticalbreak
F vpack
F write
F xscaled
F yscaled
F effectiveglue
F endofmath
F family_font
F fields
F findattribute
F flattendiscretionaries
F flushlist
F flushnode
F free
F getattribute
F getcachestate
F getfield
F getfielderror

F getglue
F getnodeerrorvalues
F getpropertiestable
F getproperty
F gluetostring
F hasattribute
F hasfield
F hasglyph
F hpack
F hyphenating
F id
F insertafter
F insertbefore
F instock
F intracking
F inuse
F isnode
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F makeextensible
F mlisttohlist
F new
F protectglyph
F protectglyphs
F protrusionskippable
F rangedimensions
F remove
F serialized
F setattribute
F setfield
F setfielderror
F setglue
F setproperty
F show
F size
F slide
F subtypes
F tail
F todirect
F tonode
F tostring
F traverse
F traverseid
F type
F types
F unprotectglyph
F unprotectglyphs
F unsetattribute
F usedlist
F usesfont
F vpack
F write
T nodes
D accentcodes
T adaptive
F handlehorizontal
F handlevertical
T methods
F set
F aligned
F append
F apply
F applyvisuals
F astable
F basepoints
D boundarycodes
T boxes
F count
F dimensions
F direct
F dispose
F found
F prune
F reset
F restore
F save
F savenode
T builders
D choicecodes
F concat
F copy
F copy_node
F copylist
F countall
F currentattributes

F delete
T destinations
  N attribute
  T done
  F handler
  T stack
D dircodes
D directioncodes
D directionvalues
D dirvalues
D disccodes
D discretionarycodes
D fencecodes
F fields
T fieldtypes
D fillcodes
D fillvalues
F firstdirinbox
F flush
F flushlist
F flushnode
D fractioncodes
F fullhpack
F getattr
F getattribute
F getboth
F getbox
F getchar
F getfield
F getfont
F getid
F getleader
F getlist
F getnext
F getprev
F getproperty
F getsubtype
D gluecodes
D glyphcodes
T handlers
  F adjusters
  F aligncharacter
  F backgrounds
  F backgroundspage
  F backgroundsvbox
  F characters
  F checkglyphs
  F checkparcounter
  F cleanupbox
  F cleanuppage
  F export
  F finalizebox
  F finalizelist
  F flatten
  F flattenline
  T linebreakchecks
  F mathalignrelocate
  F mathmatrixornaments
  F mathmatrixrules
  F protectglyphs
  F recolor
  F show
  F showhyphenation
  F showpreamble
  F stripping
  F tabulateskip
  F textbackgrounds
  F unprotectglyphs
  F visualizehyphenation
  F wipe
F hasattribute
F hasfield
F hpack
F idsandsubtypes
F idstostring
T injections
  F copy
  F getligaindex
  F getthreshold
  F handler
  F installgetspaceboth
  F installnewkern
  F isspace
  F keepcounts
  F reset
  F resetcounts
  F setcursive
  F setkern

```
  F setligaindex
  F setmark
  F setmove
  F setposition
  F setspacekerns
F insertafter
F insertbefore
F insertlistafter
F installattributehandler
F is_display_math
F isdirect
F isnode
F isnut
D kerncodes
F leftmarginwidth
T linefillers
  F filler
  F handler
  F set
T lines
  T boxed
    F addlinenumbers
    F register
    F setup
  D data
  F finalize
  F number
F link
F linked
F list
D listcodes
F listtoutf
D literalvalues
F locate
D markcodes
T markers
  F get
  F set
D mathcodes
D mathvalues
F maxboxwidth
F new
D noadcodes
D nodecodes
F nopts
T nuts
  F addmargins
  F addxoffset
  F addxymargins
  F addyoffset
  F append
  F appendaftertail
  F apply
  F applyvisuals
  F beginofmath
  F checkdiscretionaries
  F checkdiscretionary
  F checkslide
  F collapsing
  T colors
    F set
  T components
    F copynocomponents
    F copyonlyglyphs
    F count
    F flush
    F get
    F set
  F concat
  F copy
  F copy_properties
  F copylist
  F copynode
  F copyonly
  F copyvisual
  F count
  F countall
  F currentattributes
  F delete
  F dimensions
  F dirdimensions
  F effectiveglue
  F endofmath
  F exchange
  F findattribute
  F findattributerange
  F findnode
  F firstchar
```

F firstglyph
F firstglyphnode
F firstitalicglyph
F flattendiscretionaries
F flattenleaders
F flush
F flushlist
F flushnode
F free
F freeze
F fullhpack
F fullhpackrl
F getanchors
F getattr
F getattribute
F getattributelist
F getattributes
F getattrlist
F getattrs
F getboth
F getbottom
F getbottomdelimiter
F getbox
F getboxglue
F getchar
F getchardict
F getcharspec
F getchoice
F getclass
F getcomponents
F getcontinuation
F getcontrol
F getcornerkerns
F getdata
F getdegree
F getdelimiter
F getdenominator
F getdepth
F getdirection
F getdisc
F getdiscpart
F getdiscretionary
F getexcept
F getexpansion
F getfam
F getfield
F getfirstdirectioninlist
F getfont
F getfontcheck
F getgeometry
F getglue
F getglyphdata
F getglyphdimensions
F getheight
F getid
F getidsubtype
F getidsubtypenext
F getindex
F getinputfields
F getkern
F getkerndimension
F getlang
F getlanguage
F getleader
F getleftdelimiter
F getlist
F getlistdimensions
F getlocalparboxstate
F getmiddle
F getmiddledelimiter
F getmvllist
F getnaturalwhd
F getnext
F getnormalizedline
F getnucleus
F getnumerator
F getoffsets
F getoptions
F getorientation
F getparstate
F getpenalty
F getpost
F getpre
F getprev
F getprime
F getprop
F getreplace
F getrightdelimiter

F getruledata
F getruledimensions
F getscale
F getscales
F getscript
F getscripts
F getshift
F getshort
F getslant
F getspeciallist
F getstate
F getsub
F getsubpre
F getsubtype
F getsup
F getsuppre
F getsurround
F gettop
F gettopdelimiter
F gettotal
F getusedattributes
F getvalue
F getweight
F getwhd
F getwidth
F getwordrange
F getxscale
F getxyscales
F getyscale
F gluetostring
F hasattribute
F hasdimensions
F hasdiscoption
F hasfield
F hasgeometry
F hasglyph
F hasglyphoption
F hasidsubtype
F hasoptions
F hpack
F hyphenating
F ignoremathskip
F insertafter
F insertbefore
F insertlistafter
F is_display_math
F isboth
F ischar
F ischarcheck
F ischardiscsetcheck
F isdirect
F isdone
F isglyph
F isitalicglyph
F isnext
F isnextchar
F isnextcharcheck
F isnextcharsetcheck
F isnextglyph
F isnode
F isnut
F isprev
F isprevchar
F isprevcharcheck
F isprevcharsetcheck
F isprevglyph
F issimilarglyph
F issnapped
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F link
F linked
F locate
F migrate
F migratebox
F mlisttohlist
F naturalhsize
F naturalwidth
F nestedtracedslide
F new
F newcontinuationatom
F newfontcheck
F newmathglyph
F openup
F patchattributes

F patchparshape
T pool
  F accent
  F baselineskip
  F boundary
  F boxrule
  F characterkern
  F choice
  F cleanup
  F delim
  F delimiter
  F direction
  F directliteral
  F disc
  F discretionaryglue
  F emptyrule
  F fence
  F fontkern
  F fraction
  F glue
  F gluespec
  F glyph
  F hlist
  F imagerule
  F indentskip
  F intercharacterglue
  F italiccorrection
  F italickern
  F kern
  F latelua
  F leader
  F lefthangskip
  F leftmarginkern
  F leftskip
  F lineskip
  F literal
  F luaboundary
  F mathchar
  F mathtextchar
  F negatedglue
  F noad
  F originliteral
  F outlinerule
  F pageliteral
  F penalizedglue
  F penalizedspace
  F penalty
  F radical
  F rawliteral
  F register
  F restore
  F righthangskip
  F rightmarginkern
  F rightskip
  F rule
  F save
  F savepos
  F setmatrix
  F setstate
  F shrink
  F spacefontkern
  F spacingrule
  F startrotation
  F startscaling
  F stock
  F stoprotation
  F stopscaling
  F stretch
  F strutrule
  F subbox
  F submlist
  F temp
  F usage
  F userdefined
  T userids
  F usernode
  F userrule
  F virtualrule
  F vlist
  F wordboundary
F prepend
F prependbeforehead
F processranges
F processwords
F protectglyph
F protectglyphs
F protectglyphsbase
F protectglyphsnone

F protrusionskippable
F rangedimensions
F rawprop
F reference
F rehpack
F remove
F removefromlist
F repack
F repackhlist
F replace
F reverse
T rules
  T ruleactions
    F box
    F draw
    F fill
    F mp
    F stroke
  F userrule
F serialized
F setanchors
F setattr
F setattribute
F setattributelist
F setattributes
F setattributesinlist
F setattrlist
F setattrs
F setattrsinlist
F setboth
F setbottom
F setbox
F setboxglue
F setchar
F setchardict
F setchoice
F setclass
F setcomponents
F setcontinuation
F setcontrol
F setdata
F setdegree
F setdelimiter
F setdenominator
F setdepth
F setdirection
F setdisc
F setdiscpart
F setdiscretionary
F setexcept
F setexpansion
F setfam
F setfield
F setfont
F setfontcheck
F setgeometry
F setglue
F setglyphdata
F setheight
F setinputfields
F setkern
F setlang
F setlanguage
F setleader
F setleftdelimiter
F setlink
F setlist
F setmiddledelimiter
F setnext
F setnucleus
F setnumerator
F setoffsets
F setoptions
F setorientation
F setparproperty
F setpenalty
F setpost
F setpre
F setprev
F setprime
F setprop
F setreplace
F setrightdelimiter
F setruledata
F setruledimensions
F setscale
F setscales
F setscript

F setscripts
F setshift
F setslant
F setsnapped
F setspeciallist
F setsplit
F setstate
F setsub
F setsubpre
F setsubtype
F setsup
F setsuppre
F setsurround
F settop
F setvalue
F setvisual
F setvisuals
F setweight
F setwhd
F setwidth
F show
F slide
F softenhyphens
F somepenalty
F somespace
F splitbox
F startofpar
F striprange
F tail
F takeattr
F takebox
F takelist
F theprop
F tonode
F tonodes
F tonut
F tosequence
F tostring
F tracedslide
F traverse
F traversechar
F traversecontent
F traverseglyph
F traverseid
F traverseitalic
F traverseleader
F traverselist
F traversepossible
T traversers
  F alignrecord
  F boundary
  F char
  F content
  F dir
  F disc
  F glue
  F glyph
  F hlist
  F leader
  F list
  F mark
  F next
  F node
  F penalty
  F possible
  F rule
  F unset
  F vlist
  F whatsit
T treversers
  F char
  F content
  F glyph
  F leader
  F list
  F node
  F possible
T typesetters
  F tohbox
  F tohpack
  F tonodes
  F tovbox
  F tovpack
F unprotectglyph
F unprotectglyphs
F unsetattribute
F unsetattributes
F untracedslide

```
  F updatefirstandbotmark
  F updatefirstmarks
  F updatemarks
  F updatetopmarks
  F usedlist
  F usesfont
  F verticalbreak
  F vianodes
  F vianuts
  F vpack
  F write
  F xscaled
  F yscaled
F packlist
D parcodes
D penaltycodes
F points
T pool
  F baselineskip
  F cleanup
  F directliteral
  F glyph
  F hlist
  F latelua
  F leader
  F lineskip
  F literal
  F originliteral
  F register
  F restore
  F save
  F savepos
  F setmatrix
  F stock
  F usage
  F usernode
  F vlist
F prepend
F print
T processors
  F trace_glyph_run_a
  F trace_glyph_run_b
T properties
  T data
F pts
D radicalcodes
T references
  N attribute
  T done
  F handler
  T stack
F rehpack
F remove
F repackhlist
F replace
F report
F rightmarginwidth
D rulecodes
T rules
  F handler
  F process
  F set
  F userrule
F serialize
F serializebox
F serialized
F setattr
F setattribute
F setattrlist
F setboth
F setbox
F setboxtonaturalwd
F setchar
F setfield
F setfont
F setleader
F setlink
F setlist
F setnext
F setprev
F setproperty
T shadows
  F handler
  F set
T shifts
  F handler
  F set
F showboxes
```

F showlist
F showsimplelist
D skipcodes
T snapshots
  F getsamples
  F resetsamples
  F takesample
F somepenalty
F somespace
T specialskipcodes
F splitbox
F startofpar
F stripdiscretionaries
T stripping
  T glyphs
  F set
D subtypes
F tail
F takeattr
F takebox
T tasks
  F actions
  F appendaction
  F disableaction
  F disablegroup
  F enableaction
  F enablegroup
  F freeze
  F freezegroup
  F new
  F prependaction
  F removeaction
  F replaceaction
  F restart
  F setaction
  F showactions
  F table
F tobasepoints
F tocentimeters
F tociceros
F todidots
F todimen
F toinches
F tomillimeters
F tonode
F tonodes
F tonut
F topicas
F topoints
F toscaledpoints
F tosequence
F tostring
F totable
F totree
F toutf
T tracers
  T colors
    F reset
    F set
    F setlist
  F directions
  F fontchar
  T frequencies
    F register
  T pool
    T nodes
      F rule
    T nuts
      F rule
  F resetproperties
  F rule
  F setlist
  F setproperties
  F start
  T steppers
    F check
    F codes
    F features
    F font
    F glyphs
    F message
    F messages
    F nofsteps
    F register
    F reset
    F start
    F stop
  F stop

```
  T transparencies
    F reset
    F set
    F setlist
F traverse
F traverseid
T typesetters
  F hbox
  F hpack
  F tohbox
  F tohpack
  F tonodes
  F tovbox
  F tovpack
  F vpack
F unsetattribute
F upcomingproperties
F usedlist
F vianodes
F vianuts
F visualizebox
T visualizers
  F attribute
  T attributes
  F box
  F definelayer
  F enable
  T filters
    N cglue
    N ckern
    N continuation
    N hglue
    N hkern
    N hpenalty
    N pglue
    N sglue
    N short
    N toddler
    N vglue
    N vkern
    N vpenalty
  F getusedfont
  F handler
  F markfonts
T modes
  N boundary
  N cglue
  N ckern
  N depth
  N dir
  N discretionary
  N expansion
  N fontkern
  N glue
  N glyph
  N hbox
  N hglue
  N hkern
  N hpenalty
  N insert
  N italic
  N kern
  N line
  N marginkern
  N mark
  N math
  N mathglue
  N mathkern
  N origin
  N par
  N penalty
  N pglue
  N sglue
  N short
  N simple
  N simplehbox
  N simplevbox
  N simplevtop
  N space
  N strut
  N toddler
  N user
  N vbox
  N vglue
  N vkern
  N vpenalty
  N vtop
  N whatsit
```

```
    F register
    F registercache
    F setfont
    F setlayer
    F setruledglyph
    F setvisual
  F vpack
  D whatsitcodes
  F write
T number
  F %
  F basepoints
  F bytetodecimal
  F clamp
  F compactfloat
  F decimaltobyte
  D dimenfactors
  F fractiontobyte
  F idiv
  N maxdimen
  F nopts
  F percent
  F points
  F pts
  F splitdimen
  F to16dot16
  F tobasepoints
  F tobitstring
  F tocentimeters
  F tociceros
  F tocontext
  F todidots
  F todimen
  F toediths
  F toinches
  F tomillimeters
  F tonumberf
  F tonumberg
  F topicas
  F topoints
  F toscaled
  F toscaledpoints
  F totoves
  F valid
T objects
  T data
  F dimensions
  F found
  N n
  F page
  F reference
  F register
  F restore
T optional
  T curl
    F escape
    F fetch
    F getversion
    F initialize
    F unescape
  T foreign
    F abivalues
    F getbuffer
    F initialize
    F load
    F newbuffer
    F totable
    F types
  T ghostscript
    F execute
    F initialize
  T graphicsmagick
    F execute
    F getnoisetypes
    F initialize
  T hb
    F getshapers
    F getversion
    F initialize
    F loadfont
    F shapestring
  T imagemagick
    F execute
    F initialize
  T kpse
    F expand_braces
    F expand_path
    F expand_var
```

```
  F find_file
  F find_files
  F get_file_types
  F initialize
  F readable_file
  F set_program_name
  F var_value
T library
  F load
T loaded
T lz4
  F compress
  F decompresssize
  F framecompress
  F framedecompress
  F initialize
T lzma
  F compress
  F decompress
  F initialize
T lzo
  F compress
  F decompresssize
  F initialize
T mujs
  F dofile
  F execute
  F initialize
  F reset
  F setclosefile
  F setconsole
  F setfindfile
  F setopenfile
  F setreadfile
  F setseekfile
T mysql
  F close
  F execute
  F getmessage
  F initialize
  F open
T openssl
  F getversion
  F initialize
  F sign
  F verify
T postgress
  F close
  F execute
  F getmessage
  F initialize
  F open
T sqlite
  F close
  F execute
  F getmessage
  F initialize
  F open
T zint
  F execute
  F initialize
T zstd
  F compress
  F decompress
  F initialize
F optionalrequire
T os
  F __getenv__
  F __setenv__
  S binsuffix
  T binsuffixes
  N bits
  F clock
  F converttime
  F date
  F difftime
  F enableansi
  D env
  F execute
  F exit
  F fulltime
  F getcodepage
  F getenv
  F getnamevalues
  F gettimeofday
  F gettypevalues
  F getunamefields
  F isleapyear
```

F launch
S libsuffix
F localtime
S name
S newline
F nofdays
F now
F pipeto
S platform
F remove
F rename
F resultof
F runtime
T selfarg
S selfbin
S selfcore
S selfdir
S selflink
S selfname
S selfpath
F serialwrite
F setenv
F setexitcode
F setlocale
F sleep
F startuptime
F time
F timezone
F tmpname
F today
S type
F uname
F uuid
F validdate
F weekday
F where
F which
T package
S config
S cpath
F extralibpath
F extralibpaths
F extraluapath
F extraluapaths
T helpers
T builtin
F path specification
F preload table
F cleanpath
F loaded
F loadedaslib
F loadedbyformat
F loadedbyname
F loadedbypath
F lualibfile
T methods
F all in one fallback
F already loaded
F cpath specification
F lib extra list
F lib variable format
F lua extra list
F lua variable format
F not loaded
F path specification
F preload table
F qualified path
F reset loaded
F registerpath
F report
T sequence
F showused
B trace
B traceused
F unload
F libpaths
T loaded
B anch-loc
B anch-pgr
B anch-snc
B back-exp
B back-exp-imp-fnt
B back-exp-imp-mth
B back-exp-imp-ref
B back-exp-imp-tag
B back-imp-lua
B back-imp-mps
B back-imp-pdf

B back-imp-pdp
B blob-ini
B buff-imp-default
B buff-imp-escaped
B buff-imp-lua
B buff-imp-mp
B buff-imp-nested
B buff-imp-parsed-xml
B buff-imp-tex
B buff-imp-xml
B buff-ini
B buff-par
B buff-ver
B char-enc
B chem-ini
B chem-str
B cldf-com
B cldf-ver
B colo-icc
B colo-ini
B cont-run
B core-con
B core-ctx
B core-dat
B core-sys
T curl
  F escape
  F fetch
  F getversion
  S libfile
  S libpath
  F unescape
B driv-shp
B file-mod
B file-syn
B font-afk
B font-agl
B font-aux
B font-cff
B font-chk
B font-cid
B font-col
B font-con
B font-ctx
B font-def
B font-dsp
B font-enc
B font-enh
B font-fbk
B font-fmp
B font-hsh
B font-imp-checks
B font-imp-combining
B font-imp-compound
B font-imp-digits
B font-imp-dimensions
B font-imp-effects
B font-imp-italics
B font-imp-ligatures
B font-imp-math
B font-imp-notused
B font-imp-properties
B font-imp-quality
B font-imp-reorder
B font-imp-scripts
B font-imp-spacekerns
B font-imp-tex
B font-imp-text
B font-imp-tracing
B font-imp-tweaks
B font-imp-unicode
B font-ini
B font-lig
B font-log
B font-lua
B font-map
B font-mpf
B font-mps
B font-nod
B font-ogr
B font-one
B font-onr
B font-osd
B font-ota
B font-otc
B font-otd
B font-oth
B font-oti

```
B font-otj
B font-otl
B font-oto
B font-otr
B font-ots
B font-ott
B font-oup
B font-pat
B font-prv
B font-san
B font-sel
B font-shp
B font-sol
B font-syn
B font-tfm
B font-tpk
B font-trt
B font-ttf
B font-txt
B font-vfc
B font-vir
B good-ctx
B good-gen
B good-ini
B good-mth
B grph-bmp
B grph-con
B grph-epd
B grph-fil
B grph-img
B grph-inc
B grph-pat
B grph-raw
B grph-rul
B grph-trf
B grph-u3d
B java-ini
T json
  F load
  F tojson
  F tolua
  F tostring
B lang-cnt
B lang-def
B lang-dis
B lang-hup
B lang-hyp
B lang-ini
B lang-lab
B lang-rep
B lang-tra
B lang-txt
B lang-url
B lang-wrd
B libs-imp-curl
B libs-imp-ghostscript
B libs-imp-graphicsmagick
B libs-ini
B lpdf-ano
B lpdf-col
B lpdf-epa
B lpdf-epd
B lpdf-fix
B lpdf-fix-imp-contents
B lpdf-fix-imp-fonts
B lpdf-fld
B lpdf-fmt
B lpdf-grp
B lpdf-img
B lpdf-ini
B lpdf-lmt
B lpdf-mis
B lpdf-ren
B lpdf-rul
B lpdf-sig
B lpdf-tag
B lpdf-u3d
B lpdf-wid
B lpdf-xmp
B lxml-css
B lxml-dir
B lxml-ent
B lxml-ini
B lxml-mms
B lxml-sor
B lxml-tex
B math-act
B math-ali
```

B math-dim
B math-ext
B math-fbk
B math-fnt
B math-frc
B math-inc
B math-ini
B math-map
B math-mps
B math-noa
B math-pre
B math-rad
B math-ren
B math-spa
B math-tag
B math-txt
B math-vfu
B meta-blb
B meta-fnt
B meta-fun
B meta-imp-txt
B meta-ini
B meta-lua
B meta-nod
B meta-pdf
B meta-tex
B mlib-ctx
B mlib-fio
B mlib-int
B mlib-lmp
B mlib-lmt
B mlib-lua
B mlib-mat
B mlib-mpf
B mlib-msh
B mlib-pdf
B mlib-pos
B mlib-pps
B mlib-ptr
B mlib-pts
B mlib-ran
B mlib-run
B mlib-scn
B mlib-snc
B mlib-svg
B node-ali
B node-bck
B node-fnt
B node-par
B node-ref
B node-rul
B node-tra
B node-typ
B pack-obj
B pack-ori
B pack-rul
B page-blk
B page-cst
B page-flt
B page-ini
B page-inj
B page-ins
B page-lin
B page-mix
B page-otr
B page-pst
B page-sel
B page-str
T pdfdecode
T pdfe
  F arraytotable
  F close
  F closestream
  F dictionarytotable
  F getarray
  F getboolean
  F getbox
  F getcatalog
  F getdictionary
  F getencodingvalues
  F getfieldtypes
  F getfromarray
  F getfromdictionary
  F getfromobject
  F getfromreference
  F getfromstream
  F getinfo
  F getinteger

```
  F getmemoryusage
  F getname
  F getnofobjects
  F getnofpages
  F getnumber
  F getobjectrange
  F getpage
  F getpages
  F getpermissions
  F getsize
  F getstatus
  F getstatusvalues
  F getstream
  F getstring
  F gettrailer
  F getversion
  F new
  F open
  F openfile
  F openstream
  F pagestotable
  F readfromstream
  F readwholestream
  F type
  F unencrypt
B phys-dim
T pngdecode
  F applyfilter
  F expand
  F frompalette
  F interlace
  F makemask
  F palettemask
  F reduce
  F setexperiment
  F splitmask
  F tocmyk
  F togray
  F tomask
  F transparentmask
T posit
  F NaN
  F NaR
  F __add
  F __band
  F __bor
  F __bxor
  F __div
  F __eq
  F __le
  F __lt
  F __mul
  S __name
  F __pow
  F __shl
  F __shr
  F __sub
  F __tostring
  F __unm
  F abs
  F acos
  F asin
  F atan
  F band
  F bor
  F bxor
  F ceil
  F conj
  F copy
  F cos
  F exp
  F exp2
  F expand
  F floor
  F frombyte
  F fromchar
  F fromposit
  F integer
  F log
  F log10
  F log1p
  F log2
  F logb
  F max
  F min
  F modf
  F new
  F pow
```

```
  F rotate
  F round
  F rounded
  F shift
  F sin
  F sqrt
  F tan
  F tobyte
  F tochar
  F tonumber
  F toposit
  F tostring
T potrace
  F checked
  F concat
  F contourplot
  F convert
  F count
  F flush
  F free
  F fromfile
  F getbitmap
  F getnewfields
  F getpolicyvalues
  F getprocessfields
  F new
  F process
  F setbitmap
  F stripped
  F totable
  F trace
T process
  F __gc
  S __name
  F __tostring
  F close
  F open
  F poll
  F read
  F tostring
B publ-aut
B publ-dat
B publ-fnd
B publ-inc
B publ-ini
B publ-jrn
B publ-oth
B publ-reg
B publ-sor
B publ-tra
B publ-usr
T qrcodegen
  F bitmap
  F generate
B regi-ini
B scrn-but
B scrn-fld
B scrn-hlp
B scrn-ini
B scrn-pag
B scrn-ref
B scrn-wid
B scrp-cjk
B scrp-eth
B scrp-ini
B scrp-tha
B scrp-tib
T security
  F checked
  F getactions
  F gettargets
  F resetdebug
  F setchecker
T sequencer
  F addbytestobuffer
  F addformattobuffer
  F addpackingtobuffer
  F addtobuffer
  T extensions
    F chruni
    F date
    F daylong
    F dayoftheweek
    F dayshort
    F edate
    F eday
    F edaylong
    F edayshort
```

```
    F eminute
    F emonth
    F emonthlong
    F emonthshort
    F esecond
    F eweek
    F eweekday
    F eyear
    F font:features
    F font:name
    F lua
    F monthlong
    F monthshort
    F tex
    F texexp
    F unichr
    F weekday
    F xml
  F fastserialize
  F format
  F getbufferdata
  F getbuffersize
  F newbuffer
  F sequenced
  F serialize
  F sortedhash
  F tabstr_boolean
  F tabstr_flat
  F tabstr_mixed
  F tabstr_normal
  F tostring
T serial
  F __gc
  S __name
  F __tostring
  F close
  F open
  F send
  F tostring
  F write
T server
  F httpserver
  F supported
T sha2
  F HASH256
  F HASH384
  F HASH512
  F HEX256
  F HEX384
  F HEX512
  F digest256
  F digest384
  F digest512
  F hash256
  F hash384
  F hash512
  F hex256
  F hex384
  F hex512
  F sum256
  F sum384
  F sum512
T sio
  F read2dot14
  F readbytes
  F readbytetable
  F readcardinal1
  F readcardinal1le
  F readcardinal2
  F readcardinal2le
  F readcardinal3
  F readcardinal3le
  F readcardinal4
  F readcardinal4le
  F readcardinaltable
  F readcline
  F readcstring
  F readdouble
  F readdoublele
  F readfixed2
  F readfixed4
  F readfloat
  F readfloatle
  F readfloatle12
  F readfloatle6
  F readinteger1
  F readinteger1le
  F readinteger2
```

```
  F readinteger2le
  F readinteger3
  F readinteger3le
  F readinteger4
  F readinteger4le
  F readintegertable
  F tocardinal1
  F tocardinal1le
  F tocardinal2
  F tocardinal2le
  F tocardinal3
  F tocardinal3le
  F tocardinal4
  F tocardinal4le
  F tocardinal8
  F tocardinal8le
  F tointeger1
  F tointeger1le
  F tointeger2
  F tointeger2le
  F tointeger3
  F tointeger3le
  F tointeger4
  F tointeger4le
  F tointeger8
  F tointeger8le
B sort-ini
B sort-lan
B spac-ali
B spac-brk
B spac-chr
B spac-hor
B spac-ovl
B spac-par
B spac-pas
B spac-prf
B spac-twi
B spac-ver
T sparse
  F concat
  F get
  F max
  F min
  F new
  F range
  F restore
  F set
  F traverse
  F wipe
T status
  F getbalancestate
  F getbufferstate
  F getcallbackstate
  F getconstants
  F getdumpstate
  F geterrorlinestate
  F geterrorstate
  F getexpandstate
  F getfilestate
  F getfontstate
  F gethalferrorlinestate
  F gethashstate
  F gethyphenationstate
  F getinputstate
  F getinsertstate
  F getlanguagestate
  F getlinebreakstate
  F getlookupstate
  F getluastate
  F getmarkstate
  F getmvlstate
  F getneststate
  F getnodestate
  F getparameterstate
  F getpoolstate
  F getreadstate
  F getsavestate
  F getsparsestate
  F getstringstate
  F gettexstate
  F gettokenstate
  F getwarningstate
  T iocodes
  F list
  F resetmessages
B strc-bkm
B strc-blk
B strc-con
```

B strc-doc
B strc-flt
B strc-ini
B strc-itm
B strc-lev
B strc-lst
B strc-mar
B strc-mat
B strc-not
B strc-num
B strc-pag
B strc-ref
B strc-reg
B strc-rsc
B strc-syn
B strc-tag
B strc-usr
T string
  F booleanstring
  F byte
  F bytepairs
  F bytes
  F bytetable
  F char
  F characterpairs
  F characters
  F checkedsplit
  F chrtointeger
  F collapsespaces
  F containsws
  F count
  F dectointeger
  F dump
  F escapedpattern
  F f6
  F fd
  F fd3
  F fd6
  F fd9
  F find
  F format
  F formatted
  F formatter
  D formatters
F formatting
F fromunicode16
F fullstrip
F g6
F gd
F gmatch
F gsub
T hashes
  T X00
  T spaces
F hextocharacters
F hextointeger
F is_boolean
F is_empty
F itself
F len
F limit
F linetable
F longtostring
F lower
F match
F nospaces
F octtointeger
F optionalquoted
F pack
F packrowscolumns
F packsize
F quote
F quoted
F rep
F replacenewlines
F reverse
F split
F splitintolines
F splitlines
F splitup
F strip
F sub
F texhashed
F texnewlines
F tformat
F toHEX
F toboolean
F tobytes

F tocontext
F todec
F todimen
F tohex
F tonodes
F topattern
F topdfeight
F topdfsixteen
F topdfstring
F totable
F tounicode16
F toutf
F toutf16
F toutf32
F toutf8
F unpack
F unquote
F unquoted
F upper
F utf16toutf8
F utfcharacter
F utfcharacters
F utfcharactertable
F utflength
F utfpadd
F utftabletostring
F utfvalue
F utfvalues
F utfvaluetable
F valid
F wordsplitter
B symb-emj
B symb-ini
B syst-cmp
B tabl-ali
B tabl-ntb
B tabl-tbl
B tabl-xtb
T table
F append
F are_equal
F combine
F compact
F concat
F contains
F copy
F count
F create
F derive
F deserialize
F fastcopy
F fastserialize
F filtered
F flattened
F fromhash
F getn
F has_one_entry
F hashed
F identical
F imerge
F imerged
F insert
F is_empty
F keys
F load
F loweredkeys
F makeweak
F merge
F merged
F mirrored
F move
F pack
F prepend
F print
F remove
F reverse
F reversed
F save
F sequenced
F serialize
F setmetatablecall
F setmetatableindex
F setmetatableindices
F setmetatablenewindex
F sort
F sorted
F sortedhash
F sortedhashkeys

F sortedhashonly
F sortedindexonly
F sortedkeys
F sortedpairs
F sparse
F strip
F sub
F swapped
F tocontext
F tocsv
F tofile
F tohash
F toxml
F unique
F unpack
B task-ini
T tex
T amcode
T attribute
F attributetracking
D automigrationcodes
D autoparagraphcodes
F badness
D badnessmodecodes
F balance
D balancecallbackcodes
T boundaries
D names
D numbers
F system
T box
D boxcontinuationcodes
D boxoptioncodes
T boxresources
F getbox
F getdimensions
F save
F use
D breakcodes
D buildcodes
T catcode
T cccode
D charactercontrolcodes
D charactertagcodes
F chardef
D classoptioncodes
T codes
D conditionals
D constants
T count
F cprint
N ctdcatcodes
N ctxcatcodes
F definefont
T delcode
T dimen
F dimensiondef
D directioncodes
D directives
D discoptioncodes
D discpartcodes
F dontcomplain
D doublescriptoptioncodes
F enableprimitives
F equal
F error
F expandasvalue
D experiments
F extraprimitives
F fatalerror
D fillcodes
D flagcodes
F fontidentifier
F fontname
F forcehmode
F forceinputstatefile
F forceinputstateline
F fprint
D frozenparcodes
F get
F getadjustoptionvalues
F getalignmentcontextvalues
F getamcode
F getappendadjustcontextvalues
F getappendmigratecontextvalues
F getattribute
F getautomigrationvalues
F getautoparagraphvalues

F getbadnessmodevalues
F getbalancecallbackvalues
F getbalanceparameterfields
F getbalanceresultfields
F getbalancestepoptionvalues
F getbox
F getboxcontinuationvalues
F getboxdir
F getboxoptionvalues
F getboxresourcebox
F getboxresourcedimensions
F getbreakcontextvalues
F getbuildcontextvalues
F getcardinalvalue
F getcatcode
F getcccode
F getcharactercontrolvalues
F getcharactertagvalues
F getcount
F getcurrentmvl
F getdelcode
F getdelcodes
F getdimen
F getdimensionvalue
F getdirectionvalues
F getdiscoptionvalues
F getdiscpartvalues
F getdoublescriptoptionvalues
F getemptyparagraphmodevalues
F geterrorrecoverymodevalues
F geterrorvalues
F getfillvalues
F getflagvalues
F getfloat
F getfontdimension
F getfontoffamily
F getfrozenparvalues
F getglue
F getglueoptionvalues
F getglyphdata
F getglyphdiscvalues
F getglyphoptionvalues
F getglyphprotectionvalues
F getglyphscales
F getglyphscript
F getglyphstate
F getgroupvalues
F gethccode
F gethelptext
F gethmcode
F gethyphenationvalues
F getiftypes
F getinputstatefile
F getinputstateline
F getinputstatemode
F getinsertcategoryvalues
F getinsertcontent
F getinsertdepth
F getinsertdistance
F getinsertheight
F getinsertlimit
F getinsertmaxplaced
F getinsertmultiplier
F getinsertoptionvalues
F getinsertsplitvalues
F getinsertwidth
F getintegervalue
F getinteraction
F getinteractionmodes
F getiovalues
F getkerneloptionvalues
F getkernoptionvalues
F getlargestusedmark
F getlccode
F getlinebreakparameterfields
F getlinebreakresultfields
F getlinebreakstatevalues
F getlinedir
F getlist
F getlistanchorvalues
F getlistfields
F getlistgeometryvalues
F getlistsignvalues
F getlocalbox
F getlocalboxlocations
F getlocallevel
F getmark
F getmarknames

F getmath
F getmathclassoptionvalues
F getmathcode
F getmathcodes
F getmathcontrolvalues
F getmathdir
F getmathgluevalues
F getmathoptionvalues
F getmathparametervalues
F getmathscriptordervalues
F getmathscriptsmodevalues
F getmathstylenamevalues
F getmathstylevalues
F getmathstylevariant
F getmathsurroundvalues
F getmathvariantpresets
F getmathvariantvalues
F getmeasure
F getmissingcharactervalues
F getmode
F getmodevalues
F getmuglue
F getmuskip
F getmvloptionvalues
F getnest
F getnestfields
F getnestlevel
F getnoadoptionvalues
F getnormalizelinevalues
F getnormalizeparvalues
F getnospacesmodevalues
F getoutputactive
F getoverloadstate
F getpacktypevalues
F getpagecontextvalues
F getpagestate
F getpagestatevalues
F getparagraphfillmodevalues
F getparagraphoptionvalues
F getparametermodevalues
F getparcontextvalues
F getpardataspecifications
F getpardir
F getparmodevalues
F getparstate
F getparstatefields
F getpartriggervalues
F getpenaltyoptionvalues
F getpositvalue
F getpreposststatevalues
F getprimitivelegacies
F getprimitiveorigins
F getprotrusionboundaryvalues
F getregisterindex
F getruleoptionvalues
F getrunstate
F getrunstatevalues
F getsfcode
F getshapingpenaltiesvalues
F getskip
F getsnappingvalues
F getspacefactorvalues
F getspaceskipvalues
F getspcode
F getspecialmathclassvalues
F getspecification
F getspecificationoptionvalues
F gettextcontrolvalues
F gettextdir
F gettoks
F getuccode
F getuleaderlocationvalues
F getunitclassvalues
F getusedmarks
F getvariablefamilyvalues
F getvsplitcontextvalues
T glue
D glueoptioncodes
D glyphdisccodes
D glyphoptioncodes
D groupcodes
F hashtokens
T hccode
T hmcode
N hshcatcodes
D hyphenationcodes
D ifs
N inicatcodes

D insertcategorycodes
D insertoptioncodes
D insertsplitcodes
F integerdef
D interactioncodes
F isattribute
F isbox
F iscount
F isdefined
F isdimen
F isfloat
F isglue
F ismuglue
F ismuskip
F isprintable
F isskip
F istoks
F lastnodetype
T lccode
F less
F lessequal
F linebreak
D linebreakstatecodes
D listanchorcodes
D listgeometrycodes
T lists
D listsigncodes
N luacatcodes
T magicconstants
  S activecharacternamespace
  N allfitnessvalues
  N assumedmathcontrol
  N awfulbad
  N decentcriterion
  N defaultcatcodetable
  N defaultcharactercontrol
  N defaultdeadcycles
  N defaulteqnogapstep
  N defaulthangafter
  N defaultoutputbox
  N defaultpredisplaygap
  N defaultrule
  N defaultspacefactor
  N defaulttolerance
N deplorable
N ejectpenalty
N ignoredepth
N infinitebad
N infinitepenalty
N infinity
N largewidthexcess
N loosecriterion
N mathallclass
N mathbeginclass
N mathdefaultpenalty
N mathendclass
N mathfirstuserclass
N mathlastuserclass
N maxattributeregisterindex
N maxboxregisterindex
N maxbytecodeindex
N maxcalculatedbadness
N maxcardinal
N maxcharactercode
N maxdatavalue
N maxdimen
N maxdimenregisterindex
N maxdimension
N maxdimensionregisterindex
N maxendlinecharacter
N maxfloatregisterindex
N maxfontadjustshrinkfactor
N maxfontadjuststep
N maxfontadjuststretchfactor
N maxfunctionreference
N maxglueregisterindex
N maxhalfvalue
N maxhalfword
N maxinteger
N maxintegerregisterindex
N maxintregisterindex
N maxlimitedscale
N maxmarkindex
N maxmathclasscode
N maxmathfamilyindex
N maxmathscalingfactor
N maxmathstylescale
N maxmugleregisterindex

N maxmvlindex
N maxnewlinecharacter
N maxnofbytecodes
N maxnofcatcodetables
N maxnoffitnessvalues
N maxnoffonts
N maxnoflanguages
N maxnofmarks
N maxnofmathfamilies
N maxquarterword
N maxscalefactor
N maxsizeofword
N maxspacefactor
N maxtoksregisterindex
N maxtwinlength
N mincardinal
N mindatavalue
N mindimen
N mindimension
N minhalfword
N mininfinity
N mininteger
N minmvlindex
N minnoffitnessvalues
N minquarterword
N minscalefactor
N minspacefactor
N nocatcodetable
N null
N nullflag
N nullfont
N onebp
N presetrulethickness
N runningrule
N saparthigh
N sapartlow
N sapartmiddle
N smallstretchability
N specialspacefactor
N texeqtbsize
N texhashprime
N texhashsize
N texmemorymode
N two
N undefinedmathparameter
N unity
N unusedattributevalue
N unusedmathfamily
N unusedmathstyle
N unusedscriptvalue
N unusedstatevalue
N zeroglue
F mathchardef
T mathcode
D mathcontrolcodes
D mathoptioncodes
D mathparametercodes
D mathscriptordercodes
D mathscriptsmodecodes
T modelevels
N horizontal
N math
N unset
N vertical
D modes
F mprint
T muglue
T muskip
D mvloptioncodes
T nest
N nilcatcodes
D noadoptioncodes
D normalizelinecodes
D normalizeparcodes
D nospacesmodecodes
N notcatcodes
F number
D paragraphfillmodecodes
D paragraphoptioncodes
D parcontextcodes
D partriggercodes
D penaltyoptioncodes
F poplocal
F popsavelevel
T posit
F positdef
F preparelinebreak
F primitives

F print
D protrusionboundarycodes
N prtcatcodes
F pushlocal
F pushsavelevel
F quitlocal
F quittoks
F resetparagraph
N rlncatcodes
F romannumeral
F round
D ruleoptioncodes
F runlocal
D runstatecodes
F runstring
F runtoks
F saveboxresource
F scale
F scantoks
F set
F setamcode
F setattribute
F setbalanceshape
F setbox
F setboxdir
F setcardinalvalue
F setcatcode
F setcccode
F setconditional
F setcount
F setdelcode
F setdimen
F setdimensionvalue
F setfloat
F setglue
F setglyphdata
F setglyphscript
F setglyphstate
F sethccode
F sethmcode
F setinputstatefile
F setinputstateline
F setinputstatemode
F setinsertcontent
F setinsertdistance
F setinsertlimit
F setinsertmaxplaced
F setinsertmultiplier
F setintegervalue
F setinteraction
F setlccode
F setlinedir
F setlist
F setlocalbox
F setmath
F setmathcode
F setmathdir
F setmuglue
F setmuskip
F setnest
F setoverloadstate
F setpardir
F setpositvalue
F setrunstate
F setsfcode
F setskip
F setspcode
F settextdir
F settoks
F setuccode
T sfcode
D shapingpenaltiescodes
F shiftparshape
F shipout
F showcontext
T skip
D snappingcodes
F snapshotpar
F sp
D spacefactorcodes
D spaceskipcodes
D specialmathclasscodes
D specificationoptioncodes
F splitbox
D splitcodes
F sprint
F stringtocodesbitmap
D systemmodes

F takebox
N texcatcodes
D textcontrolcodes
T toks
F tonumber
F toscaled
N tpacatcodes
N tpbcatcodes
F tprint
F trackedattribute
D trackers
F triggerbuildpage
N txtcatcodes
T uccode
F uprint
F useboxresource
D userdiscoptioncodes
D userglyphoptioncodes
N vrbcatcodes
F write
T texio
F closeinput
F forceendoffile
F getinputindex
F getselectorvalues
F getsourcefilename
F setlogfile
F terminal
F write
F write_nl
F writenl
F writeselector
F writeselectorlf
F writeselectornl
T timer
S __name
F __tostring
F current
F elapsed
F elapsedms
F elapsedus
F elapsedμs
F istiming
F new
F reset
F setoffset
F sleepms
F start
F stop
F tostring
T token
F create
F expand
F expand_macro
F expandmacro
F future_expand
F futureexpand
F get_active
F get_cmdchrcs
F get_cmdname
F get_command
F get_csname
F get_cstoken
F get_dimension
F get_expandable
F get_fields
F get_flags
F get_frozen
F get_id
F get_immutable
F get_index
F get_instance
F get_integer
F get_macro
F get_meaning
F get_noaligned
F get_parameters
F get_permanent
F get_primitive
F get_protected
F get_range
F get_tok
F get_tolerant
F getactive
F getcmdchrcs
F getcmdname
F getcommand
F getcommandvalues

F getconstant
F getcsname
F getcstoken
F getdimension
F getexpandable
F getexpansion
F getfields
F getflags
F getfrozen
F getfunctionvalues
F getid
F getimmutable
F getindex
F getinstance
F getinteger
F getlength
F getmacro
F getmeaning
F getnoaligned
F getparameters
F getpermanent
F getprimitive
F getprimitives
F getprotected
F getrange
F gettok
F gettolerant
F gobble
F gobble_dimension
F gobble_integer
F gobbledimension
F gobbleinteger
F grab
F grabstring
F inhibit
F is_defined
F is_next_char
F is_token
F isactivestring
F isdefined
F isnextchar
F istoken
F locatemacro
F new
F peek_next
F peek_next_char
F peek_next_expanded
F peeknext
F peeknextchar
F peeknextexpanded
F pop_macro
F popmacro
F push_macro
F pushmacro
F put_back
F put_next
F putback
F putnext
F save_lua
F savelua
F scan_argument
F scan_box
F scan_cardinal
F scan_char
F scan_cmdchr
F scan_cmdchr_expanded
F scan_code
F scan_csname
F scan_delimited
F scan_dimen
F scan_float
F scan_glue
F scan_integer
F scan_key
F scan_keyword
F scan_keyword_cs
F scan_letters
F scan_luacardinal
F scan_luainteger
F scan_luanumber
F scan_next
F scan_next_char
F scan_next_expanded
F scan_real
F scan_scale
F scan_skip
F scan_string
F scan_token

F scan_token_code
F scan_tokenlist
F scan_toks
F scan_value
F scan_word
F scanargument
F scanbox
F scancardinal
F scanchar
F scancmdchr
F scancmdchrexpanded
F scancode
F scancsname
F scancstoken
F scandelimited
F scandetokened
F scandimen
F scandimenargument
F scandimension
F scandimensionargument
F scanfloat
F scanglue
F scanint
F scaninteger
F scanintegerargument
F scankey
F scankeyword
F scankeywordcs
F scanletters
F scanluacardinal
F scanluainteger
F scanluanumber
F scannext
F scannextchar
F scannextexpanded
F scanposit
F scanreal
F scanscale
F scanskip
F scanstring
F scantoken
F scantokencode
F scantokenlist
F scantokenstring
F scantoks
F scanvalue
F scanword
F serialize
F set_dimension
F set_integer
F set_lua
F set_macro
F setdimension
F setinteger
F setlua
F setmacro
F setmacrofrommark
F setmacrotonothing
F skip_next
F skip_next_expanded
F skipnext
F skipnextexpanded
F type
F undefine_macro
F undefinemacro
B trac-bld
B trac-jus
B trac-par
B trac-riv
B trac-sig
B trac-vis
B type-ini
B typo-adj
B typo-bld
B typo-brk
B typo-cap
B typo-chr
B typo-cln
B typo-dha
B typo-dif
B typo-dig
B typo-dir
B typo-drp
B typo-duc
B typo-fkr
B typo-fln
B typo-hid
B typo-inj

B typo-itc
B typo-krn
B typo-lan
B typo-lbx
B typo-man
B typo-mar
B typo-ovl
B typo-pag
B typo-par
B typo-pnc
B typo-prc
B typo-rep
B typo-rub
B typo-spa
B typo-stc
B typo-sus
B typo-syn
B typo-tal
B typo-wrp
B unic-ini
T utf8
  F char
  S charpattern
  F codepoint
  F codes
  F len
  F offset
T vector
  F add
  F append
  F average
  F ceiling
  F checkoverlap
  F collectoverlap
  F concat
  T contour
    F average
    F bounds
    F checkoverlap
    F collectoverlap
    F getarea
    F getmesh
    F makemesh
    F overlapping
  F show
  F sort
F copy
F crossproduct
F delete
F determinant
F div
F equal
F exchange
F floor
F get
F getdimensions
F getepsilon
F getmemory
F getmesh
F getmeshtypes
F getpointtypes
F getrc
F getrow
F getsize
F getstacking
F gettype
T helpers
  F points
  F transform
  F xrotation
  F xyzscale
  F yrotation
  F zrotation
F homogenize
F identity
F inner
F insert
F inverse
F ismesh
F ispoints
F issingular
F isvector
F iszero
T mesh
  F copy
  F get
  F getaverage
  F getdimensions

```
  F gettypevalues
  F ismesh
  F new
  F set
  F setaverage
  F tostring
  F totable
  F type
F meshname
F mul
F negate
F new
F normalize
T normals
  F flip
  F get
  F isnormals
  F new
  F set
  F tostring
  F totable
  F type
F onecolumn
F onerow
T point
  F add
  F copy
  F cross
  F crossproduct
  F dist
  F distance
  F div
  F dot
  F dotproduct
  F equal
  F get
  F ispoint
  F iszero
  F len
  F length
  F mul
  F neg
  F negate
  F new
  F norm
  F normalize
  F perp
  F perpendicular
  F set
  F sub
  F tostring
  F totable
  F type
T points
  F copy
  F get
  F getbounds
  F getindex
  F getnormal
  F getpool
  F gettriangle
  F getxy
  F getxytable
  F getxyz
  F getxyztable
  F grow
  F index
  F ispoints
  F new
  F prune
  F set
  F setindex
  F setnormal
  F setxy
  F setxyz
  F size
  F tostring
  F totable
  F type
F product
F remove
F replace
F round
F rowechelon
F set
F setepsilon
F setnext
F setrc
```

```
  F setstacking
  F slice
  F sort
  F sub
  F swap
  F tostring
  F totable
  F transpose
  F triangulate
  F truncate
  F type
T xcomplex
  F I
  F __add
  F __div
  F __eq
  F __mul
  S __name
  F __pow
  F __sub
  F __tostring
  F __unm
  F abs
  F acos
  F acosh
  F arg
  F asin
  F asinh
  F atan
  F atanh
  F conj
  F cos
  F cosh
  F dawson
  F erf
  F erfc
  F erfcx
  F erfi
  F exp
  F i
  F imag
  F log
  F new
  F pow
  F proj
  F real
  F sin
  F sinh
  F sqrt
  F tan
  F tanh
  F topair
  F tostring
  F totable
  F voigt
  F voigt_hwhm
T xdecimal
  F __add
  F __band
  F __bor
  F __bxor
  F __div
  F __eq
  F __idiv
  F __le
  F __lt
  F __mod
  F __mul
  S __name
  F __pow
  F __shl
  F __shr
  F __sub
  F __tostring
  F __unm
  F abs
  F band
  F bor
  F bxor
  F conj
  F copy
  F exp
  F getprecision
  F ln
  F log
  F max
  F min
  F minus
```

F new
F plus
F pow
F rotate
F setprecision
F shift
F sqrt
F toengstring
F tonumber
F tostring
F trim
T xinterval
F __add
F __div
F __eq
F __le
F __lt
F __mod
F __mul
S __name
F __pow
F __sub
F __tostring
F __unm
F abs
F acos
F acosh
F asin
F asinh
F asstring
F atan
F atanh
F cos
F cosh
F diameter
F equal
F erf
F erfc
F exp
F exp10
F exp2
F expm1
F greater
F greaterequal
F hull
F intersect
F less
F lessequal
F log
F log10
F log1p
F log2
F mid
F mod
F new
F neweps
F pow
F seteq
F setge
F setgt
F setle
F setlt
F sin
F sinh
F sqr
F sqrt
F tan
F tanh
F topair
F tostring
F totable
F usedendian
F within
T xmath
F acos
F acosh
F asin
F asinh
F atan
F atan2
F atanh
F cbrt
F ceil
F copysign
F cos
F cosh
F crossproduct
F deg

F dotproduct
F erf
F erfc
F exp
F exp2
F expm1
F fabs
F fdim
F floor
F fma
F fmax
F fmin
F fmod
F frexp
F gamma
F hypot
N inf
F isfinite
F isinf
F isnan
F isnormal
F j0
F j1
F jn
F ldexp
F lgamma
F log
F log10
F log1p
F log2
F logb
F modf
N nan
F nearbyint
F nextafter
F normalize
N pi
F pow
F rad
F remainder
F remquo
F round
F scalbn
F sin
F sinh
F sqrt
F tan
F tanh
F tgamma
F trunc
F y0
F y1
F yn
T xzip
F adler32
F compress
F compresssize
F crc32
F decompress
F decompresssize
T zbuffer
F bounds
F composite
F crop
F edgepoint
F flatten
F get
F getcolor
F getconstants
F getdepth
F getnormal
F getnormalmodes
F getopacity
F getsize
F implicit
F iszbuffer
F meshmesh
F new
F points
F process
F project
F resolve
F set
F setcolor
F setdepth
F setnormal
F setopacity
F setup

```
    F smoothen
    F stipple_0
    F stipple_1
    F stipple_2
    F stipple_3
    F stipple_4
    F stipple_setup
    F tobytes
    F tostring
    F totable
    F transform
    F trianglebounds
    F triangled
    F triangles
    F type
  T loaders
  F loadlib
  F luapaths
  S path
  F poplibpath
  F popluapath
  T preload
  F pushlibpath
  F pushluapath
  F searchpath
T pagebuilders
  T columnsets
    F add
    F addmvl
    F block
    F blockrows
    F check
    F checkmvl
    F clean
    T data
    F define
    F definesub
    F delayedsheet
    F finishflush
    F flushareas
    F flushcolumn
    F goto
    F gotoslot
    F limit
    F noto
    F prepareflush
    F presetsheets
    F presetspreadsheets
    F put
    F putdirect
    F registerarea
    F registersheet
    F registerspreadsheets
    F reset
    F resetdirect
    F reshape
    F setarea
    F setextra
    F sethsize
    F sethspan
    F setlines
    F setmvl
    F setpresent
    F setproperties
    F setstart
    F shape
    F showshape
    F state
    F status
    F submvl
    F submvlbalance
  T injections
    F flushafter
    F flushbefore
    F save
  T mixedcolumns
    F cleanup
    F finalize
    F getlist
    F getrest
    F getsplit
    F setsplit
F pairs
T parametersets
F pcall
T pdf
  F immediateobj
F pdfembeddedlink
```

T physics
  T units
    F registershortcut
    F registerunit
    D tables
F print
T publications
  F addtexentry
  F analyze
  F anywhere
  D authorcache
  D authorcollapsers
  T authorhashers
    F invertedshort
    F normal
    F normalinverted
    F normalshort
    F sequential
    F sequentialshort
    F short
  D authormap
  F authortoregister
  T btx
  T casters
    F author
    F keyword
    F pagenumber
    F range
  F checkeddataset
  T citevariants
    F author
    F authornum
    F authoryear
    F authoryears
    F category
    F default
    F entry
    F index
    F keywords
    F num
    F page
    F short
    F tag
    F textnum
    F year
D collected
T components
  F author
F concatstate
F converttoxml
T currentspecification
  S author
  T categories
    T article
      S category
      T extra
      T fields
        S author
        S editor
        S journal
        S keywords
        S note
        S number
        S pages
        S title
        S volume
        S year
      T optional
      T required
      T sets
        T author
      T virtual
    T book
      S category
      T extra
      T fields
        S address
        S author
        S edition
        S editor
        S keywords
        S note
        S number
        S publisher
        S subtitle
        S title
        S volume
        S year

```
    T optional
    T required
    T sets
      T author
      T editionset
    T virtual
  T demo-a
    S category
    T extra
    T fields
      S author
      S institution
      S organization
      S subtitle
      S title
      S year
    T optional
    T required
    T sets
      T author
    T virtual
  T demo-b
    S category
    T extra
    T fields
      S author
      S institution
      S organization
      S subtitle
      S title
      S year
    T optional
    T required
    T sets
      T authors
    T virtual
S comment
S copyright
T fields
S name
T types
  S author
  S editor
  S keywords
    S number
    S page
    S pages
    S volume
  S version
  D virtual
  T virtualfields
    B authornum
    B authoryear
    B authoryears
    B num
    B suffix
T datasets
T detailed
F endnotes_to_btx
T enhancer
  S arguments
  T askip
  T attr
  B dirty
  T gskip
  T kind
  T list
    T system
  T order
  N steps
T enhancers
  F details
  F order
  F suffixes
F finder
F firstofrange
F found
F get
F getcasted
F getdetail
F getdirect
F getfaster
F getfield
F getfuzzy
F getindex
D inspectors
T journals
  F abbreviated
```

```
  F add
  F expanded
  F load
  F save
F lastofrange
T lists
  F collectentries
  F combiinlist
  F fetchentries
  F filterall
  F flushcombi
  F flushentry
  F flushtag
  T methods
    F dataset
    F force
    F global
    F label
    F local
  F nofregistered
  F prepareentries
  F register
  F sameasprevious
  T sorters
    F cite
    F dataset
    F default
    F index
    F list
    F reference
    F short
    F used
  F uservariable
T listvariants
  F default
  F index
  F num
  F short
  F tag
F load
F loadbibdata
F loaddefinitionfile
T loaders
  F bbl
  F bib
  F buffer
  F endnote
  F json
  F lua
  F refman
  F registercleaner
  F xml
F loadreplacementfile
T meanings
F new
F okay
F oneorrange
F parenttag
F permitted
F prerollcmdstring
F refman_to_btx
F resolvedname
F save
T savers
  F bib
  F lua
  F xml
F search
F setcategory
F setspecification
F singularorplural
F sortedentries
T sortmethods
  T authortitle
    T sequence
  T authoryear
    T sequence
  T dataset
    T sequence
  T key
    T sequence
T specifications
F splitauthor
F splitoneauthor
T statistics
  N nofbytes
  N nofdatasets
  N nofdefinitions
```

```
    N nofshortcuts
  T tables
    D implicits
    D origins
    D privates
    D sets
    D specials
    D types
    D virtuals
  F tags
  T tracers
    F showdatasetauthors
    F showdatasetcompleteness
    F showdatasetfields
    F showentry
    F showfields
    F showhashedauthors
    F showtables
    F showvariants
  T typesetters
    F author
    F string
  F usedataset
  F usedentries
  T writers
    F author
    F keyword
    F pagenumber
    F range
F rawequal
F rawget
F rawlen
F rawset
T regimes
  D backmapping
  F cleanup
  F disable
  F enable
  F fromregime
  F list
  D mapping
  F pop
  F process
  F push
  F toregime
  F translate
F require
T resolvers
  F allprefixes
  F appendhash
  F automount
  F booleanvariable
  S cacheversion
  F checkedvariable
  F cleanedpathlist
  D cleaners
  F cleanpath
  F cleanpathlist
  F cleanupbinfile
  D concatinators
  S configbanner
  F configurationfiles
  D dangerous
  F datastate
  T decompressors
    F register
    F unregister
  T defaultsuffixes
  F dirstatus
  F dowithfilesandreport
  F dowithfilesintree
  F dowithpath
  F dowithvariable
  F expandbraces
  F expandedpathfromlist
  F expandedpathlist
  F expandedpathlistfromvariable
  F expandpath
  F expandpathfromvariable
  F expansion
  F extendtexmfvariable
  F filtered_from_content
  F find_file
  F find_files
  F findbinfile
  F findctxfile
  D finders
  F findfile
```

F findfiles
F findgivenfile
F findgivenfiles
F findlib
F findpath
F findpk
F findtexfile
F findwildcardfile
F findwildcardfiles
F formatofsuffix
F formatofvariable
D formats
F foundintree
F foundintrees
D generators
F get_from_content
F getdetails
F getenv
F getextrapaths
F getfilehashes
F gethashes
F getownpath
F getreadfilename
D hashers
S homedir
F ignorelibrary
F initialized
F installinputfilehandler
F installinputlinehandler
F jobpath
T jobs
  F collectstructure
  F currentcomponent
  F currentenvironment
  F currentproduct
  F currentproject
  F currentstructure
  F justacomponent
  F namelist
  D processors
  F productcomponent
  F usefile
F joinpath
F knownvariables
T libraries
  F optionalloaded
  F validoptional
F load
F loadbinfile
D loaders
F loadlualib
F loadtexfile
F loadtime
F locateformat
D locators
S luacnffallback
S luacnfname
S luacnfspec
S luacnfstate
T macros
  F convertfile
  F decodecomment
  F enablecomment
  F encodecomment
  F preprocessed
  F processmk
  F processmklx
  F processmkvi
  F version
N maxreadlevel
F methodhandler
F missinglibrary
F openbinfile
D openers
F openfile
F opentexfile
S ownpath
F popextrapath
F popinputname
F poppath
D prefixes
F prependhash
F pushextrapath
F pushinputname
F pushpath
F registerextrapath
F registerfile
F registerfilehash

F registerintrees
F registermethod
F registerzipfile
D relations
F renew
F renewcache
F repath
F reset
F resetextrapaths
F resetresolve
F resolve
D savers
F scandata
F scanfiles
T schemes
  T cleaners
    F md5
    F none
    F strip
  F cleanname
  F fetchstring
  F fetchtable
  F install
F setdynamic
F setenv
F showdetails
F showpath
F simplescanfiles
F splitconfigurationpath
F splitexpansions
F splitmethod
F splitpath
F stackpath
F starttiming
F stoptiming
D suffixes
D suffixmap
F suffixofformat
F texdatablob
F toppath
D tracers
F unexpandedpath
F unexpandedpathlist
F unresolve
F updaterelations
F uselibrary
D usertypes
F usezipfile
F validatedpath
F variable
F variableofformat
F variableofformatorsuffix
F wildcardpattern
T sandbox
  F enable
  F getrunner
  F possiblepath
  F registerrunner
  F setfilenamelogger
T scripts
  T autofontfeature
    F disable
    F enable
    F handler
  D colors
  F decomposehangul
  T defaults
    N inter_char_half_shrink_factor
    N inter_char_half_stretch_factor
    N inter_char_hangul_penalty
    N inter_char_quarter_shrink_factor
    N inter_char_quarter_stretch_factor
    N inter_char_shrink_factor
    N inter_char_stretch_factor
    N inter_word_stretch_factor
  F getdata
  F getinjector
  F getsplitter
  F getstatus
  D handlers
  D helpers
  D injectors
  T inserters
    F nobreakspace_after
    F nobreakspace_before
    F space_after
    F space_before
    F zerowidthspace_after

```
    F zerowidthspace_before
  F installdataset
  F installmethod
  D numbertodataset
  D numbertohandler
  F reset
  F set
  F setstatus
  D splitters
F select
T set
  F contains
  F create
  F tolist
  F tonumber
  F totable
F setinspector
F setmathparameters
F setmetatable
T sorters
  F basicsorter
  T comparers
    F basic
  T constants
    S defaultdigits
    S defaultlanguage
    S defaultmethod
    N digitsmaximum
    N digitsoffset
    N ignoredoffset
    N replacementoffset
    T validmethods
      B ch
      B mc
      B mm
      B pc
      B pm
      B uc
      B zc
      B zm
  D definitions
  F firstofsplit
  F packch
  F packuc
  F replacementlist
  F setlanguage
  F sort
  T splitters
    F utf
  F strip
  D tracers
  F update
T statistics
  F benchmarktimer
  F checkfmtstatus
  F currenttime
  F elapsed
  F elapsedindeed
  F elapsedseconds
  F elapsedtime
  B enable
  T feedback
    F info
    F processstates
    F register
    F reportstates
    F setstate
  F formatruntime
  F istiming
  F memused
  F register
  F resettiming
  F runtime
  F savefmtstatus
  F show
  F showmemory
  F showusage
  F starttiming
  F stoptiming
  N threshold
  F timed
  F tracefunction
T storage
  F allocate
  T data
  F mark
  F marked
  N max
```

```
  N min
  N nofmodules
  N noftables
  F register
  D shared
  D storedfunctions
  B strip
  N tofmodules
  N toftables
T streams
  F collect
  F disable
  F enable
  F flush
  F initialize
  F push
  F start
  F stop
  F synchronize
T structures
  F atlocation
  T blocks
    D collected
    F define
    F empty
    F print
    F save
    F select
    F setstate
    D states
    D tobesaved
    F uservariable
  T bookmarks
    T extras
      F get
      F mergesections
      F register
      F reset
      F tosections
    F finalize
    F flatten
    F installhandler
    F merge
    S method
    F overload
    F place
    F register
    F setopened
    F setup
  T counters
    F add
    F analyze
    F check
    D collected
    F compact
    F converted
    F currentvalue
    D data
    F define
    F first
    F get
    F isset
    F last
    F next
    F prev
    F previous
    F raw
    F record
    F reset
    F restart
    F restore
    F save
    F set
    F setlevel
    F setoffset
    F setown
    F setstate
    F setvalue
    T specials
      F userpage
    F subs
    D tobesaved
    F value
    F way
  F currentsectionnumber
  T descriptions
  T documents
    D data
```

F initialize
F preset
F reset
T floats
T formulas
T helpers
F analyze
F formulanumber
F merged
F page
F pageofinternal
F prefix
F prefixlastpage
F prefixpage
F simplify
F title
F touserdata
T inserts
F attach
D data
F define
F detach
F getdata
F getlocation
F getname
F getnumber
F nofdetached
F setlocation
F setup
D stored
T itemgroups
D collected
D tobesaved
T lists
F addto
F analyze
F bookmark
D cached
D collected
F discard
F enhance
T enhancers
F external
F filter
F formulanumber
F getresult
F groupindex
F hasnumberdata
F haspagedata
F hastitledata
F integrate
F iscached
D kinds
F label
F location
D names
F number
D ordered
F page
F popnesting
F prefix
F prefixednumber
F prefixedpage
F process
D pushed
F pushnesting
F rawnumber
F rawrealpage
F rawuserpage
F realpage
F reorder
F reordered
T result
F savedlistnumber
F savedlistprefixednumber
F savedlisttitle
D sectionblocks
F size
F title
D tobesaved
F use
F userdata
F userpage
F uservalue
T marks
F number
F title
T notes

```
  F checkpagechange
  F define
  F flushrange
  F get
  F getdeltapage
  F getinternal
  F getn
  F getstate
  F getstorecount
  F getstoreflushed
  F hascontent
  F internal
  F internalid
  F listindex
  D numbers
  F ordered
  F postpone
  F resetpostponed
  F restore
  F save
  F setstate
  D states
  F store
T pages
  F allmarked
  F analyze
  D collected
  F fraction
  F getlabels
  F in_body
  F is_odd
  F mark
  F marked
  F markedlist
  N nofpages
  F number
  F on_right
  F save
  D tobesaved
  F toranges
T references
  F analyze
  F checked
  F checkedfile
  F checkedfileorurl
  F checkedprogram
  F checkedrealpage
  F checkedurl
  D collected
U componentsplitter
  F currentmetadata
  F currentorder
  D currentset
  F define
  D defined
  D derived
  F enhance
  D executers
  F export
  T files
    T data
    F define
    F found
    F get
  F filter
  F filterdefault
  D filters
  D flaginternals
  F forceinnermode
  F from
  D functions
  F get
  F getcurrentlabel
  F getcurrentmetadata
  F getcurrentprefixspec
  F getinnermethod
  F getinternalcachedlistreference
  F getinternallistreference
  F getinternalreference
  F getoutermethod
  D handlers
  F identify
  F import
  F inject
  F injectcurrentset
S innermethod
  F integrate
  D internals
```

F load
F loadpresets
F mark
S outermethod
F pagefromhash
D pages
U prefixsplitter
D productdata
T programs
  T data
  F define
  F get
F realpageofpage
F referenced
U referencesplitter
D referred
F referredpage
F registerfinalizer
F registerinitializer
F registerpage
F reset
D runners
F set
F setandgetattribute
F setinternalreference
F setlinkmethod
F setnextinternal
F setnextorder
F setreferencerealpage
F setstructure
D specials
F splitcomponent
F splitprefix
F splitreference
F synchronizepage
T testrunners
  F inner
  F special
  F special operation
  F special operation with arguments
T testspecials
  F deltapage
  F embedded
  F i
  F internal
  F page
  F realpage
  F section
  F userpage
 D tobereferred
 D tobesaved
 D tracedpages
 T urls
   T data
   F define
   F found
   F get
   F untex
 D usedinternals
 D usedviews
 F valid
T registers
 F analyze
 D collected
 F compare
 F define
 F enhance
 F extend
 F filter
 F filtercollected
 F finalize
 F findinternal
 F flush
 F get
 F integrate
 F prepare
 F process
 F setmethod
 F sort
 F store
 D tobesaved
 F tweak
 F unique
 F use
 F userdata
T sections
 F autodepth
 F cct

```
  D collected
  F current
  F currentblock
  F currentid
  F currentlevel
  F currentsectionindex
  F depthnumber
  F finddata
  F findnumber
  F fullnumber
  F getcurrentlevel
  F getlevel
  F getnumber
  F internalreference
  D levelmap
  D levels
  F matchingtilldepth
  F numberatdepth
  F numbers
  F popblock
  F prefixedconverted
  F pushblock
  F register
  D registered
  F reportstructure
  F save
  T sectionblockdata
    T bodypart
      S bookmark
  F set
  F setblock
  F setchecker
  F setentry
  F setinitialblock
  F setlevel
  F setnumber
  F showstructure
  F structuredata
  F title
  D tobesaved
  F typesetnumber
  F userdata
  B verbose
T sets
  F define
  F get
  F getall
  D setlist
T specials
  D collected
  F retrieve
  F store
  D tobesaved
T synonyms
  F analyzed
  D collected
  F compare
  F define
  F enhance
  F filter
  F finalize
  F firstuserpage
  F flush
  F isshown
  F isused
  F meaning
  F pages
  F prepare
  F process
  F register
  F registershown
  F registerused
  F reset
  F resetall
  F resetlist
  F resetshown
  F resetused
  F sort
  F synonym
  D tobesaved
  F userpages
T tags
  F analyze
  T backend
    T checks
      F marginanchor
      F margintext
      F math
```

```
  F mrow
  F mtable
T destinationhash
T extras
  F adddestination
  F addimplicit
  F addinternal
  F addreference
  F combination
  F combinationpair
  F delimitedsymbol
  F description
  F descriptionsymbol
  F document
  F float
  F formulacontent
  F image
  F item
  F itemgroup
  F link
  F listitem
  F mmultiscripts
  F mover
  F mpgraphic
  F msub
  F msubsup
  F msup
  F munder
  F munderover
  F paragraph
  F publication
  F reference
  F registerlocation
  F registerpages
  F registerseparator
  F section
  F sorting
  F subsentencesymbol
  F synonym
  F tablecell
  F tabulate
  F tabulatecell
T finalizers
  F descriptions
  T fixes
    F linenumber
  F fontfaced
  T listdata
  T referencehash
  F setattribute
  F tofontface
  T usedimages
    T image
    T mpgraphic
  T usedstyles
    T construct
    T highlight
F checknesting
F current
F elementtag
F enabled
F exportbox
F finishexport
F getdescriptionindex
F getextradata
F getid
F getitemgroup
F getmetadata
F getoption
F getsorting
F getsynonym
F gettablecell
F gettabulatecell
F gettagreferencedescription
F handler
T ignored
F initializeexport
D labels
F last
F lastinchain
F localexport
F locatedtag
T modes
  S BlockQuote
  S FENote
  S H1
  S H2
  S H3
```

S H4
S H5
S H6
S H7
S H8
S H9
S Lbl
S NonStruct
S P
S Part
S Sect
D overloads
T patterns
U splitter
F pop
D properties
F push
F registerextradata
F registermetadata
F restart
F setaspect
F setattributehash
F setcodepoint
F setcombination
F setcombinationpair
F setconstruct
F setdescriptionindex
F setfigure
F setfloat
F setformulacontent
F sethighlight
F setitem
F setitemgroup
F setmpgraphic
F setnotation
F setnotationsymbol
F setparagraph
F setproperty
F setpublication
F setregister
F setsorting
F setsynonym
F settablecell
F settabulatecell
F settagdelimitedsymbol
F settagsubsentencesymbol
F setupexport
F setuserproperties
D specifications
F start
F stop
F strip
D taglist
T unsupported
B Annot
B Art
B BibEntry
B Caption
B Document
B DocumentFragment
B Em
B Form
B H
B Index
B Link
B Note
B Quote
B Reference
B Strong
B TOC
B TOCI
B Title
T usewithcare
T where
S Art
S Artifact
S Aside
S BibEntry
S BlockQuote
S Code
S DocumentFragment
S Em
S FENote
S H1
S H2
S H3
S H4
S H5

```
      S H6
      S H7
      S H8
      S H9
      S Index
      S Note
      S Private
      S Quote
      S Reference
      S Strong
      S Sub
      S TOC
      S TOCI
      S Title
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
D texconditionals
T texconfig
  T buffersize
    N size
    N step
  T errorlinesize
    N size
  T expandsize
    N size
  T filesize
    N size
    N step
  S firstline
  T fontsize
    N size
    N step
  S formatname
  N functionsize
  T halferrorlinesize
    N size
  T hashsize
    N size
    N step
  F init
  T inputsize
    N size
    N step
  T insertsize
    N size
    N step
  B kpse_init
  T languagesize
    N size
    N step
  T marksize
    N size
    N step
  T nestsize
    N size
    N step
  T nodesize
    N size
    N step
  T parametersize
    N size
    N step
  T poolsize
    N size
    N step
  N propertiessize
  T savesize
    N size
    N step
  S shell_escape
  T stringsize
    N size
    N step
  T tokensize
    N size
    N step
D texconstants
D texifs
D texisdefined
D texmodes
D texsystemmodes
T thirddata
F toboolean
F todecimal
T tokens
  T accessors
```

```
  F active
  F cmd
  F cmdchrcs
  F cmdname
  F command
  F csname
  F expandable
  F frozen
  F index
  F name
  F protected
  F range
F astable
T bits
  N active
  N alignment
  N begingroup
  N character
  N close
  N comment
  N endgroup
  N endofline
  N escape
  N ignore
  N invalid
  N letter
  N mathshift
  N open
  N other
  N parameter
  N space
  N subscript
  N superscript
  N whitespace
D cache
D commands
F compile
F constant
T converters
  S toboolean
  S todimen
  S toglue
  S tonumber
  S tostring
F create
F defined
F flags
F getinteger
T getters
  F box
  F count
  F cstoken
  F dimen
  F glue
  F macro
  F meaning
  F skip
  F token
F gobble
F isactivestring
F isdefined
F istoken
F new
F pickup
F popmacro
T presets
  T 1 argument
  T 1 integer
  T 1 optional
  T 1 string
  T 2 arguments
  T 2 integers
  T 2 optionals
  T 2 strings
  T 3 arguments
  T 3 integers
  T 3 optionals
  T 3 strings
  T 4 arguments
  T 4 integers
  T 4 optionals
  T 4 strings
  T 5 strings
  T 6 strings
  T 7 strings
  T 8 strings
F pushmacro
T scanners
```

F argument
F argumentasis
F array
F boolean
F box
F bracketed
F bracketedasis
F cardinal
F char
F cmdchr
F cmdchrexpanded
F code
F conditional
F count
F csname
F csnameunchecked
F delimited
F detokened
F dimen
F dimension
F dimensionargument
F float
F glue
F gluespec
F gluevalues
F hash
F hbox
F integer
F integerargument
F ischar
F key
F keyword
F keywordcs
F letters
F list
F lua
F luacardinal
F luainteger
F luanumber
F lxmlid
F next
F nextchar
F nextexpanded
F number
F optional
F peek
F peekchar
F peekexpanded
F posit
F real
F scanclose
F scanopen
F skip
F skipexpanded
F string
F table
F token
F tokencode
F tokenlist
F tokens
F tokenstring
F toks
F value
F vbox
F verbatim
F vtop
F whd
F word
F setinteger
T setters
F box
F char
F count
F dimen
F glue
F lua
F macro
F skip
T shortcuts
N close
F inspect
N open
F report
F scanargument
F scanargumentasis
F scanarray
F scanboolean
F scanbox

```
  F scanbracketed
  F scanbracketedasis
  F scancardinal
  F scanclose
  F scancode
  F scanconditional
  F scancsname
  F scancsnameunchecked
  F scandelimited
  F scandetokened
  F scandimen
  F scandimension
  F scandimensionargument
  F scanfloat
  F scanglue
  F scangluespec
  F scangluevalues
  F scanhash
  F scanhbox
  F scaninteger
  F scanintegerargument
  F scankeyword
  F scankeywordcs
  F scanletters
  F scanlist
  F scanlua
  F scannumber
  F scanopen
  F scanoptional
  F scanposit
  F scanstring
  F scantable
  F scantokenlist
  F scantokenstring
  F scantoks
  F scanvbox
  F scanverbatim
  F scanvtop
  F scanword
  F toboolean
  F todimen
  F tonumber
  F tostring
D values
  F tonumber
  F tostring
  F tostring_u1
  F tostring_u2
  T tracers
    F printerror
    F printwarning
    F processerror
    F showlines
  T trackers
    D data
    F default
    F disable
    T done
    F dumphashtofile
    F enable
    F list
    S name
    F register
    F report
    F reset
    F savehash
    F set
    F show
    F value
    F values
  F type
  T typesetters
    T alignments
      F handler
      F set
    T breakpoints
      F define
      F handler
      D mapping
      T methods
      T numbers
      F set
      F setreplacement
    T cases
      T actions
      F handler
      F register
      F set
```

```
T characteralign
  F handler
  F resetcharacteralign
  F setcharacteralign
T characters
  F handler
  T methods
  F replacenbsp
  F replacenbspaces
T checkers
  F handler
  F reset
  F set
T cleaners
  F handler
  F set
T compare
  F handler
  F reset
  F set
  F setpair
  F setup
T corrections
  F handler
T digits
  T actions
  F handler
  F set
T directions
  F getfences
  F getglobal
  F getmethod
  F handler
  T handlers
  F installhandler
  F set
  F setcolor
  F tomode
T firstlines
  T actions
    F default
    F line
    F word
  F handler
  F set
T fontkerns
  F handler
T initials
  T actions
    F default
  F handler
  F set
T injectors
  F check
  T list
  F mark
  F reset
  F set
  F show
T italics
  F enablemath
  F enabletext
  F handler
T kerns
  D factors
  F handler
  F keepligature
  D mapping
  F set
T localboxes
  F handler
T manipulators
  F apply
  F applyspecification
  T methods
    F Word
    F Words
    F abbreviatedjournal
    F expandedjournal
    F lowercase
    F stripperiod
    F uppercase
  T patterns
    U list
    U pair
  F splitspecification
T margins
  F finalhandler
```

```
  F globalhandler
  F localhandler
  F save
F marksuspects
T paragraphs
  F addanchortoline
  F addtoline
  F calculatedelta
  F checkline
  F moveinline
T periodkerns
  D factors
  F handler
  D mapping
  F set
T processors
  F apply
  F register
  F reset
  F split
  F startapply
  F stopapply
  F stripped
  F tostring
T rubies
  F attach
  F check
F showinvisibles
F showsuspects
T spacings
  F define
  F handler
  D mapping
  T numbers
    T frenchpunctuation
      T characters
      S name
      N number
  F reset
  F set
  F setup
T stacking
  F getindex
  F getselection
    F handler
  T swapping
    F handler
  T synchronize
    F handler
  T tighten
    F handler
  T wrappers
  T xtables
    F cleanup
    F construct
    F create
    F finish_row
    F flush
    F initialize_construct
    F initialize_reflow_height
    F initialize_reflow_width
    F next_row
    F reflow_height
    F reflow_width
    F set_construct
    F set_reflow_height
    F set_reflow_width
F unpack
T updaters
  F apply
  F register
T url
  F addscheme
  F barepath
  F construct
  F decode
  F encode
  F escape
  F filename
  F hashed
  F hasscheme
  F query
  F split
  F toquery
  F unescape
  F unescapeget
T userdata
T utf
```

```
  F byte
  F bytepairs
  F char
  F characters
  F chrlen
  F count
  F filetype
  F is_valid
  F len
  F length
  F lower
  F remapper
  F replacer
  F split
  F splitlines
  F sub
  F substituter
  F tocodes
  F toeight
  F toentities
  F tostring
  F totable
  F upper
  F ustring
  F utf16_to_utf8_be
  F utf16_to_utf8_be_t
  F utf16_to_utf8_le
  F utf16_to_utf8_le_t
  F utf16_to_utf8_t
  F utf32_to_utf8_be
  F utf32_to_utf8_be_t
  F utf32_to_utf8_le
  F utf32_to_utf8_le_t
  F utf32_to_utf8_t
  F utf8_to_utf16
  F utf8_to_utf16_be
  F utf8_to_utf16_le
  F utf8_to_utf8_t
  F values
  F xstring
T utilities
  T debugger
    F disable
    F enable
    F savestats
    F showstats
    F showtraceback
  T formatters
    F formatcolumns
    F list
    F stripzeros
  T ghostscript
    F convert
    F statistics
  T graphicmagick
    F convert
    F statistics
  T lua
    B alwaysstripcode
    F checkmemory
    F compile
    F loadedluacode
    F loadstring
    F loadstripped
    N nofstrippedbytes
    N nofstrippedchunks
    B stripcode
    T strippedchunks
    F strippedloadstring
    T suffixes
      S lmt
      S lua
      S luc
      S lui
      S luj
      S luv
      S tma
      S tmc
      S tua
      S tuc
  T packers
    F hashed
    F new
    F pack
    F simplehashed
    F strip
    F unpack
    N version
```

T parsers
F add_settings_to_array
F arguments_to_table
F array_to_string
F csvsplitter
F getparameters
F groupedsplitat
F hash_to_string
T hashes
T settings_to_list
T settings_to_set
T min,max,fit,broad,auto
B auto
B broad
B fit
B max
B min
T text,hidden,paper,page,leftpage,rightpage
B hidden
B leftpage
B page
B paper
B rightpage
B text
F iterator
F keq_to_hash
F listitem
F make_settings_to_hash_pattern
F mergehashes
F options_to_array
F options_to_hash
T patterns
U settings_to_array
U settings_to_hash_a
U settings_to_hash_b
U settings_to_hash_c
U settings_to_hash_d
U unittotex
F process_stripped_settings
F rfc4180splitter
F runtime
F settings_to_array
F settings_to_array_obey_fences
F settings_to_array_with_repeat
F settings_to_hash
F settings_to_hash_colon_too
F settings_to_hash_strict
F settings_to_hash_tolerant
F settings_to_numbers
F settings_to_set
F simple_hash_to_string
F splitmethod
F splitthousands
F stepper
F stripped_settings_to_array
F totime
F unittotex
F unittoxml
T randomizer
F get
F getnumber
F getrepeatable
F getrepeatableseed
F getseed
F newrepeatable
F popseed
F pushseed
F repeatable
F reuseseed
F setseed
F setseedi
T randomizers
F poisson
T sequencers
F appendaction
F appendgroup
F compile
F disableaction
F disablegroup
F enableaction
F enablegroup
D functions
F localize
F new
F nodeprocessor
F prependaction
F prependgroup
F removeaction

F replaceaction
F setkind
F tostring
T setters
F disable
F enable
F initialize
F list
F new
F register
F report
F reset
F show
T signals
S configuration
F initialize
F loadstate
F report
F savestate
F serialclose
F serialfast
F serialopen
S serialprefix
F serialsend
F serialwrite
N version
T stacker
F new
T storage
F allocate
F checked
F mark
F marked
F setinitializer
F sparse
T streams
F close
F getposition
F getsize
F getstring
F look
F open
F openstring
F read2dot14
F readbyte
F readbytes
F readbytetable
F readcardinal
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable
F readchar
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat
F readfloatle
F readfloatle12
F readfloatle6
F readinteger
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F readline
F readsignedbyte
F readstring
F setposition
F size
F skip
F skipbytes
F skiplong
F skipshort
F tocardinal1
F tocardinal1le

```
  F tocardinal2
  F tocardinal2le
  F tocardinal3
  F tocardinal3le
  F tocardinal4
  F tocardinal4le
T strings
  F collapse
  T formatters
    F add
    F new
  T luaformatters
    S _connector_
    T _environment_
      F FD
      F FD3
      F FD6
      F FD9
      F FORMAT
      F autodouble
      F autosingle
      F basepoints
      F concat
      F escapedquotes
      F format
      F formattedfloat
      F formattedinteger
      F formattednumber
      F lpegmatch
      U luaescape
      F nubasepoints
      F nupoints
      F points
      F sequenced
      F signed
      F sparseexponent
      U stripzero
      U stripzeros
      U texescape
      F tonumber
      F tostring
      F tracedchar
      F type
      F utfbyte
      F utfchar
      F utfpadding
      U xmlescape
    T _extensions_
      S lua
      S tex
      S xml
    S _preamble_
    S _type_
  F newcollector
  F newrepeater
  T striplinepatterns
    U collapse
    U collapse all
    U prune
    U prune and collapse
    U prune and no empty
    U prune and to space
    U retain
    U retain and collapse
    U retain and no empty
  F striplines
  F tabtospace
T tables
  F accesstable
  F definedtable
  F definetable
  F encapsulate
  F insertaftervalue
  F insertbeforevalue
  F migratetable
  F removevalue
  F replacevalue
T tar
  T archives
  F closearchive
  T files
    F fetch
    F hash
    F list
    F pack
    F unpack
  F openarchive
  T registeredfiles
```

```
    T streams
      F fetch
      F hash
      F list
      F pack
      F unpack
    T strings
      F fetch
      F hash
      F list
      F pack
      F unpack
  T templates
    F load
    F replace
    F replacer
    F resolve
  T zipfiles
    F close
    F found
    F hash
    F list
    F open
    F unzip
    F unzipdir
    F zipdir
T visualizers
  D escapepatterns
  F getspecification
  F getvisualizer
  F load
  F makenested
  F makepattern
  F newgrammar
  F newhandler
  F parsedxml
  F pattern
  F register
  F registerescapecommand
  F registerescapeline
  F registerescapepattern
  S signal
  U signalpattern
  D specifications
    F visualize
    F visualizebuffer
    F visualizefile
    F visualizestring
    F write
    F writeargument
    F writedefault
    F writeemptyline
    F writenewline
    F writespace
  F warn
  T xml
    F addentitiesdoctype
    F addspecialcode
    F after
    F all
    F applylpath
    F applyselector
    F assign
    F attribute
    F badinclusions
    F before
    F body
    T builtinentities
      B amp
      B apos
      B gt
      B lt
      B quot
    F cdata
    F cdatatotext
    F checkbom
    F checkedempty
    F checkerror
    F checknamespace
    F checkns
    F cleansed
    F collect
    F collect_elements
    F collect_tags
    F collect_texts
    F collected
    F collecttexts
    F compactelement
```

```
F content
F convert
F copy
F count
F cprint
T css
  F applyselector
  F colorspecification
  F dimension
  F family
  F fontspecification
  F mappedstylevalue
  F padding
  F size
  F style
  F stylevalue
  F todimension
  F variant
  F weight
T defaulthandlers
  D file
  D parsedxml
  D string
  D tex
  D texline
  D texspace
  D verbose
S defaultprotocol
F delete
F delete_element
F despecialized
F each
F each_element
F elements
F elementtocdata
F empty
D entities
F erase
F errorhandler
F escaped
F expand
T expressions
  F attribute
  F boolean
  F child
  F contains
  F count
  F error
  F find
  F hasclass
  F idstring
  F lower
  F name
  F number
  F oneof
  F print
  F quit
  F tag
  F text
  F undefined
  F upper
F fillin
F filter
T finalizers
  F paragraphs
  T tex
    F all
    F attribute
    F chainattribute
    F chainpath
    F collapsed
    F command
    F concat
    F concatrange
    F context
    F count
    F ctxtext
    F default
    F depth
    F first
    F function
    F index
    F last
    F lettered
    F lower
    F lowerall
    F match
    F name
```

```
    F param
    F parameter
    F position
    F reverse
    F stripped
    F tag
    F tags
    F text
    F upper
    F upperall
    F url
    F xml
  T xml
    F all
    F att
    F attribute
    F attributes
    F cdata
    F chainattribute
    F count
    F default
    F elements
    F empty
    F first
    F function
    F index
    F last
    F lowerall
    F match
    F name
    F position
    F reverse
    F table
    F tag
    F tags
    F text
    F texts
    F tomacro
    F upperall
    F url
F first
F found
T functions
  F classes
    F hasclass
F getbuffer
F gethandlers
F gethandlersfunction
T helpers
  F recursetext
F include
F inclusion
F inclusions
F index
F inheritattributes
F inheritedconvert
F inject
F inject_element
F inject_element_after
F inject_element_before
F injectafter
F injectbefore
F insert
F insert_element
F insert_element_after
F insert_element_before
F insertafter
F insertbefore
F insertcdata
F insertcomment
F inspect
F is_valid
F kind
F last
F lastmatch
F load
F lpath
F lpathcached
F lpathcalls
F lshow
F makestandalone
F match
T mml
  F stripped
  F verbose
F name
F newhandlers
F nodesettostring
```

T obsolete
  F collect_elements
  F collect_texts
  F delete_element
  F each_element
  F inject_element
  F inject_element_after
  F inject_element_before
  F insert_element_after
  F insert_element_before
  F process_attributes
  F process_elements
  F remap_name
  F remap_namespace
  F remap_tag
  F replace_element
  F strip_whitespace
F originalload
F package
F parent
U parsedentitylpeg
T pihandlers
  F injector
  F tex
T placeholders
  F unknown_any_entity
  F unknown_dec_entity
  F unknown_hex_entity
F popmatch
F position
D privatecodes
F privatetoken
F process
F process_attributes
F process_elements
F processattributes
T profiled
F pure
F pushmatch
F raw
F registerentity
F registerns
F reindex
F remap_name
F remap_namespace
F remap_tag
F remapname
F remapnamespace
F remaptag
F rename
F renamespace
U reparsedentitylpeg
F replace
F replace_element
F resetinjectors
F resolvens
F root
F save
F selection
F separate
F serialize
F serializetotext
F setcdata
F setcomment
F sethandlersfunction
F setinjectors
F setproperty
F settings
D specialcodes
T specialhandler
F sprint
F string
F strip
F strip_whitespace
F stripelement
F stripleadingspaces
F table
F text
F textonly
F texttocdata
F tocdata
F toelement
F tostring
F totable
F toxml
F tprint
F traverse
F unescaped

U unescapedentitylpeg
F unprivatized
F unspecialized
F wipe
F withelement
F withelements
F wrap
T xmlns
F xpcall
T zip
T archives
F closearchive
F openarchive
T registeredfiles
F inspect
F ipairs
F load
D loaders
F loadfile
F loadstring
F next
F optionalrequire
F pairs
F pcall
F pdfembeddedlink
F print
F rawequal
F rawget
F rawlen
F rawset
F require
F select
F setinspector
F setmathparameters
F setmetatable
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
D texconditionals
D texconstants
D texifs
D texisdefined
D texmodes
D texsystemmodes
F toboolean
F todecimal
F tonumber
F tostring
F tostring_u1
F tostring_u2
F type
F unpack
F warn
F xpcall

globals table

N CONTEXTLMTXMODE
B JITSUPPORTED
N LUAFORMAT
N LUAMAJORVERSION
N LUAMINORVERSION
S LUATEXENGINE
N LUATEXFORMATID
N LUATEXFUNCTIONALITY
S LUATEXVERBOSE
N LUATEXVERSION
N LUAVERSION
F SAVEDREQUIRE
F assert
F characterkern
F collectgarbage
F dimen
F dofile
F error
F getmetatable
F inspect
F ipairs
F load
D loaders
F loadfile
F loadstring
F next
F optionalrequire
F pairs
F pcall
F pdfembeddedlink
F print
F rawequal

F rawget
F rawlen
F rawset
F require
F select
F setinspector
F setmathparameters
F setmetatable
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
D texconditionals
D texconstants
D texifs
D texisdefined
D texmodes
D texsystemmodes
F toboolean
F todecimal
F tonumber
F tostring
F tostring_u1
F tostring_u2
F type
F unpack
F warn
F xpcall

graphics table

F bpsize
F identify
F registerpdfcompactor
F registerpdffont

gzip table

F compress
F compressed
F decompress
F load
F save
F suffix

helper table

F getprofile
F mathnested
F mathprocess
F mathstep
F snapindeed
F snaplist
F traversecharmethod
F traverseglyphmethod
F traversehorizontal
F traversevertical

images table

F check
F checksize
F copy
F create
F embed
F embedfromstore
F fetchdata
F print
F resetdata
F resetstore
F scan
F serialize
F storedata
F totable
F wrap

inspect function

interactions table

D attachments
D linkedlists
D renderings

interfaces table

D cachedsetups
F cachesetup
F checkedspecification
D complete
D constants
D corenamespaces
S currentinterface
S currentresponse
F definecommand
F defined
F doifelsemessage
D elements
D formats
F getmessage
F getnamespace

F getsetupstring
D hashedsetups
F implement
F interfacedcommand
F knownscanner
F message
F nameofscanner
F registernamespace
F registerscanner
D scanners
F setconstant
F setcount
F setdimen
F setelement
F setformat
F setmacro
F setmessage
F setmessages
F settranslation
D setupstrings
F setvariable
F showmessage
D storedscanners
F tolist
D translations
D usednamespaces
D variables
F writestatus

io table

F ask
F bytes
F characters
F close
F copydata
F exists
S fileseparator
F flush
F gobble
F input
F lines
F loadchunk
F loaddata
F loadlines
F newreader
F noflines
F open
F output
S pathseparator
F popen
F read
F readall
F readnumber
F readstring
F savedata
F size
U stderr
U stdin
U stdout
F tmpfile
F type
F write

ipairs function

job table

F comment
F disablesave
F getrandomseed
F initialize
F load
F loadother
B pack
N packversion
F register
F save
N version

kdtree table

F delete
F found
F insert
F nearest
F nearestindex
F new
F newweighted
F reset
F totable
F traverse

kpse table

language table

F clean

F clearhyphenation
F clearpatterns
F current
F gethjcode
F haslanguage
F hyphenate
F hyphenation
F hyphenationmin
F id
F new
F patterns
F postexhyphenchar
F posthyphenchar
F preexhyphenchar
F prehyphenchar
F sethjcode
F setwordhandler

languages table

F addgoodiesdata
F addgoodiesfile
F associate
D associated
F association
D counters
F current
D data
D decimals
F define
F explicithyphen
F exportlanguage
F flatten
F getdata
F getmetadata
F getnumber
F goodiefiles
F hyphenate
F installed
F installhandler
F loadable
F loadwords
F nofflattened
D numbers
F pdflanguage
F postexhyphenchar
F posthyphenchar
F preexhyphenchar
F prehyphenchar
D registered
F serializediscretionary
F setexceptions
F setgoodieshandler
F setoptions
F setpatterns
F setsynonym
F setwordhandler
F showdiscretionaries
F strippedgoodiewords
F tolang
F unload
N version
F visualizediscretionaries

layouts table

F getcanvas
F getpagedimensions
F setupcanvas

lfs table

F attributes
F canonicalize
F chdir
F currentdir
F dir
F expandpath
F isdir
F isfile
F isfound
F isreadabledir
F isreadablefile
F iswriteabledir
F iswriteablefile
F lessweird
F link
F mkdir
F mkdirs
F modification
F moreweird
F readlink
F rmdir
F setexecutable

F setloadshebang
F symlink
F symlinktarget
F touch
F walkdir

libraries table
D basiclua
D basictex
D builtin
D extralua
D extratex
D functions
D globals
D obsolete
D optional

lmx table
F color
F convert
F convertfile
F convertstring
F einject
F eprint
F escape
F finalized
F finject
F fprint
F get
F getvariables
F htmfile
F include
F initialize
F inject
F lmxfile
F loadedfile
F make
F new
F popupfile
F print
F pv
F report
F reset
F result
F set
F show
F stripcss
F tv
F type
F urlescape
F variable

load function

loaders data table

loadfile function

loadstring function

logs table
F application
F categories
F direct
F disable
F enable
F finalactions
F flush
F format
F formatted
F loggingerrors
F messenger
F new
F newline
F poplogfile
F poptarget
F pushlogfile
F pushtarget
F registerfinalactions
F report
F reporter
F resetlogfile
F setformatters
F setlogfile
F setmessenger
F setprocessor
F settarget
F settimedlog
F settranslations
F show
F start_page_number
F start_run
F starterrorlogging
F startfilelogging
F status

F stop_page_number
F stoperrorlogging
F stopfilelogging
F subdirect
F subreport
F system
F texerrormessage
F writer

lpdf table

F action
F adddocumentcolorspace
F adddocumentextgstate
F adddocumentpattern
F adddocumentshade
F addtocatalog
F addtoinfo
F addtonames
F addtopageattributes
F addtopageresources
F addtopagesattributes
F addxmpinfo
F annotationspecification
F array
F attachmentsymbols
F boolean
F border
F checkedkey
F checkedresources
F checkedvalue
F circularshade
F close
F cmykcode
F collectedresources
F color
F colorspace
D colorspaceconstants
F colorspec
F colorvalue
F colorvalues
F commentsymbols
F compressdata
F compresslevel
F constant
F copyarray
F copyboolean
F copyconstant
F copydictionary
F copyfloat
F copyinteger
F copynumber
F copystring
F copyunicode
F deferredobject
F delayedobject
F destinationspecification
F dictionary
F docstring
F escaped
F finalizedocument
F finalizepage
F finalizesignature
F finishtransparencycode
F flushfonts
F flushgroup
F flushobject
F flushstreamfileobject
F flushstreamobject
D formats
F frombytes
F fromeight
F frompdfdoc
F fromsixteen
F getcatalog
F getcompression
F getfontname
F getfontobjectnumber
F getformatoption
F getinfo
F getmatrix
F getnofpages
F getpageproperties
F getpagereference
F getpagetags
F getpos
F gettaggingstatus
F gettrailerid
F getversion
F getxformname

F graycode
F hasmatrix
F immediateobject
F includeimage
F initialize
F injectxmpinfo
F insertxmpinfo
F lastreferredpage
F layerreference
F limited
F linearshade
F literal
F majorversion
F makenametree
F minorversion
F noffontregistries
F nofpages
F null
F number
F object
F objectcompresslevel
F pagereference
F patternstream
F pdfcolor
F pdftimestamp
F preparesignature
F print
F procset
B protectresources
F quads
F rectangle
F reference
F registerannotation
F registerdestination
F registerdocumentfinalizer
F registerfontmethod
F registerinitializer
F registerpagefinalizer
F registerpattern
F registersignature
F replacexmpinfo
F reserveobject
F rgbcode
F rotationcm
F setcompression
F setencryption
F setpageorder
F setpagestate
F setpagetag
F setutfstringmode
F setversion
F sharedobject
F shareobject
F shareobjectreference
F splitsixteen
F spotcode
F stream
F string
F supportedformats
F tocidset
F toeight
F topdfdoc
F topermissions
F tosixteen
F transparency
F transparencycode
F transparencyvalue
F unicode
D usedfontstreams
F verbose

lpeg table

F B
F C
F Carg
F Cb
F Cc
F Cf
F Cg
F Cmt
F Cp
F Cs
F Ct
F P
F R
F S
F UP
F UR
F US

F V
F afterprefix
F anywhere
F append
F balancer
F beforesuffix
F checkedsplit
F containsws
F counter
F endstripper
F finder
F firstofsplit
F frontstripper
F instringchecker
F is_lpeg
F keeper
F locale
F match
F oneof
D patterns
F pcode
F print
F ptree
F replacer
F secondofsplit
F setmaxstack
F setutfcasers
F split
F splitat
F splitter
F stripper
F times
F tsplitat
F tsplitter
F type
F utfR
F utfchartabletopattern
F utfreplacer
S version

lua table

F addnibble
D bytedata
F callbytecode
F comparekeys
F finalizeinitex
N firstbytecode
F get_functions_table
F getallkeys
F getbytecode
F getcheckedkeys
F getcurrenttime
F getdebuginfo
F getexitcode
F getfunctionstable
F getnibble
F getnumerickeys
F getpreciseseconds
F getpreciseticks
F getruntime
F getstacktop
F getstartupfile
F getstringkeys
F getversion
N lastbytecode
F luastringcall
D messages
F mpsstringcall
F newindex
F newtable
D numbers
F protectglobal
F registercode
F registeredcodes
F registerglobal
F registerinitexfinalizer
F registername
F setbytecode
F setexitcode
F setnibble
S startupfile
F subnibble
F usestringcall
S version

luac table

F inspect
F print

luatex table

F abort

F cleanup
F cleanuptempfiles
F currentfile
F currentlevel
F currenttotal
F poprunstate
F pushrunstate
F registerdumpactions
F registerpageactions
F registerstartactions
F registerstopactions
F registertempfile
N starttime
F wrapup

lxml table

F addindex
F all
F applyfunction
F applyselectors
F att
F attribute
F badinclusions
F chainattribute
F checkindex
F collected
F command
F concat
F concatrange
F content
F context
F convert
F count
F delete
F depth
F direct
F displayverbatim
F doif
F doifelse
F doifelseempty
F doifelsetext
F doifempty
F doifnot
F doifnotempty
F doifnottext
F doiftext
F element
F elements
D entities
F fileline
F filename
F filter
F filterlist
F first
F flush
F flushlinewise
F flushsetups
F flushspacewise
F get_id
F getid
F getindex
F id
U idsplitter
F ifatt
F ifattempty
F include
F inclusion
F inclusions
F index
F inlineverbatim
F installsetup
F last
F lastatt
F lastmatch
F lastpar
F load
F loadbuffer
F loaddata
F main
F match
F name
F namespace
F nonspace
F par
F param
F parameter
F path
F popmatch
F pos

F position
F pure
F pushmatch
F raw
F rawroot
F rawtex
F refatt
F register
F registerentity
F removesetup
F replace
F resetcdata
F resetsetups
F resolvedentity
F root
F save
F serialize
F setaction
F setatt
F setattribute
F setcdata
F setcommandtonone
F setcommandtotext
F setpar
F setparam
F setparameter
F setsetup
F snippet
F splitid
F startraw
F startunescaped
F stopraw
F stopunescaped
F store
F strip
F stripped
F tag
F texatt
F text
F tobuffer
F tofile
F toparameters
F toverbatim
F verbatim
F withindex
D xmltexhandler

math table

F abs
F acos
F asin
F atan
F atan2
F ceil
F ceiling
F cos
F cosd
F cosh
F deg
F div
F even
F exp
F floor
F fmod
F frexp
N huge
N initialseed
F ldexp
F log
F log10
F max
N maxinteger
F min
N mininteger
F mod
F modf
F odd
N pi
F pow
F rad
F random
F randomseed
F round
F setrandomseedi
F sin
F sind
F sinh
F sqrt
F tan

F tand
F tanh
F tointeger
F type
F ult

mathematics table

F addfallbacks
F addvariant
D alphabets
D alternatives
F beforepassingfonttotex
F big
D boldmap
D charactersets
F checkaftercopyingfont
D classes
D classnames
D codes
F define
F dimensions
F disablecollecting
F enablecollecting
F extensiblecode
D extensibles
N extrabase
F fallbackstyleattr
F familyname
F functiontype
D gaps
F getblobindex
F getboth
F getdomainname
F getextensibledata
F getmathblob
F getoptionallabel
F getstyle
F gettextblob
F getverboselabel
F horizontalcode
F initializeparameters
F makefont
D mapremap
F markblobindexdone
F overloadparameters
F preset
N privatebase
F registerextensible
F registersimplematrix
F registerverboselabel
F remapalphabets
F renderextensible
F renderset
F resetattributes
F scaleparameters
F setextensibledata
F setmathsymbol
D sets
F setsnapping
F setvariant
F strutcode
D styles
F syncboth
F syncname
F syncstyle
F toengineclass
F toname
F tostyle
F tweakaftercopyingfont
F tweakbeforecopyingfont
F utfmathaccent
F utfmathclass
F utfmathcommand
F utfmathfiller
F utfmathstretch
F variantcode
F variantcount
F virtualize
D virtualized

md5 table

F HEX
F dec
F hex
F sum
F sumHEXA
F sumhexa

metapost table

F checkformat
F checktracingonline

F cm
F colorinitializer
F convert
F currentmpx
F currentmpxstatus
S defaultformat
S defaultinstance
S defaultmethod
F directrun
F escaped
D extensiondata
F filter
F filterclippath
F flush
F flushnormalpath
F format_number
F format_string
F formatnumber
F getbackendoption
F getbendtolerance
F getbuffer
F getclippath
F getextensions
F getextradata
F gethashentries
F getinstancebyname
F getinstanceinfo
F getinstancenames
F getjobdata
F getmovetolerance
F getparameter
F getparameterpreset
F getparameterset
F getrecord
F getstatistics
F gettext
F gettolerance
F graphic
F graphic_base_pass
F hascurvature
F includesvgbuffer
F includesvgfile
F installplugin
F isobject
S lastlog
F load
F maketext
F mesh
F mesher
F meshupper
N n
F newlogger
N nofruns
F nofscriptruns
F nvformat
F pdfliterals
F pluginactions
F points
F pointset
F popformat
F popscriptrunner
F popvariable
F popvariables
F preparetextextsdata
F process
F processing
F processplugins
F pushformat
F pushscriptrunner
F pushvariable
F pushvariables
B quitonerror
B reducetogray
F registerdirect
F registerfilter
F registermesher
F registermeshupper
F registerpointset
F registerscript
F registertokens
F remappedtext
F remaptext
F reporterror
F reportsvgfonts
F reset
F resetbackendoptions
F resetlastlog
F resetplugins

F run
F runinternal
F runscript
F scanparameters
F scriptindex
F setbendtolerance
F setbuffer
F setextensions
F setlogging
F setmovetolerance
F setoutercolor
F setparameter
F setparameterset
F setrecord
F settext
F settolerance
F setvariable
B showlog
F showsvgpage
F simple
F splitprescript
F startgraphic
F startsvghashing
F stopgraphic
F stopsvghashing
F svformat
B svgcachefile
F svgcolorremapper
F svgglyphtomp
F svgshapestomp
F svgshapestopdf
F svgsplitcolor
F svgtomp
F svgtopdf
F sxsy
B texerrors
F texexp
F theclippath
F tographic
F totable
F typesvgpage
F unload
F untagvariable

moduledata table

modules table

D anch-loc
D anch-pgr
D anch-snc
D back-exp
D back-exp-imp-fnt
D back-exp-imp-mth
D back-exp-imp-ref
D back-exp-imp-tag
D back-imp-lua
D back-imp-mps
D back-imp-pdf
D back-imp-pdp
D blob-ini
D buff-imp-default
D buff-imp-escaped
D buff-imp-lua
D buff-imp-mp
D buff-imp-nested
D buff-imp-parsed-xml
D buff-imp-tex
D buff-imp-xml
D buff-ini
D buff-par
D buff-ver
D char-enc
D chem-ini
D chem-str
D cldf-com
D cldf-ver
D colo-icc
D colo-ini
D cont-run
D core-con
D core-ctx
D core-dat
D core-sys
D driv-shp
D file-mod
D file-syn
D font-afk
D font-agl
D font-aux
D font-cff

D font-chk
D font-cid
D font-col
D font-con
D font-ctx
D font-def
D font-dsp
D font-enc
D font-enh
D font-fbk
D font-fmp
D font-hsh
D font-imp-checks
D font-imp-combining
D font-imp-compound
D font-imp-digits
D font-imp-dimensions
D font-imp-effects
D font-imp-italics
D font-imp-ligatures
D font-imp-math
D font-imp-notused
D font-imp-properties
D font-imp-quality
D font-imp-reorder
D font-imp-scripts
D font-imp-spacekerns
D font-imp-tex
D font-imp-text
D font-imp-tracing
D font-imp-tweaks
D font-imp-unicode
D font-ini
D font-lig
D font-log
D font-lua
D font-map
D font-mpf
D font-mps
D font-nod
D font-ogr
D font-one
D font-onr
D font-osd
D font-ota
D font-otc
D font-otd
D font-oth
D font-oti
D font-otj
D font-otl
D font-oto
D font-otr
D font-ots
D font-ott
D font-oup
D font-pat
D font-prv
D font-san
D font-sel
D font-shp
D font-sol
D font-syn
D font-tfm
D font-tpk
D font-trt
D font-ttf
D font-txt
D font-vfc
D font-vir
D good-ctx
D good-gen
D good-ini
D good-mth
D grph-bmp
D grph-con
D grph-epd
D grph-fil
D grph-img
D grph-inc
D grph-pat
D grph-raw
D grph-rul
D grph-trf
D grph-u3d
D java-ini
D lang-cnt
D lang-def

D lang-dis
D lang-exc
D lang-hup
D lang-hyp
D lang-ini
D lang-lab
D lang-rep
D lang-tra
D lang-txt
D lang-url
D lang-wrd
D libs-imp-curl
D libs-imp-ghostscript
D libs-imp-graphicsmagick
D libs-ini
D lpdf-ano
D lpdf-col
D lpdf-epa
D lpdf-epd
D lpdf-fix
D lpdf-fix-imp-contents
D lpdf-fix-imp-fonts
D lpdf-fld
D lpdf-fmt
D lpdf-grp
D lpdf-img
D lpdf-ini
D lpdf-lmt
D lpdf-mis
D lpdf-ren
D lpdf-rul
D lpdf-sig
D lpdf-tag
D lpdf-u3d
D lpdf-wid
D lpdf-xmp
D lxml-css
D lxml-dir
D lxml-ent
D lxml-ini
D lxml-mms
D lxml-sor
D lxml-tex
D math-act
D math-ali
D math-dim
D math-ext
D math-fbk
D math-fnt
D math-frc
D math-inc
D math-ini
D math-map
D math-mps
D math-noa
D math-pre
D math-rad
D math-ren
D math-spa
D math-tag
D math-txt
D math-vfu
D meta-blb
D meta-fnt
D meta-fun
D meta-imp-txt
D meta-ini
D meta-lua
D meta-nod
D meta-pdf
D meta-tex
D mlib-ctx
D mlib-fio
D mlib-int
D mlib-lmp
D mlib-lmt
D mlib-lua
D mlib-mat
D mlib-mpf
D mlib-msh
D mlib-pdf
D mlib-pos
D mlib-pps
D mlib-ptr
D mlib-pts
D mlib-ran
D mlib-run
D mlib-scn

D mlib-snc
D mlib-svg
D node-ali
D node-bck
D node-fnt
D node-par
D node-ref
D node-rul
D node-tra
D node-typ
D pack-obj
D pack-ori
D pack-rul
D page-blk
D page-cst
D page-flt
D page-ini
D page-inj
D page-ins
D page-lin
D page-mix
D page-otr
D page-pst
D page-sel
D page-str
D phys-dim
D publ-aut
D publ-dat
D publ-fnd
D publ-inc
D publ-ini
D publ-jrn
D publ-oth
D publ-reg
D publ-sor
D publ-tra
D publ-usr
D regi-ini
D scrn-but
D scrn-fld
D scrn-hlp
D scrn-ini
D scrn-pag
D scrn-ref
D scrn-wid
D scrp-cjk
D scrp-eth
D scrp-ini
D scrp-tha
D scrp-tib
D sort-ini
D sort-lan
D spac-ali
D spac-brk
D spac-chr
D spac-hor
D spac-ovl
D spac-par
D spac-pas
D spac-prf
D spac-twi
D spac-ver
D strc-bkm
D strc-blk
D strc-con
D strc-doc
D strc-flt
D strc-ini
D strc-itm
D strc-lev
D strc-lst
D strc-mar
D strc-mat
D strc-not
D strc-num
D strc-pag
D strc-ref
D strc-reg
D strc-rsc
D strc-syn
D strc-tag
D strc-usr
D symb-emj
D symb-ini
D syst-cmp
D tabl-ali
D tabl-ntb
D tabl-tbl

D tabl-xtb
D task-ini
D trac-bld
D trac-jus
D trac-par
D trac-riv
D trac-sig
D trac-vis
D type-ini
D typo-adj
D typo-bld
D typo-brk
D typo-cap
D typo-chr
D typo-cln
D typo-dha
D typo-dif
D typo-dig
D typo-dir
D typo-drp
D typo-duc
D typo-fkr
D typo-fln
D typo-hid
D typo-inj
D typo-itc
D typo-krn
D typo-lan
D typo-lbx
D typo-man
D typo-mar
D typo-ovl
D typo-pag
D typo-par
D typo-pnc
D typo-prc
D typo-rep
D typo-rub
D typo-spa
D typo-stc
D typo-sus
D typo-syn
D typo-tal
D typo-wrp
D unic-ini

mp function

F autoinject
F boolean
F bytemap_load_from_file
F cleaned
F color
F dataset
F direct
F downgradebytemap
F downsamplebytemap
F draw
F expandtex
F fill
F fillbytemap
F flatten
F flush
F format
F formatted
F fprint
F getbytemap
F getbytemapdata
F getbytemapdirect
F getlastaddtype
F graphformat
F integer
F lmt_function_x
F lmt_glyphshape_accent
F lmt_glyphshape_baseline
F lmt_glyphshape_boundingbox
F lmt_glyphshape_depth
F lmt_glyphshape_height
F lmt_glyphshape_italic
F lmt_glyphshape_llx
F lmt_glyphshape_n
F lmt_glyphshape_path
F lmt_glyphshape_start
F lmt_glyphshape_stop
F lmt_glyphshape_usedbox
F lmt_glyphshape_usedline
F lmt_glyphshape_width
F lmt_mesh_set
F lmt_mesh_update
F lmt_poisson_generate

F lmt_start_potrace
F lmt_step_potrace
F lmt_stop_potrace
F lmt_svg_include
F loadbytemap
F loadbytemapfile
F mesh_register
F mf_blob_add
F mf_blob_dimensions
F mf_blob_index
F mf_blob_new
F mf_blob_raw_content
F mf_blob_raw_dimensions
F mf_blob_raw_reset
F mf_blob_raw_toutf
F mf_blob_raw_wipe
F mf_blob_size
F mf_blob_width
F mf_external_figure
F mf_finish_saving_data
F mf_formatted_text
F mf_get_outline_text
F mf_graphic_text
F mf_inject_blob
F mf_map_move
F mf_map_text
F mf_named_color
F mf_outline_text
F mf_save_data
F mf_script_index
F mf_start_saving_data
F mf_stop_saving_data
F mode
F n
F newbytemap
F number
F numeric
F pair
F pairpoints
F path
F pathpoints
F points
F points_register
F processbytemap
F processingmode
F quadruple
F quadruplepoints
F quoted
F report
F setbytemap
F setbytemapoctave
F size
F solve
F string
F systemmode
F transform
F triplet
F tripletpoints
F vprint

mplib table

F downgradebytemap
F downsamplebytemap
F execute
F expandtex
F fillbytemap
F finder
F finish
F getbytemap
F getbytemapdata
F getbytemapdirect
F getcallbackstate
F getcodes
F getcolormodels
F getfields
F gethashentries
F gethashentry
F getinternalactions
F getknotstates
F getlastaddtype
F getlogtargets
F getobjectdata
F getobjectpeninfo
F getobjectstacking
F getobjecttypes
F getprimitivelegacies
F getprimitiveorigins
F getprimitives
F getpruneoptions

F getresultstates
F getscaledbits
F getscantypes
F getstates
F getstatistics
F getstatus
F gettolerance
F gettype
F gettypes
F injectboolean
F injectcmykcolor
F injectcolor
F injectinteger
F injectnumber
F injectnumeric
F injectpair
F injectpath
F injectpoints
F injectstring
F injecttokens
F injecttransform
F injectvector
F injectvectors
F injectwhatever
F new
F newbytemap
F peninfo
F processbytemap
B realtimelogging
F scanboolean
F scancmykcolor
F scancolor
F scanexpression
F scaninteger
F scannext
F scannumber
F scannumeric
F scanpair
F scanpath
F scanpen
F scanproperty
F scanstring
F scansymbol
F scantoken
F scantransform
F setbytemap
F setbytemapoctave
F settolerance
F showcontext
F skiptoken
F solvepath
F version

nanojpeg table
F decode

next function

noads table
F getmathmode
F process
F processnested
F processouter

node table
F checkdiscretionaries
F checkdiscretionary
F copy
F copylist
F count
F currentattributes
F dimensions
F effectiveglue
F endofmath
F family_font
F fields
F findattribute
F flattendiscretionaries
F flushlist
F flushnode
F free
F getattribute
F getcachestate
F getfield
F getfielderror
F getglue
F getnodeerrorvalues
F getpropertiestable
F getproperty
F gluetostring
F hasattribute
F hasfield

F hasglyph
F hpack
F hyphenating
F id
F insertafter
F insertbefore
F instock
F intracking
F inuse
F isnode
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F makeextensible
F mlisttohlist
F new
F protectglyph
F protectglyphs
F protrusionskippable
F rangedimensions
F remove
F serialized
F setattribute
F setfield
F setfielderror
F setglue
F setproperty
F show
F size
F slide
F subtypes
F tail
F todirect
F tonode
F tostring
F traverse
F traverseid
F type
F types
F unprotectglyph
F unprotectglyphs
F unsetattribute
F usedlist
F usesfont
F vpack
F write

nodes table

D accentcodes
F aligned
F append
F apply
F applyvisuals
F astable
F basepoints
D boundarycodes
D choicecodes
F concat
F copy
F copy_node
F copylist
F countall
F currentattributes
F delete
D dircodes
D directioncodes
D directionvalues
D dirvalues
D disccodes
D discretionarycodes
D fencecodes
F fields
D fillcodes
D fillvalues
F firstdirinbox
F flush
F flushlist
F flushnode
D fractioncodes
F fullhpack
F getattr
F getattribute
F getboth
F getbox
F getchar
F getfield
F getfont

F getid
F getleader
F getlist
F getnext
F getprev
F getproperty
F getsubtype
D gluecodes
D glyphcodes
F hasattribute
F hasfield
F hpack
F idsandsubtypes
F idstostring
F insertafter
F insertbefore
F insertlistafter
F installattributehandler
F is_display_math
F isdirect
F isnode
F isnut
D kerncodes
F leftmarginwidth
F link
F linked
F list
D listcodes
F listtoutf
D literalvalues
F locate
D markcodes
D mathcodes
D mathvalues
F maxboxwidth
F new
D noadcodes
D nodecodes
F nopts
F packlist
D parcodes
D penaltycodes
F points
F prepend
F print
F pts
D radicalcodes
F rehpack
F remove
F repackhlist
F replace
F report
F rightmarginwidth
D rulecodes
F serialize
F serializebox
F serialized
F setattr
F setattribute
F setattrlist
F setboth
F setbox
F setboxtonaturalwd
F setchar
F setfield
F setfont
F setleader
F setlink
F setlist
F setnext
F setprev
F setproperty
F showboxes
F showlist
F showsimplelist
D skipcodes
F somepenalty
F somespace
F splitbox
F startofpar
F stripdiscretionaries
D subtypes
F tail
F takeattr
F takebox
F tobasepoints
F tocentimeters
F tociceros

F todidots
F todimen
F toinches
F tomillimeters
F tonode
F tonodes
F tonut
F topicas
F topoints
F toscaledpoints
F tosequence
F tostring
F totable
F totree
F toutf
F traverse
F traverseid
F unsetattribute
F upcomingproperties
F usedlist
F vianodes
F vianuts
F visualizebox
F vpack
D whatsitcodes
F write

number table
F %
F basepoints
F bytetodecimal
F clamp
F compactfloat
F decimaltobyte
D dimenfactors
F fractiontobyte
F idiv
N maxdimen
F nopts
F percent
F points
F pts
F splitdimen
F to16dot16
F tobasepoints
F tobitstring
F tocentimeters
F tociceros
F tocontext
F todidots
F todimen
F toediths
F toinches
F tomillimeters
F tonumberf
F tonumberg
F topicas
F topoints
F toscaled
F toscaledpoints
F totoves
F valid

objects table
F dimensions
F found
N n
F page
F reference
F register
F restore

optional table

optionalrequire function

os table
F __getenv__
F __setenv__
S binsuffix
N bits
F clock
F converttime
F date
F difftime
F enableansi
D env
F execute
F exit
F fulltime
F getcodepage
F getenv
F getnamevalues

F gettimeofday
F gettypevalues
F getunamefields
F isleapyear
F launch
S libsuffix
F localtime
S name
S newline
F nofdays
F now
F pipeto
S platform
F remove
F rename
F resultof
F runtime
S selfbin
S selfcore
S selfdir
S selflink
S selfname
S selfpath
F serialwrite
F setenv
F setexitcode
F setlocale
F sleep
F startuptime
F time
F timezone
F tmpname
F today
S type
F uname
F uuid
F validdate
F weekday
F where
F which

package table

S config
S cpath
F extralibpath
F extralibpaths
F extraluapath
F extraluapaths
F libpaths
F loadlib
F luapaths
S path
F poplibpath
F popluapath
F pushlibpath
F pushluapath
F searchpath

pagebuilders table

pairs function

parametersets table

pcall function

pdf table

F immediateobj

pdfdecode table

pdfe table

F arraytotable
F close
F closestream
F dictionarytotable
F getarray
F getboolean
F getbox
F getcatalog
F getdictionary
F getencodingvalues
F getfieldtypes
F getfromarray
F getfromdictionary
F getfromobject
F getfromreference
F getfromstream
F getinfo
F getinteger
F getmemoryusage
F getname
F getnofobjects
F getnofpages
F getnumber
F getobjectrange

F getpage
F getpages
F getpermissions
F getsize
F getstatus
F getstatusvalues
F getstream
F getstring
F gettrailer
F getversion
F new
F open
F openfile
F openstream
F pagestotable
F readfromstream
F readwholestream
F type
F unencrypt

pdfembeddedlink function

physics table

pngdecode table

F applyfilter
F expand
F frompalette
F interlace
F makemask
F palettemask
F reduce
F setexperiment
F splitmask
F tocmyk
F togray
F tomask
F transparentmask

posit table

F NaN
F NaR
F __add
F __band
F __bor
F __bxor
F __div
F __eq
F __le
F __lt
F __mul
S __name
F __pow
F __shl
F __shr
F __sub
F __tostring
F __unm
F abs
F acos
F asin
F atan
F band
F bor
F bxor
F ceil
F conj
F copy
F cos
F exp
F exp2
F expand
F floor
F frombyte
F fromchar
F fromposit
F integer
F log
F log10
F log1p
F log2
F logb
F max
F min
F modf
F new
F pow
F rotate
F round
F rounded
F shift
F sin

F sqrt
F tan
F tobyte
F tochar
F tonumber
F toposit
F tostring

potrace table
F checked
F concat
F contourplot
F convert
F count
F flush
F free
F fromfile
F getbitmap
F getnewfields
F getpolicyvalues
F getprocessfields
F new
F process
F setbitmap
F stripped
F totable
F trace

print function

process table
F __gc
S __name
F __tostring
F close
F open
F poll
F read
F tostring

publications table
F addtexentry
F analyze
F anywhere
D authorcache
D authorcollapsers
D authormap
F authortoregister
F checkeddataset
D collected
F concatstate
F converttoxml
F endnotes_to_btx
F finder
F firstofrange
F found
F get
F getcasted
F getdetail
F getdirect
F getfaster
F getfield
F getfuzzy
F getindex
D inspectors
F lastofrange
F load
F loadbibdata
F loaddefinitionfile
F loadreplacementfile
F new
F okay
F oneorrange
F parenttag
F permitted
F prerollcmdstring
F refman_to_btx
F resolvedname
F save
F search
F setcategory
F setspecification
F singularorplural
F sortedentries
F splitauthor
F splitoneauthor
F tags
F usedataset
F usedentries

qrcodegen table
F bitmap
F generate

rawequal function
rawget function
rawlen function
rawset function
regimes table
- D backmapping
- F cleanup
- F disable
- F enable
- F fromregime
- F list
- D mapping
- F pop
- F process
- F push
- F toregime
- F translate

require function
resolvers table
- F allprefixes
- F appendhash
- F automount
- F booleanvariable
- S cacheversion
- F checkedvariable
- F cleanedpathlist
- D cleaners
- F cleanpath
- F cleanpathlist
- F cleanupbinfile
- D concatinators
- S configbanner
- F configurationfiles
- D dangerous
- F datastate
- F dirstatus
- F dowithfilesandreport
- F dowithfilesintree
- F dowithpath
- F dowithvariable
- F expandbraces
- F expandedpathfromlist
- F expandedpathlist
- F expandedpathlistfromvariable
- F expandpath
- F expandpathfromvariable
- F expansion
- F extendtexmfvariable
- F filtered_from_content
- F find_file
- F find_files
- F findbinfile
- F findctxfile
- D finders
- F findfile
- F findfiles
- F findgivenfile
- F findgivenfiles
- F findlib
- F findpath
- F findpk
- F findtexfile
- F findwildcardfile
- F findwildcardfiles
- F formatofsuffix
- F formatofvariable
- D formats
- F foundintree
- F foundintrees
- D generators
- F get_from_content
- F getdetails
- F getenv
- F getextrapaths
- F getfilehashes
- F gethashes
- F getownpath
- F getreadfilename
- D hashers
- S homedir
- F ignorelibrary
- F initialized
- F installinputfilehandler
- F installinputlinehandler
- F jobpath
- F joinpath
- F knownvariables
- F load

F loadbinfile
D loaders
F loadlualib
F loadtexfile
F loadtime
F locateformat
D locators
S luacnffallback
S luacnfname
S luacnfspec
S luacnfstate
N maxreadlevel
F methodhandler
F missinglibrary
F openbinfile
D openers
F openfile
F opentexfile
S ownpath
F popextrapath
F popinputname
F poppath
D prefixes
F prependhash
F pushextrapath
F pushinputname
F pushpath
F registerextrapath
F registerfile
F registerfilehash
F registerintrees
F registermethod
F registerzipfile
D relations
F renew
F renewcache
F repath
F reset
F resetextrapaths
F resetresolve
F resolve
D savers
F scandata
F scanfiles
F setdynamic
F setenv
F showdetails
F showpath
F simplescanfiles
F splitconfigurationpath
F splitexpansions
F splitmethod
F splitpath
F stackpath
F starttiming
F stoptiming
D suffixes
D suffixmap
F suffixofformat
F texdatablob
F toppath
D tracers
F unexpandedpath
F unexpandedpathlist
F unresolve
F updaterelations
F uselibrary
D usertypes
F usezipfile
F validatedpath
F variable
F variableofformat
F variableofformatorsuffix
F wildcardpattern

sandbox table

F enable
F getrunner
F possiblepath
F registerrunner
F setfilenamelogger

scripts table

D colors
F decomposehangul
F getdata
F getinjector
F getsplitter
F getstatus
D handlers

D helpers
D injectors
F installdataset
F installmethod
D numbertodataset
D numbertohandler
F reset
F set
F setstatus
D splitters

security table
F checked
F getactions
F gettargets
F resetdebug
F setchecker

select function

sequencer table
F addbytestobuffer
F addformattobuffer
F addpackingtobuffer
F addtobuffer
F fastserialize
F format
F getbufferdata
F getbuffersize
F newbuffer
F sequenced
F serialize
F sortedhash
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
F tostring

serial table
F __gc
S __name
F __tostring
F close
F open
F send
F tostring
F write

server table
F httpserver
F supported

set table
F contains
F create
F tolist
F tonumber
F totable

setinspector function

setmathparameters function

setmetatable function

sha2 table
F HASH256
F HASH384
F HASH512
F HEX256
F HEX384
F HEX512
F digest256
F digest384
F digest512
F hash256
F hash384
F hash512
F hex256
F hex384
F hex512
F sum256
F sum384
F sum512

sio table
F read2dot14
F readbytes
F readbytetable
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable

F readcline
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat
F readfloatle
F readfloatle12
F readfloatle6
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F tocardinal1
F tocardinal1le
F tocardinal2
F tocardinal2le
F tocardinal3
F tocardinal3le
F tocardinal4
F tocardinal4le
F tocardinal8
F tocardinal8le
F tointeger1
F tointeger1le
F tointeger2
F tointeger2le
F tointeger3
F tointeger3le
F tointeger4
F tointeger4le
F tointeger8
F tointeger8le

sorters table

F basicsorter
D definitions
F firstofsplit
F packch
F packuc
F replacementlist
F setlanguage
F sort
F strip
D tracers
F update

sparse table

F concat
F get
F max
F min
F new
F range
F restore
F set
F traverse
F wipe

statistics table

F benchmarktimer
F checkfmtstatus
F currenttime
F elapsed
F elapsedindeed
F elapsedseconds
F elapsedtime
B enable
F formatruntime
F istiming
F memused
F register
F resettiming
F runtime
F savefmtstatus
F show
F showmemory
F showusage
F starttiming
F stoptiming
N threshold
F timed
F tracefunction

status table

F getbalancestate

F getbufferstate
F getcallbackstate
F getconstants
F getdumpstate
F geterrorlinestate
F geterrorstate
F getexpandstate
F getfilestate
F getfontstate
F gethalferrorlinestate
F gethashstate
F gethyphenationstate
F getinputstate
F getinsertstate
F getlanguagestate
F getlinebreakstate
F getlookupstate
F getluastate
F getmarkstate
F getmvlstate
F getneststate
F getnodestate
F getparameterstate
F getpoolstate
F getreadstate
F getsavestate
F getsparsestate
F getstringstate
F gettexstate
F gettokenstate
F getwarningstate
F list
F resetmessages

storage table

F allocate
F mark
F marked
N max
N min
N nofmodules
N noftables
F register
D shared
D storedfunctions
B strip
N tofmodules
N toftables

streams table

F collect
F disable
F enable
F flush
F initialize
F push
F start
F stop
F synchronize

string table

F booleanstring
F byte
F bytepairs
F bytes
F bytetable
F char
F characterpairs
F characters
F checkedsplit
F chrtointeger
F collapsespaces
F containsws
F count
F dectointeger
F dump
F escapedpattern
F f6
F fd
F fd3
F fd6
F fd9
F find
F format
F formatted
F formatter
D formatters
F formatting
F fromunicode16
F fullstrip
F g6

F gd
F gmatch
F gsub
F hextocharacters
F hextointeger
F is_boolean
F is_empty
F itself
F len
F limit
F linetable
F longtostring
F lower
F match
F nospaces
F octtointeger
F optionalquoted
F pack
F packrowscolumns
F packsize
F quote
F quoted
F rep
F replacenewlines
F reverse
F split
F splitintolines
F splitlines
F splitup
F strip
F sub
F texhashed
F texnewlines
F tformat
F toHEX
F toboolean
F tobytes
F tocontext
F todec
F todimen
F tohex
F tonodes
F topattern
F topdfeight
F topdfsixteen
F topdfstring
F totable
F tounicode16
F toutf
F toutf16
F toutf32
F toutf8
F unpack
F unquote
F unquoted
F upper
F utf16toutf8
F utfcharacter
F utfcharacters
F utfcharactertable
F utflength
F utfpadd
F utftabletostring
F utfvalue
F utfvalues
F utfvaluetable
F valid
F wordsplitter

structures table

F atlocation
F currentsectionnumber

table table

F append
F are_equal
F combine
F compact
F concat
F contains
F copy
F count
F create
F derive
F deserialize
F fastcopy
F fastserialize
F filtered
F flattened
F fromhash

F getn
F has_one_entry
F hashed
F identical
F imerge
F imerged
F insert
F is_empty
F keys
F load
F loweredkeys
F makeweak
F merge
F merged
F mirrored
F move
F pack
F prepend
F print
F remove
F reverse
F reversed
F save
F sequenced
F serialize
F setmetatablecall
F setmetatableindex
F setmetatableindices
F setmetatablenewindex
F sort
F sorted
F sortedhash
F sortedhashkeys
F sortedhashonly
F sortedindexonly
F sortedkeys
F sortedpairs
F sparse
F strip
F sub
F swapped
F tocontext
F tocsv
F tofile
F tohash
F toxml
F unique
F unpack

tabstr_boolean function

tabstr_flat function

tabstr_mixed function

tabstr_normal function

tex table

F attributetracking
D automigrationcodes
D autoparagraphcodes
F badness
D badnessmodecodes
F balance
D balancecallbackcodes
D boxcontinuationcodes
D boxoptioncodes
D breakcodes
D buildcodes
D charactercontrolcodes
D charactertagcodes
F chardef
D classoptioncodes
D conditionals
D constants
F cprint
N ctdcatcodes
N ctxcatcodes
F definefont
F dimensiondef
D directioncodes
D directives
D discoptioncodes
D discpartcodes
F dontcomplain
D doublescriptoptioncodes
F enableprimitives
F equal
F error
F expandasvalue
D experiments
F extraprimitives
F fatalerror

D fillcodes
D flagcodes
F fontidentifier
F fontname
F forcehmode
F forceinputstatefile
F forceinputstateline
F fprint
D frozenparcodes
F get
F getadjustoptionvalues
F getalignmentcontextvalues
F getamcode
F getappendadjustcontextvalues
F getappendmigratecontextvalues
F getattribute
F getautomigrationvalues
F getautoparagraphvalues
F getbadnessmodevalues
F getbalancecallbackvalues
F getbalanceparameterfields
F getbalanceresultfields
F getbalancestepoptionvalues
F getbox
F getboxcontinuationvalues
F getboxdir
F getboxoptionvalues
F getboxresourcebox
F getboxresourcedimensions
F getbreakcontextvalues
F getbuildcontextvalues
F getcardinalvalue
F getcatcode
F getcccode
F getcharactercontrolvalues
F getcharactertagvalues
F getcount
F getcurrentmvl
F getdelcode
F getdelcodes
F getdimen
F getdimensionvalue
F getdirectionvalues
F getdiscoptionvalues
F getdiscpartvalues
F getdoublescriptoptionvalues
F getemptyparagraphmodevalues
F geterrorrecoverymodevalues
F geterrorvalues
F getfillvalues
F getflagvalues
F getfloat
F getfontdimension
F getfontoffamily
F getfrozenparvalues
F getglue
F getglueoptionvalues
F getglyphdata
F getglyphdiscvalues
F getglyphoptionvalues
F getglyphprotectionvalues
F getglyphscales
F getglyphscript
F getglyphstate
F getgroupvalues
F gethccode
F gethelptext
F gethmcode
F gethyphenationvalues
F getiftypes
F getinputstatefile
F getinputstateline
F getinputstatemode
F getinsertcategoryvalues
F getinsertcontent
F getinsertdepth
F getinsertdistance
F getinsertheight
F getinsertlimit
F getinsertmaxplaced
F getinsertmultiplier
F getinsertoptionvalues
F getinsertsplitvalues
F getinsertwidth
F getintegervalue
F getinteraction
F getinteractionmodes
F getiovalues

F getkerneloptionvalues
F getkernoptionvalues
F getlargestusedmark
F getlccode
F getlinebreakparameterfields
F getlinebreakresultfields
F getlinebreakstatevalues
F getlinedir
F getlist
F getlistanchorvalues
F getlistfields
F getlistgeometryvalues
F getlistsignvalues
F getlocalbox
F getlocalboxlocations
F getlocallevel
F getmark
F getmarknames
F getmath
F getmathclassoptionvalues
F getmathcode
F getmathcodes
F getmathcontrolvalues
F getmathdir
F getmathgluevalues
F getmathoptionvalues
F getmathparametervalues
F getmathscriptordervalues
F getmathscriptsmodevalues
F getmathstylenamevalues
F getmathstylevalues
F getmathstylevariant
F getmathsurroundvalues
F getmathvariantpresets
F getmathvariantvalues
F getmeasure
F getmissingcharactervalues
F getmode
F getmodevalues
F getmuglue
F getmuskip
F getmvloptionvalues
F getnest
F getnestfields
F getnestlevel
F getnoadoptionvalues
F getnormalizelinevalues
F getnormalizeparvalues
F getnospacesmodevalues
F getoutputactive
F getoverloadstate
F getpacktypevalues
F getpagecontextvalues
F getpagestate
F getpagestatevalues
F getparagraphfillmodevalues
F getparagraphoptionvalues
F getparametermodevalues
F getparcontextvalues
F getpardataspecifications
F getpardir
F getparmodevalues
F getparstate
F getparstatefields
F getpartriggervalues
F getpenaltyoptionvalues
F getpositvalue
F getpreposststatevalues
F getprimitivelegacies
F getprimitiveorigins
F getprotrusionboundaryvalues
F getregisterindex
F getruleoptionvalues
F getrunstate
F getrunstatevalues
F getsfcode
F getshapingpenaltiesvalues
F getskip
F getsnappingvalues
F getspacefactorvalues
F getspaceskipvalues
F getspcode
F getspecialmathclassvalues
F getspecification
F getspecificationoptionvalues
F gettextcontrolvalues
F gettextdir
F gettoks

F getuccode
F getuleaderlocationvalues
F getunitclassvalues
F getusedmarks
F getvariablefamilyvalues
F getvsplitcontextvalues
D glueoptioncodes
D glyphdisccodes
D glyphoptioncodes
D groupcodes
F hashtokens
N hshcatcodes
D hyphenationcodes
D ifs
N inicatcodes
D insertcategorycodes
D insertoptioncodes
D insertsplitcodes
F integerdef
D interactioncodes
F isattribute
F isbox
F iscount
F isdefined
F isdimen
F isfloat
F isglue
F ismuglue
F ismuskip
F isprintable
F isskip
F istoks
F lastnodetype
F less
F lessequal
F linebreak
D linebreakstatecodes
D listanchorcodes
D listgeometrycodes
D listsigncodes
N luacatcodes
F mathchardef
D mathcontrolcodes
D mathoptioncodes
D mathparametercodes
D mathscriptordercodes
D mathscriptsmodecodes
D modes
F mprint
D mvloptioncodes
N nilcatcodes
D noadoptioncodes
D normalizelinecodes
D normalizeparcodes
D nospacesmodecodes
N notcatcodes
F number
D paragraphfillmodecodes
D paragraphoptioncodes
D parcontextcodes
D partriggercodes
D penaltyoptioncodes
F poplocal
F popsavelevel
F positdef
F preparelinebreak
F primitives
F print
D protrusionboundarycodes
N prtcatcodes
F pushlocal
F pushsavelevel
F quitlocal
F quittoks
F resetparagraph
N rlncatcodes
F romannumeral
F round
D ruleoptioncodes
F runlocal
D runstatecodes
F runstring
F runtoks
F saveboxresource
F scale
F scantoks
F set
F setamcode

F setattribute
F setbalanceshape
F setbox
F setboxdir
F setcardinalvalue
F setcatcode
F setcccode
F setconditional
F setcount
F setdelcode
F setdimen
F setdimensionvalue
F setfloat
F setglue
F setglyphdata
F setglyphscript
F setglyphstate
F sethccode
F sethmcode
F setinputstatefile
F setinputstateline
F setinputstatemode
F setinsertcontent
F setinsertdistance
F setinsertlimit
F setinsertmaxplaced
F setinsertmultiplier
F setintegervalue
F setinteraction
F setlccode
F setlinedir
F setlist
F setlocalbox
F setmath
F setmathcode
F setmathdir
F setmuglue
F setmuskip
F setnest
F setoverloadstate
F setpardir
F setpositvalue
F setrunstate
F setsfcode
F setskip
F setspcode
F settextdir
F settoks
F setuccode
D shapingpenaltiescodes
F shiftparshape
F shipout
F showcontext
D snappingcodes
F snapshotpar
F sp
D spacefactorcodes
D spaceskipcodes
D specialmathclasscodes
D specificationoptioncodes
F splitbox
D splitcodes
F sprint
F stringtocodesbitmap
D systemmodes
F takebox
N texcatcodes
D textcontrolcodes
F tonumber
F toscaled
N tpacatcodes
N tpbcatcodes
F tprint
F trackedattribute
D trackers
F triggerbuildpage
N txtcatcodes
F uprint
F useboxresource
D userdiscoptioncodes
D userglyphoptioncodes
N vrbcatcodes
F write

texconditionals data table

texconfig table

S firstline
S formatname
N functionsize

F init
B kpse_init
N propertiessize
S shell_escape

texconstants data table

texifs data table

texio table

F closeinput
F forceendoffile
F getinputindex
F getselectorvalues
F getsourcefilename
F setlogfile
F terminal
F write
F write_nl
F writenl
F writeselector
F writeselectorlf
F writeselectornl

texisdefined data table

texmodes data table

texsystemmodes data table

thirddata table

timer table

S __name
F __tostring
F current
F elapsed
F elapsedms
F elapsedus
F elapsedμs
F istiming
F new
F reset
F setoffset
F sleepms
F start
F stop
F tostring

toboolean function

todecimal function

token table

F create
F expand
F expand_macro
F expandmacro
F future_expand
F futureexpand
F get_active
F get_cmdchrcs
F get_cmdname
F get_command
F get_csname
F get_cstoken
F get_dimension
F get_expandable
F get_fields
F get_flags
F get_frozen
F get_id
F get_immutable
F get_index
F get_instance
F get_integer
F get_macro
F get_meaning
F get_noaligned
F get_parameters
F get_permanent
F get_primitive
F get_protected
F get_range
F get_tok
F get_tolerant
F getactive
F getcmdchrcs
F getcmdname
F getcommand
F getcommandvalues
F getconstant
F getcsname
F getcstoken
F getdimension
F getexpandable
F getexpansion
F getfields
F getflags

F getfrozen
F getfunctionvalues
F getid
F getimmutable
F getindex
F getinstance
F getinteger
F getlength
F getmacro
F getmeaning
F getnoaligned
F getparameters
F getpermanent
F getprimitive
F getprimitives
F getprotected
F getrange
F gettok
F gettolerant
F gobble
F gobble_dimension
F gobble_integer
F gobbledimension
F gobbleinteger
F grab
F grabstring
F inhibit
F is_defined
F is_next_char
F is_token
F isactivestring
F isdefined
F isnextchar
F istoken
F locatemacro
F new
F peek_next
F peek_next_char
F peek_next_expanded
F peeknext
F peeknextchar
F peeknextexpanded
F pop_macro
F popmacro
F push_macro
F pushmacro
F put_back
F put_next
F putback
F putnext
F save_lua
F savelua
F scan_argument
F scan_box
F scan_cardinal
F scan_char
F scan_cmdchr
F scan_cmdchr_expanded
F scan_code
F scan_csname
F scan_delimited
F scan_dimen
F scan_float
F scan_glue
F scan_integer
F scan_key
F scan_keyword
F scan_keyword_cs
F scan_letters
F scan_luacardinal
F scan_luainteger
F scan_luanumber
F scan_next
F scan_next_char
F scan_next_expanded
F scan_real
F scan_scale
F scan_skip
F scan_string
F scan_token
F scan_token_code
F scan_tokenlist
F scan_toks
F scan_value
F scan_word
F scanargument
F scanbox
F scancardinal

F scanchar
F scancmdchr
F scancmdchrexpanded
F scancode
F scancsname
F scancstoken
F scandelimited
F scandetokened
F scandimen
F scandimenargument
F scandimension
F scandimensionargument
F scanfloat
F scanglue
F scanint
F scaninteger
F scanintegerargument
F scankey
F scankeyword
F scankeywordcs
F scanletters
F scanluacardinal
F scanluainteger
F scanluanumber
F scannext
F scannextchar
F scannextexpanded
F scanposit
F scanreal
F scanscale
F scanskip
F scanstring
F scantoken
F scantokencode
F scantokenlist
F scantokenstring
F scantoks
F scanvalue
F scanword
F serialize
F set_dimension
F set_integer
F set_lua
F set_macro
F setdimension
F setinteger
F setlua
F setmacro
F setmacrofrommark
F setmacrotonothing
F skip_next
F skip_next_expanded
F skipnext
F skipnextexpanded
F type
F undefine_macro
F undefinemacro

tokens table

F astable
D cache
D commands
F compile
F constant
F create
F defined
F flags
F getinteger
F gobble
F isactivestring
F isdefined
F istoken
F new
F pickup
F popmacro
F pushmacro
F setinteger
D values

tonumber function

tostring function

tostring_u1 function

tostring_u2 function

tracers table

F printerror
F printwarning
F processerror
F showlines

trackers table

D data

F default
F disable
F dumphashtofile
F enable
F list
S name
F register
F report
F reset
F savehash
F set
F show
F value
F values
type function
typesetters table
F marksuspects
F showinvisibles
F showsuspects
unpack function
updaters table
F apply
F register
url table
F addscheme
F barepath
F construct
F decode
F encode
F escape
F filename
F hashed
F hasscheme
F query
F split
F toquery
F unescape
F unescapeget
userdata table
utf table
F byte
F bytepairs
F char
F characters
F chrlen
F count
F filetype
F is_valid
F len
F length
F lower
F remapper
F replacer
F split
F splitlines
F sub
F substituter
F tocodes
F toeight
F toentities
F tostring
F totable
F upper
F ustring
F utf16_to_utf8_be
F utf16_to_utf8_be_t
F utf16_to_utf8_le
F utf16_to_utf8_le_t
F utf16_to_utf8_t
F utf32_to_utf8_be
F utf32_to_utf8_be_t
F utf32_to_utf8_le
F utf32_to_utf8_le_t
F utf32_to_utf8_t
F utf8_to_utf16
F utf8_to_utf16_be
F utf8_to_utf16_le
F utf8_to_utf8_t
F values
F xstring
utf8 table
F char
S charpattern
F codepoint
F codes
F len
F offset
utilities table

vector table

F add
F append
F average
F ceiling
F checkoverlap
F collectoverlap
F concat
F copy
F crossproduct
F delete
F determinant
F div
F equal
F exchange
F floor
F get
F getdimensions
F getepsilon
F getmemory
F getmesh
F getmeshtypes
F getpointtypes
F getrc
F getrow
F getsize
F getstacking
F gettype
F homogenize
F identity
F inner
F insert
F inverse
F ismesh
F ispoints
F issingular
F isvector
F iszero
F meshname
F mul
F negate
F new
F normalize
F onecolumn
F onerow
F product
F remove
F replace
F round
F rowechelon
F set
F setepsilon
F setnext
F setrc
F setstacking
F slice
F sort
F sub
F swap
F tostring
F totable
F transpose
F triangulate
F truncate
F type

visualizers table

D escapepatterns
F getspecification
F getvisualizer
F load
F makenested
F makepattern
F newgrammar
F newhandler
F parsedxml
F pattern
F register
F registerescapecommand
F registerescapeline
F registerescapepattern
S signal
U signalpattern
D specifications
F visualize
F visualizebuffer
F visualizefile
F visualizestring
F write

F writeargument
F writedefault
F writeemptyline
F writenewline
F writespace

warn function

xcomplex table

F I
F __add
F __div
F __eq
F __mul
S __name
F __pow
F __sub
F __tostring
F __unm
F abs
F acos
F acosh
F arg
F asin
F asinh
F atan
F atanh
F conj
F cos
F cosh
F dawson
F erf
F erfc
F erfcx
F erfi
F exp
F i
F imag
F log
F new
F pow
F proj
F real
F sin
F sinh
F sqrt
F tan
F tanh
F topair
F tostring
F totable
F voigt
F voigt_hwhm

xdecimal table

F __add
F __band
F __bor
F __bxor
F __div
F __eq
F __idiv
F __le
F __lt
F __mod
F __mul
S __name
F __pow
F __shl
F __shr
F __sub
F __tostring
F __unm
F abs
F band
F bor
F bxor
F conj
F copy
F exp
F getprecision
F ln
F log
F max
F min
F minus
F new
F plus
F pow
F rotate
F setprecision

F shift
F sqrt
F toengstring
F tonumber
F tostring
F trim

xinterval table

F __add
F __div
F __eq
F __le
F __lt
F __mod
F __mul
S __name
F __pow
F __sub
F __tostring
F __unm
F abs
F acos
F acosh
F asin
F asinh
F asstring
F atan
F atanh
F cos
F cosh
F diameter
F equal
F erf
F erfc
F exp
F exp10
F exp2
F expm1
F greater
F greaterequal
F hull
F intersect
F less
F lessequal
F log
F log10
F log1p
F log2
F mid
F mod
F new
F neweps
F pow
F seteq
F setge
F setgt
F setle
F setlt
F sin
F sinh
F sqr
F sqrt
F tan
F tanh
F topair
F tostring
F totable
F usedendian
F within

xmath table

F acos
F acosh
F asin
F asinh
F atan
F atan2
F atanh
F cbrt
F ceil
F copysign
F cos
F cosh
F crossproduct
F deg
F dotproduct
F erf
F erfc
F exp
F exp2

F expm1
F fabs
F fdim
F floor
F fma
F fmax
F fmin
F fmod
F frexp
F gamma
F hypot
N inf
F isfinite
F isinf
F isnan
F isnormal
F j0
F j1
F jn
F ldexp
F lgamma
F log
F log10
F log1p
F log2
F logb
F modf
N nan
F nearbyint
F nextafter
F normalize
N pi
F pow
F rad
F remainder
F remquo
F round
F scalbn
F sin
F sinh
F sqrt
F tan
F tanh
F tgamma
F trunc
F y0
F y1
F yn

xml table

F addentitiesdoctype
F addspecialcode
F after
F all
F applylpath
F applyselector
F assign
F attribute
F badinclusions
F before
F body
F cdata
F cdatatotext
F checkbom
F checkedempty
F checkerror
F checknamespace
F checkns
F cleansed
F collect
F collect_elements
F collect_tags
F collect_texts
F collected
F collecttexts
F compactelement
F content
F convert
F copy
F count
F cprint
S defaultprotocol
F delete
F delete_element
F despecialized
F each
F each_element
F elements
F elementtocdata

F empty
D entities
F erase
F errorhandler
F escaped
F expand
F fillin
F filter
F first
F found
F getbuffer
F gethandlers
F gethandlersfunction
F include
F inclusion
F inclusions
F index
F inheritattributes
F inheritedconvert
F inject
F inject_element
F inject_element_after
F inject_element_before
F injectafter
F injectbefore
F insert
F insert_element
F insert_element_after
F insert_element_before
F insertafter
F insertbefore
F insertcdata
F insertcomment
F inspect
F is_valid
F kind
F last
F lastmatch
F load
F lpath
F lpathcached
F lpathcalls
F lshow
F makestandalone
F match
F name
F newhandlers
F nodesettostring
F originalload
F package
F parent
U parsedentitylpeg
F popmatch
F position
D privatecodes
F privatetoken
F process
F process_attributes
F process_elements
F processattributes
F pure
F pushmatch
F raw
F registerentity
F registerns
F reindex
F remap_name
F remap_namespace
F remap_tag
F remapname
F remapnamespace
F remaptag
F rename
F renamespace
U reparsedentitylpeg
F replace
F replace_element
F resetinjectors
F resolvens
F root
F save
F selection
F separate
F serialize
F serializetotext
F setcdata
F setcomment
F sethandlersfunction

F setinjectors
F setproperty
F settings
D specialcodes
F sprint
F string
F strip
F strip_whitespace
F stripelement
F stripleadingspaces
F table
F text
F textonly
F texttocdata
F tocdata
F toelement
F tostring
F totable
F toxml
F tprint
F traverse
F unescaped
U unescapedentitylpeg
F unprivatized
F unspecialized
F wipe
F withelement
F withelements
F wrap

xpcall function

xzip table

F adler32
F compress
F compresssize
F crc32
F decompress
F decompresssize

zbuffer table

F bounds
F composite
F crop
F edgepoint
F flatten
F get
F getcolor
F getconstants
F getdepth
F getnormal
F getnormalmodes
F getopacity
F getsize
F implicit
F iszbuffer
F meshmesh
F new
F points
F process
F project
F resolve
F set
F setcolor
F setdepth
F setnormal
F setopacity
F setup
F smoothen
F stipple_0
F stipple_1
F stipple_2
F stipple_3
F stipple_4
F stipple_setup
F tobytes
F tostring
F totable
F transform
F trianglebounds
F triangled
F triangles
F type

zip table

F closearchive
F openarchive

zlib table

F adler32
F compress
F compresssize
F crc32

F decompress

F decompresssize

globals (context)

CONTEXTLMTXMODE number
JITSUPPORTED boolean
LUAFORMAT number
LUAMAJORVERSION number
LUAMINORVERSION number
LUATEXENGINE string
LUATEXFORMATID number
LUATEXFUNCTIONALITY number
LUATEXVERBOSE string
LUATEXVERSION number
LUAVERSION number
MP function
SAVEDREQUIRE function
aes table
F decode
F encode
F random
arg table
assert function
attributes table
F applyoverloads
F checkvalues
D counts
F define
F getvalue
F getvalues
F hasvalues
D list
F markasoverload
D names
D numbers
F ofnode
F private
F public
F registervalue
F restore
F save
F setcleaner
F showcurrent
F system
F tooverloads
N unsetvalue
D values
backends table
F closeout
S current
F getcallbackstate
F initialize
F latelua
F nothing
F openout
F setencryption
F writeout
basexx table
F decode16
F decode64
F decode85
F decodeLZW
F decodeRL
F encode16
F encode64
F encode85
F encodeLZW
F encodeRL
bibtex table
bit32 table
F arshift
F band
F bnot
F bor
F btest
F bxor
F extract
F lrotate
F lshift
F replace
F rrotate
F rshift
bitset table
F assign
F asstring
F band

F bnot
F bor
F bxor
F get
F len
F new
F newonebased
F newzerobased
F reset
F set
F shl
F shr
F tostring
F totable
F traverse
F wipe

blobs table

F append
F dimensions
F dispose
F new
F pack
F strdp
F strhd
F strht
F strwd
F tohpack
F tonodes
F tovpack
F write

boolean table

F tocontext
F tonumber

buffers table

F append
F assign
F collectcontent
F empty
F erase
F exists
F get
F getcontent
F getctxlua
F getlines
F getmkvi
F gettex
F loadcontent
F prepend
F raw
F run
F samplefile
F splitsamplefile
F undent

builders table

F checkparcontext
F checksidefloat
F parpassidentifier
D passnames
F registerpaspasscallback

bytemap table

F bounds
F clip
F copy
F dimensions
F domain
F downgrade
F downsample
F fillgray
F fillrgb
F filter
F getbyte
F getbytes
F getluminance
F getvalue
F hasbytegray
F hasbyterange
F hasbytergb
F new
F newdomain
F overlay
F process
F reduce
F reset
F setgray
F setgrayadd
F setgraymin
F setrgb
F slicegray

F slicerange
F slicergb
F totable

caches table

S base
F collapsecontent
F configfiles
F contentstate
F getfirstreadablefile
F getreadablepaths
F getwritablepath
F hashed
F is_writable
F loadcontent
F loaddata
S more
F savecontent
F savedata
F setfirstwritablefile
F setluanames
F treehash
F usedpaths

callback table

F find
F getcontracts
F getcontractvalues
F getindex
F getoptions
F getoptionvalues
F getstate
F getstatevalues
F known
F list
F names
F register
F setoptions
F setstate
F testonly
F usage

callbacks table

F freeze
F getcomment
F getstates
F known
F optimizer
F pop
F push
F register
F report

catcodes table

D names
D numbers
F register

characterkern function

characters table

F addcharacternames
F adobename
D bidi
F blockrange
D blocks
D can_have_space
D categories
F category
D categorytags
D collapsed
D combined
F contextname
D csletters
D data
D decomposed
F description
D descriptions
D detailtags
F emojized
D enccodes
D entities
D fallbacks
D filters
F fromnumber
D fschars
D fscodes
F getrange
D graphemes
D hangul
F initialize
D is_character
D is_command
D is_hyphenator

D is_letter
D is_mark
D is_nothing
D is_punctuation
D is_spacing
D is_symbol
D lcchars
F lccode
D lccodes
F lettered
D lhash
D linebreaks
F lower
D mathlists
D otfscripts
D ranges
F registerentities
F remap_hangul_syllabe
F setactivecatcodes
F setlettercatcodes
F setothercatcodes
F shape
F shaped
D shash
D shchars
D shcodes
F showstring
D specialchars
D specials
D synonyms
F tonumber
D ucchars
F uccode
D uccodes
D uhash
F unicodechar
F upper
D verbosemarks

chemistry table

F component
F define
D definitions
S format
F inlinechemical
S instance
S method
F molecule
U moleculeparser
F start
F stop
F undefine

client table

F httprequest
F supported

collectgarbage function

commands table

F Alphabetic
F MPLIBconvertfollowtext
F MPLIBconvertoutlinetext
F MPc
F MPd
F MPfromhash
F MPh
F MPll
F MPlr
F MPls
F MPn
F MPp
F MPpardata
F MPplus
F MPpos
F MPr
F MPrest
F MPrs
F MPul
F MPur
F MPw
F MPwhd
F MPx
F MPxy
F MPxywhd
F MPy
F Romannumerals
F actualday
F actualmonth
F actualyear
F adaptfontfeature
F adaptivecheckbox

F addbtxentry
F addcounter
F adddefaultsuffix
F addfeature
F addfontpath
F addgrapheme
F addlinenumbers
F addlinklistelement
F addreplacements
F addreplacementslist
F addrivers
F addtocolumnset
F addtocolumnsetmvl
F addtojavascriptpreamble
F addtolist
F align_point_delta
F allinputpaths
F alphabetic
F analysefloatmethod
F analyzeitemgroup
F analyzelist
F analyzelocalanchors
F analyzeregister
F analyzerotate
F analyzeupcomingitemgroup
F applypattern
F applytobox
F applytofirstcharacter
F arraycompare
F arrayequals
F arraymaxvalue
F arrayminvalue
F arraysize
F arrayvalue
F ascender
F askedreference
F assignbuffer
F async
F attachinsertion
F attachinsertions
F atwordboundary
F autofinishstructurelevels
F autoinsertnextspace
F automigrationcodestring
F autonextstructurelevel
F autorule
F autosetups
F autostarttext
F autostoptext
F badnessmodecodestring
F balanceshapeextra
F benchmarktimer
F bf
F bi
F bitmapimage
F bitwise
F bitwiseand
F bitwiseflip
F bitwisenil
F bitwisenot
F bitwiseor
F bitwiseset
F bitwiseshift
F bitwisexor
F blockcolumnset
F blockligatures
F boolcase
F boxdir
F boxline
F boxlinedp
F boxlineht
F boxlineil
F boxlinein
F boxlineir
F boxlinelh
F boxlinelp
F boxlinels
F boxlinemaxdp
F boxlinemaxht
F boxlinemaxwd
F boxlinend
F boxlinenh
F boxlinenw
F boxlinerh
F boxlinerp
F boxliners
F boxlines
F boxlinewd

F boxoptioncodestring
F boxrangedp
F boxrangeht
F boxrangewd
F boxtostring
F bposcolumn
F bposcolumnregistered
F bs
F btxabbreviatedjournal
F btxaddentry
F btxaddjournal
F btxauthor
F btxauthorfield
F btxauthortoregister
F btxcmdstring
F btxcollectlistentries
F btxcurrentfirstnames
F btxcurrentinitials
F btxcurrentjuniors
F btxcurrentsurnames
F btxcurrentvons
F btxdetail
F btxdirect
F btxdoif
F btxdoifelse
F btxdoifelsecitedone
F btxdoifelsecombiinlist
F btxdoifelsematches
F btxdoifelsesameasprevious
F btxdoifelseuservariable
F btxdoifnot
F btxentrytobuffer
F btxentrytostring
F btxexpandedjournal
F btxfetchlistentries
F btxfield
F btxfirstofrange
F btxflush
F btxflushlistcombi
F btxflushlistentry
F btxflushlisttag
F btxflushmarked
F btxflushpages
F btxhandlecite
F btxhandlenocite
F btxlastofrange
F btxlistvariant
F btxloaddefinitionfile
F btxloadjournallist
F btxloadreplacementfile
F btxmissing
F btxoneorrange
F btxpreparelistentries
F btxremapauthor
F btxsavedataset
F btxsavejournallist
F btxsetdataset
F btxsetentry
F btxsetregister
F btxsetspecification
F btxshortcut
F btxshowauthorremapping
F btxsingularorplural
F btxtoregister
F btxusedataset
F btxuservariable
F build_page_after_shipout
F build_page_before_shipout
F build_page_setup
F capheight
F charactercontrolcodestring
F chardescription
F checkcolumnset
F checkcolumnsetmvl
F checkcountersetup
F checkedconversion
F checkedemoji
F checkedpagefloat
F checkinjector
F checkinterfacechain
F checkmarkedpages
F checknesting
F checkspacingavailable
F checkstrutdepth
F chemicalcomponent
F chinesenumerals
F chr
F classoptioncodestring

F cleancolumnset
F cleanfontname
F cleanupattributes
F cleanupbox
F cleanuplayers
F clonefield
F closein
F closeout
F codedef
F collectedmath
F collectfloat
F collecthelp
F columnsetbalancefirst
F columnsetbalancelast
F columnsetbalancepage
F columnsetcolumnwidth
F columnsetdisablewide
F columnsetenablewide
F columnsetgoto
F columnsethascontent
F columnsethspan
F columnsetlastfuture
F columnsetlastmvl
F columnsetlimit
F columnsetnoto
F columnsetresetdirect
F columnsetresetshapeextra
F columnsetreshape
F columnsetsblockrows
F columnsetsetshapeextra
F columnsetshape
F columnsetshapebalancecheck
F columnsetshapebalanceextend
F columnsetshapecolumn
F columnsetshapecount
F columnsetshapeindex
F columnsetshapepage
F columnsetshapesetbalancerange
F columnsetshapeslots
F columnsetshapespread
F columnsetshapevsize
F columnsetshapeworst
F columnsetshowgrid
F columnsetshowshape
F columnsetshowtracedgrid
F columnsetstate
F columnsetstatus
F combineglyphs
F component
F concatcommalist
F consultfloat
F continueifinputfile
F convertbtxdatasettoxml
F converteddimen
F convertmpstopdf
F copyboxfromcache
F copyboxline
F copyposition
F cos
F cosd
F ctxfunction
F ctxluamatch
F ctxluamatchfile
F ctxresetter
F ctxscanner
F currentcomponent
F currentdate
F currentdesignsize
F currentenvironment
F currentfontinstancespec
F currentposthyphenchar
F currentprehyphenchar
F currentproduct
F currentproject
F currentsectiontolist
F datasetsize
F datasetvariable
F day
F daymnem
F dayname
F decimals
F decrementcounter
F decrementsubcounter
F deferredenhancelist
F deferredenhancereference
F deferredenhanceregister
F defineaccents
F defineattribute

F defineboundary
F definebreakpoint
F definebreakpoints
F definecharacterspacing
F definechemical
F definecolumnset
F defineconversion
F definecounter
F definedlayoutcomponent
F definefallbackfamily
F definefield
F definefieldset
F definefilefallback
F definefilesynonym
F definefont_one
F definefont_two
F definefontcolorpalette
F definefontfamily
F definefontfamilypreset
F definefontfeature
F definefontscriptset
F definefontsolution
F definehyphenationfeatures
F defineinsertion
F defineintermediatecolor
F definelabcolorglobal
F definelabcolorlocal
F definelabels
F definelanguage
F definelinkedlist
F definemathpreset
F definemultitonecolorglobal
F definenamespace
F definenote
F defineparallel
F defineparbuilder
F defineprocesscolordummy
F defineprocesscolorglobal
F defineprocesscolorlocal
F defineprogram
F definereference
F defineregister
F definesectionlevels
F definespotcolorglobal
F definestructureblock
F definestructureset
F definesubcolumnset
F definetransparency
F definetransparencyglobal
F definetypeface
F defineviewerlayer
F delayedcolumnsetsheet
F depthnumber
F depthofstring
F descender
F detachinsertions
F diagnostic
F digits_normal
F digits_reverse
F directboxfromcache
F disableautofontscript
F disablecollectingmath
F disabledirectives
F disableexperiments
F disablejobsave
F disableparbuilder
F disableregime
F disablespellchecking
F disablestream
F disabletrackers
F discardfromlist
F discoptioncodestring
F disposeboxesincache
F disposeluatable
F doanalyzeframedbox
F doif
F doifcounter
F doifelse
F doifelseblack
F doifelseboxincache
F doifelsebuffer
F doifelsebufferempty
F doifelsecharinfont
F doifelseconverter
F doifelsecounter
F doifelsecounteractive
F doifelsecurrentfonthasfeature
F doifelsedimenstring

F doifelsedrawingblack
F doifelsefieldcategory
F doifelsefieldset
F doifelsefiledefined
F doifelsefileexist
F doifelsefirstchar
F doifelsefirstsectionpage
F doifelsefontfeature
F doifelsefontpresent
F doifelseindented
F doifelseinelement
F doifelseinputfile
F doifelseleapyear
F doifelselisthasentry
F doifelselisthasnumber
F doifelselisthaspage
F doifelselisthastitle
F doifelsemarkedcontent
F doifelsemarkedpage
F doifelsemessage
F doifelsenoteonsamepage
F doifelseobjectfound
F doifelseobjectreferencefound
F doifelseolderversion
F doifelseoverlapping
F doifelseparallel
F doifelseparentfile
F doifelsepathexist
F doifelsependingpagecontent
F doifelseposition
F doifelsepositiononpage
F doifelsepositionsonsamepage
F doifelsepositionsonthispage
F doifelsepositionsused
F doifelserangeonpage
F doifelsereference
F doifelsereferencechecked
F doifelsereferenced
F doifelserighttoleftinbox
F doifelsesame
F doifelsesomething
F doifelsespaces
F doifelsestackedfloats
F doifelsestructureblocksempty
F doifelsesynonymshown
F doifelsesynonymused
F doifelsetaggednoteonsamepage
F doifelseurldefined
F doifelseutfmathaccent
F doifelseutfmathfiller
F doifelseutfmathlimop
F doifelsevalidhashedfiles
F doifelsevisualizer
F doifmarkedpage
F doifnot
F doifnotcounter
F doifnotecontent
F doifnotsame
F doifnotthing
F doifposition
F doifsame
F doifsomething
F doifunknownfontfeature
F domainattribute
F doreshapeframedbox
F doresyncframedbox
F dosaveposition
F dosavepositionplus
F dosavepositionwhd
F dosetposition
F dosetpositionbox
F dosetpositionplus
F dosetpositionstrut
F dosetpositionstrutkind
F dosetpositionwhd
F dostarttextfile
F dostoptextfile
F doublescriptmodecodestring
F droptablegroup
F elapsedsteptime
F elapsedtime
F embedimagefromstore
F enablealignmentcharacter
F enablealignskips
F enableasciimode
F enableautofences
F enableautofontscript
F enablebackgroundalign

F enablebackgroundboxes
F enablecollectingmath
F enablecolor
F enablecolorintents
F enablecrlf
F enabledirectives
F enabledriver
F enableexperiments
F enablefontcolorschemes
F enablehidecontent
F enablemathalignrelocate
F enablematrixornaments
F enablematrixrules
F enableparbuilder
F enableregime
F enablescriptunstacking
F enablesidefloatchecker
F enablespellchecking
F enablestacking
F enablestream
F enableswapping
F enabletighten
F enabletrackers
F enabletransparency
F enableutf
F enhancelinkedlist
F enhancelist
F enhanceregister
F enhancesynonym
F environment
F eposcolumn
F eposcolumnregistered
F erasebuffer
F execute
F exportbox
F exportformdata
F exportreferences
F expression
F extendregister
F extendregisterlate
F extensiblecode
F fakeword
F featureattribute
F feedback
F fetchlanguagetext
F fetchmultipar
F fetchposboxes
F fetchterminaldata
F figure_flush_registered_pages
F figure_mergegoodies
F figure_nof_registered_pages
F figure_register_page
F figuresetdimensions
F filebasename
F filedirname
F filenameonly
F filesuffix
F filterdefaultreference
F filterreference
F finalizeobjectbox
F finalizeshipoutbox
F findregisterinternal
F finishcolumnsetflush
F finishexport
F firstinset
F firstsectionpage
F firstsubcountervalue
F flagcodestring
F flushcolumnsetareas
F flushcolumnsetcolumn
F flushfloat
F flushlabeledfloat
F flushnoterange
F flushnotes
F flushpageblocks
F flushpageinjectionsafter
F flushpageinjectionsbefore
F flushpostponedblocks
F flushpostponednotes
F flushstream
F flushstreamcopy
F fontchar
F fontcharbyindex
F fontcollectionclone
F fontcollectiondefine
F fontcollectionprepare
F fontcollectionregister
F fontcollectionreport

F fontcollectionreset
F fontlookupgetkey
F fontlookupgetkeyofindex
F fontlookupinitialize
F fontlookupnoffound
F forceendjob
F forcepageflush
F forcequitjob
F forcestrutdepth
F format
F formatcolor
F formatgray
F formatluminance
F formatluminanceratio
F formatone
F framedoutline
F from
F frozenparcodestring
F frule
F getMPdata
F getbidimode
F getbodyfontsizes
F getboxcountfromcache
F getboxdpfromcache
F getboxfromcache
F getboxhtdpfromcache
F getboxhtfromcache
F getboxwdfromcache
F getbuffer
F getbuffercontent
F getbufferctxlua
F getbuffermkvi
F getbuffertex
F getcharactercasingcategory
F getclubpenalties
F getcurrentprefixspec
F getcurrentreferencelabel
F getcurrentreferencemetadata
F getdefaultfieldvalue
F getdisplaywidowpenalties
F getdocumentargument
F getdocumentfilename
F getfieldcategory
F getfile
F getfirstcharacter
F getfloatvariable
F getfromluatable
F getfullstructurenumber
F getinterlinepenalties
F getinternalcachedlistreference
F getinternallistreference
F getinternalorderreference
F getmathblobindex
F getmathblobmapping
F getmathcharone
F getmathchartwo
F getmathmathblob
F getmathtextblob
F getmathvariant
F getmessage
F getmpextensions
F getnaturaldimensions
F getnaturalwd
F getnofpreviouslines
F getnotestate
F getnotestorecount
F getnotestoreflushed
F getobjectdimensions
F getobjectreference
F getobjectreferencepage
F getparshape
F getparwrapper
F getprivatechar
F getprivateglyphslot
F getprivatemathchar
F getprivateslot
F getprogram
F getrandomdimen
F getrandomfloat
F getrandomnumber
F getrandomseed
F getreadfilename
F getreferencesectionnumber
F getrivers
F getsetupstring
F getshapeparameter
F getsomefullstructurenumber
F getsomestructurenumber

F getspecificstructuretitle
F getstructurelevel
F getstructurenumber
F getsubstring
F getsynchronizemarking
F geturl
F getvisual
F getwidowpenalties
F globalpopmacro
F globalpushmacro
F gluetolinesinbox
F glyphoptioncodestring
F gobblenested
F gotocolumnsetslot
F grabbuffer
F groupcodestring
F groupsetgroup
F grph_nodes_initialize
F grph_nodes_register
F grph_nodes_reset
F grph_nodes_resolve
F handlemathhang
F hboxtovbox
F heightofstring
F helpaction
F helpreference
F hour
F hpackbox
F hpackedbox
F hsplit
F hyphenateddigits
F hyphenatedlist
F hyphenationcodestring
F ic
F idxfromluatable
F if_common
F ifallmodes
F ifbitwiseand
F ifblobindexdone
F ifboxhaslist
F ifcommon
F ifeof
F ifgluelineinbox
F ifinset
F iflua
F ifmode
F ifmodes
F ifmvl
F ifpositunum
F ifsetups
F ifsystemmode
F iftext
F ifxml
F ifxmlatt
F ifxmlattempty
F ifxmlempty
F ifxmlselfempty
F ifxmltext
F ignorefile
F ignoretagsinexport
F immediatemessage
F includesvgbuffer
F includesvgfile
F incrementcounter
F incrementsubcounter
F inhibitprimitive
F initializeexport
F initializejob
F initializemathcollapsing
F initializemathfencing
F initializemathitalics
F initializemathkernpairs
F initializemathnumbers
F initializemathspacing
F initializestream
F initializetexdirectives
F initializetexexperiments
F initializetextrackers
F injectcurrentreference
F injectcurrentreferencehtdp
F injectdisable
F injectnowhite
F injectreference
F injectvpenalty
F injectvskip
F injectvspacing
F injectzerobaselineskip
F inlinechemical

F inputfilebarename
F inputfilename
F inputfilerealsuffix
F inputfilesuffix
F insertattachment
F insertcategorycodestring
F insertcomment
F insertfield
F insertionnumber
F insertoptioncodestring
F insertrenderingwindow
F inspectluatable
F installedlanguages
F installtexdirective
F installtexexperiment
F installtextracker
F interceptsamepagecontent
F it
F jobfilefullname
F jobfilename
F jobfilesuffix
F jobposd
F jobposh
F jobposp
F jobposw
F jobposx
F jobposy
F languagecharwidth
F languagenumber
F lastblobindex
F lastnodeequals
F lastnodeid
F lastnodeidstring
F lastnodesubtypestring
F lastparwrapper
F lastrpos
F lastsavedboxresourceindex
F lastsavedimageresourceindex
F lastsavedimageresourcepages
F lastsectionpage
F lastsubcountervalue
F lastunitstring
F lastxpos
F lastypos
F lateindent
F latelua
F lateundent
F lchexnumber
F lchexnumbers
F leapyear
F limitated
F linebuffering
F linedir
F lineprofilebox
F linesegment
F listanchorcodestring
F listbookmark
F listexternal
F listgroupindex
F listlabel
F listlocation
F listnamespaces
F listprefixednumber
F listprefixedpage
F listrawnumber
F listrawrealpage
F listrawuserpage
F listsigncodestring
F listsize
F listtitle
F listuserdata
F lmt_parameters_define
F lmt_parameters_preset
F lmt_parameters_reset
F loadcldfile
F loadcldfileonce
F loadexamodes
F loadfontgoodies
F loadlibrary
F loadluafile
F loadluafileonce
F loadluamodule
F loadmapfile
F loadmapline
F loadspellchecklist
F loadtexfile
F loadtexfileonce
F loadtypescriptfile

F loadvisualizer
F loadxmlfile
F loadxmlfileonce
F localanchorx
F localanchory
F localboxindent
F localboxindex
F localboxlefthang
F localboxleftoffset
F localboxleftskip
F localboxlinenumber
F localboxlinewidth
F localboxlocalwidth
F localboxmarkonce
F localboxovershoot
F localboxparfillleftskip
F localboxparfillrightskip
F localboxparinitleftskip
F localboxparinitrightskip
F localboxprogress
F localboxrighthang
F localboxrightoffset
F localboxrightskip
F localpopmacro
F localpushmacro
F locatefilepath
F loopcs
F loopcsn
F lousiness
F luacardinal
F luacount
F luadimen
F luaexpression
F luafloat
F luainteger
F luanumber
F luarandom
F luascript
F luathread
F lxmlid
F manipulated
F markblobindexdone
F markcontent
F markedpageparameter
F markedpages
F markingnumber
F markingtitle
F markinjector
F markpage
F markregionbox
F markregionboxcorrected
F markregionboxtagged
F markregionboxtaggedkind
F markregionboxtaggedn
F markvisualfonts
F mathclassvalue
F mathcontrolcodestring
F mathhorizontalcode
F mathoptioncodestring
F mathrenderset
F mathstrutcode
F mathvariantcode
F mathvariantcount
F mathvariantslot
F maxbufferwidth
F message
F metapostescaped
F metapostformatted
F metapostgraphformat
F minute
F mixcleanup
F mixfinalize
F mixflushlist
F mixflushrest
F mixgetsplit
F mixsetsplit
F mixstate
F modecodestring
F molecule
F month
F monthmnem
F monthname
F mpblobtext
F mpcolor
F mpgetblob
F mpgettext
F mpgraphic
F mpgraphictexttoks

F mpoptions
F mpoutlinetoks
F mppopvariables
F mppushvariables
F mprunset
F mpruntab
F mprunvar
F mpsetclippath
F mpsetoutercolor
F mpsetsxsy
F mpsettext
F mptexget
F mptexreset
F mptexset
F mptexsetfrombuffer
F mptexttoks
F mvloptioncodestring
F namedstructureuservariable
F namedstructurevariable
F naturalwd
F negatedcolorcomponent
F newarray
F newhashedtable
F newindexedtable
F newluatable
F newparwrapper
F newrepeatablerandom
F newstacking
F nextparallel
F nextsubcountervalue
F nodimen
F nofbufferlines
F nofconversions
F nofdays
F nofdetachedinsertions
F noflinesinbox
F nofmathvariants
F nofstackedfloats
F nologbuffering
F normalizecodestring
F normalizedbodyfontsize
F normalizeparcodestring
F nospacesmodecodestring
F notedeltapage
F noteinternal
F notelistindex
F noteprefixednumber
F notetitle
F ntb_split_section_check
F ntb_split_section_fetch
F ntb_split_section_locate
F ntb_split_section_reset
F ntimes
F number
F numbers
F objectreference
F objectreferencepage
F octnumber
F openin
F openout
F operatingsystem
F ordinal
F outputfilename
F overloadbookmark
F overloadlowercase
F overloadsattribute
F overloaduppercase
F pageblockrealpage
F pageofinternal
F pageoverflow
F pagestaterealpage
F pagestaterealpageorder
F paragraphfillmodecodestring
F paragraphoptioncodestring
F parcontextcodestring
F pardir
F parpasscallback
F parpassidentifier
F parpos
F partriggercodestring
F pdfbackendcurrentresources
F pdfbackendsetcatalog
F pdfbackendsetcolorspace
F pdfbackendsetextgstate
F pdfbackendsetinfo
F pdfbackendsetname
F pdfbackendsetpageattribute
F pdfbackendsetpageresource

F pdfbackendsetpagesattribute
F pdfbackendsetpattern
F pdfbackendsetshade
F pdfcolor
F pdfextension
F pdffeedback
F pdflastobj
F pdfliteral
F pdfobj
F pdfrefobj
F pdfsetuserdata
F pdfvariable
F percentageof
F pfabs
F pfacos
F pfacosh
F pfasin
F pfasinh
F pfatan
F pfatanh
F pfatantwo
F pfceil
F pfcos
F pfcosh
F pfdeg
F pfexp
F pffloor
F pflog
F pfmod
F pfpow
F pfrad
F pfrem
F pfround
F pfsin
F pfsinh
F pfsqrt
F pftan
F pftanh
F pgfxcolorspec
F pickupbuffer
F pickupmarkedcontent
F pickuppunctuation
F placeparallel
F popfloat
F pophyphenation
F poplist
F poplocalanchors
F poplogfile
F popparagraphtweak
F poppath
F poprandomseed
F popreferenceprefix
F popregime
F poprunstate
F popsectionblock
F positunum
F positunumdef
F postlistbox
F postlistcopy
F postponenotes
F prefixedconverted
F prelistbox
F prelistcopy
F preparecolumnsetflush
F prerolledpages
F presetcolumnsetsheets
F presetcolumnsetspreadsheets
F presetmathematics
F presetmathfontalternate
F presetsymbollist
F previoussubcountervalue
F privatecharacter
F privatecharactercode
F processbodyfontsizes
F processbuffer
F processcollectedmath
F processedfile
F processedfiles
F processfile
F processfilemany
F processfilenone
F processfileonce
F processjob
F processlist
F processregister
F processsplit
F processsynonyms
F product

F profilebox
F profilemacro
F project
F pruneboxesincache
F purefontname
F pushfloat
F pushhyphenation
F pushlist
F pushlocalanchors
F pushlogfile
F pushparagraphtweak
F pushpath
F pushrandomseed
F pushreferenceprefix
F pushregime
F pushrunstate
F pushsectionblock
F pushstream
F putboxincache
F putincolumnset
F putincolumnsetdirect
F putnextboxincache
F qrcodebuffer
F qrcodestring
F rawMPdata
F rawcharacter
F rawsetupstring
F rawsubcountervalue
F read
F readfromterminal
F readline
F readlinedirect
F recolorbox
F referencecolumn
F referencepagedetail
F referencepagestate
F referenceposx
F referenceposy
F referencerealpage
F registeranchorbox
F registerattachment
F registerbackendsymbol
F registerbackground
F registerbodyfontsize
F registerbookmark
F registerboxglyph
F registerbuttons
F registercolorintent
F registercolumnsetarea
F registercolumnsetsheet
F registercolumnsetspreadsheets
F registerengineclass
F registerfallbackfont
F registerfiguremask
F registerfigurepattern
F registerfigurerange
F registerfiguresuffix
F registerfilescheme
F registerfontalternative
F registerfontfamily
F registerforcedbreak
F registergroupset
F registerhashedfiles
F registerhelp
F registerhyphenationexception
F registerhyphenationpattern
F registeritemgroup
F registerlabel
F registerlanguagefeatures
F registerlinenumbering
F registermaintextcolor
F registermpextensible
F registernamedlua
F registernamespace
F registerobject
F registerpattern
F registerpostponedblock
F registerreferencedobject
F registerrendering
F registersection
F registershownsynonym
F registersnaprange
F registerstructureprocessor
F registersynchronize
F registersynonym
F registertransliteration
F registerunit
F registerunitshortcut

F registerunknownbodysize
F registerusedsynonym
F registeruserdata
F registerverbosemathlabel
F removelastline
F renderingvar
F reorderfloats
F replacefeature
F replacepospxywhd
F replacewildcard
F reportstructure
F resavefloat
F reservedautoregiontag
F resetMPinstance
F resetalternate
F resetbackgroundrowdata
F resetboxesincache
F resetcharacteralign
F resetcolumnset
F resetcomparingtext
F resetcounter
F reseteffect
F resetfeature
F resetfontfeature
F resetfontsolution
F resetforcedbreak
F resetinjector
F resetlogfile
F resetmapfiles
F resetmathattributes
F resetnullfont
F resetparallel
F resetpath
F resetreference
F resetscript
F resetstructureprocessor
F resetsubcounter
F resetsynchronizemarking
F resetsynonyms
F resettimer
F resettrackers
F resolvedemoji
F restartcounter
F restartsubcounter
F restorecounter
F restorecurrentattributes
F restorenote
F restoreobject
F reuserandomseed
F reversevboxcontent
F revivefeature
F rightmathkern
F romannumerals
F rotateparshape
F rounded
F roundedfill
F roundedoutline
F ruby
F ruleoptioncodestring
F runcontextjob
F safechar
F samplefile
F saveboxresource
F savebuffer
F savecounter
F savecurrentattributes
F savecurrentvalue
F savedlistnumber
F savedlistprefixednumber
F savedlisttitle
F savefloat
F saveimageresource
F savemargindata
F savenote
F savepagedata
F savepageinjections
F saveparallel
F savepos
F savespecificfloat
F savestructureblock
F scangivendimensions
F scriptsmodecodestring
F second
F selectstructureblock
F set_extensible_data
F setadaptive
F setalternate
F setautoprefix

F setbackgroundrowdata
F setboxglyph
F setboxline
F setbreakpoints
F setcharacteralign
F setcharacteraligndetail
F setcharactercasing
F setcharactercleaning
F setcharacterkerning
F setcharacterspacing
F setcharacterstripping
F setclosedocumentaction
F setclosepageaction
F setcolormodel
F setcolumnsetarea
F setcolumnsetlines
F setcolumnsetmvl
F setcolumnsetpresent
F setcolumnsetproperties
F setcolumnsetstart
F setcomparetext
F setcomparingtext
F setcounter
F setdataset
F setdestinationattribute
F setdigitsmanipulation
F setdirection
F setdocumentargument
F setdocumentcommandline
F setdocumentctxfile
F setdocumentdefaultargument
F setdocumentenvironments
F setdocumentfilename
F setdocumentfilenames
F setdocumentmodes
F setdocumentmodules
F seteffect
F setelementbackendtag
F setelementnature
F setextrafontkerns
F setfieldcalculationset
F setfigureconversion
F setfigurelookuporder
F setfigurepaths
F setfirstline
F setfontfeature
F setfontofid
F setfontsolution
F setformat
F setformsmethod
F sethsizecolumnset
F sethsizecolumnspan
F sethyphenatedurlcharacters
F sethyphenationfeatures
F sethyphenationmethod
F setidentityvariable
F setinitial
F setinitialsectionblock
F setinjector
F setinsertionlocation
F setinsertmigration
F setinterfaceconstant
F setinterfaceelement
F setinterfacemessage
F setinterfacemessages
F setinterfacevariable
F setinternalreference
F setitaliccorrection
F setjavascriptpreamble
F setjobcomment
F setlanguageexceptions
F setlanguageoptions
F setlanguagepatterns
F setlanguagesynonym
F setlinefiller
F setlineprofile
F setlocalalignanchor
F setlocalmarkanchor
F setlocalsyncanchor
F setluatable
F setmathalphabet
F setmathattribute
F setmathfontalternate
F setmathfontstyle
F setmathsnapping
F setmathvariant
F setmetaglyph
F setmpextensions

F setnaturalwd
F setnegative
F setnextinternalreferences
F setnextreferenceorder
F setnotestate
F setopendocumentaction
F setopenpageaction
F setowncounter
F setownsubcounter
F setpagecolormodel
F setpagestate
F setpagestaterealpageno
F setpagetransition
F setparagraphmetashape
F setparagraphshape
F setparbuilder
F setparwrapper
F setpdfcompression
F setperiodkerning
F setpostlistbox
F setprelistbox
F setprofile
F setrandomseed
F setrealign
F setrealspaces
F setreferencelinkmethod
F setregionbox
F setregionboxtagged
F setregistermethod
F setreplacements
F setruby
F setrule
F setscript
F setsectionblock
F setsectionentry
F setshadow
F setshift
F setsofthyphens
F setsplitlisthtdp
F setstacking
F setstructureblockstate
F setstructurelevel
F setstructurenumber
F setsubcounter
F settagcodepoint
F settagcombination
F settagcombinationpair
F settagconstruct
F settagdelimitedsymbol
F settagdescriptionindex
F settagfigure
F settagfloat
F settagformulacontent
F settaggedmetadata
F settaggingcomment
F settaggingoption
F settaggingpresets
F settaghighlight
F settagitem
F settagitemgroup
F settaglist
F settagmarginanchor
F settagmargintext
F settagmpgraphic
F settagnotation
F settagnotationsymbol
F settagparagraph
F settagproperty
F settagpublication
F settagregister
F settagsetreferencedescription
F settagsorting
F settagsubsentencesymbol
F settagsynonym
F settagtablecell
F settagtabulatecell
F settransliteration
F setupbookmarks
F setupcanvas
F setupcharacterspacing
F setupcomparingtext
F setupexport
F setupfontexpansion
F setupfontprotrusion
F setupinsertion
F setuplinenumbering
F setupsynctex
F setupusermetadata

F setupviewerlayer
F setvisual
F setvisualfont
F setvisuallayer
F setvisuals
F setvsizecolumnset
F setxmpfile
F shiftmatrixornaments
F shiftparshape
F shipoutpage
F showarray
F showassignerror
F showattributes
F showbits
F showboxinbuffer
F showbtxdatasetauthors
F showbtxdatasetcompleteness
F showbtxdatasetfields
F showbtxentry
F showbtxfields
F showbtxhashedauthors
F showbtxtables
F showbtxvariants
F showchardata
F showcounter
F showdirectives
F showdiscretionaries
F showexperiments
F showfontparameters
F showhyphenatedinlist
F showhyphenationtrace
F showinjector
F showjustification
F showlogcategories
F showluatables
F showluatokens
F showmacrostack
F showmessage
F showpagelist
F showparagraphshape
F showprofiledmacros
F showstructure
F showtrackers
F silliness
F simplealign
F simplecases
F simplematrix
F sin
F sind
F sl
F spaceddigits
F spacefactorcodestring
F spaceskipcodestring
F special
F specificationoptioncodestring
F specifiedfont
F specifiedfontsize
F specifiedfontspec
F splitfilename
F splitsamplefile
F spotcolorname
F spotcolorparent
F spotcolorvalue
F squid_check
F startactualtext
F startalternativetext
F startchemical
F startclipping
F startcollectingmath
F startcolorset
F startcomponent
F startenvironment
F startfontsolution
F startgraphicgroup
F startlocalcomponent
F startmarkpages
F startmatrix
F startmirroring
F startpageblock
F startparbuilder
F startprerollpageblock
F startproduct
F startproject
F startregime
F startrotation
F startruby
F startscaling
F startsectionlevel

F startstream
F starttext
F startviewerlayer
F step
F stopactualtext
F stopalternativetext
F stopchemical
F stopclipping
F stopcollectingmath
F stopcolorset
F stopcomponent
F stopenvironment
F stopfontsolution
F stopgraphicgroup
F stoplocalcomponent
F stopmarkpages
F stopmatrix
F stopmirroring
F stoppageblock
F stopparbuilder
F stopprerollpageblock
F stopproduct
F stopproject
F stopregime
F stoprotation
F stopscaling
F stopsectionlevel
F stopstream
F stoptext
F stopviewerlayer
F storejavascriptcode
F storejavascriptpreamble
F storenote
F storeregister
F strc_tags_document_pop
F strc_tags_document_push
F strc_tags_get_element_tag
F strc_tags_parcounter_pop
F strc_tags_parcounter_push
F strc_tags_set_aspect
F strc_tags_set_element_user_properties
F strc_tags_start
F strc_tags_start_chained
F strc_tags_start_detail
F strc_tags_start_ignore
F strc_tags_start_userdata
F strc_tags_stop
F stringtoorientation
F stripinserts
F structureautocatcodedget
F structureblockuservariable
F structurecatcodedget
F structuregivencatcodedget
F structurenumber
F structuretitle
F structureuservariable
F structurevariable
F subcountervalue
F subsubcountervalues
F subtocolumnsetmvl
F subtocolumnsetmvlbalance
F subtractfeature
F svghashed
F sync
F synccolor
F synccolorclone
F synccolorcount
F synchronizelocalanchors
F synchronizemarking
F synchronizesteps
F synchronizestream
F synctexblockfilename
F synctexdisable
F synctexpause
F synctexpopline
F synctexpushline
F synctexresetfilename
F synctexresume
F synctexsetfilename
F synonymfirstuserpage
F synonymmeaning
F synonymname
F synonympages
F synonymuserpages
F systemlog
F tabl_ntb_get_sec
F tabl_ntb_set_sec
F tagmfunctionlab

F tagmfunctionlabattribute
F tan
F tand
F textdir
F textime
F tf
F thebox
F thefirstcharacter
F themaxboxwidth
F theremainingcharacters
F tightfitcompensation
F timestring
F tobigpoints
F tobit
F tobits
F tochar
F tohexa
F toorientation
F totalofstring
F tounicharnum
F towholebigpoints
F transliterate
F transliteratebuffer
F transliterated
F transliteratedbuffer
F transliterationexception
F traverseblock
F traversemath
F triggerpagebuilder
F truefilename
F truefontname
F type
F typebuffer
F typefile
F uchar
F uchexnumber
F uchexnumbers
F undefinechemical
F unicodechar
F unihex
F unit
F unloadlanguage
F unstripinserts
F unsupportedcs
F useMPlibrary
F useanyfile
F useanyfileonce
F useboxresource
F usecolors
F usecomponent
F useenvironment
F usefigurebase
F usefile
F useimageresource
F usejavascriptpreamble
F usejavascriptscripts
F uselibrary
F uselist
F useluamodule
F useluatable
F usemathpluginlibrary
F usemodules
F usepath
F useproduct
F useproject
F usereferences
F useregister
F usesubpath
F usesymbols
F usetransliteration
F useurl
F usezipfile
F utfchar
F utflower
F utfmathclass
F utfmathcommand
F utfmathcommandfiller
F utfmathfiller
F utfmathstretch
F utfshape
F utfstrip
F utfupper
F uuid
F vboxlisttohbox
F verbose
F vpackbox
F vpackedbox
F way

F weekday
F weekdayname
F widthofstring
F widthuptohere
F write
F writeline
F writestatus
F writestring
F x_table_c
F x_table_cleanup
F x_table_construct
F x_table_create
F x_table_finish_row
F x_table_flush
F x_table_init_construct
F x_table_init_reflow_height
F x_table_init_reflow_height_option
F x_table_init_reflow_width
F x_table_init_reflow_width_option
F x_table_next_row
F x_table_next_row_option
F x_table_r
F x_table_reflow_height
F x_table_reflow_width
F x_table_set_construct
F x_table_set_reflow_height
F x_table_set_reflow_width
F xmladdindex
F xmlaftersetup
F xmlall
F xmlappendsetup
F xmlapplyselectors
F xmlatt
F xmlattdef
F xmlattribute
F xmlattributedef
F xmlbadinclusions
F xmlbeforesetup
F xmlchainatt
F xmlchainattdef
F xmlchecknamespace
F xmlcommand
F xmlconcat
F xmlconcatrange
F xmlcontext
F xmlcount
F xmlcssmappedstylevalue
F xmlcssstylevalue
F xmldelete
F xmldepth
F xmldirect
F xmldirectives
F xmldirectivesafter
F xmldirectivesbefore
F xmldisplayverbatim
F xmldoif
F xmldoifatt
F xmldoifelse
F xmldoifelseatt
F xmldoifelseempty
F xmldoifelseselfempty
F xmldoifelsetext
F xmldoifempty
F xmldoifnot
F xmldoifnotatt
F xmldoifnotempty
F xmldoifnotselfempty
F xmldoifnottext
F xmldoifselfempty
F xmldoiftext
F xmlelement
F xmlfileline
F xmlfilename
F xmlfilter
F xmlfilterlist
F xmlfirst
F xmlflush
F xmlflushcontext
F xmlflushlinewise
F xmlflushpure
F xmlflushsetups
F xmlflushspacewise
F xmlflushtext
F xmlformulatobuffer
F xmlfunction
F xmlgetindex
F xmlinclude
F xmlincludeoptions

F xmlinclusion
F xmlinclusionbase
F xmlinclusions
F xmlindex
F xmlinlineverbatim
F xmlinstalldirective
F xmllast
F xmllastatt
F xmllastmatch
F xmllastpar
F xmlloadbuffer
F xmlloaddata
F xmlloaddirectives
F xmlloadentities
F xmlloadfile
F xmlmain
F xmlmatch
F xmlname
F xmlnamespace
F xmlnonspace
F xmlpar
F xmlparam
F xmlpath
F xmlpopmatch
F xmlpos
F xmlprependsetup
F xmlpure
F xmlpushmatch
F xmlraw
F xmlrawtex
F xmlrefatt
F xmlregisterns
F xmlremapname
F xmlremapnamespace
F xmlremovesetup
F xmlresetinjectors
F xmlresetsetups
F xmlsave
F xmlsetatt
F xmlsetattribute
F xmlsetcommandtonone
F xmlsetcommandtotext
F xmlsetentity
F xmlsetinjectors
F xmlsetpar
F xmlsetparam
F xmlsetsetup
F xmlsnippet
F xmlstartraw
F xmlstarttiming
F xmlstopraw
F xmlstoptiming
F xmlstrip
F xmlstripanywhere
F xmlstripeverything
F xmlstripnolines
F xmlstripped
F xmlstrippednolines
F xmltag
F xmltexatt
F xmltexentity
F xmltext
F xmltobuffer
F xmltobuffertextonly
F xmltobufferverbose
F xmltofile
F xmltoparameters
F xmlverbatim
F xmlwithindex
F year

containers table

F cleanname
F content
F define
F is_usable
F is_valid
F read
B usecache
F write

context function

F bc
F bgroup
F char
F concat
D conditionals
F cssdimension
F ctxescape
F ctxescaped

F direct
F egroup
F escape
F escaped
F firstofoneargument
F firstoftwoarguments
F fprint
F getlogger
F glyph
F gobbleoneargument
F latelua
F loadfile
F loadviafile
D modes
F newindexer
F newtexthandler
F newverbosehandler
F nr
F par
F popcatcodes
F poplogger
F printlines
F printtable
F protect
F pushcatcodes
F pushlogger
F rule
F runfile
F runstring
F safechar
F secondoftwoarguments
F setconditional
F setfontid
F setmode
F setsystemmode
F settracing
F settrialtypesettingmethod
F space
F sprint
F startcollecting
F step
F stepwise
F stopcollecting
D systemmodes
F tobuffer
D tokenizedcs
F tolines
F trialtypesetting
F unprotect
F utfchar
F viafile

converters table

F A
F A:es
F A:ru
F A:sl
F AK
F Alphabetic
F Alphabetic:es
F Alphabetic:ru
F Alphabetic:sl
F Character
F Characters
F I
F KA
F KR
F R
F RK
F Romannumerals
F Russiannumerals
F Sloveniannumerals
F Spanishnumerals
F Word
F Words
F a
F a:es
F a:ru
F a:sl
F abjadnodotnumerals
F abjadnumerals
F alphabetic
F alphabetic:es
F alphabetic:ru
F alphabetic:sl
F character
F characters
F chineseallnumerals
F chinesecapnumerals

F chinesedatenumerals
F chinesenumerals
F chr
F chrs
F cn
F cn-a
F cn-c
F cn-d
F convert
F decimals
F define
F gregorian_to_hebrew
F gregorian_to_jalali
F hebrewnumerals
F hexstringtonumber
F i
F isleapyear
F jalali_to_gregorian
F lchexnumber
F lchexnumbers
F leapyear
F lower
F max
F maxchrs
F nicenumber
F nofdays
F number
F numbers
F octnumber
F octstringtonumber
F ordinal
F r
F romannumerals
F russiannumerals
D sequences
F settime
F sloveniannumerals
F spaceddigits
F spanishnumerals
F textime
F toabjad
F tochinese
F tohebrew
F toroman
F totime
F uchexnumber
F uchexnumbers
F upper
F weekday
F word
F words

coroutine table

F close
F create
F isyieldable
F resume
F running
F status
F wrap
F yield

ctxrunner table

F load
F preparedfile
D prepfiles
F resolve

debug table

F getinfo
F sethook
F traceback

dimen function

dir table

F collectpattern
F current
F expandlink
F expandname
F found
F glob
F globdirs
F globfiles
F globpattern
F ls
F makedirs
F mkdirs
F pop
F push

directives table

D data
F default

F disable
F enable
F list
S name
F register
F report
F reset
F set
F show
F value
F values

document table

D arguments
F getargument
F getfilename
F pdf_cleanup_cidsets
F pdf_cleanup_procsets
F pdf_identify_content
F pdf_serialize_content
F pdf_strip_content
F pdf_strip_page
F setargument
F setcommandline
F setdefaultargument
F setenvironments
F setfilename
F setfilenames
F setmodes
F setmodules
D variables

documentdata table

F variable

dofile function

drivers table

F applyanchor
F applyorientation
F convert
F enable
F finalize
F gethpos
F gethvrpos
F getpos
F getrpos
F getvpos
F initialize
F install
N lmtxversion
F outputfilename
F report

effects table

F brownianmotion
F browniannoise
F getoctaveloops
F getoctavemethods
F getoctavestatus
F getoctavevariants
F newoctave
F octave
F octavebytemap
F perlinmotion
F perlinnoise
F simplexangle
F simplexdetail
F simplexnoise
F stepoctave
F worleybounds
F worleymotion
F worleynoise

environment table

F argument
D arguments
D basicengines
N currentrun
F definefilefallback
F definefilesynonym
D engineflags
S filename
D filesynonyms
N forcedruns
F getargument
F globfiles
S homedir
B initex
B initexmode
F initializearguments
F initializefilenames
S inputfilebarename
S inputfilename

S inputfilesuffix
S jobfilefullname
S jobfilename
S jobfilesuffix
N kindofrun
N lmtxmode
F loadexamodes
F loadluafile
F luafile
F luafilechunk
S luatexengine
N luatexfunctionality
S luatexverbose
N luatexversion
N maxnofruns
S oldhome
D originalarguments
S outputfilename
S ownbin
S ownmain
S ownname
S ownpath
B prerollrun
D rawarguments
F reconstructcommandline
F relativepath
F setargument
F splitarguments
S suffix
F texfile
S texmfos
S texos
S texroot
F truefilename
F useluamodule
F usemodules
D validengines
S version

error function

experiments table

D data
F default
F disable
F enable
F list
S name
F register
F report
F reset
F set
F show
F value
F values

figures table

F applyratio
F badname
D bases
F bitmapimage
N boxnumber
F bytepalette
D cachepaths
F check
D checkers
D conversions
D converters
F current
N defaultdepth
N defaultheight
B defaultsearch
N defaultwidth
F done
F dummy
D existers
F exists
D formats
D found
F get
F getinfo
F getpdfinfo
F getrealpage
F guess
F guessfromstring
F hash
D identifiers
F identify
F include
D includers
F initialize

D loaded
D localpaths
D magics
F mergegoodies
N nofmissing
N nofprocessed
D order
D paths
D patterns
F pop
B preferquality
D programs
F push
F qrcode
F registerpattern
F registerresource
F registersuffix
D remappers
D resources
F scale
F set
F setconversion
F setlookups
F setorder
F setpaths
D suffixes
D used

file table

F addsuffix
F basename
F checksum
F collapsepath
F copy
F dirname
F expandname
F extname
F is_qualified_path
F is_readable
F is_rootbased_path
F is_writable
F isreadable
F iswritable
F join
F joinpath
F loadchecksum
F nameonly
F nametotable
F needs_updating
F needsupdating
F pathpart
F readdata
F removesuffix
F replacesuffix
F reslash
F robustname
F savechecksum
F savedata
F size
F splitbase
F splitname
F splitpath
F suffix
F suffixes
F suffixesonly
F suffixonly
F syncmtimes
F withinbase

fio table

F getposition
F read2dot14
F readbytes
F readbytetable
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable
F readcline
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat

F readfloatle
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F setposition
F skipposition
F writecardinal1
F writecardinal1le
F writecardinal2
F writecardinal2le
F writecardinal3
F writecardinal3le
F writecardinal4
F writecardinal4le
F writedouble
F writedoublele
F writefloat
F writefloatle

floats table

F analysemethod
F checkedpagefloat
F collect
F consult
F flush
F getvariable
F hasstacked
F nofstacked
F pop
F push
F resave
F save
F stacked

font table

F addcharacters
F addquality
F current
F define
F getfont
F getfontdimen
F getfontfields
F getfontspec
F getmathcharacterfields
F getmathindex
F getmathspec
F getparameterfields
F gettextcharacterfields
F id
F max
F nextid
F setfont
F setfontdimen
F xscaled
F yscaled

fonts table

F current
F currentid
F definetypeface
F enhanceid
D expansions
D formats
F getalternate
F getindices
F getkern
F getmultiple
F getsubstitution
F infofont
F mode
D names
D nulldata
D protrusions
F registersanitizer
F reserveid
F toeffect

functions table

F dummy

getmetatable function

globaldata table

N CONTEXTLMTXMODE
B JITSUPPORTED
N LUAFORMAT
N LUAMAJORVERSION
N LUAMINORVERSION

S LUATEXENGINE
N LUATEXFORMATID
N LUATEXFUNCTIONALITY
S LUATEXVERBOSE
N LUATEXVERSION
N LUAVERSION
F SAVEDREQUIRE
F assert
F characterkern
F collectgarbage
F dimen
F dofile
F error
F getmetatable
F inspect
F ipairs
F load
D loaders
F loadfile
F loadstring
F next
F optionalrequire
F pairs
F pcall
F pdfembeddedlink
F print
F rawequal
F rawget
F rawlen
F rawset
F require
F select
F setinspector
F setmathparameters
F setmetatable
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
D texconditionals
D texconstants
D texifs
D texisdefined
D texmodes
D texsystemmodes
F toboolean
F todecimal
F tonumber
F tostring
F tostring_u1
F tostring_u2
F type
F unpack
F warn
F xpcall

globals table

N CONTEXTLMTXMODE
B JITSUPPORTED
N LUAFORMAT
N LUAMAJORVERSION
N LUAMINORVERSION
S LUATEXENGINE
N LUATEXFORMATID
N LUATEXFUNCTIONALITY
S LUATEXVERBOSE
N LUATEXVERSION
N LUAVERSION
F SAVEDREQUIRE
F assert
F characterkern
F collectgarbage
F dimen
F dofile
F error
F getmetatable
F inspect
F ipairs
F load
D loaders
F loadfile
F loadstring
F next
F optionalrequire
F pairs
F pcall
F pdfembeddedlink
F print
F rawequal

F rawget
F rawlen
F rawset
F require
F select
F setinspector
F setmathparameters
F setmetatable
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
D texconditionals
D texconstants
D texifs
D texisdefined
D texmodes
D texsystemmodes
F toboolean
F todecimal
F tonumber
F tostring
F tostring_u1
F tostring_u2
F type
F unpack
F warn
F xpcall

graphics table

F bpsize
F identify
F registerpdfcompactor
F registerpdffont

gzip table

F compress
F compressed
F decompress
F load
F save
F suffix

helper table

F getprofile
F mathnested
F mathprocess
F mathstep
F snapindeed
F snaplist
F traversecharmethod
F traverseglyphmethod
F traversehorizontal
F traversevertical

images table

F check
F checksize
F copy
F create
F embed
F embedfromstore
F fetchdata
F print
F resetdata
F resetstore
F scan
F serialize
F storedata
F totable
F wrap

inspect function

interactions table

D attachments
D linkedlists
D renderings

interfaces table

D cachedsetups
F cachesetup
F checkedspecification
D complete
D constants
D corenamespaces
S currentinterface
S currentresponse
F definecommand
F defined
F doifelsemessage
D elements
D formats
F getmessage
F getnamespace

F getsetupstring
D hashedsetups
F implement
F interfacedcommand
F knownscanner
F message
F nameofscanner
F registernamespace
F registerscanner
D scanners
F setconstant
F setcount
F setdimen
F setelement
F setformat
F setmacro
F setmessage
F setmessages
F settranslation
D setupstrings
F setvariable
F showmessage
D storedscanners
F tolist
D translations
D usednamespaces
D variables
F writestatus

io table

F ask
F bytes
F characters
F close
F copydata
F exists
S fileseparator
F flush
F gobble
F input
F lines
F loadchunk
F loaddata
F loadlines
F newreader
F noflines
F open
F output
S pathseparator
F popen
F read
F readall
F readnumber
F readstring
F savedata
F size
U stderr
U stdin
U stdout
F tmpfile
F type
F write

ipairs function

job table

F comment
F disablesave
F getrandomseed
F initialize
F load
F loadother
B pack
N packversion
F register
F save
N version

kdtree table

F delete
F found
F insert
F nearest
F nearestindex
F new
F newweighted
F reset
F totable
F traverse

kpse table

language table

F clean

F clearhyphenation
F clearpatterns
F current
F gethjcode
F haslanguage
F hyphenate
F hyphenation
F hyphenationmin
F id
F new
F patterns
F postexhyphenchar
F posthyphenchar
F preexhyphenchar
F prehyphenchar
F sethjcode
F setwordhandler

languages table

F addgoodiesdata
F addgoodiesfile
F associate
D associated
F association
D counters
F current
D data
D decimals
F define
F explicithyphen
F exportlanguage
F flatten
F getdata
F getmetadata
F getnumber
F goodiefiles
F hyphenate
F installed
F installhandler
F loadable
F loadwords
F nofflattened
D numbers
F pdflanguage
F postexhyphenchar
F posthyphenchar
F preexhyphenchar
F prehyphenchar
D registered
F serializediscretionary
F setexceptions
F setgoodieshandler
F setoptions
F setpatterns
F setsynonym
F setwordhandler
F showdiscretionaries
F strippedgoodiewords
F tolang
F unload
N version
F visualizediscretionaries

layouts table

F getcanvas
F getpagedimensions
F setupcanvas

lfs table

F attributes
F canonicalize
F chdir
F currentdir
F dir
F expandpath
F isdir
F isfile
F isfound
F isreadabledir
F isreadablefile
F iswriteabledir
F iswriteablefile
F lessweird
F link
F mkdir
F mkdirs
F modification
F moreweird
F readlink
F rmdir
F setexecutable

F setloadshebang
F symlink
F symlinktarget
F touch
F walkdir

libraries table
D basiclua
D basictex
D builtin
D extralua
D extratex
D functions
D globals
D obsolete
D optional

lmx table
F color
F convert
F convertfile
F convertstring
F einject
F eprint
F escape
F finalized
F finject
F fprint
F get
F getvariables
F htmfile
F include
F initialize
F inject
F lmxfile
F loadedfile
F make
F new
F popupfile
F print
F pv
F report
F reset
F result
F set
F show
F stripcss
F tv
F type
F urlescape
F variable

load function
loaders data table
loadfile function
loadstring function
logs table
F application
F categories
F direct
F disable
F enable
F finalactions
F flush
F format
F formatted
F loggingerrors
F messenger
F new
F newline
F poplogfile
F poptarget
F pushlogfile
F pushtarget
F registerfinalactions
F report
F reporter
F resetlogfile
F setformatters
F setlogfile
F setmessenger
F setprocessor
F settarget
F settimedlog
F settranslations
F show
F start_page_number
F start_run
F starterrorlogging
F startfilelogging
F status

F stop_page_number
F stoperrorlogging
F stopfilelogging
F subdirect
F subreport
F system
F texerrormessage
F writer

lpdf table

F action
F adddocumentcolorspace
F adddocumentextgstate
F adddocumentpattern
F adddocumentshade
F addtocatalog
F addtoinfo
F addtonames
F addtopageattributes
F addtopageresources
F addtopagesattributes
F addxmpinfo
F annotationspecification
F array
F attachmentsymbols
F boolean
F border
F checkedkey
F checkedresources
F checkedvalue
F circularshade
F close
F cmykcode
F collectedresources
F color
F colorspace
D colorspaceconstants
F colorspec
F colorvalue
F colorvalues
F commentsymbols
F compressdata
F compresslevel
F constant
F copyarray
F copyboolean
F copyconstant
F copydictionary
F copyfloat
F copyinteger
F copynumber
F copystring
F copyunicode
F deferredobject
F delayedobject
F destinationspecification
F dictionary
F docstring
F escaped
F finalizedocument
F finalizepage
F finalizesignature
F finishtransparencycode
F flushfonts
F flushgroup
F flushobject
F flushstreamfileobject
F flushstreamobject
D formats
F frombytes
F fromeight
F frompdfdoc
F fromsixteen
F getcatalog
F getcompression
F getfontname
F getfontobjectnumber
F getformatoption
F getinfo
F getmatrix
F getnofpages
F getpageproperties
F getpagereference
F getpagetags
F getpos
F gettaggingstatus
F gettrailerid
F getversion
F getxformname

F graycode
F hasmatrix
F immediateobject
F includeimage
F initialize
F injectxmpinfo
F insertxmpinfo
F lastreferredpage
F layerreference
F limited
F linearshade
F literal
F majorversion
F makenametree
F minorversion
F noffontregistries
F nofpages
F null
F number
F object
F objectcompresslevel
F pagereference
F patternstream
F pdfcolor
F pdftimestamp
F preparesignature
F print
F procset
B protectresources
F quads
F rectangle
F reference
F registerannotation
F registerdestination
F registerdocumentfinalizer
F registerfontmethod
F registerinitializer
F registerpagefinalizer
F registerpattern
F registersignature
F replacexmpinfo
F reserveobject
F rgbcode
F rotationcm
F setcompression
F setencryption
F setpageorder
F setpagestate
F setpagetag
F setutfstringmode
F setversion
F sharedobject
F shareobject
F shareobjectreference
F splitsixteen
F spotcode
F stream
F string
F supportedformats
F tocidset
F toeight
F topdfdoc
F topermissions
F tosixteen
F transparency
F transparencycode
F transparencyvalue
F unicode
D usedfontstreams
F verbose

lpeg table

F B
F C
F Carg
F Cb
F Cc
F Cf
F Cg
F Cmt
F Cp
F Cs
F Ct
F P
F R
F S
F UP
F UR
F US

F V
F afterprefix
F anywhere
F append
F balancer
F beforesuffix
F checkedsplit
F containsws
F counter
F endstripper
F finder
F firstofsplit
F frontstripper
F instringchecker
F is_lpeg
F keeper
F locale
F match
F oneof
D patterns
F pcode
F print
F ptree
F replacer
F secondofsplit
F setmaxstack
F setutfcasers
F split
F splitat
F splitter
F stripper
F times
F tsplitat
F tsplitter
F type
F utfR
F utfchartabletopattern
F utfreplacer
S version

lua table

F addnibble
D bytedata
F callbytecode
F comparekeys
F finalizeinitex
N firstbytecode
F get_functions_table
F getallkeys
F getbytecode
F getcheckedkeys
F getcurrenttime
F getdebuginfo
F getexitcode
F getfunctionstable
F getnibble
F getnumerickeys
F getpreciseseconds
F getpreciseticks
F getruntime
F getstacktop
F getstartupfile
F getstringkeys
F getversion
N lastbytecode
F luastringcall
D messages
F mpsstringcall
F newindex
F newtable
D numbers
F protectglobal
F registercode
F registeredcodes
F registerglobal
F registerinitexfinalizer
F registername
F setbytecode
F setexitcode
F setnibble
S startupfile
F subnibble
F usestringcall
S version

luac table

F inspect
F print

luatex table

F abort

F cleanup
F cleanuptempfiles
F currentfile
F currentlevel
F currenttotal
F poprunstate
F pushrunstate
F registerdumpactions
F registerpageactions
F registerstartactions
F registerstopactions
F registertempfile
N starttime
F wrapup

lxml table

F addindex
F all
F applyfunction
F applyselectors
F att
F attribute
F badinclusions
F chainattribute
F checkindex
F collected
F command
F concat
F concatrange
F content
F context
F convert
F count
F delete
F depth
F direct
F displayverbatim
F doif
F doifelse
F doifelseempty
F doifelsetext
F doifempty
F doifnot
F doifnotempty
F doifnottext
F doiftext
F element
F elements
D entities
F fileline
F filename
F filter
F filterlist
F first
F flush
F flushlinewise
F flushsetups
F flushspacewise
F get_id
F getid
F getindex
F id
U idsplitter
F ifatt
F ifattempty
F include
F inclusion
F inclusions
F index
F inlineverbatim
F installsetup
F last
F lastatt
F lastmatch
F lastpar
F load
F loadbuffer
F loaddata
F main
F match
F name
F namespace
F nonspace
F par
F param
F parameter
F path
F popmatch
F pos

F position
F pure
F pushmatch
F raw
F rawroot
F rawtex
F refatt
F register
F registerentity
F removesetup
F replace
F resetcdata
F resetsetups
F resolvedentity
F root
F save
F serialize
F setaction
F setatt
F setattribute
F setcdata
F setcommandtonone
F setcommandtotext
F setpar
F setparam
F setparameter
F setsetup
F snippet
F splitid
F startraw
F startunescaped
F stopraw
F stopunescaped
F store
F strip
F stripped
F tag
F texatt
F text
F tobuffer
F tofile
F toparameters
F toverbatim
F verbatim
F withindex
D xmltexhandler

math table

F abs
F acos
F asin
F atan
F atan2
F ceil
F ceiling
F cos
F cosd
F cosh
F deg
F div
F even
F exp
F floor
F fmod
F frexp
N huge
N initialseed
F ldexp
F log
F log10
F max
N maxinteger
F min
N mininteger
F mod
F modf
F odd
N pi
F pow
F rad
F random
F randomseed
F round
F setrandomseedi
F sin
F sind
F sinh
F sqrt
F tan

F tand
F tanh
F tointeger
F type
F ult

mathematics table

F addfallbacks
F addvariant
D alphabets
D alternatives
F beforepassingfonttotex
F big
D boldmap
D charactersets
F checkaftercopyingfont
D classes
D classnames
D codes
F define
F dimensions
F disablecollecting
F enablecollecting
F extensiblecode
D extensibles
N extrabase
F fallbackstyleattr
F familyname
F functiontype
D gaps
F getblobindex
F getboth
F getdomainname
F getextensibledata
F getmathblob
F getoptionallabel
F getstyle
F gettextblob
F getverboselabel
F horizontalcode
F initializeparameters
F makefont
D mapremap
F markblobindexdone
F overloadparameters
F preset
N privatebase
F registerextensible
F registersimplematrix
F registerverboselabel
F remapalphabets
F renderextensible
F renderset
F resetattributes
F scaleparameters
F setextensibledata
F setmathsymbol
D sets
F setsnapping
F setvariant
F strutcode
D styles
F syncboth
F syncname
F syncstyle
F toengineclass
F toname
F tostyle
F tweakaftercopyingfont
F tweakbeforecopyingfont
F utfmathaccent
F utfmathclass
F utfmathcommand
F utfmathfiller
F utfmathstretch
F variantcode
F variantcount
F virtualize
D virtualized

md5 table

F HEX
F dec
F hex
F sum
F sumHEXA
F sumhexa

metapost table

F checkformat
F checktracingonline

F cm
F colorinitializer
F convert
F currentmpx
F currentmpxstatus
S defaultformat
S defaultinstance
S defaultmethod
F directrun
F escaped
D extensiondata
F filter
F filterclippath
F flush
F flushnormalpath
F format_number
F format_string
F formatnumber
F getbackendoption
F getbendtolerance
F getbuffer
F getclippath
F getextensions
F getextradata
F gethashentries
F getinstancebyname
F getinstanceinfo
F getinstancenames
F getjobdata
F getmovetolerance
F getparameter
F getparameterpreset
F getparameterset
F getrecord
F getstatistics
F gettext
F gettolerance
F graphic
F graphic_base_pass
F hascurvature
F includesvgbuffer
F includesvgfile
F installplugin
F isobject
S lastlog
F load
F maketext
F mesh
F mesher
F meshupper
N n
F newlogger
N nofruns
F nofscriptruns
F nvformat
F pdfliterals
F pluginactions
F points
F pointset
F popformat
F popscriptrunner
F popvariable
F popvariables
F preparetextextsdata
F process
F processing
F processplugins
F pushformat
F pushscriptrunner
F pushvariable
F pushvariables
B quitonerror
B reducetogray
F registerdirect
F registerfilter
F registermesher
F registermeshupper
F registerpointset
F registerscript
F registertokens
F remappedtext
F remaptext
F reporterror
F reportsvgfonts
F reset
F resetbackendoptions
F resetlastlog
F resetplugins

F run
F runinternal
F runscript
F scanparameters
F scriptindex
F setbendtolerance
F setbuffer
F setextensions
F setlogging
F setmovetolerance
F setoutercolor
F setparameter
F setparameterset
F setrecord
F settext
F settolerance
F setvariable
B showlog
F showsvgpage
F simple
F splitprescript
F startgraphic
F startsvghashing
F stopgraphic
F stopsvghashing
F svformat
B svgcachefile
F svgcolorremapper
F svgglyphtomp
F svgshapestomp
F svgshapestopdf
F svgsplitcolor
F svgtomp
F svgtopdf
F sxsy
B texerrors
F texexp
F theclippath
F tographic
F totable
F typesvgpage
F unload
F untagvariable

moduledata table

modules table

D anch-loc
D anch-pgr
D anch-snc
D back-exp
D back-exp-imp-fnt
D back-exp-imp-mth
D back-exp-imp-ref
D back-exp-imp-tag
D back-imp-lua
D back-imp-mps
D back-imp-pdf
D back-imp-pdp
D blob-ini
D buff-imp-default
D buff-imp-escaped
D buff-imp-lua
D buff-imp-mp
D buff-imp-nested
D buff-imp-parsed-xml
D buff-imp-tex
D buff-imp-xml
D buff-ini
D buff-par
D buff-ver
D char-enc
D chem-ini
D chem-str
D cldf-com
D cldf-ver
D colo-icc
D colo-ini
D cont-run
D core-con
D core-ctx
D core-dat
D core-sys
D driv-shp
D file-mod
D file-syn
D font-afk
D font-agl
D font-aux
D font-cff

D font-chk
D font-cid
D font-col
D font-con
D font-ctx
D font-def
D font-dsp
D font-enc
D font-enh
D font-fbk
D font-fmp
D font-hsh
D font-imp-checks
D font-imp-combining
D font-imp-compound
D font-imp-digits
D font-imp-dimensions
D font-imp-effects
D font-imp-italics
D font-imp-ligatures
D font-imp-math
D font-imp-notused
D font-imp-properties
D font-imp-quality
D font-imp-reorder
D font-imp-scripts
D font-imp-spacekerns
D font-imp-tex
D font-imp-text
D font-imp-tracing
D font-imp-tweaks
D font-imp-unicode
D font-ini
D font-lig
D font-log
D font-lua
D font-map
D font-mpf
D font-mps
D font-nod
D font-ogr
D font-one
D font-onr
D font-osd
D font-ota
D font-otc
D font-otd
D font-oth
D font-oti
D font-otj
D font-otl
D font-oto
D font-otr
D font-ots
D font-ott
D font-oup
D font-pat
D font-prv
D font-san
D font-sel
D font-shp
D font-sol
D font-syn
D font-tfm
D font-tpk
D font-trt
D font-ttf
D font-txt
D font-vfc
D font-vir
D good-ctx
D good-gen
D good-ini
D good-mth
D grph-bmp
D grph-con
D grph-epd
D grph-fil
D grph-img
D grph-inc
D grph-pat
D grph-raw
D grph-rul
D grph-trf
D grph-u3d
D java-ini
D lang-cnt
D lang-def

D lang-dis
D lang-exc
D lang-hup
D lang-hyp
D lang-ini
D lang-lab
D lang-rep
D lang-tra
D lang-txt
D lang-url
D lang-wrd
D libs-imp-curl
D libs-imp-ghostscript
D libs-imp-graphicsmagick
D libs-ini
D lpdf-ano
D lpdf-col
D lpdf-epa
D lpdf-epd
D lpdf-fix
D lpdf-fix-imp-contents
D lpdf-fix-imp-fonts
D lpdf-fld
D lpdf-fmt
D lpdf-grp
D lpdf-img
D lpdf-ini
D lpdf-lmt
D lpdf-mis
D lpdf-ren
D lpdf-rul
D lpdf-sig
D lpdf-tag
D lpdf-u3d
D lpdf-wid
D lpdf-xmp
D lxml-css
D lxml-dir
D lxml-ent
D lxml-ini
D lxml-mms
D lxml-sor
D lxml-tex
D math-act
D math-ali
D math-dim
D math-ext
D math-fbk
D math-fnt
D math-frc
D math-inc
D math-ini
D math-map
D math-mps
D math-noa
D math-pre
D math-rad
D math-ren
D math-spa
D math-tag
D math-txt
D math-vfu
D meta-blb
D meta-fnt
D meta-fun
D meta-imp-txt
D meta-ini
D meta-lua
D meta-nod
D meta-pdf
D meta-tex
D mlib-ctx
D mlib-fio
D mlib-int
D mlib-lmp
D mlib-lmt
D mlib-lua
D mlib-mat
D mlib-mpf
D mlib-msh
D mlib-pdf
D mlib-pos
D mlib-pps
D mlib-ptr
D mlib-pts
D mlib-ran
D mlib-run
D mlib-scn

D mlib-snc
D mlib-svg
D node-ali
D node-bck
D node-fnt
D node-par
D node-ref
D node-rul
D node-tra
D node-typ
D pack-obj
D pack-ori
D pack-rul
D page-blk
D page-cst
D page-flt
D page-ini
D page-inj
D page-ins
D page-lin
D page-mix
D page-otr
D page-pst
D page-sel
D page-str
D phys-dim
D publ-aut
D publ-dat
D publ-fnd
D publ-inc
D publ-ini
D publ-jrn
D publ-oth
D publ-reg
D publ-sor
D publ-tra
D publ-usr
D regi-ini
D scrn-but
D scrn-fld
D scrn-hlp
D scrn-ini
D scrn-pag
D scrn-ref
D scrn-wid
D scrp-cjk
D scrp-eth
D scrp-ini
D scrp-tha
D scrp-tib
D sort-ini
D sort-lan
D spac-ali
D spac-brk
D spac-chr
D spac-hor
D spac-ovl
D spac-par
D spac-pas
D spac-prf
D spac-twi
D spac-ver
D strc-bkm
D strc-blk
D strc-con
D strc-doc
D strc-flt
D strc-ini
D strc-itm
D strc-lev
D strc-lst
D strc-mar
D strc-mat
D strc-not
D strc-num
D strc-pag
D strc-ref
D strc-reg
D strc-rsc
D strc-syn
D strc-tag
D strc-usr
D symb-emj
D symb-ini
D syst-cmp
D tabl-ali
D tabl-ntb
D tabl-tbl

D tabl-xtb
D task-ini
D trac-bld
D trac-jus
D trac-par
D trac-riv
D trac-sig
D trac-vis
D type-ini
D typo-adj
D typo-bld
D typo-brk
D typo-cap
D typo-chr
D typo-cln
D typo-dha
D typo-dif
D typo-dig
D typo-dir
D typo-drp
D typo-duc
D typo-fkr
D typo-fln
D typo-hid
D typo-inj
D typo-itc
D typo-krn
D typo-lan
D typo-lbx
D typo-man
D typo-mar
D typo-ovl
D typo-pag
D typo-par
D typo-pnc
D typo-prc
D typo-rep
D typo-rub
D typo-spa
D typo-stc
D typo-sus
D typo-syn
D typo-tal
D typo-wrp
D unic-ini

mp function

F autoinject
F boolean
F bytemap_load_from_file
F cleaned
F color
F dataset
F direct
F downgradebytemap
F downsamplebytemap
F draw
F expandtex
F fill
F fillbytemap
F flatten
F flush
F format
F formatted
F fprint
F getbytemap
F getbytemapdata
F getbytemapdirect
F getlastaddtype
F graphformat
F integer
F lmt_function_x
F lmt_glyphshape_accent
F lmt_glyphshape_baseline
F lmt_glyphshape_boundingbox
F lmt_glyphshape_depth
F lmt_glyphshape_height
F lmt_glyphshape_italic
F lmt_glyphshape_llx
F lmt_glyphshape_n
F lmt_glyphshape_path
F lmt_glyphshape_start
F lmt_glyphshape_stop
F lmt_glyphshape_usedbox
F lmt_glyphshape_usedline
F lmt_glyphshape_width
F lmt_mesh_set
F lmt_mesh_update
F lmt_poisson_generate

F lmt_start_potrace
F lmt_step_potrace
F lmt_stop_potrace
F lmt_svg_include
F loadbytemap
F loadbytemapfile
F mesh_register
F mf_blob_add
F mf_blob_dimensions
F mf_blob_index
F mf_blob_new
F mf_blob_raw_content
F mf_blob_raw_dimensions
F mf_blob_raw_reset
F mf_blob_raw_toutf
F mf_blob_raw_wipe
F mf_blob_size
F mf_blob_width
F mf_external_figure
F mf_finish_saving_data
F mf_formatted_text
F mf_get_outline_text
F mf_graphic_text
F mf_inject_blob
F mf_map_move
F mf_map_text
F mf_named_color
F mf_outline_text
F mf_save_data
F mf_script_index
F mf_start_saving_data
F mf_stop_saving_data
F mode
F n
F newbytemap
F number
F numeric
F pair
F pairpoints
F path
F pathpoints
F points
F points_register
F processbytemap
F processingmode
F quadruple
F quadruplepoints
F quoted
F report
F setbytemap
F setbytemapoctave
F size
F solve
F string
F systemmode
F transform
F triplet
F tripletpoints
F vprint

mplib table

F downgradebytemap
F downsamplebytemap
F execute
F expandtex
F fillbytemap
F finder
F finish
F getbytemap
F getbytemapdata
F getbytemapdirect
F getcallbackstate
F getcodes
F getcolormodels
F getfields
F gethashentries
F gethashentry
F getinternalactions
F getknotstates
F getlastaddtype
F getlogtargets
F getobjectdata
F getobjectpeninfo
F getobjectstacking
F getobjecttypes
F getprimitivelegacies
F getprimitiveorigins
F getprimitives
F getpruneoptions

F getresultstates
F getscaledbits
F getscantypes
F getstates
F getstatistics
F getstatus
F gettolerance
F gettype
F gettypes
F injectboolean
F injectcmykcolor
F injectcolor
F injectinteger
F injectnumber
F injectnumeric
F injectpair
F injectpath
F injectpoints
F injectstring
F injecttokens
F injecttransform
F injectvector
F injectvectors
F injectwhatever
F new
F newbytemap
F peninfo
F processbytemap
B realtimelogging
F scanboolean
F scancmykcolor
F scancolor
F scanexpression
F scaninteger
F scannext
F scannumber
F scannumeric
F scanpair
F scanpath
F scanpen
F scanproperty
F scanstring
F scansymbol
F scantoken
F scantransform
F setbytemap
F setbytemapoctave
F settolerance
F showcontext
F skiptoken
F solvepath
F version

nanojpeg table
F decode

next function

noads table
F getmathmode
F process
F processnested
F processouter

node table
F checkdiscretionaries
F checkdiscretionary
F copy
F copylist
F count
F currentattributes
F dimensions
F effectiveglue
F endofmath
F family_font
F fields
F findattribute
F flattendiscretionaries
F flushlist
F flushnode
F free
F getattribute
F getcachestate
F getfield
F getfielderror
F getglue
F getnodeerrorvalues
F getpropertiestable
F getproperty
F gluetostring
F hasattribute
F hasfield

F hasglyph
F hpack
F hyphenating
F id
F insertafter
F insertbefore
F instock
F intracking
F inuse
F isnode
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F makeextensible
F mlisttohlist
F new
F protectglyph
F protectglyphs
F protrusionskippable
F rangedimensions
F remove
F serialized
F setattribute
F setfield
F setfielderror
F setglue
F setproperty
F show
F size
F slide
F subtypes
F tail
F todirect
F tonode
F tostring
F traverse
F traverseid
F type
F types
F unprotectglyph
F unprotectglyphs
F unsetattribute
F usedlist
F usesfont
F vpack
F write

nodes table

D accentcodes
F aligned
F append
F apply
F applyvisuals
F astable
F basepoints
D boundarycodes
D choicecodes
F concat
F copy
F copy_node
F copylist
F countall
F currentattributes
F delete
D dircodes
D directioncodes
D directionvalues
D dirvalues
D disccodes
D discretionarycodes
D fencecodes
F fields
D fillcodes
D fillvalues
F firstdirinbox
F flush
F flushlist
F flushnode
D fractioncodes
F fullhpack
F getattr
F getattribute
F getboth
F getbox
F getchar
F getfield
F getfont

F getid
F getleader
F getlist
F getnext
F getprev
F getproperty
F getsubtype
D gluecodes
D glyphcodes
F hasattribute
F hasfield
F hpack
F idsandsubtypes
F idstostring
F insertafter
F insertbefore
F insertlistafter
F installattributehandler
F is_display_math
F isdirect
F isnode
F isnut
D kerncodes
F leftmarginwidth
F link
F linked
F list
D listcodes
F listtoutf
D literalvalues
F locate
D markcodes
D mathcodes
D mathvalues
F maxboxwidth
F new
D noadcodes
D nodecodes
F nopts
F packlist
D parcodes
D penaltycodes
F points
F prepend
F print
F pts
D radicalcodes
F rehpack
F remove
F repackhlist
F replace
F report
F rightmarginwidth
D rulecodes
F serialize
F serializebox
F serialized
F setattr
F setattribute
F setattrlist
F setboth
F setbox
F setboxtonaturalwd
F setchar
F setfield
F setfont
F setleader
F setlink
F setlist
F setnext
F setprev
F setproperty
F showboxes
F showlist
F showsimplelist
D skipcodes
F somepenalty
F somespace
F splitbox
F startofpar
F stripdiscretionaries
D subtypes
F tail
F takeattr
F takebox
F tobasepoints
F tocentimeters
F tociceros

F todidots
F todimen
F toinches
F tomillimeters
F tonode
F tonodes
F tonut
F topicas
F topoints
F toscaledpoints
F tosequence
F tostring
F totable
F totree
F toutf
F traverse
F traverseid
F unsetattribute
F upcomingproperties
F usedlist
F vianodes
F vianuts
F visualizebox
F vpack
D whatsitcodes
F write

number table
F %
F basepoints
F bytetodecimal
F clamp
F compactfloat
F decimaltobyte
D dimenfactors
F fractiontobyte
F idiv
N maxdimen
F nopts
F percent
F points
F pts
F splitdimen
F to16dot16
F tobasepoints
F tobitstring
F tocentimeters
F tociceros
F tocontext
F todidots
F todimen
F toediths
F toinches
F tomillimeters
F tonumberf
F tonumberg
F topicas
F topoints
F toscaled
F toscaledpoints
F totoves
F valid

objects table
F dimensions
F found
N n
F page
F reference
F register
F restore

optional table

optionalrequire function

os table
F __getenv__
F __setenv__
S binsuffix
N bits
F clock
F converttime
F date
F difftime
F enableansi
D env
F execute
F exit
F fulltime
F getcodepage
F getenv
F getnamevalues

F gettimeofday
F gettypevalues
F getunamefields
F isleapyear
F launch
S libsuffix
F localtime
S name
S newline
F nofdays
F now
F pipeto
S platform
F remove
F rename
F resultof
F runtime
S selfbin
S selfcore
S selfdir
S selflink
S selfname
S selfpath
F serialwrite
F setenv
F setexitcode
F setlocale
F sleep
F startuptime
F time
F timezone
F tmpname
F today
S type
F uname
F uuid
F validdate
F weekday
F where
F which

package table

S config
S cpath
F extralibpath
F extralibpaths
F extraluapath
F extraluapaths
F libpaths
F loadlib
F luapaths
S path
F poplibpath
F popluapath
F pushlibpath
F pushluapath
F searchpath

pagebuilders table

pairs function

parametersets table

pcall function

pdf table

F immediateobj

pdfdecode table

pdfe table

F arraytotable
F close
F closestream
F dictionarytotable
F getarray
F getboolean
F getbox
F getcatalog
F getdictionary
F getencodingvalues
F getfieldtypes
F getfromarray
F getfromdictionary
F getfromobject
F getfromreference
F getfromstream
F getinfo
F getinteger
F getmemoryusage
F getname
F getnofobjects
F getnofpages
F getnumber
F getobjectrange

F getpage
F getpages
F getpermissions
F getsize
F getstatus
F getstatusvalues
F getstream
F getstring
F gettrailer
F getversion
F new
F open
F openfile
F openstream
F pagestotable
F readfromstream
F readwholestream
F type
F unencrypt

pdfembeddedlink function

physics table

pngdecode table

F applyfilter
F expand
F frompalette
F interlace
F makemask
F palettemask
F reduce
F setexperiment
F splitmask
F tocmyk
F togray
F tomask
F transparentmask

posit table

F NaN
F NaR
F __add
F __band
F __bor
F __bxor
F __div
F __eq
F __le
F __lt
F __mul
S __name
F __pow
F __shl
F __shr
F __sub
F __tostring
F __unm
F abs
F acos
F asin
F atan
F band
F bor
F bxor
F ceil
F conj
F copy
F cos
F exp
F exp2
F expand
F floor
F frombyte
F fromchar
F fromposit
F integer
F log
F log10
F log1p
F log2
F logb
F max
F min
F modf
F new
F pow
F rotate
F round
F rounded
F shift
F sin

F sqrt
F tan
F tobyte
F tochar
F tonumber
F toposit
F tostring

potrace table
F checked
F concat
F contourplot
F convert
F count
F flush
F free
F fromfile
F getbitmap
F getnewfields
F getpolicyvalues
F getprocessfields
F new
F process
F setbitmap
F stripped
F totable
F trace

print function

process table
F __gc
S __name
F __tostring
F close
F open
F poll
F read
F tostring

publications table
F addtexentry
F analyze
F anywhere
D authorcache
D authorcollapsers
D authormap
F authortoregister
F checkeddataset
D collected
F concatstate
F converttoxml
F endnotes_to_btx
F finder
F firstofrange
F found
F get
F getcasted
F getdetail
F getdirect
F getfaster
F getfield
F getfuzzy
F getindex
D inspectors
F lastofrange
F load
F loadbibdata
F loaddefinitionfile
F loadreplacementfile
F new
F okay
F oneorrange
F parenttag
F permitted
F prerollcmdstring
F refman_to_btx
F resolvedname
F save
F search
F setcategory
F setspecification
F singularorplural
F sortedentries
F splitauthor
F splitoneauthor
F tags
F usedataset
F usedentries

qrcodegen table
F bitmap
F generate

rawequal function
rawget function
rawlen function
rawset function
regimes table
- D backmapping
- F cleanup
- F disable
- F enable
- F fromregime
- F list
- D mapping
- F pop
- F process
- F push
- F toregime
- F translate

require function
resolvers table
- F allprefixes
- F appendhash
- F automount
- F booleanvariable
- S cacheversion
- F checkedvariable
- F cleanedpathlist
- D cleaners
- F cleanpath
- F cleanpathlist
- F cleanupbinfile
- D concatinators
- S configbanner
- F configurationfiles
- D dangerous
- F datastate
- F dirstatus
- F dowithfilesandreport
- F dowithfilesintree
- F dowithpath
- F dowithvariable
- F expandbraces
- F expandedpathfromlist
- F expandedpathlist
- F expandedpathlistfromvariable
- F expandpath
- F expandpathfromvariable
- F expansion
- F extendtexmfvariable
- F filtered_from_content
- F find_file
- F find_files
- F findbinfile
- F findctxfile
- D finders
- F findfile
- F findfiles
- F findgivenfile
- F findgivenfiles
- F findlib
- F findpath
- F findpk
- F findtexfile
- F findwildcardfile
- F findwildcardfiles
- F formatofsuffix
- F formatofvariable
- D formats
- F foundintree
- F foundintrees
- D generators
- F get_from_content
- F getdetails
- F getenv
- F getextrapaths
- F getfilehashes
- F gethashes
- F getownpath
- F getreadfilename
- D hashers
- S homedir
- F ignorelibrary
- F initialized
- F installinputfilehandler
- F installinputlinehandler
- F jobpath
- F joinpath
- F knownvariables
- F load

F loadbinfile
D loaders
F loadlualib
F loadtexfile
F loadtime
F locateformat
D locators
S luacnffallback
S luacnfname
S luacnfspec
S luacnfstate
N maxreadlevel
F methodhandler
F missinglibrary
F openbinfile
D openers
F openfile
F opentexfile
S ownpath
F popextrapath
F popinputname
F poppath
D prefixes
F prependhash
F pushextrapath
F pushinputname
F pushpath
F registerextrapath
F registerfile
F registerfilehash
F registerintrees
F registermethod
F registerzipfile
D relations
F renew
F renewcache
F repath
F reset
F resetextrapaths
F resetresolve
F resolve
D savers
F scandata
F scanfiles
F setdynamic
F setenv
F showdetails
F showpath
F simplescanfiles
F splitconfigurationpath
F splitexpansions
F splitmethod
F splitpath
F stackpath
F starttiming
F stoptiming
D suffixes
D suffixmap
F suffixofformat
F texdatablob
F toppath
D tracers
F unexpandedpath
F unexpandedpathlist
F unresolve
F updaterelations
F uselibrary
D usertypes
F usezipfile
F validatedpath
F variable
F variableofformat
F variableofformatorsuffix
F wildcardpattern

sandbox table

F enable
F getrunner
F possiblepath
F registerrunner
F setfilenamelogger

scripts table

D colors
F decomposehangul
F getdata
F getinjector
F getsplitter
F getstatus
D handlers

D helpers
D injectors
F installdataset
F installmethod
D numbertodataset
D numbertohandler
F reset
F set
F setstatus
D splitters

security table
F checked
F getactions
F gettargets
F resetdebug
F setchecker

select function

sequencer table
F addbytestobuffer
F addformattobuffer
F addpackingtobuffer
F addtobuffer
F fastserialize
F format
F getbufferdata
F getbuffersize
F newbuffer
F sequenced
F serialize
F sortedhash
F tabstr_boolean
F tabstr_flat
F tabstr_mixed
F tabstr_normal
F tostring

serial table
F __gc
S __name
F __tostring
F close
F open
F send
F tostring
F write

server table
F httpserver
F supported

set table
F contains
F create
F tolist
F tonumber
F totable

setinspector function

setmathparameters function

setmetatable function

sha2 table
F HASH256
F HASH384
F HASH512
F HEX256
F HEX384
F HEX512
F digest256
F digest384
F digest512
F hash256
F hash384
F hash512
F hex256
F hex384
F hex512
F sum256
F sum384
F sum512

sio table
F read2dot14
F readbytes
F readbytetable
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable

F readcline
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat
F readfloatle
F readfloatle12
F readfloatle6
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F tocardinal1
F tocardinal1le
F tocardinal2
F tocardinal2le
F tocardinal3
F tocardinal3le
F tocardinal4
F tocardinal4le
F tocardinal8
F tocardinal8le
F tointeger1
F tointeger1le
F tointeger2
F tointeger2le
F tointeger3
F tointeger3le
F tointeger4
F tointeger4le
F tointeger8
F tointeger8le

sorters table

F basicsorter
D definitions
F firstofsplit
F packch
F packuc
F replacementlist
F setlanguage
F sort
F strip
D tracers
F update

sparse table

F concat
F get
F max
F min
F new
F range
F restore
F set
F traverse
F wipe

statistics table

F benchmarktimer
F checkfmtstatus
F currenttime
F elapsed
F elapsedindeed
F elapsedseconds
F elapsedtime
B enable
F formatruntime
F istiming
F memused
F register
F resettiming
F runtime
F savefmtstatus
F show
F showmemory
F showusage
F starttiming
F stoptiming
N threshold
F timed
F tracefunction

status table

F getbalancestate

F getbufferstate
F getcallbackstate
F getconstants
F getdumpstate
F geterrorlinestate
F geterrorstate
F getexpandstate
F getfilestate
F getfontstate
F gethalferrorlinestate
F gethashstate
F gethyphenationstate
F getinputstate
F getinsertstate
F getlanguagestate
F getlinebreakstate
F getlookupstate
F getluastate
F getmarkstate
F getmvlstate
F getneststate
F getnodestate
F getparameterstate
F getpoolstate
F getreadstate
F getsavestate
F getsparsestate
F getstringstate
F gettexstate
F gettokenstate
F getwarningstate
F list
F resetmessages

storage table

F allocate
F mark
F marked
N max
N min
N nofmodules
N noftables
F register
D shared
D storedfunctions
B strip
N tofmodules
N toftables

streams table

F collect
F disable
F enable
F flush
F initialize
F push
F start
F stop
F synchronize

string table

F booleanstring
F byte
F bytepairs
F bytes
F bytetable
F char
F characterpairs
F characters
F checkedsplit
F chrtointeger
F collapsespaces
F containsws
F count
F dectointeger
F dump
F escapedpattern
F f6
F fd
F fd3
F fd6
F fd9
F find
F format
F formatted
F formatter
D formatters
F formatting
F fromunicode16
F fullstrip
F g6

F gd
F gmatch
F gsub
F hextocharacters
F hextointeger
F is_boolean
F is_empty
F itself
F len
F limit
F linetable
F longtostring
F lower
F match
F nospaces
F octtointeger
F optionalquoted
F pack
F packrowscolumns
F packsize
F quote
F quoted
F rep
F replacenewlines
F reverse
F split
F splitintolines
F splitlines
F splitup
F strip
F sub
F texhashed
F texnewlines
F tformat
F toHEX
F toboolean
F tobytes
F tocontext
F todec
F todimen
F tohex
F tonodes
F topattern
F topdfeight
F topdfsixteen
F topdfstring
F totable
F tounicode16
F toutf
F toutf16
F toutf32
F toutf8
F unpack
F unquote
F unquoted
F upper
F utf16toutf8
F utfcharacter
F utfcharacters
F utfcharactertable
F utflength
F utfpadd
F utftabletostring
F utfvalue
F utfvalues
F utfvaluetable
F valid
F wordsplitter

structures table

F atlocation
F currentsectionnumber

table table

F append
F are_equal
F combine
F compact
F concat
F contains
F copy
F count
F create
F derive
F deserialize
F fastcopy
F fastserialize
F filtered
F flattened
F fromhash

F getn
F has_one_entry
F hashed
F identical
F imerge
F imerged
F insert
F is_empty
F keys
F load
F loweredkeys
F makeweak
F merge
F merged
F mirrored
F move
F pack
F prepend
F print
F remove
F reverse
F reversed
F save
F sequenced
F serialize
F setmetatablecall
F setmetatableindex
F setmetatableindices
F setmetatablenewindex
F sort
F sorted
F sortedhash
F sortedhashkeys
F sortedhashonly
F sortedindexonly
F sortedkeys
F sortedpairs
F sparse
F strip
F sub
F swapped
F tocontext
F tocsv
F tofile
F tohash
F toxml
F unique
F unpack

tabstr_boolean function

tabstr_flat function

tabstr_mixed function

tabstr_normal function

tex table

F attributetracking
D automigrationcodes
D autoparagraphcodes
F badness
D badnessmodecodes
F balance
D balancecallbackcodes
D boxcontinuationcodes
D boxoptioncodes
D breakcodes
D buildcodes
D charactercontrolcodes
D charactertagcodes
F chardef
D classoptioncodes
D conditionals
D constants
F cprint
N ctdcatcodes
N ctxcatcodes
F definefont
F dimensiondef
D directioncodes
D directives
D discoptioncodes
D discpartcodes
F dontcomplain
D doublescriptoptioncodes
F enableprimitives
F equal
F error
F expandasvalue
D experiments
F extraprimitives
F fatalerror

D fillcodes
D flagcodes
F fontidentifier
F fontname
F forcehmode
F forceinputstatefile
F forceinputstateline
F fprint
D frozenparcodes
F get
F getadjustoptionvalues
F getalignmentcontextvalues
F getamcode
F getappendadjustcontextvalues
F getappendmigratecontextvalues
F getattribute
F getautomigrationvalues
F getautoparagraphvalues
F getbadnessmodevalues
F getbalancecallbackvalues
F getbalanceparameterfields
F getbalanceresultfields
F getbalancestepoptionvalues
F getbox
F getboxcontinuationvalues
F getboxdir
F getboxoptionvalues
F getboxresourcebox
F getboxresourcedimensions
F getbreakcontextvalues
F getbuildcontextvalues
F getcardinalvalue
F getcatcode
F getcccode
F getcharactercontrolvalues
F getcharactertagvalues
F getcount
F getcurrentmvl
F getdelcode
F getdelcodes
F getdimen
F getdimensionvalue
F getdirectionvalues
F getdiscoptionvalues
F getdiscpartvalues
F getdoublescriptoptionvalues
F getemptyparagraphmodevalues
F geterrorrecoverymodevalues
F geterrorvalues
F getfillvalues
F getflagvalues
F getfloat
F getfontdimension
F getfontoffamily
F getfrozenparvalues
F getglue
F getglueoptionvalues
F getglyphdata
F getglyphdiscvalues
F getglyphoptionvalues
F getglyphprotectionvalues
F getglyphscales
F getglyphscript
F getglyphstate
F getgroupvalues
F gethccode
F gethelptext
F gethmcode
F gethyphenationvalues
F getiftypes
F getinputstatefile
F getinputstateline
F getinputstatemode
F getinsertcategoryvalues
F getinsertcontent
F getinsertdepth
F getinsertdistance
F getinsertheight
F getinsertlimit
F getinsertmaxplaced
F getinsertmultiplier
F getinsertoptionvalues
F getinsertsplitvalues
F getinsertwidth
F getintegervalue
F getinteraction
F getinteractionmodes
F getiovalues

F getkerneloptionvalues
F getkernoptionvalues
F getlargestusedmark
F getlccode
F getlinebreakparameterfields
F getlinebreakresultfields
F getlinebreakstatevalues
F getlinedir
F getlist
F getlistanchorvalues
F getlistfields
F getlistgeometryvalues
F getlistsignvalues
F getlocalbox
F getlocalboxlocations
F getlocallevel
F getmark
F getmarknames
F getmath
F getmathclassoptionvalues
F getmathcode
F getmathcodes
F getmathcontrolvalues
F getmathdir
F getmathgluevalues
F getmathoptionvalues
F getmathparametervalues
F getmathscriptordervalues
F getmathscriptsmodevalues
F getmathstylenamevalues
F getmathstylevalues
F getmathstylevariant
F getmathsurroundvalues
F getmathvariantpresets
F getmathvariantvalues
F getmeasure
F getmissingcharactervalues
F getmode
F getmodevalues
F getmuglue
F getmuskip
F getmvloptionvalues
F getnest
F getnestfields
F getnestlevel
F getnoadoptionvalues
F getnormalizelinevalues
F getnormalizeparvalues
F getnospacesmodevalues
F getoutputactive
F getoverloadstate
F getpacktypevalues
F getpagecontextvalues
F getpagestate
F getpagestatevalues
F getparagraphfillmodevalues
F getparagraphoptionvalues
F getparametermodevalues
F getparcontextvalues
F getpardataspecifications
F getpardir
F getparmodevalues
F getparstate
F getparstatefields
F getpartriggervalues
F getpenaltyoptionvalues
F getpositvalue
F getpreposststatevalues
F getprimitivelegacies
F getprimitiveorigins
F getprotrusionboundaryvalues
F getregisterindex
F getruleoptionvalues
F getrunstate
F getrunstatevalues
F getsfcode
F getshapingpenaltiesvalues
F getskip
F getsnappingvalues
F getspacefactorvalues
F getspaceskipvalues
F getspcode
F getspecialmathclassvalues
F getspecification
F getspecificationoptionvalues
F gettextcontrolvalues
F gettextdir
F gettoks

F getuccode
F getuleaderlocationvalues
F getunitclassvalues
F getusedmarks
F getvariablefamilyvalues
F getvsplitcontextvalues
D glueoptioncodes
D glyphdisccodes
D glyphoptioncodes
D groupcodes
F hashtokens
N hshcatcodes
D hyphenationcodes
D ifs
N inicatcodes
D insertcategorycodes
D insertoptioncodes
D insertsplitcodes
F integerdef
D interactioncodes
F isattribute
F isbox
F iscount
F isdefined
F isdimen
F isfloat
F isglue
F ismuglue
F ismuskip
F isprintable
F isskip
F istoks
F lastnodetype
F less
F lessequal
F linebreak
D linebreakstatecodes
D listanchorcodes
D listgeometrycodes
D listsigncodes
N luacatcodes
F mathchardef
D mathcontrolcodes
D mathoptioncodes
D mathparametercodes
D mathscriptordercodes
D mathscriptsmodecodes
D modes
F mprint
D mvloptioncodes
N nilcatcodes
D noadoptioncodes
D normalizelinecodes
D normalizeparcodes
D nospacesmodecodes
N notcatcodes
F number
D paragraphfillmodecodes
D paragraphoptioncodes
D parcontextcodes
D partriggercodes
D penaltyoptioncodes
F poplocal
F popsavelevel
F positdef
F preparelinebreak
F primitives
F print
D protrusionboundarycodes
N prtcatcodes
F pushlocal
F pushsavelevel
F quitlocal
F quittoks
F resetparagraph
N rlncatcodes
F romannumeral
F round
D ruleoptioncodes
F runlocal
D runstatecodes
F runstring
F runtoks
F saveboxresource
F scale
F scantoks
F set
F setamcode

F setattribute
F setbalanceshape
F setbox
F setboxdir
F setcardinalvalue
F setcatcode
F setcccode
F setconditional
F setcount
F setdelcode
F setdimen
F setdimensionvalue
F setfloat
F setglue
F setglyphdata
F setglyphscript
F setglyphstate
F sethccode
F sethmcode
F setinputstatefile
F setinputstateline
F setinputstatemode
F setinsertcontent
F setinsertdistance
F setinsertlimit
F setinsertmaxplaced
F setinsertmultiplier
F setintegervalue
F setinteraction
F setlccode
F setlinedir
F setlist
F setlocalbox
F setmath
F setmathcode
F setmathdir
F setmuglue
F setmuskip
F setnest
F setoverloadstate
F setpardir
F setpositvalue
F setrunstate
F setsfcode
F setskip
F setspcode
F settextdir
F settoks
F setuccode
D shapingpenaltiescodes
F shiftparshape
F shipout
F showcontext
D snappingcodes
F snapshotpar
F sp
D spacefactorcodes
D spaceskipcodes
D specialmathclasscodes
D specificationoptioncodes
F splitbox
D splitcodes
F sprint
F stringtocodesbitmap
D systemmodes
F takebox
N texcatcodes
D textcontrolcodes
F tonumber
F toscaled
N tpacatcodes
N tpbcatcodes
F tprint
F trackedattribute
D trackers
F triggerbuildpage
N txtcatcodes
F uprint
F useboxresource
D userdiscoptioncodes
D userglyphoptioncodes
N vrbcatcodes
F write

texconditionals data table

texconfig table

S firstline
S formatname
N functionsize

F init
B kpse_init
N propertiessize
S shell_escape

texconstants data table

texifs data table

texio table

F closeinput
F forceendoffile
F getinputindex
F getselectorvalues
F getsourcefilename
F setlogfile
F terminal
F write
F write_nl
F writenl
F writeselector
F writeselectorlf
F writeselectornl

texisdefined data table

texmodes data table

texsystemmodes data table

thirddata table

timer table

S __name
F __tostring
F current
F elapsed
F elapsedms
F elapsedus
F elapsedμs
F istiming
F new
F reset
F setoffset
F sleepms
F start
F stop
F tostring

toboolean function

todecimal function

token table

F create
F expand
F expand_macro
F expandmacro
F future_expand
F futureexpand
F get_active
F get_cmdchrcs
F get_cmdname
F get_command
F get_csname
F get_cstoken
F get_dimension
F get_expandable
F get_fields
F get_flags
F get_frozen
F get_id
F get_immutable
F get_index
F get_instance
F get_integer
F get_macro
F get_meaning
F get_noaligned
F get_parameters
F get_permanent
F get_primitive
F get_protected
F get_range
F get_tok
F get_tolerant
F getactive
F getcmdchrcs
F getcmdname
F getcommand
F getcommandvalues
F getconstant
F getcsname
F getcstoken
F getdimension
F getexpandable
F getexpansion
F getfields
F getflags

F getfrozen
F getfunctionvalues
F getid
F getimmutable
F getindex
F getinstance
F getinteger
F getlength
F getmacro
F getmeaning
F getnoaligned
F getparameters
F getpermanent
F getprimitive
F getprimitives
F getprotected
F getrange
F gettok
F gettolerant
F gobble
F gobble_dimension
F gobble_integer
F gobbledimension
F gobbleinteger
F grab
F grabstring
F inhibit
F is_defined
F is_next_char
F is_token
F isactivestring
F isdefined
F isnextchar
F istoken
F locatemacro
F new
F peek_next
F peek_next_char
F peek_next_expanded
F peeknext
F peeknextchar
F peeknextexpanded
F pop_macro
F popmacro
F push_macro
F pushmacro
F put_back
F put_next
F putback
F putnext
F save_lua
F savelua
F scan_argument
F scan_box
F scan_cardinal
F scan_char
F scan_cmdchr
F scan_cmdchr_expanded
F scan_code
F scan_csname
F scan_delimited
F scan_dimen
F scan_float
F scan_glue
F scan_integer
F scan_key
F scan_keyword
F scan_keyword_cs
F scan_letters
F scan_luacardinal
F scan_luainteger
F scan_luanumber
F scan_next
F scan_next_char
F scan_next_expanded
F scan_real
F scan_scale
F scan_skip
F scan_string
F scan_token
F scan_token_code
F scan_tokenlist
F scan_toks
F scan_value
F scan_word
F scanargument
F scanbox
F scancardinal

F scanchar
F scancmdchr
F scancmdchrexpanded
F scancode
F scancsname
F scancstoken
F scandelimited
F scandetokened
F scandimen
F scandimenargument
F scandimension
F scandimensionargument
F scanfloat
F scanglue
F scanint
F scaninteger
F scanintegerargument
F scankey
F scankeyword
F scankeywordcs
F scanletters
F scanluacardinal
F scanluainteger
F scanluanumber
F scannext
F scannextchar
F scannextexpanded
F scanposit
F scanreal
F scanscale
F scanskip
F scanstring
F scantoken
F scantokencode
F scantokenlist
F scantokenstring
F scantoks
F scanvalue
F scanword
F serialize
F set_dimension
F set_integer
F set_lua
F set_macro
F setdimension
F setinteger
F setlua
F setmacro
F setmacrofrommark
F setmacrotonothing
F skip_next
F skip_next_expanded
F skipnext
F skipnextexpanded
F type
F undefine_macro
F undefinemacro

tokens table

F astable
D cache
D commands
F compile
F constant
F create
F defined
F flags
F getinteger
F gobble
F isactivestring
F isdefined
F istoken
F new
F pickup
F popmacro
F pushmacro
F setinteger
D values

tonumber function

tostring function

tostring_u1 function

tostring_u2 function

tracers table

F printerror
F printwarning
F processerror
F showlines

trackers table

D data

F default
F disable
F dumphashtofile
F enable
F list
S name
F register
F report
F reset
F savehash
F set
F show
F value
F values
type function
typesetters table
F marksuspects
F showinvisibles
F showsuspects
unpack function
updaters table
F apply
F register
url table
F addscheme
F barepath
F construct
F decode
F encode
F escape
F filename
F hashed
F hasscheme
F query
F split
F toquery
F unescape
F unescapeget
userdata table
utf table
F byte
F bytepairs
F char
F characters
F chrlen
F count
F filetype
F is_valid
F len
F length
F lower
F remapper
F replacer
F split
F splitlines
F sub
F substituter
F tocodes
F toeight
F toentities
F tostring
F totable
F upper
F ustring
F utf16_to_utf8_be
F utf16_to_utf8_be_t
F utf16_to_utf8_le
F utf16_to_utf8_le_t
F utf16_to_utf8_t
F utf32_to_utf8_be
F utf32_to_utf8_be_t
F utf32_to_utf8_le
F utf32_to_utf8_le_t
F utf32_to_utf8_t
F utf8_to_utf16
F utf8_to_utf16_be
F utf8_to_utf16_le
F utf8_to_utf8_t
F values
F xstring
utf8 table
F char
S charpattern
F codepoint
F codes
F len
F offset
utilities table

vector table

F add
F append
F average
F ceiling
F checkoverlap
F collectoverlap
F concat
F copy
F crossproduct
F delete
F determinant
F div
F equal
F exchange
F floor
F get
F getdimensions
F getepsilon
F getmemory
F getmesh
F getmeshtypes
F getpointtypes
F getrc
F getrow
F getsize
F getstacking
F gettype
F homogenize
F identity
F inner
F insert
F inverse
F ismesh
F ispoints
F issingular
F isvector
F iszero
F meshname
F mul
F negate
F new
F normalize
F onecolumn
F onerow
F product
F remove
F replace
F round
F rowechelon
F set
F setepsilon
F setnext
F setrc
F setstacking
F slice
F sort
F sub
F swap
F tostring
F totable
F transpose
F triangulate
F truncate
F type

visualizers table

D escapepatterns
F getspecification
F getvisualizer
F load
F makenested
F makepattern
F newgrammar
F newhandler
F parsedxml
F pattern
F register
F registerescapecommand
F registerescapeline
F registerescapepattern
S signal
U signalpattern
D specifications
F visualize
F visualizebuffer
F visualizefile
F visualizestring
F write

F writeargument
F writedefault
F writeemptyline
F writenewline
F writespace

warn function

xcomplex table

F I
F __add
F __div
F __eq
F __mul
S __name
F __pow
F __sub
F __tostring
F __unm
F abs
F acos
F acosh
F arg
F asin
F asinh
F atan
F atanh
F conj
F cos
F cosh
F dawson
F erf
F erfc
F erfcx
F erfi
F exp
F i
F imag
F log
F new
F pow
F proj
F real
F sin
F sinh
F sqrt
F tan
F tanh
F topair
F tostring
F totable
F voigt
F voigt_hwhm

xdecimal table

F __add
F __band
F __bor
F __bxor
F __div
F __eq
F __idiv
F __le
F __lt
F __mod
F __mul
S __name
F __pow
F __shl
F __shr
F __sub
F __tostring
F __unm
F abs
F band
F bor
F bxor
F conj
F copy
F exp
F getprecision
F ln
F log
F max
F min
F minus
F new
F plus
F pow
F rotate
F setprecision

F shift
F sqrt
F toengstring
F tonumber
F tostring
F trim

xinterval table

F __add
F __div
F __eq
F __le
F __lt
F __mod
F __mul
S __name
F __pow
F __sub
F __tostring
F __unm
F abs
F acos
F acosh
F asin
F asinh
F asstring
F atan
F atanh
F cos
F cosh
F diameter
F equal
F erf
F erfc
F exp
F exp10
F exp2
F expm1
F greater
F greaterequal
F hull
F intersect
F less
F lessequal
F log
F log10
F log1p
F log2
F mid
F mod
F new
F neweps
F pow
F seteq
F setge
F setgt
F setle
F setlt
F sin
F sinh
F sqr
F sqrt
F tan
F tanh
F topair
F tostring
F totable
F usedendian
F within

xmath table

F acos
F acosh
F asin
F asinh
F atan
F atan2
F atanh
F cbrt
F ceil
F copysign
F cos
F cosh
F crossproduct
F deg
F dotproduct
F erf
F erfc
F exp
F exp2

F expm1
F fabs
F fdim
F floor
F fma
F fmax
F fmin
F fmod
F frexp
F gamma
F hypot
N inf
F isfinite
F isinf
F isnan
F isnormal
F j0
F j1
F jn
F ldexp
F lgamma
F log
F log10
F log1p
F log2
F logb
F modf
N nan
F nearbyint
F nextafter
F normalize
N pi
F pow
F rad
F remainder
F remquo
F round
F scalbn
F sin
F sinh
F sqrt
F tan
F tanh
F tgamma
F trunc
F y0
F y1
F yn

xml table

F addentitiesdoctype
F addspecialcode
F after
F all
F applylpath
F applyselector
F assign
F attribute
F badinclusions
F before
F body
F cdata
F cdatatotext
F checkbom
F checkedempty
F checkerror
F checknamespace
F checkns
F cleansed
F collect
F collect_elements
F collect_tags
F collect_texts
F collected
F collecttexts
F compactelement
F content
F convert
F copy
F count
F cprint
S defaultprotocol
F delete
F delete_element
F despecialized
F each
F each_element
F elements
F elementtocdata

F empty
D entities
F erase
F errorhandler
F escaped
F expand
F fillin
F filter
F first
F found
F getbuffer
F gethandlers
F gethandlersfunction
F include
F inclusion
F inclusions
F index
F inheritattributes
F inheritedconvert
F inject
F inject_element
F inject_element_after
F inject_element_before
F injectafter
F injectbefore
F insert
F insert_element
F insert_element_after
F insert_element_before
F insertafter
F insertbefore
F insertcdata
F insertcomment
F inspect
F is_valid
F kind
F last
F lastmatch
F load
F lpath
F lpathcached
F lpathcalls
F lshow
F makestandalone
F match
F name
F newhandlers
F nodesettostring
F originalload
F package
F parent
U parsedentitylpeg
F popmatch
F position
D privatecodes
F privatetoken
F process
F process_attributes
F process_elements
F processattributes
F pure
F pushmatch
F raw
F registerentity
F registerns
F reindex
F remap_name
F remap_namespace
F remap_tag
F remapname
F remapnamespace
F remaptag
F rename
F renamespace
U reparsedentitylpeg
F replace
F replace_element
F resetinjectors
F resolvens
F root
F save
F selection
F separate
F serialize
F serializetotext
F setcdata
F setcomment
F sethandlersfunction

F setinjectors
F setproperty
F settings
D specialcodes
F sprint
F string
F strip
F strip_whitespace
F stripelement
F stripleadingspaces
F table
F text
F textonly
F texttocdata
F tocdata
F toelement
F tostring
F totable
F toxml
F tprint
F traverse
F unescaped
U unescapedentitylpeg
F unprivatized
F unspecialized
F wipe
F withelement
F withelements
F wrap

xpcall function

xzip table

F adler32
F compress
F compresssize
F crc32
F decompress
F decompresssize

zbuffer table

F bounds
F composite
F crop
F edgepoint
F flatten
F get
F getcolor
F getconstants
F getdepth
F getnormal
F getnormalmodes
F getopacity
F getsize
F implicit
F iszbuffer
F meshmesh
F new
F points
F process
F project
F resolve
F set
F setcolor
F setdepth
F setnormal
F setopacity
F setup
F smoothen
F stipple_0
F stipple_1
F stipple_2
F stipple_3
F stipple_4
F stipple_setup
F tobytes
F tostring
F totable
F transform
F trianglebounds
F triangled
F triangles
F type

zip table

F closearchive
F openarchive

zlib table

F adler32
F compress
F compresssize
F crc32

F decompress

F decompresssize

graphics (context)

backgrounds table
- F fetchmultipar

bitmaps table
- F flush
- F load
- F new
- F placeholder
- F tocontext

bpsize function

colorspaces table

identifiers table
- F bitmap
- F jp2
- F jpeg
- F jpg
- F png

identify function

registerpdfcompactor function

registerpdffont function

synchronizers table
- F collapse
- F collect
- F extend
- F getbottom
- F getd
- F geth
- F getkind
- F getsize
- F gettask
- F gettop
- F getw
- F getx
- F gety
- F prune

gzip (context)

compress	function	**load**	function
compressed	function	**save**	function
decompress	function	**suffix**	function

helper (context)

getprofile	function	**snaplist**	function
mathnested	function	**traversecharmethod**	function
mathprocess	function	**traverseglyphmethod**	function
mathstep	function	**traversehorizontal**	function
snapindeed	function	**traversevertical**	function

images (context)

check function
checksize function
copy function
create function
embed function
embedfromstore function
fetchdata function
keys table
print function
resetdata function
resetstore function
scan function
serialize function
sizes table
- B art
- B bleed
- B crop
- B media
- B none
- B trim

storedata function
totable function
types table
- N jbig2
- N jp2
- N jpg
- N none
- N pdf
- N png
- N stream

wrap function

interactions (context)

attachments data table
fields table
- F clone
- F define
- F defineset
- F insert

general table
- F getidentity
- F getidentityvariable

help table
- F collect
- F reference
- F register

javascripts table
- F addtopreamble
- F code
- D codes
- F flushpreambles
- D functions
- D preambles
- F setpreamble
- F storecode
- F storepreamble
- F usepreamblenow
- F usescripts

linkedlists data table
pages table
- F setpagetransition
- F setupcanvas

references table
- F setclosedocumentaction
- F setclosepageaction
- F setopendocumentaction
- F setopenpageaction

renderings data table

interfaces (context)

arrays	table	**namesofscanners**	table
cachedsetups	data table	**namespaces**	table
cachesetup	function	F define	
cardinals	table	F list	
checkedspecification	function	**numbers**	table
complete	data table	**registernamespace**	function
constants	data table	**registerscanner**	function
corenamespaces	data table	**scanners**	data table
currentinterface	string	**setconstant**	function
currentresponse	string	**setcount**	function
definecommand	function	**setdimen**	function
defined	function	**setelement**	function
doifelsemessage	function	**setformat**	function
elements	data table	**setmacro**	function
floats	table	**setmessage**	function
formats	data table	**setmessages**	function
getmessage	function	**settranslation**	function
getnamespace	function	**setupstrings**	data table
getsetupstring	function	**setvariable**	function
hashedsetups	data table	**showmessage**	function
implement	function	**storedscanners**	data table
integers	table	**tolist**	function
interfacedcommand	function	**translations**	data table
interfaces	table	**usednamespaces**	data table
knownscanner	function	**variables**	data table
message	function	**writestatus**	function
nameofscanner	function		

io (basic lua)

ask	function	**open**	function
bytes	function	**output**	function
characters	function	**pathseparator**	string
close	function	**popen**	overloaded function
copydata	function	**read**	function
exists	function	**readall**	function
fileseparator	string	**readnumber**	function
flush	function	**readstring**	function
gobble	function	**savedata**	function
input	function	**size**	function
lines	function	**stderr**	userdata
loadchunk	function	**stdin**	userdata
loaddata	function	**stdout**	userdata
loadlines	function	**tmpfile**	function
newreader	function	**type**	function
noflines	function	**write**	function

job (context)

comment function
datasets table
D collected
F extend
F getdata
F setdata
D tobesaved
disablesave function
embedded table
D collected
D tobesaved
fileobjreferences table
D collected
D tobesaved
files table
D collected
F context
B forcerun
F run
D tobesaved
getrandomseed function
initialize function
linkedlists table
D collected
D tobesaved
load function
loadother function
meshedup table
D collected
D tobesaved
objects table
D collected
F get
F number
F page
F save
F set
D tobesaved
pack boolean
packversion number
pagestates table
D collected
F countervalue
F extend
F realpage
F realpageorder
F setstate
D tobesaved
parwrappers table
D collected
D tobesaved
positions table
F b_column
F b_region
F c
D collected
F column
F columnofpos
F copy
F depth
F e_column
F e_region
F enhance
F extra
F get
F getcolumndata
F getfree
F gethpos
F gethvrpos
F getpos
F getreserved
F getrpos
F getsync
F gettobesaved
F getvpos
F hangafter
F hangindent
F height
F hsize
N lastr
N lastx
N lasty

F leftskip
F lowerleft
F lowerright
F markregionbox
F n
F onsamepage
F overlapping
F p
F page
F paragraph
F parindent
F position
F r
F region
F registerhandlers
F replace
F rightskip
F set
F setall
F setregionbox
F setspec
F settobesaved
D tobesaved
F upperleft
F upperright
F used
F whd
F width
F x
F xy
F y

register function

save function

structure table

D collected

variables table

D checksums
D collected
F getchecksum
F makechecksum
F restore
F save
F setchecksum
D tobesaved

version number

kdtree (context)

delete	function	**new**	function
found	function	**newweighted**	function
insert	function	**reset**	function
nearest	function	**totable**	function
nearestindex	function	**traverse**	function

language (basic tex)

clean	function	**id**	function
clearhyphenation	function	**new**	function
clearpatterns	function	**patterns**	function
current	function	**postexhyphenchar**	function
gethjcode	function	**posthyphenchar**	function
haslanguage	function	**preexhyphenchar**	function
hyphenate	function	**prehyphenchar**	function
hyphenation	function	**sethjcode**	function
hyphenationmin	function	**setwordhandler**	function

languages (context)

addgoodiesdata function
addgoodiesfile function
appliedoptions table
associate function
associated data table
association function
counters data table
current function
data data table
decimals data table
define function
explicithyphen function
exportlanguage function
flatten function
frequencies table
F averagecharwidth
F getdata
getdata function
getmetadata function
getnumber function
goodiefiles function
hjcounts table
hyphenate function
hyphenators table
D featuresets
F handler
F popmethod
F pushmethod
F setmethod
F setup
F showhyphenationtrace
installed function
installhandler function
labels table
F define
F split
loadable function
loadwords function
logger table
F report
nofflattened function
numbers data table
pdflanguage function
postexhyphenchar function
posthyphenchar function
preexhyphenchar function
prehyphenchar function
registered data table
registeredactions table
replacements table
F add
F addlist
F handler
F set
serializediscretionary function
setexceptions function
setgoodieshandler function
setoptions function
setpatterns function
setsynonym function
setwordhandler function
showdiscretionaries function
strippedgoodiewords function
tolang function
transliteration table
F exception
F handler
F register
F set
F use
unload function
urls table
D characters
N lefthyphenmin
D mapping
B packslashes
N righthyphenmin
F setcharacters
version number
visualizediscretionaries function
words table
F check

F disable

F enable

B enables

F found

F load

N threshold

layouts (context)

getcanvas function
getpagedimensions function
setupcanvas function

status table
- F isleftpage
- F leftorrightpageaction

lfs (extra lua)

attributes	function	**link**	function
canonicalize	function	**mkdir**	function
chdir	function	**mkdirs**	function
currentdir	function	**modification**	function
dir	function	**moreweird**	function
expandpath	function	**readlink**	function
isdir	overloaded function	**rmdir**	function
isfile	overloaded function	**setexecutable**	function
isfound	function	**setloadshebang**	function
isreadabledir	function	**symlink**	function
isreadablefile	function	**symlinktarget**	function
iswriteabledir	function	**touch**	function
iswriteablefile	function	**walkdir**	function
lessweird	function		

libraries (context)

basiclua data table
basictex data table
builtin data table
extralua data table
extratex data table
functions data table
globals data table
optional data table

lmx (context)

color function
convert function
convertfile function
convertstring function
einject function
eprint function
escape function
finalized function
finject function
fprint function
get function
getvariables function
htmfile function
html table
- F a
- F td
- F th

include function
inherited table
- S color-background-four
- S color-background-one
- S color-background-three
- S color-background-two
- S title

initialize function
inject function
lmxfile function
loadedfile function
make function
new function
popupfile function
print function
pv function
report function
reset function
result function
set function
show function
stripcss function
tv function
type function
urlescape function
variable function
variables table
- S color-background-blue
- S color-background-body
- S color-background-green
- S color-background-main
- S color-background-purple
- S color-background-yellow
- S title-default

logs (context)

application	function	**resetlogfile**	function
categories	function	**setformatters**	function
direct	function	**setlogfile**	function
disable	function	**setmessenger**	function
enable	function	**setprocessor**	function
finalactions	function	**settarget**	function
flush	function	**settimedlog**	function
format	function	**settranslations**	function
formatted	function	**show**	function
loggingerrors	function	**start_page_number**	function
messenger	function	**start_run**	function
new	function	**starterrorlogging**	function
newline	function	**startfilelogging**	function
poplogfile	function	**status**	function
poptarget	function	**stop_page_number**	function
private	table	**stoperrorlogging**	function
F enablepagetiming		**stopfilelogging**	function
F getpagetiming		**subdirect**	function
pushlogfile	function	**subreport**	function
pushtarget	function	**system**	function
registerfinalactions	function	**texerrormessage**	function
report	function	**writer**	function
reporter	function		

lpdf (context)

action function
adddocumentcolorspace function
adddocumentextgstate function
adddocumentpattern function
adddocumentshade function
addtocatalog function
addtoinfo function
addtonames function
addtopageattributes function
addtopageresources function
addtopagesattributes function
addxmpinfo function
annotationspecification function
array function
attachmentsymbols function
boolean function
border function
checkedkey function
checkedresources function
checkedvalue function
circularshade function
close function
cmykcode function
collectedresources function
color function
colorspace function
colorspaceconstants data table
colorspec function
colorvalue function
colorvalues function
commentsymbols function
compressdata function
compresslevel function
constant function
copyarray function
copyboolean function
copyconstant function
copydictionary function
copyfloat function
copyinteger function
copynumber function
copystring function
copyunicode function
deferredobject function
delayedobject function
destinationspecification function
dictionary function
docstring function
encodingvalues table
N base16
N base85
N decoded
N encoded
N plain
N utf16be
N utf16le
endpoints table
S Div
S Part
S Sect
epdf table
F allcontent
F analyzefonts
F contentplugin
F contenttostring
F contenttotext
D encryptioncodes
F expanded
F expandwidths
F fontplugin
F getpagecontent
F getstructure
F load
F mergewidths
D objectcodes
F objectrange
F objecttype
F pageplugin
F parsecontent
F producer
F unload
F verboseobject

escaped function
finalizedocument function
finalizepage function
finalizesignature function
finishtransparencycode function
flags table
flushfonts function
flushgroup function
flushobject function
flushstreamfileobject function
flushstreamobject function
fonts table
F color_direct
F color_indirect
formats data table
frombytes function
fromeight function
frompdfdoc function
fromsixteen function
getcatalog function
getcompression function
getfontname function
getfontobjectnumber function
getformatoption function
getinfo function
getmatrix function
getnofpages function
getpageproperties function
getpagereference function
getpagetags function
getpos function
gettaggingstatus function
gettrailerid function
getversion function
getxformname function
graycode function
h_hex_2 table
S
S
S
S
S
S (
S)
S \
h_hex_4 table
hasmatrix function
immediateobject function
includeimage function
initialize function
injectors table
F bitmap
F jp2
F jpg
F png
injectxmpinfo function
insertxmpinfo function
lastreferredpage function
layerreference function
limited function
linearshade function
literal function
majorversion function
makenametree function
minorversion function
noffontregistries function
nofpages function
null function
number function
object function
objectcompresslevel function
pagereference function
patternstream function
pdfcolor function
pdftimestamp function
permissions table
N access
N add
N assemble
N extract
N fillin
N modify
N print
N quality
preparesignature function
print function
procset function
protectresources boolean

quads function
rectangle function
reference function
registerannotation function
registerdestination function
registerdocumentfinalizer function
registerfontmethod function
registerinitializer function
registerpagefinalizer function
registerpattern function
registersignature function
replacexmpinfo function
reserveobject function
rgbcode function
rotationcm function
setcompression function
setencryption function
setpageorder function
setpagestate function
setpagetag function
setutfstringmode function
setversion function
sharedobject function
shareobject function
shareobjectreference function
splitsixteen function
spotcode function
stream function
string function
supportedformats function
tocidset function
toeight function
topdfdoc function
topermissions function
tosixteen function
transparency function
transparencycode function
transparencygroups table
    B none
transparencyvalue function
unicode function
usedcharacters table
usedfontnames table
    N dejavusansmonoboldttf-1-0-0
usedfontobjects table
    N dejavusansmonoboldttf-1-0-0
usedfontstreams data table
usedindices table
verbose function

lpeg (basic lua)

B	function	**firstofsplit**	function
C	function	**frontstripper**	function
Carg	function	**instringchecker**	function
Cb	function	**is_lpeg**	function
Cc	function	**keeper**	function
Cf	function	**locale**	function
Cg	function	**match**	function
Cmt	function	**oneof**	function
Cp	function	**patterns**	data table
Cs	function	**pcode**	function
Ct	function	**print**	function
P	function	**ptree**	function
R	function	**replacer**	function
S	function	**secondofsplit**	function
UP	function	**setmaxstack**	function
UR	function	**setutfcasers**	function
US	function	**split**	function
V	function	**splitat**	function
afterprefix	function	**splitter**	function
anywhere	function	**stripper**	function
append	function	**times**	function
balancer	function	**tsplitat**	function
beforesuffix	function	**tsplitter**	function
checkedsplit	function	**type**	function
containsws	function	**utfR**	function
counter	function	**utfchartabletopattern**	function
endstripper	function	**utfreplacer**	function
finder	function	**version**	string

lua (basic tex)

addnibble	function	**getstringkeys**	function
bytecode	table	**getversion**	function
bytedata	data table	**lastbytecode**	number
bytedone	table	**luastringcall**	function
callbytecode	function	**messages**	data table
comparekeys	function	**mpsstringcall**	function
finalizeinitex	function	**newindex**	function
firstbytecode	number	**newtable**	function
get_functions_table	function	**numbers**	data table
getallkeys	function	**protectglobal**	function
getbytecode	function	**registercode**	function
getcheckedkeys	function	**registeredcodes**	function
getcurrenttime	function	**registerglobal**	function
getdebuginfo	function	**registerinitexfinalizer**	function
getexitcode	function	**registername**	function
getfunctionstable	overloaded function	**setbytecode**	function
getnibble	function	**setexitcode**	function
getnumerickeys	function	**setnibble**	function
getpreciseseconds	function	**startupfile**	string
getpreciseticks	function	**subnibble**	function
getruntime	function	**usestringcall**	function
getstacktop	function	**version**	string
getstartupfile	function		

luac (extra lua)

inspect function
print function

luatex (context)

abort function
cleanup function
cleanuptempfiles function
currentfile function
currentlevel function
currenttotal function
poprunstate function
pushrunstate function
registerdumpactions function
registerpageactions function
registerstartactions function
registerstopactions function
registertempfile function
starttime number
synctex table
F blockfilename
F collect
F disable
F enable
F finish
F isenabled
F pause
F popline
F pushline
F registerdisabler
F registerenabler
F resetfilename
F resume
F setfilename
F setup
F start
F stop
F wrapup
wrapup function

lxml (context)

addindex	function
all	function
applyfunction	function
applyselectors	function
att	function
attribute	function
badinclusions	function
chainattribute	function
checkindex	function
collected	function
command	function
concat	function
concatrange	function
content	function
context	function
convert	function
count	function
delete	function
depth	function
direct	function
directives	table
F after	
F before	
F handle	
F load	
F setup	
displayverbatim	function
doif	function
doifelse	function
doifelseempty	function
doifelsetext	function
doifempty	function
doifnot	function
doifnotempty	function
doifnottext	function
doiftext	function
element	function
elements	function
entities	data table
fileline	function
filename	function
filter	function
filterlist	function
first	function
flush	function
flushlinewise	function
flushsetups	function
flushspacewise	function
~~**get_id**~~	~~function~~
getid	function
getindex	function
id	function
idsplitter	userdata
ifatt	function
ifattempty	function
include	function
inclusion	function
inclusions	function
index	function
inlineverbatim	function
installsetup	function
last	function
lastatt	function
lastmatch	function
lastpar	function
load	function
loadbuffer	function
loaddata	function
loaded	table
main	function
match	function
name	function
namespace	function
nonspace	function
par	function
param	function
parameter	function
path	function
popmatch	function
pos	function
position	function
pure	function

pushmatch function
raw function
rawroot function
rawtex function
refatt function
register function
registerentity function
removesetup function
replace function
resetcdata function
resetsetups function
resolvedentity function
root function
save function
serialize function
setaction function
setatt function
setattribute function
setcdata function
setcommandtonone function
setcommandtotext function
setpar function
setparam function
setparameter function
setsetup function
snippet function
sorters table
F add
F compare
F flush
F reset
F show
F sort
splitid function
startraw function
startunescaped function
stopraw function
stopunescaped function
store function
strip function
stripped function
tag function
texatt function
text function
tobuffer function
tofile function
toparameters function
toverbatim function
verbatim function
withindex function
xmltexhandler data table

math (basic lua)

abs	function	**maxinteger**	number
acos	function	**min**	function
asin	function	**mininteger**	number
atan	function	**mod**	function
atan2	function	**modf**	function
ceil	function	**odd**	function
ceiling	function	**pi**	number
cos	function	**pow**	function
cosd	function	**rad**	function
cosh	function	**random**	overloaded function
deg	function	**randomseed**	function
div	function	**round**	function
even	function	**setrandomseedi**	function
exp	function	**sin**	function
floor	function	**sind**	function
fmod	function	**sinh**	function
frexp	function	**sqrt**	function
huge	number	**tan**	function
initialseed	number	**tand**	function
ldexp	function	**tanh**	function
log	function	**tointeger**	function
log10	function	**type**	function
max	function	**ult**	function

mathematics (context)

addfallbacks function
addvariant function
alphabets data table
alternatives data table
beforepassingfonttotex function
big function
boldmap data table
categories table
D functions
charactersets data table
checkaftercopyingfont function
classes data table
classnames data table
codes data table
define function
dictionaries table
D data
D defaults
D groups
F groupset
F groupsetgroup
F name
D names
F registercharacter
F registergroup
F registergroupset
D sets
D variants
dimensions function
disablecollecting function
domainlabels table
domainnames table
N default
enablecollecting function
extensiblecode function
extensibles data table
extrabase number
fallbacks table
F apply
F install
fallbackstyleattr function
familyname function
functiontype function
gaps data table
getblobindex function
getboth function
getdomainname function
getextensibledata function
getmathblob function
getoptionallabel function
getstyle function
gettextblob function
getverboselabel function
horizontalcode function
initializeparameters function
makefont function
mapremap data table
markblobindexdone function
overloadparameters function
preset function
presets table
privatebase number
registerextensible function
registersimplematrix function
registerverboselabel function
remapalphabets function
renderextensible function
renderings table
D mappings
D numbers
D sets
renderset function
resetattributes function
scaleparameters function
setextensibledata function
setmathsymbol function
sets data table
setsnapping function
setvariant function
strutcode function
styles data table
syncboth function

syncname function
syncstyle function
tagging table
B mfenced
toengineclass function
toname function
tostyle function
tweakaftercopyingfont function
tweakbeforecopyingfont function
tweaks table
F accentdimensions
F action
F addactuarian
F addarrows
F addbars
F addcomposites
F addequals
F addfourier
F addmirrors
F addparts
F addprivates
F addrules
F addscripts
F bigslots
F checkaccents
F checkspacing
F copyaccents
F dimensions
F extendaccents
F fallbacks
F fixaccents
F fixellipses
F fixintegrals
F fixoldschool
F fixprimes
F fixradicals
F fixslashes
F fixvariants
F flattenaccents
F fontname
F inspect
F keepbases
F kernpairs
F kerns
F margins
F message
F moveitalics
F movelimits
F parameters
F radicalbodymargins
F radicaldegreeanchors
F replace
F replacealphabets
F replacerules
F setoptions
F setovershoots
F showinfo
F simplifykerns
F sortvariants
F strut
F substitute
F topanchors
F tweaks
F version
F wipeanchors
F wipecues
F wipeitalics
F wipevariants
utfmathaccent function
utfmathclass function
utfmathcommand function
utfmathfiller function
utfmathstretch function
variantcode function
variantcount function
virtualize function
virtualized data table

md5 (extra lua)

HEX	function	**sum**	function
dec	function	**sumHEXA**	function
hex	function	**sumhexa**	function

metapost (context)

checkformat function
checktracingonline function
cm function
codes table

- N addto
- N ampersand
- N and
- N assignment
- N atleast
- N begingroup
- N btex
- N capsule
- N colon
- N comma
- N controls
- N curl
- N cycle
- N definedmacro
- N delimiters
- N endgroup
- N equals
- N etex
- N everyjob
- N exittest
- N expandafter
- N fiorelse
- N if
- N input
- N interim
- N internal
- N iteration
- N leftbrace
- N leftbracket
- N leftdelimiter
- N let
- N macrodef
- N macrospecial
- N maketext
- N message
- N mode
- N newbytemap
- N newinternal
- N nullary
- N numeric
- N of
- N ofbinary
- N onlyset
- N parametertype
- N pathconnect
- N pathjoin
- N plusorminus
- N primarybinary
- N primarydef
- N property
- N protection
- N relax
- N repeatloop
- N rightbrace
- N rightbracket
- N rightdelimiter
- N runscript
- N save
- N scantokens
- N secondarybinary
- N secondarydef
- N semicolon
- N setbounds
- N shipout
- N show
- N slash
- N step
- N stop
- N str
- N string
- N tag
- N tension
- N tertiarybinary
- N tertiarydef
- N thingstoadd
- N to
- N typename
- N unary

N undefinedcs
N until
N void
N with
N within
N write

colorinitializer function
convert function
currentmpx function
currentmpxstatus function
defaultformat string
defaultinstance string
defaultmethod string
directrun function
escaped function
exectime table
extensiondata data table
filter function
filterclippath function
flush function
flushers table
flushnormalpath function
fonts table
F define
format_number function
format_string function
formatnumber function
getbackendoption function
getbendtolerance function
getbuffer function
getclippath function
getextensions function
getextradata function
gethashentries function
getinstancebyname function
getinstanceinfo function
getinstancenames function
getjobdata function
getmovetolerance function
getparameter function
getparameterpreset function
getparameterset function
getrecord function
getstatistics function
gettext function
gettolerance function
graphic function
graphic_base_pass function
hascurvature function
includesvgbuffer function
includesvgfile function
installplugin function
isobject function
knownparameters table
lastlog string
load function
maketext function
mesh function
mesher function
meshupper function
metafonts table
metafun table
F interpolate
F topath
mptopdf table
F convertmpstopdf
N nofconverted
n number
newlogger function
nofruns number
nofscriptruns function
nvformat function
pdfliterals function
pluginactions function
points function
pointset function
popformat function
popscriptrunner function
popvariable function
popvariables function
preparetextextsdata function
process function
processing function
processplugins function
properties table
pushformat function
pushscriptrunner function
pushvariable function

pushvariables function
quitonerror boolean
reducetogray boolean
registerdirect function
registerfilter function
registermesher function
registermeshupper function
registerpointset function
registerscript function
registertokens function
remappedtext function
remaptext function
reporterror function
reportsvgfonts function
reset function
resetbackendoptions function
resetlastlog function
resetplugins function
run function
runinternal function
runscript function
scanparameters function
scriptindex function
setbendtolerance function
setbuffer function
setextensions function
setlogging function
setmovetolerance function
setoutercolor function
setparameter function
setparameterset function
setrecord function
settext function
settolerance function
setvariable function
showlog boolean
showsvgpage function
simple function
splitprescript function
startgraphic function
startsvghashing function
stopgraphic function
stopsvghashing function
svformat function
svgcachefile boolean
svgcolorremapper function
svgfactors table
N %
N bp
N cm
N em
N ex
N in
N mm
N pc
N pt
N px
svgglyphtomp function
svgshapestomp function
svgshapestopdf function
svgsplitcolor function
svgtomp function
svgtopdf function
sxsy function
tex table
F get
F reset
F set
F setfrombuffer
texerrors boolean
texexp function
theclippath function
tographic function
totable function
types table
N boolean
N cmykcolor
N color
N dependent
N independent
N known
N nep
N numeric
N pair
N path
N pen
N picture
N protodependent

N string
N structured
N suffixedmacro
N tokenlist
N transform
N unknownboolean
N unknownnep
N unknownpath
N unknownpen
N unknownpicture
N unknownstring
N unsuffixedmacro
N vacuous

typesvgpage	function
unload	function
untagvariable	function
variables	table

mp (context)

autoinject function
aux function
- F boolean
- F color
- F direct
- F draw
- F fill
- F flush
- F fprint
- F integer
- F number
- F numeric
- F pair
- F pairpoints
- F path
- F pathpoints
- F points
- F print
- F quadruple
- F quadruplepoints
- F quoted
- F size
- F string
- F transform
- F triplet
- F tripletpoints
- F vprint

boolean function
bytemap_load_from_file function
cleaned function
color function
dataset function
datasets function
- F load

direct function
downgradebytemap function
downsamplebytemap function
draw function
expandtex function
fill function
fillbytemap function
flatten function
flush function
format function
formatted function
fprint function
get table
- F hashentry

getbytemap function
getbytemapdata function
getbytemapdirect function
getlastaddtype function
graphformat function
inject function
- F boolean
- F cmykcolor
- F color
- F integer
- F number
- F numeric
- F pair
- F path
- F points
- F pt
- F quadruplet
- F string
- F tokens
- F transform
- F triplet
- F vector
- F vectors
- F whatever
- F whd
- F xy

integer function
lmt_function_x function
lmt_glyphshape_accent function
lmt_glyphshape_baseline function
lmt_glyphshape_boundingbox function
lmt_glyphshape_depth function
lmt_glyphshape_height function
lmt_glyphshape_italic function

lmt_glyphshape_llx function
lmt_glyphshape_n function
lmt_glyphshape_path function
lmt_glyphshape_start function
lmt_glyphshape_stop function
lmt_glyphshape_usedbox function
lmt_glyphshape_usedline function
lmt_glyphshape_width function
lmt_mesh_set function
lmt_mesh_update function
lmt_poisson_generate function
lmt_start_potrace function
lmt_step_potrace function
lmt_stop_potrace function
lmt_svg_include function
loadbytemap function
loadbytemapfile function
mesh_register function
mf_blob_add function
mf_blob_dimensions function
mf_blob_index function
mf_blob_new function
mf_blob_raw_content function
mf_blob_raw_dimensions function
mf_blob_raw_reset function
mf_blob_raw_toutf function
mf_blob_raw_wipe function
mf_blob_size function
mf_blob_width function
mf_external_figure function
mf_finish_saving_data function
mf_formatted_text function
mf_get_outline_text function
mf_graphic_text function
mf_inject_blob function
mf_map_move function
mf_map_text function
mf_named_color function
mf_outline_text function
mf_save_data function
mf_script_index function
mf_start_saving_data function
mf_stop_saving_data function
mode function
n function
newbytemap function
number function
numeric function
pair function
pairpoints function
path function
pathpoints function
points function
points_register function
print function
F boolean
F color
F direct
F draw
F fill
F flush
F fprint
F integer
F number
F numeric
F pair
F pairpoints
F path
F pathpoints
F points
F print
F quadruple
F quadruplepoints
F quoted
F size
F string
F transform
F triplet
F tripletpoints
F vprint
processbytemap function
processingmode function
quadruple function
quadruplepoints function
quoted function
report function
scan table
F boolean

F cmykcolor
F color
F expression
F integer
F next
F number
F numeric
F pair
F path
F pen
F property
F string
F symbol
F token
F transform

F whatever

set	table
setbytemap	function
setbytemapoctave	function
size	function
skip	table

F token

solve	function
string	function
systemmode	function
transform	function
triplet	function
tripletpoints	function
vprint	function

mplib (extra tex)

downgradebytemap	function
downsamplebytemap	function
execute	function
expandtex	function
fillbytemap	function
finder	function
finders	table
F file	
F mpstemplate	
finish	function
getbytemap	function
getbytemapdata	function
getbytemapdirect	function
getcallbackstate	function
getcodes	function
getcolormodels	function
getfields	function
gethashentries	function
gethashentry	function
getinternalactions	function
getknotstates	function
getlastaddtype	function
getlogtargets	function
getobjectdata	function
getobjectpeninfo	function
getobjectstacking	function
getobjecttypes	function
getprimitivelegacies	function
getprimitiveorigins	function
getprimitives	function
getpruneoptions	function
getresultstates	function
getscaledbits	function
getscantypes	function
getstates	function
getstatistics	function
getstatus	function
gettolerance	function
gettype	function
gettypes	function
injectboolean	function
injectcmykcolor	function
injectcolor	function
injectinteger	function
injectnumber	function
injectnumeric	function
injectpair	function
injectpath	function
injectpoints	function
injectstring	function
injecttokens	function
injecttransform	function
injectvector	function
injectvectors	function
injectwhatever	function
new	overloaded function
newbytemap	function
peninfo	function
processbytemap	function
propertycodes	table
realtimelogging	boolean
scanboolean	function
scancmykcolor	function
scancolor	function
scanexpression	function
scaninteger	function
scannext	function
scannumber	function
scannumeric	function
scanpair	function
scanpath	function
scanpen	function
scanproperty	function
scanstring	function
scansymbol	function
scantoken	function
scantransform	function
setbytemap	function
setbytemapoctave	function
settolerance	function
showcontext	function
skiptoken	function

solvepath function
version function

nanojpeg (context)

decode function

noads (context)

getmathmode function
handlers table
F alternates
F autofences
F classes
F collapse
F dictionaries
F export
F families
F fencing
F intervals
F kernpairs
F makeup
F normalize
F numbers
F relocate
F render
F showtree
F snap
F spacing
F suspicious
F tags
F unscript
F unstack
F variants
process function
processnested function
processors table
processouter function

node (basic tex)

checkdiscretionaries function
checkdiscretionary function
copy function
copylist function
count function
currentattributes function
dimensions function
direct table

- F addmargins
- F addxoffset
- F addxymargins
- F addyoffset
- F appendaftertail
- F appendcurrenttail
- F beginofmath
- F checkdiscretionaries
- F checkdiscretionary
- F collapsing
- F copy
- F copylist
- F copyonly
- F count
- F currentattributes
- F dimensions
- F effectiveglue
- F endofmath
- F exchange
- F fields
- F findattribute
- F findattributerange
- F findnode
- F firstchar
- F firstglyph
- F firstglyphnode
- F firstitalicglyph
- F flattendiscretionaries
- F flattenleaders
- F flushlist
- F flushnode
- F free
- F freeze
- F getanchors
- F getattribute
- F getattributelist
- F getattributes
- F getboth
- F getbottom
- F getbottomdelimiter
- F getbox
- F getcachestate
- F getchar
- F getchardict
- F getcharspec
- F getchoice
- F getclass
- F getcontinuation
- F getcontrol
- F getcornerkerns
- F getcurrenttail
- F getdata
- F getdegree
- F getdelimiter
- F getdenominator
- F getdepth
- F getdirection
- F getdisc
- F getdiscpart
- F getexcept
- F getexpansion
- F getfam
- F getfield
- F getfielderror
- F getfirstdirectioninlist
- F getfont
- F getfontcheck
- F getgeometry
- F getglue
- F getglyphdata
- F getglyphdimensions
- F getheight
- F getid
- F getidsubtype

F getidsubtypenext
F getindex
F getinputfields
F getkern
F getkerndimension
F getlanguage
F getleader
F getleftdelimiter
F getlist
F getlistdimensions
F getlocalparboxstate
F getmvllist
F getnaturalwhd
F getnext
F getnodeerrorvalues
F getnodes
F getnormalizedline
F getnucleus
F getnumerator
F getoffsets
F getoptions
F getorientation
F getparstate
F getpenalty
F getpost
F getpre
F getprev
F getprime
F getpropertiestable
F getproperty
F getreplace
F getrightdelimiter
F getruledimensions
F getscale
F getscales
F getscript
F getscripts
F getshift
F getshort
F getslant
F getspeciallist
F getstate
F getsub
F getsubpre
F getsubtype
F getsup
F getsuppre
F gettop
F gettopdelimiter
F gettotal
F getusage
F getusedattributes
F getweight
F getwhd
F getwidth
F getwordrange
F getxscale
F getxyscales
F getyscale
F gluetostring
F hasattribute
F hasdimensions
F hasdiscoption
F hasfield
F hasgeometry
F hasglyph
F hasglyphoption
F hasidsubtype
F hasoptions
F hasusage
F hpack
F hyphenating
F id
F ignoremathskip
F insertafter
F insertbefore
F insertcurrenthead
F isboth
F ischar
F ischarcheck
F ischardisc
F ischardiscsetcheck
F isdirect
F isfontcheck
F isglyph
F isitalicglyph
F isloop
F isnext

F isnextchar
F isnextcharcheck
F isnextcharsetcheck
F isnextglyph
F isnode
F isprev
F isprevchar
F isprevcharcheck
F isprevcharsetcheck
F isprevglyph
F issimilarglyph
F issnapped
F isspeciallist
F isvalid
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F makeextensible
F markglyphprocessing
F migrate
F mlisttohlist
F naturalhsize
F naturalwidth
F new
F newcontinuationatom
F newfontcheck
F newmathglyph
F newtextglyph
F patchattributes
F patchparshape
F prependbeforehead
F prependcurrenttail
F protectglyph
F protectglyphs
F protectglyphsbase
F protectglyphsnone
F protrusionskippable
F rangedimensions
F remove
F removefromlist
F repack
F reverse
F samefontcheck
F serialized
F setanchors
F setattribute
F setattributelist
F setattributes
F setattributesinlist
F setboth
F setbottom
F setbottomdelimiter
F setbox
F setchar
F setchardict
F setchoice
F setclass
F setcontinuation
F setcontrol
F setcurrenttail
F setdata
F setdegree
F setdelimiter
F setdenominator
F setdepth
F setdirection
F setdisc
F setdiscpart
F setexcept
F setexpansion
F setfam
F setfield
F setfielderror
F setfont
F setfontcheck
F setgeometry
F setglue
F setglyphdata
F setheight
F setindex
F setinputfields
F setkern
F setlanguage
F setleader
F setleftdelimiter
F setlink

F setlist
F setnext
F setnucleus
F setnumerator
F setoffsets
F setoptions
F setorientation
F setpenalty
F setpost
F setpre
F setprev
F setprime
F setproperty
F setreplace
F setrightdelimiter
F setruledimensions
F setscale
F setscales
F setscript
F setscripts
F setshift
F setslant
F setsnapped
F setspeciallist
F setsplit
F setstate
F setsub
F setsubpre
F setsubtype
F setsup
F setsuppre
F settop
F settopdelimiter
F settotal
F setweight
F setwhd
F setwidth
F show
F size
F slide
F softenhyphens
F startofpar
F subtypes
F tail
F todirect
F tonode
F tostring
F tovaliddirect
F traverse
F traversechar
F traversecontent
F traverseglyph
F traverseid
F traverseitalic
F traverseleader
F traverselist
F traversepossible
F type
F types
F unprotectglyph
F unprotectglyphs
F unsetattribute
F unsetattributes
F updatefirstandbotmark
F updatefirstmarks
F updatemarks
F updatetopmarks
F usedlist
F usesfont
F vbalance
F verticalbreak
F vpack
F write
F xscaled
F yscaled

effectiveglue function
endofmath function
family_font function
fields function
findattribute function
flattendiscretionaries function
flushlist function
flushnode function
free function
getattribute function
getcachestate function
getfield function
getfielderror function

getglue	function	**rangedimensions**	function
getnodeerrorvalues	function	**remove**	function
getpropertiestable	function	**serialized**	function
getproperty	function	**setattribute**	function
gluetostring	function	**setfield**	function
hasattribute	function	**setfielderror**	function
hasfield	function	**setglue**	function
hasglyph	function	**setproperty**	function
hpack	function	**show**	function
hyphenating	function	**size**	function
id	function	**slide**	function
insertafter	function	**subtypes**	function
insertbefore	function	**tail**	function
instock	function	**todirect**	function
intracking	function	**tonode**	function
inuse	function	**tostring**	function
isnode	function	**traverse**	function
iszeroglue	function	**traverseid**	function
kerning	function	**type**	function
lastnode	function	**types**	function
length	function	**unprotectglyph**	function
ligaturing	function	**unprotectglyphs**	function
makeextensible	function	**unsetattribute**	function
mlisttohlist	function	**usedlist**	function
new	function	**usesfont**	function
protectglyph	function	**vpack**	function
protectglyphs	function	**write**	function
protrusionskippable	function		

nodes (context)

accentcodes data table
adaptive table
F handlehorizontal
F handlevertical
F set
aligned function
append function
apply function
applyvisuals function
astable function
basepoints function
boundarycodes data table
boxes table
F count
F dimensions
F direct
F dispose
F found
F prune
F reset
F restore
F save
F savenode
builders table
choicecodes data table
concat function
copy function
copy_node function
copylist function
countall function
currentattributes function
delete function
destinations table
N attribute
F handler
dircodes data table
directioncodes data table
directionvalues data table
dirvalues data table
disccodes data table
discretionarycodes data table
fencecodes data table
fields function
fieldtypes table
fillcodes data table
fillvalues data table
firstdirinbox function
flush function
flushlist function
flushnode function
fractioncodes data table
fullhpack function
getattr function
getattribute function
getboth function
getbox function
getchar function
getfield function
getfont function
getid function
getleader function
getlist function
getnext function
getprev function
getproperty function
getsubtype function
gluecodes data table
glyphcodes data table
handlers table
F adjusters
F aligncharacter
F backgrounds
F backgroundspage
F backgroundsvbox
F characters
F checkglyphs
F checkparcounter
F cleanupbox
F cleanuppage
F export
F finalizebox
F finalizelist

F flatten
F flattenline
F mathalignrelocate
F mathmatrixornaments
F mathmatrixrules
F protectglyphs
F recolor
F show
F showhyphenation
F showpreamble
F stripping
F tabulateskip
F textbackgrounds
F unprotectglyphs
F visualizehyphenation
F wipe

hasattribute function
hasfield function
hpack function
idsandsubtypes function
idstostring function
injections table
F copy
F getligaindex
F getthreshold
F handler
F installgetspaceboth
F installnewkern
F isspace
F keepcounts
F reset
F resetcounts
F setcursive
F setkern
F setligaindex
F setmark
F setmove
F setposition
F setspacekerns
insertafter function
insertbefore function
insertlistafter function
installattributehandler function
is_display_math function
isdirect function
isnode function
isnut function
kerncodes data table
leftmarginwidth function
linefillers table
F filler
F handler
F set
lines table
D data
F finalize
F number
link function
linked function
list function
listcodes data table
listtoutf function
literalvalues data table
locate function
markcodes data table
markers table
F get
F set
mathcodes data table
mathvalues data table
maxboxwidth function
new function
noadcodes data table
nodecodes data table
nopts function
nuts table
F addmargins
F addxoffset
F addxymargins
F addyoffset
F append
F appendaftertail
F apply
F applyvisuals
F beginofmath
F checkdiscretionaries
F checkdiscretionary
F checkslide

F collapsing
F concat
F copy
F copy_properties
F copylist
F copynode
F copyonly
F copyvisual
F count
F countall
F currentattributes
F delete
F dimensions
F dirdimensions
F effectiveglue
F endofmath
F exchange
F findattribute
F findattributerange
F findnode
F firstchar
F firstglyph
F firstglyphnode
F firstitalicglyph
F flattendiscretionaries
F flattenleaders
F flush
F flushlist
F flushnode
F free
F freeze
F fullhpack
F fullhpackrl
F getanchors
F getattr
F getattribute
F getattributelist
F getattributes
F getattrlist
F getattrs
F getboth
F getbottom
F getbottomdelimiter
F getbox
F getboxglue
F getchar
F getchardict
F getcharspec
F getchoice
F getclass
F getcomponents
F getcontinuation
F getcontrol
F getcornerkerns
F getdata
F getdegree
F getdelimiter
F getdenominator
F getdepth
F getdirection
F getdisc
F getdiscpart
F getdiscretionary
F getexcept
F getexpansion
F getfam
F getfield
F getfirstdirectioninlist
F getfont
F getfontcheck
F getgeometry
F getglue
F getglyphdata
F getglyphdimensions
F getheight
F getid
F getidsubtype
F getidsubtypenext
F getindex
F getinputfields
F getkern
F getkerndimension
F getlang
F getlanguage
F getleader
F getleftdelimiter
F getlist
F getlistdimensions

F getlocalparboxstate
F getmiddle
F getmiddledelimiter
F getmvllist
F getnaturalwhd
F getnext
F getnormalizedline
F getnucleus
F getnumerator
F getoffsets
F getoptions
F getorientation
F getparstate
F getpenalty
F getpost
F getpre
F getprev
F getprime
F getprop
F getreplace
F getrightdelimiter
F getruledata
F getruledimensions
F getscale
F getscales
F getscript
F getscripts
F getshift
F getshort
F getslant
F getspeciallist
F getstate
F getsub
F getsubpre
F getsubtype
F getsup
F getsuppre
F getsurround
F gettop
F gettopdelimiter
F gettotal
F getusedattributes
F getvalue
F getweight
F getwhd
F getwidth
F getwordrange
F getxscale
F getxyscales
F getyscale
F gluetostring
F hasattribute
F hasdimensions
F hasdiscoption
F hasfield
F hasgeometry
F hasglyph
F hasglyphoption
F hasidsubtype
F hasoptions
F hpack
F hyphenating
F ignoremathskip
F insertafter
F insertbefore
F insertlistafter
F is_display_math
F isboth
F ischar
F ischarcheck
F ischardiscsetcheck
F isdirect
F isdone
F isglyph
F isitalicglyph
F isnext
F isnextchar
F isnextcharcheck
F isnextcharsetcheck
F isnextglyph
F isnode
F isnut
F isprev
F isprevchar
F isprevcharcheck
F isprevcharsetcheck
F isprevglyph
F issimilarglyph

F issnapped
F iszeroglue
F kerning
F lastnode
F length
F ligaturing
F link
F linked
F locate
F migrate
F migratebox
F mlisttohlist
F naturalhsize
F naturalwidth
F nestedtracedslide
F new
F newcontinuationatom
F newfontcheck
F newmathglyph
F openup
F patchattributes
F patchparshape
F prepend
F prependbeforehead
F processranges
F processwords
F protectglyph
F protectglyphs
F protectglyphsbase
F protectglyphsnone
F protrusionskippable
F rangedimensions
F rawprop
F reference
F rehpack
F remove
F removefromlist
F repack
F repackhlist
F replace
F reverse
F serialized
F setanchors
F setattr
F setattribute
F setattributelist
F setattributes
F setattributesinlist
F setattrlist
F setattrs
F setattrsinlist
F setboth
F setbottom
F setbox
F setboxglue
F setchar
F setchardict
F setchoice
F setclass
F setcomponents
F setcontinuation
F setcontrol
F setdata
F setdegree
F setdelimiter
F setdenominator
F setdepth
F setdirection
F setdisc
F setdiscpart
F setdiscretionary
F setexcept
F setexpansion
F setfam
F setfield
F setfont
F setfontcheck
F setgeometry
F setglue
F setglyphdata
F setheight
F setinputfields
F setkern
F setlang
F setlanguage
F setleader
F setleftdelimiter
F setlink

F setlist
F setmiddledelimiter
F setnext
F setnucleus
F setnumerator
F setoffsets
F setoptions
F setorientation
F setparproperty
F setpenalty
F setpost
F setpre
F setprev
F setprime
F setprop
F setreplace
F setrightdelimiter
F setruledata
F setruledimensions
F setscale
F setscales
F setscript
F setscripts
F setshift
F setslant
F setsnapped
F setspeciallist
F setsplit
F setstate
F setsub
F setsubpre
F setsubtype
F setsup
F setsuppre
F setsurround
F settop
F setvalue
F setvisual
F setvisuals
F setweight
F setwhd
F setwidth
F show
F slide
F softenhyphens
F somepenalty
F somespace
F splitbox
F startofpar
F striprange
F tail
F takeattr
F takebox
F takelist
F theprop
F tonode
F tonodes
F tonut
F tosequence
F tostring
F tracedslide
F traverse
F traversechar
F traversecontent
F traverseglyph
F traverseid
F traverseitalic
F traverseleader
F traverselist
F traversepossible
F unprotectglyph
F unprotectglyphs
F unsetattribute
F unsetattributes
F untracedslide
F updatefirstandbotmark
F updatefirstmarks
F updatemarks
F updatetopmarks
F usedlist
F usesfont
F verticalbreak
F vianodes
F vianuts
F vpack
F write
F xscaled
F yscaled

packlist function
parcodes data table
penaltycodes data table
points function
pool table
F baselineskip
F cleanup
F directliteral
F glyph
F hlist
F latelua
F leader
F lineskip
F literal
F originliteral
F register
F restore
F save
F savepos
F setmatrix
F stock
F usage
F usernode
F vlist
prepend function
print function
processors table
F trace_glyph_run_a
F trace_glyph_run_b
properties table
pts function
radicalcodes data table
references table
N attribute
F handler
rehpack function
remove function
repackhlist function
replace function
report function
rightmarginwidth function
rulecodes data table
rules table
F handler
F process
F set
F userrule
serialize function
serializebox function
serialized function
setattr function
setattribute function
setattrlist function
setboth function
setbox function
setboxtonaturalwd function
setchar function
setfield function
setfont function
setleader function
setlink function
setlist function
setnext function
setprev function
setproperty function
shadows table
F handler
F set
shifts table
F handler
F set
showboxes function
showlist function
showsimplelist function
skipcodes data table
snapshots table
F getsamples
F resetsamples
F takesample
somepenalty function
somespace function
specialskipcodes table
splitbox function
startofpar function
stripdiscretionaries function
stripping table
F set
subtypes data table

tail function
takeattr function
takebox function
tasks table
F actions
F appendaction
F disableaction
F disablegroup
F enableaction
F enablegroup
F freeze
F freezegroup
F new
F prependaction
F removeaction
F replaceaction
F restart
F setaction
F showactions
F table
tobasepoints function
tocentimeters function
tociceros function
todidots function
todimen function
toinches function
tomillimeters function
tonode function
tonodes function
tonut function
topicas function
topoints function
toscaledpoints function
tosequence function
tostring function
totable function
totree function
toutf function
tracers table
F directions
F fontchar
F resetproperties
F rule
F setlist
F setproperties
F start
F stop
traverse function
traverseid function
typesetters table
F hbox
F hpack
F tohbox
F tohpack
F tonodes
F tovbox
F tovpack
F vpack
unsetattribute function
upcomingproperties function
usedlist function
vianodes function
vianuts function
visualizebox function
visualizers table
F attribute
F box
F definelayer
F enable
F getusedfont
F handler
F markfonts
F register
F registercache
F setfont
F setlayer
F setruledglyph
F setvisual
vpack function
whatsitcodes data table
write function

number (context)

	function
basepoints	function
bytetodecimal	function
clamp	function
compactfloat	function
decimaltobyte	function
dimenfactors	data table
fractiontobyte	function
idiv	function
maxdimen	number
nopts	function
percent	function
points	function
pts	function
splitdimen	function
to16dot16	function
tobasepoints	function
tobitstring	function
tocentimeters	function
tociceros	function
tocontext	function
todidots	function
todimen	function
toediths	function
toinches	function
tomillimeters	function
tonumberf	function
tonumberg	function
topicas	function
topoints	function
toscaled	function
toscaledpoints	function
totoves	function
valid	function

objects (context)

data	table	**page**	function
dimensions	function	**reference**	function
found	function	**register**	function
n	number	**restore**	function

optional (context)

curl table
- F escape
- F fetch
- F getversion
- F initialize
- F unescape

foreign table
- F abivalues
- F getbuffer
- F initialize
- F load
- F newbuffer
- F totable
- F types

ghostscript table
- F execute
- F initialize

graphicsmagick table
- F execute
- F getnoisetypes
- F initialize

hb table
- F getshapers
- F getversion
- F initialize
- F loadfont
- F shapestring

imagemagick table
- F execute
- F initialize

kpse table
- F expand_braces
- F expand_path
- F expand_var
- F find_file
- F find_files
- F get_file_types
- F initialize
- F readable_file
- F set_program_name
- F var_value

library table
- F load

loaded table

lz4 table
- F compress
- F decompresssize
- F framecompress
- F framedecompress
- F initialize

lzma table
- F compress
- F decompress
- F initialize

lzo table
- F compress
- F decompresssize
- F initialize

mujs table
- F dofile
- F execute
- F initialize
- F reset
- F setclosefile
- F setconsole
- F setfindfile
- F setopenfile
- F setreadfile
- F setseekfile

mysql table
- F close
- F execute
- F getmessage
- F initialize
- F open

openssl table
- F getversion
- F initialize
- F sign
- F verify

postgress table
- F close

F execute
F getmessage
F initialize
F open

sqlite table
F close
F execute
F getmessage
F initialize
F open

zint table
F execute
F initialize

zstd table
F compress
F decompress
F initialize

os (basic lua)

__getenv__	function	**platform**	string
__setenv__	function	**remove**	function
binsuffix	string	**rename**	function
binsuffixes	table	**resultof**	function
bits	number	**runtime**	function
clock	function	**selfarg**	table
converttime	function	**selfbin**	string
date	overloaded function	**selfcore**	string
difftime	function	**selfdir**	string
enableansi	function	**selflink**	string
env	data table	**selfname**	string
execute	overloaded function	**selfpath**	string
exit	overloaded function	**serialwrite**	function
fulltime	function	**setenv**	overloaded function
getcodepage	function	**setexitcode**	function
getenv	overloaded function	**setlocale**	overloaded function
getnamevalues	function	**sleep**	function
gettimeofday	function	**startuptime**	function
gettypevalues	function	**time**	function
getunamefields	function	**timezone**	function
isleapyear	function	**tmpname**	function
launch	overloaded function	**today**	function
libsuffix	string	**type**	string
localtime	function	**uname**	function
name	string	**uuid**	function
newline	string	**validdate**	function
nofdays	function	**weekday**	function
now	function	**where**	function
pipeto	function	**which**	function

package (basic lua)

config	string	**loadlib**	function
cpath	string	**luapaths**	function
extralibpath	function	**path**	string
extralibpaths	function	**poplibpath**	function
extraluapath	function	**popluapath**	function
extraluapaths	function	**preload**	table
helpers	table	**pushlibpath**	function
libpaths	function	**pushluapath**	function
loaded	table	**searchers**	table
loaders	table	**searchpath**	function

pagebuilders (context)

columnsets table

- F add
- F addmvl
- F block
- F blockrows
- F check
- F checkmvl
- F clean
- F define
- F definesub
- F delayedsheet
- F finishflush
- F flushareas
- F flushcolumn
- F goto
- F gotoslot
- F limit
- F noto
- F prepareflush
- F presetsheets
- F presetspreadsheets
- F put
- F putdirect
- F registerarea
- F registersheet
- F registerspreadsheets
- F reset
- F resetdirect
- F reshape
- F setarea
- F setextra
- F sethsize
- F sethspan
- F setlines
- F setmvl
- F setpresent
- F setproperties
- F setstart
- F shape
- F showshape
- F state
- F status
- F submvl
- F submvlbalance

injections table

- F flushafter
- F flushbefore
- F save

mixedcolumns table

- F cleanup
- F finalize
- F getlist
- F getrest
- F getsplit
- F setsplit

pdf (context)

immediateobj function

pdfe (extra tex)

arraytotable	function
close	function
closestream	function
dictionarytotable	function
getarray	function
getboolean	function
getbox	function
getcatalog	function
getdictionary	function
getencodingvalues	function
getfieldtypes	function
getfromarray	function
getfromdictionary	function
getfromobject	function
getfromreference	function
getfromstream	function
getinfo	function
getinteger	function
getmemoryusage	function
getname	function
getnofobjects	function
getnofpages	function
getnumber	function
getobjectrange	function
getpage	function
getpages	function
getpermissions	function
getsize	function
getstatus	function
getstatusvalues	function
getstream	function
getstring	function
gettrailer	function
getversion	function
new	function
open	function
openfile	function
openstream	function
pagestotable	function
readfromstream	function
readwholestream	function
type	function
unencrypt	function

physics (context)

units table

F registershortcut

F registerunit

D tables

pngdecode (extra tex)

applyfilter	function
expand	function
frompalette	function
interlace	function
makemask	function
palettemask	function
reduce	function
setexperiment	function
splitmask	function
tocmyk	function
togray	function
tomask	function
transparentmask	function

posit (extra lua)

NaN	function
NaR	function
__add	function
__band	function
__bor	function
__bxor	function
__div	function
__eq	function
__le	function
__lt	function
__mul	function
__name	string
__pow	function
__shl	function
__shr	function
__sub	function
__tostring	function
__unm	function
abs	function
acos	function
asin	function
atan	function
band	function
bor	function
bxor	function
ceil	function
conj	function
copy	function
cos	function
exp	function
exp2	function
expand	function
floor	function
frombyte	function
fromchar	function
fromposit	function
integer	function
log	function
log10	function
log1p	function
log2	function
logb	function
max	function
min	function
modf	function
new	function
pow	function
rotate	function
round	function
rounded	function
shift	function
sin	function
sqrt	function
tan	function
tobyte	function
tochar	function
tonumber	function
toposit	function
tostring	function

potrace (extra tex)

checked	function	**getnewfields**	function
concat	function	**getpolicyvalues**	function
contourplot	function	**getprocessfields**	function
convert	function	**new**	function
count	function	**process**	function
flush	function	**setbitmap**	function
free	function	**stripped**	function
fromfile	function	**totable**	function
getbitmap	function	**trace**	function

process (context)

__gc	function	**open**	function
__name	string	**poll**	function
__tostring	function	**read**	function
close	function	**tostring**	function

publications (context)

addtexentry function
analyze function
anywhere function
authorcache data table
authorcollapsers data table
authorhashers table
F invertedshort
F normal
F normalinverted
F normalshort
F sequential
F sequentialshort
F short
authormap data table
authortoregister function
btx table
casters table
F author
F keyword
F pagenumber
F range
checkeddataset function
citevariants table
F author
F authornum
F authoryear
F authoryears
F category
F default
F entry
F index
F keywords
F num
F page
F short
F tag
F textnum
F year
collected data table
components table
F author
concatstate function
converttoxml function
currentspecification table
S author
S comment
S copyright
S name
S version
D virtual
datasets table
detailed table
endnotes_to_btx function
enhancer table
S arguments
B dirty
N steps
enhancers table
F details
F order
F suffixes
finder function
firstofrange function
found function
get function
getcasted function
getdetail function
getdirect function
getfaster function
getfield function
getfuzzy function
getindex function
inspectors data table
journals table
F abbreviated
F add
F expanded
F load
F save
lastofrange function
lists table
F collectentries

F combiinlist
F fetchentries
F filterall
F flushcombi
F flushentry
F flushtag
F nofregistered
F prepareentries
F register
F sameasprevious
F uservariable
listvariants table
F default
F index
F num
F short
F tag
load function
loadbibdata function
loaddefinitionfile function
loaders table
F bbl
F bib
F buffer
F endnote
F json
F lua
F refman
F registercleaner
F xml
loadreplacementfile function
meanings table
new function
okay function
oneorrange function
parenttag function
permitted function
prerollcmdstring function
refman_to_btx function
resolvedname function
save function
savers table
F bib
F lua
F xml
search function
setcategory function
setspecification function
singularorplural function
sortedentries function
sortmethods table
specifications table
splitauthor function
splitoneauthor function
statistics table
N nofbytes
N nofdatasets
N nofdefinitions
N nofshortcuts
tables table
D implicits
D origins
D privates
D sets
D specials
D types
D virtuals
tags function
tracers table
F showdatasetauthors
F showdatasetcompleteness
F showdatasetfields
F showentry
F showfields
F showhashedauthors
F showtables
F showvariants
typesetters table
F author
F string
usedataset function
usedentries function
writers table
F author
F keyword
F pagenumber
F range

qrcodegen (context)

bitmap function
generate function

regimes (context)

backmapping	data table	**mapping**	data table
cleanup	function	**pop**	function
disable	function	**process**	function
enable	function	**push**	function
fromregime	function	**toregime**	function
list	function	**translate**	function

resolvers (context)

allprefixes function
appendhash function
automount function
booleanvariable function
cacheversion string
checkedvariable function
cleanedpathlist function
cleaners data table
cleanpath function
cleanpathlist function
cleanupbinfile function
concatinators data table
configbanner string
configurationfiles function
dangerous data table
datastate function
decompressors table
- F register
- F unregister

defaultsuffixes table
dirstatus function
dowithfilesandreport function
dowithfilesintree function
dowithpath function
dowithvariable function
expandbraces function
expandedpathfromlist function
expandedpathlist function
expandedpathlistfromvariable function
expandpath function
expandpathfromvariable function
expansion function
extendtexmfvariable function
filtered_from_content function
find_file function
find_files function
findbinfile function
findctxfile function
finders data table
findfile function
findfiles function
findgivenfile function
findgivenfiles function
findlib function
findpath function
findpk function
findtexfile function
findwildcardfile function
findwildcardfiles function
formatofsuffix function
formatofvariable function
formats data table
foundintree function
foundintrees function
generators data table
get_from_content function
getdetails function
getenv function
getextrapaths function
getfilehashes function
gethashes function
getownpath function
getreadfilename function
hashers data table
homedir string
ignorelibrary function
initialized function
installinputfilehandler function
installinputlinehandler function
jobpath function
jobs table
- F collectstructure
- F currentcomponent
- F currentenvironment
- F currentproduct
- F currentproject
- F currentstructure
- F justacomponent
- F namelist
- D processors
- F productcomponent
- F usefile

joinpath function
knownvariables function
libraries table
F optionalloaded
F validoptional
load function
loadbinfile function
loaders data table
loadlualib function
loadtexfile function
loadtime function
locateformat function
locators data table
luacnffallback string
luacnfname string
luacnfspec string
luacnfstate string
macros table
F convertfile
F decodecomment
F enablecomment
F encodecomment
F preprocessed
F processmk
F processmklx
F processmkvi
F version
maxreadlevel number
methodhandler function
missinglibrary function
openbinfile function
openers data table
openfile function
opentexfile function
ownpath string
popextrapath function
popinputname function
poppath function
prefixes data table
prependhash function
pushextrapath function
pushinputname function
pushpath function
registerextrapath function
registerfile function
registerfilehash function
registerintrees function
registermethod function
registerzipfile function
relations data table
renew function
renewcache function
repath function
reset function
resetextrapaths function
resetresolve function
resolve function
savers data table
scandata function
scanfiles function
schemes table
F cleanname
F fetchstring
F fetchtable
F install
setdynamic function
setenv function
showdetails function
showpath function
simplescanfiles function
splitconfigurationpath function
splitexpansions function
splitmethod function
splitpath function
stackpath function
starttiming function
stoptiming function
suffixes data table
suffixmap data table
suffixofformat function
texdatablob function
toppath function
tracers data table
unexpandedpath function
unexpandedpathlist function
unresolve function
updaterelations function
uselibrary function

usertypes	data table	**variableofformat**	function
usezipfile	function	**variableofformatorsuffix**	function
validatedpath	function	**wildcardpattern**	function
variable	function		

sandbox (context)

enable	function	**registerrunner**	function
getrunner	function	**setfilenamelogger**	function
possiblepath	function		

scripts (context)

autofontfeature table
- F disable
- F enable
- F handler

colors data table

decomposehangul function

defaults table
- N inter_char_half_shrink_factor
- N inter_char_half_stretch_factor
- N inter_char_hangul_penalty
- N inter_char_quarter_shrink_factor
- N inter_char_quarter_stretch_factor
- N inter_char_shrink_factor
- N inter_char_stretch_factor
- N inter_word_stretch_factor

getdata function

getinjector function

getsplitter function

getstatus function

handlers data table

helpers data table

injectors data table

inserters table
- F nobreakspace_after
- F nobreakspace_before
- F space_after
- F space_before
- F zerowidthspace_after
- F zerowidthspace_before

installdataset function

installmethod function

numbertodataset data table

numbertohandler data table

reset function

set function

setstatus function

splitters data table

security (context)

checked	function	**resetdebug**	function
getactions	function	**setchecker**	function
gettargets	function		

sequencer (context)

addbytestobuffer function
addformattobuffer function
addpackingtobuffer function
addtobuffer function
extensions table
- F chruni
- F date
- F daylong
- F dayoftheweek
- F dayshort
- F edate
- F eday
- F edaylong
- F edayshort
- F eminute
- F emonth
- F emonthlong
- F emonthshort
- F esecond
- F eweek
- F eweekday
- F eyear
- F font:features
- F font:name
- F lua
- F monthlong
- F monthshort
- F tex
- F texexp
- F unichr
- F weekday
- F xml

fastserialize function
format function
getbufferdata function
getbuffersize function
newbuffer function
sequenced function
serialize function
sortedhash function
tabstr_boolean function
tabstr_flat function
tabstr_mixed function
tabstr_normal function
tostring function

serial (context)

__gc	function	**open**	function
__name	string	**send**	function
__tostring	function	**tostring**	function
close	function	**write**	function

server (context)

httpserver function
supported function

set (context)

contains function
create function
tolist function
tonumber function
totable function

sha2 (extra lua)

HASH256	function	**hash256**	function
HASH384	function	**hash384**	function
HASH512	function	**hash512**	function
HEX256	function	**hex256**	function
HEX384	function	**hex384**	function
HEX512	function	**hex512**	function
digest256	function	**sum256**	function
digest384	function	**sum384**	function
digest512	function	**sum512**	function

sio (extra lua)

read2dot14	function	**readinteger3**	function
readbytes	function	**readinteger3le**	function
readbytetable	function	**readinteger4**	function
readcardinal1	function	**readinteger4le**	function
readcardinal1le	function	**readintegertable**	function
readcardinal2	function	**tocardinal1**	function
readcardinal2le	function	**tocardinal1le**	function
readcardinal3	function	**tocardinal2**	function
readcardinal3le	function	**tocardinal2le**	function
readcardinal4	function	**tocardinal3**	function
readcardinal4le	function	**tocardinal3le**	function
readcardinaltable	function	**tocardinal4**	function
readcline	function	**tocardinal4le**	function
readcstring	function	**tocardinal8**	function
readdouble	function	**tocardinal8le**	function
readdoublele	function	**tointeger1**	function
readfixed2	function	**tointeger1le**	function
readfixed4	function	**tointeger2**	function
readfloat	function	**tointeger2le**	function
readfloatle	function	**tointeger3**	function
readfloatle12	function	**tointeger3le**	function
readfloatle6	function	**tointeger4**	function
readinteger1	function	**tointeger4le**	function
readinteger1le	function	**tointeger8**	function
readinteger2	function	**tointeger8le**	function
readinteger2le	function		

sorters (context)

basicsorter function
comparers table
F basic
constants table
S defaultdigits
S defaultlanguage
S defaultmethod
N digitsmaximum
N digitsoffset
N ignoredoffset
N replacementoffset
definitions data table
firstofsplit function
packch function
packuc function
replacementlist function
setlanguage function
sort function
splitters table
F utf
strip function
tracers data table
update function

sparse (extra lua)

concat	function	**range**	function
get	function	**restore**	function
max	function	**set**	function
min	function	**traverse**	function
new	function	**wipe**	function

statistics (context)

benchmarktimer function
checkfmtstatus function
currenttime function
elapsed function
elapsedindeed function
elapsedseconds function
elapsedtime function
enable boolean
feedback table
- F info
- F processstates
- F register
- F reportstates
- F setstate

formatruntime function
istiming function
memused function
register function
resettiming function
runtime function
savefmtstatus function
show function
showmemory function
showusage function
starttiming function
stoptiming function
threshold number
timed function
tracefunction function

status (basic tex)

getbalancestate	function	**getluastate**	function
getbufferstate	function	**getmarkstate**	function
getcallbackstate	function	**getmvlstate**	function
getconstants	function	**getneststate**	function
getdumpstate	function	**getnodestate**	function
geterrorlinestate	function	**getparameterstate**	function
geterrorstate	function	**getpoolstate**	function
getexpandstate	function	**getreadstate**	function
getfilestate	function	**getsavestate**	function
getfontstate	function	**getsparsestate**	function
gethalferrorlinestate	function	**getstringstate**	function
gethashstate	function	**gettexstate**	function
gethyphenationstate	function	**gettokenstate**	function
getinputstate	function	**getwarningstate**	function
getinsertstate	function	**iocodes**	table
getlanguagestate	function	**list**	function
getlinebreakstate	function	**resetmessages**	function
getlookupstate	function		

storage (context)

allocate	function	**noftables**	number
data	table	**register**	function
mark	function	**shared**	data table
marked	function	**storedfunctions**	data table
max	number	**strip**	boolean
min	number	**tofmodules**	number
nofmodules	number	**toftables**	number

streams (context)

collect	function	**push**	function
disable	function	**start**	function
enable	function	**stop**	function
flush	function	**synchronize**	function
initialize	function		

string (basic lua)

booleanstring	function	linetable	function
byte	function	longtostring	function
bytepairs	function	lower	function
bytes	function	match	function
bytetable	function	nospaces	function
char	function	octtointeger	function
characterpairs	function	optionalquoted	function
characters	function	pack	function
checkedsplit	function	packrowscolumns	function
chrtointeger	function	packsize	function
collapsespaces	function	quote	function
containsws	function	quoted	function
count	function	rep	function
dectointeger	function	replacenewlines	function
dump	function	reverse	function
escapedpattern	function	split	function
f6	function	splitintolines	function
fd	function	splitlines	function
fd3	function	splitup	function
fd6	function	strip	function
fd9	function	sub	function
find	function	texhashed	function
format	function	texnewlines	function
formatted	function	tformat	function
formatter	function	toHEX	function
formatters	function	toboolean	function
formatting	function	tobytes	function
fromunicode16	function	tocontext	function
fullstrip	function	todec	function
g6	function	todimen	function
gd	function	tohex	function
gmatch	function	tonodes	function
gsub	function	topattern	function
hashes	table	topdfeight	function
hextocharacters	function	topdfsixteen	function
hextointeger	function	topdfstring	function
is_boolean	function	totable	function
is_empty	function	tounicode16	function
itself	function	toutf	function
len	function	toutf16	function
limit	function	toutf32	function

toutf8	function	**utflength**	function
unpack	function	**utfpadd**	function
unquote	function	**utftabletostring**	function
unquoted	function	**utfvalue**	function
upper	function	**utfvalues**	function
utf16toutf8	function	**utfvaluetable**	function
utfcharacter	function	**valid**	function
utfcharacters	function	**wordsplitter**	function
utfcharactertable	function		

structures (context)

atlocation function
blocks table
- D collected
- F define
- F empty
- F print
- F save
- F select
- F setstate
- D states
- D tobesaved
- F uservariable

bookmarks table
- F finalize
- F flatten
- F installhandler
- F merge
- S method
- F overload
- F place
- F register
- F setopened
- F setup

counters table
- F add
- F analyze
- F check
- D collected
- F compact
- F converted
- F currentvalue
- D data
- F define
- F first
- F get
- F isset
- F last
- F next
- F prev
- F previous
- F raw
- F record
- F reset
- F restart
- F restore
- F save
- F set
- F setlevel
- F setoffset
- F setown
- F setstate
- F setvalue
- F subs
- D tobesaved
- F value
- F way

currentsectionnumber function
descriptions table
documents table
- D data
- F initialize
- F preset
- F reset

floats table
formulas table
helpers table
- F analyze
- F formulanumber
- F merged
- F page
- F pageofinternal
- F prefix
- F prefixlastpage
- F prefixpage
- F simplify
- F title
- F touserdata

inserts table
- F attach
- D data
- F define
- F detach

F getdata
F getlocation
F getname
F getnumber
F nofdetached
F setlocation
F setup
D stored

itemgroups table

D collected
D tobesaved

lists table

F addto
F analyze
F bookmark
D cached
D collected
F discard
F enhance
F external
F filter
F formulanumber
F getresult
F groupindex
F hasnumberdata
F haspagedata
F hastitledata
F integrate
F iscached
D kinds
F label
F location
D names
F number
D ordered
F page
F popnesting
F prefix
F prefixednumber
F prefixedpage
F process
D pushed
F pushnesting
F rawnumber
F rawrealpage
F rawuserpage
F realpage
F reorder
F reordered
F savedlistnumber
F savedlistprefixednumber
F savedlisttitle
D sectionblocks
F size
F title
D tobesaved
F use
F userdata
F userpage
F uservalue

marks table

F number
F title

notes table

F checkpagechange
F define
F flushrange
F get
F getdeltapage
F getinternal
F getn
F getstate
F getstorecount
F getstoreflushed
F hascontent
F internal
F internalid
F listindex
D numbers
F ordered
F postpone
F resetpostponed
F restore
F save
F setstate
D states
F store

pages table

F allmarked
F analyze
D collected
F fraction
F getlabels
F in_body
F is_odd
F mark
F marked
F markedlist
N nofpages
F number
F on_right
F save
D tobesaved
F toranges

references table

F analyze
F checked
F checkedfile
F checkedfileorurl
F checkedprogram
F checkedrealpage
F checkedurl
D collected
U componentsplitter
F currentmetadata
F currentorder
D currentset
F define
D defined
D derived
F enhance
D executers
F export
F filter
F filterdefault
D filters
D flaginternals
F forceinnermode
F from
D functions
F get
F getcurrentlabel
F getcurrentmetadata
F getcurrentprefixspec
F getinnermethod
F getinternalcachedlistreference
F getinternallistreference
F getinternalreference
F getoutermethod
D handlers
F identify
F import
F inject
F injectcurrentset
S innermethod
F integrate
D internals
F load
F loadpresets
F mark
S outermethod
F pagefromhash
D pages
U prefixsplitter
D productdata
F realpageofpage
F referenced
U referencesplitter
D referred
F referredpage
F registerfinalizer
F registerinitializer
F registerpage
F reset
D runners
F set
F setandgetattribute
F setinternalreference
F setlinkmethod
F setnextinternal
F setnextorder
F setreferencerealpage
F setstructure
D specials
F splitcomponent
F splitprefix

F splitreference
F synchronizepage
D tobereferred
D tobesaved
D tracedpages
D usedinternals
D usedviews
F valid

registers table

F analyze
D collected
F compare
F define
F enhance
F extend
F filter
F filtercollected
F finalize
F findinternal
F flush
F get
F integrate
F prepare
F process
F setmethod
F sort
F store
D tobesaved
F tweak
F unique
F use
F userdata

sections table

F autodepth
F cct
D collected
F current
F currentblock
F currentid
F currentlevel
F currentsectionindex
F depthnumber
F finddata
F findnumber
F fullnumber
F getcurrentlevel
F getlevel
F getnumber
F internalreference
D levelmap
D levels
F matchingtilldepth
F numberatdepth
F numbers
F popblock
F prefixedconverted
F pushblock
F register
D registered
F reportstructure
F save
F set
F setblock
F setchecker
F setentry
F setinitialblock
F setlevel
F setnumber
F showstructure
F structuredata
F title
D tobesaved
F typesetnumber
F userdata
B verbose

sets table

F define
F get
F getall
D setlist

specials table

D collected
F retrieve
F store
D tobesaved

synonyms table

F analyzed
D collected

F compare
F define
F enhance
F filter
F finalize
F firstuserpage
F flush
F isshown
F isused
F meaning
F pages
F prepare
F process
F register
F registershown
F registerused
F reset
F resetall
F resetlist
F resetshown
F resetused
F sort
F synonym
D tobesaved
F userpages

tags table

F analyze
F checknesting
F current
F elementtag
F enabled
F exportbox
F finishexport
F getdescriptionindex
F getextradata
F getid
F getitemgroup
F getmetadata
F getoption
F getsorting
F getsynonym
F gettablecell
F gettabulatecell
F gettagreferencedescription
F handler
F initializeexport
D labels
F last
F lastinchain
F localexport
F locatedtag
D overloads
F pop
D properties
F push
F registerextradata
F registermetadata
F restart
F setaspect
F setattributehash
F setcodepoint
F setcombination
F setcombinationpair
F setconstruct
F setdescriptionindex
F setfigure
F setfloat
F setformulacontent
F sethighlight
F setitem
F setitemgroup
F setmpgraphic
F setnotation
F setnotationsymbol
F setparagraph
F setproperty
F setpublication
F setregister
F setsorting
F setsynonym
F settablecell
F settabulatecell
F settagdelimitedsymbol
F settagsubsentencesymbol
F setupexport
F setuserproperties
D specifications
F start

F stop

F strip

D taglist

table (basic lua)

append	function	**pack**	function
are_equal	function	**prepend**	function
combine	function	**print**	function
compact	function	**remove**	function
concat	function	**reverse**	function
contains	function	**reversed**	function
copy	function	**save**	function
count	function	**sequenced**	function
create	function	**serialize**	function
derive	function	**setmetatablecall**	function
deserialize	function	**setmetatableindex**	function
fastcopy	function	**setmetatableindices**	function
fastserialize	function	**setmetatablenewindex**	function
filtered	function	**sort**	function
flattened	function	**sorted**	function
fromhash	function	**sortedhash**	function
getn	function	**sortedhashkeys**	function
has_one_entry	function	**sortedhashonly**	function
hashed	function	**sortedindexonly**	function
identical	function	**sortedkeys**	function
imerge	function	**sortedpairs**	function
imerged	function	**sparse**	function
insert	function	**strip**	function
is_empty	function	**sub**	function
keys	function	**swapped**	function
load	function	**tocontext**	function
loweredkeys	function	**tocsv**	function
makeweak	function	**tofile**	function
merge	function	**tohash**	function
merged	function	**toxml**	function
mirrored	function	**unique**	function
move	function	**unpack**	function

tex (basic tex)

amcode	table
attribute	table
attributetracking	function
automigrationcodes	data table
autoparagraphcodes	data table
badness	function
badnessmodecodes	data table
balance	function
balancecallbackcodes	data table
boundaries	table
D names	
D numbers	
F system	
box	table
boxcontinuationcodes	data table
boxoptioncodes	data table
boxresources	table
F getbox	
F getdimensions	
F save	
F use	
breakcodes	data table
buildcodes	data table
catcode	table
cccode	table
charactercontrolcodes	data table
charactertagcodes	data table
chardef	function
classoptioncodes	data table
codes	table
conditionals	data table
constants	data table
count	table
cprint	function
ctdcatcodes	number
ctxcatcodes	number
definefont	function
delcode	table
dimen	table
dimensiondef	function
directioncodes	data table
directives	data table
discoptioncodes	data table
discpartcodes	data table
dontcomplain	function
doublescriptoptioncodes	data table
enableprimitives	function
equal	function
error	function
expandasvalue	function
experiments	data table
extraprimitives	function
fatalerror	function
fillcodes	data table
flagcodes	data table
fontidentifier	function
fontname	function
forcehmode	function
forceinputstatefile	function
forceinputstateline	function
fprint	function
frozenparcodes	data table
get	function
getadjustoptionvalues	function
getalignmentcontextvalues	function
getamcode	function
getappendadjustcontextvalues	function
getappendmigratecontextvalues	function
getattribute	function
getautomigrationvalues	function
getautoparagraphvalues	function
getbadnessmodevalues	function
getbalancecallbackvalues	function
getbalanceparameterfields	function
getbalanceresultfields	function
getbalancestepoptionvalues	function
getbox	function
getboxcontinuationvalues	function
getboxdir	function
getboxoptionvalues	function
getboxresourcebox	function
getboxresourcedimensions	function

getbreakcontextvalues	function	**getinsertcategoryvalues**	function
getbuildcontextvalues	function	**getinsertcontent**	function
getcardinalvalue	function	**getinsertdepth**	function
getcatcode	function	**getinsertdistance**	function
getcccode	function	**getinsertheight**	function
getcharactercontrolvalues	function	**getinsertlimit**	function
getcharactertagvalues	function	**getinsertmaxplaced**	function
getcount	function	**getinsertmultiplier**	function
getcurrentmvl	function	**getinsertoptionvalues**	function
getdelcode	function	**getinsertsplitvalues**	function
getdelcodes	function	**getinsertwidth**	function
getdimen	function	**getintegervalue**	function
getdimensionvalue	function	**getinteraction**	function
getdirectionvalues	function	**getinteractionmodes**	function
getdiscoptionvalues	function	**getiovalues**	function
getdiscpartvalues	function	**getkerneloptionvalues**	function
getdoublescriptoptionvalues	function	**getkernoptionvalues**	function
getemptyparagraphmodevalues	function	**getlargestusedmark**	function
geterrorrecoverymodevalues	function	**getlccode**	function
geterrorvalues	function	**getlinebreakparameterfields**	function
getfillvalues	function	**getlinebreakresultfields**	function
getflagvalues	function	**getlinebreakstatevalues**	function
getfloat	function	**getlinedir**	function
getfontdimension	function	**getlist**	function
getfontoffamily	function	**getlistanchorvalues**	function
getfrozenparvalues	function	**getlistfields**	function
getglue	function	**getlistgeometryvalues**	function
getglueoptionvalues	function	**getlistsignvalues**	function
getglyphdata	function	**getlocalbox**	function
getglyphdiscvalues	function	**getlocalboxlocations**	function
getglyphoptionvalues	function	**getlocallevel**	function
getglyphprotectionvalues	function	**getmark**	function
getglyphscales	function	**getmarknames**	function
getglyphscript	function	**getmath**	function
getglyphstate	function	**getmathclassoptionvalues**	function
getgroupvalues	function	**getmathcode**	function
gethccode	function	**getmathcodes**	function
gethelptext	function	**getmathcontrolvalues**	function
gethmcode	function	**getmathdir**	function
gethyphenationvalues	function	**getmathgluevalues**	function
getiftypes	function	**getmathoptionvalues**	function
getinputstatefile	function	**getmathparametervalues**	function
getinputstateline	function	**getmathscriptordervalues**	function
getinputstatemode	function	**getmathscriptsmodevalues**	function

getmathstylenamevalues	function	**getrunstate**	function
getmathstylevalues	function	**getrunstatevalues**	function
getmathstylevariant	function	**getsfcode**	function
getmathsurroundvalues	function	**getshapingpenaltiesvalues**	function
getmathvariantpresets	function	**getskip**	function
getmathvariantvalues	function	**getsnappingvalues**	function
getmeasure	function	**getspacefactorvalues**	function
getmissingcharactervalues	function	**getspaceskipvalues**	function
getmode	function	**getspcode**	function
getmodevalues	function	**getspecialmathclassvalues**	function
getmuglue	function	**getspecification**	function
getmuskip	function	**getspecificationoptionvalues**	function
getmvloptionvalues	function	**gettextcontrolvalues**	function
getnest	function	**gettextdir**	function
getnestfields	function	**gettoks**	function
getnestlevel	function	**getuccode**	function
getnoadoptionvalues	function	**getuleaderlocationvalues**	function
getnormalizelinevalues	function	**getunitclassvalues**	function
getnormalizeparvalues	function	**getusedmarks**	function
getnospacesmodevalues	function	**getvariablefamilyvalues**	function
getoutputactive	function	**getvsplitcontextvalues**	function
getoverloadstate	function	**glue**	table
getpacktypevalues	function	**glueoptioncodes**	data table
getpagecontextvalues	function	**glyphdisccodes**	data table
getpagestate	function	**glyphoptioncodes**	data table
getpagestatevalues	function	**groupcodes**	data table
getparagraphfillmodevalues	function	**hashtokens**	function
getparagraphoptionvalues	function	**hccode**	table
getparametermodevalues	function	**hmcode**	table
getparcontextvalues	function	**hshcatcodes**	number
getpardataspecifications	function	**hyphenationcodes**	data table
getpardir	function	**ifs**	data table
getparmodevalues	function	**inicatcodes**	number
getparstate	function	**insertcategorycodes**	data table
getparstatefields	function	**insertoptioncodes**	data table
getpartriggervalues	function	**insertsplitcodes**	data table
getpenaltyoptionvalues	function	**integerdef**	function
getpositvalue	function	**interactioncodes**	data table
getprepoststatevalues	function	**isattribute**	function
getprimitivelegacies	function	**isbox**	function
getprimitiveorigins	function	**iscount**	function
getprotrusionboundaryvalues	function	**isdefined**	function
getregisterindex	function	**isdimen**	function
getruleoptionvalues	function	**isfloat**	function

isglue function
ismuglue function
ismuskip function
isprintable function
isskip function
istoks function
lastnodetype function
lccode table
less function
lessequal function
linebreak function
linebreakstatecodes data table
listanchorcodes data table
listgeometrycodes data table
lists table
listsigncodes data table
luacatcodes number
magicconstants table
S activecharacternamespace
N allfitnessvalues
N assumedmathcontrol
N awfulbad
N decentcriterion
N defaultcatcodetable
N defaultcharactercontrol
N defaultdeadcycles
N defaulteqnogapstep
N defaulthangafter
N defaultoutputbox
N defaultpredisplaygap
N defaultrule
N defaultspacefactor
N defaulttolerance
N deplorable
N ejectpenalty
N ignoredepth
N infinitebad
N infinitepenalty
N infinity
N largewidthexcess
N loosecriterion
N mathallclass
N mathbeginclass
N mathdefaultpenalty
N mathendclass
N mathfirstuserclass
N mathlastuserclass
N maxattributeregisterindex
N maxboxregisterindex
N maxbytecodeindex
N maxcalculatedbadness
N maxcardinal
N maxcharactercode
N maxdatavalue
N maxdimen
N maxdimenregisterindex
N maxdimension
N maxdimensionregisterindex
N maxendlinecharacter
N maxfloatregisterindex
N maxfontadjustshrinkfactor
N maxfontadjuststep
N maxfontadjuststretchfactor
N maxfunctionreference
N maxglueregisterindex
N maxhalfvalue
N maxhalfword
N maxinteger
N maxintegerregisterindex
N maxintregisterindex
N maxlimitedscale
N maxmarkindex
N maxmathclasscode
N maxmathfamilyindex
N maxmathscalingfactor
N maxmathstylescale
N maxmugleregisterindex
N maxmvlindex
N maxnewlinecharacter
N maxnofbytecodes
N maxnofcatcodetables
N maxnoffitnessvalues
N maxnoffonts
N maxnoflanguages
N maxnofmarks
N maxnofmathfamilies
N maxquarterword
N maxscalefactor

N maxsizeofword
N maxspacefactor
N maxtoksregisterindex
N maxtwinlength
N mincardinal
N mindatavalue
N mindimen
N mindimension
N minhalfword
N mininfinity
N mininteger
N minmvlindex
N minnoffitnessvalues
N minquarterword
N minscalefactor
N minspacefactor
N nocatcodetable
N null
N nullflag
N nullfont
N onebp
N presetrulethickness
N runningrule
N saparthigh
N sapartlow
N sapartmiddle
N smallstretchability
N specialspacefactor
N texeqtbsize
N texhashprime
N texhashsize
N texmemorymode
N two
N undefinedmathparameter
N unity
N unusedattributevalue
N unusedmathfamily
N unusedmathstyle
N unusedscriptvalue
N unusedstatevalue
N zeroglue

mathchardef function
mathcode table
mathcontrolcodes data table
mathoptioncodes data table
mathparametercodes data table
mathscriptordercodes data table
mathscriptsmodecodes data table
modelevels table
N horizontal
N math
N unset
N vertical
modes data table
mprint function
muglue table
muskip table
mvloptioncodes data table
nest table
nilcatcodes number
noadoptioncodes data table
normalizelinecodes data table
normalizeparcodes data table
nospacesmodecodes data table
notcatcodes number
number function
paragraphfillmodecodes data table
paragraphoptioncodes data table
parcontextcodes data table
partriggercodes data table
penaltyoptioncodes data table
poplocal function
popsavelevel function
posit table
positdef function
preparelinebreak function
primitives function
print function
protrusionboundarycodes data table
prtcatcodes number
pushlocal function
pushsavelevel function
quitlocal function
quittoks function
resetparagraph function
rlncatcodes number
romannumeral function
round function

ruleoptioncodes	data table	**setmathcode**	function
runlocal	function	**setmathdir**	function
runstatecodes	data table	**setmuglue**	function
runstring	function	**setmuskip**	function
runtoks	function	**setnest**	function
saveboxresource	function	**setoverloadstate**	function
scale	function	**setpardir**	function
scantoks	function	**setpositvalue**	function
set	function	**setrunstate**	overloaded func
setamcode	function	**setsfcode**	function
setattribute	function	**setskip**	function
setbalanceshape	function	**setspcode**	function
setbox	function	**settextdir**	function
setboxdir	function	**settoks**	function
setcardinalvalue	function	**setuccode**	function
setcatcode	function	**sfcode**	table
setcccode	function	**shapingpenaltiescodes**	data table
setconditional	function	**shiftparshape**	function
setcount	function	**shipout**	function
setdelcode	function	**showcontext**	function
setdimen	function	**skip**	table
setdimensionvalue	function	**snappingcodes**	data table
setfloat	function	**snapshotpar**	function
setglue	function	**sp**	function
setglyphdata	function	**spacefactorcodes**	data table
setglyphscript	function	**spaceskipcodes**	data table
setglyphstate	function	**specialmathclasscodes**	data table
sethccode	function	**specificationoptioncodes**	data table
sethmcode	function	**splitbox**	function
setinputstatefile	function	**splitcodes**	data table
setinputstateline	function	**sprint**	function
setinputstatemode	function	**stringtocodesbitmap**	function
setinsertcontent	function	**systemmodes**	data table
setinsertdistance	function	**takebox**	function
setinsertlimit	function	**texcatcodes**	number
setinsertmaxplaced	function	**textcontrolcodes**	data table
setinsertmultiplier	function	**toks**	table
setintegervalue	function	**tonumber**	function
setinteraction	function	**toscaled**	function
setlccode	function	**tpacatcodes**	number
setlinedir	function	**tpbcatcodes**	number
setlist	function	**tprint**	function
setlocalbox	function	**trackedattribute**	function
setmath	function	**trackers**	data table

triggerbuildpage	function	**userdiscoptioncodes**	data table
txtcatcodes	number	**userglyphoptioncodes**	data table
uccode	table	**vrbcatcodes**	number
uprint	function	**write**	function
useboxresource	function		

texconfig (basic tex)

buffersize table
- N size
- N step

errorlinesize table
- N size

expandsize table
- N size

filesize table
- N size
- N step

firstline string

fontsize table
- N size
- N step

formatname string

functionsize number

halferrorlinesize table
- N size

hashsize table
- N size
- N step

init overloaded function

inputsize table
- N size
- N step

insertsize table
- N size
- N step

kpse_init boolean

languagesize table
- N size
- N step

marksize table
- N size
- N step

nestsize table
- N size
- N step

nodesize table
- N size
- N step

parametersize table
- N size
- N step

poolsize table
- N size
- N step

propertiessize number

savesize table
- N size
- N step

shell_escape string

stringsize table
- N size
- N step

tokensize table
- N size
- N step

texio (basic tex)

closeinput	function	**write**	function
forceendoffile	function	**write_nl**	function
getinputindex	function	**writenl**	function
getselectorvalues	function	**writeselector**	function
getsourcefilename	function	**writeselectorlf**	function
setlogfile	function	**writeselectornl**	function
terminal	function		

timer (context)

__name	string	**new**	function
__tostring	function	**reset**	function
current	function	**setoffset**	function
elapsed	function	**sleepms**	function
elapsedms	function	**start**	function
elapsedus	function	**stop**	function
elapsedμs	function	**tostring**	function
istiming	function		

token (basic tex)

create	function	getexpandable	function
expand	function	getexpansion	function
expand_macro	function	getfields	function
expandmacro	function	getflags	function
future_expand	function	getfrozen	function
futureexpand	function	getfunctionvalues	function
get_active	function	getid	function
get_cmdchrcs	function	getimmutable	function
get_cmdname	function	getindex	function
get_command	function	getinstance	function
get_csname	function	getinteger	function
get_cstoken	function	getlength	function
get_dimension	function	getmacro	function
get_expandable	function	getmeaning	function
get_fields	function	getnoaligned	function
get_flags	function	getparameters	function
get_frozen	function	getpermanent	function
get_id	function	getprimitive	function
get_immutable	function	getprimitives	function
get_index	function	getprotected	function
get_instance	function	getrange	function
get_integer	function	gettok	function
get_macro	function	gettolerant	function
get_meaning	function	gobble	function
get_noaligned	function	gobble_dimension	function
get_parameters	function	gobble_integer	function
get_permanent	function	gobbledimension	function
get_primitive	function	gobbleinteger	function
get_protected	function	grab	function
get_range	function	grabstring	function
get_tok	function	inhibit	function
get_tolerant	function	is_defined	function
getactive	function	is_next_char	function
getcmdchrcs	function	is_token	function
getcmdname	function	isactivestring	function
getcommand	function	isdefined	function
getcommandvalues	function	isnextchar	function
getconstant	function	istoken	function
getcsname	function	locatemacro	function
getcstoken	function	new	function
getdimension	function	peek_next	function

peek_next_char	function	scan_tokenlist	function
peek_next_expanded	function	scan_toks	function
peeknext	function	scan_value	function
peeknextchar	function	scan_word	function
peeknextexpanded	function	scanargument	function
pop_macro	function	scanbox	function
popmacro	function	scancardinal	function
push_macro	function	scanchar	function
pushmacro	function	scancmdchr	function
put_back	function	scancmdchrexpanded	function
put_next	function	scancode	function
putback	function	scancsname	function
putnext	function	scancstoken	function
save_lua	function	scandelimited	function
savelua	function	scandetokened	function
scan_argument	function	scandimen	function
scan_box	function	scandimenargument	function
scan_cardinal	function	scandimension	function
scan_char	function	scandimensionargument	function
scan_cmdchr	function	scanfloat	function
scan_cmdchr_expanded	function	scanglue	function
scan_code	function	scanint	function
scan_csname	function	scaninteger	function
scan_delimited	function	scanintegerargument	function
scan_dimen	function	scankey	function
scan_float	function	scankeyword	function
scan_glue	function	scankeywordcs	function
scan_integer	function	scanletters	function
scan_key	function	scanluacardinal	function
scan_keyword	function	scanluainteger	function
scan_keyword_cs	function	scanluanumber	function
scan_letters	function	scannext	function
scan_luacardinal	function	scannextchar	function
scan_luainteger	function	scannextexpanded	function
scan_luanumber	function	scanposit	function
scan_next	function	scanreal	function
scan_next_char	function	scanscale	function
scan_next_expanded	function	scanskip	function
scan_real	function	scanstring	function
scan_scale	function	scantoken	function
scan_skip	function	scantokencode	function
scan_string	function	scantokenlist	function
scan_token	function	scantokenstring	function
scan_token_code	function	scantoks	function

scanvalue	function	**setmacro**	function
scanword	function	**setmacrofrommark**	function
serialize	function	**setmacrotonothing**	function
set_dimension	function	**skip_next**	function
set_integer	function	**skip_next_expanded**	function
set_lua	function	**skipnext**	function
set_macro	function	**skipnextexpanded**	function
setdimension	function	**type**	function
setinteger	function	**undefine_macro**	function
setlua	function	**undefinemacro**	function

tokens (context)

accessors table
- F active
- F cmd
- F cmdchrcs
- F cmdname
- F command
- F csname
- F expandable
- F frozen
- F index
- F name
- F protected
- F range

astable function
bits table
- N active
- N alignment
- N begingroup
- N character
- N close
- N comment
- N endgroup
- N endofline
- N escape
- N ignore
- N invalid
- N letter
- N mathshift
- N open
- N other
- N parameter
- N space
- N subscript
- N superscript
- N whitespace

cache data table
commands data table
compile function
constant function
converters table
- S toboolean
- S todimen
- S toglue
- S tonumber
- S tostring

create function
defined function
flags function
getinteger function
getters table
- F box
- F count
- F cstoken
- F dimen
- F glue
- F macro
- F meaning
- F skip
- F token

gobble function
isactivestring function
isdefined function
istoken function
new function
pickup function
popmacro function
presets table
pushmacro function
scanners table
- F argument
- F argumentasis
- F array
- F boolean
- F box
- F bracketed
- F bracketedasis
- F cardinal
- F char
- F cmdchr
- F cmdchrexpanded
- F code
- F conditional

F count
F csname
F csnameunchecked
F delimited
F detokened
F dimen
F dimension
F dimensionargument
F float
F glue
F gluespec
F gluevalues
F hash
F hbox
F integer
F integerargument
F ischar
F key
F keyword
F keywordcs
F letters
F list
F lua
F luacardinal
F luainteger
F luanumber
F lxmlid
F next
F nextchar
F nextexpanded
F number
F optional
F peek
F peekchar
F peekexpanded
F posit
F real
F scanclose
F scanopen
F skip
F skipexpanded
F string
F table
F token
F tokencode
F tokenlist
F tokens
F tokenstring
F toks
F value
F vbox
F verbatim
F vtop
F whd
F word

setinteger function

setters table

F box
F char
F count
F dimen
F glue
F lua
F macro
F skip

shortcuts table

N close
F inspect
N open
F report
F scanargument
F scanargumentasis
F scanarray
F scanboolean
F scanbox
F scanbracketed
F scanbracketedasis
F scancardinal
F scanclose
F scancode
F scanconditional
F scancsname
F scancsnameunchecked
F scandelimited
F scandetokened
F scandimen
F scandimension
F scandimensionargument

F scanfloat
F scanglue
F scangluespec
F scangluevalues
F scanhash
F scanhbox
F scaninteger
F scanintegerargument
F scankeyword
F scankeywordcs
F scanletters
F scanlist
F scanlua
F scannumber
F scanopen
F scanoptional
F scanposit
F scanstring
F scantable
F scantokenlist
F scantokenstring
F scantoks
F scanvbox
F scanverbatim
F scanvtop
F scanword
F toboolean
F todimen
F tonumber
F tostring

values data table

tracers (context)

printerror	function	**processerror**	function
printwarning	function	**showlines**	function

trackers (context)

data	data table	**register**	function
default	function	**report**	function
disable	function	**reset**	function
done	table	**savehash**	function
dumphashtofile	function	**set**	function
enable	function	**show**	function
list	function	**value**	function
name	string	**values**	function

typesetters (context)

alignments table
- F handler
- F set

breakpoints table
- F define
- F handler
- D mapping
- F set
- F setreplacement

cases table
- F handler
- F register
- F set

characteralign table
- F handler
- F resetcharacteralign
- F setcharacteralign

characters table
- F handler
- F replacenbsp
- F replacenbspaces

checkers table
- F handler
- F reset
- F set

cleaners table
- F handler
- F set

compare table
- F handler
- F reset
- F set
- F setpair
- F setup

corrections table
- F handler

digits table
- F handler
- F set

directions table
- F getfences
- F getglobal
- F getmethod
- F handler
- F installhandler
- F set
- F setcolor
- F tomode

firstlines table
- F handler
- F set

fontkerns table
- F handler

initials table
- F handler
- F set

injectors table
- F check
- F mark
- F reset
- F set
- F show

italics table
- F enablemath
- F enabletext
- F handler

kerns table
- D factors
- F handler
- F keepligature
- D mapping
- F set

localboxes table
- F handler

manipulators table
- F apply
- F applyspecification
- F splitspecification

margins table
- F finalhandler
- F globalhandler
- F localhandler

F save
marksuspects function
paragraphs table
F addanchortoline
F addtoline
F calculatedelta
F checkline
F moveinline
periodkerns table
D factors
F handler
D mapping
F set
processors table
F apply
F register
F reset
F split
F startapply
F stopapply
F stripped
F tostring
rubies table
F attach
F check
showinvisibles function
showsuspects function
spacings table
F define
F handler
D mapping
F reset
F set
F setup
stacking table
F getindex
F getselection
F handler
swapping table
F handler
synchronize table
F handler
tighten table
F handler
wrappers table
xtables table
F cleanup
F construct
F create
F finish_row
F flush
F initialize_construct
F initialize_reflow_height
F initialize_reflow_width
F next_row
F reflow_height
F reflow_width
F set_construct
F set_reflow_height
F set_reflow_width

updaters (context)

apply function
register function

url (context)

addscheme	function	**hashed**	function
barepath	function	**hasscheme**	function
construct	function	**query**	function
decode	function	**split**	function
encode	function	**toquery**	function
escape	function	**unescape**	function
filename	function	**unescapeget**	function

utf8 (basic lua)

char	function	**codes**	function
charpattern	string	**len**	function
codepoint	function	**offset**	function

utilities (context)

debugger table
- F disable
- F enable
- F savestats
- F showstats
- F showtraceback

files table
- F close
- F getposition
- F getsize
- F look
- F open
- F read2dot14
- F readbyte
- F readbytes
- F readbytetable
- F readcardinal
- F readcardinal1
- F readcardinal1le
- F readcardinal2
- F readcardinal2le
- F readcardinal3
- F readcardinal3le
- F readcardinal4
- F readcardinal4le
- F readcardinaltable
- F readchar
- F readcline
- F readcstring
- F readfixed2
- F readfixed4
- F readinteger
- F readinteger1
- F readinteger1le
- F readinteger2
- F readinteger2le
- F readinteger3
- F readinteger3le
- F readinteger4
- F readinteger4le
- F readintegertable
- F readsignedbyte
- F readstring
- F readtag
- F setposition
- F size
- F skip
- F skiplong
- F skipposition
- F skipshort
- F writebyte
- F writecardinal1
- F writecardinal1le
- F writecardinal2
- F writecardinal2le
- F writecardinal3
- F writecardinal3le
- F writecardinal4
- F writecardinal4le
- F writeinteger1
- F writeinteger1le
- F writeinteger2
- F writeinteger2le
- F writeinteger3
- F writeinteger3le
- F writeinteger4
- F writeinteger4le
- F writestring

formatters table
- F formatcolumns
- F list
- F stripzeros

ghostscript table
- F convert
- F statistics

graphicmagick table
- F convert
- F statistics

graphicsmagick table
- F convert
- F statistics

json table

F load
F tojson
F tolua
F tostring

lua table
B alwaysstripcode
F checkmemory
F compile
F loadedluacode
F loadstring
F loadstripped
N nofstrippedbytes
N nofstrippedchunks
B stripcode
F strippedloadstring

packers table
F hashed
F new
F pack
F simplehashed
F strip
F unpack
N version

parsers table
F add_settings_to_array
F arguments_to_table
F array_to_string
F csvsplitter
F getparameters
F groupedsplitat
F hash_to_string
F iterator
F keq_to_hash
F listitem
F make_settings_to_hash_pattern
F mergehashes
F options_to_array
F options_to_hash
F process_stripped_settings
F rfc4180splitter
F runtime
F settings_to_array
F settings_to_array_obey_fences
F settings_to_array_with_repeat
F settings_to_hash
F settings_to_hash_colon_too
F settings_to_hash_strict
F settings_to_hash_tolerant
F settings_to_numbers
F settings_to_set
F simple_hash_to_string
F splitmethod
F splitthousands
F stepper
F stripped_settings_to_array
F totime
F unittotex
F unittoxml

randomizer table
F get
F getnumber
F getrepeatable
F getrepeatableseed
F getseed
F newrepeatable
F popseed
F pushseed
F repeatable
F reuseseed
F setseed
F setseedi

randomizers table
F poisson

sequencers table
F appendaction
F appendgroup
F compile
F disableaction
F disablegroup
F enableaction
F enablegroup
D functions
F localize
F new
F nodeprocessor
F prependaction
F prependgroup
F removeaction

F replaceaction
F setkind
F tostring

setters table
F disable
F enable
F initialize
F list
F new
F register
F report
F reset
F show

signals table
S configuration
F initialize
F loadstate
F report
F savestate
F serialclose
F serialfast
F serialopen
S serialprefix
F serialsend
F serialwrite
N version

stacker table
F new

storage table
F allocate
F checked
F mark
F marked
F setinitializer
F sparse

streams table
F close
F getposition
F getsize
F getstring
F look
F open
F openstring
F read2dot14
F readbyte
F readbytes
F readbytetable
F readcardinal
F readcardinal1
F readcardinal1le
F readcardinal2
F readcardinal2le
F readcardinal3
F readcardinal3le
F readcardinal4
F readcardinal4le
F readcardinaltable
F readchar
F readcstring
F readdouble
F readdoublele
F readfixed2
F readfixed4
F readfloat
F readfloatle
F readfloatle12
F readfloatle6
F readinteger
F readinteger1
F readinteger1le
F readinteger2
F readinteger2le
F readinteger3
F readinteger3le
F readinteger4
F readinteger4le
F readintegertable
F readline
F readsignedbyte
F readstring
F setposition
F size
F skip
F skipbytes
F skiplong
F skipshort
F tocardinal1
F tocardinal1le

F tocardinal2
F tocardinal2le
F tocardinal3
F tocardinal3le
F tocardinal4
F tocardinal4le

strings table
F collapse
F newcollector
F newrepeater
F striplines
F tabtospace

tables table
F accesstable
F definedtable
F definetable
F encapsulate
F insertaftervalue
F insertbeforevalue
F migratetable
F removevalue
F replacevalue

tar table
F closearchive
F openarchive

templates table
F load
F replace
F replacer
F resolve

zipfiles table
F close
F found
F hash
F list
F open
F unzip
F unzipdir
F zipdir

vector (extra lua)

add function
append function
average function
ceiling function
checkoverlap function
collectoverlap function
concat function
contour table
- F average
- F bounds
- F checkoverlap
- F collectoverlap
- F getarea
- F getmesh
- F makemesh
- F overlapping
- F show
- F sort

copy function
crossproduct function
delete function
determinant function
div function
equal function
exchange function
floor function
get function
getdimensions function
getepsilon function
getmemory function
getmesh function
getmeshtypes function
getpointtypes function
getrc function
getrow function
getsize function
getstacking function
gettype function
helpers table
- F points
- F transform
- F xrotation
- F xyzscale
- F yrotation
- F zrotation

homogenize function
identity function
inner function
insert function
inverse function
ismesh function
ispoints function
issingular function
isvector function
iszero function
mesh table
- F copy
- F get
- F getaverage
- F getdimensions
- F gettypevalues
- F ismesh
- F new
- F set
- F setaverage
- F tostring
- F totable
- F type

meshname function
mul function
negate function
new function
normalize function
normals table
- F flip
- F get
- F isnormals
- F new
- F set
- F tostring
- F totable
- F type

onecolumn function
onerow function
point table
- F add
- F copy
- F cross
- F crossproduct
- F dist
- F distance
- F div
- F dot
- F dotproduct
- F equal
- F get
- F ispoint
- F iszero
- F len
- F length
- F mul
- F neg
- F negate
- F new
- F norm
- F normalize
- F perp
- F perpendicular
- F set
- F sub
- F tostring
- F totable
- F type

points table
- F copy
- F get
- F getbounds
- F getindex
- F getnormal
- F getpool
- F gettriangle
- F getxy
- F getxytable
- F getxyz
- F getxyztable
- F grow
- F index
- F ispoints
- F new
- F prune
- F set
- F setindex
- F setnormal
- F setxy
- F setxyz
- F size
- F tostring
- F totable
- F type

product function
remove function
replace function
round function
rowechelon function
set function
setepsilon function
setnext function
setrc function
setstacking function
slice function
sort function
sub function
swap function
tostring function
totable function
transpose function
triangulate function
truncate function
type function

visualizers (context)

escapepatterns	data table	**signal**	string
getspecification	function	**signalpattern**	userdata
getvisualizer	function	**specifications**	data table
load	function	**visualize**	function
makenested	function	**visualizebuffer**	function
makepattern	function	**visualizefile**	function
newgrammar	function	**visualizestring**	function
newhandler	function	**write**	function
parsedxml	function	**writeargument**	function
pattern	function	**writedefault**	function
register	function	**writeemptyline**	function
registerescapecommand	function	**writenewline**	function
registerescapeline	function	**writespace**	function
registerescapepattern	function		

xcomplex (extra lua)

I	function	**erf**	function
__add	function	**erfc**	function
__div	function	**erfcx**	function
__eq	function	**erfi**	function
__mul	function	**exp**	function
__name	string	**i**	function
__pow	function	**imag**	function
__sub	function	**log**	function
__tostring	function	**new**	function
__unm	function	**pow**	function
abs	function	**proj**	function
acos	function	**real**	function
acosh	function	**sin**	function
arg	function	**sinh**	function
asin	function	**sqrt**	function
asinh	function	**tan**	function
atan	function	**tanh**	function
atanh	function	**topair**	function
conj	function	**tostring**	function
cos	function	**totable**	function
cosh	function	**voigt**	function
dawson	function	**voigt_hwhm**	function

xdecimal (extra lua)

__add	function	**bxor**	function
__band	function	**conj**	function
__bor	function	**copy**	function
__bxor	function	**exp**	function
__div	function	**getprecision**	function
__eq	function	**ln**	function
__idiv	function	**log**	function
__le	function	**max**	function
__lt	function	**min**	function
__mod	function	**minus**	function
__mul	function	**new**	function
__name	string	**plus**	function
__pow	function	**pow**	function
__shl	function	**rotate**	function
__shr	function	**setprecision**	function
__sub	function	**shift**	function
__tostring	function	**sqrt**	function
__unm	function	**toengstring**	function
abs	function	**tonumber**	function
band	function	**tostring**	function
bor	function	**trim**	function

xinterval (context)

__add	function	**greaterequal**	function
__div	function	**hull**	function
__eq	function	**intersect**	function
__le	function	**less**	function
__lt	function	**lessequal**	function
__mod	function	**log**	function
__mul	function	**log10**	function
__name	string	**log1p**	function
__pow	function	**log2**	function
__sub	function	**mid**	function
__tostring	function	**mod**	function
__unm	function	**new**	function
abs	function	**neweps**	function
acos	function	**pow**	function
acosh	function	**seteq**	function
asin	function	**setge**	function
asinh	function	**setgt**	function
asstring	function	**setle**	function
atan	function	**setlt**	function
atanh	function	**sin**	function
cos	function	**sinh**	function
cosh	function	**sqr**	function
diameter	function	**sqrt**	function
equal	function	**tan**	function
erf	function	**tanh**	function
erfc	function	**topair**	function
exp	function	**tostring**	function
exp10	function	**totable**	function
exp2	function	**usedendian**	function
expm1	function	**within**	function
greater	function		

xmath (extra lua)

acos	function
acosh	function
asin	function
asinh	function
atan	function
atan2	function
atanh	function
cbrt	function
ceil	function
copysign	function
cos	function
cosh	function
crossproduct	function
deg	function
dotproduct	function
erf	function
erfc	function
exp	function
exp2	function
expm1	function
fabs	function
fdim	function
floor	function
fma	function
fmax	function
fmin	function
fmod	function
frexp	function
gamma	function
hypot	function
inf	number
isfinite	function
isinf	function
isnan	function
isnormal	function
j0	function
j1	function
jn	function
ldexp	function
lgamma	function
log	function
log10	function
log1p	function
log2	function
logb	function
modf	function
nan	number
nearbyint	function
nextafter	function
normalize	function
pi	number
pow	function
rad	function
remainder	function
remquo	function
round	function
scalbn	function
sin	function
sinh	function
sqrt	function
tan	function
tanh	function
tgamma	function
trunc	function
y0	function
y1	function
yn	function

xml (context)

addentitiesdoctype function
addspecialcode function
after function
all function
applylpath function
applyselector function
assign function
attribute function
badinclusions function
before function
body function
builtinentities table
- B amp
- B apos
- B gt
- B lt
- B quot

cdata function
cdatatotext function
checkbom function
checkedempty function
checkerror function
checknamespace function
checkns function
cleansed function
collect function
~~**collect_elements**~~ ~~function~~
collect_tags function
~~**collect_texts**~~ ~~function~~
collected function
collecttexts function
compactelement function
content function
convert function
copy function
count function
cprint function
css table
- F applyselector
- F colorspecification
- F dimension
- F family
- F fontspecification
- F mappedstylevalue
- F padding
- F size
- F style
- F stylevalue
- F todimension
- F variant
- F weight

defaulthandlers table
- D file
- D parsedxml
- D string
- D tex
- D texline
- D texspace
- D verbose

defaultprotocol string
delete function
~~**delete_element**~~ ~~function~~
despecialized function
each function
~~**each_element**~~ ~~function~~
elements function
elementtocdata function
empty function
entities data table
erase function
errorhandler function
escaped function
expand function
expressions table
- F attribute
- F boolean
- F child
- F contains
- F count
- F error
- F find
- F hasclass

F idstring
F lower
F name
F number
F oneof
F print
F quit
F tag
F text
F undefined
F upper
fillin function
filter function
finalizers table
F paragraphs
first function
found function
functions table
F classes
F hasclass
getbuffer function
gethandlers function
gethandlersfunction function
helpers table
F recursetext
include function
inclusion function
inclusions function
index function
inheritattributes function
inheritedconvert function
inject function
~~**inject_element**~~ ~~function~~
~~**inject_element_after**~~ ~~function~~
~~**inject_element_before**~~ ~~function~~
injectafter function
injectbefore function
insert function
insert_element function
~~**insert_element_after**~~ ~~function~~
~~**insert_element_before**~~ ~~function~~
insertafter function
insertbefore function
insertcdata function
insertcomment function
inspect function
is_valid function
kind function
last function
lastmatch function
load function
lpath function
lpathcached function
lpathcalls function
lshow function
makestandalone function
match function
mml table
F stripped
F verbose
name function
newhandlers function
nodesettostring function
originalload function
package function
parent function
parsedentitylpeg userdata
pihandlers table
F injector
F tex
placeholders table
F unknown_any_entity
F unknown_dec_entity
F unknown_hex_entity
popmatch function
position function
privatecodes data table
privatetoken function
process function
~~**process_attributes**~~ ~~function~~
~~**process_elements**~~ ~~function~~
processattributes function
profiled table
pure function
pushmatch function
raw function
registerentity function
registerns function

reindex	function	**specialhandler**	table
~~**remap_name**~~	~~function~~	**sprint**	function
~~**remap_namespace**~~	~~function~~	**string**	function
~~**remap_tag**~~	~~function~~	**strip**	function
remapname	function	~~**strip_whitespace**~~	~~function~~
remapnamespace	function	**stripelement**	function
remaptag	function	**stripleadingspaces**	function
rename	function	**table**	function
renamespace	function	**text**	function
reparsedentitylpeg	userdata	**textonly**	function
replace	function	**texttocdata**	function
~~**replace_element**~~	~~function~~	**tocdata**	function
resetinjectors	function	**toelement**	function
resolvens	function	**tostring**	function
root	function	**totable**	function
save	function	**toxml**	function
selection	function	**tprint**	function
separate	function	**traverse**	function
serialize	function	**unescaped**	function
serializetotext	function	**unescapedentitylpeg**	userdata
setcdata	function	**unprivatized**	function
setcomment	function	**unspecialized**	function
sethandlersfunction	function	**wipe**	function
setinjectors	function	**withelement**	function
setproperty	function	**withelements**	function
settings	function	**wrap**	function
specialcodes	data table	**xmlns**	table

xzip (extra lua)

adler32	function	**crc32**	function
compress	function	**decompress**	function
compresssize	function	**decompresssize**	function

zbuffer (context)

bounds	function	**set**	function
composite	function	**setcolor**	function
crop	function	**setdepth**	function
edgepoint	function	**setnormal**	function
flatten	function	**setopacity**	function
get	function	**setup**	function
getcolor	function	**smoothen**	function
getconstants	function	**stipple_0**	function
getdepth	function	**stipple_1**	function
getnormal	function	**stipple_2**	function
getnormalmodes	function	**stipple_3**	function
getopacity	function	**stipple_4**	function
getsize	function	**stipple_setup**	function
implicit	function	**tobytes**	function
iszbuffer	function	**tostring**	function
meshmesh	function	**totable**	function
new	function	**transform**	function
points	function	**trianglebounds**	function
process	function	**triangled**	function
project	function	**triangles**	function
resolve	function	**type**	function

zip (context)

archives	table	**openarchive**	function
closearchive	function	**registeredfiles**	table

zlib (context)

adler32	function	**crc32**	function
compress	function	**decompress**	function
compresssize	function	**decompresssize**	function