### Routes in Hapi

Routing Hapi-ly

#### Basic routing - get

```
server.route({
   method: 'GET',
   path: '/',
   handler: function (request, reply) {
      reply ('Hello!');
});
```

### Post Example



#### Post Example

```
server.route({
   method: ['PUT', 'POST'].
   path: '/',
   handler: function (request, reply) {
      reply ('Oh hai there Empire Noder!');
});
```

#### **Paths**

```
server.route({
   method: 'GET',
   path: '/hello/{user}',
   handler: function (request, reply) {
      reply ('Oh Hai' + user '!');
});
```

#### Hapchat Routes

```
// /lib/index.js
  server.route([
    { method: 'GET', path: '/', config: Handlers.home },
    { method: 'GET', path: '/upload', config: Handlers.uploadView },
    { method: 'POST', path: '/upload', config: Handlers.upload },
    { method: 'GET', path: '/photos', config: Handlers.photos },
    { method: 'GET', path: '/photos/{photoId}', config: Handlers.photo },
    { method: 'GET', path: '/login', config: Handlers.login },
    { method: 'GET', path: '/logout', config: Handlers.logout },
    { method: 'GET', path: '/static/{path*}', config: Handlers.stat(server) }
  ]);
```

#### Hapchat Routes

```
// /lib/index.js
  server.route([
    { method: 'GET', path: '/', config: Handlers.home },
    { method: 'GET', path: '/upload', config: Handlers.uploadView },
    { method: 'POST', path: '/upload', config: Handlers.upload },
    { method: 'GET', path: '/photos', config: Handlers.photos },
    { method: 'GET', path: '/photos/{photoId}', config: Handlers.photo },
    { method: 'GET', path: '/login', config: Handlers.login },
    { method: 'GET', path: '/logout', config: Handlers.logout },
    { method: 'GET', path: '/static/{path*}', config: Handlers.stat(server) }
  ]);
```

### Hapchat Routes

```
// hapchat/lib/handlers/index.js
module.exports.home = {
  description: 'Home page view for hapchat',
  auth: {
    mode: 'try'
  handler: function (request, reply) {
    reply.view('index');
```

# What If I don't like the hard stuff, and want to use config?

```
server.route({
  method: 'GET',
  path: '/hello/{user?}',
  handler: function (request, reply) {
    var user = request.params.user ? encodeURIComponent(request.params.
user): 'stranger';
    reply('Hello ' + request.params.user + '!');
  config: {
    description: 'Say hello!',
    notes: 'The user parameter defaults to \'stranger\' if unspecified',
    tags: ['api', 'greeting']
```

# What other cool stuff can I put in my config? How about Validation!

```
server.route({
  method: 'GET',
  path: '/hello/{name}',
  handler: function (request, reply) {
    reply('Hello ' + request.params.name + '!');
  },
  config: {
    validate: {
       params: {
         name: Joi.string().min(3).max(10)
```

# Any other cool stuff we can put in our route configs?

YES, Authentication!!!