

EU4 Innovation
Kosovo - eID

eID Platform API

This project is funded
by the European Union

A project implemented by
EVOLUXER

Contents

1. SUMMARY 3

2. EID SIGNING API 3

2.1. BASE URL 3
2.2. SIGNATURE AND TIMESTAMPING BASE URL 3

3. SIGNATURE AND TIMESTAMPING API 4

3.1. ECHO 4
3.2. SEND OTP 5
3.3. SIGN 5
3.4. SIGN WITH TIMESTAMP 7
3.5. TIMESTAMP 8

1. Summary

The primary aim of this document is to present a comprehensive and detailed description of the various APIs offered by the eID platform. These APIs are designed to facilitate seamless and efficient integration with third-party applications that require their functionality. By providing in-depth information and guidance, this document seeks to ensure that developers and stakeholders can easily understand and implement the APIs to enhance the interoperability and capabilities of their systems.

2. eID signing API

The following chapter highlights the APIs made available by the eID platform for signing and timestamping documents.

- Echo
- Send OTP
- Sign
- Sign with timestamp
- Timestamp

2.1. Base URL

Environment	Hostname
TEST	eid-cms.kren-ks.eu
PRODUCTION	eid-cms.rks-gov.net

2.2. Signature and Timestamping base URL

In pre-production the base URL to be used to invoke the API below is as follows:

```
http://eid.kren-ks.eu
```

In production, instead, the base URL to be used to invoke the API below is as follows:

```
https://eid-signcloud.rks-gov.net
```

Depending on whether you want to apply a signature or a timestamp, only the path changes, which for the signature is **`/signbox`** while for the timestamp is **`/tsa`**

3. Signature and Timestamping API

The APIs described in this chapter provide a set of interfaces for integrating file signing and timestamping capabilities into third-party applications

3.1. Echo

Description: replies back what it receives to check the service availability.

URL: `https://{host}/signbox/api/v1/echo?message=test`

Method: `GET`

Header parameters:

- **No parameters**

Parameters in request body:

- **No parameters**

Sample response in case of success:

- **HTML Code:** 200 OK
- **Content:** {STRING}

Sample response in case of error:

- **HTML Code:** 401 Unauthorized
- **Content:**

```
{
  "error_code": 0,
  "detail": "string"
}
```

- **HTML Code:** 422 Unprocessable Entity
- **Content:**

```
{
  "error_code": 0,
  "detail": "string"
}
```

3.2. Send OTP

Description: generates and send an OTP via SMS for the specified digital identity.

URL: `https://{host}/signbox/api/v1/otp`

Method: POST

Header parameters:

- **No parameters**

Parameters in request body:

- **username**: required, represent the digital identity username
    - type: {STRING}
- **password**: required, represent the digital identity password
    - type: {STRING}
- **uses**: optional, this parameter represents the max uses of the OTP. If not specified, the API can be used for massive signature; the important thing in this case is that no more than 3 minutes elapses between each signature.
    - type: {INTEGER}

Sample response in case of success:

- **HTML Code:** 200 OK
- **Content:** {}

Sample response in case of error:

- **HTML Code:** 422 Unprocessable Entity
- **Content:**

```
{
  "error_code": 0,
  "detail": "string"
}
```

3.3. Sign

Description: signs the submitted file.

URL: `https://{host}/signbox/api/v1/sign`

Method: POST

Header parameters:

- **No parameters**

Parameters in request body:

- **file**: required, represent the file to be signed
    - type: {STRING}
- **username**: required, represent the digital identity username
    - type: {STRING}
- **password**: required, represent the digital identity password
    - type: {STRING}
- **pin**: required, represent the digital identity PIN
    - type: {STRING}
- **format**: Types of supported signature profiles:
    - PADES for PDF files
        - type: {STRING}
    - XADES for XML files
        - type: {STRING}
    - CADES for other files
        - type: {STRING}
- **otp**: required, represent the OTP code previously sent to the user via SMS.
    - type: {STRING}
- **level**: optional, represent the signature level to address the need to protect the validity of the signature in time.
    - Values:
        - BASIC (the lowest and simplest version containing at least a signature value, a reference to or a copy of the signing certificate as a signed attribute)
        - T (A timestamp regarding the time of signing is added to protect against repudiation.)
    - type: {STRING}

Sample response in case of success:

- **HTML Code:** 200 OK
- **Content:** file signed

Sample response in case of error:

- **HTML Code:** 401 Unauthorized
- **Content:**

```
{
  "error_code": 0,
  "detail": "string"
}
```

3.4. Sign with timestamp

Description: apply a signature and a timestamp to the submitted file.

URL: `https://{host}/signbox/api/v1/sign`

Method: POST

Header parameters:

- **No parameters**

Parameters in request body:

- **file**: required, represent the file to be timestamped
  - type: {STRING}
- **username**: required, represent the digital identity username
  - type: {STRING}
- **password**: required, represent the digital identity password
  - type: {STRING}
- **pin**: required, represent the digital identity PIN
  - type: {STRING}
- **otp**: required, represent the OTP code previously sent to the user via SMS.
  - type: {STRING}
- **format**: optional, supported timestamp formats
  - supported format:
    - PDF
    - P7M
  - type: {STRING}

- **level**: optional, represent the signature level to address the need to protect the validity of the signature in time.
    - supported value:
        - BASIC (the lowest and simplest version containing at least a signature value, a reference to or a copy of the signing certificate as a signed attribute)
        - T (a timestamp regarding the time of signing is added to protect against repudiation.)
- **tsa_url**: required, represent the timestamp service URL required for signatures with level T
    - type: {STRING}

Sample response in case of success:

- **HTML Code:** 200 OK
- **Content:** file signed and timestamped

Sample response in case of error:

- **HTML Code:** 401 Unauthorized
- **Content:**

```
{
  "error_code": 0,
  "detail": "string"
}
```

3.5. Timestamp

Description: apply a timestamp to the submitted file.

URL: `https://{host}/signbox/api/v1/timestamp`

Method: POST

Header parameters:

- **No parameters**

Parameters in request body:

- **file**: required, represent the file to be timestamped
    - type: {STRING}
- **url**: required, represent the timestamp service URL

    - type: {STRING}
- **format**: supported timestamp formats
    - supported format:
        - PDF
        - P7M
    - type: {STRING}

Sample response in case of success:

- **HTML Code:** 200 OK
- **Content:** file timestamped

Sample response in case of error:

- **HTML Code:** 401 Unauthorized
- **Content:**

```
{
  "error_code": 0,
  "detail": "string"
}
```