

When Memory Metrics Hide Memory Policies

A Same-Stream Evaluation Method and Policy-Facing Lookup Diagnostic for Persistent-Agent Memory

Manav Malhotra

May 2026

Abstract

Existing agent-memory benchmarks ask whether the system got the right answer; this paper asks whether the memory policy had the right governable evidence handle. Persistent-agent memory systems can score well while hiding whether the underlying policy can govern, query, and repair the evidence it depends on. We present a preregistered attribution test for memory-policy claims and demonstrate it on Consolidation Queue (CQ), a staged-write policy that keeps low-confidence claims pending and contestable.

The method holds the upstream candidate stream and scoped storage substrate fixed across policies, gates noisy comparisons on extractor quality, and adds a policy-facing lookup-contract (PFLC) diagnostic that asks whether the system exposes the evidence handle a policy must actually query. It preserves negative transfer on LongMemEval rather than rescuing it, and pairs interface repairs with controls that reproduce the failure on a previously winning baseline. In the case study, the discipline detects CQ’s contradiction-handling survival on internal noisy extraction, surfaces a stable LongMemEval loss on evidence completeness, isolates that v1 loss as an answer-time readout-cardinality gap, and closes the gap with a preregistered repair corroborated by a capped Reflection control. These results support the attribution discipline, not a broad performance or deployment-readiness claim for CQ.

1 Introduction

An agent helping a user across months learns small facts incrementally. In March, the user mentions they prefer espresso; in August, they are cutting caffeine and want tea in the morning. A naive memory system overwrites the older preference; a less naive one stores both as parallel facts. Neither resolves the conflict when the user later asks what to order. The policy question for persistent memory is whether the system can keep both claims, scope them, contest one with the other, and demote a durable claim when the evidence shifts.

Most agent-memory benchmarks ask whether the system got the right answer; this report instead asks whether the memory policy had the right governable evidence handle. Recall, retrieval, and answer metrics are important, but they can hide whether a memory policy handled contradiction, scope, source independence, and reversibility, or merely benefited from easier inputs, richer private state, or a metric that did not inspect the handle the policy must query. Recent memory benchmarks broaden what systems are tested on; this report narrows how policy-level credit is assigned.

This report therefore argues for a stricter attribution posture. Memory-policy comparisons should hold the upstream candidate stream fixed, use the same storage substrate for the policies being compared, separate oracle-mode policy claims from noisy-pipeline claims, and preserve artifacts that make failure cases inspectable. The running case study is a lightweight consolidation

queue policy (CQ),¹ compared with immediate-write Reflection, a Mem0-style write-only baseline (Mem0WritePolicyLite, not the production Mem0 system), and ablated variants. We use CQ to test which memory-policy distinctions survive the interfaces around them.

Concretely, CQ is a staged-write policy. Incoming candidate memories enter a queue with scope, provenance, support, contradiction, and lifecycle metadata. High-scoring candidates promote to durable memory; lower-scoring but usable candidates can remain pending and still answer scoped lookups. Contradictory evidence contests earlier candidates and can demote active durable memories, while narrower pending overrides can shadow a wider durable claim without globally overwriting it. In the opening example, CQ keeps both the espresso preference and the morning-tea preference as scoped claims: the narrower morning-tea claim shadows the broader espresso claim at read time, and either can be contested or demoted when stronger evidence arrives.

Internally, under a preregistered noisy policy comparison, CQ’s contradiction-edge-driven contestation and demotion mechanism remains visible on forced contradiction and partially visible on preference drift. Other rows stay recorded as nulls or policy-facing lookup-contract failures. Externally, a controlled LongMemEval v1 transfer probe produces a stable negative result for base CQ on evidence completeness. A later preregistered follow-up repairs that specific failure by exposing all eligible same-slot pending evidence at answer time, while a cardinality-capped Reflection control reproduces the original loss. The paper preserves the failure and the repair as separate evidence.

Table 1: Contribution map.

Layer	Contribution
Problem	Memory scores can hide whether policy-level governance succeeded.
Method	Same-stream, same-substrate, extractor-gated comparison makes policy attribution inspectable.
Diagnostic	PFLC checks whether the policy-facing evidence handle is exposed, not just whether text is relevant.
Case study	CQ shows one clean noisy mechanism-survival row, bounded nulls, and a preserved LongMemEval loss.
Repair pattern	A plural-readout repair plus capped Reflection control isolates answer-time readout cardinality.

The contribution is the attribution discipline; CQ is the case study used to test what the discipline can detect. The paper collapses the repository’s detailed evidence ledger into four claims, with the following reader contract.

¹A non-archival design sketch is available at [The Consolidation Queue: How Persistent AI Earns Durable Change](#).

Table 2: Reader contract for the methods-first reading of this report.

This paper does not claim	Boundary used in the paper
CQ is broadly superior to immediate-write memory systems.	CQ is a case-study policy. The supported noisy result is mechanism-local: forced contradiction survives cleanly and preference drift survives partially.
The LongMemEval follow-up proves broad external generalization.	The follow-up repairs a v1 evidence-completeness loss caused by answer-time readout cardinality; distractor-heavy retrieval and natural-language QA remain out of scope.
The Mem0-style baseline is a full reproduction of production Mem0.	The baseline is an ADD/UPDATE/NOOP published-family policy over the shared candidate stream and substrate, not the production system.
PFLC is a replacement leaderboard metric or a new pass/fail gate.	PFLC is a diagnostic for whether the policy-facing evidence handle is exposed; it supplements clustering, retrieval, and answer metrics.

Claim 1: Same-stream evaluation makes policy attribution inspectable. Same-stream, same-substrate, extractor-gated evaluation with preserved lifecycle traces removes the main stream, substrate, and extractor-quality confounds. Noisy policy comparison unlocks only after the extractor-quality gate records sufficient component quality. The benchmark fixes the upstream `CandidateUpdate` stream and the scoped memory substrate across policies, then records lifecycle traces, manifests, failure examples, and replay checks.

Claim 2: Standard memory metrics can pass while policy-facing lookup fails. Cluster-partition, retrieval-at-k, and answer-accuracy metrics can all be passed by systems that fail exact policy-facing lookup. A policy-facing lookup contract (PFLC) asks whether the system exposes the evidence handle the policy must actually query, not just whether retrieved text is semantically relevant. PFLC diagnostics name this class of metric blind spots. Proposition 1 and Lemmas 1–2 formalize the gap for clustering, retrieval, and answer metrics; the field survey shows when released benchmark artifacts do or do not expose the handles needed to replay it.

Claim 3: Preserved negative transfer exposes interface failures. A controlled external-transfer pipeline that preserves negative results instead of rescuing them can surface stable interface failures that answer-only, any-hit, or semantic-relevance scoring would hide. The LongMemEval workstream builds a redacted same-stream adapter, hidden-answer protocol, judge gate, PFLC scorer, and contract-sensitivity audit before policy execution. The result is stable and negative for base CQ on `all_hit_at_50`; the missing second evidence session drives the loss.

Claim 4: A paired repair/control isolates readout cardinality. When a transfer-probe loss is paired with both a single-variable interface repair and a capped-baseline control that reproduces the loss on a winning baseline, the loss can be attributed to an interface — here, answer-time readout cardinality — rather than to storage asymmetry or input asymmetry. The separately preregistered follow-up exposes plural pending evidence for CQ and caps a winning Reflection baseline to one returned candidate. Both predictions hold, supporting a mechanism-local repair pattern rather than broad external generalization.




Figure 1: Method-stage view of the four claims. Stage 1 makes policy attribution inspectable by fixing the stream, substrate, and extractor gate. Stage 2 adds PFLC to test whether the policy-facing evidence handle is exposed. Stage 3 preserves the LongMemEval loss and then uses a paired repair/control to isolate answer-time readout cardinality. The figure preserves the claim numbering but frames the contribution as an attribution method.

All empirical claims in this paper cite committed artifacts. Where a result is diagnostic-only, descriptive-only, or blocked by missing artifacts, the paper keeps that boundary in the main text rather than relegating it to a caveat.

2 Related Work

External memory benchmarks. LongMemEval evaluates long-term chat memory across information extraction, multi-session reasoning, knowledge updates, temporal reasoning, and abstention [13]. Here, the released v1 oracle split becomes a controlled-pilot anchor only after a preregistered adapter creates a redacted same candidate stream for all local policies. The resulting PFLC target is dialog-evidence-id completeness over the v1 evidence-only oracle split, so the result should be read as evidence exposure and completeness under a fixed policy surface, with distractor-heavy retrieval quality over LongMemEval-S or LongMemEval-V2 left to future work. LoCoMo is the other key long-conversation benchmark used in the PFLC survey: it collects very long multimodal conversations and evaluates question answering, event summarization, and multimodal dialogue generation [7].

MemoryAgentBench and MemBench are important external-evaluation references because they stress incremental interaction, long-range memory, factual memory, and selective forgetting [5, 11]. They occupy the benchmark lane, separate from this report’s fair-policy-comparison lane, because standard benchmark outputs need not enforce same-candidate-stream and same-substrate constraints. The PFLC survey treats their released artifacts as a diagnostic question: do standard outputs expose the per-question identifiers needed to test whether a memory policy can query the right handle?

Recent and concurrent benchmark efforts broaden this lane further. STATE-Bench measures whether memory improves reliability, task completion, efficiency, and user experience in stateful enterprise tasks [6]. MemGym adds long-horizon agentic tracks across tool-use dialogue, deep research, coding, and computer-use settings [15]. EvoMemBench evaluates self-evolving memory across in-episode/cross-episode and knowledge/execution-oriented axes [12]. These benchmarks broaden what memory systems are tested on; this report narrows how policy-level credit is assigned.

The answer splits. Most surveyed released outputs are artifact-blocked, but published Agent Memory Benchmark (AMB) LoCoMo runs (Hindsight, hybrid-search, Cognee) inject context with

recoverable LoCoMo `dia_ids` and admit a published-output PFLC replay, which decomposes aggregate answer accuracy into evidence exposure, rank, and answer-generation residuals (Section 4.4).

Belief revision and truth maintenance. CQ’s contestation and demotion behavior is adjacent to classical truth maintenance and belief-revision work, which tracked reasons for beliefs, assumption sets, and revision under inconsistent or changing evidence [4, 3, 1]. This paper does not claim a new general belief-revision logic. It uses that lineage as a local memory-policy pattern for LLM agents, adding scoped candidate streams, queryable pending state, and same-stream comparison against eager-write policies.

Memory systems and write policies. Mem0 proposes a production-oriented memory architecture with dynamic memory extraction, update, and retrieval, including a graph variant for relational memory [2]. A-MEM emphasizes dynamic indexing, memory linking, and memory evolution [14]. MemGPT/Letta frames stateful agents through virtual context management and self-editing memory tiers [9]. Zep/Graphiti and Cognee represent graph-oriented memory and retrieval stacks that motivate the related-system lane without defining this report’s fair policy-comparison surface [10, 8]. These systems motivate comparison targets and terminology. The local Mem0-style write-only baseline (`Mem0WritePolicyLite`) is a narrow ADD/UPDATE/NOOP write-time policy over the same candidate stream and substrate as CQ and `ReflectionEagerWriteLite`; that narrowness keeps the policy comparison inspectable. `Mem0WritePolicyLite` is *not* an end-to-end reproduction of the Mem0 system, and our results do not characterize production Mem0; we use this paper-facing label (renamed from the repo identifier `Mem0Lite`) to make that boundary unambiguous to readers.

Preregistration and audit discipline. The methodological stance is closer to a preregistered evaluation audit than to a recall leaderboard. The project locks prediction grids, outcome buckets, adapter pins, judge gates, and follow-up boundaries before running each major comparison. It also records aborts as evidence. The canonical-id resolution audit, for example, refused to emit a verdict twice when locked run JSON payloads could not be reproduced. That posture prevents a methodology repair from becoming a post-hoc result rescue.

This is not a claim that preregistration itself is novel to machine learning. The ML Reproducibility Challenge, preregistration tracks hosted through OpenReview venues, and MLPerf-style standardized evaluation streams are all part of the existing methodological toolkit. The contribution here is narrower: PFLC as a metric-class concept for memory governance, same-stream and same-substrate controls applied to persistent-memory policy comparisons, and a case study that preserves negative external transfer while using paired controls to isolate a specific interface mechanism.

3 Method

3.1 Notation and Evaluation Stages

The core unit is a `CandidateUpdate`: a proposed memory item with claim content, scope key, provenance, evidence links, and lifecycle state. A *durable* memory is committed state. A *pending* candidate is not durable, but CQ can still expose it to scoped lookup while it remains reversible. A *same-stream* comparison gives every policy the same ordered `CandidateUpdate` stream. A *same-substrate* comparison stores every policy’s state through the same scoped memory interface.

PFLC means policy-facing lookup contract: the identifier or handle a memory policy must expose so a query can be evaluated against the intended evidence. The *canonical-id lookup diagnostic* is

this paper’s canonical-id PFLC instance. It reuses the set-membership metric and alias function from the earlier *canonical-id resolution audit*, but it is a small committed diagnostic table rather than a replay of the large noisy same-stream policy comparison run payloads.

This paper uses descriptive names in body text. Appendix A collects the repository-label mapping for artifact navigation. The evaluation has four steps:

- The *prompt-regression guard* runs before noisy component scoring.
- The *noisy extractor-quality gate* scores local extractor outputs and licenses downstream policy comparison.
- The *noisy same-stream policy comparison* runs after that gate passes.
- The *cardinality-repair follow-up* addresses a specific external-transfer interface gap.

Preregistered interpretation labels distinguish a planned gate or thesis condition firing, a completed mixed or partial result, and an abort or surprise-lane boundary that prevents the stronger claim. The 7B and 32B labels denote local extractor model cells, not memory-policy sizes.

3.2 Benchmark Objects

The benchmark centers on scoped candidate updates and a shared memory substrate. Candidate updates carry claim content, scope, provenance, evidence relations, and lifecycle state. All policies receive the same upstream observations. They differ in when they promote, demote, contest, or expose these candidates. The load-bearing invariant is that CQ and the immediate-write baselines compare memory policy over the same inputs.

The principal policies are `ConsolidationQueueLite`, `ReflectionEagerWriteLite`, the Mem0-style baseline (`Mem0WritePolicyLite`), `NaiveEagerWriteLite`, `NoMemoryLite`, and CQ ablations that remove contestation/demotion, pending lookup, source-independence gating, or wider-scope pending override. Two follow-up policies are explicitly outside the original headline set: an oracle-mode dated-evidence repair (artifact label `CQDatedContestation`) and the LongMemEval plural-pending readout repair (artifact label `CQPendingMultiEvidence`). The cardinality-repair follow-up also includes a Reflection readout-cap control (artifact label `ReflectionEagerWriteCardinalityCapped`) as a diagnostic control.




Figure 2: CQ lifecycle. Candidate updates come from the same upstream stream used by every policy in the comparison. CQ differs from eager writing by allowing a candidate to stay pending while still being queryable, by promoting only when support is strong enough, and by preserving contradiction edges so an active durable memory can be contested or demoted. A narrower pending candidate may shadow a wider durable claim for scoped lookup without globally overwriting it.

CQ trace example. Suppose a candidate says the user prefers espresso under the coffee-preference scope. With one source and moderate support, CQ can keep the candidate pending: it is answerable to scoped coffee queries, but it has not become durable memory. Later, a narrower morning-coffee candidate says the user prefers tea in the morning and carries stronger support plus a contradiction edge. CQ records the conflict, lets the narrower pending candidate shadow the broader coffee claim for morning lookups, and, if an older espresso claim had already promoted, demotes that durable record into contested state instead of deleting it. The record’s source history remains inspectable. The eager baseline receives the same candidate stream, but writes immediately.

3.3 Oracle Stage

The oracle stage tests policy behavior when candidate observations, scope keys, contradiction/support relations, and source metadata are known. It includes forced contradiction, scope contamination, preference drift, useful pending memory, false corroboration, memory poisoning, mechanism-diverse frozen held-out scenarios, adversarial upstream noise, and the evidence-conflict spectrum. This stage establishes policy behavior under controlled evidence before extraction quality enters the experiment.

3.4 Noisy Stage

The noisy stage renders transcripts, scores local extractor outputs against component labels, converts accepted predictions into shared candidate streams, and only then runs policies. The component gate has layered checks: aggregate confidence-bound gates, per-family observed gates, frozen mechanism-diverse sentinels, prompt-regression checks, deterministic replay, and exact adapter pin validation. The 7B anchor passed aggregate gates but stayed locked because it had concentrated scenario errors and family/sentinel failures. The preregistered 32B cells cleared the gate and licensed the separate noisy same-stream policy comparison.

3.5 Attribution Stage

Policy results require separate attribution. The mixed-support mechanism audit reads policy-comparison artifacts, component-eval artifacts, ablation patterns, exact policy-query canonical-id alignment, and representative traces. It attributes forced contradiction cleanly to contradiction-edge preservation and contestation/demotion. Preference drift is partial survival: the policy delta remains, but absolute CQ performance drops relative to oracle and the 32B artifacts show residual drift. Other rows remain null, descriptive, or policy-facing lookup-contract failures unless an artifact directly supports a stronger claim.

3.6 Policy-Facing Lookup Contracts

PFLC is operational rather than a metric nicety because the governance operations a persistent-agent memory must support all require identifier-bearing state, not just relevant content. The evaluated operations in this paper are contradiction handling, contestation, demotion, provenance preservation, and scoped override: each must address a specific prior claim by handle, not by paraphrase or similarity. Cluster-partition metrics cannot test this because they are invariant to relabeling. Retrieval-at-k metrics cannot test it because they score content overlap, not handle identity. Answer-accuracy metrics cannot test it because a correct answer can be produced from non-canonical state. Production deletion, right-to-be-forgotten, and enterprise compliance are motivating examples of why a queryable, identifier-bearing memory state matters in deployed systems. This paper does not evaluate them.

PFLC diagnostics ask whether the system exposes the identifier or handle that a memory policy actually needs to query. In plain terms, clustering metrics treat labels as interchangeable, so a system that perfectly groups items into clusters $\{A, B, C\}$ scores 1.00 even if it called them $\{1, 2, 3\}$ internally. A governance query that asks "is item X in slot B?" fails when the system has slot 2 instead. The formal core makes this precise in three parts. Proposition 1 shows that for non-singleton label alphabets and cluster-partition metrics invariant to injective relabeling, the predicted partition can equal the gold partition while set-membership PFLC is zero for a queried gold id. Lemma 1 constructs the same gap for retrieval-at-k metrics: retrieved content can be relevant while the policy-facing evidence id is missing. Lemma 2 constructs it for answer-accuracy metrics: a generated answer can be correct while the system fails to expose the handle needed for memory governance.

The lookup diagnostic instantiates this PFLC class on canonical-id queries within the internal audit. It reuses the locked resolution audit's Section A set-membership metric and alias function, reads a committed per-question source table, and reports Wilson intervals plus a joint B-cubed/lookup table. It is diagnostic and leaves the noisy same-stream policy comparison verdict unchanged.

3.7 Controlled External Transfer

The LongMemEval workstream adapts an external benchmark into a controlled same-stream pilot. The protocol selects LongMemEval v1 as the primary anchor, freezes dual-path annotations, verifies the hidden-answer boundary, pins the adapter, calibrates a local judge, and uses PFLC scoring over answer-session ids. The v1 oracle split is evidence-only, so the PFLC metric measures whether policies preserve and expose gold evidence sessions they received, not whether they search through distractor haystacks.

The LongMemEval transfer probe uses `all_hit_at_50` as the headline metric and preserves `answer_correct` as diagnostic-only because policy answers are structured memory traces. The follow-up keeps the same adapter, judge, and headline metric but changes the policy-facing readout




Figure 3: PFLC formal gap (Proposition 1, worked example). The predicted partition is identical to the gold partition, so any cluster-partition metric (M_{cluster} : B-cubed F1, ARI, NMI, V-measure, pairwise cluster F1) scores 1.00. The injective relabeling ρ maps L_{gold} into Σ with image disjoint from $\{g^*\}$, so set-membership PFLC for the queried id g^* is 0. The two outcomes depend on disjoint properties of the same predicted state: partition structure versus label image.




Figure 4: Controlled LongMemEval externalization. The v1 oracle source is annotated by two independent paths whose agreement is verified before any policy sees data. The redacted adapter strips the gold answer, pins a SHA-locked candidate stream, and feeds the same stream to every policy. The judge calibration gate must clear stability before scoring runs; the PFLC scorer reads policy outputs across three contract-sensitivity cells.

interface under a new preregistration: CQ exposes all eligible same-slot pending candidates, and capped Reflection returns only one durable candidate id at answer time.

4 Results

Table 3 maps the paper’s four claims to their principal evidence anchors. The full artifact index is in Appendix E; this section emphasizes each result’s supported scope.

Table 3: Claim-level evidence ledger.

Claim	Evidence	Readout	Boundary
Same-stream evaluation makes policy attribution inspectable	Frozen oracle sweep; noisy extractor-quality gate; noisy same-stream policy comparison	All 108 frozen oracle deltas matched. The 7B gate blocked a false unlock. The 32B-gated comparison reaches mixed/partial support.	Mechanism-local noisy support.

Claim	Evidence	Readout	Boundary
Standard mem- ory metrics can pass while policy-facing lookup fails	Lookup diagnostic; PFLC proposition and field survey	Five of seven comparison rows pass the B-cubed floor while ex- act canonical-id match is below 5 percent; formal and constructive counterexamples cover clustering, retrieval, and answer metrics.	Diagnostic PFLC; resolution audit verdict unchanged.
Preserved neg- ative transfer exposes interface failures	LongMemEval trans- fer probe	Methodology gates pass, but CQ minus Reflection on <code>all_hit_at_50</code> is -1.0 in all three cells.	Stable base-CQ transfer loss.
A paired re- pair/control isolates readout cardinality	Pending multi- evidence follow-up	<code>CQPendingMultiEvidence</code> moves base CQ from 0/71 to 71/71 on the primary cell; capped Reflec- tion falls from 71/71 to 0/71.	Interface repair; ex- ternal generalization out of scope.

Read the subsections in clusters rather than as independent claims. Oracle Results frames baseline behavior under known evidence; the noisy component gate and same-stream comparison carry Claim 1. The lookup diagnostic and released-artifact PFLC replay carry Claim 2, while the LongMemEval transfer probe carries Claim 3. The all-hit floor is a scoring-property bridge that bounds the follow-up, and the pending multi-evidence follow-up carries Claim 4.

4.1 Oracle Results

The frozen mechanism-diverse oracle sweep matched all preregistered deltas. CQ and the Mem0-style baseline tied on aggregate answer correctness, false assertion, poison promotion, clean durable displacement, and leakage. CQ’s narrower advantage was lower premature promotion, especially on false-corroboration mixed-source rows. The result supports staged promotion as a way to reduce premature durable commitment under oracle inputs; broad answer-quality superiority over the Mem0-style baseline remains outside the supported claim.

The adversarial upstream-noise sweep is similarly mixed. CQ wins retraction, witness conflict, scope narrowing, and pending competition, but loses temporal skew. The post-hoc dated-evidence repair (`CQDatedContestation`) turns base CQ’s temporal-skew abstention into a correct answer from fresher dated evidence and preserves the four original wins. The CQ-vs-Reflection win criterion remains unmet because Reflection also lands at the correctness ceiling.

4.2 Noisy Component Gate and Policy Comparison

The component gate demonstrates why aggregate extractor metrics are insufficient. The locked 7B row passed prompt-regression, determinism, aggregate confidence-bound gates, and aggregate observed gates. It still stayed locked because it had 45 primary scenario errors, eight per-family observed failures, and three frozen-sentinel observed failures. An aggregate-only rule would have authorized a false noisy policy comparison.

The preregistered 32B rows cleared the gate and licensed the noisy same-stream policy comparison. The comparison reaches mixed/partial support: CQ wins against `ReflectionEagerWriteLite` on forced contradiction (delta +0.93, lower confidence bound +0.88) and preference drift (delta +0.13, lower confidence bound +0.07), records no countable directional losses, ties the Mem0-style baseline on frozen sentinel primary metrics, and has no replicate contradictions. The mechanism




Figure 5: Noisy same-stream policy comparison mechanism audit summary. Only forced contradiction is a clean survival row; preference drift is partial, and other rows remain bounded, diagnostic, or descriptive evidence (component defects, lookup-contract failures, the descriptive-only event-source proxy for false corroboration, or the frozen-sentinel held-out tie).

audit narrows this: forced contradiction is the clean mechanism-survival row, preference drift is partial survival, and the remaining rows stay null, descriptive, or bounded by component evidence.

4.3 Lookup Diagnostic and PFLC

The lookup diagnostic adds a second diagnostic layer to several tied rows. On `useful_pending_memory`, `memory_poisoning`, `false_corroboration`, and the frozen sentinel, B-cubed F1 is at or near 1.00 while exact policy-query canonical-id agreement is 0.00. The locked alias-normalized variant also stays at zero on those rows. The diagnostic does not replace the mechanism-audit labels in Figure 5: the `false_corroboration` row remains descriptive-only source-proxy evidence, the mechanism-diverse row remains the frozen sentinel aggregate, and the policy verdict does not change. It shows that the extractor can look cluster-correct while the policy-facing lookup contract fails.

The field-level PFLC work generalizes this observation. Proposition 1 and Lemmas 1–2 show that clustering, retrieval, and answer-accuracy metrics are insufficient evidence of policy-facing lookup success. The four-anchor survey over LongMemEval, Mem0/LoCoMo, MemoryAgentBench, and MemBench splits on artifact accessibility: most released baseline outputs are artifact-blocked, but a subset of published Agent Memory Benchmark (AMB) LoCoMo runs expose recoverable per-question evidence ids and support a published-output PFLC replay. The split is summarized below; benchmark-targeted synthetic counterexample rows ship alongside.

4.4 Released-Artifact PFLC: Blocked vs Replayable

Across the surveyed memory-benchmark artifacts, public outputs divide cleanly into two classes. Most rows—Mem0’s `memory-benchmarks` platform, A-MEM/AgenticMemory, SNAP LoCoMo RAG, Backboard, MemoryLake, Engram, and external AMB comparison rows for Mem0, Zep,

Letta, LangMem, and MemoryBank—do not commit per-question retrieved context, retrieved memory ids, or LoCoMo evidence ids in their released artifacts, and so admit no published-output PFLC replay. Three AMB LoCoMo runs do: Hindsight (1,540 cases), hybrid-search (1,540), and Cognee (152). Each injects per-question context whose source blocks carry recoverable LoCoMo `dia_ids`, enabling a context-derived PFLC replay against the official LoCoMo `qa[].evidence` field.

Table 4: Published-output PFLC on AMB LoCoMo runs (lookup-relevant denominator).

Run	Scored	Lookup-rel.	PFLC@10	PFLC@20	PFLC@50
AMB <code>locomo-hindsight</code>	1,540	1,536	65.8%	83.1%	97.6%
AMB <code>hybrid-search</code>	1,540	1,536	64.8%	75.7%	90.5%
AMB <code>cognee</code>	152	150	60.0%	73.3%	92.0%

The replayable runs are not lookup-contract collapses. They decompose LoCoMo’s aggregate answer accuracy into three components that the aggregate conflates. For example, AMB hybrid-search produces 276 cases where the answer is wrong while every gold evidence `dia_id` is already present in the emitted context by PFLC@50, isolating an answering or judging residual from a retrieval-contract residual. Conversely, 100 cases are correct while all gold evidence is missing at PFLC@50, flagging answer success not fully backed by the LoCoMo evidence contract as scored here. PFLC@10 and PFLC@20 carry the rank-sensitivity signal because Hindsight averages 36,235 context tokens per question.

The operational claim is therefore narrow: once per-question context is published, PFLC decomposes LoCoMo scores into evidence exposure, evidence rank or context saturation, and answer-generation residuals. Without those artifacts, the same decomposition is impossible, which is why the artifact-blocked subset remains the headline survey gap.

4.5 LongMemEval Transfer Probe

The LongMemEval transfer probe produces an inspectable negative external result. The run covers 1,935 policy/cell/case rows across `primary_contract`, `path_a_only_denominator`, and `path_b_only_denominator`. Candidate-stream hash invariants pass in all cells. The headline result is shown in Table 5.

Table 5: LongMemEval transfer probe: CQ-vs-Reflection result.

Cell	<code>all_hit_at_50</code> delta	<code>any_hit_at_50</code> delta
<code>primary_contract</code>	-1.0	0.0
<code>path_a_only_denominator</code>	-1.0	0.0
<code>path_b_only_denominator</code>	-1.0	0.0

The stable sign fires the preregistered-gate condition, but the sign is negative. CQ retrieves at least one gold evidence session in every case and therefore ties eager baselines on `any_hit_at_50`. It never retrieves both evidence sessions, so it loses `all_hit_at_50`. The methodology gate passes, but transfer is CQ-negative and isolates a policy-facing pending-readout gap.

LongMemEval X.4 sensitivity status

CQ – Reflection delta is invariant across the primary and denominator-sensitivity cells.

	primary_contract (n=71)	path_a_only_denominator (n=72)	path_b_only_denominator (n=72)	interpretation
all_hit_at_50 CQ – Reflection	-1.0 loss	-1.0 loss	-1.0 loss	stable completeness loss
any_hit_at_50 CQ – Reflection	+0.0 tie	+0.0 tie	+0.0 tie	stable exposure tie

Figure 6: LongMemEval transfer probe sensitivity status. The CQ-vs-Reflection delta is stable across the primary and denominator-sensitivity cells: -1.0 on `all_hit_at_50` and 0.0 on `any_hit_at_50`.

4.6 All-Hit Metric Floor

The LongMemEval v1 transfer probe is evidence-only: in the committed transfer rows, the observed unique session-id pool for each scored case contains exactly the two gold evidence sessions. A scorer-only random floor therefore exposes a sharp cardinality property of the metric. A singleton readout has zero chance to satisfy `all_hit_at_50`; a random two-session readout has a 100% closed-form floor in all three cells, confirmed by five seeded draws per case. This does not weaken the original base-CQ loss, because base CQ returns only one session. It does bound the follow-up interpretation: the plural-pending readout variant succeeds on v1 by exposing plural same-slot evidence, not by demonstrating broad distractor-heavy retrieval quality.

Table 6: Scorer-only random-readout floor for LongMemEval `all_hit_at_50`.

Cell	Cases	Mean pool	Mean gold	Random $r=1$	Random $r=2$	5-seed $r=2$ band
path_a_only_denominator	72	2.00	2.00	0.0%	100.0%	100.0%–100.0%
path_b_only_denominator	72	2.00	2.00	0.0%	100.0%	100.0%–100.0%
primary_contract	71	2.00	2.00	0.0%	100.0%	100.0%–100.0%

4.7 Pending Multi-Evidence Follow-Up

The follow-up is structured around a paired pre-registration: a CQ-side *repair* hypothesis and a Reflection-side *symmetric falsifier*. The repair hypothesis is that the transfer-probe loss is induced by answer-time readout cardinality, not by CQ-only storage or asymmetric inputs. If that is correct, two things must hold in the same cells. First, the plural-pending readout variant (CQPendingMultiEvidence) must close the gap on `all_hit_at_50`. Second, the capped Reflection control (ReflectionEagerWriteCardinalityCapped) must reproduce the original base-CQ loss with the same magnitude. The plural-pending readout variant changes the no-durable pending fallback to expose all eligible same-slot pending candidates, with no change to storage, adapter, judge, or headline metric. The capped Reflection control preserves Reflection’s winning write path and only caps answer readout to one durable candidate id. The symmetric falsifier is the load-bearing half: it rules out CQ-only storage and asymmetric-input explanations for the loss by reproducing it on a baseline that previously won the metric.

Both predictions hold (Table 7). Plural pending readout moves base CQ from 0/71 to 71/71 in the primary cell. Capping Reflection moves it from 71/71 to 0/71 in the same cell. The pattern is stable across both denominator-sensitivity cells.

Table 7: Pending multi-evidence follow-up on `all_hit_at_50`: the repair (`CQPendingMultiEvidence`) and the symmetric falsifier (`ReflectionEagerWriteCardinalityCapped`).

Cell	Base CQ	Follow-up CQ	Reflection	Capped Reflection
<code>primary_contract</code>	0/71	71/71	71/71	0/71
<code>path_a_only_denominator</code>	0/72	72/72	72/72	0/72
<code>path_b_only_denominator</code>	0/72	72/72	72/72	0/72

The internal regression gate reports maximum checked overall delta 0.0 across forced contradiction, preference drift, mechanism-diverse held-out, adversarial upstream noise, and evidence-conflict spectrum. The committed metrics are aggregate policy rows rather than per-scenario CQ-Multi-vs-base-CQ pairs, so the regression table reports per-family overall deltas only.

Table 8: CQ-Multi internal regression replay over aggregate policy rows.

Family	Scenarios	Checked metrics	Max $ \Delta $	Non-zero deltas
Forced contradiction	25	26	0.000000	none
Preference drift	25	26	0.000000	none
Mechanism-diverse held-out	3	26	0.000000	none
Adversarial upstream noise	25	26	0.000000	none
Evidence-conflict spectrum	25	26	0.000000	none

The aggregate maximum checked overall delta is 0.000000. The committed CQ-Multi CSV artifacts contain policy-summary rows, so this table reports per-family overall deltas only; no per-scenario confidence intervals are inferred from these aggregate files.

Focused negative-control tests confirm that below-floor poisoned siblings, contested siblings, wrong-scope siblings, mirrored-source weak siblings, and demoted siblings are not returned by plural pending lookup. With the symmetric falsifier holding, this mechanism-local repair supports answer-time readout cardinality, not a richer CQ-only memory substrate or broader CQ-vs-Reflection superiority.

5 Discussion

The results map when CQ’s mechanisms remain visible. When the noisy stream preserves contradiction edges and the policy-query surface stays aligned, CQ’s contestation and demotion behavior survives. When the stream or interface omits canonical slots, source identity, scope handles, or the relevant policy-facing identifier, policy ties become evidence about the benchmark surface rather than about policy equivalence.

The negative and mixed rows carry that evidence. The 7B gate shows that aggregate component metrics can hide concentrated failures, while the 32B mixed-support audit leaves several ties as bounded nulls rather than convergence evidence. The lookup diagnostic shows that clustering-quality metrics can pass perfectly while exact lookup handles fail. The LongMemEval transfer shows that an external adapter can pass methodology gates and still produce a stable CQ-negative result; the pending multi-evidence follow-up then isolates one interface failure mechanism without rewriting the original result.




Figure 7: Cardinality-repair follow-up. Changing the CQ pending-readout cardinality from singleton to plural converts a 0/71 loss into a 71/71 win on `all_hit_at_50` in the primary cell. Capping the durable Reflection readout to a single id reproduces the original CQ loss with the same magnitude. The symmetric swap isolates answer-time evidence cardinality as the responsible interface variable; nothing else in the pipeline changes.

The main claim is methodological: same-stream memory-policy evaluation makes policy distinctions auditable. It surfaces both positive mechanism survival (forced contradiction under 32B extraction) and cases where an interface hides the distinction, such as exact policy-query canonical-id failure under perfect clustering or evidence-completeness failure under singleton pending readout.

The CQ case study also illustrates why immediate-write baselines must be strong and fair. Reflection sometimes wins for mechanistically uninteresting reasons, such as overwriting into a durable state that happens to include both evidence sessions, but the comparison remains valid because the baseline received the same stream and used the same substrate. The follow-up uses that interpretation directly: the interface change is registered before execution, and the capped-Reflection control rules out CQ-only storage and asymmetric-input explanations by reproducing the original loss on a winning baseline through a single-variable readout change. This isolates answer-time readout cardinality as the mechanism, but does not generalize to a broader metric-fitting defense.

6 Extractor Reproducibility Check

The extractor reproducibility check bridges failure-taxonomy evidence and noisy policy execution. It reruns the locked 7B anchor and two 32B primary cells under preregistered model tags, schema profiles, digest checks, and frozen sentinel requirements. The 7B anchor reproduces the locked failure counts. Both 32B cells clear the preregistered gate, with zero primary scenario errors, zero primary observed failures, zero aggregate failures, and zero frozen-sentinel observed failures.

This section is intentionally short because the unlock is not itself a memory policy result. Its role is licensing. It shows that the later noisy same-stream policy comparison was not run on an extractor stream that the preregistration would have rejected, while the 7B anchor remains a clean example of an aggregate-passing false unlock that the full gate prevented.

7 Limitations

This is not a broad CQ superiority paper. The noisy-mode support is mechanism-local: CQ separates from `ReflectionEagerWriteLite` on forced contradiction and partially on preference drift under the current 32B artifacts, ties the Mem0-style baseline on the frozen sentinel, and leaves source-independence, scope-contamination, useful-pending, and poisoning-defense rows unsupported. A

stronger extractor could turn those bounded nulls into CQ separations, policy ties, or CQ weaknesses; this revision does not claim any outcome there.

The LongMemEval result is also bounded. The completed transfer probe is stable and negative for base CQ on evidence completeness, and the pending multi-evidence follow-up supports a readout-cardinality repair for that v1 loss. LongMemEval-S is not evaluated here: the 2026-05-25 feasibility gate failed because no local source artifact was available to pin, so no held-out adapter or policy run is authorized in this revision. LongMemEval-V2, distractor-heavy retrieval quality, and natural-language QA success remain future targets; `answer_correct` is diagnostic-only because policy answers are trace-shaped. The follow-up is a controlled evidence-only repair, not a claim that CQ-Multi solves external long-memory retrieval.

PFLC is a diagnostic class rather than a new pass/fail gate. The field-level survey records what released baseline artifacts expose. LoCoMo’s evidence field is a clean gold-side target, and MemoryAgentBench’s conflict-resolution tasks are PFLC-relevant. Most released artifact contracts and standard output surfaces are blocked for PFLC, while the AMB LoCoMo subset admits a published-output replay that decomposes aggregate accuracy without resolving the blocked majority. PFLC is partly an obvious identifier requirement; the contribution is the practical consequence that common clustering, retrieval, and answer metrics do not test that identifier-bearing contract, and many released artifacts do not make it replayable.

The resolution audit replay repair remains an abort. The lookup diagnostic leaves the aborted audit and the noisy same-stream policy comparison’s mixed-support verdict unchanged. A subsequent fresh archived replay was executed under the publication-hardening preregistration §5 and is documented as Bucket `B_inconclusive_min_n`: zero alias-CQR hits surfaced for `useful_pending_memory` or `memory_poisoning` under the locked alias function and the 32B extractor cell, leaving the cross-tab of lookup hit versus per-policy answer success non-evaluatable under the pre-registered minimum-N gate. Prior PFLC null rows for those families remain unattributed, and Claim 2’s null-row attribution is unchanged. The full readout and skip carve-out are recorded in `docs/publication_hardening_step3_results.md` and `docs/publication_hardening_step3_precondition_skip.md`.

The baseline and deployment scope are deliberately narrow. The Mem0-style write-only baseline (`Mem0WritePolicyLite`) is a rule-based ADD/UPDATE/NOOP baseline inspired by Mem0’s write-policy framing, not a reproduction of the Mem0 system. The experiments do not evaluate real-user weeks-long helpfulness, learned semantic scope inference, production retrieval stacks, or API-hosted extractors. A PFLC-surface deletion experiment also remains future work: the current local policies do not expose pre-existing separable policy-facing query surfaces that would support such an experiment without refactoring. The source package and branch-pinned reproduction path for the present claims are recorded in Appendix C.

8 Future Work

Closing bounded-null rows under stronger extraction. The noisy same-stream policy comparison leaves four rows—source-independence, scope-contamination, useful-pending, and poisoning—uninformative under the current extractor: the candidate stream collapses the policies to the same measured outcomes. A preregistered extension would rerun these rows with a stronger extractor, either a larger local model or an API-hosted extractor under the same redacted same-stream guarantee. The prediction is that at least scope-contamination and useful-pending separate CQ from Reflection with a 95% lower confidence bound above zero. If not, we can conclude these rows are policy ties under this benchmark, not merely extraction-floor artifacts.

LongMemEval beyond the v1 transfer probe. The pending multi-evidence repair is scoped to the v1 evidence-only split. The 2026-05-25 LongMemEval-S feasibility gate did not find a local source artifact to pin, so this revision does not run a held-out -S adapter. A future extension must first pin the dataset, inspect the answer/evidence and distractor-session fields, and decide whether filler sessions enter the same candidate stream or only the retrieval surface. If that mechanism-alignment check passes, the extension should keep evidence-id completeness as the primary PFLC target, add `all_hit_at_k` at small k as a precision-sensitive co-primary, and classify the predicted failure mode before unblinding.

External-transfer boundary to conflict resolution. MemoryAgentBench’s conflict-resolution tasks are the closest external surface to CQ’s contestation and demotion mechanism. A rigorous transfer must satisfy three preconditions before policy execution: an adapter that exposes per-question identifiers sufficient for PFLC scoring; hidden-answer verification analogous to the LongMemEval dual-path protocol; and a preregistered abort criterion if the source benchmark does not commit to a stable evidence id across releases. If any precondition fails, we will preregister the transfer as descriptive-only and will not run policies.

Resolving the resolution audit abort. The second of the two acceptable paths has been executed: a fresh replay with hash-pinned manifests ran under the publication-hardening preregistration §5 and is recorded as Bucket `B_inconclusive_min_n` in `docs/publication_hardening_step3_results.md`. Per the repository’s artifact policy, large per-scenario run JSON, component-eval, and prediction payloads remain regeneratable rather than committed; the Step 3 manifest archives their content hashes alongside the noisy-comparison manifests so the replay can be verified byte-for-byte against locally retained component-gate caches plus the runner command. A clean clone must first regenerate the gitignored per-family prediction and component-eval payloads before Step 3 can re-execute. The replay produced zero alias-CQR hits on either thesis family under the locked alias function and 32B extractor cell, so the lookup-versus-answer-success cross-tab is not evaluable. The remaining open question is narrower than before: either a post-hoc preregistered amendment to the alias function, or a stronger extractor cell that surfaces more canonical-id-aliasing candidates, could populate the cross-tab. The first path (materializing the original locked run JSON payloads) is no longer required, because Step 3’s manifests now serve as the new archived canonical record.

PFLC as a benchmark output contract. The field-level PFLC survey divides into an artifact-blocked majority and a PFLC-replayable subset (the AMB LoCoMo runs); the blocked subset is what prevents a uniform diagnostic. A concrete next step is a minimal PFLC output schema—per question, the gold evidence id set and the policy-returned id set—offered as a patch to one surveyed benchmark in the blocked subset. The success criterion is adoption by at least one benchmark maintainer. The acceptable failure criterion is principled rejection on the grounds that the schema cannot represent a specific task family. Silent neglect is the failure mode this paper’s survey already documents and is not acceptable evidence against the schema.

Deployment realism and policy-facing surfaces. Production deletion, right-to-be-forgotten, and enterprise compliance are the natural deployment-realism lane for PFLC. The current local policies are not ready for that experiment because they share the same `answer_question` surface and query the substrate directly, rather than exposing separable policy-facing lookup contracts. A

future deletion experiment should first define those surfaces and deletion semantics, then preregister leakage metrics before any policy execution.

9 Conclusion

Memory metrics can pass while memory policies fail. The CQ case study demonstrates this concretely: same-stream evaluation reveals one clean mechanism-survival row, several bounded nulls, and a stable external-transfer loss that a single-variable repair and a symmetric falsifier together isolate as an answer-time interface gap. None of these results would have been visible to clustering, retrieval, or answer-accuracy scoring alone. The contribution is the evaluation discipline. Its four claims are: same-stream evaluation makes policy attribution inspectable, standard memory metrics can pass while policy-facing lookup fails, preserved negative transfer exposes interface failures, and a paired repair/control isolates readout cardinality. These claims are not CQ superiority. The discipline is portable to other persistent-agent memory systems. The CQ artifacts and preregistration locks are released as worked examples of how to apply it.

References

- [1] Carlos E. Alchourrón, Peter Gärdenfors, and David Makinson. On the logic of theory change: Partial meet contraction and revision functions. *Journal of Symbolic Logic*, 50(2):510–530, 1985.
- [2] Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. Mem0: Building production-ready AI agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*, 2025.
- [3] Johan de Kleer. An assumption-based TMS. *Artificial Intelligence*, 28(2):127–162, 1986.
- [4] Jon Doyle. A truth maintenance system. *Artificial Intelligence*, 12(3):231–272, 1979.
- [5] Yuanzhe Hu, Yu Wang, and Julian McAuley. Evaluating memory in LLM agents via incremental multi-turn interactions. *arXiv preprint arXiv:2507.05257*, 2025.
- [6] Lewis Liu and Nishant Yadav. Introducing STATE-Bench: A benchmark for AI agent memory. Microsoft Open Source Blog, May 2026. Published May 19, 2026.
- [7] Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. Evaluating very long-term conversational memory of LLM agents. *arXiv preprint arXiv:2402.17753*, 2024.
- [8] Vasilije Markovic, Lazar Obradovic, Laszlo Hajdu, and Jovan Pavlovic. Optimizing the interface between knowledge graphs and LLMs for complex reasoning. *arXiv preprint arXiv:2505.24478*, 2025.
- [9] Charles Packer, Sarah Wooders, Kevin Lin, Vivian Fang, Shishir G. Patil, Ion Stoica, and Joseph E. Gonzalez. MemGPT: Towards LLMs as operating systems. *arXiv preprint arXiv:2310.08560*, 2024.
- [10] Preston Rasmussen, Pavlo Paliychuk, Travis Beauvais, Jack Ryan, and Daniel Chalef. Zep: A temporal knowledge graph architecture for agent memory. *arXiv preprint arXiv:2501.13956*, 2025.

- [11] Haoran Tan, Zeyu Zhang, Chen Ma, Xu Chen, Quanyu Dai, and Zhenhua Dong. MemBench: Towards more comprehensive evaluation on the memory of LLM-based agents. In *Findings of the Association for Computational Linguistics: ACL*, 2025.
- [12] Yuyao Wang, Zhongjian Zhang, Mo Chi, Kaichi Yu, Yuhao Li, Miao Peng, Bing Tong, Chen Zhang, Yan Zhou, and Jia Li. EvoMemBench: Benchmarking agent memory from a self-evolving perspective. *arXiv preprint arXiv:2605.18421*, 2026.
- [13] Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. Long-MemEval: Benchmarking chat assistants on long-term interactive memory. In *International Conference on Learning Representations*, 2025.
- [14] Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-MEM: Agentic memory for LLM agents. In *Advances in Neural Information Processing Systems*, 2025.
- [15] Wujiang Xu, Yu Wang, Kai Mei, Kaiqu Liang, Zhenting Wang, Mingyu Jin, Han Zhang, Shi-Xiong Zhang, Wenyue Hua, Sambit Sahu, and Dimitris N. Metaxas. MemGym: a long-horizon memory environment for LLM agents. *arXiv preprint arXiv:2605.20833*, 2026.

A Glossary: Reader-Facing Names and Repository Labels

The paper uses reader-facing descriptive names in body text and introduces the matching repository label once, in parentheses, on first use. This appendix collects the full mapping for readers who encounter a label in the codebase or in committed artifact paths.

Table 9: Glossary: descriptive names and repository labels.

Reader-facing name	Repo label	Meaning
prompt-regression guard	Phase A	Pre-scoring check that the extractor’s prompt has not regressed against locked reference outputs.
noisy extractor-quality gate	Phase 3	Component-quality gate that scores local extractor outputs and licenses downstream policy comparison.
noisy same-stream policy comparison	Phase 4	The main noisy-pipeline policy comparison that runs only after the extractor-quality gate passes.
cardinality-repair follow-up	Phase Y	The LongMemEval follow-up that isolates answer-time readout cardinality as the mechanism behind the transfer-probe loss.
LongMemEval transfer probe	X.4	The controlled-pilot external transfer of the same-stream protocol to LongMemEval v1.
preregistered-gate condition fired	Bucket A	A planned gate or thesis condition fired during a preregistered comparison.
mixed/partial support	Bucket B	A completed result that is mixed or partial; rows split between mechanism-survival, partial survival, and bounded nulls.

Reader-facing name	Repo label	Meaning
abort / unsupported claim	Bucket D	A preregistered abort or surprise-lane boundary that prevents the stronger claim.
lookup diagnostic	QR-canon	The canonical-id PFLC instance: a small committed diagnostic table over per-question canonical ids.
resolution audit	CQR	The earlier canonical-id/query-resolution replay audit whose set-membership metric and alias function the lookup diagnostic reuses.
Mem0-style write-only baseline	MemOLite (repo); Mem0 WritePolicyLite (paper)	Narrow ADD/UPDATE/NOOP write-time baseline; <i>not</i> an end-to-end reproduction of the production Mem0 system. Repo identifier kept stable for artifact compatibility; paper-facing label changed to remove brand collision.
oracle-mode dated-evidence repair	CQDatedContestation (macro \textbackslash cqdated)	Oracle-mode repair variant that prefers dated evidence on temporal-skew rows; used in the adversarial upstream-noise follow-up.
CQ plural-pending readout variant	CQPendingMultiEvidence (macro \textbackslash cqmulti)	CQ-side follow-up that exposes all eligible same-slot pending candidates at answer time; the repair half of the cardinality-repair follow-up.
symmetric capped-Reflection control	ReflectionEagerWrite CardinalityCapped (macro \textbackslash refcapped)	Reflection-side control with answer readout capped to one durable candidate id; the symmetric mechanism falsifier in the cardinality-repair follow-up.

The 7B and 32B labels in body text refer to local extractor model cells used by the noisy pipeline (Qwen2.5-7B-Instruct and Qwen2.5-32B-Instruct, both quantized), not memory-policy sizes.

B Failure Taxonomy

The noisy extractor-quality gate taxonomy groups component failures into four recurring modes: required-field omission, ID-namespace confusion, durable-claim drift into temporary/session framing, and contradiction-edge misses. These categories are used to explain why the 7B aggregate-passing run stayed locked and why some 32B rows remain unsafe to interpret as policy convergence.

Representative inspection traces are:

- `data/results/audit_trace_forced_contradiction_default.html`
- `data/results/audit_trace_scope_contamination_default.html`
- `data/results/audit_trace_useful_pending_memory_default.html`

The traces are qualitative inspection aids. Numeric claims come from metrics, manifests, component summaries, and compact audit evidence.

C Reproducibility

The full source repository, frozen at the tag matching this paper, is at <https://github.com/contromo/consolidation-queue/tree/paper-v2>. The `paper/repro/README.md` entry in that tree is the reviewer entry point and lists local verification commands.

The repository records provenance at several layers: preregistration lock hashes, adapter pins, model tags and digests, prompt/schema profiles, candidate-stream hashes, clean-worktree checks, Python version, commands, and artifact hashes. Small headline verification artifacts are committed. Large per-scenario run payloads are regeneratable-only unless a preregistration requires byte-stable replay.

The paper was prepared on branch `paper/ship-paper-draft`, based on:

`longmemeval-externalization-gate`

The release plan allowed either merging the LongMemEval follow-up branch into `main` or pinning the paper package to the exact branch and commit. Because `main` and the pinned branch diverged after the earlier merge, the paper package uses the branch-pinning path. The reproducibility README in `paper/repro/README.md` records that decision, the final pinned commit, and the commands for local verification.

The resolution audit replay aborts are reproducibility evidence. The path-normalized repair preserved stable checks and still refused to emit a verdict when locked run JSON payloads could not be reproduced. The paper treats that as support for strict replay discipline. The subsequent publication-hardening Step 3 fresh archived replay (`docs/publication_hardening_step3_results.md`) continues that lineage: it executed under preregistered preconditions, archived per-family source-run hashes alongside its own outputs in `data/runs/publication_hardening_step3_manifest.json`, and emitted Bucket `B_inconclusive_min_n` rather than rescuing a verdict.

The revision package also includes two deterministic report-generation scripts for the CQ-Multi aggregate regression table and the LongMemEval all-hit random floor. Both consume committed artifacts only and do not execute memory policies. The LongMemEval-S and PFLC-surface feasibility gates are recorded as no-go/design-note artifacts rather than silently authorizing new policy runs.

D Preregistration Locks

The main preregistration and lock documents are:

- `docs/preregistered_memory_governance_evaluation_template.md`
- `docs/preregistration.md`
- `docs/local_unlock_probe_preregistration.md`
- `docs/noisy_policy_comparison_preregistration.md`
- `docs/adversarial_upstream_noise_preregistration.md`
- `docs/adversarial_upstream_noise_dated_followup_preregistration.md`
- `docs/abstention_quality_preregistration.md`
- `docs/canonical_id_resolution_audit_preregistration.md`

- docs/canonical_id_resolution_audit_repair_preregistration.md
- docs/qr_canon_audit_registration.md
- docs/policy_facing_lookup_contract_registration.md
- docs/fair_stream_externalization_preregistration.md
- docs/cq_pending_multi_evidence_preregistration.md
- docs/publication_hardenening_preregistration.md

The pending multi-evidence follow-up lock SHA is:

84b3c44148494c1b6f72e8201a8da886f8e1f48e49ce00197f535c7e08638840

The publication-hardening lock SHA is:

05671290ae8ebcc665c915521128c18c48b13be075ace55472b5931874672590

The canonical-id PFLC alias function remains the byte-locked resolution-audit alias function; the PFLC workstream does not generalize that alias rule to retrieval-id, slot-id, fact-id, or answer-handle instances.

E Artifact Index

The most important artifact paths for this paper are:

- docs/predictions_vs_results.md
- docs/adversarial_upstream_noise_results.md
- docs/adversarial_upstream_noise_dated_followup_results.md
- docs/abstention_quality_results.md
- data/results/component_gate_decision_general_v1_summary.json
- data/results/component_gate_decision_qwen2_5_7b-instruct-q4_K_M_default_summary.json
- data/results/component_gate_decision_qwen2_5_32b-instruct-q4_K_M_default_summary.json
- data / results / component _ gate _ decision _ qwen2 _ 5 _ 32b-instruct-q4 _ K _ M _ scenario _ conditioned_summary.json
- docs/noisy_policy_comparison_results.md
- data/results/noisy_policy_comparison_summary.json
- docs/noisy_policy_mechanism_audit.md
- data/results/noisy_policy_mechanism_audit_evidence.json
- docs/canonical_id_resolution_audit_results.md
- data/results/canonical_id_resolution_audit_stop_2026-05-15.json
- data/results/canonical_id_resolution_audit_stop_2026-05-16.json
- docs/qr_canon_audit_results.md
- data/results/qr_canon_audit_metrics.csv

- docs/policy_facing_lookup_contract_proposition.md
- docs/qr_canon_field_diagnostic_results.md
- data/results/qr_canon_field_diagnostic_metrics.csv
- docs/locomo_baseline_replay_survey.md
- data/results/locomo_amb_pflc_summary.json
- docs/longmemeval_transfer_results.md
- data/external/longmemeval/transfer_summary.json
- data/external/longmemeval/transfer_per_case_rows.csv
- data/external/longmemeval/transfer_manifest.json
- docs/cq_pending_multi_evidence_results.md
- data/external/longmemeval/transfer_followup_summary.json
- data/external/longmemeval/transfer_followup_per_case_rows.csv
- data/external/longmemeval/transfer_followup_manifest.json
- data/results/cqmulti_per_row_regression_summary.json
- data/external/longmemeval/all_hit_random_floor.json
- docs/longmemeval_s_dataset_pin.json
- docs/longmemeval_s_feasibility_note.md
- docs/pflc_surface_audit_note.md
- docs/publication_hardenening_preregistration.md
- docs/publication_hardenening_step3_precondition_skip.md
- docs/publication_hardenening_step3_results.md
- data/results/publication_hardenening_step3_summary.json
- data/results/publication_hardenening_step3_family_rows.csv
- data/runs/publication_hardenening_step3_manifest.json

Figures ship in two forms. The five conceptual diagrams (CQ lifecycle, evidence ledger, externalization protocol, PFLC formal gap, cardinality-repair follow-up) are TikZ source files under `paper/figures/` that PDFLaTeX compiles inline at build time. The two quantitative charts (noisy same-stream policy comparison mechanism audit; LongMemEval transfer probe cells) are matplotlib output committed as paired PNG/PDF and regenerated from the committed artifacts above by `paper/repro/render_charts.py`. All figure values trace to the documents and result JSONs listed in this index; the AMB LoCoMo PFLC numbers in Section 4.4 come from `data/results/locomo_amb_pflc_summary.json` (SHA recorded in the summary file’s manifest).