

WBMSG

WhatsApp API

Developer Guide

Send messages, manage templates and receive delivery and inbound events from your own application.

Version	1.0 · October 2026
Base URL	<code>https://wbmsg-production.up.railway.app/v1/Account/{auth_id}/</code>
Authentication	HTTP Basic (Auth ID and Auth Token)
Format	JSON requests, JSON responses, form-encoded callbacks
Support	Contact your WBMSG account manager

Contents

1. Getting started
2. Basics: authentication, limits, errors
3. Send a message
4. Read messages
5. Callbacks: delivery status and inbound messages
6. Templates
7. Errors
8. WhatsApp rules to know
9. Support checklist

1. Getting started

1. In the WBMSG dashboard open **Settings > API Credentials**. You need the Settings API permission (organization admins have it).
2. Create a credential. You receive an **Auth ID** (a UUID) and an **Auth Token**. **The token is shown once.** Store it securely. You can rotate it at any time (the old token stops working immediately) or revoke the credential.
3. Optionally set a **status callback URL** and an **inbound URL** on the credential. Both must be public `https` URLs.
4. Your WhatsApp Business number and templates are your own, managed in WBMSG. Conversation charges are billed to you directly by Meta.

An organization can hold up to 10 active credentials. The **Settings > API Usage** page shows request counts, success and error rates per credential and per endpoint.

2. Basics

Item	Detail
Base URL	<code>https://wbmsg-production.up.railway.app/v1/Account/{auth_id}/</code>
Authentication	HTTP Basic. User = Auth ID, password = Auth Token. The <code>{auth_id}</code> in the path must be the same credential.
Request body	JSON, <code>Content-Type: application/json</code>
Rate limit	300 requests per minute per credential. Exceeding it returns HTTP <code>429</code> with a <code>Retry-After</code> header.
Error body	<code>{"api_id", "error", "error_code", "hint"}</code> . See Errors .

HTTP	Meaning
------	---------

200 / 202 / 204	Success. <code>202</code> means a message was queued; <code>204</code> is a successful delete with no body.
400	Validation problem. The <code>error</code> text says what to fix.
401	Missing or wrong credentials.
403	The account is not active, or API access is not available for it.
404	Unknown resource. The same response is used for resources that belong to another account.
413	The request body is too large.
415	The <code>Content-Type</code> is not <code>application/json</code> .
429	Rate limited. Retry after a short pause.
500	Something went wrong on our side. Retry in a few seconds; quote the <code>api_id</code> if it keeps failing.
502	WhatsApp (Meta) could not be reached or refused the request. Safe to retry later.

3. Send a message

POST `/Message/`

Field	Notes
<code>src</code>	Your connected WhatsApp Business number, digits only (for example <code>14155552671</code>).
<code>dst</code>	One or more recipients in international format, separated by <code><</code> . At most 20 per request. Duplicates are removed. Phone numbers may contain digits, an optional leading <code>+</code> , spaces, dashes and parentheses only.
<code>type</code>	<code>whatsapp</code>
One of: <code>text</code> , <code>media_urls</code> , <code>template</code> , <code>interactive</code> , <code>location</code>	Exactly one content field per request. Details below.
<code>url</code>	Optional status callback URL for this request. Overrides the credential's callback URL. Maximum 2000 characters.
<code>method</code>	<code>POST</code> (default) or <code>GET</code> : how the status callback is delivered. Must be <code>GET</code> or <code>POST</code> ; blank means <code>POST</code> .

Content types

- **text:** a string of up to 4096 characters.
- **media_urls:** an array of `https` URLs to an image, video, audio file or document.
- **template:** `{"name": "...", "language": "en", "components": [...]}`. The template must exist in your account with status `APPROVED`, and `language` must be exactly the code the template was created with

(for example `en` or `en_US`). The template `name` uses lowercase letters, digits and underscores only. See the example below.

- **location:** `{"latitude": "...", "longitude": "...", "name": "...", "address": "..."}` , all four as strings.
- **interactive:** reply-button, call-to-action and list messages.

Example: send a template

```
curl -u AUTH_ID:AUTH_TOKEN -H "Content-Type: application/json" \
-X POST https://wbmsg-production.up.railway.app/v1/Account/AUTH_ID/Message/ \
-d '{
  "src": "14155552671",
  "dst": "14155552672<14155552673",
  "type": "whatsapp",
  "template": {
    "name": "order_update",
    "language": "en",
    "components": [
      {"type": "header", "parameters": [{"type": "media", "media":
"https://example.com/logo.png"}]},
      {"type": "body", "parameters": [{"type": "text", "text": "Alex"}, {"type": "text",
"text": "WB-1001"}]}
    ]
  }
}'
```

Response, HTTP 202 :

```
{
  "api_id": "5d935d21-46de-4566-9232-ac9c8a9ce569",
  "message": "message(s) queued",
  "message_uuid": ["426ed7b5-7b63-46b9-a659-39ac815a52cd", "cbe73c0d-..."]
}
```

One `message_uuid` is returned per recipient, in order. The call returns as soon as the message is queued. Delivery is reported by [callbacks](#) or by [reading the message](#).

Template components. `header` takes a media parameter when the template has an image, video or document header. `body` takes one text parameter per `{{1}}`, `{{2}}`, ... placeholder. For numbered variables (`{{1}}`) parameters go in order; for named variables order does not matter. Button parameters use `"type": "button"` with `sub_type` (`quick_reply` or `url`) and `index` .

Example: template with named variables

```
{
  "src": "14155552671",
  "dst": "14155552672",
  "type": "whatsapp",
  "template": {
    "name": "order_confirmation",
    "language": "en",
    "components": [
      { "type": "body", "parameters": [
        { "type": "text", "parameter_name": "username", "text": "Alex" },
        { "type": "text", "parameter_name": "order_id", "text": "WB-1001" }
      ] }
    ]
  }
}
```

For templates with named variables (`{{username}}`) send `parameter_name` on every parameter; order does not matter. For numbered variables (`{{1}}`) omit `parameter_name` . Typical `400` errors:

- `template parameters not matched for BODY: expected [username, order_id]; got [username]`
- `Template "x" not found`
- `Template "x" has no language "en"; available: en_US`
- `Template "x" (en) is not approved (status: pending)`

These checks now return `400` immediately when you send the request (they used to fail later, after queuing):

- wrong number of body parameters for the template
- empty parameter text
- a `parameter_name` sent to a template that uses numbered variables

4. Read messages

GET `/Message/`

Lists the messages sent with your account, newest first.

Query parameter	Notes
<code>limit</code>	Page size, maximum 20 (default 20).
<code>offset</code>	Number of records to skip (default 0).
<code>message_state</code>	Filter by state, for example <code>delivered</code> .
<code>message_direction</code> , <code>message_type</code> , <code>error_code</code>	Optional filters.

The response contains `meta` (`limit` , `offset` , `total_count` , `previous` , `next`) and `objects` .

GET /Message/{message_uuid}/

Returns one message: `message_uuid`, `message_state`, `message_direction`, `message_type`, `to_number`, `from_number`, `error_code`, `error_message` and `message_time`. `error_message` is a readable sentence for `error_code` (`null` when there is no error). See [Errors](#).

message_state	Meaning
queued	Accepted by WBMSG, not yet sent to WhatsApp.
sent	Handed to WhatsApp.
delivered	Delivered to the recipient's phone.
read	Opened by the recipient.
failed	Could not be sent. See <code>error_code</code> .
undelivered	Sent, but WhatsApp could not deliver it. See <code>error_code</code> .

5. Callbacks

Delivery status callbacks

WBMSG calls your callback URL each time a message changes state. The call is a form-encoded `POST` (or a query-string `GET` if you chose `method=GET`) with these fields:

Field	Notes
MessageUUID	The id returned when you sent the message.
To , From	Recipient and your business number.
Type	whatsapp
Status	queued , sent , delivered , read , failed or undelivered
ErrorCode	Only present when <code>Status</code> is failed or undelivered . See error codes .
ErrorMessage	A readable sentence explaining <code>ErrorCode</code> . Present together with it.
Sequence	Increases with each status change of the same message. Use it to ignore out-of-order calls.
MessageTime	Time of the status change.

Reply with any `2xx` status within a few seconds. If your endpoint fails or times out, WBMSG retries after 60, 120 and 240 seconds.

Inbound messages

Messages your customers send to your WhatsApp number are forwarded to your inbound URL as a form-encoded `POST` with `From`, `To`, `Text`, `Type` and `MessageUUID`.

Verifying a callback

Every callback carries two headers:

- `X-WBMSG-Signature` : the signature
- `X-WBMSG-Signature-Nonce` : a random value used in the signature

Compute `base64( HMAC-SHA256( key = your Auth Token, message = callback_url_without_query_string + nonce ) )` and compare it with the header. Reject the callback if they differ.

```
// Node.js
const crypto = require("crypto");
function valid(url, nonce, signature, authToken) {
  const base = url.split("?")[0];
  const expected = crypto.createHmac("sha256", authToken).update(base + nonce).digest("base64");
  return crypto.timingSafeEqual(Buffer.from(expected), Buffer.from(signature));
}
```

Callbacks are only sent to public `https` addresses. Private, internal and local addresses are refused.

6. Templates

All template calls use `/WhatsApp/Template/{waba_id}/`, where `waba_id` is your WhatsApp Business Account ID. Any other id returns `404`. `template_id` is the id WhatsApp assigns to the template.

POST `/WhatsApp/Template/{waba_id}/`

Creates a template and submits it to WhatsApp for review.

Field	Notes
<code>name</code>	Lowercase letters, digits and underscores.
<code>language</code>	For example <code>en</code> or <code>en_US</code> . Use the same code when sending.
<code>category</code>	<code>MARKETING</code> , <code>UTILITY</code> or <code>AUTHENTICATION</code>
<code>components</code>	Must include a <code>BODY</code> . May also include <code>HEADER</code> , <code>FOOTER</code> and <code>BUTTONS</code> . An image, video or document header needs <code>example.header_handle</code> (a WhatsApp upload handle).
<code>allow_category_change</code>	Optional boolean. Lets WhatsApp re-categorize the template if it judges the category wrong.

```
curl -u AUTH_ID:AUTH_TOKEN -H "Content-Type: application/json" \
-X POST https://wbmsg-production.up.railway.app/v1/Account/AUTH_ID/WhatsApp/Template/WABA_ID/ \
-d '{
  "name": "account_update",
  "language": "en",
  "category": "UTILITY",
  "components": [
    {"type": "BODY",
     "text": "Hi {{1}}, your account setup was updated. Reference: {{2}}.",
     "example": {"body_text": [{"Alex", "WB-1001"}]}},
    {"type": "FOOTER", "text": "Example Company"}
  ]
}'
```

Response: {"api_id": "...", "status": "success", "message": "template submitted to meta for review", "template_id": "1098860766374195", "template_name": "account_update", "template_status": "PENDING", "template_language": "en", "template_category": "UTILITY"}

GET /WhatsApp/Template/{waba_id}/

Lists templates. Query: `template_name` (substring filter), `limit` (maximum 20), `offset`. Returns `meta` and `objects`, each with `template_id`, `name`, `language`, `category` and `status`.

GET /WhatsApp/Template/{waba_id}/{template_id}/

Returns one template with `quality_score` ({"score": "GREEN"} and similar), `rejected_reason` and the full `components`.

POST /WhatsApp/Template/{waba_id}/{template_id}/

Edits a template's components. The body has the same shape as `create`. `name`, `language` and `category` cannot change. Only **approved**, **rejected** and **paused** templates can be edited; the template returns to review. WhatsApp limits how often a template can be edited.

DELETE /WhatsApp/Template/{waba_id}/{template_id}/?name={template_name}

Deletes the template at WhatsApp and in WBMSG. `name` is required and must match the template. Returns `204`. If WhatsApp refuses, the template is kept and you receive `502`.

Template status values

Status	Meaning
PENDING	Under review. Utility templates are often approved within minutes; others can take up to 24 hours.
APPROVED	Ready to send.
REJECTED	Not approved. <code>rejected_reason</code> says why. Edit and resubmit.
PAUSED	Paused by WhatsApp after poor quality feedback. Cannot be sent until it recovers.
DISABLED	Disabled by WhatsApp. Cannot be sent.
IN_APPEAL	A review of a rejection or restriction is in progress.

FLAGGED	At risk of being disabled because of quality issues.
LIMIT_EXCEEDED	The template count or sending limit for the account was reached.
PENDING_DELETION	Scheduled for deletion.
ARCHIVED	Removed from use.

7. Errors

Every failed API call returns a JSON body with the same four fields:

```
{
  "api_id": "3f1c2a9e-5b7d-4e0a-9c11-2d8f6a4b7e90",
  "error": "Template \"order_confirmation\" not found",
  "error_code": "TEMPLATE_NOT_FOUND",
  "hint": "Check the template name and language in your WBMSG account."
}
```

- `api_id` : identifies this exact request on our side. **Quote it when you contact support**; it lets us find the request immediately.
- `error` : what went wrong, in a sentence. For validation errors it names the field to fix.
- `error_code` : a stable code (table below). Branch your code on this, not on the `error` text, which can change.
- `hint` : a suggestion for fixing the problem. It is advice and may be absent.

On HTTP 429 the response also carries a `Retry-After` header with the number of seconds to wait before retrying.

error_code	HTTP	Meaning	What to do
INVALID_JSON	400	The request body is not valid JSON.	Send a JSON object with <code>Content-Type: application/json</code> .
EMPTY_BODY	400	The request body is empty.	Send a JSON object with <code>Content-Type: application/json</code> .
UNSUPPORTED_CONTENT_TYPE	415	Content-Type must be application/json.	Add the header <code>Content-Type: application/json</code> . A <code>text/plain</code> body is not rejected with 415: it is read as text and returns 400 <code>VALIDATION_FAILED</code> "Request body must be a JSON object" with a Content-Type hint.
BODY_TOO_LARGE	413	The request body is too large.	Reduce the size of the request.
VALIDATION_FAILED	400	The request is invalid.	The <code>error</code> text names the missing or invalid field. Fix it and send again. Also used when WhatsApp rejects a template you create or edit.

TEMPLATE_PARAMS_MISMATCH	400	The template parameters do not match the template.	Send one parameter for every variable in the template body and header, using the same names (or numbers) as the template.
TEMPLATE_NOT_FOUND	400 when sending, 404 on the template endpoints	Template not found.	When sending (400): check the template name and language in your WBMSG account. On the template endpoints (404): check the waba_id and template_id in the URL.
TEMPLATE_NOT_APPROVED	400	The template is not approved.	Only approved templates can be sent. Check its status in your WBMSG account.
WHATSAPP_NOT_CONNECTED	400	No WhatsApp number is connected to this account.	Connect a WhatsApp Business number in WBMSG first.
SRC_MISMATCH	400	src is not the WhatsApp Business number connected to this account.	Set src to the connected number.
CALLBACK_URL_INVALID	400	The callback url is not allowed.	Use a public https URL.
AUTH_MISSING	401	The Authorization header is missing.	Use HTTP Basic auth: auth_id as the username and the auth token as the password.
AUTH_MALFORMED	401	The Authorization header is not valid Basic auth.	Use HTTP Basic auth: <code>base64(auth_id:auth_token)</code> .
AUTH_ID_MISMATCH	401	The auth_id in the URL does not match the username in the Authorization header.	Use the same auth_id in <code>/v1/Account/{auth_id}/</code> and as the Basic-auth username.
AUTH_INVALID	401	The auth_id or auth token is invalid, or the credential was revoked.	Check both values, or create a new credential in WBMSG under Settings > API Credentials.
ACCOUNT_INACTIVE	403	This account is not active.	Contact WBMSG support.
API_NOT_AVAILABLE	403	API access is not available for this account.	Contact WBMSG support to enable it.
MESSAGE_NOT_FOUND	404	Message not found.	Check the message_uuid ; it must belong to this account.

NOT_FOUND	404	The requested resource was not found.	Check the URL path and the id in it. Unknown paths under <code>/v1/Account/{auth_id}/</code> return this error.
RATE_LIMITED	429	Too many requests.	Wait for the number of seconds in the <code>Retry-After</code> header, then retry.
QUEUE_FAILED	500	We could not queue your message.	Nothing was sent. Retry in a few seconds. If it keeps failing, contact support and quote the <code>api_id</code> .
INTERNAL_ERROR	500	Something went wrong on our side. Your request was not processed.	Retry in a few seconds. If it keeps failing, contact support and quote the <code>api_id</code> .
META_UNAVAILABLE	502	WhatsApp (Meta) did not accept the request right now.	Retry later. If it keeps failing, contact support and quote the <code>api_id</code> .

Any other `4xx` status not listed above is returned as `VALIDATION_FAILED`.

Failures after a message is accepted

A `202` means the message was queued, not delivered. If it later fails, the outcome is reported on the message itself:

- In the status callback: `ErrorCode` plus a readable `ErrorMessage` (only when `Status` is `failed` or `undelivered`).
- In `GET /Message/{message_uuid}/` and the list: `error_code` plus `error_message`.

ErrorCode	ErrorMessage
310	The sending phone number is not registered on the WhatsApp Business Platform.
330	WhatsApp does not support this message type. Check the message type and try again.
340	The template does not exist in this language, is not approved, or has been paused or disabled. Check its status in WBMSG.
350	The template parameters do not match the template (count, format or length). Send values for every parameter in the format the template defines.
360	The WhatsApp Business account is restricted or failed verification. Contact support.
370	WhatsApp is limiting sending from this number right now (too many messages too fast, too many to one recipient, or a spam/quality restriction). Retry later; if it persists, check your number's quality in WBMSG or contact support.
380	The customer has not replied in the last 24 hours, so only an approved template message can be sent.
131049	WhatsApp did not deliver this marketing message to this recipient to keep engagement healthy. Wait at least 24 hours before trying again.

131026	WhatsApp could not deliver the message. The recipient may not be a WhatsApp user, may not have accepted WhatsApp's terms, or may be on an outdated WhatsApp version.
any other number	WhatsApp's own error code, passed through unchanged. <code>ErrorMessage</code> is "WhatsApp could not deliver the message (code N)." with the code in place of N.

Error 131049. WhatsApp limits how many marketing templates one person receives from businesses in a period, and may decline to deliver the message. Do not retry immediately. Wait at least 24 hours before resending a marketing template to the same person. Utility templates are not affected, and messages sent inside an open 24-hour window are not counted. Details for any failure are in the WBMSG Message Log.

8. WhatsApp rules to know

- **24-hour window.** Free-form messages (text, media, interactive, location) can only be delivered within 24 hours after the customer last messaged you. Outside the window, use an approved template.
- **Templates are reviewed by WhatsApp.** Keep utility templates plainly transactional. Promotional wording makes WhatsApp classify them as marketing.
- **Opt-in.** Only message people who agreed to hear from you on WhatsApp.
- **Quality.** Low quality feedback can pause a template or limit your number. Watch `quality_score` on your templates.

9. Support checklist

When you contact support, include: the `message_uuid` or `api_id`, the time with its time zone, and your Auth ID. **Never send your Auth Token.**