

WBMSG

WhatsApp API

Developer Guide

Send messages, manage templates and receive delivery and inbound events from your own application.

Version	1.0 · October 2026
Base URL	<code>https://wbmsg-production.up.railway.app/v1/Account/{auth_id}/</code>
Authentication	HTTP Basic (Auth ID and Auth Token)
Format	JSON requests, JSON responses, form-encoded callbacks
Support	Contact your WBMSG account manager

Contents

1. Getting started
2. Basics: authentication, limits, errors
3. Send a message
4. Read messages
5. Callbacks: delivery status and inbound messages
6. Templates
7. Error codes
8. WhatsApp rules to know
9. Support checklist

1. Getting started

1. In the WBMSG dashboard open **Settings > API Credentials**. You need the Settings API permission (organization admins have it).
2. Create a credential. You receive an **Auth ID** (a UUID) and an **Auth Token**. **The token is shown once.** Store it securely. You can rotate it at any time (the old token stops working immediately) or revoke the credential.
3. Optionally set a **status callback URL** and an **inbound URL** on the credential. Both must be public `https` URLs.
4. Your WhatsApp Business number and templates are your own, managed in WBMSG. Conversation charges are billed to you directly by Meta.

An organization can hold up to 10 active credentials. The **Settings > API Usage** page shows request counts, success and error rates per credential and per endpoint.

2. Basics

Item	Detail
Base URL	<code>https://wbmsg-production.up.railway.app/v1/Account/{auth_id}/</code>
Authentication	HTTP Basic. User = Auth ID, password = Auth Token. The <code>{auth_id}</code> in the path must be the same credential.
Request body	JSON, <code>Content-Type: application/json</code>
Rate limit	300 requests per minute per credential. Exceeding it returns HTTP <code>429</code> .
Error body	<code>{"api_id": "<uuid>", "error": "<message>"}</code>

HTTP	Meaning
200 / 202 / 204	Success. <code>202</code> means a message was queued; <code>204</code> is a successful delete with no body.

400	Validation problem. The <code>error</code> text says what to fix.
401	Missing or wrong credentials.
403	The account is not active, or API access is not available for it.
404	Unknown resource. The same response is used for resources that belong to another account.
429	Rate limited. Retry after a short pause.
502	WhatsApp (Meta) could not be reached or refused the request. Safe to retry later.

3. Send a message

POST `/Message/`

Field	Notes
<code>src</code>	Your connected WhatsApp Business number, digits only (for example <code>918269150291</code>).
<code>dst</code>	One or more recipients in international format, separated by <code><</code> . At most 20 per request. Duplicates are removed.
<code>type</code>	<code>whatsapp</code>
One of: <code>text</code> , <code>media_urls</code> , <code>template</code> , <code>interactive</code> , <code>location</code>	Exactly one content field per request. Details below.
<code>url</code>	Optional status callback URL for this request. Overrides the credential's callback URL.
<code>method</code>	<code>POST</code> (default) or <code>GET</code> : how the status callback is delivered.

Content types

- **text**: a string of up to 4096 characters.
- **media_urls**: an array of `https` URLs to an image, video, audio file or document.
- **template**: `{"name": "...", "language": "en", "components": [...]}` . The template must exist in your account with status `APPROVED` , and `language` must be exactly the code the template was created with. See the example below.
- **location**: `{"latitude": "...", "longitude": "...", "name": "...", "address": "..."} , all four as strings.`
- **interactive**: reply-button, call-to-action and list messages.

Example: send a template

```
curl -u AUTH_ID:AUTH_TOKEN -H "Content-Type: application/json" \
-X POST https://wbmsg-production.up.railway.app/v1/Account/AUTH_ID/Message/ \
-d '{
  "src": "918269150291",
  "dst": "919876543210<918109760150",
  "type": "whatsapp",
  "template": {
    "name": "order_update",
    "language": "en",
    "components": [
      {"type": "header", "parameters": [{"type": "media", "media":
"https://example.com/logo.png"}]},
      {"type": "body", "parameters": [{"type": "text", "text": "Alex"}, {"type": "text",
"text": "WB-1001"}]}
    ]
  }
}'
```

Response, HTTP 202 :

```
{
  "api_id": "5d935d21-46de-4566-9232-ac9c8a9ce569",
  "message": "message(s) queued",
  "message_uuid": ["426ed7b5-7b63-46b9-a659-39ac815a52cd", "cbe73c0d-..."]
}
```

One `message_uuid` is returned per recipient, in order. The call returns as soon as the message is queued. Delivery is reported by [callbacks](#) or by [reading the message](#).

Template components. `header` takes a media parameter when the template has an image, video or document header. `body` takes one text parameter per `{{1}}`, `{{2}}`, ... placeholder, in order. Button parameters use `"type": "button"` with `sub_type` (`quick_reply` or `url`) and `index`.

4. Read messages

GET /Message/

Lists the messages sent with your account, newest first.

Query parameter	Notes
<code>limit</code>	Page size, maximum 20 (default 20).
<code>offset</code>	Number of records to skip (default 0).
<code>message_state</code>	Filter by state, for example <code>delivered</code> .
<code>message_direction</code> , <code>message_type</code> , <code>error_code</code>	Optional filters.

The response contains `meta` (`limit`, `offset`, `total_count`, `previous`, `next`) and `objects`.

GET /Message/{message_uuid}/

Returns one message: `message_uuid` , `message_state` , `message_direction` , `message_type` , `to_number` , `from_number` , `error_code` and `message_time` .

message_state	Meaning
queued	Accepted by WBMSG, not yet sent to WhatsApp.
sent	Handed to WhatsApp.
delivered	Delivered to the recipient's phone.
read	Opened by the recipient.
failed	Could not be sent. See <code>error_code</code> .
undelivered	Sent, but WhatsApp could not deliver it. See <code>error_code</code> .

5. Callbacks

Delivery status callbacks

WBMSG calls your callback URL each time a message changes state. The call is a form-encoded `POST` (or a query-string `GET` if you chose `method=GET`) with these fields:

Field	Notes
<code>MessageUUID</code>	The id returned when you sent the message.
<code>To</code> , <code>From</code>	Recipient and your business number.
<code>Type</code>	<code>whatsapp</code>
<code>Status</code>	<code>queued</code> , <code>sent</code> , <code>delivered</code> , <code>read</code> , <code>failed</code> or <code>undelivered</code>
<code>ErrorCode</code>	Only present when <code>Status</code> is <code>failed</code> or <code>undelivered</code> . See error codes .
<code>Sequence</code>	Increases with each status change of the same message. Use it to ignore out-of-order calls.
<code>MessageTime</code>	Time of the status change.

Reply with any `2xx` status within a few seconds. If your endpoint fails or times out, WBMSG retries after 60, 120 and 240 seconds.

Inbound messages

Messages your customers send to your WhatsApp number are forwarded to your inbound URL as a form-encoded `POST` with `From` , `To` , `Text` , `Type` and `MessageUUID` .

Verifying a callback

Every callback carries two headers:

- `X-WBMSG-Signature` : the signature
- `X-WBMSG-Signature-Nonce` : a random value used in the signature

Compute `base64( HMAC-SHA256( key = your Auth Token, message = callback_url_without_query_string + nonce ) )` and compare it with the header. Reject the callback if they differ.

```
// Node.js
const crypto = require("crypto");
function valid(url, nonce, signature, authToken) {
  const base = url.split("?")[0];
  const expected = crypto.createHmac("sha256", authToken).update(base + nonce).digest("base64");
  return crypto.timingSafeEqual(Buffer.from(expected), Buffer.from(signature));
}
```

Callbacks are only sent to public `https` addresses. Private, internal and local addresses are refused.

6. Templates

All template calls use `/WhatsApp/Template/{waba_id}/`, where `waba_id` is your WhatsApp Business Account ID. Any other id returns `404`. `template_id` is the id WhatsApp assigns to the template.

POST `/WhatsApp/Template/{waba_id}/`

Creates a template and submits it to WhatsApp for review.

Field	Notes
<code>name</code>	Lowercase letters, digits and underscores.
<code>language</code>	For example <code>en</code> or <code>en_US</code> . Use the same code when sending.
<code>category</code>	<code>MARKETING</code> , <code>UTILITY</code> or <code>AUTHENTICATION</code>
<code>components</code>	Must include a <code>BODY</code> . May also include <code>HEADER</code> , <code>FOOTER</code> and <code>BUTTONS</code> . An image, video or document header needs <code>example.header_handle</code> (a WhatsApp upload handle).
<code>allow_category_change</code>	Optional boolean. Lets WhatsApp re-categorize the template if it judges the category wrong.

```
curl -u AUTH_ID:AUTH_TOKEN -H "Content-Type: application/json" \
-X POST https://wbmsg-production.up.railway.app/v1/Account/AUTH_ID/WhatsApp/Template/WABA_ID/ \
-d '{
  "name": "account_update",
  "language": "en",
  "category": "UTILITY",
  "components": [
    {"type": "BODY",
     "text": "Hi {{1}}, your account setup was updated. Reference: {{2}}.",
     "example": {"body_text": [{"Alex", "WB-1001"}]}},
    {"type": "FOOTER", "text": "Example Company"}
  ]
}'
```

Response: {"api_id": "...", "status": "success", "message": "template submitted to meta for review", "template_id": "1098860766374195", "template_name": "account_update", "template_status": "PENDING", "template_language": "en", "template_category": "UTILITY"}

GET /WhatsApp/Template/{waba_id}/

Lists templates. Query: `template_name` (substring filter), `limit` (maximum 20), `offset`. Returns `meta` and `objects`, each with `template_id`, `name`, `language`, `category` and `status`.

GET /WhatsApp/Template/{waba_id}/{template_id}/

Returns one template with `quality_score` ({"score": "GREEN"} and similar), `rejected_reason` and the full `components`.

POST /WhatsApp/Template/{waba_id}/{template_id}/

Edits a template's components. The body has the same shape as `create`. `name`, `language` and `category` cannot change. Only **approved**, **rejected** and **paused** templates can be edited; the template returns to review. WhatsApp limits how often a template can be edited.

DELETE /WhatsApp/Template/{waba_id}/{template_id}/?name={template_name}

Deletes the template at WhatsApp and in WBMSG. `name` is required and must match the template. Returns `204`. If WhatsApp refuses, the template is kept and you receive `502`.

Template status values

Status	Meaning
PENDING	Under review. Utility templates are often approved within minutes; others can take up to 24 hours.
APPROVED	Ready to send.
REJECTED	Not approved. <code>rejected_reason</code> says why. Edit and resubmit.
PAUSED	Paused by WhatsApp after poor quality feedback. Cannot be sent until it recovers.
DISABLED	Disabled by WhatsApp. Cannot be sent.
IN_APPEAL	A review of a rejection or restriction is in progress.

FLAGGED	At risk of being disabled because of quality issues.
LIMIT_EXCEEDED	The template count or sending limit for the account was reached.
PENDING_DELETION	Scheduled for deletion.
ARCHIVED	Removed from use.

7. Error codes

`ErrorCode` appears on failed and undelivered messages, in callbacks and when reading a message.

Code	Meaning
310	The phone number is not registered on WhatsApp.
330	The message type is not supported.
340	The template does not exist, is paused or is disabled.
350	Template parameters do not match the template (wrong count or format).
360	The WhatsApp Business account is locked or disabled.
370	WhatsApp throughput or rate limit reached. Slow down and retry.
380	More than 24 hours since the customer last wrote to you. Send an approved template instead.
6-digit number	WhatsApp's own error code, passed through unchanged (for example <code>131049</code>). Details for any failure are in the WBMSG Message Log.

Error 131049. WhatsApp limits how many marketing templates one person receives from businesses in a period, and may decline to deliver the message. Do not retry immediately. Wait at least 24 hours before resending a marketing template to the same person. Utility templates are not affected, and messages sent inside an open 24-hour window are not counted.

8. WhatsApp rules to know

- **24-hour window.** Free-form messages (text, media, interactive, location) can only be delivered within 24 hours after the customer last messaged you. Outside the window, use an approved template.
- **Templates are reviewed by WhatsApp.** Keep utility templates plainly transactional. Promotional wording makes WhatsApp classify them as marketing.
- **Opt-in.** Only message people who agreed to hear from you on WhatsApp.
- **Quality.** Low quality feedback can pause a template or limit your number. Watch `quality_score` on your templates.

9. Support checklist

When you contact support, include: the `message_uuid` or `api_id`, the time with its time zone, and your Auth ID. **Never send your Auth Token.**