

SINCE 1977



CARAVEL



CARAVEL 1 CV



CARAVEL 2 CV COMPACT



CARAVEL 2 CV



CARAVEL 3 CV

CARAVEL

	CARAVEL 1	CARAVEL 2 COMPACT	CARAVEL 2	CARAVEL 3
Groups Grupos	1	2	2	3
Temperature control Controlo de temperatura	PRESSOSTAT / PRESSÓSTATO			
Boiler technology Tecnologia de caldeira	SINGLE BOILER HEAT EXCHANGER / CALDEIRA COM SISTEMA TERMOSSIFÓNICO			
Boiler capacity Capacidade da caldeira	51	6.5	11	18 I
Power Potência	1.95 kW	2.7 kW	3.7 kW	5.2 kW
Voltage Alimentação	~220-240 V ⁽¹⁾	~220-240 V ⁽¹⁾	~220-240 V ⁽¹⁾	~220-240 V/ 400 V ~2N
LED lights Iluminação LED	optional / opcional	optional / opcional	optional / opcional	optional / opcional
Steam wands Lanças de vapor	1	1	2	2
Water tap Torneira de água	1	1	1	1
Cup warmer Escalda-chávenas	-	-	yes / sim	yes / sim
Standard Colors Cores standard	• 0	• 0	• 0	• 0
Other colors / Customization Outras cores / Personalização	yes / sim	yes / sim	yes / sim	yes / sim
Automatic cleaning Limpeza automática	CV MODEL / MODELO CV	CV MODEL / MODELO CV	CV MODEL / MODELO CV	CV MODEL / MODELO CV
Dimensions Tall Cups Dimensões Tall Cups	475x563x530 mm	475x563x530 mm	665x563x530 mm	875x563x530 mm
Dimensions Small Cups Dimensões Small Cups	475x563x530 mm	475x563x530 mm	665x563x530 mm	875x563x530 mm
Packaging Embalagem	630x630x670 mm	630x630x670 mm	790x630x670 mm	1080x710x740 mm
Weight (Gross/net) Peso (bruto/líquido)	56 kg / 45 kg	62 kg / 52.5 kg	77 kg / 59 kg	94 kg / 76 kg

(1) optional 110V / opcional 110V







