





- | | |
|--|-----------------------|
| 1. Power cable entry 3x1,5 (230Vx1-50Hz) | 4. Equipotential |
| 2. Water drain pipe Ø30 Hmax=13cm. | 5. Dosing pumps entry |
| 3. Water loading pipe Ø3/4"G | |



- Single wall.
- Tank with rounded corners.
- Fully automatic operation with electromechanical controls.
- Magnetic microswitch to cut out operation of the appliance when door is opened.
- Useful washing height 25 cm.
- Square basket 35x35 cm. (supplied with 1 basket for glasses, 1 saucer insert, 1 cutlery holder).
- Independent lower washing and rinsing arms (upper rinsing arm only).
- Washing cycle time 150 seconds (capacity 800 pz/h).

- Standard built-in rinse-aid pump.
- Built-in insulated boiler made in AISI 304L stainless steel.
- Boiler and tank heating through thermostatically protected armoured heating elements (in exchange).
- Tank capacity lt. 9,5 and boiler capacity lt. 3,7.
- Water consumption per cycle lt. 2,9 - Water pressure input ATE 1,5-3,0 - Max temperature of inlet water 50°C.
- Tank heating element kW 1,4 - Boiler heating element kW 3,0.
- Washing pump power Hp 0,27.
- Noise level at 1 mt. < 70 dbA.
- Total power kW 3,23.