BT-R101 (R290) BlastChiller ShockFreezer

TECHNICAL FEATURES:

- Made of AISI 304 stainless steel, exterior with scotch-brite finish
- Interior in AISI 304 polished finish
- High density polyurethane foam insulation until 60 mm thick

- Shaped internal bottom for containment, with central drain for washing and defrosting water
- Magnetic seals on 4 sides of the door
- Heating element to ensure perfect adherence of the door gasket.
- Door lock at 110 ° for inserting levels

INTERNAL SETUP:

- Tray holder structure in AISI304 stainless steel, easily removable for easy cleaning
- Microswitch that blocks the ventilation when the door is opened
- Conical core probe included

FUNCTIONS:

- Blast Chilling SOFT and HARD
- Shock Freezing SOFT and HARD
- Time control or with core probe

- Automatic storage at the end of the cycle
- Manual defrosting
- Fish sanitization
- Ice-cream hardening

COOLING SYSTEM:

- Environmentally friendly refrigerant gas R290
- Standard air condensation
- Evaporator with anti-corrosion cataphoresis treatment

- High thermal output condenser

- High pressure fans
- Climate class 5

CONTROL BOARD:

- Electronic touch control
- HACCP system with alarms storage

SETUP:

| 10 LEVELS	530x325 + 600x400	REMOVABLE TRAYHOLDER PITCH 67 mm	Touch control DISPLAY 5"

GN 1/1 600x400

FEATURES:

STAINLESS STEEL AISI304	THICKNESS 60 mm	REMOVABLE DOOR GASKET WITHOUT TOOLWS

AISI 304 — 60

| INDIRECT AIRFLOW	EVAPORATOR WITH CATAPHORESIS TREATMENT	DEFROSTING WITH VENTILATION	CONICAL CORE PROBE

The company reserves the right to make any necessary changes to improve the product.

PRIMAX

BT-R101 (R290) BlastChiller ShockFreezer

TECHNICAL SHEET	BT-R101
Automatic, by compressor stop mm	GN1/1-EN1 (600x400)
Total	10
Pitch mm	70
Trays insertion	CROSSWISE
Net dimensions (LxWxH) mm	820x825x1690
Depth with 90° door mm	1580
Door opening (WxH) mm	715x770
Net nternal depth mm	465
Internal volume l	
Insulation thickness mm	60
Insulated floor thickness mm	60
Net weight kg	155
Packing	Pallet + carton
Packaging dimensions (WxDxH) mm	840x910x1835
Packing volume m3	1.4
Gross weight kg	187
Max power consumption KW	2,726
Max absorbed current A	11,84
Power supply V/~/Hz	230/1/50
Electric cable n° x mm²	3X1,5
IP protection	IP 22
Temperature range °C	-36
Refrigeration system	Ventilated
Blast Chiller capacity +65°C ▯ +3°C (kg) kg/ciclo	36
Freezing capacity +65°C ▯ -18°C (kg) kg/ciclo	25
YIELD EN17032 BLAST-CHILLING kg/ciclo	35
YIELD EN17032 SHOCK-FREEZING kg/ciclo	25
Refrigerant gas	R290
Refrigerant gas quantity, water cooling g	150 X 2
Cooling power EN12900 W	897 X 2
Compressor hp	1 (x 2)
Defrosting	Forced ventilation
Climatic class	5
Compressor start type	Diretto
Nr. of condenser fans	1
Condenser fan diameter	350
External temperature °C	40 °C

The company reserves the right to make any necessary changes to improve the product.

PRIMAX

BT-R101 (R290) BlastChiller ShockFreezer

820

1690

150

110   600   110

800

61   620   59

PRIMAX