Transform Data with

Slides CC BY-SA RStudio

Exercise: What do you already know?

- I will use Zoom to split you into groups of two.
- Ask you partner:
  - *What do you already know about dplyr?*
  - *What type of "data transformations" do you normally do?*
- 5 minutes

Notes form & Cheat Sheet

Please take out

babynames

Names of male and female babies born in the US from 1880 to 2015. 1.8M rows.

```
# install.packages("babynames")
library(babynames)
```

babynames

year <dbl>	sex <chr>	name <chr>	n <int>	prop <dbl>
1880	F	Mary	7065	7.238433e-02
1880	F	Anna	2604	2.667923e-02
1880	F	Emma	2003	2.052170e-02
1880	F	Elizabeth	1939	1.986599e-02
1880	F	Minnie	1746	1.788861e-02
1880	F	Margaret	1578	1.616737e-02
1880	F	Ida	1472	1.508135e-02
1880	F	Alice	1414	1.448711e-02
1880	F	Bertha	1320	1.352404e-02
1880	F	Sarah	1288	1.319618e-02

1–10 of 1,858,689 rows Previous 1 2 3 4 5 6 ... 100 Next

Proportion of boys with the name Garrett

How to isolate?

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081
1881	M	William	8524	0.0787
1881	M	James	5442	0.0503
1881	M	Charles	4664	0.0431
1881	M	Garrett	7	0.0001
1881	M	Gideon	7	0.0001

→

year	sex	name	n	prop
1880	M	Garrett	13	0.0001
1881	M	Garrett	7	0.0001
…	…	Garrett	…	…

dplyr

dplyr

A package that transforms data.

dplyr implements a *grammar* for transforming tabular data.

Isolating data

select() - extract **variables (columns)**

filter() - extract **cases (rows)**

arrange() - reorder **cases**

select()

select()

Extract columns by name.

```
select(.data, …)
```

data frame to transform

name(s) of columns to extract
(or a select helper function)

select()

Extract columns by name.

```
select(babynames, name, prop)
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

name	prop
John	0.0815
William	0.0805
James	0.0501
Charles	0.0451
Garrett	0.0001
John	0.081

Your Turn 1

Open up **exercises/02-dplyr-exercises.Rmd**

Alter the code to select just the **n** column:

```
select(babynames, name, prop)
```

```
select(babynames, n)
#       n
#   <int>
# 1  7065
# 2  2604
# 3  2003
# 4  1939
# 5  1746
# …    …
```

```
> name
Error: object 'name' not found
> select(babynames, name)
# A tibble: 1,924,665 x 1
   name
   <chr>
 1 Mary
 2 Anna
 3 Emma
 4 Elizabeth
```

Non Standard Evaluation (NSE)

Using Column Names as Parameters

select() helpers

: - Select range of columns

```
select(storms, storm:pressure)
```

- - Select every column but

```
select(storms, -c(storm, pressure))
```

starts_with() - Select columns that start with…

```
select(storms, starts_with("w"))
```

ends_with() - Select columns that end with…

```
select(storms, ends_with("e"))
```

select() helpers

Extract Variables

Column functions return a set of columns as a new table. Use a variant that ends in _ for non-standard evaluation friendly code.

select(.data, …**)**
Extract columns by name. Also **select_if()**
select(iris, Sepal.Length, Species)

Use these helpers with select(),
e.g. *select(iris, starts_with("Sepal"))*

contains(match**)**
ends_with(match**)**
matches(match**)**
num_range(prefix, range**)**
one_of(…**)**
starts_with(match**)**
:, e.g. mpg:cyl
-, e.g, -Species

Quiz

Which of these is NOT a way to select the **name** and **n** columns together?

```
select(babynames, -c(year, sex, prop))

select(babynames, name:n)

select(babynames, starts_with("n"))

select(babynames, ends_with("n"))
```

Quiz

Which of these is NOT a way to select the **name** and **n** columns together?

```
select(babynames, -c(year, sex, prop))

select(babynames, name:n)

select(babynames, starts_with("n"))

select(babynames, ends_with("n"))
```

filter()

filter()

Extract rows that meet logical criteria.

```
filter(.data, … )
```

data frame to transform

one or more logical tests (filter returns each row for which the test is TRUE)

common syntax

Each function takes a data frame / tibble as its first argument and returns a data frame / tibble.

```
filter(.data, … )
```

dplyr function

data frame to transform

function specific arguments

filter()

Extract rows that meet logical criteria.

```
filter(babynames, name == "Garrett")
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop
1880	M	Garrett	13	0.0001
1881	M	Garrett	7	0.0001
…	…	Garrett	…	…

filter()

Extract rows that meet logical criteria.

```
filter(babynames, name == "Garrett")
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

= sets
(returns nothing)

== tests if equal
(returns TRUE or FALSE)

Logical tests

?Comparison

`x < y`	Less than
`x > y`	Greater than
`x == y`	Equal to
`x <= y`	Less than or equal to
`x >= y`	Greater than or equal to
`x != y`	Not equal to
`x %in% y`	Group membership
`is.na(x)`	Is NA
`!is.na(x)`	Is not NA

Your Turn 2

See if you can use the logical operators to manipulate our code below to show:

- All of the names where **prop** is greater than or equal to 0.08
- All of the children named “Sea”
- All of the names that have a missing value for **n**
  (Hint: this should return an empty data set).

```r
filter(babynames, prop >= 0.08)
#    year   sex    name     n       prop
# 1  1880     M    John  9655 0.08154630
# 2  1880     M William  9531 0.08049899
# 3  1881     M    John  8769 0.08098299
```

```r
filter(babynames, name == "Sea")
#    year   sex  name     n         prop
# 1  1982     F   Sea     5 2.756771e-06
# 2  1985     M   Sea     6 3.119547e-06
# 3  1986     M   Sea     5 2.603512e-06
# 4  1998     F   Sea     5 2.580377e-06
```

```r
filter(babynames, is.na(n))
#  0 rows
```

Two common mistakes

1. Using `=` instead of `==`

```
filter(babynames, name = "Sea")
filter(babynames, name == "Sea")
```

2. Forgetting quotes

```
filter(babynames, name == Sea)
filter(babynames, name == "Sea")
```

filter()

Extract rows that meet *every* logical criteria.

```
filter(babynames, name == "Garrett", year == 1880)
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop
1880	M	Garrett	13	0.0001

Boolean operators

?base::Logic

`a & b`	and
`a | b`	or
`xor(a,b)`	exactly or
`!a`	not
`a %in% c(a, b)`	one of (in)

filter()

Extract rows that meet *every* logical criteria.

```
filter(babynames, name == "Garrett" & year == 1880)
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop
1880	M	Garrett	13	0.0001

Your Turn 3

Use Boolean operators to alter the code below to return only the rows that contain:

- Girls named Sea
- Names that were used by exactly 5 or 6 children in 1880
- Names that are one of Acura, Lexus, or Yugo

```
filter(babynames, name == "Sea" | name == "Anemone")
```

```r
filter(babynames, name == "Sea", sex == "F")
#    year   sex  name      n         prop
# 1  1982     F   Sea      5 2.756771e-06
# 2  1998     F   Sea      5 2.580377e-06
```

```r
filter(babynames, n == 5 | n == 6, year == 1880)
#    year   sex    name      n         prop
# 1  1880     F    Abby      6 6.147289e-05
# 2  1880     F  Aileen      6 6.147289e-05
# …     …     …       …      …            …
```

```r
filter(babynames, name == "Acura" | name =="Lexus" |name =="Yugo"))
#    year   sex  name      n         prop
# 1  1990     F Lexus    36 1.752932e-05
# 2  1990     M Lexus    12 5.579156e-06
# …     …     …     …     …            …
```

Two more common mistakes

3. Collapsing multiple tests into one

```
filter(babynames, 10 < n < 20)
filter(babynames, 10 < n, n < 20)
```

4. Stringing together many tests (when you could use %in%)

```
filter(babynames, n == 5 | n == 6 | n == 7 | n == 8)
filter(babynames, n %in% c(5, 6, 7, 8))
```

```r
filter(babynames, name == "Sea", sex == "F")
#    year   sex  name      n         prop
# 1  1982     F   Sea      5 2.756771e-06
# 2  1998     F   Sea      5 2.580377e-06
```

```r
filter(babynames, n == 5 | n == 6, year == 1880)
#    year   sex    name      n         prop
# 1  1880     F    Abby      6 6.147289e-05
# 2  1880     F  Aileen      6 6.147289e-05
# …     …     …       …      …            …
```

```r
filter(babynames, name %in% c("Acura", "Lexus", "Yugo"))
#    year   sex  name      n         prop
# 1  1990     F Lexus     36 1.752932e-05
# 2  1990     M Lexus     12 5.579156e-06
# …     …     …     …      …            …
```

arrange()

arrange()

Order rows from smallest to largest values.

```
arrange(.data, …)
```

data frame to transform

one or more columns to order by (additional columns will be used as tie breakers)

arrange()

Order rows from smallest to largest values.

```
arrange(babynames, n)
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop
1880	M	Garrett	13	0.0001
1880	M	Charles	5348	0.0451
1880	M	James	5927	0.0501
1881	M	John	8769	0.081
1880	M	William	9532	0.0805
1880	M	John	9655	0.0815

Your Turn 4

Arrange babynames by **n**. Add **prop** as a second (tie breaking) variable to arrange by.

Can you tell what the smallest value of **n** is?

```
arrange(babynames, n, prop)
#    year   sex        name     n         prop
#  1  2007     M       Aaban     5 2.259872e-06
#  2  2007     M      Aareon     5 2.259872e-06
#  3  2007     M       Aaris     5 2.259872e-06
#  4  2007     M         Abd     5 2.259872e-06
#  5  2007     M  Abdulazeez     5 2.259872e-06
#  6  2007     M   Abdulhadi     5 2.259872e-06
#  7  2007     M  Abdulhamid     5 2.259872e-06
#  8  2007     M  Abdulkadir     5 2.259872e-06
#  9  2007     M Abdulraheem     5 2.259872e-06
# 10  2007     M  Abdulrahim     5 2.259872e-06
# ... with 1,858,679 more rows
```

desc()

Changes ordering to largest to smallest.

```
arrange(babynames, desc(n))
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1881	M	John	8769	0.081
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001

Your Turn 5

Use **desc()** to find the names with the highest **prop**.

Then, use **desc()** to find the names with the highest **n**.

```
arrange(babynames, desc(prop))
#     year   sex    name     n       prop
#  1  1880     M    John  9655 0.08154630
#  2  1881     M    John  8769 0.08098299
#  3  1880     M William  9531 0.08049899
#  4  1883     M    John  8894 0.07907324
#  5  1881     M William  8524 0.07872038
#  6  1882     M    John  9557 0.07831617
#  7  1884     M    John  9388 0.07648751
#  8  1882     M William  9298 0.07619375
#  9  1886     M    John  9026 0.07582198
# 10  1885     M    John  8756 0.07551791
# ... with 1,858,679 more rows
```

```
arrange(babynames, desc(n))
#     year   sex    name     n       prop
#  1  1947     F   Linda 99680 0.05483609
#  2  1948     F   Linda 96211 0.05521159
#  3  1947     M   James 94763 0.05102057
#  4  1957     M Michael 92726 0.04238659
#  5  1947     M  Robert 91646 0.04934237
#  6  1949     F   Linda 91010 0.05184281
#  7  1956     M Michael 90623 0.04225479
#  8  1958     M Michael 90517 0.04203881
#  9  1948     M   James 88588 0.04969679
# 10  1954     M Michael 88493 0.04279403
# ... with 1,858,679 more rows
```

%>%

Steps

```
boys_2015 <- filter(babynames, year == 2015, sex == "M")
boys_2015 <- select(boys_2015, name, n)
boys_2015 <- arrange(boys_2015, desc(n))
boys_2015
```

1. Filter babynames to just boys born in 2015
2. Select the *name* and *n* columns from the result
3. Arrange the results so the n column is descending

Steps

```
boys_2015 <- filter(babynames, year == 2015, sex == "M")
boys_2015 <- select(boys_2015, name, n)
boys_2015 <- arrange(boys_2015, desc(n))
boys_2015
```

Steps

```
arrange(select(filter(babynames, year == 2015,
  sex == "M"), name, n), desc(n))
```

The pipe operator %>%

```
babynames          filter(_______, n == 99680)
```

Passes result on left into first argument of function on right.
So, for example, these do the same thing. Try it.

```
filter(babynames, n == 99680)
babynames %>% filter(n == 99680)
```

Pipes

```
babynames
boys_2015 <- filter(babynames, year == 2015, sex == "M")
boys_2015 <- select(boys_2015, name, n)
boys_2015 <- arrange(boys_2015, desc(n))
boys_2015
```

```
babynames %>%
  filter(year == 2015, sex == "M") %>%
  select(name, n) %>%
  arrange(desc(n))
```

```
foo_foo <- little_bunny()
```

```
foo_foo %>%
  hop_through(forest) %>%
  scoop_up(field_mouse) %>%
  bop_on(head)
```

vs.

```
foo_foo2 <- hop_through(foo_foo, forest)
foo_foo3 <- scoop_up(foo_foo2, field_mouse)
bop_on(foo_foo3,  head)
```

Shortcut to type %>%

Cmd + Shift + M (Mac)

Ctrl + Shift + M (Windows)

Your Turn 6

Use **%>%** to write a sequence of functions that:

1. Filter babynames to just the girls that were born in 2015
2. Select the **name** and **n** columns
3. Arrange the results so that the most popular names are near the top.

```r
babynames %>%
  filter(year == 2015, sex == "F") %>%
  select(name, n) %>%
  arrange(desc(n))
#         name     n
#  1      Emma 20355
#  2    Olivia 19553
#  3    Sophia 17327
#  4       Ava 16286
#  5  Isabella 15504
#  6       Mia 14820
#  7   Abigail 12311
#  8     Emily 11727
#  9 Charlotte 11332
# 10    Harper 10241
# ... with 18,983 more rows
```

Exam

1. Trim babynames to just the rows that contain your **name** and your **sex**
2. Trim the result to just the columns that will appear in your graph (not strictly necessary, but useful practice)
3. Plot the results as a line graph with **year** on the x axis and **prop** on the y axis

```
babynames %>%
  filter(name == "Ari", sex == "M") %>%
  select(year, prop) %>%
  ggplot() +
  geom_line(mapping = aes(year, prop))
```

Adding a Title

- Google *"How to add a title in ggplot2"*

```
p + ggitle("Popularity of ...")
```

Removing Scientific Notation

- Google *"ggplot2 remove scientific notation from y axis"*

```
library(scales)

p +
scale_y_continuous(labels=comma)
```

The "Google -> Stack Overflow" Loop

"ggplot2 remove scientific notation from y axis"

What are the most popular names?

Deriving information

summarise() - summarise **variables**

group_by() - group **cases**

mutate() - create new **variables**

summarise()

summarise()

Compute table of summaries.

```
babynames %>% summarise(total = sum(n), max = max(n))
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

total	max
348120517	99686

Summary functions

Take a vector as input.

Return a single value as output.

Summary Functions

to use with summarise()

summarise() applies summary functions to columns to create a new table. Summary functions take vectors as input and return single values as output.

Counts

dplyr::**n()** - number of values/rows
dplyr::**n_distinct()** - # of uniques
sum(!is.na()) - # of non-NA's

Location

mean() - mean, also **mean(is.na())**
median() - median

Logicals

mean() - Proportion of TRUE's
sum() - # of TRUE's

Position/Order

dplyr::**first()** - first value
dplyr::**last()** - last value
dplyr::**nth()** - value in nth location of location of vector

Rank

quantile() - nth quantile
min() - minimum value
max() - maximum value

Spread

IQR() - Inter-Quartile Range
mad() - mean absolute deviation
sd() - standard deviation
var() - variance

Your Turn 7

Use summarise() to compute three statistics *about the data*:

1. The first (minimum) year in the dataset
2. The last (maximum) year in the dataset
3. The total number of children represented in the data

```
babynames %>%
  summarise(first = min(year),
            last = max(year),
            total = sum(n))
#   first  last     total
# 1  1880  2015 340851912
```

Your Turn 8

Extract the rows where **name == "Khaleesi"**. Then use summarise() and a summary function to find:

1. The total number of children named Khaleesi
2. The first **year** Khaleesi appeared in the data

```
babynames %>%
  filter(name == "Khaleesi") %>%
  summarise(total = sum(n), first = min(year))
#   total first
# 1  1127  2011
```

n()

The number of rows in a dataset/group

```
babynames %>% summarise(n = n())
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

n
1924665

n_distinct()

The number of distinct values in a variable

```
babynames %>% summarise(n = n(), nname = n_distinct(name))
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

n	nname
1924665	97310

Grouping cases

group_by()

Groups cases by common values of one or more columns.

```
babynames %>%
  group_by(sex)
```

```
Source: local data frame [1,825,433 x 5]
Groups: sex [2]

     year    sex       name      n        prop
    <dbl> <chr>      <chr> <int>       <dbl>
1   1880      F       Mary  7065 0.07238359
```

group_by()

Groups cases by common values.

```
babynames %>%
  group_by(sex) %>%
  summarise(total = sum(n))
```

sex	total
F	167070477
M	170064949

Transform Data Notebook

02-Transform-Data.Rmd

Preview Insert Run

```
---
title: "Transform Data"
output: html_notebook
---

```{r setup}
library(tidyverse)
library(babynames)

# Toy datasets to use

pollution <- tribble(
       ~city,    ~size, ~
  "New York", "large",
  "New York", "small",
    "London", "large",
    "London", "small",
   "Beijing", "large",
   "Beijing", "small",
)

band <- tribble(
    ~name,      ~band,
  "Mick",   "Stones",
  "John",  "Beatles",
  "Paul",  "Beatles"
)

instrument <- tribble(
     ~name,    ~plays,
   "John", "guitar",
   "Paul",    "bass",
  "Keith", "guitar"
)
```

Your Turn 1
```

34:2 Chunk 1: setup R Markdown

```
pollution <- tribble(
       ~city,    ~size, ~amount,
  "New York", "large",      23,
  "New York", "small",      14,
    "London", "large",      22,
    "London", "small",      16,
   "Beijing", "large",      121,
   "Beijing", "small",      56
)
```

Toy data sets to practice with

```r
pollution <- tribble(
       ~city,    ~size, ~amount,
  "New York", "large",      23,
  "New York", "small",      14,
    "London", "large",      22,
    "London", "small",      16,
   "Beijing", "large",      121,
   "Beijing", "small",      56
)
```

pollution

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

mean	sum	n
42	252	6

```
pollution %>%
 summarise(mean = mean(amount), sum = sum(amount), n = n())
```

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

mean	sum	n
18.5	37	2
19.0	38	2
88.5	177	2

group_by() + summarise()

group_by()

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

city	mean	sum	n
New York	18.5	37	2
London	19.0	38	2
Beijing	88.5	177	2

```
pollution %>%
  group_by(city) %>%
  summarise(mean = mean(amount), sum = sum(amount), n = n())
```

group_by()

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

city	particle size	amount ($\mu g/m^3$)
New York	large	23
New York	small	14
London	large	22
London	small	16
Beijing	large	121
Beijing	small	56

city	particle size	mean	sum	n
New York	large	23	23	1
New York	small	14	14	1
London	large	22	22	1
London	small	16	16	1
Beijing	large	121	121	1
Beijing	small	56	56	1

```
pollution %>%
  group_by(city, size) %>%
  summarise(mean = mean(amount), sum = sum(amount), n = n())
```

Your Turn 9

Use **group_by()**, **summarise()**, and **arrange()** to display the ten most popular names. Compute popularity as the total number of children of a single gender given a name.

```r
babynames %>%
  group_by(name, sex) %>%
  summarise(total = sum(n)) %>%
  arrange(desc(total))
#       name   sex   total
#  1   James     M 5120990
#  2    John     M 5095674
#  3  Robert     M 4803068
#  4 Michael     M 4323928
#  5    Mary     F 4118058
#  6 William     M 4071645
#  7   David     M 3589754
#  8  Joseph     M 2581785
#  9 Richard     M 2558165
# 10 Charles     M 2371621
# ... with 105,376 more rows
```

5000000
4000000
3000000
2000000
1000000
0
total
James
John
Robert
Michael
Mary
William
David
Joseph
Richard
Charles
name
sex
F
M

```
babynames %>%
  group_by(name, sex) %>%
  summarise(total = sum(n)) %>%
  arrange(desc(total)) %>%
  ungroup() %>%
  slice(1:10) %>%
  ggplot() +
    geom_col(mapping = aes(x = fct_reorder(name,
      desc(total)), y = total, fill = sex)) +
    theme_bw() +
    scale_fill_brewer() +
    labs(x = "name")
```

Your Turn 10

Use grouping to calculate **number of children born each year**.

Plot the results as a line graph.

05:00

```
library(scales)

babynames %>%
    group_by(year) %>%
    summarise(n_children = sum(n)) %>%
    ggplot() +
        geom_line(mapping = aes(x = year, y = n_children)) +
        scale_y_continuous(label=comma) +
        ggtitle("Number of Children Born Each Year")
```

Number of Children Born Each Year
4,000,000
3,000,000
2,000,000
1,000,000
0
n_children
1880
1920
1960
2000
year

Custom Scale Labels

- Google *"ggplot2 change axis labels"*

```
p +
  labs(x = "Year", y = "Number of Children")
```

ungroup()

Removes grouping criteria from a data frame.

```
babynames %>%
  group_by(name, sex) %>%
  summarise(total = sum(n)) %>%
  arrange(desc(total))
#       name   sex   total
#  1   James     M 5120990
#  2    John     M 5095674
#  3  Robert     M 4803068
#  4 Michael     M 4323928
#  5    Mary     F 4118058
```

ungroup()

Removes grouping criteria from a data frame.

```
babynames %>%
  group_by(name, sex) %>%
  ungroup() %>%
  summarise(total = sum(n)) %>%
  arrange(desc(total))
#       total
# 1 340851912
```

mutate()

mutate()

Create new columns.

```
babynames %>%
  mutate(percent = round(prop*100, 2))
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop	percent
1880	M	John	9655	0.0815	8.15
1880	M	William	9532	0.0805	8.05
1880	M	James	5927	0.0501	5.01
1880	M	Charles	5348	0.0451	4.51
1880	M	Garrett	13	0.0001	0.01
1881	M	John	8769	0.081	8.1

mutate()

Create new columns.

```
babynames %>%
  mutate(percent = round(prop*100, 2), nper = round(percent))
```

babynames

year	sex	name	n	prop
1880	M	John	9655	0.0815
1880	M	William	9532	0.0805
1880	M	James	5927	0.0501
1880	M	Charles	5348	0.0451
1880	M	Garrett	13	0.0001
1881	M	John	8769	0.081

→

year	sex	name	n	prop	percent	nper
1880	M	John	9655	0.0815	8.15	8
1880	M	William	9532	0.0805	8.05	8
1880	M	James	5927	0.0501	5.01	5
1880	M	Charles	5348	0.0451	4.51	5
1880	M	Garrett	13	0.0001	0.01	0
1881	M	John	8769	0.081	8.1	8

Vectorized functions

Take a vector as input.

Return a vector of the same length as output.

Vectorized Functions

to use with mutate()

mutate() and **transmute()** apply vectorized functions to columns to create new columns. Vectorized functions take vectors as input and return vectors of the same length as output.

Offsets

dplyr::**lag()** - Offset elements by 1

dplyr::**lead()** - Offset elements by -1

Cumulative Aggregates

dplyr::**cumall()** - Cumulative all()

dplyr::**cumany()** - Cumulative any()

cummax() - Cumulative max()

dplyr::**cummean()** - Cumulative mean()

cummin() - Cumulative min()

cumprod() - Cumulative prod()

cumsum() - Cumulative sum()

Rankings

dplyr::**cume_dist()** - Proportion of all values <=

dplyr::**dense_rank()** - rank with ties = min, no gaps

dplyr::**min_rank()** - rank with ties = min

dplyr::**ntile()** - bins into n bins

dplyr::**percent_rank()** - min_rank scaled to [0,1]

dplyr::**row_number()** - rank with ties = "first"

Math

+, - , *, ?, ^, %/%, %% - arithmetic ops

log(), log2(), log10() - logs

<, <=, >, >=, !=, == - logical comparisons

Misc

dplyr::**between()** - x > right & x < left

dplyr::**case_when()** - multi-case if_else()

dplyr::**coalesce()** - first non-NA values by element across a set of vectors

if_else() - element-wise if() + else()

dplyr::**na_if()** - replace specific values with NA

pmax() - element-wise max()

pmin() - element-wise min()

dplyr::**recode()** - Vectorized switch()

dplyr::**recode_factor()** - Vectorized switch() for factors

dplyr

Your Turn 11

Dataframe **weights** lists the name and weight (in pounds) of professional martial artists. Add a column **kgs** that lists their weight to kilograms.

Hint: multiply the **lbs** column by .45 to get the number of kilograms

```
> weights
# A tibble: 5 x 2
  name      lbs
  <chr>   <dbl>
1 Stipe     255
2 Jan       205
```

03:00

```r
weights %>%
  mutate(kgs = lbs *.45)
```

```
> weights %>%
+     mutate(kgs = lbs *.45)
# A tibble: 5 x 3
  name     lbs   kgs
  <chr>  <dbl> <dbl>
1 Stipe    255 115.
2 Jan      205  92.2
3 Israel   185  83.2
4 Karamu   170  76.5
5 Khabib   150  67.5
```

Recap: Single table verbs

Extract variables / columns with **select()**

Extract cases / rows with **filter()**

Arrange rows, with **arrange()**.

Make tables of summaries with **summarise()**.

Make new variables, with **mutate()**.

Joining Datasets

nycflights13

Data about every flight that departed La Guardia, JFK, or Newark airports in 2013

```
# install.packages("nycflights13")
library(nycflights13)
```

modelr	Modelling Functions that Work with the Pipe	0.1.8	
munsell	Utilities for Using Munsell Colours	0.5.0	
nlme	Linear and Nonlinear Mixed Effects Models	3.1-150	
nnet	Feed-Forward Neural Networks and Multinomial Log-Linear Models	7.3-14	
numDeriv	Accurate Numerical Derivatives	2016.8-1.1	
nycflights13	Flights that Departed NYC in 2013	1.0.1	
openssl	Toolkit for Encryption, Signatures and Certificates Based on OpenSSL	1.4.3	
packrat	A Dependency Management System for Projects and their R Package Dependencies	0.5.0	
parallel	Support for Parallel computation in R	4.0.3	

Documentation for package 'nycflights13' version 1.0.1

- DESCRIPTION file.

Help Pages

airlines	Airline names.
airports	Airport metadata
flights	Flights data
planes	Plane metadata.
weather	Hourly weather data

Package Description

5 tables

Flights

```
View(flights)
```

year	month	day	dep_time	sched_dep_time	dep_delay	arr_time	sched_arr_time	arr_delay	carrier	flight	tailnum	origin	dest	air_time	distance	hour	minute	time_hour
2013	1	1	517	515	2	830	819	11	UA	1545	N14228	EWR	IAH	227	1400	5	15	2013-01-01 05:00:00
2013	1	1	533	529	4	850	830	20	UA	1714	N24211	LGA	IAH	227	1416	5	29	2013-01-01 05:00:00
2013	1	1	542	540	2	923	850	33	AA	1141	N619AA	JFK	MIA	160	1089	5	40	2013-01-01 05:00:00
2013	1	1	544	545	-1	1004	1022	-18	B6	725	N804JB	JFK	BQN	183	1576	5	45	2013-01-01 05:00:00
2013	1	1	554	600	-6	812	837	-25	DL	461	N668DN	LGA	ATL	116	762	6	0	2013-01-01 06:00:00
2013	1	1	554	558	-4	740	728	12	UA	1696	N39463	EWR	ORD	150	719	5	58	2013-01-01 05:00:00
2013	1	1	555	600	-5	913	854	19	B6	507	N516JB	EWR	FLL	158	1065	6	0	2013-01-01 06:00:00
2013	1	1	557	600	-3	709	723	-14	EV	5708	N829AS	LGA	IAD	53	229	6	0	2013-01-01 06:00:00
2013	1	1	557	600	-3	838	846	-8	B6	79	N593JB	JFK	MCO	140	944	6	0	2013-01-01 06:00:00
2013	1	1	558	600	-2	753	745	8	AA	301	N3ALAA	LGA	ORD	138	733	6	0	2013-01-01 06:00:00
2013	1	1	558	600	-2	849	851	-2	B6	49	N793JB	JFK	PBI	149	1028	6	0	2013-01-01 06:00:00
2013	1	1	558	600	-2	853	856	-3	B6	71	N657JB	JFK	TPA	158	1005	6	0	2013-01-01 06:00:00
2013	1	1	558	600	-2	924	917	7	UA	194	N29129	JFK	LAX	345	2475	6	0	2013-01-01 06:00:00
2013	1	1	558	600	-2	923	937	-14	UA	1124	N53441	EWR	SFO	361	2565	6	0	2013-01-01 06:00:00
2013	1	1	559	600	-1	941	910	31	AA	707	N3DUAA	LGA	DFW	257	1389	6	0	2013-01-01 06:00:00
2013	1	1	559	559	0	702	706	-4	B6	1806	N708JB	JFK	BOS	44	187	5	59	2013-01-01 05:00:00
2013	1	1	559	600	-1	854	902	-8	UA	1187	N76515	EWR	LAS	337	2227	6	0	2013-01-01 06:00:00
2013	1	1	600	600	0	851	858	-7	B6	371	N595JB	LGA	FLL	152	1076	6	0	2013-01-01 06:00:00

Details

⚠ The class of service you searched may not be available on one or more flights

BNA - ORD
Flight 1 of 2

ORD - YVR
Flight 2 of 2

Nashville, TN to Chicago, IL

Thursday, July 26, 2018

4:10 PM → 6:03 PM

AA 3246 ▪ CR7-Canadair RJ 700

Operated by SkyWest Airlines As American Eagle

Travel info

Travel time: **1h 53m**
Connection time: **2h 33m**

Performanc

On time: **52**
Late: **43%**

Main Cabin

Meals: Beverage service
Booking code: V
Class: Economy

Business

Meals: Beverage service
Booking code: I
Class: First

* This is based on information from the month of May 2018

** The on-time arrival percentage for the selected flight is based on arrival within 14 minutes after

Performance*

On time: **52%****

Late: **43%**

** The on-time arrival percentage for the selected flight is based on arrival within 14 minutes after the scheduled arrival as reported monthly to the U.S. Department of Transportation.

Carriers (airlines)

```
View(airlines)
```

	carrier	name
1	9E	Endeavor Air Inc.
2	AA	American Airlines Inc.
3	AS	Alaska Airlines Inc.
4	B6	JetBlue Airways

nycflights13

nycflights13

What airline had the longest delays?

Types of joins

common syntax

Each join function returns a data frame / tibble.

```
left_join(x, y, by = NULL, … )
```

join function

data frames to join

names of columns to join on

Toy data

```r
band <- tribble(
   ~name,      ~band,
  "Mick",   "Stones",
  "John",  "Beatles",
  "Paul",  "Beatles"
)
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

```r
instrument <- tribble(
    ~name,    ~plays,
   "John",  "guitar",
   "Paul",    "bass",
  "Keith",  "guitar"
)
```

instrument

name	plays
John	guitar
Paul	bass
Keith	guitar

Toy data

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

instrument

name	plays
John	guitar
Paul	bass
Keith	guitar

inner

```
band %>% inner_join(instrument, by = "name")
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

+

instrument

name	plays
John	guitar
Paul	bass
Keith	guitar

=

name	band	plays
John	Beatles	guitar
Paul	Beatles	bass

left

```
band %>% left_join(instrument, by = "name")
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

+

instrument

name	plays
John	guitar
Paul	bass
Keith	guitar

=

name	band	plays
Mick	Stones	<NA>
John	Beatles	guitar
Paul	Beatles	bass

right

```
band %>% right_join(instrument, by = "name")
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

+

instrument

name	plays
John	guitar
Paul	bass
Keith	guitar

=

name	band	plays
John	Beatles	guitar
Paul	Beatles	bass
Keith	<NA>	guitar

full

```
band %>% full_join(instrument, by = "name")
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

+

instrument

name	plays
John	guitar
Paul	bass
Keith	guitar

=

name	band	plays
Mick	Stones	<NA>
John	Beatles	guitar
Paul	Beatles	bass
Keith	<NA>	guitar

Your Turn 12

Which airline had the most flights?

```
flights %>%
    group_by(__________) %>%
    summarize(_____) %>%
    arrange(_______) %>%
    left_join(_____)
```

1. Start with a normal "group by / summarize / arrange"

2. Then do a "left_join" to get the carrier"

```
flights %>%
   group_by(carrier) %>%
   summarize(n=n()) %>%
   arrange(desc(n)) %>%
   left_join(airlines)
```

```
  carrier     n name
  <chr>   <int> <chr>
1 UA      58665 United Air Lines Inc.
2 B6      54635 JetBlue Airways
3 EV      54173 ExpressJet Airlines Inc.
4 DL      48110 Delta Air Lines Inc.
5 AA      32729 American Airlines Inc.
```

Your Turn 13

Which airlines had the largest arrival delays?

```
flights %>%
  drop_na(arr_delay) %>%
  ...
```

1. Drop rows with NA delays

2. Calculate average delay with group_by / summarize / arrange

3. Use left_join to get airline name

```
flights %>%
  drop_na(arr_delay) %>%
  group_by(carrier) %>%
  summarize(avg_arr_delay = mean(arr_delay)) %>%
  arrange(desc(avg_arr_delay)) %>%
  left_join(airlines)
```

```
  carrier avg_arr_delay name
  <chr>           <dbl> <chr>
1 F9             21.9   Frontier Airlines Inc.
2 FL             20.1   AirTran Airways Corporation
3 EV             15.8   ExpressJet Airlines Inc.
4 YV             15.6   Mesa Airlines Inc.
5 OO             11.9   SkyWest Airlines Inc.
```

Toy data

```r
band <- tribble(
   ~name,      ~band,
  "Mick",   "Stones",
  "John",  "Beatles",
  "Paul",  "Beatles"
)
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

```r
instrument2 <- tribble(
    ~artist,    ~plays,
   "John",  "guitar",
   "Paul",    "bass",
  "Keith",  "guitar"
)
```

instrument2

artist	plays
John	guitar
Paul	bass
Keith	guitar

What if the names do not match?

Use a named vector to match on variables with different names.

```
band %>% left_join(instrument2, by = c("name" = "artist"))
```

A named vector

The name of the element = the column name in the first data set

The value of the element = the column name in the second data set

common syntax - matching names

```
band %>% left_join(instrument2, by = c("name" = "artist"))
```

band

name	band
Mick	Stones
John	Beatles
Paul	Beatles

+

instrument2

artist	plays
John	guitar
Paul	bass
Keith	guitar

=

name	band	plays
Mick	Stones	<NA>
John	Beatles	guitar
Paul	Beatles	bass

Airport names

```
View(flights["dest"])
```

	dest
1	IAH
2	IAH
3	MIA
4	BQN
5	ATL
6	ORD

```
View(airports)
```

faa	name
04G	Lansdowne Airport
06A	Moton Field Municipal Airport
06C	Schaumburg Regional
06N	Randall Airport
09J	Jekyll Island Airport
0A9	Elizabethton Municipal Airport

common syntax - matching names

```
airports %>% left_join(flights, by = c("faa" = "dest"))
```

faa <chr>	name <chr>
04G	Lansdowne Airport
06A	Moton Field Municipal Airport
06C	Schaumburg Regional
06N	Randall Airport
09J	Jekyll Island Airport
0A9	Elizabethton Municipal Airport
0G6	Williams County Airport
0G7	Finger Lakes Regional Airport

dest <chr>	air_time <dbl>
IAH	227
IAH	227
MIA	160
BQN	183
ATL	116
ORD	150
FLL	158
IAD	53

Recap: Two table verbs

left_join() retains all cases in **left** data set

right_join() retains all cases in **right** data set

full_join() retains all cases in **either** data set

inner_join() retains only cases in **both** data sets

Two table verbs

Combine Tables

Combine Variables

x

A	B	C
a	t	1
b	u	2
c	v	3

+

y

A	B	D
a	t	3
b	u	2
d	w	1

=

Use **bind_cols()** to paste tables beside each other as they are.

A	B	C	A	B	D
a	t	1	a	t	3
b	u	2	b	u	2
c	v	3	d	w	1

bind_cols(…)
Returns tables placed side by side as a single table.
BE SURE THAT ROWS ALIGN.

Use a "**Mutating Join**" to join one table to columns from another, matching values with the rows that they correspond to. Each join retains a different combination of values from the tables.

A	B	C	D
a	t	1	3
b	u	2	2
c	v	3	NA

left_join(x, y, by = NULL, copy=FALSE, suffix=c(".x",".y"),…)
Join matching values from y to x.

A	B	C	D
a	t	1	3
b	u	2	2
d	w	NA	1

right_join(x, y, by = NULL, copy = FALSE, suffix=c(".x",".y"),…)
Join matching values from x to y.

A	B	C	D
a	t	1	3
b	u	2	2

inner_join(x, y, by = NULL, copy = FALSE, suffix=c(".x",".y"),…)
Join data. Retain only rows with matches.

A	B	C	D
a	t	1	3
b	u	2	2
c	v	3	NA
d	w	NA	1

full_join(x, y, by = NULL, copy=FALSE, suffix=c(".x",".y"),…)
Join data. Retain all values, all rows.

A	B.x	C	B.y	D
a	t	1	t	3
b	u	2	u	2
c	v	3	NA	NA

Use **by = c("col1", "col2")** to specify the column(s) to match on.
left_join(x, y, by = "A")

A.x	B.x	C	A.y	B.y
a	t	1	d	w
b	u	2	b	u
c	v	3	a	t

Use a named vector, **by = c("col1" = "col2")**, to match on columns with different names in each data set.
left_join(x, y, by = c("C" = "D"))

A1	B1	C	A2	B2
a	t	1	d	w
b	u	2	b	u
c	v	3	a	t

Use **suffix** to specify suffix to give to duplicate column names.
left_join(x, y, by = c("C" = "D"), suffix = c("1", "2"))

Combine Cases

A	B	C
a	t	1
b	u	2
c	v	3

x

+

A	B	C
c	v	3
d	w	4

z

Use **bind_rows()** to paste tables below each other as they are.

DF	A	B	C
x	a	t	1
x	b	u	2
x	c	v	3
z	c	v	3
z	d	w	4

bind_rows(…, .id = NULL)
Returns tables one on top of the other as a single table. Set .id to a column name to add a column of the original table names (as pictured)

A	B	C
c	v	3

intersect(x, y, …)
Rows that appear in both x and z.

A	B	C
a	t	1
b	u	2

setdiff(x, y, …)
Rows that appear in both x but not z.

A	B	C
a	t	1
b	u	2
c	v	3
d	w	4

union(x, y, …)
Rows that appear in x or z. (Duplicates removed). **union_all()** retains duplicates.

Use **setequal()** to test whether two data sets contain the exact same rows (in any order).

Extract Rows

x

A	B	C
a	t	1
b	u	2
c	v	3

+

y

A	B	C
a	t	3
b	u	2
d	w	1

=

Use a "**Filtering Join**" to filter one table against the rows of another.

A	B	C
a	t	1
b	u	2

semi_join(x, y, by = NULL, …)
Return rows of x that have a match in y.
USEFUL TO SEE WHAT WILL BE JOINED.

A	B	C
c	v	3

anti_join(x, y, by = NULL, …)
Return rows of x that do not have a match in y. USEFUL TO SEE WHAT WILL NOT BE JOINED.

Tidy tools

Vignettes and other documentation

Vignettes from package 'tidyverse'

tidyverse::manifesto	The tidy tools manifesto
tidyverse::paper	Welcome to the tidyverse

There are four basic principles to a tidy API:

1. Reuse existing data structures.
2. Compose simple functions with the pipe.
3. Embrace functional programming.
4. Design for humans.

The Tidy Tools Manifesto

Really

Designed for Humans:

Functions do one thing, and they do it well

filter() - extract **cases**
arrange() - reorder **cases**
group_by() - group **cases**
select() - extract **variables**
mutate() - create new **variables**
summarise() - summarise **variables** / create **cases**

Compose simple functions with the pipe

```
babynames          mutate(______, percent = prop * 100)
```

Each dplyr function takes a data frame as its first argument and returns a data frame. As a result, you can directly pipe the output of one function into the next.

Closing Exercise

- Fill out the "Summary" section
- Fill out the "How I can apply to to my work"
- Share with your neighbor!

Any Questions?