		FABRICATION MATERIALS				N													流水	號:20	9
	PT NO	COMPONENT DESCRIPTION	N.S. ITEM CO	DDE	QTY	N													7712.5	3,70 0	
完	1	PIPE PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	1 S1P1/P-	1"-40S	0.4M																
	2	FITTINGS TEE 3000# SW A182-F304 ASME B16.11	1 x 1 S1P1/TS	S-1"	1										2	5					
後	3	FLANGES FLANGE SW 150# RF A182-F304 SCH40S BORE	1 S1P1/FF	RSW-1"	3		le					-166			1	1"x1"NS EL.+9248	\I	<5>1 (23)	3 127 24	_104	
請		ASME B16.5 ERECTION MATERIALS				CONT. OI	N()=		<u><6>1</u>	======	>		=====		=====			=======================================			
速	PT NO	COMPONENT DESCRIPTION	N.S. ITEM CO	DDE	QTY	3										15	16	22 F3 G6 B7		25)	
歸	<u>NO</u>	FITTINGS	(INS)																	45°	
還	4	NIPPLE (L=100MM) TOE(NPT) A312-TP304 SMLS SCH80S ASME B36.19M		P-1"X100LXTOE	1														/ _		
	5	CAP 3000# SCRD (FNPT) A182-F304 ASME B16.11	1 S1P1/C	Г-1"	1												311	1	1	3 G6 B7	
	6	GASKETS GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	1 S1P1/G	R-1"	4					377		_					3.			"-4144 EM W 45 N	
		BOLTS													/	26—	: II		VENT		
	7	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD	1/2 S1P1/B3	S4-1/2"X65L	16								H	/ /		-	· !Iı				
		HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2 VALVES / IN-LINE ITEMS											\ Ĭ				44×11 1"NS				
	8	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	1 S1P1/V	\-1"-4144	2												#				
	NO <4> <6>	LENGTH (INS) NO 100 1 <5>	LENGTH (INS) 100 1											8 S1P1	DF 1/VA-1"-4		EL	.+9117 <u>G6 B7</u>			
																	Г				П
																	L	OR CO	NSIRU	CHON	
																		JUL	L. 04, 20	25	
																		管線編號			
						1 55 4 = 15	/1\ ± /*/	(公 日)	145 Ba You	N =		T 165-455				₩ ₩	* 4-2-		08-4"-S1P		
					1	① 管件序號 & 須設計會驗	管線	編號 [1] 管理	名	稱 :				配合現場焊接—————————————————————————————————	-	_	学 蒸汽追蹤管 	Gobine '	鴻勝化學科技 E-shine Advanc	ed Chemicals Li	td.
	\triangle					操作壓力: 6.1		操作溫度: 12		泉等級:	S1P1	製圖		2025.04.2	- = -				台工程股· -TAI ENGINE	份有限公	司
		2025 07 02			店沒□	設計壓力: 9.7	,	会計温度: 65		图(冷)等級: 白ᄴ等级:	; C40	設計		2025.04.2	1			-	-TAI ENGINE 管線]		_
	Â	2025.07.03 FOR CONSTRUCTION 2025.04.21 FOR APPROVAL		陳至鉉 陳至鉉	陳逢明 陳逢明	試驗基準: Air 管路塗裝:	10	.67 KG/CM ² G X 6(管 材 塗	U // 訊是	自縱等級:_ 妾基準:		審 核 認 可	1	2025.04.2	— TOD —			上 一 一 一 一 一 一 一 一 一 一 一 一 一 一 一 一 一 一 一			$\binom{2}{3}$
	序次	日 期 修 改	 說 明	修 改	認可	日 近 空 衣。 焊道。 塗装・	—————————————————————————————————————	管材塗 供鋼及不銹,鋼保溫(冷),不銹鋼	NIDE	<u> </u>	10 %	(依據圖號	1		' 	<u> </u> :			<u>اعظظ</u> 1-15308-S1P1-		
	1.4 "	12 27		1 " "	1 30 1	至权	1=	一 小奶剛	וטוון	_ ₁ш⋈Ж •	. , 0							1 - 4.0.			