		FABRICATION MATERIALS				N		35
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY	<i>N</i>		
	1	TEE BW A403-WP304 SMLS SCH40S ASME B16.9	2 x 2	S1P1/TB-2"	2		S8 / C-501	
	2	FLANGES  FLANGE WN 150# RF A182-F304 SCH40S BORE ASME B16.5	2	S1P1/FRWN-2"	6			
後 請		ERECTION MATERIALS						
	PT NO	COMPONENT DESCRIPTION  GASKETS	N.S. (INS)	ITEM CODE	QTY		3	
	3	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	2	S1P1/GR-2"	4		F2 C-501 1 128 2"x2"NS	
還	4	BOLTS  STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	5/8	S1P1/BS4-5/8"X85L	16		E 80018 N 50970 EL.+2309	
	5	VALVES / IN-LINE ITEMS  BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	2	S1P1/VA-2"-4144-E	2	CON V-605		
		(VOC<100 vppm)  INSTRUMENTS				E 803 N 506 EL.+2	00 55 LT G3 B4 F2 178	
	6 7	LEVEL TRANSMITTER 150# RF LT 60502 LEVEL GAUGE 150# RF LG 60502 SUPPORTS	2 2		1 1		E 80018	
	8	FLANGE GROUNDING CONDUCTOR (C-501)	2	MISC/C-501	4		EL.+1287 S8 C-501 178 N 51253 EL.+1287	
							2"x2"NS	
							S1P1/VA-2"-4144-E	
							G3 B4 2"NS 60502	
							5 S1P1/VA-2"-4144-E F2 G3 B4	
							C-501 CONN. TO V-605/N46B	
☆ 會 簽							E 80300 N 50655 EL.+1350	
分配 △	<u>,                                    </u>						FOR CONSTRUCTION	N
							JUL. 04, 2025	
							管線編號	
							TRIM-V605-N46AB-2"-S1P1-C60	
						① 管件序號 <1>直管編號 [1] 管段編號 & 須設計會驗管線	T	
						操作壓力: 0.05 KG/CM <sup>2</sup> G 操作溫度: -16~38 °(	管線等級: S1P1 製 圖 <b>陳怡如</b> 2025.04.21 <sub>會</sub>	 公司
	$\bigwedge$					設計壓力: 0.14 KG <sub>CM<sup>2</sup></sub> G 設計溫度: -26~80 °C	保溫(冷)等級: C60	LTD.
		2025.07.03 FOR CONSTRUCTION		黄炳富	陳逢明	試驗基準: Air 0.18 KC/M² G X 60 万 管路塗裝: 管路塗裝: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	熱追縱等級:     審核     陳安誠     2025.04.21     簽     編尾一期       「焊接基準:     認可     陳逢明     2025.04.21     金     世級工程	$-\left(\begin{array}{c}1\\1\end{array}\right)$
	序次	2025.04.21   FOR APPROVAL	說 明	<b>黃炳富</b> 修 改	<b>陳逢明</b> 認 可	管路塗装:		
	1,1,4		u/i 4/7	III LX		塗装'	NDE 抽驗: 10 %   依據圖號: C2418-4-509   圖號:   檔號: TRIM-V605-N46AB-S1P1- 1	