PIPE 1 PIPE A3 B36.19M FITTINGS 2 90 ELBC FLANGES ASME B ERECT PT COMPO NO FITTINGS 4 NIPPLE SCH80S 5 CAP 300 GASKETS 6 GASKETS 7 STUD B HEAVY VALVES 8 BALL 15 PORT F (FOR VA	PIPE A312-TP316L SMLS SCH40S PE ASME B36.19M ITTINGS 90 ELBOW 3000# SW A182-F316L ASME B16.11 LANGES FLANGE SW 150# RF A182-F316L SCH40S BORE ASME B16.5 ERECTION MATERIALS COMPONENT DESCRIPTION ITTINGS NIPPLE (L=100MM) TOE(NPT) A312-TP316L SML SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16 GASKETS GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 'ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM—60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	(INS)	1PL/P-1"-40S 1PL/ES-1"X90 1PL/FRSW-1" TEM CODE 1PL/NIP-1"X100LXTOE 1PL/GT-1" 1PL/GR-1"-ZW#7500 1PL/BS6-1/2"X65L	QTY 0.2M 1 3 QTY 1 1 1 1	CONN. TO STR-21201A./D E 80665 N 72010 EL.+532	流水號:1047
1 PIPE A3 B36.19M FITTINGS 2 90 ELBC FLANGES 3 FLANGE ASME B PT COMPO NO FITTINGS 4 NIPPLE SCH80S 5 CAP 300 GASKETS 6 GASKET 7 STUD B HEAVY VALVES 8 BALL 15 PORT F (FOR V) CUT P PIECE CUT NO LENGTI <1>100	PIPE A312-TP316L SMLS SCH40S PE ASME B36.19M ITTINGS 90 ELBOW 3000# SW A182-F316L ASME B16.11 LANGES FLANGE SW 150# RF A182-F316L SCH40S BORE ASME B16.5 ERECTION MATERIALS COMPONENT DESCRIPTION ITTINGS NIPPLE (L=100MM) TOE(NPT) A312-TP316L SML SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16 GASKETS GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 'ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM—60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	6.11 1 S1 BORE 1 S1 N.S. (INS) SMLS 1 S1 EB16.11 1 S1 FE 1 S1 EAD 1/2 S1 JLL 1 S1	1PL/ES-1"X90 1PL/FRSW-1" TEM CODE 1PL/NIP-1"X100LXTOE 1PL/CT-1" 1PL/GR-1"-ZW#7500 1PL/BS6-1/2"X65L	1 3 QTY 1 1 3	STR-21201A./D E 80665 N 72010 EL.+532	
2 90 ELBC FLANGES FLANGES 3 FLANGE ASME B PT COMPO NO FITTINGS 4 NIPPLE SCHBOS 5 CAP 300 GASKETS 6 GASKET 7 STUD B HEAVY VALVES 8 BALL 15 PORT F (FOR V) CUT P PIECE CUT NO LENGTI <1>> 100	90 ELBOW 3000# SW A182-F316L ASME B16.11 LANGES FLANGE SW 150# RF A182-F316L SCH40S BORE ASME B16.5 ERECTION MATERIALS COMPONENT DESCRIPTION ITTINGS NIPPLE (L=100MM) TOE(NPT) A312-TP316L SML SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16 GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 'ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	N.S. (INS) SMLS 1 S1 EB16.11 1 S1 FE 1 S1 EAD 1/2 S1 JLL 1 S1	1PL/FRSW-1" TEM CODE 1PL/NIP-1"X100LXTOE 1PL/CT-1" 1PL/GR-1"-ZW#7500	3 QTY 1 1 3	STR-21201A./D E 80665 N 72010 EL.+532	
THE PROPERTY OF THE PROPERTY O	ERECTION MATERIALS COMPONENT DESCRIPTION ITTINGS NIPPLE (L=100MM) TOE(NPT) A312-TP316L SML SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16.3ASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 (ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	N.S. (INS) —— SMLS 1 S1 E B16.11 1 S1 FE 1 S1 EAD 1/2 S1 JLL 1 S1	1PL/NIP-1"X100LXTOE 1PL/CT-1" 1PL/GR-1"-ZW#7500	QTY 1 1 3	77NS F3 G6 B7	
PT COMPONO NO FITTINGS 4 NIPPLE SCH80S 5 CAP 300 GASKETS 6 GASKET 2W#750 BOLTS 7 STUD B HEAVY VALVES 8 BALL 15 PORT F (FOR VA CUT P PIECE CUT NO LENGTI <1>>100	COMPONENT DESCRIPTION ITTINGS NIPPLE (L=100MM) TOE(NPT) A312-TP316L SML SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16. GASKETS GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM—60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	(INS) SMLS 1 S1 EB16.11 1 S1 FE 1 S1 EAD 1/2 S1 JLL 1 S1	1PL/NIP-1"X100LXTOE 1PL/CT-1" 1PL/GR-1"-ZW#7500 1PL/BS6-1/2"X65L	1 1 3	217	
FITTINGS 4 NIPPLE SCH80S 5 CAP 300 GASKETS 6 GASKET 7 STUD B HEAVY VALVES 8 BALL 15 PORT (FOR V) CUT P PIECE CUT NO LENGTI <1>> 100	MIPPLE (L=100MM) TOE(NPT) A312-TP316L SML SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16.6ASKETS GASKET S GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	SMLS 1 S1 EB16.11 1 S1 FE 1 S1 EAD 1/2 S1 JLL 1 S1	1PL/GR-1"-ZW#7500 1PL/BS6-1/2"X65L	1 1 3	2	
SCHBUS 5 CAP 300 GASKETS 6 GASKET 7 STUD B HEAVY VALVES 8 BALL 15 PORT F (FOR VA CUT P PIECE CUT NO LENGTI <1>> 100	SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F316L ASME B16 GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	E B16.11 1 S1 FE 1 S1 EAD 1/2 S1 JLL 1 S1	1PL/GR-1"-ZW#7500 1PL/BS6-1/2"X65L	1 3	2	
ZW#750 BOLTS 7 STUD B HEAVY VALVES, 8 BALL 15 PORT F (FOR V) CUT P PIECE CUT NO LENGTI <1>> 100	ZW#7500 ASME B16.21/B16.5 OLTS STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 ALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	EAD 1/2 S1 2 JLL 1 S1 16.34	1PL/BS6-1/2"X65L	12	2 3	
7 STUD B HEAVY VALVES (8 BALL 15 PORT F (FOR V/ CUT P PIECE CUT NO LENGTI <1> 100	STUD BOLT A193 GR.B8M W/ TWO HEX. HEAD HEAVY NUT A194 GR.8M ASME B1.1 B18.2.2 VALVES / IN-LINE ITEMS BALL 150# RF A351-CF3M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIELENGTH (INS)	2 JLL 1 S1 16.34			3	
8 BALL 15 PORT F (FOR V/	BALL 150# RF A351-C73M/316LSS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (FOR VACCUM-60 TORR) (VOC<100 vppm) CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIE LENGTH (INS)	_Y	1PL/VA-1"-4133-VT-E	1		
PIECE CUT NO LENGTI <1> 100	CUT N.S. REMARKS PIE LENGTH (INS) NO					
會簽		PIECE CUT N.S. NO LENGTH (INS) <2> 100 1	REMARKS		3 (2) 127 1 N/S (3) 8 S1PL/VA-1"-4133-VT-E 17	F3 G6 B7 5
					104 F3 G6 B7	DRAIN 5
會 簽 					[1 3 30 b]	
						FOR CONSTRUCTION
						JUL. 04, 2025
						F
						管線編號 TRIM-STR21201A-D-1"-S1PL-HC1
				T	① 管件序號 <1>直管編號 [1] 管段編號 資料庫	— — — Gibine E-shine Advanced Chemicals Ltd
					操作壓力: 0.6 KG/M² G 操作溫度: 88.5 °C 管線等級: S1PL 製 圖 謝鳳菁 2025.04.21 會 設計壓力: 6 KG/M² G 設計溫度: 120 °C 保溫(冷)等級: HC1 設 計 鄧基宏 2025.04.21	富台工程股份有限公司 a bull and in the substitution of
+ + + = +						崙尾一期
<u>A</u> 2025.0	2025.07.03 FOR CONSTRUCTION 2025.04.21 FOR APPROVAL	ION	野基宏 野基宏	陳逢明 陳逢明	試驗基準: Air 6.6 KC	建廠工程 立體配管圖