本		FABRICATION MATERIALS				N	
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY		//it/j\ j//0.122
完	ĺ	<u>PIPE</u>					
	1 2	PIPE A312-TP304 EFW SCH10S BE ASME B36.19M PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	4 1	S1P1/P-4"-10S S1P1/P-1"-40S	0.3M 0.3M		
	3	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M FITTINGS	1/2	S1P1/P-1/2"-40S	0.1M		
後	4	REDUCER ECC BW A403-WP304 SMLS	4 x 2	S1P1/RE-4"X2"	2		14
1 11	5	SCH10S/SCH40S ASME B16.9 SOCKOLET 3000# SW A182-F304 MSS SP-97	4 x 1	S1P1/SOL-4"X1"	1		TG (21118) EL.+15089
請	6	SWAGE ECC BLE/PSE A403-WP304 SMLS SCH40S MSS-SP-95 REDUCING TEE 3000# SW A182-F304 ASME	2 x 1 1 x 1/2	S1P1/SE-2"BX1"P S1P1/TS-1"X1/2"	2	121	
速	8	B16.11 FULL COUPLING 3000# SW A182-F304 ASME	1 x 1/2	S1P1/CFS-1"	1	121	43 F9
1 11	ĺ	B16.11				CONT. FROM	
歸	9	FLANGES FLANGE SW 150# RF A182-F304 SCH40S BORE	1	S1P1/FRSW-1"	1		
還	10	ASME B16.5 FLANGE SW 150# RF A182-F304 SCH40S BORE	1/2	S1P1/FRSW-1/2"	1	157	$\stackrel{13}{\sim}$
	1	ASME B16.5				100	10 165 102 15 PG
	ĺ	ERECTION MATERIALS				1"NS	165 102 (PG 21117) EL.+15083
	PT	COMPONENT DESCRIPTION	N.S.	ITEM CODE	QTY		
	NO		(INS)				13 S1P1//A-1/2"-4144
	11	GASKETS GASKET 150# RF 4.5 MM THICK 304SS SPIRAL	1/2	S1P1/GR-1/2"	1		108 45 45 45 45 45 45 45 45
	1	WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5			•		F10 G11 B12
	ĺ	BOLTS				6 2"x1"NS	
	12	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2	S1P1/BS4-1/2"X60L	4	14MM OFF FLAT FACE	
	ĺ	VALVES / IN-LINE ITEMS					14MM OFFSET
	13	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	1/2	S1P1/VA-1/2"-4144	1	4"x2"NS	EL. + 14002/
	ĺ	INSTRUMENTS				27MM OFF FLAT FACI	FFSET S16 / 14 165 102 7
	14	TEMPERATURE GAUGE 150# RF TG 21118	1		1		150
	15	PRESSURE GAUGE 150# RF PG 21117 SUPPORTS	1/2		1		(<u>S17)</u> FS1-2-06
	16	PIPE A312-TP304 EFW SCH40S BE ASME B36.19M	4	S1P1/P-2"-4"	1		DUMMY WELD (15) (18)
	17	(P-2"-109) FIELD SUPPORT (FS1-2-06)	4	SUP/FS1-2-4"	1		4
							4"x2"NS Z7MM OFFSET Z Z3 CONT. ON
	DIFOE	CUT PIPE LENGTH FOR REFERENCE ONLY	OUT	O DEMARKO			FLAT FACE DOWN 1"X1/2"NS 3
	PIECE NO <6>	CUT N.S. REMARKS PIECE LENGTH (INS) NO 157 1 <7>	CUT N. LENGTH (II 126 1	S. REMARKS NS)			123
	<8>	300 4 <9>	100 1	/2			
	ĺ						
會簽	ĺ						DEVICED
	ĺ						REVISED
	ĺ						FOR CONSTRUCTION
	1						SEP. 12, 2025
	ĺ						
	ĺ						
	ĺ						管線編號
	ĺ						CW-21104-1"-S1P1
						□ 管件序號 <1>直管編號 [1] 管段編號 資料	T 原焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽追蹤管 A B B B B B B B B B B B B B B B B B B
						操作壓力: 3 KC _{CM} ² G 操作温度: 39.6 °C 管統	F線等級: S1P1 製 圖 謝鳳菁 2025.04.21 會 ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■
 	1 - 1	2025.09.12 REVISED FOR CONSTRI	UCTION	鄧基宏	陳逢明	,	R溫(冷)等級: 訳計 鄧基宏 2025.04.21 FU−TAI ENGINEERING CO., LTD.
 		2025.07.03 FOR CONSTRUCTION		鄧基宏	陳逢明	試驗基準: Air 8.8 KC _{CM} G X 60 分 熱進	・
	A	2025.04.21 FOR APPROVAL 日期 修改		鄧基宏	陳逢明	<u> </u>	接基準: 認 可 陳逢明 2025.04.21
	序次	日期 修改	說明	修改	認可		DE 抽驗: 10 % 依據圖號: C2418-4-504 圖號: 檔號: CW-21104-S1P1- 2