7	<b>*</b>		FABRICATION	MATERIALS					N									ì	流水號:	1039
1		PT NO	COMPONENT DE	ESCRIPTION	N.S. (INS)	ITEM CODE		QTY	N									••		
7	司	1	PIPE A312-TP310 B36.19M	6L SMLS SCH40S PE ASME	1	S1PL/P-1"-40S		0.2M												
			FITTINGS										CONN.	TO 1101A./D\						
	_ <u> </u>	2	90 ELBOW 3000# FLANGES	\$ SW A182-F316L ASME B16.11	1	S1PL/ES-1"X90		1					E 80669 N 7701	5 0						
	請	3	FLANGE SW 150 ASME B16.5	# RF A182-F316L SCH40S BORE	1	S1PL/FRSW-1"		3					EL.+53	2						
1	<u>,, ,</u>		ERECTION MA	TERIALS																
I	اا <del>د</del>	PT NO	COMPONENT DE	ESCRIPTION	N.S. (INS)	ITEM CODE		QTY					1'NS	F3 G6 B7						
	翌		FITTINGS								127									
[ /2		4	SCH80S ASME B			S1PL/NIP-1"X100	OLXTOE	1												
		5	GASKETS	O (FNPT) A182-F316L ASME B16.11	1 1	S1PL/CT-1"		1			2/7/3									
		6	ZW#7500 ASME	F 3.0 MM THICK VIRGIN PTFE B16.21/B16.5	1	S1PL/GR-1"-ZW#	¥7500	3		2										
		7	BOLTS OTUB BOLT A40	OD DOMAN, TWO LIEV, LIEAD	4/0	0401/0004/001	oe.	40			② ≈.									
		/		3 GR.B8M W/ TWO HEX. HEAD 4 GR.8M ASME B1.1 B18.2.2	1/2	S1PL/BS6-1/2"X6	DOL.	12		3										
			VALVES / IN-LINE																	
		8	PORT FIRE SAFI	351-CF3M/316LSS+PTFE FULL E WRENCH OPER. ASME B16.34 60 TORR) (VOC<100 vppm)	1	S1PL/VA-1"-4133	3-VI-E	1					. F2							
				1								125	1"No.	, 						
		PIECE		STH FOR REFERENCE ONLY S. REMARKS PIECE	E CUT	N.S. REMARK	(S					<b>\</b> /								
		NO <1>	LENGTH (IN	IS) NO		(INS)	.0													
															S. G	F3 G6	B7			
															4	5				
													8	PL/VA-1"-4133-VT-E			6			
													311	1:	27		DRAIN	5		
														Œ	104 / 3 G6 B7	<b>/</b> \4				
														U_	3 G0 D7)	V				
	簽																			
分配 △																	F	OR CON	ISTRUC'	TION
																			04 0005	
																		JUL.	04, 2025	
	+																ı	等给作品		
	+																	管線編號 TRIM-STR21:	101A-D-1"-S1PL	-HC1
									□ 管件序號 <1>直	T管編號 [1] 管段編號	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~			秦焊 螺紋銜接 配合現場焊接 [	配合現場接	医合點 管支撑	蒸汽追蹤管	হল	· · · · · · · · · · · · · ·	
									& 須設計會驗管線		名稱 :	-	<u> </u>	<del></del>	-			asononiae E	-shine Advanced C	Chemicals Ltd.
		$\triangle$								操作溫度: 88.5 °C		1PL	製圖	謝鳳菁 2025.04.21				富台 FU-	工程股份	有限公司
	+						3kn ++	<u>μ</u> + \b -□			保溫(冷)等級: HC	C1	設計	鄧基宏 2025.04.21	<b> </b>				TAI ENGINEERIN	
				FOR CONSTRUCTION			鄧基宏 鄧基宏	陳逢明		6.6 KG/CM <sup>2</sup> G X 60 分 管 管 材 塗 装	熱追縱等級:		審 核 認 可	陳安誠 2025.04.21 陳逢明 2025.04.21	1 TO 1—			崙尾一期 建廠工程	管線工程 立體配管[	
		序次	2025.04.21	FOR APPROVAL 修改	 		<b>野奉左</b> 修 改	<b>陳逢明</b> 認 可	管路塗裝: 焊道. 塗裝:	管材塗裝 一支 一支 一数網及不第 一 一支 一数網保溫(冷) 一 不銹鋼	焊接基準:	9 1	• •	<b>陳運明</b>   2025.04.21   C2418-4-501					-STR21101A-D-	
		11.47	山 柳	½ LA	u/6 47		i/ W	nn: _1	塗装・	1手  木銹鋼	NDE 抽驗:	/0   I	V 113V 11⊒∏ 기//I	, 02710-7-001	<u>, 11211 ≯/ 1</u>			ı⊞ Wu. IIXIIVI	211121101A-D-	