		FABRICATION MATERIALS				<sub>&gt;√</sub> N 流水號:255
	PT NO	COMPONENT DESCRIPTION	N.S. I	ITEM CODE	QTY	<b>川小玩.299</b>
		PIPE	<u>· · · ·</u>			
元	1	PIPE A53 GR.B GALV. SMLS SCH40 BE ASME B36.10M	4 (	C1A1/P-4"-40	2.8M	
	2	PIPE A106 GR.B GALV. SMLS SCH80 PE ASME B36.10M	1 (	C1A1/P-1"-80	0.1M	
<u>↓ </u>   後	3	PIPE A106 GR.B GALV. SMLS SCH80 PE ASME B36.10M	1/2	C1A1/P-1/2"-80	0.1M	
1 11		FITTINGS		0444/001 45745		
請問	4 5 6	SOCKOLET 3000# SW A105 GALV. MSS SP-97 SOCKOLET 3000# SW A105 GALV. MSS SP-97 90 ELBOW LR BW A234 GR.WPB GALV. SMLS SCH40 ASME B16.9	4 x 1/2	C1A1/SOL-4"X1" C1A1/SOL-4"X1/2" C1A1/EB-4"X90	1 1 1	6 F7 G12 B15 229
速		FLANGES				13
	7	FLANGE WN 150# RF A105 GALV. STD BORE ASME B16.5		C1A1/FRWN-4"	6	
還	8	FLANGE SW 150# RF A105 GALV. SCH80 BORE ASME B16.5	1/2	C1A1/FRSW-1/2"	1	17 C1A1/VA-4"-1112 C1A1/VA-4"-1112 C1A1/VA-4"-1112 S
	PT NO	COMPONENT DESCRIPTION	N.S. <u> </u>	ITEM CODE	QTY	F7 G12 B14 4 PT FL 4040
		FITTINGS				229 F8 G13 B16 C4A40/A 4/28 A442
	9	SPECTACLE BLIND 150# RF A105 GALV. <std dwg.=""></std>	4 (	C1A1/SB-4"	1	F7 G12 B15 EL.+935
	10	NIPPLE (L=100MM) TOE(NPT) A106 GR.B GALV. SMLS SCH80 ASME B36.10M	1 (	C1A1/NIP-1"X100LXTOE	1	CONT. ON F7 G12 B15 <2>2
	11	CAP 3000# SCRD (FNPT) A105 GALV. ASME B16.11	1 (	C1A1/CT-1"	1	E 163652 N 87650 T8
	12	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/CS OUTER RING	4 (	C1A1/GR-4"	7	C1A1/VA-1"-1812 10 F7 G12 B15 4"x1/2"NS
	13	ASME B16.20/B16.5 GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/CS OUTER RING ASME B16.20/B16.5	1/2	C1A1/GR-1/2"	1	地下管:ISO 13  BL.+404  TO  S22  GR1-2  R1-2  R39  FL.+404
		BOLTS				S21 FS1-2-05 ®
	14	STUD BOLT A193 GR.B7 GALV. W/ TWO HEX. HEAD HEAVY NUT A194 GR.2H GALV. ASME B1.1	5/8	C1A1/BS1-5/8"X115L	8	DUMMY WELD 250
	15	B18.2.2 STUD BOLT A193 GR.B7 GALV. W/TWO HEX. HEAD HEAVY NUT A194 GR.2H GALV. ASME B1.1 B18.2.2	5/8	C1A1/BS1-5/8"X95L	40	
	16	STUD BOLT A193 GR.B7 GALV. W/TWO HEX. HEAD HEAVY NUT A194 GR.2H GALV. ASME B1.1 B18.2.2	1/2	C1A1/BS1-1/2"X60L	4	F7 G12 B15
		VALVES / IN-LINE ITEMS				FT CONT. ON 2
	17	GATE 150# RF A216-WCB BB OS &Y RS TRIM 13CR STELLITED FLEXIBLE WEDGE API-600	R 4	C1A1/VA-4"-1112	2	(11001)
	18	GATE 800# SW A105 BB OS &Y RS TRIM 13CR STELLITED SOLID WEDGE API-602	1 (	C1A1/VA-1"-1812	1	
	19	BALL 150# RF A216-WCB/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	1/2	C1A1/VA-1/2"-4112	1	
<b>今</b> ′交	20	VORTEX FLOWMETER 150# RF FT 11001	4		1	HOLD!
會 簽		SUPPORTS				
	21 22	FIELD SUPPORT (FS1-2-05) GROUT (GR1-2)		SUP/FS1-2-4" SUP/GR1-2-4"	1 1	
		CUT PIPE LENGTH FOR REFERENCE ONLY				FOR CONSTRUCTION
	PIECE					UU 04 0005
	NO <1> <3>	LENGTH (INS) NO 129 4 <2> 200 4 <4>	LENGTH (INS) 100 1 100 1/2			JUL. 04, 2025
	<5>	2412 4	100 1/2			管線編號
						W-11001-4"-C1A1
						① 管件序號 <1>直管編號 [1] 管段編號 資料庫
	$\triangle$					操作壓力: 0.5   KC <sub>M</sub> ² G 操作溫度: 30   C   管線等級: C1A1   製
				7± 1.4	∏±\b=⊓	$\frac{1}{1}$ $\frac{1}$
	<u>/0\</u>	2025.07.03 FOR CONSTRUCTION		陳至鉉	陳逢明	試驗基準: Air
	<u>A</u> 序次	2025.04.21     FOR APPROVAL       日期     修改	 	陳至鉉       修改	<b>陳逢明</b> 認 可	
	11. 1/		마. 박	16 LX		<sup>焊道</sup> :