		FABRICATION MATERIALS					:: 465
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY	流水就	,, , , ,
		FITTINGS					
元	1	REDUCER ECC BW A403-WP304 SMLS SCH40S	6 x 4	S1P4/RE-6"X4"	1		
	2	ASME B16.9 REDUCING TEE BW A403-WP304 SMLS SCH40S ASME B16.9	6 x 4	S1P4/TB-6"X4"	1		
	3	45 ELBOW LR BW A403-WP304 SMLS SCH40S ASME B16.9	6	S1P4/EB-6"X45	1	<u> S9</u>	
後		FLANGES				GR2-5	
請	4	FLANGE WN 150# RF A182-F304 SCH40S BORE ASME B16.5	6	S1P4/FRWN-6"	3	CONT. ON / P-61703-4"-S1P4	
		Nome Bro.0				/ 1 \ // E 110615	
速		ERECTION MATERIALS				// N 26893 EL.+1138 704	
記	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY		
	11	FITTINGS	(1143)			S11 S12 C-601 F4 G6 B7	
還	5	FLEXIBLE HOSE 150# RF L= 1200mm PER DATA	6	S1P4/FLX-6"	1	464 P-4"-122 143 5 5	
	-	SHEET (FLEX-61803)				CONT. FROM 140 FLEX-61803 50MM OFFSET UP	
	6	GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE	6	S1P4/GR-6"-ZW#7500	4		
		ZW#7500 ASME B16.21/B16.5				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
	7	BOLTS OTUB POLT A400 OR POWETHYOUSY USAR	0/4	0404/004-0/4894051	20	1 6"x4"NS 2 2	
	'	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	3/4	S1P4/BS4-3/4"X105L	32	27MM OFFSET 6"x4"NS FLAT FACE DOWN EL.+1008	
		VALVES / IN-LINE ITEMS				1200	
	8	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE GEAR OPER. ASME B16.34 (VOC<100	6	S1P4/VA-6"-4144A-E	1	BA1-4-07 H	
		vppm) SUPPORTS				DOWN WELD 87	
	9	GROUT (GR2-5)	6	SUP/GR2-6"	1	S12 G6 B7 CONN. TO	
	10 11	BASE ANCHOR (BA1-4-07) PIPE A312-TP304 EFW SCH40S BE ASME B36.19M	6 6	SUP/BA1-4-6" S1P4/P-4"-6"	1 1	C-601 TK-618/N11 E 112680	
	12	(P-4"-122) FLANGE GROUNDING CONDUCTOR (C-601)	6	MISC/C-601	4	276 150 C-601 N 26618 R C-601 EL.+1058	
						S1P4/VA-6"-4144A-E	
						CSO	
△ 會 簽						DEVICED.	
分配△△	\subseteq					REVISED	TION
						FOR CONSTRUCT	IION
						SEP. 12, 2025	,
						管線編號	
	_					P-10105-4"-S1P4	
						□ 管件序號 <1>直管編號 [1] 管段編號 資料庫 工廠焊接 套焊 螺紋銜接 配合現場接合點 管支撑 蒸汽追蹤管 鴻勝化學科技股份有 经 通訊 中央	有限公司
				ı		Q. 須畝自智観自称 ロ仲 ここ // ■ E-STITUTE ADVANCED CHEMIN	
	\ <u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>	0005 00 40 051 #055 555 551	U.O.T.O.	11 /= 1	14 17± 1/2 an	操作壓力: 2.9 KC/ _{CM²} G 操作溫度: 38 C 管線等級: S1P4 製 圖 胡庭瑋 2025.04.21 會 富台工程股份有限	限公司
	1	2025.09.12 REVISED FOR CONSTR	CUCTION	林信即		W. R. L. A. C. A. C. L. C.	
	<u> </u>	2025.07.03 FOR CONSTRUCTION		林信即			8
	<u>A</u> 序次	2025.04.21 FOR APPROVAL	 說 明	林信即			
	1111	日期修改	說 明	修己	改 認 可	可 ^{焊道} :	

Ν

FABRICATION MATERIALS