		FABRICATIO	N MATERIALS					N N										流水號	:1180
昌	PT NO	COMPONENT	DESCRIPTION	N.S. (INS)	ITEM	CODE	QTY	W										7712 3 4 3770	
	-	PIPE		(1110)															
完	1 2		804 EFW SCH40S BE ASME B36.19N 804 EFW SCH40S PE ASME B36.19N			I/P-4"-40S I/P-3/4"-40S	52.2M 0.1M												
		FITTINGS	304 ET W 3011403 FE A3WE B30.19W	3/4	3174	HF-014 -400	O. HW												
1/4.	3		00# SW A182-F304 MSS SP-97 BW A403-WP304 SMLS SCH40S	4 x 3/4 4		I/SOL-4"X3/4" I/EB-4"X45	1 1					^					S10 S1	35) 5	
後	5	ASME B16.9 90 ELBOW LR	BW A403-WP304 SMLS SCH40S	4		I/EB-4"X90	3			~	/	1				C10		1 96	
請		ASME B16.9								100	\sim \sim				[S11 SRP-4	34 5000	36	<26>1
速		ERECTION M	ATERIALS							EL.+1019	91					-00-		337	4"NS
	PT NO	COMPONENT	DESCRIPTION	N.S.	ITEM	CODE	QTY				L			S11 SRP-4	S10 S1	600	<24>[1 $<25>1$ CONT	. ON 8067-4"-S1P4
記帚	NO	FITTINGS		(INS)					VENT	7 / <18>1			00	S10 \ \	32 31		S9	S11 E 1861 SRP-4 N 4972	120
還	6		OMM) TOE(NPT) A312-TP304 SMLS	3/4	S1P4	I/NIP-3/4"X100LXTOE	1	<i>\</i>	EL.+10091		8 S1P4/VA-3/4	4"-1844	S9 G5-2	S1		33	G5-2	EL.+80	
/4X	7	SCH80S ASME CAP 3000# SC	: B36.19M RD (FNPT) A182-F304 ASME B16.11	3/4	S1P4	I/CT-3/4"	1		[0]		<u>S11</u>	\wedge	S10 (31) S1	6000	10	<23>[22>]1 \S11	1	1	196
		VALVES / IN-LIN						<17>	EL.+10028	63	SRP-4\ <19>1	(30)		38	₅₂ 70×<2	SRP-4	ŀ		190
	8		V A182-F304 BB OS &Y RS TRIM TED SOLID WEDGE API-602	3/4	S1P4	I/VA-3/4"-1844	1			[63]	1050	600	0	_					
		SUPPORTS						3 4"x3/4	4"NS / 548		0000	1		<21>1					
	9 10 11			4 4 4	SUP/	'G5-2-4" 'S1-4" 'SRP-4"	4 10 10		S10 (62) S1	1550		1 \ /	<20>1	\S11 SRP-4					
			(6.4)	·				4 45	50 25 2332			S10							
		CUT PIPE LE	NGTH FOR REFERENCE ONLY							61 3722	S	S1							
	NO) LENGTH	N.S. REMARKS PIECI (INS) NO	LENGTH	N.S. (INS)	REMARKS		<16>1		2732	29 \ S1	G5-2							
	<15 <17 <19	7> 100	4 <16> 3/4 <18> 4 <20>	4725 4066 6000	4 4 4			S10	24	~9	S11	 P-4							
	<21 <23	1> 6000 3> 6000	4 <22> 4 <24>	6000 6000	4			S1	8 SRP-4	511	>								
	<25	5> 5966	4 <26>	493	4			🗆 (2 / 2	SRP-4									
								<15>1											
								4"١		<i>/</i>	5 EL.+8657								
								45		1629									
	+									S11 SRP-4									
	-									SRP-4 G5-2									
	+							CONT	. FROM 4250										
	1							2	1170										
	1								1179										
△ 會 簽																		DEVICED	
分配△△																	FOR	REVISED CONSTRUC	TION
																		SEP. 12, 202	5
	-																		
	+																管線編號	ਰੈ 6047-4"-S1P4	
	+							□ 管件序號 <1		編號 咨判	17	「厭悍接 奈!	星 螺紋銜接 i	配合银場焊接	1000円開接合	點 管支撑 蒸汽追			- 大阪ハヨ
	1							& 須設計會驗管緩		■ ル 貝 付 単 . 名稱 :	-			\	-		l Gabiae	鴻勝化學科技股份 E-shine Advanced Che	
		<u> </u>							K _M ² G 操作温度: 25	℃ 管線等級:	S1P4	製圖	胡庭瑋	2025.04.21	☆			· [台工程股份有	限公司
	1	•	REVISED FOR CONST	RUCTION		林信助	陳逢明		℃M² G 設計溫度: 70	℃ 保溫(冷)等級	₹:	設計		2025.04.21				FU—TAI ENGINEERING	CO., LTD.
	<u> </u>					林信助	陳逢明	試驗基準: Air	4.4 KG/CM ² G X 60			審核		2025.04.21	 簽		編尾一期 建成工程		
	Â	_		<u> </u>	n	林信助	陳逢明	管路塗裝:	管 材 塗 装 供網及不銹. 「費」「大調」(一)「「」」「「」」「「」」「「」」「「」」「」」「」」「」」「」」「」」「」」「	开汉至于 ,		認可		2025.04.21			建廠工程		3
	序次	7 日期	修改	說 E	明	修改	認可	焊道. 塗裝:	撑 ጃ嬌鋼 :	NDE 抽驗:	10 %	X據圖號:	C2418-4-536	6	圖號:		檔號: W	/W-18047-S1P4- 3	