	-	FABRICATION MA	ATERIALS				<sub>→</sub> N 流水號:1140
			CCRIPTION	N.S. (INS)	ITEM CODE	QTY	》
	- 11	FITTINGS		(11.0)			
	_ _ _	TEE BW A403-WP3	304 SMLS SCH40S ASME B16.9	2 x 2	S1P1/TB-2"	2	
	_   2	2 FLANGE WN 150# ASME B16.5	RF A182-F304 SCH40S BORE	2	S1P1/FRWN-2"	6	
	11	ERECTION MATE	RIALS				
	11	0	CRIPTION	N.S. (INS)	ITEM CODE	QTY	1 2"x2"NS
記売	∄ 3	GASKET 150# RF 4 WOUND W/GRAPH RING ASME B16.20	4.5 MM THICK 304SS SPIRAL HITE FILLER W/SS304 OUTER D/B16.5	2	S1P1/GR-2"	4	E 68548 N 47000 EL.+2309
還	4		GR.B8 W/ TWO HEX. HEAD GR.8 ASME B1.1 B18.2.2	5/8	S1P1/BS4-5/8"X85L	16	E 68830 178 5
	5	5 BALL 150# RF A35	1-CF8/304SS+PTFE FULL PORT CH OPER. ASME B16.34	2	S1P1/VA-2"-4144-E	2	EL.+2309 7 CONN. TO V-606/N46A
	6		TER 150# RF LT 60602 J# RF LG 60602	2 2		1	7 <sub>28</sub> ②
		SUPPORTS					E 68548 C-501
	8	3 FLANGE GROUND	ING CONDUCTOR (C-501)	2	MISC/C-501	4	N 47000 EL.+1287
							E 68830
							LT S1P1/VA-2"-4144-E
							1
							LG 60602
	5						
分配							FOR CONSTRUCTION
							JUL. 04, 2025
							管線編號 TRIM-V606-N46AB-2"-S1P1-C60
					ı	1	① 管件序號 <1>直管編號 [1] 管段編號 資料庫.
	-						操作壓力: 0.05 KG/LG 操作溫度: -16~38 C 管線等級: S1P1 製 圖 陳怡如 2025.04.21 會 富台工程股份有限公司 設計壓力: 0.14 KS/LG 設計溫度: -26~80 C 保溫(冷)等級: C60 設 計 黃炳富 2025.04.21
			EOD OCNOTOUSTICS		****	⊯冷□□	N. H. E. C.
	<u> </u>		FOR CONSTRUCTION FOR APPROVAL		黄炳富 黄炳富	陳逢明 陳逢明	試驗基準: Air
	_						1
	序:	次 日 期	修改	說 明	修改	認可	焊道: