本		FABRICATION MATERIALS				→ N 流水號:279
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY	<b>加水流:279</b>
完	1	PIPE	1/2	S1P1F/P-1/2"-40S	3.2M	
1/4	2 3	FITTINGS  TEE 3000# SW A182-F304 ASME B16.11 SWAGE CONC PLE/TSE(NPT) A403-WP304 SML	1/2 x 1/2 S 1/2 x 1/4	S1P1F/TS-1/2" S1P1F/SC-1/2"PX1/4"T	1 1	5 EL.+1011\
後	4	SCH40S/SCH80S MSS-SP-95 REDUCING TEE 3000# SCRD (FNPT) A182-F304	1/2 x 1/4	S1P1F/TT-1/2"X1/4"	1	$\sqrt{}$
請	5	ASME B16.11 90 ELBOW 3000# SW A182-F304 ASME B16.11	1/2	S1P1F/ES-1/2"X90	5	
- 11		FLANGES				
速 歸	6	FLANGE SW 150# RF A182-F304 SCH40S BORE ASME B16.5	1/2	S1P1F/FRSW-1/2"	2	000 V V V V V V V V V V V V V V V V V V
還	PT	COMPONENT DESCRIPTION	N.S.	ITEM CODE	QTY	
/4X	NO	GASKETS	(INS)			1/2"NS CONT. FROM 1/2"NS 1
	7	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	1/2	S1P1F/GR-1/2"	1	② 2 1/2"x1/2"NS
	8	BOLTS  STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2	S1P1F/BS4-1/2"X60L	4	19 PG(F) 36 36
		VALVES / IN-LINE ITEMS				23 21 23 23
	9	GLOBE 800# SW A182-F304 BB OS &Y RS TRIM 304SS STELLITED LOOSE DISC API-602	1/2	S1P1F/VA-1/2"-2844	2	9 S1P1F/VA-1/2"-2844 GR2-1 S1P1F/VA-1/2"-2844 GONN TO
		SUPPORTS				S1P1F/VA-1/2"-2844 CONN. TO P-116A/4
	10 11	GROUT (GR2-1) FIELD SUPPORT (FS5-1-04)	1/2 1/2	SUP/GR2-1/2" SUP/FS5-1-1/2"	1 1	<19>1
	NO	LENGTH (INS) NO	2> 568 4> 489 6> 120 8> 317	N.S. REMARKS (INS) 1/2 1/2 1/2 1/2 1/2		75 75 4 1/2"x1/4"NS F6 G7 B8 S2, N F1 F2 F1 F1 F2 F1 F2 F1 F1 F2 F1 F1 F2 F1 F1 F2 F1
						<15>1 1/2"NS 33
						FOR CONSTRUCTION
						JUL. 15, 2025
+						管線編號 FW 00340 4/2" S4D4E
						FW-90219-1/2"-S1P1F
						& 須設計會驗管線
						Q. 須飲計書級目标 口冊 ここ // 量 E-Shirke Advanced Chemicut's Etd.
	$\triangle$					操作壓力: 10   K
	<u>^</u>	2025.07.15 FOR CONSTRUCTION	N	陳至鉉		操作壓力: 10   KC   KC   KC   KC   KC   KC   KC   K
	$\triangle$	2025.07.15 FOR CONSTRUCTION 2025.04.21 FOR APPROVAL 日期 修改		陳至鉉	陳逢明	操作壓力: 10   KC   KC   KC   KC   KC   KC   KC   K