本		FABRICATION	MATERIALS				流水號	1060
	PT	COMPONENT D	ESCRIPTION	N.S.	ITEM CODE	QTY		,. 1000
	NO NO	FLANGES		(INS)				
75	11	FLANGE SW 15 ASME B16.5	0# RF A182-F304 SCH40S BORE	3/4	S1P4/FRSW-3/4"	1		
		ERECTION MA	TERIALS					
後	PT	COMPONENT D	ESCRIPTION	N.S.	ITEM CODE	QTY		
言	II NO	FITTINGS		(INS)		_		
速		NIPPLE (L=100M SCH80S ASME	MM) TOE(NPT) A312-TP304 SMLS B36.19M	3/4	S1P4/NIP-3/4"X100LXTOE	1		
	11	CAP 3000# SCR GASKETS	D (FNPT) A182-F304 ASME B16.11	3/4	S1P4/CT-3/4"	1		
歸	11		RF 3.0 MM THICK VIRGIN PTFE B16.21/B16.5	3/4	S1P4/GR-3/4"-ZW#7500	2		
還		BOLTS						
	5		93 GR.B8 W/ TWO HEX. HEAD 94 GR.8 ASME B1.1 B18.2.2	1/2	S1P4/BS4-1/2"X65L	8		
	6	VALVES / IN-LINE	ITEMS 	3/4	S1P4/VA-3/4"-4144-E	1		
			ENCH OPER. ASME B16.34	. .				
	7	SUPPORTS ELANGE GROUI	NDING CONDUCTOR (C-401)	3/4	MISC/C-401	2		
	,	TEANGE GROOM	NEING CONECTON (C-401)	3/4	WIIGC/G-401	2	VENT EL.+1327	
							CONN. TO EL.+1219 C-401	
							STR-61301./V E 104495 N 32000 S1P4/VA-3/4"-4144-E	
							N 32000 S1P4/VA-3/4"-4144-E EL.+1099 C-401	
☆ 會 簽								
分配△△							FOR CONSTRUC	CTION
	-						JUL. 04, 202	
							30L. 04, 202	
	_							
							管線編號	3/4"-S1P4
							① 管件序號 <1>直管編號 [1] 管段編號 資料庫. 工廠焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽追蹤管 Gdb8oo 鴻勝化學科技	股份有限公司
							O. And a	
							設計壓力: 3.5 KG/CM² G 設計溫度: 80 C 保溫(冷)等級: 設計 黃炳富 2025.04.21	RING CO., LTD.
	<u>ô</u>		FOR CONSTRUCTION		黄炳富		月 試驗基準: Air 3.85 KC M² G X 60 分 熱追縱等級: 審 核 陳安誠 2025.04.21 簽 崙尾一期 管線工	
	A F		FOR APPROVAL	÷A no	黃炳富	陳逢明	月 管路塗裝:	
	序次	日期	修改	說 明	修改	認可	「	7-5114- 1