	_						NI NE L. III E.	
			FABRICATION MATERIALS				│	645
		PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	<u>QTY</u>		
7	钊	1	PIPE PIPE A312-TP304 EFW SCH10S BE ASME B36.19M	4	S1P1/P-4"-10S	10.7M	VENT, L.+9841 7	
	$T \parallel$	2	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M FITTINGS	3/4	S1P1/P-3/4"-40S	0.1M	51 . 2744 @ \\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
-	<u></u>	3	TEE BW A403-WP304 WELD SCH10S ASME B16.9 SOCKOLET 3000# SW A182-F304 MSS SP-97	4 x 4 4 x 3/4	S1P1/TB-4" S1P1/SOL-4"X3/4"	1	EL.+9741 E	
	叁	5	90 ELBOW LR BW A403-WP304 WELD SCH10S ASME B16.9	4	S1P1/EB-4"X90	5	13 S1P1/VA-3/4"-1844-E <a> This is a second of the second	
	請		FLANGES					
$\frac{1}{2}$	東	6	FLANGE WN 150# RF A182-F304 SCH10S BORE ASME B16.5	4	S1P1/FRWN-4"	2	4"x3/4"NS \	
			ERECTION MATERIALS				12 /S1P1/VA-4"-4144-F	
	- 11	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY		
7.	翌		FITTINGS	(110)			C-501 CONN. TO C-4-75	
		7	NIPPLE (L=100MM) TOE(NPT) A312-TP304 SMLS SCH80S ASME B36.19M	3/4	S1P1/NIP-3/4"X100LX	ΓΟE 1	E-605/N2 E 76450 P-19017-8"	S1P1
		8	CAP 3000# SCRD (FNPT) A182-F304 ASME B16.11 FLANGES	3/4	S1P1/CT-3/4"	1	EL.+3575 S I +0507	498
		9	FLANGE BLIND 150# RF A182-F304 ASME B16.5	4	S1P1/FBR-4"	1	(G10 B11) (S10) (S	1 00
			GASKETS				S14 C-501	
		10	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	4	S1P1/GR-4"	4	5 S14 S1P1/VA-4"-4144-E	
			BOLTS				S17 C-501	
		11	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	5/8	S1P1/BS4-5/8"X95L	32		
			VALVES / IN-LINE ITEMS				S15 FS17-5-0508 EL.+3756	
		12	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (VOC<100 vppm)	4	S1P1/VA-4"-4144-E	2	S16 / ³ 00 S14 C-501	
		13	GATE 800# SW A182-F304 BB OS &Y RS TRIM 304SS STELLITED SOLID WEDGE API-602 (VOC<100 vppm)	3/4	S1P1/VA-3/4"-1844-E	1	F6 G10 B11	
			SUPPORTS					
		14 15	FLANGE GROUNDING CONDUCTOR (C-501) FIELD SUPPORT (FS17-5-0508)	4	MISC/C-501 SUP/FS17-5-4"	4	3 4"x4"NS ⑤	
		16 17 18	CRADLE SHOE (C-4-75) PIPE GUIDE (G5-2) FIELD SUPPORT (FS17-1-0308)	4 4 4	SUP/C-4"-75 SUP/G5-2-4" SUP/FS17-1-4"	2 1 1		
							600	
		PIECE	CUT PIPE LENGTH FOR REFERENCE ONLY CUT N.S. REMARKS PIECE	CUT	N.S. REMARKS			
		NO <1> <3>	LENGTH (INS) NO 434 4 <2> 343 4 <4>		(INS) 4 4			
	簽	<5> <7>	5628 4 <6> 2346 4 <8>		3/4 4			
分配/							[5] _<4>[1]	
							FOR CONSTRUCTIO	N
							III 04 2025	
							JUL. 04, 2025	
							To the second of the second o	
							P-60510-4"-S1P1-C75	
	+						① 管件序號 <1>直管編號 [1] 管段編號 資料庫 工廠焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽追蹤管 & 独勝化學科技股份有	
	1.	\triangle					操作壓力: 0.05 KCM² G 操作溫度: -16 C 管線等級: S1P1 製 圖 陳怡如 2025.04.21 🚖 I 富台工程股份有图	
	 	\triangle				= n+\n -n	設計壓力; 2/-0.1 KS _{CM} ² G 設計溫度; 80/-26 °C 保溫(冷)等級; C75 以 計 黃炳富 2025.04.21 □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	0., LTD.
			2025.07.03 FOR CONSTRUCTION 2025.04.21 FOR APPROVAL		黄炉 黄炉			$-\left(\begin{array}{c}1\\1\end{array}\right)$
		/A\ 序次	日 期			改 認 可	1 日田主人· 1	
			1		I	1		