<u></u>		FABRICATION MATERIALS				N					
	PT	COMPONENT DESCRIPTION	N.S.	ITEM CODE	QTY	N					流水號:1192
	NO NO		(INS)	TEM CODE	<u> </u>		CONT.	ON			
元	1	PIPE A312-TP304 EFW SCH40S BE ASME B36.19M	3	S1P4/P-3"-40S	0.3M		EL.+1380				
	2	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M FITTINGS	1	S1P4/P-1"-40S	0.6M		C &				
1/4.	3	REDUCER CONC BW A403-WP304 SMLS SCH40S ASME B16.9	3 x 2	S1P4/RC-3"X2"	1						
後	11 5	SOCKOLET 3000# SW A182-F304 MSS SP-97 TEE 3000# SW A182-F304 ASME B16.11	3 x 1 1 x 1	S1P4/SOL-3"X1" S1P4/TS-1"	1		-173				
請	6 7	SWAGE CONC PBE A403-WP304 SMLS SCH40S MSS-SP-95 90 ELBOW LR BW A403-WP304 SMLS SCH40S	1 x 1/2 3	S1P4/SC-1"PX1/2"P S1P4/EB-3"X90	1		6 1"x1/2"NS\				
速		ASME B16.9 FLANGES					46 89 23			044	
歸	8	FLANGE WN 150# RF A182-F304 SCH40S BORE ASME B16.5	3	S1P4/FRWN-3"	1		PG 18061B 23			CONT. ON 241	G10
	11 ~		2	S1P4/FRWN-2"	1	16	21)	14		184
還		ERECTION MATERIALS				S1P4/VA-1/2	~ / %		S1	P4/VA-3"-3144 F8 G10 B12	/ / N / EL ±144E
	PT	COMPONENT DESCRIPTION	N.S.	ITEM CODE	QTY		5 1"x1"NS	25;			(S) ELL-11443
	NO NO	GASKETS	(INS)					2573 2373		, and the second	
	10	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER	3	S1P4/GR-3"	2			13/3			
	11	RING ASME B16.20/B16.5 GASKET 150# RF 4.5 MM THICK 304SS SPIRAL	2	S1P4/GR-2"	1				76 15		44
		WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5							S1P4/\	/A-1"-1844	
	12	BOLTS STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD	5/8	S1P4/BS4-5/8"X95L	4				DRAIN 23		
	13	HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2 STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	5/8	S1P4/BS4-5/8"X85L	4				24	75/3	33.
		VALVES / IN-LINE ITEMS								371	
	14	STELLITED API-600		S1P4/VA-3"-3144	1						
	15 16	304SS STELLITED SOLID WEDGE API-602 GATE 800# SW/SCRD(NPT) A182-F304 BB OS &Y	1/2	S1P4/VA-1"-1844 S1P4/VA-1/2"-1U44	1						
		RS TRIM 304SS STELLITED SOLID WEDGE API-602								4 3"x1	<u></u>
		CUT PIPE LENGTH FOR REFERENCE ONLY								3"x1	"NS 23 EL.+1208
	PIEC	CE CUT N.S. REMARKS PIECE LENGTH (INS) NO	CUT N.: LENGTH (IN	S. REMARKS							
	<1> <3>	> 206 1 <2>	235 1 223 3								
	_										100
											S N. S
										CONN. TO	② EL.+1108
分配 △△	7									P-1830B/DISCH E 149500	153 3"x2"NS
							FOR CONSTRU	JCTION		N 63200 EL.+950	F9 G11 B13
						JUL. 04, 2025					
											管線編號
	-					11 0A 44 == 0=	管件序號 <1>直管編號 [1] 管段編號 資料庫 工廠焊接 套焊			WW-18064-3"-S1P4	
	1					① 管件序號 & 須設計會驗	管線	名稱 [:]		-	海勝化學科技股份有限公司 E-shine Advanced Chemicals Ltd.
	\triangle					操作壓力: 2	7 0111	管線等級: S1P4	製 圖 陳郁惟 2025.04.21	· · · · · · · · · · · · · · · · · · ·	富台工程股份有限公司 FU-TAI ENGINEERING CO., LTD.
	\bigcirc	2025.07.03 FOR CONSTRUCTION		陳至鉉	陳逢明	設計壓力: 4 試驗基準: Air	KG _{M²} G 設計溫度: 70 ℃ 4.4 KG _{M²} G X 60 分	保溫(冷)等級: 勃治縱等級·	設計 陳至鉉 2025.04.21 審核 陳安誠 2025.04.21		FU-TAI ENGINEERING CO., LTD. 管線工程 1
	Â			陳至鉉	陳逢明	管路塗裝:	··· /CM··· ∧ ♥∪ // 管 材 塗 装	焊接基準:	部 可 陳逢明 2025.04.21	篇	建廠工程 立體配管圖 2
	序次		說 明	修改	認可	焊道.	管 材 塗 装	NDE 抽驗: 10 %	依據圖號: C2418-4-530	圖號:	檔號: WW-18064-S1P4- 1