		FABRICATION MATERIALS					N				
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	<u>(</u>	NTY	₩ N				//IL/J\ J//U-1 ZO
	1	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	3/4	S1P1/P-3/4"-40S		2.6M					
	,	FITTINGS  SWACE COME PRE A402 WP204 CM C SCLIAGE	4 2/4	CADA/CC ANDV2/AND	D.	4					
	3	SWAGE CONC PBE A403-WP304 SMLS SCH40S MSS-SP-95 FULL COUPLING 3000# SW A182-F304 ASME	1 x 3/4 3/4	S1P1/SC-1"PX3/4"i S1P1/CFS-3/4"		1					
後	3	B16.11 90 ELBOW 3000# SW A182-F304 ASME B16.11	3/4	S1P1/CFS-3/4 S1P1/ES-3/4"X90		2					
	-	FLANGES				_					
	5	FLANGE SW 150# RF A182-F304 SCH40S BORE	1	S1P1/FRSW-1"		1				017	G8 B9
速	6	ASME B16.5 FLANGE SW 150# RF A182-F304 SCH40S BORE	3/4	S1P1/FRSW-3/4"		2				11 C-401	ⓐ CONT. ON
記売		ASME B16.5  ERECTION MATERIALS								S1P1/VA-3/4"-4144-E	P-61716-4"-S1P1
還	PT	COMPONENT DESCRIPTION	N.S.	ITEM CODE	(	)TY		4		S13 G5-1	3/4"NS N 48304 EL.+3927
	NO —		(INS)		_	<u></u>		EL.+	3927		
		GASKETS				_			(5)	000	514
	7	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	1	S1P1/GR-1"		2		4—			S1A \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\
	8	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	3/4	S1P1/GR-3/4"		2		O	53/1	6 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
		BOLTS							500	SAN A SA	
	9	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2	S1P1/BS4-1/2"X65I	L	16			\frac{\frac{1}{\finn}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}}		
		VALVES / IN-LINE ITEMS								4	
	10	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT	1	S1P1/VA-1"-4144-E	Ē	1			6		
	44	FIRE SAFE WRENCH OPER. ASME B16.34 (VOC<100 vppm) BALL 150# RF A351-CF8/304SS+PTFE FULL PORT	2/4	C4D40/0 2/4" 4444	-	1			<b>   </b>		
	11	FIRE SAFE WRENCH OPER. ASME B16.34 (VOC<100 vppm)	3/4	S1P1/VA-3/4"-4144		1		[3]			
		SUPPORTS							S		
	12 13	FLANGE GROUNDING CONDUCTOR (C-401) PIPE GUIDE (G5-1)	1 3/4	MISC/C-401 SUP/G5-1-3/4"		2		F5 G7 B9	8/4"NS		
	14 15	PIPE SHOE (S1A) SUPPORT REINFORCING PAD (SRPA-3/4)	3/4 3/4	SUP/S1A-3/4" SUP/SRPA-3/4"		1			EL.+2949	2	
	16 17	FIELD SUPPORT (FS6-1A-03) FLANGE GROUNDING CONDUCTOR (C-401)	3/4 3/4	SUP/FS6-1A-3/4" MISC/C-401		1		10	3		
							_	LL.72939	\2	NS	
		CUT PIPE LENGTH FOR REFERENCE ONLY						CONN. TO	1"x3/4"N		
	PIEC NO	LENGTH (INS) NO	LENGTH	N.S. REMARKS (INS)			,	V-617/N7		INSUL	
	<1> <3>	959 3/4 <2> 1049 3/4 <4>	462 100	3/4 3/4				E 104600 G7 B9 N 47000 EL +2710 S12		C60	
								EL.+2710 C-401	10 S1P	P1/VA-1"-4144-E	
▲ 會 簽											
分配△△											FOR CONSTRUCTION
											JUL. 04, 2025
											332.3., 2323
											管線編號
											P-61719-3/4"-S1P1
							① 管件序號 <1>1 & 須設計會驗管線	1管編號 [1] 管段編號	資料庫. 名稱	工廠焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽 ———————————————————————————————————	
								G 操作溫度: -16~38 ℃	管線等級: S1P1	製 圖 陳怡如 2025.04.21	
								G 設計溫度: 80/-26 ℃		設計 黃炳富 2025.04.21	—— 富台工程股份有限公司 FU-TAI ENGINEERING CO., LTD.
		2025.07.03 FOR CONSTRUCTION		黄	抗菌	陳逢明	試驗基準: Air	2.2 KG/M <sup>2</sup> G X 60 分		審 核 陳安誠 2025.04.21	<b>崙尾一期</b>
	Â	2025.04.21 FOR APPROVAL		黄	炳富	陳逢明	管路塗裝:	管材塗裝 一大類保溫(今) 「大調」「大調」「大調」「大調」「大調」「大調」「大調」「大調」「大調」「大調」	焊接基準:	認 可 陳逢明 2025.04.21	建廠工程 立體配管圖 1
	序次	日期 修改	說 明	修	改	認可	焊道. 塗裝·	ー ズ   鉤保温(冷)   撑   不銹鋼 :	NDE 抽驗: 10 %	依據圖號: C2418-4-512 圖號:	檔號: P-61719-S1P1- 1
				1							1