		FABRICATION MATERIALS				N 流水號:307
	PT NO	COMPONENT DESCRIPTION	N.S. ITE	M CODE	QTY	
		PIPE		4/D 0// 40		
	1	PIPE A53 GR.B GALV. SMLS SCH40 BE ASME B36.10M PIPE A106 GR.B GALV. SMLS SCH80 PE ASME		x1/P-8"-40 x1/P-3/4"-80	0.8M 0.3M	
	3	B36.10M PVC PIPE TYPE B SMLS SCH80 UPVC PE ASME		/C/P-3/4"-80	1.1M	
1/4		D-1785				
		FITTINGS COCKOL ET 2000# CW A405 CALV MCC CD 07	0 :: 0/4	4/001 001/0/48	4	CONT. FROM 1
	5	SOCKOLET 3000# SW A105 GALV. MSS SP-97 90 ELBOW LR BW A234 GR.WPB GALV. SMLS SCH40 ASME B16.9		x1/SOL-8"X3/4" x1/EB-8"X90	1 1	
	6 7	90 ELBOW 3000# SW A105 GALV. ASME B16.11 90 ELBOW SW SCH80 UPVC		x1/ES-3/4"X90 /C/ES-3/4"X90	1 1	322 8"NS
速						
記		ERECTION MATERIALS				
	PT NO	COMPONENT DESCRIPTION	N.S. ITE	M CODE	QTY	\bigcirc
湿	"	VALVES / IN-LINE ITEMS	(INS)			
	8	GATE 800# SW A105 BB OS&Y RS TRIM 13CR	3/4 C1/	1/VA-3/4"-1812	1	CONT. ON 690 (49)
		STELLITED SOLID WEDGE API-602				EL.+915
	9	SUPPORTS FIELD SUPPORT (ESA 6.03)	0 0111	0/504 6 0"	4	48 8"x3/4"NS
	9	FIELD SUPPORT (FS1-6-03)	8 SUI	P/FS1-6-8"	1	8"NS (14)
		CUT PIPE LENGTH FOR REFERENCE ONLY				
	PIECE		CUT N.S. LENGTH (INS)	REMARKS		70 V K FS FS1-6-03 FS1-6-03
	NO <7>	100 3/4 <8>	130 3/4			DUMMY WELD
	<9> <11>	822 3/4 <10> 707 8	201 3/4			838
						E 18850 MATL 87
						MATL C1A1
						UPVC N
						8 C1A1/VA-3/4"-1812 63
						CTAT/VA-3/4 - 1812 63/ 52/ 50
						6 EL.+367
						⑤1 ► EL.+367
△ 會 簽						
分配 △						
						FOR CONSTRUCTION
						JUN. 09, 2025
						FW-909A01-8"-C1A1
						□ 官仟万號 < 1>直官柵號 □ 百段柵號 □ 百段柵號 ■ A B C B C B C B C B C B C B C B C B C B
						操作壓力: 10 KC/CM² G 操作溫度: 25 °C 管線等級: C1A1 製 圖 林宜靜 2025.06.09 🚊 🖺 富台工程股份有限公司
						設計壓力: 12.3 KS _{CM²} G 設計溫度: 60 ℃ 保溫(冷)等級: 設計 江珍芳 2025.06.09
						試驗基準: water 18.45 KC M² G X 60 分 熱追縱等級: 審 核 江珍芳 2025.06.09 🙊 編尾一期 管線工程 2
		2025.06.09 FOR CONSTRUCTION		江珍芳	陳逢明	管路塗装:
	序次		說 明	修改	認可	管路塗装: 管 材 塗 装
		ı		1	I	